

PoPPy: A Point Process Toolbox Based on PyTorch

Hongteng Xu
 Infinia ML, Inc. and Duke University
 hongtengxu313@gmail.com



1 Overview

1.1 What is PoPPy?

PoPPy is a **Point Process** toolbox based on **PyTorch**, which achieves flexible designing and efficient learning of point process models. It can be used for interpretable sequential data modeling and analysis, *e.g.*, Granger causality analysis of multivariate point processes, point process-based modeling of event sequences, and event prediction.

1.2 The Goal of PoPPy

Many real-world sequential data are often generated by complicated interactive mechanisms among multiple entities. Treating the entities as events with different discrete categories, we can represent their sequential behaviors as event sequences in continuous time. Mathematically, an event sequence s can be denoted as $\{(t_i^s, c_i^s, f_{c_i^s})\}_{i=1}^{I_s}$, where t_i^s and c_i^s are the timestamp and the event type (*i.e.*, the index of entity) of the i -th event, respectively. Optionally, each event type may be associated with a feature vector $f_c \in \mathbb{R}^{D_c}$, $c \in \mathcal{C}$, and each event sequence may also have a feature vector $f_s \in \mathbb{R}^{D_s}$, $s \in \mathcal{S}$. Many real-world scenarios can be formulated as event sequences, as shown in Table 1.

Table 1: Typical event sequences in practice.

Scene	Patient admission	Job hopping	Online shopping
Entities (Event types)	Diseases	Companies	Items
Sequences	Patients' admission records	LinkedIn users' job history	Buying/rating behaviors
Event feature	Diagnose records	Job descriptions	Item profiles
Sequence feature	Patient profiles	User profiles	User profiles
Task	Build Disease network	Model talent flow	Recommendation system

Given a set of event sequences \mathcal{S} , we aim to model the dynamics of the event sequences, capture the interactive mechanisms among different entities, and predict their future behaviors. Temporal point processes provide us with a potential solution to achieve these aims. In particular, a multivariate temporal point process can be represented by a set of counting processes $N = \{N_c(t)\}_{c \in \mathcal{C}}$, in which $N_c(t)$ is the number of type- c events occurring till time t . For each $N_c(t)$, the expected instantaneous

happening rate of type- c events at time t is denoted as $\lambda_c(t)$, which is called “**intensity function**”:

$$\lambda_c(t) = \frac{\mathbb{E}[dN_c(t)|\mathcal{H}_t]}{dt}, \mathcal{H}_t = \{(t_i, c_i)|t_i < t, c_i \in \mathcal{C}\}, \quad (1)$$

where \mathcal{H}_t represents historical observations before time t .




Figure 1: Event sequences and intensity functions.

As shown in Fig. 1, the counting processes can be represented as a set of intensity functions, each of which corresponds to a specific event type. The temporal dependency within the same event type and that across different event types (*i.e.*, the red arrows in Fig. 1) can be captured by choosing particular intensity functions. Therefore, the key points of point process-based sequential data modeling include

1. How to design intensity functions to describe the mechanism behind observed data?
2. How to learn the proposed intensity functions from observed data?

The goal of PoPPy is providing a user-friendly solution to the key points above and achieving large-scale point process-based sequential data analysis, simulation, and prediction.

1.3 Installation of PoPPy

PoPPy is developed on Mac OS 10.13.6 but also tested on Ubuntu 16.04. The installation of PoPPy is straightforward. In particular,

1. Install Anaconda3 and create a conda environment.
2. Install PyTorch0.4 in the environment.
3. Download PoPPy from <https://github.com/HongtengXu/PoPPy/> and unzip it to the directory in the environment. The unzipped folder should contain several subfolders, as shown in Fig. 2.
4. Open `dev/util.py` and change `POPPY_PATH` to the directory, as shown in Fig. 3.

PoPPy				
Name	^	Date Modified	Size	Kind
▶ data		Oct 13, 2018 at 8:52 PM	--	Folder
▶ dev		Yesterday at 3:25 PM	--	Folder
▶ docs		Today at 3:29 PM	--	Folder
▶ example		Today at 2:24 PM	--	Folder
📄 LICENSE		Today at 2:55 PM	35 KB	TextEdit
▶ model		Today at 1:53 PM	--	Folder
▶ output		Today at 2:29 PM	--	Folder
▶ preprocess		Today at 1:17 PM	--	Folder
📄 README.md		Today at 4:02 PM	1 KB	TextEdit

Figure 2: The subfolders in the package of PoPPy.

The subfolders in the package include

- `data`: It contains a toy dataset in `.csv` format.
- `dev`: It contains a `util.py` file, which configures the path and the logger of the package.
- `docs`: It contains the tutorial of PoPPy.

```

util.py x
1 """
2 Development utilities, including:
3 data and model directory path and lazy creation
4 the configuration of logger
5 """
6 import os
7 import logging
8 logging.basicConfig()
9 logger = logging.getLogger(__name__)
10 logger.setLevel(logging.DEBUG)
11
12 # standard data directory names
13 POPPY_PATH = "/Users/hongtengxu/PycharmProjects/PopPy"
14 DATA_DIR = "data"
15 PREPROCESSED_DIR = "preprocess"
16 MODEL_DIR = "model"
17 OUTPUT_DIR = "output"
18 EXAMPLE_DIR = "example"

```

Figure 3: An example of the path of PoPPy.

- `example`: It contains some demo scripts for testing the functionality of the package.
- `model`: It contains the classes of predefined point process models and their modules.
- `output`: It contains the output files generated by the demo scripts in the `example` folder.
- `preprocess`: It contains the classes and the functions of data I/O and preprocessing.

In the following sections, we will introduce the details of PoPPy.

2 Data: Representation and Preprocessing

2.1 Representations of Event Sequences

PoPPy represents observed event sequences as a nested dictionary. In particular, the proposed database has the following structure:

```

database = {
    'event_features' : None or (De, C) float array of event features,
                        C is the number of event types.
                        De is the dimension of event feature.
    'type2idx'      : a Dict = {'event_name': event_index}
    'idx2type'      : a Dict = {event_index: 'event_name'}
    'seq2idx'       : a Dict = {'seq_name': seq_index}
    'idx2seq'       : a Dict = {seq_index: 'seq_name'}
    'sequences'     : a List = [seq_1, seq_2, ..., seq_N].
}

```

For the i -th sequence:

```

seq_i = {
    'times'         : (N,) float array of timestamps,
                        N is the number of events.
    'events'        : (N,) int array of event types.
    'seq_feature'   : None or (Ds,) float array of sequence feature.
                        Ds is the dimension of sequence feature
    't_start'       : a float number, the start timestamp of the sequence.
    't_stop'        : a float number, the stop timestamp of the sequence.
    'label'         : None or int/float number, the labels of the sequence
}

```

PoPPy provides three functions to load data from `.csv` file and convert it to the proposed database.

2.1.1 preprocess.DataIO.load_sequences_csv

This function loads event sequences and converts them to the proposed database. The IO and the description of this function are shown in Fig. 4.

```
def load_sequences_csv(file_name: str, domain_names: Dict):
    """
    Load event sequences from a csv file
    :param file_name: the path and name of the target csv file
    :param domain_names: a dictionary contains the names of the key columns
                        corresponding to {'seq_id', 'time', 'event'}
    The format should be
    domain_names = {'seq_id': the column name of sequence name,
                  'time': the column name of timestamps,
                  'event': the column name of events}
    :return: database: a dictionary containing observed event sequences
    database = {'event_features': None,
               'type2idx': a Dict = {'event_name': event_index}
               'idx2type': a Dict = {'event_index': 'event_name'}
               'seq2idx': a Dict = {'seq_name': seq_index}
               'idx2seq': a Dict = {'seq_index': 'seq_name'}
               'sequences': a List = [seq_1, seq_2, ..., seq_N].
               }

    For the i-th sequence:
    seq_i = {'times': (N,) float array of timestamps, N is the number of events.
            'events': (N,) int array of event types.
            'seq_feature': None.
            't_start': a float number, the start timestamp of the sequence.
            't_stop': a float number, the stop timestamp of the sequence.
            'label': None
            }
    """
```

Figure 4: The description of load_sequences_csv.

For example, the *Linkedin.csv* file in the folder *data* records a set of linkedin users' job-hopping behaviors among different companies, whose format is shown in Fig. 5.

Linkedin

id	time	event	option1
1	29	Google	Intern Research
1	29.2521	UC Berkeley	Graduate Student Research
1	34.0849	Google	Sr Research Science
6	29	Google	Software Eng Intern
6	30	Google	Software Eng Intern
6	32.0027	Google	Software Eng Intern
6	32.2548	eBay	Software Eng Intern
6	32.5918	Baidu	Software Eng
6	33.5068	Google	Software Eng
8	31	Microsoft	Software Eng Intern
8	32.0849	LinkedIn	Software Eng Intern
8	32.9178	UCLA	Graduate Teaching Assistant

Figure 5: Some rows of *Linkedin.csv*.

Here, the column *id* corresponds to the names of sequences (*i.e.* the index of users), the column *time* corresponds to the timestamps of events (*i.e.* the ages that the users start to work), and the column *event* corresponds to the event types (*i.e.*, the companies). Therefore, we can define the input *domain_names* as

```
domain_names = {
    'seq_id' : 'id',
    'time'   : 'time',
    'event'  : 'event'
```

```
}
```

```
and database = load_sequences_csv('Linkedin.csv', domain_names).
```

Note that the database created by `load_sequences_csv()` does not contain event features and sequence features, whose values in database are **None**. PoPPy supports to load categorical or numerical features from `.csv` files, as shown below.

2.1.2 preprocess.DataIO.load_seq_features_csv

This function loads sequence features from a `.csv` file and import them to the proposed database. The IO and the description of this function are shown in Fig. 6. Take the `Linkedin.csv` file as an ex-

```
def load_seq_features_csv(file_name: str, seq_domain: str, domain_dict: Dict, database: Dict, normalize: int=0):
    """
    load sequences' features from a csv file
    :param file_name: the path and the name of the csv file
    :param seq_domain: the name of the key column corresponding to sequence index.
    :param domain_dict: a dictionary containing the names of the key columns corresponding to the features.
    The format should be
        domain_dict = {'domain_name': domain's feature type}
    Two types are considered:
    1) 'numerical': each element (row) in the corresponding domain should be a string containing D numbers
        separated by spaces, and D should be the same for various elements.
        D-dimensional real-value features will be generated for this domain.
        If each sequence has multiple rows, the average of the features will be recorded.
    2) 'categorical': each element (row) in the corresponding domain should be a strong containing N keywords
        separated by spaces, but N can be different for various elements.
        D-dimensional binary features will be generated for this domain. Here D is the number of distinguished
        keywords (vocabulary size).
        If each sequence has multiple rows, the aggregation of the binary features will be recorded.
    :param database: a dictionary of data generated by the function "load_sequences_csv()"
    :param normalize: 0 = no normalization, 1 = normalization across features, 2 = normalization across sequences
    :return: a database having sequences' features
    """
```

Figure 6: The description of `load_seq_features_csv`.

ample. Suppose that we have already create database by the function `load_sequences_csv`, and we want to take the column `option1` (*i.e.*, the job titles that each user had) as the categorical features of event sequences. We should have

```
domain_names = {
    'option1' : 'categorical'
}
database = load_seq_features_csv(
    file_name = 'Linkedin.csv',
    seq_domain = 'seq_id',
    domain_dict = domain_names,
    database = database)
```

Here the input `normalize` is set as default 0, which means that the features in `database['sequences'][i]['seq_feature']`, $i = 1, \dots, |S|$, are not normalized.

2.1.3 preprocess.DataIO.load_event_features_csv

This function loads event features from a `.csv` file and import them to the proposed database. The IO and the description of this function are shown in Fig. 7. Similarly, if we want to take the column `option1` in `Linkedin.csv` as the categorical features of event types, we should have

```
domain_names = {
    'option1' : 'categorical'
}
database = load_event_features_csv(
    file_name = 'Linkedin.csv',
    event_domain = 'event',
    domain_dict = domain_names,
```

```
def load_event_features_csv(file_name: str, event_domain: str, domain_dict: Dict, database: Dict, normalize: int=0):
    """
    Load events' features from a csv file
    :param file_name: the path and the name of the csv file
    :param event_domain: the name of the key column corresponding to event index.
    :param domain_dict: a dictionary containing the names of the key columns corresponding to the features.
    The format should be
        domain_dict = {'domain_name': domain's feature type}
    Two types are considered:
    1) 'numerical': each element (row) in the corresponding domain should be a string containing D numbers
        separated by spaces, and D should be the same for various elements.
        D-dimensional real-value features will be generated for this domain.
        If each event type has multiple rows, the average of the features will be recorded.
    2) 'categorical': each element (row) in the corresponding domain should be a string containing N keywords
        separated by spaces, but N can be different for various elements.
        D-dimensional binary features will be generated for this domain. Here D is the number of distinguished
        keywords (vocabulary size).
        If each event type has multiple rows, the aggregation of the binary features will be recorded.
    :param database: a dictionary of data generated by the function "load_sequences_csv()"
    :param normalize: 0 = no normalization, 1 = normalization across features, 2 = normalization across event types
    :return: a database having events' features
    """
```

Figure 7: The description of load_event_features_csv.

database = database)

2.2 Operations for Data Preprocessing

Besides necessary sequence/feature loaders and converters mentioned above, PoPPy contains multiple useful functions and classes for data preprocessing, including sequence stitching, superposing, aggregating, and batch sampling. Fig. 8 illustrates the corresponding data operations.




Figure 8: The illustration of four data operations.

2.2.1 preprocess.DataOperation.stitching

This function stitches the sequences in two database randomly or based on their seq_feature and time information (t_start, t_stop). Its description is shown in Fig. 9.

When `method = 'random'`, for each sequence in `database1` the function randomly selects a sequence in `database2` as its follower and stitches them together. When `method = 'feature'`, the similarity between the sequence in `database1` and that in `database2` is defined by the multiplication of a temporal Gaussian kernel and a sequence feature's Gaussian kernel, and the function selects the sequence in `database2` yielding to a distribution defined by the similarity. The stitching method has been proven to be useful for enhancing the robustness of learning results, especially when the training sequences are very short [9, 4].

```
def stitching(database1: Dict, database2: Dict, method: str = 'random') -> Dict:
    """
    Stitch each sequence in database2 to the end of one sequence of database1
    :param database1: the observed event sequences
    :param database2: another observed event sequences
        database = {'event_features': None or (De, C) float array of event's static features,
                   C is the number of event types.
                   'type2idx': a Dict = {'event_name': event_index}
                   'idx2type': a Dict = {'event_index': 'event_name'}
                   'seq2idx': a Dict = {'seq_name': seq_index}
                   'idx2seq': a Dict = {'seq_index': 'seq_name'}
                   'sequences': a List = {seq_1, seq_2, ..., seq_N}.
                   }

    For the i-th sequence:
    seq_i = {'times': (N,) float array of timestamps, N is the number of events.
            'events': (N,) int array of event types.
            'seq_feature': None or (Ds,) float array of sequence's static feature.
            't_start': a float number indicating the start timestamp of the sequence.
            't_stop': a float number indicating the stop timestamp of the sequence.
            'label': None or int/float number indicating the labels of the sequence}

    :param method: a string indicates stitching method:
    "random": stitch the seq_j in sequences2 to the seq_i in sequences1 for j ~ {1,...,N}, i=1,...,N and
    time-shifting is applied to sequences2.
    This method is suitable for the sequences generated by a same stationary point process.

    "feature": stitch the seq_j in sequences2 to the seq_i in sequences1 for j ~ {1,...,N}, i=1,...,N and
    j is sampled according to the similarity between two sequences.
    The similarity is calculated by the Gaussian kernel of seq_features, labels and times.
    When seq_features/labels are not available, only timestamp information are taken into account.

    :return:
    the output sequences are with the same format as database1.
    """
```

Figure 9: The description of stitching.

2.2.2 preprocess.DataOperation.superposing

This function superposes the sequences in two database randomly or based on their `seq_feature` and time information (`t_start`, `t_stop`). Its description is shown in Fig. 10.

When `method = 'random'`, for each sequence in `database1` the function randomly selects a sequence in `database2` and superposes them together. When `method = 'feature'`, the similarity between the sequence in `database1` and that in `database2` is defined by the multiplication of a temporal Gaussian kernel and a sequence feature's Gaussian kernel, and the function selects the sequence in `database2` yielding to a distribution defined by the similarity.

Similar to the stitching operation, the superposing method has been proven to be useful for learning linear Hawkes processes robustly. However, it should be noted that different from stitching operation, which stitches similar sequences with a high probability, the superposing process would like to superpose the dissimilar sequences with a high chance. The rationality of such an operation can be found in my paper [8, 5].

2.2.3 preprocess.DataOperation.aggregating

This function discretizes each event sequence into several bins and counts the number of events with specific types in each bin. Its description is shown in Fig. 11.

2.2.4 preprocess.DataOperation.EventSampler

This class is a subclass of `torch.utils.data.Dataset`, which samples batches from database. For each sample in the batch, an event (*i.e.*, its event type and timestamp) and its history with length `memorysize` (*i.e.*, the last `memorysize` events and their timestamps) are

```

def superposing(database1: Dict, database2: Dict, method: str = 'random') -> Dict:
    """
    Superpose each sequence in database2 to one sequence of database1
    :param database1: the observed event sequences
    :param database2: another observed event sequences
    database = {'event_features': None or (C, De) float array of event's static features,
               C is the number of event types,
               'type2idx': a Dict = {'event_name': event_index}
               'idx2type': a Dict = {'event_index': 'event_name'}
               'seq2idx': a Dict = {'seq_name': seq_index}
               'idx2seq': a Dict = {'seq_index': 'seq_name'}
               'sequences': a List = [seq_1, seq_2, ..., seq_N].
            }

    For the i-th sequence:
    seq_i = {'times': (N,) float array of timestamps, N is the number of events.
            'events': (N,) int array of event types.
            'seq_feature': None or (Ds,) float array of sequence's static feature.
            't_start': a float number indicating the start timestamp of the sequence.
            't_stop': a float number indicating the stop timestamp of the sequence.
            'label': None or int/float number indicating the labels of the sequence}

    :param method: a string indicates superposing method:
    "random": superpose the seq_j in sequences2 to the seq_i in sequences1 for j ~ {1,...,N}, i=1,...,N and
    time-shifting is applied to sequences2.
    This method is suitable for the sequences generated by a same stationary point process.

    "feature": superpose the seq_j in sequences2 to the seq_i in sequences1 for j ~ {1,...,N}, i=1,...,N and
    j is sampled according to the similarity between two sequences.
    The similarity is calculated by the Gaussian kernel of seq_features, labels and times.
    When seq_features/labels are not available, only timestamp information are taken into account.

    Different from stitching operation, to enlarge the power of superposition,
    the sequences with large dissimilarity are more likely to be superposed together

    :return:
    the output sequences are with the same format as database1.
    """

```

Figure 10: The description of superposing.

recorded. If the features of events (or sequences) are available, the sample will record these features as well.

3 Temporal Point Process Models

3.1 Modular design of point process model

PoPPy applies a flexible strategy to build point process's intensity functions from interpretable modules. Such a modular design strategy is very suitable for the Hawkes process and its variants. Fig. 13 illustrates the proposed modular design strategy. In the following sections, we take the Hawkes process and its variants as examples and introduce the modules (*i.e.*, the classes) in PoPPy.

3.2 `model.PointProcess.PointProcessModel`

This class contains basic functions of a point process model, including

- `fit`: learn model's parameters given training data. Its description is shown in Fig. 14
- `validation`: test model given validation data. Its description is shown in Fig. 15
- `simulation`: simulate new event sequences from scratch or following observed sequences by Ogata's thinning algorithm [3]. Its description is shown in Fig. 16
- `prediction`: predict expected counts of the events in the target time interval given learned model and observed sequences. Its description is shown in Fig. 17
- `model_save`: save model or save its parameters. Its description is shown in Fig. 18
- `model_load`: load model or load its parameters. Its description is shown in Fig. 19
- `print_info`: print basic information of model
- `plot_exogenous`: print exogenous intensity.

In PoPPy, the instance of this class implements an inhomogeneous Poisson process, in which the exogenous intensity is used as the intensity function.


```

def aggregating(database, dt):
    """
    Count the number of events in predefined time bins,
    and convert event sequences to aggregate time series
    :param database: the observed event sequences
    :param dt: a float number indicating the length of time bin.
    :return:
        the output's format is shown as follows:

        output = {'event_features': None or (De, C) float array of event's static features,
                  C is the number of event types.
                  'type2idx': a Dict = {'event_name': event_index}
                  'idx2type': a Dict = {'event_index': 'event_name'}
                  'seq2idx': a Dict = {'seq_name': seq_index}
                  'idx2seq': a Dict = {'seq_index': 'seq_name'}
                  'sequences': a List = {seq_1, seq_2, ..., seq_N}.
                }

        For the i-th sequence:
        seq_i = {'times': (N,) float array of discrete timestamps,
                N = [(t_stop - t_start)/dt] is the number of bins.
                'events': (N, C) int array of event types,
                events[n, c] counts the number of type-c events in the n-th bin
                'seq_feature': None or (Ds,) float array of sequence's static feature.
                't_start': a float number indicating the start timestamp of the sequence.
                't_stop': a float number indicating the stop timestamp of the sequence.
                'label': None or int/float number indicating the labels of the sequence}
    """

```

Figure 11: The description of aggregate.

```

class EventSampler(Dataset):
    """Load event sequences via minbatch"""
    def __init__(self, database, memorysize):
        """
        :param database: the observed event sequences
        database = {'event_features': None or (C, De) float array of event's static features,
                  C is the number of event types.
                  'type2idx': a Dict = {'event_name': event_index}
                  'idx2type': a Dict = {'event_index': 'event_name'}
                  'seq2idx': a Dict = {'seq_name': seq_index}
                  'idx2seq': a Dict = {'seq_index': 'seq_name'}
                  'sequences': a List = {seq_1, seq_2, ..., seq_N}.
                }

        For the i-th sequence:
        seq_i = {'times': (N,) float array of timestamps, N is the number of events.
                'events': (N,) int array of event types.
                'seq_feature': None or (Ds,) float array of sequence's static feature.
                't_start': a float number indicating the start timestamp of the sequence.
                't_stop': a float number indicating the stop timestamp of the sequence.
                'label': None or int/float number indicating the labels of the sequence}

        :param memorysize: how many historical events remembered by each event
        """

```

Figure 12: The description of EventSampler.

An important subclass of this class is `model.HawkesProcess.HawkesProcessModel`. This subclass inherits most of the functions above except `print_info` and `plot_exogenous`. Additionally, because the Hawkes process considers the triggering patterns among different event types, this subclass has a new function `plot_causality`, which plots the adjacency matrix of the event types' Granger causality graph. The typical visualization results of the exogenous intensity of different event types and the Granger causality among them are shown in Fig. 20.

Compared with its parent class, `model.HawkesProcess.HawkesProcessModel` uses a specific intensity function, which is defined in the class `model.HawkesProcess.HawkesProcessIntensity`.




Figure 13: An illustration of proposed modular design strategy. Each color block represents a class with some functions. For each block, the dotted frame represents one of its subclass, which inherits some functions (the white ones) while overrides some others or creates new ones (the yellow ones). The black arrow means that the destination class will call the instance of the source class as input.

```
def fit(self, dataloader, optimizer, epochs: int, scheduler=None, sparsity: float=None, nonnegative=None,
        use_cuda: bool=False, validation_set=None):
    """
    Learn parameters of a generalized Hawkes process given observed sequences
    :param dataloader: a pytorch batch-based data loader
    :param optimizer: the sgd optimization method defined by PyTorch
    :param epochs: the number of training epochs
    :param scheduler: the method adjusting the learning rate of SGD defined by PyTorch
    :param sparsity: None or a float weight of L1 regularizer
    :param nonnegative: None or a float lower bound, typically the lower bound = 0
    :param use_cuda: use cuda (true) or not (false)
    :param validation_set: None or a validation dataloader
    """
```

Figure 14: The description of fit.

3.3 model.HawkesProcess.HawkesProcessIntensity

This class inherits the functions in torch.nn.Module. It defines the intensity function of a generalized Hawkes process, which contains the following functions:

- print_info: print the basic information of the intensity function.
- intensity: calculate $\lambda_{c_i}(t_i)$ of the i -th sample in the batch sampled by EventSampler.
- expected_counts: calculate $\int_{t_{i-1}}^{t_i} \lambda_c(s)ds$ for $c \in \mathcal{C}$ and for the i -th sample in the batch.

```

def validation(self, dataloader, use_cuda):
    """
    Compute the averaged loss per event of a generalized Hawkes process
    given observed sequences and current model
    :param dataloader: a pytorch batch-based data loader
    :param use_cuda: use cuda (true) or not (false)
    """

```

Figure 15: The description of validation.

```

def simulate(self,
            history,
            memory_size: int = 10,
            time_window: float = 1.0,
            interval: float = 1.0,
            max_number: int = 100,
            use_cuda: bool = False):
    """
    Simulate one or more event sequences from given model.
    :param history: historical observations
        history = {'event_features': None or (C, De) float array of event's static features,
                  C is the number of event types.
                  'type2idx': a Dict = {'event_name': event_index}
                  'idx2type': a Dict = {'event_index': 'event_name'}
                  'seq2idx': a Dict = {'seq_name': seq_index}
                  'idx2seq': a Dict = {'seq_index': 'seq_name'}
                  'sequences': a List = {seq_1, seq_2, ..., seq_N}.
                }

    For the i-th sequence:
    seq_i = {'times': (N,) float array of timestamps, N is the number of events.
            'events': (N,) int array of event types.
            N can be "0" (i.e., no observations)
            'seq_feature': None or (Ds,) float array of sequence's static feature.
            't_start': a float number indicating the start timestamp of the sequence.
            't_stop': a float number indicating the stop timestamp of the sequence.
            'label': None or int/float number indicating the labels of the sequence}
    :param memory_size: the number of historical events used for simulation
    :param time_window: duration of simulation process.
    :param interval: the interval size calculating the supremum of intensity
    :param max_number: the maximum number of simulated events
    :param use_cuda: use cuda (true) or not (false)
    :return:
        new_data: having the same format as history
        counts: a list of (C,) ndarray, which counts the number of simulated events for each type
    """

```

Figure 16: The description of simulate.

- **forward**: override the forward function in `torch.nn.Module`. It calculates $\lambda_{c_i}(t_i)$ and $\int_{t_{i-1}}^{t_i} \lambda_c(s) ds$ for $c \in \mathcal{C}$ for SGD.

Specifically, the intensity function of type- c event at time t is defined as

$$\lambda_c(t) = g\lambda \left(\underbrace{\mu_c(\mathbf{f}_c, \mathbf{f}_s)}_{\text{exogenous intensity}} + \underbrace{\sum_{t_i < t} \phi_{cc_i}(t - t_i, \mathbf{f}_c, \mathbf{f}_{c_i})}_{\text{endogeneous impact}} \right) \quad (2)$$

$$= \mu_c(\mathbf{f}_c, \mathbf{f}_s) + \sum_{t_i < t} \sum_{m=1}^M \alpha_{cc_im}(\mathbf{f}_c, \mathbf{f}_{c_i}) \kappa_m(t - t_i).$$

Here, the intensity function is consist of two parts:

- **Exogenous intensity** $\mu_c(\mathbf{f}_c, \mathbf{f}_s)$: it is independent with time, which measures the intensity contributed by the intrinsic properties of sequence and event type.

```

def predict(self,
            history,
            memory_size: int = 10,
            time_window: float = 1.0,
            interval: float = 1.0,
            max_number: int = 1e5,
            use_cuda: bool = False,
            num_trial: int = 2):
    """
    Predict the expected number of events in the proposed target time window
    :param history: historical observations
        history = {'event_features': None or (C, De) float array of event's static features,
                  C is the number of event types.
                  'type2idx': a Dict = {'event_name': event_index}
                  'idx2type': a Dict = {event_index: 'event_name'}
                  'seq2idx': a Dict = {'seq_name': seq_index}
                  'idx2seq': a Dict = {seq_index: 'seq_name'}
                  'sequences': a List = {seq_1, seq_2, ..., seq_N}.
                  }

        For the i-th sequence:
        seq_i = {'times': (N,) float array of timestamps, N is the number of events.
                'events': (N,) int array of event types.
                N can be "0" (i.e., no observations)
                'seq_feature': None or (Ds,) float array of sequence's static feature.
                'dyn_features': None or (N, Dt) float array of event's dynamic features.
                't_start': a float number indicating the start timestamp of the sequence.
                't_stop': a float number indicating the stop timestamp of the sequence.
                'label': None or int/float number indicating the labels of the sequence}
    :param memory_size: the number of historical events used for simulation
    :param time_window: duration of simulation process.
    :param interval: the interval size calculating the supremum of intensity
    :param max_number: the maximum number of simulated events
    :param use_cuda: whether use cuda or not
    :param num_trial: the number of simulation trials.
    """

```

Figure 17: The description of predict.

```

def save_model(self, full_path, mode: str='entire'):
    """
    Save trained model
    :param full_path: the path of directory
    :param mode: 'parameter' for saving only parameters of the model,
                'entire' for saving entire model
    """

```

Figure 18: The description of model_save.

- **Endogenous impact** $\sum_{t_i < t} \phi_{cc_i}(t - t_i, \mathbf{f}_c, \mathbf{f}_{c_i})$: it sums up the influences of historical events quantitatively via **impact functions** $\{\phi_{cc'}(t)\}_{c, c' \in \mathcal{C}}$, which measures the intensity contributed by the historical observations.

Furthermore, the impact function is decomposed with the help of basis representation, where $\kappa_m(t)$ is called the m -th **decay kernel** and $\alpha_{ccim}(\mathbf{f}_c, \mathbf{f}_{c_i})$ is the corresponding **coefficient**.

$g_\lambda(\cdot)$ is an activation function, which can be

- **Identity**: $g(x) = x$.
- **ReLU**: $g(x) = \max\{x, 0\}$.
- **Softplus**: $g(x) = \frac{1}{\beta} \log(1 + \exp(-\beta x))$.

PoPPy provides multiple choices to implement various intensity functions — each module can be parametrized in different ways.

```

def load_model(self, full_path, mode: str='entire'):
    """
    Load pre-trained model
    :param full_path: the path of directory
    :param mode: 'parameter' for saving only parameters of the model,
                 'entire' for saving entire model
    """

```

Figure 19: The description of model_load.




Figure 20: Typical visualization results.

3.3.1 model.ExogenousIntensity.BasicExogenousIntensity

This class and its subclasses in model.ExogenousIntensityFamily implements several models of exogenous intensity, as shown in Table 2.

Table 2: Typical models of exogenous intensity.

Class	Formulation
ExogenousIntensity.BasicExogenousIntensity	$\mu_c(\mathbf{f}_c, \mathbf{f}_s) = \mu_c$
ExogenousIntensityFamily.NaiveExogenousIntensity	$\mu_c(\mathbf{f}_c, \mathbf{f}_s) = g(\mu_c)$
ExogenousIntensityFamily.LinearExogenousIntensity	$\mu_c(\mathbf{f}_c, \mathbf{f}_s) = g(\mathbf{w}_c^\top \mathbf{f}_s)$
ExogenousIntensityFamily.NeuralExogenousIntensity	$\mu_c(\mathbf{f}_c, \mathbf{f}_s) = NN(\mathbf{f}_c, \mathbf{f}_s)$

Here, the activation function $g(\cdot)$ is defined as aforementioned g_λ .

Note that the last two models require event and sequence features as input. When they are called while the features are not given, PoPPy will add one more embedding layer to generate event/sequence features from their index, and learn this layer during training.

3.3.2 model.EndogenousImpact.BasicEndogenousImpact

This class and its subclasses in model.EndogenousImpactFamily implement several models of the coefficients of the impact function, as shown in Table 3.

Here, the activation function $g(\cdot)$ is defined as aforementioned g_λ .

Note that the last two models require event and sequence features as input. When they are called while the features are not given, PoPPy will add one more embedding layer to generate event/sequence features from their index, and learn this layer during training.

Table 3: Typical models of endogenous impact's coefficient.

Class	Formulation
EndogenousImpactFamily.BasicEndogenousImpact	$\alpha_{cc'm}(\mathbf{f}_c, \mathbf{f}_{c'}) = \alpha_{cc'm}$
EndogenousImpactFamily.NaiveEndogenousImpact	$\alpha_{cc'm}(\mathbf{f}_c, \mathbf{f}_{c'}) = g(\alpha_{cc'm})$
EndogenousImpactFamily.FactorizedEndogenousImpact	$\alpha_{cc'm}(\mathbf{f}_c, \mathbf{f}_{c'}) = g(\mathbf{w}_{cm}^\top \mathbf{v}_{c'm})$
EndogenousImpactFamily.LinearEndogenousImpact	$\alpha_{cc'm}(\mathbf{f}_c, \mathbf{f}_{c'}) = g(\mathbf{w}_{cm} \mathbf{f}_{c'})$
EndogenousImpactFamily.BiLinearEndogenousImpact	$\alpha_{cc'm}(\mathbf{f}_c, \mathbf{f}_{c'}) = g(\mathbf{f}_c^\top \mathbf{W}_m \mathbf{f}_{c'})$

3.3.3 model.DecayKernel.BasicDecayKernel

This class and its subclasses in model.DecayKernelFamily implements several models of the decay kernel, as shown in Table 4.

Table 4: Typical models of decay kernel.

Class	M	Formulation
DecayKernelFamily.ExponentialKernel [13]	1	$\kappa(t) = \begin{cases} \omega \exp(-\omega(t - \delta)), & t \geq \delta, \\ 0, & t < \delta \end{cases}$
DecayKernelFamily.RayleighKernel	1	$\kappa(t) = \omega t \exp(-\omega t^2/s)$
DecayKernelFamily.GaussianKernel	1	$\kappa(t) = \frac{1}{\sqrt{2\pi}\sigma} \exp(-\frac{t^2}{2\sigma^2})$
DecayKernelFamily.PowerlawKernel [12]	1	$\kappa(t) = \begin{cases} (\omega - 1)\delta^{\omega-1}t^{-\omega}, & x \geq \delta, \\ (\omega - 1)/\delta, & 0 < x < \delta \end{cases}$
DecayKernelFamily.GateKernel	1	$\kappa(t) = \frac{1}{\delta}, t \in [\omega, \omega + \delta]$
DecayKernelFamily.MultiGaussKernel [6]	>1	$\kappa_m(t) = \frac{1}{\sqrt{2\pi}\sigma_m} \exp(-\frac{(t-t_m)^2}{2\sigma_m^2})$

Fig. 21 visualizes some examples.




Figure 21: Examples of decay kernels and their integration values.

4 Learning Algorithm

4.1 Loss functions

With the help of PyTorch, PoPPy learns the point process models above efficiently by stochastic gradient descent on CPU or GPU [2]. Different from existing point process toolboxes, which mainly focuses on the maximum likelihood estimation of point process models, PoPPy integrates three loss functions to learn the models, as shown in Table 5.

Table 5: A list of loss functions.

Maximum Likelihood Estimation [13, 6]
- Class: <code>OtherLayers.MaxLogLike</code>
- Formulation: $L(\theta) = -\sum_{i \in \mathcal{D}} \left(\log \lambda_{c_i}(t_i) - \sum_{c \in \mathcal{C}} \int_{t_{i-1}}^{t_i} \lambda_c(s) ds \right)$
Least Square Estimation [8, 7]
- Class: <code>OtherLayers.LeastSquare</code>
- Formulation: $L(\theta) = \sum_{i \in \mathcal{D}} \left\ \int_{t_{i-1}}^{t_i} \boldsymbol{\lambda}(s) ds - \mathbf{1}_{c_i} \right\ _2^2$
Conditional Likelihood Estimation [10]
- Class: <code>OtherLayers.CrossEntropy</code>
- Formulation: $L(\theta) = -\sum_{i \in \mathcal{D}} \log p(c_i t_i, \mathcal{H}_i) = -\sum_{i \in \mathcal{D}} \log \text{softmax} \left(\int_{t_{i-1}}^{t_i} \boldsymbol{\lambda}(s) ds \right)$.

Here $\boldsymbol{\lambda}(t) = [\lambda_1(t), \dots, \lambda_{|C|}(t)]$ and $\mathbf{1}_c$ is an one-hot vector whose the c -th element is 1.

4.2 Stochastic gradient decent

All the optimizers and the learning rate schedulers in PyTorch are applicable to PoPPy. A typical configuration is using Adam + Exponential learning rate decay strategy, which should achieve good learning results in most situations. The details can be found in the demo scripts in the folder `example`.

Trick: Although most of the optimizers are applicable, generally, Adam achieves the best performance in our experiments [2].

4.3 Optional regularization

Besides the L2-norm regularizer in PyTorch, PoPPy provides two more regularizers when learning models.

1. **Sparsity:** L1-norm of model’s parameters can be applied to the models, which helps to learn structural parameters.
2. **Nonnegativeness:** If it is required, PoPPy can ensure the parameters to be nonnegative during training.

Trick: When the activation function of impact coefficient is `softplus`, you’d better close the nonnegative constraint by setting the input `nonnegative` of the function `fit` as **None**.

5 Examples

As a result, using PoPPy, users can build their own point process models by combining different modules with high flexibility. As shown in Fig. 22, Each point process model can be built by selecting different modules and combining them. The red dots represent the module with learnable parameters, the blue dots represent the module without parameters, and the green dots represent loss function modules. Moreover, users can add their own modules and design specific point process models for their applications quickly, as long as the new classes override the corresponding functions.

Finally, we list some typical models implemented by PoPPy in Table 6.




Figure 22: Illustration the construction of a point process model.

References

- [1] M. Engelhard, H. Xu, L. Carin, J. A. Oliver, M. Hallyburton, and F. J. McClellon. Predicting smoking events with a time-varying semi-parametric Hawkes process model. *arXiv preprint arXiv:1809.01740*, 2018.
- [2] H. Mei and J. M. Eisner. The neural Hawkes process: A neurally self-modulating multivariate point process. In *Advances in Neural Information Processing Systems*, pages 6754–6764, 2017.
- [3] Y. Ogata. On Lewis’ simulation method for point processes. *IEEE Transactions on Information Theory*, 27(1):23–31, 1981.
- [4] H. Xu, L. Carin, and H. Zha. Learning registered point processes from idiosyncratic observations. In *International Conference on Machine Learning*, 2018.
- [5] H. Xu, X. Chen, and L. Carin. Superposition-assisted stochastic optimization for Hawkes processes. *arXiv preprint arXiv:1802.04725*, 2018.
- [6] H. Xu, M. Farajtabar, and H. Zha. Learning Granger causality for Hawkes processes. In *International Conference on Machine Learning*, pages 1717–1726, 2016.
- [7] H. Xu, D. Luo, and L. Carin. Online continuous-time tensor factorization based on pairwise interactive point processes. In *Proceedings of the 27th International Conference on Artificial Intelligence*. AAAI Press, 2018.
- [8] H. Xu, D. Luo, X. Chen, and L. Carin. Benefits from superposed Hawkes processes. In *International Conference on Artificial Intelligence and Statistics*, pages 623–631, 2018.
- [9] H. Xu, D. Luo, and H. Zha. Learning Hawkes processes from short doubly-censored event sequences. In *International Conference on Machine Learning*, pages 3831–3840, 2017.
- [10] H. Xu, W. Wu, S. Nemati, and H. Zha. Patient flow prediction via discriminative learning of mutually-correcting processes. *IEEE Transactions on Knowledge and Data Engineering*, 29(1):157–171, 2017.
- [11] H. Xu, Y. Zhen, and H. Zha. Trailer generation via a point process-based visual attractiveness model. In *Proceedings of the 24th International Conference on Artificial Intelligence*, pages 2198–2204. AAAI Press, 2015.
- [12] Q. Zhao, M. A. Erdogdu, H. Y. He, A. Rajaraman, and J. Leskovec. Seismic: A self-exciting point process model for predicting tweet popularity. In *Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 1513–1522. ACM, 2015.
- [13] K. Zhou, H. Zha, and L. Song. Learning social infectivity in sparse low-rank networks using multi-dimensional Hawkes processes. In *Artificial Intelligence and Statistics*, pages 641–649, 2013.

Table 6: Typical models implemented by PoPPy.

Model	Linear Hawkes process [13]
Exogenous Intensity	NaiveExogenousIntensity
Endogenous Impact	NavieEndogenousImpact
Decay Kernel	ExponentialKernel
Activation g_λ	Identity
Loss	MaxLogLike
Model	Linear Hawkes process [6, 5]
Exogenous Intensity	NaiveExogenousIntensity
Endogenous Impact	NavieEndogenousImpact
Decay Kernel	MultiGaussKernel
Activation g_λ	Identity
Loss	MaxLogLike
Model	Linear Hawkes process [8]
Exogenous Intensity	NaiveExogenousIntensity
Endogenous Impact	NavieEndogenousImpact
Decay Kernel	MultiGaussKernel
Activation g_λ	Identity
Loss	LeastSquares
Model	Factorized point process [7]
Exogenous Intensity	LinearExogenousIntensity
Endogenous Impact	FactorizedEndogenousImpact
Decay Kernel	ExponentialKernel
Activation g_λ	Identity
Loss	LeastSquares
Model	Semi-Parametric Hawkes process [1]
Exogenous Intensity	LinearExogenousIntensity
Endogenous Impact	NavieEndogenousImpact
Decay Kernel	MultiGaussKernel
Activation g_λ	Identity
Loss	MaxLogLike
Model	Parametric self-correcting process [11]
Exogenous Intensity	LinearExogenousIntensity
Endogenous Impact	LinearEndogenousImpact
Decay Kernel	GateKernel
Activation g_λ	Softplus
Loss	MaxLogLike
Model	Mutually-correcting process [10]
Exogenous Intensity	LinearExogenousIntensity
Endogenous Impact	LinearEndogenousImpact
Decay Kernel	GaussianKernel
Activation g_λ	Softplus
Loss	CrossEntropy