Cardinalities estimation under sliding time window by sharing HyperLogLog Counter

Jie $Xu^{1,}$

Abstract

Cardinalities estimation is an important research topic in network management and security. How to solve this problem under sliding time window is a hot topic. HyperLogLog is a memory efficient algorithm work under a fixed time window. A sliding version of HyperLogLog can work under sliding time window by replacing every counter of HyperLogLog with a list of feature possible maxim (LFPM). But LFPM is a dynamic structure whose size is variable at running time. This paper proposes a novel counter for HyperLogLog which consumes smaller size of memory than that of LFPM. Our counter is called bit distance recorder BDR, because it maintains the distance of every left most "1" bit position. The size of BDR is fixed. Based on BDR, we design a multi hosts' cardinalities estimation algorithm under sliding time window, virtual bit distance recorder VBDR. VBDR allocate a virtual vector of BDR for every host and every physical BDR is shared by several hosts to improve the memory usage. After a small modification, we propose another two parallel versions of VBDR which can run on GPU to handle high speed traffic. One of these parallel VBDR is fast in IP pair scanning and the other one is memory efficient. BDR is also suitable for other cardinality estimation algorithms such as PCSA, LogLog.

1. Introduction

Generally speaking, cardinality is the distinct number of elements in a data stream. It is a crucial attribute in network management and research[1][2][3]. In network field, cardinality maybe flows cardinality(the number of distinct flows in a particular period[4]), host cardinality(the number of other hosts contacting with it[5]). Cardinality estimating algorithm could be applied to all these kind of problems. For a brief description, cardinality in this paper means host's cardinality.

The cardinality of a host aip is the number of other hosts communicating with it through an edge router ER in a particular period[6]. We call these hosts, which communicate with aip in a certain period, as aip's opposite hosts. The period could be a discrete time window or a sliding time window as shown in fig.1. The traffic is divided into regular time slices. The size of a time slice could set to 1 second, 1 minute, 5 minutes or any fix duration of different applications.

The time window moves forward a time slice once a time. The sliding time window contains k successive time slices [7], but the discrete time window only has a time slice. Let W(t, k) represent a time window starting from the tth time slice with k time slices. The size of a time window is the duration it covers. For a sliding time window, its size is the sum duration of the k time slices. For a discrete time window, its size is the duration of a time slice. When the size of a sliding time window equals to that of a discrete time window, the size of a time slice in the sliding time window is k times smaller than that in the discrete time window. The small size of the time slice let the cardinality acquired under sliding time window is more accurate and prompt than that under a discrete time window.

But calculating cardinality under sliding time window is much more complex than that under discrete time window because it needs to preserve the host state of previous time slices when the sliding time window moves forward[8]. Let OP(aip, t, k)represent the set of aip's opposite hosts in W(t, k). If $bip \in OP(aip, t, k)$, we say that bip is active for aip in W(t, k). The primary problem of cardinality estimating under sliding time window is to de-

Email address: xujieip@163.com (Jie Xu)

Preprint submitted to Elsevier



Figure 1: Sliding time window and discrete time window

termine if a *bip* in OP(aip, t, k) is still active in W(t + 1, k) at the beginning of time slice t + k. For example, if *bip* appears in W(t + 1, k - 1), it will be still active at the beginning of time slice t + k; if *bip* only appears in time slice t, it will be inactive at the beginning of time slice t + k. Sliding time window algorithm must distinguish active and inactive opposite hosts in every time slices. We solve this problem by designing a novel counter, Bit Distance Recorder(BDR). We use BDR as the counter of HyperLogLog[9] and share with different hosts[10] to design a novel algorithm VBDR which can estimate several hosts' cardinalities under sliding time window. The main contributions of this paper is listed below:

- 1. Propose a novel counter, Bit Distance Recorder(BDR), to record the state of the host under a sliding time window;
- Propose a cardinalities estimating algorithm under a sliding time window, virtual Bit Distance Recorder VBDR. VBDR estimates different hosts' cardinalities with a fixed size of memory.
- 3. Deploy VBDR on GPU to estimate cardinalities in real time;

This paper is arranged as below. In the next section, we will introduce the related works. In section 3, we will describe how BDR works and why it can maintain the most left "1" bit position under sliding time window. Based on BDR, algorithm VBDR is proposed in section 4. Section 4 also introduces a method to deploy VBDR on GPU.

2. Background & Related work

2.1. Problem definition

Measuring the core network's properties, such as traffic size, packets number, host cardinality and so on, is the foundation of network management. This paper focuses on how to estimate different hosts' cardinalities over sliding time window. Suppose there is a core network, ANet, which is under the management of some organizations, institutes or ISP(internet service provider). ANet communicates with other networks, denoted as BNet, through a set of edge routers ER. For a host $aip \in$ ANet, its cardinality is the number of hosts in BNet which communicate with aip through ER is a time window. The managers of ANet have the authority to inspect every packet between ANet and BNet through ER. So the task of cardinality estimation is to estimate hosts' cardinalities by scanning all packets passing through ER.

2.2. Cardinality estimation

For a host $aip \in ANet$, let Pkt(aip, t, k) represent the stream of packets passing through ERin time window W(t,k) whose source or destination IP address is *aip*. An IP pair which is similar to $\langle aip, bip \rangle$ could be extracted from each packet in Pkt(aip, t, k) where bip is the other host in the packet. We also call bip the opposite host of aip. Let IPair(aip, t, k) represent to the stream of IP pairs corresponding to Pkt(aip, t, k). Because a host $bip \in BNet$ could send several packets to or receive several packets from *aip* in a time window, IP pair $\langle aip, bip \rangle$ can appear many times in IPair(aip, t, k). The number of distinct IP pairs in IPair(aip, t, k) is the cardinality of aip. Let OP(aip, t, k) represent the set of hosts in BNet that communicate with aip in W(t,k) and |OP(aip)| represent the number of hosts in OP(aip, t, k). Estimating the cardinality of aip in W(t,k) is to calculate |OP(aip, t, k)| by scanning IPair(aip, t, k).

Many cardinality estimation algorithms have been proposed. Cardinality estimation algorithms use fix number of the counter to record and calculate the cardinality of a host. All these algorithms use a counter vector containing g counters. What is preserved in a counter, how to update counters and how to estimate the cardinality from the counter vector are unique in different algorithms.

Flajolet et al. [11]firstly proposed such an algorithm which is called Probabilistic Counting with Stochastic Averaging, PCSA. Each counter in

PCSA is a bitmap containing 32 bits. For every opposite host of aip, a random selecting counter is used to record the least significant bit of this element. Least significant bit, LSB, is the first '1' bit starting from the right. After scanning all items in the stream, the value of each counter is its least zero position starting from the right. Cardinality could be acquired according to the sum of every counter. Scheuermann et al. proposed a more accuracy estimating equation when the load factor is smaller than 20. Load factor is the ratio of cardinality to g.

The task of every counter in PCSA is to record the lowest zero position of every element. For an IPv4 address, the biggest value of least zero position is 32. But PCSA uses 32 bits to record the least zero position which leaves great improvement space. Because the biggest value of each counter is 32, 5 bits are big enough to represent it. Motivated by this idea, Philippe et al. proposed the LogLog counting algorithm[12]. Unlike PCSA, each counter of LogLog records the leftmost '1' bit position of every element in the stream. Loglog estimates the cardinality according to the geometric mean value of all counters. Many algorithms are derived from LogLog. Flajolet et al. [9] found that when using the harmonic mean value of all the counters, the accuracy will be improved. And their proposed HyperLogLog algorithm based on this idea. HyperLogLog is the most memory efficient algorithms for large cardinality estimation. But the traditional HyperLogLog only works under discrete time window. Sliding time window has higher monitor resolution and many works have been done for cardinality estimation under sliding time window.

2.3. Sliding time window vs. discrete time window Discrete time window and sliding time window are two kinds of the period for cardinality estimat-

are two kinds of the period for cardinality estimating as shown in figure 1.

Traffic between network ANet and BNet could be divided into successive time slices which have the same duration. The length of a time slice could be 1 second, 1 minute or any period in different situations. A sliding time window, denoted as W(t, k), contains k successive time slices starting from time point t as shown in the top part of figure 1. Sliding time window will move forward one time slice a time. So two adjacent sliding time windows contain k-1 same slices. When k is set to 1, there is no duplicate period between two adjacent windows, which is the case of the discrete time window in the bottom part of figure 1. In figure 1, the size of the time slice is set to 1 second for sliding time window and 300 seconds for the discrete time window. A sliding window in figure 1 contains 300 time slices. In figure 1, the size of a sliding time window is equal to that of a discrete time window.

Cardinality estimation under discrete time window is straightforward because it doesn't need to maintain the appearance of opposite hosts in another time window. But the result is affected by the starting of the discrete time window. When a super point has different opposite hosts in two adjacent time windows, it may be neglected under discrete time window.

Sliding time window has higher accuracy than discrete time window because it monitors traffic in a much more scalable way[13].

Being required to preserve the state of opposite hosts in previous time slices, cardinality estimation under a sliding time window is more burdensome. But many works have been down trying to solve this problem. The main idea is to replace each counter used in a discrete time window with a more powerful structure which can tell if itself is active in the current time window. For a counter, if it is updated in W(t, k), it is called active in this time window.

Fusy et al. [14] extended MinCount to sliding window by maintaining a list of hosts that may become a minimum in a future window. The new algorithm is called Sliding MinCount. The minimum host is the latest arrived hosts among the set of hosts whose hashed value realizes the minimum in a sliding time window. When the time window sliding, Sliding MinCount updates every list and removes inactive hosts from these hosts list. But Sliding MinCount requires much space to store the minimum value of different time slices. In the worst case, each counter will maintain k minimum values in a sliding time window with k time slices. When using 32 bits to represent a minimum amount, each counter of Sliding MinCount requires 32*k bits.

Chabchoub et al. [13] replaced each counter in HyperLogLog with a list of future possible maxima(LFPM). Each cell of LFPM uses 4 bytes to store timestamp and 1 byte to store the max leftmost 1-bit. In a sliding time window with k time slices, LFPM contains ln(n/g) cells on average where n is the cardinality. So the size of a LFPM is 40 * ln(n/g) bits. Denote this algorithm as LFPM-HLL. The size of LFPM-HLL is variable because every LFPM's size is not fixed. And LFPM-HLL is expected to consume $g^*40^*log2(n/g)$ bits of memory on average. Dynamic memory is a burden for running time especially for parallel platform such as GPU. LFPM's purpose is to store the maxima left "1" bit position in the current time window. In this paper we propose a fixed size counter, bit distance recorder to solve this problem with smaller memory consumption.

2.4. Multi hosts cardinality estimation

In the core network, there are huge hosts. A precisely way to acquire all of these hosts' cardinalities is to allocate an estimator for each of them. But this way is memory wasting and slow. Recent algorithms use a fixed number of estimators to maintain and calculate all hosts' cardinalities. Virtual estimator algorithm is one of the popular multi cardinalities estimation algorithms. Every host's logical counter vector shares counter with others in a counter pool as shown in fig.2. The estimator of a virtual estimator could be LE [15][16], HyperLogLog[10]. Virtual counter based algorithms only need to update a counter for a packet and have faster packets scanning speed. Ev-



Figure 2: Virtual counter vector

ery host has a virtual counter vector to estimate its cardinality. Every counter in the virtual counter vector is relative to a physical counter in the pool. A physical counter is shared by several virtual counter vector. Counters in [10] records the biggest left 1 bits position under discrete time window. In this paper we change every counter in it with a powerful counter to let it work under sliding time window.

3. Bit distance recorder

Under a discrete time window, a counter with $log_2(log_2(n/g))$ bits is big enough to store the most left "1" bit position where n is the number of distinct opposite hosts. Let LBP1 represent the most left "1" bit position as defined in HyperLogLog. But under sliding time window, the value of this

counter may become inactive when the window slides forward. The critical step to maintain the LBP1 under sliding time window is to determine it is active in the current time window. In this section, we will introduce a novel counter, Bit distance recorder(BDR), to solve this problem.

Suppose a sliding time window contains k time slices at most. Let BDR contains two part: current time slice LBP1(denoted as nowLBP1) and a vector consisting of $ceil(log_2(n/g))$ distance recorders(denoted as DRV). A distance recorder, written as DR, is z bits where z is an integer at least $ceil(log_2(k+1))$ bits. LBP1 has $ceil(log_2(n/g))$ different values, and one value is corresponding to a DR. Let DRV[i] represent the DR of LBP with value *i*. DR is designed to indicate if a LBP is active in the current time window. A DR has the following operations:

- 1. InitDR(dr): set the value of "dr" to $2^z 1$. This operation initializes an dr at the beginning.
- 2. SetDR(dr): set the value of "dr" to 0.
- 3. SlideDR(dr): if $dr \le 2^k 1$, dr + +.
- 4. IsActiveDR(dr): return if dr is active. if dr < k, dr is active and return true, else dr is inactive and return false.

For a BDR, let ST'(t) represent the stream of hashed opposite hosts that mapped to it in the time slice t. The hashed opposite host is the result of a hash function as defined in HyperLogLog to make sure that the opposite hosts are distributed uniformly. While scanning ST'(t), nowLBP1 stores the LBP1 of ST'(t). After scanning all elements in ST'(t), BDR is updated by EndSliceUpdateBDR() as show in algorithm 1.

Algorithm 1 EndSliceUpdateBDR	
Input: BDR	\triangleright
//BDR.DRV represent the DRV of BDR	
for d dor in BDR.DRV	
SlideDR(dr)	
end for	\triangleright
//BDR.nowLBP1 represent the nowLBP1	of
BDR	
SetDR(BDR.DRV[BDR.nowLBP1])	
Return	

After being updated, the LBP1 used for cardinality estimation could be acquired by algorithm GetLBP1BDR() as show below.

Algorithm 2 GetLBP1BDR	
Input: BDR	
Output: LBP1	
//BDR.DRV represent the DRV of BDR	
$lbp1 \Leftarrow log_2(n/g)$	
while $lbp1 \ge 0$ do	
if IsActiveDR(BDR.DRV[lbp1]) then	
if $BDR.DRV[lbp1] < k$ then	
return lbp1	
end if	
end if	
lbp1	
end while	
return ()	

The "nowLBP1" member of BDR helps to reduce the memory writing because when the new LBP1 is smaller than nowLBP1, it won't be recorded. The "DRV" member of BDR could also be updated directly while scanning IP pair without using nowLBP1, and this method will be discussed in the following section to handle IP pair parallel in GPU.

GetLBP1BDR(BDR) acquires the value of BDR by scanning the most active LBP1 in DRV. After acquire LBP1 in the current time window, cardinality could be estimated like the HyperLogLog. The next section will introduce the VBDR which estimates several hosts' cardinalities at the same time.

4. Sliding cardinalities estimation

For the sake of brevity, we suppose there are two networks, ANet and BNet. All traffic between ANet and BNet are transmitted through an edge router ER. And we want to calculate the cardinalities of hosts in ANet. From the perspective of ER, the cardinality of a host is defined as below.

Definition 1. Host cardinality For a host $aip \in ANet$, its cardinality in time window W(t, k) is the number of hosts in BN that send packets to or receive packets from it through ER in W(t, k), written as |OP(aip, t, k)|.

This paper uses a novel algorithm, Virtual Bit Distance Recorder(VBDR), to estimate different hosts' cardinalities under a sliding time window. VBDR is derived from HyperLogLog and Virtual Estimator.

4.1. Virtual Bit Distance Recorder

VBDR contains a pool of BDR denoted as BDRP. There are total z BDR in BDRP and let BDRP[i] represent the *i*-th BDR in it. For every host "aip" in ANet, there are g different BDR selected from BDRP corresponding with it, and $g = 2^b$ where b is a positive integer smaller than 32. Let VBV(aip) represent these g BDR in BDRP and VBV(aip)[i] represent the *i*-th BDR in VBV(aip). VBV(aip)[i] is related with a physical BDR in BDRP. Let H(x, N, A) represent a random hash function with seed A that maps an integer x to an integer smaller than N. The index of physical BDR of VBV(aip)[i] could be acquired by algorithm 3.

Algorithm 3 getPhyIdx
Input: Host IP: aip
Virtual index: i
Hash function seed: A_0
Output: Physical index: j
$s_1 \leftarrow H(i, 2^{32}, A_0)$
$j \Leftarrow H(aip, z, s_1)$
$\mathbf{return} j$

Every BDR in BDRP is shared with different hosts in ANet. An IP pair, like $\langle aip, bip \rangle$ where $aip \in ANet$ and $bip \in BNet$, could be extracted from every packet between ANet and BNet. Let IPpiar(t) represent the stream of IP pair in time slice t. VBDR scans every IP pair in IPpair(t) as shown in algorithm 4. Let LB(x, i) return the left i bits of the binary form of integer x.

After scanning all IP pairs in IPpair(t), BDRPstores the latest hosts' LBP1. Cardinalities could be estimated from BDRP. According to paper [10], to estimate a host's cardinality we should get the sum of LBP1. For a host "aip" in ANet, its sum of LBP1 in W(t,k) could be acquired by algorithm 5 after processing IPpair(t + k - 1) by algorithm 4.

After getting the sum LBP1 of "aip" we could get its cardinality by equation (5) in paper [10]. Noted that, *BDRP* could also be used in PCSA[11], LogLogcount[17] by replacing its nowLBP1 with the value recorded in other algorithms. VBDR is also suitable for parallel running after a few modification. In the next section we will introduce how to run it on a famous parallel platform GPU.

Algorithm 4 scanIPpair

Algorithm	5	getSumLBP1
-----------	----------	------------

Input: Host IP: <i>aip</i>		
Hash function seed: A_0		
Output: The sum of LBP1 of <i>aip</i>		
$sLBP1 \leftarrow 0$		
for $i \in [0, g-1]$ do		
$pidx \Leftarrow getPhyIdx(aip, i, A_0)$		
$sLBP1 \Leftarrow$	sLBP1	+
GetLBP1BDR(BDRP[pidx])		
end for		
return sLBP1		

4.2. Running on GPU

VBDR can also run on GPU. Only IP pair of a packet is necessary and transmit only IP pairs to GPU is a more efficient way. In a high-speed network, such as 40 Gb/s, there are millions of packets passing through the edge of the network. To scan so many packets in real time requires plenty of computing resource. CPU is one of the most general computing parts, and each core of it is potent to deal with complex tasks running different instructions. Though a core in the CPU is powerful, its price is very high. If we want to use hundreds of CPU cores to deal with high-speed traffic parallel, we have to generate a cluster with several CPUs. The cost of the cluster will be increased with its scale. Graphics processing unit (GPU) is one of the most popular parallel computing platforms in recent years. GPU contains hundreds of processing unit in a chip, much more than that CPU has. For these tasks that have no data accessing conflict and processing different data with the same instructions (SIMD), GPU can acquire a high-speed up[18][19]. Every packet is processed by algorithm 4.

Algorithm 4 scans every IP pair and sets the nowLBP1 of BDR to the biggest value. Under parallel environment, reading-writing conflict may arise because of parallel updating. For example, two threads, thd_1 and thd_2 , are scanning two different opposite hosts, bip_1 and bip_2 , at the same time. Because a counter is sharing by several host, these two threads may updating the same physical BDR. Suppose these two threads are updating the *i*th *BDR* in *BDRP* and $r_0 = BDRP[i].nowLBP1$. Let $r_1 = LBP1((H(bip_1, 2^{32}, A_0) < b))$ and $r_2 = LBP1((H(bip_2, 2^{32}, A_0) << b)).$ If $r_0 <$ $r_1 < r_2$, BDRP[i].nowLBP1 maybe set to r_1 by mistake. Because when thd_2 reads r_0 it will rewrite BDRP[i].nowLBP1 with r_2 . If thd_1 read r_0 before thd_2 rewrite it, thd_2 will rewrite BDRP[i].nowLBP1 with r_1 . If the the rewriting task of thd_1 is submitted to the memory after that of thd_2 , r_1 will cover r_2 . But according to algorithm 4 under serial process, BDRP[i].nowLBP1 should be r_2 after thd_1 and thd_2 finishing. To over come this problem, we replace nowLBP1 of every BDR with a bit string with size 32 - b, denoted as bsLBP1. Every bit of bsLBP1 corresponds with a LBP1 and let bsLBP1[i] represent the *i*-th bit in bsLBP1. Every bit of bsLBP1 is reset to 0 at the beginning of every time slice. When scanning IP pair, if LBP1(bip') = r, then set bsLBP1[r] = 1. The LBP1 of a DR at a time slice is acquired by finding the biggest "1" bit position. The BDR updating algorithm at the end of a time slice on GPU, EndSliceUpdateBDRGpu(), is show in algorithm 6.

Algorithm 6 EndSliceUpdateBDRGpu
Input: BDR >
//BDR.DRV represent the DRV of BDR
for dr in BDR.DRV do
$\operatorname{SlideDR}(\operatorname{dr})$
end for >
//BDR.bsLBP1 represent the bsLBP1 of BDR
$lbp1 \leftarrow 0$
for $i \in [0, 32 - g - 1]$ do
if $BDR.bsLBP1[i] == 0$ then
$lbp1 \leftarrow i$
end if
end for
SetDR(BDR.DRV[lbp1])
Return

Because algorithm 5 only read BDV, so it is not affected by the parallel running. A bit could be set by several threads at the same time, so BDR with bsLBP1 could be running on GPU to scan several IP pair parallel. Algorithm 7 shows how to scan IP pair on GPU. Every thread of GPU reads a IP pair from IPpair(t) and running algorithm 7 to handle it. Thousands of threads on GPU handle the same number of IP pairs at the same time. After scanning all IP pairs in IPpair(t), every BDR will be updated by a GPU thread with algorithm 6. Thousands of threads on GPU handle the same number of BDR at the same time. So no matter IP pair scanning or BDR updating, GPU can finished more quickly than that under CPU.

Algorithm 7 scanIPpairOnGpu	
Input: An IP pair: < aip, bip >	
Hash function seed: A_0, A_1	
$bip' \Leftarrow H(bip, 2^{32}, A_1)$	
$vidx \leftarrow LB(bip', b)$	
$bip' \Leftarrow bip' << b$	
$pidx \leftarrow getPhyIdx(aip, vidx, A_0)$	
BDRP[pidx].bsLBP1[LBP1(bip')] = 1	

Algorithm 7 uses a bsLBP1 to recorder the presentation a LBP1 in the current time slice. Because the bsLBP1 is only updated by bit-wise operations, exactly to speak is the "bit-wise OR" operation, so it has a fast speed. But bsLBP1 requires at least $log_2(n/g)$ bits which increases the memory requirement. As mentioned before, DRV could be used to record the LBP1 directly, and nowLBP1 could be removed. Algorithm 9 shows how to merely use DRV while scanning IP pair. When we use DRV to record the LBP1 of every IP pair's LBP1, DR preserves the latest LBP1. But the max LBP1 could be acquired from DRV by algorithm 2 too. When BDR only contains the DRV, preserving the state of BDR after scanning all IP pairs in IPpair(t)is simple as shown in algorithm 8.But algorithm 8 should be done at the beginning of a time slice before scanning the IP pairs. For a time slice, before scanning the IP pairs in it, every BDR will be updated by a GPU thread with algorithm 8. Thousands of threads on GPU handle the same number of BDR at the same time.

Algorithm 8 BeginSliceUpdateDRV	
Input: BDR	⊳
//BDR.DRV represent the DRV of BDR	
for $dr \in BDR.DRV$ do	
SlideDR(dr)	
end for	
Return	

Algorithm 9 scanIPpairUpdatDRV
Input: An IP pair: $\langle aip, bip \rangle$
Hash function seed: A_0, A_1
$bip' \Leftarrow H(bip, 2^{32}, A_1)$
$vidx \leftarrow LB(bip', b)$
$bip' \Leftarrow bip' << b$
$pidx \Leftarrow getPhyIdx(aip, vidx, A_0)$
SetDR(BDRP[pidx].DRV[LBP1(bip')])

Algorithm 9 only sets DR while scanning IP pairs. The SetDR() operation just set a DR to zero and this operation could be launched by different threads parallel. So algorithm 9 could be launched by different threads of GPU parallel. No matter algorithm 7 or algorithm 9, their just effect the IP pair scanning process. After scanning all IP pairs in IPpair(t) by one of these algorithms, the LBP1 of BDR could be acquired by algorithm 2. So these algorithms can use the same cardinality estimation method as mentioned before.

Not only IP pairs scanning but also hosts' cardinalities estimation can run on GPU. A BDR could be read by several threads without conflict. So several hosts' cardinalities could be estimated at the

Table 1: Memory consumption of different kinds of VBDRAlgorithmSize of a BDR (bits)VBDR-serial $log_2(log_2(n/g)) + log_2(n/g) * log_2(k+1)$ VBDR-gfast $log_2(n/g) + log_2(n/g) * log_2(k+1)$ VBDR-gsmall $log_2(n/g) * log_2(k+1)$

same time.

From the discussion before, we see that VBDR has three versions: serial running VBDR (VBDRserial), parallel running VBDR with high speed on GPU(VBDR - gfast) and parallel running VBDR with small memory requirement on GPU(VBDRgsmall). The memory consumption of BDR of these versions are listed in table 1. Although VBDR-gfast consumes the most memory among these VBDR algorithms, but it has the fastest IP pair scanning speed. VBDR-serial only works under serial environment such as on a single CPU thread. VBDRgfast and VBDR-gsmall can works under both serial and parallel environment, but their IP pair scanning speed or memory requirement is not as good as that of VBDR-serial. All of these algorithms have their merits and weaknesses. Users can choose the suitable one for different situations. For example, if the platform has no GPU card, VBDR-serial is the only choice. If the server has a low level GPU card, such as GTX 650 with only 1 GB graphical memory, VBDR-gsmall is a better choice because it can save memory. If the server has an advanced GPU card, such as Nvidia Titan XP with 12 GB memory, users can choose VBDR-gfast to acquire the fast speed.

5. Conclusion

VBDR is a fast and memory efficient cardinalities estimating algorithm under a sliding time window. It uses BDR to preserve the LBP1 of every time slice. With BDR, memory efficient cardinality estimating algorithms, such as PCSA, LogLogCount, HyperLogLog and so on, could be extended to sliding window environment. VBDR is such one that uses BDR as counter of virtual estimator to estimate several hosts' cardinalities at the same time. VBDR estimates every host's cardinality with a virtual BDR vector from a BDR pool. The more BDR in the pool, the higher accuracy of VBDR will be. In this paper we also improve the performance of VBDR, and propose three versions of VBDR to estimate cardinalities under serial environment and parallel environment. Users can choose one from these three versions for different environments.

- C. C. Lo, C. C. Huang, J. Ku, A cooperative intrusion detection system framework for cloud computing networks, in: 2010 39th International Conference on Parallel Processing Workshops, 2010, pp. 280–284. doi:10.1109/ICPPW.2010.46.
- [2] S. Karthik, J. J. Shah, Analysis of simulation of ddos attack in cloud, in: International Conference on Information Communication and Embedded Systems (ICI-CES2014), 2014, pp. 1–5. doi:10.1109/ICICES.2014. 7033841.
- R. E. Harang, P. Mell, Evasion-resistant network scan detection, Security Informatics 4 (1) (2015) 4. doi:10.1186/s13388-015-0019-7. URL http://dx.doi.org/10.1186/ s13388-015-0019-7
- [4] N. Duffield, C. Lund, M. Thorup, Estimating flow distributions from sampled flow statistics, in: Proceedings of the 2003 Conference on Applications, Technologies, Architectures, and Protocols for Computer Communications, SIGCOMM '03, ACM, New York, NY, USA, 2003, pp. 325–336. doi:10.1145/863955.863992. URL http://doi.acm.org/10.1145/863955.863992
- [5] S. Venkataraman, D. Song, P. B. Gibbons, A. Blum, New streaming algorithms for fast detection of superspreaders, in: in Proceedings of Network and Distributed System Security Symposium (NDSS, 2005, pp. 149–166.
- [6] X. Zhou, W. Liu, Z. Li, W. Gao, A continuous virtual vector-based algorithm for measuring cardinality distribution, in: Algorithms and Architectures for Parallel Processing: 14th International Conference, ICA3PP 2014, Dalian, China, August 24-27, 2014. Proceedings, Part II, Springer International Publishing, Cham, 2014, pp. 43–53.
- [7] L. Golab, D. DeHaan, E. D. Demaine, A. Lopez-Ortiz, J. I. Munro, Identifying frequent items in sliding windows over on-line packet streams, in: Proceedings of the 3rd ACM SIGCOMM Conference on Internet Measurement, IMC '03, ACM, New York, NY, USA, 2003, pp. 173–178. doi:10.1145/948205.948227. URL http://doi.acm.org/10.1145/948205.948227
- [8] P. B. Gibbons, S. Tirthapura, Distributed streams algorithms for sliding windows, Theory of Computing Systems 37 (3) (2004) 457–478. doi:10.1007/ s00224-004-1156-4.

URL https://doi.org/10.1007/s00224-004-1156-4

[9] P. Flajolet, E. Fusy, O. Gandouet, F. Meunier, HyperLogLog: the analysis of a near-optimal cardinality estimation algorithm, in: P. Jacquet (Ed.), Analysis of Algorithms 2007 (AofA07), Juan les pins, France, 2007, pp. 127–146.

URL https://hal.archives-ouvertes.fr/ hal-00406166

- [10] Q. Xiao, S. Chen, Y. Zhou, M. Chen, J. Luo, T. Li, Y. Ling, Cardinality estimation for elephant flows: A compact solution based on virtual register sharing, IEEE/ACM Transactions on Networking 25 (6) (2017) 3738-3752. doi:10.1109/TNET.2017.2753842.
- P. Flajolet, G. N. Martin, Probabilistic counting algorithms for data base applications, Journal of Computer and System Sciences 31 (2) (1985) 182 209. doi: https://doi.org/10.1016/0022-0000(85)90041-8. URL http://www.sciencedirect.com/science/article/pii/0022000085900418
- M. Durand, P. Flajolet, Loglog counting of large cardinalities, in: G. Di Battista, U. Zwick (Eds.), Algorithms ESA 2003: 11th Annual European Symposium, Budapest, Hungary, September 16-19, 2003. Proceedings, Springer Berlin Heidelberg, Berlin, Heidelberg, 2003, pp. 605–617.
- [13] Y. Chabchoub, G. Hebrail, Sliding hyperloglog: Estimating cardinality in a data stream over a sliding window, in: 2010 IEEE International Conference on Data Mining Workshops, 2010, pp. 1297–1303. doi: 10.1109/ICDMW.2010.18.
- [14] E. Fusy, F. Giroire, Estimating the number of active flows in a data stream over a sliding window, in: Proceedings of the Meeting on Analytic Algorithmics and Combinatorics, ANALCO '07, Society for Industrial and Applied Mathematics, Philadelphia, PA, USA, 2007, pp. 223–231. URL http://dl.acm.org/citation.cfm?id=2791135.
- 2791142
 [15] T. Li, S. Chen, W. Luo, M. Zhang, Y. Qiao, Spreader classification based on optimal dynamic bit sharing, IEEE/ACM Transactions on Networking 21 (3) (2013) 817-830. doi:10.1109/TNET.2012.2218255.
- [16] S.-H. Shin, E.-J. Im, M. Yoon, A grand spread estimator using a graphics processing unit, Journal of Parallel and Distributed Computing 74 (2) (2014) 2039 - 2047. doi: http://dx.doi.org/10.1016/j.jpdc.2013.10.007. URL http://www.sciencedirect.com/science/ article/pii/S0743731513002189
- [17] C. Callegari, A. D. Pietro, S. Giordano, T. Pepe, G. Procissi, The loglog counting reversible sketch: A distributed architecture for detecting anomalies in backbone networks, in: 2012 IEEE International Conference on Communications (ICC), 2012, pp. 1287–1291. doi:10.1109/ICC.2012.6363825.
- [18] M. Bernaschi, M. Bisson, D. Rossetti, Benchmarking of communication techniques for gpus, Journal of Parallel and Distributed Computing 73 (2) (2013) 250 - 255. doi:https://doi.org/10.1016/j.jpdc.2012.09.006. URL http://www.sciencedirect.com/science/ article/pii/S0743731512002213
- [19] F. Silber-Chaussumier, A. Muller, R. Habel, Generating data transfers for distributed gpu parallel programs, Journal of Parallel and Distributed Computing 73 (12) (2013) 1649 - 1660, heterogeneity in Parallel and Distributed Computing. doi:https://doi.org/10.1016/j.jpdc.2013.07.022. URL http://www.sciencedirect.com/science/ article/pii/S0743731513001603