ELIAS JARLEBRING, KTH Royal Institute of Technology MAX BENNEDICH, KTH Royal Institute of Technology GIAMPAOLO MELE, KTH Royal Institute of Technology EMIL RINGH, KTH Royal Institute of Technology PARIKSHIT UPADHYAYA, KTH Royal Institute of Technology

We present NEP-PACK a novel open-source library for the solution of nonlinear eigenvalue problems (NEPs). The package provides a framework to represent NEPs, as well as efficient implementations of many state-of-the-art algorithms. The package makes full use of the efficiency of Julia, yet maintains usability, and integrates well with other software packages. The package is designed to be easy to use for application researchers as well as algorithm developers. Particular attention is paid to algorithm neutrality, in order to make performance comparisons between algorithms easier. This paper describes the main functionality of NEP-PACK, as well as design decisions and theory needed for the design.

1 INTRODUCTION

This package concerns nonlinear eigenvalue problems defined as the problem of determining the singular points of a matrix, i.e., find (λ, v) such that

$$M(\lambda)\upsilon = 0\tag{1}$$

where $v \neq 0$ and $M : \mathbb{C} \to \mathbb{C}^{n \times m}$ is a holomorphic (or meromorphic with only a few poles).

Nonlinear problems which are not the linear or generalized eigenvalue problem, occur in many situations. Some of the most common situations are

- higher order differential equations (references in [71]) leading to matrix polynomials
- systems and control for time-delay systems, leading to exponential nonlinearities [48] [35]
- quantum physics (quantum dots) [5, 6]) leading to rational nonlinear functions
- fluid mechanics (scaling exponent in turbulent flow) [50] leading to exponential nonlinearities
- fluid-solid interations [76, 78] leading to rational terms,
- boundary element method applied to resoncance problems [64, 65, 72], see also [19] and the softare package [62],
- absorbing boundary conditions (frequency dependent) leading to square root nonlinearities [16, 69, 70] or Bessel functions [2], e.g., in fiber optics design [43],
- chatter in machine tool milling [15, 33, 34, 36, 55],
- periodic structures, e.g., in crystals [20, 23, 24, 57]

In most of these applications there is need for performance, and robustness. Our package is implemented in the Julia programming language [14], in order to obtain efficiency and still have access to high-level functionality. A milestone for computing in the Julia language was carried out within the Celeste project, which qualifies as petascale computation [52].

The numerical treatment of this problem has received attention in a large number of works, see summary papers such as [56], [46] [80] and [28] as well as software packages [8] and [29, 30, 54].

As we shall further describe in Section 3, many applications and algorithms are based on a sum of products representation of the M matrix. We will provide considerable functionality and efficiency for problems that can be expressed as

$$M(\lambda) = A_1 f_1(\lambda) + \dots + A_m f_m(\lambda).$$
⁽²⁾

In theory, any NEP can be expressed as (2), if one sets $m = n^2$. However, most algorithms based on (2) also assume that *m* is not too large, and become less attractive due to an increase in computation time unless *m* is relatively small. Our framework is efficient for structures as (2).

Our softare is designed to not be based on (2) but rather on certain interface functions, which define a NEP. This allows to represent NEPs, where (2) is not efficient. These framework interfaces are described in Section 3.1.

All of the NEP-algorithms are carefully documented in terms of references, and in order to encourage users to give credit to the original algorithm researchers.

2 BASIC USAGE

NEP-PACK is a registered package in the Julia central package repository, which makes it possible to install the package with very little effort

```
julia> ]
(v1.0) pkg> add NonlinearEigenproblems
julia> using NonlinearEigenproblems
```

Nonlinear eigenvalue problems are represented as objects of the type NEP, which can be created in a number of different ways. We have a gallery of problems available, which can be accessed through the nep_gallery command (further described in Section 6).

```
julia> nep=nep_gallery("neuron0");
```

This creates a NEP object which is used to model a neuron. This gallery problem stems from [60] which is also available as a model problem in DDE-BIFTOOL [21, 22]. The problem describes the stability the delay differential equation

$$\dot{x}_1(t) = -\kappa x_1(t) + \beta \tanh(x_1(t-\tau_3)) + a_1 \tanh(x_2(t-\tau_2))$$
(3)

$$\dot{x}_2(t) = -\kappa x_2(t) + \beta \tanh(x_2(t-\tau_3)) + a_2 \tanh(x_1(t-\tau_1)).$$
(4)

In particular, the stability of the zero solution is characterized by the eigenvalues with the largest real part of the following NEP

$$M(\lambda) := -\lambda I + A_0 + A_1 e^{-\tau_1 \lambda} + A_2 e^{-\tau_2 \lambda} + A_3 e^{-\tau_3 \lambda},$$

which belongs to the class of NEP commonly called a delay eigenvalue problems (DEP), see Section 3.2. The typeof command reveals that the problem is represented as a DEP:

```
julia> typeof(nep)
DEP{Float64,Array{Complex{Float64},2}}
```

As an illustration we solve this problem with our implementation of the NLEIGS method [27]

```
 \begin{array}{ll} julia> \Sigma = [-3.0-10\,\text{im}, -3+10\,\text{im}, 1+10\,\text{im}, 1-10\,\text{im}]; & \texttt{Region of interest} \\ julia> (\lambda, V) = \texttt{nleigs(nep}, \Sigma) \\ julia> using Plots; plotly(); \\ julia> plot(\lambda, linewidth=0, markershape=:xcross, label="\lambda") \\ \end{array}
```

The same results are obtained with the infinite Arnoldi method [39]

```
julia> (\lambda, V) = iar_chebyshev(nep, \sigma = -2) # keyword argument \sigma = target point
```

The result is given in Figure 1.



Fig. 1. The eigenvalues of the neuron example.

3 THE NEP REPRESENTATION

3.1 Accessing the data in a NEP

The vast amount of numerical methods and the vast amount of applications that have been developed and formulated in the literature have typically been expressed in the way that is the most natural for that specific method/application. Different methods require data from the NEP in different ways. Different applications are expressed in different ways. Our package is designed for algorithms and problems which can be (efficiently) expressed with the following quantities, which are selected to match the need from as many applications and algorithms as possible.

• compute_Mder(lambda,k) computes the kth derivative of M and evaluates it in λ

$$M_k = M^{(k)}(\lambda) \tag{5}$$

• compute_Mlincomb(lambda,V) computes the linear combination

$$\sum_{i=1}^{k} M^{(i-1)}(\lambda) v_i.$$
(6)

given the evaluation point λ and a matrix $V \in \mathbb{C}^{n \times k}$.

• compute_MM(S,V) computes the expression

$$\mathbb{M}(S,V) = \frac{1}{2\pi i} \int_{\Gamma} M(\xi) V(\xi I - S)^{-1} d\xi$$
⁽⁷⁾

for given matrices $S \in \mathbb{C}^{p \times p}$ and $V \in \mathbb{C}^{n \times p}$, and the contour Γ includes the eigenvalues of S. The form (7) is more commonly expressed in terms of matrix functions

$$\mathbb{M}(S,V) = A_1 V f_1(S) + \dots + A_m V f_m(S),$$

if A_1, \ldots , and f_1, \ldots are given as in (2).

Note that these compute functions are mathematically equivalent, i.e., there are explicit procedures to compute one quantity from any other quantity. We specify further relations in Section 3.3. Although they are mathematically equivalent, they are computationally very different and the transformations are not necessarily very efficient. For instance, in many applications (particular types of matrix-free situations) the matrix may not be directly available, but only available as a subroutine. In this case the user can specify (6), whereas computing a matrix as in (5) may not be computationally feasable.

Routines for some additional secondary quantities are also available:

- lin_solve solves a linear system associated with $M(\lambda)$. Further specifications can be made by inheriting from the type LinSolver.
- compute_rf computes the Rayleigh functional for the NEP, i.e., solves the nonlinear (scalar) equation

$$y^H M(\lambda) x = 0. ag{8}$$

• Several algorithms require the solution to a projected problem

$$Y^H M(\lambda) X z = 0 \tag{9}$$

which is again a NEP, see Section 5.3. The fact that projected NEPs are also of the type NEP, allows us to apply any of our methods as an inner solver.

errmeasure is a keyword argument accepted by most functions. The function handle should accept two arguments errmeasure(lambda, v) and computes an error estimate based on λ and v. The default_errmeasure computes the relative residual norm

$$\|M(\lambda)v\|$$

$\|v\|$

The construction allows the user to specify in which way the error should be measured. Hence other error measurements, such as the backward error presented in [32], can be implemented by the user.

In what follows we describe in what way state-of-the-art algorithms can be implemented with these compute functions.

• A large class of methods can be derived from Newton's metod, e.g., [1, 37, 49, 56, 58, 63, 73]. See also the summary of papers in, e.g., [28, 66? –68]. These algorithms have in common that one needs to compute for some vectors u_1 and u_2

$$M(\lambda)u_1 + M'(\lambda)u_2$$

where in some settings u_1 is zero. This is clearly possible with (6). They also require the solution to one (or many) linear systems, which can be computed with the lin_solve functionality.

- The standard application of contour integral methods require the solution to many linear systems (for different evaluation points) and only require a matrix vector product, i.e., (6). Methods in these papers can be classified in this way: [3, 4, 11] and the FEAST software [51], and acceleration techniques [81].
- Jacobi-Davidson methods [10, 18, 61, 79] are projection methods and hence require (9). For the deflation technique presented in [18], the quantity

$$U(\mu) = \frac{1}{2\pi} \int_{\Gamma} M(\xi) V(\xi I - S)^{-1} (\xi - \mu)^{-1} d\xi$$

and its derivatives are required in order for the deflated problem to implement the interfaces desired by the solvers of (9). These derivatives can be computed via the interface (6) and

the observations that $U^{(k)}(\mu) = (-M^{(k)}(\mu)V + kU^{(k-1)}(\mu))(S - \mu I)^{-1}$, and $U(\mu) = (\mathbb{M}(S, V) - \mathbb{M}(\mu I, V))(S - \mu I)^{-1}$. Specifically, due to structure the action of $\mathbb{M}(\mu I, V)$ can be computed using (6), and for an invariant pair $\mathbb{M}(S, V) = 0$.

- Other projection methods such as the nonlinear Arnoldi method [77] and variation [42] require the projection (9). Also the block preconditioned PCG for NEPs in [82] is a projection method. When solving large-scale problems, the storage of the projection subspace becomes costly as the number of iterations increase. In such cases, we need restarting techniques as discussed in [7], which can be directly implemented with manipulations of the projected NEP.
- Infinite Arnoldi type methods such as [38, 39, 41] and two-sided version [25] require (6). The restarted versions [40, 47] additionally require (7).
- Rayleigh functional methods, e.g., [49, 58, 59] depend on solution methods for the Rayleigh quotient.
- Certain algorithms are based on directly working with the block residual (7), e.g., block Newton [12, 13, 17, 19, 20, 44]
- Methods based on the QR-method, e.g., [26, 45] require (5)
- Rational Krylov methods such as, e.g., [27, 74, 75] requires access to linear solvers. Moreover, for a general NEP either (5) or (6) is used, and in the special case of an SPMF, see Section 3.2, it uses matrix function evaluations $f_0(S), \ldots, f_m(S)$.

3.2 The common types

We provide the user with efficient implementations of the compute functions in the previous section, for many common types:

- PEP: $M(\lambda) = A_1 + \lambda A_2 + \cdots \lambda^{m-1} A_m$
- DEP: $M(\lambda) = -\lambda I + A_0 + \sum_{i=1}^m e^{-\tau_i \lambda} A_i$
- SumNEP: $M(\lambda) = A(\lambda) + B(\lambda)$ where A and B are also NEPs
- SPMF_NEP: See below.
- LowRankNEP: An SPMF where the matrices are represented as low-rank factorizations

The most general of the above is the SPMF_NEP which represents the sum of products of matrices and functions (2). The functions f_i , i = 1, ..., m have to be defined in scalar sense, as well as in a matrix function sense. The implementation of the SPMF is designed to be efficient when $m \ll n$. The example below solves the NEP

$$M(\lambda) = \lambda A + e^{\lambda} B + \left(1 + \sqrt{\lambda}\right) C$$

with the block Newton method [44]:

```
julia> using LinearAlgebra
julia> A=ones(5,5); B=ones(5,5)+I; C=reverse(B,dims=1)
julia> f1= S-> S;
julia> f2= S-> exp(S)
julia> f3= S-> one(S)+sqrt(S);
julia> nep=SPMF_NEP([A,B,C],[f1,f2,f3]);
julia> blocknewton(nep,S=[1 0; 0 1.0], X=[1 0; 0 1; zeros(3,2)],displaylevel=1)
Iteration 1: Error: 2.112578 e+0 1
Iteration 2: Error: 3.705499 e+00
Iteration 3: Error: 2.361554 e+0 0
Iteration 4: Error: 2.361554 e+0 0
Iteration 5: Error: 3.543752 e-0 3
Iteration 6: Error: 4.080188 e-0 7
Iteration 7: Error: 2.885914 e-15
(Complex{Float64}[0.557832+0.0im -3.03756 e-16+0.0im; -7.18644 e-16+0.0im;
0.557832+0.0im], Complex{Float64}[-0.617521+0.0im -0.00206428+0.0im;
```

```
0.00206428-0.0 im -0.617521+0.0 im; ...; -0.00206428+0.0 im 0.617521-0.0 im; 0.617521-0.0 im])
```

3.3 Equivalence of interfaces

As an example how (6) can be computed from (7): $\mathbb{M}(S, V)e_1$ is equal to (6) where $S \in \mathbb{R}^{k \times k}$ is the bidiagonal matrix with λ in the main diagonal, $S_{i+1,i} = i$ and $V = [v_1, \ldots, v_k]$. This equivalence follows by expressing $M(\lambda)$ in SPMF_NEP format (2) in (6) and by using [31, Definition 1.2] with a proper rescaling.

4 PROBLEM TRANSFORMATIONS

The abstraction of the NEPs to be essentially specified by well-defined compute functions (Section 3) leads to the advantage that problems can be transformed leading by defining new compute functions.

We have implemented a number of ways to transform the problem

• One can shift and scale the problem, i.e., define a new NEP

$$\tilde{M}(\lambda) = M(\alpha \lambda + \sigma) \tag{10}$$

This functionality is available in the shift_and_scale function.

• One can carry out a Möbius transformation of the problem, i.e., define a new NEP

$$\tilde{M}(\lambda) = M((a\lambda + b)/(c\lambda + d))$$

This functionality is available in the mobius_transformation function.

• One can deflate eigenvalue (or invariant pairs) from a NEP as specified, e.g., in [17]. This is provided by the function effenberger_deflation

Although the above functions provide convenient features for a user, they may not always lead to extremely efficient algorithms, since a transformed problem may have some computational overhead. Therefore, certain functionality is also provided at an algorithm level, e.g., shifting and scaling is available in the infinite Arnoldi methods.

The deflation can be used to compute one pair at a time and avoid reconvergence, e.g., as follows:

```
julia> nep=nep_gallery("dep0");
julia> (s,v)=newton(nep);
julia> n=size(nep,1);
julia> S0=reshape([s],1,1);
julia> V0=reshape(v,n,1);
julia> dnep=effenberger_deflation(nep,S0,V0)
julia> (s2,v2)=augnewton(dnep); # this converges to different eigval
julia> minimum(svdvals(compute_Mder(nep,s2)))
9.323003321058995 e=17
```

5 NEP-SOLVER ALGORITHM IMPLEMENTATIONS

We have implemented several algorithms as well as extensions.

5.1 Newton-type methods

Several flavors of Newton's method are available. Armijo rule steplength combined with deflation increases reliability of these methods considerably.

- augnewton: Augmented Newton [73]
- resinv: Residual inverse iteration [49]
- blocknewton: Block Newton method [44]

- quasinewton: Quasi-Newton method [37]
- implicitdet: Implicit determinant [63]
- newtonqr: Newton QR approach [45]
- mslp: Method of successive linear problems [56]
- sgiter: Safe-guarded iteration [77]
- rfi: Rayleigh functional iteration [58]
- broyden: Broydens method [36]

5.2 Krylov-based methods

- nlar Nonlinear Arnoldi method [77]
- nleigs NLEIGS [27]
- iar (and variants) infinite Arnoldi method [16, 41]

5.3 Projection methods

- nlar Nonlinear Arnoldi method [77]
- jd Jacobi-Davidson method [10] and [18]

5.4 Contour integral methods

• beyn_contour [12]

6 BENCHMARK PROBLEMS

We have made a number of benchmark problems available via the nep_gallery command, e.g., a standardized delay eigenvalue problem can be loaded with

julia> nep=nep_gallery("dep0");

Several large-scale problems, such as the model of the waveguide in [16, 53] are available.

The library of Berlin-Manchester benchmark problem in the MATLAB NLEVP package [9], can be accessed in NEP-PACK in two ways. A subset of the problems from that collection have been converted to native NEP-PACK format, e.g., the "gun" problem can be loaded with the commands

julia> nep=nep_gallery("nlevp_native_gun");

Several implementation techniques had to be adapted to Julia in order to become efficient, e.g., the Bessel function nonlinearity in the "fiber" benchmark as described in Section A. The NLEVP problems can also be accessed by using the Julia packages which can communicate with a MATLAB process running in the background. We have provided wrappers such that the problems can be loaded with the command:

Note that the wrapper is completely transparent such that quasinewton makes a call to the NLEVP library (available in a MATLAB process which runs in the background) every time it accesses the NEP. Due to the communication overhead, it is generally preferred to use the native methods for larger problems, due to the overhead generated by the communication between Julia and MATLAB.

7 PERFORMANCE COMPARISON

7.1 NLEIGS Julia implementation

We want to provide empirical support for the performance of our package, and the Julia language. In order to do so, we used the MATLAB NLEIGS implementation¹ described in [27]. For illustration purposes we converted the MATLAB code to Julia and the NEP-PACK procedures to access data, such that it can be considered a good candidate to assess the performance of Julia vs MATLAB.

We used the same two large scale problems as in the above paper and included as benchmarks in the MATLAB implementation; the "gun" problem, and the "particle in a canyon" problem, and we ran the same six experiments. See [27] for full details. The experiments were run on a MacBook Pro, with a 2.9 GHz Intel i7-6920HQ, 2x4 cores, and 16 GB memory. We used MATLAB v8.4.0 (R2014b) and Julia v1.0.2. The results are reported in Table 1. Our Julia reimplementation is faster and consumes less memory. The general explanation is the way Julia handles data structures, which improves the possibility to carry out Just-In-Time compilation. More precisely, we observed that the inner loops (often consisting of orthgonalization) were considerably faster, also handling of sparse matrices differed considerably in performance.

Each MATLAB experiment was carried out 20 times, and the fastest run is reported. For the Julia implementation we used the Benchmark toolbox, with parameter seconds=500. We report the median CPU-time for the NEP-PACK implementation in Table 1. The memory usage is the amount of memory used at the end of the algorithm, including cached LU factors. Note that although the implementations should behave identically, the number of iterations required for convergence may vary a bit due to different start vectors and tiny rounding errors that build up over time.

	MATLAB				Julia / NEP-PACK			
	Iter	Conv. λ	CPU	Memory	Iter	Conv. λ	CPU	Memory
Gun P	100	17	6.4 s	420 MB	100	17	3.9 s	59 MB
Gun R1	100	21	6.9 s	421 MB	100	21	4.0 s	59 MB
Gun R2	95	21	20.1 s	413 MB	95	21	12.7 s	51 MB
Gun S	70	21	5.2 s	408 MB	71	21	3.7 s	46 MB
Particle R2	78	2	16.6 s	213 MB	74	2	7.5 s	73 MB
Particle S	141	2	13.0 s	239 MB	134	2	5.9 s	92 MB

Table 1. Performance comparison of NLEIGS implementation in NEP-PACK and the original MATLAB implementation

7.2 Computation of many derivatives

In order to show the extendability of our framework, we now show an unusual NEP with 200 terms. It can be created and solved as follows.

¹NLEIGS version 0.5 available for download at http://twr.cs.kuleuven.be/research/software/nleps/nleigs.html.

```
julia> using Random, BenchmarkTools
julia> Random.seed!(0)
julia> fv=Vector{Function}(undef,m);
julia> fv=Vector{Function}(undef,m);
julia> for i=1:m; fv[i]=(x-> exp(i^(1/6)*x)); end;
julia> fv[1]=x->one(x); fv[2]=x->x;
julia> Av=Vector{SparseMatrixCSC}(undef,m);
julia> an=50;
julia> for i=1:m; Av[i]=sprand(n,n,0.01); end;
julia> nep=SPMF_NEP(Av,fv);
julia> v0=ones(n);
julia> @btime iar(nep,maxit=100,v=v0)
7.568 s (13079550 allocations: 3.88 GiB)
```

Due to the fact that the problem has many exponential terms, the evaluation of the derivatives required in the infinite Arnoldi method becomes dominant. Precomputation of derivates are available through the DerSPMF-type, which essentially precomputes derivatives in a given point, but otherwise behaves as the parent NEP. The following code shows the improvement.

```
julia> dnep=DerSPMF(nep,0.0,100);
julia> @btime iar(dnep,maxit=100,v=v0)
3.365 s (12254494 allocations: 1.07 GiB)
```

Note that DerSPMF is extending the functionality of standard NEPs, by allowing a precomputation to take place, but maintain all other functionality of the original NEP. The DerSPMF is again a NEP and precomputation in several points can be achieved by successive application of the DerSPMF.

8 CONCLUSIONS

We have presented and described the current release of the package NEP-PACK. The current state of the software is ready to be used for many use-cases, e.g., comparison of algorithms and development of new algorithms, as we have shown in Section 7.1 that it already outperforms other publicly available implementations of NEP-solvers. Several implementations currently do not have the full functionality, e.g., some functions do not return eigenvectors but only eigenvalues, although they are available in theory. Further testing of other NEP-types, applications and algorithms to obtain improvements of efficiency for large-scale problems. The package has been tested on the HPC-environment at KTH Royal Institute of Technology, and results will be reported in a later version. The development of this package is done in a public GIT-HUB repository² and has a public users manual³, in order to improve possibilities to interact with users and other developers.

ACKNOWLEDGMENTS

The authors wish to thank Antti Koskela (Univ. Helsinki) for comments, suggestions and discussions regarding an early version of the package. We also wish to express our thanks to researchers who have made their software available online, e.g., C. Effenberger and R. Van Beeumen.

REFERENCES

- P. Anselone and L. Rall. 1968. The solution of characteristic value-vector problems by Newton's method. Numer. Math. 11 (1968), 38–45.
- [2] Juan Carlos Araujo-Cabarcas, Christian Engström, and Elias Jarlebring. 2018. Efficient resonance computations for Helmholtz problems based on a Dirichlet-to-Neumann map. J. Comput. Appl. Math. 330 (2018), 177 – 192. https: //doi.org/10.1016/j.cam.2017.08.012

²https://github.com/nep-pack/NonlinearEigenproblems.jl

³https://nep-pack.github.io/NonlinearEigenproblems.jl

- [3] J. Asakura, T. Sakurai, H. Tadano, T. Ikegami, and K. Kimura. 2009. A numerical method for nonlinear eigenvalue problems using contour integrals. JSIAM Letters 1 (2009), 52–55.
- [4] J. Asakura, T. Sakurai, H. Tadano, T. Ikegami, and K. Kimura. 2010. A numerical method for polynomial eigenvalue problems using contour integral. Japan J. Indust. Appl. Math. 27 (2010), 73–90.
- [5] M. Betcke. 2007. Iterative projection methods for symmetric nonlinear eigenvalue problems with applications. Ph.D. Dissertation. Technical University Hamburg-Harburg.
- [6] M. Betcke and H. Voss. 2007. Stationary Schrödinger equations governing electronic states of quantum dots in the presence of spinorbit splitting. Appl. Math. 52 (2007), 267 – 284.
- [7] Marta M. Betcke and Heinrich Voss. 2017. Restarting iterative projection methods for Hermitian nonlinear eigenvalue problems with minmax property. Numer. Math. 135, 2 (01 Feb 2017), 397–430. https://doi.org/10.1007/s00211-016-0804-3
- [8] T. Betcke, N. J. Higham, V. Mehrmann, C. Schröder, and F. Tisseur. 2010. NLEVP: A Collection of Nonlinear Eigenvalue Problems. Technical Report. University of Manchester.
- [9] Timo Betcke, Nicholas J. Higham, Volker Mehrmann, Christian Schröder, and Françoise Tisseur. 2013. NLEVP: A Collection of Nonlinear Eigenvalue Problems. ACM Trans. Math. Softw. 39, 2, Article 7 (Feb. 2013), 28 pages. https://doi.org/10.1145/2427023.2427024
- [10] T. Betcke and H. Voss. 2004. A Jacobi-Davidson type projection method for nonlinear eigenvalue problems. Future Generation Computer Systems 20, 3 (2004), 363–372.
- W.-J. Beyn. 2012. An integral method for solving nonlinear eigenvalue problems. *Linear Algebra Appl.* 436, 10 (2012), 3839–3863.
- [12] Wolf-Jürgen Beyn, Cedric Effenberger, and Daniel Kressner. 2011. Continuation of eigenvalues and invariant pairs for parameterized nonlinear eigenvalue problems. *Numer. Math.* 119, 3 (10 Jul 2011), 489. https://doi.org/10.1007/ s00211-011-0392-1
- [13] Wolf-Jürgen Beyn and Vera Thümmler. 2010. Continuation of invariant subspaces for parameterized quadratic eigenvalue problems. SIAM J. Matrix Anal. Appl. 31, 3 (2010), 1361–1381. https://doi.org/10.1137/080723107
- [14] Jeff Bezanson, Alan Edelman, Stefan Karpinski, and Viral B. Shah. 2017. Julia: A Fresh Approach to Numerical Computing. SIAM Rev. 59, 1 (2017), 65–98. https://doi.org/10.1137/141000671 arXiv:https://doi.org/10.1137/141000671
- [15] E. Bueler. 2007. Error bounds for approximate eigenvalues of periodic-coefficient linear delay differential equations. SIAM J. Numer. Anal. 45, 6 (2007), 2510–2536.
- [16] O. Runborg E. Jarlebring, G. Mele. 2017. The waveguide eigenvlaue problem and the tensor infinite Arnoldi method. SIAM J. Sci. Comput. 39 (2017), A1062–A1088.
- [17] C. Effenberger. 2013. Robust Solution Methods for Nonlinear Eigenvalue Problems. Ph.D. Dissertation. EPF Lausanne.
- [18] C. Effenberger. 2013. Robust successive computation of eigenpairs for nonlinear eigenvalue problems. SIAM J. Matrix Anal. Appl. 34, 3 (2013), 1231–1256. https://doi.org/10.1137/120885644
- [19] C. Effenberger and D. Kressner. 2012. Chebyshev interpolation for nonlinear eigenvalue problems. BIT 52, 4 (2012), 933–951.
- [20] C. Effenberger, D. Kressner, and C. Engström. 2012. Linearization techniques for band structure calculations in absorbing photonic crystals. Int. J. Numer. Methods Eng. 89, 2 (2012), 180–191.
- [21] K. Engelborghs, T. Luzyanina, and D. Roose. 2002. Numerical Bifurcation Analysis of Delay Differential Equations Using DDE-BIFTOOL. ACM Trans. Math. Softw. 28, 1 (2002), 1–24.
- [22] K. Engelborghs, T. Luzyanina, and G. Samaey. 2001. DDE-BIFTOOL v. 2.00: a Matlab package for bifurcation analysis of delay differential equations. Technical Report. K.U.Leuven, Belgium.
- [23] C. Engström. 2010. On the spectrum of a holomorphic operator-valued function with applications to absorptive photonic crystals. *Math. Models Methods Appl. Sci.* 20, 8 (2010), 1319–1341.
- [24] Sonia Fliss. 2013. A Dirichlet-to-Neumann Approach for The Exact Computation of Guided Modes in Photonic Crystal Waveguides. SIAM J. Sci. Comput. 35, 2 (2013), B438–B461.
- [25] S. W. Gaaf and E. Jarlebring. 2017. The infinite bi-Lanczos method for nonlinear eigenvalue problems. SIAM J. Sci. Comput. 39, SIAM J. Sci. Comput. (2017), S898–S919. https://doi.org/10.1137/16M1084195 arXiv:https://doi.org/10.1137/16M1084195
- [26] C. Kristopher Garrett, Zhaojun Bai, and Ren-Cang Li. 2016. A nonlinear QR algorithm for banded nonlinear eigenvalue problems. ACM Trans. Math. Softw. 43, 1, Article 4 (Aug. 2016), 19 pages. https://doi.org/10.1145/2870628
- [27] S. Güttel, R. Van Beeumen, K. Meerbergen, and W. Michiels. 2014. NLEIGS: A Class of Fully Rational Krylov Methods for Nonlinear Eigenvalue Problems. SIAM J. Sci. Comput. 36, 6 (2014), A2842–A2864.
- [28] Stefan Güttel and Francoise Tisseur. 2017. The nonlinear eigenvalue problem. Acta Numerica 26 (2017), 1–94. https://doi.org/10.1017/S0962492917000034
- [29] V. Hernandez, J. E. Roman, and V. Vidal. 2003. SLEPc: Scalable Library for Eigenvalue Problem Computations. Lect. Notes Comput. Sci. 2565 (2003), 377–391.

- [30] Vicente Hernandez, Jose E. Roman, and Vicente Vidal. 2005. SLEPc: A scalable and flexible toolkit for the solution of eigenvalue problems. ACM Trans. Math. Software 31, 3 (2005), 351–362.
- [31] N. J. Higham. 2006. Functions of Matrices. In Handbook of linear algebra, L. Hogben (Ed.). CRC Press.
- [32] N. J. Higham, R.-C. Li, and F. Tisseur. 2008. Backward error of polynomial eigenproblems solved by linearization. SIAM J. Matrix Anal. Appl. 29, 4 (2008), 1218-1241.
- [33] T. Insperger and G. Stépán. 2002. Semi-discretization method for delayed systems. Int. J. Numer. Methods Eng. 55, 5 (2002), 503–518.
- [34] T. Insperger and G. Stépán. 2002. Stability chart for the delayed Mathieu equation. Proc. R. Soc. Lond., Ser. A, Math. Phys. Eng. Sci. 458, 2024 (2002), 1989–1998.
- [35] E. Jarlebring. 2008. The spectrum of delay-differential equations: numerical methods, stability and perturbation. Ph.D. Dissertation. TU Braunschweig.
- [36] E. Jarlebring. 2017. Broyden's method for nonlinear eigenproblems. Technical Report. KTH Royal Institute of Technology.
- [37] E. Jarlebring, A. Koskela, and G. Mele. 2018. Disguised and new quasi-Newton methods for nonlinear eigenvalue problems. Numer. Algor. 79, 1 (01 Sep 2018), 311–335. https://doi.org/10.1007/s11075-017-0438-2
- [38] Elias Jarlebring, Karl Meerbergen, and Wim Michiels. 2010. An Arnoldi method with structured starting vectors for the delay eigenvalue problem, In Proceedings of the 9th IFAC workshop on time-delay systems, Prague. *IFAC Proceedings Volumes* 43, 2, 57 – 62. http://www.sciencedirect.com/science/article/pii/S1474667016325034 9th IFAC Workshop on Time Delay Systems.
- [39] E. Jarlebring, K. Meerbergen, and W. Michiels. 2010. A Krylov method for the delay eigenvalue problem. SIAM J. Sci. Comput. 32, 6 (2010), 3278–3300.
- [40] E. Jarlebring, K. Meerbergen, and W. Michiels. 2014. Computing a partial Schur factorization of nonlinear eigenvalue problems using the infinite Arnoldi method. SIAM J. Matrix Anal. Appl. 35, 2 (2014), 411–436. https://doi.org/10.1137/ 110858148 arXiv:https://doi.org/10.1137/110858148
- [41] E. Jarlebring, W. Michiels, and K. Meerbergen. 2012. A linear eigenvalue algorithm for the nonlinear eigenvalue problem. *Numer. Math.* 122, 1 (2012), 169–195.
- [42] E. Jarlebring and H. Voss. 2005. Rational Krylov for nonlinear eigenproblems, an iterative projection method. Appl. Math. 50, 6 (2005), 543–554.
- [43] L. Kaufman. 2006. Eigenvalue problems in fiber optic design. SIAM J. Matrix Anal. Appl. 28, 1 (2006), 105–117.
- [44] D. Kressner. 2009. A block Newton method for nonlinear eigenvalue problems. Numer. Math. 114, 2 (2009), 355-372.
- [45] V. Kublanovskaya. 1970. On an approach to the solution of the generalized latent value problem for λ -matrices. *SIAM J. Numer. Anal.* 7 (1970), 532–537.
- [46] V. Mehrmann and H. Voss. 2004. Nonlinear eigenvalue problems: A Challange for modern eigenvalue methods. GAMM Mitteilungen 27 (2004), 121–152.
- [47] Giampaolo Mele and Elias Jarlebring. 2018. On restarting the tensor infinite Arnoldi method. BIT 58, 1 (01 Mar 2018), 133–162. https://doi.org/10.1007/s10543-017-0671-z
- [48] W. Michiels and S.-I. Niculescu. 2007. Stability and Stabilization of Time-Delay Systems: An Eigenvalue-Based Approach. SIAM Publications, Philadelphia.
- [49] A. Neumaier. 1985. Residual inverse iteration for the nonlinear eigenvalue problem. SIAM J. Numer. Anal. 22 (1985), 914–923.
- [50] Kouhei Ooi, Yoshinori Mizuno, Tomohiro Sogabe, Yusaku Yamamoto, and Shao-Liang Zhang. 2017. Solution of a nonlinear eigenvalue problem using signed singular values. *East Asian Journal on Applied Mathematics* 7, 4 (2017), 799–809. https://doi.org/10.4208/eajam.181016.300517c
- [51] Eric Polizzi. 2009. Density-matrix-based algorithm for solving eigenvalue problems. Phys. Rev. B 79 (Mar 2009), 115112. Issue 11. https://doi.org/10.1103/PhysRevB.79.115112
- [52] Jeffrey Regier, Kiran Pamnany, Keno Fischer, Andreas Noack, Maximilian Lam, Jarrett Revels, Steve Howard, Ryan Giordano, David Schlegel, Jon McAuliffe, and Rollin Thomas. 2018. *Cataloging the Visible Universe through Bayesian Inference at Petascale.* Technical Report. University of California, Berkeley. arXiv preprint arXiv:1801.10277.
- [53] E. Ringh, G. Mele, J. Karlsson, and E. Jarlebring. 2018. Sylvester-based preconditioning for the waveguide eigenvalue problem. *Linear Algebra Appl.* 542 (2018), 441 – 463. https://doi.org/10.1016/j.laa.2017.06.027 Proceedings of the 20th ILAS Conference, Leuven, Belgium 2016.
- [54] J. E. Roman, C. Campos, E. Romero, and A. Tomas. 2018. SLEPc Users Manual. Technical Report DSIC-II/24/02 Revision 3.10. D. Sistemes Informàtics i Computació, Universitat Politècnica de València.
- [55] O. Rott and E. Jarlebring. 2010. An iterative method for the multipliers of periodic delay-differential equations and the analysis of a PDE milling model. In *Proceedings of the 9th IFAC workshop on time-delay systems, Prague.* 1–6.
- [56] A. Ruhe. 1973. Algorithms for the nonlinear eigenvalue problem. SIAM J. Numer. Anal. 10 (1973), 674-689.
- [57] K. Schmidt and P. Kauf. 2009. Computation of the band structure of two-dimensional photonic crystals with hp finite elements. Computer Methods in Applied Mechanics and Engineering 198, 13 (2009), 1249 – 1259. https://doi.org/10.

1016/j.cma.2008.06.009 HOFEM07.

- [58] K. Schreiber. 2008. Nonlinear Eigenvalue Problems: Newton-type Methods and Nonlinear Rayleigh Functionals. Ph.D. Dissertation. TU Berlin.
- [59] Hubert Schwetlick and Kathrin Schreiber. 2012. Nonlinear Rayleigh functionals. *Linear Algebra Appl.* 436, 10 (2012), 3991 – 4016. http://www.sciencedirect.com/science/article/pii/S0024379510003447 Special Issue dedicated to Heinrich Voss's 65th birthday.
- [60] L. P. Shayer and S. A. Campbell. 2000. Stability, bifurcation, and multistability in a system of two coupled neurons with multiple time delays. *SIAM J. Appl. Math.* 61, 2 (2000), 673–700.
- [61] G. Sleijpen, A. G. Booten, D. R. Fokkema, and H. A. van der Vorst. 1996. Jacobi-Davidson type methods for generalized eigenproblems and polynomial eigenproblems. BIT 36, 3 (1996), 595–633.
- [62] Wojciech Śmigaj, Timo Betcke, Simon Arridge, Joel Phillips, and Martin Schweiger. 2015. Solving Boundary Integral Problems with BEM++. ACM Trans. Math. Softw. 41, Article 6 (Feb. 2015), 40 pages. https://doi.org/10.1145/2590830
- [63] A. Spence and C. Poulton. 2005. Photonic band structure calculations using nonlinear eigenvalue techniques. J. Comput. Phys. 204, 1 (2005), 65–81.
- [64] O. Steinbach. 2007. Numerical approximation methods for elliptic boundary value problems: finite and boundary elements. Springer.
- [65] O. Steinbach and G. Unger. 2009. A boundary element method for the Dirichlet eigenvalue problem of the Laplace operator. *Numer. Math.* 113 (2009), 281–298.
- [66] D. B. Szyld and F. Xue. 2013. Local convergence analysis of several inexact Newton-type algorithms for general nonlinear eigenvalue problems. Numer. Math. 123, 2 (2013), 333–362. https://doi.org/10.1007/s00211-012-0489-1
- [67] D. B. Szyld and F. Xue. 2014. Several properties of invariant pairs of nonlinear algebraic eigenvalue problems. IMA J. Numer. Anal. 34 (2014), 921–954.
- [68] D. B. Szyld and F. Xue. 2015. Local convergence of Newton-like methods for degenerate eigenvalues of nonlinear eigenproblems. Numer. Math. 129, 2 (2015), 353–381. https://doi.org/10.1007/s00211-014-0639-8
- [69] J. Tausch and J. Butler. 2000. Floquet multipliers of periodic waveguides via Dirichlet-to-Neumann maps. J. Comput. Phys. 159, 1 (2000), 90–102.
- [70] J. Tausch and J. Butler. 2002. Efficient analysis of periodic dielectric waveguides using Dirichlet-to-Neumann maps. J Opt Soc Am A Opt Image Sci Vis. 19, 6 (2002), 1120–8.
- [71] F. Tisseur and K. Meerbergen. 2001. The quadratic eigenvalue problem. SIAM Rev. 43, 2 (2001), 235-286.
- [72] G. Unger. 2013. Convergence orders of iterative methods for nonlinear eigenvalue problems. In Advanced Finite Element Methods and Applications. Springer, 217–237.
- [73] H. Unger. 1950. Nichtlineare Behandlung von Eigenwertaufgaben. Z. Angew. Math. Mech. 30 (1950), 281–282. English translation: http://www.math.tu-dresden.de/~schwetli/Unger.html.
- [74] R. Van Beeumen, K. Meerbergen, and W. Michiels. 2013. A rational Krylov method based on Hermite interpolation for Nonlinear Eigenvalue Problems. SIAM J. Sci. Comput. 35, 1 (2013), A327–A350.
- [75] R. Van Beeumen, K. Meerbergen, and W. Michiels. 2015. Compact rational Krylov methods for Nonlinear Eigenvalue Problems. SIAM J. Sci. Comput. 36, 2 (2015), 820–838.
- [76] H. Voss. 2003. A maxmin principle for nonlinear eigenvalue problems with application to a rational spectral problem in fluid-solid vibration. Appl. Math., Praha 48, 6 (2003), 607–622.
- [77] H. Voss. 2004. An Arnoldi method for nonlinear eigenvalue problems. BIT 44 (2004), 387 401.
- [78] H. Voss. 2005. Locating real eigenvalues of a spectral problem in fluid-solid type structures. J. Appl. Math. 2005, 1 (2005), 37–48.
- [79] H. Voss. 2007. A new justification of the Jacobi-Davidson method for large eigenproblems. *Linear Algebra Appl.* 424 (2007), 448–455.
- [80] H. Voss. 2012. Chapter Nonlinear Eigenvalue Problems. CRC press. Handbook in Linear Algebra.
- [81] J. Xiao, C. Zhang, T.-M. Huang, and T. Sakurai. 2017. Solving large-scale nonlinear eigenvalue problems by rational interpolation and resolvent sampling based Rayleigh-Ritz method. *Internat. J. Numer. Methods Engrg* 110, 8 (2017), 776–800.
- [82] F. Xue. 2018. A Block Preconditioned Harmonic Projection Method for Large-Scale Nonlinear Eigenvalue Problems. SIAM J. Matrix Anal. Appl. 40, 3 (2018), A1809–A1835. https://doi.org/10.1137/17M112141X

A THE FIBER BENCHMARK

The benchmark problem in [9] called "fiber" contains a term defined as

 $f(\lambda) = g(\sqrt{\lambda}L)$

where

$$g(x) = \frac{L+0.5}{L^2} x \frac{K_1'(x)}{K_1(x)}$$

Bessel matrix functions are not available, so we use an interpolation approach to create a matrix function.

$$g(x) = \frac{\alpha(x)}{\beta(x)}$$

where

$$\alpha(x) = \frac{L+0.5}{L^2} \frac{x}{K_1(x)^2}$$
(11)

$$\beta(x) = \frac{1}{K_1'(x)K_1(x)}$$
(12)

The functions α and β are selected such that we can carry out polynomial interpolation. Note that $K_1(x)$ has a singularity at zero. We create Newton polynomials which interpolate α and β in certain interpolation points. The interpolation is carried out in BigFloat, and subsequently rounded to Float64 in order to lessen the impact of round-off error with many interpolation points.

B INTERFACE TO IAR CHEBYSHEV VARIANT

The method iar_chebyshev requires, at each iteration, the computation of the vector y_0 defined in [41, (22)]. We refer to that paper for all the notation we use. Our interface handles this computation for PEP, DEP, with the derivation of [41], and we have further derived the analogous formula for SPMF_NEP. More precisely, by using the Taylor series expansion on (2), it holds

$$y_0 = \sum_{i=0}^m A_i X b_i (D_N) \hat{T}_N(0) - Y \hat{T}_N(0)$$

where $\hat{T}_N(\theta) := (\hat{T}_0(\theta), \hat{T}_1(\theta), \dots, \hat{T}_N(\theta))^T$, D_N is the derivation matrix in Chebyshev basis, defined as

$$D_N := \begin{pmatrix} 0\\ I_{N,N+1}L_{N+1}^{-1} \end{pmatrix} \in \mathbb{R}^{(n+1) \times (n+1)}$$

and derived from [41, (21)] and $b_i(\lambda) = (f_i(0) - f_i(\lambda))/\lambda = f_i[\lambda, 0]$. With the same technique, this formula can be extended to the computation of \tilde{y}_0 for the shifted and scaled problem (10) without explicitly constructing (10) but directly using (2) as follows

$$\tilde{y}_0 = -\alpha \sum_{i=0}^m M_i X b_i (\sigma I + \alpha D_N) \hat{T}_N(0) - Y \hat{T}_N(0),$$

where $b_i(\sigma + \alpha\lambda) = (f_i(\sigma) - f_i(\sigma + \alpha\lambda))/\lambda = -\alpha f[\sigma + \alpha\lambda, \sigma]$. The computation of the divided differences matrices $b_i(\sigma I + \alpha D_N) = -\alpha f_i[\sigma I + \alpha D_N, \sigma I]$ can be carried out in terms of functions defining the original problem (2) by applying the following result, which is a consequence of the theory for Fréchet derivative in [31, Section 3.2].

LEMMA B.1. Given $S, I \in \mathbb{C}^{n \times n}$ where I is the identity matrix, $\sigma, \alpha \in \mathbb{C}$ and f is a complex analytic function, the following relation is fulfilled

$$f\left(\begin{bmatrix}\sigma I + \alpha S & I\\ 0 & \sigma I\end{bmatrix}\right) = \begin{bmatrix}f(S) & f[\sigma I + \alpha S, \sigma I]\\ 0 & f(\sigma)I\end{bmatrix}.$$

0X:13