UFANS: U-SHAPED FULLY-PARALLEL ACOUSTIC NEURAL STRUCTURE FOR STATISTICAL PARAMETRIC SPEECH SYNTHESIS WITH 20X FASTER

Dabiao Ma, Zhiba Su, Yuhao Lu

Turing Robot co.ltd Multi-modal Group Beijing, China

ABSTRACT

Neural networks with Auto-regressive structures, such as Recurrent Neural Networks (RNNs), have become the most appealing structures for acoustic modeling of parametric text to speech synthesis (TTS) in recent studies. Despite the prominent capacity to capture long-term dependency, these models consist of massive sequential computations that cannot be fully parallel. In this paper, we propose a U-shaped Fully-parallel Acoustic Neural Structure (UFANS), which is a deconvolutional alternative of RNNs for Statistical Parametric Speech Synthesis (SPSS). The experiments verify that our proposed model is over **20** times faster than RNN based acoustic model, both training and inference on GPU with comparable speech quality. Furthermore, We also investigate that how long information dependence really matters to synthesized speech quality.

Index Terms— Text-to-Speech, Acoustic Model, UFANS, U-Net, Fully-parallel

1 Introduction

Text-to-Speech (TTS) is to convert a text string to speech of a specific speaker's voice. The typical parametric TTS system extracts linguistic features from raw text by front-end text analyzer, which is then feed into an acoustic neural networks for intermediate acoustic features extraction [1]. Afterwards, the obtained acoustic features are converted to waveforms by a vocoder, e.g. WORLD [2], STRAIGHT [3], and WaveNet based vocoder [4], to obtain the final speech.

Recurrent neural structures have achieved great success as acoustic models due to their capacity to capture longterm dependencies. Variants like Long Short-Term Memory (LSTM) [5], Gated Recurrent Unit (GRU) [6] and other RNN structures are now broadly used in text-to-speech [7] with very good records. But all the recurrent structures result in a high time latency since the computation of current step depends on the completion of previous computations. Quasi-Recurrent Neural Network (QRNN) [8] and Simple Recurrent Wenxuan Wang, Zhen Li*

Chinese University of Hongkong, Shenzhen School of Science and Engineering Shenzhen Research Institute of Big Data (SRIBD) Shenzhen, Guangdong, China

Unit (SRU) [9] tries to make most of the computations independent of the previous computations and claims that it is 5-10 times faster than an optimized LSTM on GPU. But it cannot fully utilize the power of GPU since it still preserves recurrent structures.

CNN has also been used as acoustic model in recent studies. In [10], [11] and [12], Convolutional layers are used to model low-dimensional audio representation in an autoregressive manner. It effectively accelerates training, but the output variable depends linearly on its own previous values, which causes high inference latency.

U-Net, which was first proposed for image segmentation [13], is a neural network designed with one contraction path and one expansive path. Within U_Net, those pooling and up-sampling operation along the spatial dimension make the receptive field increases exponentially and high way connection allows the combination of different scales features. Inspired by the success of U_Net in image segmentation, U-shaped models have been proposed for various acoustic applications, e.g., denoise [14], audio source separation [15].

Here we propose a fully convolutional structure UFANS motivated by U-Net[13] that models long time dependencies while dozens of times speed-up both on training and inference period. As far as our knowledge, no fully parallel convolutional or transposed convolutional structure including U-net has ever been proposed for acoustic decoder in speech synthesis. And we also try to answer the question that how long information dependency really matters mentioned in [16].

In section 2, our UFANS model is introduced in detail. In section 3, we describe the experiments and try to explain the important features of UFANS. And we draw our conclusion in section 4.

2 U-shaped Fully-parallel Acoustic Neural Structure (UFANS)

2.1 Overall structure of our UFANS model

Considering the superiority of U-shaped model, we first propose an UFANS model, whose components are all paralleliz-

^{*} indicates the corresponding authors

able convolutional and transposed convolutional layers. The structure of UFANS model is shown in Fig. 1, with 2 down-samplings and 2 up-samplings along the frame dimension.



Fig. 1. UFANS, with 2 down-sampling and up-samplings.

Different convolution blocks are designed sophisticated for different phases in UFANS model. Fig. 2 is the revised structure of convolution block of the contraction phase in U-shaped model. Inspired by the gated activation unit used in [5] and [6], we novelty split the output of convolutions layers along channel dimension in half [17], which enhances the capacity of UFANS to adaptively control the input flow. Besides, in UFANS, average pooling is used to keep more information in our regression task. The formula is presented as follows,

$$P_1, P_2 = Split(Conv(Input)) \tag{1}$$

$$Output = tanh(P_1) * sigmoid(P_2)$$
(2)



Fig. 2. Convolution block (A in figure 1) of contraction phase, here the operation 'split is performed on the channel size.

Correspondingly, the similar structure of convolution block in expansive phase (D in Fig. 1) in presented in Fig. 3. The input of this block consists of two parts, one from the previous layer, another from the corresponding output of the contraction phase. Besides, dropout is added here as a regulization to increase the generalization capacity of our UFANS. The formula is as follows,

$$P_1, P_2 = Split(Conv(Dropout(Input1 + Input2))) \quad (3)$$

$$Output = tanh(P_1) * sigmoid(P_2)$$
(4)



Fig. 3. Convolution block (D in Figure 1) of expansive phase, here the operation 'split' is performed on the channel size.

The final block consists of a convolution with *tanh* activation function and a dense layer for output. It's worthy mentioning that all the components in UFANS are parallelizable convolutional layers. Thus, the model can be accelerated significantly.

2.2 Multi-speaker embedding

It is straightforward to extend our UFANS model to multiple speaker cases. We insert trainable speaker embeddings into every gated activation unit to globally condition the models. These embeddings behave like biases. Now the Eqn. (2) becomes

$$Output = tanh(P_1 + h_{id}) * sigmoid(P_2 + g_{id})$$
 (5)

Where h_{id}, g_{id} are speaker embedding biases, We use different embedding biases for different layers and different phases.

2.3 Information dependency

UFANS can model very long information dependency since pooling make the receptive field increase exponentially. Suppose N downward and upward samplings are performed, then the number of adjacent frames that offer information to one specific output frame S_N is determined by the following iteration.

$$S_i = 2 * (S_{i-1} + 2), S_0 = 0, i = 1, ..., N$$
(6)

Table 1 shows the rapid increase of information field. A 5-

N	3	4	5	6	7	8	9
S_N	28	60	124	252	508	1020	2044

Table 1. Receptive field increases exponentially

second speech sample consist of 1000 frames, which means when $N \ge 9$ UFANS can model information dependency of the whole utterance.

3 Experiments

3.1 Dataset

The datasets are speeches from two female Mandarin speakers, about 9000 utterances (around 10 hours,3 to 7s each)

each for training, 1000 each for validation, and 500 each for test. The speech signals are sampled at 24 kHz rate, and Fourier transformed with hop length 5 ms. we extracted 60dimensional mel-cepstral coefficients, 5-dimensional bandaperiodicity parameters, 1-dimensional logarithmic fundamental frequency and their delta, delta-delta dynamic features [18], and one additional voiced/unvoiced dimension, that is 193 dimensions in total. The input features are frame based linguistic features of dimension 165, upsampled and aligned with manually annotated ground truth duration tagging. MLPG [18] is used to process the predicted features and WORLD [2] deterministic vocoder is used to synthesize waves. Both the linguistic and acoustic features are normalized before training.

3.2 Model hyper-parameters

The Bi-LSTM baseline system consists of four dense layers with 1024 channels, followed by one Bi-LSTM layer with 384 channels for each direction, as is used in [7]. We also train a larger one that consists of one dense layer with 2048 channels followed by three Bi-LSTM layers with 1024 channels for each direction, which is used as baseline model in [16]. The Bi-SRU system consists of three dense layers with 1024 channels followed by four Bi-SRU layers with 512 channels for each direction. The DNN system consists of Three dense layers with 1024 channels [19].UFANS uses nine down-samplings, 3*3 kernel convolutions with 256 channels in all blocks except in the final block where a convolution with 512 channels is used.

The frame level based mean squared error (MSE) is taken as the training criteria. We train all the models by Adam [20] method with batch size 16, initial learning rate 0.0004 and β_1, β_2 to be 0.9, 0.999. The model is implemented with MXNET. We trained all models to achieve best validation records. Training finished in 5 hours on single Nvidia Titan X GPU.

3.3 Evalution

Two types evaluations are applied for the performance of our generated speech, i.e., quantitative results and user study.

3.3.1 Quantitative results

The quantitative results of our experiments are presented in Table 2, where MSE term is averaged between the two speaker test cases. The inference speed is evaluated as the time latency to synthesize one-second speech, which includes data transfer from main memory to GPU global memory, GPU calculations and data transfer back to main memory. The larger Bi-LSTM system got the lowest MSE while at the cost of a much larger parameter size and very low inference speed. Actually, as we will see in the following section, the speeches synthesized from UFANS even have better quality than the speeches synthesized from the larger Bi-LSTM system. Bi-SRU got slightly better MSE than Bi-LSTM system used in [7], while Bi-SRU is faster. UFANS also got better MSE than Bi-LSTM in [7] with a speed-up factor of 23, and a speed-up of 76 compared to the larger Bi-LSTM. We did all the experiments on GeForce GTX TITAN X devices.

3.3.2 User study

We did a user study to compare the quality of synthesized speeches from all the systems. We randomly selected 20 Mandarin reviewers (10 female and 10 male) to listen to 20 utterances generated by each system and score each utterance. The text of the 20 utterances are randomly chosen from websites. The reviewers do not know which model the utterances come from. Results of mean opinion score (MOS) are shown in Fig. 5, where A, B, C, D represents DNN in [19],Bi-LSTM in [7], Bi-SRU[9], larger Bi-LSTM in [16], and UFANS, correspondingly. A same Bi-LSTM based duration model trained on the same dataset is used in user study.

For DNN, Bi-SRU and Bi-LSTM, the subjective MOS matches the objective evaluation. While UFANS surprisingly reaches the highest MOS with a worse objective evaluation than the larger Bi-LSTM. The reason for this behavior is to be further studied, but we believe it is related to specific features of UFANS.



Fig. 4. User study of different systems. A: DNN, B: Bi-LSTM, C: Bi-SRU, D:Large Bi-LSTM, E: UFANS.

3.4 Importance of information dependency

To answer the question that dependency within how long time really matters to synthesized speech quality, we increase the down-sampling number N of UFANS from 3 to 9 and observe how evaluation results change. Table 3 and Figure 5 show the results.

The average frame length of utterances used in the subjective evaluation is about 1208, which means when N = 9 the information dependency covers nearly all the frames, when N = 8 the information dependency covers about half of the utterance. The MOS of N = 8 is very close to that of N = 9,

Model	MSE	Parameter size (MB)	Fully parallel	GPU Inference Time (ms)
Bi-LSTM [16]	192.8	292	No	243
Bi-LSTM [7]	195.3	30	No	69
Bi-SRU	194.9	74	No	44
UFANS	194.6	42	Yes	3.2
DNN[19]	209.2	9.5	Yes	0.84

Table 2. Comparison of objective results.

and MOS begins to fall dramatically when N < 8. From this observation we can conclude that longer information dependency leads to better synthesized speech quality and dependency as long as half of the utterance is a necessity to achieve good speech quality.

N	Frame dependence	MSE
3	28	202.58
4	60	200.84
5	124	199.15
6	252	197.55
7	508	196.05
8	1020	194.63
9	2044	194.60

Table 3. MSE when N ranges from 3 to 9.





3.5 Ablation study

The fully convolutional structure of UFANS makes it possible to fully utilize the advantage of a GPU device; The rapidly increasing receptive field helps to model very long information dependency. While another important structure of UFANS is the skip connection between block A and block D (Figure 1). On one hand, In [21] the information bottleneck theory

skip connection	N	MSE
Yes	9	194.60
No	9	214.51

Table 4. MSE with and without skip connection.

is applied to analyze the dynamic process of neural networks. They show that the mutual information between layers and inputs become smaller when layers go deeper, which means that information becomes more compressed through the network. The direct connection between contraction phase and expansive phase is actually a combination of higher level of abstraction and lower level of abstraction. On the other hand, the information from contraction phase focuses on local fields, while the information from expansive phase are abstracted from long fields, which means the skip connection can also be taken as a combination of local and global field information. To illustrate the importance of this connection, we remove the skip connection from our UFANS (N = 9) and find that we can only get a final MSE of about 214.5 (Table 4) which proves the importance of the connection.

4 Conclusion and Future Work

In this paper, we propose an U-shaped Fast Acoustic Neural Structure (UFANS). Our structure greatly reduces time latency in the context of GPU computation with comparable speech quality. We show the possibility and prospect of applying fully-parallel CNN structure in TTS tasks. We also show that the huge receptive field (long-time information dependency) and the high-way skip connection structure(combination of different level features) in our UFANS ensure the speech quality .In future, we plan to search better structures on the basis of UFANS to get improved synthesized speech quality. We are doing some experiments about incorporating UFANS into end-to-end TTS system by replacing the internal RNN structures to speed up the whole system.

5 References

- [1] Jonathan Allen, M Sharon Hunnicutt, Dennis H Klatt, Robert C Armstrong, and David B Pisoni, *From text to speech: The MITalk system*, Cambridge University Press, 1987.
- [2] Masanori Morise, Fumiya Yokomori, , and Kenji Ozawa, "World : A vocoder-based high-quality speech synthesis system for real-time applications," *IEICE Trans. on Information and Systems*, vol. 99, no. 7, pp. 1877–1884, 2016.
- [3] Hideki Kawahara, Ikuyo Masuda-Katsuse, and Alain de Cheveigne, "Restructuring speech representations using a pitch-adaptive time-frequency smoothing and an instantaneous-frequencybased f0 extraction: Possible role of a repetitive structure in sounds," *Speech Communication*, vol. 27, pp. 187–207, 1999.
- [4] Aäron van den Oord, Sander Dieleman, Heiga Zen, Karen Simonyan, Oriol Vinyals, Alex Graves, Nal Kalchbrenner, Andrew W. Senior, and Koray Kavukcuoglu, "Wavenet: A generative model for raw audio," *CoRR*, vol. abs/1609.03499, 2016.
- [5] Sepp Hochreiter and Jrgen Schmidhuber, "Long shortterm memory," *Neural Computation*, vol. 9(8), pp. 1735–1780, 1997.
- [6] Kyunghyun Cho, Bart van Merrienboer, Çaglar Gülçehre, Fethi Bougares, Holger Schwenk, and Yoshua Bengio, "Learning phrase representations using RNN encoder-decoder for statistical machine translation," *Empirical Methods on Natural Language Processing*, pp. 355–362, 2014.
- [7] Zhizheng Wu, Oliver Watts, and Simon King, "Merlin: An open source neural network speech synthesis system," 9th ISCA Speech Synthesis Workshop (2016), pp. 202–207, 9 2016.
- [8] James Bradbury, Stephen Merity, Caiming Xiong, and Richard Socher, "Quasi-recurrent neural networks," *ICLR*, 2017.
- [9] Tao Lei, Yu Zhang, and Yoav Artzi, "Training rnns as fast as cnns," *CoRR*, vol. abs/1709.02755, 2017.
- [10] Merlijn Blaauw and Jordi Bonada, "A neural parametric singing synthesizer," *arXiv preprint arXiv:1704.03809*, 2017.
- [11] Hideyuki Tachibana, Katsuya Uenoyama, and Shunsuke Aihara, "Efficiently trainable text-to-speech system based on deep convolutional networks with guided attention," in 2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2018, pp. 4784–4788.

- [12] Wei Ping, Kainan Peng, Andrew Gibiansky, Sercan O Arik, Ajay Kannan, Sharan Narang, Jonathan Raiman, and John Miller, "Deep voice 3: Scaling text-to-speech with convolutional sequence learning," 2018.
- [13] Olaf Ronneberger, Philipp Fischer, and Thomas Brox, "U-net: Convolutional networks for biomedical image segmentation," *Medical Image Computing and Computer Assisted Intervention*, pp. 234–241, 2015.
- [14] Bin Liu, Shuai Nie, Yaping Zhang, Dengfeng Ke, Shan Liang, and Wenju Liu, "Boosting noise robustness of acoustic model via deep adversarial training," arXiv preprint arXiv:1805.01357, 2018.
- [15] Daniel Stoller, Sebastian Ewert, and Simon Dixon, "Wave-u-net: A multi-scale neural network for endto-end audio source separation," arXiv preprint arXiv:1806.03185, 2018.
- [16] Mengxiao Bi, Heng Lu, Shiliang Zhang, Ming Lei, and Zhijie Yan, "Deep feed-forward sequential memory networks for speech synthesis," *ICASSP*, 2018.
- [17] Aäron van den Oord, Nal Kalchbrenner, Oriol Vinyals, Lasse Espeholt, Alex Graves, and Koray Kavukcuoglu, "Conditional image generation with pixelcnn decoders," *Neural Information Processing Systems*, 2016.
- [18] Keiichi Tokuda, Takayoshi Yoshimura, Takashi Masuko, Takao Kobayashi, and Tadashi Kitamura, "Speech parameter generation algorithms for hmm-based speech synthesis," in *ICASSP*, 2000.
- [19] Yao Qian, Yuchen Fan, Wenping Hu, and Frank K Soong, "On the training aspects of deep neural network (dnn) for parametric tts synthesis," in Acoustics, Speech and Signal Processing (ICASSP), 2014 IEEE International Conference on. IEEE, 2014, pp. 3829–3833.
- [20] Diederik P. Kingma and Jimmy Ba, "Adam: A method for stochastic optimization," *3rd International Conference for Learning Representations*, 2014.
- [21] Ravid Shwartz-Ziv and Naftali Tishby, "Opening the black box of deep neural networks via information," *CoRR*, vol. abs/1703.00810, 2017.