# **Classification of Cervical Cancer Dataset**

# Abstract ID: 2423

# Y. M. S. Al-Wesabi, Avishek Choudhury, Daehan Won Binghamton University, USA

#### Abstract

Cervical cancer is the leading gynecological malignancy worldwide. This paper presents diverse classification techniques and shows the advantage of feature selection approaches to the best predicting of cervical cancer disease. There are thirty-two attributes with eight hundred and fifty-eight samples. Besides, this data suffers of missing values and imbalance data. Therefore, over-sampling, under-sampling and imbedded over and under sampling have been used. Furthermore, dimensionality reduction techniques are required for improving the accuracy of the classifier. Therefore, feature selection methods have been studied as they divided into two distinct categories, filters and wrappers. The results show that age, first sexual intercourse, number of pregnancies, smokes, hormonal contraceptives and STDs:genital herpes are the main predictive features with high accuracy with 97.5%. Decision Tree classifier is shown to be advantageous in handling classification assignment with excellent performance.

# **Keywords**

Cervical cancer, feature selection, classification, imbalanced data, over-sampling.

# **1. Introduction**

Cervical cancer is the most common cancer among women in developing countries, the WHO report [1]. In the United States, there are 129,001 new cases in 2015 despite the provided healthcare facilities, where 273,000 deaths in 2002 worldwide [1]. Cervical cancer dataset has been published in 2017 by [2], which involves 858 samples and 32 features as well as four targets. These attributes include demographic information, habits like smoking and historic medical records. The complexity of this data is the multiple screening and diagnosis approaches that leads to a complex ecosystem. Consequently, the prediction of patient's factor risk and the best screening strategy is a main problem.

Cervical cancer data has been studied from different researchers in last few years . [2] is the first contributor such that transform learning method was the main purpose of the study to show its impact on sharping the accuracy. [3] have studied the same data using cost-sensitive classification with Decision Tree classifier. The good results have been reported by [4] such that Support vector machine with different approaches were applied to yield almost 94% accuracy. However, cervical cancer disease has been deliberated from different angles. For instance, [5] pointed out the cervical cancer control in HIV-positive women and expectation of reducing the mortality in 2030. Interesting investigation has been conducted by [6] to develop novel biomarkers for early diagnosis from specific proteins, enzymes and metabolites.

There are three main steps in the data mining, preprocessing, classification process and the decision-making with analysis [3]. This data includes 3,622 missing values out of 27,456 observations, which forms 13.2% of the data. This survey investigates different machine learning classifiers such as Gaussian Naive Bayes (GNB), Decision Tree (DT), Logistic Regression (LR), k-nearest neighbors (KNN) and Support Vector Machines (SVM), see [7-12]. Further investigation involves wrapper methods such as Sequential Feature Selector, both Forward and Backward version. Some recommended resources for feature selection techniques are available in [13-16].

# 2. Data Description

Cervical cancer data involves 858 samples and 32 features as well as four classes (Hinselmann, Schiller, Cytology and Biopsy) has been published in [2]. This paper focuses on studying the Biopsy target as it recommended by the literature review.

Attribute	Туре	Attribute	Туре	Attribute	Туре
Age	Integer	STDs	Bool	STDs:HIV	Bool
Number of sexual partners	Integer	STDs (number)	Integer	STDs:Hepatitis B	Bool
First sexual intercourse (age)	Integer	STDs:condylomatosis	Bool	STDs:HPV	Bool
Number of pregnancies	Integer	STDs:cervical condylomatosis	Bool	STDs: Number of diagnosis	Integer
Smokes	Bool	STDs:vaginal condylomatosis	Bool	STDs: Time since first diagnosis	Integer
Smokes (years)	Bool	STDs:vulvo-perineal condylomatosis	Bool	STDs: Time since last diagnosis	Integer
Smokes (packs/year)	Bool	STDs:syphilis	Bool	Dx:Cancer	Bool
Hormonal Contraceptives	Bool	STDs:pelvic inflammatory disease	Bool	Dx:CIN	Bool
Hormonal Contraceptives (years)	Integer	STDs:genital herpes	Bool	Dx:HPV	Bool
IUD	Bool	STDs:molluscum contagiosum	Bool	Dx	Bool
IUD (years)	Integer	STDs:AIDS	Bool		

# 3. Methodology

This section concentrates on the methodology of this survey, which can be described into three main parts. First, the preprocessing experiments, this involves missing values treatment using standard measurements like the mean for numerical values and mode for categorical attributes. Several patients decided to not answer some questions due to personality. As a result, 13% of total questions were missed. There are two features with 92% of missing values which are STDs: Time since first diagnosis and STDs: Time since last diagnosis, so they have been omitted. Secondly, five classifiers including the GNB, KNN, DT, LR and SVM are applied to figure out the appropriate classifier for this data. Imbalanced data have been studied by applying three techniques, over-sampling, under sampling and both together. Eventually, for sharping the results and looking at the main risk factors of the cervical cancer, feature selection methods are applied like wrapper methods. Wrapper methods such as Sequential Feature Selector, both Forward and Backward version are used. Table 2 shows some basic notations.

Table 2: Basic notations				
Term	Term Formula			
Accuracy	(TP + TN)/(P+N)	Rate of the correct prediction for both		
		healthy and not healthy patients		
Sensitivity=recall=	TP/(TP+FN)	The percentage of sick people who are		
true positive rate		correctly identified as having the disease.		
Specificity= true	TN/(FP+TN)	The percentage of healthy people who		
negative rate		are correctly diagnosed as healthy.		
Precision	TP/(TP+FP)	positive predictive value		
F-measure	(2 x recall x precision)/	Harmonic mean that combines Precision		
	(recall+precision)	and recall.		

# 4. Results

The data has been divided into 758 training and 100 samples are testing except some experiments that will be specified. Python is the used software for whole experiments.

### 4.1 The basic classification

The result shows that the LR, SVM and KNN perform better than DT and GNB. Besides, the GNB is the worst classifier for this data.

Table 3: Five classifiers result							
Classifier /Performance	Gaussian Naive Bayes	Decision Tree	Logistic regression	SVM	KNN		
Accuracy	5.696	90.116	93.671	93.671	93.671		
Sensitivity=TP	100.0	96.226	95.484	95.484	95.484		
Specificity	4.790	15.385	0.000	0.000	0.000		
Precision	1.325	93.293	98.013	98.013	98.013		
F-measure	2.614	94.737	96.732	96.732	96.732		

Due to the imbalancy on our data set, we have this results. So, we need to resolve this problem.

#### 4.2 Imbalanced data

To address the biased data, there are several methods available. This study will apply SMOTETomek (combine method), under-sampling and over-sampling method that available in *imblearn class* in Python language.

#### 4.2.1 SMOTETomek method

Table 4: Five classifiers results using combine sampling method

			0		
Classifier	Gaussian	Decision	Logistic	SVM	KNN
/Performance	Naive Bayes	Tree	regression		
Accuracy	50.633	91.772	72.152	85.759	84.494
Sensitivity=TP	100	91.464	67.961	93.985	96.694
Specificity	49.677	92.105	80.0	79.781	76.92
Precision	3.703	92.593	86.419	77.160	72.222
F-measure	7.142	92.025	76.087	84.746	82.686

The DT classifier performs the best in this experiment, while the GNB performs poorly. Therefore, the GNB will be omitted from further studies.

#### 4.2.2 Under-sampling

Table 5: Four classifiers results using under-sampling method						
Classifier	Classifier Decision Logistic SVM KNN					
/Performance	Tree	regression				
Accuracy	68.182	54.545	68.182	54.545		
Sensitivity=TP	77.778	66.667	72.727	60.0		
Specificity	61.538	50.0	63.636	50.0		
Precision	58.333	33.333	66.667	50.0		
<b>F-measure</b>	66.667	44.444	69.565	54.545		

This is expected results due to the small samples size, it was reduced from 800+ to only 100+.

#### 4.2.3 Oversampling

 Table 6: Four classifiers results using over-sampling method

Classifier /Performance	Decision Tree	Logistic regression	SVM	KNN
Accuracy	93.788	63.975	81.677	90.683

	,	,		
Sensitivity=TP	100.0	62.32	79.569	100.0
Specificity	88.439	67.289	84.559	83.606
Precision	88.165	79.289	87.574	82.249
<b>F-measure</b>	93.711	69.792	83.380	90.259

Al-Wesabi, Choudhury and Won

Table 7: Comparison between the DT classifier and corresponding imbalanced sampling methods

Over-	Under-	Both
sampling	Sampling	
93.788	68.182	91.772
100.0	77.778	91.464
88.439	61.538	92.105
88.165	58.333	92.593
93.711	66.667	92.025
	sampling 93.788 100.0 88.439 88.165	sampling         Sampling           93.788         68.182           100.0         77.778           88.439         61.538           88.165         58.333

## 4.3 Feature selection based on Sequential Backward Selection (SBS) method

This experiment focuses on wrapper methods, practically SBS and SFS with 12-selected features and 10-cross-validation.

Classifier	Indices
LR	5, 6, 7, 8, 9, 11, 13, 15, 19, 22, 26, 27
SVM	0, 1, 2, 3, 5, 8, 9, 11, 14, 25, 27, 28
DT	0, 1, 2, 3, 7, 8, 14, 16, 17, 20, 21, 23
KNN	0, 1, 2, 5, 6, 7, 8, 11, 12, 25, 28, 29

Table 8: Four classifiers results using the SBS method

Classifier	Decision	Logistic	SVM	KNN
/Performance	Tree	regression		
Accuracy	95.652	64.596	90.062	90.062
Sensitivity=TP	100.0	62.790	91.017	100.0
Specificity	91.617	68.22	89.032	82.702
Precision	91.716	79.881	89.941	81.065
<b>F-measure</b>	95.679	70.313	90.476	89.542

## 4.4 Feature selection based on Sequential Forward Selection (SFS) method

Classifier	Indices
LR	2, 5, 7, 8, 10, 11, 14, 15, 17, 19, 26, 27
SVM	0, 1, 2, 3, 4, 5, 7, 8, 9, 11, 12, 29
DT	0, 1, 2, 3, 4, 7, 16, 18, 19, 23, 24, 27
KNN	0, 2, 3, 4, 7, 11, 14, 15, 19, 22, 26, 28

Table 9: Four classifiers results using the SFS method

Classifier /Performance	Decision Tree	Logistic regression	SVM	KNN
Accuracy	95.652	65.838	90.373	90.062
Sensitivity=TP	100.0	63.849	91.071	100.0
Specificity	91.617	69.725	89.61	82.703
Precision	91.716	80.473	90.532	81.065
F-measure	95.679	71.204	90.801	89.542

Both Forward and Backward feature selection techniques are comparable and equivalent.

#### 4.5 Selecting some features

Another interesting result can be obtained by selecting the common factors between the DT and the KNN. Then by applying the main classifiers, it yields the following results.

Classifier /Performance	Decision Tree	Logistic regression	SVM	KNN
Accuracy	97.515	49.068	88.198	87.577
Sensitivity=TP	100.0	51.533	90.683	100.0
Specificity	95.031	46.540	85.714	79.274
Precision	95.266	49.704	86.390	76.331
F-measure	97.576	50.602	88.485	86.577

TT 11 10	r	1 'C'	1.	•	selective features	
I ahle I ()	Hour	alaccitiere	reculte	110100	selective teatures	
1 auto 10.	I UUI V	classificis	resuits	using	sciective reatures	

Overall, it is noticeable that the DT is the recommended classifier model for this cervical cancer data. Moreover, this result is better than published work in [3].

Table 11: Comparison between published work in [3] and our result using the DT

	[3] result	Our result
Sensitivity=TP	42.9	100
Precision	42.9	95
F-measure	30.6	97

# **5.** Conclusion

To sum up, this article presents the comparison between different machine learning classifiers respect to the best predictive model for Cervical Cancer Dataset. Results show that this data is biased and addressing the imbalanced data is the first step for evaluation. Three techniques have been used to address the imbalanced data; over-sampling, under-sampling and combine both methods. Over-sampling yields better results than other two methods due to higher accuracy obtained by over-sampling . Further studies are conducted by using feature selection methods. Consequently, the SBS and SFS are superior techniques to enhance the performance of the prediction with accuracy 95%. By selecting the common features among the DT and KNN in Section 4.4, we obtain the best overall result with accuracy exceeds 97%. The selective features are Age, First sexual intercourse, number of pregnancies, Smokes, Hormonal Contraceptives and STDs:genital herpes. Interestingly, all six-selective feature make sense for diagnosing the cervical cancer. Eventually, we prefer DT classifier over GNB classifier. As a future work, selection features by LASSO method have not been tested with the classifiers to see their influence. Second potential work is multi-class classification with the four targets.

# References

- Sharma, P., and Pattanshetty ,S.M., 2017 ,"A Study on Risk Factors of Cervical Cancer Among Patients Attending A Tertiary Care Hospital: A Case-Control Study,". *Clinical Epidemiology and Global Health* (In press).
- 2. Fernandes, K., J.S. Cardoso, and J. Fernandes., 2017," Transfer Learning with Partial Observability Applied to Cervical Cancer Screening" In Iberian Conference on Pattern Recognition and Image Analysis, *Springer*.

- 3. Fatlawi, H.K., 2017, "Enhanced Classification Model for Cervical Cancer Dataset based on Cost Sensitive Classifier", *International Journal of Computer Techniques*, 4(4).
- 4. Wu, W. and H. Zhou, 2017, "Data-Driven Diagnosis of Cervical Cancer With Support Vector Machine-Based Approaches", *IEEE Access*, 5:p. 25189-25195.
- 5. Ghebre, R.G., et al., 2017, "Cervical cancer control in HIV-infected women: Past, present and future", *Gynecologic oncology reports*, 21: p. 101-108.
- 6. Dasari, S., R. Wudayagiri, and L. Valluru, 2015, "Cervical cancer: Biomarkers for diagnosis and treatment", *Clinica chimica acta*, 445: p. 7-11.
- 7. Zhang, H., 2004, "The optimality of naive Bayes", AA, 1(2), 3.
- 8. Safavian, S.R, and Landgrebe, D, 1991, "A Survey of Decision Tree Classifier Methodology", *IEEE Transactions on Systems, Man and Cybernetics*, 21(3), 660-674.
- Kleinbaum, D.G. and Klein, M., 2010, "Analysis of Matched Data Using Logistic Regression", In Logistic Regression., Springer, 389-428.
- 10. Peterson, L.E., 2009," K-Nearest Neighbor", Scholarpedia, 4(2),1883.
- 11. Chang, C.-C. and Lin, C.-J., 2011, "LIBSVM: A Library for Support Vector Machines," ACM Transactions on Intelligent Systems and Technology (TIST)", 2(3), 27.
- Torheim, T., et al., 2014," Classification of Dynamic Contrast Enhanced MR Images of Cervical Cancers Using Texture Analysis and Support Vector Machines," *IEEE Transactions on Medical Imaging*, 33(8), 1648-1656.
- 13. Dash, M. and Liu, H., 1997," Feature Selection for Classification," *Intelligent Data Analysis*, 1(1-4), 131-156.
- 14. Saeys, Y., Inza, I., and Larrañaga, P.,2007, "A review of Feature Selection Techniques in Bioinformatics," *Bioinformatics*, 23(19), 2507-2517.
- 15. Lakshmi, G.K. and Krishnaveni, K., 2016, "Feature Extraction and Feature Set Selection for Cervical Cancer Diagnosis," *Indian Journal of Science and Technology*, 9(19).
- 16. Khalid, S., Khalil, T., and Nasreen, S., 2014, "A Survey of Feature Selection and Feature Extraction Techniques in Machine Learning," In Science and Information Conference (SAI), *IEEE*, Aug 27, 372-378.