Data-driven biological network alignment that uses topological, sequence, and functional information

Shawn Gu and Tijana Milenković^{*}

Department of Computer Science and Engineering, Eck Institute for Global Health, and Center for Network and Data Science, University of Notre Dame, Notre Dame, IN 46556

^{*}To whom correspondence should be addressed (email: tmilenko@nd.edu)

Abstract

Network alignment (NA) can transfer functional knowledge between species' conserved biological network regions. Traditional NA assumes that it is topological similarity (isomorphic-like matching) between network regions that corresponds to the regions' functional relatedness. However, we recently found that functionally unrelated proteins are as topologically similar as functionally related proteins. So, we redefined NA as a data-driven framework, TARA, which learns from network and protein functional data what kind of topological *relatedness* (rather than similarity) between proteins corresponds to their functional relatedness. TARA used topological information (within each network) but not sequence information (between proteins across networks). Yet, TARA yielded higher protein functional prediction accuracy than existing NA methods, even those that used both topological and sequence information. Here, we propose TARA++ that is also data-driven, like TARA and unlike other existing methods, but that uses across-network sequence information on top of within-network topological information, unlike TARA. To deal with the within-and-across-network analysis, we adapt social network embedding to the problem of biological NA. TARA++ outperforms protein functional prediction accuracy of existing methods.

1 Introduction

1.1 Background

Many proteins remain functionally unannotated (Ellens *et al.*, 2017). A popular way to uncover missing annotations is to transfer functional knowledge across proteins of different species. This task of *across-species* protein functional prediction is the focus of this paper. The orthogonal task of *within-a-species* protein functional prediction, where a function of a protein in a species is predicted from function(s) of other protein(s) in *the same* species (Shehu *et al.*, 2016), is out of the scope.

Genomic sequence alignment is commonly used for the task of across-species protein functional prediction, by transferring functional knowledge between conserved (aligned) sequence regions of proteins in different species. However, sequence alignment often fails: many sequence-similar proteins do not perform the same function(s), i.e., are functionally unrelated, and many sequence-dissimilar proteins are functionally related (Gu and Milenković, 2019); "functionally related" means that, according to current Gene Ontology (GO) annotation data (Ashburner *et al.*, 2000), two proteins share a GO term, while "functionally unrelated" means that they share no GO terms. For example, of all yeast-human sequence orthologs from YeastMine (Balakrishnan *et al.*, 2012), \sim 42% are *not* functionally related (Gu and Milenković, 2019). Such imperfect performance of sequence alignment could be due to sequence alignment failing to consider interactions between the genes, i.e., their protein products. However, a protein does not function alone. Instead, it interacts in complex networked ways with other proteins. So, accounting for protein-protein interactions (PPIs) is important for better protein functional prediction across species.

Luckily, large amounts of PPI network data are available (Chatr-Aryamontri *et al.*, 2017). Hence, network alignment (NA) can be used to compare PPI networks of different species, in order to find

a "good" mapping between their nodes (proteins), i.e., a node mapping that uncovers regions of high network topological (and often sequence) conservation between the species; conservation typically means similarity. So, analogous to sequence alignment, NA can be used to transfer functional knowledge between conserved (aligned) PPI network, rather than just sequence, regions of different species (Faisal *et al.*, 2015; Meng *et al.*, 2016; Emmert-Streib *et al.*, 2016; Elmsallati *et al.*, 2016; Guzzi and Milenković, 2017). While we focus on computational biology, NA is also applicable to many other domains (Emmert-Streib *et al.*, 2016).

NA can be categorized into several broad types, whose high-level input/output/goal differences are as follows (more detailed algorithmic differences between specific NA methods are discussed in Section 1.4).

First, NA can be pairwise (aligns two networks) or multiple (aligns three or more networks) (Faisal *et al.*, 2015; Guzzi and Milenković, 2017). We focus on pairwise NA because current multiple NA is more computationally complex (Vijayan and Milenković, 2018b) while also generally less accurate (Vijayan *et al.*, 2020) than current pairwise NA.

Second, NA can be local or global (Meng *et al.*, 2016; Guzzi and Milenković, 2017), like sequence alignment. Local NA aims to find highly conserved network regions but usually results in such regions being small. Global NA aims to maximize overall network similarity; while it usually results in large aligned network regions, these regions are suboptimally conserved. Both have their own (dis)advantages (Meng *et al.*, 2016; Guzzi and Milenković, 2017). (More on local versus global NA follows shortly. We first need to define one-to-one versus many-to-many NA.)

Third, NA can be one-to-one (each node can be aligned to exactly one distinct node in another network) or many-to-many (a node may be aligned to more than one node in another network).

Traditionally, given networks $G_1(V_1, E_1)$ and $G_2(V_2, E_2)$, local NA has meant the same as many-tomany NA: a relation $R \subseteq V_1 \times V_2$. Also, global NA has meant the same as one-to-one NA: an injective function $f: V_1 \to V_2$. Over time, local one-to-one and global many-to-many NA methods have been proposed. So, both local and global NA are now $R \subseteq V_1 \times V_2$. The two differ in how many nodes are covered by the aligned node pairs in R – much fewer for local than global NA.

As global NA has received more attention recently than local NA, we focus on global NA. Both one-to-one and many-to-many alignments can be used in our considered task of across-species protein functional prediction. Yet, it is many-to-many NA methods that are the state-of-the-art in this task, which is why our considered methods happen to be many-to-many.

Fourth, three NA method groups exist based on how input data are processed. The first group consists of NA methods that, given two PPI networks, calculate each node's feature using only the topological information within the given node's own network. As such, we refer to them as within-network-only NA methods. The nodes' topological features, which aim to summarize the nodes' extended PPI network neighborhoods, are then used in various alignment processes (Section 1.4). For state-of-the-art NA methods from this group, the topological features are based on graphlets (Milenković and Pržulj, 2008), which are subgraphs, i.e., small, Lego-like building blocks of networks. The second group consists of NA methods that, given two PPI networks and also sequence information for nodes across networks, first calculate each node's topological feature in the same way as within-network-only methods, and only afterwards combine the sequence information with the topological features. Then, the combined data are used in various alignment processes (Section 1.4). Because both within-network topological and across-network sequence information are used, but the two are initially processed in isolation from each other and are combined only after the fact, we refer to this second group as isolated-within-andacross-network methods. Within-network-only methods can easily be used as isolated-within-and-acrossnetwork methods when sequence information is available; the latter usually lead to better alignments than the former (Meng et al., 2016). The third group consists of NA methods that, given two PPI networks and sequence information for nodes across networks, first "integrate" the two networks into one by adding across-network "anchor" links (edges) between the highly sequence-similar proteins and only then proceed with any feature extraction or alignment process. So, the third group uses both withinnetwork topological and across-network sequence information. But, they first integrate the two data types and only then process them. As such, we refer to them as integrated-within-and-across-network methods.

1.2 Motivation

Regardless of which NA category they belong to, almost all existing NA methods assume that it is topological similarity between nodes (i.e., a high level of isomorphism-like matching between their extended PPI network neighborhoods as captured by the nodes' topological features) that corresponds to the nodes' functional relatedness, and thus they try to align topologically similar nodes. However, multiple studies observed that while existing NA methods yield high topological alignment quality (many edges are conserved, i.e., the aligned network regions indeed have a high level of isomorphism-like match), their functional alignment quality is far from perfect (often, the aligned nodes are *not* functionally related) (Elmsallati *et al.*, 2016; Meng *et al.*, 2016; Guzzi and Milenković, 2017).

Only recently, an attempt was made to understand this observation, and this was done by us (Gu and Milenković, 2019). Namely, we questioned the key assumption of current NA – that topologically similar nodes correspond to functionally related nodes. We found for both synthetic and PPI networks that the functionally related nodes were only marginally more topologically similar than the functionally unrelated nodes, no matter which topological similarity measure was used (Gu and Milenković, 2019).

This shocking result - the current NA assumption failing – led us to redefine the NA problem as a data-driven framework, which learns from PPI network and protein functional data what kind of "topological relatedness" between proteins corresponds to the proteins' functional relatedness, without assuming that topological relatedness means topological similarity. To understand this framework, we next explain topological similarity versus topological relatedness (Fig. 1).



Figure 1: Illustration of topological (a) similarity vs. (b) relatedness.

Suppose that: (i) PPI networks of yeast and human are being aligned, (ii) the toy networks in Fig. 1 are parts of the full networks, (iii) each node performs either the "green" or "yellow" function, and (iv) because of incompleteness/noisiness of PPI network data or molecular evolutionary events such as gene duplication, deletion, or mutation, the green functional module in human (nodes 1, 2, 3, and 9) has an extra protein compared to the green module in yeast (nodes a, b, and c), and the yellow module in yeast has an extra interaction compared to the yellow module in human (Fig. 1). An NA method based on topological similarity will align yellow nodes e, f, g, and h in yeast to green nodes 1, 2, 3, and 9 in human (Fig. 1(a)), because both node sets form the same subgraph – a square with a diagonal, i.e., because the set of yellow nodes in yeast are topologically more similar to the set of green nodes in human than to the set of yellow nodes in human. However, this alignment is functionally incorrect because yellow and green nodes perform different functions. Instead, our NA framework based on topological relatedness will use the topological and functional data to learn that a triangle in yeast (a, b, and c) should be aligned to a square-with-diagonal in human (1, 2, 3, and 9) because both perform the same function (green), and that a square-with-diagonal in yeast (e, f, g, and h) should be aligned to a square in human (5, 6, 7, and h)8) because both perform the same function (yellow) (Fig. 1(b)). Then, in other parts of the networks, our framework will try to align these learned patterns, to transfer knowledge between them. Loosely speaking, topological relatedness aims to account for data noisiness/incompleteness, evolutionary events, or other, yet-to-be-discovered factors that are likely to break the isomorphism-like assumption of the traditional topological similarity-based NA.

We named our topological relatedness-based NA framework TARA (Gu and Milenković, 2019). TARA uses supervised classification to learn what topological patterns should be aligned to each other. Given (i) a set of node pairs across the networks being aligned, such that the nodes in a given pair are functionally related, (ii) a set of node pairs across the network topological features of each node pair, TARA divides the node pairs into training and testing data. Then, it uses a classifier to learn from the training data what graphlet features distinguish between the functionally related and functionally unrelated node pairs. Next, given node pairs from the testing data and their graphlet features, TARA predicts whether the nodes in a given pair are functionally related or unrelated. Node pairs predicted as functionally related are added to TARA's alignment, and this alignment is given to an established across-species protein functional prediction methodology (Meng *et al.*, 2016) to obtain a list of protein functional annotations (i.e., protein-GO term pairs).

By learning topological relatedness patterns, TARA outperformed, in the task of across-species protein functional prediction between yeast and human, three state-of-the-art NA methods, WAVE (Sun et al., 2015), SANA (Mamano and Hayes, 2017), and PrimAlign (Kalecky and Cho, 2018). To better understand the implications of these results, it is important to understand what type, i.e., within-network-only, isolated-within-and-across-network, or integrated-within-and-across-network, each method is. TARA, WAVE, and SANA are all within-network-only methods. They also all use graphlet-based topological node features. Their key difference is that TARA is supervised, i.e., it uses topological relatedness, while WAVE and SANA are unsupervised, i.e., they use topological similarity. Thus, WAVE and SANA were the most fairly comparable methods to TARA. So, we could fairly evaluate whether moving from WAVE's and SANA's topological similarity to TARA's supervision-based topological relatedness helped. TARA significantly outperformed WAVE and SANA, so we could conclude that it did help. PrimAlign is one of very few existing integrated-within-and-across-network methods. Because PrimAlign was already shown to outperform many isolated-within-and-across-network methods (Kalecky and Cho, 2018) on the exact same data as in TARA's evaluation (Gu and Milenković, 2019), there was no need to evaluate TARA against any methods of that type. Importantly, TARA still outperformed PrimAlign, despite the former not using any sequence information. This already showed how powerful the supervised NA paradigm is. In this study, we push the boundary further. TARA "only" showed that going from unsupervised to supervised for within-network-only methods improved alignment accuracy, but we also already know that going from within-network-only to isolated-within-and-across-network to integratedwithin-and-across-network in the unsupervised context also improves accuracy. So, a method that is both supervised and of the integrated-within-and-across-network type should further improve alignment accuracy. Thus, here, we propose the first ever method of this type.

1.3 Our contributions

We introduce TARA-TS (<u>TARA</u> within-network <u>T</u>opology and across-network <u>S</u>equence information) as a novel framework implementing the above idea. Like TARA, TARA-TS is supervised. Unlike TARA and like PrimAlign, TARA-TS extracts features from an integrated yeast-human network. As a solution to feature extraction, we leverage the extensive research on graph representation learning (Cai *et al.*, 2018), which embeds nodes of a network into a low dimensional space such that network structure is preserved; the low-dimensional node representations are then used as node features. Network embedding has primarily been studied in the social network domain. So, we extend it to the domain of computational biology: TARA-TS generalizes a prominent network embedding method that was proposed for singlenetwork analysis in machine learning tasks such as node classification, clustering, and link prediction, to the multi-network task of biological NA. Given the node features extracted by network embedding, TARA-TS works just as TARA to produce an alignment. Then, we use this alignment for across-species protein functional prediction.

We compare prediction accuracy of TARA-TS (pairwise, global, many-to-many, integrated-withinand-across-network, supervised) with accuracies of TARA and PrimAlign, as they are state-of-the-art NA methods that were already shown to outperform many other existing NA methods on the *exact same data* as what we use here. So, by transitivity, if TARA-TS is shown to be superior to TARA and PrimAlign, this will mean that TARA-TS is superior to the other existing methods as well. Also, of all existing methods, TARA and PrimAlign are the most similar and thus fairly comparable to TARA-TS. Namely, TARA is pairwise, global, many-to-many, and supervised, like TARA-TS. The difference is that TARA is a within-network-only method while TARA-TS is an integrated-within-and-across-network method. So, we can fairly test the effect of going from within-network-only to integrated-within-and-across-network in the supervised context. PrimAlign is a pairwise, global, many-to-many, and integrated-within-andacross-network method, like TARA-TS. The difference is that PrimAlign is unsupervised while TARA-TS is supervised. So, we can fairly test the effect of going from unsupervised to supervised for integratedwithin-and-across-network methods.

When we compare TARA-TS against TARA, we actually compare whether using across-network sequence information on top of within-network topological information leads to more accurate predictions, as we expect. Shockingly, we find that TARA-TS and TARA are almost equally as accurate. Closer examination reveals that their quantitatively similar results are *not* because the two methods are predicting the same information (which would make one of them redundant). Instead, their predicted protein functional annotations are quite complementary. So, we then look at those predictions (protein-GO term associations) that are made by both methods, only those predictions made by TARA-TS but not TARA, and only those predictions made by TARA but not TARA-TS. We find the former (the overlapping predictions) to be more accurate than the predictions made by any one of TARA-TS or TARA alone. So, we take this overlapping version of TARA-TS and TARA as our final method, TARA++. In a sense, TARA++ is integrating state-of-the-art research knowledge across computational biology and social network domains, by combining TARA's graphlet-based topology-only features with TARA-TS's embedding-based topology-and-sequence features, each of which boosts the other's performance. Very few studies have explored such a promising direction to date (Nelson *et al.*, 2019). Importantly, we find that TARA++ not only outperforms TARA but also PrimAlign.

1.4 Related work

First, we discuss within-network-only and isolated-within-and-across-network methods. They have two parts. First, similarities are computed for all pairs of nodes across networks. For within-network-only methods, these are topological similarities (computed by comparing the nodes' topological features). For isolated-within-and-across-network methods, these are a weighted sum of the nodes' topological and sequence similarities. Second, an alignment strategy aims to maximize the total similarity over all aligned nodes while also conserving many edges. Two types of alignment strategies exist. One type is "seed-and-extend", which progressively builds an alignment by adding to it one node pair at a time. WAVE (Sun et al., 2015), when paired with graphlet-based topological similarities, is a state-of-the-art method of this type. The other type is a "search algorithm" that optimizes an objective function over the solution space of possible alignments. We pioneered search algorithm-based NA with MAGNA and MAGNA++ (Saraph and Milenković, 2014; Vijayan et al., 2015). The more recent SANA (Mamano and Hayes, 2017) is a state-of-the-art approach of this type, whose objective function is generally graphlet-based.

Next, we discuss integrated-within-and-across-network NA methods. PrimAlign (Kalecky and Cho, 2018) is a state-of-the-art method of this type. After linking networks being aligned via anchors, PrimAlign creates a Markov chain out of the integrated network, converting the edge weights to transition probabilities (in an unweighted network, the weights are set to 1 before converting to transition probabilities). The chain is then repeatedly transitioned until convergence, redistributing the across-network node pair scores using a PageRank-like algorithm. Node pairs across networks that are above some threshold are then taken as the alignment.

MUNK also links the original networks via anchors, but it uses matrix factorization to obtain an alignment (Fan *et al.*, 2019). In our preliminary analyses, MUNK's similarity scores were not able to distinguish between functionally related and functionally unrelated proteins. Furthermore, Nelson et al. (Nelson *et al.*, 2019) found IsoRank (Singh *et al.*, 2008) to outperform MUNK, despite the former being an early method and the latter a recent method. IsoRank was already outperformed by many NA methods that appeared after it, which in turn were outperformed by WAVE and SANA, which were then outperformed by TARA and PrimAlign (see below). Because we consider TARA and PrimAlign in this study, there is no need to also consider MUNK, an inferior method.

Unlike TARA++, the above methods do not use functional (GO) information to produce alignments but only to evaluate them. DualAligner (Seah *et al.*, 2014) does use such information, but not to determine classification labels ("functionally related" and "functionally unrelated") like TARA++ does. Instead, the method aligns groups of nodes that are all annotated with a given GO term, and then seedsand-extends around these groups to match proteins that do not have any GO annotations, resulting in the final alignment. We do not consider DualAligner in this study, as it is quite old. More recent, state-of-the-art methods have appeared since.

The above methods are unsupervised. Many other such methods exist (Guzzi and Milenković, 2017). TARA and PrimAlign, which we consider in this study, already outperformed the other methods, including AlignMCL, AlignNemo, CUFID, HubAlign, IsoRankN, L-GRAAL, MAGNA, MAGNA++, MI-GRAAL, NETAL, NetCoffee, NetworkBLAST, PINALOG, SANA, SMETANA, and WAVE (Sun *et al.*, 2015; Mamano and Hayes, 2017; Kalecky and Cho, 2018; Gu and Milenković, 2019). In turn, these outperformed GHOST, IsoRank, NATALIE, PISwap, and SPINAL (Mamano and Hayes, 2017). This, plus TARA and PrimAlign being the most similar and thus fairly comparable to TARA++, is why we focus on these two existing methods. Also, some supervised methods (besides TARA, already discussed) exist, as follows.

IMAP (Cao *et al.*, 2017) uses supervised learning differently than TARA++. As input, IMAP requires a starting (unsupervised, topological similarity-based) alignment between two networks; as such, it still suffers from the topological similarity assumption. Then, it obtains graphlet features for node pairs. Node pairs from the starting alignment form the positive class, while the other node pairs are sampled to form the negative class. Then, IMAP trains a linear regression classifier on these two classes. After, this data is "re-classified", but instead of assigning a class, IMAP assigns a score corresponding to the probability that the two nodes should be aligned. A matching algorithm (e.g., Hungarian) is applied to these scores to form a new alignment, which is then fed back to IMAP. This process iterates while alignment quality improves. We did try to test IMAP. Its code was not available. Our attempts at implementing IMAP ourselves led to significantly worse results than those reported in the IMAP paper. So, we could not consider IMAP in our evaluation.

MEgo2Vec (Zhang *et al.*, 2018), also supervised, is a social NA method for matching user profiles across different online media platforms. Features of user profiles are obtained using graph neural networks and natural language processing techniques, and these are used to train a classifier to predict whether two profiles from different platforms correspond to the same person. A big part of MEgo2Vec is the various text processing techniques to match users' names, affiliations, or research interests, meaning that it cannot be easily applied to PPI networks.

2 Methods

2.1 Data

As typically done in NA studies, we analyze PPI networks of yeast (5,926 nodes and 88,779 edges) and human (15,848 nodes and 269,120 edges) from BioGRID (Chatr-Aryamontri *et al.*, 2017). Also, like the PrimAlign study (Kalecky and Cho, 2018), we consider 55,594 yeast-human protein pairs with E-value sequence similarities $\leq 10^{-7}$ as anchor links.

Our supervised NA framework requires knowledge about whether two proteins are functionally related. As typically done, we define functional relatedness using GO annotation data (from August 2019). Considering biological process GO terms and experimentally inferred protein-GO term annotations (evidence codes EXP, IDA, IPI, IMP, IGI, or IEP), if at least k GO terms are shared between a yeast protein and a human protein, we define that protein pair as functionally related; we vary k from 1 to 3. Regardless of the k value, we define a protein pair as functionally unrelated if the two proteins share no GO terms of any kind. This gives three ground truth datasets: *atleast1-EXP*, *atleast2-EXP*, and *atleast3-EXP*.

While traditionally every GO term available in a given ground truth dataset has been considered for NA evaluation, recent work (Hayes and Mamano, 2017) suggested that accounting for the frequency of GO terms (how many proteins a GO term annotates out of all proteins analyzed) is important for reducing GO term redundancy. Indeed, in our TARA study, we found that considering rarer GO terms led to higher protein functional prediction accuracy (Gu and Milenković, 2019). So, here, we consider the same three GO term rarity thresholds as in the TARA study: (i) all GO terms (i.e., ALL), which corresponds to traditional NA evaluation, (ii) GO terms that appear 50 times or fewer (i.e., threshold of 50), and (iii) GO terms that appear 25 times or fewer (i.e., threshold of 25).

For a given GO term rarity threshold, all GO terms not satisfying the threshold are filtered out. Then, for each atleast k-EXP ground truth dataset, only proteins that share at least k GO terms from the remaining list are considered to be functionally related, and still, proteins that share no GO terms, regardless of rarity, are considered to be functionally unrelated. For example, proteins that share at least one (experimentally inferred biological process) GO term, such that each GO term annotates 50 or fewer proteins, are considered functionally related in the "atleast1-EXP at the 50 GO term rarity threshold" dataset. There is a total of nine such "ground truth-rarity" datasets, resulting from combinations of the three atleast k-EXP ground truth datasets and the three GO term rarity thresholds.

2.2 TARA-TS's feature extraction methodology

TARA-TS needs to extract features that capture both within-network topological and across-network sequence information from the integrated network, which consists of 21,774 nodes (5,926 yeast + 15,848 human proteins) and 413,493 edges (88,779 yeast PPIs + 269,120 human PPIs + 55,594 anchor links). We examine several feature extraction approaches.

First, we use the same feature extraction method as TARA, simply applied to the integrated network rather than the two individual networks. TARA relies on graphlets, small subgraphs (a path, triangle, square, etc., generally up to five nodes). Graphlets are often used to summarize the extended neighborhood of a node into its feature vector, as follows. For a node, for each automorphism orbit (intuitively, node symmetry group) in a graphlet, one can count how many times the node touches each graphlet at each of its orbits. The resulting counts for all considered graphlets/orbits are the node's graphlet degree vector (GDV) (Milenković and Pržulj, 2008). Then, to obtain the feature of a node pair, TARA takes the element-wise absolute difference of the nodes' GDVs. So TARA-TS can apply the same graphlet counting procedure to the integrated network, obtaining the GDV for each yeast and human node, and taking the absolute difference of two nodes' GDVs to obtain the feature vector of the yeast-human node *pair*. We refer to this version of TARA-TS as "TARA-TS (graphlets)".

Second, we use a prominent network embedding method on the integrated network to extract features, namely node2vec (Grover and Leskovec, 2016). This method uses random walks to explore the neighborhood of a node in a network. For a node u, random walks starting at u are performed, and the sequence of nodes visited by each random walk is recorded. The number of random walks performed per node is controlled by the parameter "Number of walks per source (-r:)", and the length of a random walk is controlled by the parameter "Length of walk per source (-1:)". This process is repeated for every node in the network. Then, a skip-gram model is applied over all sequences of nodes and the feature vector of each node is obtained. The only way to use node2vec, a single-network method, in the multi-network NA task, is to first integrate the two networks via anchor links, as we do. Otherwise, node2vec fails if applied to the two networks individually (Gu and Milenković, 2018). We first apply node2vec to the integrated network with the default parameters to obtain a feature vector for each *node*. Then, as suggested by the node2vec study (Grover and Leskovec, 2016), to get the feature vector of a yeast-human node *pair*, we take the element-wise average of the nodes' feature vectors. We refer to this version of TARA-TS as "TARA-TS (node2vec)".

We use node2vec over other network embedding methods for three reasons. (i) Even more recent methods, when evaluated in their own papers, achieve similar performance as node2vec in many tasks. So, we do not expect them to outperform node2vec in our task. (ii) The node2vec source code is available and well documented, unlike for many other methods. (iii) The goal of this study is not to find the absolute best feature vector for supervised NA, but to test how combining topological and sequence information in supervised NA affects protein functional prediction. If using node2vec already improves upon current NA methods, then using any more sophisticated ways to extract features will only improve further. In our proposed framework, features from any new extraction method can simply be "swapped" in, allowing flexibility for further advancements.

Third, node2vec does not capture heterogeneous information in the integrated network, i.e., does not distinguish between different types of nodes (yeast and human) or edges (yeast PPIs, human PPIs, and yeast-human sequence-based anchor links). So, we also test metapath2vec (Dong et al., 2017), i.e., node2vec generalized to heterogeneous networks. Metapath2vec requires the user to define "metapaths", which direct how the random walks move. A metapath example is "human-human-yeast-yeast" (or "human $\times 2 \rightarrow \text{yeast} \times 2$ "): start at a human node, move to a randomly chosen neighboring (RCN) human node, move to an RCN yeast node, and move to an RCN yeast node. This metapath is extended such that its length is as close as possible to the -1: parameter value. For example, if this value is 12, then this metapath would be repeated |12/4| = 3 times. Then, given a node u and the extended metapath, random walks starting at u are performed such that the nodes visited follow the constraints of the metapath, and the sequence of nodes visited by each random walk is recorded. In the process, node2vec's -1: and -r: parameters apply to metapath2vec as well. The procedure is repeated for every node in the network. Then, a skip-gram model is applied over all sequences of nodes to obtain node features. We use the metapath2vec++ implementation of metapath2vec (Dong et al., 2017) with the default parameters to obtain each node's feature vector, and again take the element-wise average of two nodes' feature vectors to compute the feature vector of a node pair. Choosing "optimal" metapaths is non-trivial and often the selection process involves using the same paths as those of previous studies (Shang et al., 2016; Dong et al., 2017). However, to our knowledge, this study is the first to investigate metapaths on an integrated across-species biological network. Thus, our only option is to do our due diligence and examine reasonable metapaths, to give a fighting chance to metapath2vec. We test these metapaths: "human \times n \rightarrow yeast \times n" and "yeast \times n \rightarrow human \times n" for $3 \le n \le 10$, "human $\times 25 \rightarrow$ yeast $\times 25$ " and "yeast $\times 25 \rightarrow$ human $\times 25$ ", "human $\times 50 \rightarrow$ yeast $\times 50$ " and "yeast $\times 50 \rightarrow$ human $\times 50$ ", and the combination of all of the individual metapaths (i.e., we apply the skip-gram model to all node sequences obtained from all considered metapaths). We verified that the choice of metapath does not impact alignment accuracy (results not shown). So, for simplicity, we continue with the combination of the metapaths. We refer to this version as "TARA-TS (metapath2vec)".

Henceforth, we refer to TARA-TS (graphlets), TARA-TS (node2vec), and TARA-TS (metapath2vec) as different "TARA-TS versions". If we just say "TARA-TS", the discussion applies to all three versions.

In theory, the heterogeneous information could be captured not just via metapaths but also via heterogeneous graphlets (Gu *et al.*, 2018) (versus homogeneous graphlets discussed thus far). However, in practice, heterogeneous graphlet counting is infeasible for as large networks as studied in this paper, due to its exponential computational complexity. This is not an issue for homogeneous graphlet counting because methods such as Orca (Hočevar and Demšar, 2014) rely on combinatorics to infer the counts of some

(larger) graphlets from the counts of other (smaller) graphlets, significantly reducing the computational complexity. However, no publicly available implementation of combinatorial relationships for counting heterogeneous graphlets exists. Similar holds for a method that *directly* extracts the feature vector of a *node pair* (Hulovatyy *et al.*, 2014), versus extracting graphlet features of *individual nodes* and then combining these, as TARA does: no combinatorial approach for direct node pair graphlets exists. Instead, current heterogeneous and node pair graphlet counting require exhaustive graphlet enumeration and are thus infeasible.

Lastly, we discuss why we do not use feature vectors from PrimAlign, the next most comparable method to TARA (Gu and Milenković, 2019) that already integrates within-network topological and across-network sequence information. This is because PrimAlign's algorithmic design does not allow for feature vector extraction. Recall from Section 1.4 that PrimAlign models the integrated network as a Markov chain, which is then repeatedly transitioned until convergence. This means that the weights between every node pair are updated at the same time, based on the weights of every node pair from the previous state of the chain. So, PrimAlign operates on every node pair *at once* with respect to their weights, rather than on *individual nodes or node pairs* with respect to any kind of feature vector, meaning that we cannot extract such information.

2.3 TARA-TS's classification and alignment generation

We must first evaluate whether TARA-TS can correctly predict nodes as functionally (un)related. If not, there would be no point to use it to form an alignment. To evaluate this, we train and test a classifier as follows.

For a given ground truth-rarity dataset (Section 2.1), the positive class consists of functionally related node pairs, and the negative class consists of functionally unrelated node pairs. Because the latter is much larger, we create a balanced dataset by undersampling the negative class to match the size of the positive class, as typically done (Sun *et al.*, 2009). Due to randomness in sampling, we create 10 balanced datasets and repeat the classification process for each, averaging results over them.

For a given balanced dataset, we split it into two sets: y percent of the data is randomly sampled and put into one set, and the remaining (100 - y) percent is put into the other set. This sampling is done with the constraint that in each of the two sets, 50% of the data instances have the positive class and 50% have the negative class. Again, due to randomness in sampling, we repeat this 10 times to create 10 data splits of y/(100 - y) percent and repeat the classification process for each, averaging results over them.

For a given y/(100 - y) split, we train a logistic regression classifier on the set containing y percent of the data (i.e., the training set). We use this trained classifier to predict on the remaining (100 - y)percent of the data (i.e., the testing set), measuring the accuracy and area under receiver operating characteristic curve (AUROC).

In summary, for a given y, for each balanced dataset, we have 10 accuracy and 10 AUROC scores, corresponding to the 10 data splits; for each measure, we compute the average over the 10 splits, obtaining a single accuracy and single AUROC. Then, for a given y, given the single accuracy and single AUROC for each balanced dataset, i.e., given 10 accuracy and 10 AUROC scores for the 10 balanced datasets, for each measure, we compute the average over the 10 balanced datasets, for each measure, we compute the average over the 10 balanced datasets to obtain a final accuracy and a final AUROC score for that y. In our evaluation, we vary y from 10 to 90 in increments of 10; each variation is called a "y percent training test". This allows us to test how the amount of training data affects the results, which is important because in many real-world applications, only a small amount of data may be available for training.

Only if the average accuracy and AUROC are high, i.e., if TARA-TS accurately predicts functionally (un)related nodes to be functionally (un)related, does it make sense to use TARA-TS to create an alignment for protein functional prediction. If this is the case, we create an alignment as follows. Given one y/(100 - y) split and the classifier trained on it, we take every node pair from the testing set that is predicted as functionally related and add it to the alignment. Here, it is important to only use the testing set for the alignment. This way, there is no overlap between node pairs in the testing set and node pairs in the training set. Consequently, this avoids any circular argument. For simplicity, we do not repeat this process for all data splits, as we found that the split choice had no major effect on the classification performance. We only use the "first" one, which in our implementation corresponds to a starting seed of 0 for Python's random number generator when performing sampling. We have a total of 270 alignments, corresponding to all combinations of the 3 TARA-TS versions, the 9 percent training tests, and the 10 balanced datasets.

2.4 Using an alignment for protein functional prediction

An ultimate goal of biological NA is across-species protein functional prediction, so each NA method must be evaluated in this context. For a given ground truth-rarity dataset (atleast*k*-EXP at the *r* rarity threshold), we consider GO terms that annotate at least two yeast proteins and at least two human proteins; these minimums are required to be able to make predictions for the GO term. Then, we use a (TARA-TS's or an existing method's) alignment in an established protein functional prediction framework (Meng *et al.*, 2016), as follows. In the alignment, for each protein *u* that is annotated by at least *k* GO term(s), such that the GO term(s) annotate *r* or fewer proteins (i.e., for each protein for which a prediction can actually be made), *u*'s true GO term(s) are hidden. Then, for each GO term *g*, the framework determines if the alignment is significantly "enriched" in *g*. The hypergeometric test is used for this, calculating if the number of aligned node pairs in which the aligned proteins share *g* is significantly high (*p*-value less than 0.05 (Meng *et al.*, 2016)). If so, node *u* is predicted to be annotated by GO term *g*. Repeating for all applicable proteins and GO terms results in the final list of predicted protein-GO term associations. From this prediction list, the framework calculates the precision (percentage of the predictions that are in a given ground truth-rarity dataset) and recall (percentage of the protein-GO term association from a given ground truth-rarity dataset that are among the predictions).

3 Results

3.1 Comparison of TARA-TS versions

Classification. Here, we study classification performance of the three TARA-TS versions (graphlets, node2vec, metapath2vec) and TARA, i.e., how correctly they predict as functionally (un)related the protein pairs from testing data in a given y percent training test. We would ideally do this on all nine ground truth-rarity datasets. However, two of them, atleast3-EXP at the 50 and 25 thresholds, are too small for TARA-TS and TARA to perform any classification on; inability to learn on small datasets is a drawback of machine learning methods in general, not just TARA-TS and TARA. Thus, we have seven viable ground truth-rarity datasets.

Due to space constraints, we discuss the effect of various parameters (k in atleastk-EXP, GO term rarity threshold, and y percent training test) on the classification performance of a given TARA-TS version, for each version, in Supplementary Section S1.1. Instead, here we focus on comparing the three TARA-TS versions and TARA.

We expect all TARA-TS versions to have higher accuracy and AUROC than TARA, as they extract topology plus sequence features from the integrated yeast-human network, unlike TARA, which extracts topology features only within each individual network. However, we find that this is not always the case (Fig. 2(a) and Supplementary Figs. S1-S2): (i) The *relative* accuracy change of TARA-TS (graphlets) over TARA ranges from -3% (decrease) to 5% (increase), depending on the atleast*k*-EXP ground truth dataset, GO term rarity threshold, and *y* percent training test, with an average change of 0%; and its relative AUROC change ranges from -3% to 5%, with an average change of 1%. (ii) TARA-TS (node2vec) does always improve over TARA though. Its relative accuracy change over TARA ranges from 6% to 27%, with an average change of 14%; and its relative AUROC change ranges from 9% to 32% with an average change of 16%. (iii) As for TARA-TS (metapath2vec), we also see improvement over TARA, though not as large as for TARA-TS (node2vec). In particular, the relative accuracy change of TARA-TS (metapath2vec) over TARA ranges from -1% to 14% with an average change of 6%; and its relative AUROC change ranges from 2% to 15%, with an average change of 7%.

Overall, we find that in terms of classification performance, TARA-TS (node2vec) to perform the best, followed by TARA-TS (metapath2vec), and followed by TARA-TS (graphlets) and TARA that are tied; all four perform significantly better than at random (Supplementary Figs. S1-S2).

Protein functional prediction. Here, we evaluate the protein functional prediction accuracy of alignments of the three TARA-TS versions and TARA. For simplicity, we consider a subset of all nine y percent training tests, focusing on the extremes (10 and 90) and the middle (50), because classification accuracy does not vary much between the different percent training options. Recall that classification cannot be performed on two (small) ground truth-rarity datasets, atleast3-EXP at thresholds 50 and 25, so no alignments exist for them, and thus protein functional prediction is not possible. So, for each TARA-TS version and TARA, we have 21 evaluation tests, resulting from combinations of the three selected y values and the seven viable (as opposed to all nine) ground truth-rarity datasets.

First, we study the performance of the three TARA-TS versions. For each version, we expect that as we increase the amount of training data (10 to 50 to 90), precision will increase and recall will



Figure 2: Comparison of the three TARA-TS versions and TARA, for GO term rarity threshold 25 and ground truth dataset atleast1-EXP, in terms of: (a) classification accuracy, (b) protein functional prediction accuracy, (c) overlap between aligned yeast-human protein pairs, and (d) overlap between predicted protein-GO term associations. In panel (b), the alignment for e.g., TARA contains 1,716 aligned protein pairs and predicts 3,474 protein-GO term associations. In panels (c)-(d), the pairwise overlaps are measured via the Jaccard index. Panel (a) encompasses all y percent training tests. Panels (b)-(d) are for the 90% training test. Results for the other ground-truth rarity datasets and percent training tests are shown in Supplementary Figs. S1-S7.

decrease. This is because a larger training dataset likely means that the classifier will be better (increasing precision), but will lead to a smaller testing dataset and thus smaller alignments and fewer predictions (decreasing recall). We expect that as k increases (in our atleast k-EXP ground truth datasets), precision will increase and recall will decrease. This is because at higher k, TARA-TS will be trained on higherquality data (increasing precision), but there will be less data overall, resulting in smaller alignments and fewer predictions (decreasing recall). We expect that as we consider rarer GO terms, precision will increase and recall will decrease. Rarer GO terms may be more meaningful (Hayes and Mamano, 2017; Gu and Milenković, 2019), so the data will be of higher quality (increasing precision), but there will be less of it overall (decreasing recall). Indeed, we observe all of these expected trends for all TARA-TS versions (Supplementary Fig. S3-S5).

Second, we compare the performance of the three TARA-TS versions and TARA. Shockingly, all four methods yield almost equal protein functional prediction accuracy (Fig. 2(b) and Supplementary Figs. S3-S5). This is unexpected, as TARA-TS uses sequence information that TARA does not. We take a closer look at the alignments and predictions made by each method to see if the different methods are aligning the same nodes, or predicting the same protein-GO term associations. So, we investigate how much their alignments overlap (Fig. 2(c)), and how much their predictions overlap (Fig. 2(d)). We find that the different methods are all aligning and predicting at least somewhat different information from each other. Yet, their predictions are equally accurate. Also, we find that TARA is more similar to (i.e., overlaps the most with) TARA-TS (graphlets) than to TARA-TS (node2vec) and TARA-TS (metapath2vec), which makes sense since the former also uses graphlets to extract feature vectors like TARA, and the latter two do not. Also, TARA-TS (node2vec) and (metapath2vec) are more similar to each other than to the other methods, which makes sense since they use a similar random walk-based feature extraction method.

It is surprising that TARA-TS (graphlets) does not improve upon TARA, i.e., that the additional sequence information does not improve upon only topological information. A reason may be that the across-network sequence information complements, rather than enhances, the within-network topology information. Some of the predictions made by TARA-TS (graphlets), specifically those that overlap with TARA's, may be due to the within-network topology information used by both methods, and the remaining predictions made by TARA-TS (graphlets) may be due to the across-network sequence information, which is not used by TARA.

Also, it is surprising that TARA-TS (metapath2vec) does not improve upon TARA-TS (node2vec). Both use a similar random walk-based embedding process, but metapath2vec additionally accounts for the heterogeneous information in the integrated network. The lack of improvement may be because the additional information captured by the considered metapaths is not useful in this task, or because constraining random walks by node type leads to less neighborhood structure being explored. For example, at some point in a random walk, a human node may have many human neighbors, but the walk is forced to move to a yeast node due to the metapath constraints. Then, the neighborhood of that human node will not be well explored. However, because the number of possible metapaths to test in order to find the best one(s) is exponential with respect to the length of the path, it is not feasible to test every possibility, even for short lengths. Thus, an efficient way of selecting appropriate metapaths for a given network would be necessary to continue to pursue metapath-based embedding methods for this task. However, to our knowledge no such selection process exists, which is why we do not pursue this problem beyond the metapaths we have considered.

Because TARA-TS (node2vec) not only yields the best classification performance, i.e., predicts functional (un)relatedness the best out of all TARA-TS versions but also captures the most novel protein functional information compared to TARA (i.e., the predictions it makes overlap the least to those made by TARA out of all TARA-TS versions), we continue only with TARA-TS (node2vec) as the selected TARA-TS version.

3.2 TARA-TS versus TARA in the task of protein functional prediction: toward TARA++

Focusing on TARA-TS (node2vec) as the selected TARA-TS version (i.e., simply as TARA-TS), we zoom into the comparison between it and TARA. The two methods have different alignments and make different predictions (Fig. 3), so how can they still have similar protein functional prediction accuracy? To answer this, we look at the precision and recall of predictions made by both methods, only those predictions made by TARA-TS but not TARA, and only those predictions made by TARA but not TARA-TS (Fig. 3(b) and Supplementary Fig. S9). From this, we highlight two findings. First, graphlets, which use only topological information, perform as well as network embedding features that use both topological and sequence information. This is supported by the fact that predictions made only by TARA and only by TARA-TS produce similar accuracy in almost all evaluation tests. This motivates the need to develop better graphlet-based methods for integrated networks as future work. Second, predictions made by both methods are significantly more accurate than predictions made by any one method alone. In a sense, their overlap is integrating state-of-the-art research across the computational biology and social network domains, by combining TARA's graphlet-based topology-only features with TARA-TS's embedding-based topology-and-sequence features. So, the overlapping predictions combine the strengths of both domains.

Because the overlap of TARA-TS and TARA has such high prediction accuracy, we take it as our new TARA++ method, which we consider further. Then, to simplify comparisons between TARA++ and existing NA methods, we choose a representative percent training test (either TARA++10, TARA++50, or TARA++90) for each of the seven viable ground truth-rarity datasets. In other words, we go from 21 "TARA++ versus existing methods" evaluation tests to seven. Generally, for each viable ground truth-rarity dataset, we try to choose the percent training test that has both high precision (predictions are accurate) and a large number of predictions (we uncover as much of biological knowledge as possible), as these represent TARA++'s best results. So, we choose TARA++90 for all ground truth-rarity datasets except atleast2-EXP at the 50 and 25 rarity thresholds, where we choose TARA++10. Henceforth, we refer to all of the selected TARA++ versions simply as TARA++.

3.3 TARA++ versus existing NA methods in the task of protein functional prediction

We compare TARA++'s predictions against those of two most fairly comparable state-of-the-art methods, TARA and PrimAlign. Also, we consider predictions resulting from using only sequence information, Sequence. Here, we treat the 55,594 anchor links by themselves as the alignment; as no topological information is used, this is not an NA method. With TARA and Sequence, we can separately analyze each aspect, i.e., within-network topological information only and across-network sequence information only, and evaluate how each compares to our integrative TARA++. (TARA++'s predictions are by definition a subset of TARA's predictions, and so we expect TARA++ to have higher precision but lower recall than TARA.) With PrimAlign, we can evaluate how this integrative but unsupervised method compares to our also integrative but supervised TARA++. Importantly, TARA and PrimAlign were already shown to outperform many previous NA methods (Section 1.4). So, comparing to these two methods is sufficient. Also, keep in mind that like with TARA, a theoretical precision of 1 is not



Figure 3: Comparison of the selected TARA-TS version and TARA, for GO term rarity threshold 50, ground truth dataset atleast1-EXP, and the 90% training test, in terms of overlap between their: (a) aligned yeasthuman protein pairs and (b) predicted protein-GO term associations. In panel (b), precision and recall are shown for each of the three prediction sets captured by the Venn diagram; TARA++'s predictions are those in the overlap. The overlaps are for one of the 10 balanced datasets; so, the alignment size and prediction number of a method may differ from those in Fig. 2(b), where the statistics are averaged over all balanced datasets. Results for the other ground truth-rarity datasets are shown in Supplementary Figs. S8-S9.

practically possible with TARA++. This is because for a given training/testing split, TARA++ uses a part (up to 90%) of the ground truth functional data for training, and so for that split, it is impossible to make predictions for the training data portion.

We believe that precision is more important than recall. This is because for potential wet lab validation of predictions, it is more important to have fewer but mostly correct predictions (e.g., 90 correct out of 100 made) than a greater number of mostly incorrect predictions (e.g., 300 correct out of 1000 made). While in the latter example more predictions are correct, leading to higher recall, many more are also incorrect, leading to lower precision. We do not entirely discount recall though, as it still brings value.

Our key results are as follows (Fig. 4 and Supplementary Fig. S10). In terms of precision, TARA++ is the best for 6/7 ground truth-rarity datasets. It is only slightly inferior to PrimAlign for 1/7 datasets (atleast1-EXP for ALL GO terms), but TARA++ has much higher recall than PrimAlign on this dataset. Speaking of recall, TARA is expected to always outperform TARA++, and this is what we observe. Of the remaining existing methods, TARA++ is the best for 2/7 datasets – atleast1-EXP at the ALL and 50 rarity thresholds – even though TARA++ makes much *fewer* predictions than the next best method, Sequence. For the other datasets, TARA++'s recall is lower than that of PrimAlign and Sequence. This is expected, since TARA++ and every other method is relatively small, for example only 0.06 lower on average compared to TARA, while TARA++ is much better in terms of precision than every other method, for example 0.2 greater on average compared to TARA. As discussed above, such a trade-off between precision and recall is worth it for our task.

We see that the precision of TARA++ is much greater than simply the sum of precision from TARA and Sequence, suggesting that integrating within-network topological and across-network sequence information has compounded effects. This further highlights the need for such approaches.

Finally, we look at the time it takes to obtain an alignment for TARA-TS, TARA, and PrimAlign, for the ALL GO term rarity threshold, which has the most data and is thus the worst case time-wise out of all thresholds. As TARA++ comes from the intersection of TARA-TS's and TARA's results, its time is either the maximum or sum of TARA-TS's and TARA's, if the two are run at the same time or one after the other, respectively. Our findings are as follows (also, see Supplementary Table S1).

For TARA-TS, as k (in the atleast k-EXP) increases, the time to produce an alignment is expected to decrease, as there is less (but higher-quality) data overall, and thus less data to train on. This is what we observe. When comparing TARA-TS and TARA, the former is faster, and this comes from the feature computation time, as both use the same supervised framework. TARA-TS's node2vec computation is expectedly faster than TARA's graphlet counting even when using Orca for two reasons. First, the random walks produced by node2vec can be thought of as sampling the network structure, which is much faster than capturing the full network structure like graphlets do. Second, node2vec is parallelized while Orca is not. Parallelization benefits node2vec a lot: the same number of random walks is performed for each node (parameter -r:), so no single node takes much longer than any other. However, for graphlet



Figure 4: Comparison of TARA++ and three existing methods in the task of protein functional prediction, for rarity thresholds (a) 50 and (b, c) 25, and for ground truth datasets (a, b) atleast1-EXP and (c) atleast2-EXP. The alignment size (the number of aligned yeast-protein pairs) and number of functional predictions (predicted protein-GO term associations) are shown for each method, except that TARA++ does not have an alignment *per se.* i.e., TARA++ comes from the overlap of *predictions* made by TARA and TARA-TS; hence the "N/A"s. For TARA++ and TARA, results are averages over all balanced datasets; the standard deviations are small and thus invisible. Results for the other ground truth-rarity datasets are shown in Supplementary Fig. S10.

counting, nodes with e.g., high degrees are the limiting time factor, and so parallelization would not help as much. Also note that TARA-TS's (and PrimAlign's) running time is missing the step of computing sequence-based anchor links; these anchors were precomputed and provided by the PrimAlign study. So, TARA-TS (and PrimAlign) has an unfair advantage over TARA. Despite this missing step, regardless of how TARA-TS and TARA are combined to form TARA++, PrimAlign will still be faster. However, it is about half as precise as TARA++. Even though TARA++ is slower, it is still practically feasible. So, the extra time is worth the almost doubling of precision.

4 Conclusion

TARA++ pushes the data-driven NA paradigm further. We showed that by integrating research knowledge across the computational biology and social network domains, TARA++ outperforms state-of-theart NA methods in the task of protein functional prediction, an ultimate goal of NA. As TARA++ is the first data-driven NA method to integrate topological and sequence information, it is just a proofof-concept approach. This work can be taken further. We found that graphlet-based features on the isolated networks (on topological information alone) perform as well as embedding-based features on the integrated network (on topological and sequence information combined), even though the latter (using more data) was expected to be better. So, developing a graphlet feature that would efficiently deal with an integrated network could yield further improvements. This might include novel algorithms for speeding up counting of heterogeneous graphlets in large data. Heterogeneous graphlets, or heterogeneous network embedding features other than metapath2vec, could better distinguish between different node/edge types in an integrated network and thus only improve over the features considered in this study. Also, we focused on NA of static networks. However, research in NA of dynamic (e.g., aging- or disease progression-related) networks is becoming popular (Vijayan *et al.*, 2017; Vijayan and Milenković, 2018a). So, our framework can be adapted to such novel NA categories.

Funding

National Science Foundation (NSF) CAREER CCF-1452795 award.

References

Ashburner, M., Ball, C. A., Blake, J. A., Botstein, D., Butler, H., et al. (2000). Gene Ontology: tool for the unification of biology. Nature Genetics, 25(1), 25.

- Balakrishnan, R., Park, J., Karra, K., Hitz, B. C., Binkley, G., et al. (2012). YeastMine—an integrated data warehouse for Saccharomyces cerevisiae data as a multipurpose tool-kit. Database, **2012**.
- Cai, H., Zheng, V. W., and Chang, K. C.-C. (2018). A comprehensive survey of graph embedding: Problems, techniques, and applications. *IEEE Transactions on Knowledge and Data Engineering*, 30(9), 1616–1637.
- Cao, X., Chen, Z., Zhang, X., and Yu, Y. (2017). IMAP: An iterative method for aligning protein-protein interaction networks. In 2017 IEEE International Conference on Bioinformatics and Biomedicine (BIBM), pages 317–324. IEEE.
- Chatr-Aryamontri, A., Oughtred, R., Boucher, L., Rust, J., Chang, C., et al. (2017). The BioGRID interaction database: 2017 update. Nucleic Acids Research, 45(D1), D369–D379.
- Dong, Y., Chawla, N. V., and Swami, A. (2017). metapath2vec: Scalable representation learning for heterogeneous networks. In Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pages 135–144. ACM.
- Ellens, K. W., Christian, N., Singh, C., Satagopam, V. P., May, P., and Linster, C. L. (2017). Confronting the catalytic dark matter encoded by sequenced genomes. *Nucleic Acids Research*, 45(20), 11495–11514.
- Elmsallati, A., Clark, C., and Kalita, J. (2016). Global alignment of protein-protein interaction networks: A survey. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, **13**(4), 689–705.
- Emmert-Streib, F., Dehmer, M., and Shi, Y. (2016). Fifty years of graph matching, network alignment and network comparison. *Information Sciences*, 346, 180–197.
- Faisal, F. E., Meng, L., Crawford, J., and Milenković, T. (2015). The post-genomic era of biological network alignment. EURASIP Journal on Bioinformatics and Systems Biology, 2015(1), 3.
- Fan, J., Cannistra, A., Fried, I., Lim, T., Schaffner, T., et al. (2019). Functional protein representations from biological networks enable diverse cross-species inference. Nucleic Acids Research, 47(9), e51–e51.
- Grover, A. and Leskovec, J. (2016). node2vec: Scalable feature learning for networks. In Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pages 855-864. ACM.
- Gu, S. and Milenković, T. (2018). Graphlets versus node2vec and struc2vec in the task of network alignment. In Proceedings of the 14th International Workshop on Mining and Learning with Graphs (MLG) at the 24th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining.
- Gu, S. and Milenković, T. (2019). Data-driven network alignment. arXiv preprint arXiv:1902.03277.
- Gu, S., Johnson, J., Faisal, F. E., and Milenković, T. (2018). From homogeneous to heterogeneous network alignment via colored graphlets. *Scientific Reports*, 8(1), 12524.
- Guzzi, P. H. and Milenković, T. (2017). Survey of local and global biological network alignment: the need to reconcile the two sides of the same coin. *Briefings in Bioinformatics*, **19**(3), 472–481.
- Hayes, W. B. and Mamano, N. (2017). SANA NetGO: a combinatorial approach to using Gene Ontology (GO) terms to score network alignments. *Bioinformatics*, 34(8), 1345–1352.
- Hočevar, T. and Demšar, J. (2014). A combinatorial approach to graphlet counting. Bioinformatics, 30(4), 559-565.
- Hulovatyy, Y., Solava, R. W., and Milenković, T. (2014). Revealing missing parts of the interactome via link prediction. *PLOS ONE*, **9**(3), e90073.
- Kalecky, K. and Cho, Y.-R. (2018). PrimAlign: PageRank-inspired Markovian alignment for large biological networks. Bioinformatics, **34**(13), i537–i546.
- Mamano, N. and Hayes, W. B. (2017). SANA: simulated annealing far outperforms many other search algorithms for biological network alignment. *Bioinformatics*, 33(14), 2156–2164.
- Meng, L., Striegel, A., and Milenković, T. (2016). Local versus global biological network alignment. *Bioinformatics*, **32**(20), 3155–3164.
- Milenković, T. and Pržulj, N. (2008). Uncovering biological network function via graphlet degree signatures. *Cancer Informatics*, **6**, CIN–S680.
- Nelson, W., Zitnik, M., Wang, B., Leskovec, J., Goldenberg, A., and Sharan, R. (2019). To embed or not: network embedding as a paradigm in computational biology. *Frontiers in Genetics*, **10**.
- Saraph, V. and Milenković, T. (2014). MAGNA: maximizing accuracy in global network alignment. Bioinformatics, 30(20), 2931–2940.
- Seah, B.-S., Bhowmick, S. S., and Dewey Jr, C. F. (2014). DualAligner: a dual alignment-based strategy to align protein interaction networks. *Bioinformatics*, **30**(18), 2619–2626.

- Shang, J., Qu, M., Liu, J., Kaplan, L. M., Han, J., and Peng, J. (2016). Meta-path guided embedding for similarity search in large-scale heterogeneous information networks. arXiv preprint arXiv:1610.09769.
- Shehu, A., Barbará, D., and Molloy, K. (2016). A survey of computational methods for protein function prediction. In Big Data Analytics in Genomics, pages 225–298. Springer.
- Singh, R., Xu, J., and Berger, B. (2008). Global alignment of multiple protein interaction networks with application to functional orthology detection. Proceedings of the National Academy of Sciences, 105(35), 12763-12768.
- Sun, Y., Wong, A. K., and Kamel, M. S. (2009). Classification of imbalanced data: A review. International Journal of Pattern Recognition and Artificial Intelligence, 23(04), 687–719.
- Sun, Y., Crawford, J., Tang, J., and Milenković, T. (2015). Simultaneous optimization of both node and edge conservation in network alignment via WAVE. In International Workshop on Algorithms in Bioinformatics, pages 16–39. Springer.
- Vijayan, V. and Milenković, T. (2018a). Aligning dynamic networks with DynaWAVE. Bioinformatics, 34(10), 1795– 1798.
- Vijayan, V. and Milenković, T. (2018b). Multiple network alignment via multiMAGNA++. IEEE/ACM Transactions on Computational Biology and Bioinformatics, 15(5), 1669–1682.
- Vijayan, V., Saraph, V., and Milenković, T. (2015). MAGNA++: Maximizing Accuracy in Global Network Alignment via both node and edge conservation. *Bioinformatics*, **31**(14), 2409–2411.
- Vijayan, V., Critchlow, D., and Milenković, T. (2017). Alignment of dynamic networks. Bioinformatics, 33(14), i180– i189.
- Vijayan, V., Gu, S., Krebs, E., Meng, L., and Milenković, T. (2020). Pairwise versus multiple global network alignment. IEEE Access, 8, 41961–41974.
- Zhang, J., Chen, B., Wang, X., Chen, H., Li, C., Jin, F., Song, G., and Zhang, Y. (2018). MEgo2Vec: Embedding Matched Ego Networks for User Alignment Across Social Networks. In Proceedings of the 27th ACM International Conference on Information and Knowledge Management, pages 327–336. ACM.

Supplementary material: Data-driven biological network alignment that uses topological, sequence, and functional information

Shawn Gu and Tijana Milenković

Snawn Gu and Tijana Milenković

Department of Computer Science and Engineering, ECK Institute for Global Health, Center for Network and Data Science, University of Notre Dame, IN 46556.

E-mail: tmilenko@nd.edu

S1
Results

S1.1
TARA-TS versus TARA in the classification context

Here, we comment on the performance of TARA-TS; recall that we use TARA-TS to refer to any of TARA-TS (graphlets, node2vec, metapath2vec). For a fixed GO term rarity threshold, as k in our atleastk-EXP ground truth datasets increases, we expect TARA-TS's (and TARA's) accuracy and AUROC to increase, as the condition for proteins to be functionally related becomes more stringent and thus the functional back in the stringent back in the string proteins to be functionally related becomes more stringent and thus the functional data becomes of higher quality. Also, for a fixed k, as we decrease the GO term rarity threshold (i.e., consider rarer GO terms), we expect accuracy and AUROC to increase, since rarer GO terms may be meaningful (Hayes and Mamano, 2017), again resulting in higher-quality data. We find the former expectation to hold, for all GO term rarity thresholds (Supplementary Figs. S1-S2). However, for the latter expectation, we find that classification accuracy and AUROC somewhat decrease (Supplementary Figs. S1-S2). This may be because as rarer GO terms are considered, the amount of training data decreases, which is what could be causing performance decreases.

As we increase y, the amount of training data, we expect accuracy and AUROC to increase, as more data is used during classification. For accuracy, for TARA-TS (graphlets), we observe this for 6/7 ground truth-rarity datasets, although for 4/6 of the datasets, the increase is minimal ($\sim 1\%$). In the remaining case, the accuracy increases until about 60% training data, and then drops. For TARA-TS (node2vec), we observe this for 6/7 ground truth-rarity datasets, although for 4/6, the increase is minimal. In the remaining case, the accuracy increases until about 60% training data, and then drops. For TARA-TS (metapath2vec), we observe this for all 7 ground-truth rarity datasets. For AUROC, for TARA-TS (graphlets), we observe the expected trend for all ground truth-rarity datasets, although for 4/7 of these datasets, the increase is minimal (~1%). For both TARA-TS (node2vec) and TARA-TS (metapath2vec), we observe the expected trend for all ground-truth rarity datasets, although for 3/7 of these datasets, the increase is minimal. These unexpected trends (mostly minor increase of accuracy and AUROC even with large increase of y) are promising though, because they mean that TARA-TS does not have to use a majority of the functional data for training to still obtain good results; even using only 10% of the data seems to suffice.

S2 Supplementary figures and tables

	atleast1-EXP	atleast2-EXP	atleast3-EXP
TARA-TS	3811	480	444
TARA	8090	4676	4634
PrimAlign	16	16	16
Sequence	N/A	N/A	N/A

Supplementary Table S1: Running times (in seconds) of TARA-TS, TARA, PrimAlign, and Sequence, when considering ALL GO terms. TARA++'s running time is a function of TARA-TS's and TARA's (see Section 3.3 in the main paper). We use a precomputed alignment for Sequence (see Section 3.3 in the main paper), hence the "N/A"s.



Supplementary Figure S1: Average prediction accuracy of percent training tests for rarity thresholds (a, d, g) ALL, (b, e) 50, and (c, f) 25 using ground truth datasets (a, b, c) atleast1-EXP, (d, e, f) atleast2-EXP, and (g) atleast3-EXP. A dotted black line indicates the accuracy expected if the classifier makes random predictions. Qualitatively similar results for AUROC are shown in Supplementary Figs. S2.



Supplementary Figure S2: Average AUROC of percent training tests for rarity thresholds (**a**, **d**, **g**) ALL, (**b**, **e**) 50, and (**c**, **f**) 25 using ground truth datasets (**a**, **b**, **c**) atleast1-EXP, (**d**, **e**, **f**) atleast2-EXP, and (**g**) atleast3-EXP. A dotted black line indicates the AUROC expected if the classifier makes random predictions.



Supplementary Figure S3: Comparison of TARA and TARA-TS using 10% of the data as training for rarity thresholds (**a**, **d**, **g**) ALL, (**b**, **e**) 50, and (**c**, **f**) 25 using ground truth datasets (**a**, **b**, **c**) atleast1-EXP, (**d**, **e**, **f**) atleast2-EXP, and (**g**) atleast3-EXP in the task of protein functional prediction. The alignment size (i.e., the number of aligned yeast-protein pairs) and number of functional predictions (i.e., predicted protein-GO term associations) made by each method are shown above. For example, the alignment for TARA-10 in (**a**) contains 244,433 aligned yeast-human protein pairs, and predicts 538,397 protein-GO term associations. Raw precision and recall values are color-coded inside each panel.



Supplementary Figure S4: Comparison of TARA and TARA-TS using 50% of the data as training for rarity thresholds (**a**, **d**, **g**) ALL, (**b**, **e**) 50, and (**c**, **f**) 25 using ground truth datasets (**a**, **b**, **c**) atleast1-EXP, (**d**, **e**, **f**) atleast2-EXP, and (**g**) atleast3-EXP in the task of protein functional prediction. The alignment size (i.e., the number of aligned yeast-protein pairs) and number of functional predictions (i.e., predicted protein-GO term associations) made by each method are shown above. For example, the alignment for TARA-10 in (**a**) contains 244,433 aligned yeast-human protein pairs, and predicts 538,397 protein-GO term associations. Raw precision and recall values are color-coded inside each panel.



Supplementary Figure S5: Comparison of TARA and TARA-TS using 90% of the data as training for rarity thresholds (**a**, **d**, **g**) ALL, (**b**, **e**) 50, and (**c**, **f**) 25 using ground truth datasets (**a**, **b**, **c**) atleast1-EXP, (**d**, **e**, **f**) atleast2-EXP, and (**g**) atleast3-EXP in the task of protein functional prediction. The alignment size (i.e., the number of aligned yeast-protein pairs) and number of functional predictions (i.e., predicted protein-GO term associations) made by each method are shown above. For example, the alignment for TARA-10 in (**a**) contains 244,433 aligned yeast-human protein pairs, and predicts 538,397 protein-GO term associations. Raw precision and recall values are color-coded_inside each panel.



Supplementary Figure S6: Pairwise overlap, measured by Jaccard index, of the alignments made by TARA and TARA-TS for rarity thresholds (**a**, **d**, **g**) ALL, (**b**, **e**) 50, and (**c**, **f**) 25 using ground truth datasets (**a**, **b**, **c**) atleast1-EXP, (**d**, **e**, **f**) atleast2-EXP, and (**g**) atleast3-EXP, using percent training amounts described in Section 3.2.



Supplementary Figure S7: Pairwise overlap, measure by Jaccard index, of the predictions made by TARA and TARA-TS for rarity thresholds (**a**, **d**, **g**) ALL, (**b**, **e**) 50, and (**c**, **f**) 25 using ground truth datasets (**a**, **b**, **c**) atleast1-EXP, (**d**, **e**, **f**) atleast2-EXP, and (**g**) atleast3-EXP, using percent training amounts described in Section 3.2.



Supplementary Figure S8: Overlap of the alignments made by TARA and TARA-TS for rarity thresholds (**a**, **d**, **g**) ALL, (**b**, **e**) 50, and (**c**, **f**) 25 using ground truth datasets (**a**, **b**, **c**) atleast1-EXP, (**d**, **e**, **f**) atleast2-EXP, and (**g**) atleast3-EXP. Percentages are out of the total number of unique aligned node pairs made by both methods combined. The overlaps are for one of the 10 balanced datasets; so, the alignment size of a method may differ from those in Supplementary Figs. S3-S5, where the statistics are averaged over all balanced datasets.





	TARA only	TARA++	TARA-TS only
Precision	0.047	0.22	0.032
Recall	0.15	0.28	0.10









GO terms appearing ≤ 50 times

	TARA only	TARA++	TARA-TS only
ecision	0.18	0.54	0.18
Recall	0.038	0.047	0.038



TARA only TARA++ TARA-TS only 0.36 0.51 0.48 0.020 0.053 0.023

(e)

TARA-TS TARA (node2vec) 2592 719 2962 41% 12% 47%

TARA only	TARA++	TARA-TS only
0.33	0.71	0.35
0.12	0.070	0.14

(c)



GO terms appearing ≤ 25 times

TARA only	TARA++	TARA-TS only
0.63	0.79	0.47
0.018	0.061	0.015

(f)

(g)

Supplementary Figure S9: Overlap of the predictions made by TARA and TARA-TS for rarity thresholds (a, d, g) ALL, (b, e) 50, and (c, f) 25 using ground truth datasets (a, b, c) atleast1-EXP, (d, e, f) atleast2-EXP, and (g) atleast3-EXP. Percentages are out of the total number of unique predictions made by both methods combined. Precision and recall are shown for each of the three prediction sets captured by the Venn diagram; TARA++'s predictions are those in the overlap. The overlaps are for one of the 10 balanced datasets; so, the prediction number of a method may differ from those in Supplementary Figs. S3-S5, where the statistics are averaged over all balanced datasets.



Supplementary Figure S10: Comparison of four NA methods for rarity thresholds (**a**, **d**, **g**) ALL, (**b**, **e**) 50, and (**c**, **f**) 25 using ground truth datasets (**a**, **b**, **c**) atleast1-EXP, (**d**, **e**, **f**) atleast2-EXP, and (**g**) atleast3-EXP in the task of protein functional prediction. The alignment size (i.e., the number of aligned yeast-protein pairs) and number of functional predictions (i.e., predicted protein-GO term associations) made by each method are shown above, except that TARA++ does not have an alignment *per se.* i.e., TARA++ comes from the overlap of *predictions* made by TARA and TARA-TS; hence the "N/A"s. For example, the alignment for TARA in (**a**) contains 27,155 aligned yeast-human protein pairs, and predicts 91,618 protein-GO term associations. Raw precision and recall values are color-coded inside each panel. For TARA++ and TARA, results are averages over all balanced datasets; the standard deviations are small and thus invisible.