# Optimizing Query Predicates with Disjunctions for Column-Oriented Engines

Albert Kim MIT alkim@csail.mit.edu Atalay Mert Ileri Kansas State University atalay@k-state.edu Sam Madden MIT madden@csail.mit.edu

#### Abstract

Despite decades of work on query optimization, database research has given limited attention to optimizing predicates with disjunctions. What little past work there is, has mostly focused on optimizations for traditional row-oriented databases. However, a key difference between how roworiented and column-oriented engines evaluate predicates is that while row-oriented engines apply predicates to a *single* tuple at a time, column-oriented engines apply predicates to *sets* of tuples, adding another dimension to the problem. As such, row-oriented engines are focused only on the best order to apply predicates in to "short-circuit" the overall predicate expression, but column-oriented engines must additionally decide on the input sets of tuples for each predicate application. This is important, since smaller inputs lead to faster runtimes, and nontrivial, since the results of earlier predicates can be used to reduce the inputs to later predicates and predicates may be combined via disjunctions in the predicate expression. In this work, we formally analyze the predicate evaluation problem for column-oriented engines and present BESTD/UPDATE, the first ever polynomial-time, provably optimal algorithms to deduce the minimum input sets for each predicate application. BESTD/UPDATE's optimality is guaranteed under a wide range of cost models, representing different real-world scenarios. Furthermore, when combined with the predicate ordering algorithm HANANI, BESTD/UPDATE reduce into EVALPRED, a simple  $O(n \log^2 n)$  algorithm, which we recommend for practical use and optimal for all predicate expressions of nested depth 2 or less. Our evaluation shows, thanks to its optimality and polynomial planning time, EVALPRED outperforms not implementing any disjunction optimizations and exiting optimal algorithms by up to 2.6× and 28× respectively for synthetic workloads and by up to 1.3× and 100× respectively for queries from TPC-H and the CH-benchmark.

# 1 Introduction

Despite being a core topic of database research for decades, query optimization paid surprisingly little attention to optimizing queries with disjunctions. What little work there is, has mostly focused on optimizations for traditional row-oriented databases. However, there is a critical difference in how row-oriented and column-oriented execution engines handle predicates. In row-oriented engines, the input to a predicate is a *single* tuple and the output is a true/false value. Thus, given a predicate expression, the main focus is on finding the best order to apply the base predicates in to maximize the chances of "short-circuiting" the predicate expression as soon as possible (i.e., derive a true/false value for the predicate engines are *sets* of tuples, and evaluating a predicate expression must return the set of all tuples which satisfy that predicate expression. This adds another dimension to the problem. Not only must column-oriented engines determine the best order to apply predicate in, but they must also determine what input sets to use for each predicate application and how to combine the output sets to form the final result; we call this the *set management* problem. Smaller inputs lead to less time spent

on predicate evaluation, and this is particularly important if predicates include expensive components, such as JSON processing and unoptimized user-defined functions, or if the I/O to retrieve the values for predicate evaluation is slow. Thus, the engine must strive to select the smallest possible input sets for each predicate application, while still ensuring it can form the final result from the output sets. As a simple example, consider:

Query 1. Query with both conjunction and disjunction.

SELECT \* FROM T WHERE ( $(P_1 \text{ AND } P_2)$  OR  $P_3$ ) AND  $P_4$ 

Here, a row-oriented engine would only be interested in finding the best ordering for the base predicates  $P_1$ ,  $P_2$ ,  $P_3$ , and  $P_4$ . However, a column-oriented engine must go one step further and manage the input and output sets of each predicate application. Specifically, if the engine determines the best ordering is  $[P_4, P_3, P_1, P_2]$ , to ensure the smallest possible input to each predicate, it would:

- (1) Evaluate  $P_4$  on the set of all tuples in *T*.
- (2) Evaluate  $P_3$  on the resulting tuples from the previous step.
- (3) Evaluate  $P_1$  on the resulting tuples from step 1 minus the resulting tuples from step 2.
- (4) Evaluate  $P_2$  on the resulting tuples from the previous step.
- (5) Return the union of the resulting tuples from steps 2 and 4.

How can we be sure this is the best we can do, and how does the ordering of predicates affect set management? What happens when the predicate expression becomes more complex and has more predicates? These are the questions which we seek to address in this work.

## 1.1 Our Work

In our work, we formally analyze the predicate evaluation problem for column-oriented engines. We show through our analysis that the problem can be split into the two aforementioned components: 1. predicate ordering 2. set management. This split allows us to reuse existing work [13] [19] from traditional row-oriented databases for the predicate ordering component. For set management, we present BESTD/UPDATE, the first polynomial-time algorithms to produce provably optimal set management plans for any ordering of predicates. Here, we define optimality as incurring the fewest number of predicate evaluations possible. Our proofs show that BESTD/UPDATE deduce the smallest possible input set for each predicate application, and this analysis holds under a wide range of cost models, representing different real-world situations, as long as the cost model obeys a few properties. Furthermore, when combined with the predicate ordering algorithm HANANI [13], BESTD/UPDATE reduce into EVALPRED. EVALPRED is a simple  $O(n \log^2 n)$  algorithm which generates optimal predicate evaluation plans for all predicate expressions of nested depth 2 or less (e.g., ANDs of ORs) and is the algorithm which we recommend for practical use; note *n* here is the number of predicates. Compared to other optimal algorithms [18] which iterate over an exponential space, EVALPRED's strong theoretical backing allows it to achieve optimality while remaining almost trivially simple. Even for predicate expressions of depth 3 or greater (e.g., ANDs of ORs or ANDs), we show via experimentation that EVALPRED comes quite close to optimal; for 92% of the queries, the number of predicate applications invoked was within within 5% of minimum required.

Contributions. In short, our contributions are:

1. Our algorithms. EVALPRED, a simple, practical algorithm which generates optimal predicate evaluation plans for all predicate expression of depth 2 or less, and BESTD/UPDATE, which generate the best set management plans for any predicate ordering.

- 2. Our various theoretical results, including a formal analysis of the predicate evaluation problem for column-oriented engines and proofs of optimality for BESTD/UPDATE and EVALPRED.
- 3. Evaluation of our algorithms, which outperform not implementing any disjunction optimizations and existing optimal algorithms by up to 2.6× and 28× respectively for synthetic workloads and by up to 1.3× and 100× respectively for queries from TPC-H and the CH-benchmark.

The remainder of this paper is structured as follows. We start by presenting related work in Section 2. We formulate the predicate evaluation problem in Section 3 and present the practical EVALPRED first in Section 4. The more theoretical parts of the paper, including the problem analysis, BESTD/UPDATE, and the proofs of optimality are all presented later in Section 5. Section 6 shows our evaluation, and we conclude with Section 7.

# 2 Related Work

**TDACB/BYP.** As far as the authors are aware, Kastrati and Moerkotte's work on TDACB [18] and BYP [17] are the only other works which focus on optimizing queries with disjunctions for column-oriented engines. TDACB also stands unique from other related works in that it too generates optimal predicate evaluation plans. As such, it is the main competitor of our work. However, in contrast to the formal approach taken by our work, TDACB achieves its optimality by searching over the exponential space of all query plans. Despite several clever optimizations to prune the search space, such as branch-and-bound and memoization, TDACB still incurs a time complexity of  $O(n3^n)$ , in which *n* is the number of predicates. Given that Fontoura et al. report a real workload (from Yahoo Inc.) of up to 150k predicates with hundreds of unique attributes [11], clearly this solution is not scalable. In fact, our evaluation shows the planning time for TDACB can be quite expensive for even as few as 16 predicates. In comparison, EVALPRED is able to produce the optimal predicate evaluation plan in  $O(n \log^2 n)$  time, and our experiments show a 28× speedup in planning time over TDACB. Byp is Kastrati and Moerkotte's previous work which they improved upon with TDACB. BYP requires its input to be in DNF and is only locally optimal while still searching the entire search space of predicate evaluation plans. Thus, BYP is strictly worse than TDACB. Finally, both BYP and TDACB are meant for in-memory systems, and they assume little to no overhead in fetching the actual data. Thus, their guarantees of optimality do not extend to situations in which data is not stored in memory. In contrast, EVALPRED makes no such assumption.

HANANI. In 1977, Hanani introduced a predicate ordering algorithm [13], which we refer to as HANANI henceforth. Although HANANI was developed for row-oriented databases, the same algorithm can be used for column-oriented engines thanks to our split between predicate ordering and set management. As mentioned, combining HANANI with BESTD/UPDATE gives us the practical EVALPRED. However, while HANANI (and thus EVALPRED) is optimal for all predicate expressions of nested depth 2 or less, this is no longer the case for predicate expressions of nested depth 3 or greater due to an implicit assumption of a depth-first search (DFS) traversal of the predicate expression. In Section 5, we present a property called "determinability" which identifies this issue.

**Boolean Difference Calculus.** Kemper et al. [19] propose an alternative ordering for predicates based on Boolean Difference Calculus (BDC). In BDC, each predicate's "importance" is measured based on their likelihood of affecting the overall result, and predicates are ordered based on decreasing importance. In our evaluation, we compare the performance of using BDC with BESTD/UPDATE against EVALPRED (HANANI and BESTD/UPDATE).

**Bypass.** Some of the most seminal works in optimizing disjunctions are the works regarding the bypass technique [20] [26] [8]. This technique splits the incoming tuples of a predicate into "true" and "false" streams based on the results, and only the tuples in the false stream are evaluated further, while tuples in the true stream are allowed to bypass the other predicates. While this technique was developed for row-oriented databases, Kastrati and Moerkotte's BYP adapt the main ideas for column-oriented engines.

**Factorization.** Chaudhuri et al. [7] present a work on factorizing predicate expressions with disjunctions to take advantage of existing indexes. As we discuss later, a key assumption to the optimality of our algorithms is the uniqueness of predicates. If the input predicate expression has reappearing predicates, we can use the algorithm presented by Chaudhuri et al. to minimize the number of reappearing predicates before applying our algorithms.

**Dewey Evaluation.** Fontoura et al. [11] present a way to efficiently encode predicate expressions with disjunctions and tens of thousands of predicates into simple labels. This encoding scheme could be used with our algorithms to reduce memory footprint.

**CNF/DNF.** The remaining works on disjunction optimization all focus on first trying to convert the predicate expression into either conjunctive normal form (CNF) or disjunctive normal form (DNF) and optimizing the execution from there [15] [30] [6] [23]. Unfortunately, the conversion process into CNF/DNF can result in an exponential number of terms [25], so just transforming the input into the correct form could be quite expensive. In addition, Kastrati and Moerkotte report that CNF/DNF-based evaluations generally tend to produce very poor plans and should be avoided [17].

**In Practice.** Other than simple factorization and reduction via Boolean implication, existing, well-used database systems implement few, if any, optimizations for disjunctions. PostgreSQL [29], for example, does partial transformations to CNF if separate clauses contain accesses to the same table to minimize the number of tuples for joins. MonetDB [14] and Spark SQL [3] do not seem to implement any additional optimizations, and based on conversations with developers from Vertica [21], Vertica "doesn't do anything special for ORs". The lack of exploration into this area has affected these systems, and we hope EVALPRED will serve as a good "rule-of-thumb" for systems to follow.

**Number of Predicates.** Some readers may doubt whether queries have enough predicates to warrant such optimizing efforts. However, as Fontoura et al. [11] report, advertising exchanges and automatic query builders can result in queries with tens of thousands of predicates. In addition, Chaudhuri et al. [7] discuss a workload that ranges up to over a hundred predicates. Johnson et al. [16] also evaluate their work on up to 40 predicates and report that for in-memory systems, the cost of evaluating predicates outweighs the cost of performing joins. All of this suggests that further research into this area can be highly beneficial.

# 3 **Problem Formulation**

This section presents a formulation of the exact problem which we wish to solve. We discuss the setting in which our work is applicable in Section 3.1 and describe the expected query properties in Section 3.2. Section 3.3 presents the model of the predicate evaluation system that we use in our analysis, and Section 3.4 lists the cost model properties required for our algorithms' optimality, as well as a few example cost models.

# 3.1 Setting

We first discuss the setting in which this work is applicable. Our analysis and algorithms are applicable to both column-oriented traditional databases and column-oriented distributed computing systems (together which we call column-oriented engines). As is common with column-oriented engines, we assume intermediate representations of tuples during query execution are simple indices into the tables which they come from and that the values of tuples are only materialized when needed. We assume sets of tuples are represented using lightweight data structures, such as bitmaps, and although no strong assumptions are made about the data storage, we assume that the time to fetch and process the data is significantly greater than the time to manipulate the lightweight indices of tuples in memory. Note that data storages such as hard disk drives, flash drives, and distributed file storages all fit within this criteria.

The primary resource we are concerned with is time. We assume we either have enough memory to hold the data needed to process the query or that the query can be executed off disk using a conventional buffer pool design. If indexing structures to accelerate query execution exist, our algorithms can take advantage of them, but the absence of them does not affect the correctness of our algorithms.

Finally, our algorithms produce plans at the *logical* layer. They dictate which tuples should be evaluated by which predicates to minimize the total number of evaluations. When actually executing the predicate evaluation, the system may choose to implement additional *physical* layer optimizations, such as retrieving extra tuples in the case of block-based data storages or even applying the predicate on additional tuples for vector processing. While these optimizations may blunt some of the benefits of our algorithms, it does not render our work meaningless. Many workloads contain predicates whose evaluation times overshadow the time it takes to fetch the data [16], and common predicates involving components such as regular expression matching and JSON processing cannot be vector processed. In fact, our own evaluation system fetches data in blocks, but we still see speedups of up to  $2.6 \times$  over not implementing any disjunction optimization.

# 3.2 Query Properties

We assume that the queries given to us are selection queries with complex predicate expressions. Predicate expressions may be composed of any number and depth of conjunctions and disjunctions of Boolean-result predicates. Predicates may be expensive (perhaps user-defined), and different predicates may have different costs. In our proofs, we assume a query's predicates are unique and that each appears only once in the predicate expression. If the same predicate occurs multiple times in the given predicate expression, one of the many common subexpression elimination algorithms from either research [7] or from practice [29] [12] may be applied to reduce the number of reoccurring predicates. Note that without uniqueness, our algorithms are no longer guaranteed to be optimal, but they will still return correct results. For clarity's sake, this paper assumes that we are working with single-table queries, but this is not a strict requirement. As long as each tuple in the source (single or joined) table has a global id (real or virtual), our algorithms are applicable. Even with pushdown optimizations, our algorithms still apply to pushed-down predicates at the individual table level.

# 3.3 Predicate Evaluation System

In our formulation, we model the predicate evaluation system as follows. The system initially starts with the set of all tuples (in the table), and its goal is to find the set of all tuples which satisfy the given predicate expression. To accomplish this, the system can perform two possible types of actions as many times as it wants:

- 1. The system can *apply* a predicate to a set of tuples to obtain the subset of tuples which satisfy that predicate.
- 2. The system can perform a *set operation* (i.e., union, intersection, difference) on known sets of tuples to derive a new set of tuples.

The application of a predicate corresponds to fetching the values of the input tuples and actually performing the predicate evaluation. Since this involves both fetching the data from storage and applying potentially expensive predicates (e.g., regular expression matching, JSON processing, and user-defined functions), we assume this action to be much more costly than performing a set operation action, which can be performed using bitwise operations on bitmaps in memory. To be called optimal, our algorithms should be able to find the sequence of actions which deduce the set of all tuples that satisfy the given predicate expression, while minimizing the costs of the actions in the sequence.

## 3.4 Cost Model

The cost model assigns a cost to each possible action the predicate evaluation system can take, as previously introduced. Our analysis and proofs of optimality hold for any cost model as long as they exhibit following three properties:

- 1. The cost of a predicate application is significantly greater than the cost of a set operation.
- 2. The cost of a predicate application increases with the input size.
- 3. When applying the same predicate to two different input sets, it is cheaper to apply the predicate once on the union of those sets than it is to apply the predicate separately on each set.

The first property comes from the basic setting under which this work is applicable, and the second property is often trivially true. The third property is a "triangle-inequality"-like property; if  $C_P(D)$  measures the cost of applying predicate *P* to input set *D*, then the property can be stated as:

$$C_P(D \cup E) < C_P(D) + C_P(E)$$

Our algorithms are optimal for any cost model which satisfies the above three properties. A simple example cost model might be:

### Cost Model 1.

$$C_P(D) = F_P|D| + \kappa$$
$$C_{\star}(D, E) = \epsilon (|D| + |E| + |D \star E| + \kappa')$$

The first line shows the cost of applying predicate *P* to input set *D*. Here,  $F_P$  is some cost constant cost factor specific to *P* (depending on what type of predicate *P* is), |D| is the number of tuples in *D*, and  $\kappa$  is some constant overhead cost. The second line shows the cost of applying set operation  $\star$  to input sets *D* and *E*. Here,  $\star$  is one of  $\cup$  (union),  $\cap$  (intersection), or  $\setminus$  (difference),  $\epsilon$  is the ratio of costs between set operations and predicate applications, and  $\kappa'$  is some other constant overhead cost. The cost includes the sizes of the input sets as well as the size of the output set. With respect to  $\epsilon$ , depending on the environment, a predicate application can easily cost  $30 \times \sim 100000 \times$  more than a set operation. In our experimental environment, simply reading 10M 4-byte int values from a RAID5 setup of HDDs took 274ms, while ANDing together two bitmaps of 10M elements in memory to produce another bitmap only took 8ms. Thus,  $\epsilon$  can be thought of as approaching 0 in most cases. The above cost model satisfies all three properties needed for our analysis. A small  $\epsilon$  value ensures the first property, and the costs of predicate applications grow proportionally with the sizes of the input sets, ensuring the second property. The inclusion of the constant overhead cost  $\kappa$  ensures the third property.

However, aside from the simple cost model presented above, more complex cost models representing different real-world scenarios also fit under our analysis. For example, for spinning disk drives, random I/O is often significantly more expensive than sequential I/O, so if the selectivity of the input set is above a certain threshold (e.g., 20%), then it is cheaper to simply scan the entire data column than it is to retrieve only the relevant tuples using random I/O. A different cost model that takes this into account would be:

## Cost Model 2.

$$C_P(D) = \begin{cases} F_{scan} + F_P|D| + \kappa & \text{if selectivity} > 20\% \\ F_{rnd} \text{blocks}(D) + F_P|D| + \kappa & \text{otherwise} \end{cases}$$
$$C_{\star}(D, E) = \epsilon (|D| + |E| + |D \star E| + \kappa')$$

Here, the set operation cost is the same as the previous cost model, but the cost the of the predicate application changes with respect to the selectivity of the input set D. If the input set contains more than 20% of all tuples in the table, the cost model chooses to scan the entire data column and incurs cost  $F_{scan}$ . If the input set contains fewer tuples, then it retrieves only the blocks which contains tuples in D using random I/O. Accordingly, blocks(D) returns the number of blocks, and  $F_{rnd}$  is the cost factor associated with random I/O. After fetching the data, the predicate is applied to the input tuples, incurring the cost  $F_P|D|$ . Note that despite its complexity, this cost model still satisfies our three properties, so our algorithms would be optimal for this case as well. Other cost models, representing other real-world scenarios, may also be used. As long as the three properties are satisfies, our analysis holds.

# 4 EVALPRED

We now introduce EVALPRED, our simple predicate evaluation algorithm, optimal for all predicate expressions of depth 2 or less, and what we recommend practitioners implement for most cases. Algorithm 1 presents EVALPRED. The algorithm first orders predicates from the given predicate expression<sup>1</sup> according to HANANI<sup>2</sup> and creates a *predicate tree* with that ordering (using makeTree). In the predicate tree, each node represents a predicate subexpression: leaf nodes represent base predicates, and intermediate AND/OR nodes combine children subexpression nodes; the root node refers to the entire predicate

<sup>&</sup>lt;sup>1</sup>We expect the given predicate expression to be in negation normal form (NOT operators are pushed inwards until they appear only in front of predicates); if not, this conversion can be done in linear time. Also, all negative predicates are replaced with positive predicates:  $P' = \neg P$ .

<sup>&</sup>lt;sup>2</sup>We present a compatible version of HANANI in Appendix A.



**Figure 1:** Predicate tree of Query 1 in  $[P_4, P_3, P_1, P_2]$  order.

expression. The tree is also normalized such that the parent of each AND node is an OR node and vice versa, resulting in an interleaving of ANDs and ORs across different levels of the predicate tree. Figure 1 depicts the predicate tree for the predicate expression in Query 1 for the ordering  $[P_4, P_3, P_1, P_2]$ .

EVALNODE then uses this predicate tree to determine the input set to each predicate and performs the actual evaluation. Conceptually, EVALNODE(node, D) returns the subset of tuples in D which satisfy the predicate subexpression represented by node. Thus, assuming R represents the set of all tuples in the table, EVALNODE(root, R) returns the set of all tuples which satisfy the given predicate expression  $P^*$ . As for the algorithm itself, EVALNODE traverses the predicate tree in a depth-first search (DFS) manner and reduces the input set sizes using various set operations. For leaf nodes, EVALNODE simply applies node's associated predicate to D. For AND nodes, the tuples that EVALNODE returns must satisfy every one of node's children, so each child updates D with its results, and later children are evaluated on only the set of tuples which have satisfied all previous children. For OR nodes, each tuple that EVALNODE returns can satisfy any one of node's children, so the tuples that satisfy one child are removed from the set of tuples which still have to be checked, and later children are evaluated on only the set of tuples which have not satisfied any previous children. Also, both AND and OR nodes return early if there are no tuples left to check (Lines 9-10 and 17-18). An example of running EVALPRED with the ordering  $[P_4, P_3, P_1, P_2]$  was provided in the introduction.

We hope Algorithm 1 appears simple and maybe somewhat even obvious to the reader. In fact, most column-oriented engines implement some variation of EVALPRED. However, they do not remove the done tuples from the todo tuples as shown in Line 16 and instead call EVALNODE(child, D) for each OR node child without any filtration. Furthermore, rather than its novelty, EVALPRED's true compelling point is that despite its simplicity, it is *optimal* for all predicate expressions of depth 2 or less, as we show later in Section 5. Thus, we can use this polynomial-time  $O(n \log^2 n)$  algorithm to generate optimal predicate evaluation plans, instead of the existing exponential-time algorithms.

**Implementation.** Although EVALPRED is presented as one algorithm here, in a real system, Lines 1 and 2 would be done during planning time, and only the call to EVALNODE in Line 3 would be performed during execution time. Furthermore, a real system would most likely use bitmaps to represent sets of tuples and all set operations would be replaced with bitwise operations.

**Time Complexity.** EVALPRED's plan time complexity is bounded by HANANI, which takes  $O(n \log^2 n)$  time. The other operation (makeTree) simply creates the predicate tree according to the given predicate ordering and can be done in O(n) time. Thus, the overall plan time complexity of EVALPRED is  $O(n \log^2 n)$ .

**Correctness.** The correctness of EVALPRED can be proven by showing EVALNODE(node, *D*) returns the subset of tuples in *D* which satisfy the predicate subexpression represented by node (the full proof is in Appendix B.1).

# 5 Theory

This section presents the theory backing EVALPRED. We first formalize the problem and show that a predicate evaluation system can be modeled as a sequence of operator/operand steps in Section 5.1. We constrain the solution space and show that the only operators we need to worry about are predicate applications in Section 5.2. We present BESTD/UPDATE and prove their optimality for the set management problem in Section 5.3. Finally, in Section 5.4, we discuss the predicate ordering problem, the conditions to reduce BESTD/UPDATE into EVALPRED, and HANANI's issues with depth-3+ predicate expressions. Note that this section contains proofs for only the main theorems. The proofs for lemmas can be found in Appendix E.

## 5.1 Formalization

#### 5.1.1 Valuations

Rather than reasoning directly about sets of tuples, it is easier for us to instead borrow from propositional logic [4] and reason about *valuations* (or true/false assignments) instead.

# Definition 1. A valuation is a tuple of true/false values.

Given a predicate expression with *n* unique predicates  $(P_1, P_2, ..., P_n)$  and a (data) tuple *r*, an *n*-length valuation can be constructed by evaluating each predicate on that tuple:  $(P_1(r), P_2(r), ..., P_n(r))$ . The resulting valuation is an *n*-length tuple of true/false values (e.g., (T, F, ..., T)). In our analysis, we can use a valuation to represent the set of all data tuples which evaluate to it<sup>3</sup>. Furthermore, we can use a set of valuations (or a *valuation set*) to represent the union of the tuples represented by each valuation. For example, the set of all  $2^n$  valuations represents the set of all tuples. Valuation sets allow us to reason about tuples based on their predicate results and are sufficient to prove the optimality of our algorithms.

As an example, consider the relation from Table 1 and the predicate expression: (age < 35 OR height > 175). Let  $P_1$  = age < 35 and  $P_2$  = height > 175. The valuation (*T*, *F*) represents the set of tuples containing Alice and Eve, since both are under the age of 35 and do not have a height greater than 175. The set of all valuations which satisfy the predicate expression is {(*T*, *T*), (*T*, *F*), (*F*, *T*)}, and this represents the set of tuples containing Alice, Bob, Dave, and Eve.

#### 5.1.2 Predicate Evaluation System

As mentioned in Section 3.3, a predicate evaluation system starts with the set of all valuations (i.e, the set of all tuples), and its goal is to derive the set of all valuations that satisfy the predicate expression using two types of operators: predicate applications and set operations. We define them as:

 $<sup>^{3}</sup>$ Note that the mapping from valuations to data tuples is merely logical and only used in our reasoning, so no actual evaluations have to be performed.

name	age	height
Alice	25	160
Bob	32	180
Charlie	48	170
Dave	56	178
Eve	30	165

 Table 1: Example relation T

**Definition 2.** The *predicate application* of predicate P on valuation set D is denoted P(D) and returns the subset of valuations in D which satisfy P.

**Definition 3.** A set operation is one of union  $(\cup)$ , intersection  $(\cap)$ , or difference  $(\setminus)$ .

The system performs these actions in a sequence of *steps*:

**Definition 4.** A step is an (operator, operand) pair: S = (O, D), in which operator O is either a predicate or a set operation, and operand D is the input valuations set(s). Applying the operator to operand results in the step's output and is denoted O(D).

Assuming  $S_i$  denotes the *i*th step,  $S_1 = (P, D)$  states that the first step is the predicate application of P on the valuation set D. Each step outputs a new valuation set, and later steps may use the outputs of previous steps. To keep track of all output valuation sets:

**Definition 5.** Given the sequence of steps  $[(O_1, \mathbf{D}_1), (O_2, \mathbf{D}_2), ..., (O_m, \mathbf{D}_m)]$ , **universe**  $U_i$  is defined by the recurrence relation:

$$U_i = U_{i-1} \cup \{O_i(\mathbf{D}_i)\}$$

with the initial universe:  $U_0 = \{\{T, F\}^n\}.$ 

**Definition 6.** A sequence of steps  $[(O_1, \mathbf{D}_1), (O_2, \mathbf{D}_2), ..., (O_m, \mathbf{D}_m)]$  is valid if, for each step  $(O_i, \mathbf{D}_i)$ , all valuation sets in  $\mathbf{D}_i$  are members of  $U_{i-1}$ .

Universe  $U_i$  contains all output valuations sets from the first *i* steps, and the (i + 1)th step can select any valuation set(s) from it to use as its input(s). The original universe  $U_0$  contains only the set of all valuations, since the predicate evaluation system must consider all tuples for its first step/predicate application. The system can be said to have achieved its goal after the *m*th step if universe  $U_m$  contains the set of all valuations which satisfy the predicate expression.

i	Step $(O_i, \mathbf{D}_i)$	Output $(X_i)$	Universe $(U_i)$
1	$(P_1, \{T, F\}^n)$	$\{(T,T),(T,F)\}$	$\{\{T,F\}^n, \{(T,T),(T,F)\}\}\$
2	$(\backslash, [\{T, F\}^n, X_1])$	$\{(F,F),(F,T)\}$	$\{\{T,F\}^n, \{(T,T), (T,F)\}, \{(F,F), (F,T)\}\}\$
3	$(P_2, X_2)$	$\{(F,T)\}$	$\{\{T,F\}^n, \{(T,T), (T,F)\}, \{(F,F), (F,T)\}, \{(F,T)\}\}$
4	$(\cup, [X_1, X_3])$	$\{(T,T), (T,F), (F,T)\}$	$ \{\{T,F\}^n, \{(T,T), (T,F)\}, \{(F,F), (F,T)\}, \{(F,T)\}, \\ \{(T,T), (T,F), (F,T)\}\} $

**Table 2:** Example sequence of steps for the predicate expression ( $P_1$  OR  $P_2$ ).

As an example, consider once again the relation from Table 1 and the predicate expression: (age < 35 OR height > 175), in which  $P_1$  = (age < 35) and  $P_2$  = (height > 175). Table 2 shows an example sequence of steps to deduce the set of all valuations which satisfy this predicate expression. The table shows, for each step, the operator and operand pair, the step's output (denoted  $X_i$ ), and the universe after that step. For example, the first step applies  $P_1$  to the set of all valuations  $\{T, F\}^n$ . This results in the valuation set  $\{(T, T), (T, F)\}$ , and this valuation set is added to the universe to form  $U_1$ . The second step is a set operation step and evaluates  $\{T, F\}^n \setminus X_1$ , in which  $X_1$  is the output valuation set from the first step (i.e.,  $\{(T, T), (T, F)\}$ ). After the last step, the universe contains the valuation set  $\{(T, T), (T, F), (F, T)\}$ , which is the set of all valuations that satisfies the predicate expression ( $P_1 \text{ OR } P_2$ ), so the predicate evaluation system is done after this step. As another point of reference, Table 3 presents the same sequence of steps as Table 2, but uses sets of tuples from Table 1 rather than valuation sets. Note that the valuation sets in Table 2 (i.e.,  $\{(T, T), (T, F)\}$ ) represents the output of the first step in Table 2 (i.e.,  $\{Alice, Bob, Eve\}$ ), and the set of all valuations which satisfy the predicate expression (i.e.,  $\{Alice, Bob, Dave, Eve\}$ ).

		-		
i	Step $(O_i, \mathbf{D}_i)$	Output (in tuples)	Universe (in tuples)	
1	$(P_1, \{T, F\}^n)$	{Alice, Bob, Eve}	{{Alice, Bob, Charlie, Dave, Eve}, {Alice, Bob, Eve}}	
2	2 $( \setminus, [\{T, F\}^n, X_1] )$	{Charlie, Dave}	{{Alice, Bob, Charlie, Dave, Eve}, {Alice, Bob, Eve},	
			{Charlie, Dave}}	
2	$2 \qquad (D \ V)$	{Dave}	{{Alice, Bob, Charlie, Dave, Eve}, {Alice, Bob, Eve},	
$\left  \begin{array}{c} \mathbf{J} \\ \mathbf{J} \\ \mathbf{J} \end{array} \right  = \left( \left  \mathbf{F}_{2}, \mathbf{A}_{2} \right  \right)$	$(\Gamma_2, \Lambda_2)$		{Charlie, Dave}, {Dave}}	
4	$(\cup, [X_1, X_3])$	{Alice, Bob, Dave, Eve}	{{Alice, Bob, Charlie, Dave, Eve}, {Alice, Bob, Eve},	
			{Charlie, Dave}, {Dave}, {Alice, Bob, Dave, Eve}}	

**Table 3:** Example sequence of steps for the predicate expression ( $P_1$  OR  $P_2$ ) using tuples from Table 1.

#### 5.1.3 Cost Model

Given the definitions above, we can now formally state the cost model properties from Section 3.4. **Definition 7.** The cost of a step  $(O, \mathbf{D})$  is denoted as  $C_O(\mathbf{D})$ , and the cost of a sequence of steps  $[(O_1, \mathbf{D}1), (O_2, \mathbf{D}2), ... (O_m, \mathbf{D}m)]$  is the sum of the costs of its individual steps:  $\sum_{i=1}^m C_{O_i}(\mathbf{D}_i)$ .

**Property 1.** The cost of any predicate application step (P, D) is significantly greater than the cost of any set operation step (O, D'):

$$C_O(\mathbf{D}')/C_P(D) \approx 0$$

**Property 2.** For any predicate P, if step (P, D) is more costly than step (P, D'), then D' cannot be a superset of D.

$$C_P(D) > C_P(D') \implies D' \not\supseteq D$$

Similarly, if D' is a strict superset of D, then step (P, D') is more costly than step (P, D):

$$D' \supset D \implies C_P(D') > C_P(D)$$

**Property 3.** For any predicate *P* and valuation sets *D* and *E*, applying *P* once to  $D \cup E$  is less costly than applying *P* to *D* and *E* individually:

$$C_P(D \cup E) < C_P(D) + C_P(E)$$

Note that Property 2 has a more relaxed condition than the one stated in Section 3.4. With these properties, we can formally state:

**Problem 1.** Given a predicate expression  $P^*$ , find the lowest cost, valid sequence of steps such that universe after the sequence contains the set of all valuations which satisfy  $P^*$ .

# 5.2 **Problem Reduction**

We now leverage the cost model properties to reduce the solution space. The reduction allows us to think about the problem using only predicate applications and constrains the total number of steps.

#### 5.2.1 Predicate-only Sequences

According to Property 1, set operations are practically free compared to predicate applications. Rather than worrying about what set operation steps can be added at which points to create a lower cost sequence, let us instead consider that after each predicate application step, all possible set operation steps are performed before the next predicate application step. This way, we only need to consider the order of predicate application steps in finding our optimal solution. Once the optimal sequence of predicate application steps has been found, we can reconstruct the intermediate set operation steps with bookkeeping. Thus, instead of considering sequences of steps, in which each step can be either a set operation or a predicate application, let us now consider sequences of only predicate application steps. We provide the following definitions to formalize this idea.

**Definition 8.** A set formula is any combination of sets (as operands) using any number of set operations and predicates (as operators). The result of a set formula is its value after evaluation.

**Definition 9.** Let O be a set of operators, and D be a set of sets. The **set formula space**  $\Psi_O(D)$  is the set of all possible formula results that can be constructed using only the operators in O as the operators and the sets in D as the operands.

For example, P(D) and  $D_1 \cap (D_2 \setminus D_3)$  are both examples of set formulas, and the set formula space  $\Psi_{\{\cap,\cup\}}(\{D_1,D_2\})$  is  $\{D_1,D_2,D_1 \cap D_2,D_1 \cup D_2\}$ . Although an infinite number of set formulas can be constructed from a set of operators and operands, the number of unique results, and thus the set formula space itself, is finite.

**Definition 10.** Set D is said to be **derived** from set of sets D if there exists some set formula which only uses the elements of D as operands and results in D. More explicitly, set D can be derived from the **origin** set D using the operators in O if  $D \in \Psi_O(D)$ .

For example, both  $\{(T, T)\}$  and  $\{(T, F)\}$  can be derived from  $\{\{(T, T), (T, F)\}, \{(T, T), (F, T)\}\}$  with the operators  $\{\cap, \setminus\}$ , but  $\{(F, F)\}$  can never be derived from this set of sets using the same operators. With these definitions, we can extend the idea of a universe to contain all valuation sets which can be derived from the first *i* predicate application-only steps using any number of set operations.

**Definition 11.** Given the sequence of predicate application steps  $[(P_1, D_1), (P_2, D_2), ..., (P_m, D_m)]$ , the **extended universe**  $U'_i$  is defined by the recurrence relation:

$$U_i' = \Psi_{\{\cap, \cup, \setminus\}}(U_{i-1}' \cup \{P_i(D_i)\})$$

with the initial extended universe:  $U'_0 = \{\{T, F\}^n\}.$ 

Although the initial extended universe once again contains only the set of all valuations, the (i + 1)th step of a predicate application-only sequence may now select any valuation set(s) from the extended universe  $U'_i$  as its input(s), rather than the regular universe  $U_i$ . For each solution to Problem 1, there must exist a corresponding solution in this setup<sup>4</sup>, so our problem can be restated with:

**Definition 12.** Given a predicate expression, a **solution sequence** is a valid sequence of predicate application steps, after which the extended universe contains the set of all valuations which satisfy the predicate expression.

Problem 2. Given a predicate expression, find the lowest cost solution sequence.

#### 5.2.2 Length of Predicate-only Sequences

It turns out that the lowest cost sequence of predicate application-only steps must apply each unique predicate exactly once. The proof for this is encapsulated in two theorems. First, Theorem 1 states each

 $<sup>^{4}</sup>$ Note the extended universe is an abstract concept used only in our analysis and not actually realized in memory by any of our algorithms.

predicate must appear as part of a predicate application step at least once in the sequence to ensure correctness. Next, Theorem 2 states that in the lowest cost solution sequence, each predicate appears as part of a predicate application step exactly once.

**Theorem 1.** Given a predicate expression and a solution sequence S, for each predicate P in the predicate expression, there must be a step S in S such that S = (P, D) for some valuation set D.

*Proof.* We first introduce some notation. For any valuation v, let  $v_i$  refer to the *i*th value of v (i.e., the result of predicate of  $P_i$ ). In addition, given valuation v, let the valuation  $v|_{i=T}$  be the same valuation as v except the *i*th value is true. Similarly,  $v|_{i=F}$  is the same valuation as v except that the *i*th value is false. Note that one of  $v|_{i=T}$  and  $v|_{i=F}$  must be equivalent to v. Multiple values may be assigned as well; the valuation  $v|_{i=T,i=F}$  is the same as v except the *i*th value is false.

Next, we introduce Lemmas 1 and 2. Lemma 1 states that for each predicate  $P_i$ , there must exist some valuation for which only the result of  $P_i$  (i.e., the *i*th element of the valuation) can determine whether the valuation satisfies the overall given predicate expression. In addition, Lemma 2 states that before applying predicate  $P_i$ , there is no way to split a set of valuations based on the *i*th value of a valuation.

**Lemma 1.** Let  $P_i$  refer to the *i*th predicate of the given predicate expression. There exists a valuation v such that  $v|_{i=T}$  satisfies the overall predicate expression, but  $v|_{i=F}$  does not.

**Lemma 2.** Given a predicate expression with predicates  $\{P_1, ..., P_n\}$ , some valuation  $v \in \{T, F\}^n$ , and some set of valuation sets **D**, if every valuation set  $D \in \mathbf{D}$  contains either both or neither  $v|_{i=T}$  and  $v|_{i=F}$ , then every valuation set which can be derived from **D** without using  $P_i$  as an operator must also contain either both or neither  $v|_{i=T}$  and  $v|_{i=F}$ . In other words:

$$\begin{aligned} \forall D \in \mathbf{D}, (v|_{i=T} \in D \land v|_{i=F} \in D) \lor (v|_{i=F} \notin D \land v|_{i=F} \notin D) \\ \implies \forall \mathbf{O} \subseteq \{\cup, \cap, \backslash, P_1, ..., P_{i-1}, P_{i+1}, ..., P_n\}, \forall D' \in \Psi_{\mathbf{O}}(\mathbf{D}), \\ (v|_{i=T} \in D' \land v|_{i=F} \in D') \lor (v|_{i=T} \notin D' \land v|_{i=F} \notin D') \end{aligned}$$

Assume to the contrary, sequence  $[S_1, ..., S_m]$  does not contain any step with  $P_i$ . Based on Lemma 1, let v be the valuation such that  $v|_{i=T}$  satisfies the overall predicate expression and  $v|_{i=F}$  does not. For  $[S_1, ..., S_m]$  to be a solution sequence, there must exist a valuation set in the final extended universe  $U'_m$  which contains  $v|_{i=T}$  but does not contain  $v|_{i=F}$ . However, based on our definition of the extended universe,  $U'_m \subseteq \Psi_{\{\cap, \cup, \setminus, P_1, ..., P_{i-1}, P_{i+1}, ..., P_n\}}(\{\{T, F\}^n\})$ . Since the origin set only contains the set of all valuations, and this obviously contains both  $v|_{i=T}$  and  $v|_{i=F}$ , the precondition of Lemma 2 is met. Thus, every valuation set in the extended universe  $U'_m$  must contain either both  $v|_{i=T}$  and  $v|_{i=F}$  or neither  $v|_{i=T}$  nor  $v|_{i=F}$ . This is a contradiction, so the sequence  $[S_1, ..., S_n]$  must contain predicate  $P_i$  as an operator.  $\Box$ 

**Theorem 2.** Given a predicate expression with n unique predicates, the lowest cost solution sequence must have exactly n steps.

*Proof.* Assume to the contrary that the lowest cost solution sequence is n + k steps long for some  $k \ge 1$  (note the sequence must be at least n thanks to Theorem 1). By the pigeonhole principle, at least one predicate must appear at least twice in the sequence. Let P be the first predicate to do so, and let indices i and j, for some i < j, be the first two steps that P appears in:  $S_i = (P, D_i)$  and  $S_j = (P, D_j)$ . We show that we can always construct a new, less costly sequence which does not include both  $S_i$  and  $S_j$  as steps, leading to a contradiction. There are two major cases:

 $D_i \cap D_j \neq \emptyset$ : We can replace  $S_j$  with  $S'_j = (P, D_j \setminus D_i)$  and still construct every valuation set derived from  $U_{j-1} \cup \{P(D_j)\}$ , since we can derive  $P(D_j) = P(D_j \setminus D_i) \cup (D_j \cap P(D_i))$ . Based on Property 2,  $S'_j$  is

cheaper than  $S_j$ , so replacing  $S_j$  with  $S'_j$  gives us a less costly sequence while maintaining equivalence, leading to a contradiction.

 $\underline{D_i \cap D_j} = \emptyset$ : In this case, instead of applying *P* separately, we can combine steps  $S_i$  and  $S_j$  and replace them with a single step  $S' = (P, D_i \cup D_j)$ . With step S', we can directly calculate both  $P(D_i) = P(D_i \cup D_j) \cap D_i$  and  $P(D_j) = P(D_i \cup D_j) \cap D_j$ . Property 3 states that performing a single S' is less costly than performing both  $S_i$  and  $S_j$ , so by replacing  $S_i$  with S' and removing  $S_j$ , we have found a less costly sequence while maintaining equivalence, leading to a contradiction<sup>5</sup>.

## 5.3 **BESTD and UPDATE**

Theorem 2 states that for a predicate expression with *n* predicates, the lowest cost solution sequence has exactly *n* steps, so a predicate evaluation system should be looking for sequences of the form  $[(P_1, D_1), ..., (P_n, D_n)]$ . This search can be be split into two:

- (1) Predicate ordering: Searching for the best ordering of predicates  $[P_1, ..., P_n]$ .
- (2) Set management: Given an ordering of predicates, searching for the operands  $[D_1, ..., D_n]$  which lead to the lowest overall cost, while still ensuring the final output set can be constructed.

As mentioned, we can reuse past work for predicate ordering. For set management, we present BESTD/UPDATE.

#### 5.3.1 Algorithms

To understand BESTD and UPDATE, we first provide some definitions. In the following definitions, the expression node.*P* denotes the predicate associated with leaf node.

**Definition 13.** Given a predicate expression and some ordering of its predicates predicates  $[P_1, ..., P_n]$ , node node of the associated predicate tree is **complete** on the ith step, if:

 $complete(node, i) = \begin{cases} node. P = P_j \text{ and } j < i & if \text{ leaf node} \\ \bigwedge_{c \in children(node)} complete(c, i) & otherwise \end{cases}$ 

**Definition 14.** Given a predicate expression and some ordering of its predicates predicates  $[P_1, ..., P_n]$ , node node of the associated predicate tree is **positively determinable** on the *i*th step, if:

$$determ^{+}(\text{node}, i) = \begin{cases} \text{node}.P = P_j \text{ and } j < i & \text{if leaf node} \\ \bigwedge_{c \in children(\text{node})} determ^{+}(c, i) & \text{if AND node} \\ \bigvee_{c \in children(\text{node})} determ^{+}(c, i) & \text{if OR node} \end{cases}$$

**Definition 15.** Given a predicate expression and some ordering of its predicates predicates  $[P_1, ..., P_n]$ , node node of the associated predicate tree is **negatively determinable** on the *i*th step, if:

	node. $P = P_j$ and $j < i$	if leaf node
$determ^{-}(node, i) = \langle$	$\bigvee_{c \in children(node)} determ^{-}(c, i)$	if AND node
	$(\bigwedge_{c \in children(node)} determ^{-}(c, i))$	if OR node

<sup>&</sup>lt;sup>5</sup>There is a caveat when  $D_i \cap D_j = \emptyset$  but  $D_j$  is derived from  $U_{i-1} \cup \{P(D_i)\}$ . Calculating  $D_i \cup D_j$  requires  $D_j$ , which in turn requires  $P(D_i)$  which is not available before the *i*th step. Fortunately, we show that this situation cannot arise in Appendix C.

If node is complete on step *i*, then every predicate leaf node descendant of node has already been applied by step *i*, and the extended universe  $U'_{i-1}$  contains the set of all valuations which satisfy the predicate subexpression represented by node. Positively (negatively) determinable nodes, on the other hand, can determine a *subset* of valuations which satisfy (do not satisfy) the predicate subexpression represented by node.

Algorithm 2 BESTD

**Input:** Predicate tree node node, algorithm state state, predicate  $P_i$ , step index *i* **Output:** Optimal operand  $D_i$  to apply  $P_i$  to 1: **if** node = NIL **then** return  $\{T, F\}^n$ 2: 3: else if isAndNode(node) then  $X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)$ 4: **for** child ∈ children(node) **do** 5: if complete(child, *i*) then 6:  $X \leftarrow X \cap \text{state[child].cmp}$ 7: **else if** determ<sup>-</sup>(child, *i*) and ¬isAnc(child, *P<sub>i</sub>*) **then** 8:  $X \leftarrow X \setminus \text{state[child].det}^{-}$ 9: return X 10: 11: **else**  $X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)$ 12:  $Y \leftarrow \{\}$ 13: **for** child ∈ children(node) **do** 14: **if** complete(child, *i*) **then** 15:  $Y \leftarrow Y \cup \text{state[child].cmp}$ 16: else if determ<sup>+</sup>(child, *i*) and  $\neg$ isAnc(child, *P<sub>i</sub>*) then 17:  $Y \leftarrow Y \cup \text{state[child].det}^+$ 18: **return**  $X \setminus Y$ 19:

BESTD and UPDATE are presented in Algorithm 2 and 3 (next page) respectively. We also provide pseudocode of how to use these algorithms with some ordering algorithm ORDERP in Algorithm 4 (next page). As shown in Algorithm 4, BESTD determines the optimal operands  $[D_1, ..., D_n]$ , while UPDATE applies predicates to these operands and uses the state variable to keep track of valuation sets for complete and positively/negatively determinable nodes. The valuation sets in state are used by BESTD to reduce the size of generated operands.

In Algorithm 4, leafNodes is a mapping from predicate  $P_i$  to the leaf node containing that predicate. Variable state is an object which has three attributes: cmp, det<sup>+</sup>, and det<sup>-</sup>. Each of these attributes is a mapping from a predicate tree node to the valuation sets that can be determined by completion, positive determinability, and negative determinability respectively. The "initState" function initializes each of these attributes to the empty set for every node in the predicate tree. The expression  $\neg$ isAnc(node,  $P_i$ ) is true if  $P_i$  is not a descendant of node. Finally, the "parent" function returns NIL if called on the root node.

BESTD determines the optimal operand for a predicate  $P_i$  by traversing the predicate tree in a bottomup manner. In the beginning, no nodes are complete nor determinable, so BESTD has no choice but to return the set of all possible valuations  $\{T, F\}^n$ . As state gets updated, the operand is trimmed according to the completeness and determinability of sibling nodes. The intersection is taken for complete AND children, and additional sets are added to the set subtraction for complete OR children. Additionally, for AND (OR) children which are negatively (positively) determinable, the sets in det<sup>-</sup> (det<sup>+</sup>) are Algorithm 3 UPDATE

**Input:** Predicate tree node node, algorithm state state, predicate  $P_i$ , set of valuations  $D_i$ , step index *i* 1: **if** node = NIL **then** 

```
2:
          return
 3: else if isLeafNode(node) then
          state[node].cmp \leftarrow P_i(D_i)
 4:
          state[node].det<sup>+</sup> \leftarrow P_i(D_i)
 5:
          state[node].det \leftarrow D_i \setminus P_i(D_i)
 6:
 7: else if isAndNode(node) then
          X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)
 8:
          if complete(node, i + 1) then
 9:
                state[node].cmp \leftarrow \bigcap_{\text{child}} \text{state[child].cmp} \cap X
10:
          if determ<sup>+</sup> (node, i + 1) then
11:
                state[node].det<sup>+</sup> \leftarrow \bigcap_{\text{child}} \text{state[child].det}^+ \cap X
12:
          if determ<sup>-</sup>(node, i + 1) then
13:
               state[node].det \leftarrow \bigcup_{child} state[child].det \cap X
14:
15: else
          X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)
16:
          if complete(node, i + 1) then
17:
                state[node].cmp \leftarrow \bigcup_{\text{child}} \text{state[child].cmp} \cap X
18:
          if determ<sup>+</sup> (node, i + 1) then
19:
                \mathsf{state[node].det}^{+} \leftarrow \bigcup_{\mathsf{child}} \mathsf{state[child].det}^{+} \cap X
20:
          if determ<sup>-</sup>(node, i + 1) then
21:
                state[node].det \leftarrow \bigcap_{\text{child}} \text{state[child].det} \cap X
22:
23: UPDATE(parent(node), state, P_i, D_i, i)
```

Algorithm 4 GENERALEVALPRED

**Input:** Predicate expression  $P^*$  **Output:** The set of all valuations which satisfy  $P^*$ 1:  $[P_1, ..., P_n] \leftarrow ORDERP(P^*)$ 2: root  $\leftarrow$  makeTree $(P^*, [P_1, ..., P_n])$ 3: leafNodes  $\leftarrow$  createMapping(root,  $[P_1, ..., P_n]$ ) 4: state  $\leftarrow$  initState(root) 5: **for**  $i \leftarrow 1, ..., n$  **do** 6:  $D_i \leftarrow \text{BestD}(\text{parent}(\text{leafNodes}[P_i]), \text{state}, P_i, i)$ 7: UPDATE(leafNodes $[P_i], \text{state}, P_i, D_i, i)$ 8: **return** state[root].cmp

removed from the returned operand. UPDATE applies predicate  $P_i$  to the generated operand  $D_i$ . Then, it traverses up the ancestors of the applied predicate leaf node and updates the cmp, det<sup>+</sup>, and det<sup>-</sup> values for complete, positively determinable, and negatively determinable nodes respectively.

#### 5.3.2 Optimality

We now prove the optimality of BESTD/UPDATE. **Theorem 3.** For a given predicate expression and some ordering of its predicates  $[P_1, ..., P_n]$ , let  $[D_1, ..., D_n]$ 

# be the sequence of operands generated by BESTD/UPDATE. The sequence of steps $[(P_1, D_1), ..., (P_n, D_n)]$ must have the lowest cost of any solution sequence.

*Proof.* Assume to the contrary that there exists a better sequence of operands  $[D'_1, ..., D'_n]$ . This must mean that there is at least one step *i* for which  $C_{P_i}(D'_i) < C_{P_i}(D_i)$ . Let *i* be the index of the first such step. To incur a cheaper cost, based on Property 2,  $D'_i$  must be missing at least one valuation *v* that is present in  $D_i$ . However, we show that if we apply  $P_i$  to the operand  $D'_i$  that is missing *v*, we are not able to generate the set of all valuations which satisfy the given predicate expression, leading to a contradiction.

Let us consider valuation set  $D_i$  from the extended universe  $U'_{i-1} \subseteq \Psi_{\{\cap, \cup, \setminus, P_1, \dots, P_{i-1}\}}(\{\{T, F\}^n\})$ . In this case, the set of all possible valuations  $\{T, F\}^n$  obviously contains all valuations (satisfying the precondition), thus the derived valuation set  $D_i \in U'_{i-1}$  must also contain either both or neither  $v|_{i=T}$  and  $v|_{i=F}$  for any valuation v according to Lemma 2. If valuation  $v \in D_i$ , then both  $v|_{i=T}$  and  $v|_{i=F}$  must be in  $D_i$ . Furthermore, since  $P_{i+1}$  is also not included as an operator in the construction of  $U'_{i-1}$  and  $v|_{i=T} \in D_i$ ,  $\{v|_{i=T,(i+1)=T}, v|_{i=F,(i+1)=T}, v|_{i=F,(i+1)=F}\}$  must be a subset of  $D_i$  by Lemma 2. This same logic can be applied recursively for all indices in i, ..., n and in converse for when  $v \notin D_i$ .

**Definition 16.** The *ith valuation group* of a valuation v is the set of all valuations for which the first i - 1 values of the valuation are equal to the first i - 1 values of v. In other words, if  $\Gamma(v, i)$  represents the *ith valuation group of v*:

$$\Gamma(v,i) = \{ u \in \{T,F\}^n \mid \bigwedge_{j=1}^{i-1} v_j = u_j \}$$

**Corollary 1.** Given a predicate expression, some ordering of its predicates  $[P_1, ..., P_n]$ , and some valuation  $v \in \{T, F\}^n$ , any set derived from  $\{\{T, F\}^n\}$  without using  $\{P_i, ..., P_n\}$  as operators must either be a superset of the *i*th valuation group of v or be disjoint from it:

$$\begin{aligned} \forall v \in \{T, F\}^n, \forall D \in \Psi_{\{\cap, \cup, \setminus, P_1, \dots, P_{i-1}\}}(\{\{T, F\}^n\}), \\ (\Gamma(v, i) \subseteq D) \lor (\Gamma(v, i) \cap D = \emptyset) \end{aligned}$$

In a similar vein, we present the following lemma which remarks that since each predicate is necessary for the final result, there exists at least one pair of valuations which must be distinguished by the *i*th value of valuation v using the *i*th predicate  $P_i$ :

**Lemma 3.** Given a predicate expression and some ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$  be the ith operand generated by BESTD/UPDATE. For all valuations  $v \in D_i$ , there exists a valuation  $u \in \Gamma(v, i)$  such that only one of  $u|_{i=T}$  and  $u|_{i=F}$  satisfies the given predicate expression.

As we initially stated, if the step  $(P_i, D'_i)$  is cheaper than operand  $(P_i, D_i)$ , then  $D_i$  must contain some valuation v that is not in  $D'_i$ . Since  $D_i$  and  $D'_i$  must both come from the extended universe  $U'_{i-1}$ , Corollary 1 applies. Valuation v's *i*th valuation group must be a subset of  $D_i$ , and at the same time, cannot have any elements in common with  $D'_i$ :  $(\Gamma(v, i) \subseteq D_i) \land (\Gamma(v, i) \cap D'_i = \emptyset)$ . By Lemma 3, there must exist at least one valuation  $u \in \Gamma(v, i)$  such that only one of  $u|_{i=T}$  and  $u|_{i=F}$  satisfies the predicate expression. However, since  $\Gamma(v, i)$  is mutually exclusive with  $D'_i$ , any derived valuation set from  $U'_{i-1} \cup \{P_i(D'_i)\}$ without  $P_i$  as an operator must contain either both or neither  $u|_{i=T}$  and  $u|_{i=F}$  according to Lemma 2. Since each predicate can be applied once at most, we have no more opportunities to apply  $P_i$ , and every valuation set in the final extended universe will contain either both or neither  $u|_{i=T}$  and  $u|_{i=F}$ . However, this is a contradiction since the set of all valuations which satisfy the given predicate expression must come from the final extended universe and contains only one of  $u|_{i=T}$  and  $u|_{i=F}$ . Thus, the sequence  $[D_1, ..., D_n]$  generated by BESTD/UPDATE is optimal.

# 5.4 Predicate Ordering

We now turn our attention to the ordering of predicates. We first discuss the reduction from BESTD/UPDATE to EVALPRED, then we explain why HANANI is not optimal for predicate expressions of nested depth 3 or greater.

#### 5.4.1 Reduction from BESTD/UPDATE to EVALPRED

As mentioned, there already exist works which focus on predicate ordering [13] [19], and we can use any of these works as ORDERP in Algorithm 4. However, in the special case that ORDERP = HANANI, BESTD/UPDATE can be reduced to EVALPRED. This is because the ordering returned by HANANI is guaranteed to traverse the predicate tree in a DFS manner. A DFS ordering ensures that a node is complete before moving on to its siblings, so no incomplete, positively/negatively determinable children ever exist. Thus, for DFS orderings, all logic regarding determinability can be removed from BESTD/UPDATE, and from this point on, the reduction is straightforward (see Appendix D for details).

#### 5.4.2 Depth-3+ Predicate Expressions

HANANI always returns a DFS ordering. For predicate expressions of depth 2 or less, this is not a problem since the optimal ordering is guaranteed to be in DFS as well due to the following lemma:

**Theorem 4.** Given a predicate expression of depth 2 or less and an ordering of its predicates  $\mathbf{P} = [P_1, ..., P_n]$ , let  $[D_1, ..., D_n]$  be the sequence of operands generated by BESTD/UPDATE. If the sequence of steps  $[(P_1, D_1), ..., (P_n, D_n)]$  has the lowest cost of any solution sequence,  $\mathbf{P}$  must be in DFS ordering.

*Proof.* Assume to the contrary that there exists a non-DFS predicate ordering  $\mathbf{P}'$  which instead leads to the lowest cost solution sequence. Since  $\mathbf{P}'$  has a non-DFS ordering, there must be a node q and step index *i*, such that:

- 1. *q* is not complete on the *i*th step
- 2. *q* has some descendant predicate  $P_j$  such that j < i
- 3. Predicate  $P_i$  is not a descendant of q

In other words, one of q's predicate descendant (i.e.,  $P_j$ ) comes before  $P_i$ , but before completing q,  $P_i$  is applied. Let i be the last step index for which the above conditions hold for any node q. We argue that we can find a predicate ordering which leads to a lower cost solution sequence by taking all of q's predicate descendants and placing them after  $P_i$  in the same relative ordering, thus causing a contradiction.

To make this argument, we first introduce Lemma 4 (shown below), which states that, for predicate expressions of depth 2 or less, all negatively determinable children of AND nodes must also be complete, and all positively determinable children of OR nodes must also be complete. In other words, an incomplete node can be neither a negatively determinable child of an AND node nor a positively determinable child of an OR node. Based on Algorithms 2 and 3, this means that predicate descendants of *q* cannot affect the operands generated by BESTD/UPDATE for any non-descendant predicate until *q*'s completion. Thus, regardless of whether *q*'s predicate descendants are all moved to be after  $P_i$  or not, the non-descendant predicates in  $[P_1, ..., P_i]$  will generate the same BESTD/UPDATE operands and have the same cost. On the other hand, since *q* is the last node for which the above conditions hold,  $P_i$  must complete a sibling of *q*; let us refer to this newly completed sibling as *q'* (if  $P_i$  does not complete node, *q'* must have a non-empty cmp value, and this cmp value must help reduce the BESTD/UPDATE-generated operands of all predicates which come after  $P_i$ . Thus, moving the predicate descendants of *q* to after  $P_i$ reduces their respective operands and lowers the costs of the steps containing these predicates. Note that moving the predicate descendants to after  $P_i$  does not change the cmp value of q upon completion, so the cost of any predicates after q's completion remains the same as well. As such, taking the predicate descendants of q and placing them after  $P_i$  (in the same relative ordering) leads to a lower cost ordering, and a contradiction is reached.

**Lemma 4.** Given any ordering of predicates for a predicate expression of depth 2 or less, if node node of the associated predicate tree is the child of an AND node and negatively determinable, then node must be complete. Similarly, if node is the child of an OR node and positively determinable, then node must be complete.

However, for predicate expressions of depth 3 or greater, Theorem 4 no longer holds, and a non-DFS predicate ordering may lead to a lower cost solution sequence. To take an example, let us once again consider the predicate expression from Query 1, and for this example let us use a simplified version of Cost Model 1, in which we ignore the constant overhead  $\kappa$  and the costs of set operations:

**Example 1.** Consider the predicate expression be  $((P_1 \land P_2) \lor P_3) \land P_4$ . Let the selectivities of  $P_1$ ,  $P_2$ ,  $P_3$ , and  $P_4$  be  $\gamma_1 = 0.469$ ,  $\gamma_2 = 0.984$ ,  $\gamma_3 = 0.313$ , and  $\gamma_4 = 0.820$  respectively. Let the constant cost factors of all predicates be 1:  $F_1 = F_2 = F_3 = F_4 = 1$ .

For this example, HANANI returns the ordering  $[P_1, P_2, P_3, P_4]$ . When combined with the operands from BESTD/UPDATE, the cost of the resulting sequence of steps can be calculated with the following (assuming the total number of tuples is |R|):

- 1.  $P_1$  is applied to all tuples, so it has a cost of |R|.
- 2.  $P_2$  is applied to all tuples for which  $P_1$  is true, so the cost is  $\gamma_1 |R| = 0.469 |R|$ .
- 3.  $P_3$  is then applied to all tuples for which either  $P_1$  or  $P_2$  is not satisfied. Using the independence assumption,  $\gamma_{1\wedge 2} = \gamma_1 \gamma_2 = 0.461$ . Thus, the cost is (1 0.461)|R| = 0.539|R|.
- 4. Finally,  $P_1$  is applied to all tuples for which  $P_B \vee (P_C \wedge P_D)$  is satisfied. Using the independence assumption:  $\gamma_{B\vee(C\wedge D)} = \gamma_B + \gamma_{C\wedge D} \gamma_B\gamma_{C\wedge D} = 0.630$ , so the cost is 0.630|R|.

Thus, this sequence has a total cost of |R| + 0.469|R| + 0.539|R| + 0.630|R| = 2.638|R|. Let us now consider the non-DFS ordering  $[P_3, P_1, P_4, P_2]$ :

- 1.  $P_3$  is applied to all tuples, so it has a cost of |R|.
- 2.  $P_1$  is applied to all tuples for which  $P_3$  is false, for a cost of  $(1 \gamma_3)|R| = 0.687|R|$ .
- 3.  $P_4$  is applied to all tuples for which either  $P_1$  or  $P_3$  is true:  $\gamma_{1\vee3} = \gamma_1 + \gamma_3 \gamma_1\gamma_3 = 0.635$ , so the cost is 0.635|R|.
- 4. Finally,  $P_2$  is applied to all tuples for which  $P_4 \wedge \neg P_3 \wedge P_1$  is true:  $\gamma_{4 \wedge \neg 3 \wedge 1} = \gamma_4(1 \gamma_3)\gamma_1 = 0.264$ , so the cost is 0.264|R|.

This leads to a total cost of 2.586|R|, confirming the suboptimality of HANANI for depth-3 predicate expressions. Even though  $P_1$ 's parent was not complete during the third step, it was negatively determinable, and this determinability helped reduce the input set of tuples for  $P_4$ 's application in step 3. Thus, for predicate expressions of depth 3 or greater, determinability prevents us from dividing the problem into well-contained subproblems, so a DFS ordering is no longer always optimal.

As such, rather than using EVALPRED for these predicate expressions, it may be beneficial to use a combination of BESTD/UPDATE and another ordering algorithm instead. For example, we could combine BESTD/UPDATE with an ordering algorithm based on Boolean Difference Calculus (BDC) [19] as mentioned in Section 2. Another example might be to use the following greedy, one-step lookahead

algorithm ONELOOKAHEADP. ONELOOKAHEADP generates the predicate ordering one step at a time, and for each step, it selects the predicate which it estimates will lead to the lowest cost evaluation of the remaining predicates (the estimate for each predicate P is the cost of applying P plus the cost of evaluating the remaining predicates other than P using EVALPRED). Although neither of these algorithms can guarantee optimality, as HANANI did for predicate expressions of 2 or less, they serve as alternatives which can sometimes generate better plans for predicate expressions of depth 3 or greater. In fact, our experiments showed that although HANANI outperformed ONELOOKAHEADP for most cases, for 6% of the queries, ONELOOKAHEADP led to better plans than HANANI.

# 6 Evaluation

**Algorithms.** We evaluated a total of five algorithms in our experiments: EVALPRED, NOOROPT, TDACB [18], GREEDYD3, and BDC.

- 1. EVALPRED (BESTD/UPDATE + HANANI). Our recommended algorithm, with  $O(n \log^2 n)$  planning time, and optimal for all predicate expressions of 2 or less.
- 2. NOOROPT. The baseline algorithm with no optimizations for disjunctions; essentially the same as EVALPRED, except the outputs of disjunctive clauses do not help reduce the inputs of other disjunctive clauses. Note this is the actual strategy employed by many real-world systems for disjunctions.
- 3. TDACB. Our main competitor and the current state-of-the-art algorithm for generating optimal predicate evaluation plans. It can generate optimal plans for predicate expressions of any depth, but its planning time complexity is exponential.
- 4. GREEDYD3 (BESTD/UPDATE + ONELOOKAHEADP). The combination of BESTD/UPDATE and the greedy, one-step lookahead algorithm ONELOOKAHEADP described at the end of Section 5.4.2. Used as a comparison point for depth-3+ predicate expressions.
- 5. BDC (BESTD/UPDATE + BDC). Combination of BESTD/UPDATE and BDC [19], described in Section 2. Used as a comparison point for depth-3+ predicate expressions.

**Workload and Metric.** We evaluated our algorithms on both a synthetic workload using the Forest dataset [1] and on Q19 (which has disjunctions) from TPC-H [2] and the CH-benchmark [9] with the following metrics:

- (1) Runtime: The total time it takes to generate and execute a predicate evaluation plan.
- (2) Number of Evaluations: The sum total number of times a query's predicates are evaluated (each evaluation of a predicate on a tuple counts as 1). This provides an implementation-agnostic measure of our algorithms.

Note that for the synthetic workload, with the exception of TDACB, the plan times for all other algorithms accounted for only 0.01% of the total runtime, so we do not report the plan times separately there. For TPC-H and the CH-benchmark, we present the plan times and execution times separately.

**System.** All experiments were performed on our column-oriented execution engine CHAM<sup>6</sup>, which implements all five aforementioned algorithms. CHAM is coded in ~6500 lines of Rust, stores data on disk, and internally represents sets of tuples with Roaring bitmaps [5]. The hardware for our experiments was a server with 64 Intel(R) Xeon(R) CPU E7-4830 @ 2.13GHz processors, 256GB of memory, and a RAID5 configuration of 7200rpm HDDs.

<sup>&</sup>lt;sup>6</sup>A chameleon's eyes can move in complete "disjunction" with one another [24]!

**Key Takeaways:** In general, EVALPRED performed the best out of any algorithm. For the synthetic workload, EVALPRED had average speedups of up to 2.6× over NOOROPT, 1.4× over GREEDYD3, and 1.8× over BDC for the top 10% of queries. As for TDACB, while executions times were consistently low, due to its exponential planning time, its total runtimes ended up being several orders of magnitude greater than even NOOROPT for the more complex expressions. For depth-2 predicate expressions, EVALPRED had the same number of evaluations as TDACB, verifying that it is optimal for the depth-2 case. For depth-3 predicate expressions, EVALPRED still came quite close to the optimal number of evaluations, with 92% of queries within 5% of the minimum possible. For TPC-H and the CH-benchmark, EVALPRED once again had the fastest runtimes. In comparison, TDACB's substantial planning times for TPC-H made its total runtime 100× slower than EVALPRED's for this benchmark. For the CH-benchmark, the number of unique predicates in the predicate expression was fewer, so TDACB had similar total runtimes to EVALPRED.

The remainder of this section presents the results of the synthetic workload first, with Section 6.1 describing the details of the workload, Section 6.2 presenting the results for depth-2 predicate expressions, and Section 6.3 presenting the results for depth-3+ predicate expressions. The results for TPC-H and the CH-benchmark are presented later in Section 6.4.

# 6.1 Synthetic Workload

**Dataset.** We used the Forest dataset [1] that was used in the majority of the experiments evaluating TDACB [18]. The dataset has 10 quantitative attributes and 2 qualitative attributes. However, because we wanted to evaluate our algorithms on more than just 12 independent predicates, we duplicated the original dataset 40 times, shuffled the tuples of each duplicate dataset, and added the attributes of the shuffled datasets as additional attributes of the original dataset, giving us a total of 480 attributes. Furthermore, the original dataset only contained 581K tuples, so we repeated the tuples 100 times for a total of 58M tuples. Altogether, the size of the generated dataset was 208GB.

Queries. To mirror the evaluation of TDACB [18], we used selection queries with randomly generated predicate expressions ranging up to 16 predicates. However, Kastrati and Moerkotte's evaluation of TDACB included logically related predicates, and TDACB leveraged Boolean implication (e.g.,  $P_1$  implies  $\neg P_2$ ) to significantly increase its runtime performance. Since we wanted to directly measure the impact of the number of predicates on our algorithms, we chose to make every predicate independent of each other. Furthermore, TDACB was only evaluated on CNF and DNF queries, meaning their predicate expressions had a maximum depth of 2. In contrast, our predicate expressions were generated according to the following criteria. The root of the predicate tree was randomly chosen to either be an AND or an OR. Each predicate expression had a predetermined max depth of 2, 3, or 4. Each non-leaf node had a randomly chosen number of children between 2 and 5, and each child had some chance to be a leaf node, ensuring that we did not only test on balanced trees. For each of the quantitative attributes, we generated a simple x < c comparison predicate where c could one of 9 different constants, resulting in selectivities of [0.1, 0.2, ..., 0.9]. For the two qualitative attributes, we had equality predicates of the form x = c where c is one of the possible values of that attribute (one had 4 possible values and the other had 7). For experiments with variable-cost predicates, sleep times of 1-10ns were added per evaluation of a tuple to emulate variable cost.

**Experiments.** We conducted a total of 6 sets of experiments. Each set of experiments had either a uniform or varying cost for all its predicates and a fixed depth for its predicate expressions. 500 queries with randomly generated predicate expressions were used for each experiment.



Figure 2: Runtimes and number of evaluations for depth-2 predicate expressions with uniform-cost predicates.



Figure 3: Runtimes and CDFs of speedups for depth-3 predicate expressions with varying-cost predicates.

# 6.2 Depth-2 Predicate Expressions

Figure 2 shows the results of our experiments for depth-2 predicate expressions with uniform predicate cost. We plot the average runtimes of EVALPRED, NOOROPT, and TDACB when grouped by the number of predicates in Figure 2(a). The same data is shown zoomed-in in Figure 2(b). Finally, we plot the average total number of evaluations incurred by each algorithm when grouped by the number of predicates in Figure 2(c). As can be seen, TDACB quickly becomes unviable for higher numbers of predicates due to its exponential planning time, incurring total runtimes orders of magnitude greater than even NOOROPT. Even for smaller numbers of predicates, EVALPRED outperformed TDACB with average speedups of 1.12× and 1.28× for 8 and 10 predicates respectively. Since Figure 2(c) shows that number of evaluations performed by EVALPRED and TDACB are the same, this disparity must come from the difference in planning time. With respect to NOOROPT, EVALPRED enjoyed a consistent 1.41× average speedup in runtime and a total average of 1.88× speedup in number of evaluations. For the top 10% of queries, EVALPRED had an average speedup of 2.12× in runtime and 4.04× in number of evaluations over NOOROPT.

The same patterns arose for depth-2 predicate expressions with varying-cost predicates. TDACB exhibited the same exponential behavior, but EVALPRED outperformed TDACB for even smaller numbers of predicates with the same average speedups of  $1.12 \times$  and  $1.28 \times$  for 8 and 10 predicates respectively. EVALPRED also consistently outperformed NOOROPT with a total average speedup of  $1.43 \times$  in runtime and a total average speedup of  $1.86 \times$  in number of evaluations.

# 6.3 Depth-3+ Predicate Expressions

Figure 3 (next page) shows the results of our experiments for depth-3 predicate expressions with varyingcost predicates. We plot the average runtimes of EVALPRED, NOOROPT, GREEDYD3, BDC, and TDACB when grouped by the number of predicates in Figure 3(a). As Figure 3(a) shows, despite not being optimal, EVALPRED still achieved the best runtime performance out of any algorithm, with total average speedups of 1.43× over NOOROPT, 1.13× over GREEDYD3, and 1.29× over BDC. For the top 10% of queries, EVALPRED had average speedups of 2.60× over NoOROPT, 1.36× over GREEDYD3, and 1.84× over BDC. TDACB exhibited the same exponential behavior as before and had runtimes orders of magnitude greater than NoOROPT for 14-16 predicates. Even for 8 and 10 predicates, EVALPRED outperformed TDACB with average speedups of 1.10× and 1.21× respectively.

Though TDACB's runtimes may be high, the plans that it generates are still optimal. As such, the number of evaluations incurred by TDACB can be seen as the minimum possible for any given query and serve as a reference for how close EVALPRED comes to optimal for depth-3+ predicate expressions. Figure 3(b) shows the CDF of speedups in number of evaluations of various algorithms over TDACB. It is apparent that EVALPRED comes quite close to achieving optimal performance even for depth-3 predicate expressions, with 92% of queries invoking within 5% of the minimum number of evaluations possible. In comparison, the other algorithms fare much worse. To serve as another comparison point, Figure 3(c) shows the CDF of speedups in runtime of EVALPRED over GREEDYD3. GREEDYD3 is able to generate orderings which are not DFS traversals, and this makes a difference for 6% of queries, in which GREEDYD3 had faster runtimes than EVALPRED. However, for the vast majority of queries, EVALPRED still performed at least as well as, if not better than, GREEDYD3. BDC also had similar results with only 4% of queries performing better than EVALPRED.

Depth-3, uniform-cost predicate expressions and depth-4 predicate expressions exhibited very similar patterns to the depth-3, varying-cost case. With less than a 2% difference in total average speedups, the plotted figures were almost identical, so we do not show them separately here.

## 6.4 TPC-H and CH-benchmark

In addition to our synthetic workload, we looked at the queries from TPC-H and the CH-benchmark and found that Q19 from each benchmark has disjunctions. TPC-H's joined table has 6M tuples and its predicate expression is in DNF with 18 total predicates, but only 14 unique predicates. CH-benchmark's joined table has 15M tuples and its predicate expression is also in DNF with 15 total predicates, but only 9 unique predicates. The results for TPC-H and CH-benchmark are shown in Tables 4 and 5 respectively. The tables show the average runtimes of executing each query 5 times for each algorithm. For TPC-H, although EVALPRED and TDACB had similar execution times, TDACB's planning time took an enormous 416 seconds, so EVALPRED had a 100× speedup over TDACB in total runtime. In comparison, NoOROPT exhibited similar runtimes to EVALPRED for this query. For the CH-benchmark, there were only 9 unique predicates. Thus,TDACB's planning time was significantly reduced, and it had comparable total runtimes to EVALPRED. NoOROPT, on the other hand, was slower for this query, and EVALPRED had a 1.3× speedup

Algorithm	Plan Time (s)	Exec Time (s)	# of Evaluations
EvalPred	0	4.20	10.8M
NoOrOpt	0	4.28	10.9M
Tdacb	416	4.21	10.8M
GreedyD3	0	4.25	10.9M
BDC	0.09	5.64	61.1M

Table 4: TPC-H results for Query 19.

Algorithm	Plan Time (ms)	Exec Time (s)	# of Evaluations
EvalPred	0	12.6	77.3M
NoOrOpt	0	16.1	102M
Tdacb	12	12.6	77.3M
GreedyD3	0	13.5	89.2M
BDC	0	16.6	118M

Table 5: CH-benchmark results for Query 19.

over it in runtime.

# 7 Conclusion

In this paper, we formally analyze the problem of predicate evaluation for column-oriented engines and present EVALPRED as our recommended algorithm. Our analysis and evaluation shows that EVALPRED is optimal for all predicate expressions of depth 2 or less and still quite close to optimal for depth-3+ predicate expressions. Thus, we hope that many systems can take advantage of our work and implement these optimizations to improve the performance of predicate evaluation.

# References

- [1] Forest dataset. http://kdd.ics.uci.edu/databases/covertype/covertype.data.html, 1999.
- [2] TPC-H Homepage, 2022. URL https://www.tpc.org/tpch/.
- [3] Michael Armbrust, Reynold S. Xin, Cheng Lian, Yin Huai, Davies Liu, Joseph K. Bradley, Xiangrui Meng, Tomer Kaftan, Michael J. Franklin, and Ali Ghodsi. Spark sql: Relational data processing in spark. In *Proceedings of the 2015 ACM SIGMOD International Conference on Management of Data*, pages 1383–1394. ACM, 2015.
- [4] Hans Kleine Büning and Theodor Lettmann. *Propositional logic: deduction and algorithms*, volume 48. Cambridge University Press, 1999.
- [5] Samy Chambi, Daniel Lemire, Owen Kaser, and Robert Godin. Better bitmap performance with roaring bitmaps. *Software: practice and experience*, 46(5):709–719, 2016.
- [6] Jae-young Chang and Sang-goo Lee. An optimization of disjunctive queries: union-pushdown. In COMPSAC, pages 356–361. IEEE Computer Society, 1997.
- [7] Surajit Chaudhuri, Prasanna Ganesan, and Sunita Sarawagi. Factorizing complex predicates in queries to exploit indexes. In *SIGMOD 2003*. ACM, 2003.
- [8] Jens Claussen, Alfons Kemper, Guido Moerkotte, Klaus Peithner, and Michael Steinbrunn. Optimization and Evaluation of Disjunctive Queries. *IEEE Trans. Knowl. Data Eng.*, 12(2):238–260, 2000.
- [9] Richard Cole, Florian Funke, Leo Giakoumakis, Wey Guy, Alfons Kemper, Stefan Krompass, Harumi Kuno, Raghunath Nambiar, Thomas Neumann, Meikel Poess, et al. The mixed workload ch-benchmark. In *Proceedings of the Fourth International Workshop on Testing Database Systems*, pages 1–6, 2011.

- [10] Akos. Csaszar. General topology. Disquisitiones mathematicae Hungaricae ; v. 9. A. Hilger, Bristol [Eng, 1978. ISBN 0852742754.
- [11] Marcus Fontoura, Suhas Sadanandan, Jayavel Shanmugasundaram, Sergei Vassilvitskii, Erik Vee, Srihari Venkatesan, and Jason Y. Zien. Efficiently evaluating complex boolean expressions. In SIGMOD Conference, pages 3–14. ACM, 2010.
- [12] Martin Grund, Jens Krüger, Hasso Plattner, Alexander Zeier, Philippe Cudré-Mauroux, and Samuel Madden. HYRISE - A main memory hybrid storage engine. *Proc. VLDB Endow.*, 2010.
- [13] Michael Z. Hanani. An Optimal Evaluation of Boolean Expressions in an Online Query System. *Commun. ACM*, 20(5):344–347, May 1977. ISSN 0001-0782. doi: 10.1145/359581.359600. URL http: //doi.acm.org/10.1145/359581.359600.
- [14] S. Idreos, F. Groffen, N. Nes, S. Manegold, S. Mullender, and M. Kersten. Monetdb: Two decades of research in column-oriented database. *IEEE Data Engineering Bulletin*, 35(1):40–45, 2012. Publisher: Citeseer.
- [15] JarkeMatthias and KochJurgen. Query Optimization in Database Systems. *ACM Computing Surveys* (*CSUR*), June 1984. URL https://dl.acm.org/doi/abs/10.1145/356924.356928.
- [16] Ryan Johnson, Vijayshankar Raman, Richard Sidle, and Garret Swart. Row-wise parallel predicate evaluation. *Proceedings of the VLDB Endowment*, 1(1):622–634, 2008. Publisher: VLDB Endowment.
- [17] Fisnik Kastrati and Guido Moerkotte. Optimization of disjunctive predicates for main memory column stores. In SIGMOD Conference, pages 731–744. ACM, 2017.
- [18] Fisnik Kastrati and Guido Moerkotte. Generating optimal plans for boolean expressions. In ICDE, pages 1013–1024. IEEE Computer Society, 2018.
- [19] Alfons Kemper, Guido Moerkotte, and Michael Steinbrunn. Optimizing boolean expressions in object-bases. In VLDB, pages 79–90. Morgan Kaufmann, 1992.
- [20] Alfons Kemper, Guido Moerkotte, Klaus Peithner, and Michael Steinbrunn. Optimizing disjunctive queries with expensive predicates. In SIGMOD Conference. ACM, 1994.
- [21] Andrew Lamb, Matt Fuller, Ramakrishna Varadarajan, Nga Tran, Ben Vandier, Lyric Doshi, and Chuck Bear. The vertica analytic database: C-store 7 years later. arXiv preprint arXiv:1208.4173, 2012.
- [22] J Donald Monk. Introduction to set theory. Journal of Symbolic Logic, 38(1), 1973.
- [23] Murali Muralikrishna. Optimization of multiple-disjunct queries in a relational database system. Technical report, University of Wisconsin-Madison Department of Computer Sciences, 1988.
- [24] Matthias Ott. Chameleons have independent eye movements but synchronise both eyes during saccadic prey tracking. *Experimental Brain Research*, 139:173–179, 2001.
- [25] Stuart J. Russell and Peter Norvig. *Artificial Intelligence: A Modern Approach*. Malaysia; Pearson Education Limited,, 2016.
- [26] Michael Steinbrunn, Klaus Peithner, Guido Moerkotte, and Alfons Kemper. Bypassing joins in disjunctive queries. In VLDB, volume 95, pages 11–15, 1995.
- [27] Tamon Stephen and Timothy Yusun. Counting inequivalent monotone boolean functions. *Discrete Applied Mathematics*, 167:15–24, 2014.

- [28] Robert Roth Stoll. Set Theory and Logic. Courier Corporation, October 1979. ISBN 978-0-486-63829-4.
- [29] Michael Stonebraker and Lawrence A. Rowe. The Design of Postgres, volume 15. ACM, 1986.
- [30] David D. Straube and M. Tamer Özsu. Queries and query processing in object-oriented database systems. *ACM Transactions on Information Systems (TOIS)*, 1990.

# A HANANI

For the reader's convenience, we provide a modern, updated version of HANANI in Algorithm 5 (next page). As mentioned, this returns the optimal ordering of predicates for any Boolean predicate expression of depth 2 or less. The majority of the work is done by ORDERNODE, which returns the best ordering of all descendent predicates for a given node. If node is a leaf node, node. *P* is used to refer to the predicate that node points to.  $\gamma_P$  is the selectivity of *P* (i.e., the fraction of tuples which satisfy *P*), and  $F_P$  is the constant cost factor discussed in Cost Model 1. Since a leaf node only has one descendent predicate, it is the only predicate in the returned sequence. If node is an AND/OR node, ORDERNODE is called on each of its children, and the returned suborderings are sorted in increasing/decreasing selectivity respectively. Once suborderings has been sorted, ORDERNODEHELPER calculates the total selectivity and cost for node (using the independence assumption), flattens suborderings, and returns the combination of these values to the parent.

Algorithm 5 HANANI

**Input:** Predicate expression *P*\* **Output:** Ordered sequence of predicates [*P*<sub>1</sub>, ..., *P<sub>n</sub>*] 1: root  $\leftarrow$  makeUnorderedTree( $P^*$ ) 2:  $(\gamma, \text{cost}, \mathbf{P}) \leftarrow \text{OrderNode}(\text{root})$ 3: return P 4: **function** OrderNode(node) if isLeafNode(node) then 5:  $P \leftarrow \mathsf{node.}P$ 6: return  $(\gamma_P, F_P, [P])$ 7: 8: 9: suborderings  $\leftarrow$  [] **for**  $c \in$  children(node) **do** 10:  $(\gamma, \text{cost}, \mathbf{P}) \leftarrow \text{OrderNode}(c)$ 11: suborderings  $\leftarrow$  suborderings + [( $\gamma$ , cost, P)] 12: if isAndNode(node) then 13: suborderings ← increasingSort(suborderings, GetAndWeiGHT) 14: else 15: suborderings ← increasingSort(suborderings, GetOrWEIGHT) 16: 17: return OrderNodeHelper(suborderings, node) 18: **function** OrderNodeHelper(suborderings, node) totalCost  $\leftarrow 0$ 19:  $\gamma_{\text{total}} \leftarrow 1$ 20:  $P_{all} \leftarrow []$ 21: for  $i \leftarrow 1, ..., |$ suborderings| do 22: 23:  $(\gamma, \text{cost}, \mathbf{P}) \leftarrow \text{suborderings}[i]$ if isAndNode(node) then 24: 25: totalCost  $\leftarrow$  totalCost +  $\gamma_{total} \cdot cost$ 26:  $\gamma_{\text{total}} \leftarrow \gamma_{\text{total}} \cdot \gamma$ else 27: totalCost  $\leftarrow$  totalCost +  $(1 - \gamma_{total}) \cdot cost$ 28:  $\gamma_{\text{total}} \leftarrow \gamma + \gamma_{\text{total}} \cdot (1-\gamma)$ 29:  $P_{\text{all}} \gets P_{\text{all}} + P$ 30: **return** ( $\gamma_{total}$ , totalCost,  $P_{all}$ ) 31: 32: **function** GetAndWeight(γ, cost, **P**) **return**  $\cos t/(1 - \gamma)$ 33: 34: **function** GetOrWeight(γ, cost, **P**) return  $cost/\gamma$ 35:

Algorithm 1 EVALPRED

```
Input: Predicate expression P*, set of all tuples R
Output: The set of all tuples which satisfy P*
 1: [P_1, ..., P_n] \leftarrow \text{HANANI}(P^*)
 2: root \leftarrow makeTree(P^*, [P_1, ..., P_n])
 3: return EvalNode(root, R)
 4: function EVALNODE(node, D)
         if isLeafNode(node) then
 5:
             return node.applyPred(D)
 6:
         else if isAndNode(node) then
 7:
             for child in children(node) do
 8:
                  if D = \emptyset then
 9:
                      return D
10:
                  D \leftarrow \text{EvalNode}(\text{child}, D)
11:
12:
             return D
         else
13:
             done \leftarrow \emptyset
14:
             for child in children(node) do
15:
                  \mathsf{todo} \leftarrow D \setminus \mathsf{done}
16:
                  if todo = \emptyset then
17:
                      return done
18:
19:
                  done \leftarrow done \cup EvalNoDE(child, todo)
20:
             return done
```

# **B** Correctness Proofs

# **B.1** EVALPRED

In this section, we prove the correctness of EVALPRED. For the reader's convenience, we restate Algorithm 1 above. We first introduce Theorem 5, shown below. Theorem 5 states that, for any predicate tree node node and set of tuples D, EVALNODE(node, D) returns the subset of tuples in D which satisfy the predicate subexpression represented by node. Thus, if R represents the set of all tuples (in the table), EVALNODE(root, R) in Line 3 must return the set of all tuples which satisfy the given predicate expression.

**Theorem 5.** Given a predicate expression and an ordering of its predicates, let node be any node in the associated predicate tree, and let  $ref_{node}$  be the set of all tuples which satisfy the predicate subexpression represented by node. For any set of tuples D, EVALNODE(node, D) returns the subset of D which satisfies the predicate subexpression represented by node, or:

 $EvalNode(node, D) = ref_{node} \cap D$ 

*Proof.* Our proof is by strong induction on the height of the tree referred to by node. In the base case (height 1), node refers to a leaf node. Thus, node must be a predicate application node. By definition, node.applyPred(node, D) returns the subset of tuples in D which satisfy node's predicate, taking care of the base case:

 $\mathsf{node.applyPred}(\mathsf{node}, D) = \mathsf{ref}_{\mathsf{node}} \cap D$ 

As the inductive hypothesis, we assume Theorem 5 applies to all predicate trees with height k or less. If node has a height of k + 1, node must be either an AND or an OR node. For the purpose of this proof, let us first ignore the early returns featured in Lines 9-10 and Lines 17-18. We examine the AND and OR cases separately.

If node is an AND node, the inductive hypothesis must hold for each child of node since they must all be trees of height k or less. Let  $D^{(i)}$  be the updated value of D in Line 11 after the EVALNODE call to the *i*th child of node (denoted child<sub>i</sub>). We can express  $D^{(i)}$  with the recurrence relationship:

$$D^{(i)} = \operatorname{ref}_{\operatorname{child}_i} \cap D^{(i-1)}$$

If we assume  $D^{(0)}$  is the original value of *D* passed in as the argument to EVALNODE and node has *t* children, the return value of Line 12 will be:

$$D^{(0)} \cap \mathsf{ref}_{\mathsf{child}_1} \cap \mathsf{ref}_{\mathsf{child}_2} \cap \ldots \cap \mathsf{ref}_{\mathsf{child}_t}$$

The set of tuples which satisfy an AND node is the intersection of its children's satisfying sets, thus the above can be written as:

$$D^{(0)} \cap \mathsf{ref}_{\mathsf{node}}$$

If node is an OR node, the inductive hypothesis must again hold for each child of node. Let done<sup>(i)</sup> be the updated value of done in Line 19 after the EVALNODE call to the *i*th child of node (denoted child<sub>i</sub>). We can express done<sup>(i)</sup> with the recurrence relationship:

$$done^{(i)} = done^{(i-1)} \cup \left( ref_{child_i} \cap \left( D \setminus done^{(i-1)} \right) \right)$$

For any sets *A*, *B*, and *C*:  $A \cup (B \cap (C \setminus A)) = A \cup (B \cap C)$  (Appendix F). Thus, the recurrence relationship can be rewritten as:

$$done^{(i)} = done^{(i-1)} \cup (ref_{child_i} \cap D)$$

Assuming once again node has *t* children, Line 20's return value is:

$$(\mathsf{ref}_{\mathsf{child}_1} \cap D) \cup (\mathsf{ref}_{\mathsf{child}_2} \cap D) \cup \ldots \cup (\mathsf{ref}_{\mathsf{child}_t} \cap D)$$

Using the distributive property, we can clean this up as:

$$D \cap (\mathsf{ref}_{\mathsf{child}_1} \cup \mathsf{ref}_{\mathsf{child}_2} \cup \ldots \cup \mathsf{ref}_{\mathsf{child}_\ell})$$

The set of tuples which satisfy an OR node is the union of its children's satisfying sets, thus the above can be simplified to:

$$D \cap \mathsf{ref}_{\mathsf{node}}$$

#### **B.2 BESTD and UPDATE**

Next, we prove the correctness of BESTD and UPDATE. For the reader's convenience, we restate Algorithms 2 (BESTD) and 3 (UPDATE). In addition, before diving into the proofs, we first provide some definitions, notation, and basic properties that will be used throughout these proofs.

**Definition 17.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let node be any node in the associated predicate tree. The **rank** of node on the ith step (denoted r(node, i)) is the largest index j such that j < i and  $P_j$  is a predicate leaf node descendant of node. If no such j exists, r(node, i) = 0. The **final rank** of node (denoted  $r^*(node)$ ) is the largest index j such that  $P_j$  is a predicate leaf node descendant of node.

Algorithm 2 BESTD

Inp	<b>put:</b> Predicate tree node node, algorithm state state, predicate $P_i$ , step index <i>i</i>
Ou	<b>tput:</b> Optimal operand $D_i$ to apply $P_i$ to
1:	if node = NIL then
2:	return $\{T,F\}^n$
3:	else if isAndNode(node) then
4:	$X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)$
5:	<b>for</b> child $\in$ children(node) <b>do</b>
6:	<pre>if complete(child, i) then</pre>
7:	$X \leftarrow X \cap \texttt{state[child].cmp}$
8:	else if determ <sup>-</sup> (child, i) and $\neg$ isAnc(child, $P_i$ ) then
9:	$X \leftarrow X \setminus \texttt{state[child].det}^-$
10:	return X
11:	else
12:	$X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)$
13:	$Y \leftarrow \{\}$
14:	<b>for</b> child $\in$ children(node) <b>do</b>
15:	<pre>if complete(child, i) then</pre>
16:	$Y \leftarrow Y \cup \texttt{state[child].cmp}$
17:	else if determ <sup>+</sup> (child, i) and $\neg$ isAnc(child, $P_i$ ) then
18:	$Y \leftarrow Y \cup \texttt{state[child].det}^+$
19:	return $X \setminus Y$

Put another way, the rank of node on the *i*th step is the latest step index on which a predicate descendant of node is applied. More explicitly, if node has predicate  $P_j$  as a descendant and j < i, and node has no other predicate descendants  $P_k$  such that j < k < i, then r(node, i) = j. If node is a leaf node, it considers itself as a descendant, so if node refers to predicate  $P_j$ , r(node, i) = j if j < i and r(node, i) = 0 otherwise. The final rank of node is the largest index among its predicate descendants and can be seen as the last step before node becomes complete. Note that  $r^*(\text{node}) = r(\text{node}, n + 1)$ , since all predicates must be complete after *n* steps.

To reason about the state variable whose value continuously changes throughout multiple steps in BESTD/UPDATE, we denote state<sub>i</sub> to be the value of state at the beginning of the *i*th step (before any updates). We also need a way to refer to node's complete, positively determinable, and negatively determinable children on the *i*th step. For this, we introduce the functions: children° (node, *i*), children<sup>+</sup> (node, *i*), and children<sup>-</sup> (node, *i*) which return node's complete, (incomplete) positively determinable, and (incomplete) negatively determinable children on the *i*th step respectively. We also use the convention of  $c^{\circ}$ ,  $c^{+}$ , and  $c^{-}$  to refer to a complete, positively determinable, and negatively determinable child respectively. Throughout the section we may refer to leaf nodes which contains predicates as the predicates themselves. For example, if node is a leaf node which contains predicate  $P_i$ , the expression " $P_i$ 's parent" may be used to refer to node's parent. As another example, if we talk about all predicate descendants of a node, we are referring to the predicates of the leaf node descendants of that node. Finally, in calls to BESTD, we omit the state argument since it refers to the same object every time.

Next, we present some properties which we use throughout the proofs.

Algorithm 3 UPDATE

Input: Predicate tree node node, algorithm state state, predicate  $P_i$ , set of valuations  $D_i$ , step index i1: if node = NIL then 2: return 3: else if isLeafNode(node) then 4: state[node].cmp  $\leftarrow P_i(D_i)$ 5: state[node].det<sup>+</sup>  $\leftarrow P_i(D_i)$ 6: state[node].det<sup>-</sup>  $\leftarrow D_i \setminus P_i(D_i)$ 7: else if isAndNode(node) then

```
X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)
 8:
          if complete(node, i + 1) then
 9:
                state[node].cmp \leftarrow \bigcap_{\text{child}} \text{state[child].cmp} \cap X
10:
11:
          if determ<sup>+</sup> (node, i + 1) then
               state[node].det^{+} \leftarrow \bigcap_{child} state[child].det^{+} \cap X
12:
          if determ<sup>-</sup>(node, i + 1) then
13:
               state[node].det \leftarrow \bigcup_{child} state[child].det \cap X
14:
15: else
          X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)
16:
          if complete(node, i + 1) then
17:
                state[node].cmp \leftarrow \bigcup_{\text{child}} \text{state[child].cmp} \cap X
18:
          if determ<sup>+</sup>(node, i + 1) then
19:
                state[node].det<sup>+</sup> \leftarrow \bigcup_{\text{child}} \text{state[child].det}^+ \cap X
20:
          if determ<sup>-</sup>(node, i + 1) then
21:
               state[node].det \leftarrow \bigcap_{\text{child}} \text{state[child].det} \cap X
22:
23: UPDATE(parent(node), state, P_i, D_i, i)
```

**Property 4.** For any predicate *P* and valuation sets *D* and *E*:

 $P(D \cap E) = P(D) \cap E$  $P(D \cup E) = P(D) \cup P(E)$  $P(D \setminus E) = P(D) \setminus E$ 

If we imagine that each predicate *P* has a corresponding set  $ref_P$  which contains all possible valuations that satisfy *P*, then applying P(D) is akin to taking the intersection of  $ref_P$  and  $D: P(D) = ref_P \cap D$ . Thus, any properties which pertain to normal intersection of sets also pertain to applied predicates. **Property 5.** If node is not complete on the *i*th step but complete on the (i + 1)th step, then for all j > i:

state<sub>i+1</sub>[node].cmp = state<sub>i</sub>[node].cmp

This property simply states that state[node].cmp does not change once node is complete. This is easy to see since the cmp attribute of state[node] is only ever updated once: right after node becomes complete. Once a node is complete, all its predicate descendants have already been applied, and it can never again become an ancestor of an incomplete predicate node. Thus, it will never be updated again as an ancestor in UPDATE.

**Property 6.** For any node and step indices i and j:

 $state_i[node].cmp \cap state_i[node].det^{-} = \emptyset$ 

and

 $state_i [node].det^+ \cap state_i [node].det^- = \emptyset$ 

This should make intuitive sense since the cmp/det<sup>+</sup> attributes for node holds valuations which satisfy the subexpression represented by node, while det<sup>-</sup> hold valuations which do not satisfy the subexpression represented by node.

Property 7. If node is complete on the ith step:

state<sub>i</sub>[node].cmp = state<sub>i</sub>[node].det<sup>+</sup>

This is easy to verify with induction. For leaf nodes, the cmp and det<sup>+</sup> attributes are set to the same value, and the lines in UPDATE updating cmp and det<sup>+</sup> for non-leaf nodes become equivalent once they are complete.

We prove the correctness of BESTD/UPDATE and GENERALEVALPRED with Theorem 6. Theorem 6 states that if node is complete on the *i*th step, then state<sub>*i*</sub>[node].cmp must be the set of valuations in BESTD(parent(node), state<sub>*r*\*(node)</sub>,  $r^*(node)$ ) which satisfy the predicate subexpression represented by node. root has *n* predicate descendants, so it must be complete after *n* steps. Given that parent(root) is NIL, according to Algorithm 2, BESTD(parent(root),  $\star, \star$ ) returns  $\{T, F\}^n$ . Since root represents the entire predicate expression, state<sub>*n*+1</sub>[root].cmp must return the subset of  $\{T, F\}^n$  which satisfies the predicate expression.

**Theorem 6.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , and let node be a node in the associated predicate tree. Furthermore, let  $ref_{node}$  be the set of all valuations which satisfy the predicate subexpression represented by node. On the *i*th step, if node is complete:

 $state_i [node].cmp = ref_{node} \cap BestD(parent(node), r^*(node))$ 

*Proof.* Our proof for Theorem 6 is by strong induction on the height of the tree referred to by node. As the base case, let node be a leaf node which refers to predicate  $P_j$ . Since node is complete on the *i*th step, that must mean that j < i, and node has been complete since the (j + 1)th step. Thus:

$$state_i[node].cmp = state_{i+1}[node].cmp$$
 (i)

 $= P_j(\text{BestD}(\text{parent}(\text{node}), j))$ (ii)

 $= P_i(\text{BestD}(\text{parent}(\text{node}), r^*(\text{node})))$ (iii)

 $= ref_{node} \cap BestD(parent(node), r^*(node))$ (iv)

Step (i) is a direct application of Property 5. Step (ii) comes directly from Algorithm 3. Step (iii) is simply the definition of  $r^*(\text{node})$ . Finally, since node is a leaf node pointing to predicate  $P_j$ ,  $\text{ref}_{\text{node}} = P_j(\{T, F\}^n)$ , and by applying Property 4, we get the last step, thereby proving the base case.

As the inductive hypothesis, assume that the theorem applies for all nodes in the predicate tree with height k or less. If node has a height of k + 1, node must either be an AND or OR node.

If node is an AND node, and node is complete on the *i*th step, Property 5 tells us that  $state_i$  [node].cmp =  $state_{r^*(node)+1}$  [node].cmp. Furthermore, Line 10 of Algorithm 3 states:

$$state_{r^{*}(node)+1}[node].cmp = \bigcap_{c \in children(node)} state_{r^{*}(node)+1}[c].cmp \cap BESTD(parent(node), r^{*}(node))$$
(1)

Since all children of node must have height k or less and must be complete by the time node is complete, they must follow the inductive hypothesis. For any child c of node:

$$state_{r^{*}(node)+1}[c].cmp = ref_{c} \cap BestD(parent(c), r^{*}(c))$$
(2)

Based on Lines 7 and 9 of Algorithm 2:

$$BestD(parent(c), r^{*}(c)) = BestD(parent(node), r^{*}(c)) \cap \left(\bigcap_{c^{\circ} \in children^{\circ}(node, r^{*}(c))} state_{r^{*}(c)}[c^{\circ}].cmp\right)$$
$$\setminus \left(\bigcup_{c^{-} \in children^{-}(node, r^{*}(c)) \setminus \{c\}} state_{r^{*}(c)}[c^{-}].det^{-}\right)$$

Thus, Equation 2 expands to:

$$state_{r^{*}(node)+1}[c].cmp = ref_{c} \cap BestD(parent(node), r^{*}(c)) \cap \left(\bigcap_{c^{\circ} \in children^{\circ}(node, r^{*}(c))} state_{r^{*}(c)}[c^{\circ}].cmp\right)$$
$$\setminus \left(\bigcup_{c^{-} \in children^{-}(node, r^{*}(c)) \setminus \{c\}} state_{r^{*}(c)}[c^{-}].det^{-}\right) (3)$$

Since node is only complete once all its children are complete, we can apply Lemma 5 (stated below) and assert BestD(parent(node),  $r^*(node)$ )  $\subseteq$  BestD(parent(node),  $r^*(c)$ ). Then, we substitute Equation 3 back into Equation 1 to derive:

$$state_{r^{*}(node)+1}[node].cmp = \bigcap_{c \in children(node)} ref_{c} \cap BestD(parent(node), r^{*}(node))$$

$$\bigcap_{c^{\circ} \in children^{\circ}(node, r^{*}(c))} state_{r^{*}(c)}[c^{\circ}].cmp$$

$$\setminus \left(\bigcup_{c^{-} \in children^{-}(node, r^{*}(c)) \setminus \{c\}} state_{r^{*}(c)}[c^{-}].det^{-}\right) \quad (4)$$

We observe that the state<sub>*r*\*(*c*)</sub>[*c*°].cmp component in the second line of Equation 4 can be expanded using Equation 3. By repeatedly plugging Equation 3 into Equation 4, using Lemma 5, applying the identities  $(1) A \cap (B \setminus C) = (A \cap B) \setminus C$ ,  $(2) A \cap (B \setminus (C \cup D)) = (A \setminus C) \cap (B \setminus D)$ ,  $(3) (A \setminus B) \setminus C = A \setminus (B \cup C)$  for any sets *A*, *B*, *C*, and *D* (Appendix F), and removing duplicates, we get:

$$\mathsf{state}_{r^*(\mathsf{node})+1}[\mathsf{node}].\mathsf{cmp} = \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), r^*(\mathsf{node})) \cap \bigcap_{c \in \mathsf{children}(\mathsf{node})} \mathsf{ref}_c \setminus \left(\bigcup_{i_c} \mathsf{state}_{i_c}[c].\mathsf{det}^{\mathsf{rade}}_{i_c}\right)$$

for some set of step indices  $i_c$  for each child c. However, Property 6 states that  $ref_c$  and  $state_i[c].det^-$  must be mutually exclusive for any step index i, so this simplifies to:

 $state_{r^{*}(node)+1}[node].cmp = BestD(parent(node), r^{*}(node)) \cap \bigcap_{c \in children(node)} ref_{c}$ 

Since the  $ref_{node} = \bigcap_{c \in children(node)} ref_c$ :

$$state_{r^{*}(node)+1}[node].cmp = BestD(parent(node), r^{*}(node)) \cap ref_{node}$$

**Lemma 5.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-leaf node in the associated predicate tree. For all pairs of node's predicate descendants  $P_i$  and  $P_j$  for which i < j:

$$BestD(parent(node), j) \subseteq BestD(parent(node), i)$$

If node is an OR node, and node is complete on the *i*th step, Property 5 tells us again that  $state_i$  [node].cmp =  $state_{r^*(node)+1}$  [node].cmp. Line 18 of Algorithm 3 states:

$$state_{r^{*}(node)+1}[node].cmp = \bigcup_{c \in children(node)} state_{r^{*}(node)+1}[c].cmp \cap BESTD(parent(node), r^{*}(node))$$
(5)

Since all children of node must have height k or less and must be complete by the time node is complete, they must follow the inductive hypothesis. For any child c of node:

$$state_{r^*(node)+1}[c].cmp = ref_c \cap BestD(parent(c), r^*(c))$$

Based on Algorithm 2, this expands to:

$$state_{r^{*}(node)+1}[c].cmp = ref_{c} \cap BestD(parent(node), r^{*}(c))$$

$$\setminus \left( \bigcup_{c^{\circ} \in children^{\circ}(node, r^{*}(c))} state_{r^{*}(c)}[c^{\circ}].cmp \bigcup_{c^{+} \in children^{+}(node, r^{*}(c)) \setminus \{c\}} state_{r^{*}(c)}[c^{+}].det^{+} \right)$$

Property 7 states that for all complete children  $c^{\circ}$ , state $[c^{\circ}]$ .cmp = state $[c^{\circ}]$ .det<sup>+</sup>, so this reduces to:

$$state_{r^{*}(node)+1}[c].cmp = ref_{c} \cap BestD(parent(node), r^{*}(c))$$

$$\setminus \left( \bigcup_{c' \in (children^{\circ}(node, r^{*}(c)) \cup children^{+}(node, r^{*}(c)) \setminus \{c\})} state_{r^{*}(c)}[c'].det^{+} \right)$$

We can once again apply Lemma 5 (BestD(parent(node),  $r^*(node)$ )  $\subseteq$  BestD(parent(node),  $r^*(c)$ )) and substitute back into Equation 5 to get:

$$state_{r^{*}(node)+1}[node].cmp = \bigcup_{c \in children(node)} ref_{c} \cap BestD(parent(node), r^{*}(node)) \\ \setminus \left( \bigcup_{c' \in (children^{\circ}(node, r^{*}(c)) \cup children^{+}(node, r^{*}(c)) \setminus \{c\})} state_{r^{*}(c)}[c'].det^{+} \right)$$

We can apply the distributive property to pull the BESTD outwards:

$$state_{r^{*}(node)+1}[node].cmp = BestD(parent(node), r^{*}(node))$$

$$\cap \left( \bigcup_{c \in children(node)} ref_{c} \setminus \left( \bigcup_{c' \in (children^{\circ}(node, r^{*}(c)) \cup children^{+}(node, r^{*}(c)) \setminus \{c\})} state_{r^{*}(c)}[c'].det^{+} \right) \right) (6)$$

Next, we introduce Lemma 6.

**Lemma 6.** For any sets A, B, C, D, E, and F, if  $F \subseteq B$  and  $F \cap C = \emptyset$ , then:

$$A \cup (B \setminus C) \cup (D \setminus (E \cup F)) = A \cup (B \setminus C) \cup (D \setminus E)$$

In our case, for two different children  $c^*$  and c':

$$A = \bigcup_{c \in children(node) \setminus \{c^*, c'\}} \operatorname{ref}_c \setminus \left( \bigcup_{c^* \in (children^\circ(node, r^*(c)) \cup children^+(node, r^*(c)) \setminus \{c\})} \operatorname{state}_{r^*(c)} [c^+].det^+ \right)$$

$$B = \operatorname{ref}_{c^*}$$

$$C = \bigcup_{c^* \in (children^\circ(node, r^*(c^*)) \cup children^+(node, r^*(c^*)) \setminus \{c^*\})} \operatorname{state}_{r^*(c^*)} [c^+].det^+$$

$$D = \operatorname{ref}_{c'}$$

$$E = \bigcup_{c^* \in (children^\circ(node, r^*(c')) \cup children^+(node, r^*(c')) \setminus \{c^*, c'\})} \operatorname{state}_{r^*(c')} [c^+].det^+$$

$$F = \operatorname{state}_{r^*(c')} [c^*].det^+$$

Lemma 7 (shown below) states that  $state_i[c]$ .det<sup>+</sup>  $\subseteq$  ref<sub>c</sub> for any child c. The C term explicitly does not iterate over  $c^*$ , and Lemma 8 (shown below) states state<sub>i</sub>[c].det<sup>+</sup>  $\cap$  state<sub>i</sub>[c<sup>\*</sup>].det<sup>+</sup> =  $\emptyset$  if c and c<sup>\*</sup> are different children. Thus, we satisfy the preconditions for Lemma 6. If we apply this lemma to every positively determinable child  $c^+$  in the *E* term, Equation 6 reduces to:

$$state_{r^{*}(node)+1}[node].cmp = BESTD(parent(node), r^{*}(node))$$

$$\cap \left( ref_{c'} \cup \left( \bigcup_{c \in children(node) \setminus \{c'\}} ref_{c} \setminus \left( \bigcup_{c^{*} \in (children^{\circ}(node, r^{*}(c)) \cup children^{+}(node, r^{*}(c)) \setminus \{c\}} state_{r^{*}(c)}[c^{+}].det^{+} \right) \right) \right)$$

If we apply this trick to every child c of node, this simplifies to:

$$\mathsf{state}_{r^*(\mathsf{node})+1}[\mathsf{node}].\mathsf{cmp} = \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), r^*(\mathsf{node})) \cap \left(\bigcup_{c \in \mathsf{children}(\mathsf{node})} \mathsf{ref}_c\right)$$

7

For OR nodes,  $ref_{node} = \bigcup_{c \in children(node)} ref_c$ , the above equation reduces to:

 $state_{r^*(node)+1}[node].cmp = ref_{node} \cap BestD(node, r^*(node))$ 

`

١
**Lemma 7.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a node in the associated predicate tree. For any step index i:

$$state_i[node].det^+ \subseteq ref_{node}$$

**Lemma 8.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-leaf node in the associated predicate tree. Furthermore, Let c and c' be two different children of node. If node is an OR node, for all step indices i and j:

 $state_i[c].det^+ \cap state_i[c'].det^+ = \emptyset$ 

If node is an AND node, then for all step indices i and j:

 $state_i[c].det^- \cap state_j[c'].det^- = \emptyset$ 

# C Caveat in Proof of Theorem 2

There is a caveat in the proof of Theorem 2 when  $D_i \cap D_j = \emptyset$ , but  $D_j$  is derived from  $U_{i-1} \cup \{P(D_i)\}$ . Calculating  $D_i \cup D_j$  requires  $D_j$ , which in turn requires  $P(D_i)$  which is not available before the *i*th step. However, Lemma 9 (stated below) explicitly states that either this situation cannot arise or  $D_j$  does not require  $P(D_i)$  when being derived. Thus, the contradiction is maintained.

**Lemma 9.** Given a predicate expression with n unique predicates, let  $[(P_1, D_1), ..., (P_m, D_m)]$  be a solution sequence, for which m > n. If step indices i and j are the first two times that predicate P appears in such a sequence (i.e.,  $P_i = P_j = P$ ) and  $D_i \cap D_j = \emptyset$ , then either  $D_j$  can be derived directly from  $U_{i-1}$  without using P as an operator, or  $D_j$  cannot be derived at all from  $U_{i-1} \cup \{P(D_i)\}$  without using P as an operator.

# **D** Reduction from BESTD/UPDATE to EVALPRED

To show the reduction from BESTD/UPDATE to EVALPRED for DFS predicate orderings, we first introduce Lemma 10 below. The lemma basically states that for DFS orderings, all negatively determinable children of AND nodes must also be complete, and all positively determinable determinable children of OR nodes must also be complete.

**Lemma 10.** Given a predicate expression and a DFS ordering of its predicates, if node node of the associated predicate tree is the child of an AND node and negatively determinable on the ith step, then node must also be complete on the ith step. Similarly, if node is the child of an OR node and positively determinable on the ith step, then node must also be complete on the ith step.

Lemma 10 allows us to effectively ignore determinability in BESTD, since all relevant determinable nodes are also complete. Since determinability is never checked, both det<sup>+</sup> and det<sup>-</sup> mappings are unused, and we can ignore the lines updating them in UPDATE. Algorithm 6 and 7 on the next page (BESTD' and UPDATE' respectively) show what BESTD and UPDATE would look like after removing these lines.

Algorithm 6 BESTD'

```
Input: Predicate tree node node, algorithm state state, predicate P_i, step index i
Output: Optimal operand D_i to apply P_i to
 1: if node = NIL then
 2:
         return \{T, F\}^n
 3: else if isLeafNode(node) then
         return BESTD(parent(node), state, P_i, i)
 4:
 5: else if isAndNode(node) then
         X \leftarrow \text{BestD'}(\text{parent}(\text{node}), \text{state}, i)
 6:
         for child \in children(node) do
 7:
             if complete(child, i) then
 8:
                  X \leftarrow X \cap \text{state[child].cmp}
 9:
10:
         return X
11: else
         X \leftarrow \text{BestD'}(\text{parent}(\text{node}), \text{state}, i)
12:
         Y \leftarrow \{\}
13:
14:
         for child ∈ children(node) do
             if complete(child, i) then
15:
                  Y \leftarrow Y \cup \text{state[child].cmp}
16:
         return X \setminus Y
17:
```

### Algorithm 7 UPDATE'

**Input:** Predicate tree node node, algorithm state state, predicate  $P_i$ , set of valuations  $D_i$ , step index *i* 1: **if** node = NIL **then** return 2: 3: else if isLeafNode(node) then state[node].cmp  $\leftarrow P_i(D_i)$ 4: 5: else if isAndNode(node) then if complete(node, *i* + 1) then 6:  $\texttt{state[node].cmp} \leftarrow \bigcap_{\texttt{child}} \texttt{state[child].cmp} \cap \texttt{BestD'}(\texttt{parent}(\texttt{node}),\texttt{state}, i)$ 7: 8: else if complete(node, *i* + 1) then 9: state[node].cmp  $\leftarrow \bigcup_{child}$  state[child].cmp  $\cap$  BESTD'(parent(node), state, i) 10: 11: UPDATE' (parent(node), state,  $P_i, D_i, i$ )

Algorithm 6 works by traversing the predicate tree in a bottom-up fashion. Each node calls BESTD' on its parent, takes the returned value, modify it based on completed children, and return the filtered value to the child which called it. We can instead imagine constructing a dual algorithm which traverses the predicate top-down for any specific predicate; this is presented in Algorithm 8 (next page). For any predicate  $P_i$ :

```
BESTDFLIPPED(root, state, P_i, i, \{T, F\}^n) = BESTD'(leafNodes[P_i], state, P_i, i)
```

Note that the expression childOfAndAncestorOf(node,  $P_i$ ) returns the child of node which is the ancestor of the node referring to  $P_i$ .

Next, we can combine BESTDFLIPPED with UPDATE'. This will traverse top-down from the root node to  $P_i$  for the BESTD' value and then traversing back up to the root node, updating state for complete

Algorithm 8 BestDFLIPPED

**Input:** Predicate tree node node, filtered valuation set X, algorithm state state, predicate  $P_i$ , step index *i* 

```
Output: Equivalent to BESTD' (parent(P_i), state, i)
 1: if isLeafNode(node) then
        return X
 2:
 3: else if isAndNode(node) then
        for child ∈ children(node) do
 4:
             if complete(child, i) then
 5:
                 X \leftarrow X \cap \text{state[child].cmp}
 6:
        child \leftarrow childOfAndAncestorOf(node, P_i)
 7:
        return BESTDFLIPPED(child, X, state, P<sub>i</sub>, i)
 8:
 9: else
        Y \leftarrow \{\}
10:
        for child \in children(node) do
11:
            if complete(child, i) then
12:
13:
                 Y \leftarrow Y \cup \text{state[child].cmp}
        child \leftarrow childOfAndAncestorOf(node, P_i)
14:
        return BESTDFLIPPED(child, X \setminus Y, state, P_i, i)
15:
```

# Algorithm 9 COMBINED

**Input:** Predicate tree node node, filtered valuation set X, algorithm state state, predicate  $P_i$ , step index *i* 

```
1: if isLeafNode(node) then
        state[node].cmp \leftarrow P_i(X)
 2:
 3: else if isAndNode(node) then
        for child ∈ children(node) do
 4:
            if complete(child, i) then
 5:
                 X \leftarrow X \cap \text{state[child].cmp}
 6:
 7:
        child \leftarrow childOfAndAncestorOf(node, P_i)
        COMBINED(child, X, state, P_i, i)
 8:
        if complete(node, i + 1) then
 9:
             state[node].cmp \leftarrow \bigcap_{\text{child}} \text{state[child].cmp} \cap X
10:
11: else
        Y \leftarrow \{\}
12:
        for child ∈ children(node) do
13:
            if complete(child, i) then
14:
                 Y \leftarrow Y \cup \text{state[child].cmp}
15:
        child \leftarrow childOfAndAncestorOf(node, P_i)
16:
        COMBINED(child, X \setminus Y, state, P_i, i)
17:
        if complete(node, i + 1) then
18:
             state[node].cmp \leftarrow \bigcup_{\text{child}} \text{state[child].cmp} \cap X
19:
```

nodes. Algorithm 9 presents this combined algorithm (COMBINED). A return value is no longer needed because they are stored in the cmp attributes of state. COMBINED is used to traverse down and update only a single predicate  $P_i$ . If multiple children are being updated with COMBINED, many extra checks

for completeness can be avoided, since a DFS traversal guarantees completeness for any traversed child. Algorithm 10 shows what it would look like if COMBINED calls to separate predicates were combined together into one algorithm. We assume that the nodes of the predicate tree already sorted in the ordering given by  $[P_1, ..., P_n]$ . Also, since everything is done in one pass, instead of a separate state variable, we simply use the returned values of each child.

Algorithm 10 COMBINEDALL

```
Input: Predicate tree node node, filtered valuation set X
 1: if isLeafNode(node) then
         return P_i(X)
 2:
 3: else if isAndNode(node) then
         for child ∈ children(node) do
 4:
             X \leftarrow X \cap \text{COMBINEDALL}(\text{child}, X)
 5:
         return X
 6:
 7: else
         Y \leftarrow \{\}
 8:
         for child ∈ children(node) do
 9:
             Y \leftarrow Y \cup \text{CombinedAll}(\text{child}, X \setminus Y)
10:
         return Y
11:
```

As we can see, there is a 1-to-1 correspondence between Algorithm 10 and EVALPRED. The only difference is that Algorithm 10 does not feature any early returns.

# **E** Supplementary Proofs

# **E.1 Additional Definitions**

We first provide some additional definitions that we will use throughout this section.

**Definition 18.** For any predicate tree node node, we define the **lineage** of node as the sequence of ancestor nodes  $[A_1, ..., A_m]$  in which  $A_1$  is the parent of node, and  $A_{i+1}$  is the parent of  $A_i$  for all  $i \in \{1, ..., m-1\}$ , and  $A_m$  is the root node.

Simply put, the lineage of node is the sequence of its ancestors starting with the parent up to the root.

**Definition 19.** Let node be a node in the predicate tree, and let  $ref_{node}$  refer to the set of all valuations which satisfy the subexpression represented by node. Evaluating a valuation v with respect to the subexpression represented by node, denoted node[v], is true if and only if  $v \in ref_{node}$ .

For example, if node a leaf node referring to the predicate  $P_i$ , node[v] = T if and only if  $v_i = T$ . In the following text, we may say that v is "evaluated against the subexpression represented by node" or "evaluated against node" to refer to the same thing.

**Definition 20.** Let node be a node in the predicate tree. We say that node is **statically true** with respect to a valuation set D if  $D \subseteq ref_{node}$  and **statically false** with respect to D if  $D \cap ref_{node} = \emptyset$ . If node is either statically true or statically false with respect to a valuation set, it is said to be **static** with respect to that valuation set. Otherwise, node is **dynamic** with respect to that valuation set.

More colloquially, node is statically true (false) with respect to a valuation set D if every valuation in D evaluates to true (false) against node, and node is static with respect to valuation set D if all valuations in D evaluate to the same value against node (otherwise, the node is dynamic with respect to D).

# E.2 Reference

For the reader's convenience, before diving into the proofs, we first list both BESTD and UPDATE algorithms and all definitions, properties, and lemmas used in this paper. The reader may refer to this section when reading through the proofs. In addition, Table 6 provides a table of some notation that we think would be helpful for the reader to remember when reading this section. Good luck.

```
Algorithm 2 BESTD
```

```
Input: Predicate tree node node, algorithm state state, predicate P_i, step index i
Output: Optimal operand D_i to apply P_i to
  1: if node = NIL then
          return \{T, F\}^n
 2:
 3: else if isAndNode(node) then
          X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)
 4:
          for child ∈ children(node) do
 5:
              if complete(child, i) then
 6:
                   X \leftarrow X \cap \text{state[child].cmp}
  7:
              else if determ<sup>-</sup>(child, i) and isNotAncestor(child, P<sub>i</sub>) then
 8:
                   X \leftarrow X \setminus \text{state[child].det}^-
 9:
          return X
10:
11: else
          X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)
12:
13:
          Y \leftarrow \{\}
          for child ∈ children(node) do
14:
              if complete(child, i) then
15:
                   Y \leftarrow Y \cup \text{state[child].cmp}
16:
              else if determ<sup>+</sup>(child, i) and isNotAncestor(child, P<sub>i</sub>) then
17:
                   Y \leftarrow Y \cup \texttt{state[child].det}^+
18:
          return X \setminus Y
19:
```

Algorithm 3 UPDATE

**Input:** Predicate tree node node, algorithm state state, predicate  $P_i$ , set of valuations  $D_i$ , step index *i* 1: **if** node = NIL **then** 

```
2:
          return
 3: else if isLeafNode(node) then
          state[node].cmp \leftarrow P_i(D_i)
 4:
          state[node].det<sup>+</sup> \leftarrow P_i(D_i)
 5:
          state[node].det \leftarrow D_i \setminus P_i(D_i)
 6:
 7: else if isAndNode(node) then
          X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)
 8:
          if complete(node, i + 1) then
 9:
                state[node].cmp \leftarrow \bigcap_{\text{child}} \text{state[child].cmp} \cap X
10:
          if determ<sup>+</sup> (node, i + 1) then
11:
               state[node].det<sup>+</sup> \leftarrow \bigcap_{\text{child}} \text{state[child].det}^+ \cap X
12:
          if determ<sup>-</sup> (node, i + 1) then
13:
               state[node].det \leftarrow \bigcup_{\text{child}} \text{state[child].det} \cap X
14:
15: else
          X \leftarrow \text{BestD}(\text{parent}(\text{node}), \text{state}, i)
16:
          if complete(node, i + 1) then
17:
               \texttt{state[node].cmp} \leftarrow \bigcup_{\texttt{child}} \texttt{state[child].cmp} \cap X
18:
          if determ<sup>+</sup>(node, i + 1) then
19:
               state[node].det^{+} \leftarrow \bigcup_{child} state[child].det^{+} \cap X
20:
          if determ<sup>-</sup> (node, i + 1) then
21:
               state[node].det \leftarrow \bigcap_{\text{child}} \text{state[child].det} \cap X
22:
23: UPDATE(parent(node), state, P_i, D_i, i)
```

Symbol	Meaning			
vi	The value of the <i>i</i> th element of valuation <i>v</i>			
$v _{i=T}$	Refers to the valuation that is the same as $v$ except $v_i = T$			
$\Gamma(v, i)$	All valuations for which the first $i - 1$ elements are the same as $v$			
ref <sub>node</sub>	The set of all valuations which satisfy node's predicate subexpression			
node[v]	Evaluating valuation $v$ against the subexpression represented by node			
r(node, i)	The step index of node's last predicate descendant before <i>i</i>			
$r^*(node)$	The step index of node's final predicate descendant (i.e., $r(node, n + 1)$ )			
children°(node, <i>i</i> )	The set of complete children of node on step <i>i</i>			
children <sup>+</sup> (node, <i>i</i> )	The set of positively determinable (but not complete) children of node on step <i>i</i>			
children <sup>-</sup> (node, <i>i</i> )	The set of negatively determinable (but not complete) children of node on step <i>i</i>			
$c^{\circ}$	A complete child			
<i>c</i> <sup>+</sup>	A positively determinable child			
<i>c</i> <sup>-</sup>	A negatively determinable child			
<pre>state[node].cmp</pre>	Contains valuations which satisfy node's subexpression			
$state[node].det^+$	Contains a subset of valuations which satisfy node's subexpression			
state[node].det⁻	Contains a subset of valuations which do not satisfy node's subexpression			

Table 6: Notation for common symbols and expressions.

### E.2.1 Definitions

**Definition 1.** A valuation is a tuple of true/false values.

**Definition 2.** The *predicate application* of predicate P on valuation set D is denoted P(D) and returns the subset of valuations in D which satisfy P.

**Definition 3.** A set operation is one of union  $(\cup)$ , intersection  $(\cap)$ , or difference  $(\setminus)$ .

**Definition 4.** A step is an (operator, operand) pair: S = (O, D), in which operator O is either a predicate or a set operation, and operand D is the input valuations set(s). Applying the operator to operand results in the step's output and is denoted O(D).

**Definition 5.** Given the sequence of steps  $[(O_1, \mathbf{D}_1), (O_2, \mathbf{D}_2), ..., (O_m, \mathbf{D}_m)]$ , **universe**  $U_i$  is defined by the recurrence relation:

$$U_i = U_{i-1} \cup \{O_i(\mathbf{D}_i)\}$$

with the initial universe:  $U_0 = \{\{T, F\}^n\}.$ 

**Definition 6.** A sequence of steps  $[(O_1, \mathbf{D}_1), (O_2, \mathbf{D}_2), ..., (O_m, \mathbf{D}_m)]$  is **valid** if, for each step  $(O_i, \mathbf{D}_i)$ , all valuation sets in  $\mathbf{D}_i$  are members of  $U_{i-1}$ .

**Definition 7.** The cost of a step  $(O, \mathbf{D})$  is denoted as  $C_O(\mathbf{D})$ , and the cost of a sequence of steps  $[(O_1, \mathbf{D}1), (O_2, \mathbf{D}2), ... (O_m, \mathbf{D}m)]$  is the sum of the costs of its individual steps:  $\sum_{i=1}^m C_{O_i}(\mathbf{D}_i)$ .

**Definition 8.** A set formula is any combination of sets (as operands) using any number of set operations and predicates (as operators). The result of a set formula is its value after evaluation.

**Definition 9.** Let **O** be a set of operators, and **D** be a set of sets. The **set formula space**  $\Psi_{O}(D)$  is the set of all possible formula results that can be constructed using only the operators in **O** as the operators and the sets in **D** as the operands.

**Definition 10.** Set D is said to be **derived** from set of sets D if there exists some set formula which only uses the elements of D as operands and results in D. More explicitly, set D can be derived from the **origin** set D using the operators in O if  $D \in \Psi_O(D)$ .

**Definition 11.** Given the sequence of predicate application steps  $[(P_1, D_1), (P_2, D_2), ..., (P_m, D_m)]$ , the *extended universe*  $U'_i$  is defined by the recurrence relation:

$$U_i' = \Psi_{\{\cap, \cup, \setminus\}} (U_{i-1}' \cup \{P_i(D_i)\})$$

with the initial extended universe:  $U'_0 = \{\{T, F\}^n\}.$ 

**Definition 12.** Given a predicate expression, a **solution sequence** is a valid sequence of predicate application steps, after which the extended universe contains the set of all valuations which satisfy the predicate expression.

**Definition 13.** Given a predicate expression and some ordering of its predicates predicates  $[P_1, ..., P_n]$ , node node of the associated predicate tree is **complete** on the ith step, if:

 $complete(node, i) = \begin{cases} node. P = P_j \text{ and } j < i & if \text{ leaf node} \\ \land_{c \in children(node)} \text{ complete}(c, i) & otherwise \end{cases}$ 

**Definition 14.** Given a predicate expression and some ordering of its predicates predicates  $[P_1, ..., P_n]$ , node node of the associated predicate tree is **positively determinable** on the *i*th step, if:

$$determ^{+}(\mathsf{node}, i) = \begin{cases} \mathsf{node}.P = P_j \text{ and } j < i & \text{if leaf node} \\ \bigwedge_{c \in children(\mathsf{node})} determ^{+}(c, i) & \text{if AND node} \\ \bigvee_{c \in children(\mathsf{node})} determ^{+}(c, i) & \text{if OR node} \end{cases}$$

**Definition 15.** Given a predicate expression and some ordering of its predicates predicates  $[P_1, ..., P_n]$ , node node of the associated predicate tree is **negatively determinable** on the *i*th step, if:

$$determ^{-}(\text{node}, i) = \begin{cases} \text{node}.P = P_j \text{ and } j < i & \text{if leaf node} \\ \bigvee_{c \in children(\text{node})} determ^{-}(c, i) & \text{if AND node} \\ \bigwedge_{c \in children(\text{node})} determ^{-}(c, i) & \text{if OR node} \end{cases}$$

**Definition 16.** The *ith valuation group* of a valuation v is the set of all valuations for which the first i - 1 values of the valuation are equal to the first i - 1 values of v. In other words, if  $\Gamma(v, i)$  represents the *ith valuation group of v*:

$$\Gamma(v,i) = \{ u \in \{T,F\}^n \mid \bigwedge_{j=1}^{i-1} v_j = u_j \}$$

**Definition 17.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let node be any node in the associated predicate tree. The **rank** of node on the ith step (denoted r(node, i)) is the largest index j such that j < i and  $P_j$  is a predicate leaf node descendant of node. If no such j exists, r(node, i) = 0. The **final rank** of node (denoted  $r^*(node)$ ) is the largest index j such that  $P_j$  is a predicate leaf node descendant of node.

**Definition 18.** For any predicate tree node node, we define the **lineage** of node as the sequence of ancestor nodes  $[A_1, ..., A_m]$  in which  $A_1$  is the parent of node, and  $A_{i+1}$  is the parent of  $A_i$  for all  $i \in \{1, ..., m - 1\}$ , and  $A_m$  is the root node.

**Definition 19.** Let node be a node in the predicate tree, and let  $ref_{node}$  refer to the set of all valuations which satisfy the subexpression represented by node. Evaluating a valuation v with respect to the subexpression represented by node, denoted node[v], is true if and only if  $v \in ref_{node}$ .

**Definition 20.** Let node be a node in the predicate tree. We say that node is **statically true** with respect to a valuation set D if  $D \subseteq ref_{node}$  and **statically false** with respect to D if  $D \cap ref_{node} = \emptyset$ . If node is either statically true or statically false with respect to a valuation set, it is said to be **static** with respect to that valuation set. Otherwise, node is **dynamic** with respect to that valuation set.

## E.2.2 Properties

**Property 1.** The cost of any predicate application step (P, D) is significantly greater than the cost of any set operation step (O, D'):

$$C_O(\mathbf{D}')/C_P(D) \approx 0$$

**Property 2.** For any predicate P, if step (P, D) is more costly than step (P, D'), then D' cannot be a superset of D.

$$C_P(D) > C_P(D') \implies D' \not\supseteq D$$

Similarly, if D' is a strict superset of D, then step (P, D') is more costly than step (P, D):

$$D' \supset D \implies C_P(D') > C_P(D)$$

**Property 3.** For any predicate *P* and valuation sets *D* and *E*, applying *P* once to  $D \cup E$  is less costly than applying *P* to *D* and *E* individually:

$$C_P(D \cup E) < C_P(D) + C_P(E)$$

**Property 4.** For any predicate P and valuation sets D and E:

$$P(D \cap E) = P(D) \cap E$$
$$P(D \cup E) = P(D) \cup P(E)$$
$$P(D \setminus E) = P(D) \setminus E$$

**Property 5.** If node is not complete on the *i*th step but complete on the (i + 1)th step, then for all j > i:

 $state_{i+1}[node].cmp = state_{i}[node].cmp$ 

**Property 6.** For any node and step indices *i* and *j*:

 $state_i [node].cmp \cap state_i [node].det^- = \emptyset$ 

and

 $state_i [node].det^+ \cap state_i [node].det^- = \emptyset$ 

**Property 7.** If node is complete on the ith step:

state<sub>i</sub>[node].cmp = state<sub>i</sub>[node].det<sup>+</sup>

**Property 8.** Let node node be a node in the predicate tree. For any step index i:

 $BestD(node, i) \subseteq BestD(parent(node), i)$ 

#### E.2.3 Theorems

**Theorem 1.** Given a predicate expression and a solution sequence S, for each predicate P in the predicate expression, there must be a step S in S such that S = (P, D) for some valuation set D.

**Theorem 2.** Given a predicate expression with n unique predicates, the lowest cost solution sequence must have exactly n steps.

**Theorem 3.** For a given predicate expression and some ordering of its predicates  $[P_1, ..., P_n]$ , let  $[D_1, ..., D_n]$  be the sequence of operands generated by BESTD/UPDATE. The sequence of steps  $[(P_1, D_1), ..., (P_n, D_n)]$  must have the lowest cost of any solution sequence.

**Theorem 5.** Given a predicate expression and an ordering of its predicates, let node be any node in the associated predicate tree, and let  $ref_{node}$  be the set of all tuples which satisfy the predicate subexpression represented by node. For any set of tuples D, EVALNODE(node, D) returns the subset of D which satisfies the predicate subexpression represented by node, or:

 $EvalNode(node, D) = ref_{node} \cap D$ 

**Theorem 6.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , and let node be a node in the associated predicate tree. Furthermore, let  $ref_{node}$  be the set of all valuations which satisfy the predicate subexpression represented by node. On the *i*th step, if node is complete:

 $state_i[node].cmp = ref_{node} \cap BestD(parent(node), r^*(node))$ 

#### E.2.4 Lemmas

**Lemma 1.** Let  $P_i$  refer to the *i*th predicate of the given predicate expression. There exists a valuation v such that  $v|_{i=T}$  satisfies the overall predicate expression, but  $v|_{i=F}$  does not.

**Lemma 2.** Given a predicate expression with predicates  $\{P_1, ..., P_n\}$ , some valuation  $v \in \{T, F\}^n$ , and some set of valuation sets **D**, if every valuation set  $D \in \mathbf{D}$  contains either both or neither  $v|_{i=T}$  and  $v|_{i=F}$ , then

every valuation set which can be derived from **D** without using  $P_i$  as an operator must also contain either both or neither  $v|_{i=T}$  and  $v|_{i=F}$ . In other words:

$$\begin{aligned} \forall D \in \mathbf{D}, (v|_{i=T} \in D \land v|_{i=F} \in D) \lor (v|_{i=F} \notin D \land v|_{i=F} \notin D) \\ \implies \forall \mathbf{O} \subseteq \{\cup, \cap, \backslash, P_1, ..., P_{i-1}, P_{i+1}, ..., P_n\}, \forall D' \in \Psi_{\mathbf{O}}(\mathbf{D}), \\ (v|_{i=T} \in D' \land v|_{i=F} \in D') \lor (v|_{i=T} \notin D' \land v|_{i=F} \notin D') \end{aligned}$$

**Lemma 3.** Given a predicate expression and some ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$  be the ith operand generated by BESTD/UPDATE. For all valuations  $v \in D_i$ , there exists a valuation  $u \in \Gamma(v, i)$  such that only one of  $u|_{i=T}$  and  $u|_{i=F}$  satisfies the given predicate expression.

**Lemma 4.** Given any ordering of predicates for a predicate expression of depth 2 or less, if node node of the associated predicate tree is the child of an AND node and negatively determinable, then node must be complete. Similarly, if node is the child of an OR node and positively determinable, then node must be complete.

**Lemma 5.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-leaf node in the associated predicate tree. For all pairs of node's predicate descendants  $P_i$  and  $P_j$  for which i < j:

 $BestD(parent(node), j) \subseteq BestD(parent(node), i)$ 

**Lemma 6.** For any sets A, B, C, D, E, and F, if  $F \subseteq B$  and  $F \cap C = \emptyset$ , then:

$$A \cup (B \setminus C) \cup (D \setminus (E \cup F)) = A \cup (B \setminus C) \cup (D \setminus E)$$

**Lemma 7.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a node in the associated predicate tree. For any step index i:

$$state_i[node].det^+ \subseteq ref_{node}$$

**Lemma 8.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-leaf node in the associated predicate tree. Furthermore, Let c and c' be two different children of node. If node is an OR node, for all step indices i and j:

$$state_i[c].det^+ \cap state_i[c'].det^+ = \emptyset$$

If node is an AND node, then for all step indices i and j:

$$state_i[c].det^- \cap state_i[c'].det^- = \emptyset$$

**Lemma 9.** Given a predicate expression with n unique predicates, let  $[(P_1, D_1), ..., (P_m, D_m)]$  be a solution sequence, for which m > n. If step indices i and j are the first two times that predicate P appears in such a sequence (i.e.,  $P_i = P_j = P$ ) and  $D_i \cap D_j = \emptyset$ , then either  $D_j$  can be derived directly from  $U_{i-1}$  without using P as an operator, or  $D_j$  cannot be derived at all from  $U_{i-1} \cup \{P(D_i)\}$  without using P as an operator.

**Lemma 10.** Given a predicate expression and a DFS ordering of its predicates, if node node of the associated predicate tree is the child of an AND node and negatively determinable on the ith step, then node must also be complete on the ith step. Similarly, if node is the child of an OR node and positively determinable on the ith step, then node must also be complete on the ith step.

**Lemma 11.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let node be a nonroot node in the associated predicate tree. If node's parent is an OR node, node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

$$state_{i+1}$$
[node].det<sup>+</sup>  $\supseteq$  state<sub>i</sub>[node].det<sup>+</sup>  $\cap$  *BestD*(parent(parent(node)), r(node, i + 1))

If node's parent is an AND node, node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

 $state_{i+1}[node].det^{-} \supseteq state_{i}[node].det^{-} \cap BestD(parent(parent(node)), r(node, i + 1))$ 

**Lemma 12.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-root node in the associated predicate tree. If node's parent is an OR node, node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}[node].det^{+} \supseteq state_{i}[node].det^{+} \cap BestD(parent(parent(node)), r(node, i + 1))$ 

If node's parent is an AND node, node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}[node].det^{-} \supseteq state_{i}[node].det^{-} \cap BestD(parent(parent(node)), r(node, i + 1))$ 

**Lemma 13.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a node in the associated predicate tree. If node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

 $state_{i+1}$ [node].det<sup>+</sup>  $\supseteq$  state<sub>i</sub>[node].det<sup>+</sup>  $\cap$  *BestD*(parent(node), r(node, i + 1))

If node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

 $state_{i+1}$ [node].det  $\supseteq$  state<sub>i</sub>[node].det  $\cap$  *BestD*(parent(node), r(node, i + 1))

**Lemma 14.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a node in the associated predicate tree. If node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}$ [node].det<sup>+</sup>  $\supseteq$  state<sub>i</sub>[node].det<sup>+</sup>  $\cap$  *BestD*(parent(node), r(node, i + 1))

If node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}[node].det^{-} \supseteq state_{i}[node].det^{-} \cap BestD(parent(node), r(node, i + 1))$ 

**Lemma 15.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-leaf node in the associated predicate tree. Furthermore, Let c and c' be two different children of node. If node is an OR node, Lemma 5 holds true up to step  $j_{max}$ , and Lemma 14 holds true up to node's children, then for all steps i and j such that  $max(i, j) \leq j_{max}$ :

 $state_i[c].det^+ \cap state_i[c'].det^+ = \emptyset$ 

If node is an AND node, Lemma 5 holds true up to step  $j_{max}$ , and Lemma 14 holds true up to node's children, then for all steps i and j such that  $max(i, j) \le j_{max}$ :

 $state_i[c].det^- \cap state_i[c'].det^- = \emptyset$ 

**Lemma 16.** For any set of valuation sets **D**, predicate *P*, and any  $D \in \mathbf{D}$ , let *E* be some valuation set derived from  $\mathbf{D} \cup \{P(D)\}$  without using *P* as an operator. There exists a valuation set *E'* derived from **D** without using *P* as an operator, such that:

$$E \setminus D = E' \setminus D$$

**Lemma 17.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$  be the ith operand generated by BESTD and UPDATE. In addition, let A be an ancestor in  $P_i$ 's lineage. For all  $v \in D_i$ , there exists a  $u \in \Gamma(v, i)$  such that all incomplete children of A that are not ancestors of  $P_i$  are statically true/false with respect to  $\{u|_{i=T}, u|_{i=F}\}$  if A is an AND/OR node respectively.

**Lemma 18.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$  be the ith operand generated by BESTD and UPDATE. In addition, let A be an ancestor in  $P_i$ 's lineage. For all  $v \in D_i$ , an incomplete child of A which is not an ancestor of  $P_i$  cannot be statically false/true with respect to  $\Gamma(v, i)$  if A is an AND/OR node respectively.

**Lemma 19.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$  be the ith operand generated by BESTD and UPDATE. In addition, let node be a node in the associated predicate tree. For all  $v \in D_i$ , if node is not positively determinable on step *i*, then node cannot be statically true with respect to  $\Gamma(v, i)$ . Similarly, for all  $v \in D_i$ , if node is not negatively determinable on step *i*, then node cannot be statically node cannot be statically false with respect to  $\Gamma(v, i)$ .

**Lemma 20.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let node be a node in the associated predicate tree. If node is positively determinable on step i, then  $state_i[node].det^+$  is the set of valuations  $v \in BestD(node, r(node, i))$  such that every  $u \in \Gamma(v, i)$  evaluated against node is true:

state<sub>*i*</sub>[node].det<sup>+</sup> = { $v \in BestD(parent(node), r(node, i)) | \forall u \in \Gamma(v, i), node[u] = T$ }

Similarly, if node is negatively determinable on step i, then  $state_i[node].det^-$  is the set of valuations  $v \in BestD(node, r(node, i))$  such that every  $u \in \Gamma(v, i)$  evaluated against node is false:

 $state_i[node].det^- = \{v \in BestD(parent(node), r(node, i)) \mid \forall u \in \Gamma(v, i), node[u] = F\}$ 

# E.3 Proofs

Before we begin, a special note on Lemmas 5, 14, and 15. The co-dependent nature of BESTD and UPDATE require that these lemmas use each other in their proofs. However, both Lemmas 5 and 14 are inductive proofs, and by depending on the inductive hypotheses, we can avoid a cyclical dependency. To take an example, in the proof for Lemma 5, it is assumed the lemma holds up to step k. Then, for the (k + 1)th step, Lemma 14 is used<sup>7</sup> but the conditions to use Lemma 14 only requires that Lemma 5 hold up to step k. Thus, a cyclical dependency is avoided. A similar situation occurs with Lemma 15.

### E.3.1 Proof of Lemma 1

**Lemma 1.** Let  $P_i$  refer to the *i*th predicate of the given predicate expression. There exists a valuation v such that  $v|_{i=T}$  satisfies the overall predicate expression, but  $v|_{i=F}$  does not.

*Proof.* We prove the lemma by construction with the following algorithm:

- 1. Start with an empty *n*-length valuation  $v = (\_, \_, ..., \_)$ .
- 2. Starting from  $P_i$ 's direct parent, for each ancestor A in Pi's lineage:
  - For each predicate descendant  $P_i$  of A that is not  $P_i$ :
    - If  $v_i$  is unset, set  $v_i = T$  if A is an AND node and  $v_i = F$  if A is an OR node.
- 3. Return the pair of valuations  $(v|_{i=T}, v|_{i=F})$ .

To see why  $v|_{i=T}$  satisfies the overall predicate expression but  $v|_{i=F}$  does not, let A refer to an ancestor node in  $P_i$ 's lineage, and let A' be A's child which is either also in  $P_i$ 's lineage or is  $P_i$  itself. Furthermore, let all predicates that are descendants of A but not A' be called "other" predicates. If A is an AND node, setting the elements of v corresponding to "other" predicate descendants to true ensures that every child other than A' will evaluate to true. As a result, A's overall evaluation on v is wholly dependent on whether A' evaluates to true or false. In the case that A is an OR node, setting the elements of vcorresponding to the "other" predicates to false also ensures that every child other A' will evaluate to false. As a result, A's overall evaluation on v once again is wholly dependent on whether A' evaluates to true or false. The above algorithm applies this logic recursively to construct  $v|_{i=T}$  and  $v|_{i=F}$ , so the sole outcome of  $P_i$  determines the outcome of the entire predicate expression.

## E.3.2 Proof of Lemma 2

**Lemma 2.** Given a predicate expression with predicates  $\{P_1, ..., P_n\}$ , some valuation  $v \in \{T, F\}^n$ , and some set of valuation sets **D**, if every valuation set  $D \in \mathbf{D}$  contains either both or neither  $v|_{i=T}$  and  $v|_{i=F}$ , then every valuation set which can be derived from **D** without using  $P_i$  as an operator must also contain either both or neither  $v|_{i=T}$  and  $v|_{i=F}$ . In other words:

$$\begin{aligned} \forall D \in \mathbf{D}, (v|_{i=T} \in D \land v|_{i=F} \in D) \lor (v|_{i=F} \notin D \land v|_{i=F} \notin D) \\ \implies \forall \mathbf{O} \subseteq \{\cup, \cap, \backslash, P_1, ..., P_{i-1}, P_{i+1}, ..., P_n\}, \forall D' \in \Psi_{\mathbf{O}}(\mathbf{D}), \\ (v|_{i=T} \in D' \land v|_{i=F} \in D') \lor (v|_{i=T} \notin D' \land v|_{i=F} \notin D') \end{aligned}$$

<sup>&</sup>lt;sup>7</sup>Lemma 5 actually uses Lemma 11, but this uses Lemma 12, which uses Lemma 13, which uses Lemma 14. However, the assumption is carried all the way through.

*Proof.* We give a proof by case analysis. Let *X* be a valuation set which has either both  $v|_{i=T}$  and  $v|_{i=F}$  or neither  $v|_{i=T}$  nor  $v|_{i=F}$ . If we apply a predicate  $P_j$  which is not  $P_i$  to *X*, the result  $P_j(X)$  will have both  $(v|_{i=T}, v|_{i=F})$  if  $v_j = T$  and neither valuations if  $v_j = F$ . Let *Y* be another valuation set which also has either both or neither of  $v|_{i=T}$  and  $v|_{i=F}$ . We show for every set operation between the two valuation sets, the result will also have either have both or neither valuations. Table 7 shows the results. The table elements reflect whether both or neither valuations are present in the results of set operations between *X* and *Y*. Thus, if every valuation set in **D** contains either both or neither of  $v|_{i=T}$  and  $v|_{i=F}$ , then all derived sets which do not use  $P_i$  as an operator must also contain either both or neither of  $v|_{i=T}$  and  $v|_{i=F}$ .

Set Op	Both in X		Neither in X	
	<b>Both</b> in Y	Neither in Y	<b>Both in</b> <i>Y</i>	Neither in Y
$X \cup Y$	Both	Both	Both	Neither
$X \cap Y$	Both	Neither	Neither	Neither
$X \setminus Y$	Neither	Both	Neither	Neither
$Y \setminus X$	Neither	Neither	Both	Neither

**Table 7:** Outcomes of set operations between valuation sets that have either both or neither  $v|_{i=T}$  and  $v|_{i=F}$ .

### E.3.3 Proof of Lemma 3

**Lemma 3.** Given a predicate expression and some ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$  be the ith operand generated by BESTD/UPDATE. For all valuations  $v \in D_i$ , there exists a valuation  $u \in \Gamma(v, i)$  such that only one of  $u|_{i=T}$  and  $u|_{i=F}$  satisfies the given predicate expression.

*Proof.* We first introduce the concept of *static* and *dynamic* nodes.

**Definition 20.** Let node be a node in the predicate tree. We say that node is **statically true** with respect to a valuation set D if  $D \subseteq ref_{node}$  and **statically false** with respect to D if  $D \cap ref_{node} = \emptyset$ . If node is either statically true or statically false with respect to a valuation set, it is said to be **static** with respect to that valuation set. Otherwise, node is **dynamic** with respect to that valuation set.

More intuitively, if every valuation within a valuation set would evaluate to true when evaluated against node, then node is considered statically true with respect to that valuation set. Similarly, if every valuation within a valuation set would evaluate to false, then node is considered statically false with respect to that valuation set. If different valuations in a valuation set would result in different values when evaluated against node, then node is considered dynamic with respect to that valuation set.

Based on this definition, we present the following lemma about incomplete nodes.

**Lemma 17.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$  be the ith operand generated by BESTD and UPDATE. In addition, let A be an ancestor in  $P_i$ 's lineage. For all  $v \in D_i$ , there exists a  $u \in \Gamma(v, i)$  such that all incomplete children of A that are not ancestors of  $P_i$  are statically true/false with respect to  $\{u|_{i=T}, u|_{i=F}\}$  if A is an AND/OR node respectively.

We are now ready to prove Lemma 3. Assume to the contrary that there exists a valuation  $v \in D_i$ such that for all  $u \in \Gamma(v, i)$ , the root node is static with respect to  $\{u|_{i=T}, u|_{i=F}\}$ . By definition,  $P_i$  must be dynamic with respect to  $\{u|_{i=T}, u|_{i=F}\}$ . Therefore, somewhere along  $P_i$ 's lineage, the nodes change from being dynamic to static with respect to  $\{u|_{i=T}, u|_{i=F}\}$ . Let A' be the ancestor in  $P_i$ 's lineage closest to the root such that A' is dynamic with respect to  $\{u|_{i=T}, u|_{i=F}\}$  while A''s parent A is static with respect to  $\{u|_{i=T}, u|_{i=F}\}$ . We show that A cannot be static, leading to a contradiction. If *A* is an AND node, based on Algorithm 2, we see that BESTD(*A*, *i*) returns only valuations which satisfy every one of *A*'s complete children on step *i*. Based on Property 8 (shown below),  $D_i$  must be a subset of BESTD(*A*, *i*), so all complete children of *A* must be statically true with respect to  $D_i$ . Corollary 1 states that  $\Gamma(v, i) \subseteq D_i$  and  $\{u|_{i=T}, u|_{i=F}\} \subseteq \Gamma(v, i)$ , so all of *A*'s complete children must also be statically true with respect to  $\{u|_{i=T}, u|_{i=F}\}$  as well. Based on Lemma 17, for all  $v \in D_i$ , there must exist a  $u \in \Gamma(v, i)$  such that all incomplete children of *A* except *A*' are statically true with respect to  $\{u|_{i=T}, u|_{i=F}\}$ . In other words, for this *u*, all children except *A*' are statically true with respect to  $\{u|_{i=T}, u|_{i=F}\}$ . Since we only have positive predicate expressions,  $u|_{i=T}$  must evaluate to true against *A*' and therefore evaluates to true against *A* as well. On the other hand,  $u|_{i=F}$  must evaluate to false against *A* as well. Therefore, *A* is dynamic with respect to  $\{u|_{i=T}, u|_{i=F}\}$ , and a contradiction is reached.

The reasoning is basically the same if *A* is an OR node. Based on Algorithm 2, we see that BESTD(*A*, *i*) returns only valuations which do not satisfy any one of *A*'s complete children on step *i*, meaning all of *A*'s complete children are statically false with respect to BESTD(*A*, *i*). Based on Property 8,  $D_i$  must be a subset of BESTD(*A*, *i*), and Corollary 1 states that  $\Gamma(v, i) \subseteq D_i$ . Since,  $\{u|_{i=T}, u|_{i=F}\} \subseteq \Gamma(v, i)$ , all of *A*'s complete children must also be statically false with respect to  $\{u|_{i=T}, u|_{i=F}\}$ . Based on Lemma 17, for all  $v \in D_i$ , there must exist a  $u \in \Gamma(v, i)$  such that all incomplete children of *A* except *A*' are statically false with respect to  $\{u|_{i=T}, u|_{i=F}\}$ . In other words, for this *u*, all children except *A*' are statically false with respect to  $\{u|_{i=T}, u|_{i=F}\}$ . Since we only have positive predicate expressions,  $u|_{i=T}$  must evaluate to true against *A*' and also against *A*. On the other hand,  $u|_{i=F}$  evaluates to false against *A*' and must also evaluate to false against *A*. Therefore, *A* is dynamic with respect to  $\{u|_{i=T}, u|_{i=F}\}$  and a contradiction is reached.

**Property 8.** Let node node be a node in the predicate tree. For any step index i:

$$BestD(node, i) \subseteq BestD(parent(node), i)$$

This property is easy to see since BestD(node, i) only ever removes sets from BestD(parent(node), i) (by intersection or sub subtraction) and never adds any sets.

#### E.3.4 Proof of Lemma 4

**Lemma 4.** Given any ordering of predicates for a predicate expression of depth 2 or less, if node node of the associated predicate tree is the child of an AND node and negatively determinable, then node must be complete. Similarly, if node is the child of an OR node and positively determinable, then node must be complete.

*Proof.* We prove this by case analysis on the type of node.

- 1. If node is a leaf node, the conditions for being complete are the same as the conditions for being positively and negatively determinable, so the lemma is true.
- 2. If node is the child of an AND node, it must be an OR node (leaf nodes go to the first case). As an OR node, if node is negatively determinable, each child of node must also be negatively determinable by definition. However, the entire predicate tree has a maximum depth of 2, so all of node's children must be leaf nodes. All leaf nodes which are negatively determinable are also complete, so node must also be complete.
- 3. If node is the child of an OR node and positively determinable, the reasoning is the same as when node is the child of AND node and negatively determinable. As an AND node, if node is positively determinable, each child of node must also be positively determinable by definition. However, the entire predicate tree has a maximum depth of 2, so all of node's children must be leaf nodes. All leaf nodes which are positively determinable are also complete, so node must also be complete.

#### E.3.5 Proof of Lemma 5

**Lemma 5.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-leaf node in the associated predicate tree. For all pairs of node's predicate descendants  $P_i$  and  $P_j$  for which i < j:

$$BestD(parent(node), j) \subseteq BestD(parent(node), i)$$

*Proof.* We prove this by performing induction over the maximum value that j can be (i.e.,  $j_{\text{max}} \ge j$ ). The base case occurs when  $j_{\text{max}} = 2$ . Since both  $P_i$  an  $P_j$  are descendants of node, there can be no positively or negatively determinable children along node's ancestors. Thus, BESTD(parent(node), 1) = BESTD(parent(node), 2) = {T, F}<sup>n</sup>, and the lemma is satisfied.

As the inductive hypothesis, assume the lemma holds for  $j_{max} = k$ . For the inductive step,  $j_{max} = k+1$ . Let us assume that  $P_j = P_{k+1}$  is a descendant of node. Otherwise, the lemma is trivially true based on the inductive hypothesis. Furthermore, assume that i = r(node, j). Due to the monotonicity of  $\subseteq$ , if the lemma holds for i = r(node, j), then the lemma holds for all i < j.

We prove the case for  $j_{\text{max}} = k + 1$  by induction over the distance of node from the root node (henceforth referred to as the "inner" induction). For the base case of the inner induction, node is the root node. In this case, BESTD(parent(node), i) = BESTD(parent(node), j) = {T, F}<sup>n</sup> for all i and j, so the lemma is satisfied. Next, we assume as the inner inductive hypothesis that the lemma holds for when node is k distance away from the root node. For the inner inductive step, we assume node is k + 1 distance away from the root node.

If node's parent is an AND node, based on Algorithm 2, we can expand BESTD(parent(node), *j*) as:

$$BESTD(parent(node), j) = BESTD(parent(parent(node)), j)$$
  

$$\cap \left( \left( \bigcap_{c^{\circ} \in children^{\circ}(parent(node), j)} state_{j}[c^{\circ}].cmp \right) \setminus \left( \bigcup_{c^{-} \in children^{-}(parent(node), j) \setminus \{node\}} state_{j}[c^{-}].det^{-} \right) \right)$$
(7)

For any sets *A*, *B*, and *C* it is trivially true that  $A \supseteq A \cap (B \setminus C)$ . Thus:

$$BestD(parent(node), i) \supseteq BestD(parent(node), i)$$

$$\cap \left( \bigcap_{c^{\circ} \in \text{children}^{\circ}(\text{parent}(\text{node}), j)} \text{state}_{j}[c^{\circ}].\text{cmp} \setminus \text{state}_{j}[c^{\circ}].\text{det}^{-} \right) \\ \setminus \left( \bigcup_{c^{-} \in \text{children}^{-}(\text{parent}(\text{node}), j) \setminus \{\text{node}\}} \text{state}_{j}[c^{-}].\text{det}^{-} \right)$$

We show that the right-hand side of this equation is a superset of BESTD(parent(node), *j*), completing

the proof for the AND case. We start by expanding BESTD(parent(node), *i*) according to Algorithm 2:

$$BestD(parent(node), i) \supseteq BestD(parent(parent(node)), i)$$

$$\cap \left( \left( \bigcap_{c^{\circ} \in \text{children}^{\circ}(\text{parent}(\text{node}),i)} \text{state}_{i}[c^{\circ}].\text{cmp} \right) \setminus \left( \bigcup_{c^{-} \in \text{children}^{-}(\text{parent}(\text{node}),i) \setminus \{\text{node}\}} \text{state}_{i}[c^{-}].\text{det}^{-} \right) \right) \\ \cap \left( \bigcap_{c^{\circ} \in \text{children}^{\circ}(\text{parent}(\text{node}),j)} \text{state}_{j}[c^{\circ}].\text{cmp} \setminus \text{state}_{j}[c^{\circ}].\text{det}^{-} \right) \\ \setminus \left( \bigcup_{c^{-} \in \text{children}^{-}(\text{parent}(\text{node}),j) \setminus \{\text{node}\}} \text{state}_{j}[c^{-}].\text{det}^{-} \right) \right)$$

We can use the identity  $(A \setminus B) \cap (C \setminus D) = (A \cap C) \setminus (B \cup D)$  for all sets *A*, *B*, *C*, and *D* (Appendix F) to rearrange:

 $BestD(parent(node), i) \supseteq BestD(parent(parent(node)), i)$ 

1

$$\cap \left( \bigcap_{c^{\circ} \in \text{children}^{\circ}(\text{parent}(\text{node}),i)} \text{state}_{i}[c^{\circ}].\text{cmp}} \bigcap_{c^{\circ'} \in \text{children}^{\circ}(\text{parent}(\text{node}),j)} \text{state}_{j}[c^{\circ'}].\text{cmp}} \right) \\ \setminus \left( \left( \bigcup_{c^{-} \in \text{children}^{-}(\text{parent}(\text{node}),i) \setminus \{\text{node}\}} \text{state}_{i}[c^{-}].\text{det}^{-} \right) \right) \\ \cup \left( \bigcup_{c^{-\prime} \in (\text{children}^{-}(\text{parent}(\text{node}),j) \cup \text{children}^{\circ}(\text{parent}(\text{node}),j) \setminus \{\text{node}\})} \text{state}_{j}[c^{-\prime'}].\text{det}^{-} \right) \right)$$

Since j > i, the set of complete children at step j must be a superset of the complete children at step *i* (children°(parent(node), *j*)  $\supseteq$  children°(parent(node), *i*)). Furthermore, based on the Property 5, the cmp values of these complete children do not change, so the second line can be simplified:

$$BestD(parent(node), i) \supseteq BestD(parent(parent(node)), i) \cap \left( \bigcap_{c^{\circ} \in children^{\circ}(parent(node), j)} state_{j}[c^{\circ}].cmp \right)$$
$$\setminus \left( \left( \bigcup_{c^{-} \in children^{-}(parent(node), i) \setminus \{node\}} state_{i}[c^{-}].det^{-} \right) \right)$$
$$\cup \left( \bigcup_{c^{-\prime} \in (children^{-}(parent(node), j) \cup children^{\circ}(parent(node), j) \setminus \{node\})} state_{j}[c^{-\prime}].det^{-} \right) \right)$$
(8)

Next, the set of negatively determinable children at step *j* must be also superset of the negatively determinable children at step i. Some of these children may have graduated to also becoming complete, but the union in the third line is also over complete children. For each of these negatively determinable children, we apply Lemma 11<sup>8</sup> (shown below):

$$state_i[c^-].det^- \supseteq state_i[c^-].det^- \cap BestD(parent(parent(node)), r(c^-, j))$$
 (9)

<sup>&</sup>lt;sup>8</sup>To apply Lemma 11 to Equation 9, Lemma 5 must hold true up until (j - 1)th step. The inductive hypothesis applies in this case, so there is no cyclical dependency.

By the inner inductive hypothesis, BESTD(parent(parent(node)), i)  $\subseteq$  BESTD(parent(parent(node)),  $r(c^-, j)$ ). Using the identity that  $A \setminus B = A \setminus (B \cap A)$  for any sets A and B (Appendix F), we move a copy of the BESTD(parent(node)), i) term in Equation 8 inward and intersect with state<sub>i</sub>[ $c^-$ ].det<sup>-</sup> to reduce to:

 $BestD(parent(node), i) \supseteq BestD(parent(parent(node)), i)$ 

$$\cap \left( \bigcap_{c^{\circ} \in \text{children}^{\circ}(\text{parent}(\text{node}), j)} \text{state}_{j}[c^{\circ}].\text{cmp} \right) \\ \setminus \left( \bigcup_{c^{-} \in (\text{children}^{-}(\text{parent}(\text{node}), j) \cup \text{children}^{\circ}(\text{parent}(\text{node}), j) \setminus \{\text{node}\})} \text{state}_{j}[c^{-}].\text{det}^{-} \right)$$

Using Property 6's mutual exclusivity once again, we can get rid of the det<sup>-</sup> values of complete children:

$$BestD(parent(node), i) \supseteq BestD(parent(parent(node)), i)$$

$$\cap \left( \bigcap_{c^{\circ} \in \text{children}^{\circ}(\text{parent}(\text{node}), j)} \text{state}_{j}[c^{\circ}].\text{cmp} \right) \\ \setminus \left( \bigcup_{c^{-} \in \text{children}^{-}(\text{parent}(\text{node}), j) \setminus \{\text{node}\}} \text{state}_{j}[c^{-}].\text{det}^{-} \right)$$

At this point, we can take the intersection of BestD(parent(node)), j) to both sides and apply the inner inductive hypothesis which states that:

$$BestD(parent(parent(node)), j) \subseteq BestD(parent(parent(node)), i)$$

We end up with:

 $BestD(parent(node), i) \cap BestD(parent(parent(node)), j) \supseteq BestD(parent(parent(node)), j)$ 

$$\cap \left( \bigcap_{c^{\circ} \in \operatorname{children}^{\circ}(\operatorname{parent}(\operatorname{node}), j)} \operatorname{state}_{j}[c^{\circ}].\operatorname{cmp} \right) \\ \setminus \left( \bigcup_{c^{-} \in \operatorname{children}^{-}(\operatorname{parent}(\operatorname{node}), j) \setminus \{\operatorname{node}\}} \operatorname{state}_{j}[c^{-}].\operatorname{det}^{-} \right)$$

Note that the right-hand side of this equation is equivalent to Equation 7. Thus:

 $BestD(parent(node), i) \supseteq BestD(parent(node), j)$ 

**Lemma 11.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let node be a nonroot node in the associated predicate tree. If node's parent is an OR node, node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

 $state_{i+1}[node].det^+ \supseteq state_i[node].det^+ \cap BestD(parent(parent(node)), r(node, i + 1))$ 

If node's parent is an AND node, node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

 $state_{i+1}[node].det \supseteq state_{i}[node].det \cap BestD(parent(parent(node)), r(node, i + 1))$ 

If node's parent is an OR node, based on Algorithm 2, we can expand BestD(parent(node), j) as:

BESTD(parent(node), *j*) = BESTD(parent(parent(node)), *j*)

$$\setminus \left( \left( \bigcup_{c^{\circ} \in \text{children}^{\circ}(\text{parent(node)}, j)} \text{state}_{j}[c^{\circ}].\text{cmp} \right) \cup \left( \bigcup_{c^{+} \in \text{children}^{+}(\text{parent(node)}, j) \setminus \{\text{node}\}} \text{state}_{j}[c^{+}].\text{det}^{+} \right) \right)$$

Property 7 allows us to convert the cmp values of complete children into  $det^+$ , so this can be rewritten as:

$$BestD(parent(node), j) = BestD(parent(parent(node)), j) \\ \left( \bigcup_{c \in (children^{\circ}(parent(node), j) \cup children^{+}(parent(node), j) \setminus \{node\})} state_{j}[c].det^{+} \right)$$
(10)

For any sets *A* and *B* it is trivially true that  $A \supseteq A \setminus B$ . Thus:

 $BestD(parent(node), i) \supseteq BestD(parent(node), i)$ 

$$\left(\bigcup_{c \in (\text{children}^{\circ}(\text{parent}(\text{node}), j) \cup \text{children}^{+}(\text{parent}(\text{node}), j) \setminus \{\text{node}\})} \text{state}_{j}[c].\text{det}^{+}\right)$$

We once again show that the right-hand side of this equation is a superset of BestD(parent(node), j), completing the proof for the OR case. We start by expanding BestD(parent(node), i) according to Algorithm 2:

 $BestD(parent(node), i) \supseteq BestD(parent(parent(node)), i)$ 

$$\setminus \left( \left( \bigcup_{c \in (\text{children}^{\circ}(\text{parent}(\text{node}), j) \cup \text{children}^{+}(\text{parent}(\text{node}), j) \setminus \{\text{node}\})} \text{state}_{j}[c].\text{det}^{+} \right) \\ \cup \left( \bigcup_{c^{\circ} \in \text{children}^{\circ}(\text{parent}(\text{node}), i)} \text{state}_{i}[c^{\circ}].\text{cmp}} \bigcup_{c^{+} \in \text{children}^{+}(\text{parent}(\text{node}), i) \setminus \{\text{node}\}} \text{state}_{i}[c^{+}].\text{det}^{+} \right) \right)$$

We use Property 7 again to convert all cmp values to det<sup>-</sup>:

 $BestD(parent(node), i) \supseteq BestD(parent(parent(node)), i) \\ \setminus \left( \left( \bigcup_{c \in (children^{\circ}(parent(node), j) \cup children^{+}(parent(node), j) \setminus \{node\})} state_{j}[c].det^{+} \right) \\ \cup \left( \bigcup_{c' \in (children^{\circ}(parent(node), i) \cup children^{+}(parent(node), i) \setminus \{node\})} state_{i}[c'].det^{+} \right) \right)$ (11)

Since j > i, the set of complete and positively determinable children at step j must be a superset of the complete and positively determinable children at step i. Furthermore, Lemma 11 states if c is a positively determinable child of an OR node:

$$state_j[c].det^* \supseteq state_i[c].det^* \cap BestD(parent(parent(node)), r(c, j))$$

Using the inner inductive hypothesis once again, Equation 11 simplifies to:

$$BestD(parent(node), i) \supseteq BestD(parent(parent(node)), i) \\ \setminus \left( \bigcup_{c \in (children^{\circ}(parent(node), j) \cup children^{+}(parent(node), j) \setminus \{node\})} state_{j}[c].det^{+} \right)$$

At this point, we can take the intersection of BESTD(parent(node)), *j*) to both sides and apply the inner inductive hypothesis which states that:

$$BestD(parent(node)), j) \subseteq BestD(parent(parent(node)), i)$$

We end up with:

$$BestD(parent(node), i) \cap BestD(parent(parent(node)), j) \supseteq BestD(parent(parent(node)), j)$$

$$\left(\bigcup_{c \in (\text{children}^{\circ}(\text{parent}(\text{node}), j) \cup \text{children}^{+}(\text{parent}(\text{node}), j) \setminus \{\text{node}\})} \text{state}_{j}[c].\text{det}^{+}\right)$$

Note that the right-hand side of this equation is equivalent to Equation 10. Thus:

$$BESTD(parent(node), i) \supseteq BESTD(parent(node), j)$$

## E.3.6 Proof of Lemma 6

**Lemma 6.** For any sets A, B, C, D, E, and F, if  $F \subseteq B$  and  $F \cap C = \emptyset$ , then:

$$A \cup (B \setminus C) \cup (D \setminus (E \cup F)) = A \cup (B \setminus C) \cup (D \setminus E)$$

*Proof.* Here, *A* is a common term on the outside, so it is sufficient to prove  $(B \setminus C) \cup (D \setminus (E \cup F)) = (B \setminus C) \cup (D \setminus E)$ .

$$(B \setminus C) \cup (D \setminus (E \cup F)) = ((B \setminus C) \cup D) \setminus ((E \cup F) \setminus (B \setminus C))$$
$$= ((B \setminus C) \cup D) \setminus ((E \setminus (B \setminus C)) \cup (F \setminus (B \setminus C)))$$
$$= ((B \setminus C) \cup D) \setminus ((E \setminus (B \setminus C)) \cup ((F \cap C) \cup (F \setminus B)))$$
$$= ((B \setminus C) \cup D) \setminus ((E \setminus (B \setminus C)) \cup (\emptyset \cup \emptyset))$$
$$= ((B \setminus C) \cup D) \setminus (E \setminus (B \setminus C))$$
$$= (B \setminus C) \cup (D \setminus E)$$

The first, second, and third steps use the following identities respectively (Appendix F). For any sets *A*, *B*, and *C*:

$$A \cup (B \setminus C) = (A \cup B) \setminus (C \setminus A)$$
  
(A \ (B \ C) = (A \ B) \ (C \ A)  
(A \ (B \ C) = (A \ B) \ (A \ C)

The fourth step uses the assumptions  $B \supseteq F$  and  $F \cap C = \emptyset$ . The last step uses the same identity as the first step in reverse.

### E.3.7 Proof of Lemma 7

**Lemma 7.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a node in the associated predicate tree. For any step index i:

$$\mathsf{state}_i[\mathsf{node}].\mathsf{det}^+ \subseteq \mathsf{ref}_\mathsf{node}$$

*Proof.* We prove this by strong induction on the height of the tree referred to by node. As the base case, let node be a leaf node which refers to predicate  $P_i$ . The variable state[node].det<sup>+</sup> is initially set to the empty set, and until  $P_i$  is positively determinable, the lemma is trivially true. Once node is positively determinable, state[node].det<sup>+</sup> is updated with  $P_i(D_i)$ . By definition ref<sub>node</sub> =  $P_i({T, F}^n)$ , and the largest  $D_i$  can be is  ${T, F}^n$ . As a result, the lemma holds even when node is positively determinable.

As the inductive hypothesis, assume that the lemma holds for all predicate tree nodes of height k or less. If node has a height of k + 1, node must either be an AND or OR node. Once again if node is not positively determinable, then the lemma holds trivially. Thus, we assume node is positively determinable on step i.

If node is an AND node, based on the definition of ref<sub>node</sub>:

$$ref_{node} = \bigcap_{c \in children(node)} ref_c$$

By the inductive hypothesis, for any child *c* of node and any step index *i*,  $ref_c \supseteq state_i[c].det^+$ , so:

$$ref_{node} \supseteq \bigcap_{c \in children(node)} state_i[c].det^+$$
$$\supseteq \bigcap_{c \in children(node)} state_i[c].det^+ \cap BestD(parent(node), r(node, i))$$

Recall that r(node, i) is the largest index among node's predicate descendants that is smaller than i; in other words, r(node, i) is the last time node was updated before step i. By definition if node is an AND node and positively determinable, all of it children must also be positively determinable. Then, by Algorithm 3:

$$\mathsf{state}_i[\mathsf{node}].\mathsf{det}^* = \bigcap_{c \in \mathsf{children}(\mathsf{node})} \mathsf{state}_i[c].\mathsf{det}^* \cap \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), r(\mathsf{node}, i))$$

Thus,  $ref_{node} \supseteq state_i [node].det^+$  for any step *i*.

If node is an OR node, based on the definition of ref<sub>node</sub>:

$$ref_{node} = \bigcup_{c \in children(node)} ref_c$$

By the inductive hypothesis, for any child *c* of node and any step index *i*,  $ref_c \supseteq state_i[c].det^+$ , so:

$$\begin{aligned} \mathsf{ref}_{\mathsf{node}} &\supseteq \bigcup_{c \in \mathsf{children}(\mathsf{node})} \mathsf{state}_i[c].\mathsf{det}^+ \\ &\supseteq \bigcup_{c^+ \in \mathsf{children}^+(\mathsf{node},i)} \mathsf{state}_i[c^+].\mathsf{det}^+ \\ &\supseteq \bigcup_{c^+ \in \mathsf{children}^+(\mathsf{node},i)} \mathsf{state}_i[c^+].\mathsf{det}^+ \cap \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), r(\mathsf{node}, i)) \end{aligned}$$

The second step is valid because the set of positively determinable children will be at most the set of all children. By Algorithm 3:

 $\texttt{state}_i[\texttt{node}].\texttt{det}^{+} = \bigcup_{c^+ \in \texttt{children}^+(\texttt{node},i)} \texttt{state}[c^+].\texttt{det}^+ \cap \texttt{BestD}(\texttt{parent}(\texttt{node}), r(\texttt{node},i))$ 

Thus,  $ref_{node} \supseteq state_i [node].det^+$  for any step *i*.

### E.3.8 Proof of Lemma 8

**Lemma 8.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-leaf node in the associated predicate tree. Furthermore, Let c and c' be two different children of node. If node is an OR node, for all step indices i and j:

$$\mathsf{state}_i[c].\mathsf{det}^+ \cap \mathsf{state}_i[c'].\mathsf{det}^+ = \emptyset$$

If node is an AND node, then for all step indices i and j:

 $state_i[c].det \cap state_i[c'].det = \emptyset$ 

*Proof.* This is just the non-conditional form of Lemma 15. The proof for Lemma 15 depends on Lemma 5 and Lemma 14. Since we have already shown Lemma 5 to be true for any node in the predicate tree, Lemma 14 must apply to predicate tree nodes of all height, and Lemma 15 must apply to all step indices as well, giving us this non-conditional form.

E.3.9 Proof of Lemma 9

**Lemma 9.** Given a predicate expression with n unique predicates, let  $[(P_1, D_1), ..., (P_m, D_m)]$  be a solution sequence, for which m > n. If step indices i and j are the first two times that predicate P appears in such a sequence (i.e.,  $P_i = P_j = P$ ) and  $D_i \cap D_j = \emptyset$ , then either  $D_j$  can be derived directly from  $U_{i-1}$  without using P as an operator, or  $D_j$  cannot be derived at all from  $U_{i-1} \cup \{P(D_i)\}$  without using P as an operator.

*Proof.* We prove Lemma 9 by showing that if  $D_j \cap D_i = \emptyset$ , all valuation sets  $D_j$  which can be derived from  $U_{i-1} \cup \{P(D_i)\}$  without using P as an operator can also be constructed from  $U_{i-1}$  without using P as an operator. We do this by applying the identity  $A = (A \setminus B) \cup (A \cap B)$  for any sets A and B (Appendix F):

$$D_j = (D_j \setminus D_i) \cup (D_j \cap D_i)$$
$$= (D_j \setminus D_i) \cup \emptyset$$
$$= D_i \setminus D_i$$

The second step comes from the precondition. Lemma 16 (shown below) states that there must exist some  $D'_j$  derived from  $U_{i-1}$  without using P as an operator such that  $D_j \setminus D_i = D'_j \setminus D_i$ . Since  $D_j = D'_j \setminus D_i$ ,  $D_j$  can also be derived from  $U_{i-1}$  without using P as an operator.

**Lemma 16.** For any set of valuation sets **D**, predicate *P*, and any  $D \in \mathbf{D}$ , let *E* be some valuation set derived from  $\mathbf{D} \cup \{P(D)\}$  without using *P* as an operator. There exists a valuation set *E'* derived from **D** without using *P* as an operator, such that:

$$E \setminus D = E' \setminus D$$

### E.3.10 Proof of Lemma 10

**Lemma 10.** Given a predicate expression and a DFS ordering of its predicates, if node node of the associated predicate tree is the child of an AND node and negatively determinable on the ith step, then node must also be complete on the ith step. Similarly, if node is the child of an OR node and positively determinable on the ith step, then node must also be complete on the ith step.

*Proof.* We prove this by case analysis on the type of node.

- 1. If node is a leaf node, the conditions for being complete are the same as the conditions for being positively and negatively determinable, so the lemma is true.
- 2. If node is the child of an AND node, it must be an OR node (leaf nodes go to the first case). As an OR node, if node is negatively determinable, each child of node must also be negatively determinable by definition. A node can only be negatively determinable if at least one predicate descendant of it has already been applied, so all of node's children must have at least one applied predicate descendant each. However, we have a DFS ordering, so if node's child has one applied predicate descendant, all of its predicate descendants must be applied, marking the child as complete. Since all of node's children are complete, node is also complete.
- 3. If node is the child of an OR node and positively determinable, the reasoning is the same as when node is the child of AND node and negatively determinable. As an AND node, if node is positively determinable, each child of node must also be positively determinable by definition. A node can only be positively determinable if at least one predicate descendant of it has already been applied, so all of node's children must have at least one applied predicate descendant. However, we have a DFS ordering, so if node's child has one applied predicate descendant, all of its predicate descendants must be applied, marking the child as complete. Since all of node's children are complete, node is also complete.

### 

#### E.3.11 Proof of Lemma 11

**Lemma 11.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let node be a nonroot node in the associated predicate tree. If node's parent is an OR node, node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

 $state_{i+1}[node].det^+ \supseteq state_j[node].det^+ \cap BestD(parent(parent(node)), r(node, i + 1))$ 

If node's parent is an AND node, node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

 $state_{i+1}[node].det^{-} \supseteq state_{i}[node].det^{-} \cap BestD(parent(parent(node)), r(node, i + 1))$ 

Proof. We break the proof up into two parts. First, we claim that:

**Lemma 12.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-root node in the associated predicate tree. If node's parent is an OR node, node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}[node].det^* \supseteq state_i[node].det^* \cap BestD(parent(parent(node)), r(node, i + 1))$ 

If node's parent is an AND node, node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}$ [node].det<sup>-</sup>  $\supseteq$  state<sub>i</sub>[node].det<sup>-</sup>  $\cap$  *BestD*(parent(parent(node)), r(node, i + 1))

Note that the difference between Lemma 12 and Lemma 11 is that Lemma 12 only applies between consecutive steps *i* and *i* + 1. Once Lemma 12 has been shown to be true, we can show by strong induction on *j* that the lemma is true for all  $j \le i$ . Assume as the base case j = 1. This case is trivially satisfied because  $state_1[node] = \emptyset$  for any node based on initialization. Next, assume as the inductive hypothesis, the lemma holds for when j = k. For the inductive step, j = k + 1. For all  $r(node, i + 1) < j \le i$ , state[node] is not updated. Hence  $state_j[node] = state_i[node]$  for these *j*, and by Lemma 12, if node's parent is an OR node:

 $state_{i+1}$ [node].det<sup>+</sup>  $\supseteq$  state<sub>i</sub>[node].det<sup>+</sup>  $\cap$  BESTD(parent(parent(node)), r(node, i + 1)) (12)

The inductive hypothesis states that for all  $j \le r(\text{node}, i + 1)$ :

 $state_{r(node,i+1)+1}$ [node].det<sup>+</sup>  $\supseteq$  state<sub>i</sub>[node].det<sup>+</sup>  $\cap$  BestD(parent(parent(node)), r(node, r(node, i+1)))

Intersecting both sides with BestD(parent(parent(node)), r(node, i + 1)) and applying Lemma 5 yields:

 $state_{r(node,i+1)+1}[node].det^{+} \cap BestD(parent(parent(node)), r(node, i + 1))$  $\supseteq state_{i}[node].det^{+} \cap BestD(parent(parent(node)), r(node, i + 1))$ 

The left-hand side of this equation is one of the cases of the right-hand side of Equation 12. Thus, for all  $j \le i$ :

 $state_{i+1}[node].det^{+}i + 1)) \supseteq state_{j}[node].det^{+} \cap BestD(parent(parent(node)), r(node, i + 1))$ 

The exact same reasoning applies to det<sup>-</sup> if node's parent is an AND node.

### E.3.12 Proof of Lemma 12

**Lemma 12.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-root node in the associated predicate tree. If node's parent is an OR node, node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}[node].det^+ \supseteq state_i[node].det^+ \cap BestD(parent(parent(node)), r(node, i + 1))$ 

If node's parent is an AND node, node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}[node].det^{-} \supseteq state_{i}[node].det^{-} \cap BestD(parent(parent(node)), r(node, i + 1))$ 

*Proof.* Let us assume that node is positively or negatively determinable on step *i* if node's parent is an OR or AND node respectively. Otherwise,  $state_i[node].det^+ = state_i[node].det^- = \emptyset$  from initialization, and the lemma is satisfied trivially.

Next, we introduce Lemma 13.

**Lemma 13.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a node in the associated predicate tree. If node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

 $state_{i+1}[node].det^+ \supseteq state_i[node].det^+ \cap BestD(parent(node), r(node, i + 1))$ 

If node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

 $state_{i+1}[node].det^{-} \supseteq state_{j}[node].det^{-} \cap BestD(parent(node), r(node, i + 1))$ 

Note that the relationship in Lemma 13 refers to just the parent of node, whereas Lemma 12 refers to the grandparent of node.

If node's parent is an OR node, based on Lemma 13:

 $state_{i+1}[node].det^+ \supseteq state_i[node].det^+ \cap BestD(parent(node), r(node, i + 1))$ 

Expanding out BESTD based on Algorithm 2 gives us:

 $state_{i+1}[node].det^+ \supseteq state_i[node].det^+ \cap BestD(parent(parent(node)), r(node, i + 1))$ 

$$\setminus \left( \left( \bigcup_{c^{\circ} \in \text{children}^{\circ}(\text{parent(node)}, r(\text{node}, i+1))} \text{state}_{r(\text{node}, i+1)} [c^{\circ}].\text{cmp} \right) \\ \cup \left( \bigcup_{c^{+} \in \text{children}^{+}(\text{parent(node)}, r(\text{node}, i+1)) \setminus \{\text{node}\}} \text{state}_{r(\text{node}, i+1)} [c^{+}].\text{det}^{+} \right) \right)$$

Property 7 states that  $state_i[c^\circ]$ .cmp =  $state_i[c^\circ]$ .det<sup>+</sup> for all complete children  $c^\circ$ , so:

$$state_{i+1}[node].det^+ \supseteq state_i[node].det^+ \cap BestD(parent(parent(node)), r(node, i + 1))$$

$$\left(\bigcup_{c^{+} \in (\text{children}^{\circ}(\text{parent(node}), r(\text{node}, i+1)) \cup \text{children}^{+}(\text{parent(node}), r(\text{node}, i+1)) \setminus \{\text{node}\})} \text{state}_{r(\text{node}, i+1)} [c^{+}].\text{det}^{+}\right)$$

Lemma 15 (a conditional version of Lemma 8; shown below) states for two different nodes c and c', state[c].det<sup>+</sup> and state[c'].det<sup>+</sup> are mutually exclusive. Thus, all set subtraction terms can be removed, and:

 $state_{i+1}[node].det^+ \supseteq state_i[node].det^+ \cap BestD(parent(parent(node)), r(node, i + 1))$ 

**Lemma 15.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-leaf node in the associated predicate tree. Furthermore, Let c and c' be two different children of node. If node is an OR node, Lemma 5 holds true up to step  $j_{max}$ , and Lemma 14 holds true up to node's children, then for all steps i and j such that  $max(i, j) \leq j_{max}$ :

 $state_i[c].det^+ \cap state_i[c'].det^+ = \emptyset$ 

If node is an AND node, Lemma 5 holds true up to step  $j_{max}$ , and Lemma 14 holds true up to node's children, then for all steps i and j such that  $max(i, j) \le j_{max}$ :

 $state_i[c].det \cap state_i[c'].det = \emptyset$ 

If node's parent is an AND node, based on Lemma 13:

 $state_{i+1}[node].det^{-} \supseteq state_{i}[node].det^{-} \cap BestD(parent(node), r(node, i + 1))$  (13)

Expanding out BESTD based on Algorithm 2 gives us:

 $state_{i+1}[node].det^{-} \supseteq state_{i}[node].det^{-} \cap BestD(parent(parent(node)), r(node, i + 1))$ 

$$\cap \left( \bigcap_{c^{\circ} \in \text{children}^{\circ}(\text{parent}(\text{node},i+1))} \text{state}_{r(\text{node},i+1)} [c^{\circ}].\text{cmp} \right) \\ \setminus \left( \bigcup_{c^{-} \in \text{children}^{-}(\text{parent}(\text{node}),r(\text{node},i+1)) \setminus \{\text{node}\}} \text{state}_{r(\text{node},i+1)} [c^{-}].\text{det}^{-} \right)$$

Lemma 15 states that the det<sup>-</sup> values of two different node must also be mutually exclusive. Thus, all set subtraction terms can be removed once again:

$$state_{i+1}[node].det^{-} \supseteq state_{i}[node].det^{-} \cap BestD(parent(parent(node)), r(node, i + 1))$$
$$\cap \left( \bigcap_{\substack{c^{\circ} \in children^{\circ}(parent(node), r(node, i + 1))}} state_{r(node, i + 1)}[c^{\circ}].cmp \right) (14)$$

At this point, we establish the following relationships thanks to Algorithm 3:

 $\begin{aligned} & \texttt{state}_i[\texttt{node}].\texttt{det}^- \subseteq \texttt{BestD}(\texttt{node}, r(\texttt{node}, i)) \\ & \texttt{state}_{r(\texttt{node}, i+1)}[c^\circ].\texttt{cmp} \subseteq \texttt{BestD}(\texttt{node}, r(c^\circ, r(\texttt{node}, i+1))) \end{aligned}$ 

If  $r(\text{node}, i) < r(c^\circ, r(\text{node}, i + 1))$  (meaning a predicate descendant of  $c^\circ$  was applied more recently than one of node), as part of calculating BESTD, the det<sup>-</sup> values of all negatively determinable children are subtracted away. As such, node must have been one of these children:

 $state_{r(node,i+1)}[c^{\circ}].cmp \subseteq BestD(node, r(c^{\circ}, r(node, i+1))) \setminus state_{r(c^{\circ}, r(node, i+1))}[node].det^{-1}$ 

Since  $r(\text{node}, i) < r(c^{\circ}, r(\text{node}, i+1))$ , state<sub> $r(c^{\circ}, r(\text{node}, i+1))$ </sub> [node] = state<sub>i</sub> [node], thus state<sub>i</sub> [ $c^{\circ}$ ].cmp must be mutually exclusive with state<sub>i</sub> [node].det<sup>-</sup>.

On the other hand, if  $r(\text{node}, i) > r(c^\circ, r(\text{node}, i+1))$  (meaning a predicate descendant of node was applied more recently than one of  $c^\circ$ ), as part of calculating BESTD, an intersection with the cmp values of all complete children is performed. Since  $r(\text{node}, i) > r(c^\circ, r(\text{node}, i+1))$ ,  $c^\circ$  must have be one of these children:

 $\mathsf{state}_i[\mathsf{node}].\mathsf{det}^- \subseteq \mathsf{BestD}(\mathsf{node}, r(\mathsf{node}, i)) \cap \mathsf{state}_{r(\mathsf{node}, i)}[c^\circ].\mathsf{cmp}$ 

Since  $r(\text{node}, i) > r(c^{\circ}, r(\text{node}, i + 1))$ ,  $\text{state}_{r(\text{node}, i)}[c^{\circ}] = \text{state}_{i}[c^{\circ}]$ , thus  $\text{state}_{i}[\text{node}].\text{det}^{-} \subseteq \text{state}_{i}[c^{\circ}]$ .

If the first case is true for any complete child node in Equation 14, then the right-hand side simplifies to the empty set, and the lemma is trivially true. If all complete children  $c^{\circ}$  of belong to the second case, then state<sub>i</sub>[node].det<sup>-</sup> is a subset of that intersection, and Equation 14 simplifies to:

 $state_{i+1}[node].det^{-} \supseteq state_{i}[node].det^{-} \cap BestD(parent(parent(node)), r(node, i))$ 

#### E.3.13 Proof of Lemma 13

**Lemma 13.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a node in the associated predicate tree. If node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

 $state_{i+1}[node].det^+ \supseteq state_i[node].det^+ \cap BestD(parent(node), r(node, i + 1))$ 

If node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then for all  $j \le i$ :

 $state_{i+1}$ [node].det<sup>-</sup>  $\supseteq$  state<sub>i</sub>[node].det<sup>-</sup>  $\cap$  *BestD*(parent(node), r(node, i + 1))

Proof. Similar to the proof for Lemma 11, this proof is divided into two parts. First, we present:

**Lemma 14.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a node in the associated predicate tree. If node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}[node].det^+ \supseteq state_i[node].det^+ \cap BestD(parent(node), r(node, i + 1))$ 

If node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}[node].det^{-} \supseteq state_{i}[node].det^{-} \cap BestD(parent(node), r(node, i + 1))$ 

Similar to before, the difference between Lemma 14 and Lemma 13 is that Lemma 14 only applies between consecutive steps *i* and *i* + 1. Once Lemma 14 has shown to be true, we can show by strong induction on *j* that the lemma is true for all  $j \le i$ . Assume as the base case j = 1. This case is trivially satisfied since state<sub>1</sub>[node] =  $\emptyset$  for any node based on initialization. Next, assume as the inductive hypothesis, the lemma holds for when j = k. For the inductive step, j = k + 1. For all  $r(node, i+1) < j \le i$ , state[node] is not updated. Hence state<sub>*i*</sub>[node] = state<sub>*i*</sub>[node] for these *j*, and by Lemma 14:

 $state_{i+1}[node].det^{+} \supseteq state_{i}[node].det^{+} \cap BestD(parent(node), r(node, i + 1))$  (15)

The inductive hypothesis states that for all  $j \le r(\text{node}, i + 1)$ :

 $state_{r(node, i+1)+1}[node].det^{+} \supseteq state_{i}[node].det^{+} \cap BestD(parent(node), r(node, r(node, i+1)))$ 

Intersecting both sides with BESTD(parent(node), r(node, i + 1)) and applying Lemma 5 yields:

 $state_{r(node,i+1)+1}[node].det^{+} \cap BestD(parent(node), r(node, i + 1))$  $\supseteq state_{i}[node].det^{+} \cap BestD(parent(node), r(node, i + 1))$ 

The left-hand side of this equation is one of the cases of the right-hand side of Equation 15. Thus, for all  $j \leq i$ :

 $state_{i+1}$ [node].det<sup>+</sup>  $\supseteq$  state<sub>i</sub>[node].det<sup>+</sup>  $\cap$  BESTD(parent(node), r(node, i + 1))

The exact same reasoning applies to state[node].det<sup>-</sup>.

#### E.3.14 Proof of Lemma 14

**Lemma 14.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a node in the associated predicate tree. If node is positively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}[node].det^+ \supseteq state_i[node].det^+ \cap BestD(parent(node), r(node, i + 1))$ 

If node is negatively determinable on step i + 1, and Lemma 5 holds true up to step i, then:

 $state_{i+1}$ [node].det<sup>-</sup>  $\supseteq$  state<sub>i</sub>[node].det<sup>-</sup>  $\cap$  *BestD*(parent(node), r(node, i + 1))

*Proof.* We prove this by strong induction on the height of the tree referred to by node. As the base case, let node be a leaf node, which refers to  $P_j$ . A leaf node's det<sup>+</sup> value is only ever updated once (at the time of its completion). If j < i, then  $P_j$  has already been applied. Thus, state<sub>*i*+1</sub>[node] = state<sub>*j*</sub>[node], and the lemma is satisfied. If j = i, then state<sub>*j*</sub>[node].det<sup>+</sup> =  $\emptyset$  because it still holds its initialized state, and the lemma is trivially satisfied.

Assume as the inductive hypothesis that the lemma holds for any node with a height of k. Next, for the inductive step, let node refer to a node with a height of k+1. Let us also assume that  $P_i$  is a descendant of node. Otherwise, node's state will not be updated and  $state_{i+1}[node] = state_i[node]$ , and the lemma is trivially true. Furthermore, we assume that node is positively and negatively determinable on step *i*. Otherwise,  $state_i[node].det^+ = state_i[node].det^- = \emptyset$  based on initialization, and the lemma is trivially satisfied once again.

If node is an AND node and positively determinable, then all of its children must be positively determinable by definition. Based on Algorithm 3:

$$state_{i+1}[node].det^{+} = \bigcap_{c \in children(node)} state_{i+1}[c].det^{+} \cap BestD(parent(node), i)$$
(16)

$$state_{i}[node].det^{+} = \bigcap_{c \in children(node)} state_{i}[c].det^{+} \cap BestD(parent(node), r(node, i))$$
(17)

As stated in the precondition, we assume that Lemma 5 holds up to step *i*. Thus, BESTD(parent(node), *i*)  $\subseteq$  BESTD(parent(node), *r*(node, *i*)), and:

$$\mathsf{state}_i[\mathsf{node}].\mathsf{det}^+ \cap \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), i) = \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), i) \cap \left(\bigcap_{c \in \mathsf{children}(\mathsf{node})} \mathsf{state}_i[c].\mathsf{det}^+\right)$$
(18)

All children of node except  $P_i$ 's ancestor do not have their state values updated between steps *i* and i + 1. For these children state<sub>*i*</sub> = state<sub>*i*+1</sub>. Let  $c^*$  be node's child that is  $P_i$ 's ancestor and let:

$$X = \bigcap_{c \in \text{children(node)} \setminus \{c^*\}} \text{state}_i[c].\text{det}^*$$

We can rewrite Equations 16 and 18 as:

$$state_{i+1}[node].det^{+} = BestD(parent(node), i) \cap X \cap state_{i+1}[c^{*}].det^{+}$$
(19)

 $state_i[node].det^+ \cap BestD(parent(node), i) = BestD(parent(node), i) \cap X \cap state_i[c^*].det^+$  (20)

The inductive hypothesis states that for child  $c^*$ :

$$\mathsf{state}_{i+1}[c^*].\mathsf{det}^* \supseteq \mathsf{state}_i[c^*].\mathsf{det}^* \cap \mathsf{BestD}(\mathsf{node},i)$$

Expanding out BESTD based on Algorithm 2, we get:

$$state_{i+1}[c^*].det^* \supseteq state_i[c^*].det^* \cap BESTD(parent(node), i)$$
$$\cap \left( \left( \bigcap_{c^\circ \in children^\circ(node, i)} state_i[c^\circ].cmp \right) \setminus \left( \bigcup_{c^- \in children^-(node, i) \setminus \{c^*\}} state_i[c^-].det^- \right) \right)$$

If we intersect both sides with  $X \cap BESTD(parent(node), i)$ , the left-hand side is the same as Equation 19. Thus:

$$state_{i+1}[node].det^{+} \supseteq state_{i}[c^{*}].det^{+} \cap BestD(parent(node), i) \cap X$$
$$\cap \left( \left( \bigcap_{c^{\circ} \in children^{\circ}(node, i)} state_{i}[c^{\circ}].cmp \right) \setminus \left( \bigcup_{c^{-} \in children^{-}(node, i) \setminus \{c^{*}\}} state_{i}[c^{-}].det^{-} \right) \right)$$

Property 7 states that state  $[c^{\circ}]$ .cmp = state  $[c^{\circ}]$ .det<sup>+</sup> for all complete children, so these terms can be absorbed into X. Expanding out X leaves us with:

$$state_{i+1}[node].det^{+} \supseteq state_{i}[c^{*}].det^{+} \cap BESTD(parent(node), i) \\ \cap \left( \left( \bigcap_{c \in children(node, i) \setminus \{c^{*}\}} state_{i}[c].det^{+} \right) \setminus \left( \bigcup_{c^{-} \in children^{-}(node, i) \setminus \{c^{*}\}} state_{i}[c^{-}].det^{-} \right) \right)$$

Using the identity  $(A \cap B) \setminus (C \cup D) = (A \setminus C) \cap (B \setminus D)$  for all sets *A*, *B*, *C*, and *D* (Appendix F), we can rearrange this to:

$$state_{i+1}$$
[node].det<sup>+</sup>  $\supseteq$  state<sub>i</sub>[ $c^*$ ].det<sup>+</sup>  $\cap$  BestD(parent(node), i)

$$\cap \left( \bigcap_{c \in \text{children}(\text{node},i) \setminus \{c^*\}} \text{state}_i[c].\text{det}^+ \setminus \text{state}_i[c].\text{det}^- \right)$$

1

Not all children may be negatively determinable, but the det<sup>-</sup> value of those children will be  $\emptyset$  anyway based on initialization. Based on Property 6, the det<sup>+</sup> and det<sup>-</sup> values for any node must mutually exclusive for any time step, so we can remove the set subtraction terms:

$$\texttt{state}_{i+1}[\texttt{node}].\texttt{det}^+ \supseteq \texttt{state}_i[c^*].\texttt{det}^+ \cap \texttt{BestD}(\texttt{parent}(\texttt{node}), i) \cap \left(\bigcap_{c \in \texttt{children}(\texttt{node}, i) \setminus \{c^*\}} \texttt{state}_i[c].\texttt{det}^+\right)$$

The right-hand side of this equation is equivalent to Equation 20, so:

$$state_{i+1}$$
[node].det<sup>+</sup>  $\supseteq$  state<sub>i</sub>[node].det<sup>+</sup>  $\cap$  BESTD(parent(node), i)

If node is an OR node and positively determinable, then based on Algorithm 3:

$$state_{i+1}[node].det^{+} = \bigcup_{c^{+} \in children^{+}(node, i+1)} state_{i+1}[c^{+}].det^{+} \cap BestD(parent(node), i)$$
(21)

$$\mathsf{state}_{i}[\mathsf{node}].\mathsf{det}^{+} = \bigcup_{c^{+} \in \mathsf{children}^{+}(\mathsf{node},i)} \mathsf{state}_{i}[c^{+}].\mathsf{det}^{+} \cap \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), r(\mathsf{node},i))$$
(22)

Similar to before, based on Lemma 5, Equation 22 can be intersected with BESTD(parent(node), i) to get:

 $\texttt{state}_i[\texttt{node}].\texttt{det}^+ \cap \texttt{BestD}(\texttt{parent}(\texttt{node}), i) = \bigcup_{c^+ \in \texttt{children}^+(\texttt{node}, i)} \texttt{state}_i[c^+].\texttt{det}^+ \cap \texttt{BestD}(\texttt{parent}(\texttt{node}), i)$ (23)

All children of node except  $P_i$ 's ancestor do not have their state values updated between steps i and i + 1. For these children state<sub>i</sub> = state<sub>i+1</sub>. Let  $c^*$  be node's child that is  $P_i$ 's ancestor and let:

$$X = \bigcup_{c^+ \in \text{children}^+(\text{node},i) \setminus \{c^*\}} \text{state}_i[c^+].\text{det}^+$$

We can rewrite Equations 21 and 23 as:

$$state_{i+1}[node].det^{+} = BestD(parent(node), i) \cap (X \cup state_{i+1}[c^{*}].det^{+})$$
(24)

 $\mathtt{state}_i[\mathtt{node}].\mathtt{det}^+ \cap \mathtt{BestD}(\mathtt{parent}(\mathtt{node}), i) = \mathtt{BestD}(\mathtt{parent}(\mathtt{node}), i) \cap (X \cup \mathtt{state}_i[c^*].\mathtt{det}^+)$ (25) The inductive hypothesis states that for child  $c^*$ :

$$\mathsf{state}_{i+1}[c^*].\mathsf{det}^+ \supseteq \mathsf{state}_i[c^*].\mathsf{det}^+ \cap \mathrm{BestD}(\mathsf{node}, i)$$

Expanding out BESTD based on Algorithm 2, we get:

$$state_{i+1}[c^*].det^+ \supseteq state_i[c^*].det^+ \cap BestD(parent(node), i)$$

$$\setminus \left( \bigcup_{c^{\circ} \in \mathrm{children}^{\circ}(\mathrm{node},i)} \mathrm{state}_{i}[c^{\circ}].\mathrm{cmp}} \bigcup_{c^{+} \in \mathrm{children}^{+}(\mathrm{node},i) \setminus \{c^{*}\}} \mathrm{state}_{i}[c^{+}].\mathrm{det}^{+} \right)$$

Once again, based on Property 7, for complete children  $c^{\circ}$ , state[ $c^{\circ}$ ].cmp = state[ $c^{\circ}$ ].det<sup>+</sup>, so:

1

$$state_{i+1}[c^*].det^+ \supseteq state_i[c^*].det^+ \cap BestD(parent(node), i)$$

$$\left(\bigcup_{c \in (\text{children}^{\circ}(\text{node},i) \cup \text{children}^{+}(\text{node},i) \setminus \{c^{*}\})} \text{state}_{i}[c].\text{det}^{+}\right)$$

Lemma 15 states that for two different children c and c', state<sub>i</sub>[c].det<sup>+</sup> and state<sub>i</sub>[c'].det<sup>+</sup> are mutually exclusive<sup>9</sup>, so this simplifies to:

$$state_{i+1}[c^*].det^* \supseteq state_i[c^*].det^* \cap BestD(parent(node), i)$$

We can take the union with respect to  $BestD(parent(node), i) \cap X$  on both sides. This results in the left-hand side being equivalent to Equation 24, and the right-hand side being equivalent to Equation 25. Thus:

$$state_{i+1}[node].det^* \supseteq state_i[node].det^* \cap BestD(parent(node), i)$$

If node is an AND node and negatively determinable, then based on Algorithm 3:

$$state_{i+1}[node].det^{-} = \bigcup_{c^{-} \in children^{-}(node, i+1)} state_{i+1}[c^{-}].det^{-} \cap BestD(parent(node), i)$$
(26)

$$state_{i}[node].det^{-} = \bigcup_{c^{-} \in children^{-}(node,i)} state_{i}[c^{-}].det^{-} \cap BestD(parent(node), r(node, i))$$
(27)

Once again, based on Lemma 5, Equation 27 can be intersected with BESTD(parent(node), *i*) to get:

$$state_{i}[node].det^{-} \cap BestD(parent(node), i) = \bigcup_{c^{-} \in children^{-}(node, i)} state_{i}[c^{-}].det^{-} \cap BestD(parent(node), i)$$
(28)

All children of node except  $P_i$ 's ancestor do not have their state values updated between steps *i* and i + 1. For these children state<sub>*i*</sub> = state<sub>*i*+1</sub>. Let  $c^*$  be node's child that is  $P_i$ 's ancestor and let:

$$X = \bigcup_{c^- \in \text{children}^-(\text{node},i) \setminus \{c^*\}} \text{state}_i[c^-].\text{det}$$

We can rewrite Equations 26 and 28 as:

$$state_{i+1}[node].det^{-} = BestD(parent(node), i) \cap (X \cup state_{i+1}[c^*].det^{-})$$
(29)

 $state_{i}[node].det^{-} \cap BestD(parent(node), i) = BestD(parent(node), i) \cap (X \cup state_{i}[c^{*}].det^{-})$ (30)

<sup>&</sup>lt;sup>9</sup>To apply Lemma 15 to node's children here, Lemma 14 must hold true up up to node's children. The inductive hypothesis applies in this case, so there is no cyclical dependency.

The inductive hypothesis states that for child  $c^*$ :

$$\mathsf{state}_{i+1}[c^*].\mathsf{det}^- \supseteq \mathsf{state}_i[c^*].\mathsf{det}^- \cap \mathsf{BestD}(\mathsf{node},i)$$

Expanding out BESTD based on Algorithm 2, we get:

$$state_{i+1}[c^*].det^- \supseteq state_i[c^*].det^- \cap BESTD(parent(node), i) \\ \cap \left( \left( \bigcap_{c^\circ \in children^\circ(node, i)} state_i[c^\circ].cmp \right) \setminus \left( \bigcup_{c^- \in children^-(node, i) \setminus \{c^*\}} state_i[c^-].det^- \right) \right) \right)$$

Lemma 15 tells us that the det<sup>-</sup> values of two different children are mutually exclusive, so we can remove the set subtraction terms:

$$\mathsf{state}_{i+1}[c^*].\mathsf{det}^- \supseteq \mathsf{state}_i[c^*].\mathsf{det}^- \cap \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), i) \cap \left(\bigcap_{c^\circ \in \mathsf{children}^\circ(\mathsf{node}, i)} \mathsf{state}_i[c^\circ].\mathsf{cmp}\right)$$
(31)

1

١

At this point, we establish the following relationships thanks to Algorithm 3: For  $c^*$  and any complete child  $c^\circ$  of node on step *i*:

state<sub>i</sub>[
$$c^*$$
].det<sup>-</sup>  $\subseteq$  BestD(node,  $r(c^*, i)$ )  
state<sub>i</sub>[ $c^\circ$ ].cmp  $\subseteq$  BestD(node,  $r(c^\circ, i)$ )

If  $r(c^*, i) < r(c^\circ, i)$  (meaning a predicate descendant of  $c^\circ$  was applied more recently than one of  $c^*$ ), as part of calculating BESTD, the det<sup>-</sup> values of all negatively determinable children are subtracted away. Since  $r(c^*, i) < r(c^\circ, i)$ ,  $c^*$  must be one of these children:

$$state_i[c^\circ].cmp \subseteq BestD(node, r(c^\circ, i)) \setminus state_{r(c^\circ, i)}[c^*].det$$

Since  $r(c^*, i) < r(c^\circ, i)$ , state<sub> $r(c^\circ, i)$ </sub>  $[c^*] = state_i[c^*]$ , thus state<sub>i</sub> $[c^\circ]$ .cmp must be mutually exclusive with state<sub>i</sub> $[c^*]$ .det<sup>-</sup>.

On the other hand, if  $r(c^*, i) > r(c^\circ, i)$  (meaning a predicate descendant of  $c^*$  was applied more recently than one of  $c^\circ$ ), as part of calculating BESTD, an intersection with the cmp values of all complete children is performed. Since  $r(c^*, i) > r(c^\circ, i)$ ,  $c^\circ$  must have be one of these children:

$$state_i[c^*].det^- \subseteq BestD(node, r(c^*, i)) \cap state_{r(c^*, i)}[c^\circ].cmp$$

Since  $r(c^*, i) > r(c^\circ, i)$ , state<sub> $r(c^*,i)$ </sub>  $[c^\circ] = state_i[c^\circ]$ , thus state<sub> $i</sub> <math>[c^*]$ .det<sup>-</sup>  $\subseteq$  state<sub> $i</sub> <math>[c^\circ]$ .cmp.</sub></sub>

If the first case is true for any complete child  $c^{\circ}$  in Equation 31, then the right-hand side simplifies to the empty set, and the lemma is trivially true. If all complete children  $c^{\circ}$  of belong to the second case, then state<sub>i</sub>[child].det<sup>-</sup> must be a subset of the intersection, and Equation 31 simplifies to:

$$state_{i+1}[child].det \supseteq state_i[child].det \cap BestD(parent(node), i)$$

We can take the union with respect to  $BestD(parent(node), i) \cap X$  on both sides. This results in the left-hand side being equivalent to Equation 29, and the right-hand side being equivalent to Equation 30. Thus:

$$state_{i+1}$$
[node].det  $\supseteq$  state<sub>i</sub>[node].det  $\cap$  BESTD(parent(node), i)

If node is an OR node and negatively determinable, then all of its children must be negatively determinable by definition. Based on Algorithm 3:

$$state_{i+1}[node].det^{-} = \bigcap_{c \in children(node)} state_{i+1}[c].det^{-} \cap BestD(parent(node), i)$$
(32)

$$\mathsf{state}_i[\mathsf{node}].\mathsf{det}^- = \bigcap_{c \in \mathsf{children}(\mathsf{node})} \mathsf{state}_i[c].\mathsf{det}^- \cap \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), r(\mathsf{node}, i))$$
(33)

Since we assumed that Lemma 5 holds up to step *i*, BESTD(parent(node), *i*)  $\subseteq$  BESTD(parent(node), *r*(node, *i*)), and:

$$\mathsf{state}_i[\mathsf{node}].\mathsf{det}^- \cap \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), i) = \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), i) \cap \left(\bigcap_{c \in \mathsf{children}(\mathsf{node})} \mathsf{state}_i[c].\mathsf{det}^-\right)$$
(34)

All children of node except  $P_i$ 's ancestor do not have their state values updated between steps i and i + 1. For these children state<sub>i</sub> = state<sub>i+1</sub>. Let  $c^*$  be node's child that is  $P_i$ 's ancestor and let:

$$X = \bigcap_{c \in children(node) \setminus \{c^*\}} state_i[c].det$$

We can rewrite Equations 32 and 34 as:

$$state_{i+1}[node].det^{-} = BestD(parent(node), i) \cap X \cap state_{i+1}[c^*].det^{-}$$

(35)

١

 $state_i[node].det^{-} \cap BestD(parent(node), i) = BestD(parent(node), i) \cap X \cap state_i[c^*].det^{-}$  (36)

The inductive hypothesis states that for child  $c^*$ :

$$state_{i+1}[c^*].det^- \supseteq state_i[c^*].det^- \cap BestD(node, i)$$

Expanding out BESTD based on Algorithm 2, we get:

$$state_{i+1}[c^*].det^- \supseteq state_i[c^*].det^- \cap BestD(parent(node), i) \\ \setminus \left( \bigcup_{c^\circ \in children^\circ(node, i)} state_i[c^\circ].cmp \bigcup_{c^+ \in children^+(node, i) \setminus \{c^*\}} state_i[c^+].det^+ \right)$$

Once again, based on Property 7, for complete children  $c^{\circ}$ , state $[c^{\circ}]$ .cmp = state $[c^{\circ}]$ .det<sup>+</sup>, so:

 $state_{i+1}[c^*].det^- \supseteq state_i[c^*].det^- \cap BestD(parent(node), i)$ 

$$\setminus \left( \bigcup_{c \in (\text{children}^{\circ}(\text{node},i) \cup \text{children}^{+}(\text{node},i) \setminus \{c^{*}\})} \text{state}_{i}[c].\text{det}^{+} \right)$$

If we intersect both sides with  $X \cap BESTD$  (parent(node), *i*), the left-hand side is the same as Equation 35. Thus:

state<sub>*i*+1</sub>[node].det<sup>-</sup> 
$$\supseteq$$
 state<sub>*i*</sub>[ $c^*$ ].det<sup>-</sup>  $\cap$  BESTD(parent(node), *i*)  $\cap X$ 

$$\left(\bigcup_{c \in (\text{children}^{\circ}(\text{node},i) \cup \text{children}^{+}(\text{node},i) \setminus \{c^{*}\})} \text{state}_{i}[c].\text{det}^{+}\right)$$

Using the identity  $(A \cap B) \setminus (C \cup D) = (A \setminus C) \cap (B \setminus D)$  for all sets *A*, *B*, *C*, and *D* (Appendix F) and expanding *X*, we can rearrange this to:

 $state_{i+1}[node].det^{-} \supseteq state_i[c^*].det^{-} \cap BestD(parent(node), i)$ 

 $\cap \left( \bigcap_{c \in \text{children(node)} \setminus \{c^*\}} \text{state}_i[c].\text{det}^- \setminus \text{state}_i[c].\text{det}^+ \right)$ 

Not all children may be positively determinable, but the  $det^+$  value of those children will be  $\emptyset$  anyway based on initialization. Based on Property 6, the  $det^-$  and  $det^+$  values for any node must mutually exclusive for any time step, so we can remove the set subtraction terms:

$$\mathsf{state}_{i+1}[\mathsf{node}].\mathsf{det}^{-} \supseteq \mathsf{state}_{i}[c^*].\mathsf{det}^{-} \cap \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), i) \cap \left(\bigcap_{c \in \mathsf{children}(\mathsf{node}) \setminus \{c^*\}} \mathsf{state}_{i}[c].\mathsf{det}^{-}\right)$$

The right-hand side of this equation is equivalent to Equation 36, so:

 $state_{i+1}[node].det^{-} \supseteq state_{i}[node].det^{-} \cap BestD(parent(node), i)$ 

# E.3.15 Proof of Lemma 15

**Lemma 15.** Let  $[P_1, ..., P_n]$  be any ordering of predicates for the given predicate expression, and let node be a non-leaf node in the associated predicate tree. Furthermore, Let c and c' be two different children of node. If node is an OR node, Lemma 5 holds true up to step  $j_{max}$ , and Lemma 14 holds true up to node's children, then for all steps i and j such that  $max(i, j) \leq j_{max}$ :

$$state_i[c].det^+ \cap state_i[c'].det^+ = \emptyset$$

If node is an AND node, Lemma 5 holds true up to step  $j_{max}$ , and Lemma 14 holds true up to node's children, then for all steps i and j such that  $max(i, j) \le j_{max}$ :

$$state_i[c].det \cap state_i[c'].det = \emptyset$$

*Proof.* We prove this by induction over the value of  $j_{\text{max}}$ . Let us first assume node is an OR node. As the base case, i = j = 1. Since all det<sup>+</sup> values are initialized to the empty set: state<sub>1</sub>[c].det<sup>+</sup> = state<sub>1</sub>[c'].det<sup>+</sup> =  $\emptyset$ , and the lemma is trivially satisfied.

As the inductive hypothesis, assume that for  $j_{max} = k$ , the lemma holds. For the inductive step  $j_{max} = k + 1$ , there are three cases:

1. Predicate  $P_k$  is not a descendant of either *c* or *c'*. In this case, the state does not change for either *c* and *c'* between steps *k* and *k* + 1, and:

 $state_{k+1}[c].det^+ = state_k[c].det^+$   $state_{k+1}[c'].det^+ = state_k[c'].det^+$ 

Thus, We can apply the inductive hypothesis directly.

2. Predicate  $P_k$  is a descendant of c. We assume that  $state_{k+1}[c].det^+ \neq state_k[c].det^+$ . Otherwise, this situation reduces to the first case. If state is updated, based on Algorithm 3, we know

that: state<sub>k+1</sub>[c].det<sup>+</sup>  $\subseteq$  BESTD(node, k). However, as a part of calculating BESTD(node, k), state<sub>k</sub>[c'].det<sup>+</sup> is explicitly removed from result, so:

$$\mathsf{state}_{k+1}[c].\mathsf{det}^+ \cap \mathsf{state}_k[c'].\mathsf{det}^+ = \emptyset$$

In addition, since  $P_k$  is not a descendant of c', state[c'].det<sup>+</sup> remains unchanged between steps k and k + 1. In fact, state[c'] remains unchanged for all steps since the last predicate descendant of predicate, so for all  $r(c', k) < j \leq (k + 1)$ :

$$state_{k+1}[c].det^{+} \cap state_{j}[c'].det^{+} = \emptyset$$

Based on Lemma 14, we know that  $\text{state}_{r(c',k)+1}[c'].\text{det}^+ \supseteq \text{state}_{r(c',k)}[c'].\text{det}^+ \cap \text{BestD}(\text{node}, r(c',k))$ . Furthermore, Lemma 5 tells us that  $\text{BestD}(\text{node}, k) \subseteq \text{BestD}(\text{node}, r(c', k))$ , so:

$$\begin{split} \mathsf{state}_{r(c',k)+1}[c'].\mathsf{det}^+ &\supseteq \mathsf{state}_{r(c',k)}[c'].\mathsf{det}^+ \cap \mathsf{BESTD}(\mathsf{node}, r(c',k)) \\ &\mathsf{state}_{r(c',k)+1}[c'].\mathsf{det}^+ \supseteq \mathsf{state}_{r(c',k)}[c'].\mathsf{det}^+ \cap \mathsf{BESTD}(\mathsf{node}, k) \\ &\mathsf{state}_{k+1}[c].\mathsf{det}^+ \cap \mathsf{state}_{r(c',k)+1}[c'].\mathsf{det}^+ \supseteq \mathsf{state}_{r(c',k)}[c'].\mathsf{det}^+ \cap \mathsf{BESTD}(\mathsf{node}, k) \cap \mathsf{state}_{k+1}[c].\mathsf{det}^+ \\ &\varnothing \supseteq \mathsf{state}_{r(c',k)}[c'].\mathsf{det}^+ \cap \mathsf{BESTD}(\mathsf{node}, k) \cap \mathsf{state}_{k+1}[c].\mathsf{det}^+ \\ &\varnothing \supseteq \mathsf{state}_{r(c',k)}[c'].\mathsf{det}^+ \cap \mathsf{state}_{k+1}[c].\mathsf{det}^+ \\ \end{split}$$

The final step comes from the fact that  $state_{k+1}[c].det^+ \subseteq BESTD(node, k)$ . This reasoning can be applied recursively for all  $j \leq r(node, k)$ , such that for all  $1 \leq j \leq k + 1$ :

$$state_{k+1}[c].det^{+} \cap state_{j}[c'].det^{+} = \emptyset$$

For cases in which  $i \le k$  and j = k + 1, state[c'].det<sup>+</sup> remains unchanged between steps k and k + 1, so the inductive hypothesis can be directly applied.

3. Predicate  $P_k$  is a descendant of c'. This is the same as the second case, except c and c' are flipped. The same reasoning applies.

The exact same reasoning applies to state[c].det<sup>-</sup> and state[c'].det<sup>-</sup> if node is an AND node.  $\Box$ 

#### E.3.16 Proof of Lemma 16

**Lemma 16.** For any set of valuation sets **D**, predicate *P*, and any  $D \in \mathbf{D}$ , let *E* be some valuation set derived from  $\mathbf{D} \cup \{P(D)\}$  without using *P* as an operator. There exists a valuation set *E'* derived from **D** without using *P* as an operator, such that:

$$E \setminus D = E' \setminus D$$

*Proof.* We prove this by structural induction over all sets *E* which can be derived from  $\mathbf{D} \cup \{P(D)\}$ . If  $E \in \mathbf{D}$ , the lemma is trivially satisfied with E' = E. Thus, *E* must be a valuation set that can be derived from  $\mathbf{D} \cup \{P(D)\}$  but not  $\mathbf{D}$ . The base case is E = P(D). By definition,  $P(D) \subseteq D$ , so:  $E \setminus D = \emptyset$ , and the lemma is satisfied with E' = D.

Next, assume as the inductive hypothesis that *F* and *G* are some valuation sets derived from  $\mathbf{D} \cup \{P(D)\}$  and *F'* and *G'* are the corresponding valuation set derived from  $\mathbf{D}$  such that  $F \setminus D = F' \setminus D$  and  $G \setminus D = G' \setminus D$ . We can construct a new valuation set *E* derived from  $\mathbf{D} \cup \{P(D)\}$  by performing an operation on *F* (and *G*):

1. E = P'(F) for some predicate  $P' \neq P$ :

$$E \setminus D = P'(F) \setminus D$$
$$= P'(F \setminus D)$$
$$= P'(F' \setminus D)$$
$$= P'(F' \setminus D)$$

Thus, E' = P'(F'). The second and fourth steps come from Property 4, and the third step is the application of the inductive hypothesis.

2.  $E = F \cap G$ :

$$E \setminus D = (F \cap G) \setminus D$$
$$= (F \setminus D) \cap (G \setminus D)$$
$$= (F' \setminus D) \cap (G' \setminus D)$$
$$= (F' \cap G') \setminus D$$

Thus,  $E' = F' \cap G'$ . The second and fourth steps are from the identity  $(A \cap B) \setminus C = (A \setminus C) \cap (B \setminus C)$  for any sets A, B, and C (Appendix F), and the third step is the application of the inductive hypothesis.

3. 
$$E = F \cup G$$
:

$$E \setminus D = (F \cup G) \setminus D$$
$$= (F \setminus D) \cup (G \setminus D)$$
$$= (F' \setminus D) \cup (G' \setminus D)$$
$$= (F' \cup G') \setminus D$$

Thus,  $E' = F' \cup G'$ . The second and fourth steps are from the identity  $(A \cup B) \setminus C = (A \setminus C) \cup (B \setminus C)$  for any sets *A*, *B*, and *C* (Appendix F), and the third step is the application of the inductive hypothesis.

4.  $E = F \setminus G$ :

$$E \setminus D = (F \setminus G) \setminus D$$
$$= (F \setminus D) \setminus G$$
$$= (F' \setminus D) \setminus G$$
$$= F' \setminus (G \cup D)$$
$$= F' \setminus ((G \setminus D) \cup D)$$
$$= F' \setminus ((G' \setminus D) \cup D)$$
$$= F' \setminus (G' \cup D)$$
$$= (F' \setminus G') \setminus D$$

Thus,  $E' = F' \setminus G'$ . The following identities are used (Appendix F). For any sets *A*, *B*, and *C*:

$$(A \setminus B) \setminus C = (A \setminus C) \setminus B \qquad (A \setminus B) \setminus C = A \setminus (B \cup C) \qquad A \cup B = (A \setminus B) \cup B$$

The third and sixth steps are the applications of the inductive hypothesis.

### E.3.17 Proof of Lemma 17

**Lemma 17.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$  be the ith operand generated by BESTD and UPDATE. In addition, let A be an ancestor in  $P_i$ 's lineage. For all  $v \in D_i$ , there exists a  $u \in \Gamma(v, i)$  such that all incomplete children of A that are not ancestors of  $P_i$  are statically true/false with respect to  $\{u|_{i=T}, u|_{i=F}\}$  if A is an AND/OR node respectively.

*Proof.* In our setup, all predicate expressions are positive, so the given predicate expression and all subexpressions are monotone Boolean functions [27]. Monotone Boolean functions are functions  $f : \{0, 1\}^n \rightarrow \{0, 1\}$  which have the property that if  $x \leq y$ , then  $f(x) \leq f(y)$ , in which  $x \leq y$  is defined as  $x_i \leq y_i$  for all i in  $1 \leq i \leq n$ . Here 1 is used to represent true values and 0 is used to represent false values.

Let ancestor *A* be an AND node. We prove by construction that for all  $v \in D_i$ , there exists a  $u \in \Gamma(v, i)$  that evaluates to true against all incomplete children of *A*. Using the same notation as monotone Boolean functions, the construction of valuation u is as follows:

- 1. For all j in  $(1 \le j \le i 1)$ , set  $u_j = v_j$ .
- 2. For all *j* in  $(i \le j \le n)$ , set  $u_j = 1$ .

Lemma 18 (shown below) states that an incomplete child of *A* that is not an ancestor of  $P_i$  cannot be statically false with respect to  $\Gamma(v, i)$ . Thus, for each incomplete child of *A*, there must exist at least one  $u' \in \Gamma(v, i)$  that evaluates to true against that child. In other words, if we let node be the incomplete child of *A*, then there exists a  $u' \in \Gamma(v, i)$  such that node[u'] = 1. When compared with the above constructed  $u, u' \leq u$  because  $u' \in \Gamma(v, i)$ . Thus, based on the property of monotone Boolean functions, if node[u'] = 1, then node[u] = 1. This reasoning holds for all incomplete children of *A*, so *u* must evaluate to true against all incomplete children of *A*.

**Lemma 18.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$  be the ith operand generated by BESTD and UPDATE. In addition, let A be an ancestor in  $P_i$ 's lineage. For all  $v \in D_i$ , an incomplete child of A which is not an ancestor of  $P_i$  cannot be statically false/true with respect to  $\Gamma(v, i)$  if A is an AND/OR node respectively.

Similarly, if *A* is an OR node, we can construct a  $u \in \Gamma(v, i)$  that evaluates to false against all incomplete children of *A* with:

- 1. For all *j* in  $(1 \le j \le i 1)$ , set  $u_j = v_j$ .
- 2. For all *j* in  $(i \le j \le n)$ , set  $u_j = 0$ .

Once again, Lemma 18 states that for each incomplete child of *A* that is not an ancestor of  $P_i$  cannot be statically true with respect to  $\Gamma(v, i)$ . Thus, if node is an incomplete child of *A*, then there exists a  $u' \in \Gamma(v, i)$  such that node[u'] = 0. When compared with the above constructed  $u, u \le u'$  because  $u' \in \Gamma(v, i)$ . Thus, based on the property of monotone Boolean functions, if node[u'] = 0, then node[u] = 0. This reasoning holds for all incomplete children of *A*, so *u* must evaluate to false against all incomplete children of *A*.

### E.3.18 Proof of Lemma 18

**Lemma 18.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$ be the ith operand generated by BESTD and UPDATE. In addition, let A be an ancestor in  $P_i$ 's lineage. For all  $v \in D_i$ , an incomplete child of A which is not an ancestor of  $P_i$  cannot be statically false/true with respect to  $\Gamma(v, i)$  if A is an AND/OR node respectively.

Proof. First we introduce Lemmas 19 and 20.
**Lemma 19.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$  be the ith operand generated by BESTD and UPDATE. In addition, let node be a node in the associated predicate tree. For all  $v \in D_i$ , if node is not positively determinable on step *i*, then node cannot be statically true with respect to  $\Gamma(v, i)$ . Similarly, for all  $v \in D_i$ , if node is not negatively determinable on step *i*, then node cannot be statically node cannot be statically false with respect to  $\Gamma(v, i)$ .

**Lemma 20.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let node be a node in the associated predicate tree. If node is positively determinable on step i, then  $state_i[node].det^+$  is the set of valuations  $v \in BESTD(node, r(node, i))$  such that every  $u \in \Gamma(v, i)$  evaluated against node is true:

state<sub>*i*</sub>[node].det<sup>+</sup> = { $v \in BestD(parent(node), r(node, i)) | \forall u \in \Gamma(v, i), node[u] = T$ }

Similarly, if node is negatively determinable on step i, then  $state_i[node].det^-$  is the set of valuations  $v \in BestD(node, r(node, i))$  such that every  $u \in \Gamma(v, i)$  evaluated against node is false:

state<sub>*i*</sub>[node].det<sup>-</sup> = { $v \in BestD(parent(node), r(node, i)) | \forall u \in \Gamma(v, i), node[u] = F$ }

We are now ready to prove Lemma 18. Let A be an AND node, and let node be an incomplete child of A. If node is not negatively determinable on step i, Lemma 19 states that node cannot be statically false with respect to  $\Gamma(v, i)$ , trivially satisfying the lemma. Thus, let us assume node is negatively determinable. According to Algorithm 2, part of calculating BESTD(A, i) involves set subtracting state<sub>i</sub>[node].det<sup>-</sup> from BESTD(parent(A), i) if node is negatively determinable. More specifically, BESTD(A, i)  $\subseteq$  BESTD(parent(A), i)  $\setminus$  state<sub>i</sub>[node].det<sup>-</sup>. Property 8 states that  $D_i \subseteq$  BESTD(A, i), so  $D_i \cap$  state<sub>i</sub>[node].det<sup>-</sup> =  $\emptyset$ . We can substitute the value of state<sub>i</sub>[node].det<sup>-</sup> based on Lemma 20 to get:

$$D_i \cap \{v \in \text{BestD}(\text{parent}(\text{node}), r(\text{node}, i)) \mid \forall u \in \Gamma(v, i), \text{node}[u] = F\} = \emptyset$$

Since,  $D_i \subseteq \text{BestD}(\text{parent}(\text{node}), i)$ , and  $\text{BestD}(\text{parent}(\text{node}), i) \subseteq \text{BestD}(\text{parent}(\text{node}), r(\text{node}, i))$ based on Lemma 5:

$$\{v \in D_i \mid \forall u \in \Gamma(v, i), node[u] = F\} = \emptyset$$

In other words, node is not statically false with respect to  $\Gamma(v, i)$ , for any  $v \in D_i$ .

The same reasoning applies if A is an OR node. If node is not positively determinable on step i, Lemma 19 states that node cannot be statically true with respect to  $\Gamma(v, i)$ , trivially satisfying the lemma. Thus, let us assume node is positively determinable. According to Algorithm 2, part of calculating BESTD(A, i) involves set subtracting state<sub>i</sub> [node].det<sup>+</sup> from BESTD(parent(A), i) if node is positively determinable. More specifically, BESTD(A, i)  $\subseteq$  BESTD(parent(A), i)  $\setminus$  state<sub>i</sub> [node].det<sup>+</sup>. Property 8 states that  $D_i \subseteq$  BESTD(A, i), so  $D_i \cap$  state<sub>i</sub> [node].det<sup>+</sup> =  $\emptyset$ . We can substitute the value of state<sub>i</sub> [node].det<sup>+</sup> based on Lemma 20 to get:

$$D_i \cap \{v \in \text{BestD}(\text{parent}(\text{node}), r(\text{node}, i)) \mid \forall u \in \Gamma(v, i), \text{node}[u] = T\} = \emptyset$$

Since,  $D_i \subseteq \text{BestD}(\text{parent}(\text{node}), i)$ , and  $\text{BestD}(\text{parent}(\text{node}), i) \subseteq \text{BestD}(\text{parent}(\text{node}), r(\text{node}, i))$ based on Lemma 5:

$$\{v \in D_i \mid \forall u \in \Gamma(v, i), \operatorname{node}[u] = T\} = \emptyset$$

In other words, node is not statically true with respect to  $\Gamma(v, i)$ , for any  $v \in D_i$ .

## E.3.19 Proof of Lemma 19

**Lemma 19.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let valuation set  $D_i$  be the ith operand generated by BESTD and UPDATE. In addition, let node be a node in the associated predicate tree. For all  $v \in D_i$ , if node is not positively determinable on step i, then node cannot be statically true with respect to  $\Gamma(v, i)$ . Similarly, for all  $v \in D_i$ , if node is not negatively determinable on step i, then node cannot be statically node cannot be statically false with respect to  $\Gamma(v, i)$ .

*Proof.* We prove this by strong induction on the height of the tree referred to by node. As the base case, let node be a leaf node which refers to predicate  $P_j$ . If  $j \ge i$ , then node cannot be statically true or false with respect to  $\Gamma(v, i)$  for any v. If j < i, then node must be complete by step i, so it must also be positively and negatively determinable by step i. Thus, the base case is trivially resolved.

As the inductive hypothesis, assume that the lemma holds for any predicate tree nodes of height k or less. Next, as the inductive step, let node have a height of k + 1. We prove the contrapositive of the lemma for node: For all  $v \in D_i$ , if node is statically true with respect to  $\Gamma(v, i)$ , then node is positively determinable on step i. If node is statically false with respect to  $\Gamma(v, i)$ , then node is negatively determinable on step i.

If node is an AND node and statically true with respect to  $\Gamma(v, i)$ , then each  $u \in \Gamma(v, i)$  must resolve to true against every child of node. Thus, all of node's children must be statically true with respect to  $\Gamma(v, i)$ , and by the inductive hypothesis, positively determinable on step *i*. Therefore, by definition, node itself must also be positively determinable.

In the case that node is an AND node and statically false with respect to  $\Gamma(v, i)$ , we claim that there exists a child of node which is statically false with respect to  $\Gamma(v, i)$ . By the inductive hypothesis, if a child of node is statically false, it must be negatively determinable. By definition, if one of node's child is negatively determinable, node must be negatively determinable, completing the proof for this case. Assume to the contrary that all children of node are not statically false with respect to  $\Gamma(v, i)$ . (2) There are two cases for each child of node: (1) The child is statically true with respect to  $\Gamma(v, i)$ . (2) The child is dynamic with respect to  $\Gamma(v, i)$ . The first case is valid, but not all children can fall into this category because that would imply that node is statically true with respect to  $\Gamma(v, i)$ . Now consider once again that our predicate expression is a monotone Boolean function [27]. Using the same notation as before, consider the valuation *u* which is constructed according to:

- 1. For all j in  $(1 \le j \le i 1)$ , set  $u_j = v_j$ .
- 2. For all *j* in  $(i \le j \le n)$ , set  $u_j = 1$ .

Since node is statically false with respect to  $\Gamma(v, i)$ , there must exist a child node child of node such that child[u] = 0. However, for all  $u' \in \Gamma(v, i)$ ,  $u' \leq u$ , so based on the property of monotone Boolean functions, child[u'] = 0. This would mean that child is statically false with respect to  $\Gamma(v, i)$ , leading to another contradiction.

If node is an OR node, the same reasoning applies but in reverse. In the case that node is an OR node and statically true with respect to  $\Gamma(v, i)$ , we claim that there exists a child of node which is statically true with respect to  $\Gamma(v, i)$ . By the inductive hypothesis, if a child of node is statically true, it must be positively determinable. By definition, if one of node's child is positively determinable, node must be positively determinable, completing the proof for this case. Assume to the contrary that all children of node are not statically true with respect to  $\Gamma(v, i)$ . There are two cases for each child of node: (1) The child is statically false with respect to  $\Gamma(v, i)$ . (2) The child is dynamic with respect to  $\Gamma(v, i)$ . The first case is valid, but not all children can fall into this category because that would imply that node is statically false with respect to  $\Gamma(v, i)$ . Now consider once again that our predicate expression is a monotone Boolean function. Using the same notation as before, consider the valuation u which is constructed according to:

- 1. For all j in  $(1 \le j \le i 1)$ , set  $u_j = v_j$ .
- 2. For all j in  $(i \le j \le n)$ , set  $u_j = 0$ .

Since node is statically true with respect to  $\Gamma(v, i)$ , there must exist a child node child of node such that child[u] = 1. However, for all  $u' \in \Gamma(v, i)$ ,  $u \leq u'$ , so based on the property of monotone Boolean functions, child[u'] = 1. However, this would mean that child is statically true with respect to  $\Gamma(v, i)$ , leading to another contradiction.

If node is an OR node and statically false with respect to  $\Gamma(v, i)$ , then each  $u \in \Gamma(v, i)$  must resolve to false against every child of node. Thus, all of node's children must be statically false with respect to  $\Gamma(v, i)$ , and by the inductive hypothesis, negatively determinable on step *i*. Therefore, by definition, node itself must also be negatively determinable.

## E.3.20 Proof of Lemma 20

**Lemma 20.** Given a predicate expression and an ordering of its predicates  $[P_1, ..., P_n]$ , let node be a node in the associated predicate tree. If node is positively determinable on step i, then state<sub>i</sub>[node].det<sup>+</sup> is the set of valuations  $v \in BestD(node, r(node, i))$  such that every  $u \in \Gamma(v, i)$  evaluated against node is true:

$$state_i[node].det^+ = \{v \in BestD(parent(node), r(node, i)) \mid \forall u \in \Gamma(v, i), node[u] = T\}$$

Similarly, if node is negatively determinable on step i, then  $state_i[node].det^-$  is the set of valuations  $v \in BestD(node, r(node, i))$  such that every  $u \in \Gamma(v, i)$  evaluated against node is false:

state<sub>i</sub>[node].det<sup>-</sup> = { $v \in BestD(parent(node), r(node, i)) | \forall u \in \Gamma(v, i), node[u] = F$ }

*Proof.* We prove this by strong induction on the height of the tree referred to by node. As the base case, let node be a leaf node which refers to predicate  $P_j$ . If node is positively determinable on step *i*, it must be that j < i and j = r(node, i). When det<sup>+</sup> and det<sup>-</sup> were updated at the end of step *j*, they were updated with:

state<sub>*i*</sub>[node].det<sup>+</sup> =  $P_j$ (BestD(parent(node), *j*)) state<sub>*i*</sub>[node].det<sup>-</sup> = BestD(parent(node), *j*) \  $P_i$ (BestD(parent(node), *j*))

These expressions expand to:

state<sub>i</sub>[node].det<sup>+</sup> = { $v \in \text{BestD}(\text{parent}(\text{node}), j) \mid \text{node}[v] = T$ } state<sub>i</sub>[node].det<sup>-</sup> = { $v \in \text{BestD}(\text{parent}(\text{node}), j) \mid \text{node}[v] = F$ }

Since the value of node[v] for predicate  $P_j$  is solely determined by  $v_j$ , if node[v] = T, then for all  $u \in \Gamma(v, i)$ , node[u] = T. Similarly, if node[v] = F, then for all  $u \in \Gamma(v, i)$ , node[u] = F. Thus, the above expressions reduce to:

state<sub>*i*</sub>[node].det<sup>+</sup> = { $v \in \text{BestD}(\text{parent}(\text{node}), j) \mid \forall u \in \Gamma(v, i), \text{node}[u] = T$ } state<sub>*i*</sub>[node].det<sup>-</sup> = { $v \in \text{BestD}(\text{parent}(\text{node}), j) \mid \forall u \in \Gamma(v, i), \text{node}[u] = F$ }

and the base case is resolved.

As the inductive hypothesis, assume that the lemma holds for all predicate tree nodes of height k or less. For the inductive step, let node be a predicate tree node of height k + 1.

If node is an AND node and positively determinable on step *i*, all of its children must be positively determinable. Based on Algorithm 3:

$$\mathsf{state}_{i}[\mathsf{node}].\mathsf{det}^{+} = \bigcap_{c \in \mathsf{children}(\mathsf{node})} \mathsf{state}_{i}[c].\mathsf{det}^{+} \cap \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), r(\mathsf{node}, i))$$
(37)

The outer inductive hypothesis states that for child *c* of node:

$$state_i[c].det^+ = \{v \in BestD(node, r(c, i)) \mid \forall u \in \Gamma(v, i), c[u] = T\}$$

Based on Algorithm 2, we can expand BESTD:

$$state_{i}[c].det^{*} = \{v \in BESTD(parent(node), r(c, i)) \mid \forall u \in \Gamma(v, i), c[u] = T\}$$
  

$$\cap \left( \left( \bigcap_{c^{\circ} \in children^{\circ}(node, r(c, i))} state_{r(c, i)}[c^{\circ}].cmp \right) \setminus \left( \bigcup_{c^{-} \in children^{-}(node, r(c, i)) \setminus \{c\}} state_{r(c, i)}[c^{-}].det^{-} \right) \right)$$
(38)

Substituting into Equation 37 gives us:

$$state_{i}[node].det^{*} = \bigcap_{c \in children(node)} \{v \in BestD(parent(node), r(c, i)) \mid \forall u \in \Gamma(v, i), c[u] = T\}$$
$$\cap \left( \left( \bigcap_{c^{\circ} \in children^{\circ}(node, r(c, i))} state_{r(c, i)}[c^{\circ}].cmp \right) \setminus \left( \bigcup_{c^{-} \in children^{-}(node, r(c, i)) \setminus \{c\}} state_{r(c, i)}[c^{-}].det^{-} \right) \right)$$
$$\cap BestD(parent(node), r(node, i))$$

After using Property 7 to convert cmp values to det<sup>+</sup> values, the expression state<sub>r(c,i)</sub> [ $c^{\circ}$ ].cmp in the second line can be substituted using Equation 38. By repeatedly expanding this term, applying Lemma 5 (r(c, i) must be the latest step for any c), and applying the identities  $A \cap (B \setminus C) = (A \cap B) \setminus C$  and  $(A \setminus B) \setminus C = A \setminus (B \cup C)$  for all sets A, B, and C (Appendix F), we are left with:

$$state_{i}[node].det^{+} = \bigcap_{c \in children(node)} \{v \in BestD(parent(node), r(c, i)) \mid \forall u \in \Gamma(v, i), c[u] = T\}$$
$$\cap BestD(parent(node), r(node, i)) \setminus \left(\bigcup_{j_{c}} state_{j_{c}}[c].det^{-}\right)$$

for some set of step indices  $j_c$  for each child c. By definition,  $state_{j_c}[c].det^-$  does not contain any valuations v for which c[v] = T, whereas the expression { $v \in BestD(parent(node), r(c, i)) | \forall u \in \Gamma(v, i), c[u] = T$ } only contains valuations v for which c[v] = T (because  $v \in \Gamma(v, i)$ ). Thus, these sets are mutually exclusive, and we can get rid of the set subtraction terms:

$$\mathsf{state}_i[\mathsf{node}].\mathsf{det}^* = \bigcap_{c \in \mathsf{children}(\mathsf{node})} \{ v \in \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), r(c, i)) \mid \forall u \in \Gamma(v, i), c[u] = T \}$$

 $\cap$  BestD(parent(node), r(node, i))

Applying Lemma 5 yields:

$$\mathsf{state}_i[\mathsf{node}].\mathsf{det}^* = \bigcap_{c \in \mathsf{children}(\mathsf{node})} \{ v \in \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), r(\mathsf{node}, i)) \mid \forall u \in \Gamma(v, i), c[u] = T \}$$

The expression { $v \in \text{BESTD}(\text{parent}(\text{node}), j) | \forall u \in \Gamma(v, i), c[u] = T$ } returns only valuations v for which child c is statically true with respect to  $\Gamma(v, i)$ . The intersection of these valuations is the valuations v for which every child of node is statically true with respect to  $\Gamma(v, i)$ . For an AND node, having every child be statically true with respect to a valuation set is the requirement to be statically true to the valuation set. Thus:

state<sub>*i*</sub>[node].det<sup>+</sup> = { $v \in \text{BestD}(\text{parent}(\text{node}), r(\text{node}, i)) \mid \forall u \in \Gamma(v, i), \text{node}[u] = T$ }

If node is an AND node and negatively determinable on step *i*, we prove this case by induction on step index *i* (henceforth referred to as the "inner" induction). For node to be negatively determinable, one of its children must be negatively determinable. Let  $c^{-i}$  be the first negatively determinable child of node, and let  $c^{-i}$  be first negatively determinable on step j + 1. The base case for the inner induction is i = j + 1. Based on Algorithm 3:

 $\texttt{state}_{j+1}[\texttt{node}].\texttt{det}^{-} = \bigcup_{c^{-} \in \texttt{children}^{-}(\texttt{node}, j+1)} \texttt{state}_{j+1}[c^{-}].\texttt{det}^{-} \cap \texttt{BestD}(\texttt{parent}(\texttt{node}), j)$ 

For the base case, on step *j*, only one of node's children is negatively determinable:

state<sub>*j*+1</sub>[node].det<sup>-</sup> = state<sub>*j*+1</sub>[
$$c^{-\prime}$$
].det<sup>-</sup>  $\cap$  BESTD(parent(node), *j*)

After applying the inductive hypothesis of the outer induction, this expands to:

. .

$$state_i[node].det^- = \{v \in BestD(node, j) \mid \forall u \in \Gamma(v, i), c^{-\prime}[u] = F\} \cap BestD(parent(node), j)$$

None of node's children are negatively determinable nor complete on step j, so based on Algorithm 2, BESTD(node, j) = BESTD(parent(node), j), and the above equation reduces to:

state<sub>*i*</sub>[node].det<sup>-</sup> = { $v \in \text{BestD}(\text{parent}(\text{node}), j) \mid \forall u \in \Gamma(v, i), c^{-\prime}[u] = F$ }

Since node is an AND node, if one of node's children is statically false with respect to  $\Gamma(v, i)$ , then node itself must also be statically false with respect to  $\Gamma(v, i)$ :

state<sub>i</sub>[node].det = { $v \in \text{BestD}(\text{parent}(\text{node}), j) \mid \forall u \in \Gamma(v, i), \text{node}[u] = F$ }

Thus, the base case is resolved.

Next, as the inner inductive hypothesis, assume that the lemma holds for any step i = k. For the inductive step, let us observe step i = k + 1. If  $P_k$  is not a descendant of node,  $state_i = state_k$ , and the inner inductive hypothesis applies. Thus, let us assume  $P_k$  is a descendant of node and updates  $state[node].det^-$ . Based on Algorithm 3:

$$state_{k+1}[node].det^{-} = \bigcup_{\substack{c^{-} \in children^{-}(node,k+1)}} state_{k+1}[c^{-}].det^{-} \cap BestD(parent(node),k))$$
$$state_{k}[node].det^{-} = \bigcup_{\substack{c^{-} \in children^{-}(node,k)}} state_{k}[c^{-}].det^{-} \cap BestD(parent(node),r(node,k)))$$

There is only one step difference between k and k + 1, so at most one of node's children can be updated with respect to  $P_k$ . Let  $c^*$  be this ancestor of  $P_k$ . For all other negatively determinable children  $c^- \neq c^*$ , state<sub>k+1</sub>[ $c^-$ ] = state<sub>k</sub>[ $c^-$ ]. Lemma 5 states that BESTD(parent(node), k)  $\subseteq$  BESTD(parent(node), r(node, k)), and Lemma 11 states that state<sub>k+1</sub>[ $c^*$ ].det<sup>-</sup>  $\supseteq$  state<sub>k</sub>[ $c^*$ ].det<sup>-</sup>  $\cap$  BESTD(parent(node), k). Thus, we can write state<sub>k+1</sub>[node].det<sup>-</sup> in terms of state<sub>k</sub>[node].det<sup>-</sup>:

$$state_{k+1}$$
[node].det<sup>-</sup> = (state\_k[node].det<sup>-</sup>  $\cap$  BestD(parent(node), k))  $\cup$  state\_{k+1}[c<sup>\*</sup>].det<sup>-</sup> (39)

The outer inductive hypothesis states that:

$$\mathsf{state}_{k+1}[c^*].\mathsf{det}^- = \{v \in \mathsf{BestD}(\mathsf{node}, k) \mid \forall u \in \Gamma(v, i), c^*[u] = F\}$$

By Property 8, BESTD(node, k)  $\subseteq$  BESTD(parent(node), k), so:

$$state_{k+1}[c^*].det \subseteq \{v \in BestD(parent(node), k) \mid \forall u \in \Gamma(v, i), c^*[u] = F\}$$

Based on the inner inductive hypothesis and Lemma 5:

 $state_k[node].det^{-} \cap BestD(parent(node), k) = \{v \in BestD(parent(node), k) \mid \forall u \in \Gamma(v, i), node[u] = F\}$ 

In both cases the domain (BESTD(parent(node), k)) is the same, but the condition  $c^*[u] = F$  implies node[u] = F:

$$state_{k+1}[c^*].det^- \subseteq state_k[node].det^- \cap BestD(parent(node), k)$$

Thus, Equation 39 simplifies to:

state<sub>k+1</sub>[node].det<sup>-</sup> = state<sub>k</sub>[node].det<sup>-</sup> 
$$\cap$$
 BestD(parent(node), k)  
= {v  $\in$  BestD(parent(node), k) |  $\forall u \in \Gamma(v, i)$ , node[u] = F}

If node is an OR node and positively determinable on step *i*, the reasoning is similar as when node is an AND node and negatively determinable on step *i*. We prove this case by induction on step index *i* (henceforth referred to as the "inner" induction). Let  $c^+$  be the first positively determinable child of node, and let  $c^+$  be first positively determinable on step j + 1. The reasoning for the base case of the inner induction is the exact same as the reasoning for the negatively determinable AND node's base case. The only difference is that each positively determinable child is statically true with respect to  $\Gamma(v, i)$  instead of statically false.

Next, as the inner inductive hypothesis, assume that the lemma holds for any step i = k. For the inductive step, let us observe step i = k + 1. If  $P_k$  is not a descendant of node,  $state_i = state_k$ , and the inner inductive hypothesis applies. Thus, let us assume  $P_k$  is a descendant of node and updates  $state[node].det^+$ . Based on Algorithm 3:

$$state_{k+1}[node].det^{+} = \bigcup_{c^{+} \in children^{-}(node,k+1)} state_{k+1}[c^{+}].det^{+} \cap BestD(parent(node),k))$$
$$state_{k}[node].det^{+} = \bigcup_{c^{+} \in children^{-}(node,k)} state_{k}[c^{+}].det^{+} \cap BestD(parent(node),r(node,k)))$$

There is only one step difference between k and k + 1, so at most one of node's children can be updated with respect to  $P_k$ . Let  $c^*$  be this ancestor of  $P_k$ . For all other positively determinable children  $c^+ \neq c^*$ , state<sub>k+1</sub>[ $c^+$ ] = state<sub>k</sub>[ $c^+$ ]. Lemma 5 states that BESTD(parent(node), k)  $\subseteq$  BESTD(parent(node), r(node, k)), and Lemma 11 states that state<sub>k+1</sub>[ $c^*$ ].det<sup>+</sup>  $\supseteq$  state<sub>k</sub>[ $c^*$ ].det<sup>+</sup>  $\cap$  BESTD(parent(node), k). Therefore, we can write state<sub>k+1</sub>[node].det<sup>+</sup> in terms of state<sub>k</sub>[node].det<sup>+</sup>:

 $state_{k+1}[node].det^{+} = (state_{k}[node].det^{+} \cap BestD(parent(node), k)) \cup state_{k+1}[c^{*}].det^{+}$  (40)

The outer inductive hypothesis states that:

state<sub>k+1</sub>[ $c^*$ ].det<sup>+</sup> = { $v \in \text{BestD}(\text{node}, k) \mid \forall u \in \Gamma(v, i), c^*[u] = T$ }

By Property 8, BestD(node, k)  $\subseteq$  BestD(parent(node), k), so:

$$\mathsf{state}_{k+1}[c^*].\mathsf{det}^* \subseteq \{v \in \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), k) \mid \forall u \in \Gamma(v, i), c^*[u] = T\}$$

Based on the inner inductive hypothesis and Lemma 5:

 $state_k[node].det^+ \cap BestD(parent(node), k) = \{v \in BestD(parent(node), k) \mid \forall u \in \Gamma(v, i), node[u] = T\}$ 

In both cases the domain (BESTD(parent(node), k)) is the same, but the condition  $c^*[u] = T$  implies node[u] = T:

$$state_{k+1}[c^*].det^+ \subseteq state_k[node].det^+ \cap BestD(parent(node), k)$$

Thus, Equation 40 simplifies to:

$$\begin{aligned} \texttt{state}_{k+1}[\texttt{node}].\texttt{det}^{+} &= \texttt{state}_{k}[\texttt{node}].\texttt{det}^{+} \cap \texttt{BestD}(\texttt{parent}(\texttt{node}), k) \\ &= \{v \in \texttt{BestD}(\texttt{parent}(\texttt{node}), k) \mid \forall u \in \Gamma(v, i), \texttt{node}[u] = T\} \end{aligned}$$

If node is an OR node and negatively determinable on step *i*, all of its children must also be negatively determinable. Based on Algorithm 3:

$$state_{i}[node].det^{-} = \bigcap_{c \in children(node)} state_{i}[c].det^{-} \cap BestD(parent(node), r(node, i))$$
(41)

The outer inductive hypothesis states that for child *c* of node:

$$state_i[c].det^{-} = \{v \in BestD(node, r(c, i)) \mid \forall u \in \Gamma(v, i), c[u] = F\}$$

Based on Algorithm 2, we can expand BESTD:

$$state_{i}[c].det^{-} = \{v \in BestD(parent(node), r(c, i)) \mid \forall u \in \Gamma(v, i), c[u] = F\}$$

$$\setminus \left( \bigcup_{\substack{c^{\circ} \in children^{\circ}(node, r(c, i)))}} state_{r(c, i)}[c^{\circ}].cmp \bigcup_{\substack{c^{+} \in children^{+}(node, r(c, i)) \setminus \{c\}}} state_{r(c, i)}[c^{+}].det^{+} \right)$$

Using Property 7, all cmp values can be converted into det<sup>+</sup>:

$$state_{i}[c].det^{-} = \{v \in BestD(parent(node), r(c, i)) \mid \forall u \in \Gamma(v, i), c[u] = F\}$$
$$\setminus \left( \bigcup_{c^{+} \in (children^{\circ}(node, r(c, i)) \cup children^{+}(node, r(c, i)) \setminus \{c\})} state_{r(c, i)}[c^{+}].det^{+} \right)$$

Substituting into Equation 41 gives us:

$$state_{i}[node].det^{-} = \bigcap_{c \in children(node)} \left( \{ v \in BESTD(parent(node), r(c, i)) \mid \forall u \in \Gamma(v, i), c[u] = F \} \\ \cap BESTD(parent(node), r(node, i)) \right) \\ \setminus \left( \bigcup_{c^{+} \in (children^{\circ}(node, r(c, i)) \cup children^{+}(node, r(c, i)) \setminus \{c\})} state_{r(c, i)} [c^{+}].det^{+} \right)$$

After applying Lemma 5 ( $r(c, i) \le r(\text{node}, i)$ ), this simplifies to:

$$state_{i}[node].det^{-} = \bigcap_{c \in children(node)} \{v \in BESTD(parent(node), r(node, i)) \mid \forall u \in \Gamma(v, i), c[u] = F\}$$
$$\setminus \left( \bigcup_{c^{+} \in (children^{\circ}(node, r(c, i)) \cup children^{+}(node, r(c, i)) \setminus \{c\})} state_{r(c, i)} [c^{+}].det^{+} \right)$$

By definition, state<sub>*j<sub>c</sub>*</sub>[*c*].det<sup>+</sup> does not contain any valuations *v* for which c[v] = F, whereas the expression { $v \in \text{BestD}(\text{parent}(\text{node}), r(\text{node}, i)) | \forall u \in \Gamma(v, i), c[u] = F$ } only contains valuations *v* for which c[v] = F (because  $v \in \Gamma(v, i)$ ). Thus, these sets are mutually exclusive, and we can get rid of the set subtraction terms:

$$\mathsf{state}_i[\mathsf{node}].\mathsf{det}^- = \bigcap_{c \in \mathsf{children}(\mathsf{node})} \{ v \in \mathsf{BestD}(\mathsf{parent}(\mathsf{node}), r(\mathsf{node}, i)) \mid \forall u \in \Gamma(v, i), c[u] = F \}$$

The expression { $v \in \text{BestD}(\text{parent}(\text{node}), j) | \forall u \in \Gamma(v, i), c[u] = F$ } returns only valuations v for which child c is statically false with respect to  $\Gamma(v, i)$ . The intersection of these valuations is the valuations v for which every child of node is statically false with respect to  $\Gamma(v, i)$ . For an OR node, having every child be statically false with respect to a valuation set is the requirement to be statically false to the valuation set. Thus:

state<sub>*i*</sub>[node].det<sup>-</sup> = { $v \in \text{BestD}(\text{parent}(\text{node}), r(\text{node}, i)) \mid \forall u \in \Gamma(v, i), \text{node}[u] = F$ }

## F Set Identities

Here, we show the proofs for the various set identities we use throughout the paper. Identities which are not proven here come from related works [28] [10] [22].

1.  $A \cap (B \setminus C) = (A \cap B) \setminus C$ . 2.  $A \cap (B \setminus C) = (A \cap B) \setminus (A \cap C)$ . 3.  $(A \cap B) \setminus C = (A \setminus C) \cap (B \setminus C)$ . 4.  $A \cup B = (A \setminus B) \cup B$ . 5.  $(A \setminus B) \setminus C = A \setminus (B \cup C)$ . 6.  $A \setminus B = A \setminus (B \cap A)$ . 7.  $(A \cup B) \setminus C$  =  $(A \setminus C) \cup (B \setminus C)$ . 8.  $A \setminus (B \setminus C) = (A \setminus B) \cup (A \cap C).$ 9.  $A \cap (B \setminus (C \cup D)) = (A \setminus C) \cap (B \setminus D).$  $A \cap (B \setminus (C \cup D)) = A \cap ((B \setminus C) \cap (B \setminus D))$  $= B \cap (A \setminus C) \cap (B \setminus D)$  $= (A \setminus C) \cap (B \setminus D)$ 10.  $(A \cap B) \setminus (C \cup D) = (A \setminus C) \cap (B \setminus D).$  $(A \cap B) \setminus (C \cup D) = A \cap (B \setminus (C \cup D))$  $= (A \setminus C) \cap (B \setminus D)$ 11.  $A \cup (B \cap (C \setminus A)) = A \cup (B \cap C)$ .  $A \cup (B \cap (C \setminus A)) = A \cup (B \cap (A \cup (C \setminus A)))$  $= A \cup (B \cap (A \cup C))$  $= A \cup (B \cap C)$ 12.  $A \cup (B \setminus C) = (A \cup B) \setminus (C \setminus A)$ .  $(A \cup B) \setminus (C \setminus A) = ((A \cup B) \setminus C) \cup ((A \cup B) \cap A)$  $= ((A \cup B) \setminus C) \cup A$  $= A \cup (B \setminus C)$ 13.  $A = (A \setminus B) \cup (A \cap B)$ .

$$(A \setminus B) \cup (A \cap B) = (A \cup (A \cap B)) \setminus (B \setminus (A \cap B))$$
$$= (A) \setminus (\emptyset)$$
$$= A$$