arXiv:2002.04242v1 [cs.RO] 11 Feb 2020

Human-to-Robot Attention Transfer for Robot Execution Failure Avoidance Using Stacked Neural Networks

Boyi Song⁺, Yuntao Peng⁺, Ruijiao Luo⁺, Rui Liu^{*}

Abstract—Due to world dynamics and hardware uncertainty, robots inevitably fail in task executions, leading to undesired or even dangerous executions. To avoid failures for improved robot performance, it is critical to identify and correct robot abnormal executions in an early stage. However, limited by reasoning capability and knowledge level, it is challenging for a robot to self diagnose and correct their abnormal behaviors. To solve this problem, a novel method is proposed, human-torobot attention transfer (H2R-AT) to seek help from a human. H2R-AT is developed based on a novel stacked neural networks model, transferring human attention embedded in verbal reminders to robot attention embedded in robot visual perceiving. With the attention transfer from a human, a robot understands what and where human concerns are to identify and correct its abnormal executions. To validate the effectiveness of H2R-AT, two representative task scenarios, "serve water for a human in a kitchen" and "pick up a defective gear in a factory" with abnormal robot executions, were designed in an open-access simulation platform V-REP; 252 volunteers were recruited to provide about 12000 verbal reminders to learn and test the attention transfer model H2R-AT. With an accuracy of 73.68% in transferring attention and accuracy of 66.86% in avoiding robot execution failures, the effectiveness of H2R-AT was validated.

I. INTRODUCTION

Influenced by real-world dynamics and hardware uncertainty, robots inevitably fail in task executions. For example, obstacles impede robot motions, causing failures of delivering human-requested objects [21] [3]; sensor uncertainty gives unmanned aerial vehicle (UAV) unreliable information of teammate locations, leading to a wrong heading direction in UAV team flocking [36] [29]; commonsense shortage makes it difficult for a robot to understand tool usage and human intents, decreasing the execution flexibility of a manufacturing robot and consequently increasing the failure rate [38] [45] [4]. Robot abnormal behaviors result in various hazards, including economic loss, threats to human safety, and a decrease in robot social acceptance. For example, picking up wrong objects on the assembly line lead to lower productivity [35] [13]; undesired robot trajectories in daily assistance cause robot bumping into a human, which raises human safety concerns [33] [2]; misunderstanding the thoughts of autism children during companion hurt their feelings, reducing the reliability of the robots [27] [7].

Even though failure avoidance is in an urgent need for an improved robot performance [15] [32], it is challenging to practice it in the real world. First, it is hard for a robot



Fig. 1: An illustration of the attention transfer using the developed *H2R-AT* model. The attention region of a human (from human observation perspective) and robot (from robot perceiving perspective) are highlighted as shown. By using *H2R-AT* the attention of abnormal robot executions was transferred from a human to a robot to alert its failures in an early stage before failures happen.

to realize that its performance is abnormal [17]. Accurate and prompt failure detection is difficult due to the high requirements for both advanced sensing systems and reasoning algorithms. It is challenging to design a reasoning system that both plans task executions and meanwhile monitors its abnormalities [30] [49]. Moreover, even though a robot can realize its abnormalities, it is difficult for it to identify the abnormal executions and correct them correspondingly [46] [26]. Last, it is expensive to correct robot failures that it needs extra perceiving, reasoning, and acting systems, which largely increases the cost of robot system design and deployments [40].

To solve these challenges, a novel human-to-robot attention transfer (*H2R-AT*) method, as shown in Figure 1, was developed in this paper, by borrowing human intelligence to detect abnormal robot executions in an early stage and then correct them correspondingly for failure avoidance.Human attention is reflected in the concern of the specific area of their perceiving. When abnormal behaviors happen, human address their concern immediately on the fault area and generate the possible reason by their domain knowledge. Through *H2R-AT*, human can transfer their concern to robots and help them notice their wrong execution. In this research, we envision a human-guided robotic system. Human monitors the robot execution and verbally alerts the abnormal executions. We mainly have three contributions:

- Developed a novel attention transfer method to transfer human attention of unsatisfied performance of a robot, to alert robot failure in an early stage.
- Developed a novel attention supported method to help with the identification of robot abnormal executions for performance improvement and failure correction.
- Designed a natural failure warning interface by directly understanding human natural language suggestions to locate the problematic executions without prior training.

Authors are with the Cognitive Robotics and AI Lab (CRAI), College of Aeronautics and Engineering, Kent State University, Kent, OH 44240, USA. ⁺ denotes that the first three authors have equal contributions to this paper. * Rui Liu is the corresponding author rliu11@kent.edu



Fig. 2: The framework of *H2R-AT* using human verbal reminders for robot failure avoidance. Human attention is embedded in verbal reminders. Feature vectors extracted from human verbal reminders and feature vectors from robot visual perceiving are combined to get confined attention. With the confined attention, the robot can correct its abnormal behavior accordingly.

II. RELATED WORK

Attention sharing was investigated in the robotics field to indicate human preference and clarify robot confusion [12] [47]. The attention mechanism was used in both daily and industrial scenarios to increase robot execution efficiency, improve robot execution accuracy, ensure human safety, and raise robot social acceptance [1] [5] [37]. For example, a social robot used human-like gestures according to human attention in a conversation to increase human engagement in interactions [42] [41] [34]; a service robot changed its trajectory by estimating human intended places to avoid collision with the human [6] [23]; an industrial robot followed human head orientations to find the intended place to improve object search and delivery accuracy [43] [10]. Even though attention mechanisms have been used in robotics research, there is rare work focusing on robot failure avoidance, which largely decreases robot performance, brings safety concerns in robot deployments, while is still ignored. The H2R-AT presented in this paper targeted failure avoidance by utilizing an attention mechanism to involved in a human to send timely alerts for the robot abnormal behaviors.

Moreover, current attention transfer methods are unnatural, requiring prior user training which is expensive and timeconsuming. Non-verbal attention was used to express human expectations to guide robot executions. Safety concern attention was delivered by using human gaze to indicate the cared human location to avoid collision [9] [18]. Social etiquette attention was delivered by recognizing facial expressions to suggest human willingness of cooperation [11] [22] [39]. Human preference attention was delivered by using hand gestures to point to the human-desired personal items for daily assistance [16] [20]. Though non-verbal attention is effective in delivering human instructions to robots, due to the needs in adding extra perceiving devices and reasoning algorithms, such as computer vision systems and image intelligence methods, to extract human instructions, nonverbal attention is expensive in designing robotic systems. Also, non-verbal attentions merely allow limited interaction patterns, restricting the content in human instructions sent to a robot and further limiting the implementation scope of robotic systems. In this work, the proposed H2R-AT enables

a robot to directly process human verbal instructions with an accurate understanding, supporting natural human guidance on robot failure avoidance and have no requirements on prior user training, complex vision and sensor systems, reducing the cost for the robot failure avoidance.

Some research has been done to correct abnormal executions for robot failure avoidance. One type was choosing an alternative execution when a robot failed in one execution. For example, to open a drawer, a robot chooses an alternative action "swoop back to pull the drawer", when "grabbing the handle" was failed [8] [24]. The other type is compensating for the unsatisfactory execution to make it satisfactory. For example, when a robot moved too left to dress a disabled people, the robot adjusted its locations by measuring the deviation between the desired and actual location [26] [14]; when a robot was picking up a part but failed, the robot adjusted its gripper speed to avoid the previous failures [44]. Many of the current researches are focusing on avoiding failures in the future after the current failure. Even though these methods are effective in failure avoidance while allowing failures is risky because the initial failures will cause the loss of human trust in cooperation and cause physical system damages for the robots. Moreover, it increases challenges for robot task executions by requiring robots to detect failures autonomously. In our method, a human instructor is involved to monitor robot executions. Given the high-level intelligence, human can accurately detect abnormal executions in an early stage, enabling prevention of failures before it actually happens. Also, given the integration of human intelligence in the proposed H2R-AT, the requirements on self failure assessment will be lowered down, releasing more reasoning capability and computational sources for a robot to performance more important functions.

III. ATTENTION TRANSFER MODEL

When abnormal executions occur, people will give a verbal alert to correct robot behaviors. The transfer of attention can help the robot to understand human alert and correspondingly to identify the abnormal robot executions by localizing the human attention regions onto robot perceived actions.



Fig. 3: The model of LSTM-based human reminder processing. Words from human natural language are encoded to vectors by word embedding. The LSTM is used to process these vectors to extract human attention expressed by the verbal descriptions.

As shown in Figure 2, by using verbal reminders, human attention for suspicious robot behaviors are expressed; based on Stacked Attention Networks [50], we designed a new model, *H2R-AT*, combined with analysis methods in human verbal reminder processing and visual feature extraction of abnormal robot executions. Human attention has been correlated with specific regions in robot perceiving, which is directly correlated with some robot executions, for finally identifying the abnormal robot executions according to human attention.

A. Interpreting Human Intention from Verbal Reminders

Human verbal alerts described the location and types of robot abnormal executions. Based on an LSTM model (Fig3), the semantic meaning embedded in human verbal alerts will be extracted.

The NLP module, as shown in Figure 3, can identify different reminders (concerns) accurately because of the use of LSTM and word embedding. LSTM has a strong temporal modeling capability in extracting meaning from temporal human verbal instruction which is suitable for dynamic scenarios where a human gives a continuous description.

Considering a human natural language reminder $r = [r_1, r_2, ..., r_I]$ where *I* represents the length of the reminder and r_i represents an "one-hot" vector of the i^{st} word of the reminder.

Let M_{we} represent the word embedding matrix, which can be considered as a matrix to show the robot the relations of different words. It is used to convert the words to vectors M_i .

$$M_i = M_{we} \cdot r_i, i \in 1, 2, \dots I \tag{1}$$

Then the result vectors of each word are fed to LSTM in sequence and use the vector of the last word R_I to represent the whole-sentence reminder.

$$R_i = LSTM(M_i), i \in 1, 2, \dots I$$

$$\tag{2}$$

With this algorithm, a robot combines the meaning of a single word and the context of the whole reminder, which can help it to extract attention-related patterns from human reminders.

B. Locating Robot Attention in Visual Perceiving

The moment when human raises a reminder is considered as the moment of robots showing visually observable abnormal executions. The robot records a video at this specific moment from its own perspective for describing the abnormal



Fig. 4: The model of VGGnet-based robot attention identification. The robot visual perceiving (images) from a human-reminded abnormal execution moment are processed by VGGnet to extract visual features of abnormal robot behaviors.

executions. The visual features of robot abnormal executions are extracted by the method in Figure 4.

Each frame of the video is turned into a 448×448 size raw image *I*. The images then are converted into a $14 \times 14 \times 512$ feature map V_f by a CNN method called VGGnet16 [25]. The 14×14 dimension represents the 196 regions in the 448×448 picture and each region denoted by F_i , $i \in [0, 195]$ has 32×32 pixels. The 512 is the dimension of the features of each region. In order to combine the word vectors to the image matrix, a perception is used to convert V_f to have the same dimension as the reminder vectors.

$$F_I = CNN_{VGG}(I) \tag{3}$$

$$V_I = tanh(W_i \cdot F_I + b_i) \tag{4}$$

In the Equation 4, V_I is a matrix. And the i^{th} column of V_I stand for the visual feature vector of the i^{th} region of the image.

C. H2R-AT for Attention Transfer

The *H2R-AT* combines the human reminder and the robot view. By using two layers of attention, the most critical region in the robot view is identified as the actual attention of the robot.

When robots are showing abnormal executions, a robot uses a *H2R-AT* model to gradually filter out unrelated areas within its perceiving scope and finally focus on the abnormal regions.

Given the robot visual perceiving feature matrix V_I from the robot vision and the reminder vector R_I from a human supervisor, the robot can reason by the **H2R-AT** model, as shown in Figure 2.

There are two layers in our *H2R-AT* model. In the first layer, a single layer neural network and a softmax function are used to generate the distribution of robot attention to its view.

$$h_1 = tanh((W_{V_I} \cdot V_I) \oplus (W_{R_I} \cdot R_I + b_{R_I}))$$
(5)

$$p_1 = softmax(W_{p_1} \cdot h_1 + b_{p_1}) \tag{6}$$

 $V_I \in \mathbb{R}^{m \times d}$ represents the features of the robot visual perceiving, m means the dimension of features in a region and d means the number of regions in robot image perceiving. The vector $R_I \in \mathbb{R}^m$ represents the reminder features and is a m dimensional vector. Suppose the dimension of W_{R_I} and W_{V_I} is $k \times m$ and the dimension of W_{h_1} is $l \times k$, then the matrix p_1 is a d dimensional vector represents the attention distribution of the first layer. \oplus is used to denote the addition between a m dimension vector and a $m \times d$ matrix, which is adding each column of the matrix by the vector.

Then the robot perceiving feature V_I is combined together to a d dimension vector v according to the attention distribution p_1 and combine v with R_I to form a vector u_1 which has both the information of the robot visual perceiving and the reminder.

$$v = p_1 \cdot V_I \tag{7}$$

$$u_1 = v + R_I \tag{8}$$

Because of the use of attention, the more relevant the region is to the abnormal execution, the more likely that a robot will focus on it, which will lead to a more informative u_1 and thus a higher accuracy compared to the robot using a full view to reason. However, in a complicated case, one attention layer is not enough to locate the region which is most relevant to the abnormal execution, so the previous attention generating process is iterated by feeding the result of the first attention layer to the second layer, leading to a more fine-grained attention distribution.

$$h_2 = tanh((W_{V_I'} \cdot V_I') \oplus (W_{R_I}' \cdot u_1 + b_{R_I}'))$$
(9)

$$p_2 = softmax(W_{p_2} \cdot h_2 + b_{p_2}) \tag{10}$$

Then a new vector v' is generated like v by p_2 and added with u_1 to generate a more feature distinctive vector u_2 which also has both the visual information and the information from the reminder.

$$v' = p_2 \cdot V_I' \tag{11}$$

$$u_2 = v' + u_1 \tag{12}$$

The generated u_2 is used to infer which kind of abnormal execution the robot is making.

$$p_{ans} = softmax(W_u \cdot u_2 + b_u) \tag{13}$$

D. Attention Supported Failure Avoidance

In this research, a correction model was designed to test the feasibility of applying the proposed model H2R-AT. Basic actions for correction were put in the action pool for the robot to choose from. A prior user study was conducted to match attention messages with corresponding actions for correction. The correspond action is selected by a maximum likelihood recommendation method. When certain human attention is identified, the corresponding action for correction is the most recommended action $\hat{\alpha}$ according to $P(\alpha_i)$, the probabilities of each potential correction action α_i . In this research, the results guide the robot to choose the right action. When a human alert is received, the correction model is triggered to avoid failures. First, the robot identifies the abnormal executions using the attention message contained in the human alert. Then, it finds the corresponding action for correction of the certain attention message. Thus, the robot avoided failures through correction supported by attention transfer.

$$\hat{\alpha} = \operatorname*{arg\,max}_{\alpha} P(\alpha_i | \alpha_{attention}), i \in 1, 2, \dots$$
(14)

IV. VALIDATION

The effectiveness of the *H2R-AT* model was evaluated by both its accuracy and the reliability in transferring human attention and using it for robot failure avoidance.

A. Experiment Settings: Robot Task Scenarios and Human User Study

Robot Task Design. To learn and validate the effectiveness of the H2R-AT model in guiding robot failure avoidance, two representative task scenarios, "serve water for a human in a kitchen" and "pick up a defective gear in a factory" were designed. To represent typical failures in robot executions, four types of basic abnormal robot executions were designed as "wrong action, wrong pose, wrong region, and wrong spacial relation". Task scenarios were designed with a JACO robot arm mounted with an HD camera by using the software V-REP [19], which is a widely-used simulation platform in robotics research [28] [48]. With a real-gravity environment setting, dynamics and motions of robots could be simulated in the V-REP. Decision-making strategies were delivered to the robot by establishing real-time communication between the V-REP and Python. In our experiment, a robot arm JACO completed tasks under the monitory of a human instructor. The instructor was asked to give verbal reminders to alert the robot when the robot showed abnormal executions. At the moment of human sending alerts, the visual observation from robot perspective was recorded as video training samples. By using the H2R-AT model to align both robot visual perceiving and human verbal alerts at the moment robots showed abnormal executions, the nonlinear relation between human attention and robot attention was modeled to guide robot failure avoidance in an early stage. The robot perceiving was recorded from the mounted HD camera.

Human User Study. To learn and validate the H2R-AT model, a human user study was conducted to collect verbal instructions for abnormal execution description and suggestions for robot execution corrections. The user study was conducted on the crowd-sourcing platform, Amazon Mechanical Turk [31]. In total, 252 English-speaking volunteers were recruited with 1.5 dollar payment each. They were required to watch a 10 seconds video containing abnormal executions, and to provide abnormality descriptions, correction suggestion, and the area they paid attention to, at the moment of detecting abnormal executions. To guarantee the data quality, volunteers were required to be Amazon Turk Masters and have answer Approval Rate greater than 90%with more than fifty approved answers. After filtering the empty or partially empty questionnaires, finally, about 12000 verbal reminders like the ones shown in the figure 6, were collected to label 12000 most-typical images of abnormal robot executions. Six-fold cross-validation was implemented for training and testing the model.

Evaluation Baseline. The human attention generated by the user study was used as the baseline for the robot generated attention.



Fig. 5: Visualization of the attention transfer. The three lines in this figure show the simulated robot abnormal execution, robot attention (recommended by *H2R-AT*), and human attention (baseline) respectively. For all four cases, robot attention is highly consistent with human attention, validating the accuracy of *H2R-AT*. Due to the model uncertainties and vague human descriptions, robot attention is slightly more sparse than human attention.

| Wrong action | You released the cup before it you finished the action. | You released the cup before you poured. | The cup shouldn't have been released until the action was completed and it was back touching the table. |
|------------------------|----------------------------------------------------------------|------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Wrong region | You should have moved closer to the cup to grab it. | You tried to pick the cup without reaching the cup. | You closed your palm a bit early. |
| Wrong pose | Your hand must be fully opened before grabbing the part. | One of your fingers did not move at all during the action. | You did not open your grasp wide enough to pick up the part. |
| Wrong spatial relation | You pushed a little further. | Tried too late and pushed it. | you did not stop moving your arm right before the object. |

Fig. 6: Here is the 3 human reminder examples of 4 different cases respectively.

B. H2R-AT Performance in Attention Transfer

H2R-AT Model Accuracy. As shown in Figure 5, human attention was successfully transferred to robot attention. The three lines denote four types of abnormal executions, modeltransferred robot attention, and actual human attention (baseline), respectively. Precision is the fraction of the correct predictions among all the cases predicted to be one specific type, while recall is the fraction of the correct predictions among all cases with the same type. The accuracy of the H2R-AT model in attention transfer is calculated by the average of the precision and recall. Various levels of confidence scores for the predictions made by the *H2R-AT* model were used as the threshold to accept or reject the true positives. The results are shown in the P-R curves in Figure 7. On each curve, one dot denotes a recall-precision pair given one threshold; one curve denotes the prediction performance of H2R-AT in predicting one category of task scenarios. By setting the confidence threshold as 0.5 in reference, the average precision was about

73.73%. The average recall is about 73.63%. The precision of each case is 76.73%, 72.46%, 73.77%, and 71.99%. The recall of each case is 70.07%, 78.75%, 70.90%, and 74.79%. The stable performance and the P-R curves which are close to the upper-right corner show the effectiveness of the *H2R-AT* model in transferring human attention into a robot in various scenarios.

C. H2R-AT Reliability Analysis

Definition of Reliability. Unlike human attention, which concentrates on one area, robot attention is distributed in several regions due to the model and data uncertainty. For example, in the "wrong pose" case shown in Figure 8, the robot mapped some of its attention on the elbow, while correct attention was on the fingers. The most popular attention regions selected by volunteers in the user study were set as the baseline to measure the model reliability of attention transfer. If the model recommended attention regions are inconsistent with the human attention region, then it means predicted attention is unreliable in supporting robot failure avoidance.

Attention Supported Robot Failure Avoidance. Results show that the robot attentions, which were correctly recommended by the model, are in the same regions with that of humans, showing the good performance of the *H2R-AT* model. Meanwhile, only 73.68% of the verbal attention was correctly transferred to a robot as human expected; the most-popular solution (with the probability of 90.75%) from human volunteers will be adopted to correct robot abnormal executions. Then the robot failure avoidance rate is 66.86%, showing the largely improved robot performance under human guidance. This result shows the potential of using *H2R-AT* model to avoid robot failure in the real-world



Fig. 7: Precision-Recall (P-R) curve of four cases. The confidence threshold is 0.5 in reference. Both the average of precision and recall is about 73%, showing good performance of the model.



(a). wrong part of the robot

(b). wrong object

Fig. 8: Examples of wrong attention regions cased by vague human descriptions. Figure 9(a) shows the wrong region attention caused by the missing information of the faulty part. Figure 9(b) shows the wrong object attention caused by the missing information of object features.

environment.

Analysis of Model Instability. Vague descriptions caused wrong attention mapping. Typical kinds of these wrong attentions are shown in Figure 8. In Figure 8(a), the robot attention mainly focused on the elbow because the description was not clear enough to point out the exact part causing the error. Also, in Figure 8(b), the description was not clear about which cup to pick up. These examples show the two main types of wrong attention mapping which is focusing on the wrong part of the robot and wrong object.

There is a kind of cases in which the generated robot attention focused on random part which are often robotunrelated. These kind of cases mislead the robot to an undesired result. And it's caused because of the similarity of features of different part of the robot perceiving so these kind of cases are hard to be avoided by simply retraining the model. Thus, in order to reduce the meaningless attention focusing on robot-unrelated things, a filter is designed to filter out these distractions, such as wall and carpet. The critical part often appears near the robot and the object which often appears near the center of the perceiving. So the edge parts of the robot view were filtered out to help the robot with accurate attention mapping. It turns out that with the filter, the generated attention is more focused on the robot and the object.



(a). wrong pose without filter (b). wrong pose with filter

Fig. 9: Comparison of robot attention visualization with and without the filter. The using of filters rules out the robot execution irrelevant attention(the two bright spot on the top part of the left figure). It prevents the robot from getting inaccurate attention.

V. CONCLUSION AND DISCUSSION

In this paper, H2R-AT, a novel model using human attention to avoid robot execution failure was proposed. The robot is enabled to identify its abnormal executions by interpreting human verbal reminders. Four types of robot abnormal executions - wrong action, wrong region, wrong pose, and wrong spatial relation - in both daily and industrial scenarios were designed. Volunteers were recruited to provide verbal reminders for the robots and labeled their concerned executions for training the H2R-AT. With an average accuracy of 73.68% in transferring human attention and 67.04% performance improvement, the feasibility of verbally transferring human attention to robots for failure avoidance was validated, showing the great potential in using this H2R-AT model for naturally integrating human intelligence for robot failure avoidance, in scenarios from daily assistance to cooperated manufacturing.

In this work, our primary focus is validating the feasibility of the attention transfer from a human to a robot. It should be noticed that the simulated environment is different from the real-world environment; the verbal reminders varies in different task context with different human operators. To implement this model to practically guide robot executions in a real-world environment, appropriate visual observations, as well as accurate human verbal descriptions for abnormal robot executions need to be provided to ensure the good performance of this model. Task, operator, and environment specific verbal reminders need to be collected for further improving the model performance in robot failure avoidance.

In the future, novel attention-based correction methods will be designed to accurately correct robot executions after human reminders. Moreover, more user study will be conducted to access the satisfactory degree of human on robot abnormal execution corrections. Another potential research could be the knowledge transfer based on this attention model, making the model effective in different task scenarios to guide robot failure avoidance.

REFERENCES

[1] A. Aly, A. Griffiths, and F. Stramandinoli, Metrics and Benchmarks in Human-robot Interaction: Recent Advances in Cognitive Robotics, Cognitive Systems Research, 43, pp. 313-323, 2017.

- [2] A. Bicchi, M. A. Peshkin, and J. E. Colgate, Safety for Physical HumanRobot Interaction, Springer Handbook of Robotics, pp. 1335-1348, 2008.
- [3] A. Brian, L. P. Kaelbling, and T. LozanoPrez, Provably Safe Robot Navigation with Obstacle Uncertainty, The International Journal of Robotics Research, pp. 1760-1774, 2018.
- [4] A. Haidu, D. Kohlsdorf, and M. Beetz, Learning Action Failure Models From Interactive Physics-based Simulations, 2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), pp. 5370-5375, 2015.
- [5] A. Huber, and A. Weiss, Developing Human-Robot Interaction for an Industry 4.0 Robot: How Industry Workers Helped to Improve Remote-HRI to Physical-HRI, Proceedings of the Companion of the 2017 ACM/IEEE International Conference on Human-Robot Interaction, ACM, pp. 137-138, 2017.
- [6] A. Maldonado-Ramrez, L. A. Torres-Mndez and F. Rodrguez-Telles, "Ethologically inspired reactive exploration of coral reefs with collision avoidance: Bridging the gap between human and robot spatial understanding of unstructured environments," 2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), Hamburg, pp. 4872-4879, 2015.
- [7] A. Rossi, K. Dautenhahn, K. L. Koay. and J. Saunders, Investigating Human Perceptions of Trust in Robots for Safe HRI in Home Environments, Proceedings of the Companion of the 2017 ACM/IEEE International Conference on Human-Robot Interaction, pp. 375-376, ACM, 2017.
- [8] A. S. Wang, and O. Kroemer, Learning Robust Manipulation Strategies with Multimodal State Transition Models and Recovery Heuristics.
- [9] A. Vemula, K. Muelling, and J. Oh, Social Attention: Modeling Attention in Human Crowds, 2018 IEEE International Conference on Robotics and Automation (ICRA), Brisbane, QLD, pp. 1-7, 2018.
- [10] B. Mass, S. Ba, and R. Horaud, Simultaneous Estimation of Gaze Direction and Visual Focus of Attention for Multi-person-to-robot Interaction, 2016 IEEE International Conference on Multimedia and Expo (ICME), Seattle, WA, pp. 1-6, 2016.
- [11] B. Mutlu, J. Forlizzi, and J. Hodgins, A Storytelling Robot: Modeling and Evaluation of Human-like Gaze Behavior, 2006 6th IEEE-RAS International Conference on Humanoid Robots, pp. 518-523. IEEE, 2006.
- [12] C. Breazeal, and B. Scassellati. A Context-dependent Attention System for A Social Robot. 1999.
- [13] C. Eppner, S. Hofer, R. Jonschkowski, R. Mart'n-Mart'n, A. Sieverling, V. Wall, and O. Brock, Lessons from the Amazon Picking Challenge: Four Aspects of Building Robotic Systems, Robotics: Science and Systems, 2016.
- [14] C. Sags, and J.J. Guerrero, Visual Correction for Mobile Robot Homing, Robotics and Autonomous Systems, 50(1), pp. 41-49, 2005.
- [15] C. Shekhar, M. Jain, A. A. Raina, and J. Iqbal, Reliability Prediction of Fault Tolerant Machining System with Reboot and Recovery Delay, International Journal of System Assurance Engineering and Management 9(2), PP. 377-400, 2018.
- [16] D. Droeschel, J. Stckler, D. Holz, and S. Behnke, Towards Joint Attention for A Domestic Service Robot - Person Awareness and Gesture Recognition Using Time-of-Flight Cameras, 2011 IEEE International Conference on Robotics and Automation, Shanghai, pp. 1205-1210, 2011.
- [17] D. Park, Z. Erickson, T. Bhattacharjee, and C. C. Kemp, Multimodal Execution Monitoring for Anomaly Detection During Robot Manipulation, 2016 IEEE International Conference on Robotics and Automation (ICRA), Stockholm, pp. 407-414, , 2016.
- [18] E. Einhorn, C. Schrter, and H.M. Gro. Attention-driven Monocular Scene Reconstruction for Obstacle Detection, Robot Navigation and

Map Building, Robotics and Autonomous Systems 59.5, pp. 296-309, 2011.

- [19] E. Rohmer, S. P. N. Singh, and M. Freese, V-REP: A Versatile and Scalable Robot Simulation Framework, International Conference on Intelligent Robots and Systems, pp. 1321-1326, 2013.
- [20] F. Orabona, G. Metta, and G. Sandini, Object-based Visual Attention: a Model for a Behaving Robot, 2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05)-Workshops. IEEE, pp. 89-89, 2005.
- [21] F. Schenkelberg, How Reliable Does a Delivery Drone Have to Be?, 2016 Annual Reliability and Maintainability Symposium (RAMS), Tucson, AZ, pp. 1-5, 2016.
- [22] H. Knight, and R. Simmons, Estimating Human Interest and Attention via Gaze Analysis, 2013 IEEE International Conference on Robotics and Automation, pp. 4350-4355. IEEE, 2013.
- [23] J. Gong, H. Wang, Z. Lu, N. Feng, and F. Hu, Research on Humanrobot Iteraction Security Strategy of Movement Authorization for Service Robot Based on People's Attention Monitoring, 2018 IEEE International Conference on Intelligence and Safety for Robotics (ISR), pp. 521-526, 2018.
- [24] J. Hernandez-Vicen, S. Martinez, J. Garcia-Haro, and C. Balaguer, Correction of Visual Perception Based on Neuro-Fuzzy Learning for the Humanoid Robot TEO, Sensors, 18(4), PP. 972.
- [25] K. Simonyan and A. Zisserman. Very Deep Convolutional Networks for Large-scale Image Recognition, arXiv preprint arXiv:1409.1556, 2014.
- [26] K. Yamazaki, R. Oya, K. Nagahama, K. Okada, and M Inaba, Bottom Dressing by a Dual-arm Robot Using a Clothing State Estimation Based on Dynamic Shape Changes, International Journal of Advanced Robotic Systems 13.1, pp. 5, 2016.
- [27] L. Boccanfuso, S. Scarborough, R. K. Abramson, A. V. Hall, H. H. Wright, and J. M. OKane, A Low-cost Socially Assistive Robot and Robot-assisted Intervention for Children with Autism Spectrum Disorder: Field Trials and Lessons Learned, Auton Robot, pp. 637-655, 2017.
- [28] L. Pitonakova, M. Giuliani, A. Pipe, and A. Winfield, Feature and Performance Comparison of the V-REP, Gazebo and ARGoS Robot Simulators, Annual Conference Towards Autonomous Robotic Systems, pp. 357-368, 2018.
- [29] M. Balasundaram, and S. Muthuswamy, Implementation of Role Assignment and Fault Tree Analysis for Multi Robot Interaction, International Journal of Robotics and Automation, pp. 214-223, 2017.
- [30] M. Beetz, F. Blint-Benczdi, N. Blodow, D. Nyga, T. Wiedemeyer, and Z. Mrton, RoboSherlock: Unstructured Information Processing for Robot Perception, 2015 IEEE International Conference on Robotics and Automation (ICRA), Seattle, WA, pp. 1549-1556, 2015.
- [31] M. Buhrmester, T. Kwang, T. and Gosling, Amazons Mechanical Turk: A New Source of Inexpensive, Yet High-Quality, Data? Perspectives on Psychological Science, 6(1), 2011, pp 35.
- [32] M. Jain, and R. K. Meena, Fault Tolerant System with Imperfect Coverage, Reboot and Server Vacation, Journal of Industrial Engineering International 13(2), pp. 171-180, 2017.
- [33] N. Tanaka, T. Iwama, S. Kumagai, A. Takanishi, and H. Lim, New Collision Force Suppression Mechanism and Base Control of Human-Friendly Robot, 2018 18th International Conference on Control, Automation and Systems (ICCAS), Daegwallyeong, pp. 29-33, 2018.
- [34] P. Barros, G. I. Parisi, C. Weber, and S. Wermter, Emotion-modulated Attention Improves Expression Recognition: A Deep Learning Model, Neurocomputing, 253, pp. 104-114, 2017.
- [35] R. Knepper, S. Tellex, A. Li, N. Roy, and D. Rus, Recovering From Failure by Asking for Help, Autonomous Robots 39.3, pp. 347-362, 2015.

- [36] R. Liu, F. Jia, W. Luo, M. Chandarana, C. Nam, M. Lewis, and K. Sycara, Trust-Aware Behavior Reflection for Robot Swarm Self-Healing, Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems, pp. 122-130, 2019.
- [37] R. M. Aronson, and H. Admoni, Semantic Gaze Labeling for Human-Robot Shared Manipulation, Proceedings of the 11th ACM Symposium on Eye Tracking Research & Applications. ACM, 2019.
- [38] R. Paul, J. Arkin, D. Aksaray, N. Roy, and T. M.Howard, Efficient Grounding of Abstract Spatial Concepts for Natural Language Interaction with Robot Platforms, the International Journal of Robotics Research, pp. 1269-1299, 2018.
- [39] R. Stiefelhagen, and Jie Zhu, Head Orientation and Gaze Direction in Meetings, CHI'02 Extended Abstracts on Human Factors in Computing Systems, pp. 858-859, ACM, 2002.
- [40] S. Gharaaty, T. Shu, W. F. Xie, A. Joubair, and I. A. Bonev, Accuracy Enhancement of Industrial Robots by On-line Pose Correction, 2017 2nd Asia-Pacific Conference on Intelligent Robot Systems (ACIRS), pp. 214-220, 2017.
- [41] S. M. Anzalone, S. Boucenna, S. Ivaldi, and M. Chetouani, Evaluating the Engagement with Social Robots, International Journal of Social Robotics, 7(4), pp.465-478.
- [42] S. M. Anzalone, S. Boucenna, S. Ivaldi, and M. Chetouani. Evaluating the Engagement with Social Robots, Evaluating the Engagement with Social Robots, pp. 465-478, 2015.
- [43] S. Sheikhi, and J. Odobez, Combining Dynamic Head Posegaze Mapping with the Robot Conversational State for Attention Recognition

in Humanrobot Interactions, Pattern Recognition Letters, 66, pp.81-90, 2015.

- [44] S. Thakar, P. Rajendran, V. Annem, A. Kabir, and Satyandra Gupta, Accounting for Part Pose Estimation Uncertainties during Trajectory Generation for Part Pick-Up Using Mobile Manipulators, 2019 International Conference on Robotics and Automation (ICRA), IEEE, pp 1329-1336, 2019.
- [45] T. Mota, and M. Sridharan, Commonsense Reasoning and Knowledge Acquisition to Guide Deep Learning on Robots, Robotics Science and Systems, 2019.
- [46] T. Munzer, M. Toussaint, and M. Lopes, Efficient Behavior Learning in Humanrobot Collaboration, Auton Robot, pp. 1103-1115, 2018.
- [47] Z. Gong, and Y. Zhang, Behavior Explanation as Intention Signaling in Human-Robot Teaming, 2018 27th IEEE International Symposium on Robot and Human Interactive Communication (RO-MAN), pp. 1005-1011, 2018.
- [48] Z. Ma, X. Zhang, L. Zhang, and L. Zhu. Viewpoint Planning of Robot Measurement System Based on V-REP Platform, International Conference on Intelligent Robotics and Applications, pp. 64-75, 2019.
- [49] Z. Yan, L. Sun, T. Duckctr, and N. Bellotto, Multisensor Online Transfer Learning for 3D LiDAR-Based Human Detection with a Mobile Robot, 2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), Madrid, pp. 7635-7640, 2018.
- [50] Z. Yang, X. He, J. Gao, L. Deng, and A. Smola, Stacked Attention Networks for Image Question Answering, The IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp. 21-29, 2016.