# Practical Verification of MapReduce Computation Integrity via Partial Re-execution

Eunjung Yoon

Department of Computer Science and Engineering Pennsylvania State University University Park, USA euy109@psu.edu

arXiv:2002.09560v1 [cs.CR] 21 Feb 2020

Abstract—Big data processing is often outsourced to powerful, but untrusted cloud service providers that provide agile and scalable computing resources to weaker clients. However, untrusted cloud services do not ensure the integrity of data and computations while clients have no control over the outsourced computation or no means to check the correctness of the execution. Despite a growing interest and recent progress in verifiable computation, the existing techniques are still not practical enough for big data processing due to high verification overhead.

In this paper, we present a solution called V-MR (Verifiable MapReduce), which is a framework that verifies the integrity of MapReduce computation outsourced in the untrusted cloud via partial re-execution. V-MR is practically effective and efficient in that (1) it can detect the violation of MapReduce computation integrity and identify the malicious workers involved in the that produced the incorrect computation. (2) it can reduce the overhead of verification via partial re-execution with carefully selected input data and program code using program analysis. The experiment results of a prototype of V-MR show that V-MR can verify the integrity of MapReduce computation effectively with small overhead for partial re-execution.

*Index Terms*—big data anlytics, computation integrity, MapReduce, verification, partial re-execution, program analysis

#### I. INTRODUCTION

Large-scale distributed computations based on big data processing frameworks such as MapReduce and Apache Spark are often outsourced to public cloud service providers, which use computationally powerful platforms. While outsourced computation provisions cost-effective and flexible computing resources to a client, the client has no control over the outsourced computation or no means to check the correctness of the execution. The client expects that the cloud provider honestly executes the outsourced program over data and produce the expected output.

However, a dishonest cloud provider could simply not run a client's code to completion to save on resources or try to cheat and return incorrect computation results to the client. To this end, our goal is to provide guarantees of computation integrity (i.e., verification of execution integrity of the program over the data) that the outsourced computation had not been tampered by adversaries.

Several approaches to verify the integrity of the outsourced computation have been proposed. We consider the cryptographic and complexity-theoretic approaches [1, 2] are still Peng Liu

College of Information Sciences and Technology Pennsylvania State University University Park, USA pxl20@psu.edu

far from practical. Replication-based result verification approaches [3]–[6] in MapReduce computation rely on redundant computation resources to execute duplicated individual task for all the jobs which incurs high cost. MapReduce computation is often distributed across distributed worker nodes, so the approaches are not scalable.

In this work, we are primarily interested in the computation integrity of the user-defined MapReduce programs which are executed by distributed workers. MapReduce framework runs arbitrary binary code submitted by a client. The output is determined by the input data, ensuring its final result should be correct as long as the input data remain preserved and the computation is correct (Figure 1). A naive approach to integrity verification of MapReduce computations is to reexecute every Map and Reduce task, which the workers in the public cloud have executed to verify the correctness of the past computations. However, the overhead of this approach can be very high, particularly if the number of workers is large, as the private cloud is generally less powerful than the public cloud with limited resources. The naive replication-based resultintegrity checks in hybrid cloud [5] is not practical as well, which is the verification is done by checking the consistency of results among replicas. Most replication-based approaches [5]-[7] only provide probabilistic detection of wrong computation. Large scale data processing often requires a large number of replicas that incur very high overhead. We argue that a better approach is to selectively and partially re-execute tasks on the trusted verifier.



Fig. 1. Big Data Processing in Untrusted Cloud Environment

The goal of this work is to provide integrity guarantees of outsourced computations to the clients by efficient computation integrity auditing of workers. In particular, given the input data, the execution of the program over the data can be checked by detecting tampered computation through partial re-execution, which is the practical verification approach with smaller overhead compared to naive full re-execution or replication approach.

To this end, we propose *Verifiable MapReduce* (V-MR), a solution to detect tampered MapReduce computation and identify the malicious workers that produced the wrong output via *partial re-execution*. V-MR collects execution traces during the original execution and preprocesses the traces using data and control flow information to find data slice and program slice (executable slice) for partial re-execution. V-MR performs the partial re-execution of Map and Reduce tasks with selected input data (data slice) and program code (program slice) for efficient auditing the computation results and therefore detecting any malicious workers that did not execute the client's program as expected.

To summarize, we make the following contributions.

- We introduce the efficient and practical Verifiable MapReduce (V-MR) for verifying the integrity of the MapReduce computations via partial re-execution with the reduced re-execution overhead.
- We introduce input data slicing and program slicing by control flow filtering based on static and dynamic analysis to reduce the input dataset which is used for re-execution.
- We present a new program transformation technique using the bytecode engineering library, which automatically transforms the original program to the new code to reexecute for the verification of computation integrity.
- We show the experimental results with several MapReduce applications, the reduced overhead of V-MR compared to naive replication approach that requires full reexecution or random input selection.

## II. RELATED WORK

**Replication-based Verification:** SecureMR [7] adopts a decentralized replication-based integrity verification scheme, and utilizes the existing architecture of MapReduce for replication purposes. Replication is broadly used in distributed systems to improve reliability and fault-tolerance, as well as for computation integrity in big data computing such as MapReduce. However, the assumption that there is no collusion between workers is needed when the result checking is based on voting by the workers. Furthermore, redundant and replication based approach incurs high cost. Our solution does not require the assumption and reduces the overhead of the replication.

Hardware-based Verification: Recently, several approaches have been proposed to protect computation integrity in the cloud leveraging the hardware protection of Intel SGX, which recently has been receiving much attention. For example, Haven [8] runs service instances in hardware-protected SGX enclaves [9] and attest to a hash of the code

so that the instance owner can verify that it was launched correctly. VC3 [10], M2R [11], and Ohrimenko et al. [12] use SGX to perform data analytics, MapReduce computations, and machine learning computations while ensuring confidentiality and integrity. This ensures the integrity of the software stack loaded, but it does not gurantee the execution integrity of the program atop the software stack. Haven [8] relies on Intel SGX for shielded execution of unmodified legacy applications to protect the confidentiality and integrity of a program and its data from the platform on which it runs.

**Proof-based Verification:** Proof-based verifiable computation is a one of the approaches that verifies the integrity of the remote computation. In this class of works, the verifier (the private cloud in our setting) will generate a set of constraints C about the runtime values of variables in the program. During the execution, the prover (the public cloud in our setting) will generate the proof of the computation based on the runtime value of variables. The verifier then will perform a set of tests on the proof based on C. If the program was executed faithfully, the test will pass; otherwise, the test will fail, except for a very small probability. Systems following this direction include Pepper [13], Buffet [14], TinyRAM [15], etc. These approaches incur an expensive overhead in both the verifier and the prover amd can only support simple programs.

**Record-replay approaches:** VM replay [16], ReVirt [17], Ripley [18], POIROT [19], and OROCHI [20] are based on record-and-replay techniques. In particular, POIROT and OROCHI's approaches are mostly close to our approach but their works are for web applications while our work is for MapReduce applications.

## III. THREAT MODEL

The attack surface we consider in this work is that of MapReduce applications which run on distributed worker nodes. Malicious adversaries have capability to manipulate computation results or the user-defined map and reduce functions to produce incorrect results.

We assume that a clients program (user-defined map and reduce function) is benign when she submitted the job request to the cluster, in which the client is honest who will never intentionally try to compromise the worker nodes. However, a clients virtual machine (or container) images in the public cloud are not trusted, which execute the user-defined program. The images may have security vulnerabilities that an adversary can exploit. A powerful adversary can alter input, intermediate and final outputs of MapReduce computations or tamper the user-defined program to produce incorrect results.

We assume the master node is trusted, backed by strong security, which is responsible for job scheduling and resource management of worker nodes in the cluster while workers are not trusted. We also assume the Distributed File System (DFS) is trusted, which manages the file system namespace and regulates access to files by clients.

The verifier is assumed to be trustworthy and protected from attack. The verifier collects the execution trace logs provided by the workers in the public cloud and the  $\langle input, output \rangle$ 

of each task that has been executed and checks if worker nodes have executed the computation as expected.

An important assumption for our re-execution based verification approach is that the MapReduce program (i.e., map and reduce function) is deterministic. The assumption guarantees that all executions of the program with the same input always produce the same output. Thus, when given the same input, an honest worker always returns the correct result for its computation task while a malicious worker may return arbitrary or manipulated results.

#### A. Attacks on the MR computation

In this work, we consider two types of attacks on MR computation.

**Cheating Computation:** A cheating worker tries to skip some part or the entire of the computation and return only a subset of results to reduce its computing cost. Most machine learning and data mining applications involve iterative computations over large datasets so skipping the execution of part of the loops in the program (that has the operation of writing the output to the local disk or DFS) could be an attack example. Cheating workers are relatively easy to detect as discussed in [21].

**Malicious Computation:** A malicious worker can disrupt the computation of map or reduce instances by tampering with the code or data submitted by a client, resulting to yield the incorrect computation results. Even one worker's incorrect computation can yield the overall incorrect final results. In this work, we focused on malicious computation attack.

## B. Integrity of Execution Trace Log

In this work, the execution trace log recorded during normal execution is essential for auditing the computation results. We assume that the execution trace logs are protected from the integrity attack in which an adversary cannot alter the logs, while an untrusted worker could return the wrong computation results. We assume the hypervisor is trusted and leverage virtual machine based techniques [17] that provide hypervisor-supported inspection or tamper-evident logging [22, 23] for protecting the audit logs from the integrity attack. We make the audit logs are append-only such as LogFAS [24]. LogFAS is a PKC-based secure audit logging scheme that can produce publicly verifiable forward-secure and append-only signatures without requiring any online trusted server support.

#### IV. OVERVIEW

Our focus is on verifying the integrity of MapReduce computation in untrusted cloud computing environment. Our approach is to use *partial re-execution* for verifying whether untrusted MapReduce workers provided correct computation results for assigned program and data, by re-executing only a part of the original MapReduce computations to minimize the re-execution overhead.

Through the experiment with multiple MapReduce applications, we observed that there is much similarity among the execution traces of workers as workers assigned for the job execute the same MapReduce program in parallel. Each Map and Reduce task execution follow a relatively small number of execution paths (control flow) and the difference of execution paths is mostly caused by different input data. Our approach is similar to record and replay approaches [16]–[18] which record computation history (execution traces) and replay (reexecution).

Our approach comprises of two stages: online tracing and offline verification. Online tracing is to record execution traces of the user-defined MapReduce application on every worker node during normal execution. The offline verifier analyzes the execution traces to identify and select the requests to reexecute and prepare the new code (if optimization is possible) and the input data for partial re-execution. The verifier reexecutes the chosen requests with chosen input data and compares the outputs of the original execution and re-execution. If the outputs are different, the verifier rejects the computation for the job and reports the malicious worker that executed the request and produced the corresponding incorrect output.

The architecture of V-MR is illustrated in Figure 2. We consider parallel and distributed applications such as MapReduce applications run on worker nodes (computing nodes) in a cluster.

A client submits a job with the user-defined MapReduce program and data to the cluster and receives the computation results. All MapReduce workers assigned for a job are asked to submit the execution traces of the program as proof of the correct execution, which is recorded during program execution. The offline verifier checks if all workers performed the submitted job correctly as expected using the execution traces.

V-MR comprises of 1) offline preprocessing of bytecodelevel execution traces, 2) selection of requests for the reexecution based on control flow and data flow analysis, reexecution code generation if duplicate computations across workers are discovered, and 3) re-execution of the original or new code that has been generated, and 4) the comparison of the outputs from the two executions and make a decision to accept or reject the computation result. For the rejected computation results, V-MR identifies the corresponding workers that computed the requests and marks those as malicious workers.

#### A. Static Control-Flow Analysis

To reduce the overhead of verification, we use static analysis and generate the Control Flow Graph (CFG) from Java bytecode of the user-defined MapReduce program. Static analysis helps reduce the overhead of dynamic analysis and explores all execution paths without running the program, typically from source code. Control flow analysis determines the execution order of program instructions. It brings a global overview of the execution paths that the input data can take during the execution process. In this context, we represent a Java method of a class with its CFG that consists of a set of its execution paths because we use the MapReduce framework in Java.

V-MR generates control flow graphs for map and reduce function using static analysis of the user-defined MapReduce



Fig. 2. Overview of V-MR design

program. Control Flow Graph G=(V,E) is a directed graph which represents the execution flow of the program. Where V is the set of vertices representing basic blocks, and E is the set of edges - an edge from basic block  $BB_1$  to basic block  $BB_2$  ( $BB_1, BB_2 \in V$ ) indicates that execution of block  $BB_2$ can immediately follow the execution of block  $BB_1$ . A basic block is the sequence of executable instruction with a single entry point at the beginning and exit point at the end. Control flow analysis consists in computing the control flow graph of a method, and in performing analyses on this graph.

The Control Flow Graph is used in the verification phase for detecting invalid control flow paths and filtering out the corresponding requests from the verification, which followed the invalid execution path.

A client submits the job to the cluster with the compiled MapReduce program in binary form (jar file). We use the ASM bytecode engineering library to generates the CFG from the bytecode of the program. Figure 4 and Figure 5 show the generated and visualized CFGs for map and reduce function of WordCount program using the ASM and GraphViz [25]. V-MR uses the control flow graph in the verification phase for detecting invalid execution paths and filtering out the corresponding requests from the verification, which followed the invalid execution path.

## B. Tracing during Original Execution

V-MR records the execution trace of the user-defined MapReduce program during normal execution, which runs parallel on multiple worker nodes. An execution trace is a sequence of instructions which represents the execution history of a program and provides the details of a program's dynamic

```
public void map(Object key, Text
           value, Context context
                    ) throws IOException,
2
                        InterruptedException {
        StringTokenizer itr = new
3
            StringTokenizer(value.toString());
        while (itr.hasMoreTokens()) {
4
          word.set(itr.nextToken());
5
          context.write(word, one);
6
        }
      }
8
9
       . . . .
10
11
      public void reduce(Text key,
           Iterable<IntWritable> values,
                      Context context
12
                      ) throws IOException,
13
                           InterruptedException
        int sum = 0;
14
        for (IntWritable val : values) {
15
          sum += val.get();
16
17
        }
18
        result.set(sum);
        context.write(key, result);
19
20
      }
```

Fig. 3. WordCount example code snippet

behavior. V-MR collects and analyzes the execution traces to select the partial input data and code for efficient re-execution.



Fig. 4. Control Flow Graph of WordCount map()



Fig. 5. Control Flow Graph of WordCount reduce()

Recording all of the execution would not be practical due to significant time and space overhead. To reduce the tracing overhead, V-MR logs the selected execution trace in terms of control flow (*control flow trace*), as not all of the trace data is of our interest. V-MR also logs input < key, value > pair, branch condition and count if it is a loop, output < key, value > pair for map() and reduce() function.

V-MR performs partial re-execution during the verification phase. For the verification, V-MR re-executes the program with the same input that processed the corresponding request.

1) Tracing Control Flow: During the original execution, V-MR records the *control flow trace* of the application for each request which each map() or reduce() instance processes. A control flow trace captures the complete path followed by a program during the execution at the level of Basic Block.

```
public void map(Object key, Text
          value. Context context
                   ) throws IOException,
                       InterruptedException {
        mapID = getMapId()
        in = (<key, value>)
        StringTokenizer itr = new
6
            StringTokenizer(value.toString());
              //Basic Block
        T.0
        while (itr.hasMoreTokens())
        bcondition = itr.hasMoreTokens())
9
10
        {
        L1
         word.set(itr.nextToken());
         context.write(word, one);
13
         out = (<word, one>)
14
        }
15
16
      }
```

Fig. 6. Instrumented code snippet for WordCount map() function. The figure shows the bytecode instrumentation at the source level for clarity, but the actual instrumentation is done directly at the bytecode level. The statements in red are those instrumented.

However, tracing the entire execution of the program incurs a high space and time overhead so we trace the bytecode instructions that caused the control flow transfer, such as conditional branch instructions (e.g., ifeq, ifne, if\_icmpeq) and unconditional branch instructions (e.g., goto, jsr, ret). V-MR also records the requests that executed the basic block that includes the calls to context.write() which contributed to the output of the request.

A MapReduce job is assigned and executed by many workers in parallel with the same user-defined program so the computation performed by each Map or Reduce task is expected to follow the same control flow given the same input data. In terms of execution traces, the sequence of bytecode instructions executed is similar (not equal) but different controlflow paths by input-dependent control transfers.

In WordCount example (3 and 4), the control flow traces of map() instances with different input records are as follows. The number in the control flow trace represents the basic block index. To minimize the overhead of tracing, V-MR traces the control flow transfer only. The execution of  $BB_1$ is not recorded as the basic block doesn't have control flow transfer. All mappers commonly execute  $BB_1$  for all requests. During the preprocessing phase, V-MR groups the requests using control flow traces.

```
Input record <1, "test input">:
CTF: 2, 3, 2, 3, 2, 4
Input record <1, "test">:
CFT: 2, 3, 2, 4
```

```
13: aload
                    4
   15: invokevirtual #8
   18: ifeq
                    47
3
   . . . . . . . . . . . . . . . . .
                        . . . . . . .
   21: aload_0
   22: getfield
                    #4
   25: aload
                    4
   27: invokevirtual #9
   30: invokevirtual #10
   33: aload_3
   34: aload 0
11
   35: getfield #4
   38: getstatic #11
14
   41: invokevirtual
                         #12
   44: goto
                    13
15
16
       . . . . . . .
                  . . . . . . . . . . . . .
   47: return
```

Fig. 7. Java bytecode instructions for lines in 4-7 (while loop) in Figure 3

## C. Partial Re-execution

The goal of our work is to produce the practical verification of result integrity via efficient partial re-execution. The reexecution cost needs to be minimized for efficient verification while the correctness and completeness of the verification need to be guaranteed as well. Finding the solution that satisfies both conditions is challenging.

Through our experiments with several MapReduce applications, we observed that there are a relatively small number of control flow paths among the executions of MapReduce instances across workers. That is because the distributed workers execute the same user-defined MapReduce program in parallel on their assigned data partitions for a given job. Different inputs may cause different control flows yet a relatively small number of execution paths (i.e., control flow paths) per each Map or Reduce task. To achieve efficient integrity verification using partial re-execution, we aim to reduce the input data set and the instructions of the re-execution code. Based on our observation, we leverage the control flow trace of each Map and Reduce instance for selecting the part of the input data set (*input data slice*).

V-MR groups the Map and Reduce instances that have the same control flow into a control flow group. Then, V-MR identifies the control flow group that did not lead to the outputs by checking whether the control flow trace of the group shows the execution of the basic block that has the instruction to emit the output (calls to context.write() in Hadoop v2).

1) Input Data Slicing for Partial Re-execution: Naively reexecuting all instances of Map and Reduce function on all input data for the verification incurs the high overhead. To amortize the verification cost, V-MR re-executes only parts of the MapReduce function call instances after it filters out any input records that did not contribute to the output. MapReduce applications have a relatively simple control flows due to the defined programming model of the map and reduce function. Based on our observation that a MapReduce program has multiple identical computations across workers, we use the control flow traces for selecting parts of input data (input data slice) for partial re-execution, similar to POIROT's approach [19]. V-MR groups the Map and Reduce instances that have the same control flow trace into a control flow group such that all instances in a control flow group have the same control flow trace.

Grouping instances that have the same control flow helps to locate the deviated control flow group, which the verifier marks the workers in the group as suspicious. All Map and Reduce function call instances in a control flow group have the same control flow trace. V-MR selects the instances to be re-executed in each control flow group. If V-MR identifies any control flow group that did not take eligible execution paths, that is, one of the all execution paths found in the static CFG, V-MR rejects the computation results. In this step, V-MR can optionally select an aribitrary instance from the control flow group and re-execute it before it stops the entire verification.

Control flow based filtering helps to reduce the input data set used for the verification. However, we need a better approach for more sophisticated attack that does not change the control flow of the original program to avoid the detection while producing tampered computation results.

2) Program Slicing for Partial Re-execution: MapReduce applications have relatively simple control flows due to the defined programming model of the map and reduce function. The control flow-based filtering of the Map and the Reduce instances using their control flow trace and static CFG enables the detection of diverted control flow paths. However, control flow-based filtering may not be sufficient for detecting a more sophisticated attack that does not change the control flow.

For the correctness and completeness of integrity verification, we also consider data dependency of the program. To minimize the re-execution overhead, we try to minimize the program instructions to re-execute as well as the input data set. V-MR identifies the instructions in a control flow group that do not change the output of the program across all instances and eliminates those instructions when it generates the re-execution code using the program transformation. However, V-MR needs to re-execute any instructions that produce different outputs depending on different inputs. To identify those instructions that need to be included in the re-execution code, we adopt the taint-based dependency analysis [26]. Similar to POIROT's approach, V-MR selects an arbitrary instance from a control flow group and re-executes the instance with an input record computed on during original execution. V-MR performs taintbased dependency analysis at the level of bytecode.

An instance of Map or Reduce function emits the output only by calling context.write() method (in Hadoop V2) so we consider the calls to context.write() and an input record < key, value > pair (i.e., parameters of the function) that leads to the method call. V-MR uses taint-analysis for tracking the data dependency but from one arbitrary selected instances to reduce the tracing overhead. During the reexecution of the selected instance, V-MR marks these input parameters (variables) as "tainted" upon the start of the map or reduce function. During the execution of the instance, V-MR marks the instructions that read the tainted variables and their outputs tainted as well (Figure 8). These tainted instructions must be included in the re-execution code as they produce different outputs for different inputs while taking the same control flow path.

The instructions that depend on the tainted variables cannot be eliminated and must be included in the re-execution code. If there are identical computations, in which instructions that do not depend on the tainted variables and control flow instructions, the instructions can be eliminated when the reexecution code is generated.

Taint-based dependency tracking produces the following taint set for the execution of each instruction of the code in Figure 8.

```
Taint set:
1 {value}
2 {itr,value}
3 {itr,value}
4 {word,itr,value}
5 {word,itr,value}
```

Fig. 8. Data Dependency Tracking with Taint analysis (WordCount)

For example, the following instances produce the same control flow trace and fall into the same control flow group. While the two different executions follow the same control flow path, their inputs and outputs are different.

```
Original WordCount Code (Figure 3):
Input <1, "test">
CFT: 2, 3, 2, 4
Output: <"test", 1>
Attacker's WordCount Code (Figure 10):
Input <1, "attack">
CFT: 2, 3, 2, 4
Output: <" ", 1>
```

In this case, control flow analysis solely cannot detect the attack as the two executions follow the same control flow path (2, 3, 2, 4) so the re-execution is needed. We use the taint-based data dependency analysis to determines which instructions need to be included in the re-execution code. In this control flow group, let's suppose that the first instance with the input < 1, "test" > is selected for taint analysis, then the instructions 3, 4, 5, 6 must be included (no elimination of

the instruction). When V-MR re-executes the second instance (attacker's code) with the selected instructions 3, 4, 5, 6 on the input record < 1, "*attack*" >, the output is < "*attack*", 1 >, which is inconsistent with the actual output < "", 1 > from the original execution. V-MR detects the inconsistencies between the outputs and rejects the computation result. V-MR identifies the malicious worker that emitted the wrong output.

3) Program Transformation for Generating Re-execution Code: V-MR transforms the original program into a new program that will be used for the re-execution of selected Map and Reduce instances using the ASM bytecode manipulation library. The ASM reads the original bytecodes (the application class files) and manipulates the bytecodes to generate executable class files that will be used for partial re-execution. In this work, the ASM removes the bytecode instructions identified by our optimization in the previous step (IV-C2) from the original program.

A program transformation should preserve the semantic properties of the original program which should not break the semantics of the target program or cause any difference in outputs. The program syntax of the two programs is different but semantically equivalent, which yields the same output from the computation (execution of the program) with the same input. A program transformation is a partial function, mapping a program P to another program P'. We use the ASM bytecode engineering library to transform the original MapReduce program P into a new MapReduce program P' which the program slicing has been applied to P. V-MR re-executes the selected instances with the transformed MapReduce program during the verification phase.

4) *Re-execution:* Once V-MR completes the selection of Map and Reduce instances to re-execute and the generation of re-execution code during the preprocessing phase, V-MR partially re-executes the instances on the re-execution code and selected input records for the verification of the computation integrity. The verifier runs the re-execution code on the MapReduce runtime in the private cluster/private cloud.

V-MR partially re-executes the selected instances in each control flow group on the re-execution code and chosen input records. It then compares the outputs with those of the original execution to check whether the computations in each control flow group are correct. If the outputs of the re-execution are the same as the outputs of the original execution, V-MR accepts the original computation as correct. If the outputs from two executions are different, V-MR rejects the computation as incorrect and identifies the workers that produced the wrong computation results. V-MR checks the computation integrity of the map and the reduce function separately. If and only if the computation integrity of all mappers is verified and accepted, V-MR proceeds to the next step to verify the computation integrity of the reducers.

## V. IMPLEMENTATION

In this section, we describe our prototype implementation of a prototype of V-MR for MapReduce applications. V-MR's components are implemented in Python and the ASM bytecode library.

#### A. Bytecode Instrumentation

There are two types of bytecode instrumentation techniques - the static instrumentation and the dynamic instrumentation. The static instrumentation inserts all instrumentation code before the program starts execution, while dynamic instrumentation injects the instrumentation code into the running process at runtime. In this work, we use the dynamic instrumentation to check the behavior of the program at runtime.

We use the ASM bytecode engineering library to instrument the bytecodes of the MapReduce applications. Our selection of the ASM bytecode engineering library aside from other instrumentation libraries is for better performance and a small memory footprint. V-MR dynamically instruments the MapReduce application classes loaded into the JVM through a Java agent. Our Java agent is built on the ASM bytecode manipulation framework with the event-based ASM API, which contains a pre-main method that implements a class transformer (ClassFileTransformer) that is composed of a class reader (ClassReader) and a class writer (ClassWriter). The Java agent records the control flow traces of the target program during normal execution without any modification of the program. The control flow trace logs from workers are aggregated and sent to the verifier (Figure 9).

```
package asm;
1
   import java.lang.instrument.Instrumentation;
   public class Agent {
      public static void premain(
4
         String args, Instrumentation inst) {
5
         inst.addTransformer(new
              CustomClassTranformer());
      }
   }
8
9
   . . .
10
   public class CustomClassTransformer
11
      implements ClassFileTransformer {
      public byte[] transform(...) {
         ClassWriter cw = new ClassWriter(true);
14
         ProfilerVisitor cv = new
              ProfilerVisitor(cw);
         ClassReader cr = new
16
              ClassReader(classfileBuffer);
         cr.accept(cv, false);
18
         return cw.toByteArray();
19
      }
   }
20
```

Fig. 9. ASM Java Agent code snippet

#### B. Re-execution Code Generation

V-MR generates efficient re-execution code using program slicing [27] which extracts an executable subset (a slice) of the original program. We use the ASM library with the template which we created from the taint-based dependency tracking. For each control flow group, the new execution code is generated using ASM instrumentation with the common bytecode instructions extracted from the original code, which are also Java bytecodes (executable class file). V-MR runs the new code with the same input data for selected worker node to be checked and compare the results of two executions for the computation integrity.

## VI. EVALUATION

In this section, we show the effectiveness and the performance of our approach. First, we used three attack scenarios to show the effectiveness of V-MR. Second, we show the experiments results that we performed and the metrics that we used to evaluate the performance of V-MR. Table I describes the MapReduce applications we used for the experiment. We show the tracing overhead of V-MR and running time of partial re-execution compared with naive full re-execution.

#### A. Experimental Setup

In this section, we describe the experimental setup for evaluating a prototype of V-MR. We built an experiment Hadoop cluster with two physical machines of the 8-core CPU of 3.40 GHz. The experiment cluster consists of 6 virtual machines (VM), which are provisioned from these two physical machines using VirtualBox and have Ubuntu 14.04 LTS and Hadoop 2.6.2 installed. Among these VM nodes, one VM is configured as a master node and the other VMs configured as worker nodes. We also built a separate private verifier cluster with one physical machine of the 8-core CPU of 3.40 GHz, which consists of 4 virtual machines that have Ubuntu 14.04 LTS and Hadoop 2.6.2 are installed.

Hadoop consists of two layers: MapReduce for data processing, and Hadoop Distributed File System (HDFS) for data storage. A Hadoop cluster includes a single master node and multiple slave nodes. The master node acts as bot the ResourceManager for scheduling map or reduce jobs and the NameNode for hosting HDFS indexes. Each slave node acts as both the NodeManager for conducting the map or reduce operations and the DataNode for storing data blocks in HDFS.

#### B. Attack simulation

In this section, we use several attack cases to show that our verifier is effective to detect the tampered MapReduce computations.

To simulate our attack scenarios, a malicious code may be injected using the Hadoop's "Zip Slip" vulnerability (CVE-2018-8009) that has been recently found. The vulnerability is exploited using a specially crafted archive that holds directory traversal filenames (e.g. ../../evil.sh). The Zip Slip vulnerability [28] can affect numerous archive formats, including tar, jar, war, cpio, apk, rar and 7z. Zip Slip is a directory traversal vulnerability that can be exploited by extracting files from an archive. An attacker can gain access to parts of the file system outside of the target folder in which they should reside. The attacker can then overwrite executable files, thus

 TABLE I

 Description of MapReduce applications

Program	Description
Word Count	A MapReduce program that reads
	text files and counts how often
	words occur.
Inverted Index	A MapReduce program that is an
	index data structure storing a map-
	ping from content, such as words
	or numbers, to its locations in a
	database file, or in a document or
	a set of documents.
Web log analysis (Hit Count)	A MapReduce program that ana-
	lyze Web application logs such as
	the hit count and the frequency of
	URLs.
Web log analysis (Frequency)	A MapReduce program that makes
	frequency distribution of the num-
	ber of hits received by each URL
	sorted in ascending order, which
	simply sorts the list based on the
	number of hits that is calculated
	by the above Web log analysis (Hit
	Count) program.

achieving remote command execution on the victim's machine. The attacker also can overwrite configuration files or other sensitive resources. The vulnerability can be exploited on both client machines and servers.

*Distributed Cache* is a facility provided by the Hadoop MapReduce framework. It caches files when needed by the applications. It can cache read-only text files, archives, jar files, etc. For example, a user-defined MapReduce program will be available on each data node where MapReduce tasks are running. Thus, we can access files from all the data nodes on the MapReduce job.

To simulate the attack, Hadoop's *Distributed Cache* facility is used. The attacker's code is copied to File System and then set up the application's JobConf to add the files to *Distributed Cache* and modify the Mapper or Reducer's code to use the cached files (i.e., attacker's code).

## C. Effectiveness

Our primary focus is on detecting integrity attacks to MapReduce computation where a compromised worker produces the incorrect outputs. We show the effectiveness of our approach with following attack scenarios.

1) Attack Scenario 1: The attacker's MapReduce code ran on one of the worker nodes and produced the incorrect output. Figure 10 shows the attacker's WordCount code snippet. The attacker's code can exploit the integrity attack to WordCount application, which calls method foo() in the map function. This code disrupts the computation output by modifying the word to be emitted to an empty string right before emitting the output, which results in the output with words of the empty string. Figure 11 shows the corresponding bytecodes of map function which invoke the attacker's method call, foo().

The attack is detected by control flow analysis and control flow filtering. The control flow trace shows the diverted control flow which is different from the execution paths in CFG of

```
public class WordCount {
      public static class TokenizerMapper
         extends Mapper<Object, Text, Text,
             IntWritable>{
      private final static IntWritable one = new
          IntWritable(1);
      private Text word = new Text();
8
      public void map(Object key, Text value,
10
          Context context
                  ) throws IOException,
                       InterruptedException {
         StringTokenizer itr = new
             StringTokenizer(value.toString());
14
         while (itr.hasMoreTokens()) {
            word.set(itr.nextToken());
             if (word.getLength() > 0)
16
                foo(word);
            context.write(word, one);
18
19
         }
20
     public static void foo(Text value) {
         value.clear();
24
25
   }
```

Fig. 10. Code snippet of simulated Attack #1 (WordCount)

the original program. V-MR detects the diverted control flow and rejects the computation results.

V-MR was able to detect the attack by control flow analysis and re-execution was not needed. V-MR's verification result is REJECT.

2) Attack Scenario 2: The attacker's code produced incorrect outputs while the control flow trace shows that it followed a valid control flow path.

In the WordCount program, context.write(word, one) method call emits the output, a  $\langle key, value \rangle$  pair, where the parameter 'one' represents one occurrence of a word. The attacker's code uses '2' instead of '1', with the modified statement as follows.

```
private final static IntWritable one =
new IntWritable(2);
```

This attack does not change the control flow of the program but the modification of the constant variable alters the output. For example, the attacker's code produces < "test", 2 >, which is different from the correct output < "test", 1 >. The Figure 15 and Figure 16 show the difference in the bytecodes between the original code and the attack code. Figure 17 shows the tampered output of Mapper by the attack.

1	13:	aload 4	
2	15:	invokevirtual #	ŧ8
3	18:	ifeq 64	
4	21:	aload_0	
5	22:	getfield #4	
6	25:	aload 4	
7	27:	invokevirtual #	ŧ9
8	30:	invokevirtual #	ŧ10
9	33:	aload_0	
10	34:	getfield #4	
11	37:	invokevirtual #	ŧ11
12	40:	ifle 50	
13	43:	aload_0	
14	44:	getfield #4	
15	47:	invokestatic #1	12
16	50:	aload_3	
17	51:	aload_0	
18	52 <b>:</b>	getfield #4	
19	55:	getstatic #13	
20	58:	invokevirtual #	±14
21	61:	goto 13	
22	64:	return	
23			
24	public	static void	
	fo	o(org.apache.had	doop.io.Text);
25	Code:		
26	0:	aload_0	
27	1:	invokevirtual #	15
28	4:	return	

Fig. 11. Bytecode snippet of WordCount Attack #1

year	11
year.	2
years	14
years,	2
yelling	1
yellow,	1
yells.	1
yen	1
yet	29
yet."	1



•••			
1			
1			
1			
1			
• • • •			



	• • •	
2	years,	1
3	yellow,	1
	• • •	
	zenana,	1
5	zenith 1	
7	31	
8	57	336

Fig. 14. Incorrect final result of WordCount job caused by one compromised Mapper

The control flow trace shows the valid execution path but the re-execution can identify that the output is wrong, which is different from the original output.

Control flow analysis was not sufficient for detecting the attack and re-execution was needed. V-MR was able to detect the attack via partial re-execution and the verification result is REJECT.

1	static (	ι.		
1	Static (	57		
2	Code:			
3	0:	new	#14	
4	3:	dup		
5	4:	iconst_1		
5	5:	invokespe	cial	#15
7	8:	putstatic	#11	
8	11:	return		

Fig. 15. Attack #2: original bytecode snippet

-			
static {	};		
Code:			
0:	new	#14	
3:	dup		
4:	iconst_	_2	
5:	invokes	special	#15
8:	putstat	tic #11	
11:	return		

Fig. 16. Attack #2: attack bytecode snippet

• • •	
years,	2
yellow,	2
zenana,	2
zenith 2	

Fig. 17. Incorrect intermediate result of WordCount job by Attack #2

The attacker compromises the program without being detected by early stage of the verification. However, the re-

TABLE II DETECTION OF EXPLOITS

TABLE III TIME OVERHEAD FOR TRACING (MAPPER)

				Program	# input records	w/o tracing	w/ tracing
Exploits	Description	FP	FN	WordCount	6982	3171	3725 (17.4%)
Cheating worker Malicious worker Malicious worker	skipping computation malicious modification on map function malicious modification on reduce function	No No No	Yes No No	InvertedIndex WebLog (HitCount) WebLog (Frequency)	6982 1891715 18617	4006 33188 3683	4170 (24%) 64515 (39.6%) 3970 (7.2%)
Collusion	collusion attack	No	No				

execution will detect the output is different from the original output.

*3) Attack Scenario 3: Collaborating attackers:* The collaborating attackers' code executes on two different workers, which modifies their computation results as the same output with given the same input, using Attack #2.

This collaborating attack is detected by partial re-execution as the outputs of two computations by collaborating workers are different from the outputs of the re-executions by V-MR. While other replication-based verification approaches that use peer comparisons for checking the integrity cannot detect a collaborating attack unless the majority of the workers are honest. However, our approach can detect collaborative attacks.

Control flow analysis cannot detect the attack, while reexecution was able to detect the attack. V-MR's verification result is REJECT.

#### D. Experimental Results

We measured the efficiency of the prototype of V-MR and the overhead of tracing (with instrumentation) compared to a baseline of simple re-execution of the replication-based verification approach for the evaluation of the verifier. To measure the overhead introduced by trace logging, we performed experiments with several Hadoop applications that are obtained from [29]. We use five MapReduce applications: WordCount, InvertedIndex, and three applications for Web application log analysis using the NASA Web Log dataset, for the experiments. We measured the execution time of the original code and re-execution code.

1) *Time and Space Overhead for Tracing:* We performed experiments to study the time and space overhead for recording control flow traces of running Hadoop programs on worker nodes during original execution.

Table III shows the time overhead of V-MR with the instrumentation. While we can optimize further to reduce the tracing overhead in the future, the current prototype of V-MR incurs moderate tracing overhead. The space overhead for tracing is shown in Table IV. Since the verification is performed by a client's on-demand request and the trace logs can be deleted upon the verification is complete, the space overhead for tracing is not a concern in this work.

2) *Execution time:* We measured the execution time for each Map and Reduce task of full re-execution and partial re-execution to get the idea of speedup by our partial re-execution approach compared to a naive replication-based approach.

TABLE IV Space overhead of tracing (Mapper)

Program	# input records	Size (KB)
WordCount	6982	121
InvertedIndex	6982	182
WebLog (HitCount)	1891715	4867
WebLog (Frequency)	18617	37

Table V shows the experiment results in terms of the speedup by V-MR. Most applications we used for the experimentation show that the execution time is much faster than the naive full execution even with the small size of input data set, while the Weblog application that finds the frequency of Hit count of URLs did not speed up. We intentionally selected this uncommon type of MapReduce application to simulate the case that our partial re-execution approach is not efficient in reducing the re-execution cost. The application does not have any control flow transfer in the map and reduce function as it simply sorts the results produced by WebLog Hitcount application. There is no option to optimize for the selection of data and the instruction elimination for re-execution. In this case, while it is very rare, it can be verified by reexecuting on randomly chosen instances, which is similar to other replication-based approaches. The effect of speedup of re-execution by input data slicing and program slicing is dependent on the ratio of the slice cut on data and program code. The Hadoop applications we used for the experiment in this work have relatively small code size (a small number of instructions) in the map and reduce function with small input data set so did not lead to dramatic speedup. However, more complex applications that have much more instructions and larger input data set can benefit more from the effect of the speedup, which remains to be future work.

## VII. CONCLUSION

This work demonstrated our approach to practical verification of the integrity of outsourced computation via partial re-execution. We investigated the computation result integrity of MapReduce applications as the case study. Our verification framework, V-MR can detect the tampered MapReduce computations using partial re-execution without modifying the MapReduce framework or application source code. V-MR reduces the re-execution cost by input data slicing and program slicing techniques based on the control flow and data dependency analysis. V-MR is more effective and considerably more efficient than other naive replication-based verification

 TABLE V

 Performance comparison (re-execution time)

Program -	Input Size (# records) Baseline V-MR		Running Time (ms) Baseline V-MR		Speedup
WordCount	6982	5865	3171	2663	1.19
InvertedIndex	6982	5839	4006	2804	1.43
WebLog (HitCount)	1891715	1237097	33188	17589	1.89
WebLog (Frequency)	18617	18617	3683	3683	1

approaches as it can detect attacks against computation integrity with no false positives and few false negatives (shown in Table II) while it can also speed up the verification via efficient partial re-execution.

#### REFERENCES

- B. Parno, J. Howell, C. Gentry, and M. Raykova, "Pinocchio: Nearly practical verifiable computation," in *Proceedings of the 2013 IEEE Symposium on Security and Privacy*, ser. SP '13. Washington, DC, USA: IEEE Computer Society, 2013, pp. 238–252.
- [2] M. Rabin, R. Servedio, and C. Thorpe, "Highly efficient secrecypreserving proofs of correctness of computations and applications," in *Proc. of 22nd Annual Symposium on Logic in Computer Science*. ACM, 2007, pp. 63–76.
- [3] M. Moca, G. Silaghi, and G. Fedak, "Distributed results checking for mapreduce in volunteer computing," in *Parallel and Distributed Processing Workshops and Phd Forum (IPDPSW)*, 2011 IEEE International Symposium on, 2011, pp. 1847–1854.
- [4] S. Zhao, V. Lo, and C. Dickey, "Result verification and trust-based scheduling in peer-to-peer grids," in *Peer-to-Peer Computing*, 2005. P2P 2005. Fifth IEEE International Conference on. IEEE, 2005, pp. 31–38.
- [5] Y. Wang, J. Wei, and M. Srivatsa, "Result integrity check for mapreduce computation on hybrid clouds," in 2013 IEEE Sixth International Conference on Cloud Computing, June 2013, pp. 847–854.
- [6] Y. Wang and J. Wei, "Viaf: Verification-based integrity assurance framework for mapreduce," in *IEEE International Conference on Cloud Computing (CLOUD)*. IEEE, 2011, pp. 300–307.
- [7] W. Wei, J. Du, T. Yu, and X. Gu, "Securemr: A service integrity assurance framework for mapreduce," in *Proc. of Computer Security Applications Conference, ACSAC*, 2009, pp. 73–82.
- [8] A. Baumann, M. Peinado, and G. Hunt, "Shielding applications from an untrusted cloud with haven," in *Proceedings of the 11th USENIX Conference on Operating Systems Design and Implementation*, ser. OSDI'14. Berkeley, CA, USA: USENIX Association, 2014, pp. 267– 283.
- [9] F. McKeen, I. Alexandrovich, I. Anati, D. Caspi, S. Johnson, R. Leslie-Hurd, and C. Rozas, "Intel software guard extensions (Intel SGX) support for dynamic memory management inside an enclave," in *Proceedings of the Hardware and Architectural Support for Security and Privacy 2016*, ser. HASP 2016. Association for Computing Machinery, 2016.
- [10] F. Schuster, M. Costa, C. Fournet, C. Gkantsidis, M. Peinado, G. Mainar-Ruiz, and M. Russinovich, "VC3: Trustworthy Data Analytics in the Cloud Using SGX," in *Proceedings of the 2015 IEEE Symposium on Security and Privacy*, ser. SP '15. Washington, DC, USA: IEEE Computer Society, 2015, pp. 38–54.
- [11] T. T. A. Dinh, P. Saxena, E.-C. Chang, B. C. Ooi, and C. Zhang, "M2r: Enabling stronger privacy in mapreduce computation," in *Proceedings* of the 24th USENIX Conference on Security Symposium, ser. SEC'15. Berkeley, CA, USA: USENIX Association, 2015, pp. 447–462.
- [12] O. Ohrimenko, M. Costa, C. Fournet, C. Gkantsidis, M. Kohlweiss, and D. Sharma, "Observing and preventing leakage in mapreduce," in *Proceedings of the 22Nd ACM SIGSAC Conference on Computer and Communications Security*, ser. CCS '15. New York, NY, USA: ACM, 2015, pp. 1570–1581.

- [13] B. Braun, A. J. Feldman, Z. Ren, S. Setty, A. J. Blumberg, and M. Walfish, "Verifying computations with state," in *Proceedings of the Twenty-Fourth ACM Symposium on Operating Systems Principles*, ser. SOSP '13. ACM, 2013, pp. 341–357.
- [14] R. S. Wahby, S. Setty, Z. Ren, A. J. Blumberg, and M. Walfish, "Efficient ram and control flow in verifiable outsourced computation," in *Network* and Distributed System Security Symposium (NDSS), February 2015.
- [15] E. Ben-v, A. Chiesa, D. Genkin, E. Tromer, and M. Virza, "Snarks for c: Verifying program executions succinctly and in zero knowledge," in *Advances in Cryptology – CRYPTO 2013*, R. Canetti and J. A. Garay, Eds. Berlin, Heidelberg: Springer Berlin Heidelberg, 2013, pp. 90–108.
- [16] T. C. Bressoud and F. B. Schneider, "Hypervisor-based fault tolerance," in Proceedings of the Fifteenth ACM Symposium on Operating Systems Principles, ser. SOSP '95. New York, NY, USA: ACM, 1995, pp. 1–11.
- [17] G. W. Dunlap, S. T. King, S. Cinar, M. A. Basrai, and P. M. Chen, "Revirt: Enabling intrusion analysis through virtual-machine logging and replay," *SIGOPS Oper. Syst. Rev.*, vol. 36, no. SI, pp. 211–224, Dec. 2002.
- [18] K. Vikram, A. Prateek, and B. Livshits, "Ripley: Automatically securing web 2.0 applications through replicated execution," in *Proceedings of the* 16th ACM Conference on Computer and Communications Security, ser. CCS '09. New York, NY, USA: ACM, 2009, pp. 173–186.
- [19] T. Kim, R. Chandra, and N. Zeldovich, "Efficient patch-based auditing for web application vulnerabilities," in *Proceedings of the 10th USENIX Symposium on Operating Systems Design and Implementation (OSDI* '12), 2012.
- [20] C. Tan, L. Yu, J. B. Leners, and M. Walfish, "The efficient server audit problem, deduplicated re-execution, and the web," in *Proceedings of the 26th Symposium on Operating Systems Principles*, ser. SOSP 17. Association for Computing Machinery, 2017, p. 546564.
- [21] E. Yoon and A. C. Squicciarini, "Toward detecting compromised mapreduce workers through log analysis," in 14th IEEE/ACM International Symposium on Cluster, Cloud and Grid Computing, CCGrid 2014, Chicago, IL, USA, May 26-29, 2014. IEEE Computer Society, 2014, pp. 41–50.
- [22] S. A. Crosby and D. S. Wallach, "Efficient data structures for tamperevident logging," in *Proceedings of the 18th Conference on USENIX Security Symposium*, ser. SSYM'09. USENIX Association, 2009, pp. 317–334.
- [23] D. Ma and G. Tsudik, "A new approach to secure logging," *Trans. Storage*, vol. 5, no. 1, pp. 2:1–2:21, Mar. 2009.
- [24] A. A. Yavuz, P. Ning, and M. K. Reiter, "Efficient, compromise resilient and append-only cryptographic schemes for secure audit logging," in *Financial Cryptography and Data Security*, A. D. Keromytis, Ed. Berlin, Heidelberg: Springer Berlin Heidelberg, 2012, pp. 148–163.
- [25] J. Ellson, E. Gansner, L. Koutsofios, S. C. North, and G. Woodhull, "Graphviz— open source graph drawing tools," in *Graph Drawing*, P. Mutzel, M. Jünger, and S. Leipert, Eds. Berlin, Heidelberg: Springer Berlin Heidelberg, 2002, pp. 483–484.
- [26] J. Newsome, D. Song, J. Newsome, and D. Song, "Dynamic taint analysis: Automatic detection, analysis, and signature generation of exploit attacks on commodity software," in *In In Proceedings of the* 12th Network and Distributed Systems Security Symposium, 2005.
- [27] M. Weiser, "Program slicing," in Proceedings of the 5th International Conference on Software Engineering, ser. ICSE '81. Piscataway, NJ, USA: IEEE Press, 1981, pp. 439–449.
- [28] "Zip slip vulnerability," https://snyk.io/research/zip-slip-vulnerability.
- [29] T. Gunarathne, Hadoop MapReduce v2 Cookbook. Packt Publishing, 2015.