Fair Isaac Technical Paper

Subject: A Quadratic Programming Solution to the FICO Credit Scoring Problem

From: Bruce Hoadley (BCH – A34 X27051)

Date: July 14, 2000

Abstract

The classic Fair, Isaac score development problem is to find a score engineered scorecard that maximizes divergence. Over the years, Fair, Isaac has developed excellent solutions to this problem, but we have never solved it exactly – until now. INFORM9, INFORM11, INFORM12 (ITP), and INFORM13 (References [1], [5], [6], [7]) are all based on heuristic algorithms that find excellent solutions, but not exact solutions. We discovered this while developing the range engineering part of INFORM13. The heuristic Hooke-Jeeves algorithm was getting caught in high dimensional wedges and giving solutions that failed certain sanity checks. This stimulated Gerald Fahner and myself to look for alternative ways to solve the problem.

What we have discovered is that many of the classic Fair, Isaac score development problems can be solved by either a single quadratic program or a short (e.g., length 5) sequence of quadratic programs. In today's computing environment, this is attractive, because modern quadratic programming algorithms are very fast. For a large score engineered scorecard (171 attributes, 60 linear equality constraints, and 106 pattern constraints), the solving quadratic program ran in 7 seconds on my new Dell laptop using MATLAB.

The purpose of this paper is to describe how to solve five different score engineered score development problems with quadratic programming. The problems are called

- 1. Classic problem
- 2. Penalized classic problem
- 3. Non-zero in-weighting problem
- 4. Range engineering problem
- 5. Score engineered regression problem.

Problems 1, 2, and 5 can be solved exactly with a single quadratic program. Problems 3 and 4 require short sequences of quadratic programs.

For a fraud score test case, I provide all of the MATLAB code for solving the five problems, and provide the resulting score weights and divergences.

For the first problem, I compare my solution to two other solutions to the same problem. The first alternative solution is based on the Hooke-Jeeves version of INFORM-*NLP* (also known as INFORM13), and the second alternative solution is based on SAS quadratic programming, which was developed by Gerald Fahner.

The MATLAB and SAS versions of quadratic programming give virtually the same solution, and both yield higher divergence than INFORM13.

Table of Contents

Abstract	1
Table of Contents	3
1. Introduction	5
1.1. Score formula	5
1.2. Score moments	5
1.3. Score engineering	6
1.4. Fair Isaac score development problem	7
2. Classic Problem	8
2.1. Mathematical formulation of the classic problem	8
Classic problem	9
Alternative to classic problem Classic quadratic program	
Theorem 1	
2.2. MATLAB quadratic programming	
2.3. MATLAB formulation of classic quadratic program	
2.4. Fraud case study	
Data	14
INFORM-NLP scorecard	
2.5. MATLAB code for the classic quadratic program	
Computation of <i>C</i>	
Computation of d	
Computation of $A p$	
- <i>,</i>	
Computation of f0, bp, lb, ub	
Matrices for the classic quadratic program	
Solving the quadratic program	
Transformation to weight of evidence scale	
2.6. Fraud solution to the classic quadratic program	22
3. Penalized Classic Problem	22
3.1. Mathematical formulation of the penalized classic problem	
Penalized classic quadratic program.	
3.2. MATLAB formulation of the penalized classic quadratic program	24
3.3. MATLAB code for the penalized classic quadratic program	24
3.4 Fraud solution to the penalized classic quadratic program	25

4.0 Non-zero In-weighting Problem	25
4.1. Mathematical formulation of the non-zero in-weighting problem	25
4.2. MATLAB formulation of the non-zero in-weighting quadratic program	27
4.3. MATLAB code for the non-zero in-weighting quadratic program	28
4.4. Fraud solution to the non-zero in-weighting quadratic program	29
5. Range Engineering Problem	30
5.2 Mathematical formulation of the range engineering problem	30
5.2. MATLAB formulation of the range engineered quadratic program	33
5.3. MATLAB code for the range engineered quadratic program	33
5.4. Fraud solution to the range engineered quadratic program	35
6. Score Engineered Regression Problem	36
6.1. Mathematical formulation of the score engineered regression problem	36
6.2. MATLAB formulation of the score engineered regression quadratic program	38
6.3. MATLAB code for the score engineered regression quadratic program	38
6.4. Fraud solution to the score engineered regression quadratic program	40
References	41
Appendix 1. Program for Converting a SAS Data Set to a Unix Text File	42
Appendix 2. Score Engineered Scorecards	

1. Introduction

1.1. Score formula

In this paper I consider a score of the form

$$Score = \sum_{j=1}^{p} S_{j} X_{j},$$

Score =
$$\sum_{j=1}^{p} S_j X_j$$

where the X_j 's are arbitrary numerical predictors and the S_j 's are score weights. Of course in multiple regression theory the S_j 's are called regression coefficients and in linear discriminant analysis the score is called a linear discriminant. In the case where the X_j 's are attribute indicator variables, the score is a scorecard. In INFORM-*NLP* (formerly called INFORM13) theory the score was transformed to so-called (**S**, **X**) space (see Reference [1]), where the score was also of the above form.

The score can be written in matrix notation as

$$Score = S' * X$$
,

where

$$S' = (S_1, ..., S_p)$$

$$X' = (X_1, ..., X_p).$$

I use bold to indicate a matrix or vector and use * to indicate ordinary matrix multiplication.

1.2. Score moments

One problem considered in this paper is to maximize the divergence of *Score* subject to a large set of score engineering constraints. In order to describe this problem mathematically, I need to introduce some notation.

The relevant score moments are

$$\mu_{G} = E[Score \mid G] = E[S' * X \mid G] = S' * E[X \mid G] = S' * MG$$

$$\mu_{B} = E[Score \mid B] = S' * MB$$

$$\sigma_{G}^{2} = V[Score \mid G] = V[S' * X \mid G] = S' * Cov[X \mid G] * S = S' * CG * S$$

$$\sigma_{B}^{2} = V[Score \mid G] = S' * CB * S$$

$$\sigma_{B}^{2} = V[Score \mid G] = S' * CB * S$$

$$\sigma_{B}^{2} = S' * \left[\frac{CG + CB}{2}\right] * S = S' * C * S.$$

The above expectations and variances are computed with respect to the observation weights (e.g., the sample weights), which impose a probability distribution over the observations.

The divergence of the score is

$$Div[Score] = \frac{(\mu_{G} - \mu_{B})^{2}}{\sigma^{2}}$$

$$= \frac{(S' * MG - S' * MB)^{2}}{S' * C * S}$$

$$= \frac{(S' * (MG - MB))^{2}}{S' * C * S}$$

$$= \frac{(d' * S)^{2}}{S' * C * S}.$$

This is a ratio of quadratic functions of S.

1.3. Score engineering

At Fair, Isaac, scores are developed under what is called score engineering. For scorecards, score engineering includes centering constraints, no-inform constraints, cross restrictions, grouping restrictions, in weighting, pattern constraints, score weight size constraints, and weight of evidence scale. All of these score engineering constraints amount to constraints on the score weights, *S*. Here I write these constraints in mathematical notation.

The centering, no-inform, cross restrictions, grouping restrictions, and in-weighting constraints can be defined by a set on linear equality constraints in S. In matrix notation these can be written as

$$Ac * S = bc$$
.

The pattern constraints are a set of linear inequality constraints, which can be written as

$$Ap * S \leq bp$$
.

The size constraints are a set of linear inequality constraints, which can be written as

$$l \leq S \leq u$$
.

The two types of linear inequality constraints are specified separately, because they will be treated differently by the score development algorithm.

The weight of evidence scale constraint is the non-linear equality constraint

$$\sigma^2 = \mu_G - \mu_B$$

or

$$S' * C * S = d' * S$$
.

This is a quadratic equality constraint in S.

1.4. Fair Isaac score development problem

The Fair, Isaac score development problem can now be expressed in mathematical programming language. It is to

Find
$$S$$
 to

Maximize
$$\frac{(d'*S)^2}{S'*C*S}$$
Subject to:
$$Ac*S = bc$$

$$S'*C*S = d'*S$$

$$Ap*S \le bp$$

$$1 \le S \le u$$

As it stands, this is not a quadratic program. The objective function is a ratio of quadratic functions – not quadratic. Most of the constraints are linear – except for the weight of evidence constraint, which is non-linear. So it is a non-linear programming problem.

I find it fascinating that this problem has never been optimally solved at Fair, Isaac – until recently. The current version of the production score development system is based on the INFORM11 weights engine. Using linear programming, INFORM11 produces a score, which is a sufficient statistic for log odds under proprietary assumptions. INFORM11 usually produces a score with good divergence, but it is not maximum divergence.

The Inform Test Platform (ITP) and the SAS version of INFORM-*NLP* use the Hooke-Jeeves pattern search algorithm to solve the classic Fair, Isaac problem, which is stated above. However, recent research has shown that the Hooke-Jeeves pattern search algorithm does not always precisely maximize divergence. This is because the algorithm is a heuristic and can get stuck in small wedges of score weight space. INFORM-*NLP* usually yields a higher divergence than INFORM11, but it is not always maximum divergence.

One of the aims of this paper is to show how to solve the Fair, Isaac score development problem exactly using quadratic programming.

2. Classic Problem

2.1. Mathematical formulation of the classic problem

In most applications of the Fair, Isaac problem, we have the conditions

$$bc = 0$$

$$bp = 0$$

$$l = -\infty$$

$$u = +\infty$$

Clearly the centering constraints have zero on the right hand side. On the weight of evidence scale, the no-inform constraint has zero on the right hand side. A typical cross restriction or group restriction is of the form $S_i = S_j$, which can be written as $S_i - S_j = 0$.

The only exception to bc = 0 is non-zero in weighting, which is somewhat rare.

A typical pattern constraint is of the form $S_i \leq S_j$, which can be written as $S_i - S_j \leq 0$.

I call this typical case, the

Classic problem

Find
$$S$$
 to

Maximize
$$\frac{(d'*S)^2}{S'*C*S}$$
Subject to:
$$Ac*S = 0$$

$$S'*C*S = d'*S$$

$$Ap*S \le 0$$

One thing that makes this problem difficult is the non-linear weight of evidence constraint. The role of this constraint is to keep the score weights on a standard scale. Without this constraint, there would be no unique solution to this problem, because divergence is invariant to a multiplication of the score weights by a constant.

But there is an alternative way to constrain the score weights to be on some reasonable scale. Just use the simple linear constraint $d' * S = \delta$, where δ is an apriori guess at the maximum divergence associated with the optimal solution. Then the problem becomes

Alternative to classic problem

Find
$$S$$
 to

Maximize
$$\frac{(d'*S)^2}{S'*C*S}$$
Subject to:
$$Ac*S = 0$$

$$d'*S = \delta$$

$$Ap*S \le 0$$
.

This problem maximizes divergence on some other scale that is an approximation to the weight of evidence scale.

This problem can be re-expressed as

Find
$$S$$
 to

Maximize $\frac{\delta^2}{S'*C*S}$

Subject to:

 $Ac*S=0$
 $d'*S=\delta$
 $Ap*S \le 0$.

And this can be re-expressed as

Classic quadratic program

Find
$$S$$
 to
Minimize $S'*C*S$
Subject to:
 $Ac*S=0$
 $d'*S=\delta$
 $Ap*S \le 0$,

which is a quadratic program.

For a large sized scorecard, this quadratic program can be solved in about 7 seconds on my laptop using MATLAB.

This quadratic program maximizes divergence on a scale defined by $d' * S = \delta$, which is only an approximation to the weight of evidence scale. It turns out that if I transform the solution to the classic quadratic program to the weight of evidence scale, then I get a solution to the classic problem. I state this as a theorem.

Theorem 1

Let T be a solution to the classic quadratic program, and let $W = \beta T$ be its transformation to a weight of evidence scale. Then W is a solution to the classic problem.

<u>Proof</u>

Let *S* be the solution to the classic problem. And let

$$U = \left(\frac{\delta}{d'S}\right)S = \alpha S.$$

In Lemma 1 below, I show that Wis feasible for the classic problem. Hence,

$$Div(W) \le Div(S).$$
 (1)

In Lemma 2 below, I show that U is feasible for the classic quadratic program. Hence,

$$Div(\mathbf{U}) \leq Div(\mathbf{T}).$$

Since divergence is invariant to linear transformations, we have

$$Div(\mathbf{U}) = Div(\mathbf{S})$$

 $Div(\mathbf{T}) = Div(\mathbf{W})$.

Hence

$$Div(S) \le Div(W).$$
 (2)

Equations (1) and (2) imply

$$Div(\mathbf{W}) = Div(\mathbf{S}),$$

which proves Theorem 1.

Q.E.D

Lemma 1

Wis feasible for the classic problem.

Proof

Define $W = \beta T$, where

$$\beta = \frac{d' * T}{T' * C * T}.$$

Note that

$$Ac * W = Ac * \beta T = \beta (Ac * T) = 0 .$$

Next note that

$$W' * C * W = (\beta T)' * C * (\beta T) = \beta \beta (T' * C * T)$$
$$= \beta \left(\frac{d' * T}{T' * C * T}\right) (T' * C * T) = \beta (d' * T)$$
$$= d' * W.$$

And finally note that

$$Ap * W = Ap * \beta T = \beta (Ap * T) \le 0 .$$

So the score weight vector, $W = \beta T$, is on the weight of evidence scale, it satisfies the linear equality constraints, and it satisfies the linear inequality constraints.

Q.E.D

Lemma 2

U is feasible for the classic quadratic program.

<u>Proof</u>

First note that

$$Ac * U = Ac * \alpha S = \alpha (Ac * S) = 0$$
.

Next note that

$$d'*U = d'*\alpha S = d'*\left(\frac{\delta}{d'S}\right)S = \delta.$$

And finally note that

$$Ap * U = Ap * \alpha S = \alpha (Ap * S) \le 0$$

Q.E.D

In summary, I have shown that in order to solve the classic problem, you need only solve the classic quadratic program and transform the solution to the weight of evidence scale. This takes 7 seconds on my PC using MATLAB.

2.2. MATLAB quadratic programming

The general quadratic program solved by MATLAB is

Find
$$S$$
 to

Minimize $\left(\frac{1}{2}\right)S'*H*S+f'S$

Subject to:

 $Aeq*S=beq$
 $A*S \le b$
 $l \le S \le u$.

2.3. MATLAB formulation of classic quadratic program

In the previous section I argued that the classic problem could be reduced to the classic quadratic program

Find
$$S$$
 to
Minimize $S'*C*S$
Subject to:
 $Ac*S = 0$
 $d'*S = \delta$
 $Ap*S \le 0$,

So the matrices in the general form of the MATLAB quadratic program are

$$H = 2C$$
 $f = f0$, where $f0 = 0$
 $Aeq = \begin{bmatrix} d' \\ Ac \end{bmatrix}$
 $beq = \begin{bmatrix} \delta \\ 0 \end{bmatrix}$
 $A = Ap$
 $b = bp$, where $bp = 0$
 $l = lb$, where $lb = -\infty$
 $u = ub$, where $ub = +\infty$

2.4. Fraud case study

Data

For the case study, I use the high-risk fraud data used by Nina Shikaloff and Gerald Fahner in their INFORM-*NLP* studies. These data were also used in my previous fraud studies reported in [3] and [4].

The SAS data set that I started with is called iphr_i and is located in

/fico/prod/ap/score/rde/znxs5/bldcard/unix/db

The SAS program that I used to convert the relevant variables in the SAS data set to a UNIX text file is given in Appendix 1.

INFORM-NLP scorecard

Nina Shikaloff has applied the SAS version of INFORM-*NLP* to this data. This version of INFORM-*NLP* is based on the Hooke-Jeeves pattern search algorithm. Since this is a heuristic, it finds an excellent solution, but not necessarily the optimal solution. The scorecard is shown in Appendix 2. This large scorecard involves a heavy use of score engineering, so it is a good case study. The characteristics and attributes used are shown in this scorecard.

The attribute indicator variables in the SAS data set are of the form vc_a , where c = 1,2,...,25 (varies over characteristics) and $a = 0,1,...,A_c - 1$, where A_c is the number of attributes for characteristic c. For every characteristic, a = 0 corresponds to the NO INFORMATION attribute, which is always listed as the last attribute, even when it has no counts.

In Appendix 1, the characteristics are listed in the same order as they appear in the scorecard. And the attribute indicator variables are also ordered in the same order as they appear in the scorecard. So, for example, attribute indicator variables $v1_1 - v1_6$, $v1_0$ are associated with char170. The complete list is:

Attribute Indicator	Corresponding
<u>Variables</u>	Characteristic
v1_1-v1_6 v1_0	170
v2_1-v2_6 v2_0	191
v3_1-v3_6 v3_0	193
v4_1-v4_12	211
v5_1-v5_7 v5_0	260
v6_1-v6_10 v6_0	320
v7_1-v7_3 v7_0	330
v8_1-v8_6 v8_0	380
v9_1-v9_3 v9_0	471
v10_1-v10_2 v10_0	503
v11_1-v11_6 v11_0	533
v12_1-v12_6 v12_0	635
v13_1-v13_3 v13_0	665
v14_1-v14_7 v14_0	710
v15_1-v15_3 v15_0	830
v16_1-v16_5 v16_0	835
v17_1-v17_4 v17_0	840
v18_1-v18_4 v18_0	843
v19_1-v19_2 v19_0	860
v20_1-v20_3 v20_0	870
v21_1-v21_15 v21_0	950
v22_1-v22_4 v22_0	960
v23_1-v23_5 v23_0	961
v24_1-v24_9 v24_0	962
v25_1-v25_9 v25_0	965

2.5. MATLAB code for the classic quadratic program

As described above, in order to set up the classic quadratic program, I need to first compute the matrices

$$C, d, Ac, Ap, f0, bp, lb, ub$$
.

Computation of C

The SAS program in Appendix 1 created a UNIX text file called frdata, which had 14,000 rows and 206 variable – space delimited. This UNIX text file was converted to a

PC text file called Frdata.txt. The MATLAB command for putting this into a $14,000 \times 206$ MATLAB matrix called Frdata is

```
load Frdata.txt;
```

In the matrix Frdata, the attribute indicator variables are variables 36 through 206. The MATLAB command for creating the overall design matrix is

```
X=Frdata(:,36:206);
```

<u>Warning</u>: Unfortunately, this X is related to, but not exactly the same as the random vector of prediction variables, X, which appears in the theory.

The indicator variable for non-fraud is variable 32. So the MATLAB command for creating the overall performance vector (a $14,000 \times 1$ vector) is

```
y=Frdata(:, 32);
```

The serial number is variable 3, so the MATLAB command for creating the serial number vector is

```
sn=Frdata(:, 3);
```

The validation sample corresponds to observation with serial numbers 1,4 and 8. So the MATLAB commands for creating the development and validation performance variable are

```
yv=y(((sn==1)|(sn==4)|(sn==8)));

yd=y(\sim((sn==1)|(sn==4)|(sn==8)));
```

Similarly, to create the design matrix for the development sample and the validation sample, use the MATLAB commands

```
Xd=X(\sim((sn==1)|(sn==4)|(sn==8)),:);

Xv=X(((sn==1)|(sn==4)|(sn==8)),:);
```

To create the development and validation design matrices for the goods and bads, the MATLAB commands are

```
XdG=Xd(yd==1,:);
XdB=Xd(yd==0,:);
XvG=Xv(yv==1,:);
XvB=Xv(yv==0,:);
```

To compute the development average covariance matrix, the MATLAB command is

```
C=(Cov(XdG)+Cov(XdB))/2;
```

Computation of d

In MATLAB, this is easy. The command is

```
d=(mean(XdG)-mean(XdB))';
```

Computation of Ac

Each row of Ac corresponds to a score engineering equality constraint. In this problem there are 25 centering constraints, 25 no inform constraints, and 9 cross restriction constraints, for a total of 59. The number of score weights is 171. So Ac is a 59×171 matrix.

The first step in the process is to create a 59×171 matrix of zeros. This is done with the MATLAB command

```
Ac=zeros(59,171);
```

Centering constraints

Now I work on the first 25 rows of Ac, which are the centering constraints. There is one centering constraint for each characteristic. Define a vector, called high, of 25 score weight indices, which give the last attribute of each characteristic. For example, the last score weight index of characteristic 170 is 7 and the last score weight index of characteristic 191 is 14, etc. The MATLAB command is

Next define a vector, called low, of 25 score weigh indices, which give the first attribute of each characteristic. To do this, the MATLAB commands are

```
low=ones(1,25);
for i=2:25
    low(i)=high(i-1)+1;
end
```

The centering constraints involve attribute weights. Initially, all of these weights can be put into one vector with the MATLAB command

```
e=mean(XdG)+mean(XdB);
```

Now we can replace the first 25 rows of Ac with the correct values, which are given by the MATLAB commands

No Information constraints

The next 25 rows of A_c contain the left-hand side of the no information constraints. A no information constraint just sets a no information score weight equal to zero. The MATLAB commands for the next 25 rows are

Cross restrictions

Examination of the cross restrictions in the scorecard in Appendix 2 leads to the following MATLAB code for setting up rows 51 through 59 of Ac.

```
Ac(51,1)=1;

Ac(52,8)=1;

Ac(53,58)=1;

Ac(54,65)=1;

Ac(55,90)=1;

Ac(56,91)=1;

Ac(57,69)=1;

Ac(57,98)=-1;

Ac(58,69)=1;

Ac(58,118)=-1;

Ac(59,69)=1;

Ac(59,121)=-1;
```

Computation of Ap

From the scorecard in Appendix 2 we can see that there are 106 pattern constraints. Each pattern constraint corresponds with one row of the matrix Ap, so Ap is a 106×171 matrix. We initialize Ap with all zeros via the MATLAB command

Each pattern constraint can be written in the form $(+1)S_j + (-1)S_k \le 0$ or $(-1)S_j + (+1)S_k \le 0$, where j < k. There are 106 values or j, which I put into the MATLAB vector

```
j=[2 3 4 5 9 10 11 12 16 17 18 19 24 . . .
25 26 27 28 29 30 31 32 36 37 38 . . .
39 40 43 44 45 46 47 48 49 50 51 . . .
54 55 59 60 61 62 66 69 69 73 74 . . .
75 76 80 81 82 83 86 87 92 93 94 . . .
95 98 99 102 103 104 105 108 109 . . .
110 118 121 122 125 126 127 128 . . .
129 130 131 132 133 134 135 136 . . .
137 138 141 142 143 147 148 149 . . .
152 153 154 155 156 157 158 159 . . .
162 163 164 165 166 167 168 169];
```

Associated with each j is a value of k. In most cases, k = j + 1, but there are exceptions. The MATLAB code for computing the vector of k's is

```
k=j+1;
k(13)=31;
k(14)=30;
k(44)=71;
```

Associated with each j is a coefficient, which is either (+1) or (-1) (see above discussion). The coefficients associated with the j's are given in the MATLAB vector, \mathbf{a} , which is computed by the following MATLAB code.

```
a=ones(1,106);
a(1:4)=-1;
a(22:41)=-1;
a(43:84)=-1;
```

The coefficients associated with the k's are given in the MATLAB vector, na, which is just the negative of a, and is computed by the following MATLAB code.

$$na=-a;$$

These vectors can now be used to compute the Ap matrix as follows

Computation of f0,bp,lb,ub

```
f0=zeros(171,1);
bp=zeros(106,1);
lb=(-inf)*ones(171,1);
ub=inf*ones(171,1);
```

Matrices for the classic quadratic program

As we saw above, the matrices needed for the quadratic classic problem are

$$H = 2C$$

$$f = 0$$

$$Aeq = \begin{bmatrix} d' \\ Ac \end{bmatrix}$$

$$beq = \begin{bmatrix} \delta \\ 0 \end{bmatrix}$$

$$A = Ap$$

$$b = 0$$

$$l = -\infty$$

$$u = +\infty$$

In this paper, I will be describing many application of the MATLAB quadratic programming algorithm. The MATLAB notation for these matrices for this first problem is H1, f1, Aeq1, beq1, A1, b1, l1, and u1.

The MATLAB code for computing these matrices is

```
H1=2*C;
f1=f0;
Aeq1=[d';Ac];
beq1=[1.753;zeros(59,1)];
A1=Ap;
b1=bp;
11=1b;
u1=ub;
```

Note that I chose $\delta = 1.753$.

Initial solution for the quadratic program

To run the MATLAB quadratic program, you need an initial solution. I suspect that it is a good idea to have a pretty good initial solution. Here is how I generated a pretty good initial solution.

I first ran the quadratic program with no pattern constraints with the MATLAB code

The variable x01 is a score weight vector. I then heuristically adjusted this score weight vector so that it was feasible for the pattern constraints.

Solving the quadratic program

The MATLAB code for solving the quadratic program is

```
S1=quadprog(H1,f0,Ap,bp,Aeq1,beq1,lb,ub,x01)
;
```

Transformation to weight of evidence scale

As we have discussed, this solution is not quite on a weight of evidence scale. You convert it to the weight of evidence scale via the MATLAB code

2.6. Fraud solution to the classic quadratic program

The solution is given in Appendix 2. The development divergence is 1.753. The development divergence for the Hooke-Jeeves version of INFORM-*NLP* is 1.732, which is less than 1.753. This proves that the Hooke-Jeeves version of INFORM-*NLP* does not maximize divergence even though it is designed to do so. The reason is the heuristic nature of the Hooke-Jeeves pattern search algorithm.

The quadratic program also produced a score that has more validation divergence than the Hooke-Jeeves INFORM-*NLP* score. This would not always be the case, but it was true for this example.

Gerald Fahner has developed SAS software for maximizing divergence using SAS quadratic programming. His solution is given as the second score in Appendix 2. As you can see, Gerald's solution is virtually the same as mine.

3. Penalized Classic Problem

3.1. Mathematical formulation of the penalized classic problem

The penalized version of the classic problem is

Penalized classic quadratic program

Find
$$S$$
 to

Minimize
$$S' * C * S + \frac{\lambda}{p} S' * S$$

Subject to:

$$Ac * S = 0$$

$$d' * S = \delta$$

$$Ap * S \leq 0$$
.

This can be re-expressed as

Find S to

Minimize
$$S' * \left(C + \frac{\lambda}{p}I\right) * S$$

Subject to:

$$Ac * S = 0$$

$$d' * S = \delta$$

$$Ap * S \leq 0$$
,

where *I* is a $p \times p$ identity matrix. As you can see, this is also a quadratic program.

3.2. MATLAB formulation of the penalized classic quadratic program

For the penalized classic quadratic program, the matrices in the general form of the MATLAB quadratic program are

$$H = 2\left(C + \frac{\lambda}{p}I\right)$$

$$f = 0$$

$$Aeq = \begin{bmatrix} d' \\ Ac \end{bmatrix}$$

$$beq = \begin{bmatrix} \delta \\ 0 \end{bmatrix}$$

$$A = Ap$$

$$b = 0$$

$$l = -\infty$$

$$u = +\infty$$

3.3. MATLAB code for the penalized classic quadratic program

The MATLAB notation for these matrices for the penalized classic quadratic program is H2, f2, Aeq2, beq2, A2, b2, 12, and u2.

The MATLAB code for computing these matrices is

```
H2=2*(C+(.095/171)*eye(171));
f2=f0;
Aeq2=Aeq1;
beq2=beq1;
A2=Ap;
b2=bp;
12=lb;
u2=ub);
```

The only matrix that changes for the penalized classic quadratic program is the H matrix. Note that I chose $\lambda = .095$. This is the value that maximized divergence on the validation sample. It was found by a line search in λ space.

The MATLAB code for solving the penalized classic quadratic program is

3.4. Fraud solution to the penalized classic quadratic program

As we have discussed, this solution is not quite on a weight of evidence scale, but can be transformed to the weight of evidence scale in the usual way.

The solution is given in Appendix 2. The development divergence is 1.752, which is smaller than the development divergence for Score 1 – the un-penalized case. However, the validation divergence is slightly larger than for score 1, which is what was expected with an optimal choice of λ .

For many of the attributes, the score weights for Score 2 are closer to zero than the score weights for Score 1. This is what I expected. However, the number of attributes, for which this was not true, surprised me.

4.0 Non-zero In-weighting Problem

4.1. Mathematical formulation of the non-zero in-weighting problem

A non-zero in-weight is of the form $S_j = IW_j$, where $IW_j \neq 0$. In this case, the classic Fair, Isaac problem can not be solved by a single quadratic program. In this section I propose an iterative quadratic programming solution to the problem.

The non-zero in-weighting problem can be formulated as

Non-zero in-weighting problem

Find
$$S$$
 to

Maximize
$$\frac{(d'*S)^2}{S'*C*S} - \frac{\lambda}{p}S'*S$$
Subject to:
$$Ai*S = IW$$

$$Ac*S = 0$$

$$S'*C*S = d'*S$$

$$Ap*S \le 0$$
.

This problem can be re-expressed by plugging the weight of evidence constraint into the objective function. The result is

Find
$$S$$
 to

Maximize $d'*S - \frac{\lambda}{p}S'*S$

Subject to:

 $Ai*S = IW$
 $Ac*S = 0$
 $S'*C*S = d'*S$
 $Ap*S \le 0$.

This can be converted to a minimization problem by changing the sign of the objective function. The result is

Find
$$S$$
 to

Minimize $-d'*S + \frac{\lambda}{p}S'*S$

Subject to:

 $Ai*S = IW$
 $Ac*S = 0$
 $S'*C*S = d'*S$
 $Ap*S \le 0$.

This is almost a quadratic program. The fly in the ointment is the quadratic equality constraint S' * C * S = d' * S.

It is well known (private communication from Bob Oliver) that under regularity conditions, this problem can be solved by putting the quadratic constraint into the objective function with a Lagrange multiplier, and then solving an iterative sequence of quadratic programs.

For a fixed value of the Lagrange multiplier, ϕ , you get the quadratic program

Non-zero in-weighting quadratic program

Find S to

Minimize
$$-d'*S + \frac{\lambda}{p}S'*S + \phi(S'*C*S - d'*S)$$

Subject to:

$$Ai * S = IW$$

$$Ac * S = 0$$

$$Ap * S \leq 0$$
.

Let $S(\phi)$ be the solution to this quadratic program with a fixed ϕ . The non-zero inweighting problem can be solved by solving the non-linear equation

$$S(\phi)' * C * S(\phi) - d' * S(\phi) = 0.$$

This equation can be solved by standard line search techniques.

4.2. MATLAB formulation of the non-zero in-weighting quadratic program

The objective function for the non-zero in-weighting quadratic program can be rewritten as

$$\phi S' * C * S + \frac{\lambda}{p} S' * S - (1 + \phi)d' * S$$

$$= S' * \left(\phi C + \frac{\lambda}{p} I\right) * S - (1 + \phi)d' * S$$

$$= \left(\frac{1}{2}\right)S' * 2\left(\phi C + \frac{\lambda}{p} I\right) * S - (1 + \phi)d' * S.$$

So the matrices in the general form of the MATLAB quadratic program are

$$H = 2\left(\phi C + \frac{\lambda}{p}I\right)$$

$$f = -(1 + \phi)d$$

$$Aeq = \begin{bmatrix} Ai \\ Ac \end{bmatrix}$$

$$beq = \begin{bmatrix} IW \\ 0 \end{bmatrix}$$

$$A = Ap$$

$$b = 0$$

$$l = -\infty$$

$$u = +\infty$$

4.3. MATLAB code for the non-zero in-weighting quadratic program

In this application p = 171 and I will take $\lambda = .095$, which was the optimal value for the penalized classic quadratic program.

The MATLAB notation for the matrices in the non-zero in-weighting quadratic program is H3, f3, Aeq3, beq3, A3, b3, 13, and u3.

The MATLAB code for computing the matrices, which are the same as for the classic quadratic program, is

As an initial value of ϕ I take ϕ = .1. So the MATLAB code for computing H3 and f3 is

To compute Aeq3 and beq3 I first need to specify the non-zero in weighting. The non-zero in-weighting constraints are

$$S_2 = .5$$

 $S_{13} = .3$.

For Characteristic 170, this increases the first positive score weight, and for Characteristic 191, this increases the last positive score weight.

The MATLAB code for computing Ai is

The MATLAB code for computing Aeq3 and beq3 is

The MATLAB code for solving the non-zero in-weighting quadratic program is

4.4. Fraud solution to the non-zero in-weighting quadratic program

The iterations of this quadratic program, over ϕ during the line search, went as follows:

ф	S3' * C * S3 – d' * S3
.1	36.45
2	295
1.75	262
.75	.341
1	.019
1.025	0012

The final score weights, S3, along with the development and validation divergences are shown in Appendix 2. As expected, the development divergence is slightly smaller due to the in weighting. Also note that S_2 and S_{13} are in-weighted to the correct values of .5 and .3 respectively. And I verified that Score 3 is on the weight of evidence scale.

5. Range Engineering Problem

5.2 Mathematical formulation of the range engineering problem

A general formulation of the range engineering problem is

Find
$$S$$
 to

Minimize
$$\sum_{j=1}^{p} R_{j} \left(S_{j} - T_{j} \right)^{2} + \frac{\lambda}{p} S' * S$$

Subject to:
$$Ai * S = IW$$

$$Ac * S = 0$$

$$S' * C * S = d' * S$$

$$Ap * S \leq 0$$

$$\frac{(d' * S)^{2}}{S' * C * S} \geq Div$$

The parameter, Div, is a relaxation of the divergence obtained in Stage 1 of INFORM-NLP. If we take Score 3 to be the result of Stage 1, then the relaxation of the divergence can be something like

$$Div = (.95)(1.731)$$

= 1.64.

The T_j 's are target score weights for the range engineering. The idea is to move the score weights towards these targets without losing too much divergence. If you want to shrink certain score weights as much as possible, then you could set their T_j 's to zero. If you want to expand certain positive score weights as much as possible (within reason), then you can set their T_j 's too be something like +3. If you want to expand certain negative score weights as much as possible (within reason), then you can set their T_j 's too be something like -3.

The R_j 's allow you to put more or less emphasis on engineering the individual score weights.

In this paper I will not address the issue of a user interface to these parameters, or even what recommended values they should take. It is clear that this mathematical approach gives the user a lot of flexibility in engineering the score weight ranges.

To express this problem in matrix notation, note that

$$\sum_{j=1}^{p} R_{j} (S_{j} - T_{j})^{2} = (S - T)' * R * (S - T),$$

where R is a $p \times p$ diagonal matrix with R_j as the jth diagonal element. Further matrix algebra yields

$$(S-T)'*R*(S-T) = S'RS - 2T'RS + T'RT.$$

So the range engineering problem can be re-expressed as

Minimize
$$S'RS - 2T'RS + T'RT + \frac{\lambda}{p}S' * S$$

Subject to:

Find S to

$$Ai * S = IW$$

$$Ac * S = 0$$

$$S' * C * S = d' * S$$

$$Ap * S \leq 0$$

$$\frac{(d'*S)^2}{S'*C*S} \ge Div.$$

The term *T'RT* can be dropped from the objective function, because it is a constant. And the weight of evidence constraint can be used to simplify the divergence constraint. The result is

Minimize
$$S'RS - 2T'RS + \frac{\lambda}{p}S' * S$$

Subject to:

$$Ai * S = IW$$

$$Ac * S = 0$$

$$S' * C * S = d' * S$$

$$Ap * S \leq 0$$

$$-d'*S \leq -Div$$
.

The objective function can now be re-arranged to yield

Minimize
$$S'\left(R + \frac{\lambda}{p}I\right)S - 2T'RS$$

Subject to:

$$Ai * S = IW$$

$$Ac * S = 0$$

$$S' * C * S = d' * S$$

$$Ap * S \leq 0$$

$$-d'*S \leq -Div$$
.

This is almost a quadratic program. The fly in the ointment is the quadratic equality constraint S' * C * S = d' * S.

It is well known (private communication from Bob Oliver) that under regularity conditions, this problem can be solved by putting the quadratic constraint into the objective function with a Lagrange multiplier, and then solving an iterative sequence of quadratic programs.

For a fixed value of the Lagrange multiplier, ϕ , you get the quadratic program

Minimize
$$S'\left(R + \frac{\lambda}{p}I\right)S - 2T'RS + \phi(S'*C*S - d'*S)$$

Subject to:

$$Ai * S = IW$$

$$Ac * S = 0$$

$$Ap * S \leq 0$$

$$-d'*S \leq -Div$$
.

The objective function can be re-arranged to yield

Range engineered quadratic program

Find
$$S$$
 to

Minimize $S'\left(\phi C + R + \frac{\lambda}{p}I\right)S - \left(\phi d' + 2T'R\right)S$

Subject to:

 $Ai*S = IW$
 $Ac*S = 0$
 $-d'*S \le -Div$
 $Ap*S \le 0$.

Let $S(\phi)$ be the solution to this quadratic program with a fixed ϕ . The range engineering problem can be solved by solving the non-linear equation

$$S(\phi)' * C * S(\phi) - d' * S(\phi) = 0.$$

This equation can be solved by standard line search techniques.

5.2. MATLAB formulation of the range engineered quadratic program

The matrices in the general form of the MATLAB quadratic program are

$$H = 2\left(\phi C + R + \frac{\lambda}{p}I\right)$$

$$f = -(\phi d + 2RT)$$

$$Aeq = \begin{bmatrix} Ai \\ Ac \end{bmatrix}$$

$$beq = \begin{bmatrix} IW \\ 0 \end{bmatrix}$$

$$A = \begin{bmatrix} -d' \\ Ap \end{bmatrix}$$

$$b = \begin{bmatrix} -Div \\ 0 \end{bmatrix}$$

$$l = -\infty$$

$$u = +\infty$$

5.3. MATLAB code for the range engineered quadratic program

In this application p = 171 and I will take $\lambda = .095$, which was the optimal value for the penalized classic quadratic program.

The MATLAB notation for the matrices in the range engineering quadratic program is H4, F4, Aeq4, beq4, A4, b4, 14, and u4.

The MATLAB code for computing the matrices, which are the same as for the classic quadratic program (problem 1), is

The MATLAB code for computing the matrices, which are the same as for the non-zero in-weighting quadratic program (problem 3), is

The MATLAB code for computing the matrices A4 and b4 is

To compute H4 and f4 I need to first compute R and T. For this application, I will only do range engineering on the first two characteristics; i.e., the first 14 attributes. I will make all 14 attributes equally important, so

$$R_j = \begin{cases} 1 & \text{for } j = 1, 2, ..., 14 \\ 0 & \text{otherwise} \end{cases}$$

I want to do range restriction for characteristic 170 and range expansion for characteristic 191. For characteristic 170, the target attribute score weights will be roughly one half of the optimal score weights; i.e., 0, .15, .08, -.03, -.13, -.44, and 0. For characteristic 191, the target attribute score weights will be roughly 1.5 times the optimal score weights; i.e., 0, -1.71, -1.55, -.86, -.003, .14, and 0.

The MATLAB code for computing R is

```
R=zeros(171,171);
for i=1:14
  R(i,i)=1;
end
```

The MATLAB code for computing [⊥] is

```
T=zeros(171,1);
T(1:14)=[0 .15 .08 -.03 -.13 -.44 0 . . .
0 -1.71 -1.55 -.86 -.003 .14 0];
```

As an initial value of ϕ I take (based on some experience with this problem) ϕ = .019. So the MATLAB code for computing H4 and f4 is

$$H4=2*((.019)*C+R+(.095/171)*eye(171));$$

 $f4=-((.019)*d+2*R*T);$

The MATLAB code for solving the range engineered quadratic program is

5.4. Fraud solution to the range engineered quadratic program

The iterations of this quadratic program, over ϕ during the line search, went as follows:

ф	S4' * C * S4 – d' * S4
.019	.0120
.025	00063

The final score weights, S4, along with the development and validation divergences are shown in Table 1. As expected, the development divergence is 1.641, which is slightly above the lower bound of 1.64. Note that S_2 and S_{13} are in-weighted to the correct values of .5 and .3 respectively. The score weight range for characteristic 170 has been restricted and the score weight range for characteristic 191 has been expanded. And I verified that score 4 is on the weight of evidence scale.

6. Score Engineered Regression Problem

6.1. Mathematical formulation of the score engineered regression problem

In a regression problem there is a dependent variable, y, which usually takes on a variety of numerical values. Revenue is an example of a dependent variable. For linear regression, the model fit to the dependent variable is of the form

$$E[y | X] = S_0 + \sum_{j=1}^{p} S_j X_j.$$

The score engineered regression problem can be formulated as

Find S_0 and S to

Minimize
$$\sum_{i=1}^{n} \left(y_i - \left(S_0 + \sum_{j=1}^{p} S_j x_{ij} \right) \right)^2 + \frac{\lambda}{p} S' * S$$

Subject to:

$$Ai * S = IW$$

$$Ac * S = 0$$

$$Ap * S \leq 0$$
.

Note that in the regression case, there is no weight of evidence scale. This is because the dependent variable, y, dictates the scale of the final model. To specify reasonable in weighting, you have to know about the natural scale of the score weights.

In the case where the X_i 's are attribute indicator variables, the scorecard part of the

final model is
$$\sum_{j=1}^{p} S_j X_j$$
.

The score engineered regression problem can be put into matrix notation by defining some new matrices. Let

$$\beta' = \begin{bmatrix} S_0 & S' \end{bmatrix}$$

$$y' = \begin{bmatrix} y_1, y_2, ..., y_n \end{bmatrix}$$

$$Xr = \begin{bmatrix} 1 & x_{11} & x_{12} & \bullet & \bullet & x_{1p} \\ 1 & x_{21} & & & x_{2p} \\ \bullet & \bullet & & \bullet \\ 1 & x_{n1} & x_{n2} & \bullet & \bullet & x_{np} \end{bmatrix}$$

$$Ir = \begin{bmatrix} 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \quad ((p+1) \times (p+1) \text{ matrix})$$

$$Air = \begin{bmatrix} 0 & Ai \end{bmatrix}$$

$$Acr = \begin{bmatrix} 0 & Ac \end{bmatrix}$$

$$Apr = \begin{bmatrix} 0 & Ac \end{bmatrix}$$

$$Apr = \begin{bmatrix} 0 & Ap \end{bmatrix}.$$

In this notation, the score engineered regression problem is

Find
$$\boldsymbol{\beta}$$
 to Minimize $(y - Xr * \boldsymbol{\beta})'(y - Xr * \boldsymbol{\beta}) + \frac{\lambda}{p} \boldsymbol{\beta}' * Ir * \boldsymbol{\beta}$ Subject to:
$$Air * \boldsymbol{\beta} = IW$$

$$Acr * \boldsymbol{\beta} = 0$$

$$Apr * \boldsymbol{\beta} \leq 0$$
.

The first part of the objective function can be expanded as follows:

$$(y - Xr * \beta)' (y - Xr * \beta) = \beta' * Xr' * Xr * \beta - 2 * y' * Xr * \beta + y' * y.$$

Since y' * y is a constant, it can be dropped from the objective function. The result is

Score engineered regression quadratic program

Find
$$\beta$$
 to Minimize $\beta'*\left(Xr'*Xr+\frac{\lambda}{p}Ir\right)*\beta-2*y'*Xr*\beta$ Subject to:
$$Air*\beta=IW$$

$$Acr*\beta=0$$

$$Apr*\beta\leq0$$
.

6.2. MATLAB formulation of the score engineered regression quadratic program

For the score engineered regression quadratic program, the matrices in the general form of the MATLAB quadratic program are

$$H = 2\left(Xr' * Xr + \frac{\lambda}{p}Ir\right)$$

$$f = -2(Xr' * y)$$

$$Aeq = \begin{bmatrix} Air \\ Acr \end{bmatrix}$$

$$beq = \begin{bmatrix} IW \\ 0 \end{bmatrix}$$

$$A = Apr$$

$$b = 0$$

$$l = -\infty$$

$$u = +\infty$$

6.3. MATLAB code for the score engineered regression quadratic program

The first step to computing these matrices is to compute y, Xr, Ir, Air, Acr, Apr, and IW.

I take the variable y to be the indicator variable of non-fraud. The MATLAB vector for this variable is yd (see Section 2.5), where d stands for the development sample.

The MATLAB code for computing the rest of the preliminary matrices is

```
Xr=[ones(9907,1) Xd];
Ir=eye(172);
Ir(1,1)=0;
Air=[zeros(2,1) Ai];
Acr=[zeros(59,1) Ac];
Apr=[zeros(106,1) Ap];
IW=[.5;.3];
```

For the computation of Xd, Ai, Ac, and Ap see Sections 2.5, 4.3, 2.5, and 2.5 respectively.

The MATLAB notation for the matrices in the score engineered regression quadratic program is H5, f5, Aeq5, beq5, A5, b5, 15, and u5.

The MATLAB code for these matrices is

```
H5=2*(Xr'*Xr+(.095/171)*Ir);
f5=-2*(Xr'*yd);
Aeq5=[Air;Acr];
beq5=[IW;zeros(59,1)]
A5=Apr;
b5=bp;
15=1b;
u5=ub;
```

To run the score engineered regression quadratic program, I need a starting solution. For this I will use

```
x05=[.5;S3];
```

The MATLAB code for solving the score engineered regression quadratic program is

```
beta5=quadprog(H5,f5,Apr,bp,Aeq5,beq5,lb,ub,x05);
```

6.4. Fraud solution to the score engineered regression quadratic program

The intercept term is beta5 (1) = .499. The scorecard part of the regression formula is called S5 and is shown in Appendix 2. Note that the score weights tend to be smaller than for the other scores. This is because S5 is not on a weight of evidence scale. In fact you have to multiply S5 by 2.874 to transform it to a weight of evidence scale. However, S5 satisfies all of the score engineering constraints – including the non-zero in weighting.

The development divergence of *S*5 is only .926. This is partly due to the inappropriate in weighting, but it also shows that simple least squares regression is not the best way to solve the binary outcome problem.

References

- [1] Hoadley, Bruce, "A General Theory of Score Engineering for INFORM13," Fair, Isaac restricted Technical Paper, August 26, 1999.
- [2] Hoadley, Bruce, "The Theory of INFORM 11," Fair, Isaac restricted Technical Notes, January 3, 1996.
- [3] Hoadley, Bruce, "Boosting the Performance of Transaction Fraud Scores," Fair, Isaac Technical Paper, August 4, 1998.
- [4] Hoadley, Bruce, "RocBoost A New technology for Boosting the ROC Curve at an Operating Point," Fair, Isaac Technical Paper, December 16, 1998.
- [5] Hoadley, Bruce, "INFORM13 a Proposal for the Assimilation of Multiple Technologies into the INFORM12 Score Development Paradigm," Fair, Isaac Technical Monograph, January 28,1999.
- [6] Hoadley, Bruce, "INFORM Moment Update Formulas for Arbitrary Numerical Prediction Variables," Fair, Isaac restricted Technical Paper, February 1, 1999.
- [7] Hoadley, Bruce, "INFORM13 Weights Algorithm," Fair, Isaac restricted Technical Paper, April 1, 1999.

Appendix 1. Program for Converting a SAS Data Set to a Unix Text File

```
libname bch v603
  "/fico/prod/ap/score/rde/znxs5/bldcard/unix/db";
data _null_;
  set bch.iphr_i;
  recordno=_n_;
  blank='';
  file frdata recfm=d lrecl=805;
```

```
put (recordno) (6.) (blank) ($2.) (acctnb) ($16.)
( serialn factin prfnum
char170 char191 char193 char211 char260 char320 char330
char380 char471 char503 char533 char635 char665 char710 char830 char835
char840 char843 char860 char870 char950 char960 char961 char962
char965) (28*15.5)
( v0 0 v0 1-v0 4
v1 1-v1 6 v1 0
v2 1-v2 6
            v2 0
v3 1-v3 6
            v3 0
v4 1-v4 12 v4 0
v5 1-v5 7
            v5 0
v6 1-v6 10 v6 0
v7 1-v7 3
           v7 0
v8 1-v8 6
            v8 0
v9 1-v9 3
            v9 0
v10 1-v10 2 v10 0
v11 1-v11 6 v11 0
v12 1-v12 6 v12 0
v13 1-v13 3 v13 0
v14 1-v14 7 v14 0
v15 1-v15 3 v15 0
v16_1-v16_5 v16_0
v17 1-v17 4 v17 0
v18_1-v18_4 v18_0
v19 1-v19 2 v19 0
v20_1-v20_3 v20_0
v21 1-v21 15 v21 0
v22 1-v22 4 v22 0
v23 1-v23 5 v23 0
v24 1-v24 9 v24 0
v25 1-v25 9 v25 0) (176*2.);
run;
```

Appendix 2. Score Engineered Scorecards

Char	Attribute	Att.#	Constraint		Score Weights				>	
				INFORM- <i>NLP</i>	GEF Max Div					
-l4 7 0	0000000	4	" - 0 "			S1	S2	S3	S4	S5
		1	- 0	0.000	0.000	0.000	0.000	0.000	0.000	0
char170		2	> 3	0.303	0.306	0.306	0.307	0.500	0.500	0.5
char170		3	> 4	0.155	0.157	0.157	0.156	0.131	0.018	-0.022
char170		4	> 5	-0.060	-0.067	-0.067	-0.069	-0.078	-0.050	-0.047
char170	35-<300	5	> 6	-0.260	-0.259	-0.259	-0.260	-0.288	-0.164	-0.116
char170	300-High	6		-0.890	-0.888	-0.888	-0.874	-0.923	-0.445	-0.272
char170	NO INFORMATION	7	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char191	-9999999	8	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char191		9	< 10	-1.133	-1.152	-1.150	-1.144	-1.294	-1.712	-0.435
char191	2-<5	10	< 11	-1.086	-1.084	-1.088	-1.038	-1.144	-1.551	-0.372
char191	•	11	< 12	-0.625	-0.626	-0.630	-0.573	-0.693	-0.861	-0.29
char191		12	< 13	-0.005	0.000	0.000	-0.002	-0.134	-0.111	-0.181
char191	650-High	13		0.101	0.096	0.096	0.095	0.300	0.300	0.3
char191	NO INFORMATION	14	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
	-9999999	15		0.397	0.396	0.396	0.393	0.391	0.292	0.075
char193		16	< 17	-1.469	-1.484	-1.485	-1.443	-1.362	-0.542	-0.189
char193	1	17	< 18	-1.328	-1.317	-1.317	-1.248	-1.180	-0.346	-0.186
char193	_	18	< 19	-1.238	-1.264	-1.262	-1.193	-1.174	-0.276	-0.186
char193		19	< 20	-0.096	-0.086	-0.086	-0.091	-0.074	-0.067	0.001
char193	18-High	20		0.039	0.038	0.038	0.037	0.032	0.004	0.001
	NO INFORMATION	21	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char211	-9999999	22		-0.144	-0.096	-0.096	-0.103	-0.092	-0.219	-0.002
char211	-9999998	23		0.394	0.545	0.545	0.551	0.540	0.556	0.095
char211	0	24	< 31	0.514	0.449	0.449	0.453	0.434	0.195	0.061
char211	1-<7	25	< 30	0.025	-0.064	-0.064	-0.066	-0.061	-0.055	-0.003
char211	7-<35	26	< 27	-0.874	-0.917	-0.916	-0.923	-0.903	-0.892	-0.158
char211	35-<80	27	< 28	-0.629	-0.674	-0.674	-0.677	-0.658	-0.634	-0.106
char211		28	< 29	-0.364	-0.392	-0.392	-0.396	-0.386	-0.389	-0.065
char211	200-<400	29	< 30	-0.003	-0.064	-0.064	-0.066	-0.061	-0.055	-0.012
char211	400-<800	30	< 31	0.026	-0.064	-0.064	-0.066	-0.061	-0.055	-0.003
char211	800-<1300	31	< 32	0.515	0.449	0.449	0.453	0.434	0.381	0.061
char211	1300-<1700	32	< 33	0.516	0.449	0.449	0.453	0.434	0.381	0.061
char211	1700-High	33		0.516	0.449	0.449	0.453	0.434	0.521	0.061
char211	NO INFORMATION	34	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char260	-9999999	35		-0.138	-0.162	-0.162	-0.164	-0.160	-0.173	-0.028
char260	0-<101	36	> 37	0.429	0.464	0.463	0.466	0.461	0.489	0.085
char260	101-<210	37	> 38	0.275	0.314	0.314	0.318	0.309	0.344	0.051
char260	210-<305	38	> 39	0.275	0.312	0.312	0.312	0.305	0.258	0.051
char260	305-<565	39	> 40	0.113	0.143	0.143	0.144	0.132	0.121	0.013
char260	565-<700	40	> 41	-0.366	-0.276	-0.276	-0.271	-0.267	-0.159	-0.044
char260	700-High	41		-0.367	-0.276	-0.276	-0.271	-0.267	-0.159	-0.044
char260	NO INFORMATION	42	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0

Char	Attribute	Att.#	Constraint	←	GEF	Score	Weights			-
				NLP	Max Div	S1	S2	S3	S4	S5
char320	-9999999-<0	43	> 44	0.246	0.366	0.366	0.355	0.364	0.174	0.088
char320	0-<590	44	> 45	0.171	0.105	0.105	0.108	0.107	0.121	0.021
char320	590-<2055	45	> 46	0.171	0.105	0.105	0.108	0.107	0.121	0.021
char320	2055-<8405	46	> 47	-0.113	-0.088	-0.088	-0.087	-0.086	-0.082	-0.019
char320	8405-<16960	47	> 48	-0.186	-0.120	-0.120	-0.124	-0.127	-0.135	-0.032
char320	16960-<20000	48	> 49	-0.187	-0.120	-0.120	-0.124	-0.127	-0.135	-0.032
char320	20000-<30000	49	> 50	-0.279	-0.213	-0.213	-0.219	-0.214	-0.195	-0.032
char320	30000-<40375	50	> 51	-0.476	-0.361	-0.361	-0.370	-0.371	-0.286	-0.059
char320	40375-<70000	51	> 52	-0.566	-0.361	-0.361	-0.370	-0.371	-0.401	-0.076
char320	70000-High	52		-0.567	-0.361	-0.361	-0.370	-0.371	-0.412	-0.076
char320	NO INFORMATION	53	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char330	0	54	> 55	0.236	0.251	0.251	0.253	0.249	0.293	0.044
char330	1-<250	55	> 56	-0.143	-0.144	-0.144	-0.146	-0.142	-0.174	-0.024
char330	250-High	56		-0.311	-0.343	-0.343	-0.344	-0.341	-0.392	-0.062
char330	NO INFORMATION	57	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char380	-9999999-<0	58		0.000	0.000	0.000	0.000	0.000	0.000	0
char380	0-<635	59	> 60	0.094	0.106	0.106	0.105	0.106	0.087	0.024
char380	635-<1210	60	> 61	-0.001	-0.014	-0.014	-0.014	-0.024	-0.033	-0.017
char380	1210-<1915	61	> 62	-0.001	-0.014	-0.014	-0.014	-0.024	-0.033	-0.017
char380	1915-<5000	62	> 63	-0.304	-0.332	-0.332	-0.330	-0.335	-0.292	-0.079
char380	5000-High	63		-0.731	-0.775	-0.775	-0.765	-0.731	-0.497	-0.103
char380	NO INFORMATION	64	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char471	-9999999	65		0.000	0.000	0.000	0.000	0.000	0.000	0
char471	0	66	< 67	-0.417	-0.429	-0.429	-0.426	-0.402	-0.250	-0.039
char471	1-<101	67		0.015	0.016	0.016	0.016	0.015	0.009	0.002
char471	NO INFORMATION	68	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char503	0	69		0.010	0.010	0.010	0.009	0.009	0.004	0.002
char503	1-High	70	< 69	-1.468	-1.482	-1.482	-1.401	-1.355	-0.547	-0.219
char503	NO INFORMATION	71	" = 0 & < 69 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char533	-9999999-<1	72		0.132	0.156	0.156	0.154	0.150	0.107	0.025
char533	1	73	> 74	-0.342	-0.359	-0.359	-0.361	-0.356	-0.351	-0.065
char533	2	74	> 75	-0.712	-0.850	-0.849	-0.841	-0.815	-0.497	-0.13
char533	3	75	>76	-0.712	-0.910	-0.909	-0.893	-0.859	-0.497	-0.131
char533		76	>77	-0.713	-0.910	-0.909	-0.893	-0.859	-0.497	-0.131
char533	5-High	77		-0.714	-0.910	-0.909	-0.893	-0.859	-0.497	-0.131
	NO INFORMATION	78	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char635		79	0.4	0.000	0.004	0.004	0.002	0.002	-0.024	0.001
char635		80	> 81	0.071	0.050	0.050	0.055	0.053	0.105	0.007
char635		81	> 82	0.071	0.050	0.050	0.055	0.053	0.105	0.007
char635		82	> 83	-0.201	-0.153	-0.153	-0.144	-0.139	-0.053	-0.027
char635		83	> 84	-0.474	-0.400	-0.400	-0.376	-0.389	-0.122	-0.091
char635		84		-0.652	-0.619	-0.619	-0.601	-0.563	-0.285	-0.091
	NO INFORMATION	85	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char665		86	> 87	0.105	0.106	0.106	0.106	0.105	0.094	0.02
char665	1	87	>88	-0.532	-0.529	-0.529	-0.531	-0.523	-0.483	-0.096
char665		88	" - 0 "	-0.552	-0.572	-0.572	-0.573	-0.567	-0.483	-0.107
cnarbb5	NO INFORMATION	89	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0

Char	Attribute	Att.#	Constraint			Score	Weights			-
				INFORM- <i>NLP</i>	GEF Max Div	04	00	00	0.4	0.5
obor710	000000	00	" = 0 "			S1	S2	S3	S4	S5
char710	-9999999	90 91	- 0 " = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char710	-9999998 0	92	- 0 > 93	0.000 0.072	0.000 0.066	0.000 0.066	0.000 0.066	0.000 0.062	0.000 0.056	0 0.007
char710	1-<360	93	> 93 > 94	0.072	0.066	0.066	0.066	0.062	0.056	0.007
char710	360-<675	93 94	> 94 >95	0.072	0.043	0.043	0.066	0.036	0.030	0.007
char710	675-<2435	9 4 95	> 96	-0.359	-0.343	-0.343	-0.342	-0.320	-0.272	-0.035
char710	2435-High	96	> 30	-0.359	-0.343	-0.343	-0.342	-0.320	-0.272	-0.035
char710	NO INFORMATION	97	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0.033
char830	0	98	> 99	0.010	0.000	0.010	0.000	0.009	0.004	0.002
char830	1	99	> 100	0.008	0.009	0.009	0.009	0.009	0.004	0.002
char830	2-High	100	7 100	-0.347	-0.352	-0.353	-0.335	-0.325	-0.131	-0.052
char830	NO INFORMATION	101	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0.002
char835	0	102	. 103	0.054	0.056	0.056	0.054	0.053	0.035	0.01
char835	1	103	>104	-0.336	-0.339	-0.339	-0.337	-0.338	-0.250	-0.062
char835	2	104	> 105	-0.395	-0.420	-0.420	-0.405	-0.377	-0.250	-0.062
	3	105	> 106	-0.556	-0.566	-0.566	-0.529	-0.515	-0.250	-0.093
char835	4-High	106		-0.875	-0.910	-0.911	-0.829	-0.811	-0.250	-0.15
char835	NO INFORMATION	107	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char840	0	108	> 109	0.186	0.235	0.235	0.222	0.216	0.084	0.036
char840	1	109	> 110	-0.183	-0.313	-0.313	-0.283	-0.274	-0.001	-0.042
char840	2	110	> 111	-0.937	-1.062	-1.062	-1.027	-1.006	-0.595	-0.175
char840	3-High	111		-1.389	-1.497	-1.497	-1.449	-1.419	-0.786	-0.248
char840	NO INFORMATION	112	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char843	1	113		0.738	0.737	0.737	0.720	0.693	0.447	0.096
char843	2	114		-0.200	-0.188	-0.188	-0.213	-0.201	-0.495	-0.025
char843	3	115		0.011	0.001	0.001	0.013	0.005	0.165	-0.012
char843	4	116		-0.010	-0.013	-0.013	-0.002	-0.002	0.123	0.001
char843	NO INFORMATION	117	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char860	0	118	> 119	0.010	0.010	0.010	0.009	0.009	0.004	0.002
char860	1-High	119		-0.523	-0.528	-0.528	-0.499	-0.483	-0.195	-0.078
char860	NO INFORMATION	120	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char870	0	121	> 122	0.010	0.010	0.010	0.009	0.009	0.004	0.002
char870	1	122	> 123	-0.286	-0.289	-0.289	-0.273	-0.265	-0.081	-0.038
char870	2-High	123		-0.287	-0.289	-0.289	-0.273	-0.265	-0.114	-0.044
char870		124	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
	-9999998-<7011	125	> 126	0.627	0.659	0.659	0.664	0.641	0.633	0.098
	3300-<4901	126	> 127	0.350	0.324	0.324	0.325	0.329	0.264	0.07
	Travel	127	> 128	0.349	0.324	0.324	0.325	0.329	0.264	0.07
char950	5511-High	128	> 129	0.349	0.324	0.324	0.325	0.329	0.264	0.07
char950	MOTO	129	> 130	0.050	-0.007	-0.007	-0.009	-0.012	-0.027	-0.004
char950	5697-<7995	130	> 131	-0.026	-0.079	-0.079	-0.073	-0.069	-0.027	-0.012
char950	3723-<5945	131	> 132	-0.027	-0.079	-0.079	-0.073	-0.069	-0.027	-0.012
char950	5611-<8000	132	> 133	-0.030	-0.079	-0.079	-0.073	-0.069	-0.027	-0.012
	4814-<4830	133	> 134	-0.030	-0.079	-0.079	-0.073	-0.069	-0.027	-0.012
char950		134	> 135	-0.174	-0.157	-0.157	-0.165	-0.161	-0.185	-0.028
char950	Gas	135	> 136	-0.175	-0.157	-0.157	-0.165	-0.161	-0.185	-0.028
char950	5655-<5949	136	> 137	-0.265	-0.193	-0.193	-0.191	-0.188	-0.185	-0.032
char950	5300-<5942	137	> 138	-0.266	-0.193	-0.193	-0.191	-0.188	-0.185	-0.032
	5815-<5963	138	> 139	-0.455	-0.490	-0.490	-0.499 0.705	-0.476	-0.364	-0.064
char950	5423-<5655 NO INFORMATION	139	" = 0 "	-0.771	-0.734	-0.734	-0.705	-0.705	-0.364	-0.143
char950	NO INFORMATION	140	= 0	0.000	0.000	0.000	0.000	0.000	0.000	0

Char	Attribute	Att.#	Constraint	←INFORM-	GEF	Score	Weights			>
				NLP	Max Div	S1	S2	S3	S4	S5
char960	Below -1700	141	< 142	-0.308	-0.398	-0.398	-0.400	-0.390	-0.393	-0.066
char960	-1700-<-800	142	< 143	-0.041	0.073	0.073	0.073	0.071	0.072	0.012
char960	-800-<-450	143	< 144	-0.041	0.073	0.073	0.073	0.071	0.072	0.012
char960	" -450- <high "<="" td=""><td>144</td><td></td><td>0.136</td><td>0.073</td><td>0.073</td><td>0.073</td><td>0.071</td><td>0.072</td><td>0.012</td></high>	144		0.136	0.073	0.073	0.073	0.071	0.072	0.012
char960	NO INFORMATION	145	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char961	-9999999	146		-0.122	-0.211	-0.211	-0.215	-0.195	-0.261	-0.001
char961	-3000-<-1700	147	< 148	-0.404	-0.385	-0.385	-0.386	-0.379	-0.389	-0.067
char961	-1700-<-800	148	< 149	-0.069	-0.048	-0.048	-0.053	-0.052	-0.107	-0.01
char961	-800-<550	149	< 150	0.135	0.148	0.148	0.152	0.146	0.195	0.02
char961	550-High	150		0.205	0.186	0.186	0.188	0.179	0.202	0.022
char961	NO INFORMATION	151	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char962	Below -1500	152	< 153	-0.126	-0.085	-0.085	-0.089	-0.095	-0.176	-0.024
char962	-1500-<-1100	153	< 154	-0.060	-0.085	-0.085	-0.089	-0.095	-0.174	-0.024
char962	-1100-<-850	154	< 155	-0.054	-0.073	-0.073	-0.074	-0.072	-0.094	-0.012
char962	-850-<-550	155	< 156	-0.054	-0.073	-0.073	-0.074	-0.072	-0.094	-0.012
char962	-550-<-400	156	< 157	0.034	0.019	0.019	0.021	0.022	0.050	0.005
char962	-400-<-300	157	< 158	0.035	0.019	0.019	0.021	0.022	0.050	0.005
char962	-300-<1	158	< 159	0.035	0.019	0.019	0.021	0.022	0.065	0.005
char962	1-<200	159	< 160	0.075	0.104	0.104	0.108	0.107	0.163	0.02
char962	200-High	160		0.123	0.174	0.174	0.177	0.180	0.223	0.041
char962	NO INFORMATION	161	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
char965	Below -950	162	< 163	-0.329	-0.328	-0.328	-0.329	-0.327	-0.330	-0.065
char965	-950-<-750	163	< 164	-0.328	-0.328	-0.328	-0.329	-0.327	-0.330	-0.065
char965	-750-<-550	164	< 165	-0.269	-0.321	-0.321	-0.320	-0.313	-0.278	-0.053
char965	-550-<-400	165	< 166	-0.269	-0.321	-0.321	-0.320	-0.313	-0.278	-0.053
char965	-400-<-300	166	< 167	-0.049	-0.044	-0.044	-0.044	-0.040	-0.040	-0.001
char965	-300-<-200	167	< 168	0.162	0.186	0.186	0.186	0.187	0.153	0.03
char965	-200-<-100	168	< 169	0.192	0.201	0.201	0.203	0.187	0.191	0.03
char965	-100-<80	169	< 170	0.349	0.366	0.366	0.367	0.364	0.357	0.07
char965	80-High	170		0.350	0.366	0.366	0.367	0.364	0.357	0.07
char965	NO INFORMATION	171	" = 0 "	0.000	0.000	0.000	0.000	0.000	0.000	0
-	ment Divergence			1.732	1.753	1.753	1.752	1.731	1.641	0.926
Validatio	on Divergence			1.617	1.636	1.6360	1.6361	1.628	1.594	0.856