

NORM ONE TORI AND HASSE NORM PRINCIPLE, II: DEGREE 12 CASE

AKINARI HOSHI, KAZUKI KANAI, AND AIICHI YAMASAKI

ABSTRACT. Let k be a field, T be an algebraic k -torus, X be a smooth k -compactification of T and $\text{Pic } \overline{X}$ be the Picard group of $\overline{X} = X \times_k \overline{k}$. Hoshi, Kanai and Yamasaki [HKY22] determined $H^1(k, \text{Pic } \overline{X})$ for norm one tori $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ and gave a necessary and sufficient condition for the Hasse norm principle for extensions K/k of number fields with $[K : k] = n \leq 15$ and $n \neq 12$. In this paper, we determine 64 cases with $H^1(k, \text{Pic } \overline{X}) \neq 0$ and give a necessary and sufficient condition for the Hasse norm principle for K/k with $[K : k] = 12$.

CONTENTS

1. Introduction	1
2. Algebraic tori and Norm one tori	11
3. Hasse principle and Hasse norm principle	12
4. Flabby resolution of G -lattice and rationality of algebraic k -torus	13
5. Proof of Theorem 1.1	15
6. Drakokhrust and Platonov's method	20
7. Proof of Theorem 1.3	23
8. GAP algorithms	136
References	146

1. INTRODUCTION

Let k be a field, K/k be a separable field extension of degree n and L/k be the Galois closure of K/k with $\text{Gal}(L/k) \simeq G$. Let S_n (resp. A_n , D_n , C_n) be the symmetric (resp. the alternating, the dihedral, the cyclic) group of degree n of order $n!$ (resp. $n!/2$, $2n$, n). Let nTm be the m -th transitive subgroup of the symmetric group S_n of degree n up to conjugacy (see Butler and McKay [BM83], [GAP]). We may regard G as the transitive subgroup $G = nTm \leq S_n$. Let $H = \text{Gal}(L/K) \leq G$ with $[G : H] = n$. Then we may assume that H is the stabilizer of one of the letters in G , i.e. $L = k(\theta_1, \dots, \theta_n)$ and $K = k(\theta_i)$ for some $1 \leq i \leq n$.

Voskresenskii [Vos67] proved that all the 2-dimensional algebraic k -tori are k -rational. This implies that $H^1(k, \text{Pic } \overline{X}) \simeq A(T) \simeq \text{III}(T) = 0$ where X is a smooth k -compactification of an algebraic k -torus T , $A(T)$ is the kernel of the weak approximation of T and $\text{III}(T)$ is the Shafarevich-Tate group of T (see Section 3 and also Manin [Man74, §30]). Kunyavskii [Kun84] showed that, among 73 cases of 3-dimensional k -tori T , there exist exactly 2 cases with $H^1(k, \text{Pic } \overline{X}) \neq 0$ which are of special type called norm one tori. Hoshi, Kanai and Yamasaki [HKY22, Theorem 1.18] determined $H^1(k, \text{Pic } \overline{X})$ for norm one tori $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ with $[K : k] = n \leq 15$ and $n \neq 12$. We determine 64 cases with $H^1(k, \text{Pic } \overline{X}) \neq 0$ when $[K : k] = 12$ as follows: (Note that there exist exactly 301 transitive subgroups $12Tm$ of S_{12} up to conjugacy (see Royle [Roy87] and [GAP]).)

Theorem 1.1. *Let k be a field, K/k be a separable field extension of degree 12 and L/k be the Galois closure of K/k . Assume that $G = \text{Gal}(L/k) = 12Tm$ ($1 \leq m \leq 301$) is a transitive subgroup of S_{12} and $H = \text{Gal}(L/K)$ with $[G : H] = 12$. Let $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ be the norm one torus of K/k of dimension 11 and X be a smooth k -compactification of T . Then $H^1(k, \text{Pic } \overline{X}) \neq 0$ if and only if G is given as in Table 1. In particular, if k is a number field and L/k is an unramified extension, then $A(T) = 0$ and $H^1(k, \text{Pic } \overline{X}) \simeq \text{III}(T)$.*

In Table 1, $V_4 \simeq C_2 \times C_2$ is the Klein four group, Q_8 is the quaternion group of order 8, $\text{PSL}_2(\mathbb{F}_{11})$ is the projective special linear group of degree 2 over the finite field \mathbb{F}_{11} of 11 elements, and $S_n(m)$ and $A_n(m)$ mean that $S_n(m) \simeq S_n = mTx \leq S_m$ and $A_n(m) \simeq A_n = mTx \leq S_m$ respectively.

2010 *Mathematics Subject Classification.* Primary 11E72, 12F20, 13A50, 14E08, 20C10, 20G15.

Key words and phrases. Algebraic tori, norm one tori, Hasse norm principle, weak approximation, rationality problem.

This work was partially supported by JSPS KAKENHI Grant Numbers 16K05059, 19K03418, 20K03511. Parts of the work were finished when the first-named author and the third-named author were visiting the National Center for Theoretic Sciences (Taipei), whose support is gratefully acknowledged.

Table 1: $H^1(k, \text{Pic } \overline{X}) \simeq H^1(G, [J_{G/H}]^{fl}) \neq 0$ with $G = 12Tm$ ($1 \leq m \leq 301$)

G	$H^1(k, \text{Pic } \overline{X}) \simeq H^1(G, [J_{G/H}]^{fl})$
$12T2 \simeq C_6 \times C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T3 \simeq D_6$	$\mathbb{Z}/2\mathbb{Z}$
$12T4 \simeq A_4(12)$	$\mathbb{Z}/2\mathbb{Z}$
$12T7 \simeq A_4(6) \times C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T9 \simeq S_4$	$\mathbb{Z}/2\mathbb{Z}$
$12T10 \simeq S_3 \times V_4$	$\mathbb{Z}/2\mathbb{Z}$
$12T16 \simeq (S_3)^2$	$\mathbb{Z}/2\mathbb{Z}$
$12T18 \simeq S_3 \times C_6$	$\mathbb{Z}/2\mathbb{Z}$
$12T20 \simeq A_4(4) \times C_3$	$\mathbb{Z}/2\mathbb{Z}$
$12T31 \simeq (C_4)^2 \rtimes C_3$	$\mathbb{Z}/4\mathbb{Z}$
$12T32 \simeq (C_2)^4 \rtimes C_3$	$(\mathbb{Z}/2\mathbb{Z})^{\oplus 2}$
$12T33 \simeq A_5(12)$	$\mathbb{Z}/2\mathbb{Z}$
$12T34 \simeq (S_3)^2 \rtimes C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T37 \simeq (S_3)^2 \times C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T40 \simeq ((C_3)^2 \rtimes C_4) \times C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T43 \simeq A_4(4) \times S_3$	$\mathbb{Z}/2\mathbb{Z}$
$12T47 \simeq (C_3)^2 \rtimes Q_8$	$\mathbb{Z}/2\mathbb{Z}$
$12T52 \simeq (A_4 \times V_4) \rtimes C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T54 \simeq (S_4 \times C_2) \rtimes C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T55 \simeq ((C_4)^2 \rtimes C_3) \times C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T56 \simeq ((C_2)^4 \rtimes C_3) \times C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T57 \simeq ((C_4 \times C_2) \rtimes C_4) \rtimes C_3$	$\mathbb{Z}/4\mathbb{Z}$
$12T59 \simeq (C_2)^3 \rtimes A_4(6)$	$\mathbb{Z}/2\mathbb{Z}$
$12T61 \simeq ((C_4)^2 \rtimes C_2) \rtimes C_3$	$\mathbb{Z}/2\mathbb{Z}$
$12T64 \simeq ((C_4)^2 \rtimes C_3) \rtimes C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T65 \simeq ((C_4)^2 \rtimes C_3) \rtimes C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T66 \simeq ((C_2)^4 \rtimes C_3) \rtimes C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T70 \simeq (S_3)^2 \times C_3$	$\mathbb{Z}/2\mathbb{Z}$
$12T71 \simeq (C_3)^3 \rtimes V_4$	$\mathbb{Z}/2\mathbb{Z}$
$12T74 \simeq S_5(12)$	$\mathbb{Z}/2\mathbb{Z}$
$12T75 \simeq A_5(6) \times C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T77 \simeq (S_3)^2 \rtimes V_4$	$\mathbb{Z}/2\mathbb{Z}$

Table 1 (continued): $H^1(k, \text{Pic } \overline{X}) \simeq H^1(G, [J_{G/H}]^{fl}) \neq 0$ with $G = 12Tm$ ($1 \leq m \leq 301$)

G	$H^1(k, \text{Pic } \overline{X}) \simeq H^1(G, [J_{G/H}]^{fl})$
$12T88 \simeq (C_2)^4 \rtimes A_4(6)$	$\mathbb{Z}/2\mathbb{Z}$
$12T92 \simeq (((C_4)^2 \rtimes C_2) \rtimes C_3) \times C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T93 \simeq (((C_4 \rtimes C_4) \times C_2) \rtimes C_2) \rtimes C_3$	$\mathbb{Z}/2\mathbb{Z}$
$12T96 \simeq (((C_4)^2 \rtimes C_3) \rtimes C_2) \times C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T97 \simeq (((C_4)^2 \rtimes C_3) \rtimes C_2) \times C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T100 \simeq (((C_2)^4 \rtimes C_3) \rtimes C_2) \times C_2$	$\mathbb{Z}/2\mathbb{Z}$
$12T102 \simeq ((C_2)^4 \rtimes C_3) \rtimes C_4$	$\mathbb{Z}/2\mathbb{Z}$
$12T117 \simeq (S_3)^3$	$\mathbb{Z}/2\mathbb{Z}$
$12T122 \simeq ((C_3)^2 \rtimes Q_8) \rtimes C_3$	$\mathbb{Z}/2\mathbb{Z}$
$12T130 \simeq (C_3)^4 \rtimes V_4 \simeq C_3 \wr V_4$	$\mathbb{Z}/2\mathbb{Z}$
$12T132 \simeq ((C_3)^3 \rtimes V_4) \rtimes C_3$	$\mathbb{Z}/2\mathbb{Z}$
$12T133 \simeq (C_3)^3 \rtimes A_4(4)$	$\mathbb{Z}/2\mathbb{Z}$
$12T144 \simeq (C_2)^5 \rtimes A_4(6)$	$\mathbb{Z}/2\mathbb{Z}$
$12T168 \simeq (C_3)^4 \rtimes (C_2)^3$	$\mathbb{Z}/2\mathbb{Z}$
$12T171 \simeq (C_3)^4 \rtimes (C_4 \times C_2)$	$\mathbb{Z}/2\mathbb{Z}$
$12T172 \simeq (C_3)^4 \rtimes D_4$	$\mathbb{Z}/2\mathbb{Z}$
$12T174 \simeq (C_3)^4 \rtimes Q_8$	$\mathbb{Z}/2\mathbb{Z}$
$12T176 \simeq ((C_3)^3 \rtimes C_2) \rtimes A_4(4)$	$\mathbb{Z}/2\mathbb{Z}$
$12T179 \simeq \text{PSL}_2(\mathbb{F}_{11})$	$\mathbb{Z}/2\mathbb{Z}$
$12T188 \simeq (C_2)^6 \rtimes A_4(6) \simeq C_2 \wr A_4(6)$	$\mathbb{Z}/2\mathbb{Z}$
$12T194 \simeq (C_3)^4 \rtimes A_4(4) \simeq C_3 \wr A_4(4)$	$\mathbb{Z}/2\mathbb{Z}$
$12T210 \simeq (C_3)^4 \rtimes (D_4 \times C_2)$	$\mathbb{Z}/2\mathbb{Z}$
$12T214 \simeq (C_3)^4 \rtimes ((C_4 \times C_2) \rtimes C_2)$	$\mathbb{Z}/2\mathbb{Z}$
$12T230 \simeq (C_2)^5 \rtimes A_5(6)$	$\mathbb{Z}/2\mathbb{Z}$
$12T232 \simeq ((C_3)^4 \rtimes Q_8) \rtimes C_3$	$\mathbb{Z}/2\mathbb{Z}$
$12T234 \simeq ((C_3)^4 \rtimes C_2) \rtimes A_4(4)$	$\mathbb{Z}/2\mathbb{Z}$
$12T242 \simeq (C_3)^4 \rtimes ((C_2)^3 \rtimes V_4)$	$\mathbb{Z}/2\mathbb{Z}$
$12T246 \simeq (C_3)^4 \rtimes ((C_2)^3 \rtimes C_4)$	$\mathbb{Z}/2\mathbb{Z}$
$12T255 \simeq (C_2)^6 \rtimes A_5(6) \simeq C_2 \wr A_5(6)$	$\mathbb{Z}/2\mathbb{Z}$
$12T261 \simeq (S_3)^4 \rtimes V_4 \simeq S_3 \wr V_4$	$\mathbb{Z}/2\mathbb{Z}$
$12T271 \simeq ((C_3)^4 \rtimes (C_2)^3) \rtimes A_4(4)$	$\mathbb{Z}/2\mathbb{Z}$
$12T280 \simeq (S_3)^4 \rtimes A_4(4) \simeq S_3 \wr A_4(4)$	$\mathbb{Z}/2\mathbb{Z}$

Remark 1.2. Theorem 1.1 enables us to obtain the group $T(k)/R$ of R -equivalence classes over a local field k via $T(k)/R \simeq H^1(k, \text{Pic } \overline{X}) \simeq H^1(G, [J_{G/H}]^{fl})$ for norm one tori $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ with $[K : k] = 12$ (see Colliot-Thélène and Sansuc [CTS77, Corollary 5, page 201], Voskresenskii [Vos98, Section 17.2] and Hoshi, Kanai and Yamasaki [HKY22, Section 7, Application 1]).

Kunyavskii [Kun84] gave a necessary and sufficient condition for the Hasse norm principle for K/k with $[K : k] = 4$ ($G = 4Tm$ ($1 \leq m \leq 5$)). Drakokhrust and Platonov [DP87] gave a necessary and sufficient condition for the Hasse norm principle for K/k with $[K : k] = 6$ ($G = 6Tm$ ($1 \leq m \leq 16$))). Hoshi, Kanai and Yamasaki [HKY22, Theorem 1.18] gave a necessary and sufficient condition for the Hasse norm principle for K/k with $[K : k] = n \leq 15$ and $n \neq 12$ (see also [HKY22, Section 1]).

By Theorem 1.1 and Ono's theorem (see Theorem 3.6) which claims that the Hasse norm principle holds for K/k if and only if $\text{III}(T) = 0$ where $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ is the norm one torus of K/k , the Hasse norm principle holds for K/k with $[K : k] = 12$ as in the cases in Theorem 1.1 except for the cases as in Table 1. By using Drakokhrust and Platonov's method (see Section 6 for details) and some new useful functions of GAP [GAP] provided in Section 7, we will prove the following main theorem of this paper which gives a necessary and sufficient condition for the Hasse norm principle for K/k with $[K : k] = 12$:

Theorem 1.3. *Let k be a number field, K/k be a field extension of degree 12 and L/k be the Galois closure of K/k . Let $G = \text{Gal}(L/k) = 12Tm$ ($1 \leq m \leq 301$) be a transitive subgroup of S_{12} , $H = \text{Gal}(L/K)$ with $[G : H] = 12$ and G_v be the decomposition group of G at a place v of k . Let $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ be the norm one torus of K/k of dimension 11 and X be a smooth k -compactification of T . Then $A(T) \simeq \text{III}(T) = 0$ except for the 64 cases in Table 1. For the 64 cases in Table 1 except for 3 cases $G = 12T31, 12T32, 12T57$ as in Tables 2-3, 2-4, 2-5, we have either (a) $A(T) = 0$ and $\text{III}(T) \simeq \mathbb{Z}/2\mathbb{Z}$ or (b) $A(T) \simeq \mathbb{Z}/2\mathbb{Z}$ and $\text{III}(T) = 0$. We assume that H is the stabilizer of one of the letters in G . Then $\text{III}(T)$ is given as in Tables 2-1 to 2-5. Moreover, for the cases in Table 2-1 and Table 2-3, $\text{III}(T)$ is also given for general $H \leq G$ with $[G : H] = 12$.*

In Tables 2-1 to 2-5, $M_{16} = \langle x, y \mid x^8 = y^2 = 1, yxy^{-1} = x^5 \rangle$ is the modular type 2-group of order 16, $Z(G)$ is the center of a group G , $D(G)$ is the derived subgroup of G and $D^i(G) := D(D^{i-1}(G))$ is the i -th derived subgroup ($D^0(G) := G$), $\text{Syl}_p(G)$ is a p -Sylow subgroup of G where p is a prime number, $N_G(G')$ is the normalizer of a subgroup $G' \leq G$, $\Phi(G)$ is the Frattini subgroup of G , i.e. the intersection of all maximal subgroups of G , and $\text{Orb}_G(i)$ is the orbit of $1 \leq i \leq n$ under the action of $G \leq S_n$.

Note that a place v of k with non-cyclic decomposition group G_v as in Tables 2-1 to 2-5 must be ramified in L because if v is unramified, then G_v is cyclic.

Table 2-1: $\text{III}(T) = 0$ for $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ and $G = \text{Gal}(L/k) = 12Tm$ as in Table 1

G	$\text{III}(T) \leq \mathbb{Z}/2\mathbb{Z}$, and $\text{III}(T) = 0$ if and only if there exists a place v of k such that
$12T2 \simeq C_6 \times C_2$	
$12T3 \simeq D_6$	
$12T4 \simeq A_4(12)$	
$12T16 \simeq (S_3)^2$	
$12T18 \simeq S_3 \times C_6$	
$12T20 \simeq A_4(4) \times C_3$	
$12T33 \simeq A_5(12)$	
$12T70 \simeq (S_3)^2 \times C_3$	$V_4 \leq G_v$ (Tate [Tat67] for $12T2, 12T3, 12T4$)
$12T71 \simeq (C_3)^3 \rtimes V_4$	
$12T130$ $\simeq (C_3)^4 \rtimes V_4 \simeq C_3 \wr V_4$	
$12T132 \simeq ((C_3)^3 \rtimes V_4) \rtimes C_3$	
$12T133 \simeq (C_3)^3 \rtimes A_4(4)$	
$12T179 \simeq \text{PSL}_2(\mathbb{F}_{11})$	
$12T194$ $\simeq (C_3)^4 \rtimes A_4(4) \simeq C_3 \wr A_4(4)$	
$12T7 \simeq A_4(6) \times C_2$	
$12T9 \simeq S_4$	$V_4 \leq G_v$ where $V_4 \cap D(G) = V_4$ (equivalently, $ \text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$)
$12T74 \simeq S_5(12)$	with $D(G) \simeq V_4, A_4, A_5, A_5$ for $12T7, 12T9, 12T74, 12T75$ respectively
$12T75 \simeq A_5(6) \times C_2$	
$12T34 \simeq (S_3)^2 \rtimes C_2$	
$12T172 \simeq (C_3)^4 \rtimes D_4$	$D_4 \leq G_v$
$12T40 \simeq ((C_3)^2 \rtimes C_4) \times C_2$	
$12T171 \simeq (C_3)^4 \rtimes (C_4 \times C_2)$	$C_4 \times C_2 \leq G_v$
$12T43 \simeq A_4(4) \times S_3$	$V_4 \leq G_v$ where $V_4 \cap S_3 = 1$ for the unique characteristic subgroup $S_3 \triangleleft G$ of order 6 (equivalently, $ \text{Orb}_{V_4}(i) = 4$ for any $1 \leq i \leq 12$)
$12T47 \simeq (C_3)^2 \rtimes Q_8$	
$12T122 \simeq ((C_3)^2 \rtimes Q_8) \rtimes C_3$	$Q_8 \leq G_v$
$12T174 \simeq (C_3)^4 \rtimes Q_8$	
$12T232 \simeq ((C_3)^4 \rtimes Q_8) \rtimes C_3$	
$12T52 \simeq (A_4 \times V_4) \rtimes C_2$	(i) $V_4 \leq G_v$ where $V_4 \cap (A_4 \times V_4) \simeq C_2$, $V_4 \cap Z(G) = 1$ and $V_4 \cap D^2(G) = 1$ for the characteristic subgroup $A_4 \times V_4 \triangleleft G$ of order 48 (equivalently, $ \text{Orb}_{V_4}(i) = 4$ for any $1 \leq i \leq 12$ and $V_4 \cap D^2(G) = 1$), (ii) $C_4 \times C_2 \leq G_v$ where $(C_4 \times C_2) \cap (A_4 \rtimes C_4) \simeq V_4$ (resp. $C_4 \times C_2 \leq S_4 \times C_2$) for the characteristic subgroup $A_4 \rtimes C_4 \triangleleft G$ (resp. $S_4 \times C_2 \triangleleft G$) of order 48 (resp. 48) (equivalently, $ \text{Orb}_{C_4 \times C_2}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{C_4 \times C_2}(i) = 2$ for 4 of $1 \leq i \leq 12$), or (iii) $D_4 \leq G_v$ where $D_4 \cap A_4 \simeq V_4$ (resp. $D^2(G) \leq D_4$) for the unique characteristic subgroup $A_4 \triangleleft G$ (resp. the characteristic subgroup $D^2(G) \simeq V_4 \triangleleft G$) of order 12 (resp. 4) (equivalently, $ \text{Orb}_{D_4}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{D_4}(i) = 2$ for 4 of $1 \leq i \leq 12$)
$12T55 \simeq ((C_4)^2 \rtimes C_3) \times C_2$	$C_4 \times C_4 \leq G_v$

Table 2-1 (continued): $\text{III}(T) = 0$ for $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ and $G = \text{Gal}(L/k) = 12Tm$ as in Table 1

G	$\text{III}(T) \leq \mathbb{Z}/2\mathbb{Z}$, and $\text{III}(T) = 0$ if and only if there exists a place v of k such that
$12T64 \simeq ((C_4)^2 \rtimes C_3) \rtimes C_2$	(i) $D_4 \leq G_v$ where $\Phi(D^2(G)) \leq D_4$ for the unique characteristic subgroup $\Phi(D^2(G)) \simeq V_4 \triangleleft G$ of order 4 (equivalently, $ \text{Orb}_{D_4}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{D_4}(i) = 2$ for 4 of $1 \leq i \leq 12$), or (ii) $(C_4)^2 \leq G_v$
$12T65 \simeq ((C_4)^2 \rtimes C_3) \rtimes C_2$	(i) $M_{16} \leq G_v$, or (ii) $(C_4)^2 \leq G_v$
$12T96 \simeq (((C_4)^2 \rtimes C_3) \rtimes C_2) \times C_2$	(i) $V_4 \leq G_v$ where $V_4 \cap \text{Syl}_2(D(G)) = 1$ and $V_4 \cap Z(G) = 1$ (resp. $V_4 \cap \text{Syl}_2(D(G)) = 1$ and $V_4 \cap Z(G) = 1$, resp. $V_4 \cap Z(G) = 1$ and $V_4 \cap Z(G) = 1$), for characteristic subgroups $D(G) \simeq (C_4)^2 \rtimes C_3$, $\text{Syl}_2(D(G)) \simeq (C_4)^2$, $Z(G) \simeq C_2$, $\Phi(\text{Syl}_2(D(G))) \simeq V_4 \triangleleft G$ (equivalently, $V_4 \cap Z(G) = 1$ with $Z(G) \simeq C_2$ and $V_4 \cap D(G) = 1$ with $D(G) \simeq (C_4)^2 \rtimes C_3$), (ii) $C_4 \times C_2 \leq G_v$ where $(C_4 \times C_2) \cap 12T55 \simeq V_4$ (resp. $(C_4 \times C_2) \cap \text{Syl}_2(12T55) \simeq V_4$) for the unique characteristic subgroup $12T55 \simeq ((C_4)^2 \rtimes C_3) \times C_2 \triangleleft G$ (resp. $\text{Syl}_2(12T55) \simeq (C_4)^2 \times C_2 \triangleleft G$) of order 96 (resp. 32) (equivalently, $(C_4 \times C_2) \cap Z(G) \simeq C_2$ and $(C_4 \times C_2) \cap D(G) \simeq C_2$), (iii) $D_4 \leq G_v$ where $D_4 \cap D(G) \simeq V_4$ (resp. $D_4 \cap \text{Syl}_2(D(G)) \simeq V_4$, resp. $\Phi(\text{Syl}_2(D(G))) \leq D_4$) with $\text{Syl}_2(D(G)) \simeq (C_4)^2 \triangleleft G$, $\Phi(\text{Syl}_2(D(G))) \simeq V_4 \triangleleft G$ (equivalently, $ \text{Orb}_{D_4}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{D_4}(i) = 2$ for 4 of $1 \leq i \leq 12$), or (iv) $(C_4)^2 \leq G_v$
$12T97 \simeq (((C_4)^2 \rtimes C_3) \rtimes C_2) \times C_2$	(i) $(C_4)^2 \leq G_v$, (ii) $C_8 \times C_2 \leq G_v$, or (iii) $M_{16} \leq G_v$ where $M_{16} \cap D(G) \simeq C_4 \times C_2$ (equivalently, $ \text{Orb}_{M_{16}}(i) = 8$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{M_{16}}(i) = 2$ for 4 of $1 \leq i \leq 12$) with $D(G) \simeq (C_4)^2 \rtimes C_3$.
$12T117 \simeq (S_3)^3$	$V_4 \leq G_v$ where $V_4 \cap \text{Dih}((C_3)^3) = 1$ for the unique characteristic subgroup
$12T176 \simeq ((C_3)^3 \rtimes C_2) \rtimes A_4(4)$	$\text{Dih}((C_3)^3) \simeq (C_3)^3 \rtimes C_2 \triangleleft G$ of order 54 (equivalently, $ \text{Orb}_{V_4}(i) = 4$ for any $1 \leq i \leq 12$)
$12T168 \simeq (C_3)^4 \rtimes (C_2)^3$	$V_4 \leq G_v$ where $V_4 \cap \text{Dih}((C_3)^4) = 1$ for the unique characteristic subgroup
$12T234 \simeq ((C_3)^4 \rtimes C_2) \rtimes A_4(4)$	$\text{Dih}((C_3)^4) \simeq (C_3)^4 \rtimes C_2 \triangleleft G$ of order 162 (equivalently, $ \text{Orb}_{V_4}(i) = 4$ for any $1 \leq i \leq 12$)
$12T246 \simeq (C_3)^4 \rtimes ((C_2)^3 \rtimes C_4)$	$\text{Syl}_2(G) \simeq (C_2^3) \rtimes C_4 \leq G_v$
$12T261 \simeq (S_3)^4 \rtimes V_4 \simeq S_3 \wr V_4$	(i) $V_4 \leq G_v$ where $V_4 \cap (S_3)^4 = 1$ (resp. $V_4 \cap D(12T261) = 1$) for the unique characteristic subgroup $(S_3)^4 \triangleleft G$ (resp. $D(12T261) \simeq (C_3)^4 \rtimes (C_2)^3 \triangleleft G$) of order 1296 (resp. 648) (equivalently, $ \text{Orb}_{V_4}(i) = 4$ for any $1 \leq i \leq 12$),
$\simeq (S_3)^4 \rtimes A_4(4) \simeq S_3 \wr A_4(4)$	(ii) $C_4 \times C_2 \leq G_v$ where $(C_4 \times C_2) \cap (S_3)^4 \simeq C_2$ (resp. $(C_4 \times C_2) \cap D(12T261) \simeq C_2$) with $(S_3)^4 \triangleleft G$ (resp. $D(12T261) \simeq (C_3)^4 \rtimes (C_2)^3 \triangleleft G$) (equivalently, $ \text{Orb}_{C_4 \times C_2}(i) = 8$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{C_4 \times C_2}(i) = 4$ for 4 of $1 \leq i \leq 12$), (iii) $D_4 \leq G_v$ where $D_4 \cap (S_3)^4 \simeq C_2$ with $(S_3)^4 \triangleleft G$ (equivalently, $ \text{Orb}_{D_4}(i) = 8$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{D_4}(i) = 4$ for 4 of $1 \leq i \leq 12$), (iv) $Q_8 \leq G_v$, or (v) $(C_2)^3 \rtimes C_3 \leq G_v$

Table 2-2: $\text{III}(T) = 0$ for $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ and $G = \text{Gal}(L/k) = 12Tm$ as in Table 1

G	$\text{III}(T) \leq \mathbb{Z}/2\mathbb{Z}$, and $\text{III}(T) = 0$ if and only if there exists a place v of k such that
$12T10 \simeq S_3 \times V_4$	$V_4 \leq G_v$ where $ \text{Orb}_{V_4}(i) = 4$ for any $1 \leq i \leq 12$
$12T37 \simeq (S_3)^2 \times C_2$	
$12T54 \simeq (S_4 \times C_2) \rtimes C_2$	(i) $V_4 \leq G_v$ where $ \text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$ and $V_4 \cap D(G) \simeq C_2$ with $D(G) \simeq A_4 \times C_2$, (ii) $C_4 \times C_2 \leq G_v$ where $ \text{Orb}_{C_4 \times C_2}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{C_4 \times C_2}(i) = 2$ for 4 of $1 \leq i \leq 12$, or (iii) $D_4 \leq G_v$ where $ \text{Orb}_{D_4}(i) = 4$ for 8 of $1 \leq i \leq 12$, $ \text{Orb}_{D_4}(i) = 2$ for 4 of $1 \leq i \leq 12$, and $D^2(G) \leq D_4$ with $D^2(G) \simeq V_4 \triangleleft G$
$12T56 \simeq ((C_2)^4 \rtimes C_3) \times C_2$	(i) $V_4 \leq G_v$ where $ \text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$ and (i-1) $V_4 \cap D(G) \simeq C_2$ with $D(G) \simeq (C_2)^4 \triangleleft G$, $V_4 \cap Z(G) = 1$ with $Z(G) \simeq C_2 \triangleleft G$ and any non-zero element of V_4 is a product of 4 (different) transpositions or, (i-2) $V_4 \leq D(G)$, $V_4 \cap Z(G) = 1$ and V_4 is not a normal subgroup of $N_{S_{12}}(G)$ with $N_{S_{12}}(G) \simeq (((C_2)^4 \rtimes C_2) \times C_2) \rtimes C_3 \rtimes C_2$
$12T59 \simeq (C_2)^3 \rtimes A_4(6)$	(i) $V_4 \leq G_v$ where $ \text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$ and $V_4 \cap Z(\text{Syl}_2(G)) = 1$
$12T88 \simeq (C_2)^4 \rtimes A_4(6)$	for the characteristic subgroup $Z(\text{Syl}_2(G)) \simeq V_4 \triangleleft G$ of order 4 with $\text{Syl}_2(G) \simeq (C_2)^3 \rtimes V_4 \triangleleft G$, or (ii) $(C_4 \times C_2) \rtimes C_2 \leq G_v$
$12T61 \simeq ((C_4)^2 \rtimes C_2) \rtimes C_3$	(i) $D_4 \leq G_v$ where $ \text{Orb}_{D_4}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{D_4}(i) = 2$ for 4 of $1 \leq i \leq 12$, and $D_4 \cap N_8 \simeq C_2$ for the unique characteristic subgroup $N_8 \simeq (C_2)^3 \triangleleft G$ of order 8, or (ii) $(C_4)^2 \leq G_v$
$12T66 \simeq ((C_2)^4 \rtimes C_3) \rtimes C_2$	(i) $V_4 \leq G_v$ where $ \text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$ and $N_G(V_4) \simeq (C_2)^4 \rtimes C_3$, or (ii) $D_4 \leq G_v$ where $ \text{Orb}_{D_4}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{D_4}(i) = 2$ for 4 of $1 \leq i \leq 12$
$12T77 \simeq (S_3)^2 \rtimes V_4$	(i) $V_4 \leq G_v$ where $ \text{Orb}_{V_4}(i) = 4$ for any $1 \leq i \leq 12$,
$12T210 \simeq (C_3)^4 \rtimes (D_4 \times C_2)$	(ii) $C_4 \times C_2 \leq G_v$, or (iii) $D_4 \leq G_v$ where $ \text{Orb}_{D_4}(i) = 8$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{D_4}(i) = 4$ for 4 of $1 \leq i \leq 12$
$12T92$ $\simeq (((C_4)^2 \rtimes C_2) \rtimes C_3) \times C_2$	(i) $D_4 \leq G_v$ where $ \text{Orb}_{D_4}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{D_4}(i) = 2$ for 4 of $1 \leq i \leq 12$, and $D_4 \cap N_{16} \simeq C_2$ for the unique characteristic subgroup $N_{16} \simeq (C_2)^4 \triangleleft G$ of order 16, or (ii) $(C_4)^2 \leq G_v$
$12T93$ $\simeq (((C_4 \rtimes C_4) \times C_2) \rtimes C_2) \rtimes C_3$	(i) $C_4 \rtimes C_4 \leq G_v$ where $ \text{Orb}_{C_4 \rtimes C_4}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{C_4 \rtimes C_4}(i) = 2$ for 4 of $1 \leq i \leq 12$, or (ii) $(C_4 \rtimes C_2) \rtimes C_4 \leq G_v$
$12T100$ $\simeq (((C_2)^4 \rtimes C_3) \rtimes C_2) \times C_2$	(i) $V_4 \leq G_v$ where $ \text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$ and (i-1) $N_G(V_4) \simeq (C_2)^4$, (i-2) $N_G(V_4) \simeq ((C_2)^4 \rtimes C_3) \times C_2$, or (i-3) $N_G(V_4) \simeq (C_2)^5$ and any non-zero element of V_4 is a product of 4 (different) transpositions, or (ii) $C_4 \times C_2 \leq G_v$ where $ \text{Orb}_{C_4 \times C_2}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{C_4 \times C_2}(i) = 2$ for 4 of $1 \leq i \leq 12$, or (iii) $D_4 \leq G_v$ where $ \text{Orb}_{D_4}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{D_4}(i) = 2$ for 4 of $1 \leq i \leq 12$

Table 2-2 (continued): $\text{III}(T) = 0$ for $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ and $G = \text{Gal}(L/k) = 12Tm$ as in Table 1

G	$\text{III}(T) \leq \mathbb{Z}/2\mathbb{Z}$, and $\text{III}(T) = 0$ if and only if there exists a place v of k such that
$12T102 \simeq ((C_2)^4 \rtimes C_3) \rtimes C_4$	<p>(i) $V_4 \leq G_v$ where $\text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$ and (i-1) $V_4 \cap D(G) \simeq C_2$ with $D(G) \simeq (C_2)^4 \rtimes C_3 \triangleleft G$, $V_4 \cap Z(G) = 1$ with $Z(G) \simeq C_2 \triangleleft G$ and any non-zero element of V_4 is a product of 4 (different) transpositions or, (i-2) $V_4 \leq D(G)$, $V_4 \cap Z(G) = 1$ and V_4 is not a normal subgroup of G,</p> <p>(ii) $C_4 \times C_2 \leq G_v$ where $\text{Orb}_{C_4 \times C_2}(i) = 4$ for 8 of $1 \leq i \leq 12$ and $\text{Orb}_{C_4 \times C_2}(i) = 2$ for 4 of $1 \leq i \leq 12$, or</p> <p>(iii) $G_{16,3} := (C_4 \times C_2) \rtimes C_2 \leq G_v$ where $\text{Orb}_{G_{16,3}}(i) = 8$ for 8 of $1 \leq i \leq 12$ and $\text{Orb}_{G_{16,3}}(i) = 2$ for 4 of $1 \leq i \leq 12$</p>
$12T144 \simeq (C_2)^5 \rtimes A_4(6)$	<p>(i) $V_4 \leq G_v$ where $\text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$, $V_4 \cap D^2(G) = 1$ with $D^2(G) \simeq (C_2)^3 \triangleleft G$ and $N_G(V_4) \simeq ((C_2)^4 \rtimes C_3) \times C_2$ is transitive in S_{12},</p> <p>(ii) $(C_4)^2 \leq G_v$,</p> <p>(iii) $G_{16,3} := (C_4 \times C_2) \rtimes C_2 \leq G_v$ where $\text{Orb}_{G_{16,3}}(i) = 4$ for any $1 \leq i \leq 12$,</p> <p>(iv) $C_4 \rtimes C_4 \leq G_v$, or</p> <p>(v) $(C_4 \times C_2) \rtimes C_4 \leq G_v$</p>
$12T188$ $\simeq (C_2)^6 \rtimes A_4(6) \simeq C_2 \wr A_4(6)$	<p>(i) $V_4 \leq G_v$ where $\text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$ and $V_4 \cap E_{64} = 1$ for the unique characteristic subgroup $E_{64} \simeq (C_2)^6 \triangleleft G$ of order 64,</p> <p>(ii) $C_4 \times C_2 \leq G_v$ where $\text{Orb}_{C_4 \times C_2}(i) = 4$ for 4 of $1 \leq i \leq 12$ and $\text{Orb}_{C_4 \times C_2}(i) = 2$ for 8 of $1 \leq i \leq 12$,</p> <p>(iii) $D_4 \leq G_v$ where $\text{Orb}_{D_4}(i) = 4$ for 4 (resp. 8) of $1 \leq i \leq 12$, $\text{Orb}_{D_4}(i) = 2$ for 8 (resp. 4) of $1 \leq i \leq 12$, $D_4 \cap E_{64} \simeq C_2$ (resp. C_2) with $E_{64} \simeq (C_2)^6 \triangleleft G$ and $D_4 \cap ((C_4)^2 \times C_2) \simeq C_2$ (resp. C_4) for the unique characteristic subgroup $(C_4)^2 \times C_2 \triangleleft G$ of order 32,</p> <p>(iv) $(C_4)^2 \leq G_v$ where (iv-1) $\text{Orb}_{(C_4)^2}(i) = 4$ for 8 of $1 \leq i \leq 12$, $\text{Orb}_{(C_4)^2}(i) = 2$ for 4 of $1 \leq i \leq 12$ or (iv-2) $\text{Orb}_{(C_4)^2}(i) = 4$ for any $1 \leq i \leq 12$ and $(C_4)^2 \cap E_{64} \simeq (C_4)^2$ with $E_{64} \simeq (C_2)^6 \triangleleft G$,</p> <p>(v) $G_{16,3} := (C_4 \times C_2) \rtimes C_2 \leq G_v$ where (v-1) $\text{Orb}_{G_{16,3}}(i) = 4$ for any $1 \leq i \leq 12$, $G_{16,3} \cap G_{64} \simeq (C_4 \times C_2) \rtimes C_2$ (resp. $C_4 \times C_2$), $G_{16,3} \cap G_{128} \simeq (C_2)^3$ (resp. $C_4 \times C_2$) and $G_{16,3} \cap E_{64} \simeq V_4$ (resp. V_4), or (v-2) $\text{Orb}_{G_{16,3}}(i) = 4$ for 8 of $1 \leq i \leq 12$, $\text{Orb}_{G_{16,3}}(i) = 2$ for 4 of $1 \leq i \leq 12$, $G_{16,3} \cap G_{64} \simeq V_4$ (resp. $(C_2)^3$), $G_{16,3} \cap G_{128} \simeq C_4 \times C_2$ (resp. $(C_4 \times C_2) \rtimes C_2$) and $G_{16,3} \cap E_{64} \simeq V_4$ (resp. V_4) for the unique characteristic subgroup $G_{64} \simeq ((C_2)^4 \rtimes C_2) \times C_2 \triangleleft G$ of order 64, the unique characteristic subgroup $G_{128} \simeq (((C_2)^4 \rtimes C_2) \times C_2) \rtimes C_2 \triangleleft G$ of order 128 and $E_{64} \simeq (C_2)^6 \triangleleft G$, or</p> <p>(vi) $C_4 \rtimes C_4 \leq G_v$ where (vi-1) $\text{Orb}_{C_4 \rtimes C_4}(i) = 4$ for 8 of $1 \leq i \leq 12$, $\text{Orb}_{C_4 \rtimes C_4}(i) = 2$ for 4 of $1 \leq i \leq 12$ or (vi-2) $\text{Orb}_{C_4 \rtimes C_4}(i) = 4$ for any $1 \leq i \leq 12$ and $(C_4 \rtimes C_4) \cap ((C_4)^2 \times C_2) \simeq C_4 \times C_2$ for the unique characteristic subgroup $(C_4)^2 \times C_2 \triangleleft G$ of order 32, or</p> <p>(vii) $(C_4 \times C_2) \rtimes C_4 \leq G_v$</p>

Table 2-2 (continued): $\text{III}(T) = 0$ for $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ and $G = \text{Gal}(L/k) = 12Tm$ as in Table 1

G	$\text{III}(T) \leq \mathbb{Z}/2\mathbb{Z}$, and $\text{III}(T) = 0$ if and only if there exists a place v of k such that
$12T214$ $\simeq (C_3)^4 \rtimes ((C_4 \times C_2) \rtimes C_2)$	(i) $C_4 \times C_2 \leq G_v$ where $ \text{Orb}_{C_4 \times C_2}(i) = 8$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{C_4 \times C_2}(i) = 4$ for 4 of $1 \leq i \leq 12$, (ii) $D_4 \leq G_v$ where $ \text{Orb}_{D_4}(i) = 8$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{D_4}(i) = 4$ for 4 of $1 \leq i \leq 12$, or (iii) $Q_8 \leq G_v$
$12T230 \simeq (C_2)^5 \rtimes A_5(6)$	(i) $V_4 \leq G_v$ where $ \text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$ and $V_4 \cap E_{32} = 1$ for the unique characteristic subgroup $E_{32} \simeq (C_2)^5 \triangleleft G$ of order 32, (ii) $(C_4)^2 \leq G_v$, (iii) $G_{16,3} := (C_4 \times C_2) \rtimes C_2 \leq G_v$ where $ \text{Orb}_{G_{16,3}}(i) = 4$ for 8 of $1 \leq i \leq 12$, $ \text{Orb}_{G_{16,3}}(i) = 2$ for 4 of $1 \leq i \leq 12$ and $G_{16,3} \cap E_{32} \simeq V_4$ for $E_{32} \simeq (C_2)^5 \triangleleft G$, (iv) $C_4 \rtimes C_4 \leq G_v$, or (v) $(C_4 \times C_2) \rtimes C_4 \leq G_v$
$12T242$ $\simeq (C_3)^4 \rtimes ((C_2)^3 \rtimes V_4)$	(i) $V_4 \leq G_v$ where $ \text{Orb}_{V_4}(i) = 4$ for any $1 \leq i \leq 12$, (ii) $C_4 \times C_2 \leq G_v$ where $ \text{Orb}_{C_4 \times C_2}(i) = 8$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{C_4 \times C_2}(i) = 4$ for 4 of $1 \leq i \leq 12$,
$12T271$ $\simeq ((C_3)^4 \rtimes (C_2)^3) \rtimes A_4(4)$	(iii) $D_4 \leq G_v$ where $ \text{Orb}_{D_4}(i) = 8$ for 8 of $1 \leq i \leq 12$ and $ \text{Orb}_{D_4}(i) = 4$ for 4 of $1 \leq i \leq 12$, or (iv) $Q_8 \leq G_v$
$12T255$ $\simeq (C_2)^6 \rtimes A_5(6) \simeq C_2 \wr A_5(6)$	(i) $V_4 \leq G_v$ where $ \text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$ and $V_4 \cap E_{64} = 1$ for the unique characteristic subgroup $E_{64} \simeq (C_2)^6 \triangleleft G$ of order 64, (ii) $C_4 \times C_2 \leq G_v$ where $ \text{Orb}_{C_4 \times C_2}(i) = 4$ for 4 of $1 \leq i \leq 12$, $ \text{Orb}_{C_4 \times C_2}(i) = 2$ for 8 of $1 \leq i \leq 12$ and $(C_4 \times C_2) \cap E_{64} \simeq C_2$ for $E_{64} \simeq (C_2)^6 \triangleleft G$, (iii) $D_4 \leq G_v$ where $ \text{Orb}_{D_4}(i) = 4$ for 4 (resp. 8) of $1 \leq i \leq 12$, $ \text{Orb}_{D_4}(i) = 2$ for 8 (resp. 4) of $1 \leq i \leq 12$, $D_4 \cap E_{64} \simeq C_2$ (resp. C_2) for $E_{64} \simeq (C_2)^6 \triangleleft G$ and $N_G(D_4) \simeq D_4 \times (C_2)^3$ (resp. $D_4 \times V_4$), (iv) $(C_4)^2 \leq G_v$ where (iv-1) $ \text{Orb}_{(C_4)^2}(i) = 4$ for 8 of $1 \leq i \leq 12$, $ \text{Orb}_{(C_4)^2}(i) = 2$ for 4 of $1 \leq i \leq 12$ or (iv-2) $ \text{Orb}_{(C_4)^2}(i) = 4$ for any $1 \leq i \leq 12$ and $(C_4)^2 \leq D(G)$ with $D(G) \simeq (C_2)^5 \rtimes A_5 \triangleleft G$, (v) $G_{16,3} := (C_4 \times C_2) \rtimes C_2 \leq G_v$ where (v-1) $ \text{Orb}_{G_{16,3}}(i) = 4$ for 8 of $1 \leq i \leq 12$, $ \text{Orb}_{G_{16,3}}(i) = 2$ for 4 of $1 \leq i \leq 12$ and $G_{16,3} \cap E_{64} \simeq V_4$ for $E_{64} \simeq (C_2)^6 \triangleleft G$ or (v-2) $ \text{Orb}_{G_{16,3}}(i) = 4$ for any $1 \leq i \leq 12$ $G_{16,3} \cap E_{64} \simeq V_4$ with $E_{64} \simeq (C_2)^6 \triangleleft G$, and $N_G(G_{16,3}) \simeq ((C_2)^4 \rtimes C_2) \times C_2$ or $((C_4 \times V_4) \rtimes C_2) \times C_2$, (vi) $C_4 \rtimes C_4 \leq G_v$ where (vi-1) $ \text{Orb}_{C_4 \rtimes C_4}(i) = 4$ for 8 of $1 \leq i \leq 12$, $ \text{Orb}_{C_4 \rtimes C_4}(i) = 2$ for 4 of $1 \leq i \leq 12$ or (vi-2) $ \text{Orb}_{C_4 \rtimes C_4}(i) = 4$ for any $1 \leq i \leq 12$ and $C_4 \rtimes C_4 \leq D(G)$ with $D(G) \simeq (C_2)^5 \rtimes A_5 \triangleleft G$, or (vii) $(C_4 \times C_2) \rtimes C_4 \leq G_v$

Table 2-3: $\text{III}(T)$ for $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ and $G = \text{Gal}(L/k) = 12T31$ as in Table 1

G	$\text{III}(T) \leq \mathbb{Z}/4\mathbb{Z}$
$12T31 \simeq (C_4)^2 \rtimes C_3$	(I) $\text{III}(T) = 0$ if and only if there exists a place v of k such that $(C_4)^2 \leq G_v$; (II) $\text{III}(T) \simeq \mathbb{Z}/2\mathbb{Z}$ if and only if there exists a place v of k such that $V_4 \leq G_v$ and (I) does not hold

Table 2-4: $\text{III}(T)$ for $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ and $G = \text{Gal}(L/k) = 12T57$ as in Table 1

G	$\text{III}(T) \leq \mathbb{Z}/4\mathbb{Z}$
$12T57 \simeq ((C_4 \times C_2) \rtimes C_4) \rtimes C_3$	(I) $\text{III}(T) = 0$ if and only if there exists a place v of k such that $\text{Syl}_2(G) \simeq (C_4 \times C_2) \rtimes C_4 \leq G_v$; (II) $\text{III}(T) \simeq \mathbb{Z}/2\mathbb{Z}$ if and only if there exists a place v of k such that $C_4 \times C_2 \leq G_v$ where $ \text{Orb}_{C_4 \times C_2}(i) = 4$ for 4 (resp. 8) of $1 \leq i \leq 12$ and $ \text{Orb}_{C_4 \times C_2}(i) = 2$ for 8 (resp. 4) of $1 \leq i \leq 12$ and (I) does not hold

Table 2-5: $\text{III}(T)$ for $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ and $G = \text{Gal}(L/k) = 12T32$ as in Table 1

G	$\text{III}(T) \leq (\mathbb{Z}/2\mathbb{Z})^{\oplus 2}$
$12T32 \simeq (C_2)^4 \rtimes C_3$	(I) $\text{III}(T) = 0$ if and only if (I-i) there exists a place v of k such that $\text{Syl}_2(G) \simeq (C_2)^4 \leq G_v$, or (I-ii) there exist places v_1, v_2 of k such that $V_4 \simeq V_4^{(1)} \leq G_{v_1}$, $V_4 \simeq V_4^{(2)} \leq G_{v_2}$ where $ \text{Orb}_{V_4^{(1)}}(i) = \text{Orb}_{V_4^{(2)}}(i) = 2$ for any $1 \leq i \leq 12$ and $V_4^{(1)} \neq V_4^{(2)}$; (II) $\text{III}(T) \simeq \mathbb{Z}/2\mathbb{Z}$ if and only if there exists a place v of k such that $V_4 \leq G_v$ where $ \text{Orb}_{V_4}(i) = 2$ for any $1 \leq i \leq 12$ and (I) does not hold

Remark 1.4. As a consequence of Theorem 1.3, we obtain the Tamagawa number $\tau(T)$ of norm one tori $T = R_{k/k}^{(1)}(\mathbb{G}_m)$ over a number field k via Ono's formula $\tau(T) = |H^1(G, J_{G/H})|/|\text{III}(T)|$ where $H^1(G, J_{G/H})$ is given as in Section 9 (Appendix) of the arXiv version (arXiv:1910.01469) of [HKY22] (see Ono [Ono63, Main theorem, page 68], Voskresenskii [Vos98, Theorem 2, page 146] and Hoshi, Kanai and Yamasaki [HKY22, Section 8, Application 2]).

We organize this paper as follows. In Section 2, we prepare basic definitions and known results about algebraic k -tori, in particular, norm one tori. In Section 3, we recall some known results about Hasse norm principle. In Section 4, we give some known results about norm one tori and k -rationality. In particular, we recall a flabby resolution of G -lattices which is a basic tool to investigate algebraic k -tori. In Section 5, we give the proof of Theorem 1.1. In Section 6, we recall Drakokhrust and Platonov's method for the Hasse norm principle for K/k and results in [HKY22, Section 6]. In Section 7, we prove Theorem 1.3 by using Drakokhrust and Platonov's method and some new useful functions of GAP [GAP]. In Section 8, GAP algorithms are given which are also available from <https://www.math.kyoto-u.ac.jp/~yamasaki/Algorithm/Norm1ToriHNP>.

Acknowledgments. We would like to thank Ming-chang Kang, Shizuo Endo and Boris Kunyavskii for giving us useful and valuable comments. We also thank the referee for very careful reading of the manuscript.

2. ALGEBRAIC TORI AND NORM ONE TORI

Let k be a field, \bar{k} be a fixed separable closure of k and $\mathcal{G} = \text{Gal}(\bar{k}/k)$ be the absolute Galois group of k . Let T be an algebraic k -torus, i.e. a group k -scheme with fiber product (base change) $T \times_k \bar{k} = T \times_{\text{Spec } k} \text{Spec } \bar{k} \simeq (\mathbb{G}_{m, \bar{k}})^n$; k -form of the split torus $(\mathbb{G}_m)^n$. Then there exists a finite Galois extension K/k with Galois group $G = \text{Gal}(K/k)$ such that T splits over K : $T \times_k K \simeq (\mathbb{G}_{m, K})^n$. It is also well-known that there is the duality between the category of G -lattices, i.e. finitely generated $\mathbb{Z}[G]$ -modules which are \mathbb{Z} -free as abelian groups, and the category of algebraic k -tori which split over K (see Ono [Ono61, Section 1.2], Voskresenskii [Vos98, page 27, Example 6] and Knus, Merkurjev, Rost and Tignol [KMRT98, page 333, Proposition 20.17]). Indeed, if T is an algebraic k -torus, then the character module $\widehat{T} = \text{Hom}(T, \mathbb{G}_m)$ of T may be regarded as a G -lattice. Let X be a smooth k -compactification of T , i.e. smooth projective k -variety X containing T as a dense open subvariety, and $\overline{X} = X \times_k \bar{k}$. There exists such a smooth k -compactification of an algebraic k -torus T over any field k (due to Hironaka [Hir64] for $\text{char } k = 0$, see Colliot-Thélène, Harari and Skorobogatov [CTHS05, Corollaire 1] for any field k).

Recall the following basic definitions of G -lattices.

Definition 2.1. Let G be a finite group and M be a G -lattice, i.e. finitely generated $\mathbb{Z}[G]$ -module which is \mathbb{Z} -free as an abelian group.

- (i) M is called a *permutation* G -lattice if M has a \mathbb{Z} -basis permuted by G , i.e. $M \simeq \bigoplus_{1 \leq i \leq m} \mathbb{Z}[G/H_i]$ for some subgroups H_1, \dots, H_m of G .
- (ii) M is called a *stably permutation* G -lattice if $M \oplus P \simeq P'$ for some permutation G -lattices P and P' .
- (iii) M is called *invertible* (or *permutation projective*) if it is a direct summand of a permutation G -lattice, i.e. $P \simeq M \oplus M'$ for some permutation G -lattice P and a G -lattice M' .
- (iv) M is called *flabby* (or *flasque*) if $\widehat{H}^{-1}(H, M) = 0$ for any subgroup H of G where \widehat{H} is the Tate cohomology.
- (v) M is called *coflabby* (or *coflasque*) if $H^1(H, M) = 0$ for any subgroup H of G .

Theorem 2.2 (Voskresenskii [Vos69, Section 4, page 1213], [Vos70, Section 3, page 7], see also [Vos98, Section 4.6], [Kun07, Theorem 1.9], [Vos74] and [CT07, Theorem 5.1, page 19] for any field k). *Let k be a field and $\mathcal{G} = \text{Gal}(\bar{k}/k)$. Let T be an algebraic k -torus, X be a smooth k -compactification of T and $\overline{X} = X \times_k \bar{k}$. Then there exists an exact sequence of \mathcal{G} -lattices*

$$0 \rightarrow \widehat{T} \rightarrow \widehat{Q} \rightarrow \text{Pic } \overline{X} \rightarrow 0$$

where \widehat{Q} is *permutation* and $\text{Pic } \overline{X}$ is *flabby*.

We have $H^1(k, \text{Pic } \overline{X}) \simeq H^1(G, \text{Pic } X_K)$ where K is the splitting field of T , $G = \text{Gal}(K/k)$ and $X_K = X \times_k K$. Hence Theorem 2.2 says that for G -lattices $M = \widehat{T}$ and $P = \widehat{Q}$, the exact sequence $0 \rightarrow M \rightarrow P \rightarrow \text{Pic } X_K \rightarrow 0$ gives a flabby resolution of M and the flabby class of M is $[M]^{\text{fl}} = [\text{Pic } X_K]$ as G -lattices (see Theorem 4.3).

Definition 2.3. The kernel of the norm map $R_{K/k}(\mathbb{G}_m) \rightarrow \mathbb{G}_m$ is called the *norm one torus* $R_{K/k}^{(1)}(\mathbb{G}_m)$ of K/k where $R_{K/k}$ is the Weil restriction (see [Vos98, page 37, Section 3.12]).

A norm one torus $R_{K/k}^{(1)}(\mathbb{G}_m)$ is biregularly isomorphic to the norm hyper surface $f(x_1, \dots, x_n) = 1$ where $f \in k[x_1, \dots, x_n]$ is the polynomial of total degree n defined by the norm map $N_{K/k} : K^\times \rightarrow k^\times$. When K/k is a finite Galois extension, we have that:

Theorem 2.4 (Voskresenskii [Vos70, Theorem 7], Colliot-Thélène and Sansuc [CTS77, Proposition 1]). *Let k be a field and K/k be a finite Galois extension with Galois group $G = \text{Gal}(K/k)$. Let $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ be the norm one torus of K/k and X be a smooth k -compactification of T . Then $H^1(H, \text{Pic } X_K) \simeq H^3(H, \mathbb{Z})$ for any subgroup H of G . In particular, $H^1(k, \text{Pic } \bar{X}) \simeq H^1(G, \text{Pic } X_K) \simeq H^3(G, \mathbb{Z})$ which is isomorphic to the Schur multiplier $M(G)$ of G .*

In other words, for G -lattice $J_G = \widehat{T}$, $H^1(H, [J_G]^{fl}) \simeq H^3(H, \mathbb{Z})$ for any subgroup H of G and $H^1(G, [J_G]^{fl}) \simeq H^3(G, \mathbb{Z}) \simeq H^2(G, \mathbb{Q}/\mathbb{Z})$; the Schur multiplier of G . By the exact sequence $0 \rightarrow \mathbb{Z} \rightarrow \mathbb{Z}[G] \rightarrow J_G \rightarrow 0$, we also have $\delta : H^1(G, J_G) \simeq H^2(G, \mathbb{Z}) \simeq G^{ab} \simeq G/[G, G]$ where δ is the connecting homomorphism and G^{ab} is the abelianization of G (cf. Section 4).

3. HASSE PRINCIPLE AND HASSE NORM PRINCIPLE

Let k be a global field, i.e. a number field (a finite extension of \mathbb{Q}) or a function field of an algebraic curve over \mathbb{F}_q (a finite extension of $\mathbb{F}_q(t)$).

Definition 3.1. Let T be an algebraic k -torus and $T(k)$ be the group of k -rational points of T . Then $T(k)$ embeds into $\prod_{v \in V_k} T(k_v)$ by the diagonal map where V_k is the set of all places of k and k_v is the completion of k at v . Let $\overline{T(k)}$ be the closure of $T(k)$ in the product $\prod_{v \in V_k} T(k_v)$. The group

$$A(T) = \left(\prod_{v \in V_k} T(k_v) \right) / \overline{T(k)}$$

is called *the kernel of the weak approximation* of T . We say that T has the weak approximation property if $A(T) = 0$.

Definition 3.2. Let E be a principal homogeneous space (= torsor) under T . *Hasse principle holds for E* means that if E has a k_v -rational point for all k_v , then E has a k -rational point. The set $H^1(k, T)$ classifies all such torsors E up to (non-unique) isomorphism. We define *the Shafarevich-Tate group* of T :

$$\text{III}(T) = \text{Ker} \left\{ H^1(k, T) \xrightarrow{\text{res}} \bigoplus_{v \in V_k} H^1(k_v) \right\}.$$

Then Hasse principle holds for all torsors E under T if and only if $\text{III}(T) = 0$.

Theorem 3.3 (Voskresenskii [Vos69, Theorem 5, page 1213], [Vos70, Theorem 6, page 9], see also [Vos98, Section 11.6, Theorem, page 120]). *Let k be a global field, T be an algebraic k -torus and X be a smooth k -compactification of T . Then there exists an exact sequence*

$$0 \rightarrow A(T) \rightarrow H^1(k, \text{Pic } \bar{X})^\vee \rightarrow \text{III}(T) \rightarrow 0$$

where $M^\vee = \text{Hom}(M, \mathbb{Q}/\mathbb{Z})$ is the Pontryagin dual of M . Moreover, if L is the splitting field of T and L/k is an unramified extension, then $A(T) = 0$ and $H^1(k, \text{Pic } \bar{X})^\vee \simeq \text{III}(T)$.

For the last assertion, see [Vos98, Section 11.5]. It follows that $H^1(k, \text{Pic } \bar{X}) = 0$ if and only if $A(T) = 0$ and $\text{III}(T) = 0$, i.e. T has the weak approximation property and Hasse principle holds for all torsors E under T . Theorem 3.3 was generalized to the case of linear algebraic groups by Sansuc [San81].

Definition 3.4. Let k be a global field, K/k be a finite extension and \mathbb{A}_K^\times be the idele group of K . We say that *the Hasse norm principle holds for K/k* if $(N_{K/k}(\mathbb{A}_K^\times) \cap k^\times)/N_{K/k}(K^\times) = 1$ where $N_{K/k}$ is the norm map.

Hasse [Has31, Satz, page 64] proved that the Hasse norm principle holds for any cyclic extension K/k but does not hold for bicyclic extension $\mathbb{Q}(\sqrt{-39}, \sqrt{-3})/\mathbb{Q}$. For Galois extensions K/k , Tate [Tat67] gave the following theorem:

Theorem 3.5 (Tate [Tat67, page 198]). *Let k be a global field, K/k be a finite Galois extension with Galois group $\text{Gal}(K/k) \simeq G$. Let V_k be the set of all places of k and G_v be the decomposition group of G at $v \in V_k$. Then*

$$(N_{K/k}(\mathbb{A}_K^\times) \cap k^\times)/N_{K/k}(K^\times) \simeq \text{Coker} \left\{ \bigoplus_{v \in V_k} \widehat{H}^{-3}(G_v, \mathbb{Z}) \xrightarrow{\text{cores}} \widehat{H}^{-3}(G, \mathbb{Z}) \right\}$$

where \widehat{H} is the Tate cohomology. In particular, the Hasse norm principle holds for K/k if and only if the restriction map $H^3(G, \mathbb{Z}) \xrightarrow{\text{res}} \bigoplus_{v \in V_k} H^3(G_v, \mathbb{Z})$ is injective.

If $G \simeq C_n$ is cyclic, then $\widehat{H}^{-3}(G, \mathbb{Z}) \simeq H^3(G, \mathbb{Z}) \simeq H^1(G, \mathbb{Z}) = 0$ and hence the Hasse's original theorem follows. If there exists a place v of k such that $G_v = G$, then the Hasse norm principle also holds for K/k . For example, the Hasse norm principle holds for K/k with $G \simeq V_4$ if and only if there exists a place v of k such that $G_v = V_4$ because $H^3(V_4, \mathbb{Z}) \simeq \mathbb{Z}/2\mathbb{Z}$ and $H^3(C_2, \mathbb{Z}) = 0$. The Hasse norm principle holds for K/k with $G \simeq (C_2)^3$ if and only if (i) there exists a place v of k such that $G_v = G$ or (ii) there exist places v_1, v_2, v_3 of k such that $G_{v_i} \simeq V_4$ and $H^3(G, \mathbb{Z}) \xrightarrow{\text{res}} H^3(G_{v_1}, \mathbb{Z}) \oplus H^3(G_{v_2}, \mathbb{Z}) \oplus H^3(G_{v_3}, \mathbb{Z})$ is isomorphism because $H^3(G, \mathbb{Z}) \simeq (\mathbb{Z}/2\mathbb{Z})^{\oplus 3}$ and $H^3(V_4, \mathbb{Z}) \simeq \mathbb{Z}/2\mathbb{Z}$.

The Hasse norm principle for Galois extensions K/k was investigated by Gerth [Ger77], [Ger78] and Gurak [Gur78a], [Gur78b], [Gur80] (see also [PR94, pages 308–309]). For non-Galois extension K/k , the Hasse norm principle was investigated by Bartels [Bar81a] ($[K : k] = p$; prime), [Bar81b] ($\text{Gal}(L/k) \simeq D_n$), Voskresenskii and Kunyavskii [VK84] ($\text{Gal}(L/k) \simeq S_n$) and Macedo [Mac20] ($\text{Gal}(L/k) \simeq A_n$) where L/k be the Galois closure of K/k (see also [HKY22, Section 1]).

Ono [Ono63] established the relationship between the Hasse norm principle for K/k and the Hasse principle for all torsors E under the norm one torus $R_{K/k}^{(1)}(\mathbb{G}_m)$. The quotient group $k^\times/N_{K/k}(K^\times)$ is related to the norm one torus $R_{K/k}^{(1)}(\mathbb{G}_m)$ of K/k because by taking the cohomology of the exact sequence

$$1 \rightarrow R_{K/k}^{(1)}(\mathbb{G}_m) \rightarrow R_{K/k}(\mathbb{G}_m) \xrightarrow{N} \mathbb{G}_m \rightarrow 1,$$

we have the exact sequence

$$K^\times \xrightarrow{N_{K/k}} k^\times \rightarrow H^1(k, R_{K/k}^{(1)}(\mathbb{G}_m)) \rightarrow H^1(k, R_{K/k}(\mathbb{G}_m)) \simeq H^1(K, \mathbb{G}_m) = 0 \text{ (by Hilbert 90)}$$

and (see Platonov and Rapinchuk [PR94, Lemma 2.5, page 73])

$$H^1(k, R_{K/k}^{(1)}(\mathbb{G}_m)) \simeq k^\times/N_{K/k}(K^\times).$$

Similarly, the Hasse norm principle for K/k is related to the norm one torus $R_{K/k}^{(1)}(\mathbb{G}_m)$ of K/k (see also Platonov and Rapinchuk [PR94, Section 6.3]):

Theorem 3.6 (Ono [Ono63, page 70], see also Platonov [Pla82, page 44], Kunyavskii [Kun84, Remark 3], Platonov and Rapinchuk [PR94, page 307]). *Let k be a global field and K/k be a finite extension. Then*

$$\text{III}(R_{K/k}^{(1)}(\mathbb{G}_m)) \simeq (N_{K/k}(\mathbb{A}_K^\times) \cap k^\times)/N_{K/k}(K^\times).$$

In particular, $\text{III}(R_{K/k}^{(1)}(\mathbb{G}_m)) = 0$ if and only if the Hasse norm principle holds for K/k .

Remark 3.7. Applying Theorem 3.3 to $T = R_{K/k}^{(1)}(\mathbb{G}_m)$, it follows from Theorem 3.6 that $H^1(k, \text{Pic } \overline{X}) = 0$ if and only if $A(T) = 0$ and $\text{III}(T) = 0$, i.e. T has the weak approximation property and the Hasse norm principle holds for K/k . In the algebraic language, the latter condition $\text{III}(T) = 0$ means that for the corresponding norm hyper surface $f(x_1, \dots, x_n) = b$, it has a k -rational point if and only if it has a k_v -rational point for any place v of k where $f \in k[x_1, \dots, x_n]$ is the polynomial of total degree n defined by the norm map $N_{K/k} : K^\times \rightarrow k^\times$ and $b \in k^\times$ (see [Vos98, Example 4, page 122]).

4. FLABBY RESOLUTION OF G -LATTICE AND RATIONALITY OF ALGEBRAIC k -TORUS

Let k be a field, K/k be a separable field extension of degree n and L/k be the Galois closure of K/k . Let $G = \text{Gal}(L/k)$ and $H = \text{Gal}(L/K)$ with $[G : H] = n$. The Galois group G may be regarded as a transitive subgroup of the symmetric group S_n of degree n via an injection $G \rightarrow S_n$ which is derived from the action of G on the left cosets $\{g_1H, \dots, g_nH\}$ by $g(g_iH) = (g g_i)H$ for any $g \in G$ and we may assume that H is the stabilizer of one of the letters in G , i.e. $L = k(\theta_1, \dots, \theta_n)$ and $K = k(\theta_i)$ for some $1 \leq i \leq n$. The norm one torus $R_{K/k}^{(1)}(\mathbb{G}_m)$ has the Chevalley module $J_{G/H}$ as its character module and the field $L(J_{G/H})^G$ as its function field where $J_{G/H} = (I_{G/H})^\circ = \text{Hom}_{\mathbb{Z}}(I_{G/H}, \mathbb{Z})$ is the dual lattice of $I_{G/H} = \text{Ker } \varepsilon$ and $\varepsilon : \mathbb{Z}[G/H] \rightarrow \mathbb{Z}$ is the augmentation map (see [Vos98, Section 4.8]). We have the exact sequence

$$0 \rightarrow \mathbb{Z} \rightarrow \mathbb{Z}[G/H] \rightarrow J_{G/H} \rightarrow 0$$

and rank $J_{G/H} = n - 1$. Write $J_{G/H} = \bigoplus_{1 \leq i \leq n-1} \mathbb{Z} u_i$. We define the action of G on $L(x_1, \dots, x_{n-1})$ by $\sigma(x_i) = \prod_{j=1}^{n-1} x_j^{a_{i,j}}$ ($1 \leq i \leq n-1$) for any $\sigma \in G$, when $\sigma(u_i) = \sum_{j=1}^{n-1} a_{i,j} u_j$ ($a_{i,j} \in \mathbb{Z}$). Then the invariant field $L(x_1, \dots, x_{n-1})^G$ may be identified with the function field of the norm one torus $R_{K/k}^{(1)}(\mathbb{G}_m)$ (see [EM75, Section 1]).

Let $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ be the norm one torus of K/k . The rationality problem for norm one tori is investigated by [EM75], [CTS77], [Hür84], [CTS87], [LeB95], [CK00], [LL00], [Flo], [End11], [HY17], [HY21], [HHY20] (see also [HKY22, Section 2]).

We recall some basic facts of flabby (flasque) G -lattices (see [CTS77], [Swa83], [Vos98, Chapter 2], [Lor05, Chapter 2], [Swa10]).

Definition 4.1 (see [EM75, Section 1], [Vos98, Section 4.7]). Let $\mathcal{C}(G)$ be the category of all G -lattices. Let $\mathcal{S}(G)$ be the full subcategory of $\mathcal{C}(G)$ of all permutation G -lattices and $\mathcal{D}(G)$ be the full subcategory of $\mathcal{C}(G)$ of all invertible G -lattices. Let

$$\mathcal{H}^i(G) = \{M \in \mathcal{C}(G) \mid \widehat{H}^i(H, M) = 0 \text{ for any } H \leq G\} \quad (i = \pm 1)$$

be the class of “ \widehat{H}^i -vanish” G -lattices where \widehat{H}^i is the Tate cohomology. Then we have the inclusions $\mathcal{S}(G) \subset \mathcal{D}(G) \subset \mathcal{H}^i(G) \subset \mathcal{C}(G)$ ($i = \pm 1$).

Definition 4.2. We say that two G -lattices M_1 and M_2 are *similar* if there exist permutation G -lattices P_1 and P_2 such that $M_1 \oplus P_1 \simeq M_2 \oplus P_2$. We denote the similarity class of M by $[M]$. The set of similarity classes $\mathcal{C}(G)/\mathcal{S}(G)$ becomes a commutative monoid (with respect to the sum $[M_1] + [M_2] := [M_1 \oplus M_2]$ and the zero $0 = [P]$ where $P \in \mathcal{S}(G)$).

Theorem 4.3 (Endo and Miyata [EM75, Lemma 1.1], Colliot-Thélène and Sansuc [CTS77, Lemma 3], see also [Swa83, Lemma 8.5], [Lor05, Lemma 2.6.1]). *For any G -lattice M , there exists a short exact sequence of G -lattices $0 \rightarrow M \rightarrow P \rightarrow F \rightarrow 0$ where P is permutation and F is flabby.*

Definition 4.4. The exact sequence $0 \rightarrow M \rightarrow P \rightarrow F \rightarrow 0$ as in Theorem 4.3 is called a *flabby resolution* of the G -lattice M . $\rho_G(M) = [F] \in \mathcal{C}(G)/\mathcal{S}(G)$ is called the *flabby class* of M , denoted by $[M]^{fl} = [F]$. Note that $[M]^{fl}$ is well-defined: if $[M] = [M']$, $[M]^{fl} = [F]$ and $[M']^{fl} = [F']$ then $F \oplus P_1 \simeq F' \oplus P_2$ for some permutation G -lattices P_1 and P_2 , and therefore $[F] = [F']$ (cf. [Swa83, Lemma 8.7]). We say that $[M]^{fl}$ is *invertible* if $[M]^{fl} = [E]$ for some invertible G -lattice E .

For G -lattice M , it is not difficult to see

$$\begin{array}{ccccccc} \text{permutation} & \Rightarrow & \text{stably permutation} & \Rightarrow & \text{invertible} & \Rightarrow & \text{flabby and coflabby} \\ & & \Downarrow & & \Downarrow & & \\ & & [M]^{fl} = 0 & & \Rightarrow & & [M]^{fl} \text{ is invertible.} \end{array}$$

The above implications in each step cannot be reversed (see, for example, [HY17, Section 1]).

Definition 4.5. Let k be a field, and K and K' be finitely generated field extensions of k .

- (i) K is called *rational over k* (or *k -rational* for short) if K is purely transcendental over k , i.e. K is isomorphic to $k(x_1, \dots, x_n)$, the rational function field over k with n variables x_1, \dots, x_n for some integer n .
- (ii) K is called *stably k -rational* if $K(y_1, \dots, y_m)$ is k -rational for some algebraically independent elements y_1, \dots, y_m over K .
- (iii) K and K' are called *stably k -isomorphic* if $K(y_1, \dots, y_m) \simeq K'(z_1, \dots, z_n)$ over k for some algebraically independent elements y_1, \dots, y_m over K and z_1, \dots, z_n over K' .
- (iv) When k is an infinite field, K is called *retract k -rational* if there is a k -algebra R contained in K such that K is the quotient field of R , and the identity map $1_R : R \rightarrow R$ factors through a localized polynomial ring over k , i.e. there is an element $f \in k[x_1, \dots, x_n]$, which is the polynomial ring over k , and there are k -algebra homomorphisms $\varphi : R \rightarrow k[x_1, \dots, x_n][1/f]$ and $\psi : k[x_1, \dots, x_n][1/f] \rightarrow R$ satisfying $\psi \circ \varphi = 1_R$ (cf. [Sal84]).
- (v) K is called *k -unirational* if $k \subset K \subset k(x_1, \dots, x_n)$ for some integer n .

It is not difficult to see that “ k -rational” \Rightarrow “stably k -rational” \Rightarrow “retract k -rational” \Rightarrow “ k -unirational”.

Let L/k be a finite Galois extension with Galois group $G = \text{Gal}(L/k)$ and M be a G -lattice. The flabby class $\rho_G(M) = [M]^{fl}$ plays crucial role in the rationality problem for $L(M)^G$ as follows (see Voskresenskii’s fundamental book [Vos98, Section 4.6] and Kunyavskii [Kun07], see also e.g. Swan [Swa83], Kunyavskii [Kun90, Section 2], Lemire, Popov and Reichstein [LPR06, Section 2], Kang [Kan12], Yamasaki [Yam12], Hoshi and Yamasaki [HY17], Hoshi, Kanai and Yamasaki [HKY22]):

Theorem 4.6 (Endo and Miyata [EM73], Voskresenskii [Vos74], Saltman [Sal84]). *Let L/k be a finite Galois extension with Galois group $G = \text{Gal}(L/k)$. Let M and M' be G -lattices. Then we have:*

- (i) (Endo and Miyata [EM73, Theorem 1.6]) $[M]^{fl} = 0$ if and only if $L(M)^G$ is stably k -rational;
- (ii) (Voskresenskii [Vos74, Theorem 2]) $[M]^{fl} = [M']^{fl}$ if and only if $L(M)^G$ and $L(M')^G$ are stably k -isomorphic;
- (iii) (Saltman [Sal84, Theorem 3.14]) $[M]^{fl}$ is invertible if and only if $L(M)^G$ is retract k -rational.

It is easy to see that all the 1-dimensional algebraic k -tori T , i.e. the trivial torus \mathbb{G}_m and the norm one torus $R_{K/k}^{(1)}(\mathbb{G}_m)$ of K/k with $[K : k] = 2$, are k -rational. Voskresenskii [Vos67] showed that all the 2-dimensional algebraic k -tori T are k -rational. Kunyavskii [Kun90] gave a rational (stably rational, retract rational) classification of 3-dimensional algebraic k -tori. Hoshi and Yamasaki [HY17, Theorem 1.9 and Theorem 1.12] classified stably/retract rational algebraic k -tori of dimension 4 and 5 (see also [HKY22, Section 1]).

For norm one tori $T = R_{K/k}^{(1)}(\mathbb{G}_m)$, recall that the function field $k(T)$ may be regarded as $L(M)^G$ for the character module $M = J_{G/H}$ and hence we have:

$$[J_{G/H}]^{fl} = 0 \Rightarrow [J_{G/H}]^{fl} \text{ is invertible} \Rightarrow H^1(G, [J_{G/H}]^{fl}) = 0 \Rightarrow A(T) = 0 \text{ and } \text{III}(T) = 0$$

where the last implication holds over a global field k (see also Colliot-Thélène and Sansuc [CTS77, page 29]). The last conditions mean that T has the weak approximation property and the Hasse norm principle holds for K/k (see Section 1). In particular, it follows that $[J_{G/H}]^{fl}$ is invertible and hence $A(T) = 0$ and $\text{III}(T) = 0$ when $G = pTm \leq S_p$ is a transitive subgroup of S_p of prime degree p and $H = G \cap S_{p-1} \leq G$ with $[G : H] = p$ (see Colliot-Thélène and Sansuc [CTS87, Proposition 9.1] and [HY17, Lemma 2.17]). Hence the Hasse norm principle holds for K/k when $[K : k] = p$ (see the second paragraph after Theorem 3.5 and also the first paragraph of Section 5).

A necessary and sufficient condition for the classification of stably/retract rational norm one tori $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ with $[K : k] = n \leq 15$, but with one exception $G = 9T27 \simeq \text{PSL}_2(\mathbb{F}_8)$ for the stable rationality, was given in Hoshi and Yamasaki [HY21] (for the case n is a prime number or the case $n \leq 10$) and Hasegawa, Hoshi and Yamasaki [HY20] (for $n = 12, 14, 15$).

5. PROOF OF THEOREM 1.1

Let K/k be a separable field extension of degree 12 and L/k be the Galois closure of K/k . Let $G = \text{Gal}(L/k) = 12Tm$ ($1 \leq m \leq 301$) be a transitive subgroup of S_{12} and $H = \text{Gal}(L/K)$ with $[G : H] = 12$. Let $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ be the norm one torus of K/k of dimension 11. We have the character module $\widehat{T} = J_{G/H}$ of T and then $H^1(k, \text{Pic } \overline{X}) \simeq H^1(G, [J_{G/H}]^{fl})$ (see Section 4). We may assume that H is the stabilizer of one of the letters in G , i.e. $L = k(\theta_1, \dots, \theta_{12})$ and $K = k(\theta_i)$ for some $1 \leq i \leq 12$. In order to compute $H^1(G, [J_{G/H}]^{fl})$, we apply the functions `Norm1TorusJ(12, m)` and `FlabbyResolution(G).actionF` for $1 \leq m \leq 299$ as in [HY17, Chapter 5]. The function `Norm1TorusJ(12, m)` returns $J_{G/H}$ for $G = 12Tm \leq S_{12}$ and H is the stabilizer of one of the letters in G , and `FlabbyResolution(G).actionF` returns a flabby class $F = [J_{G/H}]^{fl}$ for $G = 12Tm \leq S_{12}$. The assertion for $G = 12Tm$ ($1 \leq m \leq 299$) follows from these computations as in Example 5.1.

For $G = 12T300 \simeq A_{12}$, $12T301 \simeq S_{12}$, we did not get an answer by the computer calculations because it needs much time and computer resources (memory) in computations. However, we already know that $H^1(G, [J_{G/H}]^{fl}) = 0$ for $G = 12T300 \simeq A_{12}$, $12T301 \simeq S_{12}$ by Macedo [Mac20] and Voskresenskii and Kunyavskii [VK84] respectively (see also [Vos88, Theorem 4, Corollary] and [HKY22, Theorem 1.10 and Theorem 1.11]).

The last assertion follows from Theorem 3.3. □

Some related functions for Example 5.1 are available from
<https://www.math.kyoto-u.ac.jp/~yamasaki/Algorithm/RatProbNorm1Tori/>.

Example 5.1 (Computation of $H^1(G, [J_{G/H}]^{fl})$ with $G = 12Tm$ ($1 \leq m \leq 299$)).

```
gap> Read("FlabbyResolutionFromBase.gap");
gap> for i in [1..299] do
> F:=FlabbyResolution(Norm1TorusJ(12,i)).actionF;
> Print([[12,i],Length(F.1),Filtered(H1(F),x->x>1)],"\n");od;
[[12, 1], 1, [ ]]
[[12, 2], 13, [2 ]]
[[12, 3], 25, [2 ]]
[[12, 4], 13, [2 ]]
[[12, 5], 13, [ ]]
[[12, 6], 43, [ ]]
[[12, 7], 43, [2 ]]
[[12, 8], 31, [ ]]
[[12, 9], 67, [2 ]]
[[12, 10], 61, [2 ]]
[[12, 11], 25, [ ]]
[[12, 12], 31, [ ]]
[[12, 13], 31, [ ]]
```

```
[ [ 12, 14 ], 31, [ ] ]
[ [ 12, 15 ], 31, [ ] ]
[ [ 12, 16 ], 53, [ 2 ] ]
[ [ 12, 17 ], 53, [ ] ]
[ [ 12, 18 ], 41, [ 2 ] ]
[ [ 12, 19 ], 41, [ ] ]
[ [ 12, 20 ], 37, [ 2 ] ]
[ [ 12, 21 ], 67, [ ] ]
[ [ 12, 22 ], 91, [ ] ]
[ [ 12, 23 ], 73, [ ] ]
[ [ 12, 24 ], 73, [ ] ]
[ [ 12, 25 ], 43, [ ] ]
[ [ 12, 26 ], 160, [ ] ]
[ [ 12, 27 ], 91, [ ] ]
[ [ 12, 28 ], 115, [ ] ]
[ [ 12, 29 ], 31, [ ] ]
[ [ 12, 30 ], 55, [ ] ]
[ [ 12, 31 ], 64, [ 4 ] ]
[ [ 12, 32 ], 172, [ 2, 2 ] ]
[ [ 12, 33 ], 61, [ 2 ] ]
[ [ 12, 34 ], 65, [ 2 ] ]
[ [ 12, 35 ], 111, [ ] ]
[ [ 12, 36 ], 123, [ ] ]
[ [ 12, 37 ], 65, [ 2 ] ]
[ [ 12, 38 ], 123, [ ] ]
[ [ 12, 39 ], 53, [ ] ]
[ [ 12, 40 ], 65, [ 2 ] ]
[ [ 12, 41 ], 65, [ ] ]
[ [ 12, 42 ], 99, [ ] ]
[ [ 12, 43 ], 121, [ 2 ] ]
[ [ 12, 44 ], 139, [ ] ]
[ [ 12, 45 ], 55, [ ] ]
[ [ 12, 46 ], 53, [ ] ]
[ [ 12, 47 ], 93, [ 2 ] ]
[ [ 12, 48 ], 97, [ ] ]
[ [ 12, 49 ], 277, [ ] ]
[ [ 12, 50 ], 97, [ ] ]
[ [ 12, 51 ], 67, [ ] ]
[ [ 12, 52 ], 115, [ 2 ] ]
[ [ 12, 53 ], 85, [ ] ]
[ [ 12, 54 ], 115, [ 2 ] ]
[ [ 12, 55 ], 64, [ 2 ] ]
[ [ 12, 56 ], 172, [ 2 ] ]
[ [ 12, 57 ], 100, [ 4 ] ]
[ [ 12, 58 ], 79, [ ] ]
[ [ 12, 59 ], 190, [ 2 ] ]
[ [ 12, 60 ], 118, [ ] ]
[ [ 12, 61 ], 142, [ 2 ] ]
[ [ 12, 62 ], 127, [ ] ]
[ [ 12, 63 ], 139, [ ] ]
[ [ 12, 64 ], 157, [ 2 ] ]
[ [ 12, 65 ], 157, [ 2 ] ]
[ [ 12, 66 ], 301, [ 2 ] ]
[ [ 12, 67 ], 259, [ ] ]
[ [ 12, 68 ], 259, [ ] ]
[ [ 12, 69 ], 109, [ ] ]
[ [ 12, 70 ], 117, [ 2 ] ]
[ [ 12, 71 ], 117, [ 2 ] ]
[ [ 12, 72 ], 77, [ ] ]
[ [ 12, 73 ], 77, [ ] ]
[ [ 12, 74 ], 91, [ 2 ] ]
[ [ 12, 75 ], 91, [ 2 ] ]
```

```

[[ 12, 76 ], 91, [ ] ]
[[ 12, 77 ], 65, [ 2 ] ]
[[ 12, 78 ], 123, [ ] ]
[[ 12, 79 ], 53, [ ] ]
[[ 12, 80 ], 123, [ ] ]
[[ 12, 81 ], 123, [ ] ]
[[ 12, 82 ], 123, [ ] ]
[[ 12, 83 ], 175, [ ] ]
[[ 12, 84 ], 147, [ ] ]
[[ 12, 85 ], 184, [ ] ]
[[ 12, 86 ], 163, [ ] ]
[[ 12, 87 ], 79, [ ] ]
[[ 12, 88 ], 190, [ 2 ] ]
[[ 12, 89 ], 118, [ ] ]
[[ 12, 90 ], 172, [ ] ]
[[ 12, 91 ], 112, [ ] ]
[[ 12, 92 ], 142, [ 2 ] ]
[[ 12, 93 ], 142, [ 2 ] ]
[[ 12, 94 ], 64, [ ] ]
[[ 12, 95 ], 175, [ ] ]
[[ 12, 96 ], 217, [ 2 ] ]
[[ 12, 97 ], 157, [ 2 ] ]
[[ 12, 98 ], 127, [ ] ]
[[ 12, 99 ], 184, [ ] ]
[[ 12, 100 ], 361, [ 2 ] ]
[[ 12, 101 ], 331, [ ] ]
[[ 12, 102 ], 301, [ 2 ] ]
[[ 12, 103 ], 283, [ ] ]
[[ 12, 104 ], 100, [ ] ]
[[ 12, 105 ], 79, [ ] ]
[[ 12, 106 ], 109, [ ] ]
[[ 12, 107 ], 109, [ ] ]
[[ 12, 108 ], 139, [ ] ]
[[ 12, 109 ], 139, [ ] ]
[[ 12, 110 ], 325, [ ] ]
[[ 12, 111 ], 325, [ ] ]
[[ 12, 112 ], 217, [ ] ]
[[ 12, 113 ], 265, [ ] ]
[[ 12, 114 ], 205, [ ] ]
[[ 12, 115 ], 205, [ ] ]
[[ 12, 116 ], 171, [ ] ]
[[ 12, 117 ], 129, [ 2 ] ]
[[ 12, 118 ], 183, [ ] ]
[[ 12, 119 ], 89, [ ] ]
[[ 12, 120 ], 183, [ ] ]
[[ 12, 121 ], 171, [ ] ]
[[ 12, 122 ], 133, [ 2 ] ]
[[ 12, 123 ], 121, [ ] ]
[[ 12, 124 ], 211, [ ] ]
[[ 12, 125 ], 123, [ ] ]
[[ 12, 126 ], 141, [ ] ]
[[ 12, 127 ], 433, [ ] ]
[[ 12, 128 ], 271, [ ] ]
[[ 12, 129 ], 202, [ ] ]
[[ 12, 130 ], 117, [ 2 ] ]
[[ 12, 131 ], 77, [ ] ]
[[ 12, 132 ], 121, [ 2 ] ]
[[ 12, 133 ], 121, [ 2 ] ]
[[ 12, 134 ], 79, [ ] ]
[[ 12, 135 ], 109, [ ] ]
[[ 12, 136 ], 163, [ ] ]
[[ 12, 137 ], 397, [ ] ]

```

[[12, 138], 505, []]
[[12, 139], 583, []]
[[12, 140], 253, []]
[[12, 141], 142, []]
[[12, 142], 190, []]
[[12, 143], 190, []]
[[12, 144], 190, [2]]
[[12, 145], 163, []]
[[12, 146], 349, []]
[[12, 147], 313, []]
[[12, 148], 409, []]
[[12, 149], 205, []]
[[12, 150], 235, []]
[[12, 151], 265, []]
[[12, 152], 457, []]
[[12, 153], 457, []]
[[12, 154], 163, []]
[[12, 155], 187, []]
[[12, 156], 183, []]
[[12, 157], 187, []]
[[12, 158], 179, []]
[[12, 159], 179, []]
[[12, 160], 287, []]
[[12, 161], 191, []]
[[12, 162], 171, []]
[[12, 163], 171, []]
[[12, 164], 184, []]
[[12, 165], 433, []]
[[12, 166], 184, []]
[[12, 167], 279, []]
[[12, 168], 129, [2]]
[[12, 169], 291, []]
[[12, 170], 89, []]
[[12, 171], 129, [2]]
[[12, 172], 129, [2]]
[[12, 173], 89, []]
[[12, 174], 129, [2]]
[[12, 175], 283, []]
[[12, 176], 133, [2]]
[[12, 177], 295, []]
[[12, 178], 295, []]
[[12, 179], 121, [2]]
[[12, 180], 281, []]
[[12, 181], 291, []]
[[12, 182], 291, []]
[[12, 183], 281, []]
[[12, 184], 397, []]
[[12, 185], 553, []]
[[12, 186], 649, []]
[[12, 187], 190, []]
[[12, 188], 190, [2]]
[[12, 189], 190, []]
[[12, 190], 397, []]
[[12, 191], 349, []]
[[12, 192], 349, []]
[[12, 193], 163, []]
[[12, 194], 229, [2]]
[[12, 195], 227, []]
[[12, 196], 291, []]
[[12, 197], 227, []]
[[12, 198], 227, []]
[[12, 199], 227, []]

```

[ [ 12, 200 ], 279, [ ] ]
[ [ 12, 201 ], 291, [ ] ]
[ [ 12, 202 ], 227, [ ] ]
[ [ 12, 203 ], 183, [ ] ]
[ [ 12, 204 ], 757, [ ] ]
[ [ 12, 205 ], 202, [ ] ]
[ [ 12, 206 ], 595, [ ] ]
[ [ 12, 207 ], 757, [ ] ]
[ [ 12, 208 ], 243, [ ] ]
[ [ 12, 209 ], 291, [ ] ]
[ [ 12, 210 ], 129, [ 2 ] ]
[ [ 12, 211 ], 89, [ ] ]
[ [ 12, 212 ], 295, [ ] ]
[ [ 12, 213 ], 295, [ ] ]
[ [ 12, 214 ], 129, [ 2 ] ]
[ [ 12, 215 ], 89, [ ] ]
[ [ 12, 216 ], 295, [ ] ]
[ [ 12, 217 ], 291, [ ] ]
[ [ 12, 218 ], 451, [ ] ]
[ [ 12, 219 ], 281, [ ] ]
[ [ 12, 220 ], 331, [ ] ]
[ [ 12, 221 ], 649, [ ] ]
[ [ 12, 222 ], 190, [ ] ]
[ [ 12, 223 ], 649, [ ] ]
[ [ 12, 224 ], 349, [ ] ]
[ [ 12, 225 ], 649, [ ] ]
[ [ 12, 226 ], 649, [ ] ]
[ [ 12, 227 ], 397, [ ] ]
[ [ 12, 228 ], 184, [ ] ]
[ [ 12, 229 ], 184, [ ] ]
[ [ 12, 230 ], 646, [ 2 ] ]
[ [ 12, 231 ], 715, [ ] ]
[ [ 12, 232 ], 241, [ 2 ] ]
[ [ 12, 233 ], 727, [ ] ]
[ [ 12, 234 ], 241, [ 2 ] ]
[ [ 12, 235 ], 339, [ ] ]
[ [ 12, 236 ], 275, [ ] ]
[ [ 12, 237 ], 275, [ ] ]
[ [ 12, 238 ], 339, [ ] ]
[ [ 12, 239 ], 757, [ ] ]
[ [ 12, 240 ], 291, [ ] ]
[ [ 12, 241 ], 291, [ ] ]
[ [ 12, 242 ], 129, [ 2 ] ]
[ [ 12, 243 ], 291, [ ] ]
[ [ 12, 244 ], 89, [ ] ]
[ [ 12, 245 ], 89, [ ] ]
[ [ 12, 246 ], 129, [ 2 ] ]
[ [ 12, 247 ], 291, [ ] ]
[ [ 12, 248 ], 291, [ ] ]
[ [ 12, 249 ], 291, [ ] ]
[ [ 12, 250 ], 649, [ ] ]
[ [ 12, 251 ], 757, [ ] ]
[ [ 12, 252 ], 739, [ ] ]
[ [ 12, 253 ], 202, [ ] ]
[ [ 12, 254 ], 757, [ ] ]
[ [ 12, 255 ], 646, [ 2 ] ]
[ [ 12, 256 ], 1141, [ ] ]
[ [ 12, 257 ], 1141, [ ] ]
[ [ 12, 258 ], 727, [ ] ]
[ [ 12, 259 ], 727, [ ] ]
[ [ 12, 260 ], 339, [ ] ]
[ [ 12, 261 ], 129, [ 2 ] ]

```

```

[[ 12, 262 ], 291, [ ] ]
[[ 12, 263 ], 291, [ ] ]
[[ 12, 264 ], 89, [ ] ]
[[ 12, 265 ], 184, [ ] ]
[[ 12, 266 ], 291, [ ] ]
[[ 12, 267 ], 291, [ ] ]
[[ 12, 268 ], 757, [ ] ]
[[ 12, 269 ], 771, [ ] ]
[[ 12, 270 ], 1141, [ ] ]
[[ 12, 271 ], 241, [ 2 ] ]
[[ 12, 272 ], 1771, [ ] ]
[[ 12, 273 ], 202, [ ] ]
[[ 12, 274 ], 291, [ ] ]
[[ 12, 275 ], 739, [ ] ]
[[ 12, 276 ], 757, [ ] ]
[[ 12, 277 ], 2801, [ ] ]
[[ 12, 278 ], 971, [ ] ]
[[ 12, 279 ], 971, [ ] ]
[[ 12, 280 ], 241, [ 2 ] ]
[[ 12, 281 ], 727, [ ] ]
[[ 12, 282 ], 727, [ ] ]
[[ 12, 283 ], 757, [ ] ]
[[ 12, 284 ], 202, [ ] ]
[[ 12, 285 ], 2801, [ ] ]
[[ 12, 286 ], 3441, [ ] ]
[[ 12, 287 ], 3441, [ ] ]
[[ 12, 288 ], 1371, [ ] ]
[[ 12, 289 ], 727, [ ] ]
[[ 12, 290 ], 757, [ ] ]
[[ 12, 291 ], 757, [ ] ]
[[ 12, 292 ], 202, [ ] ]
[[ 12, 293 ], 3441, [ ] ]
[[ 12, 294 ], 757, [ ] ]
[[ 12, 295 ], 8701, [ ] ]
[[ 12, 296 ], 1371, [ ] ]
[[ 12, 297 ], 1371, [ ] ]
[[ 12, 298 ], 1371, [ ] ]
[[ 12, 299 ], 1371, [ ] ]

```

6. DRAKOKHRUST AND PLATONOV'S METHOD

Let k be a number field, K/k be a finite extension, \mathbb{A}_K^\times be the idele group of K and L/k be the Galois closure of K/k . Let $G = \text{Gal}(L/k) = nTm$ be a transitive subgroup of S_n and $H = \text{Gal}(L/K)$ with $[G : H] = n$.

For $x, y \in G$, we denote $[x, y] = x^{-1}y^{-1}xy$ the commutator of x and y , and $[G, G]$ the commutator group of G . Let V_k be the set of all places of k and G_v be the decomposition group of G at $v \in V_k$.

Definition 6.1 (Drakokhrust and Platonov [PD85a, page 350], [DP87, page 300]). Let k be a number field, $L \supset K \supset k$ be a tower of finite extensions where L is normal over k .

We call the group

$$\text{Obs}(K/k) = (N_{K/k}(\mathbb{A}_K^\times) \cap k^\times)/N_{K/k}(K^\times)$$

the total obstruction to the Hasse norm principle for K/k and

$$\text{Obs}_1(L/K/k) = (N_{K/k}(\mathbb{A}_K^\times) \cap k^\times) / ((N_{L/k}(\mathbb{A}_L^\times) \cap k^\times) N_{K/k}(K^\times))$$

the first obstruction to the Hasse norm principle for K/k corresponding to the tower $L \supset K \supset k$.

Note that (i) $\text{Obs}(K/k) = 1$ if and only if the Hasse norm principle holds for K/k ; and (ii) $\text{Obs}_1(L/K/k) = \text{Obs}(K/k)/(N_{L/k}(\mathbb{A}_L^\times) \cap k^\times)$.

Drakokhrust and Platonov gave a formula for computing the first obstruction $\text{Obs}_1(L/K/k)$:

Theorem 6.2 (Drakokhrust and Platonov [PD85a, page 350], [PD85b, pages 789–790], [DP87, Theorem 1]). Let k be a number field, $L \supset K \supset k$ be a tower of finite extensions where L is normal over k . Let $G = \text{Gal}(L/k)$ and

$H = \text{Gal}(L/K)$. Then

$$\text{Obs}_1(L/K/k) \simeq \text{Ker } \psi_1 / \varphi_1(\text{Ker } \psi_2)$$

where

$$\begin{array}{ccc} H/[H, H] & \xrightarrow{\psi_1} & G/[G, G] \\ \uparrow \varphi_1 & & \uparrow \varphi_2 \\ \bigoplus_{v \in V_k} \left(\bigoplus_{w|v} H_w/[H_w, H_w] \right) & \xrightarrow{\psi_2} & \bigoplus_{v \in V_k} G_v/[G_v, G_v], \end{array}$$

ψ_1 , φ_1 and φ_2 are defined by the inclusions $H \subset G$, $H_w \subset H$ and $G_v \subset G$ respectively, and

$$\psi_2(h[H_w, H_w]) = x^{-1}hx[G_v, G_v]$$

for $h \in H_w = H \cap x^{-1}hx[G_v, G_v]$ ($x \in G$).

Let ψ_2^v be the restriction of ψ_2 to the subgroup $\bigoplus_{w|v} H_w/[H_w, H_w]$ with respect to $v \in V_k$ and ψ_2^{nr} (resp. ψ_2^r) be the restriction of ψ_2 to the unramified (resp. the ramified) places v of k .

Proposition 6.3 (Drakokhrust and Platonov [DP87]). *Let k , $L \supset K \supset k$, G and H be as in Theorem 6.2.*

- (i) ([DP87, Lemma 1]) *Places $w_i \mid v$ of K are in one-to-one correspondence with the set of double cosets in the decomposition $G = \bigcup_{i=1}^{r_v} Hx_iG_v$ where $H_{w_i} = H \cap x_iG_vx_i^{-1}$;*
- (ii) ([DP87, Lemma 2]) *If $G_{v_1} \leq G_{v_2}$, then $\varphi_1(\text{Ker } \psi_2^{v_1}) \subset \varphi_1(\text{Ker } \psi_2^{v_2})$;*
- (iii) ([DP87, Theorem 2]) *$\varphi_1(\text{Ker } \psi_2^{\text{nr}}) = \Phi^G(H)/[H, H]$ where $\Phi^G(H) = \langle [h, x] \mid h \in H \cap xHx^{-1}, x \in G \rangle$;*
- (iv) ([DP87, Lemma 8]) *If $[K : k] = p^r$ ($r \geq 1$) and $\text{Obs}(K_p/k_p) = 1$ where $k_p = L^{G_p}$, $K_p = L^{H_p}$, G_p and $H_p \leq H \cap G_p$ are p -Sylow subgroups of G and H respectively, then $\text{Obs}(K/k) = 1$.*

Note that the inverse direction of Proposition 6.3 (iv) does not hold in general. For example, if $n = 8$, $G = 8T13 \simeq A_4 \times C_2$ and there exists a place v of k such that $G_v \simeq V_4$, then $\text{Obs}(K/k) = 1$ but $G_2 = 8T3 \simeq (C_2)^3$ and $\text{Obs}(K_2/k_2) \neq 1$ may occur (see [HKY22, Theorem 1.18]).

Theorem 6.4 (Drakokhrust and Platonov [DP87, Theorem 3, Corollary 1]). *Let k , $L \supset K \supset k$, G and H be as in Theorem 6.2. Let $H_i \leq G_i \leq G$ ($1 \leq i \leq m$), $H_i \leq H \cap G_i$, $k_i = L^{G_i}$ and $K_i = L^{H_i}$. If $\text{Obs}(K_i/k_i) = 1$ for all $1 \leq i \leq m$ and*

$$\bigoplus_{i=1}^m \widehat{H}^{-3}(G_i, \mathbb{Z}) \xrightarrow{\text{cores}} \widehat{H}^{-3}(G, \mathbb{Z})$$

is surjective, then $\text{Obs}(K/k) = \text{Obs}_1(L/K/k)$. In particular, if $[K : k] = n$ is square-free, then $\text{Obs}(K/k) = \text{Obs}_1(L/K/k)$.

We note that if L/k is an unramified extension, then $A(T) = 0$ and $H^1(G, [J_{G/H}]^{fl}) \simeq \text{III}(T) \simeq \text{Obs}(K/k)$ where $T = R_{K/k}^{(1)}(\mathbb{G}_m)$ (see Theorem 3.3 and Theorem 3.6). If, in addition, $\text{Obs}(K/k) = \text{Obs}_1(L/K/k)$ (e.g. $[K : k] = 6, 10, 14, 15$; square-free, see Theorem 6.4), then $\text{Obs}(K/k) = \text{Obs}_1(L/K/k) = \text{Ker } \psi_1 / \varphi_1(\text{Ker } \psi_2^{\text{nr}}) \simeq \text{Ker } \psi_1 / (\Phi^G(H)/[H, H])$ (see Proposition 6.3 (iii)).

Theorem 6.5 (Drakokhrust [Dra89, Theorem 1], see also Opolka [Opo80, Satz 3]). *Let k , $L \supset K \supset k$, G and H be as in Theorem 6.2. Assume that $\tilde{L} \supset L \supset k$ is a tower of Galois extensions with $\tilde{G} = \text{Gal}(\tilde{L}/k)$ and $\tilde{H} = \text{Gal}(\tilde{L}/K)$ which correspond to a central extension $1 \rightarrow A \rightarrow \tilde{G} \rightarrow G \rightarrow 1$ with $A \cap [\tilde{G}, \tilde{G}] \simeq M(G) = H^2(G, \mathbb{C}^\times)$; the Schur multiplier of G (this is equivalent to the inflation $M(G) \rightarrow M(\tilde{G})$ being the zero map, see Beyl and Tappe [BT82, Proposition 2.13, page 85]). Then $\text{Obs}(K/k) = \text{Obs}_1(\tilde{L}/K/k)$. In particular, if \tilde{G} is a Schur cover of G , i.e. $A \simeq M(G)$, then $\text{Obs}(K/k) = \text{Obs}_1(\tilde{L}/K/k)$.*

Indeed, Drakokhrust [Dra89, Theorem 1] shows that $\text{Obs}(K/k) \simeq \text{Ker } \tilde{\psi}_1 / \tilde{\varphi}_1(\text{Ker } \tilde{\psi}_2)$ where the maps $\tilde{\psi}_1, \tilde{\psi}_2$ and $\tilde{\varphi}_1$ are defined as in [Dra89, page 31, the paragraph before Proposition 1]. The proof of [Dra89, Proposition 1] shows that this group is the same as $\text{Obs}_1(\tilde{L}/K/k)$ (see also [Dra89, Lemma 2, Lemma 3 and Lemma 4]).

Hoshi, Kanai and Yamasaki [HKY22, Section 6] made the following functions of GAP ([GAP]) which will be used in the proof of Theorem 1.3.

`FirstObstructionN(G, H).ker` returns the list $[l_1, [l_2, l_3]]$ where l_1 is the abelian invariant of the numerator of the first obstruction $\text{Ker } \psi_1 = \langle y_1, \dots, y_t \rangle$ with respect to G, H as in Theorem 6.2, $l_2 = [e_1, \dots, e_m]$ is the abelian

invariant of $H^{ab} = H/[H, H] = \langle x_1, \dots, x_m \rangle$ with $e_i = \text{order}(x_i)$ and $l_3 = [l_{3,1}, \dots, l_{3,t}]$, $l_{3,i} = [r_{i,1}, \dots, r_{i,m}]$ is the list with $y_i = x_1^{r_{i,1}} \cdots x_m^{r_{i,m}}$ for $H \leq G \leq S_n$.

`FirstObstructionN(G).ker` returns the same as `FirstObstructionN(G, H).ker` where $H = \text{Stab}_1(G)$ is the stabilizer of 1 in $G \leq S_n$.

`FirstObstructionDnr(G, H).Dnr` returns the list $[l_1, [l_2, l_3]]$ where l_1 is the abelian invariant of the unramified part of the denominator of the first obstruction $\varphi_1(\text{Ker } \psi_2^{\text{nr}}) = \Phi^G(H)/[H, H] = \langle y_1, \dots, y_t \rangle$ with respect to G , H as in Proposition 6.3 (iii), $l_2 = [e_1, \dots, e_m]$ is the abelian invariant of $H^{ab} = H/[H, H] = \langle x_1, \dots, x_m \rangle$ with $e_i = \text{order}(x_i)$ and $l_3 = [l_{3,1}, \dots, l_{3,t}]$, $l_{3,i} = [r_{i,1}, \dots, r_{i,m}]$ is the list with $y_i = x_1^{r_{i,1}} \cdots x_m^{r_{i,m}}$ for $H \leq G \leq S_n$.

`FirstObstructionDnr(G).Dnr` returns the same as `FirstObstructionDnr(G, H).Dnr` where $H = \text{Stab}_1(G)$ is the stabilizer of 1 in $G \leq S_n$.

`FirstObstructionDr(G, G_v, H).Dr` returns the list $[l_1, [l_2, l_3]]$ where l_1 is the abelian invariant of the ramified part of the denominator of the first obstruction $\varphi_1(\text{Ker } \psi_2^r) = \langle y_1, \dots, y_t \rangle$ with respect to G , G_v , H as in Theorem 6.2, $l_2 = [e_1, \dots, e_m]$ is the abelian invariant of $H^{ab} = H/[H, H] = \langle x_1, \dots, x_m \rangle$ with $e_i = \text{order}(x_i)$ and $l_3 = [l_{3,1}, \dots, l_{3,t}]$, $l_{3,i} = [r_{i,1}, \dots, r_{i,m}]$ is the list with $y_i = x_1^{r_{i,1}} \cdots x_m^{r_{i,m}}$ for $G_v, H \leq G \leq S_n$.

`FirstObstructionDr(G, G_v).Dr` returns the same as `FirstObstructionDr(G, G_v, H).Dr` where $H = \text{Stab}_1(G)$ is the stabilizer of 1 in $G \leq S_n$.

`SchurCoverG(G).SchurCover` (resp. `SchurCoverG(G).epi`) returns one of the Schur covers \tilde{G} of G (resp. the surjective map π) in a central extension $1 \rightarrow A \rightarrow \tilde{G} \xrightarrow{\pi} G \rightarrow 1$ with $A \simeq M(G)$; Schur multiplier of G (see Karpilovsky [Kap87, page 16]). The Schur covers \tilde{G} are stem extensions, i.e. $A \leq Z(\tilde{G}) \cap [\tilde{G}, \tilde{G}]$, of the maximal size. This function is based on the built-in function `EpimorphismSchurCover` in GAP.

`MinimalStemExtensions(G)[j].MinimalStemExtension` (resp. `MinimalStemExtensions(G)[j].epi`) returns the j -th minimal stem extension $\overline{G} = \tilde{G}/A'$, i.e. $\overline{A} \leq Z(\overline{G}) \cap [\overline{G}, \overline{G}]$, of G provided by the Schur cover \tilde{G} of G via `SchurCoverG(G).SchurCover` where A' is the j -th maximal subgroup of $A = M(G)$ (resp. the surjective map $\overline{\pi}$) in the commutative diagram

$$\begin{array}{ccccccc} 1 & \longrightarrow & A = M(G) & \longrightarrow & \tilde{G} & \xrightarrow{\pi} & G \longrightarrow 1 \\ & & \downarrow & & \downarrow & & \parallel \\ 1 & \longrightarrow & \overline{A} = A/A' & \longrightarrow & \overline{G} = \tilde{G}/A' & \xrightarrow{\overline{\pi}} & G \longrightarrow 1 \end{array}$$

(see Robinson [Rob96, Exercises 11.4]). This function is based on the built-in function `EpimorphismSchurCover` in GAP.

`ResolutionNormalSeries(LowerCentralSeries(G), n+1)` (resp. `ResolutionNormalSeries(DerivedSeries(G), n+1)`, `ResolutionFiniteGroup(G, n+1)`) returns a free resolution RG of G when G is nilpotent (resp. solvable, finite). This function is the built-in function of HAP ([HAP]) in GAP ([GAP]).

`ResHnZ(RG, RH, n).HnGZ` (resp. `ResHnZ(RG, RH, n).HnHZ`) returns the abelian invariants of $H^n(G, \mathbb{Z})$ (resp. $H^n(H, \mathbb{Z})$) with respect to Smith normal form, for free resolutions RG and RH of G and H respectively.

`ResHnZ(RG, RH, n).Res` returns the list $L = [l_1, \dots, l_s]$ where $H^n(G, \mathbb{Z}) = \langle x_1, \dots, x_s \rangle \xrightarrow{\text{res}} H^n(H, \mathbb{Z}) = \langle y_1, \dots, y_t \rangle$, $\text{res}(x_i) = \prod_{j=1}^t y_j^{l_{i,j}}$ and $l_i = [l_{i,1}, \dots, l_{i,t}]$ for free resolutions RG and RH of G and H respectively.

`ResHnZ(RG, RH, n).Ker` returns the list $L = [l_1, [l_2, l_3]]$ where l_1 is the abelian invariant of $\text{Ker}\{H^n(G, \mathbb{Z}) \xrightarrow{\text{res}} H^n(H, \mathbb{Z})\} = \langle y_1, \dots, y_t \rangle$, $l_2 = [d_1, \dots, d_s]$ is the abelian invariant of $H^n(G, \mathbb{Z}) = \langle x_1, \dots, x_s \rangle$ with $d_i = \text{ord}(x_i)$ and $l_3 = [l_{3,1}, \dots, l_{3,t}]$, $l_{3,j} = [r_{j,1}, \dots, r_{j,s}]$ is the list with $y_j = x_1^{r_{j,1}} \cdots x_s^{r_{j,s}}$ for free resolutions RG and RH of G and H respectively.

`ResHnZ(RG, RH, n).Coker` returns the list $L = [l_1, [l_2, l_3]]$ where $l_1 = [e_1, \dots, e_t]$ is the abelian invariant of $\text{Coker}\{H^n(G, \mathbb{Z}) \xrightarrow{\text{res}} H^n(H, \mathbb{Z})\} = \langle \overline{y_1}, \dots, \overline{y_t} \rangle$ with $e_j = \text{ord}(\overline{y_j})$, $l_2 = [d_1, \dots, d_s]$ is the abelian invariant of $H^n(H, \mathbb{Z}) = \langle x_1, \dots, x_s \rangle$ with $d_i = \text{ord}(x_i)$ and $l_3 = [l_{3,1}, \dots, l_{3,t}]$, $l_{3,j} = [r_{j,1}, \dots, r_{j,s}]$ is the list with $\overline{y_j} = \overline{x_1}^{r_{j,1}} \cdots \overline{x_s}^{r_{j,s}}$ for free resolutions RG and RH of G and H respectively.

`KerResH3Z(G, H)` returns the list $L = [l_1, [l_2, l_3]]$ where l_1 is the abelian invariant of $\text{Ker}\{H^3(G, \mathbb{Z}) \xrightarrow{\text{res}} \bigoplus_{i=1}^{m'} H^3(G_i, \mathbb{Z})\} = \langle y_1, \dots, y_t \rangle$ where $H_i \leq G_i \leq G$, $H_i \leq H \cap G_i$, $[G_i : H_i] = n$ and the action of G_i on $\mathbb{Z}[G_i/H_i]$ may be regarded as nTm ($n \leq 15, n \neq 12$) which is not in [HKY22, Table 1], $l_2 = [d_1, \dots, d_s]$ is the abelian invariant of $H^3(G, \mathbb{Z}) = \langle x_1, \dots, x_s \rangle$ with $d_{i'} = \text{ord}(x_{i'})$ and $l_3 = [l_{3,1}, \dots, l_{3,t}]$, $l_{3,j} = [r_{j,1}, \dots, r_{j,s}]$ is the list with $y_j = x_1^{r_{j,1}} \cdots x_s^{r_{j,s}}$ for groups G and H (cf. Theorem 6.5).

The functions above are available from

<https://www.math.kyoto-u.ac.jp/~yamasaki/Algorithm/Norm1ToriHNP>.

7. PROOF OF THEOREM 1.3

In order to prove Theorem 1.3, we made the following additional GAP ([GAP]) functions:

`KerResH3Z($G, H : \text{iterator}$)` returns the same as `KerResH3Z(G, H)` (in Section 6) but using the built-in function `IteratorByFunctions` of GAP in order to run fast (by applying the new function `ChooseGiIterator(G, H)` to choose suitable $G_i \leq G$ instead of the old one `ChooseGi(G, H)`) and also using nTm ($n \leq 15$) which is not in [HKY22, Table 1] or Table 1 instead of nTm ($n \leq 15, n \neq 12$) which is not in [HKY22, Table 1] (cf. Theorem 6.5).

`ConjugacyClassesSubgroupsNGHOrbitRep(ConjugacyClassesSubgroups(G), H)` returns the list $L = [l_1, \dots, l_t]$ where t is the number of subgroups of G up to conjugacy, $l_r = [l_{r,1}, \dots, l_{r,u_r}]$ ($1 \leq r \leq t$), $l_{r,s}$ ($1 \leq s \leq u_r$) is a representative of the orbit $\text{Orb}_{N_G(H) \backslash G / N_G(G_{v_{r,s}})}(G_{v_{r,s}})$ of $G_{v_{r,s}} \leq G$ under the conjugate action of G which corresponds to the double coset $N_G(H) \backslash G / N_G(G_{v_{r,s}})$ with $\text{Orb}_{G / N_G(G_{v_r})}(G_{v_r}) = \bigcup_{s=1}^{u_r} \text{Orb}_{N_G(H) \backslash G / N_G(G_{v_{r,s}})}(G_{v_{r,s}})$ corresponding to r -th subgroup $G_{v_r} \leq G$ up to conjugacy.

`MinConjugacyClassesSubgroups(l)` returns the minimal elements of the list $l = \{H_i^G\}$ where $H_i^G = \{x^{-1}H_ix \mid x \in G\}$ for some subgroups $H_i \leq G$ which satisfy the condition that if $H_i^G, H_r^G \in l$ and $H_i \leq H_r$, then $H_j^G \in l$ for any $H_i \leq H_j \leq H_r$.

`IsInvariantUnderAutG(l)` returns `true` if the list $l = \{H_i^G\}$ is closed under the action of all the automorphisms $\text{Aut}(G)$ of G where $H_i^G = \{x^{-1}H_ix \mid x \in G\}$ ($H_i \leq G$). If not, this returns `false`.

The functions above are also available from

<https://www.math.kyoto-u.ac.jp/~yamasaki/Algorithm/Norm1ToriHNP>.

Proof of Theorem 1.3.

Let $G = \text{Gal}(L/k) = 12Tm \leq S_{12}$ be the m -th transitive subgroup of S_{12} and $H = \text{Gal}(L/K) \leq G$ with $[G : H] = 12$. Let V_k be the set of all places of k and G_v be the decomposition group of G at $v \in V_k$.

We may assume that $H = \text{Stab}_1(G)$ is the stabilizer of 1 in G , i.e. $L = k(\theta_1, \dots, \theta_{12})$ and $K = L^H = k(\theta_1)$. Note that (the multi-set) $\{\text{Orb}_{G'}(i) \mid 1 \leq i \leq 12\}$ ($G' \leq G$) is invariant under the conjugacy actions of G , i.e. inner automorphisms of G .

We also include the proof for Galois cases $L = K$, i.e. $H = 1$, (see Tate [Tat67] and Theorem 3.5).

(1) Table 2-1: $G = 12Tm$ ($m = 2, 3, 4, 7, 9, 16, 18, 20, 33, 34, 40, 43, 47, 52, 55, 64, 65, 70, 71, 74, 75, 96, 97, 117, 122, 130, 132, 133, 168, 171, 172, 174, 176, 179, 194, 232, 234, 246, 261, 280$) (40 cases) with $\text{III}(T) \leq \mathbb{Z}/2\mathbb{Z}$ (cf. Tate [Tat67, page 198] for Galois cases $12T2 \simeq C_6 \times C_2$, $12T3 \simeq D_6$ and $12T4 \simeq A_4(12)$).

We split the 40 cases into 3 parts (1-1), (1-2), (1-3) according to the method to prove the assertion:

(1-1) $m = 7, 9, 34, 47, 52, 55, 64, 65, 74, 75, 96, 97, 122, 172, 174, 232, 246$ (17 cases).

Applying `FirstObstructionN(G)` and `FirstObstructionDnr(G)`, we obtain that $\text{Ker } \psi_1/\varphi_1(\text{Ker } \psi_2^{\text{nr}}) \simeq \mathbb{Z}/2\mathbb{Z}$. This implies that $\text{Obs}(K/k) = \text{Obs}_1(L/K/k)$ if L/k is unramified. Use Theorem 6.4. Applying `KerResH3Z($G, H : \text{iterator}$)`, we see $\text{Ker}\{H^3(G, \mathbb{Z}) \xrightarrow{\text{res}} \bigoplus_{i=1}^{m'} H^3(G_i, \mathbb{Z})\} = 0$ and hence $\bigoplus_{i=1}^{m'} \widehat{H}^{-3}(G_i, \mathbb{Z}) \xrightarrow{\text{cores}} \widehat{H}^{-3}(G, \mathbb{Z})$ is surjective. It follows from Theorem 6.4 that $\text{Obs}(K/k) = \text{Obs}_1(L/K/k)$. Apply the function `FirstObstructionDr($G, G_{v_{r,s}}$)` to representatives of the orbit $\text{Orb}_{N_G(H) \backslash G / N_G(G_{v_{r,s}})}(G_{v_{r,s}})$ of $G_{v_{r,s}} \leq G$ under the conjugate action of G which corresponds to the double coset $N_G(H) \backslash G / N_G(G_{v_{r,s}})$ with $\text{Orb}_{G / N_G(G_{v_r})}(G_{v_r}) = \bigcup_{s=1}^{u_r} \text{Orb}_{N_G(H) \backslash G / N_G(G_{v_{r,s}})}(G_{v_{r,s}})$ corresponding to r -th subgroup $G_{v_r} \leq G$ up to conjugacy via the function `ConjugacyClassesSubgroupsNGHOrbitRep(ConjugacyClassesSubgroups(G), H)`. Then we can get the minimal elements of the $G_{v_{r,s}}$'s with $\text{Ker } \psi_1/\varphi_1(\text{Ker } \psi_2) = 0$ via the function `MinConjugacyClassesSubgroups(l)`. Finally, we get a necessary and sufficient condition for $\text{Obs}_1(L/K/k) = 1$ for each case (see Example 7.1).

(1-2) $m = 2, 3, 4, 16, 18, 33, 43, 70, 71, 130, 132, 133, 176, 179, 234$ (15 cases). Applying `FirstObstructionN(G)` and `FirstObstructionDnr(G)`, we have $\text{Obs}_1(L/K/k) = 1$. Hence we just apply Theorem 6.5. We have the Schur multiplier $M(G) \simeq \mathbb{Z}/2\mathbb{Z}$ for $G = 12Tm$ ($m = 2, 3, 4, 16, 18, 33, 43, 70, 71, 130, 132, 133, 176, 179, 234$). We obtain a Schur cover $1 \rightarrow M(G) \simeq \mathbb{Z}/2\mathbb{Z} \rightarrow \tilde{G} \xrightarrow{\pi} G \rightarrow 1$ and $\text{Obs}(K/k) = \text{Obs}_1(\tilde{L}/K/k)$. By Theorem 1.1, we have $\text{Ker } \tilde{\psi}_1/\tilde{\varphi}_1(\text{Ker } \tilde{\psi}_2^{\text{nr}}) \simeq \mathbb{Z}/2\mathbb{Z}$. By applying the functions `FirstObstructionDr(\tilde{G}, \tilde{G}_{v_{r,s}}, \tilde{H})` and `MinConjugacyClassesSubgroups(l)` as in the case (1-1), we can get the minimal elements of the $\tilde{G}_{v_{r,s}}$'s with $\text{Ker } \tilde{\psi}_1/\tilde{\varphi}_1(\text{Ker } \tilde{\psi}_2) = 0$. Then we get a necessary and sufficient condition for $\text{Obs}_1(\tilde{L}/K/k) = 1$ for each case (see Example 7.2).

(1-3) $m = 20, 40, 117, 168, 171, 194, 261, 280$ (8 cases). Applying the functions `FirstObstructionN(G)` and `FirstObstructionDnr(G)`, we have $\text{Obs}_1(L/K/k) = 1$. For the 8 cases $G = 12Tm$ ($m = 20, 40, 117, 168, 171, 194, 261, 280$), we obtain that the Schur multipliers $M(G) \simeq \mathbb{Z}/6\mathbb{Z}, \mathbb{Z}/6\mathbb{Z}, (\mathbb{Z}/2\mathbb{Z})^{\oplus 3}, (\mathbb{Z}/2\mathbb{Z})^{\oplus 3}, \mathbb{Z}/2\mathbb{Z} \oplus (\mathbb{Z}/3\mathbb{Z})^{\oplus 2}, \mathbb{Z}/6\mathbb{Z}, (\mathbb{Z}/2\mathbb{Z})^{\oplus 4}, (\mathbb{Z}/2\mathbb{Z})^{\oplus 2}$ respectively. We can take a minimal stem extension $\overline{G} = \tilde{G}/A'$, i.e. $\overline{A} \leq Z(\overline{G}) \cap [\overline{G}, \overline{G}]$, of G in the commutative diagram

$$\begin{array}{ccccccc} 1 & \longrightarrow & A = M(G) & \longrightarrow & \tilde{G} & \xrightarrow{\pi} & G \longrightarrow 1 \\ & & \downarrow & & \downarrow & & \parallel \\ 1 & \longrightarrow & \overline{A} = A/A' & \longrightarrow & \overline{G} = \tilde{G}/A' & \xrightarrow{\overline{\pi}} & G \longrightarrow 1 \end{array}$$

with $\overline{A} \simeq \mathbb{Z}/2\mathbb{Z}$ or $\mathbb{Z}/3\mathbb{Z}$ via the function `MinimalStemExtensions(G)[j].MinimalStemExtension`. Then we apply Theorem 6.4 instead of Theorem 6.5. Applying `KerResH3Z(G, H:iterator)`, we can get $\text{Ker}\{H^3(\overline{G}_j, \mathbb{Z}) \xrightarrow{\text{res}} \bigoplus_{i=1}^{m'} H^3(G_i, \mathbb{Z})\} = 0$ for exactly one j with $\overline{A} \simeq \mathbb{Z}/2\mathbb{Z}$. Because $\bigoplus_{i=1}^{m'} \widehat{H}^{-3}(G_i, \mathbb{Z}) \xrightarrow{\text{cores}} \widehat{H}^{-3}(\overline{G}_j, \mathbb{Z})$ is surjective, it follows from Theorem 6.4 that $\text{Obs}(K/k) = \text{Obs}_1(\overline{L}_j/K/k)$. We also checked that $\text{Ker } \overline{\psi}_1/\overline{\varphi}_1(\text{Ker } \overline{\psi}_2^{\text{nr}}) \simeq \mathbb{Z}/2\mathbb{Z}$ for \overline{G}_j and $\text{Ker } \overline{\psi}_1/\overline{\varphi}_1(\text{Ker } \overline{\psi}_2^{\text{nr}}) = 0$ for $\overline{G}_{j'}$ ($j' \neq j$). Hence $\text{Obs}(K/k) \neq \text{Obs}_1(\overline{L}_j/K/k)$ when \overline{L}_j/k is unramified. By applying the functions `FirstObstructionDr(\overline{G}_j, \overline{G}_{j,v_{r,s}}, \overline{H}_j)` and `MinConjugacyClassesSubgroups(l)` as in the case (1-1), we may find the minimal elements of the $\overline{G}_{j,v_{r,s}}$'s with $\text{Ker } \overline{\psi}_1/\overline{\varphi}_1(\text{Ker } \overline{\psi}_2) = 0$. Then we get a necessary and sufficient condition for $\text{Obs}_1(\overline{L}_j/K/k) = 1$ for each case (see Example 7.3).

(2) Table 2-2: $G = 12Tm$ ($m = 10, 37, 54, 56, 59, 61, 66, 77, 88, 92, 93, 100, 102, 144, 188, 210, 214, 230, 242, 255, 271$) (21 cases) with $\text{III}(T) \leq \mathbb{Z}/2\mathbb{Z}$.

We split the 21 cases into 2 parts (2-1), (2-2) according to the method to prove the assertion:

(2-1) $m = 54, 56, 59, 61, 66, 88, 92, 93, 100, 102, 144, 188, 230, 255$ (14 cases). This case can be proved by the similar manner as in Case (1-1) (see Example 7.4).

(2-2) $m = 10, 37, 77, 210, 214, 242, 271$ (7 cases). This case can be proved by the similar manner as in Case (1-3). In particular, for the 7 cases $G = 12Tm$ ($m = 10, 37, 77, 210, 214, 242, 271$), we obtain that the Schur multipliers $M(G) \simeq (\mathbb{Z}/2\mathbb{Z})^{\oplus 3}, (\mathbb{Z}/2\mathbb{Z})^{\oplus 3}, (\mathbb{Z}/2\mathbb{Z})^{\oplus 3}, (\mathbb{Z}/2\mathbb{Z})^{\oplus 3}, (\mathbb{Z}/2\mathbb{Z})^{\oplus 2} \oplus \mathbb{Z}/3\mathbb{Z}, (\mathbb{Z}/2\mathbb{Z})^{\oplus 5}, (\mathbb{Z}/2\mathbb{Z})^{\oplus 3}$ respectively (see Example 7.5).

(3) Table 2-3: $G = 12T31$ with $\text{III}(T) \leq \mathbb{Z}/4\mathbb{Z}$. This case can be proved by the similar manner as in Case (1-1) (see Example 7.6).

(4) Table 2-4: $G = 12T57$ with $\text{III}(T) \leq \mathbb{Z}/4\mathbb{Z}$. This case can be proved by the similar manner as in Case (1-1) (see Example 7.7).

(5) Table 2-5: $G = 12T32$ with $\text{III}(T) \leq (\mathbb{Z}/2\mathbb{Z})^{\oplus 2}$. This case can be proved by the similar manner as in Case (1-1) (see Example 7.8).

The last assertion for the cases (1) Table 2-1 and (3) Table 2-3 follows because the statements can be described in terms of the characteristic subgroups of G , i.e. invariants under the automorphisms of G although for the cases (2) Table 2-2, (4) Table 2-4 and (5) Table 2-5, the statements are not stable under the action of all the automorphisms $\text{Aut}(G)$ of G . We can check this via the function `IsInvariantUnderAutG(l)`. \square

Example 7.1 ($G = 12Tm$ ($m = 7, 9, 34, 47, 52, 55, 64, 65, 74, 75, 96, 97, 122, 132, 172, 174, 232, 246$)).

(1-1-1) $G = 12T7 \simeq A_4(6) \times C_2$.

```
gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,7);
A_4(6) [x]2=[1/8.2^6]3
gap> H:=Stabilizer(G,1);
Group([ (2,8)(3,9)(4,10)(5,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
```

```

[ [ ], [ [ 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
12
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf));
[ [ [ true ], 4 ], [ [ false ], 8 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
8
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
4
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "C2", 3 ], [ "C2 x C2", 2 ], [ "C3", 1 ], [ "C6", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "A4", 1 ], [ "C2 x A4", 1 ], [ "C2 x C2", 1 ], [ "C2 x C2 x C2", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
2
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
1
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2, 2, 2 ], 1 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (1,7)(4,10)(5,11)(6,12), (2,8)(3,9)(4,10)(5,11) ])
gap> StructureDescription(DG);
"C2 x C2"
gap> List(List(GcsHNPfalseC2xC2,Representative),x->Intersection(x,DG));
[ Group([ (2,8)(3,9)(4,10)(5,11) ]), Group([ (2,8)(3,9)(4,10)(5,11) ]) ]
gap> List(List(GcsHNPtrueC2xC2,Representative),x->Intersection(x,DG));
[ Group([ (1,7)(4,10)(5,11)(6,12), (2,8)(3,9)(4,10)(5,11) ]) ]

```

(1-1-2) $G = 12T9 \simeq S_4$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,9);
1/2[1/8.2^6]S(3)=S_4(12e)
gap> H:=Stabilizer(G,1);
Group([ (2,8)(3,9)(5,11)(6,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;

```

```
[ [ ], [ [ 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
11
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf));
[ [ [ true ], 4 ], [ [ false ], 7 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
7
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
4
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "C2", 2 ], [ "C2 x C2", 1 ], [ "C3", 1 ], [ "C4", 1 ],
[ "S3", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "A4", 1 ], [ "C2 x C2", 1 ], [ "D8", 1 ], [ "S4", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
1
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
1
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2, 2, 2 ], 1 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (2,8)(3,9)(5,11)(6,12), (1,7)(2,8)(4,10)(5,11), (1,9,5)(2,10,6)
gap> StructureDescription(DG);
"A4"
gap> List(List(GcsHNPfalseC2xC2,Representative),x->Intersection(x,DG));
[ Group([ (1,7)(2,8)(4,10)(5,11) ] ]
gap> List(List(GcsHNPtrueC2xC2,Representative),x->Intersection(x,DG));
[ Group([ (2,8)(3,9)(5,11)(6,12), (1,7)(3,9)(4,10)(6,12) ] )
```

$$(1-1-3) \text{ } G = 12T34 \simeq (S_3)^2 \rtimes C_2.$$

```
gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,34);
F_36:2(12e)
gap> H:=Stabilizer(G,1);
Group([ (2,10)(3,11)(4,8)(5,9), (4,8)(5,9)(6,10)(7,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
```

```

gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
26
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 2 ], [ [ false ], 24 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
24
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
2
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3) : C2", 1 ], [ "(C3 x C3) : C4", 1 ], [ "1", 1 ], [ "C2", 3 ],
[ "C2 x C2", 2 ], [ "C3", 2 ], [ "C3 x C3", 1 ], [ "C3 x S3", 2 ],
[ "C4", 1 ], [ "C6", 2 ], [ "D12", 2 ], [ "S3", 4 ], [ "S3 x S3", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(S3 x S3) : C2", 1 ], [ "D8", 1 ] ]

```

$$(1-1-4) \quad G = 12T47 \simeq (C_3)^2 \rtimes Q_8.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,47);
[(1/3.3^3):2]E(4)_4
gap> H:=Stabilizer(G,1);
Group([ (2,6,10)(3,7,11)(4,8,12), (3,11)(4,8)(5,9)(6,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 3 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
14
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 2 ], [ [ false ], 12 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
12
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
2
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3) : C2", 1 ], [ "(C3 x C3) : C4", 3 ], [ "1", 1 ], [ "C2", 1 ],
[ "C3", 1 ], [ "C3 x C3", 1 ], [ "C4", 3 ], [ "S3", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3) : Q8", 1 ], [ "Q8", 1 ] ]

```

(1-1-5) $G = 12T52 \simeq (A_4 \times V_4) \rtimes C_2$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,52);
1/2c[1/16.D(4)^3]S(3)
gap> GeneratorsOfGroup(G);
[ (3,9)(6,12), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
  (1,5,9)(2,6,10)(3,7,11)(4,8,12), (1,11)(2,10)(3,9)(4,8)(5,7) ]
gap> H:=Stabilizer(G,1);
Group([ (3,9)(6,12), (2,8)(5,11), (2,6)(3,5)(4,10)(8,12)(9,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
62
gap> GcsH:=ConjugacyClassesNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 15 ], [ [ false ], 47 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
47
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
15
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C2", 1 ], [ "(C6 x C2) : C2", 1 ], [ "1", 1 ], [ "A4", 1 ],
  [ "A4 : C4", 1 ], [ "C2", 6 ], [ "C2 x A4", 2 ], [ "C2 x C2", 12 ],
  [ "C2 x C2 x A4", 1 ], [ "C2 x C2 x C2", 5 ], [ "C2 x C2 x C2 x C2", 1 ],
  [ "C3", 1 ], [ "C3 : C4", 1 ], [ "C4", 3 ], [ "C4 x C2", 2 ], [ "C6", 2 ],
  [ "C6 x C2", 1 ], [ "D12", 1 ], [ "D8", 3 ], [ "S3", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C2 x C2 x A4) : C2", 1 ], [ "(C2 x C2 x C2 x C2) : C2", 1 ],
  [ "(C4 x C2) : C2", 2 ], [ "C2 x C2", 1 ], [ "C2 x C2 x C2", 1 ],
  [ "C2 x D8", 3 ], [ "C2 x S4", 1 ], [ "C4 x C2", 1 ], [ "D8", 3 ],
  [ "S4", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 1 ], [ "C4 x C2", 1 ], [ "D8", 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
12
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
1
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2, 2, 2 ], 2 ],
  [ [ 2, 2, 2, 2, 4 ], 3 ], [ [ 2, 2, 4, 4 ], 3 ], [ [ 2, 4, 4 ], 1 ],
  [ [ 2, 4, 4, 4 ], 1 ] ]

```

```

[ [ [ 4, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 2, 2, 2, 2, 2, 2 ], 1 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (1,7)(3,9)(4,10)(6,12), (1,7)(2,8)(3,9)(4,10)(5,11)(6,12), (1,9,5)
(2,10,6)(3,11,7)(4,12,8) ])
gap> DDG:=DerivedSubgroup(DG);
Group([ (1,7)(2,8)(4,10)(5,11), (1,7)(3,9)(4,10)(6,12) ])
gap> Collected(List(List(GcsHNPFalseC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DDG,x))]));
[ [ [ [ 2, 2, 2, 2 ], "C2" ], 1 ], [ [ [ 2, 2, 2, 2, 2, 2 ], "C2" ], 1 ],
[ [ [ 2, 2, 2, 2, 2, 2 ], "C2 x C2" ], 1 ],
[ [ [ 2, 2, 2, 2, 4 ], "1" ], 3 ], [ [ [ 2, 2, 4, 4 ], "1" ], 1 ],
[ [ [ 2, 2, 4, 4 ], "C2" ], 2 ], [ [ [ 2, 4, 4 ], "C2" ], 1 ],
[ [ [ 4, 4, 4 ], "1" ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DDG,x))]));
[ [ [ [ 2, 2, 2, 2, 2, 2 ], "1" ], 1 ] ]
gap> ChG:=CharacteristicSubgroups(G);;
gap> List(ChG,StructureDescription);
[ ("C2 x C2 x A4) : C2", "C2 x C2 x A4", "A4 : C4", "C2 x S4",
"C2 x C2 x C2 x C2", "C2 x A4", "A4", "C2 x C2 x C2", "C2 x C2", "C2",
"C2 x C2", "1" ]
gap> List(ChG,Order);
[ 96, 48, 48, 48, 16, 24, 12, 8, 4, 2, 4, 1 ]
gap> Position(ChG,DG);
6
gap> Position(ChG,DDG);
11
gap> Collected(List(List(GcsHNPFalseC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))));
[ [ [ 4, 2, 2, 4, 2, 2, 1, 2, 2, 2, 1, 1 ], 1 ],
[ [ 4, 2, 2, 4, 2, 2, 2, 1, 1, 2, 1 ], 1 ],
[ [ 4, 4, 2, 2, 4, 2, 1, 2, 1, 1, 1 ], 2 ],
[ [ 4, 4, 2, 2, 4, 2, 1, 2, 2, 1, 1, 1 ], 1 ],
[ [ 4, 4, 2, 2, 4, 2, 1, 2, 2, 2, 1, 1 ], 1 ],
[ [ 4, 4, 2, 2, 4, 2, 1, 2, 4, 2, 1, 1 ], 1 ],
[ [ 4, 4, 2, 2, 4, 2, 2, 2, 1, 1, 2, 1 ], 1 ],
[ [ 4, 4, 2, 2, 4, 2, 2, 2, 2, 1, 2, 1 ], 1 ],
[ [ 4, 4, 2, 2, 4, 2, 4, 1, 1, 2, 1 ], 1 ],
[ [ 4, 4, 4, 4, 4, 2, 4, 1, 1, 2, 1 ], 1 ],
[ [ 4, 4, 4, 4, 4, 4, 2, 4, 2, 2, 1 ], 1 ],
[ [ 4, 4, 4, 4, 4, 4, 4, 1, 1, 4, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))));
[ [ [ 4, 2, 2, 4, 2, 2, 1, 2, 1, 1, 1 ], 1 ] ]
gap> C2xC2xA4:=ChG[2];
C2 x C2 x A4
gap> ZG:=Centre(G);
Group([ (1,7)(2,8)(3,9)(4,10)(5,11)(6,12) ])
gap> Position(ChG,ZG);
10
gap> Collected(List(List(GcsHNPFalseC2xC2,Representative),
> x->List([C2xC2xA4,ZG,DDG],y->StructureDescription(Intersection(y,x)))));
[ [ [ "C2", "1", "C2" ], 1 ],
[ [ "C2", "C2", "1" ], 1 ],
[ [ "C2 x C2", "1", "1" ], 3 ],
[ [ "C2 x C2", "1", "C2" ], 3 ],
[ [ "C2 x C2", "1", "C2 x C2" ], 1 ],
[ [ "C2 x C2", "C2", "1" ], 2 ],

```

```

[ [ "C2 x C2", "C2", "C2" ], 1 ] ]

gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List([C2xC2xA4,ZG,DDG],y->StructureDescription(Intersection(y,x))));;
[ [ [ "C2", "1", "1" ], 1 ] ]

gap> GcsHNPfalseC4xC2:=Filtered(GcsHNPfalse, # G(8,2)=C4xC2
> x->IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPfalseC4xC2);
2
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPtrueC4xC2);
1
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));;
[ [ [ 8, 4, 8, 4, 4, 2, 4, 2, 2, 2, 1 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));;
[ [ [ 8, 4, 4, 8, 4, 4, 2, 4, 2, 2, 2, 1 ], 1 ] ]
gap> A4x1C4:=ChG[3];
A4 : C4
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->StructureDescription(Intersection(A4x1C4,x))));;
[ [ "C4 x C2", 2 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->StructureDescription(Intersection(A4x1C4,x))));;
[ [ "C2 x C2", 1 ] ]
gap> C2xS4:=ChG[4];
C2 x S4
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->StructureDescription(Intersection(C2xS4,x))));;
[ [ "C2 x C2", 2 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->StructureDescription(Intersection(C2xS4,x))));;
[ [ "C4 x C2", 1 ] ]

gap> GcsHNPfalseD4:=Filtered(GcsHNPfalse, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPfalseD4);
3
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
3
gap> GcsHNPtrueMinD4:=Filtered(GcsHNPtrueMin,
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueMinD4);
1
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 4, 4 ], 1 ], [ [ 4, 8 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ], [ [ 4, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueMinD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;

```

```

[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));;
[ [ [ 8, 4, 4, 4, 2, 1, 2, 2, 2, 1, 1 ], 1 ],
  [ [ 8, 4, 4, 4, 2, 1, 2, 4, 2, 1, 1 ], 1 ],
  [ [ 8, 4, 4, 8, 4, 4, 2, 4, 1, 1, 2, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueMinD4,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));;
[ [ [ 8, 4, 4, 8, 4, 4, 4, 1, 1, 4, 1 ], 1 ] ]
gap> A4:=ChG[7];
A4
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->StructureDescription(Intersection(A4,x))));;
[ [ "1", 2 ], [ "C2", 1 ] ]
gap> Collected(List(List(GcsHNPtrueMinD4,Representative),
> x->StructureDescription(Intersection(A4,x))));;
[ [ "C2 x C2", 1 ] ]
gap> DDG:=DerivedSubgroup(DG);
Group([ (1,7)(2,8)(4,10)(5,11), (1,7)(3,9)(4,10)(6,12) ])
gap> Position(ChG,DDG);
11
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->StructureDescription(Intersection(DDG,x))));;
[ [ "1", 2 ], [ "C2", 1 ] ]
gap> Collected(List(List(GcsHNPtrueMinD4,Representative),
> x->StructureDescription(Intersection(DDG,x))));;
[ [ "C2 x C2", 1 ] ]

(1-1-6)  $G = 12T55 \simeq ((C_4)^2 \rtimes C_3) \times C_2$ .

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,55);
[1/2.4^3]3
gap> H:=Stabilizer(G,1);
Group([ (3,9)(6,12), (2,8)(5,11), (2,11,8,5)(3,6,9,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ 4 ], [ [ 2, 4 ], [ [ 1, 1 ], [ 0, 2 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 2, 4 ], [ [ 0, 2 ] ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 4 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[4];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
28
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtrf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtrf,Set));
[ [ [ true ], 5 ], [ [ false ], 23 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtrf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
23
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtrf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
5
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "1", 1 ], [ "A4", 1 ], [ "C2", 3 ], [ "C2 x A4", 1 ], [ "C2 x C2", 3 ],
  [ "C2 x C2 x C2", 1 ], [ "C3", 1 ], [ "C4", 4 ], [ "C4 x C2", 6 ],
  [ "C4 x C2 x C2", 1 ], [ "C6", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;

```

```
[ [ "(C4 x C4) : C3", 1 ], [ "C2 x ((C4 x C4) : C3)", 1 ], [ "C4 x C4", 2 ],
[ "C4 x C4 x C2", 1 ] ]
```

$$(1-1-7) G = 12T64 \simeq ((C_4)^2 \rtimes C_3) \rtimes C_2.$$

```
gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,64);
[1/2[1/2.2^2]^3]S_4(6d)_8a
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3)(6,7)(8,9), (1,5,9)(2,6,10)(3,7,11)(4,8,12),
(1,2)(3,12)(4,5)(6,9)(7,8) ]
gap> H:=Stabilizer(G,1);
Group([ (2,3)(4,5)(8,9)(10,11), (2,8,3,9)(4,10,5,11), (2,11)(3,10)(4,8)(5,9)
(6,7) ])
gap> FirstObstructionN(G,H).ker;
[ [ 4 ], [ [ 2, 4 ], [ [ 1, 1 ], [ 0, 2 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 2, 4 ], [ [ 0, 2 ] ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[4];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
24
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 7 ], [ [ false ], 17 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
17
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
7
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "A4", 1 ], [ "C2", 2 ], [ "C2 x C2", 2 ], [ "C3", 1 ],
[ "C4", 3 ], [ "C4 x C2", 2 ], [ "C8", 1 ], [ "C8 : C2", 1 ], [ "D8", 1 ],
[ "Q8", 1 ], [ "S3", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C4 x C4) : C3) : C2", 1 ], [ "(C4 x C2) : C2", 1 ],
[ "(C4 x C4) : C2", 1 ], [ "(C4 x C4) : C3", 1 ], [ "C4 x C4", 1 ],
[ "D8", 1 ], [ "S4", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C4 x C4", 1 ], [ "D8", 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPfalseD4:=Filtered(GcsHNPfalse, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPfalseD4);
1
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
1
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 8 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
```

```

> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> ChG:=CharacteristicSubgroups(G);
[ [ 1/2[1/2.2^2]^3]S_4(6d)_8a, Group([ (1,5,9)(2,6,10)(3,7,11)(4,8,12), (2,8,3,
9)(4,10,5,11), (1,6,12,7)(2,8,3,9)(4,5)(10,11), (2,3)(4,5)(8,9)
(10,11), (1,12)(2,3)(6,7)(8,9) ]), Group([ (2,8,3,9)(4,10,5,11), (1,6,12,7)
(2,8,3,9)(4,5)(10,11), (2,3)(4,5)(8,9)(10,11), (1,12)(2,3)(6,7)(8,9) ]),
Group([ (2,3)(4,5)(8,9)(10,11), (1,12)(2,3)(6,7)(8,9) ]), Group(()) ]
gap> List(ChG,StructureDescription);
[ "((C4 x C4) : C3) : C2", "(C4 x C4) : C3", "C4 x C4", "C2 x C2", "1" ]
gap> List(ChG,Order);
[ 96, 48, 16, 4, 1 ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))) ;
[ [ [ 8, 4, 4, 2, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))) ;
[ [ [ 8, 4, 4, 4, 1 ], 1 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (2,3)(4,5)(8,9)(10,11), (1,2,10)(3,11,12)(4,6,8)(5,7,9), (1,4,9)
(2,6,11)(3,7,10)(5,8,12) ])
gap> Position(ChG,DG);
2
gap> DDG:=DerivedSubgroup(DG);
Group([ (1,12)(2,3)(6,7)(8,9), (1,12)(4,5)(6,7)(10,11), (2,9,3,8)
(4,11,5,10), (1,6,12,7)(2,3)(4,11,5,10)(8,9) ])
gap> Position(ChG,DDG);
3
gap> FrDDG:=FrattiniSubgroup(DDG);
Group([ (1,12)(4,5)(6,7)(10,11), (2,3)(4,5)(8,9)(10,11) ])
gap> Position(ChG,FrDDG);
4
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->StructureDescription(Intersection(FrDDG,x))))) ;
[ [ "C2", 1 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->StructureDescription(Intersection(FrDDG,x))))) ;
[ [ "C2 x C2", 1 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,2]); # G(16,2)=C4xC4
1

```

$$(1-1-8) \quad G = 12T65 \simeq ((C_4)^2 \rtimes C_3) \rtimes C_2.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,65);
[1/2[1/2.2^2]^3]S_4(6c)_4
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3)(6,7)(8,9), (1,5,9)(2,6,10)(3,7,11)(4,8,12),
(1,3)(2,12)(4,10)(5,11)(6,8)(7,9), (1,5)(2,9)(3,8)(4,12)(6,11)(7,10) ]
gap> H:=Stabilizer(G,1);
Group([ (2,3)(4,5)(8,9)(10,11), (2,10,8,5,3,11,9,4)(6,7) ])
gap> FirstObstructionN(G,H).ker;
[ [ 4 ], [ [ 8 ], [ [ 2 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 8 ], [ [ 4 ] ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[4];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
24

```

```

gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 5 ], [ [ false ], 19 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
19
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
5
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C2", 1 ], [ "1", 1 ], [ "A4", 1 ], [ "C2", 2 ],
  [ "C2 x C2", 2 ], [ "C3", 1 ], [ "C4", 3 ], [ "C4 x C2", 2 ], [ "C8", 1 ],
  [ "D8", 2 ], [ "Q8", 1 ], [ "S3", 1 ], [ "S4", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C4 x C4) : C3) : C2", 1 ], [ "(C4 x C4) : C2", 1 ],
  [ "(C4 x C4) : C3", 1 ], [ "C4 x C4", 1 ], [ "C8 : C2", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C4 x C4", 1 ], [ "C8 : C2", 1 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));
[ [ [ 16, 2 ], 1 ], [ [ 16, 6 ], 1 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,2]); # G(16,2)=C4xC4
1

```

$$(1-1-9) \quad G = 12T74 \cong S_5(12).$$

```

gap> Read("HN.P.gap");
gap> G:=TransitiveGroup(12,74);
S_5(12)
gap> H:=Stabilizer(G,1);
Group([ (2,4,6,8,10)(3,5,7,9,11), (3,7)(4,10)(6,8)(9,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
19
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 6 ], [ [ false ], 13 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
13
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
6
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Repr
[ [ "1", 1 ], [ "C2", 2 ], [ "C2 x C2", 1 ], [ "C3", 1 ], [

```

```

[ "C5", 1 ], [ "C5 : C4", 1 ], [ "C6", 1 ], [ "D10", 1 ], [ "D12", 1 ],
[ "S3", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "A4", 1 ], [ "A5", 1 ], [ "C2 x C2", 1 ], [ "D8", 1 ], [ "S4", 1 ],
[ "S5", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));
[ [ [ 4, 2 ], 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPtrueC2xC2);
1
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPtrueC2xC2);
1
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2, 2, 2 ], 1 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (1,11,7)(2,6,10)(3,5,9)(4,12,8), (1,11,3)(2,6,4)(5,9,7)
(8,10,12), (1,3,5)(2,12,10)(4,8,6)(7,11,9) ])
gap> StructureDescription(DG);
"A5"
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(DG,x))));
[ [ "C2", 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(DG,x))));
[ [ "C2 x C2", 1 ] ]

```

$$(1-1-10) \quad G = 12T75 \simeq A_5(6) \times C_2.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,75);
L(6)[x]2
gap> GeneratorsOfGroup(G);
[ (1,3,5,7,9)(2,4,6,8,12), (1,11)(2,8)(3,9)(10,12),
(1,12)(2,3)(4,5)(6,7)(8,9)(10,11) ]
gap> H:=Stabilizer(G,1);
Group([ (2,6,4,8,10)(3,7,5,9,11), (4,8)(5,9)(6,10)(7,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
22
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtrf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtrf,Set));
[ [ [ true ], 6 ], [ [ false ], 16 ] ]
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],

```

```

> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
16
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
6
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "C10", 1 ], [ "C2", 3 ], [ "C2 x C2", 2 ], [ "C3", 1 ],
  [ "C5", 1 ], [ "C6", 1 ], [ "D10", 2 ], [ "D12", 1 ], [ "D20", 1 ],
  [ "S3", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "A4", 1 ], [ "A5", 1 ], [ "C2 x A4", 1 ], [ "C2 x A5", 1 ],
  [ "C2 x C2", 1 ], [ "C2 x C2 x C2", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPfalseC2xC2);
2
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPtrueC2xC2);
1
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ 2, 2, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ 2, 2, 2, 2, 2, 2 ], 1 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (1,3,9,11,5)(2,8,10,4,12), (1,7,9,5,11)(4,10,12,6,8) ])
gap> StructureDescription(DG);
"A5"
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->StructureDescription(Intersection(DG,x))));
[ [ "C2", 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(DG,x))));
[ [ "C2 x C2", 1 ] ]

(1-1-11)  $G = 12T96 \simeq ((C_4)^2 \rtimes C_3) \rtimes C_2 \times C_2$ .
```

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,96);
[(1/2.2^2)^3]S_4(6d)_8
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3), (1,5,9)(2,6,10)(3,7,11)(4,8,12), (2,3)(4,10)(5,11)(6,8)(7,9) ]
gap> H:=Stabilizer(G,1);
Group([ (2,3)(4,10)(5,11)(6,8)(7,9), (4,6,5,7)(8,11,9,10), (8,9)(10,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2, 2 ], [ [ 0, 1, 0 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
```

```

gap> Length(Gcs);
84
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 29 ], [ [ false ], 55 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
55
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
29
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "(C4 x C2) : C2", 3 ], [ "1", 1 ], [ "A4", 1 ], [ "C2", 5 ],
  [ "C2 x (C8 : C2)", 1 ], [ "C2 x A4", 1 ], [ "C2 x C2", 6 ],
  [ "C2 x C2 x C2", 1 ], [ "C3", 1 ], [ "C4", 6 ], [ "C4 x C2", 10 ],
  [ "C4 x C2 x C2", 1 ], [ "C6", 1 ], [ "C8", 2 ], [ "C8 : C2", 3 ],
  [ "C8 x C2", 1 ], [ "D12", 1 ], [ "D8", 5 ], [ "Q8", 3 ], [ "S3", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "((C4 x C4) : C3) : C2", 2 ], [ "(C4 x C2) : C2", 3 ],
  [ "(C4 x C4) : C2", 4 ], [ "(C4 x C4) : C3", 1 ],
  [ "C2 x (((C4 x C4) : C3) : C2)", 1 ], [ "C2 x ((C4 x C2) : C2)", 1 ],
  [ "C2 x ((C4 x C4) : C2)", 1 ], [ "C2 x ((C4 x C4) : C3)", 1 ],
  [ "C2 x C2", 1 ], [ "C2 x C2 x C2", 1 ], [ "C2 x D8", 2 ], [ "C2 x Q8", 1 ],
  [ "C2 x S4", 1 ], [ "C4 x C2", 1 ], [ "C4 x C2 x C2", 1 ], [ "C4 x C4", 2 ],
  [ "C4 x C4 x C2", 1 ], [ "D8", 2 ], [ "S4", 2 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));;
[ [ "C2 x C2", 1 ], [ "C4 x C2", 1 ], [ "C4 x C4", 2 ], [ "D8", 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
6
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
1
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2, 2, 2 ], 2 ], [ [ 2, 2, 4, 4 ], 1 ],
  [ [ 2, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2, 2, 2 ], 1 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (1,12)(2,3)(4,5)(6,7), (1,11,5)(2,9,6)(3,8,7)(4,12,10), (1,4,8)
(2,7,11)(3,6,10)(5,9,12) ])
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DG,x))]));
[ [ [ [ 2, 2, 2, 2 ], "C2" ], 1 ], [ [ [ 2, 2, 2, 2, 2, 2 ], "C2" ], 1 ],
  [ [ [ 2, 2, 2, 2, 2, 2 ], "C2 x C2" ], 1 ], [ [ [ 2, 2, 4, 4 ], "1" ], 1 ],
  [ [ [ 2, 4, 4 ], "C2" ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DG,x))]));
[ [ [ [ 2, 2, 2, 2 ], "1" ], 1 ] ]

```

```

gap> ChG:=CharacteristicSubgroups(G);;
gap> List(ChG,StructureDescription);
[ "C2 x (((C4 x C4) : C3) : C2)", "C2 x ((C4 x C4) : C3)", "C4 x C4 x C2",
  "(C4 x C4) : C3", "C2 x C2 x C2", "C4 x C4", "C2", "C2 x C2", "1" ]
gap> List(ChG,Order);
[ 192, 96, 32, 48, 8, 16, 2, 4, 1 ]
gap> Position(ChG,DG);
4
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))));
[ [ [ 4, 2, 2, 1, 2, 1, 2, 1, 1 ], 1 ],
  [ [ 4, 2, 2, 2, 2, 2, 1, 2, 1 ], 2 ],
  [ [ 4, 4, 4, 2, 4, 2, 1, 2, 1 ], 1 ],
  [ [ 4, 4, 4, 2, 4, 2, 2, 2, 1 ], 1 ],
  [ [ 4, 4, 4, 4, 4, 1, 4, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))));
[ [ [ 4, 2, 2, 1, 2, 1, 1, 1, 1 ], 1 ] ]
gap> ZG:=Centre(G);
Group([ (1,12)(2,3)(4,5)(6,7)(8,9)(10,11) ])
gap> Position(ChG,ZG);
7
gap> Syl2DG:=SylowSubgroup(DG,2);
Group([ (1,2,12,3)(4,5)(6,7)(8,11,9,10), (4,6,5,7)(8,11,9,10), (1,12)(2,3)
(8,9)(10,11), (1,12)(2,3)(4,5)(6,7) ])
gap> Position(ChG,Syl2DG);
6
gap> FrSyl2DG:=FrattiniSubgroup(Syl2DG);
Group([ (4,5)(6,7)(8,9)(10,11), (1,12)(2,3)(8,9)(10,11) ])
gap> Position(ChG,FrSyl2DG);
8
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->List([DG,ZG],y->StructureDescription(Intersection(y,x))))));
[ [ [ "1", "C2" ], 1 ], [ [ "C2", "1" ], 3 ], [ [ "C2", "C2" ], 1 ],
  [ [ "C2 x C2", "1" ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List([DG,ZG],y->StructureDescription(Intersection(y,x))))));
[ [ [ "1", "1" ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->List([Syl2DG,ZG],y->StructureDescription(Intersection(y,x))))));
[ [ [ "1", "C2" ], 1 ], [ [ "C2", "1" ], 3 ], [ [ "C2", "C2" ], 1 ],
  [ [ "C2 x C2", "1" ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List([Syl2DG,ZG],y->StructureDescription(Intersection(y,x))))));
[ [ [ "1", "1" ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->List([ZG,FrSyl2DG],y->StructureDescription(Intersection(y,x))))));
[ [ [ "1", "C2" ], 3 ], [ [ "1", "C2 x C2" ], 1 ], [ [ "C2", "1" ], 1 ],
  [ [ "C2", "C2" ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List([ZG,FrSyl2DG],y->StructureDescription(Intersection(y,x)))));
[ [ [ "1", "1" ], 1 ] ]

gap> GcsHNPfalseC4xC2:=Filtered(GcsHNPfalse, # G(8,2)=C4xC2
> x->IdSmallGroup(Representative(x))=[8,2]);
gap> Length(GcsHNPfalseC4xC2);
10
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,2]);
gap> Length(GcsHNPtrueC4xC2);
1
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),

```

```

> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 4, 4 ], 5 ], [ [ 2, 2, 8 ], 2 ], [ [ 2, 8 ], 2 ], [ [ 4, 4 ], 1 ]
]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DG,x))]));
[ [ [ [ 2, 2, 4, 4 ], "C2 x C2" ], 1 ], [ [ [ 2, 2, 4, 4 ], "C4" ], 3 ],
[ [ [ 2, 2, 4, 4 ], "C4 x C2" ], 1 ], [ [ [ 2, 2, 8 ], "C2" ], 2 ],
[ [ [ 2, 8 ], "C4" ], 2 ], [ [ [ 4, 4 ], "C4" ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DG,x))]));
[ [ [ [ 2, 2, 4, 4 ], "C2" ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));)
[ [ [ 8, 4, 4, 2, 2, 2, 1, 2, 1 ], 2 ], [ [ 8, 4, 4, 4, 2, 4, 1, 2, 1 ], 2 ],
[ [ 8, 8, 4, 4, 1, 2, 1 ], 2 ], [ [ 8, 8, 8, 4, 4, 4, 1, 4, 1 ], 1 ],
[ [ 8, 8, 8, 4, 4, 2, 2, 1 ], 2 ], [ [ 8, 8, 8, 8, 4, 8, 1, 4, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));)
[ [ [ 8, 4, 4, 2, 4, 2, 2, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x))));)
[ [ [ "C4 x C2", "C4", "C4", "C2", "C2", "1", "C2", "1" ], 2 ],
[ [ "C4 x C2", "C4", "C4", "C2", "C4", "1", "C2", "1" ], 2 ],
[ [ "C4 x C2", "C4 x C2", "C4 x C2", "C2 x C2", "C2 x C2", "C2 x C2", "1",
"C2 x C2", "1" ], 1 ],
[ [ "C4 x C2", "C4 x C2", "C4 x C2", "C4", "C2 x C2", "C4", "1", "C2", "1" ]
, 2 ],
[ [ "C4 x C2", "C4 x C2", "C4 x C2", "C4", "C2 x C2", "C4", "C2", "C2", "1"
], 2 ],
[ [ "C4 x C2", "C4 x C2", "C4 x C2", "C4 x C2", "C2 x C2", "C4 x C2", "1",
"C2 x C2", "1" ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x))));)
[ [ [ "C4 x C2", "C2 x C2", "C2 x C2", "C2", "C2 x C2", "C2", "C2", "C2",
"1" ], 1 ] ]
gap> S12:=SymmetricGroup(12);
Sym( [ 1 .. 12 ] )
gap> T55:=ChG[2];
C2 x ((C4 x C4) : C3)
gap> IsConjugate(S12,T55,TransitiveGroup(12,55));
true
gap> Syl2T55:=SylowSubgroup(T55,2);
Group([ (1,12)(2,3), (1,2,12,3)(4,7,5,6)(8,9)(10,11), (4,6,5,7)
(8,11,9,10), (4,5)(6,7)(8,9)(10,11), (1,12)(2,3)(4,5)(6,7) ])
gap> Position(ChG,Syl2T55);
3
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->StructureDescription(Intersection(T55,x))));)
[ [ "C4", 4 ], [ "C4 x C2", 6 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->StructureDescription(Intersection(T55,x))));)
[ [ "C2 x C2", 1 ] ]
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->StructureDescription(Intersection(Syl2T55,x))));)
[ [ "C4", 4 ], [ "C4 x C2", 6 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->StructureDescription(Intersection(Syl2T55,x))));)

```

```
[ [ "C2 x C2", 1 ] ]

gap> GcsHNPfalseD4:=Filtered(GcsHNPfalse, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3];;
gap> Length(GcsHNPfalseD4);
5
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
2
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 8 ], 2 ], [ [ 2, 4, 4 ], 2 ], [ [ 2, 8 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))));;
[ [ [ 8, 4, 4, 2, 2, 2, 1, 2, 1 ], 1 ], [ [ 8, 4, 4, 2, 4, 2, 1, 2, 1 ], 2 ],
[ [ 8, 4, 4, 4, 2, 4, 1, 2, 1 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))));;
[ [ [ 8, 4, 4, 4, 4, 1, 4, 1 ], 2 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x)))));;
[ [ [ "D8", "C2 x C2", "C2 x C2", "C2", "C2 x C2", "C2", "1", "C2", "1" ], 2 ]
, [ [ "D8", "C4", "C4", "C2", "C2", "C2", "1", "C2", "1" ], 1 ],
[ [ "D8", "C4", "C4", "C2", "C4", "1", "C2", "1" ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x)))));;
[ [ [ "D8", "C2 x C2", "1",
"C2 x C2", "1" ], 2 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->StructureDescription(Intersection(DG,x))));;
[ [ "C2", 3 ], [ "C4", 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->StructureDescription(Intersection(DG,x))));;
[ [ "C2 x C2", 2 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->StructureDescription(Intersection(Syl2DG,x))));;
[ [ "C2", 3 ], [ "C4", 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->StructureDescription(Intersection(Syl2DG,x))));;
[ [ "C2 x C2", 2 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->StructureDescription(Intersection(FrSyl2DG,x))));;
[ [ "C2", 5 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->StructureDescription(Intersection(FrSyl2DG,x))));;
[ [ "C2 x C2", 2 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,2]); # G(16,2)=C4xC4
2
gap> Number(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))=[16,2]);
2

(1-1-12)  $G = 12T97 \simeq ((C_4)^2 \rtimes C_3) \rtimes C_2) \times C_2.$ 

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,97);
[(1/2.2^2)^3]S_4(6c)_4
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3), (1,5,9)(2,6,10)(3,7,11)(4,8,12),
```

```
(1,3)(2,12)(4,8)(5,9)(6,11)(7,10) ]
gap> H:=Stabilizer(G,1);
Group([ (8,9)(10,11), (2,3)(4,8,7,10,5,9,6,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 4 ], [ [ 0, 2 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2, 4 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
84
gap> GcsH:=ConjugacyClassesSubgroupsNGHOOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 17 ], [ [ false ], 67 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
67
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
17
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "(C4 x C2) : C2", 6 ], [ "1", 1 ], [ "A4", 1 ], [ "C2", 5 ],
  [ "C2 x ((C4 x C2) : C2)", 1 ], [ "C2 x A4", 1 ], [ "C2 x C2", 7 ],
  [ "C2 x C2 x C2", 2 ], [ "C2 x D8", 2 ], [ "C2 x Q8", 1 ], [ "C2 x S4", 1 ],
  [ "C3", 1 ], [ "C4", 6 ], [ "C4 x C2", 11 ], [ "C4 x C2 x C2", 2 ],
  [ "C6", 1 ], [ "C8", 2 ], [ "C8 : C2", 1 ], [ "D12", 1 ], [ "D8", 7 ],
  [ "Q8", 3 ], [ "S3", 2 ], [ "S4", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "((C4 x C4) : C3) : C2", 2 ], [ "(C4 x C4) : C2", 4 ],
  [ "(C4 x C4) : C3", 1 ], [ "C2 x (((C4 x C4) : C3) : C2)", 1 ],
  [ "C2 x ((C4 x C4) : C2)", 1 ], [ "C2 x ((C4 x C4) : C3)", 1 ],
  [ "C2 x (C8 : C2)", 1 ], [ "C4 x C4", 2 ], [ "C4 x C4 x C2", 1 ],
  [ "C8 : C2", 2 ], [ "C8 x C2", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));;
[ [ "C4 x C4", 2 ], [ "C8 : C2", 2 ], [ "C8 x C2", 1 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));;
[ [ [ 16, 2 ], 2 ], [ [ 16, 5 ], 1 ], [ [ 16, 6 ], 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,2]); # G(16,2)=C4xC4
2
gap> Number(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))=[16,2]);
2

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,5]); # G(16,5)=C8xC2
1

gap> GcsHNPfalseM16:=Filtered(GcsHNPfalse, # G(16,6)=M16
> x->IdSmallGroup(Representative(x))=[16,6]);;
gap> Length(GcsHNPfalseM16);
1
gap> GcsHNPtrueM16:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[16,6]);;
gap> Length(GcsHNPtrueM16);
```

```

2
gap> Collected(List(List(GcsHNPfalseM16,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 2, 8 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueM16,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 2, 2, 8 ], 2 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (1,12)(2,3)(4,5)(6,7), (1,10,5)(2,8,6)(3,9,7)(4,12,11), (1,4,8)
(2,7,11)(3,6,10)(5,9,12) ])
gap> StructureDescription(DG);
"(C4 x C4) : C3"
gap> Collected(List(List(GcsHNPfalseM16,Representative),
> x->StructureDescription(Intersection(DG,x)))); 
[ [ "C4", 1 ] ]
gap> Collected(List(List(GcsHNPtrueM16,Representative),
> x->StructureDescription(Intersection(DG,x)))); 
[ [ "C4 x C2", 2 ] ]

(1-1-13)  $G = 12T122 \simeq ((C_3)^2 \rtimes Q_8) \rtimes C_3$ .
gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,122);
[(1/3.3^3):2]A(4)_4
gap> H:=Stabilizer(G,1);
Group([ (2,6,10)(3,7,11)(4,8,12), (2,3,4)(6,7,8)(10,11,12), (3,11)(4,8)(5,9)
(6,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 6 ], [ [ 3 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 6 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 3 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
20
gap> GcsH:=ConjugacyClassesNGHOorbitRep(Gcs,H);;
gap> GcsHHNPTf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPTf,Set));
[ [ [ true ], 4 ], [ [ false ], 16 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPTf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
16
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPTf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
4
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x)))); 
[ [ "(C3 x C3) : C2", 1 ], [ "(C3 x C3) : C3", 1 ], [ "(C3 x C3) : C4", 1 ],
[ "(C3 x C3) : C6", 1 ], [ "1", 1 ], [ "C2", 1 ], [ "C3", 3 ],
[ "C3 x C3", 3 ], [ "C3 x S3", 1 ], [ "C4", 1 ], [ "C6", 1 ], [ "S3", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x)))); 
[ [ "((C3 x C3) : Q8) : C3", 1 ], [ "(C3 x C3) : Q8", 1 ], [ "Q8", 1 ],
[ "SL(2,3)", 1 ] ]

```

$$(1-1-14) G = 12T172 \simeq (C_3)^4 \rtimes D_4.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,172);
1/2[3^4:2^2]E(4)
gap> H:=Stabilizer(G,1);

```

```

Group([ (4,8,12), (2,10)(5,9)(7,11)(8,12), (3,7,11), (2,6,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 6 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
277
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 6 ], [ [ false ], 271 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
271
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
6
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "((C3 x C3) : C2) x ((C3 x C3) : C2)", 2 ],
  [ "((C3 x C3) : C2) x S3", 8 ], [ "(C3 x C3 x C3 x C3) : C2", 1 ],
  [ "(C3 x C3 x C3 x C3) : C4", 1 ], [ "(C3 x C3 x C3) : C2", 14 ],
  [ "(C3 x C3) : C2", 46 ], [ "(C3 x C3) : C4", 7 ], [ "1", 1 ], [ "C2", 3 ],
  [ "C2 x ((C3 x C3) : C2)", 2 ], [ "C2 x C2", 2 ], [ "C3", 14 ],
  [ "C3 x ((C3 x C3) : C2)", 8 ], [ "C3 x C3", 44 ],
  [ "C3 x C3 x ((C3 x C3) : C2)", 2 ], [ "C3 x C3 x C3", 14 ],
  [ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x S3", 8 ], [ "C3 x S3", 32 ],
  [ "C4", 1 ], [ "C6", 8 ], [ "C6 x C3", 2 ], [ "D12", 8 ], [ "S3", 22 ],
  [ "S3 x S3", 20 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3 x C3 x C3) : D8", 1 ], [ "(S3 x S3) : C2", 4 ], [ "D8", 1 ] ]

```

$$(1-1-15) \quad G = 12T174 \simeq (C_3)^4 \rtimes Q_8.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,174);
[3^4:2]E(4)_4
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (2,10)(5,9)(7,11)(8,12), (3,7,11), (2,6,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 3, 3, 3 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
157
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 6 ], [ [ false ], 151 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);

```

```

151
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPTf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
6
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "(C3 x C3 x C3 x C3) : C2", 1 ], [ "(C3 x C3 x C3 x C3) : C4", 3 ],
[ "(C3 x C3 x C3) : C2", 10 ], [ "(C3 x C3) : C2", 40 ],
[ "(C3 x C3) : C4", 21 ], [ "1", 1 ], [ "C2", 1 ], [ "C3", 10 ],
[ "C3 x C3", 40 ], [ "C3 x C3 x C3", 10 ], [ "C3 x C3 x C3 x C3", 1 ],
[ "C4", 3 ], [ "S3", 10 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "(C3 x C3 x C3 x C3) : Q8", 1 ], [ "(C3 x C3) : Q8", 4 ], [ "Q8", 1 ] ]

```

$$(1-1-16) \quad G = 12T232 \simeq ((C_3)^4 \rtimes Q_8) \rtimes C_3.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,232);
[3^4:2]A(4)_4
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (2,8,7)(3,6,12)(4,11,10), (5,9)(6,10)(7,11)(8,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 6 ], [ [ 3 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 6 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 3 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
120
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPTf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPTf,Set));
[ [ [ true ], 7 ], [ [ false ], 113 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPTf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
113
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPTf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
7
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "(C3 x C3 x C3) : C3", 3 ],
[ "(C3 x ((C3 x C3 x C3) : C3)) : C2", 1 ],
[ "(C3 x ((C3 x C3) : C3)) : C2", 1 ], [ "(C3 x C3 x C3 x C3) : C2", 1 ],
[ "(C3 x C3 x C3 x C3) : C4", 1 ], [ "(C3 x C3 x C3) : C2", 6 ],
[ "(C3 x C3 x C3) : C3", 6 ], [ "(C3 x C3) : C2", 16 ],
[ "(C3 x C3) : C3", 4 ], [ "(C3 x C3) : C4", 7 ], [ "(C3 x C3) : C6", 3 ],
[ "1", 1 ], [ "C2", 1 ], [ "C3", 8 ], [ "C3 x ((C3 x C3 x C3) : C3)", 1 ],
[ "C3 x ((C3 x C3) : C2)", 1 ], [ "C3 x ((C3 x C3) : C3)", 1 ],
[ "C3 x (C9 : C3)", 1 ], [ "C3 x C3", 21 ], [ "C3 x C3 x C3", 7 ],
[ "C3 x C3 x C3 x C3", 1 ], [ "C3 x S3", 4 ], [ "C4", 1 ], [ "C6", 1 ],
[ "C9", 3 ], [ "C9 : C3", 5 ], [ "C9 x C3", 1 ], [ "S3", 6 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "((C3 x C3 x C3 x C3) : Q8) : C3", 1 ], [ "((C3 x C3) : Q8) : C3", 1 ],
[ "(C3 x C3 x C3 x C3) : Q8", 1 ], [ "(C3 x C3) : Q8", 2 ], [ "Q8", 1 ],
[ "SL(2,3)", 1 ] ]

```

$$(1-1-17) \quad G = 12T246 \simeq (C_3)^4 \rtimes ((C_2)^3 \rtimes C_4).$$

```
gap> Read("HNP.gap");
```

```

gap> G:=TransitiveGroup(12,246);
1/2[S(3)^4]E(4)
gap> GeneratorsOfGroup(G);
[ (4,8,12), (2,10)(4,8), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
  (1,7)(2,8,10,4)(3,9)(5,11)(6,12) ]
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (2,10)(4,8), (7,11)(8,12), (3,11)(8,12), (5,9)
(8,12), (2,6,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2, 2 ], [ [ 2, 2, 2 ], [ [ 1, 0, 1 ], [ 0, 1, 0 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 2, 2, 2 ], [ [ 1, 1, 1 ] ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=
> x->Number(FirstObstructionDr(G,x,H).Dr[2][2],y->(y[1]+y[2]) mod 2=1)>0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
291
gap> GcsH:=ConjugacyClassesNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 2 ], [ [ false ], 289 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
289
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
2
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "((C3 x C3) : C2) x ((C3 x C3) : C2)", 4 ],
  [ "((C3 x C3) : C2) x S3", 5 ], [ "((C3 x C3) : C4) x S3", 1 ],
  [ "(C3 x C3 x C3 x C3) : ((C4 x C2) : C2)", 2 ],
  [ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 2 ],
  [ "(C3 x C3 x C3 x C3) : (C2 x D8)", 1 ],
  [ "(C3 x C3 x C3 x C3) : (C4 x C2)", 3 ], [ "(C3 x C3 x C3 x C3) : C2", 1 ],
  [ "(C3 x C3 x C3 x C3) : C4", 1 ], [ "(C3 x C3 x C3 x C3) : D8", 2 ],
  [ "(C3 x C3 x C3) : (C2 x C2)", 2 ], [ "(C3 x C3 x C3) : C2", 6 ],
  [ "(C3 x C3 x C3) : C4", 2 ], [ "(C3 x C3) : ((C4 x C2) : C2)", 2 ],
  [ "(C3 x C3) : (C4 x C2)", 2 ], [ "(C3 x C3) : C2", 20 ],
  [ "(C3 x C3) : C4", 7 ], [ "(C4 x C2) : C2", 2 ], [ "(S3 x S3) : C2", 6 ],
  [ "1", 1 ], [ "C12", 2 ], [ "C2", 5 ], [ "C2 x ((C3 x C3) : C2)", 4 ],
  [ "C2 x ((C3 x C3) : C4)", 3 ], [ "C2 x ((S3 x S3) : C2)", 1 ],
  [ "C2 x C2", 6 ], [ "C2 x C2 x C2", 2 ], [ "C2 x C2 x S3", 2 ],
  [ "C2 x D8", 1 ], [ "C2 x S3 x S3", 5 ], [ "C3", 6 ], [ "C3 : C4", 2 ],
  [ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 2 ],
  [ "C3 x ((C3 x C3 x C3) : C4)", 2 ], [ "C3 x ((C3 x C3) : C2)", 9 ],
  [ "C3 x ((C3 x C3) : C4)", 2 ], [ "C3 x (C3 : C4)", 2 ], [ "C3 x C3", 16 ],
  [ "C3 x C3 x ((C3 x C3) : C2)", 4 ], [ "C3 x C3 x C3", 6 ],
  [ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x S3", 9 ], [ "C3 x S3", 26 ],
  [ "C3 x S3 x S3", 6 ], [ "C4", 3 ], [ "C4 x C2", 3 ], [ "C4 x S3", 2 ],
  [ "C6", 9 ], [ "C6 x C2", 2 ], [ "C6 x C3", 4 ], [ "C6 x S3", 6 ],
  [ "D12", 15 ], [ "D8", 2 ], [ "S3", 15 ], [ "S3 x ((C3 x C3) : C2)", 4 ],
  [ "S3 x ((C3 x C3) : C4)", 1 ], [ "S3 x S3", 25 ], [ "S3 x S3 x S3", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C2 x C2 x C2) : C4", 1 ],
  [ "(C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : C4)", 1 ] ]
gap> Number(List(GcsHNPfalse,Representative),x->Order(x) mod 32=0);
0

```

Example 7.2 ($G = 12Tm$ ($m = 2, 3, 4, 16, 18, 33, 43, 70, 71, 130, 132, 133, 176, 179, 234$))).

(1-2-1) $G = 12T2 \simeq C_6 \times C_2$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,2);
E(4)[x]C(3)=6x2
gap> H:=Stabilizer(G,1);
Group(())
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ ], [ ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (1,2,3)(4,5,6)(7,8,9)(10,11,12), (1,4)(2,5)(3,6)
  (7,10)(8,11)(9,12), (4,7)(5,8)(6,9) ]), Tid := [ 12, 14 ],
  epi := [ (1,2,3)(4,5,6)(7,8,9)(10,11,12), (1,4)(2,5)(3,6)(7,10)(8,11)(9,12),
    (4,7)(5,8)(6,9) ] -> [ (1,5,9)(2,6,10)(3,7,11)(4,8,12),
    (1,7)(2,8)(3,9)(4,10)(5,11)(6,12), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11) ] )
gap> tG:=ScG.SchurCover;
Group([ (1,2,3)(4,5,6)(7,8,9)(10,11,12), (1,4)(2,5)(3,6)(7,10)(8,11)
  (9,12), (4,7)(5,8)(6,9) ])
gap> StructureDescription(tG);
"C3 x D8"
gap> tH:=PreImage(ScG.epi,H);
Group([ (1,10)(2,11)(3,12)(4,7)(5,8)(6,9) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
10
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 2 ], [ [ false ], 8 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
  > x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
8
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
  > x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
2
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "C2", 3 ], [ "C3", 1 ], [ "C6", 3 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 1 ], [ "C6 x C2", 1 ] ]

```

(1-2-2) $G = 12T3 \simeq D_6$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,3);
D_6(6)[x]2=1/2[3:2]E(4)
gap> H:=Stabilizer(G,1);
Group(())
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ ], [ ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);

```

```

rec( SchurCover := Group([ (5,6), (2,3)(4,5)(6,7), (1,2,3) ]),
  epi := [ (5,6), (2,3)(4,5)(6,7), (1,2,3) ] ->
  [ (1,12)(2,3)(4,5)(6,7)(8,9)(10,11), (1,11)(2,8)(3,9)(4,6)(5,7)(10,12),
    (1,5,9)(2,6,10)(3,7,11)(4,8,12) ] )
gap> tG:=ScG.SchurCover;
Group([ (5,6), (2,3)(4,5)(6,7), (1,2,3) ])
gap> tH:=PreImage(ScG.epi,H);
Group([ (4,7)(5,6) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
10
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 2 ], [ [ false ], 8 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
  > x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
8
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
  > x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
2
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "C2", 3 ], [ "C3", 1 ], [ "C6", 1 ], [ "S3", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 1 ], [ "D12", 1 ] ]

```

(1-2-3) $G = 12T4 \simeq A_4(12)$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,4);
A_4(12)
gap> H:=Stabilizer(G,1);
Group(())
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ ], [ ] ] ]
gap> GroupCohomology(G,3); #  $H^3(G, \mathbb{Z}) = M(G)$ : Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (2,4,5)(3,7,8), (1,2,6,3)(4,5,7,8) ]),
  Tid := [ 8, 12 ], epi := [ (2,4,5)(3,7,8), (1,2,6,3)(4,5,7,8) ] ->
  [ (1,9,5)(2,4,3)(6,8,7)(10,12,11), (1,4)(2,11)(3,6)(5,8)(7,10)(9,12) ] )
gap> tG:=ScG.SchurCover;
Group([ (2,4,5)(3,7,8), (1,2,6,3)(4,5,7,8) ])
gap> StructureDescription(tG);
"SL(2,3)"
gap> tH:=PreImage(ScG.epi,H);
Group([ (1,6)(2,3)(4,7)(5,8) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);

```

```

5
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 2 ], [ [ false ], 3 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
3
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
2
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "1", 1 ], [ "C2", 1 ], [ "C3", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "A4", 1 ], [ "C2 x C2", 1 ] ]

```

$$(1\text{-}2\text{-}4) \quad G = 12T16 \simeq (S_3)^2.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,16);
[3^2]E(4)
gap> H:=Stabilizer(G,1);
Group([ (2,10,6)(4,8,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ 3 ], [ [ 3 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 3 ], [ [ 3 ], [ [ 1 ] ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (2,3)(7,8)(9,10), (1,2)(3,4)(5,6)(7,9)
  (8,10), (6,7,8) ]),
  epi := [ (2,3)(7,8)(9,10), (1,2)(3,4)(5,6)(7,9)(8,10), (6,7,8) ] ->
    [ (1,7)(2,8)(3,9)(4,10)(5,11)(6,12), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
      (2,10,6)(4,8,12) ] )
gap> tG:=ScG.SchurCover;
Group([ (2,3)(7,8)(9,10), (1,2)(3,4)(5,6)(7,9)(8,10), (6,7,8) ])
gap> StructureDescription(tG);
"(C6 x S3) : C2"
gap> tH:=PreImage(ScG.epi,H);
Group([ (6,7,8), (1,4)(2,3) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 6 ], [ [ 6 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ 3 ], [ [ 6 ], [ [ 2 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Product(FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]) mod 2=0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
22
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 4 ], [ [ false ], 18 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
18
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;

```

```

gap> Length(GcsHNPtrue);
4
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3) : C2", 1 ], [ "1", 1 ], [ "C2", 3 ], [ "C3", 3 ],
  [ "C3 x C3", 1 ], [ "C3 x S3", 2 ], [ "C6", 2 ], [ "S3", 5 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 1 ], [ "D12", 2 ], [ "S3 x S3", 1 ] ]

(1-2-5)  $G = 12T18 \simeq S_3 \times C_6$ .

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,18);
[3^2]E(4)
gap> H:=Stabilizer(G,1);
Group([ (2,6,10)(4,8,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 3 ], [ ] ] ]
gap> GroupCohomology(G,3); #  $H^3(G, \mathbb{Z}) = M(G)$ : Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (2,5)(6,9)(7,10), (1,2)(3,6)(4,7)(5,8)(9,11)
  (10,12), (2,6,7)(5,9,10), (1,3,4)(2,7,6)(5,10,9)(8,11,12) ]),
  Tid := [ 12, 42 ],
  epi := [ (2,5)(6,9)(7,10), (1,2)(3,6)(4,7)(5,8)(9,11)(10,12),
    (2,6,7)(5,9,10), (1,3,4)(2,7,6)(5,10,9)(8,11,12) ] ->
    [ (1,7)(2,8)(3,9)(4,10)(5,11)(6,12), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
      (2,6,10)(4,8,12), (1,5,9)(2,10,6)(3,7,11)(4,12,8) ] )
gap> tG:=ScG.SchurCover;
Group([ (2,5)(6,9)(7,10), (1,2)(3,6)(4,7)(5,8)(9,11)(10,12), (2,6,7)
  (5,9,10), (1,3,4)(2,7,6)(5,10,9)(8,11,12) ])
gap> StructureDescription(tG);
"C3 x ((C6 x C2) : C2)"
gap> tH:=PreImage(ScG.epi,H);
Group([ (2,6,7)(5,9,10), (1,8)(2,5)(3,11)(4,12)(6,9)(7,10) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 2 ], [ [ 6 ], [ [ 3 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ ], [ [ 6 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
22
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtrf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtrf,Set));
[ [ [ true ], 4 ], [ [ false ], 18 ] ]
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtrf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
18
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtrf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
4
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "C2", 3 ], [ "C3", 3 ], [ "C3 x C3", 1 ], [ "C3 x S3", 2 ],
  [ "C6", 5 ], [ "C6 x C3", 1 ], [ "S3", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 1 ], [ "C6 x C2", 1 ], [ "C6 x S3", 1 ], [ "D12", 1 ] ]

```

(1-2-6) $G = 12T33 \simeq A_5(12)$.

```

gap> Read("HNP.gap");

```

```

gap> G:=TransitiveGroup(12,33);
A_5(12)
gap> H:=Stabilizer(G,1);
Group([ (2,7,5,8,11)(3,6,4,9,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ 5 ], [ [ 5 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 5 ], [ [ 5 ], [ [ 1 ] ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (1,4,10,7)(2,5,11,8)(3,6,12,9)(13,18,17,15)
    (14,19,16,20)(21,24,23,22), (1,2,3)(4,13,15)(5,9,16)(6,14,8)(7,17,18)
    (10,11,12)(19,21,22)(20,23,24) ]), Tid := [ 24, 201 ],
  epi := [ (1,4,10,7)(2,5,11,8)(3,6,12,9)(13,18,17,15)(14,19,16,20)(21,24,23,
    22), (1,2,3)(4,13,15)(5,9,16)(6,14,8)(7,17,18)(10,11,12)(19,21,22)(20,
    23,24) ] -> [ (1,12)(2,4)(3,5)(6,7)(8,10)(9,11),
    (1,7,8)(2,11,4)(3,10,5)(6,9,12) ] )
gap> tG:=ScG.SchurCover;
Group([ (1,4,10,7)(2,5,11,8)(3,6,12,9)(13,18,17,15)(14,19,16,20)
(21,24,23,22), (1,2,3)(4,13,15)(5,9,16)(6,14,8)(7,17,18)(10,11,12)(19,21,22)
(20,23,24) ])
gap> tH:=PreImage(ScG.epi,H);
Group([ (1,20,24,12,17)(3,13,10,19,22)(4,15,9,23,14)(6,21,16,7,18), (1,10)
(2,11)(3,12)(4,7)(5,8)(6,9)(13,17)(14,16)(15,18)(19,20)(21,23)(22,24) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 10 ], [ [ 10 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ 5 ], [ [ 10 ], [ [ 2 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Product(FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]) mod 2=0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
9
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 3 ], [ [ false ], 6 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
6
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
3
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "C2", 1 ], [ "C3", 1 ], [ "C5", 1 ], [ "D10", 1 ],
  [ "S3", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "A4", 1 ], [ "A5", 1 ], [ "C2 x C2", 1 ] ]

```

(1-2-7) $G = 12T43 \simeq A_4(4) \times S_3$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,43);
A(4)[x]S(3)
gap> GeneratorsOfGroup(G);
[ (2,8,11)(3,6,12)(4,7,10), (1,7,10)(2,5,11)(3,6,9),
  (1,5,9)(2,6,10)(3,7,11)(4,8,12), (1,5)(2,10)(4,8)(7,11) ]
gap> H:=Stabilizer(G,1);
Group([ (2,8,11)(3,6,12)(4,7,10), (2,6)(3,11)(5,9)(8,12) ])

```

```

gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 6 ], [ ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := <permutation group of size 144 with 4 generators>,
      Tid := [ 24, 249 ],
      epi := [ (2,3)(6,8)(7,9)(15,20)(16,21)(17,22)(18,23)(19,24),
                (1,2,3)(4,6,8)(5,7,9)(10,15,20)(11,16,21)(12,17,22)(13,18,23)(14,19,24),
                (4,10,11)(5,13,14)(6,15,16)(7,18,19)(8,20,21)(9,23,24),
                (1,4,12,5)(2,6,17,7)(3,8,22,9)(10,11,13,14)(15,16,18,19)(20,21,23,24)
              ] -> [ (2,6)(3,11)(5,9)(8,12), (1,5,9)(2,6,10)(3,7,11)(4,8,12),
                (2,8,11)(3,6,12)(4,7,10), (1,4)(2,11)(3,6)(5,8)(7,10)(9,12) ] )
gap> tG:=ScG.SchurCover;
<permutation group of size 144 with 4 generators>
gap> StructureDescription(tG);
"SL(2,3) x S3"
gap> tH:=PreImage(ScG.epi,H);
Group([ (2,3)(6,8)(7,9)(15,20)(16,21)(17,22)(18,23)(19,24), (4,10,11)(5,13,14)
(6,15,16)(7,18,19)(8,20,21)(9,23,24), (1,12)(2,17)(3,22)(4,5)(6,7)(8,9)(10,13)
(11,14)(15,18)(16,19)(20,23)(21,24) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 2 ], [ [ 2, 6 ], [ [ 1, 0 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ ], [ [ 2, 6 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
26
gap> GcsH:=ConjugacyClassesNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 11 ], [ [ false ], 15 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
15
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
11
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "1", 1 ], [ "C2", 3 ], [ "C2 x C2", 1 ], [ "C3", 3 ], [ "C3 x C3", 1 ],
  [ "C3 x S3", 1 ], [ "C6", 2 ], [ "D12", 1 ], [ "S3", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "A4", 2 ], [ "A4 x S3", 1 ], [ "C2 x A4", 1 ], [ "C2 x C2", 2 ],
  [ "C2 x C2 x C2", 1 ], [ "C2 x C2 x S3", 1 ], [ "C3 x A4", 1 ],
  [ "C6 x C2", 1 ], [ "D12", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));;
[ [ "C2 x C2", 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
1
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);

```

```

2
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 4, 4, 4 ], 2 ] ]
gap> ChG:=CharacteristicSubgroups(G);;
gap> List(ChG,Order);
[ 72, 24, 36, 12, 12, 6, 3, 4, 1 ]
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))); 
[ [ [ 4, 4, 2, 2, 2, 1, 2, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))); 
[ [ [ 4, 4, 2, 2, 1, 1, 2, 1 ], 1 ],
  [ [ 4, 4, 4, 4, 1, 1, 4, 1 ], 1 ] ]
gap> S3:=ChG[6];
Group([ (2,6)(3,11)(5,9)(8,12), (1,9,5)(2,10,6)(3,11,7)(4,12,8) ])
gap> StructureDescription(S3);
"S3"
gap> List(List(GcsHNPfalseC2xC2,Representative),x->Intersection(S3,x));
[ Group([ (2,6)(3,11)(5,9)(8,12) ])]
gap> List(List(GcsHNPtrueC2xC2,Representative),x->Intersection(S3,x));
[ Group(), Group() ]

```

$$(1-2-8) \quad G = 12T70 \simeq (S_3)^2 \times C_3.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,70);
1/2[3^3:2]E(4)
gap> H:=Stabilizer(G,1);
Group([ (2,6,10)(3,7,11)(4,8,12), (3,11,7)(4,8,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ 3 ], [ [ 3, 3 ], [ [ 1, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 3 ], [ [ 3, 3 ], [ [ 1, 1 ] ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (1,2)(5,6)(7,8)(9,15)(10,16)(11,13)(12,14), (1,3)
  (2,4)(5,7)(6,8)(9,13)(10,14)(11,15)(12,16), (6,9,10)(8,13,14), (7,11,12)
  (8,14,13) ]),
  epi := [ (1,2)(5,6)(7,8)(9,15)(10,16)(11,13)(12,14),
    (1,3)(2,4)(5,7)(6,8)(9,13)(10,14)(11,15)(12,16), (6,9,10)(8,13,14),
    (7,11,12)(8,14,13) ] -> [ (1,7)(2,8)(3,9)(4,10)(5,11)(6,12),
    (1,2)(3,12)(4,11)(5,10)(6,9)(7,8), (3,7,11)(4,12,8), (2,10,6)(4,8,12) ]
)
gap> tG:=ScG.SchurCover;
Group([ (1,2)(5,6)(7,8)(9,15)(10,16)(11,13)(12,14), (1,3)(2,4)(5,7)(6,8)(9,13)
  (10,14)(11,15)(12,16), (6,9,10)(8,13,14), (7,11,12)(8,14,13) ])
gap> StructureDescription(tG);
"C3 x ((C6 x S3) : C2)"
gap> tH:=PreImage(ScG.epi,H);
Group([ (7,12,11)(8,13,14), (6,9,10)(7,12,11)(8,14,13), (1,2)(3,4) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 6 ], [ [ 3, 6 ], [ [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ 3 ], [ [ 3, 6 ], [ [ 0, 2 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Product(FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]) mod 2=0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
```

```

gap> Length(Gcs);
54
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 8 ], [ [ false ], 46 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
46
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
8
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "(C3 x C3) : C2", 1 ], [ "1", 1 ], [ "C2", 3 ], [ "C3", 7 ],
  [ "C3 x ((C3 x C3) : C2)", 1 ], [ "C3 x C3", 7 ], [ "C3 x C3 x C3", 1 ],
  [ "C3 x C3 x S3", 2 ], [ "C3 x S3", 9 ], [ "C6", 7 ], [ "C6 x C3", 2 ],
  [ "S3", 5 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "C2 x C2", 1 ], [ "C3 x S3 x S3", 1 ], [ "C6 x C2", 1 ], [ "C6 x S3", 2 ],
  [ "D12", 2 ], [ "S3 x S3", 1 ] ]

```

$$(1-2-9) \quad G = 12T71 \simeq (C_3)^3 \rtimes V_4.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,71);
[3^3]E(4)
gap> H:=Stabilizer(G,1);
Group([ (2,6,10)(3,7,11)(4,8,12), (3,7,11)(4,12,8) ])
gap> FirstObstructionN(G,H).ker;
[ [ 3, 3 ], [ [ 3, 3 ], [ [ 1, 0 ], [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 3, 3 ], [ [ 3, 3 ], [ [ 1, 0 ], [ 0, 1 ] ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (1,2)(5,6)(7,8)(9,15)(10,16)(11,14)(12,13), (1,3)
  (2,4)(5,7)(6,8)(9,14)(10,13)(11,15)(12,16), (7,11,12)(8,13,14), (6,9,10)
  (8,13,14) ]),
  epi := [ (1,2)(5,6)(7,8)(9,15)(10,16)(11,14)(12,13),
    (1,3)(2,4)(5,7)(6,8)(9,14)(10,13)(11,15)(12,16), (7,11,12)(8,13,14),
    (6,9,10)(8,13,14) ] -> [ (1,7)(2,8)(3,9)(4,10)(5,11)(6,12),
    (1,10)(2,5)(3,12)(4,7)(6,9)(8,11), (2,6,10)(4,12,8), (3,7,11)(4,12,8) ]
 )
gap> tG:=ScG.SchurCover;
Group([ (1,2)(5,6)(7,8)(9,15)(10,16)(11,14)(12,13), (1,3)(2,4)(5,7)(6,8)(9,14)
  (10,13)(11,15)(12,16), (7,11,12)(8,13,14), (6,9,10)(8,13,14) ])
gap> StructureDescription(tG);
"(C3 x C3 x C3) : D8"
gap> tH:=PreImage(ScG.epi,H);
Group([ (7,12,11)(8,14,13), (6,9,10)(7,11,12)(8,14,13), (1,2)(3,4) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 3, 6 ], [ [ 3, 6 ], [ [ 1, 0 ], [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ 3, 3 ], [ [ 3, 6 ], [ [ 1, 0 ], [ 0, 2 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Number(FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[2][2],
> y->y[2] mod 2=1)>0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
54

```

```

gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 8 ], [ [ false ], 46 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
46
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
8
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "(C3 x C3) : C2", 3 ], [ "1", 1 ], [ "C2", 3 ], [ "C3", 7 ],
  [ "C3 x ((C3 x C3) : C2)", 3 ], [ "C3 x C3", 7 ], [ "C3 x C3 x C3", 1 ],
  [ "C3 x S3", 9 ], [ "C6", 3 ], [ "S3", 9 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "(C3 x C3 x C3) : (C2 x C2)", 1 ], [ "C2 x C2", 1 ], [ "D12", 3 ],
  [ "S3 x S3", 3 ] ]

```

$$(1\text{-}2\text{-}10) \quad G = 12T130 \simeq (C_3)^4 \rtimes V_4 \simeq C_3 \wr V_4.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,130);
[3^4]E(4)=3wrE(4)
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (3,11,7), (2,10,6) ])
gap> FirstObstructionN(G,H).ker;
[ [ 3, 3 ], [ [ 3, 3, 3 ], [ [ 1, 0, 1 ], [ 0, 1, 2 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 3, 3 ], [ [ 3, 3, 3 ], [ [ 1, 0, 1 ], [ 0, 1, 2 ] ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (1,2)(3,6)(4,9)(5,10)(7,11)(8,12)(13,14)(15,18)
  (16,21)(17,22)(19,23)(20,24), (2,3)(4,8)(5,7)(9,10)(11,12)(14,15)(16,19)
  (17,20), (2,4,5)(3,7,8)(14,16,17)(15,19,20) ]),
  epi := [ (1,2)(3,6)(4,9)(5,10)(7,11)(8,12)(13,14)(15,18)(16,21)(17,22)(19,
    23)(20,24), (2,3)(4,8)(5,7)(9,10)(11,12)(14,15)(16,19)(17,20),
    (2,4,5)(3,7,8)(14,16,17)(15,19,20) ] ->
  [ (1,7)(2,8)(3,9)(4,10)(5,11)(6,12), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
    (4,8,12) ] )
gap> tG:=ScG.SchurCover;
Group([ (1,2)(3,6)(4,9)(5,10)(7,11)(8,12)(13,14)(15,18)(16,21)(17,22)(19,23)
  (20,24), (2,3)(4,8)(5,7)(9,10)(11,12)(14,15)(16,19)(17,20), (2,4,5)(3,7,8)
  (14,16,17)(15,19,20) ])
gap> StructureDescription(tG);
"C3 x ((C3 x C3 x C3) : D8)"
gap> tH:=PreImage(ScG.epi,H);
<permutation group of size 54 with 4 generators>
gap> FirstObstructionN(tG,tH).ker;
[ [ 3, 6 ], [ [ 3, 3, 6 ], [ [ 1, 0, 0 ], [ 0, 1, 2 ], [ 0, 0, 3 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ 3, 3 ], [ [ 3, 3, 6 ], [ [ 1, 0, 0 ], [ 0, 1, 2 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Product(FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]) mod 2=0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
174
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));

```

```
[ [ [ true ], 16 ], [ [ false ], 158 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
158
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
16
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3) : C2", 3 ], [ "1", 1 ], [ "C2", 3 ], [ "C3", 16 ],
[ "C3 x ((C3 x C3) : C2)", 9 ], [ "C3 x C3", 46 ],
[ "C3 x C3 x ((C3 x C3) : C2)", 3 ], [ "C3 x C3 x C3", 16 ],
[ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x S3", 9 ], [ "C3 x S3", 30 ],
[ "C6", 9 ], [ "C6 x C3", 3 ], [ "S3", 9 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3 x C3) : (C2 x C2)", 1 ], [ "C2 x C2", 1 ],
[ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 1 ], [ "C3 x S3 x S3", 3 ],
[ "C6 x C2", 1 ], [ "C6 x S3", 3 ], [ "D12", 3 ], [ "S3 x S3", 3 ] ]
```

$$(1-2-11) \quad G = 12T132 \simeq ((C_3)^3 \rtimes V_4) \rtimes C_3.$$

```
gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,132);
1/3[3^4]A(4)
gap> H:=Stabilizer(G,1);
Group([ (2,6,10)(3,7,11)(4,8,12), (3,7,11)(4,12,8), (2,8,3,10,4,11,6,12,7) ])
gap> FirstObstructionN(G,H).ker;
[ [ 3 ], [ [ 3, 3 ], [ [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 3 ], [ [ 3, 3 ], [ [ 0, 1 ] ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (2,3,5)(6,8,7)(9,16,18,11,15,20,10,17,19)
(12,13,14), (1,7,4,5)(2,3,6,8)(9,20)(10,18)(11,19)(12,17)(13,15)
(14,16), (15,16,17)(18,20,19) ]),
epi := [ (2,3,5)(6,8,7)(9,16,18,11,15,20,10,17,19)(12,13,14),
(1,7,4,5)(2,3,6,8)(9,20)(10,18)(11,19)(12,17)(13,15)(14,16),
(15,16,17)(18,20,19) ] ->
[ (1,4,11,5,8,3,9,12,7), (1,7)(2,12)(3,9)(4,6)(5,11)(8,10),
(3,7,11)(4,12,8) ] )
gap> tG:=ScG.SchurCover;
Group([ (2,3,5)(6,8,7)(9,16,18,11,15,20,10,17,19)(12,13,14), (1,7,4,5)
(2,3,6,8)(9,20)(10,18)(11,19)(12,17)(13,15)(14,16), (15,16,17)(18,20,19) ])
gap> StructureDescription(tG);
"((C3 x C3 x C3) : Q8) : C3"
gap> tH:=PreImage(ScG.epi,H);
Group([ (12,14,13)(15,17,16)(18,20,19), (1,4)(2,6)(3,8)(5,7)(15,16,17)
(18,20,19), (1,5,2,4,7,6)(3,8)(9,11,10)(12,17,20,13,15,18,14,16,19) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 6 ], [ [ 3, 6 ], [ [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ 3 ], [ [ 3, 6 ], [ [ 0, 2 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Product(FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]) mod 2=0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
32
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf,Set));
```

```
[ [ [ true ], 6 ], [ [ false ], 26 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
26
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
6
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3 x C3) : C3", 1 ], [ "(C3 x C3) : C2", 1 ],
  [ "(C3 x C3) : C3", 1 ], [ "1", 1 ], [ "C2", 1 ], [ "C3", 4 ],
  [ "C3 x ((C3 x C3) : C2)", 1 ], [ "C3 x C3", 4 ], [ "C3 x C3 x C3", 1 ],
  [ "C3 x S3", 3 ], [ "C6", 1 ], [ "C9", 2 ], [ "C9 : C3", 2 ], [ "S3", 3 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C3 x C3 x C3) : (C2 x C2)) : C3", 1 ],
  [ "(C3 x C3 x C3) : (C2 x C2)", 1 ], [ "A4", 1 ], [ "C2 x C2", 1 ],
  [ "D12", 1 ], [ "S3 x S3", 1 ] ]
```

$$(1-2-12) \quad G = 12T133 \simeq (C_3)^3 \rtimes A_4(4).$$

```
gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,133);
[3^3]A(4)
gap> H:=Stabilizer(G,1);
Group([ (2,6,10)(3,7,11)(4,8,12), (2,8,11)(3,6,12)(4,7,10), (3,7,11)
(4,12,8) ])
gap> FirstObstructionN(G,H).ker;
[ [ 3 ], [ [ 3, 3 ], [ [ 1, 0 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 3 ], [ [ 3, 3 ], [ [ 1, 0 ] ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (2,4,5)(3,7,8)(10,11,12)(13,16,17)(14,15,18), (1,2,
  6,3)(4,5,7,8)(9,10)(11,12)(13,16)(14,15)(17,19)(18,20), (11,13,14)
(12,15,16) ]),
  epi := [ (2,4,5)(3,7,8)(10,11,12)(13,16,17)(14,15,18),
    (1,2,6,3)(4,5,7,8)(9,10)(11,12)(13,16)(14,15)(17,19)(18,20),
    (11,13,14)(12,15,16) ] ->
    [ (1,7,4)(3,12,9)(5,11,8), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
    (3,11,7)(4,8,12) ] )
gap> tG:=ScG.SchurCover;
Group([ (2,4,5)(3,7,8)(10,11,12)(13,16,17)(14,15,18), (1,2,6,3)(4,5,7,8)(9,10)
(11,12)(13,16)(14,15)(17,19)(18,20), (11,13,14)(12,15,16) ])
gap> StructureDescription(tG);
"((C3 x C3 x C3) : Q8) : C3"
gap> tH:=PreImage(ScG.epi,H);
Group([ (11,14,13)(12,16,15), (1,8,4)(5,7,6)(9,12,11)(13,19,16)
(14,20,15), (9,20,19)(11,14,13)(12,15,16), (1,6)(2,3)(4,7)(5,8) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 6 ], [ [ 3, 6 ], [ [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ 3 ], [ [ 3, 6 ], [ [ 0, 2 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Product(FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]) mod 2=0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
32
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf,Set));
```

```
[ [ [ true ], 6 ], [ [ false ], 26 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
26
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
6
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3 x C3) : C3", 1 ], [ "(C3 x C3) : C2", 1 ],
  [ "(C3 x C3) : C3", 1 ], [ "1", 1 ], [ "C2", 1 ], [ "C3", 4 ],
  [ "C3 x ((C3 x C3) : C2)", 1 ], [ "C3 x C3", 4 ], [ "C3 x C3 x C3", 1 ],
  [ "C3 x S3", 3 ], [ "C6", 1 ], [ "C9", 2 ], [ "C9 : C3", 2 ], [ "S3", 3 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C3 x C3 x C3) : (C2 x C2)) : C3", 1 ],
  [ "(C3 x C3 x C3) : (C2 x C2)", 1 ], [ "A4", 1 ], [ "C2 x C2", 1 ],
  [ "D12", 1 ], [ "S3 x S3", 1 ] ]
```

$$(1-2-13) \quad G = 12T176 \simeq ((C_3)^3 \rtimes C_2) \rtimes A_4(4).$$

```
gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,176);
[3^3:2]A(4)
gap> GeneratorsOfGroup(G);
[ (2,6,10)(3,7,11)(4,8,12), (1,5)(2,10)(4,8)(7,11), (2,8,11)(3,6,12)(4,7,10),
  (1,7,10)(2,5,11)(3,6,9) ]
gap> H:=Stabilizer(G,1);
Group([ (2,6,10)(3,7,11)(4,8,12), (2,8,11)(3,6,12)(4,7,10), (3,11)(4,12)(5,9)
(6,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 6 ], [ ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (2,4,5)(3,7,8)(9,10,11)(13,14,18)(15,19,20), (1,2,
  6,3)(4,5,7,8)(9,12)(10,11)(13,14)(15,20)(16,19)(17,18), (10,13)(11,14)
(12,16)(18,19), (11,15,14)(12,17,16) ]),
  epi := [ (2,4,5)(3,7,8)(9,10,11)(13,14,18)(15,19,20),
    (1,2,6,3)(4,5,7,8)(9,12)(10,11)(13,14)(15,20)(16,19)(17,18),
    (10,13)(11,14)(12,16)(18,19), (11,15,14)(12,17,16) ] ->
  [ (1,7,4)(3,12,9)(5,11,8), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
    (4,8)(5,9)(6,10)(7,11), (2,6,10)(4,12,8) ] )
gap> tG:=ScG.SchurCover;
Group([ (2,4,5)(3,7,8)(9,10,11)(13,14,18)(15,19,20), (1,2,6,3)(4,5,7,8)(9,12)
(10,11)(13,14)(15,20)(16,19)(17,18), (10,13)(11,14)(12,16)(18,19), (11,15,14)
(12,17,16) ])
gap> StructureDescription(tG);
"((C3 x C3 x C3) : (C2 x Q8)) : C3"
gap> tH:=PreImage(ScG.epi,H);
Group([ (10,13,20)(11,14,15)(12,17,16), (1,8,4)(5,7,6)(10,12,11)(13,17,14)
(15,20,16), (11,15)(12,16)(13,20)(18,19), (1,6)(2,3)(4,7)(5,8) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 2 ], [ [ 2, 6 ], [ [ 1, 0 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ ], [ [ 2, 6 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
76
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
```

```

gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 20 ], [ [ false ], 56 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
56
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
20
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3 x C3) : C3" , 1 ], [ "(C3 x C3) x S3" , 1 ],
  [ "(C3 x C3 x C3) : C2" , 1 ], [ "(C3 x C3) : C3" , 1 ],
  [ "(C3 x C3) : C2" , 4 ], [ "(C3 x C3) : C3" , 1 ], [ "(C3 x C3) : C6" , 1 ],
  [ "1" , 1 ], [ "C2" , 3 ], [ "C2 x ((C3 x C3) : C2)" , 1 ], [ "C2 x C2" , 1 ],
  [ "C3" , 4 ], [ "C3 x ((C3 x C3) : C2)" , 1 ], [ "C3 x C3" , 4 ],
  [ "C3 x C3 x C3" , 1 ], [ "C3 x C3 x S3" , 1 ], [ "C3 x S3" , 7 ],
  [ "C6" , 5 ], [ "C6 x C3" , 1 ], [ "C9" , 1 ], [ "C9 : C3" , 1 ], [ "D12" , 4 ],
  [ "S3" , 7 ], [ "S3 x S3" , 3 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(((C3 x C3 x C3) : (C2 x C2)) : C3) : C2" , 1 ],
  [ "((C3 x C3 x C3) : (C2 x C2)) : C3" , 1 ],
  [ "(C3 x C3 x C3) : (C2 x C2)" , 1 ], [ "A4" , 1 ], [ "C2 x A4" , 1 ],
  [ "C2 x C2" , 2 ], [ "C2 x C2 x C2" , 1 ], [ "C2 x C2 x S3" , 1 ],
  [ "C2 x S3 x S3" , 1 ], [ "C3 x S3 x S3" , 1 ], [ "C6 x C2" , 1 ],
  [ "C6 x S3" , 2 ], [ "D12" , 3 ], [ "S3 x S3" , 2 ], [ "S3 x S3 x S3" , 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2" , 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
1
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
2
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ] , 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ] , 2 ] ]
gap> ChG:=CharacteristicSubgroups(G);;
gap> List(ChG,Order);
[ 648, 324, 216, 54, 108, 27, 1 ]
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))));;
[ [ [ 4, 2, 4, 2, 2, 1, 1 ] , 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))));;
[ [ [ 4, 2, 4, 1, 2, 1, 1 ] , 1 ],
  [ [ 4, 4, 4, 1, 4, 1, 1 ] , 1 ] ]
gap> DihE27:=ChG[4];
Group([ (4,8)(5,9)(6,10)(7,11), (3,11,7)(4,8,12), (1,5,9)(3,11,7), (2,6,10)
(3,7,11)(4,8,12) ])
gap> StructureDescription(DihE27);
"(C3 x C3 x C3) : C2"
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),

```

```

> x->StructureDescription(Intersection(DihE27,x)));
[ [ "C2", 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(DihE27,x))));
[ [ "1", 2 ] ]

(1-2-14)  $G = 12T179 \simeq \mathrm{PSL}_2(\mathbb{F}_{11})$ .

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,179);
L(2,11)
gap> H:=Stabilizer(G,1);
Group([ (2,3,6,7,11)(4,12,9,5,10), (2,10,12,8,11)(3,5,7,6,4) ])
gap> FirstObstructionN(G,H).ker;
[ [ 5 ], [ [ 5 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 5 ], [ [ 5 ], [ [ 1 ] ] ] ]
gap> GroupCohomology(G,3); #  $H^3(G, \mathbb{Z}) = M(G)$ : Schur multiplier of  $G$ 
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := Group([ (1,4,23,22)(2,14,12,9)(3,10,24,8)(5,21,17,7)
  (6,13,11,18)(15,16,19,20), (1,3,2)(4,10,20)(5,11,21)(6,7,17)(8,16,22)
  (9,18,15)(12,23,24)(13,19,14) ]), Tid := [ 24, 2947 ],
  epi := [ (1,4,23,22)(2,14,12,9)(3,10,24,8)(5,21,17,7)(6,13,11,18)(15,16,19,
    20), (1,3,2)(4,10,20)(5,11,21)(6,7,17)(8,16,22)(9,18,15)(12,23,24)(13,
    19,14) ] -> [ (1,5)(2,12)(3,7)(4,11)(6,8)(9,10),
    (1,11,2)(3,7,12)(4,9,6)(5,10,8) ] )
gap> tG:=ScG.SchurCover;
Group([ (1,4,23,22)(2,14,12,9)(3,10,24,8)(5,21,17,7)(6,13,11,18)
  (15,16,19,20), (1,3,2)(4,10,20)(5,11,21)(6,7,17)(8,16,22)(9,18,15)(12,23,24)
  (13,19,14) ])
gap> StructureDescription(tG);
"SL(2,11)"
gap> tH:=PreImage(ScG.epi,H);
Group([ (2,20,24,7,17)(3,21,5,12,16)(4,10,18,11,14)(6,9,22,8,13), (1,20,6,7,
  17,24,22,13,8,2,9)(3,4,18,10,12,14,23,16,11,21,5), (1,23)(2,12)(3,24)(4,22)
  (5,17)(6,11)(7,21)(8,10)(9,14)(13,18)(15,19)(16,20) ])
gap> FirstObstructionN(tG,tH).ker;
[ [ 10 ], [ [ 10 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ 5 ], [ [ 10 ], [ [ 2 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Product(FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]) mod 2=0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
16
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 6 ], [ [ false ], 10 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
10
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
6
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "C11", 1 ], [ "C11 : C5", 1 ], [ "C2", 1 ], [ "C3", 1 ],
  [ "C5", 1 ], [ "C6", 1 ], [ "D10", 1 ], [ "S3", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
```

```
[ [ "A4", 1 ], [ "A5", 2 ], [ "C2 x C2", 1 ], [ "D12", 1 ],
[ "PSL(2,11)", 1 ] ]

(1-2-15)  $G = 12T234 \simeq ((C_3)^4 \rtimes C_2) \rtimes A_4(4)$ .
```

```
gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,234);
[3^4:2]A(4)
gap> GeneratorsOfGroup(G);
[ (4,8,12), (1,5)(2,10)(4,8)(7,11), (2,8,11)(3,6,12)(4,7,10),
(1,7,10)(2,5,11)(3,6,9) ]
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (2,8,11)(3,6,12)(4,7,10), (5,9)(6,10)(7,11)(8,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 6 ], [ ] ] ]
gap> GroupCohomology(G,3); #  $H^3(G, \mathbb{Z}) = M(G)$ : Schur multiplier of  $G$ 
[ 2 ]
gap> ScG:=SchurCoverG(G);
rec( SchurCover := <permutation group of size 3888 with 6 generators>,
      epi := [ (2,5,6)(3,9,10)(8,12,13)(11,15,16)(17,18,19)(20,24,25)(21,23,26),
                (1,2,7,3)(4,8,14,11)(5,6,9,10)(12,13,15,16)(17,18)(19,22)(20,25)(21,
                26)(23,28)(24,27), (1,4)(2,8)(3,11)(5,12)(6,13)(7,14)(9,15)(10,16)(18,
                20)(19,23)(25,26)(27,28), (22,27,28), (19,24,23)(22,27,28),
                (18,20,21)(19,24,23)(22,27,28) ] ->
      [ (1,10,7)(2,11,5)(3,9,6), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
        (5,9)(6,10)(7,11)(8,12), (4,12,8), (3,11,7)(4,12,8),
        (2,10,6)(3,11,7)(4,12,8) ] )
gap> tG:=ScG.SchurCover;
<permutation group of size 3888 with 6 generators>
gap> StructureDescription(tG);
"((C3 x C3 x C3 x C3) : (C2 x Q8)) : C3"
gap> tH:=PreImage(ScG.epi,H);
<permutation group of size 324 with 4 generators>
gap> FirstObstructionN(tG,tH).ker;
[ [ 2 ], [ [ 2, 6 ], [ [ 1, 0 ] ] ] ]
gap> FirstObstructionDnr(tG,tH).Dnr;
[ [ ], [ [ 2, 6 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(tG,PreImage(ScG.epi,x),tH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
236
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 42 ], [ [ false ], 194 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
194
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
42
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "((C3 x C3 x C3) : C3) : C2", 3 ],
[ "((C3 x C3) : C2) x ((C3 x C3) : C2)", 1 ],
[ "((C3 x C3) : C2) x S3", 6 ], [ "(C3 x ((C3 x C3 x C3) : C3)) : C2", 1 ],
[ "(C3 x ((C3 x C3) : C3)) : C2", 1 ], [ "(C3 x C3 x C3 x C3) : C2", 1 ],
[ "(C3 x C3 x C3) : C2", 8 ], [ "(C3 x C3 x C3) : C3", 6 ],
[ "(C3 x C3) : C2", 20 ], [ "(C3 x C3) : C3", 4 ], [ "(C3 x C3) : C6", 3 ],
[ "1", 1 ], [ "C2", 3 ], [ "C2 x ((C3 x C3) : C2)", 2 ], [ "C2 x C2", 1 ],
[ "C3", 10 ], [ "C3 x ((C3 x C3 x C3) : C3)", 1 ],
```

```

[ "C3 x ((C3 x C3) : C2)", 7 ], [ "C3 x ((C3 x C3) : C3)", 1 ],
[ "C3 x (C9 : C3)", 1 ], [ "C3 x C3", 23 ],
[ "C3 x C3 x ((C3 x C3) : C2)", 2 ], [ "C3 x C3 x C3", 9 ],
[ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x S3", 6 ], [ "C3 x S3", 24 ],
[ "C6", 7 ], [ "C6 x C3", 2 ], [ "C9", 3 ], [ "C9 : C3", 5 ],
[ "C9 x C3", 1 ], [ "D12", 6 ], [ "S3", 14 ], [ "S3 x S3", 10 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ ((C3 x C3 x C3) : (C2 x C2)) : C3", 2 ],
[ "(C3 x (((C3 x C3 x C3) : (C2 x C2)) : C3)) : C2", 1 ],
[ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 1 ],
[ "(C3 x C3 x C3) : (C2 x C2)", 2 ], [ "(S3 x S3 x S3) : C3", 1 ],
[ "A4", 2 ], [ "A4 x S3", 1 ], [ "C2 x A4", 1 ], [ "C2 x C2", 2 ],
[ "C2 x C2 x C2", 1 ], [ "C2 x C2 x S3", 2 ], [ "C2 x S3 x S3", 2 ],
[ "C3 x (((C3 x C3 x C3) : (C2 x C2)) : C3)", 1 ],
[ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 2 ], [ "C3 x A4", 1 ],
[ "C3 x S3 x S3", 4 ], [ "C6 x C2", 2 ], [ "C6 x S3", 4 ], [ "D12", 4 ],
[ "S3 x S3", 4 ], [ "S3 x S3 x S3", 2 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2];;
gap> Length(GcsHNPfalseC2xC2);
1
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2];;
gap> Length(GcsHNPtrueC2xC2);
2
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 2 ] ]
gap> ChG:=CharacteristicSubgroups(G);;
gap> List(ChG,Order);
[ 1944, 972, 648, 162, 324, 324, 108, 81, 3, 27, 1 ]
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))));;
[ [ [ 4, 2, 4, 2, 2, 2, 1, 1, 1, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))));;
[ [ [ 4, 2, 4, 1, 2, 2, 1, 1, 1, 1 ], 1 ],
[ [ 4, 4, 4, 1, 4, 4, 1, 1, 1, 1 ], 1 ] ]
gap> DihE81:=ChG[4];
Group([ (5,9)(6,10)(7,11)(8,12), (1,5,9), (2,6,10), (3,7,11), (4,8,12) ])
gap> StructureDescription(DihE81);
"(C3 x C3 x C3 x C3) : C2"
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->StructureDescription(Intersection(DihE81,x))));;
[ [ "C2", 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(DihE81,x))));;
[ [ "1", 2 ] ]

```

Example 7.3 ($G = 12Tm$ ($m = 20, 40, 117, 168, 171, 194, 261, 280$))).

(1-3-1) $G = 12T20 \simeq A_4(4) \times C_3$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,20);

```

```

A(4)[x]C(3)
gap> H:=Stabilizer(G,1);
Group([ (2,8,11)(3,6,12)(4,7,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 3 ], [ ] ] ]
gap> GroupCohomology(G,3); #  $H^3(G, \mathbb{Z}) = M(G)$ : Schur multiplier of G
[ 2, 3 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2 ][ ]
[ 3 ][ 3 ]
gap> cG:=cGs[1];
rec( MinimalStemExtension := <permutation group of size 72 with 5 generators>,
      epi := [ (1,6,18)(2,11,29)(3,14,33)(4,16,35)(5,17,36)(7,22,43)(8,25,47)(9,
              27,49)(10,28,50)(12,31,52)(13,32,53)(15,34,54)(19,39,58)(20,41,60)(21,
              42,61)(23,45,63)(24,46,64)(26,48,65)(30,51,66)(37,56,68)(38,57,69)(40,
              59,70)(44,62,71)(55,67,72), (1,2,7)(3,23,20)(4,8,37)(5,10,21)(6,11,
              22)(9,19,12)(13,44,40)(14,45,41)(15,24,55)(16,25,56)(17,28,42)(18,29,
              43)(26,38,30)(27,39,31)(32,62,59)(33,63,60)(34,46,67)(35,47,68)(36,50,
              61)(48,57,51)(49,58,52)(53,71,70)(54,64,72)(65,69,66),
              (1,12,5,30)(2,23,10,44)(3,15,13,4)(6,31,17,51)(7,37,21,55)(8,26,24,
              9)(11,45,28,62)(14,34,32,16)(18,52,36,66)(19,40,38,20)(22,56,42,
              67)(25,48,46,27)(29,63,50,71)(33,54,53,35)(39,59,57,41)(43,68,61,
              72)(47,65,64,49)(58,70,69,60) ] -> [ (1,5,9)(2,6,10)(3,7,11)(4,8,12),
              (2,8,11)(3,6,12)(4,7,10), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11) ] )
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 72 with 5 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 6 with 2 generators>
gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 3 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2 ], [ [ 6 ], [ [ 3 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ ], [ [ 6 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
14
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 6 ], [ [ false ], 8 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
8
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
6
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "C2", 1 ], [ "C3", 4 ], [ "C3 x C3", 1 ], [ "C6", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "A4", 3 ], [ "C2 x C2", 1 ], [ "C3 x A4", 1 ], [ "C6 x C2", 1 ] ]

```

$$(2\text{-}3\text{-}2) G = 12T40 \simeq ((C_3)^2 \rtimes C_4) \times C_2.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,40);
F_36(6)[x]2
gap> H:=Stabilizer(G,1);
Group([ (2,10)(3,11)(4,8)(5,9), (2,6,10)(3,7,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 2 ], [ ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2, 3 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 3 ][ 3 ]
[ 2 ][ ]
gap> cG:=cGs[2];;
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 144 with 6 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 12 with 3 generators>
gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 2, 6 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 0 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
26
gap> GcsH:=ConjugacyClassesNGHOorbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 2 ], [ [ false ], 24 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
24
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
2
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "(C3 x C3) : C2", 2 ], [ "(C3 x C3) : C4", 2 ], [ "1", 1 ], [ "C2", 3 ],
  [ "C2 x ((C3 x C3) : C2)", 1 ], [ "C2 x C2", 1 ], [ "C3", 2 ],
  [ "C3 x C3", 1 ], [ "C4", 2 ], [ "C6", 2 ], [ "C6 x C3", 1 ], [ "D12", 2 ],
  [ "S3", 4 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "C2 x ((C3 x C3) : C4)", 1 ], [ "C4 x C2", 1 ] ]

```

$$(1\text{-}3\text{-}3) G = 12T117 \simeq (S_3)^3.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,117);
[3^3:2]E(4)
gap> GeneratorsOfGroup(G);

```

```

[ (2,6,10)(3,7,11)(4,8,12), (1,5)(2,10)(4,8)(7,11),
  (1,10)(2,5)(3,12)(4,7)(6,9)(8,11), (1,7)(2,8)(3,9)(4,10)(5,11)(6,12) ]
gap> H:=Stabilizer(G,1);
Group([ (2,6,10)(3,7,11)(4,8,12), (3,11)(4,12)(5,9)(6,10), (4,8)(5,9)(6,10)
(7,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 2 ], [ ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2, 2, 2 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
gap> cG:=cGs[5];;
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 432 with 7 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 36 with 3 generators>
gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
162
gap> GcsH:=ConjugacyClassesNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 40 ], [ [ false ], 122 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
122
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
40
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "(C3 x C3) : C2) x S3", 3 ], [ "(C3 x C3 x C3) : C2", 1 ],
  [ "(C3 x C3) : C2", 10 ], [ "1", 1 ], [ "C2", 7 ],
  [ "C2 x ((C3 x C3) : C2)", 3 ], [ "C2 x C2", 3 ], [ "C3", 7 ],
  [ "C3 x ((C3 x C3) : C2)", 3 ], [ "C3 x C3", 7 ], [ "C3 x C3 x C3", 1 ],
  [ "C3 x C3 x S3", 3 ], [ "C3 x S3", 18 ], [ "C6", 12 ], [ "C6 x C3", 3 ],
  [ "D12", 12 ], [ "S3", 19 ], [ "S3 x S3", 9 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "(C3 x C3 x C3) : (C2 x C2)", 1 ], [ "C2 x C2", 4 ],
  [ "C2 x C2 x C2", 1 ], [ "C2 x C2 x S3", 3 ], [ "C2 x S3 x S3", 3 ],
  [ "C3 x C3 x S3", 1 ], [ "C3 x S3", 18 ], [ "C6", 12 ], [ "C6 x C3", 3 ],
  [ "D12", 12 ], [ "S3", 19 ], [ "S3 x S3", 9 ] ]

```

```

[ "C3 x S3 x S3", 3 ], [ "C6 x C2", 3 ], [ "C6 x S3", 6 ], [ "D12", 9 ],
[ "S3 x S3", 6 ], [ "S3 x S3 x S3", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));;
[ [ "C2 x C2", 4 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
3
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
4
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 4 ] ]
gap> ChG:=CharacteristicSubgroups(G);;
gap> List(ChG,Order);
[ 216, 54, 108, 27, 1 ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))));
[ [ [ 4, 2, 2, 1, 1 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))));
[ [ [ 4, 1, 2, 1, 1 ], 3 ],
[ [ 4, 1, 4, 1, 1 ], 1 ] ]
gap> DihE27:=ChG[2];
Group([ (4,8)(5,9)(6,10)(7,11), (3,7,11)(4,12,8), (1,5,9)(3,7,11)
(4,8,12), (2,6,10)(3,7,11)(4,8,12) ])
gap> StructureDescription(DihE27);
"(C3 x C3 x C3) : C2"
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(DihE27,x))));;
[ [ "C2", 3 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(DihE27,x))));;
[ [ "1", 4 ] ]

```

$$(1-3-4) \quad G = 12T168 \simeq (C_3)^4 \rtimes (C_2)^3.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,168);
[3^4:2]E(4)
gap> GeneratorsOfGroup(G);
[ (4,8,12), (1,5)(2,10)(4,8)(7,11), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
(1,7)(2,8)(3,9)(4,10)(5,11)(6,12) ]
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (2,10)(5,9)(7,11)(8,12), (3,11,7), (5,9)(6,10)(7,11)
(8,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 2 ], [ ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2, 2, 2 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);

```

```

> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][  ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
gap> cG:=cGs[4];
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 1296 with 8 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 108 with 5 generators>
gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 0 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
474
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 80 ], [ [ false ], 394 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
394
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
80
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "((C3 x C3) : C2) x ((C3 x C3) : C2)", 3 ],
  [ "((C3 x C3) : C2) x S3", 18 ], [ "(C3 x C3 x C3 x C3) : C2", 1 ],
  [ "(C3 x C3 x C3) : C2", 16 ], [ "(C3 x C3) : C2", 52 ], [ "1", 1 ],
  [ "C2", 7 ], [ "C2 x ((C3 x C3) : C2)", 6 ], [ "C2 x C2", 3 ],
  [ "C3", 16 ], [ "C3 x ((C3 x C3) : C2)", 18 ], [ "C3 x C3", 46 ],
  [ "C3 x C3 x ((C3 x C3) : C2)", 6 ], [ "C3 x C3 x C3", 16 ],
  [ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x S3", 18 ], [ "C3 x S3", 60 ],
  [ "C6", 18 ], [ "C6 x C3", 6 ], [ "D12", 18 ], [ "S3", 34 ],
  [ "S3 x S3", 30 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 1 ],
  [ "(C3 x C3 x C3) : (C2 x C2)", 4 ], [ "C2 x C2", 4 ],
  [ "C2 x C2 x C2", 1 ], [ "C2 x C2 x S3", 4 ], [ "C2 x S3 x S3", 6 ],
  [ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 4 ], [ "C3 x S3 x S3", 12 ],
  [ "C6 x C2", 4 ], [ "C6 x S3", 12 ], [ "D12", 12 ], [ "S3 x S3", 12 ],
  [ "S3 x S3 x S3", 4 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 4 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

```

```

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2];;
gap> Length(GcsHNPfalseC2xC2);
3
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2];;
gap> Length(GcsHNPtrueC2xC2);
4
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 4 ] ]
gap> ChG:=CharacteristicSubgroups(G);
[ [3^4:2]E(4), Group([ (5,9)(6,10)(7,11)(8,12), (1,5,9), (2,6,10), (3,7,11),
(4,8,12) ]), Group([ (1,5,9), (2,6,10), (3,7,11), (4,8,12) ]), Group() ]
gap> List(ChG,Order);
[ 648, 162, 81, 1 ]
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))));
[ [ [ 4, 2, 1, 1 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))));
[ [ [ 4, 1, 1, 1 ], 4 ] ]
gap> DihE81:=ChG[2];
Group([ (5,9)(6,10)(7,11)(8,12), (1,5,9), (2,6,10), (3,7,11), (4,8,12) ])
gap> StructureDescription(DihE81);
"(C3 x C3 x C3 x C3) : C2"
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->StructureDescription(Intersection(DihE81,x))));;
[ [ "C2", 3 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(DihE81,x))));;
[ [ "1", 4 ] ]

```

(1-3-5) $G = 12T171 \simeq (C_3)^4 \rtimes (C_4 \times C_2)$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,171);
[3^4:2]E(4)_2
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (2,10)(5,9)(7,11)(8,12), (3,11,7), (5,9)(6,10)(7,11)
(8,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 2 ], [ ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2, 3, 3 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2 ][ ]
[ ][ ]
[ ][ ]
[ ][ ]
[ ][ ]
gap> cG:=cGs[1];;
gap> bG:=cG.MinimalStemExtension;

```

```

<permutation group of size 1296 with 8 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 108 with 5 generators>
gap> KerResHZ(bG,bH:iterator);
[ [ ], [ [ 6, 6 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 0 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=
> x->FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
216
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 4 ], [ [ false ], 212 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
212
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
4
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "((C3 x C3) : C2) x ((C3 x C3) : C2)", 1 ],
  [ "((C3 x C3) : C2) x S3", 4 ], [ "(C3 x C3 x C3 x C3) : C2", 1 ],
  [ "(C3 x C3 x C3 x C3) : C4", 2 ], [ "(C3 x C3 x C3) : C2", 12 ],
  [ "(C3 x C3) : C2", 44 ], [ "(C3 x C3) : C4", 12 ], [ "1", 1 ],
  [ "C2", 3 ], [ "C2 x ((C3 x C3) : C2)", 2 ], [ "C2 x C2", 1 ],
  [ "C3", 12 ], [ "C3 x ((C3 x C3) : C2)", 4 ], [ "C3 x C3", 42 ],
  [ "C3 x C3 x ((C3 x C3) : C2)", 2 ], [ "C3 x C3 x C3", 12 ],
  [ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x S3", 4 ], [ "C3 x S3", 16 ],
  [ "C4", 2 ], [ "C6", 4 ], [ "C6 x C3", 2 ], [ "D12", 4 ], [ "S3", 16 ],
  [ "S3 x S3", 8 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3 x C3 x C3) : (C4 x C2)", 1 ], [ "C2 x ((C3 x C3) : C4)", 2 ],
  [ "C4 x C2", 1 ] ]

```

$$(1\text{-}3\text{-}6) \quad G = 12T194 \simeq (C_3)^4 \rtimes A_4(4) \simeq C_3 \wr A_4(4).$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,194);
[3^4] A(4)=3wrA(4)
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (2,8,11)(3,6,12)(4,7,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 3, 3 ], [ ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2, 3 ]
gap> cGs:=MinimalStemExtensions(G);
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2 ][ ]
[ 3 ][ 3 ]

```

```

gap> cG:=cGs[1];
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 1944 with 8 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 162 with 3 generators>
gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 3 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2 ], [ [ 3, 6 ], [ [ 0, 3 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ ], [ [ 3, 6 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
124
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 16 ], [ [ false ], 108 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
108
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
16
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3 x C3) : C3", 9 ], [ "(C3 x C3) : C2", 1 ],
  [ "(C3 x C3) : C3", 5 ], [ "1", 1 ], [ "C2", 1 ], [ "C3", 11 ],
  [ "C3 x ((C3 x C3 x C3) : C3)", 1 ], [ "C3 x ((C3 x C3) : C2)", 3 ],
  [ "C3 x ((C3 x C3) : C3)", 1 ], [ "C3 x (C9 : C3)", 2 ], [ "C3 x C3", 24 ],
  [ "C3 x C3 x ((C3 x C3) : C2)", 1 ], [ "C3 x C3 x C3", 9 ],
  [ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x S3", 3 ], [ "C3 x S3", 10 ],
  [ "C6", 3 ], [ "C6 x C3", 1 ], [ "C9", 6 ], [ "C9 : C3", 10 ],
  [ "C9 x C3", 2 ], [ "S3", 3 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C3 x C3 x C3) : (C2 x C2)) : C3", 3 ],
  [ "(C3 x C3 x C3) : (C2 x C2)", 1 ], [ "A4", 3 ], [ "C2 x C2", 1 ],
  [ "C3 x (((C3 x C3 x C3) : (C2 x C2)) : C3)", 1 ],
  [ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 1 ], [ "C3 x A4", 1 ],
  [ "C3 x S3 x S3", 1 ], [ "C6 x C2", 1 ], [ "C6 x S3", 1 ], [ "D12", 1 ],
  [ "S3 x S3", 1 ] ]

```

$$(1-3-7) \quad G = 12T261 \simeq (S_3)^4 \rtimes V_4 \simeq S_3 \wr V_4.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,261);
[S(3)^4]E(4)=S(3)wrE(4)
gap> GeneratorsOfGroup(G);
[ (4,8,12), (4,8), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
  (1,7)(2,8)(3,9)(4,10)(5,11)(6,12) ]
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (4,8), (3,11,7), (7,11), (2,10,6), (6,10), (5,9) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2, 2, 2 ],
  [ [ 2, 2, 2, 2 ], [ [ 1, 0, 0, 1 ], [ 0, 1, 0, 1 ], [ 0, 0, 1, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2, 2, 2 ],
  [ [ 2, 2, 2, 2 ], [ [ 1, 0, 0, 1 ], [ 0, 1, 0, 1 ], [ 0, 0, 1, 1 ] ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2, 2, 2, 2 ]

```



```

[ "((C3 x C3) : C2) x S3", 18 ], [ "((C3 x C3) : C2) x S3 x S3", 1 ],
[ "((C3 x C3) : C4) x S3", 2 ], [ "((S3 x S3) : C2) x S3", 2 ],
[ "(C2 x C2 x C2 x C2) : C2", 3 ],
[ "(C3 x C3 x C3 x C3) : ((C2 x C2 x C2 x C2) : C2)", 3 ],
[ "(C3 x C3 x C3 x C3) : ((C4 x C2) : C2)", 6 ],
[ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 4 ],
[ "(C3 x C3 x C3 x C3) : (C2 x C2)", 3 ],
[ "(C3 x C3 x C3 x C3) : (C2 x D8)", 6 ],
[ "(C3 x C3 x C3 x C3) : (C4 x C2)", 6 ], [ "(C3 x C3 x C3 x C3) : C2", 1 ],
[ "(C3 x C3 x C3 x C3) : C4", 3 ], [ "(C3 x C3 x C3 x C3) : D8", 9 ],
[ "(C3 x C3 x C3) : (C2 x C2)", 10 ], [ "(C3 x C3 x C3) : C2", 7 ],
[ "(C3 x C3 x C3) : C4", 3 ], [ "(C3 x C3 x C3) : D8", 9 ],
[ "(C3 x C3) : ((C2 x C2 x C2 x C2) : C2)", 3 ],
[ "(C3 x C3) : ((C4 x C2) : C2)", 9 ], [ "(C3 x C3) : (C2 x D8)", 3 ],
[ "(C3 x C3) : (C4 x C2)", 3 ], [ "(C3 x C3) : C2", 28 ],
[ "(C3 x C3) : C4", 15 ], [ "(C4 x C2) : C2", 6 ], [ "(C6 x C2) : C2", 6 ],
[ "(C6 x S3) : C2", 3 ], [ "(S3 x S3) : C2", 18 ], [ "1", 1 ],
[ "C12", 3 ], [ "C2", 9 ], [ "C2 x (((C3 x C3) : C2) x S3)", 1 ],
[ "C2 x ((C3 x C3 x C3) : (C2 x C2))", 1 ],
[ "C2 x ((C3 x C3 x C3) : C2)", 1 ], [ "C2 x ((C3 x C3) : C2)", 19 ],
[ "C2 x ((C3 x C3) : C4)", 6 ], [ "C2 x ((S3 x S3) : C2)", 6 ],
[ "C2 x (S3 x ((C3 x C3) : C2))", 2 ], [ "C2 x C2", 20 ],
[ "C2 x C2 x ((C3 x C3) : C2)", 3 ], [ "C2 x C2 x C2", 9 ],
[ "C2 x C2 x C2 x C2", 1 ], [ "C2 x C2 x C2 x S3", 1 ],
[ "C2 x C2 x S3", 20 ], [ "C2 x C2 x S3 x S3", 3 ], [ "C2 x C6 x S3", 3 ],
[ "C2 x D8", 6 ], [ "C2 x S3 x S3", 30 ], [ "C2 x S3 x S3 x S3", 1 ],
[ "C3", 6 ], [ "C3 : C4", 3 ], [ "C3 x (((C3 x C3) : C2) x S3)", 1 ],
[ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 4 ],
[ "C3 x ((C3 x C3 x C3) : C2)", 1 ], [ "C3 x ((C3 x C3 x C3) : C4)", 3 ],
[ "C3 x ((C3 x C3 x C3) : D8)", 3 ], [ "C3 x ((C3 x C3) : C2)", 19 ],
[ "C3 x ((C3 x C3) : C4)", 3 ], [ "C3 x ((C6 x C2) : C2)", 3 ],
[ "C3 x ((S3 x S3) : C2)", 3 ], [ "C3 x (C3 : C4)", 3 ],
[ "C3 x (S3 x ((C3 x C3) : C2))", 2 ], [ "C3 x C3", 15 ],
[ "C3 x C3 x ((C3 x C3) : C2)", 6 ], [ "C3 x C3 x C3", 6 ],
[ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x C3 x S3", 1 ],
[ "C3 x C3 x S3", 19 ], [ "C3 x C3 x S3 x S3", 3 ], [ "C3 x C6 x S3", 3 ],
[ "C3 x D8", 3 ], [ "C3 x S3", 47 ], [ "C3 x S3 x S3", 24 ],
[ "C3 x S3 x S3 x S3", 1 ], [ "C4", 6 ], [ "C4 x C2", 6 ], [ "C4 x S3", 3 ],
[ "C6", 20 ], [ "C6 x ((C3 x C3) : C2)", 3 ], [ "C6 x C2", 13 ],
[ "C6 x C2 x C2", 1 ], [ "C6 x C3", 13 ], [ "C6 x C3 x C3", 1 ],
[ "C6 x C6", 3 ], [ "C6 x S3", 30 ], [ "C6 x S3 x S3", 3 ], [ "D12", 53 ],
[ "D24", 3 ], [ "D8", 12 ], [ "D8 x S3", 3 ], [ "S3", 26 ],
[ "S3 x ((C3 x C3) : C2)", 7 ], [ "S3 x ((C3 x C3) : C2) x S3", 2 ],
[ "S3 x ((C3 x C3) : C4)", 1 ], [ "S3 x ((S3 x S3) : C2)", 1 ],
[ "S3 x S3", 67 ], [ "S3 x S3 x S3", 14 ], [ "S3 x S3 x S3 x S3", 1 ] ]
gap> Collected(List(GcsHNtrue,x->StructureDescription(Representative(x))));
[ [ "((C2 x C2 x C2 x C2) : C2) : C2", 1 ],
[ "(C2 x C2 x C2) : (C2 x C2)", 1 ], [ "(C2 x C2 x C2) : C4", 3 ],
[ "(C3 x C3 x C3 x C3) : (((C2 x C2 x C2 x C2) : C2) : C2)", 1 ],
[ "(C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : (C2 x C2))", 1 ],
[ "(C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : C4)", 3 ],
[ "(C3 x C3 x C3 x C3) : ((C4 x C2) : C2)", 3 ],
[ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 1 ],
[ "(C3 x C3 x C3 x C3) : (C2 x D8)", 3 ],
[ "(C3 x C3 x C3 x C3) : (C4 x C2)", 3 ], [ "(C3 x C3 x C3 x C3) : D8", 3 ],
[ "(C3 x C3 x C3 x C3) : Q8", 1 ], [ "(C3 x C3 x C3) : (C2 x C2)", 1 ],
[ "(C3 x C3) : Q8", 1 ], [ "(C4 x C2) : C2", 3 ], [ "(S3 x S3) : C2", 6 ],
[ "C2 x ((C3 x C3) : C4)", 3 ], [ "C2 x ((S3 x S3) : C2)", 3 ],
[ "C2 x C2", 1 ], [ "C2 x C2 x C2", 1 ], [ "C2 x C2 x S3", 1 ],
[ "C2 x D8", 3 ], [ "C2 x S3 x S3", 3 ],
[ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 1 ], [ "C3 x S3 x S3", 3 ],
[ "C4 x C2", 3 ], [ "C6 x C2", 1 ], [ "C6 x S3", 3 ], [ "D12", 3 ],

```

```

[ "D8", 3 ], [ "Q8", 1 ], [ "S3 x S3", 3 ], [ "S3 x S3 x S3", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));;
[ [ "(C2 x C2 x C2) : C4", 3 ], [ "C2 x C2", 1 ], [ "C4 x C2", 3 ],
  [ "D8", 3 ], [ "Q8", 1 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));;
[ [ [ 4, 2 ], 1 ], [ [ 8, 2 ], 3 ], [ [ 8, 3 ], 3 ], [ [ 8, 4 ], 1 ],
  [ [ 32, 6 ], 3 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->Order(Representative(x))=4 and IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
20
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=4 and IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
1
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2 ], 3 ], [ [ 2, 2, 2 ], 4 ], [ [ 2, 2, 2, 2 ], 7 ],
  [ [ 2, 2, 2, 2, 4 ], 3 ], [ [ 2, 2, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 1 ] ]
gap> ChG:=CharacteristicSubgroups(G);
[ [S(3)^4]E(4)=S(3)wrE(4), <permutation group of size 1296 with 8 generators>,
<permutation group of size 2592 with 9 generators>, Group([ (3,7,11)(4,8)
(5,9), (2,10)(4,8), (4,8)(7,11), (1,5,9), (2,6,10), (3,7,11), (4,8,12) ]),
Group([ (2,10)(3,11)(4,8)(5,9), (1,5,9), (2,6,10), (3,7,11), (4,8,12) ]),
Group([ (1,5,9), (2,6,10), (3,7,11), (4,8,12) ]), Group() ]]
gap> List(ChG,StructureDescription);
[ ("(C3 x C3 x C3 x C3) : (((C2 x C2 x C2 x C2) : C2) : C2)",
  "S3 x S3 x S3 x S3", "(C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : (C2 x C2))",
  "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", "(C3 x C3 x C3 x C3) : C2",
  "C3 x C3 x C3 x C3", "1" ]
gap> List(ChG,Order);
[ 5184, 1296, 2592, 648, 162, 81, 1 ]
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))));;
[ [ [ 4, 2, 4, 2, 1, 1, 1 ], 3 ],
  [ [ 4, 2, 4, 2, 2, 1, 1 ], 3 ],
  [ [ 4, 4, 2, 2, 1, 1, 1 ], 9 ],
  [ [ 4, 4, 2, 2, 2, 1, 1 ], 1 ],
  [ [ 4, 4, 4, 4, 1, 1, 1 ], 1 ],
  [ [ 4, 4, 4, 4, 2, 1, 1 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))));;
[ [ [ 4, 1, 4, 1, 1, 1, 1 ], 1 ] ]
gap> S3xS3xS3xS3:=ChG[2];
S3 x S3 x S3 x S3
gap> DG:=DerivedSubgroup(G);
Group([ (4,12,8), (3,11,7)(4,8,12), (4,8)(7,11), (2,10,6)(4,8,12), (2,10)
(4,8), (1,9)(2,10,6)(7,11), (3,7,11)(4,8)(5,9) ])
gap> Position(ChG,DG);
4
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x))));;
[ [ "C2", 6 ], [ "C2 x C2", 14 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x))));;

```

```

[ [ "1", 1 ] ]

gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->StructureDescription(Intersection(DG,x))));

[ [ "C2", 16 ], [ "C2 x C2", 4 ] ]

gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(DG,x))));

[ [ "1", 1 ] ]

gap> GcsHNPfalseC4xC2:=Filtered(GcsHNPfalse, # G(8,2)=C4xC2
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,2]);
gap> Length(GcsHNPfalseC4xC2);
6
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,2]);
gap> Length(GcsHNPtrueC4xC2);
3
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));

[ [ [ 2, 2, 4, 4 ], 6 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));

[ [ [ 4, 8 ], 3 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));

[ [ [ 8, 4, 4, 2, 1, 1 ], 3 ],
  [ [ 8, 4, 8, 4, 2, 1, 1 ], 3 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));

[ [ [ 8, 2, 8, 2, 2, 1, 1 ], 3 ] ]

gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x))));

[ [ [ "C4 x C2", "C2 x C2", "C2 x C2", "C2 x C2", "C2", "1", "1" ], 3 ],
  [ [ "C4 x C2", "C2 x C2", "C4 x C2", "C2 x C2", "C2", "1", "1" ], 3 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x))));

[ [ [ "C4 x C2", "C2", "C4 x C2", "C2", "C2", "1", "1" ], 3 ] ]

gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x))));

[ [ "C2 x C2", 6 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x))));

[ [ "C2", 3 ] ]

gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->StructureDescription(Intersection(DG,x))));

[ [ "C2 x C2", 6 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->StructureDescription(Intersection(DG,x))));

[ [ "C2", 3 ] ]

gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue, # G(8,3)=D4
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,3]);
gap> Length(GcsHNPtrueD4);
12
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,3]);
gap> Length(GcsHNPtrueD4);
3
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));

[ [ [ 2, 2, 2, 2, 4 ], 3 ], [ [ 2, 2, 4, 4 ], 9 ] ]

gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));
```

```

[ [ [ 4, 8 ], 3 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))); 
[ [ [ 8, 4, 4, 2, 1, 1, 1 ], 6 ],
  [ [ 8, 4, 8, 4, 2, 1, 1 ], 6 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))); 
[ [ [ 8, 2, 8, 2, 2, 1, 1 ], 3 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x)))); 
[ [ [ "D8", "C2 x C2", "C2 x C2", "C2", "1", "1", "1" ], 6 ],
  [ [ "D8", "C2 x C2", "D8", "C2 x C2", "C2", "1", "1" ], 6 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x)))); 
[ [ [ "D8", "C2", "D8", "C2", "C2", "1", "1" ], 3 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x)))); 
[ [ "C2 x C2", 12 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x)))); 
[ [ "C2", 3 ] ]

gap> Number(Gcs, # G(8,4)=Q8
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,4]);
1

gap> Number(Gcs, # G(32,6)=(C2)^3:C4
> x->Order(Representative(x))=32 and IdSmallGroup(Representative(x))=[32,6]);
3

gap> Number(GcsHNPtrueMin,
> x->Order(Representative(x))=32 and IdSmallGroup(Representative(x))=[32,6]);
3

```

$$(1-3-8) \quad G = 12T280 \simeq (S_3)^4 \rtimes A_4(4) \simeq S_3 \wr A_4(4).$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,280);
[S(3)^4]A(4)=S(3)wrA(4)
gap> GeneratorsOfGroup(G);
[ (4,8,12), (4,8), (2,8,11)(3,6,12)(4,7,10), (1,7,10)(2,5,11)(3,6,9) ]
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (4,8), (2,8,11)(3,6,12)(4,7,10), (5,9) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 6 ], [ [ 1, 0 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 2, 6 ], [ [ 1, 0 ] ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2, 2 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2 ][ 2 ]
[ 2, 2 ][ 2 ]
[ 2 ][ 2 ]
gap> cG:=cGs[2];;
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 31104 with 12 generators>
gap> bH:=PreImage(cG.epi,H);

```

```

<permutation group of size 2592 with 5 generators>
gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2, 2 ], [ [ 2, 2, 6 ], [ [ 1, 1, 0 ], [ 0, 0, 3 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ 2 ], [ [ 2, 2, 6 ], [ [ 1, 1, 0 ] ] ] ]
gap> HNPtruefalsefn:=x->Number(
> FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[2][2],
> y->y[3]=3)>0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
458
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf));
[ [ [ true ], 51 ], [ [ false ], 407 ] ]
gap> GcsHNPFalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPFalse);
407
gap> GcsHNPTrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPTrue);
51
gap> Collected(List(GcsHNPFalse,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2) : C3", 1 ],
[ "(C3 x C3 x C3) : (C2 x C2) : C3", 2 ],
[ "(C3 x C3 x C3) : (C2 x C2) x S3", 1 ],
[ "(C3 x C3 x C3) : C2) x S3", 1 ], [ "(C3 x C3 x C3) : C3) : C2", 4 ],
[ "(C3 x C3) : C2) x ((C3 x C3) : C2)", 2 ],
[ "(C3 x C3) : C2) x S3", 7 ], [ "(C3 x C3) : C2) x S3 x S3", 1 ],
[ "(C3 x C3) : C4) x S3", 1 ], [ "(C2 x C2 x C2 x C2) : C2", 1 ],
[ "(C3 x ((C3 x C3 x C3) : C3)) : C2", 1 ],
[ "(C3 x ((C3 x C3) : C3)) : C2", 1 ],
[ "(C3 x C3 x C3 x C3) : ((C2 x C2 x C2 x C2) : C2)", 1 ],
[ "(C3 x C3 x C3 x C3) : ((C4 x C2) : C2)", 2 ],
[ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 2 ],
[ "(C3 x C3 x C3 x C3) : (C2 x C2)", 1 ],
[ "(C3 x C3 x C3 x C3) : (C2 x D8)", 2 ],
[ "(C3 x C3 x C3 x C3) : (C4 x C2)", 2 ], [ "(C3 x C3 x C3 x C3) : C2", 1 ],
[ "(C3 x C3 x C3 x C3) : C4", 1 ], [ "(C3 x C3 x C3 x C3) : D8", 3 ],
[ "(C3 x C3 x C3) : (C2 x C2)", 4 ], [ "(C3 x C3 x C3) : C2", 5 ],
[ "(C3 x C3 x C3) : C3", 4 ], [ "(C3 x C3 x C3) : C4", 1 ],
[ "(C3 x C3 x C3) : D8", 3 ],
[ "(C3 x C3) : ((C2 x C2 x C2 x C2) : C2)", 1 ],
[ "(C3 x C3) : ((C4 x C2) : C2)", 3 ], [ "(C3 x C3) : (C2 x D8)", 1 ],
[ "(C3 x C3) : (C4 x C2)", 1 ], [ "(C3 x C3) : C2", 12 ],
[ "(C3 x C3) : C3", 3 ], [ "(C3 x C3) : C4", 5 ], [ "(C3 x C3) : C6", 4 ],
[ "(C4 x C2) : C2", 2 ], [ "(C6 x C2) : C2", 2 ], [ "(C6 x S3) : C2", 1 ],
[ "(S3 x S3 x S3) : C3", 3 ], [ "(S3 x S3) : C2", 6 ], [ "1", 1 ],
[ "A4", 2 ], [ "A4 x S3", 2 ], [ "C12", 1 ], [ "C18", 1 ], [ "C2", 5 ],
[ "C2 x (((C3 x C3 x C3) : (C2 x C2)) : C3) : C2)", 1 ],
[ "C2 x (((C3 x C3 x C3) : (C2 x C2)) : C3)", 1 ],
[ "C2 x (((C3 x C3 x C3) : C3) : C2)", 1 ],
[ "C2 x (((C3 x C3) : C2) x S3)", 1 ],
[ "C2 x ((C3 x C3 x C3) : (C2 x C2))", 1 ],
[ "C2 x ((C3 x C3 x C3) : C2)", 1 ], [ "C2 x ((C3 x C3 x C3) : C3)", 1 ],
[ "C2 x ((C3 x C3) : C2)", 7 ], [ "C2 x ((C3 x C3) : C3)", 1 ],
[ "C2 x ((C3 x C3) : C4)", 2 ], [ "C2 x ((C3 x C3) : C6)", 1 ],
[ "C2 x ((S3 x S3) : C2)", 2 ], [ "C2 x (C9 : C3)", 1 ], [ "C2 x A4", 4 ],

```

```

[ "C2 x C2", 8 ], [ "C2 x C2 x ((C3 x C3) : C2)", 1 ],
[ "C2 x C2 x A4", 1 ], [ "C2 x C2 x C2", 5 ], [ "C2 x C2 x C2 x C2", 1 ],
[ "C2 x C2 x C2 x S3", 1 ], [ "C2 x C2 x S3", 8 ],
[ "C2 x C2 x S3 x S3", 1 ], [ "C2 x C6 x S3", 1 ], [ "C2 x D8", 2 ],
[ "C2 x S3 x A4", 1 ], [ "C2 x S3 x S3", 10 ], [ "C2 x S3 x S3 x S3", 1 ],
[ "C3", 6 ], [ "C3 : C4", 1 ],
[ "C3 x (((C3 x C3 x C3) : (C2 x C2)) : C3) : C2)", 1 ],
[ "C3 x (((C3 x C3 x C3) : (C2 x C2)) : C3)", 1 ],
[ "C3 x (((C3 x C3 x C3) : C3) : C2)", 1 ],
[ "C3 x (((C3 x C3) : C2) x S3)", 1 ],
[ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 2 ],
[ "C3 x ((C3 x C3 x C3) : C2)", 1 ], [ "C3 x ((C3 x C3 x C3) : C3)", 1 ],
[ "C3 x ((C3 x C3 x C3) : C4)", 1 ], [ "C3 x ((C3 x C3 x C3) : D8)", 1 ],
[ "C3 x ((C3 x C3) : C2)", 8 ], [ "C3 x ((C3 x C3) : C3)", 1 ],
[ "C3 x ((C3 x C3) : C4)", 1 ], [ "C3 x ((C3 x C3) : C6)", 1 ],
[ "C3 x ((C6 x C2) : C2)", 1 ], [ "C3 x ((S3 x S3) : C2)", 1 ],
[ "C3 x (C3 : C4)", 1 ], [ "C3 x (C9 : C3)", 1 ], [ "C3 x A4", 1 ],
[ "C3 x C3", 11 ], [ "C3 x C3 x ((C3 x C3) : C2)", 2 ],
[ "C3 x C3 x C3", 5 ], [ "C3 x C3 x C3 x C3", 1 ],
[ "C3 x C3 x C3 x S3", 1 ], [ "C3 x C3 x S3", 9 ],
[ "C3 x C3 x S3 x S3", 1 ], [ "C3 x C6 x S3", 1 ], [ "C3 x D8", 1 ],
[ "C3 x S3", 23 ], [ "C3 x S3 x S3", 9 ], [ "C3 x S3 x S3 x S3", 1 ],
[ "C4", 2 ], [ "C4 x C2", 2 ], [ "C4 x S3", 1 ], [ "C6", 12 ],
[ "C6 x ((C3 x C3) : C2)", 1 ], [ "C6 x A4", 1 ], [ "C6 x C2", 6 ],
[ "C6 x C2 x C2", 1 ], [ "C6 x C3", 7 ], [ "C6 x C3 x C3", 1 ],
[ "C6 x C6", 1 ], [ "C6 x S3", 12 ], [ "C6 x S3 x S3", 1 ], [ "C9", 2 ],
[ "C9 : C3", 3 ], [ "C9 x C3", 1 ], [ "C9 x S3", 1 ], [ "D12", 19 ],
[ "D24", 1 ], [ "D8", 4 ], [ "D8 x S3", 1 ], [ "S3", 12 ],
[ "S3 x (((C3 x C3 x C3) : (C2 x C2)) : C3) : C2)", 1 ],
[ "S3 x (((C3 x C3 x C3) : (C2 x C2)) : C3)", 1 ],
[ "S3 x (((C3 x C3 x C3) : C3) : C2)", 1 ],
[ "S3 x ((C3 x C3 x C3) : C3)", 1 ], [ "S3 x ((C3 x C3) : C2)", 2 ],
[ "S3 x ((C3 x C3) : C3)", 1 ], [ "S3 x ((C3 x C3) : C6)", 1 ],
[ "S3 x ((S3 x S3) : C2)", 1 ], [ "S3 x (C9 : C3)", 1 ], [ "S3 x S3", 23 ],
[ "S3 x S3 x S3", 6 ], [ "S3 x S3 x S3 x S3", 1 ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(((C2 x C2 x C2 x C2) : C2) : C2) : C3", 1 ],
[ "(((C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : (C2 x C2))) : C3) : C2", 1 ],
[ "((C2 x C2 x C2 x C2) : C2) : C2", 1 ],
[ "((C2 x C2 x C2) : (C2 x C2)) : C3", 1 ],
[ "((C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : (C2 x C2))) : C3", 1 ],
[ "((C3 x C3 x C3 x C3) : (C2 x C2 x C2)) : C3", 1 ],
[ "((C3 x C3 x C3 x C3) : Q8) : C3", 1 ],
[ "((C3 x C3 x C3) : (C2 x C2)) : C3", 2 ], [ "((C3 x C3) : Q8) : C3", 1 ],
[ "(C2 x C2 x C2) : (C2 x C2)", 1 ], [ "(C2 x C2 x C2) : C4", 1 ],
[ "(C3 x C3 x C3 x C3) : (((C2 x C2 x C2 x C2) : C2) : C2)", 1 ],
[ "(C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : (C2 x C2))", 1 ],
[ "(C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : C4)", 1 ],
[ "(C3 x C3 x C3 x C3) : ((C4 x C2) : C2)", 1 ],
[ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 1 ],
[ "(C3 x C3 x C3 x C3) : (C2 x D8)", 1 ],
[ "(C3 x C3 x C3 x C3) : (C4 x C2)", 1 ], [ "(C3 x C3 x C3 x C3) : D8", 1 ],
[ "(C3 x C3 x C3 x C3) : Q8", 1 ], [ "(C3 x C3 x C3) : (C2 x C2)", 1 ],
[ "(C3 x C3) : Q8", 1 ], [ "(C4 x C2) : C2", 1 ],
[ "(S3 x S3 x S3) : C3", 1 ], [ "(S3 x S3) : C2", 2 ], [ "A4", 2 ],
[ "A4 x S3", 1 ], [ "C2 x ((C3 x C3) : C4)", 1 ],
[ "C2 x ((S3 x S3) : C2)", 1 ], [ "C2 x A4", 1 ], [ "C2 x C2", 1 ],
[ "C2 x C2 x C2", 1 ], [ "C2 x C2 x S3", 1 ], [ "C2 x D8", 1 ],
[ "C2 x S3 x S3", 1 ], [ "C3 x (((C3 x C3 x C3) : (C2 x C2)) : C3)", 1 ],
[ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 1 ], [ "C3 x A4", 1 ],
[ "C3 x S3 x S3", 1 ], [ "C4 x C2", 1 ], [ "C6 x C2", 1 ], [ "C6 x S3", 1 ],
[ "D12", 1 ], [ "D8", 1 ], [ "Q8", 1 ], [ "S3 x S3", 1 ],

```

```

[ "S3 x S3 x S3", 1 ], [ "SL(2,3)", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x)))); 
[ [ "(C2 x C2 x C2) : C4", 1 ], [ "C2 x C2", 1 ], [ "C4 x C2", 1 ],
  [ "D8", 1 ], [ "Q8", 1 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x)))); 
[ [ [ 4, 2 ], 1 ], [ [ 8, 2 ], 1 ], [ [ 8, 3 ], 1 ], [ [ 8, 4 ], 1 ],
  [ [ 32, 6 ], 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
true

gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue, # G(4,2)=C2xC2
> x->Order(Representative(x))=4 and IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
8
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=4 and IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
1
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 2, 2 ], 1 ], [ [ 2, 2, 2 ], 2 ], [ [ 2, 2, 2, 2 ], 3 ],
  [ [ 2, 2, 2, 4 ], 1 ], [ [ 2, 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 4, 4, 4 ], 1 ] ]
gap> ChG:=CharacteristicSubgroups(G);;
gap> ChG=NormalSubgroups(G);
true
gap> List(ChG,StructureDescription);
[ "(((C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : (C2 x C2))) : C3) : C2",
  "((C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : (C2 x C2))) : C3",
  "(C3 x C3 x C3 x C3) : (((C2 x C2 x C2 x C2) : C2) : C2)",
  "S3 x S3 x S3 x S3", "(C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : (C2 x C2))",
  "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", "(C3 x C3 x C3 x C3) : C2",
  "C3 x C3 x C3 x C3", "1" ]
gap> List(ChG,Order);
[ 15552, 7776, 5184, 1296, 2592, 648, 162, 81, 1 ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))); 
[ [ [ 4, 2, 4, 4, 2, 2, 1, 1, 1 ], 3 ],
  [ [ 4, 2, 4, 4, 2, 2, 2, 1, 1 ], 1 ],
  [ [ 4, 4, 4, 2, 4, 2, 1, 1, 1 ], 1 ],
  [ [ 4, 4, 4, 2, 4, 2, 2, 1, 1 ], 1 ],
  [ [ 4, 4, 4, 4, 4, 4, 1, 1, 1 ], 1 ],
  [ [ 4, 4, 4, 4, 4, 2, 1, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))); 
[ [ [ 4, 4, 4, 1, 4, 1, 1, 1, 1 ], 1 ] ]
gap> S3xS3xS3xS3:=ChG[4];
S3 x S3 x S3 x S3
gap> T261:=ChG[3];
(C3 x C3 x C3 x C3) : (((C2 x C2 x C2 x C2) : C2) : C2)
gap> T261=TransitiveGroup(12,261);
true
gap> DT261:=DerivedSubgroup(T261);
Group([ (1,5,9)(2,6,10)(4,8)(7,11), (1,5,9)(2,6,10)(4,12)(7,11), (1,5)(3,11)
(4,12,8), (1,5)(2,6)(3,7)(8,12) ])
gap> Position(ChG,DT261);
6
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x))));
```

```

[ [ "C2", 2 ], [ "C2 x C2", 6 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x)))); 
[ [ "1", 1 ] ]

gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->StructureDescription(Intersection(DT261,x)))); 
[ [ "C2", 6 ], [ "C2 x C2", 2 ] ]

gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Intersection(DT261,x)))); 
[ [ "1", 1 ] ]

gap> GcsHNPfalseC4xC2:=Filtered(GcsHNPfalse, # G(8,2)=C4xC2
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPfalseC4xC2);
2
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPtrueC4xC2);
1
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 2, 2, 4, 4 ], 2 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 4, 8 ], 1 ] ]

gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))); 
[ [ [ 8, 4, 8, 4, 4, 2, 1, 1 ], 1 ],
  [ [ 8, 8, 4, 8, 4, 2, 1, 1 ], 1 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))); 
[ [ [ 8, 8, 8, 2, 8, 2, 2, 1, 1 ], 1 ] ]

gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x))))); 
[ [ [ "C4 x C2", "C2 x C2", "C4 x C2", "C2 x C2", "C2 x C2", "C2 x C2",
      "C2", "1", "1" ], 1 ],
  [ [ "C4 x C2", "C4 x C2", "C4 x C2", "C2 x C2", "C4 x C2", "C2 x C2",
      "C2", "1", "1" ], 1 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x))))); 
[ [ [ "C4 x C2", "C4 x C2", "C4 x C2", "C2", "C4 x C2", "C2", "C2", "1",
      "1" ], 1 ] ]

gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x)))); 
[ [ "C2 x C2", 2 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x)))); 
[ [ "C2", 1 ] ]

gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->StructureDescription(Intersection(DT261,x)))); 
[ [ "C2 x C2", 2 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->StructureDescription(Intersection(DT261,x)))); 
[ [ "C2", 1 ] ]

gap> GcsHNPfalseD4:=Filtered(GcsHNPfalse, # G(8,3)=D4
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPfalseD4);
4
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);

```

```

1
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 2, 2, 2, 2, 4 ], 1 ], [ [ 2, 2, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 4, 8 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))); 
[ [ [ 8, 4, 8, 4, 4, 2, 1, 1, 1 ], 2 ],
  [ [ 8, 8, 8, 4, 8, 4, 2, 1, 1 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))); 
[ [ [ 8, 8, 8, 2, 8, 2, 1, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x))))); 
[ [ [ "D8", "C2 x C2", "D8", "C2 x C2", "C2 x C2", "C2", "1", "1", "1" ], 2 ],
  [ [ "D8", "D8", "D8", "C2 x C2", "D8", "C2 x C2", "C2", "1", "1" ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x))))); 
[ [ [ "D8", "D8", "D8", "C2", "D8", "C2", "1", "1" ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x)))); 
[ [ "C2 x C2", 4 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->StructureDescription(Intersection(S3xS3xS3xS3,x)))); 
[ [ "C2", 1 ] ]

gap> Number(Gcs, # G(8,4)=Q8
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,4]);
1

gap> Number(Gcs, # G(32,6)=(C2)^3:C4
> x->Order(Representative(x))=32 and IdSmallGroup(Representative(x))=[32,6]);
1

```

Example 7.4 ($G = 12Tm$ ($m = 54, 56, 59, 61, 66, 88, 92, 93, 100, 102, 144, 188, 230, 255$))).

(2-1-1) $G = 12T54 \simeq (S_4 \times C_2) \rtimes C_2$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,54);
[(1/2.2^2)^3]D(6)_4
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3), (1,5,9)(2,6,10)(3,7,11)(4,8,12), (2,3)(4,9)(5,8)(6,10)(7,11),
  (1,2)(3,12)(4,11)(5,10)(6,9)(7,8) ]
gap> H:=Stabilizer(G,1);
Group([ (2,3)(4,9)(5,8)(6,10)(7,11), (8,9)(10,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 0 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
56
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 13 ], [ [ false ], 43 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
```

```

> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
43
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
13
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "A4", 1 ], [ "C12", 1 ], [ "C2", 5 ], [ "C2 x A4", 1 ],
  [ "C2 x C2", 8 ], [ "C2 x C2 x C2", 2 ], [ "C2 x D8", 1 ], [ "C2 x S4", 1 ],
  [ "C3", 1 ], [ "C4", 4 ], [ "C4 x A4", 1 ], [ "C4 x C2", 3 ],
  [ "C4 x C2 x C2", 1 ], [ "C6", 1 ], [ "D12", 2 ], [ "D24", 1 ],
  [ "D8", 5 ], [ "S3", 2 ], [ "S4", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C2 x S4) : C2", 1 ], [ "(C4 x C2 x C2) : C2", 1 ],
  [ "(C4 x C2) : C2", 2 ], [ "C2 x C2", 1 ], [ "C2 x C2 x C2", 1 ],
  [ "C2 x D8", 2 ], [ "C2 x S4", 1 ], [ "C4 : C4", 1 ], [ "C4 x C2", 1 ],
  [ "D8", 1 ], [ "S4", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 1 ], [ "C4 x C2", 1 ], [ "D8", 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
8
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
1
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2, 2, 2 ], 2 ],
  [ [ 2, 2, 2, 2, 4 ], 1 ], [ [ 2, 2, 4, 4 ], 2 ], [ [ 2, 4, 4 ], 1 ],
  [ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2, 2, 2 ], 1 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (1,12)(2,3)(4,5)(6,7), (1,8,5)(2,11,6)(3,10,7)(4,12,9), (1,12)(2,3)
(4,5)(6,7)(8,9)(10,11) ])
gap> StructureDescription(DG);
"C2 x A4"
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DG,x))]));
[ [ [ [ 2, 2, 2, 2 ], "C2 x C2" ], 1 ],
  [ [ [ 2, 2, 2, 2, 2 ], "C2 x C2" ], 2 ],
  [ [ [ 2, 2, 2, 2, 4 ], "C2" ], 1 ], [ [ [ 2, 2, 4, 4 ], "C2" ], 2 ],
  [ [ [ 2, 4, 4 ], "C2" ], 1 ], [ [ [ 4, 4, 4 ], "C2" ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DG,x))]));
[ [ [ [ 2, 2, 2, 2, 2, 2 ], "C2" ], 1 ] ]

gap> GcsHNPfalseC4xC2:=Filtered(GcsHNPfalse, # G(8,2)=C4xC2
> x->IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPfalseC4xC2);

```

```

3
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPtrueC4xC2);
1
gap> IsInvariantUnderAutG(GcsHNPtrueC4xC2);
false
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ] ]

gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
5
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
1
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ], [ [ 2, 4, 4 ], 1 ], [ [ 4, 4, 4 ], 1 ],
[ [ 4, 8 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DG,x))]));
[ [ [ [ 2, 2, 4, 4 ], "C2 x C2" ], 1 ], [ [ [ 2, 4, 4 ], "C2 x C2" ], 1 ],
[ [ [ 4, 4, 4 ], "C2 x C2" ], 1 ], [ [ [ 4, 8 ], "C2" ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DG,x))]));
[ [ [ [ 2, 2, 4, 4 ], "C2 x C2" ], 1 ] ]
gap> DDG:=DerivedSubgroup(DG);
Group([ (4,5)(6,7)(8,9)(10,11), (1,12)(2,3)(4,5)(6,7) ])
gap> StructureDescription(DDG);
"C2 x C2"
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DDG,x))]));
[ [ [ [ 2, 2, 4, 4 ], "C2" ], 1 ], [ [ [ 2, 4, 4 ], "C2" ], 1 ],
[ [ [ 4, 4, 4 ], "C2 x C2" ], 1 ], [ [ [ 4, 8 ], "1" ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DDG,x))]));
[ [ [ [ 2, 2, 4, 4 ], "C2 x C2" ], 1 ] ]

```

$$(2\text{-}1\text{-}2) \quad G = 12T56 \simeq ((C_2)^4 \rtimes C_3) \times C_2.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,56);
[1/2..2^6]3
gap> GeneratorsOfGroup(G);
[ (3,9)(6,12), (1,10)(3,12)(4,7)(6,9), (1,5,9)(2,6,10)(3,7,11)(4,8,12) ]
gap> H:=Stabilizer(G,1);
Group([ (3,9)(6,12), (2,8)(5,11), (2,5)(3,12)(6,9)(8,11) ])

```

```

gap> FirstObstructionN(G,H).ker;
[ [ 2, 2 ], [ [ 2, 2, 2 ], [ [ 1, 1, 0 ], [ 0, 0, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 2, 2, 2 ], [ [ 1, 1, 0 ] ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2, 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->Number(FirstObstructionDr(G,x,H).Dr[2][2],y->y[3]=1)>0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
148
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf));
[ [ [ true ], 35 ], [ [ false ], 113 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
113
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
35
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "A4", 3 ], [ "C2", 11 ], [ "C2 x A4", 3 ], [ "C2 x C2", 51 ],
  [ "C2 x C2 x C2", 39 ], [ "C2 x C2 x C2 x C2", 3 ], [ "C3", 1 ],
  [ "C6", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C2 x C2 x C2 x C2) : C3", 1 ], [ "A4", 2 ],
  [ "C2 x ((C2 x C2 x C2 x C2) : C3)", 1 ], [ "C2 x A4", 2 ],
  [ "C2 x C2", 4 ], [ "C2 x C2 x C2", 16 ], [ "C2 x C2 x C2 x C2", 8 ],
  [ "C2 x C2 x C2 x C2 x C2", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 4 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false
gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse,
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPfalseC2xC2);
51
gap> Sum(GcsHNPfalseC2xC2,Size);
147
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPtrueC2xC2);
4
gap> Sum(GcsHNPtrueC2xC2,Size);
8
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2, 2, 2 ], 6 ],
  [ [ 2, 2, 2, 2, 4 ], 20 ], [ [ 2, 2, 4 ], 4 ], [ [ 2, 2, 4, 4 ], 14 ],
  [ [ 4, 4 ], 2 ], [ [ 4, 4, 4 ], 4 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2, 2, 2 ], 4 ] ]
gap> GcsHNPfalse222222C2xC2:=Filtered(GcsHNPfalseC2xC2,
> x->SortedList(List(Orbits(Representative(x)),Length))=[2,2,2,2,2]);
gap> Length(GcsHNPfalse222222C2xC2);
6
gap> Sum(GcsHNPfalse222222C2xC2,Size);

```

```

16
gap> ChG:=CharacteristicSubgroups(G);;
gap> Length(ChG);
6
gap> List(ChG,Order);
[ 96, 48, 32, 2, 16, 1 ]
gap> Collected(List(List(GcsHNPFalse222222C2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));;
[ [ [ 4, 2, 4, 1, 2, 1 ], 4 ], [ [ 4, 2, 4, 2, 2, 1 ], 1 ],
  [ [ 4, 4, 4, 1, 4, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPFtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));;
[ [ [ 4, 2, 4, 1, 2, 1 ], 2 ], [ [ 4, 4, 4, 1, 4, 1 ], 2 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (1,7)(3,9)(4,10)(6,12), (2,5)(3,12)(6,9)(8,11), (1,4)(2,8)(3,12)(5,11)
(6,9)(7,10), (1,10)(3,12)(4,7)(6,9) ])
gap> StructureDescription(DG);
"C2 x C2 x C2 x C2"
gap> ZG:=Centre(G);
Group([ (1,7)(2,8)(3,9)(4,10)(5,11)(6,12) ])
gap> StructureDescription(ZG);
"C2"
gap> Position(ChG,DG);
5
gap> Position(ChG,ZG);
4
gap> Collected(List(List(GcsHNPFalse222222C2xC2,Representative),
> x->List([DG,ZG],y->StructureDescription(Intersection(y,x))));;
[ [ [ "C2", "1" ], 4 ], [ [ "C2", "C2" ], 1 ], [ [ "C2 x C2", "1" ], 1 ] ]
gap> Collected(List(List(GcsHNPFtrueC2xC2,Representative),
> x->List([DG,ZG],y->StructureDescription(Intersection(y,x))));;
[ [ [ "C2", "1" ], 2 ], [ [ "C2 x C2", "1" ], 2 ] ]
gap> GcsHNPFfalse222222C2xC2D2Z1:=Filtered(GcsHNPFfalse222222C2xC2,
> x->List([DG,ZG],y->Order(Intersection(y,Representative(x))))=[2,1]);
[ Group( [ ( 1,10)( 3,12)( 4, 7)( 6, 9), ( 2, 8)( 5,11) ] )^G,
  Group( [ ( 1,10)( 3, 6)( 4, 7)( 9,12), ( 2, 8)( 5,11) ] )^G,
  Group( [ ( 1, 4)( 3,12)( 6, 9)( 7,10), ( 2, 8)( 5,11) ] )^G,
  Group( [ ( 1, 4)( 3, 6)( 7,10)( 9,12), ( 2, 8)( 5,11) ] )^G ]
gap> GcsHNPFtrueC2xC2D2Z1:=Filtered(GcsHNPFtrueC2xC2,
> x->List([DG,ZG],y->Order(Intersection(y,Representative(x))))=[2,1]);
[ Group( [ ( 1,10)( 2, 5)( 4, 7)( 8,11), ( 1,10)( 3, 6)( 4, 7)( 9,12) ] )^G,
  Group( [ ( 1, 4)( 2, 5)( 7,10)( 8,11), ( 1, 4)( 3, 6)( 7,10)( 9,12) ] )^G ]
gap> GcsHNPFfalse222222C2xC2D4Z1:=Filtered(GcsHNPFfalse222222C2xC2,
> x->List([DG,ZG],y->Order(Intersection(y,Representative(x))))=[4,1]);
[ Group( [ ( 2, 8)( 3, 9)( 5,11)( 6,12), ( 1, 7)( 3, 9)( 4,10)( 6,12) ] )^G ]
gap> GcsHNPFtrueC2xC2D4Z1:=Filtered(GcsHNPFtrueC2xC2,
> x->List([DG,ZG],y->Order(Intersection(y,Representative(x))))=[4,1]);
[ Group( [ ( 1,10)( 2, 5)( 4, 7)( 8,11), ( 1,10)( 3,12)( 4, 7)( 6, 9) ] )^G,
  Group( [ ( 1, 4)( 2,11)( 5, 8)( 7,10), ( 1, 4)( 3, 6)( 7,10)( 9,12) ] )^G ]
gap> List(GcsHNPFfalse222222C2xC2D2Z1,Size);
[ 3, 3, 3, 3 ]
gap> List(GcsHNPFtrueC2xC2D2Z1,Size);
[ 3, 3 ]
gap> List(GcsHNPFfalse222222C2xC2D4Z1,Size);
[ 1 ]
gap> List(GcsHNPFtrueC2xC2D4Z1,Size);
[ 1, 1 ]
gap> S12:=SymmetricGroup(12);
Sym( [ 1 .. 12 ] )
gap> NS12G:=Normalizer(S12,G);
Group([ (3,9)(6,12), (1,10)(3,12)(4,7)(6,9), (1,11,3)(2,6,4)(5,9,7)
(8,12,10), (3,12)(6,9), (2,9,11,12)(3,5,6,8), (2,8)(3,6,9,12)(4,10) ])

```

```

gap> StructureDescription(NS12G);
"(((C2 x ((C2 x C2 x C2 x C2) : C2) : C3) : C2"
gap> Order(NS12G);
768
gap> Collected(List(List(GcsHNPfalse222222C2xC2D2Z1,Representative),
> x->IsNormal(NS12G,x)));
[ [ false, 4 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2D2Z1,Representative),
> x->IsNormal(NS12G,x)));
[ [ false, 2 ] ]
gap> Collected(List(List(GcsHNPfalse222222C2xC2D4Z1,Representative),
> x->IsNormal(NS12G,x)));
[ [ true, 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2D4Z1,Representative),
> x->IsNormal(NS12G,x)));
[ [ false, 2 ] ]
gap> List(List(GcsHNPfalse222222C2xC2D2Z1,Elements),x->List(x,Elements));
[ [ [ (), (3,9)(6,12), (1,10)(2,5)(4,7)(8,11),
      (1,10)(2,5)(3,9)(4,7)(6,12)(8,11) ],
    [ (), (2,5)(3,12)(6,9)(8,11), (1,7)(4,10),
      (1,7)(2,5)(3,12)(4,10)(6,9)(8,11) ],
    [ (), (2,8)(5,11), (1,10)(3,12)(4,7)(6,9),
      (1,10)(2,8)(3,12)(4,7)(5,11)(6,9) ] ],
  [ [ (), (3,9)(6,12), (1,4)(2,5)(7,10)(8,11),
      (1,4)(2,5)(3,9)(6,12)(7,10)(8,11) ],
    [ (), (2,8)(5,11), (1,10)(3,6)(4,7)(9,12),
      (1,10)(2,8)(3,6)(4,7)(5,11)(9,12) ],
    [ (), (2,11)(3,12)(5,8)(6,9), (1,7)(4,10),
      (1,7)(2,11)(3,12)(4,10)(5,8)(6,9) ] ],
  [ [ (), (3,9)(6,12), (1,10)(2,11)(4,7)(5,8),
      (1,10)(2,11)(3,9)(4,7)(5,8)(6,12) ],
    [ (), (2,5)(3,6)(8,11)(9,12), (1,7)(4,10),
      (1,7)(2,5)(3,6)(4,10)(8,11)(9,12) ],
    [ (), (2,8)(5,11), (1,4)(3,12)(6,9)(7,10),
      (1,4)(2,8)(3,12)(5,11)(6,9)(7,10) ] ],
  [ [ (), (3,9)(6,12), (1,4)(2,11)(5,8)(7,10),
      (1,4)(2,11)(3,9)(5,8)(6,12)(7,10) ],
    [ (), (2,8)(5,11), (1,4)(3,6)(7,10)(9,12),
      (1,4)(2,8)(3,6)(5,11)(7,10)(9,12) ],
    [ (), (2,11)(3,6)(5,8)(9,12), (1,7)(4,10),
      (1,7)(2,11)(3,6)(4,10)(5,8)(9,12) ] ] ]
gap> List(List(GcsHNPtrueC2xC2D2Z1,Elements),x->List(x,Elements));
[ [ [ (), (2,5)(3,6)(8,11)(9,12), (1,10)(3,6)(4,7)(9,12),
      (1,10)(2,5)(4,7)(8,11) ],
    [ (), (2,5)(3,12)(6,9)(8,11), (1,4)(3,12)(6,9)(7,10),
      (1,4)(2,5)(7,10)(8,11) ],
    [ (), (2,11)(3,12)(5,8)(6,9), (1,10)(3,12)(4,7)(6,9),
      (1,10)(2,11)(4,7)(5,8) ] ],
  [ [ (), (2,5)(3,6)(8,11)(9,12), (1,4)(3,6)(7,10)(9,12),
      (1,4)(2,5)(7,10)(8,11) ],
    [ (), (2,11)(3,6)(5,8)(9,12), (1,10)(3,6)(4,7)(9,12),
      (1,10)(2,11)(4,7)(5,8) ],
    [ (), (2,11)(3,12)(5,8)(6,9), (1,4)(3,12)(6,9)(7,10),
      (1,4)(2,11)(5,8)(7,10) ] ] ]
gap> List(List(GcsHNPfalse222222C2xC2D4Z1,Elements),x->List(x,Elements));
[ [ [ (), (2,8)(3,9)(5,11)(6,12), (1,7)(3,9)(4,10)(6,12),
      (1,7)(2,8)(4,10)(5,11) ] ] ]
gap> List(List(GcsHNPtrueC2xC2D4Z1,Elements),x->List(x,Elements));
[ [ [ (), (2,5)(3,12)(6,9)(8,11), (1,10)(3,12)(4,7)(6,9),
      (1,10)(2,5)(4,7)(8,11) ],
    [ (), (2,11)(3,6)(5,8)(9,12), (1,4)(3,6)(7,10)(9,12),
      (1,4)(2,11)(5,8)(7,10) ] ] ]

```

(2-1-3) $G = 12T59 \simeq (C_2)^3 \rtimes A_4(6)$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,59);
[2^3]A_4(6)
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3)(6,7)(8,9), (1,12)(2,3)(4,5), (2,8)(3,9)(4,10)(5,11),
  (1,5,9)(2,6,10)(3,7,11)(4,8,12) ]
gap> H:=Stabilizer(G,1);
Group([ (2,8)(3,9)(4,10)(5,11), (4,5)(6,7)(8,9) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
35
gap> GcsH:=ConjugacyClassesNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf));
[ [ [ true ], 8 ], [ [ false ], 27 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
27
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
8
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "A4", 2 ], [ "C2", 4 ], [ "C2 x A4", 1 ], [ "C2 x C2", 9 ],
  [ "C2 x C2 x C2", 3 ], [ "C2 x D8", 1 ], [ "C3", 1 ], [ "C4", 1 ],
  [ "C4 x C2", 1 ], [ "C6", 1 ], [ "D8", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C2 x C2 x C2 x C2) : C2" : C3", 1 ], [ "(C2 x C2 x C2 x C2) : C2", 1 ],
  [ "(C2 x C2 x C2 x C2) : C3", 1 ], [ "(C4 x C2) : C2", 1 ], [ "A4", 1 ],
  [ "C2 x C2", 1 ], [ "C2 x C2 x C2", 1 ], [ "C2 x C2 x C2 x C2", 1 ] ]
gap> GcsHNPtrueMin:=Mincs(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C2", 1 ], [ "C2 x C2", 1 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));
[ [ [ 4, 2 ], 1 ], [ [ 16, 3 ], 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
9
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
1
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2, 2, 2 ], 1 ],
  [ [ 2, 2, 2, 2, 2, 2, 2 ], 1 ] ]

```

```

[ [ 2, 2, 2, 2, 4 ], 3 ], [ [ 2, 2, 4, 4 ], 2 ], [ [ 4, 4 ], 1 ],
[ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 2, 2, 2 ], 1 ] ]
gap> Syl2G:=SylowSubgroup(G,2);
Group([ (2,3)(6,7)(10,11), (1,7)(4,10)(5,11)(6,12), (2,8)(3,9)(4,10)
(5,11), (1,12)(4,5)(6,7)(10,11), (1,12)(2,3)(6,7)(8,9) ])
gap> IsCharacteristicSubgroup(G,Syl2G);
true
gap> ZSyl2G:=Centre(Syl2G);
Group([ (2,3)(4,5)(8,9)(10,11), (1,12)(4,5)(6,7)(10,11) ])
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(ZSyl2G,x))]));
[ [ [ [ 2, 2, 2, 2, 2 ], "C2" ], 1 ],
[ [ [ 2, 2, 2, 2, 2 ], "C2 x C2" ], 1 ],
[ [ [ 2, 2, 2, 2, 4 ], "1" ], 1 ], [ [ [ 2, 2, 2, 2, 4 ], "C2" ], 2 ],
[ [ [ 2, 2, 4, 4 ], "1" ], 1 ], [ [ [ 2, 2, 4, 4 ], "C2" ], 1 ],
[ [ [ 4, 4 ], "C2" ], 1 ], [ [ [ 4, 4, 4 ], "1" ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(ZSyl2G,x))]));
[ [ [ [ 2, 2, 2, 2, 2 ], "1" ], 1 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,3]); # G(16,3)=(C4xC2):C2
1

```

(2-1-4) $G = 12T61 \simeq ((C_4)^2 \rtimes C_2) \rtimes C_3$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,61);
[2^3]A_4(6)_4
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3)(6,7)(8,9), (1,12)(2,3)(4,5), (1,5,9)(2,6,10)(3,7,11)(4,8,12),
(2,8)(3,9)(4,11)(5,10)(6,7) ]
gap> H:=Stabilizer(G,1);
Group([ (2,8)(3,9)(4,11)(5,10)(6,7), (4,5)(6,7)(8,9) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 4 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
28
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 6 ], [ [ false ], 22 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
22
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
6
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "A4", 1 ], [ "C2", 3 ], [ "C2 x A4", 1 ], [ "C2 x C2", 5 ],

```

```

[ "C2 x C2 x C2", 2 ], [ "C2 x D8", 1 ], [ "C3", 1 ], [ "C4", 2 ],
[ "C4 x C2", 1 ], [ "C6", 1 ], [ "D8", 3 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C4 x C4) : C2) : C3", 1 ], [ "(C4 x C4) : C2", 1 ],
[ "(C4 x C4) : C3", 1 ], [ "C2 x D8", 1 ], [ "C4 x C4", 1 ], [ "D8", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C4 x C4", 1 ], [ "D8", 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3];;
gap> Length(GcsHNPtrueD4);
3
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,3];;
gap> Length(GcsHNPtrueD4);
1
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ], [ [ 2, 4, 4 ], 1 ], [ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> ChG:=CharacteristicSubgroups(G);;
gap> ChG=NormalSubgroups(G);
true
gap> List(ChG,Order);
[ 96, 48, 32, 8, 16, 4, 1 ]
gap> N8:=ChG[4];
Group([ (4,5)(6,7)(8,9), (2,3)(4,5)(8,9)(10,11), (1,12)(2,3)(6,7)(8,9) ])
gap> StructureDescription(N8);
"C2 x C2 x C2"
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(N8,x))]));
[ [ [ [ 2, 2, 4, 4 ], "C2 x C2" ], 1 ], [ [ [ 2, 4, 4 ], "C2 x C2" ], 1 ],
[ [ [ 4, 4, 4 ], "C2" ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(N8,x))]));
[ [ [ [ 2, 2, 4, 4 ], "C2" ], 1 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,2]); # G(16,2)=C4xC4
1

```

$$(2-1-5) \quad G = 12T66 \simeq ((C_2)^4 \rtimes C_3) \rtimes C_2.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,66);
[1/2[1/2.2^2]^3]S_4(6d)_2
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3)(6,7)(8,9), (1,5,9)(2,6,10)(3,7,11)(4,8,12),
(1,3,5)(2,4,12)(6,8,10)(7,9,11), (2,4)(3,5)(6,7)(8,11)(9,10) ]
gap> H:=Stabilizer(G,1);
Group([ (2,4)(3,5)(6,7)(8,11)(9,10), (2,3)(4,5)(8,9)(10,11), (2,10,3,11)
(4,8,5,9)(6,7) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;

```

```

[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
56
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf));
[ [ [ true ], 10 ], [ [ false ], 46 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
46
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
10
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C2", 3 ], [ "1", 1 ], [ "A4", 3 ], [ "C2", 5 ],
  [ "C2 x C2", 13 ], [ "C2 x C2 x C2", 4 ], [ "C2 x D8", 2 ], [ "C3", 1 ],
  [ "C4", 3 ], [ "C4 x C2", 3 ], [ "D8", 5 ], [ "S3", 1 ], [ "S4", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C2 x C2 x C2 x C2) : C3) : C2", 1 ], [ "(C2 x C2 x C2 x C2) : C2", 1 ],
  [ "(C2 x C2 x C2 x C2) : C3", 1 ], [ "A4", 1 ], [ "C2 x C2", 1 ],
  [ "C2 x C2 x C2", 1 ], [ "C2 x C2 x C2 x C2", 1 ], [ "C2 x D8", 1 ],
  [ "D8", 1 ], [ "S4", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 1 ], [ "D8", 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
13
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
1
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
true
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2, 4 ], 4 ],
  [ [ 2, 2, 4, 4 ], 4 ], [ [ 2, 4, 4 ], 1 ], [ [ 4, 4 ], 1 ],
  [ [ 4, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2, 2, 2 ], 1 ] ]
gap> GcsHNPfalse222222C2xC2:=Filtered(GcsHNPfalseC2xC2,
> x->SortedList(List(Orbits(Representative(x)),Length))=[2,2,2,2,2,2]);;
gap> Collected(List(List(GcsHNPfalse222222C2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),IsNormal(G,x)]));
[ [ [ [ 2, 2, 2, 2, 2, 2 ], true ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),IsNormal(G,x)]));
[ [ [ [ 2, 2, 2, 2, 2, 2 ], false ], 1 ] ]
gap> ChG:=CharacteristicSubgroups(G);;
```

```

gap> List(ChG,Order);
[ 96, 48, 16, 1 ]
gap> Collected(List(List(GcsHNPfalse222222C2xC2,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x))));;
[ [ [ "C2 x C2", "C2 x C2", "C2 x C2", "1" ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->StructureDescription(Intersection(y,x))));;
[ [ [ "C2 x C2", "C2 x C2", "C2 x C2", "1" ], 1 ] ]
gap> Collected(List(List(GcsHNPfalse222222C2xC2,Representative),
> x->StructureDescription(Normalizer(G,x))));;
[ [ "(C2 x C2 x C2 x C2) : C3" : C2", 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Normalizer(G,x))));;
[ [ "(C2 x C2 x C2 x C2) : C3", 1 ] ]

gap> GcsHNPfalseD4:=Filtered(GcsHNPfalse, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3];;
gap> Length(GcsHNPfalseD4);
5
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,3];;
gap> Length(GcsHNPtrueD4);
1
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 8 ], 1 ], [ [ 4, 4, 4 ], 2 ], [ [ 4, 8 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ] ]

```

$$(2-1-6) \quad G = 12T88 \simeq (C_2)^4 \rtimes A_4(6).$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,88);
[2^4]A_4(6)
gap> GeneratorsOfGroup(G);
[ (1,12)(6,7), (1,12)(2,3)(4,5), (1,5,9)(2,6,10)(3,7,11)(4,8,12),
  (1,3,11)(2,10,12)(4,6,8)(5,7,9) ]
gap> H:=Stabilizer(G,1);
Group([ (4,5)(10,11), (6,7)(8,9)(10,11), (2,8)(3,9)(4,10)(5,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2, 2 ], [ [ 1, 0, 0 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
142
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtrf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtrf,Set));
[ [ [ true ], 33 ], [ [ false ], 109 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtrf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
109
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtrf[x]),y->Gcs[y]);;

```

```

gap> Length(GcsHNPtrue);
33
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "A4", 2 ], [ "C2", 9 ], [ "C2 x A4", 4 ], [ "C2 x C2", 33 ],
  [ "C2 x C2 x A4", 1 ], [ "C2 x C2 x C2", 27 ], [ "C2 x C2 x C2 x C2", 3 ],
  [ "C2 x C2 x D8", 1 ], [ "C2 x D8", 8 ], [ "C3", 1 ], [ "C4", 2 ],
  [ "C4 x C2", 4 ], [ "C4 x C2 x C2", 1 ], [ "C6", 3 ], [ "C6 x C2", 1 ],
  [ "D8", 8 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C2 x C2 x C2 x C2) : C2) : C3", 2 ], [ "(C2 x C2 x C2 x C2) : C2", 4 ],
  [ "(C2 x C2 x C2 x C2) : C3", 1 ], [ "(C4 x C2) : C2", 4 ], [ "A4", 1 ],
  [ "C2 x (((C2 x C2 x C2 x C2) : C2) : C3)", 1 ],
  [ "C2 x ((C2 x C2 x C2 x C2) : C2)", 1 ],
  [ "C2 x ((C2 x C2 x C2 x C2) : C3)", 1 ], [ "C2 x ((C4 x C2) : C2)", 1 ],
  [ "C2 x A4", 1 ], [ "C2 x C2", 2 ], [ "C2 x C2 x C2", 8 ],
  [ "C2 x C2 x C2 x C2", 5 ], [ "C2 x C2 x C2 x C2 x C2", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C2", 4 ], [ "C2 x C2", 2 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));
[ [ [ 4, 2 ], 2 ], [ [ 16, 3 ], 4 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
33
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
2
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2 ], 2 ], [ [ 2, 2, 2, 2, 2 ], 2 ],
  [ [ 2, 2, 2, 2, 2, 2 ], 5 ], [ [ 2, 2, 2, 2, 4 ], 10 ], [ [ 2, 2, 4 ], 2 ],
  [ [ 2, 2, 4, 4 ], 8 ], [ [ 4, 4 ], 2 ], [ [ 4, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2, 2 ], 2 ] ]
gap> Syl2G:=SylowSubgroup(G,2);
Group([ (1,12)(4,5)(8,9), (1,12)(2,3)(4,5)(6,7)(8,9)(10,11), (1,7)(2,8)(3,9)
(6,12), (1,7)(4,10)(5,11)(6,12), (1,12)(2,3)(6,7)(8,9), (1,12)(4,5)(6,7)
(10,11) ])
gap> IsCharacteristicSubgroup(G,Syl2G);
true
gap> ZSyl2G:=Centre(Syl2G);
Group([ (4,5)(10,11), (2,3)(8,9), (1,12)(6,7) ])
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(ZSyl2G,x))]));
[ [ [ [ 2, 2, 2, 2 ], "C2" ], 1 ], [ [ [ 2, 2, 2, 2 ], "C2 x C2" ], 1 ],
  [ [ [ 2, 2, 2, 2 ], "C2" ], 2 ], [ [ [ 2, 2, 2, 2, 2 ], "C2" ], 3 ],
  [ [ [ 2, 2, 2, 2, 2 ], "C2 x C2" ], 2 ],
  [ [ [ 2, 2, 2, 2, 4 ], "1" ], 4 ], [ [ [ 2, 2, 2, 2, 4 ], "C2" ], 6 ],
  [ [ [ 2, 2, 4 ], "C2" ], 2 ], [ [ [ 2, 2, 4, 4 ], "1" ], 4 ],
  [ [ [ 2, 2, 4 ], "C2" ], 4 ], [ [ [ 4, 4 ], "C2" ], 2 ],
  [ [ [ 4, 4, 4 ], "1" ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),
```

```

> StructureDescription(Intersection(ZSyl2G,x))]);
[ [ [ [ 2, 2, 2, 2, 2, 2 ], "1" ], 2 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,3]); # G(16,3)=(C4xC2):C2
4
gap> Number(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))=[16,3]);
4

(2-1-7)  $G = 12T92 \simeq ((C_4)^2 \rtimes C_2) \rtimes C_3 \times C_2$ .

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,92);
[2^4] A_4(6)_4{n4}
gap> GeneratorsOfGroup(G);
[ (1,12)(6,7), (1,12)(2,3)(4,5), (1,5,9)(2,6,10)(3,7,11)(4,8,12),
  (2,8)(3,9)(4,10)(5,11)(6,7) ]
gap> H:=Stabilizer(G,1);
Group([ (2,8)(3,9)(4,10)(5,11)(6,7), (2,3)(6,7)(10,11), (6,7)(8,9)(10,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2, 2 ], [ [ 1, 0, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 4 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
108
gap> GcsH:=ConjugacyClassesSubgroupsNGHOorbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 25 ], [ [ false ], 83 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
83
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
25
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "A4", 1 ], [ "C2", 7 ], [ "C2 x A4", 3 ], [ "C2 x C2", 17 ],
  [ "C2 x C2 x A4", 1 ], [ "C2 x C2 x C2", 13 ], [ "C2 x C2 x C2 x C2", 2 ],
  [ "C2 x C2 x D8", 1 ], [ "C2 x D8", 9 ], [ "C3", 1 ], [ "C4", 4 ],
  [ "C4 x C2", 6 ], [ "C4 x C2 x C2", 1 ], [ "C6", 3 ], [ "C6 x C2", 1 ],
  [ "D8", 12 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C4 x C4) : C2) : C3", 2 ], [ "(C4 x C4) : C2", 4 ],
  [ "(C4 x C4) : C3", 1 ], [ "C2 x (((C4 x C4) : C2) : C3)", 1 ],
  [ "C2 x ((C4 x C4) : C2)", 1 ], [ "C2 x ((C4 x C4) : C3)", 1 ],
  [ "C2 x C2 x D8", 1 ], [ "C2 x D8", 7 ], [ "C4 x C4", 2 ],
  [ "C4 x C4 x C2", 1 ], [ "D8", 4 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C4 x C4", 2 ], [ "D8", 4 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPfalseD4:=Filtered(GcsHNPfalse, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPfalseD4);
12

```

```

gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
4
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 4 ], [ [ 2, 4, 4 ], 4 ], [ [ 4, 4, 4 ], 4 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 4 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (1,12)(4,5)(6,7)(10,11), (1,12)(2,3)(6,7)(8,9), (1,7,12,6)
(4,11,5,10), (1,12)(2,8,3,9)(4,11,5,10)(6,7) ])
gap> Order(DG);
16
gap> ChG:=CharacteristicSubgroups(G);;
gap> List(ChG,Order);
[ 192, 96, 64, 48, 32, 16, 8, 16, 2, 4, 1 ]
gap> Position(ChG,DG);
8
gap> N16:=ChG[6];
Group([ (6,7)(8,9)(10,11), (1,12)(2,3)(6,7)(8,9), (1,12)(4,5)(6,7)
(10,11), (1,12)(6,7) ])
gap> StructureDescription(N16);
"C2 x C2 x C2 x C2"
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(N16,x))]));
[ [ [ [ 2, 2, 4, 4 ], "C2 x C2" ], 4 ], [ [ [ 2, 4, 4 ], "C2 x C2" ], 4 ],
[ [ [ 4, 4, 4 ], "C2" ], 4 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(N16,x))]);
[ [ [ [ 2, 2, 4, 4 ], "C2" ], 4 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,2]); # G(16,2)=C4xC4
2
gap> Number(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))=[16,2]);
2

```

$$(2\text{-}1\text{-}8) \quad G = 12T93 \simeq (((C_4 \rtimes C_4) \times C_2) \rtimes C_2) \rtimes C_3.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,93);
[2^4] A_4(6)_4{n2}
gap> GeneratorsOfGroup(G);
[ (1,12)(6,7), (1,12)(2,3)(4,5), (1,5,9)(2,6,10)(3,7,11)(4,8,12),
(2,8,3,9)(4,10)(5,11) ]
gap> H:=Stabilizer(G,1);
Group([ (2,8,3,9)(4,10)(5,11), (6,7)(8,9)(10,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 4 ], [ [ 2, 4 ], [ [ 1, 1 ], [ 0, 2 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 2, 4 ], [ [ 0, 2 ] ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[4];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
51

```

```

gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 6 ], [ [ false ], 45 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
45
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
6
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C2", 2 ], [ "1", 1 ], [ "A4", 1 ], [ "C2", 5 ],
  [ "C2 x ((C4 x C2) : C2)", 1 ], [ "C2 x A4", 3 ], [ "C2 x C2", 7 ],
  [ "C2 x C2 x A4", 1 ], [ "C2 x C2 x C2", 5 ], [ "C2 x C2 x C2 x C2", 1 ],
  [ "C3", 1 ], [ "C4", 3 ], [ "C4 : C4", 1 ], [ "C4 x C2", 7 ],
  [ "C4 x C2 x C2", 2 ], [ "C6", 3 ], [ "C6 x C2", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(((C4 x C2) : C4) : C2) : C3", 1 ], [ "((C2 x (C4 : C4)) : C2) : 1", 1 ],
  [ "((C4 x C2) : C4) : C3", 1 ], [ "(C4 x C2) : C4", 1 ],
  [ "C2 x (C4 : C4)", 1 ], [ "C4 : C4", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C4", 1 ], [ "C4 : C4", 1 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));
[ [ [ 16, 4 ], 1 ], [ [ 32, 2 ], 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

```

```

gap> GcsHNPfalseC4x1C4:=Filtered(GcsHNPfalse, # G(16,4)=C4:C4
> x->IdSmallGroup(Representative(x))=[16,4]);;
gap> Length(GcsHNPfalseC4x1C4);
1
gap> GcsHNPtrueC4x1C4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[16,4]);;
gap> Length(GcsHNPtrueC4x1C4);
1
gap> IsInvariantUnderAutG(GcsHNPtrueC4x1C4);
false
gap> Collected(List(List(GcsHNPfalseC4x1C4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4x1C4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ] ]

```

```

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[32,2]); # G(32,2)=(C4xC2):C4
1

```

$$(2\text{-}1\text{-}9) \quad G = 12T100 \simeq ((C_2)^4 \rtimes C_3) \rtimes C_2.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,100);
[(1/2.2^2)^3]S_4(6d)_2
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3), (1,5,9)(2,6,10)(3,7,11)(4,8,12),
  (1,7,11)(2,4,8)(3,5,9)(6,10,12), (2,3)(4,8)(5,9)(6,11)(7,10) ]
gap> H:=Stabilizer(G,1);
Group([(2,3)(4,8)(5,9)(6,11)(7,10), (4,5)(6,7), (4,6)(5,7)(8,11)(9,10)])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2, 2 ], [ [ 1, 1, 0 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;

```

```

[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
238
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf));
[ [ [ true ], 56 ], [ [ false ], 182 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
182
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
56
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C2 x C2 x C2 x C2) : C2", 4 ], [ "(C4 x C2) : C2", 12 ], [ "1", 1 ],
  [ "A4", 3 ], [ "C2", 11 ], [ "C2 x ((C4 x C2) : C2)", 1 ], [ "C2 x A4", 3 ],
  [ "C2 x C2", 44 ], [ "C2 x C2 x C2", 33 ], [ "C2 x C2 x C2 x C2", 3 ],
  [ "C2 x D8", 15 ], [ "C2 x S4", 2 ], [ "C3", 1 ], [ "C4", 6 ],
  [ "C4 x C2", 11 ], [ "C4 x C2 x C2", 2 ], [ "C6", 1 ], [ "D12", 1 ],
  [ "D8", 22 ], [ "S3", 2 ], [ "S4", 4 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C2 x C2 x C2 x C2) : C3) : C2", 2 ], [ "(C2 x C2 x C2 x C2) : C2", 4 ],
  [ "(C2 x C2 x C2 x C2) : C3", 1 ], [ "A4", 1 ],
  [ "C2 x (((C2 x C2 x C2 x C2) : C3) : C2)", 1 ],
  [ "C2 x ((C2 x C2 x C2 x C2) : C2)", 1 ],
  [ "C2 x ((C2 x C2 x C2 x C2) : C3)", 1 ], [ "C2 x ((C4 x C2) : C2)", 2 ],
  [ "C2 x A4", 1 ], [ "C2 x C2", 3 ], [ "C2 x C2 x C2", 12 ],
  [ "C2 x C2 x C2 x C2", 7 ], [ "C2 x C2 x C2 x C2 x C2", 1 ],
  [ "C2 x C2 x D8", 3 ], [ "C2 x D8", 9 ], [ "C2 x S4", 1 ], [ "C4 x C2", 1 ],
  [ "C4 x C2 x C2", 1 ], [ "D8", 2 ], [ "S4", 2 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 3 ], [ "C4 x C2", 1 ], [ "D8", 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPfalseC2xC2);
44
gap> Sum(GcsHNPfalseC2xC2,Size);
219
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPtrueC2xC2);
3
gap> Sum(GcsHNPtrueC2xC2,Size);
20
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2, 2, 2 ], 5 ],
  [ [ 2, 2, 2, 2, 4 ], 12 ], [ [ 2, 2, 4 ], 2 ], [ [ 2, 2, 4, 4 ], 14 ],
  [ [ 2, 4, 4 ], 4 ], [ [ 4, 4 ], 2 ], [ [ 4, 4, 4 ], 4 ] ]

```

```

gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 2, 2, 2, 2, 2, 2 ], 3 ] ]
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrueC2xC2,
> x->SortedList(List(Orbits(Representative(x)),Length)=[2,2,2,2,2,2]));
gap> Length(GcsHNPtrueC2xC2);
5
gap> Sum(GcsHNPtrueC2xC2,Size);
16
gap> ChG:=CharacteristicSubgroups(G);;
gap> Length(ChG);
7
gap> List(ChG,Order);
[ 192, 96, 32, 48, 2, 16, 1 ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))); 
[ [ [ 4, 4, 4, 2, 1, 2, 1 ], 3 ], [ [ 4, 4, 4, 2, 2, 2, 1 ], 1 ],
[ [ 4, 4, 4, 4, 1, 4, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))))); 
[ [ [ 4, 2, 2, 1, 1, 1, 1 ], 1 ], [ [ 4, 4, 4, 2, 1, 2, 1 ], 1 ],
[ [ 4, 4, 4, 4, 1, 4, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Normalizer(G,x)))); 
[ [ "C2 x (((C2 x C2 x C2 x C2) : C3) : C2)", 1 ],
[ "C2 x ((C2 x C2 x C2 x C2) : C2)", 3 ], [ "C2 x C2 x C2 x C2 x C2", 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->StructureDescription(Normalizer(G,x)))); 
[ [ "C2 x ((C2 x C2 x C2 x C2) : C3)", 1 ], [ "C2 x C2 x C2 x C2", 1 ],
[ "C2 x C2 x C2 x C2 x C2", 1 ] ]
gap> GcsHNPtrueC2xC2N32:=Filtered(GcsHNPtrueC2xC2,
> x->Order(Normalizer(G,Representative(x)))=32);
[ Group( [ ( 4, 6)( 5, 7)( 8,10)( 9,11), ( 1,12)( 2, 3) ] )^G ]
gap> Length(GcsHNPtrueC2xC2N32);
1
gap> List(GcsHNPtrueC2xC2N32,Size);
[ 6 ]
gap> GcsHNPtrueC2xC2N32:=Filtered(GcsHNPtrueC2xC2,
> x->Order(Normalizer(G,Representative(x)))=32);
[ Group( [ ( 1, 3)( 2,12)( 8,10)( 9,11), ( 4, 7)( 5, 6)( 8,10)( 9,11) ] )^G ]
gap> Length(GcsHNPtrueC2xC2N32);
1
gap> List(GcsHNPtrueC2xC2N32,Size);
[ 6 ]
gap> List(List(GcsHNPtrueC2xC2N32,Elements),x->List(x,Elements));
[ [ [ (), (8,9)(10,11), (1,2)(3,12)(4,7)(5,6),
(1,2)(3,12)(4,7)(5,6)(8,9)(10,11) ],
[ (), (8,9)(10,11), (1,3)(2,12)(4,6)(5,7),
(1,3)(2,12)(4,6)(5,7)(8,9)(10,11) ],
[ (), (4,5)(6,7), (1,2)(3,12)(8,11)(9,10),
(1,2)(3,12)(4,5)(6,7)(8,11)(9,10) ],
[ (), (4,5)(6,7), (1,3)(2,12)(8,10)(9,11),
(1,3)(2,12)(4,5)(6,7)(8,10)(9,11) ],
[ (), (4,6)(5,7)(8,10)(9,11), (1,12)(2,3),
(1,12)(2,3)(4,6)(5,7)(8,10)(9,11) ],
[ (), (4,7)(5,6)(8,11)(9,10), (1,12)(2,3),
(1,12)(2,3)(4,7)(5,6)(8,11)(9,10) ] ] ]
gap> List(List(GcsHNPtrueC2xC2N32,Elements),x->List(x,Elements));
[ [ [ (), (4,6)(5,7)(8,10)(9,11), (1,2)(3,12)(8,10)(9,11),
(1,2)(3,12)(4,6)(5,7) ],
[ (), (4,6)(5,7)(8,11)(9,10), (1,2)(3,12)(8,11)(9,10),
(1,2)(3,12)(4,6)(5,7) ], ... ]

```

```

[ (), (4,6)(5,7)(8,11)(9,10), (1,3)(2,12)(8,11)(9,10),
 (1,3)(2,12)(4,6)(5,7) ],
[ (), (4,7)(5,6)(8,10)(9,11), (1,2)(3,12)(8,10)(9,11),
 (1,2)(3,12)(4,7)(5,6) ],
[ (), (4,7)(5,6)(8,10)(9,11), (1,3)(2,12)(8,10)(9,11),
 (1,3)(2,12)(4,7)(5,6) ],
[ (), (4,7)(5,6)(8,11)(9,10), (1,3)(2,12)(8,11)(9,10),
 (1,3)(2,12)(4,7)(5,6) ] ]

gap> GcsHNPfalseC4xC2:=Filtered(GcsHNPfalse, # G(8,2)=C4xC2
> x->IdSmallGroup(Representative(x))=[8,2]);
gap> Length(GcsHNPfalseC4xC2);
11
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,2]);
gap> Length(GcsHNPtrueC4xC2);
1
gap> IsInvariantUnderAutG(GcsHNPtrueC4xC2);
false
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 8 ], 2 ], [ [ 2, 8 ], 1 ], [ [ 4, 4, 4 ], 2 ], [ [ 4, 8 ], 6 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 4, 4 ], 1 ] ]

gap> GcsHNPfalseD4:=Filtered(GcsHNPfalse, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3]);
gap> Length(GcsHNPfalseD4);
22
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,3]);
gap> Length(GcsHNPtrueD4);
2
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 8 ], 2 ], [ [ 2, 4, 4 ], 2 ], [ [ 2, 8 ], 2 ], [ [ 4, 4, 4 ], 8 ],
 [ [ 4, 8 ], 8 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 4, 4 ], 2 ] ]

```

$$(2-1-10) \quad G = 12T102 \simeq ((C_2)^4 \rtimes C_3) \rtimes C_4.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,102);
[(1/2.2^2)^3]S_4(6c)_2
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3), (1,5,9)(2,6,10)(3,7,11)(4,8,12),
 (1,7,11)(2,4,8)(3,5,9)(6,10,12), (1,2,12,3)(4,8,5,9)(6,11,7,10) ]
gap> H:=Stabilizer(G,1);
Group([ (8,9)(10,11), (2,3)(4,8,6,11)(5,9,7,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 4 ], [ [ 1, 0 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2, 4 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
```

```

gap> Length(Gcs);
150
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 38 ], [ [ false ], 112 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
112
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
38
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C2", 7 ], [ "1", 1 ], [ "A4", 3 ], [ "A4 : C4", 3 ],
  [ "C2", 9 ], [ "C2 x ((C4 x C2) : C2)", 1 ], [ "C2 x A4", 3 ],
  [ "C2 x C2", 35 ], [ "C2 x C2 x C2", 28 ], [ "C2 x C2 x C2 x C2", 3 ],
  [ "C3", 1 ], [ "C3 : C4", 1 ], [ "C4", 4 ], [ "C4 x C2", 10 ],
  [ "C4 x C2 x C2", 2 ], [ "C6", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C2 x ((C4 x C2) : C2)) : C2) : 1", 1 ],
  [ "((C2 x C2 x C2 x C2) : C3) : C4", 1 ], [ "(C2 x C2 x C2 x C2) : C3", 1 ],
  [ "(C4 x C2) : C2", 5 ], [ "A4", 1 ],
  [ "C2 x ((C2 x C2 x C2 x C2) : C3)", 1 ], [ "C2 x ((C4 x C2) : C2)", 5 ],
  [ "C2 x A4", 1 ], [ "C2 x C2", 2 ], [ "C2 x C2 x C2", 9 ],
  [ "C2 x C2 x C2 x C2", 6 ], [ "C2 x C2 x C2 x C2 x C2", 1 ],
  [ "C4 x C2", 2 ], [ "C4 x C2 x C2", 2 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C2", 1 ], [ "C2 x C2", 2 ], [ "C4 x C2", 2 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));
[ [ [ 4, 2 ], 2 ], [ [ 8, 2 ], 2 ], [ [ 16, 3 ], 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
35
gap> Sum(GcsHNPfalseC2xC2,Size);
147
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
2
gap> Sum(GcsHNPtrueC2xC2,Size);
8
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2, 2, 2 ], 5 ],
  [ [ 2, 2, 2, 2, 4 ], 12 ], [ [ 2, 2, 4 ], 2 ], [ [ 2, 2, 4, 4 ], 9 ],
  [ [ 4, 4 ], 2 ], [ [ 4, 4, 4 ], 4 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2, 2, 2 ], 2 ] ]
gap> GcsHNPfalse222222C2xC2:=Filtered(GcsHNPfalseC2xC2,
> x->SortedList(List(Orbits(Representative(x)),Length))=[2,2,2,2,2]);;
gap> Length(GcsHNPfalse222222C2xC2);
5

```

```

gap> Sum(GcsHNPfalse222222C2xC2,Size);
16
gap> ChG:=CharacteristicSubgroups(G);;
gap> Length(ChG);
7
gap> List(ChG,Order);
[ 192, 96, 32, 48, 2, 16, 1 ]
gap> Collected(List(List(GcsHNPfalse222222C2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));;
[ [ [ 4, 4, 4, 2, 1, 2, 1 ], 3 ], [ [ 4, 4, 4, 2, 2, 2, 1 ], 1 ],
  [ [ 4, 4, 4, 4, 1, 4, 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));;
[ [ [ 4, 4, 4, 2, 1, 2, 1 ], 1 ], [ [ 4, 4, 4, 4, 1, 4, 1 ], 1 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (1,12)(2,3)(4,5)(6,7), (1,3)(2,12)(8,10)(9,11), (1,11,4)(2,8,7)(3,9,6)
(5,12,10) ])
gap> StructureDescription(DG);
"(C2 x C2 x C2 x C2) : C3"
gap> ZG:=Centre(G);
Group([ (1,12)(2,3)(4,5)(6,7)(8,9)(10,11) ])
gap> StructureDescription(ZG);
"C2"
gap> Position(ChG,DG);
4
gap> Position(ChG,ZG);
5
gap> Collected(List(List(GcsHNPfalse222222C2xC2,Representative),
> x->List([DG,ZG],y->StructureDescription(Intersection(y,x))));;
[ [ [ "C2", "1" ], 3 ], [ [ "C2", "C2" ], 1 ], [ [ "C2 x C2", "1" ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->List([DG,ZG],y->StructureDescription(Intersection(y,x))));;
[ [ [ "C2", "1" ], 1 ], [ [ "C2 x C2", "1" ], 1 ] ]
gap> GcsHNPfalse222222C2xC2D2Z1:=Filtered(GcsHNPfalse222222C2xC2,
> x->List([DG,ZG],y->Order(Intersection(y,Representative(x))))=[2,1]);
[ Group( [ ( 4, 6)( 5, 7)( 8,10)( 9,11), ( 1,12)( 2, 3) ] )^G,
  Group( [ ( 4, 6)( 5, 7)( 8,11)( 9,10), ( 1,12)( 2, 3) ] )^G,
  Group( [ ( 4, 7)( 5, 6)( 8,10)( 9,11), ( 1,12)( 2, 3) ] )^G ]
gap> GcsHNPtrueC2xC2D2Z1:=Filtered(GcsHNPtrueC2xC2,
> x->List([DG,ZG],y->Order(Intersection(y,Representative(x))))=[2,1]);
[ Group( [ ( 1, 3)( 2,12)( 8,10)( 9,11), ( 4, 7)( 5, 6)( 8,10)( 9,11) ] )^G ]
gap> GcsHNPfalse222222C2xC2D4Z1:=Filtered(GcsHNPfalse222222C2xC2,
> x->List([DG,ZG],y->Order(Intersection(y,Representative(x))))=[4,1]);
[ Group( [ ( 1,12)( 2, 3)( 8, 9)(10,11), ( 1,12)( 2, 3)( 4, 5)( 6, 7) ] )^G ]
gap> GcsHNPtrueC2xC2D4Z1:=Filtered(GcsHNPtrueC2xC2,
> x->List([DG,ZG],y->Order(Intersection(y,Representative(x))))=[4,1]);
[ Group( [ ( 1, 3)( 2,12)( 8,10)( 9,11), ( 4, 6)( 5, 7)( 8,10)( 9,11) ] )^G ]
gap> List(GcsHNPfalse222222C2xC2D2Z1,Size);
[ 6, 3, 3 ]
gap> List(GcsHNPtrueC2xC2D2Z1,Size);
[ 6 ]
gap> List(GcsHNPfalse222222C2xC2D4Z1,Size);
[ 1 ]
gap> List(GcsHNPtrueC2xC2D4Z1,Size);
[ 2 ]
gap> Collected(List(List(GcsHNPfalse222222C2xC2D2Z1,Representative),
> x->IsNormal(G,x)));
[ [ false, 3 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2D2Z1,Representative),
> x->IsNormal(G,x)));
[ [ false, 1 ] ]
gap> Collected(List(List(GcsHNPfalse222222C2xC2D4Z1,Representative),

```

```

> x->IsNormal(G,x)));
[ [ true, 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2D4Z1,Representative),
> x->IsNormal(G,x)));
[ [ false, 1 ] ]
gap> List(List(GcsHNPfalse222222C2xC2D2Z1,Elements),x->List(x,Elements));
[ [ [ (), (8,9)(10,11), (1,2)(3,12)(4,7)(5,6),
      (1,2)(3,12)(4,7)(5,6)(8,9)(10,11) ],
    [ (), (8,9)(10,11), (1,3)(2,12)(4,6)(5,7),
      (1,3)(2,12)(4,6)(5,7)(8,9)(10,11) ],
    [ (), (4,5)(6,7), (1,2)(3,12)(8,11)(9,10),
      (1,2)(3,12)(4,5)(6,7)(8,11)(9,10) ],
    [ (), (4,5)(6,7), (1,3)(2,12)(8,10)(9,11),
      (1,3)(2,12)(4,5)(6,7)(8,10)(9,11) ],
    [ (), (4,6)(5,7)(8,10)(9,11), (1,12)(2,3),
      (1,12)(2,3)(4,6)(5,7)(8,10)(9,11) ],
    [ (), (4,7)(5,6)(8,11)(9,10), (1,12)(2,3),
      (1,12)(2,3)(4,7)(5,6)(8,11)(9,10) ],
    [ [ (), (8,9)(10,11), (1,3)(2,12)(4,7)(5,6),
      (1,3)(2,12)(4,7)(5,6)(8,9)(10,11) ],
    [ (), (4,5)(6,7), (1,2)(3,12)(8,10)(9,11),
      (1,2)(3,12)(4,5)(6,7)(8,10)(9,11) ],
    [ (), (4,6)(5,7)(8,11)(9,10), (1,12)(2,3),
      (1,12)(2,3)(4,6)(5,7)(8,11)(9,10) ],
    [ [ (), (8,9)(10,11), (1,2)(3,12)(4,6)(5,7),
      (1,2)(3,12)(4,6)(5,7)(8,9)(10,11) ],
    [ (), (4,5)(6,7), (1,3)(2,12)(8,11)(9,10),
      (1,3)(2,12)(4,5)(6,7)(8,11)(9,10) ],
    [ (), (4,7)(5,6)(8,10)(9,11), (1,12)(2,3),
      (1,12)(2,3)(4,7)(5,6)(8,10)(9,11) ] ] ]
gap> List(List(GcsHNPtrueC2xC2D2Z1,Elements),x->List(x,Elements));
[ [ [ (), (4,6)(5,7)(8,10)(9,11), (1,2)(3,12)(8,10)(9,11),
      (1,2)(3,12)(4,6)(5,7) ],
    [ (), (4,6)(5,7)(8,11)(9,10), (1,2)(3,12)(8,11)(9,10),
      (1,2)(3,12)(4,6)(5,7) ],
    [ (), (4,6)(5,7)(8,11)(9,10), (1,3)(2,12)(8,11)(9,10),
      (1,3)(2,12)(4,6)(5,7) ],
    [ (), (4,7)(5,6)(8,10)(9,11), (1,2)(3,12)(8,10)(9,11),
      (1,2)(3,12)(4,7)(5,6) ],
    [ (), (4,7)(5,6)(8,10)(9,11), (1,3)(2,12)(8,10)(9,11),
      (1,3)(2,12)(4,7)(5,6) ],
    [ (), (4,7)(5,6)(8,11)(9,10), (1,3)(2,12)(8,11)(9,10),
      (1,3)(2,12)(4,7)(5,6) ] ] ]
gap> List(List(GcsHNPfalse222222C2xC2D4Z1,Elements),x->List(x,Elements));
[ [ [ (), (4,5)(6,7)(8,9)(10,11), (1,12)(2,3)(8,9)(10,11),
      (1,12)(2,3)(4,5)(6,7) ] ] ]
gap> List(List(GcsHNPtrueC2xC2D4Z1,Elements),x->List(x,Elements));
[ [ [ (), (4,6)(5,7)(8,10)(9,11), (1,3)(2,12)(8,10)(9,11),
      (1,3)(2,12)(4,6)(5,7) ],
    [ (), (4,7)(5,6)(8,11)(9,10), (1,2)(3,12)(8,11)(9,10),
      (1,2)(3,12)(4,7)(5,6) ] ] ]
gap> GcsHNPfalseC4xC2:=Filtered(GcsHNPfalse, # G(8,2)=C4xC2
> x->IdSmallGroup(Representative(x))=[8,2];;
gap> Length(GcsHNPfalseC4xC2);
10
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,2];;
gap> Length(GcsHNPtrueC4xC2);
2
gap> IsInvariantUnderAutG(GcsHNPtrueC4xC2);
false

```

```

gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 8 ], 2 ], [ [ 2, 8 ], 2 ], [ [ 4, 4, 4 ], 4 ], [ [ 4, 8 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 2 ] ]

gap> GcsHNPfalseG16_3:=Filtered(GcsHNPfalse, # G(16,3)=(C4xC2):C2
> x->IdSmallGroup(Representative(x))=[16,3]);;
gap> Length(GcsHNPfalseG16_3);
7
gap> GcsHNPtrueG16_3:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[16,3]);;
gap> Length(GcsHNPtrueG16_3);
5
gap> IsInvariantUnderAutG(GcsHNPtrueG16_3);
false
gap> GcsHNPtrueMinG16_3:=Filtered(GcsHNPtrueMin,
> x->IdSmallGroup(Representative(x))=[16,3]);;
gap> Length(GcsHNPtrueMinG16_3);
1
gap> IsInvariantUnderAutG(GcsHNPtrueMinG16_3);
false
gap> Collected(List(List(GcsHNPfalseG16_3,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 8 ], 1 ], [ [ 4, 4, 4 ], 1 ], [ [ 4, 8 ], 5 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 8 ], 1 ], [ [ 4, 4, 4 ], 2 ], [ [ 4, 8 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueMinG16_3,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 8 ], 1 ] ]

```

$$(2-1-11) \quad G = 12T144 \simeq (C_2)^5 \rtimes A_4(6).$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,144);
[2^5]A_4(6)
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3), (2,8)(3,9)(4,10)(5,11), (1,5,9)(2,6,10)(3,7,11)(4,8,12) ]
gap> H:=Stabilizer(G,1);
Group([ (2,8)(3,9)(4,10)(5,11), (6,7)(8,9), (8,9)(10,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2, 2, 2 ], [ [ 2, 2, 2 ], [ [ 1, 0, 0 ], [ 0, 1, 0 ], [ 0, 0, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2, 2 ], [ [ 2, 2, 2 ], [ [ 1, 0, 0 ], [ 0, 1, 0 ] ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2, 2, 4 ], [ ] ] ]
gap> HNPtruefalsefn:=x->Number(FirstObstructionDr(G,x,H).Dr[2][2],y->y[3]=1)>0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);215
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtrf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtrf,Set));
[ [ [ true ], 42 ], [ [ false ], 173 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtrf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
173
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtrf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);

```

```

42
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C2 x C2 x C2 x C2) : C2", 5 ], [ "(C2 x C2 x C2 x C2) : C3", 1 ],
  [ "(C4 x C2) : C2", 9 ], [ "1", 1 ], [ "A4", 7 ], [ "C2", 7 ],
  [ "C2 x ((C2 x C2 x C2 x C2) : C2)", 1 ],
  [ "C2 x ((C2 x C2 x C2 x C2) : C3)", 1 ], [ "C2 x ((C4 x C2) : C2)", 3 ],
  [ "C2 x A4", 7 ], [ "C2 x C2", 37 ], [ "C2 x C2 x C2", 36 ],
  [ "C2 x C2 x C2 x C2", 7 ], [ "C2 x C2 x C2 x C2", 1 ],
  [ "C2 x C2 x D8", 3 ], [ "C2 x D8", 16 ], [ "C3", 1 ], [ "C4", 4 ],
  [ "C4 x C2", 10 ], [ "C4 x C2 x C2", 3 ], [ "C6", 1 ], [ "D8", 12 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C2 x ((C2 x C2 x C2 x C2) : C2)) : C2) : 1", 1 ],
  [ "((C2 x ((C2 x C2 x C2 x C2) : C2)) : C2) : C3", 1 ],
  [ "((C2 x ((C4 x C2) : C2)) : C2) : 1", 3 ], [ "((C4 x C2) : C4) : C3", 2 ],
  [ "(C2 x C2 x C2 x C2) : C2", 3 ], [ "(C2 x C2 x C2 x C2) : C3", 1 ],
  [ "(C4 x C2) : C2", 3 ], [ "(C4 x C2) : C4", 2 ], [ "(C4 x C4) : C3", 1 ],
  [ "A4", 2 ], [ "C2 x ((C2 x C2 x C2 x C2) : C2)", 1 ],
  [ "C2 x ((C2 x C2 x C2 x C2) : C3)", 1 ], [ "C2 x ((C4 x C2) : C2)", 3 ],
  [ "C2 x ((C4 x C4) : C3)", 1 ], [ "C2 x (C4 : C4)", 1 ], [ "C2 x A4", 2 ],
  [ "C2 x C2", 2 ], [ "C2 x C2 x C2", 5 ], [ "C2 x C2 x C2 x C2", 3 ],
  [ "C2 x C2 x C2 x C2 x C2", 1 ], [ "C4 : C4", 1 ], [ "C4 x C4", 1 ],
  [ "C4 x C4 x C2", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C2", 3 ], [ "(C4 x C2) : C4", 2 ], [ "C2 x C2", 2 ],
  [ "C4 : C4", 1 ], [ "C4 x C4", 1 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));
[ [ [ 4, 2 ], 2 ], [ [ 16, 2 ], 1 ], [ [ 16, 3 ], 3 ], [ [ 16, 4 ], 1 ],
  [ [ 32, 2 ], 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
37
gap> Sum(GcsHNPfalseC2xC2,Size);
295
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
2
gap> Sum(GcsHNPtrueC2xC2,Size);
8
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2 ], 4 ], [ [ 2, 2, 2, 2 ], 5 ], [ [ 2, 2, 2, 2, 2 ], 6 ],
  [ [ 2, 2, 2, 2, 2, 2 ], 7 ], [ [ 2, 2, 2, 2, 4 ], 6 ], [ [ 2, 2, 4 ], 2 ],
  [ [ 2, 2, 4, 4 ], 4 ], [ [ 4, 4 ], 1 ], [ [ 4, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2, 2, 2 ], 2 ] ]
gap> GcsHNPfalse222222C2xC2:=Filtered(GcsHNPfalseC2xC2,
> x->SortedList(List(Orbits(Representative(x)),Length))=[2,2,2,2,2,2]);;
gap> Length(GcsHNPfalse222222C2xC2);
7
gap> Sum(GcsHNPfalse222222C2xC2,Size);
42
gap> ChG:=CharacteristicSubgroups(G);;
gap> Length(ChG);

```



```

[ (), (2,9)(3,8)(4,10)(5,11), (1,6)(4,10)(5,11)(7,12),
 (1,6)(2,9)(3,8)(7,12) ],
[ (), (2,9)(3,8)(4,11)(5,10), (1,7)(4,11)(5,10)(6,12),
 (1,7)(2,9)(3,8)(6,12) ],
[ [ (), (2,8)(3,9)(4,10)(5,11), (1,6)(4,10)(5,11)(7,12),
 (1,6)(2,8)(3,9)(7,12) ],
[ (), (2,8)(3,9)(4,11)(5,10), (1,7)(4,11)(5,10)(6,12),
 (1,7)(2,8)(3,9)(6,12) ],
[ (), (2,9)(3,8)(4,10)(5,11), (1,7)(4,10)(5,11)(6,12),
 (1,7)(2,9)(3,8)(6,12) ],
[ (), (2,9)(3,8)(4,11)(5,10), (1,6)(4,11)(5,10)(7,12),
 (1,6)(2,9)(3,8)(7,12) ] ]
gap> Collected(List(List(GcsHNPfalse222222C2xC2DD1,Representative),
> x->StructureDescription(Normalizer(G,x))));
[ [ "C2 x ((C2 x C2 x C2 x C2) : C3)", 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2DD1,Representative),
> x->StructureDescription(Normalizer(G,x))));
[ [ "C2 x ((C2 x C2 x C2 x C2) : C3)", 2 ] ]
gap> Collected(List(List(GcsHNPfalse222222C2xC2DD1,Representative),
> x->IdSmallGroup(Normalizer(G,x))));
[ [ [ 96, 229 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2DD1,Representative),
> x->IdSmallGroup(Normalizer(G,x))));
[ [ [ 96, 229 ], 2 ] ]
gap> Collected(List(List(GcsHNPfalse222222C2xC2DD1,Representative),
> x->SortedList(List(Orbits(Normalizer(G,x)),Length)))); 
[ [ [ 6, 6 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2DD1,Representative),
> x->SortedList(List(Orbits(Normalizer(G,x)),Length)))); 
[ [ [ 12 ], 2 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,2]); # G(16,2)=C4xC4
1

gap> GcsHNPfalseG16_3:=Filtered(GcsHNPfalse, # G(16,3)=(C4xC2):C2
> x->IdSmallGroup(Representative(x))=[16,3]);
gap> Length(GcsHNPfalseG16_3);
9
gap> Sum(GcsHNPfalseG16_3,Size);
54
gap> GcsHNPtrueG16_3:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[16,3]);
gap> Length(GcsHNPtrueG16_3);
3
gap> Sum(GcsHNPtrueG16_3,Size);
18
gap> IsInvariantUnderAutG(GcsHNPtrueG16_3);
false
gap> Collected(List(List(GcsHNPfalseG16_3,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 2, 2, 4, 4 ], 3 ], [ [ 2, 4, 4 ], 3 ], [ [ 4, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 2, 2, 4, 4 ], 3 ] ]
gap> GcsHNPfalse2244G16_3:=Filtered(GcsHNPfalseG16_3,
> x->SortedList(List(Orbits(Representative(x)),Length))=[2,2,4,4]);
gap> Length(GcsHNPfalse2244G16_3);
3
gap> Sum(GcsHNPfalse2244G16_3,Size);
18
gap> Collected(List(List(GcsHNPfalse2244G16_3,Representative),
> x->List(ChG,y->Order(Intersection(y,x)))));
```

```
[ [ [ 16, 16, 4, 4, 2, 1, 1 ], 1 ], [ [ 16, 16, 8, 4, 2, 1, 1 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));;
[ [ [ 16, 16, 4, 4, 2, 1, 1 ], 1 ], [ [ 16, 16, 8, 4, 2, 1, 1 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->SortedList(List(Orbits(Normalizer(G,x)),Length))));;
[ [ [ 2, 2, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->SortedList(List(Orbits(Normalizer(G,x)),Length))));;
[ [ [ 4, 4, 4 ], 3 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,4]); # G(16,4)=C4:C4
1

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[32,2]); # G(32,2)=(C4xC2):C4
2
gap> Number(GcstrueMin,x->IdSmallGroup(Representative(x))=[32,2]);
2
```

$$(2\text{-}1\text{-}12) \quad G = 12T188 \simeq (C_2)^6 \rtimes A_4(6) \simeq C_2 \wr A_4(6).$$

```
gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,188);
[2^6]A_4=2wrA_4(6)
gap> GeneratorsOfGroup(G);
[ (1,12), (2,8)(3,9)(4,10)(5,11), (1,5,9)(2,6,10)(3,7,11)(4,8,12) ]
gap> H:=Stabilizer(G,1);
Group([ (2,8)(3,9)(4,10)(5,11), (6,7), (2,3), (4,5) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2, 2, 2 ],
  [ [ 2, 2, 2, 2 ], [ [ 1, 0, 1, 0 ], [ 0, 1, 1, 0 ], [ 0, 0, 0, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2, 2 ], [ [ 2, 2, 2, 2 ], [ [ 1, 0, 1, 0 ], [ 0, 1, 1, 0 ] ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2, 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->Number(FirstObstructionDr(G,x,H).Dr[2][2],y->y[4]=1)>0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
1071
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtrf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtrf,Set));
[ [ [ true ], 189 ], [ [ false ], 882 ] ]
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtrf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
882
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtrf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
189
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C2 x C2 x C2 x C2) : C2", 39 ], [ "(C2 x C2 x C2 x C2) : C3", 1 ],
  [ "(C4 x C2 x C2) : C2", 4 ], [ "(C4 x C2) : C2", 35 ],
  [ "(C4 x C4) : C2", 1 ], [ "1", 1 ], [ "A4", 6 ], [ "C2", 14 ],
  [ "C2 x ((C2 x C2 x C2 x C2) : C2)", 16 ],
  [ "C2 x ((C2 x C2 x C2 x C2) : C3)", 3 ], [ "C2 x ((C4 x C2) : C2)", 24 ],
  [ "C2 x A4", 16 ], [ "C2 x C2", 101 ],
  [ "C2 x C2 x ((C2 x C2 x C2 x C2) : C2)", 1 ],
  [ "C2 x C2 x ((C2 x C2 x C2 x C2) : C3)", 1 ],
  [ "C2 x C2 x ((C4 x C2) : C2)", 3 ], [ "C2 x C2 x A4", 5 ],
  [ "C2 x C2 x C2", 193 ], [ "C2 x C2 x C2 x C2", 87 ],
```

```

[ "C2 x C2 x C2 x C2 x C2", 12 ], [ "C2 x C2 x C2 x C2 x C2 x C2", 1 ],
[ "C2 x C2 x C2 x D8", 3 ], [ "C2 x C2 x D8", 42 ], [ "C2 x D8", 128 ],
[ "C3", 1 ], [ "C4", 9 ], [ "C4 : C4", 2 ], [ "C4 x C2", 36 ],
[ "C4 x C2 x C2", 23 ], [ "C4 x C2 x C2 x C2", 3 ], [ "C4 x C4", 1 ],
[ "C4 x D8", 2 ], [ "C6", 3 ], [ "C6 x C2", 1 ], [ "D8", 63 ],
[ "D8 x D8", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ (((C2 x ((C2 x C2 x C2 x C2) : C2)) : C2) : C2) : C3", 1 ],
[ "(((C2 x (C4 : C4)) : C2) : C2) : C3", 1 ],
[ "(((C4 x C2) : C4) : C2) : 1", 1 ],
[ "((C2 x ((C2 x C2 x C2 x C2) : C2)) : C2) : 1", 6 ],
[ "((C2 x ((C4 x C2) : C2)) : C2) : 1", 11 ],
[ "((C2 x (C4 : C4)) : C2) : 1", 4 ], [ "((C2 x (C4 : C4)) : C2) : C3", 2 ],
[ "((C2 x C2 x ((C4 x C2) : C2)) : C2) : 1", 2 ],
[ "((C2 x C2 x C2 x C2) : C2) : C3", 2 ],
[ "((C2 x C2 x C2 x D8) : C2) : 1", 1 ], [ "((C2 x C2 x D8) : C2) : 1", 6 ],
[ "((C2 x D8 x D8) : C2) : 1", 1 ], [ "((C4 x C2 x C2 x C2) : C2) : 1", 2 ],
[ "((C4 x C2) : C4) : C3", 2 ], [ "((C4 x C4 x C2) : C2) : 1", 1 ],
[ "((C4 x C4) : C2) : C3", 2 ], [ "(C2 x C2 x C2 x C2) : C2", 11 ],
[ "(C2 x C2 x C2 x C2) : C3", 1 ], [ "(C4 x C2 x C2) : C2", 14 ],
[ "(C4 x C2) : C2", 8 ], [ "(C4 x C2) : C4", 6 ], [ "(C4 x C4) : C2", 5 ],
[ "(C4 x C4) : C3", 1 ], [ "A4", 1 ],
[ "C2 x (((C2 x C2 x C2 x C2) : C2) : C3)", 1 ],
[ "C2 x (((C4 x C4) : C2) : C3)", 1 ],
[ "C2 x ((C2 x C2 x C2 x C2) : C2)", 4 ],
[ "C2 x ((C2 x C2 x C2 x C2) : C3)", 1 ],
[ "C2 x ((C4 x C2 x C2) : C2)", 5 ], [ "C2 x ((C4 x C2) : C2)", 8 ],
[ "C2 x ((C4 x C4) : C2)", 2 ], [ "C2 x ((C4 x C4) : C3)", 1 ],
[ "C2 x (C4 : C4)", 3 ], [ "C2 x A4", 1 ], [ "C2 x C2", 1 ],
[ "C2 x C2 x C2", 3 ], [ "C2 x C2 x C2 x C2", 3 ],
[ "C2 x C2 x C2 x C2 x C2", 1 ], [ "C2 x C2 x C2 x D8", 1 ],
[ "C2 x C2 x D8", 11 ], [ "C2 x C4 x D8", 2 ], [ "C2 x D8", 18 ],
[ "C2 x D8 x D8", 1 ], [ "C4 : C4", 3 ], [ "C4 x ((C4 x C2) : C2)", 1 ],
[ "C4 x C2", 1 ], [ "C4 x C2 x C2", 3 ], [ "C4 x C2 x C2 x C2", 1 ],
[ "C4 x C4", 2 ], [ "C4 x C4 x C2", 2 ], [ "C4 x D8", 6 ], [ "D8", 3 ],
[ "D8 x D8", 7 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C2", 8 ], [ "(C4 x C2) : C4", 6 ], [ "C2 x C2", 1 ],
[ "C4 : C4", 3 ], [ "C4 x C2", 1 ], [ "C4 x C4", 2 ], [ "D8", 3 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));
[ [ [ 4, 2 ], 1 ], [ [ 8, 2 ], 1 ], [ [ 8, 3 ], 3 ], [ [ 16, 2 ], 2 ],
[ [ 16, 3 ], 8 ], [ [ 16, 4 ], 3 ], [ [ 32, 2 ], 6 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
101
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
1
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2 ], 2 ], [ [ 2, 2, 2 ], 10 ], [ [ 2, 2, 2, 2 ], 20 ],
[ [ 2, 2, 2, 2 ], 25 ], [ [ 2, 2, 2, 2, 2 ], 20 ],
[ [ 2, 2, 2, 2, 4 ], 9 ], [ [ 2, 2, 2, 4 ], 4 ], [ [ 2, 2, 4 ], 2 ],
[ [ 2, 2, 4, 4 ], 5 ], [ [ 2, 4, 4 ], 2 ], [ [ 4, 4 ], 1 ],

```

```

[ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2, 2, 2 ], 1 ] ]
gap> ChG:=CharacteristicSubgroups(G);;
gap> List(ChG,IdSmallGroup);
[ [ 768, 1084555 ], [ 384, 5863 ], [ 256, 51978 ], [ 64, 211 ],
  [ 128, 1411 ], [ 64, 267 ], [ 64, 202 ], [ 16, 14 ], [ 32, 51 ],
  [ 32, 51 ], [ 32, 21 ], [ 8, 5 ], [ 2, 1 ], [ 4, 2 ], [ 1, 1 ] ]
gap> E64:=ChG[6];
Group([ (1,12)(4,5)(6,7)(10,11), (2,3)(4,5)(8,9)(10,11), (1,12)(4,5)(8,9)
(10,11), (4,5)(10,11), (1,12)(4,5), (1,12) ])
gap> StructureDescription(E64);
"C2 x C2 x C2 x C2 x C2 x C2"
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x))]));
[ [ [ [ 2, 2 ], 4 ], 2 ], [ [ [ 2, 2, 2 ], 4 ], 10 ],
  [ [ [ 2, 2, 2, 2 ], 4 ], 20 ], [ [ [ 2, 2, 2, 2, 2 ], 2 ], 1 ],
  [ [ [ 2, 2, 2, 2, 2 ], 4 ], 24 ], [ [ [ 2, 2, 2, 2, 2, 2 ], 2 ], 3 ],
  [ [ [ 2, 2, 2, 2, 2, 2 ], 4 ], 17 ], [ [ [ 2, 2, 2, 2, 4 ], 1 ], 1 ],
  [ [ [ 2, 2, 2, 2, 4 ], 2 ], 8 ], [ [ [ 2, 2, 2, 4 ], 2 ], 4 ],
  [ [ [ 2, 2, 4 ], 2 ], 2 ], [ [ [ 2, 2, 4, 4 ], 1 ], 1 ],
  [ [ [ 2, 2, 4, 4 ], 2 ], 4 ], [ [ [ 2, 4, 4 ], 2 ], 2 ],
  [ [ [ 4, 4 ], 2 ], 1 ], [ [ [ 4, 4, 4 ], 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x))]));
[ [ [ [ 2, 2, 2, 2, 2, 2 ], 1 ], 1 ] ]

gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue, # G(8,2)=C4xC2
> x->IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPtrueC4xC2);
36
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPtrueC4xC2);
1
gap> IsInvariantUnderAutG(GcsHNPtrueC4xC2);
false
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2, 4 ], 6 ], [ [ 2, 2, 2, 4 ], 2 ], [ [ 2, 2, 4, 4 ], 17 ],
  [ [ 2, 4, 4 ], 7 ], [ [ 4, 4 ], 3 ], [ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2, 4 ], 1 ] ]

gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
63
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
3
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2, 4 ], 12 ], [ [ 2, 2, 2, 4 ], 6 ], [ [ 2, 2, 4 ], 2 ],
  [ [ 2, 2, 4, 4 ], 25 ], [ [ 2, 4, 4 ], 12 ], [ [ 4, 4 ], 3 ],
  [ [ 4, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),

```

```

> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2, 4 ], 2 ], [ [ 2, 2, 4, 4 ], 1 ] ]
gap> ChG:=CharacteristicSubgroups(G);;
gap> List(ChG,IdSmallGroup);
[ [ 768, 1084555 ], [ 384, 5863 ], [ 256, 51978 ], [ 64, 202 ],
  [ 128, 1411 ], [ 64, 267 ], [ 64, 211 ], [ 16, 14 ], [ 32, 51 ],
  [ 32, 21 ], [ 32, 51 ], [ 8, 5 ], [ 2, 1 ], [ 4, 2 ], [ 1, 1 ] ]
gap> C4xC4xC2:=ChG[10];
Group([ (1,7,12,6)(4,10,5,11), (2,8,3,9)(4,11,5,10), (1,12)(4,5)(6,7)
(10,11), (2,3)(4,5)(8,9)(10,11), (4,5)(10,11) ])
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),List([E64,C4xC4xC2],
> y->Order(Intersection(y,x))]));
[ [ [ [ 2, 2, 2, 2, 4 ], [ 4, 2 ] ], 12 ], [ [ [ 2, 2, 2, 4 ], [ 4, 2 ] ], 6 ],
  [ [ [ 2, 2, 4 ], [ 4, 2 ] ], 2 ], [ [ [ 2, 2, 4, 4 ], [ 2, 2 ] ], 4 ],
  [ [ [ 2, 2, 4, 4 ], [ 4, 2 ] ], 16 ], [ [ [ 2, 2, 4, 4 ], [ 4, 4 ] ], 5 ],
  [ [ [ 2, 4, 4 ], [ 4, 2 ] ], 10 ], [ [ [ 2, 4, 4 ], [ 4, 4 ] ], 2 ],
  [ [ [ 4, 4 ], [ 4, 2 ] ], 2 ], [ [ [ 4, 4 ], [ 4, 4 ] ], 1 ],
  [ [ [ 4, 4, 4 ], [ 2, 2 ] ], 2 ], [ [ [ 4, 4, 4 ], [ 2, 4 ] ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),List([E64,C4xC4xC2],
> y->Order(Intersection(y,x))]));
[ [ [ [ 2, 2, 2, 2, 4 ], [ 2, 2 ] ], 2 ],
  [ [ [ 2, 2, 4, 4 ], [ 2, 4 ] ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),List([E64,C4xC4xC2],
> y->StructureDescription(Intersection(y,x))]));
[ [ [ [ 2, 2, 2, 2, 4 ], [ "C2", "C2" ] ], 2 ],
  [ [ [ 2, 2, 4, 4 ], [ "C2", "C4" ] ], 1 ] ]

gap> GcsHNPfalseC4xC4:=Filtered(GcsHNPfalse, # G(16,2)=C4xC4
> x->IdSmallGroup(Representative(x))=[16,2]);;
gap> Length(GcsHNPfalseC4xC4);
1
gap> GcsHNPtrueC4xC4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[16,2]);;
gap> Length(GcsHNPtrueC4xC4);
2
gap> IsInvariantUnderAutG(GcsHNPtrueC4xC4);
false
gap> Collected(List(List(GcsHNPfalseC4xC4,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC4,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 4, 4 ], 1 ], [ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseC4xC4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(C4xC4xC2,x))]);
[ [ [ [ 4, 4, 4 ], 8 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(C4xC4xC2,x))]);
[ [ [ [ 2, 2, 4, 4 ], 8 ], 1 ], [ [ [ 4, 4, 4 ], 16 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(C4xC4xC2,x))]);
[ [ [ [ 2, 2, 4, 4 ], "C4 x C2" ], 1 ], [ [ [ 4, 4, 4 ], "C4 x C4" ], 1 ] ]

gap> GcsHNPfalseG16_3:=Filtered(GcsHNPfalse, # G(16,3)=(C4xC2):C2
> x->IdSmallGroup(Representative(x))=[16,3]);;
gap> Length(GcsHNPfalseG16_3);
35
gap> GcsHNPtrueG16_3:=Filtered(GcsHNPtrue,

```

```

> x->IdSmallGroup(Representative(x))=[16,3];;
gap> Length(GcsHNPtrueG16_3);
8
gap> IsInvariantUnderAutG(GcsHNPtrueG16_3);
false
gap> Collected(List(List(GcsHNPfalseG16_3,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 18 ], [ [ 2, 4, 4 ], 9 ], [ [ 4, 4 ], 3 ],
  [ [ 4, 4, 4 ], 5 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 5 ], [ [ 4, 4, 4 ], 3 ] ]
gap> G64_202:=ChG[4];
Group([ (1,7)(4,10)(5,11)(6,12), (2,8)(3,9)(4,11)(5,10), (1,12)(4,5)(6,7)
(10,11), (2,3)(4,5)(8,9)(10,11), (1,12)(4,5)(8,9), (4,5)(10,11) ])
gap> StructureDescription(G64_202);
"C2 x ((C2 x C2 x C2 x C2) : C2)"
gap> G128_1411:=ChG[5];
Group([ (1,7)(4,10)(5,11)(6,12), (2,8)(3,9)(4,11)(5,10), (1,12)(4,5)(6,7)
(10,11), (2,3)(4,5)(8,9)(10,11), (8,9)(10,11), (4,5)(10,11), (1,12)(4,5) ])
gap> StructureDescription(G128_1411);
"(C2 x ((C2 x C2 x C2 x C2) : C2)) : C2"
gap> Collected(List(List(GcsHNPfalseG16_3,Representative),
> x->[SortedList(List(Orbits(x),Length)),List([G64_202,G128_1411,E64]),
> y->Order(Intersection(y,x))]));
[ [ [ [ 2, 2, 4, 4 ], [ 4, 8, 8 ] ], 9 ],
  [ [ [ 2, 2, 4, 4 ], [ 4, 16, 8 ] ], 3 ],
  [ [ [ 2, 2, 4, 4 ], [ 8, 8, 8 ] ], 6 ],
  [ [ [ 2, 4, 4 ], [ 4, 16, 8 ] ], 3 ],
  [ [ [ 2, 4, 4 ], [ 8, 8, 8 ] ], 6 ],
  [ [ [ 4, 4 ], [ 4, 8, 8 ] ], 3 ],
  [ [ [ 4, 4, 4 ], [ 4, 8, 4 ] ], 2 ],
  [ [ [ 4, 4, 4 ], [ 8, 16, 4 ] ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->[SortedList(List(Orbits(x),Length)),List([G64_202,G128_1411,E64]),
> y->Order(Intersection(y,x))]);
[ [ [ [ 2, 2, 4, 4 ], [ 4, 8, 4 ] ], 2 ],
  [ [ [ 2, 2, 4, 4 ], [ 8, 16, 4 ] ], 3 ],
  [ [ [ 4, 4, 4 ], [ 8, 8, 4 ] ], 2 ],
  [ [ [ 4, 4, 4 ], [ 16, 8, 4 ] ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->[SortedList(List(Orbits(x),Length)),List([G64_202,G128_1411,E64]),
> y->StructureDescription(Intersection(y,x))]));
[ [ [ [ 2, 2, 4, 4 ], [ "C2 x C2", "C4 x C2", "C2 x C2" ] ], 2 ],
  [ [ [ 2, 2, 4, 4 ], [ "C2 x C2 x C2", "(C4 x C2) : C2", "C2 x C2" ] ], 3 ],
  [ [ [ 4, 4, 4 ], [ "(C4 x C2) : C2", "C2 x C2 x C2", "C2 x C2" ] ], 1 ],
  [ [ [ 4, 4, 4 ], [ "C4 x C2", "C4 x C2", "C2 x C2" ] ], 2 ] ]

gap> GcsHNPfalseC4x1C4:=Filtered(GcsHNPfalse, # G(16,4)=C4:C4
> x->IdSmallGroup(Representative(x))=[16,4]);;
gap> Length(GcsHNPfalseC4x1C4);
2
gap> GcsHNPtrueC4x1C4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[16,4]);;
gap> Length(GcsHNPtrueC4x1C4);
3
gap> IsInvariantUnderAutG(GcsHNPtrueC4x1C4);
false
gap> Collected(List(List(GcsHNPfalseC4x1C4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC4x1C4,Representative),

```

```

> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 4, 4 ], 2 ], [ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseC4xC4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(C4xC4xC2,x))]));
[ [ [ [ 4, 4, 4 ], 4 ], 2 ] ]

gap> Collected(List(List(GcsHNPtrueC4xC4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(C4xC4xC2,x))]);
[ [ [ [ 2, 2, 4, 4 ], 4 ], 2 ], [ [ [ 4, 4, 4 ], 8 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(C4xC4xC2,x))]);
[ [ [ [ 2, 2, 4, 4 ], "C2 x C2" ], 2 ], [ [ [ 4, 4, 4 ], "C4 x C2" ], 1 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[32,2]); # G(32,2)=(C4xC2):C4
6
gap> Number(GcstrueMin,x->IdSmallGroup(Representative(x))=[32,2]);

```

$$(2, 1, 12), G = 12T230 \approx (G_1)^5 \approx 4 \cdot (c)$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,230);
[2^5]L(6)
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3), (1,3,5,7,9)(2,4,6,8,12), (1,11)(2,8)(3,9)(10,12) ]
gap> H:=Stabilizer(G,1);
Group([ (6,7)(8,9), (2,7,5,9,11)(3,6,4,8,10), (4,8)(5,9)(6,10)(7,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2, 4 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
219
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 47 ], [ [ false ], 172 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
172
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
47
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "((C2 x C2 x C2 x C2) : C3) : C2", 2 ],
[ "((C2 x C2 x C2 x C2) : C5) : C2", 2 ], [ "(C2 x C2 x C2 x C2) : C2", 5 ],
[ "(C2 x C2 x C2 x C2) : C3", 1 ], [ "(C2 x C2 x C2 x C2) : C5", 1 ],
[ "(C4 x C2) : C2", 9 ], [ "1", 1 ], [ "A4", 6 ], [ "A5", 2 ],
[ "C10", 1 ], [ "C2", 5 ], [ "C2 x (((C2 x C2 x C2 x C2) : C3) : C2)", 1 ],
[ "C2 x (((C2 x C2 x C2 x C2) : C5) : C2)", 1 ],
[ "C2 x (((C2 x C2 x C2 x C2) : C2) : C2)", 1 ],
[ "C2 x (((C2 x C2 x C2 x C2) : C3) : C2)", 1 ],
[ "C2 x (((C2 x C2 x C2 x C2) : C5)", 1 ], [ "C2 x ((C4 x C2) : C2)", 3 ],
[ "C2 x A4", 6 ], [ "C2 x A5", 2 ], [ "C2 x C2", 25 ],
[ "C2 x C2 x C2", 24 ], [ "C2 x C2 x C2 x C2", 5 ],
[ "C2 x C2 x C2 x C2 x C2", 1 ], [ "C2 x C2 x D8", 3 ], [ "C2 x D8", 16 ],

```

```

[ "C2 x S4", 3 ], [ "C3", 1 ], [ "C4", 4 ], [ "C4 x C2", 10 ],
[ "C4 x C2 x C2", 3 ], [ "C5", 1 ], [ "C6", 1 ], [ "D10", 2 ],
[ "D12", 1 ], [ "D20", 1 ], [ "D8", 12 ], [ "S3", 2 ], [ "S4", 6 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(((C2 x ((C4 x C2) : C2)) : C2) : C2) : C3", 1 ],
[ "(((C2 x ((C2 x C2 x C2 x C2) : C2)) : C2) : 1", 1 ],
[ "(((C2 x ((C4 x C2) : C2)) : C2) : 1", 3 ],
[ "((C4 x C2) : C4) : C3", 2 ], [ "(C2 x C2 x C2 x C2 x C2) : A5", 1 ],
[ "(C2 x C2 x C2 x C2) : C2", 3 ], [ "(C2 x C2 x C2 x C2) : C3", 1 ],
[ "(C4 x C2) : C2", 3 ], [ "(C4 x C2) : C4", 2 ], [ "(C4 x C4) : C3", 1 ],
[ "A4", 2 ], [ "A5", 2 ], [ "C2 x ((C2 x C2 x C2 x C2) : C2)", 1 ],
[ "C2 x ((C2 x C2 x C2 x C2) : C3)", 1 ], [ "C2 x ((C4 x C2) : C2)", 3 ],
[ "C2 x ((C4 x C4) : C3)", 1 ], [ "C2 x (C4 : C4)", 1 ], [ "C2 x A4", 2 ],
[ "C2 x A5", 2 ], [ "C2 x C2", 2 ], [ "C2 x C2 x C2", 5 ],
[ "C2 x C2 x C2 x C2", 3 ], [ "C2 x C2 x C2 x C2 x C2", 1 ],
[ "C4 : C4", 1 ], [ "C4 x C4", 1 ], [ "C4 x C4 x C2", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "(C4 x C2) : C2", 3 ], [ "(C4 x C2) : C4", 2 ], [ "C2 x C2", 2 ],
[ "C4 : C4", 1 ], [ "C4 x C4", 1 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));
[ [ [ 4, 2 ], 2 ], [ [ 16, 2 ], 1 ], [ [ 16, 3 ], 3 ], [ [ 16, 4 ], 1 ],
[ [ 32, 2 ], 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPfalseC2xC2);
25
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPtrueC2xC2);
2
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2 ], 2 ], [ [ 2, 2, 2, 2 ], 2 ], [ [ 2, 2, 2, 2, 2 ], 2 ],
[ [ 2, 2, 2, 2, 2 ], 4 ], [ [ 2, 2, 2, 2, 4 ], 6 ], [ [ 2, 2, 4 ], 2 ],
[ [ 2, 2, 4, 4 ], 4 ], [ [ 4, 4 ], 1 ], [ [ 4, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2, 2 ], 2 ] ]
gap> ChG:=CharacteristicSubgroups(G);
[ Group(), Group([ (1,12)(2,3)(4,5)(6,7)(8,9)(10,11) ]),
Group([ (6,7)(8,9), (8,9)(10,11), (1,12)(8,9), (1,12)(2,3), (4,5)(10,11) ]),
[2^5]L(6) ]
gap> List(ChG,IdSmallGroup);
[ [ 1, 1 ], [ 2, 1 ], [ 32, 51 ], [ 1920, 240998 ] ]
gap> E32:=ChG[3];
Group([ (6,7)(8,9), (8,9)(10,11), (1,12)(8,9), (1,12)(2,3), (4,5)(10,11) ])
gap> StructureDescription(E32);
"C2 x C2 x C2 x C2 x C2"
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E32,x))]));
[ [ [ [ 2, 2, 2 ], 4 ], 2 ], [ [ [ 2, 2, 2, 2 ], 4 ], 2 ],
[ [ [ 2, 2, 2, 2, 2 ], 4 ], 2 ], [ [ [ 2, 2, 2, 2, 2, 2 ], 2 ], 1 ],
[ [ [ 2, 2, 2, 2, 2, 2 ], 4 ], 3 ], [ [ [ 2, 2, 2, 2, 4 ], 1 ], 2 ],
[ [ [ 2, 2, 2, 2, 4 ], 2 ], 4 ], [ [ [ 2, 2, 4 ], 2 ], 2 ],
[ [ [ 2, 2, 4, 4 ], 1 ], 2 ], [ [ [ 2, 2, 4, 4 ], 2 ], 2 ],
[ [ [ 4, 4 ], 2 ], 1 ], [ [ [ 4, 4, 4 ], 1 ], 2 ] ]

```

```

gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E32,x))]));
[ [ [ [ 2, 2, 2, 2, 2, 2 ], 1 ], 2 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,2]); # G(16,2)=C4xC4
1

gap> GcsHNPfalseG16_3:=Filtered(GcsHNPfalse, # G(16,3)=(C4xC2):C2
> x->IdSmallGroup(Representative(x))=[16,3]);
gap> Length(GcsHNPfalseG16_3);
9
gap> GcsHNPtrueG16_3:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[16,3]);
gap> Length(GcsHNPtrueG16_3);
3
gap> IsInvariantUnderAutG(GcsHNPtrueG16_3);
false
gap> Collected(List(List(GcsHNPfalseG16_3,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 4, 4 ], 3 ], [ [ 2, 4, 4 ], 3 ], [ [ 4, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPfalseG16_3,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E32,x))]));
[ [ [ [ 2, 2, 4, 4 ], 8 ], 3 ], [ [ [ 2, 4, 4 ], 8 ], 3 ],
  [ [ [ 4, 4, 4 ], 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E32,x))]));
[ [ [ [ 2, 2, 4, 4 ], 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(E32,x))]));
[ [ [ [ 2, 2, 4, 4 ], "C2 x C2" ], 3 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[16,4]); # G(16,4)=C4:C4
1

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[32,2]); # G(32,2)=(C4xC2):C4
2
gap> Number(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))=[32,2]);
2

```

(2-1-14) $G = 12T255 \simeq (C_2)^6 \rtimes A_5(6) \simeq C_2 \wr A_5(6)$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,255);
[2^6]L(6)=2wrL(6)
gap> GeneratorsOfGroup(G);
[ (1,12), (1,3,5,7,9)(2,4,6,8,12), (1,11)(2,8)(3,9)(10,12) ]
gap> H:=Stabilizer(G,1);
Group([ (6,7), (2,6,4,8,10)(3,7,5,9,11), (4,8)(5,9)(6,10)(7,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 0 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
963

```

```

gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 193 ], [ [ false ], 770 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
770
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
193
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "(C2 x C2 x C2 x C2) : C3" : C2", 4 ],
[ "(C2 x C2 x C2 x C2) : C5" : C2", 4 ], [ "(C2 x C2 x C2 x C2) : C2", 39 ],
[ "(C2 x C2 x C2 x C2) : C3", 1 ], [ "(C2 x C2 x C2 x C2) : C5", 1 ],
[ "(C4 x C2 x C2) : C2", 4 ], [ "(C4 x C2) : C2", 35 ],
[ "(C4 x C4) : C2", 1 ], [ "1", 1 ], [ "A4", 5 ], [ "A5", 1 ],
[ "C10", 3 ], [ "C10 x C2", 1 ], [ "C2", 10 ],
[ "C2 x (((C2 x C2 x C2 x C2) : C3) : C2)", 6 ],
[ "C2 x (((C2 x C2 x C2 x C2) : C5) : C2)", 6 ],
[ "C2 x (((C2 x C2 x C2 x C2) : C2) : C2)", 16 ],
[ "C2 x (((C2 x C2 x C2 x C2) : C3) : C3)", 3 ],
[ "C2 x (((C2 x C2 x C2 x C2) : C5) : C3)", 3 ], [ "C2 x ((C4 x C2) : C2)", 24 ],
[ "C2 x A4", 13 ], [ "C2 x A5", 1 ], [ "C2 x C2", 56 ],
[ "C2 x C2 x (((C2 x C2 x C2 x C2) : C3) : C2)", 1 ],
[ "C2 x C2 x (((C2 x C2 x C2 x C2) : C5) : C2)", 1 ],
[ "C2 x C2 x (((C2 x C2 x C2 x C2) : C2) : C2)", 1 ],
[ "C2 x C2 x (((C2 x C2 x C2 x C2) : C3) : C3)", 1 ],
[ "C2 x C2 x (((C2 x C2 x C2 x C2) : C5) : C5)", 1 ],
[ "C2 x C2 x ((C4 x C2) : C2)", 3 ], [ "C2 x C2 x A4", 4 ],
[ "C2 x C2 x C2", 95 ], [ "C2 x C2 x C2 x C2", 42 ],
[ "C2 x C2 x C2 x C2 x C2", 8 ], [ "C2 x C2 x C2 x C2 x C2 x C2", 1 ],
[ "C2 x C2 x C2 x D8", 3 ], [ "C2 x C2 x D10", 1 ], [ "C2 x C2 x D8", 42 ],
[ "C2 x C2 x S3", 1 ], [ "C2 x C2 x S4", 3 ], [ "C2 x D8", 128 ],
[ "C2 x S4", 18 ], [ "C3", 1 ], [ "C4", 9 ], [ "C4 : C4", 2 ],
[ "C4 x C2", 36 ], [ "C4 x C2 x C2", 23 ], [ "C4 x C2 x C2 x C2", 3 ],
[ "C4 x C4", 1 ], [ "C4 x D8", 2 ], [ "C5", 1 ], [ "C6", 3 ],
[ "C6 x C2", 1 ], [ "D10", 4 ], [ "D12", 6 ], [ "D20", 6 ], [ "D8", 63 ],
[ "D8 x D8", 1 ], [ "S3", 4 ], [ "S4", 12 ] ]

gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ (((C2 x ((C2 x C2 x C2 x C2) : C2)) : C2) : C2) : C3", 1 ],
[ (((C4 x C2) : C4) : C2) : 1", 4 ], [ (((C4 x C2) : C4) : C2) : C3", 2 ],
[ (((C2 x ((C2 x C2 x C2 x C2) : C2)) : C2) : 1", 6 ],
[ (((C2 x ((C2 x C2 x C2 x C2) : C2)) : C2) : C3", 1 ],
[ (((C2 x ((C4 x C2 x C2) : C2)) : C2) : 1", 1 ],
[ (((C2 x ((C4 x C2) : C2)) : C2) : 1", 16 ],
[ (((C2 x (C4 : C4)) : C2) : C2) : 1", 2 ],
[ (((C2 x C2 x ((C2 x C2 x C2 x C2) : C2)) : C2) : 1", 1 ],
[ (((C2 x C2 x ((C4 x C2) : C2)) : C2) : 1", 1 ],
[ (((C2 x C2 x C2 x C2 x C2) : A5) : C2", 1 ],
[ (((C2 x C2 x C2 x C2) : C2) : C3", 2 ], [ (((C2 x C2 x D8) : C2) : 1", 2 ],
[ (((C2 x C4 x D8) : C2) : 1", 1 ],
[ (((C4 x C2 x C2 x C2) : C2) : 1", 1 ], [ (((C4 x C2) : C4) : C3", 2 ],
[ (((C4 x C4) : C2) : C3", 2 ], [ "(C2 x C2 x C2 x C2 x C2) : A5", 1 ],
[ "(C2 x C2 x C2 x C2) : C2", 11 ], [ "(C2 x C2 x C2 x C2) : C3", 1 ],
[ "(C4 x C2 x C2) : C2", 14 ], [ "(C4 x C2) : C2", 8 ],
[ "(C4 x C2) : C4", 6 ], [ "(C4 x C4) : C2", 5 ], [ "(C4 x C4) : C3", 1 ],
[ "A4", 1 ], [ "A5", 1 ], [ "C2 x (((C2 x C2 x C2 x C2) : C2) : C3)", 1 ],
[ "C2 x (((C4 x C4) : C2) : C3)", 1 ],
[ "C2 x ((C2 x C2 x C2 x C2) : C2)", 4 ],
[ "C2 x ((C2 x C2 x C2 x C2) : C3)", 1 ],

```

```

[ "C2 x ((C4 x C2 x C2) : C2)", 5 ], [ "C2 x ((C4 x C2) : C2)", 8 ],
[ "C2 x ((C4 x C4) : C2)", 2 ], [ "C2 x ((C4 x C4) : C3)", 1 ],
[ "C2 x (C4 : C4)", 3 ], [ "C2 x A4", 1 ], [ "C2 x A5", 1 ],
[ "C2 x C2", 1 ], [ "C2 x C2 x C2", 3 ], [ "C2 x C2 x C2 x C2", 3 ],
[ "C2 x C2 x C2 x C2 x C2", 1 ], [ "C2 x C2 x C2 x D8", 1 ],
[ "C2 x C2 x D8", 11 ], [ "C2 x C4 x D8", 2 ], [ "C2 x D8", 18 ],
[ "C2 x D8 x D8", 1 ], [ "C4 : C4", 3 ], [ "C4 x ((C4 x C2) : C2)", 1 ],
[ "C4 x C2", 1 ], [ "C4 x C2 x C2", 3 ], [ "C4 x C2 x C2 x C2", 1 ],
[ "C4 x C4", 2 ], [ "C4 x C4 x C2", 2 ], [ "C4 x D8", 6 ], [ "D8", 3 ],
[ "D8 x D8", 7 ] ]

gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));;
[ [ "(C4 x C2) : C2", 8 ], [ "(C4 x C2) : C4", 6 ], [ "C2 x C2", 1 ],
[ "C4 : C4", 3 ], [ "C4 x C2", 1 ], [ "C4 x C4", 2 ], [ "D8", 3 ] ]
gap> Collected(List(GcsHNPtrueMin,x->IdSmallGroup(Representative(x))));;
[ [ [ 4, 2 ], 1 ], [ [ 8, 2 ], 1 ], [ [ 8, 3 ], 3 ], [ [ 16, 2 ], 2 ],
[ [ 16, 3 ], 8 ], [ [ 16, 4 ], 3 ], [ [ 32, 2 ], 6 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue, # G(4,2)=C2xC2
> x->Order(Representative(x))=4 and IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
56
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=4 and IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
1
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2 ], 1 ], [ [ 2, 2, 2 ], 4 ], [ [ 2, 2, 2, 2 ], 7 ],
[ [ 2, 2, 2, 2, 2 ], 9 ], [ [ 2, 2, 2, 2, 2, 2 ], 11 ],
[ [ 2, 2, 2, 2, 4 ], 9 ], [ [ 2, 2, 2, 4 ], 4 ], [ [ 2, 2, 4 ], 2 ],
[ [ 2, 2, 4, 4 ], 5 ], [ [ 2, 4, 4 ], 2 ], [ [ 4, 4 ], 1 ],
[ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2, 2, 2 ], 1 ] ]
gap> ChG:=CharacteristicSubgroups(G);;
gap> ChG=NormalSubgroups(G);
true
gap> List(ChG,Order);
[ 1, 2, 32, 1920, 64, 3840 ]
gap> List(ChG,StructureDescription);
[ "1", "C2", "C2 x C2 x C2 x C2 x C2", "(C2 x C2 x C2 x C2 x C2) : A5",
"C2 x C2 x C2 x C2 x C2 x C2", "((C2 x C2 x C2 x C2 x C2) : A5) : C2" ]
gap> E64:=ChG[5];
C2 x C2 x C2 x C2 x C2 x C2
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x))]));
[ [ [ [ 2, 2 ], 4 ], 1 ], [ [ [ 2, 2, 2 ], 4 ], 4 ],
[ [ [ 2, 2, 2, 2 ], 4 ], 7 ], [ [ [ 2, 2, 2, 2, 2 ], 2 ], 1 ],
[ [ [ 2, 2, 2, 2, 2 ], 4 ], 8 ], [ [ [ 2, 2, 2, 2, 2, 2 ], 2 ], 3 ],
[ [ [ 2, 2, 2, 2, 2, 2 ], 4 ], 8 ], [ [ [ 2, 2, 2, 2, 4 ], 1 ], 1 ],
[ [ [ 2, 2, 2, 2, 4 ], 2 ], 8 ], [ [ [ 2, 2, 2, 4 ], 2 ], 4 ],
[ [ [ 2, 2, 4 ], 2 ], [ [ [ 2, 2, 4, 4 ], 1 ], 1 ],
[ [ [ 2, 2, 4, 4 ], 2 ], 4 ], [ [ [ 2, 4, 4 ], 2 ], 2 ],
[ [ [ 4, 4 ], 2 ], 1 ], [ [ [ 4, 4, 4 ], 1 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x))]));

```

```

[ [ [ [ 2, 2, 2, 2, 2, 2 ], 1 ], 1 ] ]

gap> GcsHNPfalseC4xC2:=Filtered(GcsHNPfalse, # G(8,2)=C4xC2
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,2]);
gap> Length(GcsHNPfalseC4xC2);
36
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,2]);
gap> Length(GcsHNPtrueC4xC2);
1
gap> IsInvariantUnderAutG(GcsHNPtrueC4xC2);
false
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 2, 2, 4 ], 6 ], [ [ 2, 2, 2, 4 ], 2 ], [ [ 2, 2, 4, 4 ], 17 ],
  [ [ 2, 4, 4 ], 7 ], [ [ 4, 4 ], 3 ], [ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 2, 2, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x))]));
[ [ [ [ 2, 2, 2, 2, 4 ], 4 ], 6 ], [ [ [ 2, 2, 2, 4 ], 4 ], 2 ],
  [ [ [ 2, 2, 4, 4 ], 2 ], 2 ], [ [ [ 2, 2, 4, 4 ], 4 ], 15 ],
  [ [ [ 2, 4, 4 ], 4 ], 7 ], [ [ [ 4, 4 ], 4 ], 3 ],
  [ [ [ 4, 4, 4 ], 2 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x))]);
[ [ [ [ 2, 2, 2, 2, 4 ], 2 ], 1 ] ]

gap> GcsHNPfalseD4:=Filtered(GcsHNPtrue, # G(8,3)=D4
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,3]);
gap> Length(GcsHNPfalseD4);
63
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,3]);
gap> Length(GcsHNPtrueD4);
3
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x))]);
[ [ [ [ 2, 2, 2, 2, 4 ], 4 ], 12 ], [ [ [ 2, 2, 2, 4 ], 4 ], 6 ],
  [ [ [ 2, 2, 4 ], 4 ], 2 ], [ [ [ 2, 2, 4, 4 ], 2 ], 4 ],
  [ [ [ 2, 2, 4, 4 ], 4 ], 21 ], [ [ [ 2, 4, 4 ], 4 ], 12 ],
  [ [ [ 4, 4 ], 4 ], 3 ], [ [ [ 4, 4, 4 ], 2 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x))]);
[ [ [ [ 2, 2, 2, 2, 4 ], 2 ], 2 ], [ [ [ 2, 2, 4, 4 ], 2 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x))]);
[ [ [ [ 2, 2, 2, 2, 4 ], 4 ], 12 ], [ [ [ 2, 2, 2, 4 ], 4 ], 6 ],
  [ [ [ 2, 2, 4 ], 4 ], 2 ], [ [ [ 2, 2, 4, 4 ], 2 ], 4 ],
  [ [ [ 2, 2, 4, 4 ], 4 ], 21 ], [ [ [ 2, 4, 4 ], 4 ], 12 ],
  [ [ [ 4, 4 ], 4 ], 3 ], [ [ [ 4, 4, 4 ], 2 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x))]);
[ [ [ [ 2, 2, 2, 2, 4 ], 2 ], 2 ], [ [ [ 2, 2, 4, 4 ], 2 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->List(ChG,y->Order(Intersection(y,x))));
```

[[[1, 1, 2, 4, 2, 8], 7], [[1, 1, 2, 4, 4, 8], 32],
 [[1, 1, 4, 4, 4, 8], 12], [[1, 1, 4, 8, 4, 8], 12]]

```

gap> Collected(List(List(GcsHNPfalseD4,Representative),
```

```

> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x)),
> Order(Normalizer(G,x))]);
[ [ [ [ 2, 2, 2, 2, 4 ], 4, 64 ], 6 ], [ [ [ 2, 2, 2, 2, 4 ], 4, 128 ], 6 ],
[ [ [ 2, 2, 2, 4 ], 4, 64 ], 6 ], [ [ [ 2, 2, 4 ], 4, 128 ], 2 ],
[ [ [ 2, 2, 4, 4 ], 2, 64 ], 4 ], [ [ [ 2, 2, 4, 4 ], 4, 64 ], 15 ],
[ [ [ 2, 2, 4, 4 ], 4, 128 ], 6 ], [ [ [ 2, 4, 4 ], 4, 64 ], 12 ],
[ [ [ 4, 4 ], 4, 64 ], 1 ], [ [ [ 4, 4 ], 4, 128 ], 2 ],
[ [ [ 4, 4, 4 ], 2, 32 ], 1 ], [ [ [ 4, 4, 4 ], 2, 64 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x)),
> Order(Normalizer(G,x))]));
[ [ [ [ 2, 2, 2, 2, 4 ], 2, 64 ], 2 ], [ [ [ 2, 2, 4, 4 ], 2, 32 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x)),
> StructureDescription(Normalizer(G,x))]);
[ [ [ [ 2, 2, 2, 2, 4 ], 2, "C2 x C2 x C2 x D8" ], 2 ],
[ [ [ 2, 2, 4, 4 ], 2, "C2 x C2 x D8" ], 1 ] ]

gap> GcsHNPfalseC4xC4:=Filtered(GcsHNPfalse, # G(16,2)=C4xC4
> x->Order(Representative(x))=16 and IdSmallGroup(Representative(x))=[16,2]);;
gap> Length(GcsHNPfalseC4xC4);
1
gap> GcsHNPtrueC4xC4:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=16 and IdSmallGroup(Representative(x))=[16,2]);;
gap> Length(GcsHNPtrueC4xC4);
2
gap> IsInvariantUnderAutG(GcsHNPtrueC4xC4);
false
gap> Collected(List(List(GcsHNPfalseC4xC4,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC4,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 4, 4 ], 1 ], [ [ 4, 4, 4 ], 1 ] ]
gap> DG:=DerivedSubgroup(G);
Group([ (1,12)(2,3), (1,12)(10,11), (1,3,9,11,5)(2,8,10,4,12), (1,11,7,2,5)
(3,4,12,10,6) ])
gap> StructureDescription(DG);
"(C2 x C2 x C2 x C2 x C2) : A5"
gap> Collected(List(List(GcsHNPfalseC4xC4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(DG,x))]));
[ [ [ [ 4, 4, 4 ], 8 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(DG,x))]));
[ [ [ [ 2, 2, 4, 4 ], 8 ], 1 ], [ [ [ 4, 4, 4 ], 16 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DG,x))]);
[ [ [ [ 2, 2, 4, 4 ], "C4 x C2" ], 1 ], [ [ [ 4, 4, 4 ], "C4 x C4" ], 1 ] ]

gap> GcsHNPfalseG16_3:=Filtered(GcsHNPfalse, # G(16,3)=(C4xC2):C2
> x->Order(Representative(x))=16 and IdSmallGroup(Representative(x))=[16,3]);;
gap> Length(GcsHNPfalseG16_3);
35
gap> GcsHNPtrueG16_3:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=16 and IdSmallGroup(Representative(x))=[16,3]);;
gap> Length(GcsHNPtrueG16_3);
8
gap> IsInvariantUnderAutG(GcsHNPtrueG16_3);
false
gap> Collected(List(List(GcsHNPfalseG16_3,Representative),
> x->SortedList(List(Orbits(x),Length))));
```

```

[ [ [ 2, 2, 4, 4 ], 18 ], [ [ 2, 4, 4 ], 9 ], [ [ 4, 4 ], 3 ],
  [ [ 4, 4, 4 ], 5 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 4, 4 ], 5 ], [ [ 4, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPFalseG16_3,Representative),
> x->[SortedList(List(Orbits(x),Length)),List(ChG,
> y->Order(Intersection(y,x)))]));
[ [ [ [ 2, 2, 4, 4 ], [ 1, 1, 4, 8, 8, 16 ] ], 10 ],
  [ [ [ 2, 2, 4, 4 ], [ 1, 1, 8, 8, 8, 16 ] ], 5 ],
  [ [ [ 2, 2, 4, 4 ], [ 1, 1, 8, 16, 8, 16 ] ], 3 ],
  [ [ [ 2, 4, 4 ], [ 1, 1, 4, 8, 8, 16 ] ], 4 ],
  [ [ [ 2, 4, 4 ], [ 1, 1, 8, 8, 8, 16 ] ], 2 ],
  [ [ [ 2, 4, 4 ], [ 1, 1, 8, 16, 8, 16 ] ], 3 ],
  [ [ [ 4, 4 ], [ 1, 1, 4, 8, 8, 16 ] ], 2 ],
  [ [ [ 4, 4 ], [ 1, 1, 8, 8, 8, 16 ] ], 1 ],
  [ [ [ 4, 4, 4 ], [ 1, 1, 4, 8, 4, 16 ] ], 2 ],
  [ [ [ 4, 4, 4 ], [ 1, 1, 4, 16, 4, 16 ] ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->[SortedList(List(Orbits(x),Length)),List(ChG,
> y->Order(Intersection(y,x)))]));
[ [ [ [ 2, 2, 4, 4 ], [ 1, 1, 4, 8, 4, 16 ] ], 2 ],
  [ [ [ 2, 2, 4, 4 ], [ 1, 1, 4, 16, 4, 16 ] ], 3 ],
  [ [ [ 4, 4, 4 ], [ 1, 1, 4, 8, 4, 16 ] ], 1 ],
  [ [ [ 4, 4, 4 ], [ 1, 2, 4, 8, 4, 16 ] ], 2 ] ]
gap> Collected(List(List(GcsHNPFalseG16_3,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x)),
> Order(Normalizer(G,x))]));
[ [ [ [ 2, 2, 4, 4 ], 8, 128 ], 9 ], [ [ [ 2, 2, 4, 4 ], 8, 256 ], 9 ],
  [ [ [ 2, 4, 4 ], 8, 128 ], 9 ], [ [ [ 4, 4 ], 8, 256 ], 3 ],
  [ [ [ 4, 4, 4 ], 4, 128 ], 5 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(E64,x)),
> Order(Normalizer(G,x))]);
[ [ [ [ 2, 2, 4, 4 ], 4, 128 ], 5 ], [ [ [ 4, 4, 4 ], 4, 64 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueG16_3,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(E64,x)),
> StructureDescription(Normalizer(G,x))]);
[ [ [ [ 2, 2, 4, 4 ], "C2 x C2", "C2 x D8 x D8" ], 5 ],
  [ [ [ 4, 4, 4 ], "C2 x C2", "C2 x ((C2 x C2 x C2 x C2) : C2)" ], 1 ],
  [ [ [ 4, 4, 4 ], "C2 x C2", "C2 x ((C4 x C2 x C2) : C2)" ], 2 ] ]

gap> GcsHNPFalseC4x1C4:=Filtered(GcsHNPFalse, # G(16,4)=C4:C4
> x->Order(Representative(x))=16 and IdSmallGroup(Representative(x))=[16,4]];
gap> Length(GcsHNPFalseC4x1C4);
2
gap> GcsHNPtrueC4x1C4:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=16 and IdSmallGroup(Representative(x))=[16,4]);
gap> Length(GcsHNPtrueC4x1C4);
3
gap> IsInvariantUnderAutG(GcsHNPtrueC4x1C4);
false
gap> Collected(List(List(GcsHNPFalseC4x1C4,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 4, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC4x1C4,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 4, 4 ], 2 ], [ [ 4, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPFalseC4x1C4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(DG,x))]));
[ [ [ [ 4, 4, 4 ], 8 ], 2 ] ]

```

```

gap> Collected(List(List(GcsHNPtrueC4x1C4,Representative),
> x->[SortedList(List(Orbits(x),Length)),Order(Intersection(DG,x))]));
[ [ [ [ 2, 2, 4, 4 ], 8 ], 2 ], [ [ [ 4, 4, 4 ], 16 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4x1C4,Representative),
> x->[SortedList(List(Orbits(x),Length)),
> StructureDescription(Intersection(DG,x))]));
[ [ [ [ 2, 2, 4, 4 ], "C4 x C2" ], 2 ], [ [ [ 4, 4, 4 ], "C4 : C4" ], 1 ] ]

gap> Number(List(Gcs,Representative), # G(32,2)=(C4xC2):C4
> x->Order(Representative(x))=32 and IdSmallGroup(x)=[32,2]);
6
gap> Number(List(GcsHNPtrueMin,Representative),
> x->Order(Representative(x))=32 and IdSmallGroup(x)=[32,2]);
6

```

Example 7.5 ($G = 12Tm$ ($m = 10, 37, 77, 210, 214, 242, 271$)).

(2-2-1) $G = 12T10 \simeq S_3 \times V_4$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,10);
S(3)[x]E(4)
gap> GeneratorsOfGroup(G);
[ (1,5,9)(2,6,10)(3,7,11)(4,8,12), (1,5)(2,10)(4,8)(7,11),
  (1,10)(2,5)(3,12)(4,7)(6,9)(8,11), (1,7)(2,8)(3,9)(4,10)(5,11)(6,12) ]
gap> H:=Stabilizer(G,1);
Group([ (2,6)(3,11)(5,9)(8,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 2 ], [ ] ] ]
gap> GroupCohomology(G,3); #  $H^3(G, \mathbb{Z}) = M(G)$ : Schur multiplier of G
[ 2, 2, 2 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
gap> cG:=cGs[6];
rec( MinimalStemExtension := <permutation group of size 48 with 5 generators>,
  epi := [ (1,6)(2,10)(3,14)(4,16)(5,17)(7,21)(8,23)(9,24)(11,27)(12,29)(13,
    30)(15,31)(18,34)(19,36)(20,37)(22,38)(25,40)(26,41)(28,42)(32,44)(33,
    45)(35,46)(39,47)(43,48), (1,4)(2,8)(3,12)(5,16)(6,15)(7,19)(9,23)(10,
    22)(11,25)(13,29)(14,28)(17,31)(18,32)(20,36)(21,35)(24,38)(26,40)(27,
    39)(30,42)(33,44)(34,43)(37,46)(41,47)(45,48),
    (1,2)(3,18)(4,8)(5,9)(6,10)(7,11)(12,32)(13,33)(14,34)(15,22)(16,23)(17,
    24)(19,25)(20,26)(21,27)(28,43)(29,44)(30,45)(31,38)(35,39)(36,40)(37,
    41)(42,48)(46,47), (1,11,3)(2,18,7)(4,25,12)(5,26,13)(6,27,14)(8,32,
    19)(9,33,20)(10,34,21)(15,39,28)(16,40,29)(17,41,30)(22,43,35)(23,44,
    36)(24,45,37)(31,47,42)(38,48,46) ] ->
  [ (1,7)(2,8)(3,9)(4,10)(5,11)(6,12), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
    (2,6)(3,11)(5,9)(8,12), (1,5,9)(2,6,10)(3,7,11)(4,8,12) ] )
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 48 with 5 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 4 with 2 generators>
```

```

gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
32
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf));
[ [ [ true ], 10 ], [ [ false ], 22 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
22
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
10
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "C2", 7 ], [ "C2 x C2", 3 ], [ "C3", 1 ], [ "C6", 3 ],
[ "D12", 3 ], [ "S3", 4 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 4 ], [ "C2 x C2 x C2", 1 ], [ "C2 x C2 x S3", 1 ],
[ "C6 x C2", 1 ], [ "D12", 3 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 4 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

```

```

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPfalseC2xC2);
3
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPtrueC2xC2);
4
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 4, 4, 4 ], 4 ] ]

```

$$(2\text{-}2\text{-}2) \quad G = 12T37 \simeq (S_3)^2 \times C_2.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,37);
[3^2:2]E(4)
gap> GeneratorsOfGroup(G);
[ (2,6,10)(4,8,12), (1,5)(2,10)(4,8)(7,11), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
(1,7)(2,8)(3,9)(4,10)(5,11)(6,12) ]
gap> H:=Stabilizer(G,1);
Group([ (2,6,10)(4,8,12), (3,11)(4,12)(5,9)(6,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ ], [ [ 2 ], [ ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G

```

```

[ 2, 2, 2 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2 ][ 2 ]
[ 2 ][  ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
gap> cG:=cGs[2];;
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 144 with 6 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 12 with 2 generators>
gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 2, 2, 2 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[1]=[2];
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
69
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 20 ], [ [ false ], 49 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
49
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
20
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));;
[ [ "(C3 x C3) : C2", 2 ], [ "1", 1 ], [ "C2", 7 ],
[ "C2 x ((C3 x C3) : C2)", 1 ], [ "C2 x C2", 3 ], [ "C3", 3 ],
[ "C3 x C3", 1 ], [ "C3 x S3", 4 ], [ "C6", 7 ], [ "C6 x C3", 1 ],
[ "D12", 7 ], [ "S3", 10 ], [ "S3 x S3", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "C2 x C2", 4 ], [ "C2 x C2 x C2", 1 ], [ "C2 x C2 x S3", 2 ],
[ "C2 x S3 x S3", 1 ], [ "C6 x C2", 2 ], [ "C6 x S3", 2 ], [ "D12", 6 ],
[ "S3 x S3", 2 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));;
[ [ "C2 x C2", 4 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);

```

```

3
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
4
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 4 ] ]

```

$$(2\text{-}2\text{-}3) \quad G = 12T77 \simeq (S_3)^2 \rtimes V_4.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,77);
[S(3)^2]E(4)
gap> GeneratorsOfGroup(G);
[ (2,6,10)(4,8,12), (2,10)(4,8), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
 (1,7)(2,8)(3,9)(4,10)(5,11)(6,12) ]
gap> H:=Stabilizer(G,1);
Group([ (2,6,10)(4,8,12), (2,10)(4,8), (3,11)(5,9) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 1 ] ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2, 2, 2 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2, 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2, 2 ][ 2, 2 ]
[ 2, 2 ][ 2, 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
gap> cG:=cGs[1];;
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 288 with 7 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 24 with 3 generators>
gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 2, 2, 2, 2 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2, 2 ], [ [ 2, 2, 2 ], [ [ 1, 1, 0 ], [ 0, 0, 1 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ 2 ], [ [ 2, 2, 2 ], [ [ 1, 1, 1 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Number(FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[2][2],
> y->(y[2]+y[3]) mod 2=1)>0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
86
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtruefn:=List(GcsH,x->List(x,HNPtruefalsefn));;

```

```

gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 19 ], [ [ false ], 67 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
67
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
19
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3) : C2", 2 ], [ "(C3 x C3) : C4", 2 ], [ "(S3 x S3) : C2", 2 ],
[ "1", 1 ], [ "C2", 7 ], [ "C2 x ((C3 x C3) : C2)", 1 ], [ "C2 x C2", 7 ],
[ "C2 x C2 x C2", 1 ], [ "C2 x C2 x S3", 1 ], [ "C2 x S3 x S3", 1 ],
[ "C3", 2 ], [ "C3 x C3", 1 ], [ "C3 x S3", 4 ], [ "C4", 2 ], [ "C6", 6 ],
[ "C6 x C2", 1 ], [ "C6 x C3", 1 ], [ "C6 x S3", 1 ], [ "D12", 9 ],
[ "D8", 2 ], [ "S3", 8 ], [ "S3 x S3", 5 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(S3 x S3) : C2", 2 ], [ "C2 x ((C3 x C3) : C4)", 1 ],
[ "C2 x ((S3 x S3) : C2)", 1 ], [ "C2 x C2", 2 ], [ "C2 x C2 x C2", 1 ],
[ "C2 x C2 x S3", 1 ], [ "C2 x D8", 1 ], [ "C2 x S3 x S3", 1 ],
[ "C4 x C2", 1 ], [ "C6 x C2", 1 ], [ "C6 x S3", 1 ], [ "D12", 3 ],
[ "D8", 2 ], [ "S3 x S3", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 2 ], [ "C4 x C2", 1 ], [ "D8", 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
7
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
2
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2, 4 ], 2 ], [ [ 2, 2, 4, 4 ], 4 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 2 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[8,2]); # G(8,2)=C4xC2
1

gap> GcsHNPfalseD4:=Filtered(GcsHNPfalse, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPfalseD4);
2
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
2
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 2 ] ]

```

```

gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 8 ], 2 ] ]

(2-2-4)  $G = 12T210 \simeq (C_3)^4 \rtimes (D_4 \times C_2)$ .
```

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,210);
[3^4:2^2]E(4)
gap> GeneratorsOfGroup(G);
[ (4,8,12), (2,10)(4,8), (1,10)(2,5)(3,12)(4,7)(6,9)(8,11),
  (1,7)(2,8)(3,9)(4,10)(5,11)(6,12) ]
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (2,10)(4,8), (3,11,7), (5,9)(7,11), (6,10)(8,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 1 ] ] ] ]
gap> GroupCohomology(G,3); #  $H^3(G, \mathbb{Z}) = M(G)$ : Schur multiplier of  $G$ 
[ 2, 2, 2 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2, 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2, 2 ][ 2, 2 ]
[ 2, 2 ][ 2, 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
gap> cG:=cGs[1];;
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 2592 with 9 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 216 with 5 generators>
gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 2, 2, 2, 2 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2, 2 ], [ [ 2, 2, 2 ], [ [ 1, 0, 1 ], [ 0, 1, 0 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ 2 ], [ [ 2, 2, 2 ], [ [ 1, 0, 1 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Number(FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[2][2],y->y[2]=1)>0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
452
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 60 ], [ [ false ], 392 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
392
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);

```

```

60
gap> Collected(List(GcsHNPFalse,x->StructureDescription(Representative(x))));
[ [ "((C3 x C3) : C2) x ((C3 x C3) : C2)", 5 ],
  [ "((C3 x C3) : C2) x S3", 14 ],
  [ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 1 ],
  [ "(C3 x C3 x C3 x C3) : C2", 1 ], [ "(C3 x C3 x C3 x C3) : C4", 2 ],
  [ "(C3 x C3 x C3 x C3) : D8", 2 ], [ "(C3 x C3 x C3) : (C2 x C2)", 2 ],
  [ "(C3 x C3 x C3) : C2", 10 ], [ "(C3 x C3) : C2", 36 ],
  [ "(C3 x C3) : C4", 10 ], [ "(S3 x S3) : C2", 6 ], [ "1", 1 ], [ "C2", 7 ],
  [ "C2 x ((C3 x C3) : C2)", 6 ], [ "C2 x C2", 7 ], [ "C2 x C2 x C2", 1 ],
  [ "C2 x C2 x S3", 2 ], [ "C2 x S3 x S3", 4 ], [ "C3", 10 ],
  [ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 2 ], [ "C3 x ((C3 x C3) : C2)", 16 ],
  [ "C3 x C3", 30 ], [ "C3 x C3 x ((C3 x C3) : C2)", 6 ],
  [ "C3 x C3 x C3", 10 ], [ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x S3", 16 ],
  [ "C3 x S3", 52 ], [ "C3 x S3 x S3", 6 ], [ "C4", 2 ], [ "C6", 16 ],
  [ "C6 x C2", 2 ], [ "C6 x C3", 6 ], [ "C6 x S3", 6 ], [ "D12", 22 ],
  [ "D8", 2 ], [ "S3", 26 ], [ "S3 x ((C3 x C3) : C2)", 2 ],
  [ "S3 x S3", 40 ], [ "S3 x S3 x S3", 2 ]]

gap> Collected(List(GcsHNPMtrue,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 1 ],
  [ "(C3 x C3 x C3 x C3) : (C2 x D8)", 1 ],
  [ "(C3 x C3 x C3 x C3) : (C4 x C2)", 1 ], [ "(C3 x C3 x C3 x C3) : D8", 2 ],
  [ "(C3 x C3 x C3) : (C2 x C2)", 2 ], [ "(S3 x S3) : C2", 6 ],
  [ "C2 x ((C3 x C3) : C4)", 2 ], [ "C2 x ((S3 x S3) : C2)", 2 ],
  [ "C2 x C2", 2 ], [ "C2 x C2 x C2", 1 ], [ "C2 x C2 x S3", 2 ],
  [ "C2 x D8", 1 ], [ "C2 x S3 x S3", 4 ],
  [ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 2 ], [ "C3 x S3 x S3", 6 ],
  [ "C4 x C2", 1 ], [ "C6 x C2", 2 ], [ "C6 x S3", 6 ], [ "D12", 6 ],
  [ "D8", 2 ], [ "S3 x S3", 6 ], [ "S3 x S3 x S3", 2 ]]

gap> GcsHNPMtrueMin:=MinConjugacyClassesSubgroups(GcsHNPMtrue);
gap> Collected(List(GcsHNPMtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 2 ], [ "C4 x C2", 1 ], [ "D8", 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPMtrueMin);
false

gap> GcsHNPFalseC2xC2:=Filtered(GcsHNPFalse, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPFalseC2xC2);
7
gap> GcsHNPMtrueC2xC2:=Filtered(GcsHNPMtrue,
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPMtrueC2xC2);
2
gap> IsInvariantUnderAutG(GcsHNPMtrueC2xC2);
false
gap> Collected(List(List(GcsHNPFalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 2, 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2, 4 ], 2 ], [ [ 2, 2, 4, 4 ], 4 ] ]
gap> Collected(List(List(GcsHNPMtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length)));
[ [ [ 4, 4, 4 ], 2 ] ]

gap> Number(Gcs,x->IdSmallGroup(Representative(x))=[8,2]); # G(8,2)=C4xC2
1

gap> GcsHNPFalseD4:=Filtered(GcsHNPFalse, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3]);
gap> Length(GcsHNPFalseD4);
2
gap> GcsHNPMtrueD4:=Filtered(GcsHNPMtrue,
> x->IdSmallGroup(Representative(x))=[8,3]);
gap> Length(GcsHNPMtrueD4);

```

```

2
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 2, 2, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length)))); 
[ [ [ 4, 8 ], 2 ] ]

```

$$(2\text{-}2\text{-}5) G = 12T214 \simeq (C_3)^4 \rtimes ((C_4 \times C_2) \rtimes C_2).$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,214);
[1/2.F_36^2]2
gap> GeneratorsOfGroup(G);
[ (4,8,12), (2,10)(4,8), (1,7)(2,8,10,4)(3,9,11,5)(6,12),
  (1,12)(2,3)(4,5)(6,7)(8,9)(10,11) ]
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (2,10)(4,8), (2,6,10), (3,11)(5,9), (3,7,11) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 2, 2 ], [ [ 1, 1 ] ] ] ]
gap> GroupCohomology(G,3); # H^3(G,Z)=M(G): Schur multiplier of G
[ 2, 2, 3 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2, 2 ][ 2, 2 ]
[ 2, 2 ][ 2 ]
[ 2, 2 ][ 2, 2 ]
[ 2 ][ 2 ]
gap> cG:=cGs[2];;
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 2592 with 9 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 216 with 6 generators>
gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 2, 6 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2, 2 ], [ [ 2, 2, 2 ], [ [ 1, 0, 0 ], [ 0, 1, 1 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ 2 ], [ [ 2, 2, 2 ], [ [ 0, 1, 1 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Number(FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[2][2],y->y[1]=1)>0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
245
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtrf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtrf,Set));
[ [ [ true ], 16 ], [ [ false ], 229 ] ]
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtrf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
229

```

```

gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtrf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
16
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "((C3 x C3) : C2) x ((C3 x C3) : C2)", 3 ],
  [ "((C3 x C3) : C2) x S3", 5 ], [ "(C3 x C3 x C3 x C3) : (C4 x C2)", 1 ],
  [ "(C3 x C3 x C3 x C3) : C2", 1 ], [ "(C3 x C3 x C3 x C3) : C4", 4 ],
  [ "(C3 x C3 x C3 x C3) : D8", 2 ], [ "(C3 x C3 x C3) : C2", 8 ],
  [ "(C3 x C3) : C2", 31 ], [ "(C3 x C3) : C4", 19 ], [ "(S3 x S3) : C2", 4 ],
  [ "1", 1 ], [ "C2", 4 ], [ "C2 x ((C3 x C3) : C2)", 3 ],
  [ "C2 x ((C3 x C3) : C4)", 1 ], [ "C2 x C2", 3 ], [ "C3", 8 ],
  [ "C3 x ((C3 x C3) : C2)", 6 ], [ "C3 x C3", 28 ],
  [ "C3 x C3 x ((C3 x C3) : C2)", 3 ], [ "C3 x C3 x C3", 8 ],
  [ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x S3", 6 ], [ "C3 x S3", 24 ],
  [ "C4", 4 ], [ "C4 x C2", 1 ], [ "C6", 6 ], [ "C6 x C3", 3 ], [ "D12", 6 ],
  [ "D8", 2 ], [ "S3", 14 ], [ "S3 x ((C3 x C3) : C2)", 1 ],
  [ "S3 x S3", 18 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));;
[ [ "(C3 x C3 x C3 x C3) : ((C4 x C2) : C2)", 1 ],
  [ "(C3 x C3 x C3 x C3) : (C4 x C2)", 2 ], [ "(C3 x C3 x C3 x C3) : D8", 1 ],
  [ "(C3 x C3 x C3 x C3) : Q8", 1 ], [ "(C3 x C3) : Q8", 2 ],
  [ "(C4 x C2) : C2", 1 ], [ "(S3 x S3) : C2", 2 ],
  [ "C2 x ((C3 x C3) : C4)", 2 ], [ "C4 x C2", 2 ], [ "D8", 1 ], [ "Q8", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));;
[ [ "C4 x C2", 2 ], [ "D8", 1 ], [ "Q8", 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue, # G(8,2)=C4xC2
> x->IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPtrueC4xC2);
1
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPtrueC4xC2);
2
gap> IsInvariantUnderAutG(GcsHNPtrueC4xC2);
false
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 8 ], 2 ] ]

gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue, # G(8,3)=D4
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
2
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
1
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;

```



```

<permutation group of size 5184 with 10 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 432 with 7 generators>
gap> KerResHZ(bG,bH:iterator);
[ [ ], [ [ 2, 2, 2, 2, 2 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2, 2 ], [ [ 2, 2, 2, 2 ], [ [ 1, 0, 0, 0 ], [ 0, 1, 1, 1 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ 2 ], [ [ 2, 2, 2, 2 ], [ [ 0, 1, 1, 1 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Number(FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[2][2],y->y[1]=1)>0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
666
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ true ], 126 ], [ [ false ], 540 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPfalse);
540
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->true in GcsHHNPtf[x]),y->Gcs[y]);
gap> Length(GcsHNPtrue);
126
gap> Collected(List(GcsHNPfalse,x->StructureDescription(Representative(x))));
[ [ "(C3 x C3) : C2) x ((C3 x C3) : C2)", 9 ],
[ "((C3 x C3) : C2) x S3", 15 ],
[ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 4 ],
[ "(C3 x C3 x C3 x C3) : (C2 x D8)", 3 ],
[ "(C3 x C3 x C3 x C3) : (C4 x C2)", 3 ], [ "(C3 x C3 x C3 x C3) : C2", 1 ],
[ "(C3 x C3 x C3 x C3) : C4", 6 ], [ "(C3 x C3 x C3 x C3) : D8", 12 ],
[ "(C3 x C3 x C3) : (C2 x C2)", 4 ], [ "(C3 x C3 x C3) : C2", 7 ],
[ "(C3 x C3) : C2", 31 ], [ "(C3 x C3) : C4", 24 ],
[ "(S3 x S3) : C2", 24 ], [ "1", 1 ], [ "C2", 10 ],
[ "C2 x ((C3 x C3) : C2)", 9 ], [ "C2 x ((C3 x C3) : C4)", 3 ],
[ "C2 x ((S3 x S3) : C2)", 3 ], [ "C2 x C2", 13 ], [ "C2 x C2 x C2", 4 ],
[ "C2 x C2 x S3", 4 ], [ "C2 x D8", 3 ], [ "C2 x S3 x S3", 12 ],
[ "C3", 7 ], [ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 4 ],
[ "C3 x ((C3 x C3) : C2)", 18 ], [ "C3 x C3", 22 ],
[ "C3 x C3 x ((C3 x C3) : C2)", 9 ], [ "C3 x C3 x C3", 7 ],
[ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x S3", 18 ], [ "C3 x S3", 54 ],
[ "C3 x S3 x S3", 12 ], [ "C4", 6 ], [ "C4 x C2", 3 ], [ "C6", 18 ],
[ "C6 x C2", 4 ], [ "C6 x C3", 9 ], [ "C6 x S3", 12 ], [ "D12", 30 ],
[ "D8", 12 ], [ "S3", 25 ], [ "S3 x ((C3 x C3) : C2)", 3 ],
[ "S3 x S3", 57 ], [ "S3 x S3 x S3", 4 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C2 x C2 x C2) : (C2 x C2)", 1 ],
[ "(C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : (C2 x C2))", 1 ],
[ "(C3 x C3 x C3 x C3) : ((C4 x C2) : C2)", 6 ],
[ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 2 ],
[ "(C3 x C3 x C3 x C3) : (C2 x D8)", 6 ],
[ "(C3 x C3 x C3 x C3) : (C4 x C2)", 6 ], [ "(C3 x C3 x C3 x C3) : D8", 6 ],
[ "(C3 x C3 x C3 x C3) : Q8", 2 ], [ "(C3 x C3 x C3) : (C2 x C2)", 2 ],
[ "(C3 x C3) : Q8", 2 ], [ "(C4 x C2) : C2", 6 ], [ "(S3 x S3) : C2", 12 ],
[ "C2 x ((C3 x C3) : C4)", 6 ], [ "C2 x ((S3 x S3) : C2)", 6 ],
[ "C2 x C2", 2 ], [ "C2 x C2 x C2", 2 ], [ "C2 x C2 x S3", 2 ],
[ "C2 x D8", 6 ], [ "C2 x S3 x S3", 6 ],
[ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 2 ], [ "C3 x S3 x S3", 6 ],
[ "C4 x C2", 6 ], [ "C6 x C2", 2 ], [ "C6 x S3", 6 ], [ "D12", 6 ],

```

```

[ "D8", 6 ], [ "Q8", 2 ], [ "S3 x S3", 6 ], [ "S3 x S3 x S3", 2 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));;
[ [ "C2 x C2", 2 ], [ "C4 x C2", 6 ], [ "D8", 6 ], [ "Q8", 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue, # G(4,2)=C2xC2
> x->Order(Representative(x))=4 and IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
13
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=4 and IdSmallGroup(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
2
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2 ], 3 ], [ [ 2, 2, 2, 2, 4 ], 3 ],
  [ [ 2, 2, 4, 4 ], 6 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 2 ] ]

gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue, # G(8,2)=C4xC2
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPtrueC4xC2);
3
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,2]);;
gap> Length(GcsHNPtrueC4xC2);
6
gap> IsInvariantUnderAutG(GcsHNPtrueC4xC2);
false
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 3 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 8 ], 6 ] ]

gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue, # G(8,3)=D4
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
12
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=8 and IdSmallGroup(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
6
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 12 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 8 ], 6 ] ]

gap> Number(Gcs, # G(8,4)=Q8
> x->Order(Representative(x))=8 and
> IdSmallGroup(Representative(x))=[8,4]);

```

```

2
gap> Number(GcsHNPtrueMin,
x->Order(Representative(x))=8 and
> IdSmallGroup(Representative(x))=[8,4]);
2

(2-2-7)  $G = 12T271 \simeq ((C_3)^4 \rtimes (C_2)^3) \rtimes A_4(4)$ .

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,271);
[3^4:2^3]A(4)
gap> GeneratorsOfGroup(G);
[ (4,8,12), (4,8)(7,11), (2,8,11)(3,6,12)(4,7,10), (1,7,10)(2,5,11)(3,6,9) ]
gap> H:=Stabilizer(G,1);
Group([ (4,8,12), (4,8)(7,11), (2,8,11)(3,6,12)(4,7,10), (5,9)(8,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2 ], [ [ 6 ], [ [ 3 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 6 ], [ [ 3 ] ] ] ]
gap> GroupCohomology(G,3); #  $H^3(G, \mathbb{Z}) = M(G)$ : Schur multiplier of  $G$ 
[ 2, 2, 2 ]
gap> cGs:=MinimalStemExtensions(G);;
gap> for cG in cGs do
> bG:=cG.MinimalStemExtension;
> bH:=PreImage(cG.epi,H);
> Print(FirstObstructionN(bG,bH).ker[1]);
> Print(FirstObstructionDnr(bG,bH).Dnr[1]);
> Print("\n");
> od;
[ 2, 2 ][ 2, 2 ]
[ 2, 2 ][ 2, 2 ]
[ 2, 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
[ 2 ][ 2 ]
gap> cG:=cGs[3];;
gap> bG:=cG.MinimalStemExtension;
<permutation group of size 15552 with 11 generators>
gap> bH:=PreImage(cG.epi,H);
<permutation group of size 1296 with 4 generators>
gap> KerResH3Z(bG,bH:iterator);
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> FirstObstructionN(bG,bH).ker;
[ [ 2, 2 ], [ [ 2, 6 ], [ [ 1, 0 ], [ 0, 3 ] ] ] ]
gap> FirstObstructionDnr(bG,bH).Dnr;
[ [ 2 ], [ [ 2, 6 ], [ [ 1, 3 ] ] ] ]
gap> HNPtruefalsefn:=
> x->Number(FirstObstructionDr(bG,PreImage(cG.epi,x),bH).Dr[2][2],
> y->(3*y[1]+y[2]) mod 6=3)>0;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
344
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtrf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtrf,Set));
[ [ true ], 86 ], [ [ false ], 258 ] ]
gap> GcsHNPfalse:=List(Filtered([1..Length(Gcs)],
> x->false in GcsHHNPtrf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse);
258
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],


```

```

> x->true in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
86
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C3 x C3 x C3) : (C2 x C2)) : C3", 2 ],
  [ "((C3 x C3 x C3) : C3) : C2", 3 ],
  [ "((C3 x C3) : C2) x ((C3 x C3) : C2)", 3 ],
  [ "((C3 x C3) : C2) x S3", 5 ],
  [ "(C3 x (((C3 x C3 x C3) : (C2 x C2)) : C3)) : C2", 1 ],
  [ "(C3 x ((C3 x C3 x C3) : C3)) : C2", 1 ],
  [ "(C3 x ((C3 x C3) : C3)) : C2", 1 ],
  [ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 2 ],
  [ "(C3 x C3 x C3 x C3) : (C2 x D8)", 1 ],
  [ "(C3 x C3 x C3 x C3) : (C4 x C2)", 1 ], [ "(C3 x C3 x C3 x C3) : C2", 1 ],
  [ "(C3 x C3 x C3 x C3) : C4", 2 ], [ "(C3 x C3 x C3 x C3) : D8", 4 ],
  [ "(C3 x C3 x C3) : (C2 x C2)", 2 ], [ "(C3 x C3 x C3) : C2", 5 ],
  [ "(C3 x C3 x C3) : C3", 6 ], [ "(C3 x C3) : C2", 13 ],
  [ "(C3 x C3) : C3", 4 ], [ "(C3 x C3) : C4", 8 ], [ "(C3 x C3) : C6", 3 ],
  [ "(S3 x S3 x S3) : C3", 1 ], [ "(S3 x S3) : C2", 8 ], [ "1", 1 ],
  [ "A4", 2 ], [ "A4 x S3", 1 ], [ "C2", 4 ], [ "C2 x ((C3 x C3) : C2)", 3 ],
  [ "C2 x ((C3 x C3) : C4)", 1 ], [ "C2 x ((S3 x S3) : C2)", 1 ],
  [ "C2 x A4", 1 ], [ "C2 x C2", 5 ], [ "C2 x C2 x C2", 2 ],
  [ "C2 x C2 x S3", 2 ], [ "C2 x D8", 1 ], [ "C2 x S3 x S3", 4 ],
  [ "C3", 7 ], [ "C3 x (((C3 x C3 x C3) : (C2 x C2)) : C3)", 1 ],
  [ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 2 ],
  [ "C3 x ((C3 x C3 x C3) : C3)", 1 ], [ "C3 x ((C3 x C3) : C2)", 7 ],
  [ "C3 x ((C3 x C3) : C3)", 1 ], [ "C3 x (C9 : C3)", 1 ], [ "C3 x A4", 1 ],
  [ "C3 x C3", 15 ], [ "C3 x C3 x ((C3 x C3) : C2)", 3 ],
  [ "C3 x C3 x C3", 6 ], [ "C3 x C3 x C3 x C3", 1 ], [ "C3 x C3 x S3", 6 ],
  [ "C3 x S3", 22 ], [ "C3 x S3 x S3", 4 ], [ "C4", 2 ], [ "C4 x C2", 1 ],
  [ "C6", 7 ], [ "C6 x C2", 2 ], [ "C6 x C3", 3 ], [ "C6 x S3", 4 ],
  [ "C9", 3 ], [ "C9 : C3", 5 ], [ "C9 x C3", 1 ], [ "D12", 10 ],
  [ "D8", 4 ], [ "S3", 11 ], [ "S3 x ((C3 x C3) : C2)", 1 ],
  [ "S3 x S3", 19 ], [ "S3 x S3 x S3", 2 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C2 x C2 x C2) : (C2 x C2)) : C3", 1 ],
  [ "((C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : (C2 x C2))) : C3", 1 ],
  [ "((C3 x C3 x C3 x C3) : (C2 x C2 x C2)) : C3", 2 ],
  [ "((C3 x C3 x C3 x C3) : Q8) : C3", 2 ],
  [ "((C3 x C3 x C3) : (C2 x C2)) : C3", 4 ], [ "((C3 x C3) : Q8) : C3", 2 ],
  [ "(C2 x C2 x C2) : (C2 x C2)", 1 ],
  [ "(C3 x C3 x C3 x C3) : ((C2 x C2 x C2) : (C2 x C2))", 1 ],
  [ "(C3 x C3 x C3 x C3) : ((C4 x C2) : C2)", 2 ],
  [ "(C3 x C3 x C3 x C3) : (C2 x C2 x C2)", 2 ],
  [ "(C3 x C3 x C3 x C3) : (C2 x D8)", 2 ],
  [ "(C3 x C3 x C3 x C3) : (C4 x C2)", 2 ], [ "(C3 x C3 x C3 x C3) : D8", 2 ],
  [ "(C3 x C3 x C3 x C3) : Q8", 2 ], [ "(C3 x C3 x C3) : (C2 x C2)", 2 ],
  [ "(C3 x C3) : Q8", 2 ], [ "(C4 x C2) : C2", 2 ],
  [ "(S3 x S3 x S3) : C3", 2 ], [ "(S3 x S3) : C2", 4 ], [ "A4", 4 ],
  [ "A4 x S3", 2 ], [ "C2 x ((C3 x C3) : C4)", 2 ],
  [ "C2 x ((S3 x S3) : C2)", 2 ], [ "C2 x A4", 2 ], [ "C2 x C2", 2 ],
  [ "C2 x C2 x C2", 2 ], [ "C2 x C2 x S3", 2 ], [ "C2 x D8", 2 ],
  [ "C2 x S3 x S3", 2 ], [ "C3 x (((C3 x C3 x C3) : (C2 x C2)) : C3)", 2 ],
  [ "C3 x ((C3 x C3 x C3) : (C2 x C2))", 2 ], [ "C3 x A4", 2 ],
  [ "C3 x S3 x S3", 2 ], [ "C4 x C2", 2 ], [ "C6 x C2", 2 ], [ "C6 x S3", 2 ],
  [ "D12", 2 ], [ "D8", 2 ], [ "Q8", 2 ], [ "S3 x S3", 2 ],
  [ "S3 x S3 x S3", 2 ], [ "SL(2,3)", 2 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2", 2 ], [ "C4 x C2", 2 ], [ "D8", 2 ], [ "Q8", 2 ] ]
gap> IsInvariantUnderAutG(GcsHNPtrueMin);
false

```

```

gap> GcsHNPfalseC2xC2:=Filtered(GcsHNPfalse, # G(4,2)=C2xC2
> x->Order(Representative(x))=4 and IdSmall(Representative(x))=[4,2]);;
gap> Length(GcsHNPfalseC2xC2);
5
gap> GcsHNPtrueC2xC2:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=4 and IdSmall(Representative(x))=[4,2]);;
gap> Length(GcsHNPtrueC2xC2);
2
gap> IsInvariantUnderAutG(GcsHNPtrueC2xC2);
false
gap> Collected(List(List(GcsHNPfalseC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2 ], 1 ], [ [ 2, 2, 2, 2, 4 ], 1 ],
  [ [ 2, 2, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPtrueC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 4, 4 ], 2 ] ]

gap> GcsHNPfalseC4xC2:=Filtered(GcsHNPfalse, # G(8,2)=C4xC2
> x->Order(Representative(x))=8 and IdSmall(Representative(x))=[8,2]);;
gap> Length(GcsHNPfalseC4xC2);
1
gap> GcsHNPtrueC4xC2:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=8 and IdSmall(Representative(x))=[8,2]);;
gap> Length(GcsHNPtrueC4xC2);
2
gap> IsInvariantUnderAutG(GcsHNPtrueC4xC2);
false
gap> Collected(List(List(GcsHNPfalseC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPtrueC4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 8 ], 2 ] ]

gap> GcsHNPfalseD4:=Filtered(GcsHNPfalse, # G(8,3)=D4
> x->Order(Representative(x))=8 and IdSmall(Representative(x))=[8,3]);;
gap> Length(GcsHNPfalseD4);
4
gap> GcsHNPtrueD4:=Filtered(GcsHNPtrue,
> x->Order(Representative(x))=8 and IdSmall(Representative(x))=[8,3]);;
gap> Length(GcsHNPtrueD4);
2
gap> IsInvariantUnderAutG(GcsHNPtrueD4);
false
gap> Collected(List(List(GcsHNPfalseD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 2, 2, 4, 4 ], 4 ] ]
gap> Collected(List(List(GcsHNPtrueD4,Representative),
> x->SortedList(List(Orbits(x),Length))));;
[ [ [ 4, 8 ], 2 ] ]

gap> Number(Gcs, # G(8,4)=Q8
> x->Order(Representative(x))=8 and IdSmall(Representative(x))=[8,4]);
2
gap> Number(GcsHNPtrueMin,
> x->Order(Representative(x))=8 and IdSmall(Representative(x))=[8,4]);
2

```

Example 7.6 ($G = 12T31$).

$$(3) G = 12T31 \simeq (C_4)^2 \rtimes C_3.$$

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,31);
[4^2]3
gap> H:=Stabilizer(G,1);
Group([ (2,11,8,5)(3,6,9,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ 4 ], [ [ 4 ], [ [ 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 4 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 4 ], [ ] ] ]
gap> HNPtruefalsefn:=x->Product(FirstObstructionDr(G,x,H).Dr[1]);
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
10
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ 1 ], 5 ], [ [ 2 ], 3 ], [ [ 4 ], 2 ] ]
gap> GcsHNPfalse1:=List(Filtered([1..Length(Gcs)],
> x->1 in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse1);
5
gap> GcsHNPfalse2:=List(Filtered([1..Length(Gcs)],
> x->2 in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse2);
3
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->4 in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
2
gap> Collected(List(GcsHNPfalse1,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "C2", 1 ], [ "C3", 1 ], [ "C4", 2 ] ]
gap> Collected(List(GcsHNPfalse2,x->StructureDescription(Representative(x))));
[ [ "A4", 1 ], [ "C2 x C2", 1 ], [ "C4 x C2", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C4 x C4) : C3", 1 ], [ "C4 x C4", 1 ] ]

```

Example 7.7 ($G = 12T57$).

(4) $G = 12T57 \simeq ((C_4 \times C_2) \rtimes C_4) \rtimes C_3$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,57);
[(1/2.2^2)^3]A_4(6)_4
gap> GeneratorsOfGroup(G);
[ (1,12)(2,3), (1,5,9)(2,6,10)(3,7,11)(4,8,12), (1,2,12,3)(4,7)(5,6)(8,9) ]
gap> H:=Stabilizer(G,1);
Group([ (8,9)(10,11), (2,3)(4,7,5,6)(8,11)(9,10) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2, 4 ], [ [ 2, 4 ], [ [ 1, 0 ], [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ 2 ], [ [ 2, 4 ], [ [ 1, 0 ] ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr;
function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);;
gap> Length(Gcs);
21
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));

```

```

[ [ [ [ [ [ ] , [ [ 2, 4 ], [ ] ] ] ], 5 ],
  [ [ [ [ 2 ], [ [ 2, 4 ], [ [ 1, 0 ] ] ] ], 10 ],
  [ [ [ [ 2, 2 ], [ [ 2, 4 ], [ [ 1, 0 ], [ 0, 2 ] ] ] ], 4 ],
  [ [ [ [ 2, 4 ], [ [ 2, 4 ], [ [ 1, 0 ], [ 0, 1 ] ] ] ], 2 ] ]
gap> GcsHNPfalse1:=List(Filtered([1..Length(Gcs)],
> x->Product(GcsHHNPtf[x][1][1])<=2),y->Gcs[y]);
gap> Length(GcsHNPfalse1);
15
gap> GcsHNPfalse2:=List(Filtered([1..Length(Gcs)],
> x->Product(GcsHHNPtf[x][1][1])=4),y->Gcs[y]);
gap> Length(GcsHNPfalse2);
4
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->Product(GcsHHNPtf[x][1][1])=8),y->Gcs[y]);
gap> Length(GcsHNPtrue);
2
gap> Collected(List(GcsHNPfalse1,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "A4", 1 ], [ "C2", 3 ], [ "C2 x A4", 1 ], [ "C2 x C2", 3 ],
  [ "C2 x C2 x C2", 1 ], [ "C3", 1 ], [ "C4", 2 ], [ "C4 x C2", 1 ],
  [ "C6", 1 ] ]
gap> Collected(List(GcsHNPfalse2,x->StructureDescription(Representative(x))));
[ [ "C4 x C2", 3 ], [ "C4 x C2 x C2", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "((C4 x C2) : C4) : C3", 1 ], [ "(C4 x C2) : C4", 1 ] ]
gap> GcsHNPfalse2Min:=MinConjugacyClassesSubgroups(GcsHNPfalse2);
gap> Collected(List(GcsHNPfalse2Min,x->StructureDescription(Representative(x))));
[ [ "C4 x C2", 3 ] ]
gap> IsInvariantUnderAutG(GcsHNPfalse2Min);
false

gap> GcsHNPfalse1C4xC2:=Filtered(GcsHNPfalse1, # G(8,2)=C4xC2
> x->IdSmallGroup(Representative(x))=[8,2]);
gap> Length(GcsHNPfalse1C4xC2);
1
gap> GcsHNPfalse2C4xC2:=Filtered(GcsHNPfalse2,
> x->IdSmallGroup(Representative(x))=[8,2]);
gap> Length(GcsHNPfalse2C4xC2);
3
gap> Collected(List(List(GcsHNPfalse1C4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 4, 4 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalse2C4xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 2, 2, 4 ], 1 ], [ [ 2, 2, 4, 4 ], 2 ] ]

```

Example 7.8 ($G = 12T32$).

(5) $G = 12T32 \simeq (C_2)^4 \rtimes C_3$.

```

gap> Read("HNP.gap");
gap> G:=TransitiveGroup(12,32);
[E(4)^2]3
gap> GeneratorsOfGroup(G);
[ (1,10)(3,12)(4,7)(6,9), (1,7)(3,9)(4,10)(6,12),
  (1,5,9)(2,6,10)(3,7,11)(4,8,12) ]
gap> H:=Stabilizer(G,1);
Group([ (2,5)(3,12)(6,9)(8,11), (2,8)(3,9)(5,11)(6,12) ])
gap> FirstObstructionN(G,H).ker;
[ [ 2, 2 ], [ [ 2, 2 ], [ [ 1, 0 ], [ 0, 1 ] ] ] ]
gap> FirstObstructionDnr(G,H).Dnr;
[ [ ], [ [ 2, 2 ], [ ] ] ]
gap> KerResH3Z(G,H:iterator);
[ [ ], [ [ 2, 2, 2, 2 ], [ ] ] ]
gap> HNPtruefalsefn:=x->FirstObstructionDr(G,x,H).Dr[2][2];

```

```

function( x ) ... end
gap> Gcs:=ConjugacyClassesSubgroups(G);
gap> Length(Gcs);
34
gap> GcsH:=ConjugacyClassesSubgroupsNGHOrbitRep(Gcs,H);;
gap> GcsHHNPtf:=List(GcsH,x->List(x,HNPtruefalsefn));;
gap> Collected(List(GcsHHNPtf,Set));
[ [ [ [ ] ], 23 ], [ [ [ [ 0, 1 ] ] ], 3 ], [ [ [ [ 1, 0 ] ] ], 3 ],
  [ [ [ [ 1, 0 ], [ 0, 1 ] ] ], 2 ], [ [ [ [ 1, 1 ] ] ], 3 ] ]
gap> GcsHNPfalse1:=List(Filtered([1..Length(Gcs)],
> x->[] in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse1);
23
gap> GcsHNPfalse2a:=List(Filtered([1..Length(Gcs)],
> x->[[1,0]] in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse2a);
3
gap> GcsHNPfalse2b:=List(Filtered([1..Length(Gcs)],
> x->[[0,1]] in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse2b);
3
gap> GcsHNPfalse2c:=List(Filtered([1..Length(Gcs)],
> x->[[1,1]] in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPfalse2c);
3
gap> GcsHNPtrue:=List(Filtered([1..Length(Gcs)],
> x->[[1,0],[0,1]] in GcsHHNPtf[x]),y->Gcs[y]);;
gap> Length(GcsHNPtrue);
2
gap> Collected(List(GcsHNPfalse1,x->StructureDescription(Representative(x))));
[ [ "1", 1 ], [ "A4", 2 ], [ "C2", 5 ], [ "C2 x C2", 12 ],
  [ "C2 x C2 x C2", 2 ], [ "C3", 1 ] ]
gap> Collected(List(GcsHNPfalse2a,x->StructureDescription(Representative(x))));
[ [ "A4", 1 ], [ "C2 x C2", 1 ], [ "C2 x C2 x C2", 1 ] ]
gap> Collected(List(GcsHNPfalse2b,x->StructureDescription(Representative(x))));
[ [ "A4", 1 ], [ "C2 x C2", 1 ], [ "C2 x C2 x C2", 1 ] ]
gap> Collected(List(GcsHNPfalse2c,x->StructureDescription(Representative(x))));
[ [ "A4", 1 ], [ "C2 x C2", 1 ], [ "C2 x C2 x C2", 1 ] ]
gap> Collected(List(GcsHNPtrue,x->StructureDescription(Representative(x))));
[ [ "(C2 x C2 x C2 x C2) : C3", 1 ], [ "C2 x C2 x C2 x C2", 1 ] ]
gap> GcsHNPtrueMin:=MinConjugacyClassesSubgroups(GcsHNPtrue);;
gap> Collected(List(GcsHNPtrueMin,x->StructureDescription(Representative(x))));
[ [ "C2 x C2 x C2 x C2", 1 ] ]
gap> GcsHNPfalse2aMin:=MinConjugacyClassesSubgroups(GcsHNPfalse2a);;
gap> GcsHNPfalse2bMin:=MinConjugacyClassesSubgroups(GcsHNPfalse2b);;
gap> GcsHNPfalse2cMin:=MinConjugacyClassesSubgroups(GcsHNPfalse2c);;
gap> Collected(List(GcsHNPfalse2aMin,
> x->StructureDescription(Representative(x))));;
[ [ "C2 x C2", 1 ] ]
gap> Collected(List(GcsHNPfalse2bMin,
> x->StructureDescription(Representative(x))));;
[ [ "C2 x C2", 1 ] ]
gap> Collected(List(GcsHNPfalse2cMin,
> x->StructureDescription(Representative(x))));;
[ [ "C2 x C2", 1 ] ]
gap> IsInvariantUnderAutG(GcsHNPfalse2aMin);
false
gap> IsInvariantUnderAutG(GcsHNPfalse2bMin);
false
gap> IsInvariantUnderAutG(GcsHNPfalse2cMin);
false
gap> IsInvariantUnderAutG(Union(

```

```

> GcsHNPfalse2aMin,GcsHNPfalse2bMin,GcsHNPfalse2cMin));
false

gap> GcsHNPfalse1C2xC2:=Filtered(GcsHNPfalse1, # G(4,2)=C2xC2
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPfalse1C2xC2);
12
gap> GcsHNPfalse2aC2xC2:=Filtered(GcsHNPfalse2a,
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> GcsHNPfalse2bC2xC2:=Filtered(GcsHNPfalse2b,
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> GcsHNPfalse2cC2xC2:=Filtered(GcsHNPfalse2c,
> x->IdSmallGroup(Representative(x))=[4,2]);
gap> Length(GcsHNPfalse2aC2xC2);
1
gap> Length(GcsHNPfalse2bC2xC2);
1
gap> Length(GcsHNPfalse2cC2xC2);
1
gap> Collected(List(List(GcsHNPfalse1C2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 2, 2, 4 ], 6 ], [ [ 2, 2, 4, 4 ], 3 ], [ [ 4, 4 ], 1 ],
  [ [ 4, 4, 4 ], 2 ] ]
gap> Collected(List(List(GcsHNPfalse2aC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 2, 2, 2 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalse2bC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 2, 2, 2 ], 1 ] ]
gap> Collected(List(List(GcsHNPfalse2cC2xC2,Representative),
> x->SortedList(List(Orbits(x),Length))));
[ [ [ 2, 2, 2, 2, 2 ], 1 ] ]
gap> IsNormal(G,Representative(GcsHNPfalse2aMin[1]));
true
gap> IsNormal(G,Representative(GcsHNPfalse2bMin[1]));
true
gap> IsNormal(G,Representative(GcsHNPfalse2cMin[1]));
true
gap> NG:=NormalSubgroups(G);
gap> Length(NG);
8
gap> List(NG,Order);
[ 48, 16, 4, 4, 4, 4, 1 ]
gap> List(NG,StructureDescription);
[ "(C2 x C2 x C2 x C2) : C3", "C2 x C2 x C2 x C2", "C2 x C2",
  "C2 x C2", "C2 x C2", "C2 x C2", "1" ]
gap> NGC2xC2:=Filtered(NG,x->IdSmallGroup(x)=[4,2]);
gap> Length(NGC2xC2);
5
gap> List(List(GcsHNPfalse2aC2xC2,Representative),x->Position(NGC2xC2,x));
[ 1 ]
gap> List(List(GcsHNPfalse2bC2xC2,Representative),x->Position(NGC2xC2,x));
[ 5 ]
gap> List(List(GcsHNPfalse2cC2xC2,Representative),x->Position(NGC2xC2,x));
[ 3 ]
gap> GcsHNPfalse2abcC2xC2:=Concatenation(
> List([GcsHNPfalse2aC2xC2,GcsHNPfalse2bC2xC2,GcsHNPfalse2cC2xC2],
> x->List(x,Representative)));
gap> List(GcsHNPfalse2abcC2xC2,Elements);
[ [ (), (2,5)(3,12)(6,9)(8,11), (1,10)(3,12)(4,7)(6,9),
  (1,10)(2,5)(4,7)(8,11) ],
  [ (), (2,8)(3,9)(5,11)(6,12), (1,7)(3,9)(4,10)(6,12),
  (1,10)(2,5)(4,7)(6,9) ],
  [ (), (1,2)(3,4)(5,6)(7,8)(9,10)(11,12), (1,3)(2,4)(5,7)(6,8)(9,11)(10,12) ],
  [ (), (1,2)(3,4)(5,6)(7,8)(9,10)(11,12), (1,3)(2,4)(5,7)(6,8)(9,11)(10,12) ],
  [ () ] ]

```

```
(1,7)(2,8)(4,10)(5,11) ],
[ (), (2,11)(3,6)(5,8)(9,12), (1,4)(3,6)(7,10)(9,12),
 (1,4)(2,11)(5,8)(7,10) ] ]
gap> GcsHNPfalse1C2xC2N:=Filtered(List(GcsHNPfalse1C2xC2,Representative),
> x->IsNormal(G,x));
gap> List(GcsHNPfalse1C2xC2N,Elements);
[ [ (), (1,4)(2,5)(3,9)(6,12)(7,10)(8,11), (1,7)(2,11)(3,12)(4,10)(5,8)(6,9),
 (1,10)(2,8)(3,6)(4,7)(5,11)(9,12) ],
[ (), (1,4)(2,8)(3,12)(5,11)(6,9)(7,10), (1,7)(2,5)(3,6)(4,10)(8,11)(9,12),
 (1,10)(2,11)(3,9)(4,7)(5,8)(6,12) ] ]
```

8. GAP ALGORITHMS

We give GAP algorithms for computing the total obstruction $\text{Obs}(K/k)$ and the first obstruction $\text{Obs}_1(L/K/k)$ as in Section 6. The functions which are provided in this section are available from <https://www.math.kyoto-u.ac.jp/~yamasaki/Algorithm/Norm1ToriHNP/>.

```
LoadPackage("HAP");

Norm1TorusJ :=function(d,n)
local I,M1,M2,M,f,Sn,T;
I:=IdentityMat(d-1);
Sn:=SymmetricGroup(d);
T:=TransitiveGroup(d,n);
M1:=Concatenation(List([2..d-1],x->I[x]),[-List([1..d-1],One)]);
if d=2 then
  M:=[M1];
else
  M2:=Concatenation([I[2],I[1]],List([3..d-1],x->I[x]));
  M:=[M1,M2];
fi;
f:=GroupHomomorphismByImages(Sn,Group(M),GeneratorsOfGroup(Sn),M);
return Image(f,T);
end;

AbelianInvariantsSNF := function(G)
local n,m,s,l;
if Order(G)=1 then
  return [];
fi;
n:=AbelianInvariants(G);
m:=DiagonalMat(n);
s:=SmithNormalFormIntegerMat(m);
return Filtered(DiagonalOfMat(s),x -> x>1);
end;

AbelianizationGen:= function(G)
local Gab,pi,inv,A,iso,gen,genrep;
Reset(GlobalMersenneTwister);
Reset(GlobalRandomSource);
pi:=NaturalHomomorphismByNormalSubgroup(G,DerivedSubgroup(G));
Gab:=Image(pi);
inv:=AbelianInvariantsSNF(Gab);
A:=AbelianGroup(inv);
iso:=IsomorphismGroups(A,Gab);
gen:=List(GeneratorsOfGroup(A),x->Image(iso,x));
genrep:=List(gen,x->PreImagesRepresentative(pi,x));
return rec(Gab:=Gab, gen:=gen, genrep:=genrep, inv:=inv, pi:=pi);
end;

FindGenFiniteAbelian:= function(g)
local e,a,ga,iso;
e:=AbelianInvariants(g);
```

```

if Length(e)>1 then
  e:=SmithNormalFormIntegerMat(DiagonalMat(e));
  e:=List([1..Length(e)],x->e[x][x]);
  e:=Filtered(e,x->x>1);
fi;
a:=AbelianGroup(e);
ga:=GeneratorsOfGroup(a);
iso:=IsomorphismGroups(a,g);
return List(ga,x->Image(iso,x));
end;

EltFiniteAbelian:= function(arg)
local g,c,gg,F,gF,hom,cF,e;
g:=arg[1];
c:=arg[2];
if Length(arg)=3 then
  gg:=arg[3];
else
  gg:=GeneratorsOfGroup(g);
fi;
F:=FreeGroup(Length(gg));
gF:=GeneratorsOfGroup(F);
hom:=GroupHomomorphismByImages(F,g,gF,gg);
cF:=PreImagesRepresentative(hom,c);
e:=List(gF,x->ExponentSumWord(cF,x));
return e;
end;

FirstObstructionN:= function(arg)
local G,H,Gab,Hab,K,Kinv,mat,v,Habbase,ker1;
G:=arg[1];
if Length(arg)=1 then
  H:=Stabilizer(G,1);
else
  H:=arg[2];
fi;
Gab:=AbelianizationGen(G);
Hab:=AbelianizationGen(H);
Hab.Hab:=Hab.Gab;
Unbind(Hab.Gab);
if DerivedSubgroup(H)=H then
  return rec(ker:=[[[],[],[]]], Hab:=Hab, Gab:=Gab, psi:=[()]);
fi;
if DerivedSubgroup(G)=G then
  return rec(ker:=[Hab.inv,[Hab.inv,IdentityMat(Length(Hab.inv))]],
             Hab:=Hab, Gab:=Gab, psi:=List(Hab.inv,x->[]));
fi;
K:=Image(Hab.pi,Intersection(H,DerivedSubgroup(G)));
Kinv:=AbelianInvariantsSNF(K);
mat:=[];
for v in Hab.genrep do
  Add(mat,EltFiniteAbelian(Gab.Gab,Image(Gab.pi,v),Gab.gen));
od;
Habbase:=DiagonalMat(Hab.inv);
ker1:=List(GeneratorsOfGroup(K),x->EltFiniteAbelian(Hab.Hab,x,Hab.gen));
ker1:=LatticeBasis(Concatenation(Habbase,ker1));
ker1:=LatticeBasis(Difference(ker1,Habbase));
return rec(ker:=[Kinv,[Hab.inv,ker1]],
           Hab:=Hab, Gab:=Gab, psi:=mat);;
end;

FirstObstructionDnr:= function(arg)

```

```

local G,H,Gab,Hab,HG,HGrep,Dnrgen,h,x,Dnr,Dnrintv,Habbase,Dnrmat;
G:=arg[1];
if Length(arg)=1 then
  H:=Stabilizer(G,1);
else
  H:=arg[2];
fi;
Gab:=AbelianizationGen(G);
Hab:=AbelianizationGen(H);
Hab.Hab:=Hab.Gab;
Unbind(Hab.Gab);
if DerivedSubgroup(H)=H then
  return rec(Dnr:=[[[],[],[]]], Hab:=Hab, Gab:=Gab);
fi;
Reset(GlobalMersenneTwister);
Reset(GlobalRandomSource);
HG:=RightCosets(G,H);
HGrep:=List(HG,Representative);
Dnrgen:=[];
for x in HGrep do
  for h in GeneratorsOfGroup(Intersection(H,H^x)) do
    Add(Dnrgen,Image(Hab.pi,Comm(h,x^-1)));
  od;
od;
Dnr:=Group(Dnrgen,Identity(Hab.Hab));
Dnrintv:=AbelianInvariantsSNF(Dnr);
Habbase:=DiagonalMat(Hab.inv);
Dnrmat:=List(Dnrgen,x->EltFiniteAbelian(Hab.Hab,x,Hab.gen));
Dnrmat:=LatticeBasis(Concatenation(Habbase,Dnrmat));
Dnrmat:=LatticeBasis(Difference(Dnrmat,Habbase));
return rec(Dnr:=[Dnrintv,[Hab.inv,Dnrmat]],
           Hab:=Hab, Gab:=Gab);
end;

FirstObstructionDr:= function(arg)
local G,Gv,H,Gab,Hab,HGGv,HGGvrep,Hwi,Hwiab,Gvab,psi2i,i,psi2iimage,Hw,
      psi2,ker,phi1i,phi1iimage,phi1,Dr,Drinv,Habbase,Drmat;
G:=arg[1];
Gv:=arg[2];
if Length(arg)=2 then
  H:=Stabilizer(G,1);
else
  H:=arg[3];
fi;
Gab:=AbelianizationGen(G);
Hab:=AbelianizationGen(H);
Hab.Hab:=Hab.Gab;
Unbind(Hab.Gab);
if DerivedSubgroup(H)=H then
  return rec(Dr:=[[[],[],[]]], Hab:=Hab, Gab:=Gab);
fi;
HGGv:=DoubleCosets(G,H,Gv);
HGGvrep:=List(HGGv,Representative);
Hwi:=List(HGGvrep,x->Intersection(Gv^(x^(-1)),H));
Hwiab:=List(Hwi,AbelianizationGen);
Gvab:=AbelianizationGen(Gv);
psi2i:=[];
for i in [1..Length(HGGv)] do
  psi2iimage:=List(Hwiab[i].genrep,x->x^HGGvrep[i]);
  psi2iimage:=List(psi2iimage,x->Image(Gvab.pi,x));
  Add(psi2i,GroupHomomorphismByImages(Hwiab[i].Gab,Gvab.Gab,Hwiab[i].gen,
    psi2iimage));
end;

```

```

od;
Hw:=DirectProduct(List(Hwiab,x->x.Gab));
psi2:=GroupHomomorphismByFunction(Hw,Gvab.Gab,x->
Product([1..Length(HGGv)],i->Image(psi2i[i],Image(Projection(Hw,i),x)))); 
ker:=Kernel(psi2);
phi1i:=[];
for i in [1..Length(HGGv)] do
  phi1image:=List(Hwiab[i].genrep,x->Image(Hab.pi,x));
  Add(phi1i,GroupHomomorphismByImages(Hwiab[i].Gab,Hab.Hab,Hwiab[i].gen,
  phi1image));
od;
phi1:=GroupHomomorphismByFunction(Hw,Hab.Hab,x->
Product([1..Length(HGGv)],i->Image(phi1i[i],Image(Projection(Hw,i),x)))); 
Dr:=Image(phi1,ker);
Drinv:=AbelianInvariantsSNF(Dr);
Habbase:=DiagonalMat(Hab.inv);
Drmat:=List(GeneratorsOfGroup(Dr),x->EltFiniteAbelian(Hab.Hab,x,Hab.gen));
Drmat:=LatticeBasis(Concatenation(Habbase,Drmat));
Drmat:=LatticeBasis(Difference(Drmat,Habbase));
return rec(Dr:=[Drinv,[Hab.inv,Drmat]],
Hab:=Hab, Gab:=Gab);
end;

MaximalSubgroups2:= function(G)
  Reset(GlobalMersenneTwister);
  Reset(GlobalRandomSource);
  return SortedList(MaximalSubgroups(G));
end;

SchurCoverG:= function(G)
  local epi,iso,ScG,ScGg,GG,GGg,Gg,n,i,id;
  Reset(GlobalMersenneTwister);
  Reset(GlobalRandomSource);
  epi:=EpimorphismSchurCover(G);
  iso:=IsomorphismPermGroup(Source(epi));
  ScG:=Source(epi);
  ScGg:=GeneratorsOfGroup(ScG);
  GG:=Range(iso);
  GGg:=List(ScGg,x->Image(iso,x));
  Gg:=List(ScGg,x->Image(epi,x));
  epi:=GroupHomomorphismByImages(GG,G,GGg,Gg);
  n:=NrMovedPoints(Source(epi));
  if n>=2 and n<=30 and IsTransitive(Source(epi),[1..n]) then
    for i in [1..NrTransitiveGroups(n)] do
      if Order(TransitiveGroup(n,i))=Order(Source(epi)) and
      IsConjugate(SymmetricGroup(n),
      TransitiveGroup(n,i),Source(epi)) then
        id:=[n,i];
        break;
      fi;
    od;
    return rec(SchurCover:=Source(epi), epi:=epi, Tid:=id);
  else
    return rec(SchurCover:=Source(epi), epi:=epi);
  fi;
end;

MinimalStemExtensions:= function(G)
  local ScG,ScGg,K,MK,ans,m,pi,cG,cGg,iso,GG,GGg,Gg,epi,n,i,id;
  ScG:=SchurCoverG(G);
  ScGg:=GeneratorsOfGroup(ScG.SchurCover);
  K:=Kernel(ScG.epi);

```

```

MK:=MaximalSubgroups2(K);
ans:=[];
for m in MK do
    pi:=NaturalHomomorphismByNormalSubgroup(ScG.SchurCover,m);
    cG:=Range(pi);
    cGg:=List(ScGg,x->Image(pi,x));
    iso:=IsomorphismPermGroup(Range(pi));
    GG:=Range(iso);
    GGg:=List(cGg,x->Image(iso,x));
    Gg:=List(ScGg,x->Image(ScG.epi,x));
    epi:=GroupHomomorphismByImages(GG,G,GGg,Gg);
    n:=NrMovedPoints(Source(epi));
    if n>=2 and n<=30 and IsTransitive(Source(epi),[1..n]) then
        for i in [1..NrTransitiveGroups(n)] do
            if Order(TransitiveGroup(n,i))=Order(Source(epi)) and
                IsConjugate(SymmetricGroup(n),
                    TransitiveGroup(n,i),Source(epi)) then
                id:=[n,i];
                break;
            fi;
        od;
        Add(ans,rec(MinimalStemExtension:=Source(epi), epi:=epi, Tid:=id));
    else
        Add(ans,rec(MinimalStemExtension:=Source(epi), epi:=epi));
    fi;
od;
return ans;
end;

ResHnZ:= function(arg)
local RG,RH,n,G,H,inj,map,mapZ,CRGn,CRHn,HnG,HnH,m,res,null,ker,Hng,Hnggen,
      Hnh,Hnhgen,resHnggen,torbase,im,coker,hom,cokergen,cokergen1;
RG:=arg[1];
RH:=arg[2];
n:=arg[3];
G:=RG!.group;
H:=RH!.group;
inj:=GroupHomomorphismByFunction(H,G,x->x);
map:=EquivariantChainMap(RH,RG,inj);
mapZ:=HomToIntegers(map);
if Length(arg)>=4 then
    CRGn:=arg[4];
else
    CRGn:=CR_CocyclesAndCoboundaries(RG,n,true);
fi;
if Length(arg)=5 then
    CRHn:=arg[5];
else
    CRHn:=CR_CocyclesAndCoboundaries(RH,n,true);
fi;
HnG:=CRGn.torsionCoefficients;
HnH:=CRHn.torsionCoefficients;
if HnG=[] then
    if HnH=[] then
        return rec(HnGZ:=[],HnHZ:=HnH,Res:=[],Ker:=[[[],[],[]]],
                   Coker:=[[[],[],[]]]);
    else
        return rec(HnGZ:=[],HnHZ:=HnH,Res:=[],Ker:=[[[],[],[]]],
                   Coker:=[HnH,[HnH,IdentityMat(Length(HnH))]]));
    fi;
fi;
if HnH=[] then

```

```

        return rec(HnGZ:=HnG,HnHZ:=[],

                    Res:=List(HnG,x->[],Ker:=[HnG,[HnG,IdentityMat(Length(HnG))]],

                    Coker:=[[[],[],[]]]);

    fi;
    m:=List(IdentityMat(Length(HnG)),x->
            CRHn.cocycleToClass(mapZ!.mapping(CRGn.classToCocycle(x),n)));
    null:=NullspaceIntMat(m);
    Hng:=AbelianGroup(HnG);
    Hnggen:=GeneratorsOfGroup(Hng);
    Hnh:=AbelianGroup(HnH);
    Hnhgen:=GeneratorsOfGroup(Hnh);
    resHnggen:=List(m,x->Product([1..Length(Hnhgen)],y->Hnhgen[y]^x[y]));
    res:=GroupHomomorphismByImages(Hng,Hnh,Hnggen,resHnggen);
    ker:=Kernel(res);
    im:=Image(res);
    null:=List(GeneratorsOfGroup(ker),x->EltFiniteAbelian(Hng,x,Hnggen));
    torbase:=DiagonalMat(HnG);
    null:=LatticeBasis(Concatenation(torbase,null));
    null:=LatticeBasis(Difference(null,torbase));
    hom:=NaturalHomomorphismByNormalSubgroup(Hnh,im);
    coker:=Image(hom);
    if Order(coker)=1 then
        return rec(HnGZ:=HnG,HnHZ:=HnH,Res:=m,
                    Ker:=[AbelianInvariantsSNF(ker),[HnG,null]],Coker:=[[[],[HnH,[]]]]);
    fi;
    cokergen:=FindGenFiniteAbelian(coker);
    cokergen1:=List(cokergen,x->Representative(PreImages(hom,x)));
    cokergen1:=List(cokergen1,x->EltFiniteAbelian(Hnh,x,Hnhgen));
    return rec(HnGZ:=HnG,HnHZ:=HnH,Res:=m,
                    Ker:=[AbelianInvariantsSNF(ker),[HnG,null]],
                    Coker:=[AbelianInvariants(coker),[HnH,cokergen1]]);

end;

CosetRepresentationTid:= function(G,H)
    local Gg,HG,HGg,HGgr,n,i,id;
    Gg:=GeneratorsOfGroup(G);
    HG:=RightCosets(G,H);
    HGg:=List(Gg,x->Permutation(x,HG,OnRight));
    HGgr:=Group(HGg,());
    n:=Index(G,H);
    if n=1 then
        id:=[1,1];
    elif n<=30 then
        for i in [1..NrTransitiveGroups(n)] do
            if Order(TransitiveGroup(n,i))=Order(HGgr) and
                IsConjugate(SymmetricGroup(n),TransitiveGroup(n,i),HGgr) then
                id:=[n,i];
                break;
            fi;
        od;
    else
        id:=fail;
    fi;
    return id;
end;

AlwaysHNPholds:= function(Tid)
    local n,i,tbl,tbl4,tbl6,tbl8,tbl9,tbl10,tbl12,tbl14,tbl15;
    tbl4:=[2,4];
    tbl6:=[4,12];
    tbl8:=[2,3,4,9,11,13,14,15,19,21,22,31,32,37,38];
    tbl9:=[2,5,7,9,11,14,23];

```

```

tbl10:=[7,26,32];
tbl12:=[2,3,4,7,9,10,16,18,20,31,32,33,34,37,40,43,47,52,54,55,56,57,59,
       61,64,65,66,70,71,74,75,77,88,92,93,96,97,100,102,117,122,130,132,133,
       144,168,171,172,174,176,179,188,194,210,214,230,232,234,242,246,255,
       261,271,280];
tbl14:=[30];
tbl15:=[9,14];
tbl:=[[[],[],[],tbl14,[]],tbl16,[],tbl18,tbl19,tbl10,[]],tbl12,[],tbl14,tbl15];
if Tid=fail then
    return fail;
fi;
n:=Tid[1];
i:=Tid[2];
if IsPrime(n) or n=1 then
    return true;
elif n>15 then
    return fail;
elif i in tbl[n] then
    return false;
else
    return true;
fi;
end;

IsMetacyclic:= function(G)
local p;
if Order(G)=1 then
    return true;
fi;
for p in Set(Factors(Order(G))) do
    if not IsCyclic(SylowSubgroup(G,p)) then
        return false;
    fi;
od;
return true;
end;

ChooseGi:= function(bG,bH)
local bGs,Gicandidates,Gis,cGi,Hi,His,flag;
bGs:=ConjugacyClassesSubgroups(bG);
Gicandidates:=Filtered(bGs,x->not IsMetacyclic(Representative(x)));
Gis:=[];
for cGi in Gicandidates do
    for Gi in Elements(cGi) do
        His:=Reversed(List(ConjugacyClassesSubgroups(Intersection(Gi,bH)),
                           Representative));
        flag:=false;
        for Hi in His do
            if AlwaysHNPholds(CosetRepresentationTid(Gi,Hi))=true then
                Add(Gis,Gi);
                flag:=true;
                break;
            fi;
        od;
        if flag=true then
            break;
        fi;
    od;
    return Gis;
end;

```

```

ChooseGiIterator:= function(bG,bH)
  local bGs,Gicandidates,FindGi;
  bGs:=ConjugacyClassesSubgroups(bG);
  Gicandidates:=Filtered(bGs,x->not IsMetacyclic(Representative(x)));
  FindGi:= function(cGi,bH)
    local bG,Gi,His,Hi,flag;
    bG:=ActingDomain(cGi);
    for Gi in Elements(cGi) do
      His:=Reversed(List(ConjugacyClassesSubgroups(Intersection(Gi,bH)),
      Representative));
      for Hi in His do
        if AlwaysHNPholds(CosetRepresentationTid(Gi,Hi))=true then
          return Gi;
        fi;
      od;
    od;
    return fail;
  end;
  return IteratorByFunctions( rec(
    IsDoneIterator:= function(iter)
      local i;
      for i in [iter!.pos..Length(iter!.Gicandidates)] do
        iter!.found:=iter!.FindGi(iter!.Gicandidates[i],iter!.bH);
        if IsGroup(iter!.found) then
          iter!.pos:=i;
          return false;
        fi;
      od;
      return true;
    end,
    NextIterator:= function(iter)
      local i,Gi;
      if IsGroup(iter!.found) then
        Gi:=iter!.found;
        iter!.pos:=iter!.pos+1;
        iter!.found:=false;
        return Gi;
      else
        for i in [iter!.pos..Length(iter!.Gicandidates)] do
          iter!.found:=iter!.FindGi(iter!.Gicandidates[i],iter!.bH);
          if IsGroup(iter!.found) then
            Gi:=iter!.found;
            iter!.pos:=i+1;
            iter!.found:=false;
            return Gi;
          fi;
        od;
        return fail;
      fi;
    end,
    ShallowCopy:= function(iter)
      return rec(
        bG:=iter!.bG,
        bH:=iter!.bH,
        bGs:=iter!.bGs,
        Gicandidates:=iter!.Gicandidates,
        FindGi:=iter!.FindGi,
        pos:=iter!.pos,
        found:=iter!.found);
    end,
    bG:=bG,
    bH:=bH,
  );

```

```

bGs:=bGs,
Gicandidates:=Gicandidates,
FindGi:=FindGi,
pos:=1,
found:=false));
end;

MaximalNormalSeries:= function(G)
local M,ans,Ns,N;
Reset(GlobalMersenneTwister);
Reset(GlobalRandomSource);
M:=G;
ans:=[G];
Ns:=NormalSubgroups(G);
while Order(M)>1 do
  Ns:=Filtered(Ns,x->x<>M and IsSubgroup(M,x));
  M:=Ns[1];
  for N in Ns do
    if Order(N)>Order(M) then
      M:=N;
    fi;
  od;
  Add(ans,M);
od;
return ans;
end;

KerResH3Z:= function(G,H)
local MNS,RG,CRG3,H3Z,torbase,kerbase,Gis, Gi, RGi, ker, H3, H3g, K;
if IsNilpotent(G) then
  RG:=ResolutionNormalSeries(LowerCentralSeries(G),4);
elif IsSolvable(G) then
  RG:=ResolutionNormalSeries(DerivedSeries(G),4);
else
  MNS:=MaximalNormalSeries(G);
  if Length(MNS)>2 then
    RG:=ResolutionNormalSeries(MNS,4);
  else
    RG:=ResolutionFiniteGroup(G,4);
  fi;
fi;
CRG3:=CR_CocyclesAndCoboundaries(RG,3,true);
H3Z:=CRG3.torsionCoefficients;
if H3Z=[] then
  return [[],[],[]];
fi;
torbase:=DiagonalMat(H3Z);
kerbase:=IdentityMat(Length(H3Z));
if ValueOption("iterator")=true or ValueOption("Iterator")=true then
  Gis:=ChooseGiIterator(G,H);
else
  Gis:=ChooseGi(G,H);
fi;
for Gi in Gis do
  if IsNilpotent(Gi) then
    RGi:=ResolutionNormalSeries(LowerCentralSeries(Gi),4);
  elif IsSolvable(Gi) then
    RGi:=ResolutionNormalSeries(DerivedSeries(Gi),4);
  else
    MNS:=MaximalNormalSeries(Gi);
    if Length(MNS)>2 then
      RGi:=ResolutionNormalSeries(MNS,4);
    fi;
  fi;
od;

```

```

        else
            RGi:=ResolutionFiniteGroup(G,4);
        fi;
    fi;
    ker:=ResHnZ(RG,RGi,3,CRG3).Ker;
    kerbase:=LatticeIntersection(kerbase,Union(ker[2][2],torbase));
    kerbase:=LatticeBasis(kerbase);
    if kerbase=torbase then
        break;
    fi;
od;
kerbase:=LatticeBasis(Difference(kerbase,torbase));
H3:=AbelianGroup(H3Z);
H3g:=GeneratorsOfGroup(H3);
K:=Group(List(kerbase,x->Product([1..Length(x)],y->H3g[y]^x[y])),Identity(H3));
return [AbelianInvariantsSNF(K),[H3Z,kerbase]];
end;

ConjugacyClassSubgroupsNGHOrbitRep:= function(arg)
local G,H,Gv,NGH,NGGv,NGHNGGv,reps;
G:=arg[1];
Gv:=arg[2];
if Length(arg)=2 then
    H:=Stabilizer(G,1);
else
    H:=arg[3];
fi;
Reset(GlobalMersenneTwister);
Reset(GlobalRandomSource);
NGH:=Normalizer(G,H);
NGGv:=Normalizer(G,Gv);
reps:=List(DoubleCosets(G,NGGv,NGH),Representative);
return List(reps,x->Gv^x);
end;

ConjugacyClassesSubgroupsNGHOrbitRep:= function(arg)
local cs,G,H;
cs:=arg[1];
G:=ActingDomain(cs[1]);
if Length(arg)=1 then
    H:=Stabilizer(G,1);
else
    H:=arg[2];
fi;
return List(List(cs,Representative),x->ConjugacyClassSubgroupsNGHOrbitRep(G,x,H));
end;

MinConjugacyClassesSubgroups:= function(cslist)
local G,cs,K,MK,M,flag,ans;
if cslist=[] then
    return [];
fi;
G:=ActingDomain(cslist[1]);
ans:=[];
for cs in cslist do
    K:=Representative(cs);
    MK:=MaximalSubgroups(K);
    flag:=true;
    for M in MK do
        if ConjugacyClassSubgroups(G,M) in cslist then
            flag:=false;
            break;
    fi;
    if flag then
        ans:=ans union {K};
    fi;
done;
return ans;
end;

```

```

        fi;
    od;
    if flag=true then
        Add(ans,cs);
    fi;
od;
return ans;
end;

IsInvariantUnderAutG:= function(cslist)
local G,AutG,InAutG,OutGRep,todolist,todolistold,cs,Imcs;
if cslist=[] then
    return true;
fi;
G:=ActingDomain(cslist[1]);
AutG:=AutomorphismGroup(G);
InAutG:=InnerAutomorphismsAutomorphismGroup(AutG);
OutGRep:=List(RightCosets(AutG,InAutG),Representative);
todolist:=cslist;
while todolist<>[] do
    todolistold:=todolist;
    for cs in todolistold do
        if not cs in todolist then
            continue;
        fi;
        Imcs:=Set(OutGRep,x->ConjugacyClassSubgroups(G,Image(x,Representative(cs))));
        if not IsSubset(Set(cslist),Imcs) then
            return false;
        else
            todolist:=Difference(todolist,Imcs);
        fi;
    od;
    return true;
end;

```

REFERENCES

- [Bar81a] H.-J. Bartels, *Zur Arithmetik von Konjugationsklassen in algebraischen Gruppen*, J. Algebra **70** (1981) 179–199.
- [Bar81b] H.-J. Bartels, *Zur Arithmetik von Diedergruppenerweiterungen*, Math. Ann. **256** (1981) 465–473.
- [BT82] F. R. Beyl, J. Tappe, *Group extensions, representations, and the Schur multiplicator*, Lecture Notes in Mathematics, 958. Springer-Verlag, Berlin-New York, 1982.
- [BM83] G. Butler, J. McKay, *The transitive groups of degree up to eleven*, Comm. Algebra **11** (1983) 863–911.
- [CT07] J.-L. Colliot-Thélène, *Lectures on Linear Algebraic Groups*, Beijing lectures, Moning side centre, April 2007, <https://www.math.u-psud.fr/~colliot/BeijingLectures2Juin07.pdf>.
- [CTHS05] J.-L. Colliot-Thélène, D. Harari, A. N. Skorobogatov, *Compactification équivariante d'un tore (d'après Brylinski et Künnemann)*, Expo. Math. **23** (2005) 161–170.
- [CTS77] J.-L. Colliot-Thélène, J.-J. Sansuc, *La R-équivalence sur les tores*, Ann. Sci. École Norm. Sup. (4) **10** (1977) 175–229.
- [CTS87] J.-L. Colliot-Thélène, J.-J. Sansuc, *Principal homogeneous spaces under flasque tori: Applications*, J. Algebra **106** (1987) 148–205.
- [CK00] A. Cortella, B. Kunyavskii, *Rationality problem for generic tori in simple groups*, J. Algebra **225** (2000) 771–793.
- [Dra89] Yu. A. Drakokhrust, *On the complete obstruction to the Hasse principle*, (Russian) Dokl. Akad. Nauk BSSR **30** (1986) 5–8; translation in Amer. Math. Soc. Transl. (2) **143** (1989) 29–34.
- [DP87] Yu. A. Drakokhrust, V. P. Platonov, *The Hasse norm principle for algebraic number fields*, (Russian) Izv. Akad. Nauk SSSR Ser. Mat. **50** (1986) 946–968; translation in Math. USSR-Izv. **29** (1987) 299–322.
- [End11] S. Endo, *The rationality problem for norm one tori*, Nagoya Math. J. **202** (2011) 83–106.
- [EM73] S. Endo, T. Miyata, *Invariants of finite abelian groups*, J. Math. Soc. Japan **25** (1973) 7–26.
- [EM75] S. Endo, T. Miyata, *On a classification of the function fields of algebraic tori*, Nagoya Math. J. **56** (1975) 85–104. Corrigenda: Nagoya Math. J. **79** (1980) 187–190.
- [Flo] M. Florence, *Non rationality of some norm-one tori*, preprint (2006).
- [GAP] The GAP Group, GAP – Groups, Algorithms, and Programming, Version 4.9.3; 2018. (<http://www.gap-system.org>).
- [Ger77] F. Gerth III, *The Hasse norm principle in metacyclic extensions of number fields*, J. London Math. Soc. (2) **16** (1977) 203–208.
- [Ger78] F. Gerth III, *The Hasse norm principle in cyclotomic number fields*, J. Reine Angew. Math. **303/304** (1978) 249–252.
- [Gur78a] S. Gurak, *On the Hasse norm principle*, J. Reine Angew. Math. **299/300** (1978) 16–27.
- [Gur78b] S. Gurak, *The Hasse norm principle in non-abelian extensions*, J. Reine Angew. Math. **303/304** (1978) 314–318.

- [Gur80] S. Gurak, *The Hasse norm principle in a compositum of radical extensions*, J. London Math. Soc. (2) **22** (1980) 385–397.
- [HAP] G. Ellis, The GAP package HAP, version 1.12.6, available from <http://www.gap-system.org/Packages/hap.html>.
- [HHY20] S. Hasegawa, A. Hoshi, A. Yamasaki, *Rationality problem for norm one tori in small dimensions*, Math. Comp. **89** (2020) 923–940.
- [Has31] H. Hasse, *Beweis eines Satzes und Wiederlegung einer Vermutung über das allgemeine Normenrestsymbol*, Nachrichten von der Gesellschaft der Wissenschaften zu Göttingen, Mathematisch-Physikalische Klasse (1931) 64–69.
- [Hir64] H. Hironaka, *Resolution of singularities of an algebraic variety over a field of characteristic zero. I, II.*, Ann. of Math. (2) **79** (1964) 109–203; 205–326.
- [HKY22] A. Hoshi, K. Kanai, A. Yamasaki, *Norm one tori and Hasse norm principle*, Math. Comp. **91** (2022) 2431–2458.
- [HY17] A. Hoshi, A. Yamasaki, *Rationality problem for algebraic tori*, Mem. Amer. Math. Soc. **248** (2017) no. 1176, v+215 pp.
- [HY21] A. Hoshi, A. Yamasaki, *Rationality problem for norm one tori*, Israel J. Math. **241** (2021) 849–867.
- [Hür84] W. Hürlimann, *On algebraic tori of norm type*, Comment. Math. Helv. **59** (1984) 539–549.
- [Kan12] M. Kang, *Retract rational fields*, J. Algebra **349** (2012) 22–37.
- [Kap87] G. Karpilovsky, *The Schur multiplier*, London Mathematical Society Monographs. New Series, 2. The Clarendon Press, Oxford University Press, New York, 1987.
- [KMRT98] M.-A. Knus, A. Merkurjev, M. Rost, J.-P. Tignol, *The book of involutions*, American Mathematical Society Colloquium Publications, 44, American Mathematical Society, Providence, RI, 1998, xxii+593 pp.
- [Kun84] B. E. Kunyavskii, *Arithmetic properties of three-dimensional algebraic tori*, (Russian) Integral lattices and finite linear groups, Zap. Nauchn. Sem. Leningrad. Otdel. Mat. Inst. Steklov. (LOMI) **116** (1982) 102–107, 163; translation in J. Soviet Math. **26** (1984) 1898–1901.
- [Kun90] B. E. Kunyavskii, *Three-dimensional algebraic tori*, Selecta Math. Soviet. **9** (1990) 1–21.
- [Kun07] B. E. Kunyavskii, *Algebraic tori — thirty years after*, Vestnik Samara State Univ. (2007) 198–214.
- [LL00] N. Lemire, M. Lorenz, *On certain lattices associated with generic division algebras*, J. Group Theory **3** (2000) 385–405.
- [LPR06] N. Lemire, V. L. Popov, Z. Reichstein, *Cayley groups*, J. Amer. Math. Soc. **19** (2006) 921–967.
- [LeB95] L. Le Bruyn, *Generic norm one tori*, Nieuw Arch. Wisk. (4) **13** (1995) 401–407.
- [Lor05] M. Lorenz, *Multiplicative invariant theory*, Encyclopaedia Math. Sci., vol. 135, Springer-Verlag, Berlin, 2005.
- [Mac20] A. Macedo, *The Hasse norm principle for A_n -extensions*, J. Number Theory **211** (2020) 500–512.
- [Man74] Yu. I. Manin, *Cubic forms: algebra, geometry, arithmetic*, North-Holland Mathematical Library 4, North-Holland, Amsterdam, 1974.
- [Ono61] T. Ono, *Arithmetic of algebraic tori*, Ann. of Math. (2) **74** (1961) 101–139.
- [Ono63] T. Ono, *On the Tamagawa number of algebraic tori*, Ann. of Math. (2) **78** (1963) 47–73.
- [Opo80] H. Opolka, *Zur Auflösung zahlentheoretischer Knoten*, Math. Z. **173** (1980) 95–103.
- [Pla82] V. P. Platonov, *Arithmetic theory of algebraic groups*, (Russian) Uspekhi Mat. Nauk **37** (1982) 3–54; translation in Russian Math. Surveys **37** (1982) 1–62.
- [PD85a] V. P. Platonov, Yu. A. Drakokhrust, *On the Hasse principle for algebraic number fields*, (Russian) Dokl. Akad. Nauk SSSR **281** (1985) 793–797; translation in Soviet Math. Dokl. **31** (1985) 349–353.
- [PD85b] V. P. Platonov, Yu. A. Drakokhrust, *The Hasse norm principle for primary extensions of algebraic number fields*, (Russian) Dokl. Akad. Nauk SSSR **285** (1985) 812–815; translation in Soviet Math. Dokl. **32** (1985) 789–792.
- [PR94] V. P. Platonov, A. Rapinchuk, *Algebraic groups and number theory*, Translated from the 1991 Russian original by Rachel Rowen, Pure and applied mathematics, 139, Academic Press, 1994.
- [Rob96] D. J. S. Robinson, *A course in the theory of groups*, Second edition. Graduate Texts in Mathematics, 80. Springer-Verlag, New York, 1996.
- [Roy87] G. F. Royle, *The transitive groups of degree twelve*, J. Symbolic Comput. **4** (1987) 255–268.
- [Sal84] D. J. Saltman, *Retract rational fields and cyclic Galois extensions*, Israel J. Math. **47** (1984) 165–215.
- [San81] J.-J. Sansuc, *Groupe de Brauer et arithmétique des groupes algébriques linéaires sur un corps de nombres*, (French) J. Reine Angew. Math. **327** (1981) 12–80.
- [Swa83] R. G. Swan, *Noether's problem in Galois theory*, Emmy Noether in Bryn Mawr (Bryn Mawr, Pa., 1982), 21–40, Springer, New York-Berlin, 1983.
- [Swa10] R. G. Swan, *The flabby class group of a finite cyclic group*, Fourth International Congress of Chinese Mathematicians, 259–269, AMS/IP Stud. Adv. Math., 48, Amer. Math. Soc., Providence, RI, 2010.
- [Tat67] J. Tate, *Global class field theory*, Algebraic Number Theory (Proc. Instructional Conf., Brighton, 1965), 162–203, Thompson, Washington, D.C., 1967.
- [Vos67] V. E. Voskresenskii, *On two-dimensional algebraic tori II*, (Russian) Izv. Akad. Nauk SSSR Ser. Mat. **31** (1967) 711–716; translation in Math. USSR-Izv. **1** (1967) 691–696.
- [Vos69] V. E. Voskresenskii, *The birational equivalence of linear algebraic groups*, (Russian) Dokl. Akad. Nauk SSSR **188** (1969) 978–981; erratum, ibid. 191 1969 nos., 1, 2, 3, vii; translation in Soviet Math. Dokl. **10** (1969) 1212–1215.
- [Vos70] V. E. Voskresenskii, *Birational properties of linear algebraic groups*, (Russian) Izv. Akad. Nauk SSSR Ser. Mat. **34** (1970) 3–19; translation in Math. USSR-Izv. **4** (1970) 1–17.
- [Vos74] V. E. Voskresenskii, *Stable equivalence of algebraic tori*, (Russian) Izv. Akad. Nauk SSSR Ser. Mat. **38** (1974) 3–10; translation in Math. USSR-Izv. **8** (1974) 1–7.
- [Vos88] V. E. Voskresenskii, *Maximal tori without affect in semisimple algebraic groups*, (Russian) Mat. Zametki **44** (1988) 309–318; translation in Math. Notes **44** (1988) 651–655.
- [Vos98] V. E. Voskresenskii, *Algebraic groups and their birational invariants*, Translated from the Russian manuscript by Boris Kunyavskii, Translations of Mathematical Monographs, 179. American Mathematical Society, Providence, RI, 1998.
- [VK84] V. E. Voskresenskii, B. E. Kunyavskii, *Maximal tori in semisimple algebraic groups*, Kuibyshev State Inst., Kuibyshev (1984). Deposited in VINITI March 5, 1984, No. 1269-84 Dep. (Ref. Zh. Mat. (1984), 7A405 Dep.).
- [Yam12] A. Yamasaki, *Negative solutions to three-dimensional monomial Noether problem*, J. Algebra **370** (2012) 46–78.

DEPARTMENT OF MATHEMATICS, NIIGATA UNIVERSITY, NIIGATA 950-2181, JAPAN
Email address: hoshi@math.sc.niigata-u.ac.jp

GRADUATE SCHOOL OF SCIENCE AND TECHNOLOGY, NIIGATA UNIVERSITY, NIIGATA 950-2181, JAPAN
Email address: kanai@m.sc.niigata-u.ac.jp

DEPARTMENT OF MATHEMATICS, KYOTO UNIVERSITY, KYOTO 606-8502, JAPAN
Email address: aiichi.yamasaki@gmail.com