arXiv:2008.07940v2 [quant-ph] 19 Aug 2020

Mechanical dissipation below 1 μ Hz with a cryogenic diamagnetic-levitated micro-oscillator

Yingchun Leng,¹ Rui Li,^{2,3,4} Xi Kong,¹ Han Xie,¹ Di Zheng,¹ Peiran Yin,¹ Fang Xiong,¹ Tong

Wu,¹ Chang-Kui Duan,^{2,3,4} Youwei Du,^{1,5} Zhang-qi Yin,⁶ Pu Huang,^{1,*} and Jiangfeng Du^{2,3,4,†}

¹National Laboratory of Solid State Microstructures and Department of Physics, Nanjing University, Nanjing 210093, China

²Hefei National Laboratory for Physical Sciences at the Microscale and Department of Modern Physics,

- ³CAS Key Laboratory of Microscale Magnetic Resonance,
- University of Science and Technology of China, Hefei 230026, China

⁴Synergetic Innovation Center of Quantum Information and Quantum Physics,

University of Science and Technology of China, Hefei 230026, China

⁵Collaborative Innovation Center of Advanced Microstructures and

Jiangsu Key Laboratory for Nano Technology, Nanjing 210093, China

⁶Center for Quantum Technology Research and Key Laboratory of

Advanced Optoelectronic Quantum Architecture and Measurements (MOE),

School of Physics, Beijing Institute of Technology, Beijing 100081, China

Ultralow dissipation plays an important role in sensing applications and exploring macroscopic quantum phenomena using micro-and nano-mechanical systems. We report a diamagnetic-levitated micro-mechanical oscillator operating at a low temperature of 3K with measured dissipation as low as 0.59 μ Hz and a quality factor as high as 2×10^7 . To the best of our knowledge the achieved dissipation is the lowest in micro- and nano-mechanical systems to date, orders of magnitude improvement over the reported state-of-the-art systems based on different principles. The cryogenic diamagnetic-levitated oscillator described here is applicable to a wide range of mass, making it a good candidate for measuring both force and acceleration with ultra-high sensitivity. By virtue of the naturally existing strong magnetic gradient, this system has great potential in quantum spin mechanics study.

Introduction. —Micro- and nano-mechanical systems have been developed as force sensors for detecting a wide range of weak signals, such as charge [1], spin [2], mass [3], etc. It has also been considered recently as potential tools for exploring force from new physics, such as a variety of dark matter models [4–6], wave-function collapse models [7–12], corrections to Newtonian gravity [13, 14] and the high frequency gravitational wave [15]. In experimental realization, the signal understudy should be larger than the noise level of the force sensor that is characterized by noise power density:

$$S_{\rm FF}(\omega_0) = 4m\gamma k_B T,\tag{1}$$

where γ is the mechanical dissipation character. One direct way to improve the performance is to make the oscillator mass m extremely small [16] so as to achievable the goal even at room temperature. However, for a wide range of applications, such as the force from gravity or acceleration, sufficient large mass is important, so low temperature environments and the lower mechanical dissipation γ are more useful in improving force sensitivity.

Besides sensing applications, dissipation is also paramount important for study quantum phenomena at macroscopic scale using micro- and nano-mechanical systems [17, 18]. In order to control a macroscopic quantum state, such as generating spatial superposition, an important requitement is to overcome thermal decoherence. The finite-temperature oscillator's thermal decoherence rate $\gamma_{\rm th} = \bar{n}\gamma$ with $\bar{n} = k_B T/\hbar\omega_0$ the thermal average phonon number [19]. Especially, in order to maintain quantum coherence within one oscillation period, we obtain the relation:

$$\frac{\omega_0^2}{\gamma} > k_B T/\hbar. \tag{2}$$

The left hand side is equal to the product of oscillator resonance frequency ω_0 and quality factor $Q = \omega_0/\gamma$, known as $\omega_0 Q$ product [19], so given ω_0 and environmental temperature T, a lower mechanical dissipation γ leads to better quantum coherence.

For a solid state mechanical resonator operating at high vacuum, the dissipation mainly comes from the direct coupling between the resonator and the substrate. In general, the dissipation of the solid-state mechanical system is inversely proportional to the oscillator's mass. As the size decreases, it becomes a challenge to achieve very low mechanical dissipation. Efforts have been made to pursuit lower dissipation along different ways, such as employing novel improvement in material [20, 21], geometry [23], and strain [22]. A dissipation down to the scale of mHz [22] has been reported. For a ultra-light mechanical resonator made of 1D or 2D materials with a mass of 10^{-18} g, a dissipation of 11Hz is achieved [24].

Different from solid-state mechanical systems, the dissipation of a levitated mechanical oscillator in ultra high vacuum is theoretically considered to be much lower [25]. In a recent experiment, a dissipation about

University of Science and Technology of China, Hefei 230026, China



FIG. 1. (Color online). Experiment setup. (a), The magneto-gravitational trap (MGT) is placed on the three-stage spring-mass suspension system which is used to isolate external vibration, the whole structure is mounted inside the chamber of a cryostat, a 633 nm laser light reaches the sample chamber though fiber and is focused loosely on the micro-sphere, and piezo positioners are used to control the position of trap so that scattered light is collected via lens. A CMOS camera is used to record the position of the micro-sphere, and an avalanche photodiode detector is used to measured the real-time intensity of the scattered light that is used to feedback cool or excite the motion of the micro-sphere via magnetic force via a magnetic field generated by a small coil near the MGT. (b), Vibration isolation system, the picture of spring-mass suspension structure and the MGT placement inside it, especially, soft copper braids are used to realize thermal connection between. (c) and (d), snapshots of the excited motion of the micro-sphere corresponding to two oscillation modes of different resonant frequencies (mode 1: 11.7 Hz, mode 2: 8.4 Hz) in x-y plane, where the exposure time is 200 ms, much longer than the period of oscillation (scale bar is $30 \ \mu m$).

10 μ Hz has been realized using optical levitation in high vacuum [26–28], and a dissipation as low as about 81 μ Hz has been realized in an electric trap [29]. Typically, optical and electrical levitated oscillators work at room temperature due to the required power input, while on the other hand, magnetic levitated oscillators, either Meissner levitated [30, 31] and diamagnetic levitated [32, 33], are fully passive with no energy inputs and so naturally suitable for low temperature operation, and have recently been demonstrated to have mechanical dissipations at the order of magnitude of 10 μ Hz [31–33]. However, realization of a diamagnetic levitated oscillator operating at low temperature is still elusive [32–35].

In this letter, we report a diamagnetic levitated micro-mechanical oscillator working at low temperature. The levitation is realized with a magneto-gravitational trap, where a diamagnetic micro-sphere of mass of 540 pg (1 pg = 10^{-12} g) is stably levitated. We observed a ultra-low mechanical dissipation with damping rate $\gamma/2\pi$ of 0.59 \pm 0.11 µHz at resonance frequency of 11.7 Hz, the corresponding quality factor (Q) is 2×10^7 . The reported mechanical dissipation is more than three orders of magnitude lower than traditional solid-state oscillators [20–23], and one to three orders lower than reported optical levitated oscillators [26–28], Meissner

levitated [30, 31] and electrical levitated oscillators [29], and also about an order of magnitude improvement over previous experiments based on the same principle but working at room temperature [32–35], the reported mechanical dissipation is even slightly smaller than the start-of-art milligram-scale pendulum oscillator [36, 37]. The behavior of this system used as force and acceleration sensors is evaluated and its potential applications to realizing quantum spin-mechanics systems are discussed.

Experimental system. — The experimental setup is shown in Fig. 1. A magneto-gravitational trap (denoted as MGT hereafter) are placed in low-temperature and high-vaccum environment. The low temperature is generated by a cryogen-free cryostat. To overcome the strong vibration generated by the operation of the cryostat, a special designed string-mass suspensions system, as shown in Fig. 1 (a), is used to isolate vibration noise. The suspension structure consists of three stages, with each stage corresponds to a suspension load mass as well as character frequency. The designed isolation at frequency 8Hz is 54 dB and is expected to be better at resonance frequency of diamagnetic levitated micro-mechanical oscillator (see Table I for parameter of suspension structure).

The magneto-gravitational trap is similar to the one



FIG. 2. (Color online). Measured mechanical dissipation. (a), Logarithmic plot free ring-down of normalized oscillation energy $X(t)^2/X(0)^2$ coppresponding to oscillation mode with resonance frequency 11.7 Hz as function of time. Green and blue dots are results with statistic errors measured under high purity helium gas and vacuum. Solid curve lines are fit to the exponential decay given by Eq. (4) (b), Same as (a) but for the oscillation mode with resonance frequency 8.7 Hz, with dark yellow the helium gas and red the vacuum. (c) The mechanical dissipation $\gamma/2\pi$ and the corresponding oscillator mass for a variety of mechanical systems based on different mechanisms. Red star is dissipation of 11.7 Hz mode in this experiment, rhombuses are solid-state oscillator [20–24], squares are optical levitated oscillator [26-28], the pentagon is electrical levitated oscillator [29], triangles are Meissner levitated oscillator [30, 31] and circles is pendulum oscillator with milligram-scale [36, 37].

TABLE I. Designed parameters of the vibration isolation system. The characteristic frequency is the mass-spring suspension resonance frequency at vertical direction (z axis) which is significantly larger than the frequency in horizon (x, y), isolation give actuation in square of vibration amplitude response at frequency 8Hz.

Stage	Mass (kg)	Character frequency (Hz)	Isolation (dB)
1st	7	1.4	29
2nd	1.6	2.5	19
3rd	0.08	4.6	6

used at room temperature [33] but with modifications in geometry. It is generated by a set of SmCo magnets with octagonal bilayer geometry as shown in Fig. 1 (b). The oscillator is a microsphere of polyethylene glycol which is loaded into the trap by a home-built nebulizer, the charge on the micro-sphere is eliminated by following a standard procedure [33]. After pumping the sample chamber into vacuum, the system is cooled down to and the sample chamber is then maintained at 3K during the experiment. The temperature of the magneto-gravitational trap, due to its weak thermal connection to cold plate of sample chamber, has a higher temperature about 7K.

To obtain the position and the dynamics of the levitated micro-sphere, a weak 633 nm laser with power less than 50 μ w is sent into the chamber via single mode fiber and is loosely focused on the microsphere, and the scattered light from the microsphere is collected vertically via a lens and comes out of the cryostat via windows. To realize feedback cooling and excitation of the micro-sphere, an avalanche photodiode detector (APD) is firstly used to measure the intensity of scattered light that contains the real time information of the microsphere position, then the electrical signal of the detector is amplified and sent to a computer where its amplitude and phase corresponding to the oscillator resonance frequency are calculated, and a program based feedback circuit is used to control the arbitrary waveform generator which generated the feedback signal. Typically, the feedback bandwidth is of the scale of 0.1 Hz which is fast enough for our system. The output electric signal goes back to the sample stage via a small coil near the micro-sphere and generating a weak magnetic Combined with the magnetic field gradient of field. the MGT finally, it becomes a feedback force applied on the microsphere. Due to the limitation of the dynamic range of APD, we used a CMOS camera instead so that the absolute position of the microsphere was directly recorded. Fig. 1 (c) and (d) is typical images of micro-sphere excited motion corresponding to two resonance modes.

Measurement method and results. — To obtain the mechanical dissipation of the micro-oscillator, we start from the equation of motion of the a micro-oscillator

of math m of one oscillation mode with a resonance frequency of $\omega_0/2\pi$):

$$m\ddot{x} + m\gamma\dot{x} + m\omega_0^2 x + m\epsilon x^3 = F_{\rm fluc}(t), \qquad (3)$$

where the second term describes the dissipation the oscillator with a damping rate $\gamma/2\pi$, the fourth term is the Duffing nonlinearity, and $F_{\text{fluc}}(t)$ is the total fluctuation force, including thermal fluctuation, external vibration etc. The motion can be written in the form $x(t) = X(t) \cos(\omega_0 t + \varphi(t))$ with X(t) and $\varphi(t)$ the slow-varying amplitude and phase, respectively. There are several commonly used experimental methods to determine the dissipation γ . One is to measure the system's frequency response. For harmonic oscillator, the corresponding linewidth equals to γ/π , but in the presence of nonlinearity, the measured linewidth is broadened significantly, even when it is driven by solely the thermal fluctuation [26, 33]. We obtained γ by energy autocorrelation proportional to $\langle X(t)^2 X(0)^2 \rangle$, with X(t), as it has been shown that energy autocorrelation is insensitive to nonlinearity [38]. In the actual realization, we directly measure the free decay of $X(t)^2$, to do this we first excited the oscillator to initial amplitude X(0)that is much higher (more than 10 times) than the background stochastic motion amplitude $\langle X_{\rm ba} \rangle^2$ driven by the fluctuation force $F_{\text{fluc}}(t)$, and the theoretical evolution can be written as:

$$X(t)^{2} = X(0)^{2} e^{-t\gamma}$$
(4)

with error less than a few percent [33, 38]. Under our experimental conditions, $X(t)^2$ were obtained using a CMOS camera based on the method in Ref.[37]. The position of the microsphere was recorded for a duration so as to obtain an average of $X(t)^2$ and its statistical deviation. The measured data were then fitted with Eq. (4) to give the dissipation rate γ . Then the dissipation rate is obtained by fitting the measured data with Eq. (4).

The diameter of the micro-sphere used in this experiment is $9.8 \pm 0.9 \ \mu m$, which is obtained in advance from the dissipation γ measured at high purity helium gas environment with pressure 2×10^{-6} mbar. As the helium gas at a temperature of 3K can still be considered as a idea gas, the diameter is simply related to the microsphere oscillation damping rate and the pressure as a result of background gas collisions [25]: $\gamma = (16/\pi)(P/\nu R\rho)$, with P and ν the pressure and the mean speed of the background gas, respectively, and ρ the density of the micro-sphere. Then we turned off the helium gas and pumped the chamber to high vacuum with background pressure 3.3×10^{-7} mbar (measured at room temperature), which is maintained stable during the experiment. Fig. 2 (a) and (b) shown the normalized damping curve as $X(t)^2/X(0)^2$, and the results is summarized in Table II, for the vibrational



FIG. 3. (Color online). Estimation of performance of force and acceleration sensing. Left axis, force sensitivity as function of mass at environment temperature of 3K (light blue solid line) and 10 mK (light blue dash line), force from single electron spin (dark blue solid line) and single proton spin (dark blue dash line) are shown for comparison. Right axis, same as left but of acceleration sensitivity. The experimently measured dissipation $\gamma/2\pi = 0.59 \ \mu$ Hz and the magnetic gradient G = 10⁴ T/m are adopted in the estimation.

mode of resonance frequency 11.7 Hz (mode 1), we observed a ultra-long damping time $\tau = 1/\gamma$ of 2.7 \times 10^5 s (about 70 hours), corresponding to a mechanical dissipation of $\gamma/2\pi = 0.59 \pm 0.11 \ \mu\text{Hz}$ and a quality factor $Q = 2.0 \pm 0.4 \times 10^7$. For the vibrational mode of resonance frequency 8.7 Hz (mode 2), the mechanical dissipation is $\gamma/2\pi = 2.6 \pm 0.1 \ \mu$ Hz, about 4 times larger than that of mode 1. A possible origin of such a difference may come from boundary effects of residual helium gas [39] in carrying out our experiment. Fig. 2 (c) plots the comparison of our results with currently reported micro- and nano-mechanical using different principle. It clearly shows that our system performs with significant lower dissipation in a wide range of mass, and is even comparable to those milligram-scale mechanical system whose mass is larger by about 7 orders of magnitude [36, 37].

TABLE II. Measured mechanical dissipation at low temperature and high vacuum. The diameter of the oscillator is $9.8 \pm 0.95 \ \mu$ m, and the corresponding mass is 540 ± 160 pg. The errors show the statistic deviation at the 95 % confidence level.

Mode	$\omega_0/2\pi$ (Hz)	$\gamma/2\pi~(\mu {\rm Hz})$	$Q(10^7)$
1	11.7	0.59 ± 0.11	2.0 ± 0.4
2	8.4	2.6 ± 0.1	0.34 ± 0.02

Discussion and summary. — The potential performance of our diamagnetic-levitated oscillator used for force and acceleration sensing can be evaluated from the dissipation achieved in our experiment. The

sensitivity of force sensor is given by Eq. (1), and the sensitivity of acceleration is characterized by noise power density $S_{aa}(\omega_0) = 4\gamma k_B T/m$, which differs from that of the force in that large mass is advantageous. In principle, a magneto-gravitational trap can levitate particles of a very wide range of mass of the order of magnitude of 10^{-14} [33] to 10^{-3} g [34, 35]. Fig. 3 shows the force and acceleration at 3K which corresponding to this experiment and 10 mK which can be reached by a commercial dilution refrigerator. At 3K, we see that the force sensitivity is enough to detect a single electron when the oscillator's mass is smaller than 4×10^{-9} g. In the estimation, a magnetic gradient $G = 10^4$ T/m from a typical magneto-gravitational trap [32, 33] is adopted. A single proton spin is also detectable when the the oscillator's mass is smaller than 100 fg. On the other hand, for a mass of 10^{-6} g, the acceleration sensitivity reaches $\sqrt{S_{aa}(\omega_0)} < 10^{-10} g / \sqrt{\text{Hz}} \ (g = 9.8 \text{ m/s}^2) \text{ at } 3\text{K},$ comparable to the state-of-art method reported so far [40].

The potential of application of this system to the study of macroscopic quantum process can be estimated by assuming an oscillator resonance frequency $\omega_0/2\pi \simeq$ 100 Hz [32] and at a 10 mK environment temperature. We find that $\omega_0 Q/2\pi \simeq 10^{10} \text{ Hz} \gg k_B T/(2\pi\hbar)$ and Therefore, the quantum Eq. (2) is well satisfied. coherence of the system could last for many oscillation periods. Especially, it is interesting to consider applying the system to the realization of quantum spin-mechanics dynamics [41, 42]. Considering the interaction between electron spin, the spin-mechanical coupling strength $\lambda =$ $G x_{zpl} \mu_e / \hbar$, where $x_{zpl} = \sqrt{\hbar / m \omega_0}$ is the zero point motion and μ_e is the electron spin magnetic moment, for oscillator with mass of 10^{-13} g, we have $\lambda/2\pi \simeq$ 10 kHz, which is four orders of magnitude larger than the decoherence rate $1/T_2$ of electron spin at low temperature [43], and four orders of magnitude larger than thermal decoherence rate $\gamma_{\rm th}$ of the oscillator. The coopertivity here is $C = \lambda^2 T_2 Q \hbar / (k_B T) \simeq 10^8$, which marks the onset of highly coherent quantum effects.

In summary, we report the realization of a cryogenic diamagnetic-levitated micro-mechanical system with a recorded low dissipation value, which provides a new way to achieve high-performance sensing and quantum control of macroscopic mechanical dynamics.

We thank Zhujing Xu, Fei Xue and Jie Zhao for helpful discussion. This work was supported by the National Key R&D Program of China (Grant No. 2018YFA0306600), the National Natural Science Foundation of China (Grant No. 61635012, No. 11675163, No. 11890702, No. 81788101, No. 11761131011, and No. 11722544), the CAS (Grant No. QYZDY-SSW-SLH004, Grant No. GJJSTD20170001), the Fundamental Research Funds for the Central Universities (Grant No. 021314380149), and the Anhui Initiative in Quantum Information Technologies (Grant No. AHY050000). Z.-Q. Yin is supported by National Natural Science Foundation of China under Grant No. 61771278 and Beijing Institute of Technology Research Fund Program for Young Scholars.

- hp@nju.edu.cn
- [†] djf@ustc.edu.cn
- A. N. Cleland and M. L. Roukes, A nanometre-scale mechanical electrometer Nature (London) **392**, 160 (1998).
- [2] D. Rugar, R. Budakian, H. J. Mamin, and B. W. Chui. Single spin detection by magnetic resonance force microscopy Nature (London) 430, 329 (2004).
- [3] K. Jensen, K. Kim, and A. Zettl, An atomic-resolution nanomechanical mass sensor Nature Nanotechnology 3, 533(2008).
- [4] J. Manley, R. Stump, D. Wilson, et al. Searching for scalar dark matter with compact mechanical resonators, Phys. Rev. Lett. 124, 151301 (2019).
- [5] A. Kawasaki. Search for Kilogram-scale Dark Matter with Precision Displacement Sensors. Phys. Rev. D 99, 023005 (2019).
- [6] A. D. Rider, D. C. Moore, C. P. Blakemore, et al. Search for Screened Interactions Associated with Dark Energy below the 100μm Length Scale. Phys. Rev. Lett. 117, 101101 (2016).
- [7] S. L. Adler. Stochastic collapse and decoherence of a nondissipative forced harmonic oscillator J PHYS A-MATH 38, 2729 (2005)
- [8] M. Bahrami, M. Paternostro, A. Bassi, H. Ulbricht. Proposal for a Noninterferometric Test of Collapse Models in Optomechanical Systems. Phys. Rev. Lett. 112, 210404 (2014).
- [9] S. Nimmrichter, K. Hornberger, K. Hammerer. Optomechanical sensing of spontaneous wave-function collapse. Phys.Rev.Lett. 113, 020405 (2014).
- [10] L. Diosi . Testing spontaneous wave-function collapse models on classical mechanical oscillators. Phys.Rev.Lett.114,050403 (2015).
- [11] A. Vinante, M. Bahrami, A. Bassi, et al. Upper Bounds on Spontaneous Wave-Function Collapse Models Using Millikelvin-Cooled Nanocantilevers. Phys.Rev.Lett.116, 090402 (2015).
- [12] A. Vinante, R. Mezzena, P. Falferi, et al. Improved Noninterferometric Test of Collapse Models Using Ultracold CantileversPhys.Rev.Lett.119, 110401 (2016).
- [13] A. A. Geraci, S. B. Papp, J. Kitching. Short-range force detection using optically-cooled levitated microspheres. Phys.Rev.Lett.105, 101101 (2010).
- [14] R. S. Decca, D. Lopez, H. B. Chan, E. Fischbach, D. E. Krause, C. Jamell. Constraining New Forces in the Casimir Regime Using the Isoelectronic Technique. Phys.Rev.Lett.94, 240401 (2005).
- [15] A. Arvanitaki, A. A. Geraci. Detecting high-frequency gravitational waves with optically-levitated sensors. Phys.Rev.Lett.110, 071105 (2013).
- [16] M. J. Biercuk, H. Uys, J. W. Britton, et al. Ultrasensitive detection of force and displacement using trapped ions Nature Nanotechnology. 5, 646 (2010).
- [17] V. B. Braginsky, V. P. Mitrofanov, K. S. Thorne, et al. Systems with Small Dissipation. American Journal of

Physics. 55, 1153 (1987).

- [18] Chen Y. Macroscopic quantum mechanics: theory and experimental concepts of optomechanics. J. Phys. B. 46, 104001(2013).
- [19] M. Aspelmeyer, T. J. Kippenberg, F. Marquardt. Cavity optomechanics. Rev.Mod.Phys. 86,1391 (2013).
- [20] Tao Y, J. M. Boss, B. A. Moores, et al. Single-crystal diamond nanomechanical resonators with quality factors exceeding one million. Nature Communications 5 (2014).
- [21] H. J. Mamin, D. Rugar. Sub-attonewton force detection at millikelvin temperatures. Applied Physics Letters. 79,3358 (2001).
- [22] A. H. Ghadimi, S. A. Fedorov, N. J. Engelsen, et al. *Elastic strain engineering for ultralow mechanical* dissipation. Science. **360** (6390) 764 (2018).
- [23] Y. Tsaturyan, A. Barg, E. S. Polzik, et al. Ultracoherent nanomechanical resonators via soft clamping and dissipation dilution. Nature Nanotechnology, 12,776 (2017).
- [24] J. Moser, A. Eichler, J. Güttinger, et al. Nanotube mechanical resonators with quality factors of up to 5 million. Nature Nanotechnology, 9:1007 (2014).
- [25] D. E. Chang, C. A. Regal, S. B. Papp, et al. Cavity opto-mechanics using an optically levitated nanosphere. Proceedings of the National Academy of ences of the United States of America, 107,1005 (2009).
- [26] J. Gieseler, L. Novotny, R. Quidant. Thermal nonlinearities in a nanomechanical oscillator. Nature Physics. 9,806 (2013).
- [27] U. Deli, D. Grass, M. Reisenbauer, et al. Levitated cavity optomechanics in high vacuum. Quantum Sci. Technol. 5 025006 (2020).
- [28] F. Monteiro, Li W, G. Afek, et al. Force and acceleration sensing with optically levitated nanogram masses at microkelvin temperatures. Phys. Rev. A.101,053835 (2020).
- [29] A. Pontin, N. P. Bullier , M. Toro, et al. Ultranarrow-linewidth levitated nano-oscillator for testing dissipative wave-function collapse. Phys.Rev.Research. 2,023349 (2020).
- [30] J. Gieseler, A. Kabcenell, E. Rosenfeld, et al. Single-Spin Magnetomechanics with Levitated Micromagnets. Phys.Rev.Lett. 124,163604 (2020).
- [31] A. Vinante, P. Falferi, G. Gasbarri, A. Setter, C. Timberlake, H. Ulbricht. Ultralow Mechanical Damping with Meissner-Levitated Ferromagnetic Microparticles.

Phys.Rev.Applied 13, 064027 (2020).

- [32] B. R. Slezak, C. W. Lewandowski, J. F. Hsu, et al. Cooling the Motion of a Silica Microsphere in a Magneto-Gravitational Trap in Ultra-High Vacuum. New Journal of Physics. 20 063028 (2018).
- [33] Zheng D, Leng Y, Kong X, et al. Room temperature test of the Continuous Spontaneous Localization model using a levitated micro-oscillator. Phys.Rev.Research. 2,013057 (2020).
- [34] Yin P, Li R, Wang Z, et al. Manipulation of a Micro-object Using Topological Hydrodynamic Tweezers.Phys.Rev.Applied. 12,044017 (2019).
- [35] R. Nakashima. Diamagnetic levitation of a milligram-scale silica using permanent magnets for the use in a macroscopic quantum measurement. Phys. Lett. A, 384,126592 (2020).
- [36] K. Komori, Y. Enomoto, C. P. Ooi, et al. Attonewton-meter torque sensing with a macroscopic optomechanical torsion pendulum. Phys. Rev. A 101, 011802(R) (2020).
- [37] S. B. Catao-Lopez, J. G. Santiago-Condori, K. Edamatsu, et al. *High-Q Milligram-Scale Monolithic Pendulum for Quantum-Limited Gravity Measurements*. Phys.Rev.Lett. **124**,221102 (2020).
- [38] B. C. Stipe, H. J. Mamin, T. D. Stowe, et al. Noncontact Friction and Force Fluctuations between Closely Spaced Bodies. Phys.rev.lett. 87,096801 (2001).
- [39] M. Defoort, K. J. Lulla, T.Crozes, O. Maillet, O. Bourgeois, E. Collin. Slippage and Boundary Layer Probed in an Almost Ideal Gas by a Nanomechanical Oscillator. Phys.Rev.Lett.113,136101 (2014).
- [40] C. Timberlake, G. Gasbarri, A. Vinante, A. Setter, H. Ulbricht. Acceleration sensing with magnetically levitated oscillators above a superconductor. Applied Physics Letters. 115,224101 (2019)
- [41] P. Rabl, P. Cappellaro, M. V. Gurudev Dutt, L. Jiang, J. R. Maze, M. D. Lukin. Strong magnetic coupling between an electronic spin qubit and a mechanical resonator.Phys.Rev.B. **79**,041302 (2008).
- [42] Yin Z Q, Li T, Zhang X, et al. Large quantum superpositions of a levitated nanodiamond through spin-optomechanical coupling. Phys.Rev.A.88,033614 (2013).
- [43] M. H. Abobeih, J. Cramer, M. A. Bakker, et al. One-second coherence for a single electron spin coupled to a multi-qubit nuclear-spin environment. Nature Communications. 9,2552 (2018).