
TOOLS FOR MODELLING AND SIMULATING THE SMART GRID

Ricardo M. Czekster

Newcastle University, School of Computing
ricardo.melo-czekster@newcastle.ac.uk

ABSTRACT

The Smart Grid (SG) is a Cyber-Physical System (CPS) considered a critical infrastructure divided into cyber (software) and physical (hardware) counterparts that complement each other. It is responsible for timely power provision wrapped by Information and Communication Technologies (ICT) for handling bi-directional energy flows in electric power grids. Enacting control and performance over the massive infrastructure of the SG requires convenient analysis methods. Modelling and simulation (M&S) is a performance evaluation technique used to study virtually any system by testing designs and artificially creating ‘what-if’ scenarios for system reasoning and advanced analysis. M&S preserves stressing the actual physical infrastructure and systems in production by addressing the problem in a computational perspective. Present work compiles a non-exhaustive list of tools for M&S of interest when tackling SG capabilities. Our contribution is to delineate available options for modellers when modelling power systems in combination with ICT. We also show the auxiliary tools and details of most relevant solutions pointing out major features and combinations over the years.

Keywords Modelling & Simulation · Co-simulation · Cyber-Physical Systems · Smart Grid · Tools

1 Introduction

Modelling and simulation (M&S) is a key technique for assessing the performance of virtually any system. The Smart Grid (SG) is a Cyber-Physical System (CPS) and also a critical infrastructure amenable for M&S. The SG encompasses a large infrastructure through extensive use of Information and Communication Technologies (ICT). Gungor et al. (2012) [36] surveyed the SG in terms of ICT requirements, explaining its major features and concerns for modelling assets and new service capabilities for increased remote control. Alongside Industrial Control Systems (ICS) and Supervisory Control and Data Acquisition (SCADA) systems, they pose a large complex system requiring multiple analysis angles [61]. M&S provides means to artificially create models that map real-world settings where analysts address ‘what-if’ questions and quantitative analysis over multiple scenarios.

Simulation was revamped in past years to accommodate the embedding of power systems with telecommunication, giving rise to coupled simulations, or co-simulations for short. This technique is used to combine two or more simulation engines into one global simulation as stipulated by Gomes et al. (2018) [83]. The authors have surveyed the literature and discussed major principles behind this technique. Co-simulation is used in the SG [17, 31, 26, 28, 96] to synchronise a continuous time Electric Power Simulator (EPS) with a discrete time telecommunication network simulator. Co-simulation is a multifaceted mechanism unbounded by only these two engines. For instance, it may integrate multi-purpose simulation engines, according to the problem under consideration.

Mets et al. (2014) [54] explained the need for coupled simulation (co-simulation) in power grids whereas Vogt et al. (2018) [92] discussed available tools, discussing how the hybrid engines converge on the so called ‘synchronisation problem’. Specific to energy management, Azeroual et al. (2020) [106] investigated primarily wind turbines in microgrids discussing major tools for modelling multi-agent systems.

Energy assets are spread out over large geographical domains operating as Distributed Energy Resources (DER). These can be based on Renewable Energy Resources (RER) such as solar roof-top Photo-Voltaic (PV) or Wind Turbines Power Converter Systems (WTPCS), or storage mechanisms in batteries statically installed in buildings, or mobile ones present in Electric Vehicles (EV).

As massive numbers of DER are scattered over the infrastructure, telecommunication becomes a problem when relying on energy assets to regulate frequency as well as other so called ancillary services provision [70]. One disconcerting problem is when cyber incursions attempt to delay packets traversing the network, corrupt data, or prevent them from reaching their destinations as discussed in a wealth of work throughout the years [75, 73, 101, 95].

The contribution of this work is to point out relevant M&S tools for EPS, telecommunications, co-simulation engines, and modelling mechanisms for use in the SG. We highlight the most used ones over the years, discussing their major features and internal details, listing the auxiliary tools and libraries on their design.

The work is divided as follows. Section 2 describes modelling and simulation tools for use in the Smart Grid. In Section 3 we present a discussion on tools and models, highlighting advantages and shortcomings. Section 4 ends our work with future considerations and next developments.

2 Simulation tools

We describe next proprietary (Section 2.1) and open source or free co-simulation tools (remaining sections). Our focus is directed on modelling power and telecommunication systems. The chosen order to present results are by ascending publication year, i.e., since it was first proposed to the research community.

2.1 Proprietary

Private companies and enterprises implemented substantial power based simulation solutions over the years. A tool is considered proprietary if it used at least one proprietary solution in the mix with other open-source and free libraries or implementations. These close solutions have obfuscated their tool's internal schema and details.

- **Electric power simulators:** Examples are Siemens' Power System Simulator (PSS)¹ and PowerWorld². Another significant tool is the DiGISILENT PowerFactory³ for simulating power systems [52].
- **Telecommunication networks simulators:** A tool called OPNET Modeler⁴ was used to help users define and work with different topologies and technologies.
- **Hardware-in-the-loop (HIL) approaches:**
 - **1995:** A solution worth mentioning is the Real-Time Digital Simulator (RTDS) [2], a proprietary solution implementing a real-time simulation library for EPS and HIL modelling.
 - **2005:** OPAL-RT is a real-time EPS with HIL capabilities [8]⁵. It was coupled with the telecommunication network simulator provided by OPNET [58].
- **Co-simulation:**
 - **2006:** In terms of co-simulation, we highlight Electric Power and cOmmunication synCHronizing Simulator (EPOCHS) [12]. It uses ns-2, Power Systems Computer Aided Design (PSCAD) [6] and for transient simulation, EMTDC (electromagnetic) and the PSLF (electromechanical). EPOCHS offers a version with reduced features for free/testing.
 - **2012:** Global Event-driven CO-simulation framework (GECO) [38] uses General Electric's Positive Sequence Load Flow (PSLF), Optimal Power Flow (OPF), and ns-2 to tackle SG co-simulation. GECO is not free because it employs proprietary tools in its solution.
 - **2013:** The INtegrated co-Simulation of Power and ICT systems for Real-time Evaluation (INSPIRE) [41] uses other proprietary software such as OPNET Modeler and DiGISILENT PowerFactory. On the same direction, the Testbed for Analyzing Security of SCADA Control Systems (TASSCS) [32] uses OPNET and PowerWorld for cybersecurity in SCADA.
 - **2014:** Another tool is the Secure Operation of Sustainable Power Systems Simulation Platform (SOSPO-SP) [55]. It assesses security and stability of EPS employing proprietary tools and libraries such as PSS and RTDS for modelling SCADA and Phasor Management Units (PMU). Sun et al. (2014) [56] combined OpenDSS and OPNET for studying the reliability of control strategies in the SG composed by a high number of DER.

¹PSS@power system simulation and modeling software. Link: <https://new.siemens.com/global/en/products/energy/energy-automation-and-smart-grid/pss-software.html>.

²Link: PowerWorld » The visual approach to electric power systems <https://www.powerworld.com/>.

³Link: <https://www.digsilent.de/en/powerfactory.html>.

⁴OPNET. Link: <https://support.riverbed.com/content/support/software/opnet-model/modeler.html>.

⁵Power System Simulation Software. Link: <https://www.opal-rt.com/power-systems-overview/>.

- **2017:** The European ERIgrid project [74] implemented a tool that used the Functional Mock-up Interface (FMI)/Functional Mock-up Units (FMU) and devised a holistic approach combining PowerFactory, Mosaik, OpenModelica, MATLAB/Simulink, and ns-3 altogether. Saxena et al. (2017) [78] devised a cyber-security tool for framing risk assessments in the SG for better situational awareness. It combined PowerWorld, MATLAB, GridSim, Matlabcontrol, JADE, and ns-3 into its framework.

- **Virtual testbeds:**

- **2009:** The Virtual Power System Testbed (VPST) [16] focused on network security analysis in SCADA. The main idea behind VPST is to provide modellers with a virtual framework for experimenting with equipment reactions in extreme (e.g. under attack) situations in large-scale power and telecommunication networks. For power it used PowerWorld whereas for telecommunications it employed Rinse [10], a real-time virtual network to model the cyber part of the electrical grid.
- **2011:** VPNET [29] uses the Virtual Test Bed (VTB) with OPNET, and presented a case study using a converter model and communication issues, whereas the Multi-Agent and Communication Simulator (MAC-sim) [45] used Java Agent DEvelopment (JADE) platform [4] and OPNET Modeler.

Obvious advantages of proprietary software are usually the contractual support and constant maintenance, frequent updates and patches for defects correction, as well as fast and timely execution. The tools are usually shipped to customers with a plethora of examples and modelling possibilities, and well as a comprehensive documentation. The tools are carefully validated, so they offer higher accreditation, however, since it is a closed solution, model interoperability over other software suites is limited. As another disadvantage, we mention that sometimes costs are prohibitive, as the licensing model often entails buying a Commercial-Off-The-Shelf (COTS) solution, even though the customers will only use a fraction of the software.

Next we describe open-source and free solutions available for modellers, dividing the analysis into EPS, telecommunication, general purpose, co-simulators, TES, MATLAB, and visual editors, as follows.

2.2 Electric Power Simulators

- **2007:** The Internet-technology Based Power System Simulator (InterPSS) [13, 46, 79] is written in Java used for on-line real-time EPS. It supports cascading failure analysis, forecasting and CIM⁶ model processing.

- **2008:** GridLAB-D [14, 50] is an agent based EPS for energy distribution networks implemented at the Pacific Northwest National Laboratory (PNNL) in the US. It is written in C++, except for some scripting and MATLAB interfaces, which contributes to its performance capabilities. It is a scalable solution and well documented as modellers have access to several examples and IEEE Test Feeders to use as basis for more complex analysis.

- **2010:** MATPOWER⁷ has wide acceptance among industry, enterprises, and academia [23]. It offers MATLAB scripts for steady-state analysis of Power Flow (PF), Continuation Power Flow (CPF), extensible Optimal Power Flow (OPF), Unit Commitment (UC), and stochastic, secure multi-interval OPF/UC.

- PYPOWER⁸ is a Python solution derived from MATPOWER whereas oct2pypower⁹ serves as a Python bridge to MATPOWER.

- **2012:** The Open Distribution System Simulator (OpenDSS)¹⁰ is also a relevant EPS tool [39]. It supports modelling DER for grid modernisation and integration.

- **2016:** Krishnamurthy (2016) [63] developed the Power System Simulation Toolbox (psst)¹¹ to use in conjunction with AMES (see Section 2.6). It offered a Graphical User Interface (GUI) for modelling and it was implemented in Python.

- **2018:** pandapower¹² is also written in Python, promising higher level of modelling automation [89]. It is shipped with a comprehensive set of examples and a detailed documentation so modellers may create and adapt models to their concerns.

⁶The Common Information Model (CIM) consists of European and international standards.

⁷MATPOWER - Free, open-source tools for elec. power syst. simul. and optimization. Link: <https://matpower.org/>.

⁸PYPOWER - PyPI. Link: <https://pypi.org/project/PYPOWER/>.

⁹Link: <https://github.com/rwl/oct2pypower>.

¹⁰OpenD. Link: <https://www.epri.com/pages/sa/opendss>. According to the website, the tool has been used since 1997.

¹¹Link: <https://github.com/ames-market/psst>.

¹²pandapower. Link: <http://www.pandapower.org/>.

The Scalable Electric Power System Simulator (SEPSS) [86] employed MATLAB in a modular fashion to ease analysis. It was designed for multi-layered modeling of complex system where it allowed analysts to design multi-temporal cyber signals such as disturbances, market signals, and control set points.

2.3 Telecommunication networks simulators

- **2010:** The Network Simulator ns-3 [20] has high acceptance in both industry and academia. The latest version has multiple telecommunication modelling capabilities for diverse sets of protocols and packet transmission technologies (wired, wireless, or other medium). Despite being introduced in 2010, with its constant updates and improvements it is still a major player.

- Another tool worth mentioning is the Objective Modular Network Testbed in C++ (OMNET++) that together with the INET Framework [22] adds consistent telecommunication modelling when modelling complex networks¹³.

- The Network Security Simulator (Nessi) [21] is a network simulator built for security concerns. It offers plug-ins for profile-based automated attack generation, traffic analysis and support for detection algorithms. The main difference between other network simulators is to offer a detection Application Programming Interface (API) for integrating and evaluating Intrusion Detection Systems (IDS).

2.4 General purpose co-simulators

General Purpose (GP) co-simulators are implementations that could virtually model any real-world problem considering the restrictions imposed by the modelling abstractions.

- **2016:** The Integrated Tool Chain for Model-based Design of CPS (INTO-CPS) [64] was integrated into the co-simulator offered by Maestro [103] using Modelio Multi-Model, OpenModelica, SysmML, and 20-sim. It employs the FMI/FMU standard [24] as the middleware for communicating across the toolchain.

- **2018:** Multi-agent Environment for Complex SYstems CO-simulation (MECSYCO) [80], written in Java (a C++ version is mentioned to be under development), is a GP simulator for hybrid systems modelling. The tool uses the formal Discrete eVent system Specification (DEVS) for communicating among simulators [1, 3].

2.5 Power/telecommunications co-simulation engines

- **2011:** Mosaik¹⁴ is a co-simulation framework that promises to incorporate flexibility for the creation of large-scale scenarios for EPS [34]. It has bindings to PYPower and a demonstration scenario for modellers to learn how to use the tool.

- The SCADA_{sim} [33] framework is built on top of OMNeT++ and using MATLAB/Simulink models adapted from SimPowerSystems¹⁵.

- The co-simulation proposed by Liberatore et al. (2011) [30, 37] used Modelica for the electric grid and ns-2 for modelling the telecommunications.

- Grunewald et al. (2011) improved Nessi (Section 2.3) and developed Nessi2 [27], adding improvements over previous versions. The latter was extended to work with InterPSS [25], where the authors applied it in cybersecurity.

- **2012:** The Smart-Grid Common Open Research Emulator (SCORE) [40] offered an emulation environment for EPS, with the possibility of integrating power and telecommunication systems. It provided mechanisms for energy model programming interfaces such as shiftable and non-shiftable loads, and renewable energy resources (PV and WTPCS).

- **2014:** The Framework for Network Co-Simulation (FNCS) [51, 72] combines GridLAB-D with ns-3 for co-simulating power distribution and telecommunication. It synchronises simulation engines acting as a firmware to coordinate time passage and interaction.

- GridSpice [48] is a cloud-based solution for power transmission and generation that allowed analysts to scale designs as the platform executed in a pay-as-you-go model. It used GridLAB-D with MATPOWER in a graphical interface equipped with a geographical editor, project explorer, and wizard for importing objects from other tools. The MATPOWER dealt with the transmission and economic dispatch problem whereas GridLAB-D was used for power distribution in a master/worker schema (a supervisor catering several simultaneous tasks).

¹³Link for OMNeT++: <https://omnetpp.org>, and for INET: <https://inet.omnetpp.org/>.

¹⁴mosaik - A flexible Smart Grid co-simulation platform. Link: <https://mosaik.offis.de/>.

¹⁵The tool is available at <https://github.com/caxqueiroz/scadasim>, however, it has not being updated since 2011.

- Awad et al. (2014) [49] proposed SGsim, a co-simulation framework using OMNeT++ and OpenDSS.
- **2015:** Bytschkow et al. (2015) combined GridLAB-D, CIM, and AKKA (Java-based co-simulation engine) to model a SCADA system [59].
- Hansen et al. (2015) developed Bus.py [60], a GridLAB-D communication interface for EPS. It was used to simulated the communication between a set of customers in a distribution network and an aggregator. Bus.py also enabled the co-simulation of Energy Management Systems (EMS) and the simulation of Integrated Transmission and Distribution (ITD) systems.
- **2016:** Zambrano proposed GridTeractions [68], a framework for teaching and testing grid designs using a hardware-software architecture with miniprocessor terminals (Raspberry PI 2). The solution used OpenDSS through a graphical auxiliary front-end called OpenDSS-G¹⁶ in a co-simulation with LabVIEW [39].
- Hannon et al. (2016) [62] developed the Distribution System Solver Network (DSSnet) using Mininet’s SDN emulation for telecommunications and OpenDSS for EPS. The authors presented the details behind the architecture and a case study on load shifting.
- **2017:** FNCS is currently being replaced by a multi-federated approach called the Hierarchical Engine for Large-scale Infrastructure Co-Simulation (HELICS) [76] by the same research group.
- Python for Power System Analysis (PyPSA) [69, 84] is used for power flow and electric power system steady-state analysis. The authors compared their solution with existing (and similar) approaches in terms of grid and economical analysis as well as comparing PyPSA with MATPOWER for several examples.
- **2018:** The Cyber physical co-simulation platform for Distributed Energy Resources in smart grids (CyDER) [81, 98, 93] is a modular co-simulation framework for addressing DER in the SG. It is under development by a consortium of academic and industrial partners lead by the Lawrence Berkeley National Laboratory (US). CyDER is based on the FMI standard and GridDyn with some Python integration (PyFMI) for PV and EV modelling, building simulators and PMU. The technical report does not mention how the telecommunication among DER operates, however, the platform is still under development. We mention the effort to integrate buildings with co-simulation through FMU as described by Nouidui et al. (2018) [88].
- Hantao and Fangxing (2018) [82, 107] implemented Andes¹⁷, a Python-based co-simulation that worked with MAPOWER and PSAT combined with Mininet¹⁸, a Software Defined Networks (SDN) communication networks simulator. It employed PyPMU for M&S of networks of PMU/PDC in large scale settings. Andes opened different input models such as PSS/E raw format, MATPOWER, and Dome.
- Krishnamoorthy and Dubey [87] presented a co-simulation framework combining MATPOWER with OpenDSS for modelling the impact of DER over ITD systems. The authors validated the approach against DIGiSILENT PowerFactory [90].
- **2019:** The Zero OBvious Node Link co-simulator (ZerOBNL) [100]¹⁹ was implemented in Python and used pandapower in a so called partitioned approach, breaking down elements into more manageable parts in larger co-simulations. They employed ZeroMQ [43] for communicating among elements, a fast socket library for distributed applications and Docker for faster virtualised executions. This framework is part of a larger research project called IntegrCiTy²⁰, offering a large set of examples and auxiliary tools for EPS.
- Pallonetto et al. (2019) [99] took a different direction and developed a framework called SimApi for benchmarking building control algorithms. It employs the Building Controls Virtual Test Bed (BCVTB), a software environment that integrates different simulation engines into a global co-simulation²¹. It is cloud-based (i.e. it runs online) and allows for co-simulation of EMS and Building Energy Systems (BES). There is no comment on the software used for EPS used for executing the platform (it is encapsulated within the system).
- Steinbrink et al. (2019) [102] used Mosaik to devise a testing platform for experimenting in Cyber-Physical Energy Systems (CPES). It allowed modellers to conduct planning, quantify uncertainty and assist domain experts in collaboration efforts.

¹⁶A graphical view of OpenDSS. Link: <https://sourceforge.net/projects/dssimpc/>.

¹⁷Link: <https://github.com/cuihantao/andes>.

¹⁸Mininet: An Instant Virtual Network on your Laptop (or other PC). Link: <http://mininet.org/>.

¹⁹Link: <https://github.com/IntegrCiTy/zerobnl>.

²⁰Link: <https://github.com/IntegrCiTy>.

²¹Here is a list of software that are linked to BCVTB: EnergyPlus, Modelica and Dymola (simulation environment), FMU/FMI 1.0 and 2.0, MATLAB/Simulink, Radiance ray-tracing software for lighting analysis, ESP-r for building energy modeling, TRNSYS (system simulation program), and the BACnet stack. Link: <https://simulationresearch.lbl.gov/bcvtb>.

- Kennouche et al. (2019) developed the Asynchronous Smart Grid Simulation (ASGridS)²² [94], a framework that combines pandapower with GNU/Linux based emulators and tools to model asynchronous communication between elements. It can be deployed with different telecommunication models, i.e., emulated, simulated, or real, where modellers could for example model network impairments with GNU/Linux-based traffic and shaping tool (tc) [7] and the netem module [9] (for network emulation).

- **2020:** The SCEPTRE toolchain [109] is a virtualised (on-line) option for modelling DER and investigate communication latencies across technologies.

- The Open Platform for Energy Networks (OPEN) [111] uses pandapower internally and presents two examples for modellers, one consisting of an EV set up, and another mimicking an Energy Management System.

- The SmartGrid Cosimulation Platform [112] uses ns-3 combined with OpenDSS and Mosaik. It is shipped with two case studies, one for voltage regulation and another for setting up the power grid with telecommunications.

2.6 Transactive Energy Systems

Modelling the market within Transactive Energy Systems (TES) is a crucial element in the SG [53] as it offers customers the ability to trade power in the grid as prosumers (both consumers and producers) [36, 85]. Many authors have considered modelling of TES and its operational details throughout the years, under economical, engineering, and computing scopes.

- **2009:** Researchers addressed modelling power systems shortcomings by implementing an open-source software solution known as Agent-based Modeling of Electricity Systems (AMES) Wholesale Power Market Test Bed [18]. It consists of a framework for non-power specialists unfamiliar with the intricacies of EPS, bringing together economy related aspects into the modelling. AMES allows working with strategic trading behaviour for addressing engineering and economical problems in the grid.

- **2016:** Palmintier et al. (2016) [65] proposed the Integrated Grid Modeling System (IGMS). It focused on the automated generation of large-scale scenarios in wholesale market simulations in Transmission-Distribution interactions. IGMS used the Flexible Energy Scheduling Tool for Integration of Variable Generation (FESTIV) [35] for representing bulk markets, MATPOWER, and GridLAB-D. The case studies attest the scalability of the system by allowing hundreds of transmission nodes and over a million distribution nodes, where the authors showed examples of varying size IEEE Test Feeders.

- **2018:** The Transactive Energy Simulation Platform (TESP)²³ [85] aggregated GridLAB-D, ns-3 (using FNCS and HELICS) and it also provided means to work with buildings modelled in EnergyPlus (E+) [5]. E+ is a comprehensive building simulator addressing thermodynamics with wide acceptance and accreditation across stakeholders. In TESP, all those auxiliary tools work as libraries that are executed and linked together for executing the platform. It has an extensive list of examples and IEEE Test Feeders to extend, enjoying all the features already available in GridLAB-D as mentioned earlier.

- **2019:** The ITD-TES Platform [97]. addresses modelling the wholesale energy market in the transmission level having one or more distribution systems attached to it as DER (or grid edge resources). It is useful to evaluate designs of transactive energy in ITD systems and it employs FNCS as the co-simulator engine.

- The ETX [104] framework works with energy trading and management implementing communication with sockets.io. It uses trained neural networks for power-flow calculations, aiming at coordinated and repeatable investigations of market, operations, and regulations actions (unfortunately, the paper does not explain the internals of the software used in ETX's operation).

2.7 MATLAB

MATLAB (MATrix LABoratory) was developed by MathWorks, and Simulink is its visual interface. As mentioned in Section 2.2, MATPOWER is an EPS with large adoption in the research community. Next, we will mention other relevant MATLAB-based supporting tools for both simulation and co-simulation.

- **2008:** Power System Analysis Toolbox (PSAT)²⁴ is a MATLAB toolbox for power system analysis and simulation [15].

²²Link: <https://github.com/taqen/asgrids/tree/appeec19>.

²³For more information on the framework and documentation, visit <https://github.com/pnnl/tesp/>.

²⁴Power System Analysis Toolbox. Link: <http://faraday1.ucd.ie/psat.html>.

- **2010:** MatDyn²⁵ is a MATPOWER inspired dynamic analysis free MATLAB script for EPS [19].
- **2013:** Milano presented Dome [44], based on PSAT (which employed MATLAB), and discussed the suitability of using Python in complex power analysis and studied its performance in a IEEE 14-bus Test Feeder.
- **2014:** GridMat [47] offers a visual interface within MATLAB to model GridLAB-D elements for power and control algorithms using Simulink.
- **2015:** Amarasekara et al. (2015) used MATLAB/Simulink (module SimPowerSystems) and ns-3 [57] in a co-simulation. The authors developed a custom mediator (an agent) to coordinate events between Simulink and ns-3 exchange model. They presented a case study consisting of a small scale microgrid where they studied energy scheduling and the effects of packet losses in communication.
- **2016:** MATLAB/Simulink and ns-3 was also chosen by Pan et al. (2016) [66], where the authors presented an example of a load reconfiguration. The authors compared results against the GECON framework, discussing how their solution stands out and the reasoning behind modelling choices.
- **2017:** The integrative Power and Cyber Systems (iPaCS) [77] testbed used MATTRANS for power system modelling, a MATLAB/Simulink transient stability program combined with ns-3 (based on MATPOWER)²⁶. It studied the latency between Phasor Management Units (PMU) attached to Phasor Data Concentrators (PDC) and generated datasets for deeper analysis. The authors commented the testbed's suitability for investigating i) latency and bandwidth; ii) congestion between PMU and PDC systems, and; iii) impact of cyber attacks on EPS.
- **2018:** Vélez-Rivera et al. (2018) [91] proposed Gorilla, an open interface for co-simulation that is agnostic of EPS or telecommunications network simulation tool. The authors offered a set of simple operations to use such as read/write, call, and subscribe/call-back, for diverting simulation control. They created two examples, one for voltage regulation, and another for controlling a home microgrid, calling MATLAB/Simulink commands, however, there was no mention on modelling telecommunications.

2.8 Related tools

There is a number of auxiliary tools to complement other toolsets/toolkits, as explained next.

- **Visual editors for modelling power systems:** The Open Modelling Framework (OMF)²⁷ provides a graphical interface to define huge and complex networks (not bounded by power systems). The tool is on-line and require registering, helping modellers devise trade-off analysis (for instance, amounts of PV and WT to meet some power demand), or scaled up GridLAB-D models, to mention a few.

- Webgme-gridlabd²⁸ offers a visual front-end for creating GridLAB-D models. The tool employs Node.js and it works on an Internet browser. It is possible to download the tool and install into a local server.

- **Other tools worth mentioning:** DSATools²⁹ is a proprietary tool for a wide range of electric-related assessments. PYPOWER (no longer maintained) is a power simulator written in Python and used in other tools³⁰.

We also mention the cyber-DEFense Technology Experimental Research (Deter) [11], an on-line platform for conducting cybersecurity experiments³¹.

2.9 Co-simulation frameworks for domain specific applications

Researchers have created bespoke co-simulation frameworks to address domain specific applications such as cybersecurity. The sheer size of CPS realities mandates its consideration and attack impact analysis in both power and telecommunication networks.

- **2016:** The Attack Simulation Toolset for SG Infrastructures (ASTORIA) [67] is a framework to model SCADA sub-systems, most notably Master Terminal Units (MTU) and Remote Terminal Units (RTU). It was developed in Mosaik using PYPOWER and ns-3 focusing on cybersecurity. ASTORIA used 'Attack Profiles' to model adversaries

²⁵MatDyn - Electa. Link: <https://www.esat.kuleuven.be/electa/teaching/matdyn/>.

²⁶MATTRANS - A MATLAB/Simulink Power System Transient Stability Simulation Package. Link: <https://github.com/gelliravi/MatTrans>.

²⁷Link: https://omf.coop/login_page?next=%2F.

²⁸Link: <https://github.com/finger563/webgme-gridlabd>.

²⁹Link: <https://www.dsatools.com/>.

³⁰Link: <https://pypi.org/project/PYPOWER/>.

³¹Link: <https://deter-project.org/>.

and presented two case studies, one emulating a malicious software infection attack, and another for a Denial-of-Service (DoS).

• **2020:** Cybersecurity concerns in the SG was also addressed in GridAttackSim [110], which used FNCS to model cyber-attacks. It offered a visual tool for modelling systems using Python graphical bindings. As malicious incursions, the authors modelled a channel jamming and a False Data Injection attack (FDI) involving dynamic pricing (energy market). The tool extended examples provided by FNCS and GridLAB-D where the novelty was to present a GUI for modellers.

3 Discussion

Since the inception of the SG, researchers addressed M&S as a means to reason about operational decisions and test new designs or better configurations. That is one the reasons as to why the literature on power, telecommunications, and couple tools have witnessed a steep increase over past years.

Figure 1 details the tools discussed here in chronological order. We stress that there are more tools for co-simulating CPS, as this offers a non-comprehensive list. The set of tools highlighted in bold face are tools that have sustained




Figure 1: Non-comprehensive list of open-source/free tools and frameworks for co-simulating CPS.

a high maturity degree over the years, with wide adoption in industry and academia. The figure points out the sheer number of implementations modellers could choose from to tackle CPS research.

Table 1 shows the frameworks and tools detailed here and their auxiliary tools. One notices the recurrent use of MATLAB/Simulink, GridLAB-D, and ns-3 across several solutions.

We now focus our attention on the set of tools that are mature and stable, employed by researchers throughout the years for a wealth of models and propositions. Amidst the plethora of frameworks and tools listed here some are highlighted over the years such as GridLAB-D, OpenDSS, pandapower, Mosaik, FNCS/HELICS, SCEPTRE, GridSpice, ZerOBNL, IGMS, TESP, MATPOWER, PyPSA, PYPower, BCVTB, EnergyPlus, OMNeT++/INET, and ns-3. Because there are many features to consider in CPS infrastructures (market, transmission, distribution, transmission-distribution, telecommunications with multiple protocols/technologies, PMU/PDC, SCADA), it is difficult to compare solutions.

We now focus our attention on the set of tools that are mature and stable, employed by researchers throughout the years for a wealth of models and propositions. Table 2 shows a list of stable tools (EPS, co-simulation, and TES) for modelling the SG. The table shows the size of each tool, in Mega Bytes (MB), where the method used was to download the latest .zip file directly from the download site or GitHub link.

The tools presented in the table use BSD or Apache2 licensing. The sizes are quite reasonable apart from TESP (186 MB), requiring around 25 MB (pandapower, OpenDSS) or 75 MB (GridLAB-D, OPEN). Co-simulation requires large system modelling and timely execution. That is the main reason as to why high-performance languages are preferred such as C/C++ in GNU/Linux. We point out that Python could also be used as a scripting language to fire executions and parse output, generating graphs for analysis. Python has many advantages such as an extensive API and easy interface mechanisms to connect among solutions. However, even with substantial code modification, depending on the model, Python falls short on performance.

Table 1: Frameworks and auxiliary tools.

		20-sim, SysML	BCVTB (EnergyPlus)	EnergyPlus	FESTIV	Tk (GUI)	FNCS/HELICS	tc, netem	GridDyn	GridLAB-D	interface (tool agnostic)	LabVIEW	MATLAB/Simulink	MATPOWER	MATTRANS	Mininet	Modelica	Modelio Multi-Model	Mosaik	ns-2	ns-3	oct2py/power	OMNeT++	OpenDSS	OpenDSS-G	OpenModelica	pandapower
EPS	Andes													✓		✓											
	MATPOWER												✓														
	PYPOWER*												✓									✓					
Co-simulation frameworks	ASGridS							✓																			✓
	Bus.py									✓																	
	Bytschkow[59]									✓																	
	CyDER								✓																		
	DSSnet															✓								✓			
	FNCS/HELICS									✓											✓						
	Gorilla									✓			✓														
	GridSpice									✓			✓	✓													
	GridTeractions											✓												✓			
	IGMS				✓					✓				✓													
	Krishnamoorthy[87]													✓									✓				
	Liberatore[30]																✓			✓							
	OPEN																									✓	
	SCADAsim												✓										✓				
	SGsim																					✓					
	SG Cosim																		✓		✓		✓				
	SimApi		✓																				✓				
	ZerOBNL																										✓
MATLAB	Amarasekara[57]												✓								✓						
	Dome												✓														
	GridMat												✓														
	iPaCS														✓						✓						
	MatDyn												✓														
	Pan[66]												✓								✓						
TES	AMES									✓																	
	Hansen[71]						✓			✓											✓						
	ITD-TES						✓			✓											✓						
	TESP			✓			✓			✓											✓						
G	Maestro/INTO-CPS	✓																	✓							✓	
D	ASTORIA																		✓		✓						
	GridAttackSim					✓	✓																				

Legend: G: General Purpose; D: Domain Specific. *PYPOWER is based on MATPOWER.

A testbed mimics an infrastructure so researchers may conduct experiments without worrying about causing damages to the real systems in production. Besides Deter, mentioned earlier, there is a considerable amount of work towards SCADA in terms of testbeds [42, 32].

As general comments, power simulators are sensitive when changing energy parameters as the steady-state computation may start yielding skewed results. That certainly hinders analysis as incremental changes in models may not reflect reality, specially when the modeller is unfamiliar with the electrical engineering domain.

On a TES note, there is an increased interest in looking at ITD systems as they may impact dynamic pricing or related mechanisms in place. GridSpice offered a solution that “*blurred the boundaries between generation, transmission, distribution, and markets*” as stated by the authors. This is a nice concept, as more abstractions across layers are needed for effective modelling of other SG behaviours.

Considered individually, the simulation engines are quite strong, however, problems start when they are integrated altogether. For instance, GridLAB-D, pandapower, EnergyPlus, ns-3, MATPOWER, or OpenDSS are stable and mature tools. When modellers and developers offer integration features, then we have observed that the novel solution does not share the same amount of stability and endurance. There is also a lack of cross-platform validation to ensure that the simulations are yielding out appropriate results for deeper inspections.

4 Conclusion

As general remarks, there is research to conduct on increasing frameworks and models reproducibility. To reach this objective one must create and share model repositories, datasets, logging data, or measurements. Modellers choose

Table 2: Selected tools for modelling the Smart Grid.

Type	Tool / Framework	Size MB	License	Major Language	Platform	Version 11/2020	Toolchain/auxiliary tools Supporting frameworks
EPS	GridLAB-D	74	BSD	C/C++	Linux	4.1.0	Python, MATLAB
	pandapower	27	BSD	Python	Mult.	2.4.0	PYPOWER, pandas
	OpenDSS	27	BSD	Pascal	Mult.	9.0.0	OpenDSS-G (GUI)
Co-Sim	FNCS	0.7	BSD	C/C++	Linux	2.3.2	GridLAB-D, ns-3
	OPEN	75	Apache2	Python	Mult.	–	pandapower, several dep.
	ZerOBNL	1.1	Apache2	Python	Mult.	1.1	zeroMQ, Docker
TES	TESP	186	BSD	C++	Linux	0.6.3	GridLAB-D, FNCS/HELICS, ns-3, EnergyPlus, PYPOWER

the framework they are most familiar with, however, in terms of models, there is a lack of published artefacts so other researchers may extend, adapt, or augment existing functionalities.

Lack of cross-platform validation for frameworks is another disconcerting problem in this field. There is a lot of models and frameworks but seldom validation efforts are presented for consistent scrutiny. Sometimes the tool is available for download, however, the models and datasets are missing, or even in some cases configuration details (or options) are omitted, preventing properly execution.

Future research efforts will study models from different application domains to investigate primitives and parameters for tackling most impactful SG's challenges. One direction is consider the use of Markovian approaches to model the SG and DER such as Arnaboldi et al. (2020) [105] who modelled Load Changing Attacks over different mixes of power generation units. Another is to propose domain specific testbeds for addressing design shortcomings of SG as well as training stakeholders. The idea is to offer capabilities to detect and respond to abnormal situations in the SG as discussed by Henze et al. (2020) with a case study in cybersecurity [108].

Acronyms

BES	Building Energy Systems
CIM	Common Information Model
COTS	Commercial-Off-The-Shelf
CPES	Cyber-Physical Energy Systems
CPF	Continuation Power Flow
CPS	Cyber-Physical System
DEVS	Discrete eVent system Specification
DER	Distributed Energy Resources
DoS	Denial-of-Service
EMS	Energy Management Systems
EPS	Electric Power Simulator
EV	Electric Vehicles
FDI	False Data Injection
FMI	Functional Mock-up Interface
FMU	Functional Mock-up Units
HIL	Hardware-in-the-Loop
ICS	Industrial Control Systems
ICT	Information and Communication Technologies
ITD	Integrated Transmission and Distribution
JADE	Java Agent DEvelopment
MATLAB	MATrix LABoratory
MTU	Master Terminal Units
M&S	Modelling and Simulation
OMF	Open Modelling Framework
OPF	Optimal Power Flow
PDC	Phasor Data Concentrators

PF	Power Flow
PMU	Phasor Management Units
PNNL	Pacific Northwest National Laboratory
PSLF	Positive Sequence Load Flow
PV	Photo-Voltaic
RER	Renewable Energy Resources
RTU	Remote Terminal Units
SCADA	Supervisory Control and Data Acquisition
SDN	Software Defined Networks
SG	Smart Grid
UC	Unit Commitment
WTPCS	Wind Turbines Power Converter Systems

Acronyms for tools

AMES	Agent-based Modeling of Electricity Systems
ASGridS	Asynchronous Smart Grid Simulation
ASTORIA	Attack Simulation Toolset for Smart Grid Infrastructures
BCVTB	Building Controls Virtual Test Bed
CyDER	Cyber physical co-simulation platform for Distributed Energy Resources
Deter	cyber-DEfense Technology Experimental Research
DSSnet	Distribution System Solver Network
EPOCHS	Electric Power and cOmmunication synCHronizing Simulator
FESTIV	Flexible Energy Scheduling Tool for Integration of Variable Generation
FNCS	Framework for Network Co-Simulation
GECO	Global Event-driven CO-simulation framework
HELICS	Hierarchical Engine for Large-scale Infrastructure Co-Simulation
IGMS	Integrated Grid Modeling System
INSPIRE	INtegrated co-Simulation of Power and ICT systems for Real-time Evaluation
InterPSS	Internet-technology Based Power System Simulator
INTO-CPS	Integrated Tool Chain for Model-based Design of CPS
iPaCS	integrative Power and Cyber Systems
JADE	Java Agent DEvelopment
MATTRANS	MATLAB/Simulink Power System Transient Stability Simulation
MECSYCO	Multi-agent Environment for Complex SYstems CO-simulation
Nessi	Network Security Simulator
ns-3	Network Simulator version 3
OMF	Open Modelling Framework
OMNeT++	Objective Modular Network Testbed in C++
OpenDSS	Open Distribution System Simulator
OPEN	Open Platform for Energy Networks
PSAT	Power System Analysis Toolbox
PSCAD	Power Systems Computer Aided Design
PSS	Power System Simulator
psst	Power System Simulation Toolbox
PyPSA	Python for Power System Analysis
RTDS	Real-Time Digital Simulator
SCORE	Smart-Grid Common Open Research Emulator
SEPPS	Scalable Electric Power System Simulator
SG-Cosim	SmartGrid Cosimulation
SOSPO-SP	Secure Operation of Sustainable Power Systems Simulation Platform
TASSCS	Testbed for Analyzing Security of SCADA Control Systems
TES	Transactive Energy Systems
TESP	Transactive Energy Simulation Platform
VPST	Virtual Power System Testbed
ZerOBNL	Zero OBvious Node Link co-simulator

References

- [1] Bernard P Zeigler. “DEVS representation of dynamical systems: Event-based intelligent control”. In: *Proc. of the IEEE* 77.1 (1989), pp. 72–80.
- [2] R Kuffel, J Giesbrecht, T Maguire, RP Wierckx, and P McLaren. “RTDS-a fully digital power system simulator operating in real time”. In: *Proc. of the Int. Conf. on Energy Management and Power Delivery EMPD’95*. Vol. 2. IEEE. 1995, pp. 498–503.
- [3] Kim Tag Gon, Bernard P Zeigler, and Herbert Praehofer. “Theory of modeling and simulation: integrating discrete event and continuous complex dynamic systems”. In: (2000).
- [4] Fabio Bellifemine, Agostino Poggi, and Giovanni Rimassa. “JADE: a FIPA2000 compliant agent development environment”. In: *Proc. of the 5th Int. Conf. on Autonomous agents*. 2001, pp. 216–217.
- [5] Drury B Crawley, Linda K Lawrie, Frederick C Winkelman, Walter F Buhl, Y Joe Huang, Curtis O Pedersen, Richard K Strand, Richard J Liesen, Daniel E Fisher, Michael J Witte, et al. “EnergyPlus: creating a new-generation building energy simulation program”. In: *Energy and buildings* 33.4 (2001), pp. 319–331.
- [6] Olimpo Anaya-Lara and E Acha. “Modeling and analysis of custom power systems by PSCAD/EMTDC”. In: *IEEE Trans. Power Deliv.* 17.1 (2002), pp. 266–272.
- [7] Bert Hubert, Thomas Graf, Greg Maxwell, Remco van Mook, Martijn van Oosterhout, P Schroeder, Jasper Spaans, and Pedro Larroy. “Linux advanced routing & traffic control”. In: *Ottawa Linux Symp.* Vol. 213. 2002.
- [8] Christian Dufour, Simon Abourida, and Jean Belanger. “Hardware-in-the-loop simulation of power drives with RT-LAB”. In: *Int. Conf. on Power Electronics and Drives Systems*. Vol. 2. IEEE. 2005, pp. 1646–1651.
- [9] Stephen Hemminger. “Network emulation with NetEm”. In: *Linux and Open Source Conference (linux.conf.au)*. 2005, pp. 18–23.
- [10] Michael Liljenstam, Jason Liu, David Nicol, Yougu Yuan, Guanhua Yan, and Chris Grier. “Rinse: The real-time immersive network simulation environment for network security exercises”. In: *Workshop on Principles of Advanced and Distributed Simulation (PADS’05)*. IEEE. 2005, pp. 119–128.
- [11] Terry Benzel, Robert Braden, Dongho Kim, Clifford Neuman, Anthony Joseph, Keith Sklower, Ron Ostrenga, and Stephen Schwab. “Experience with deter: a testbed for security research”. In: *2nd Int. Conf. on Testbeds and Research Infrast. for the Devel. of Networks and Communities, TRIDENTCOM’06*. IEEE. 2006, 10–pp.
- [12] Kenneth Hopkinson, Xiaoru Wang, Renan Giovanini, James Thorp, Kenneth Birman, and Denis Coury. “EPOCHS: a platform for agent-based electric power and communication simulation built from commercial off-the-shelf components”. In: *IEEE Trans. Power Syst.* 21.2 (2006), pp. 548–558.
- [13] Michael Zhou and Shizhao Zhou. “Internet, open-source and power system simulation”. In: *Power Engineering Society Gen. Meet.* IEEE. 2007, pp. 1–5.
- [14] David P Chassin, Kevin Schneider, and Clint Gerkenmeyer. “GridLAB-D: An open-source power systems modeling and simulation environment”. In: *PES Transm. and Distr. Conf. and Exposition*. IEEE. 2008, pp. 1–5.
- [15] Federico Milano, Luigi Vanfretti, and Juan Carlos Morataya. “An open source power system virtual laboratory: The PSAT case and experience”. In: *IEEE Trans. Educ.* 51.1 (2008), pp. 17–23.
- [16] David C Bergman, Dong (Kevin) Jin, David M Nicol, and Tim Yardley. “The Virtual Power System Testbed and Inter-Testbed Integration”. In: *CSET*. 2009.
- [17] Hassan Farhangi. “The path of the smart grid”. In: *IEEE Power and Energy Magazine* 8.1 (2009), pp. 18–28.
- [18] Hongyan Li and Leigh Tesfatsion. “Development of open source software for power market research: The AMES test bed”. In: *Journal of Energy Markets* 2.2 (2009), p. 111.
- [19] Stijn Cole and Ronnie Belmans. “Matdyn, a new matlab-based toolbox for power system dynamic simulation”. In: *IEEE Trans. Power Syst.* 26.3 (2010), pp. 1129–1136.
- [20] George F Riley and Thomas R Henderson. “The ns-3 network simulator”. In: *Modeling and tools for network simulation*. Springer, 2010, pp. 15–34.
- [21] Stephan Schmidt, Rainer Bye, Joël Chinnow, Karsten Bsufka, Ahmet Camtepe, and Sahin Albayrak. “Application-level simulation for network security”. In: *Simulation* 86.5-6 (2010), pp. 311–330.
- [22] Andras Varga. “OMNeT++”. In: *Modeling and tools for network simulation*. Springer, 2010, pp. 35–59.
- [23] Ray Daniel Zimmerman, Carlos Edmundo Murillo-Sánchez, and Robert John Thomas. “MATPOWER: Steady-state operations, planning, and analysis tools for power systems research and education”. In: *IEEE Trans. Power Syst.* 26.1 (2010), pp. 12–19.
- [24] Torsten Blochwitz, Martin Otter, Martin Arnold, Constanze Bausch, Christoph Clauss, Hilding Elmqvist, Andreas Junghanns, Jakob Mauss, Manuel Monteiro, Thomas Neidhold, et al. “The functional mockup interface for tool independent exchange of simulation models”. In: *Proc. of the 8th Int. Modelica Conf.* Linköping University Press. 2011, pp. 105–114.

- [25] Joel Chinnow, Karsten Bsufka, Aubrey-Derrick Schmidt, Rainer Bye, Ahmet Camtepe, and Sahin Albayrak. "A simulation framework for smart meter security evaluation". In: *Int. Conf. on Smart Measurements of Future Grids (SMFG) Proceedings*. IEEE. 2011, pp. 1–9.
- [26] Xi Fang, Satyajayant Misra, Guoliang Xue, and Dejun Yang. "Smart grid—The new and improved power grid: A survey". In: *IEEE Commun. Surv. Tutor.* 14.4 (2011), pp. 944–980.
- [27] Dennis Grunewald, Marco Lützenberger, Joël Chinnow, Rainer Bye, Karsten Bsufka, and Sahin Albayrak. "Agent-based network security simulation". In: *The 10th Int. Conf. on Autonomous Agents and Multiagent Systems-Volume 3*. Citeseer. 2011, pp. 1325–1326.
- [28] Vehbi C Gungor, Dilan Sahin, Taskin Kocak, Salih Ergut, Concettina Buccella, Carlo Cecati, and Gerhard P Hancke. "Smart grid technologies: Communication technologies and standards". In: *IEEE Trans. Industr. Inform.* 7.4 (2011), pp. 529–539.
- [29] W Li, A Monti, Mt Luo, and Roger A Dougal. "VPNET: A co-simulation framework for analyzing communication channel effects on power systems". In: *Electric Ship Tech. Symp.* IEEE. 2011, pp. 143–149.
- [30] Vincenzo Liberatore and Ahmad Al-Hammouri. "Smart grid communication and co-simulation". In: *EnergyTech*. IEEE. 2011, pp. 1–5.
- [31] Hua Lin, Santhoshkumar Sambamoorthy, Sandeep Shukla, James Thorp, and Lamine Mili. "Power system and communication network co-simulation for smart grid applications". In: *ISGT 2011*. IEEE. 2011, pp. 1–6.
- [32] Malaz Mallouhi, Youssif Al-Nashif, Don Cox, Tejaswini Chadaga, and Salim Hariri. "A testbed for analyzing security of SCADA control systems (TASSCS)". In: *ISGT 2011*. IEEE. 2011, pp. 1–7.
- [33] Carlos Queiroz, Abdun Mahmood, and Zahir Tari. "SCADASim—A framework for building SCADA simulations". In: *IEEE Trans. Smart Grid* 2.4 (2011), pp. 589–597.
- [34] Steffen Schütte, Stefan Scherfke, and Martin Tröschel. "Mosaik: A framework for modular simulation of active components in Smart Grids". In: *1st Int. Workshop on Smart Grid Modeling and Simulation (SGMS)*. IEEE. 2011, pp. 55–60.
- [35] Erik Ela and Mark O'Malley. "Studying the variability and uncertainty impacts of variable generation at multiple timescales". In: *IEEE Trans. Power Syst.* 27.3 (2012), pp. 1324–1333.
- [36] V Cagri Gungor, Dilan Sahin, Taskin Kocak, Salih Ergut, Concettina Buccella, Carlo Cecati, and Gerhard P Hancke. "A survey on smart grid potential applications and communication requirements". In: *IEEE Trans. Industr. Inform.* 9.1 (2012), pp. 28–42.
- [37] Ahmad T Al-Hammouri. "A comprehensive co-simulation platform for cyber-physical systems". In: *Computer Communications* 36.1 (2012), pp. 8–19.
- [38] Hua Lin, Santhosh S Veda, Sandeep S Shukla, Lamine Mili, and James Thorp. "GECO: Global event-driven co-simulation framework for interconnected power system and communication network". In: *IEEE Trans. Smart Grid* 3.3 (2012), pp. 1444–1456.
- [39] D Montenegro, M Hernandez, and GA Ramos. "Real time OpenDSS framework for distribution systems simulation and analysis". In: *6th PES Transmission and Distribution: Latin America Conference and Exposition (T&D-LA)*. IEEE. 2012, pp. 1–5.
- [40] Song Tan, Wen-Zhan Song, Qifen Dong, and Lang Tong. "Score: Smart-grid common open research emulator". In: *3rd Int. Conf. on Smart Grid Communications (SmartGridComm)*. IEEE. 2012, pp. 282–287.
- [41] Hanno Georg, Sven Christian Müller, Nils Dorsch, Christian Rehtanz, and Christian Wietfeld. "INSPIRE: Integrated co-simulation of power and ICT systems for real-time evaluation". In: *Int. Conf. on Smart Grid Communications (SmartGridComm)*. IEEE. 2013, pp. 576–581.
- [42] Adam Hahn, Aditya Ashok, Siddharth Sridhar, and Manimaran Govindarasu. "Cyber-physical security testbeds: Architecture, application, and evaluation for smart grid". In: *IEEE Trans. Smart Grid* 4.2 (2013), pp. 847–855.
- [43] Pieter Hintjens. *ZeroMQ: messaging for many applications*. " O'Reilly Media, Inc.", 2013.
- [44] Federico Milano. "A Python-based software tool for power system analysis". In: *Power & Energy Society Gen. Meet.* IEEE. 2013, pp. 1–5.
- [45] Fidelis Perkonigg, Djordje Brujic, and Mike Ristic. "MAC-Sim: A multi-agent and communication network simulation platform for smart grid applications based on established technologies". In: *Int. Conf. on Smart Grid Communications (SmartGridComm)*. IEEE. 2013, pp. 570–575.
- [46] Mike Zhou. "Distributed parallel power system simulation". In: *High performance computing in power and energy systems*. Springer, 2013, pp. 71–100.
- [47] Mohammad Abdullah Al Faruque and Fereidoun Ahourai. "GridMat: Matlab toolbox for GridLAB-D to analyze grid impact and validate residential microgrid level energy management algorithms". In: *ISGT 2014*. IEEE. 2014, pp. 1–5.

- [48] Kyle Anderson, Jimmy Du, Amit Narayan, and Abbas El Gamal. “GridSpice: A distributed simulation platform for the smart grid”. In: *IEEE Trans. Industr. Inform.* 10.4 (2014), pp. 2354–2363.
- [49] Abdalkarim Awad, Peter Bazan, and Reinhard German. “SGsim: A simulation framework for smart grid applications”. In: *Int. Energy Conf. (ENERGYCON)*. IEEE. 2014, pp. 730–736.
- [50] David P Chassin, Jason C Fuller, and Ned Djilali. “GridLAB-D: An agent-based simulation framework for smart grids”. In: *Journal of Applied Mathematics* 2014 (2014).
- [51] Selim Ciraci, Jeff Daily, Jason Fuller, Andrew Fisher, Laurentiu Marinovici, and Khushbu Agarwal. “FNCS: a framework for power system and communication networks co-simulation”. In: *Proc. of the Symp. on Theory of Modeling & Simulation-DEVS integrative*. Society for Computer Simulation International. 2014, p. 36.
- [52] Francisco M Gonzalez-Longatt and José Luis Rueda. *PowerFactory applications for power system analysis*. Springer, 2014.
- [53] Christopher Greer, David A Wollman, Dean E Prochaska, Paul A Boynton, Jeffrey A Mazer, Cuong T Nguyen, Gerald J FitzPatrick, Thomas L Nelson, Galen H Koepke, Allen R Hefner Jr, et al. *NIST framework and roadmap for smart grid interoperability standards, release 3.0*. Tech. rep. 2014.
- [54] Kevin Mets, Juan Aparicio Ojea, and Chris Develder. “Combining power and communication network simulation for cost-effective smart grid analysis”. In: *IEEE Commun. Surv. Tutor.* 16.3 (2014), pp. 1771–1796.
- [55] Hugo Morais, Pieter Vancraeyveld, Allan Henning Birger Pedersen, Morten Lind, Hjörtur Jóhannsson, and Jacob Østergaard. “SOSPO-SP: Secure operation of sustainable power systems simulation platform for real-time system state evaluation and control”. In: *IEEE Trans. Industr. Inform.* 10.4 (2014), pp. 2318–2329.
- [56] Xinwei Sun, Ying Chen, Jiatai Liu, and Shaowei Huang. “A co-simulation platform for smart grid considering interaction between information and power systems”. In: *ISGT 2014*. IEEE. 2014, pp. 1–6.
- [57] Bhagya Amarasekara, Chathurika Ranaweera, Ampalavanapillai Nirmalathas, and Rob Evans. “Co-simulation platform for smart grid applications”. In: *Innovative Smart Grid Tech.-Asia (ISGT ASIA)*. IEEE. 2015, pp. 1–6.
- [58] D Bian, M Kuzlu, M Pipattanasomporn, S Rahman, and Yiming Wu. “Real-time co-simulation platform using OPAL-RT and OPNET for analyzing smart grid performance”. In: *Power & Energy Society Gen. Meet.* IEEE. 2015, pp. 1–5.
- [59] Denis Bytschkow, Martin Zellner, and Markus Duchon. “Combining SCADA, CIM, GridLab-D and AKKA for smart grid co-simulation”. In: *Power & Energy Society Innovative SG Tech. Conf. (ISGT)*. IEEE. 2015, pp. 1–5.
- [60] Timothy M Hansen, Bryan Palmintier, Siddharth Suryanarayanan, Anthony A Maciejewski, and Howard Jay Siegel. “Bus.py: A GridLAB-D communication interface for Smart distribution Grid simulations”. In: *Power & Energy Society Gen. Meet.* IEEE. 2015, pp. 1–5.
- [61] Keith Stouffer, Joe Falco, and Karen Scarfone. “Guide to industrial control systems (ICS) security – Rev. 2”. In: *NIST Special Publication* 800.82 (2015).
- [62] Christopher Hannon, Jiaqi Yan, and Dong Jin. “DSSnet: A smart grid modeling platform combining electrical power distribution system simulation and software defined networking emulation”. In: *Proc. of the 2016 ACM SIGSIM conference on principles of advanced discrete simulation*. 2016, pp. 131–142.
- [63] Dheepak Krishnamurthy. “psst: An open-source power system simulation toolbox in python”. In: *North American Power Symposium (NAPS)*. IEEE. 2016, pp. 1–6.
- [64] Peter Gorm Larsen, John Fitzgerald, Jim Woodcock, Peter Fritzson, Jörg Brauer, Christian Kleijn, Thierry Lecomte, Markus Pfeil, Ole Green, Stylianos Basagiannis, et al. “Integrated tool chain for model-based design of Cyber-Physical Systems: The INTO-CPS project”. In: *2016 2nd International Workshop on Modelling, Analysis, and Control of Complex CPS (CPS Data)*. IEEE. 2016, pp. 1–6.
- [65] Bryan Palmintier, Elaine Hale, Timothy M Hansen, Wesley Jones, David Biagioni, Harry Sorensen, Hongyu Wu, and Bri-Mathias Hodge. “IGMS: An integrated ISO-to-appliance scale grid modeling system”. In: *IEEE Trans. Smart Grid* 8.3 (2016), pp. 1525–1534.
- [66] Zhizhang Pan, Qimin Xu, Cailian Chen, and Xinping Guan. “NS3-MATLAB co-simulator for cyber-physical systems in smart grid”. In: *35th Chinese Control Conference (CCC)*. IEEE. 2016, pp. 9831–9836.
- [67] Alexandre Gustavo Wermann, Marcelo Cardoso Bortolozzo, Eduardo Germano da Silva, Alberto Schaeffer-Filho, Luciano Paschoal Gaspary, and Marinho Barcellos. “ASTORIA: A framework for attack simulation and evaluation in smart grids”. In: *NOMS 2016-2016 IEEE/IFIP Network Operations and Management Symposium*. IEEE. 2016, pp. 273–280.
- [68] Cristian Zambrano, Cesar Trujillo, David Celeita, Miguel Hernandez, and Gustavo Ramos. “GridTeractions: Simulation platform to interact with distribution systems”. In: *Power and Energy Society Gen. Meet. (PESGM)*. IEEE. 2016, pp. 1–5.
- [69] Tom Brown, Jonas Hörsch, and David Schlachtberger. “PyPSA: Python for power system analysis”. In: *arXiv preprint arXiv:1707.09913* (2017).

- [70] DM Greenwood, Khim Yan Lim, C Patsios, PF Lyons, Yun Seng Lim, and PC Taylor. "Frequency response services designed for energy storage". In: *Applied Energy* 203 (2017), pp. 115–127.
- [71] Jacob Hansen, Thomas Edgar, Jeff Daily, and Di Wu. "Evaluating transactive controls of integrated transmission and distribution systems using the framework for network co-simulation". In: *American Control Conference (ACC)*. IEEE. 2017, pp. 4010–4017.
- [72] Renke Huang, Rui Fan, Jeff Daily, Andrew Fisher, and Jason Fuller. "Open-source framework for power system transmission and distribution dynamics co-simulation". In: *IET Gener. Transm. Distrib.* 11.12 (2017), pp. 3152–3162.
- [73] Abdulmalik Humayed, Jingqiang Lin, Fengjun Li, and Bo Luo. "Cyber-physical systems security – A survey". In: *Internet of Things Journal* 4.6 (2017), pp. 1802–1831.
- [74] Arjen A van der Meer, Peter Palensky, Kai Heussen, DE Morales Bondy, Oliver Gehrke, C Steinbrink, M Blanki, Sebastian Lehnhoff, Edmund Widl, Cyndi Moyo, et al. "Cyber-physical energy systems modeling, test specification, and co-simulation based testing". In: *Workshop on Modeling and Simulation of Cyber-Physical Energy Systems (MSCPES)*. IEEE. 2017, pp. 1–9.
- [75] Vidhyashree Nagaraju, Lance Fiondella, and Thierry Wandji. "A survey of fault and attack tree modeling and analysis for cyber risk management". In: *Int. Symp. on Tech. for Homeland Security (HST)*. IEEE. 2017, pp. 1–6.
- [76] Bryan Palmintier, Dheepak Krishnamurthy, Philip Top, Steve Smith, Jeff Daily, and Jason Fuller. "Design of the HELICS high-performance transmission-distribution-communication-market co-simulation framework". In: *Workshop on Modeling and Simulation of Cyber-Physical Energy Systems (MSCPES)*. IEEE. 2017, pp. 1–6.
- [77] Gelli Ravikumar, Gelli Ramya, S Misra, S Brahma, and SA Khaparde. "iPaCS: An integrative power and cyber systems co-simulation framework for smart grid". In: *Power & Energy Society Gen. Meet.* IEEE. 2017, pp. 1–5.
- [78] Neetesh Saxena, Victor Chukwuka, Leilei Xiong, and Santiago Grijalva. "CPSA: a cyber-physical security assessment tool for situational awareness in smart grid". In: *Proc. of the 2017 Workshop on Cyber-Physical Systems Security and PrivaCy*. 2017, pp. 69–79.
- [79] Mike Zhou and Qiuhua Huang. "InterPSS: A new generation power system simulation engine". In: *arXiv preprint arXiv:1711.10875* (2017).
- [80] Benjamin Camus, Thomas Paris, Julien Vaubourg, Yannick Presse, Christine Bourjot, Laurent Ciarletta, and Vincent Chevrier. "Co-simulation of cyber-physical systems using a DEVS wrapping strategy in the MECSYCO middleware". In: *Simulation* 94.12 (2018), pp. 1099–1127.
- [81] Jonathan Coignard, Thierry Noudui, Christoph Gehbauer, Michael Wetter, Jhi-Young Joo, Philip Top, Rafael Rivera Soto, Brian Kelley, and Emma Stewart. "CyDER - a co-simulation platform for grid analysis and planning for high penetration of distributed energy resources". In: *Power & Energy Society Gen. Meet. (PESGM)*. IEEE. 2018, pp. 1–5.
- [82] Hantao Cui and Fangxing Li. "ANDES: A Python-based cyber-physical power system simulation tool". In: *North American Power Symposium (NAPS)*. IEEE. 2018, pp. 1–6.
- [83] Cláudio Gomes, Casper Thule, David Broman, Peter Gorm Larsen, and Hans Vangheluwe. "Co-simulation: a survey". In: *ACM Computing Surveys (CSUR)* 51.3 (2018), p. 49.
- [84] Jonas Hörsch, Fabian Hofmann, David Schlachtberger, and Tom Brown. "PyPSA-Eur: An open optimisation model of the European transmission system". In: *Energy Strategy Reviews* 22 (2018), pp. 207–215.
- [85] Qiuhua Huang, Thomas E McDermott, Yingying Tang, Atefe Makhmalbaf, Donald J Hammerstrom, Andrew R Fisher, Laurentiu Dan Marinovici, and Trevor Hardy. "Simulation-based valuation of transactive energy systems". In: *IEEE Trans. Power Syst.* 34.5 (2018), pp. 4138–4147.
- [86] Marija D Ilić, Rupamathi Jaddivada, and Xia Miao. "Scalable electric power system simulator". In: *PES Innovative Smart Grid Technologies Conference Europe (ISGT-Europe)*. IEEE. 2018, pp. 1–6.
- [87] Gayathri Krishnamoorthy and Anamika Dubey. "A framework to analyze interactions between transmission and distribution systems". In: *Power & Energy Society Gen. Meet. (PESGM)*. IEEE. 2018, pp. 1–5.
- [88] T Noudui and Michael Wetter. "SimulatorToFMU: A Python Utility to Support Building Simulation Tool Interoperability". In: *Proc. of the 2018 Building Perf. Analysis Conf. and SimBuild, Chicago, IL*. 2018.
- [89] Leon Thurner, Alexander Scheidler, Florian Schäfer, Jan-Hendrik Menke, Julian Dollichon, Friederike Meier, Steffen Meinecke, and Martin Braun. "pandapower - an open-source python tool for convenient modeling, analysis, and optimization of electric power systems". In: *IEEE Trans. Power Syst.* 33.6 (2018), pp. 6510–6521.
- [90] Yaswanth Nag Velaga, Aoxia Chen, PK Sen, Gayathri Krishnamoorthy, and Anamika Dubey. "Transmission-distribution co-simulation: Model validation with standalone simulation". In: *North American Power Symposium (NAPS)*. IEEE. 2018, pp. 1–6.

- [91] Carlos J Vélez-Rivera, Fabio Andrade, Emmanuel Arzuaga-Cruz, and Agustín Irizarry-Rivera. “Gorilla: An Open Interface for Smart Agents and Real-Time Power Microgrid System Simulations”. In: *Inventions* 3.3 (2018), p. 58.
- [92] Mike Vogt, Frank Marten, and Martin Braun. “A survey and statistical analysis of smart grid co-simulations”. In: *Applied Energy* 222 (2018), pp. 67–78.
- [93] Christoph Gehbauer. *CyDER: A Cyber Physical Co-simulation Platform for Distributed Energy Resources in Smartgrids*. Tech. rep. Lawrence Berkeley National Lab.(LBNL), US, 2019.
- [94] Takai-Eddine Kennouche, Florent Cadoux, Nicolas Gast, and Benoît Vinot. “ASGridS: Asynchronous Smart-Grids Distributed Simulator”. In: *PES Asia-Pacific Power and Energy Engineering Conference (APPEEC)*. IEEE. 2019, pp. 1–5.
- [95] Pardeep Kumar, Yun Lin, Guangdong Bai, Andrew Paverd, Jin Song Dong, and Andrew Martin. “Smart grid metering networks: A survey on security, privacy and open research issues”. In: *IEEE Commun. Surveys Tuts.* 21.3 (2019), pp. 2886–2927.
- [96] Tan Duy Le, Adnan Anwar, Razvan Beuran, and Seng W Loke. “Smart Grid Co-Simulation Tools: Review and Cybersecurity Case Study”. In: *7th Int. Conf. on Smart Grid (icSmartGrid)*. IEEE. 2019, pp. 39–45.
- [97] Hieu Trung Nguyen, Swathi Battula, Rohit Reddy Takkala, Zhaoyu Wang, and Leigh Tesfatsion. “An integrated transmission and distribution test system for evaluation of transactive energy designs”. In: *Applied Energy* 240.November 2018 (2019), pp. 666–679. ISSN: 03062619.
- [98] Thierry S Noudui, Jonathan Coignard, Christoph Gehbauer, Michael Wetter, Jhi-Young Joo, and Evangelos Vrettos. “CyDER - an FMI-based co-simulation platform for distributed energy resources”. In: *J. Build. Perform. Simul.* 12.5 (2019), pp. 566–579.
- [99] Fabiano Pallonetto, Eleni Mangina, Federico Milano, and Donal P Finn. “SimApi, a smartgrid co-simulation software platform for benchmarking building control algorithms”. In: *SoftwareX* 9 (2019), pp. 271–281.
- [100] Pablo Puerto, Edmund Widl, and Jessen Page. “ZerOBNL: A framework for distributed and reproducible co-simulation”. In: *7th Workshop on Modeling and Simulation of CPES (MSCPES)*. IEEE. 2019, pp. 1–6.
- [101] Panagiotis I Radoglou-Grammatikis and Panagiotis G Sarigiannidis. “Securing the smart grid: A comprehensive compilation of intrusion detection and prevention systems”. In: *IEEE Access* 7 (2019), pp. 46595–46620.
- [102] Cornelius Steinbrink, Marita Blank-Babazadeh, André El-Ama, Stefanie Holly, Bengt Lüers, Marvin Nebel-Wenner, Rebeca P Ramírez Acosta, Thomas Raub, Jan Sören Schwarz, Sanja Stark, et al. “CPES Testing with mosaic: Co-Simulation Planning, Execution and Analysis”. In: *Applied Sciences* 9.5 (2019), p. 923.
- [103] Casper Thule, Kenneth Lausdahl, Cláudio Gomes, Gerd Meisl, and Peter Gorm Larsen. “Maestro: The INTO-CPS co-simulation framework”. In: *Simulat. Model. Pract.* 92 (2019), pp. 45–61.
- [104] Shida Zhang, Daniel May, Peter Atrazhev, Mustafa Gul, Andrew Leach, Tim Weis, and Petr Musilek. “ETX: A Flexible Simulation Framework for Design of Transactive Energy Systems”. In: *Canadian Conf. of Elect. and Comp. Eng. (CCECE)*. IEEE. 2019, pp. 1–4.
- [105] Luca Arnaboldi, Ricardo M Czekster, Charles Morisset, and Roberto Metere. “Modelling Load-Changing Attacks in Cyber-Physical Systems”. In: *Electron. Notes Theor. Comput. Sci.* 353.C (2020), pp. 39–60.
- [106] Mohamed Azeroual, Tijani Lamhamdi, Hassan El Moussaoui, and Hassane El Markhi. “Simulation tools for a smart grid and energy management for microgrid with wind power using multi-agent system”. In: *Wind Engineering* 44.6 (2020), pp. 661–672.
- [107] Hantao Cui, Fangxing Li, and Kevin Tomsovic. “Hybrid Symbolic-Numeric Framework for Power System Modeling and Analysis”. In: *IEEE Trans. Power Syst.* (2020).
- [108] Martin Henze, Lennart Bader, Julian Filter, Olav Lamberts, Simon Ofner, and Dennis van der Velde. “Poster: Cybersecurity Research and Training for Power Distribution Grids—A Blueprint”. In: *ACM CCS*. 2020.
- [109] Jay Johnson, Ifeoma Onunkwo, Patricia Cordeiro, Brian J Wright, Nicholas Jacobs, and Christine Lai. “Assessing DER network cybersecurity defences in a power-communication co-simulation environment”. In: *IET Cyber-Physical Systems: Theory & Applications* 5.3 (2020), pp. 274–282.
- [110] Tan Duy Le, Adnan Anwar, Seng W Loke, Razvan Beuran, and Yasuo Tan. “GridAttackSim: A Cyber Attack Simulation Framework for Smart Grids”. In: *Electronics* 9.8 (2020), p. 1218.
- [111] Thomas Morstyn, Katherine A Collett, Avinash Vijay, Matthew Deakin, Scot Wheeler, Sivapriya M Bhagavathy, Filiberto Fele, and Malcolm D McCulloch. “OPEN: An open-source platform for developing smart local energy system applications”. In: *Applied Energy* 275 (2020), p. 115397.
- [112] Evandro de Souza, Omid Ardakanian, and Ioanis Nikolaidis. “A Co-simulation Platform for Evaluating Cyber Security and Control Applications in the Smart Grid”. In: *Int. Conf. on Communications (ICC)*. IEEE. 2020, pp. 1–7.