KD3A: Unsupervised Multi-Source Decentralized Domain Adaptation via Knowledge Distillation

Hao-Zhe Feng, Zhaoyang You, Minghao Chen, Tianye Zhang Minfeng Zhu, Fei Wu, Chao Wu, Wei Chen

Zhejiang University

{fenghz, zhaoyangyou, zhangtianye1026, wufei, chao.wu, chenvis}@zju.edu.cn, minghaochen01@gmail.com, minfeng.zhu@outlook.com

Abstract

Conventional unsupervised multi-source domain adaptation (UMDA) methods assume all source domains can be accessed directly. This neglects the privacy-preserving policy, that is, all the data and computations must be kept decentralized. There exists three problems in this scenario: (1) Minimizing the domain distance requires the pairwise calculation of the data from source and target domains, which is not accessible. (2) The communication cost and privacy security limit the application of UMDA methods (e.g., the domain adversarial training). (3) Since users have no authority to check the data quality, the irrelevant or malicious source domains are more likely to appear, which causes negative transfer. In this study, we propose a privacy-preserving UMDA paradigm named Knowledge Distillation based Decentralized Domain Adaptation (KD3A), which performs domain adaptation through the knowledge distillation on models from different source domains. KD3A solves the above problems with three components: (1) A multi-source knowledge distillation method named Knowledge Vote to learn high-quality domain consensus knowledge. (2) A dynamic weighting strategy named Consensus Focus to identify both the malicious and irrelevant domains. (3) A decentralized optimization strategy for computing domain distance named BatchNorm MMD. The extensive experiments on DomainNet demonstrate that KD3A is robust to the negative transfer and brings a $100 \times$ reduction of communication cost compared with other decentralized UMDA methods. Moreover, our KD3A significantly outperforms state-of-the-art UMDA approaches.

Introduction

Most deep learning models are trained with large-scale labeled datasets via supervised learning. Since it is often costly and time-consuming to get sufficient data, we usually use other similar datasets to train the model. However, due to the domain shift, naively combining different datasets usually results in unsatisfying performance. Unsupervised Multi-source Domain Adaptation (UMDA) (Zhang et al. 2015) addresses such problems by establishing transferable features from multiple source domains to an unlabeled target domain. Recent advanced UMDA methods (Chang et al. 2019; Zhao et al. 2020) perform the knowledge transfer within two steps: (1) Combining data from source and target domains to construct **S**ource-**T**arget pairs. (2) Establishing transferable features by minimizing the domain distance (e.g., \mathcal{H} -divergence). This prevailing paradigm works well when all source domains are available. However, we usually cannot access the original source domain data because of the privacy-preserving policy, e.g., the patient data from different hospitals and the client profiles from different companies. In these cases, all the data and computations of source domains must be kept decentralized.

Most prevailing UMDA methods are not applicable under this privacy-preserving policy due to three problems: (1) Minimizing the \mathcal{H} -divergence in UMDA requires the pairwise calculation of the data from source and target domains, which is not accessible. (2) The communication cost and privacy security limit the application of advanced UMDA methods. For example, the domain adversarial training is able to optimize the \mathcal{H} -divergence without accessing data (Peng et al. 2020). However, it requires each source domain to synchronize model with target domain after every single batch, which results in huge communication cost and causes the privacy leakage (Zhu et al. 2019). (3) The negative transfer problem (Pan and Yang 2010). Since we have no authority to check the data quality, there can exist some irrelevant source domains that are very different from the target domain or even some malicious source domains which perform the poisoning attack (Bagdasarvan et al. 2020)). With these domains, the negative transfer occurs.

In this study, we propose a solution to the above problems called Knowledge Distillation based Decentralized Domain Adaptation (KD3A), which aims to perform decentralized domain adaptation through the knowledge distillation on models from different source domains. Our approach offers the following contributions. First, we analyze the knowledge distillation (Zhang et al. 2018) in UMDA from a theoretical perspective and provide a decentralized generalization bound for KD3A. Then, we propose a multi-source knowledge distillation method named *Knowledge Vote* to obtain high-quality domain consensus knowledge. Based on the consensus quality of different source domains, we

Copyright © 2021, Association for the Advancement of Artificial Intelligence (www.aaai.org). All rights reserved.

devise a dynamic weighting strategy named *Consensus Focus* to identify the malicious and irrelevant source domains. Finally, we derive a decentralized optimization strategy of \mathcal{H} -divergence named *BatchNorm MMD*. The extensive experiments show our KD3A has the following properties:

- The KD3A brings a 100× reduction of communication cost compared with other decentralized UMDA methods and is robust to the advanced privacy leakage attack.
- The KD3A assigns low weights to those malicious or irrelevant domains. Therefore, it is robust to negative transfer.
- The KD3A significantly outperforms the *state-of-the-art* UMDA approaches with 51.1% accuracy on the large-scale DomainNet dataset.

In addition, our KD3A is easy to implement and we create an open-source framework to conduct KD3A on different benchmarks¹.

Related work

Unsupervised multi-source domain adaptation

Unsupervised Multi-source Domain Adaptation (UMDA) aims to transfer the knowledge learned from multiple labeled source domains to an unlabeled target domain. To learn the transferable features, the model needs to reduce the \mathcal{H} -divergence between source domain \mathbb{D}_S and target domain \mathbb{D}_T . There are two prevailing paradigms that provide the optimization strategy of \mathcal{H} -divergence, i.e. maximum mean discrepancy (MMD) and the adversarial training. In addition, knowledge distillation is also used to perform model-level knowledge transfer.

MMD based methods (Tzeng et al. 2014; Chen et al. 2020) construct a reproducing kernel Hilbert space (RKHS) \mathcal{H}_{κ} with a characteristic kernel κ , and optimize the \mathcal{H} -divergence by minimizing the MMD distance $d_{\text{MMD}}(\mathbb{D}_S, \mathbb{D}_T)$ on \mathcal{H}_{κ} . Using the kernel trick, MMD can be computed as

$$d_{MMD}(\mathbb{D}_{S}, \mathbb{D}_{T}) = -2\mathbb{E}_{\mathbf{X}_{S}, \mathbf{X}_{T} \sim \mathbb{D}_{S}, \mathbb{D}_{T}} \kappa(\mathbf{X}_{S}, \mathbf{X}_{T}) + \\ \mathbb{E}_{\mathbf{X}_{S}, \mathbf{X}_{S}' \sim \mathbb{D}_{S}} \kappa(\mathbf{X}_{S}, \mathbf{X}_{S}') + \mathbb{E}_{\mathbf{X}_{T}, \mathbf{X}_{T}' \sim \mathbb{D}_{T}} \kappa(\mathbf{X}_{T}, \mathbf{X}_{T}')$$
(1)

Recent works propose the variations of MMD, e.g., multikernel MMD (Long et al. 2015), class-weighted MMD(Yan et al. 2017) and domain-crossing MMD (Peng et al. 2019). However, all these methods require the pairwise calculation of the data from source and target domains, which is not allowed under the decentralization constraints.

The adversarial training strategy (Saito et al. 2018; Zhao et al. 2018; Long et al. 2018) apply adversarial training in feature space to optimize \mathcal{H} -divergence. It is proved that with the adversarial training strategy, the UMDA model can work under the privacy-preserving policy (Peng et al. 2020). However, the adversarial training requires each source domain to exchange and update model parameters with the target domain after every single batch, which consumes huge communication resources. **Knowledge distillation in domain adaptation.** Knowledge distillation (KD) (Hinton et al. 2015; Xie et al. 2020) is an efficient way of transferring knowledge between different models. Recent works (Guo et al. 2018; Meng et al. 2018) extend the knowledge distillation into domain adaptation with a teacher-student training strategy, that is, train multiple teacher models on source domains and ensemble them on target domain to train a student model. This strategy is found useful in practice. However, the theoretical analysis of how knowledge distillation works in domain adaptation has not been discussed.

Federated learning

Federated learning (Konecný et al. 2016) is a distributed machine learning approach that trains a global model across multiple decentralized datasets, while keeping the data and computation locally. Federated average (FedAvg) (McMahan et al. 2017) is the algorithm to aggregate the updates of models from different clients in each communication round. Recent works (Konecný et al. 2016; McMahan et al. 2017) find a trade-off between model performance and communication efficiency, that is, to achieve better performance, we need to conduct more communication rounds, which raises the communication costs. Besides, the frequent communication will also cause privacy leakage (Zhu et al. 2019; Wang et al. 2019), which makes the federated learning system insecure.

Federated domain adaptation. There are few works discussing the decentralized UMDA methods. FADA (Peng et al. 2020) first raises the concept of federated domain adaptation. It applies the adversarial training to optimize the \mathcal{H} -divergence without accessing data. However, FADA consumes high communication costs and is vulnerable to the privacy leakage attack. SHOT(Liang et al. 2020) provides a self-training based method to solve the single source decentralized domain adaptation. However, it is vulnerable to the negative transfer in multi-source situations.

KD3A: decentralized domain adaptation via knowledge distillation

Let \mathbb{D}_S and \mathbb{D}_T denote the source domain and target domain. In UMDA, we are given K source domains $\{\mathbb{D}_S^k\}_{k=1}^K$ where each domain contains N_k labeled examples as $\mathbb{D}_S^k :=$ $\{(\mathbf{X}_i^k, \mathbf{y}_i^k)\}_{i=1}^{N_k}$ and a *target* domain \mathbb{D}_T with N_T unlabeled examples as $\mathbb{D}_T := \{\mathbf{X}_i^T\}_{i=1}^{N_T}$. The goal of UMDA is to learn a model h which can minimize the task risk $\epsilon_{\mathbb{D}_T}$ in \mathbb{D}_T , i.e. $\epsilon_{\mathbb{D}_T}(h) = \Pr_{(\mathbf{X}, \mathbf{y}) \sim \mathbb{D}_T}[h(\mathbf{X}) \neq \mathbf{y}]$. Without loss of generality, we consider C-way classification task and assume the target domain shares the same tasks with the source domains. In a common UMDA, we combine K source domains with different domain weights to form a mixture domain denoted by $\mathbb{D}_{\tilde{S}}$, and perform domain adaptation by minimizing the following generalization bound (Ben-David et al. 2010) with the mixture domain $\mathbb{D}_{\tilde{S}}$ as:

Theorem 1 Let \mathcal{H} be the model space, $\epsilon_{\mathbb{D}_{\tilde{S}}}(h)$, $\epsilon_{\mathbb{D}_{T}}(h)$ be the task risks of the mixture source domain $\mathbb{D}_{\tilde{S}}$ and the target domain \mathbb{D}_{T} , Then $\forall h \in \mathcal{H}$, we have:

$$\epsilon_{\mathbb{D}_T}(h) \le \epsilon_{\mathbb{D}_{\tilde{S}}}(h) + d_{\mathcal{H}}(\mathbb{D}_{\tilde{S}}, \mathbb{D}_T) + C_0 \tag{2}$$

¹https://github.com/AAAI2021-255/KD3A



(b) Knowledge vote ensemble.

Figure 1: (a) Knowledge distillation in UMDA consists of two steps: obtaining the inferences from source domain models and performing knowledge ensemble to get the consensus knowledge. (b) Our knowledge vote extracts strong consensus with 3 steps: confidence gate, consensus class vote and mean ensemble. ' \times ' means the eliminated model in each step.

where C_0 is a constant recording to the complexity of model space and the risk of an optimal model for $\mathbb{D}_{\tilde{S}}$ and \mathbb{D}_T .

The common UMDA model learns transferable features by minimizing the \mathcal{H} -divergence. While in decentralized UMDA, we apply knowledge distillation to perform domain adaptation without accessing the data.

Generalization bound for knowledge distillation.

Knowledge distillation can perform knowledge transfer through different models. Suppose we have K fully-trained models from K source domains denoted by $\{h_S^k\}_{k=1}^K$. we use $q(\mathbf{X})$ to denote the confidence for each class and use the class with the maximum confidence as label, i.e. $h(\mathbf{X}) = \arg_c \max q_c(\mathbf{X})$. As shown in Figure 1(a), the knowledge distillation in UMDA consists of two steps. First, for each target domain data \mathbf{X}_i^T , we obtain the inferences of the source domain models. Then, we use the ensemble method to get the consensus knowledge of the source models, e.g., $\mathbf{p}_i = \frac{1}{K} \sum_{k=1}^K q_S^k(\mathbf{X}_i^T)$. After that, we train the model to learn the consensus with knowledge distillation loss

$$L^{\mathrm{kd}}(\mathbf{X}_i^T, q) = D_{\mathrm{KL}}(\mathbf{p}_i \| q(\mathbf{X}_i^T))$$
(3)

The KD loss (3) is empirically useful in domain adaptation (Ruder et al. 2017). A common question is, how does knowledge distillation improve the UMDA performance? We analyze the problem from a theoretical perspective and provide an important insight that KD loss improves the UMDA performance by minimizing a consensus-based generalization bound on target domain.

First, by applying knowledge distillation, we can obtain an extensive dataset of the target domain with the consensus knowledge \mathbf{p}_i for each data \mathbf{X}_i^T . We view this new dataset as an extra source domain denoting by $\mathbb{D}_S^{K+1} = \{(\mathbf{X}_i^T, \mathbf{p}_i)\}_{i=1}^{N_T}$, and the related task risk is defined as

$$\epsilon_{\mathbb{D}_{S}^{K+1}}(h) = \Pr_{(\mathbf{X},\mathbf{p}) \sim \mathbb{D}_{S}^{K+1}}[h(\mathbf{X}) \neq \arg_{c} \max \mathbf{p}_{c}]$$

It is easy to find that minimizing KD loss (3) can optimize $\epsilon_{\mathbb{D}_{S}^{K+1}}(h)$ (proof in Appendix A). With this insight, we derive the generalization bound for knowledge distillation as follows (proof in Appendix B):

Theorem 2 The generalization bound for knowledge distillation. Let \mathcal{H} be the model space and $\epsilon_{\mathbb{D}_{S}^{K+1}}(h)$ be the task risk of the extra domain \mathbb{D}_{S}^{K+1} . Then $\forall h \in \mathcal{H}$, we have:

$$\epsilon_{\mathbb{D}_T}(h) \le \epsilon_{\mathbb{D}_S^{K+1}}(h) + d_{\mathcal{H}}(\mathbb{D}_S^{K+1}, \mathbb{D}_T) + C_1 \qquad (4)$$

Notice $d_{\mathcal{H}}(\mathbb{D}_{S}^{K+1}, \mathbb{D}_{T}) = 0$ since \mathbb{D}_{S}^{K+1} and \mathbb{D}_{T} share the same input space. Theorem 2 proves that knowledge distillation improves UMDA performance by minimizing the upper bound of the target domain risk $\epsilon_{\mathbb{D}_{T}}(h)$.

Combining the original bound (2) and the KD bound (2), We further derive the generalization bound for the decentralized UMDA. In this situation, we have K decentralized source domains and models are trained separately on them. By performing knowledge distillation, we obtain an extra source domain \mathbb{D}_{S}^{K+1} . Then we train model on \mathbb{D}_{S}^{K+1} with the KD loss. Finally, we get the target model as the weighted aggregation of the models from original source domains and the extra source domain, i.e. $h := \sum_{k=1}^{K+1} \alpha_k h_S^k$. The related generalization bound is as follows:

Theorem 3 The decentralized generalization bound for KD3A. Let h be the target model, $\{\mathbb{D}_{S}^{k}\}_{k=1}^{K+1}$ be the extended source domains and $\alpha \in \mathcal{R}_{+}^{K+1}, \sum_{k=1}^{K+1} \alpha_{k} = 1$ be the domain weights. Then we have:

$$\epsilon_{\mathbb{D}_T}(h) \le \sum_{k=1}^{K+1} \alpha_k \left(\epsilon_{\mathbb{D}_S^k}(h) + d_{\mathcal{H}}(\mathbb{D}_S^k, \mathbb{D}_T) \right) + C_2 \quad (5)$$

Knowledge vote: producing high-quality consensus.

The KD3A bound (5) can be regarded as the original bound (2) plus the KD bound (2), while its performance depends on the quality of the consensus knowledge \mathbf{p} , as the following proposition shows (see Appendix C for proof):

Proposition 1 The knowledge distillation bound (2) is a tighter bound than (2), if the task risk gap between the target domain \mathbb{D}_T and the knowledge distillation domain \mathbb{D}_S^{K+1} is small enough, i.e. $\sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_T}(h) - \epsilon_{\mathbb{D}_S^{K+1}}(h)| \to 0.$

Due to the irrelevant and malicious source domains, the prevailing ensemble strategies (e.g., maximum and mean ensemble) may fail to obtain proper consensus. Therefore, we propose the knowledge vote to provide high-quality consensus. The main idea of knowledge vote is that if a certain consensus knowledge is supported by more source domains with high confidence (e.g., > 0.9), then it will be more likely to be the true label. As shown in Figure 1(b), it takes three steps to perform Knowledge Vote:

- 1. Confidence gate. For each $\mathbf{X}_i^T \in \mathbb{D}_T$, we firstly use a high-level confidence gate to filter the predictions $\{q_S^k(\mathbf{X}_i^T)\}_{k=1}^K$ of teacher models and eliminate the unconfident models.
- 2. Consensus class vote. For the remained models, the predictions are added up to find the consensus class which has the maximum value. Then we drop the models that are inconsistent with the consensus class.
- 3. Mean ensemble. After the class vote, we obtain a set of models that all support the consensus class. Then we conduct mean ensemble on these models and get the consensus knowledge \mathbf{p}_i as well as the number of domains that support \mathbf{p}_i , denoted by $n_{\mathbf{p}_i}$. For those \mathbf{X}^T with all teacher models eliminated by the confidence gate, we use the naive mean ensemble to get \mathbf{p} as \mathbf{p} = $\frac{1}{K}\sum_{k=1}^{K} q_S^k(\mathbf{X}^T)$ and assign a relatively low weight to them as $n_{\mathbf{p}} = 0.001$.

After *Knowledge Vote*, we obtain an extra domain $\mathbb{D}_{S}^{K+1} =$ $\{(\mathbf{X}_i^T, \mathbf{p}_i, n_{\mathbf{p}_i})\}_{i=1}^{N_T}$. We use the $n_{\mathbf{p}_i}$ to re-weight the knowledge distillation loss as

$$L^{\text{kv}}(\mathbf{X}_i^T, q) = n_{\mathbf{p}_i} \cdot D_{\text{KL}}(\mathbf{p}_i \| q(\mathbf{X}_i^T))$$
(6)

Compared with other ensemble strategies, our Knowledge Vote can make model learn high-quality consensus knowledge since we assign high weights to those items with high confidence and many support domains.

Consensus focus: against negative transfer.

Domain weights α determine the contribution of each source domain. Therefore, the selection of α is important for the adaptation performance. Ben-David et al. (2010) proves the optimal α should be proportional to the amount of data when all source domains are equally important. However, this condition is hard to satisfy in KD3A since some source domains are usually very different from the target domain, or even are malicious domains with many wrong labels. In these situations, negative transfer occurs. One common solution (Zhao et al. 2020) is to re-weight each source domain with the \mathcal{H} -divergence as

$$\boldsymbol{\alpha}_{k} = N_{k} e^{-d_{\mathcal{H}}(\mathbb{D}_{S}^{k},\mathbb{D}_{T})} / \sum_{k} N_{k} e^{-d_{\mathcal{H}}(\mathbb{D}_{S}^{k},\mathbb{D}_{T})}.$$
 (7)

Algorithm 1 KD3A training process with epoch t.

Input:

Source domains $S = \{\mathbb{D}_{S}^{k}\}_{k=1}^{K}$. Target domain \mathbb{D}_{T} ; Global model $h^{(t-1)}$ with parameters $\Theta^{(t-1)}$; Confidence gate $q^{(t)}$:

Output:

- Global model $h^{(t)}$ with parameters $\Theta^{(t)}$.
- 1: // Locally training on source domains:
- 2: for \mathbb{D}^k_S in \mathcal{S} do
- Model initialize: $(h_S^k, \Theta_S^k) \leftarrow (h^{(t-1)}, \Theta^{(t-1)}).$ 3:
- 4: Train h_S^k with classification loss on \mathbb{D}_S^k .
- 5: end for
- 6: Upload $\{(h_S^k, \Theta_S^k)\}_{k=1}^K$ to the target domain.
- 7: *If Knowledge Vote:* 8: $\mathbb{D}_{S}^{K+1} \leftarrow \text{KnowledgeVote}(\mathbb{D}_{T}, g^{(t)}, \{h_{S}^{k}\}_{k=1}^{K}).$ 9: Train h_{S}^{K+1} with L^{kv} loss (6) on \mathbb{D}_{S}^{K+1} .
- 10: // Consensus Focus:
- 11: $\boldsymbol{\alpha}^{\text{CF}} \leftarrow \text{ConsensusFocus}(\mathbb{D}_T, \{h_S^k\}_{k=1}^K, \{N_k\}_{k=1}^K).$

- 11. α (1, 0, 0)12: // Model Aggregation: 13: $\Theta^{(t)} \leftarrow \sum_{k=1}^{K+1} \alpha_k^{CF} \cdot \Theta_S^k$. 14: // BatchNorm MMD: 15: Obtain { $\mathbb{E}[\pi_l^k]^i, i = 1, 2$ } $_{l,k=1}^{L,K+1}$ from { (h_S^k, Θ_S^k) } $_{k=1}^{K+1}$
- 16: Train $h^{(t)}$ with BatchNorm MMD on \mathbb{D}_T .
- 17: Return $(h^{(t)}, \Theta^{(t)})$.

However, calculating \mathcal{H} -divergence requires to access the source domain data, which is not accessible. Besides, \mathcal{H} divergence only measures the domain similarity on the input space, which does not utilize the label information and fails to identify the malicious domain. For example, suppose there exists a malicious source domain that is very similar to the target domain except for the totally wrong labels. Apparently, a good task risk on the source domain will lead to a bad result on the target domain. Since the \mathcal{H} -divergence is small, the related α under (7) can be reasonable large, e.g., $\alpha = 0.5$. Then, optimizing the generalization bound (5) with α will cause a bad domain adaptation performance.

In this section, we propose Consensus Focus to identify those irrelevant and malicious domains. As mentioned in Knowledge Vote, the UMDA performance is related to the quality of consensus knowledge. With high-quality consensus, the UMDA performance can be improved. Therefore, the main idea of Consensus Focus is to assign high weights to those domains which provide high-quality consensus, and penalize those domains which provide bad consensus. To perform Consensus Focus, we first derive the definition of consensus quality and then calculate the contribution to the consensus quality for each source domain.

The definition of consensus quality. Suppose we have a set of source domains denoted by $S = \{\mathbb{D}_S^k\}_{k=1}^K$. For each coalition of source domains $S', S' \subseteq S$, we want to estimate the quality of the knowledge consensus obtained from S'. Generally speaking, if one consensus class is supported by more source domains with higher confidence, then it will be more likely to be the true label, which means the consensus quality gets better. Therefore, for each $\mathbf{X}_i^T \in \mathbb{D}_T$

with the consensus knowledge $(\mathbf{p}_i(\mathcal{S}'), n_{\mathbf{p}_i}(\mathcal{S}'))$ obtained from \mathcal{S}' , the related consensus quality can be defined as $n_{\mathbf{p}_i}(\mathcal{S}') \cdot \max \mathbf{p}_i(\mathcal{S}')$ and the total consensus quality Q is

$$Q(\mathcal{S}') = \sum_{\mathbf{X}_{i}^{T} \in \mathbb{D}_{T}} n_{\mathbf{p}_{i}}(\mathcal{S}') \cdot \max \mathbf{p}_{i}(\mathcal{S}')$$
(8)

With the consensus quality defined in (8), we derive the consensus focus (CF) value to quantify the contribution of each source domain as

$$CF(\mathbb{D}_{S}^{k}) = Q(\mathcal{S}) - Q(\mathcal{S} \setminus \{\mathbb{D}_{S}^{k}\})$$
(9)

 $\operatorname{CF}(\mathbb{D}_S^k)$ describes the marginal contribution of the single source domain \mathbb{D}_S^k to the consensus quality of all source domains S. With the consensus focus value, we can assign proper weights to different source domains. For the KD3A bound (5) with an extra source domain \mathbb{D}_S^{K+1} , we compute the domain weights with two steps. First, we obtain α for \mathbb{D}_S^{K+1} as $\alpha_{K+1} = N_T / (\sum_{k=1}^K N_k + N_T)$. Then we use the consensus focus value to re-weight each original source domain as

$$\boldsymbol{\alpha}_{k}^{\text{CF}} = (1 - \boldsymbol{\alpha}_{K+1}) \cdot \frac{N_{k} \cdot \text{CF}(\mathbb{D}_{S}^{k})}{\sum_{k=1}^{K} N_{k} \cdot \text{CF}(\mathbb{D}_{S}^{k})} \qquad (10)$$

Compared with the re-weighting strategy in (7), our *Consensus Focus* has two advantages. First, the calculation of α^{CF} does not need to access the original data. Second, the re-weight operation of the *Consensus Focus* is based on the quality of consensus, which can utilize both data and label information and is sensitive to malicious domains.

BatchNorm MMD: decentralized optimization strategy of \mathcal{H} -divergence.

To get a better UMDA performance, we need to minimize the \mathcal{H} -divergence between source domains and target domain. The kernel-based MMD distance is widely used in this optimization. Existing works (Long et al. 2015; Peng et al. 2019) use the feature π extracted by the fully-connected (fc) layers to build kernel as $\kappa(\mathbf{X}^S, \mathbf{X}^T) = \langle \pi^S, \pi^T \rangle$ and the related optimization target of KD3A bound (5) is

$$\min_{h \in \mathcal{H}} \sum_{k=1}^{K+1} \alpha_k d_{\text{MMD}}(\mathbb{D}_S^k, \mathbb{D}_T)$$
(11)

However, these methods is not applicable in decentralized UMDA since the source domain data is unavailable. Besides, only using the top features from fc-layers may lose the detailed 2-D information. Therefore, we propose the *BatchNorm MMD*, which utilizes the mean and variance parameters in each BatchNorm layer to optimize the \mathcal{H} -divergence without accessing data.

BatchNorm (BN) (Ioffe and Szegedy 2015) is a widelyused normalization technique. For the feature π , Batch-Norm is expressed as $BN(\pi) = \gamma \cdot \frac{\pi - \mathbb{E}(\pi)}{\sqrt{Var(\pi)}} + \beta$, where $(\mathbb{E}(\pi), Var(\pi))$ are estimated in training process². Supposing the model contains *L* BatchNorm layers, we consider the quadratic kernel for the feature π_l of the *l*-th BN-layer, i.e. $\kappa(\mathbf{X}^S, \mathbf{X}^T) = \left(\langle \pi_l^S, \pi_l^T \rangle + \frac{1}{2} \right)^2$. The MMD distance based on this kernel is

$$d_{\text{MMD}}(\mathbb{D}_{S}^{k}, \mathbb{D}_{T}) = \|\mathbb{E}(\boldsymbol{\pi}_{l}^{k}) - \mathbb{E}(\boldsymbol{\pi}_{l}^{T})\|_{2}^{2} + \|\mathbb{E}[\boldsymbol{\pi}_{l}^{k}]^{2} - \mathbb{E}[\boldsymbol{\pi}_{l}^{T}]^{2}\|_{2}^{2}$$
(12)

With the equation $\mathbb{E}[\pi]^2 = \operatorname{Var}(\pi) + [\mathbb{E}(\pi)]^2$, all required parameters in (12) can be obtained by the parameters $(\mathbb{E}(\pi_l), \operatorname{Var}(\pi_l))$ of BN-layers in source domain models without accessing data. Based on this property, BatchNorm MMD provides a decentralized optimization strategy with two steps. First, we obtain $\{(\mathbb{E}(\pi_l^k), \operatorname{Var}(\pi_l^k))\}_{l=1}^l$ from the models on different source domains. Then, for every minibatch $\mathbf{X}^T \in \mathbb{D}_T$, we train the model *h* to optimize the domain adaptation target (11) with the following loss

$$\sum_{l=1}^{L}\sum_{k=1}^{K+1} \boldsymbol{\alpha}_{k} \left(\|\mu(\boldsymbol{\pi}_{l}^{T}) - \mathbb{E}(\boldsymbol{\pi}_{l}^{k})\|_{2}^{2} + \|\mu[\boldsymbol{\pi}_{l}^{T}]^{2} - \mathbb{E}[\boldsymbol{\pi}_{l}^{k}]^{2}\|_{2}^{2} \right)$$

where $(\pi_1^T, \ldots, \pi_L^T)$ are the features from BatchNorm layers corresponding to the input \mathbf{X}^T . In training process, We use the mean value μ on mini-batch to estimate the expectation \mathbb{E} .

The algorithm of KD3A

In the above sections, we have proposed three essential methods that work well in KD3A, and the complete algorithm of KD3A can be obtained by combining these methods, as shown in Algorithm 1. Confidence gate is the only hyper-parameter in KD3A, and should be treated carefully. If the confidence gate is too large, almost all $\mathbf{X}^T \in \mathbb{D}_L$ will be eliminated and the knowledge vote loss will not work. If too small, then the consensus quality will be reduced. Therefore, we gradually increase $g^{(t)}$ from low (e.g., 0.8) to high (e.g., 0.95) in the training process.

The settings of communication rounds r is important in decentralized training process. Since the models on different source domains have different convergence rates, we need to aggregate model r times per epoch. To perform the r-round aggregation, we uniformly divide one epoch into r stages and aggregate model after each stage. Apparently, the original Algorithm 1 is a decentralized training strategy with r = 1 and we use this setting in all experiments.

Experiments

We perform experiments on 3 datasets: (1) **Digit-5** (Zhao et al. 2020), which is a digit classification dataset including 5 domains. (2) **Office-Caltech10** (Gong et al. 2012), which contains 10 object categories from four domains. (3) **DomainNet** (Peng et al. 2019), which is a recently introduced benchmark for large-scale multi-source domain adaptation with 345 classes and six domains, i.e. Clipart (clp), Infograph (inf), Painting (pnt), Quickdraw (qdr), Real (rel) and Sketch (skt), as shown in Figure 2. Following previous settings (Peng et al. 2019), we use a 3-layer CNN as backbone for Digit-5, and use the pretrained ResNet101 for Office-Caltech10 and DomainNet. We conduct each

²Implemented with *running-mean* and *running-var* in Pytorch.

Standards	Methods	Clipart	Infograph	Painting	Quickdraw	Real	Sketch	Avg
W/o DA	Oracle	$69.3_{\pm 0.37}$	$34.5_{\pm 0.42}$	$66.3_{\pm 0.67}$	$66.8_{\pm 0.51}$	$80.1_{\pm 0.59}$	$60.7_{\pm 0.48}$	63.0
	Source-only	$47.6_{\pm 0.52}$	$13.0_{\pm 0.41}$	$38.1_{\pm 0.45}$	$13.3_{\pm 0.39}$	$51.9_{\pm 0.85}$	$33.7_{\pm 0.54}$	32.9
MMD Based	DAN	$48.4_{\pm 0.49}$	$14.8_{\pm 0.86}$	$40.2_{\pm 0.58}$	$15.3_{\pm 0.37}$	$53.9_{\pm 0.72}$	$34.0_{\pm 0.54}$	34.5
WIND Dased	M ³ SDA	$58.6_{\pm 0.53}$	$26.0_{\pm 0.89}$	$52.3_{\pm 0.55}$	$6.3_{\pm 0.58}$	$62.7_{\pm 0.51}$	$49.5_{\pm 0.76}$	42.6
Adversarial	DANN	$52.5_{\pm 0.59}$	$11.1_{\pm 0.72}$	$42.0_{\pm 0.69}$	$14.7_{\pm 0.77}$	$52.9_{\pm 0.65}$	$38.1_{\pm 0.62}$	35.2
Training	DCTN	$48.6_{\pm 0.73}$	$23.5_{\pm 0.59}$	$48.8_{\pm 0.63}$	$7.2_{\pm 0.46}$	$53.5_{\pm 0.56}$	$47.3_{\pm 0.47}$	38.2
Others	MoE	$55.8_{\pm 0.33}$	$21.3_{\pm 0.24}$	$46.2_{\pm 0.45}$	$9.2_{\pm 0.36}$	$63.3_{\pm 0.53}$	$46.3_{\pm 0.54}$	40.4
Others	DSBN	$57.2_{\pm 0.24}$	$25.6_{\pm 0.27}$	$52.3_{\pm 0.43}$	$6.5_{\pm 0.64}$	$62.7_{\pm 0.12}$	$47.6_{\pm 0.51}$	42.0
	FADA	$52.3_{\pm 0.7}$	$16.3_{\pm 0.8}$	$41.9_{\pm 0.7}$	$13.9_{\pm 0.4}$	$52.7_{\pm 0.4}$	$36.8_{\pm 0.4}$	35.7
UMDA	SHOT	$58.8_{\pm 0.47}$	$19.8_{\pm 0.51}$	$49.9_{\pm 0.42}$	$9.7_{\pm 0.43}$	$66.0_{\pm 0.38}$	$46.3_{\pm 0.37}$	41.3
	KD3A	$72.5_{\pm 0.62}$	$23.4_{\pm 0.43}$	$60.9_{\pm0.71}$	$16.4_{\pm 0.28}$	$72.7_{\pm 0.55}$	$60.6_{\pm 0.52}$	51.1

Table 1: UMDA accuracy (%) on the DomainNet dataset. Our model KD3A achieves 51.1% accuracy, significantly outperforming all other baselines. Moreover, KD3A achieves the oracle performance on two domains: clipart and sketch.



Figure 2: The large-scale dataset DomainNet. Real is a domain of high quality containing real-world images, while quickdraw is an irrelevant source domain and may cause the negative transfer.

experiment for five times and report the results with the form mean $_{\pm std}$. Due to space limitations, we mainly show results on DomainNet; more results on Digit-5 and Office-Caltech10 are provided in Appendix D.

UMDA performance

We conduct extensive comparison experiments with the following *state-of-the-art* approaches: (1) MMD based methods, i.e. deep adaptation network (DAN) (Long et al. 2015) and moment matching (M³SDA) (Peng et al. 2019). (2) Adversarial training based methods, i.e. domain adversarial neural network (DANN) (Ganin and Lempitsky 2015) and deep cocktail network (DCTN) (Xu et al. 2018). (3) Advanced decentralized UMDA methods, i.e. SHOT (Liang et al. 2020) and FADA (Peng et al. 2020). (4) Other methods that use similar components to our KD3A. MoE (Guo et al.



Figure 3: The ablation study of KD3A. Results show that *Knowledge Vote*, *Consensus Focus* and *BatchNorm MMD* all contribute to the UMDA performance in all target domains.

2018) utilizes weighted knowledge distillation to create pseudo labels for target domain and DSBN (Chang et al. 2019) proposes a domain-specific BatchNorm. These two components are similar to *Knowledge Vote* and *Batchnorm MMD*, so we take them into comparison. We also consider two baselines without domain adaptation, i.e. oracle and source-only. Oracle directly performs supervised learning on target domains and source-only naively combines source domains to train a single model. The results are presented in Table 1. In general, our KD3A outperforms all the baselines by a large margin. Moreover, KD3A achieves the oracle performance on clipart and sketch.

To evaluate the improvement from each component, We perform **ablation study** for KD3A, as shown in Figure 3. *Knowledge Vote, Consensus Focus* and *Batchnorm MMD* are all able to improve the accuracy, while most contributions are from *Knowledge Vote*, which indicates our KD3A can

	H-divergence	Info gain	Consensus focus	Domain drop
IR-qdr	57.9	57.7	58.1	58.3
MA-15	50.5	50.5	52.1	
MA-30	49.8	48.9	51.1	50.7
MA-50	47.6	46.3	50.6	

Table 2: UMDA accuracy (%) with irrelevant and malicious domains. IR-qdr means to use the quickdraw as the irrelevant source domain, while MA-m means to create a malicious source domain with m% mislabeled data. With consensus focus, our KD3A is robust to negative transfer.



Figure 4: Weights assigned to the irrelevant and malicious domains in the training process. Our consensus focus can identify these bad domains with the low weights.

also perform well on those tasks without BatchNorm.

Robustness to negative transfer

We create irrelevant and malicious source domains on DomainNet and conduct experiments to show that with *Consensus Focus*, our KD3A is robust to negative transfer.

Since quickdraw is very different from other domains, and all models perform extremely bad on it, we view quickdraw as the irrelevant domain, denoted by **IR-qdr**. To create malicious domains, we perform poisoning attack (Bagdasaryan et al. 2020) on the high-quality domain real with m% wrong labels, denoted by **MA-m**. For the irrelevant domain IRqdr, we use the remained five domains as target domains and conduct KD3A on them separately. Then, we report the mean weight α assigned to IR-qdr with our *Consensus Focus* as well as the mean accuracy of UMDA. For the malicious domain MA-m, we conduct the same process on the remained four domains except for quickdraw. Then we report the same results as in IR-qdr.

We consider 2 advanced weighting strategies for comparison, that is, \mathcal{H} -divergence re-weighting in (7) and the *Info Gain* in FADA (Peng et al. 2020). As baselines, we conduct the same UMDA process with the bad domain dropped. According to the results provided in Table 2 and Figure 4, we can get the following insights: (1) The negative transfer occurs with IR-qdr and MA-(30,50) since the domain drop baseline outperforms the others. (2) The three weighting strategies are robust to the irrelevant domain since they

r	0.2	0.5	1	2	10	100
FADA	32.2	32.3	32.9	32.9	33.1	35.7
KD3A	50.5	50.9	51.1	51.3	51.3	52.0

Table 3: UMDA accuracy (%) with different communication rounds r for our KD3A and FADA. KD3A achieves good performance with low communication cost (e.g., $r \le 1$).



Figure 5: The gradient leakage attack on decentralized training strategy. KD3A is robust to this attack while FADA causes the privacy leakage.

all assign low weights to IR-qdr. (3) *Consensus Focus* outperforms other strategies in malicious domains since it assigns extremely low weights to the bad domain (i.e. 5% for MA-30), while other strategies can not identify the malicious domain. Moreover, our KD3A can use the correct information of less malicious domains (i.e. MA-(15,30)) and achieves better performance than baseline.

Communication efficiency and privacy security

To evaluate the communication efficiency, We conduct experiments with different communication rounds r and use the advanced FADA as comparison. The results in Table 3 show the following properties: (1) Due to the adversarial training strategy, FADA works under huge communication rounds (i.e. r = 100). (2) Our KD3A works under the low communication cost with r = 1, brings a 100 \times communication reduction. (3) KD3A is robust to communication rounds. For example, the accuracy only drops 0.9% when r decreases from 100 to 1. Moreover, we consider the extreme cases where we synchronize models every 2 and 5 epochs, i.e. r = 0.5 and 0.2. In these cases, FADA fails behind the source-only baseline while our KD3A can still achieve state-of-the-art results. Due to the low communication cost, our KD3A is robust to the advanced gradient leakage attack (Zhu et al. 2019), as shown in Figure 5.

Conclusions

In this paper, we discuss the existing problems in multisource decentralized domain adaptation and propose an effective approach KD3A to address these problems. The main idea of KD3A is to perform domain adaptation through the knowledge distillation without accessing the source domain data. Extensive experiments on the large-scale DomainNet demonstrate our KD3A outperforms other *state-of-the-art* UMDA approaches and is robust to negative transfer.

Ethics statement

We address a decentralized domain adaptation paradigm to solve the domain shift problem under the privacy-preserving policy. We offer the possible influence of our work from three aspects: fundamental theory impact, machine learning application impact, and social impact.

For the fundamental theory impact, we analyze the knowledge distillation in domain adaptation from a theoretical perspective and derive a new generalization bound for it. The new theoretical bound will inspire further studies of the following two challenges: how to theoretically describe the knowledge quality and how to bridge the domain gap without accessing data.

For the machine learning application impact, we evaluate our paradigm under the large-scale real-world datasets and show it can be applied to non-laboratory environments such as data markets.

For the social impact, our work owns two properties: decentralization and privacy protection. Therefore, it is friendly to the data providers and the governments that pay attention to the privacy-preserving policy, e.g., the general data protection regulation in the European Union.

References

Bagdasaryan, E.; Veit, A.; Hua, Y.; Estrin, D.; and Shmatikov, V. 2020. How To Backdoor Federated Learning. In Chiappa, S.; and Calandra, R., eds., *The 23rd International Conference on Artificial Intelligence and Statistics, AISTATS 2020, 26-28 August 2020, Online [Palermo, Sicily, Italy]*, volume 108 of *Proceedings of Machine Learning Research,* 2938–2948. PMLR.

Ben-David, S.; Blitzer, J.; Crammer, K.; Kulesza, A.; et al. 2010. A theory of learning from different domains. *Mach. Learn.* 79(1-2): 151–175.

Chang, W.; You, T.; Seo, S.; Kwak, S.; and Han, B. 2019. Domain-Specific Batch Normalization for Unsupervised Domain Adaptation. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019,* 7354–7362. Computer Vision Foundation / IEEE.

Chen, Y.; Song, S.; Li, S.; and Wu, C. 2020. A Graph Embedding Framework for Maximum Mean Discrepancy-Based Domain Adaptation Algorithms. *IEEE Trans. Image Process.* 29: 199–213.

Ganin, Y.; and Lempitsky, V. S. 2015. Unsupervised Domain Adaptation by Backpropagation. In Bach, F. R.; and Blei, D. M., eds., *Proceedings of the 32nd International Conference on Machine Learning, ICML 2015, Lille, France, 6-11 July 2015*, volume 37 of *JMLR Workshop and Conference Proceedings*, 1180–1189. JMLR.org.

Gong, B.; Shi, Y.; Sha, F.; and Grauman, K. 2012. Geodesic flow kernel for unsupervised domain adaptation. In 2012 *IEEE Conference on Computer Vision and Pattern Recognition, Providence, RI, USA, June 16-21, 2012, 2066–2073.* IEEE Computer Society. Guo, J.; Shah, D. J.; Barzilay, R.; et al. 2018. Multi-Source Domain Adaptation with Mixture of Experts. In Riloff, E.; Chiang, D.; Hockenmaier, J.; and Tsujii, J., eds., *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing, Brussels, Belgium, October 31 - November 4, 2018*, 4694–4703. Association for Computational Linguistics.

Hinton, G. E.; Vinyals, O.; Dean, J.; et al. 2015. Distilling the Knowledge in a Neural Network. *CoRR* abs/1503.02531.

Ioffe, S.; and Szegedy, C. 2015. Batch Normalization: Accelerating Deep Network Training by Reducing Internal Covariate Shift. In Bach, F. R.; and Blei, D. M., eds., *Proceedings of the 32nd International Conference on Machine Learning, ICML 2015, Lille, France, 6-11 July 2015*, volume 37 of *JMLR Workshop and Conference Proceedings*, 448–456. JMLR.org.

Konecný, J.; McMahan, H. B.; Yu, F. X.; Richtárik, P.; et al. 2016. Federated Learning: Strategies for Improving Communication Efficiency. *CoRR* abs/1610.05492.

Liang, J.; Hu, D.; Feng, J.; et al. 2020. Do We Really Need to Access the Source Data? Source Hypothesis Transfer for Unsupervised Domain Adaptation. *CoRR* abs/2002.08546.

Long, M.; Cao, Y.; Wang, J.; and Jordan, M. I. 2015. Learning Transferable Features with Deep Adaptation Networks. In Bach, F. R.; and Blei, D. M., eds., *Proceedings of the 32nd International Conference on Machine Learning, ICML 2015, Lille, France, 6-11 July 2015*, volume 37 of *JMLR Workshop and Conference Proceedings*, 97–105. JMLR.org.

Long, M.; Cao, Z.; Wang, J.; and Jordan, M. I. 2018. Conditional Adversarial Domain Adaptation. In Bengio, S.; Wallach, H. M.; Larochelle, H.; Grauman, K.; Cesa-Bianchi, N.; and Garnett, R., eds., Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, 3-8 December 2018, Montréal, Canada, 1647–1657.

McMahan, B.; Moore, E.; Ramage, D.; Hampson, S.; and y Arcas, B. A. 2017. Communication-Efficient Learning of Deep Networks from Decentralized Data. In Singh, A.; and Zhu, X. J., eds., *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics, AIS-TATS 2017, 20-22 April 2017, Fort Lauderdale, FL, USA*, volume 54 of *Proceedings of Machine Learning Research*, 1273–1282. PMLR.

Meng, Z.; Li, J.; Gong, Y.; and Juang, B. 2018. Adversarial Teacher-Student Learning for Unsupervised Domain Adaptation. In 2018 IEEE International Conference on Acoustics, Speech and Signal Processing, ICASSP 2018, Calgary, AB, Canada, April 15-20, 2018, 5949–5953. IEEE. doi:10.1109/ICASSP.2018.8461682. URL https://doi.org/10.1109/ICASSP.2018.8461682.

Pan, S. J.; and Yang, Q. 2010. A Survey on Transfer Learning. *IEEE Transactions on Knowledge and Data Engineering* 22(10): 1345–1359.

Peng, X.; Bai, Q.; Xia, X.; et al. 2019. Moment Matching for Multi-Source Domain Adaptation. In 2019 IEEE/CVF

International Conference on Computer Vision, ICCV 2019, Seoul, Korea (South), October 27 - November 2, 2019, 1406–1415. IEEE.

Peng, X.; Huang, Z.; Zhu, Y.; and Saenko, K. 2020. Federated Adversarial Domain Adaptation. In 8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020. OpenReview.net.

Ruder, S.; Ghaffari, P.; Breslin, J. G.; et al. 2017. Knowledge Adaptation: Teaching to Adapt. *CoRR* abs/1702.02052.

Saito, K.; Watanabe, K.; Ushiku, Y.; and Harada, T. 2018. Maximum Classifier Discrepancy for Unsupervised Domain Adaptation. In 2018 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2018, Salt Lake City, UT, USA, June 18-22, 2018, 3723–3732. IEEE Computer Society.

Tzeng, E.; Hoffman, J.; Zhang, N.; Saenko, K.; and Darrell, T. 2014. Deep Domain Confusion: Maximizing for Domain Invariance. *CoRR* abs/1412.3474.

Wang, Z.; Song, M.; Zhang, Z.; Song, Y.; Wang, Q.; and Qi, H. 2019. Beyond Inferring Class Representatives: User-Level Privacy Leakage From Federated Learning. In 2019 IEEE Conference on Computer Communications, INFOCOM 2019, Paris, France, April 29 - May 2, 2019, 2512–2520. IEEE.

Xie, Q.; Luong, M.; Hovy, E. H.; and Le, Q. V. 2020. Self-Training With Noisy Student Improves ImageNet Classification. In 2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020, 10684–10695. IEEE.

Xu, R.; Chen, Z.; Zuo, W.; Yan, J.; and Lin, L. 2018. Deep Cocktail Network: Multi-Source Unsupervised Domain Adaptation With Category Shift. In 2018 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2018, Salt Lake City, UT, USA, June 18-22, 2018, 3964–3973. IEEE Computer Society.

Yan, H.; Ding, Y.; Li, P.; et al. 2017. Mind the Class Weight Bias: Weighted Maximum Mean Discrepancy for Unsupervised Domain Adaptation. In 2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017, 945–954. IEEE Computer Society.

Zhang, H.; Cissé, M.; Dauphin, Y. N.; and Lopez-Paz, D. 2017. mixup: Beyond Empirical Risk Minimization. *CoRR* abs/1710.09412. URL http://arxiv.org/abs/1710.09412.

Zhang, K.; Gong, M.; Schölkopf, B.; et al. 2015. Multi-Source Domain Adaptation: A Causal View. In Bonet, B.; and Koenig, S., eds., *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence, January 25-30, 2015, Austin, Texas, USA*, 3150–3157. AAAI Press.

Zhang, Y.; Xiang, T.; Hospedales, T. M.; and Lu, H. 2018. Deep Mutual Learning. In 2018 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2018, Salt Lake City, UT, USA, June 18-22, 2018, 4320–4328. IEEE Computer Society. Zhao, H.; Zhang, S.; Wu, G.; Costeira, J. P.; Moura, J. M. F.; and Gordon, G. J. 2018. Multiple Source Domain Adaptation with Adversarial Learning. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Workshop Track Proceedings.* OpenReview.net.

Zhao, S.; Wang, G.; Zhang, S.; Gu, Y.; Li, Y.; Song, Z.; Xu, P.; Hu, R.; Chai, H.; and Keutzer, K. 2020. Multi-Source Distilling Domain Adaptation. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020, 12975– 12983. AAAI Press.*

Zhu, L.; Liu, Z.; Han, S.; et al. 2019. Deep Leakage from Gradients. In Wallach, H. M.; Larochelle, H.; Beygelzimer, A.; d'Alché-Buc, F.; Fox, E. B.; and Garnett, R., eds., Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, 8-14 December 2019, Vancouver, BC, Canada, 14747–14756.

Appendix

Appendix A

For the extra source domain $\mathbb{D}_{S}^{K+1} = \{(\mathbf{X}_{i}^{T}, \mathbf{p}_{i})\}_{i=1}^{N_{T}}$, we claim that the minimizing knowledge distillation loss $L^{\mathrm{kd}}(\mathbf{X}_{i}^{T}, q) = D_{\mathrm{KL}}(\mathbf{p}_{i} || q(\mathbf{X}_{i}^{T}))$ equals to optimize the task risk $\epsilon_{\mathbb{D}_{S}^{K+1}}(h) = \Pr_{(\mathbf{X}, \mathbf{p}) \sim \mathbb{D}_{S}^{K+1}}[h(\mathbf{X}) \neq \arg_{c} \max \mathbf{p}_{c}]$. The proof is as follows.

First, we prove that $\forall c = 1, \ldots, C$,

$$|q(\mathbf{X}_i^T))_c - \mathbf{p}_{i,c}| \le \sqrt{\frac{1}{2}D_{\mathrm{KL}}(\mathbf{p}_i \| q(\mathbf{X}_i^T))}$$
(1)

The widely used **Pinsker's inequality** states that, if P and Q are two probability distributions on a measurable space (\mathbf{X}, Σ) , then

$$\delta(P,Q) \le \sqrt{\frac{1}{2}} D_{\mathrm{KL}}(P \| Q)$$

where

 $\delta(P,Q) = \sup\{|P(\mathbf{A}) - Q(\mathbf{A})| | \mathbf{A} \in \Sigma \text{ is a measurable event.}\}$ In our situation, we choose the event \mathbf{A} as the probability of classifying the input \mathbf{X}_i^T into class c, and the related probability under P, Q is $\mathbf{p}_{i,c}$ and $q(\mathbf{X}_i^T))_c$. With **Pinsker's inequality**, it is easy to prove (1).

Since the inequality (1) holds for all class c, minimizing the knowledge distillation loss will make $q(\mathbf{X}_i^T) \to \mathbf{p}_i$, that is, $\epsilon_{\mathbb{D}_s^{K+1}}(h) \to 0$.

Appendix B

Theorem 2 *The generalization bound for knowledge distillation. Let* \mathcal{H} *be the model space and* $\epsilon_{\mathbb{D}_{S}^{K+1}}(h)$ *be the task risk of the extra domain* \mathbb{D}_{S}^{K+1} *. Then* $\forall h \in \mathcal{H}$ *, we have:*

$$\epsilon_{\mathbb{D}_T}(h) \le \epsilon_{\mathbb{D}_S^{K+1}}(h) + d_{\mathcal{H}}(\mathbb{D}_S^{K+1}, \mathbb{D}_T) + C_1 \qquad (2)$$

proof:

Following the Theorem 2 in Ben-David et al. (2010), for the source domain \mathbb{D}_{S}^{K+1} and the target domain \mathbb{D}_{T} , for every $h \in \mathcal{H}$, we have

$$\epsilon_{\mathbb{D}_T}(h) \le \epsilon_{\mathbb{D}_S^{K+1}}(h) + \frac{1}{2} d_{\mathcal{H} \Delta \mathcal{H}}(\mathbb{D}_S^{K+1}, \mathbb{D}_T) + \lambda \qquad (3)$$

where λ is constant of the optimal model on the source domain and the target domain as $\lambda = \min_{h \in \mathcal{H}} \epsilon_{\mathbb{D}_{S}^{K+1}}(h) + \epsilon_{\mathbb{D}_{T}}(h)$. Utilize the inequality (12) in Ganin and Lempitsky (2015), we have

$$\frac{1}{2}d_{\mathcal{H}\Delta\mathcal{H}}(\mathbb{D}_{S}^{K+1},\mathbb{D}_{T}) \leq d_{\mathcal{H}}(\mathbb{D}_{S}^{K+1},\mathbb{D}_{T})$$
(4)

Since we use the finite N_T samples to empirically estimate the $\epsilon_{\mathbb{D}_S^{K+1}}(h)$ and $d_{\mathcal{H}}(\mathbb{D}_S^{K+1}, \mathbb{D}_T)$, then for all $0 < \delta < 1$, with probability at least $1 - \delta$, the error between the groundtruth and our estimation holds the following inequality:

$$\epsilon_{\mathbb{D}_{S}^{K+1}}(h) \leq \hat{\epsilon}_{\mathbb{D}_{S}^{K+1}}(h) + \sqrt{\frac{4}{N_{T}}} \left(d\log\frac{2eN_{T}}{d} + \log\frac{4}{\delta}\right)$$
$$d_{\mathcal{H}}(\mathbb{D}_{S}^{K+1}, \mathbb{D}_{T}) \leq \hat{d}_{\mathcal{H}}(\mathbb{D}_{S}^{K+1}, \mathbb{D}_{T}) + 4\sqrt{\frac{d\log(2N_{T} + \log(\frac{2}{\delta}))}{N_{T}}}$$
(5)

where d is the VC-dimension of model space \mathcal{H} .

Substituting (4), (5) into (2), we can get one selection for the constant C_1 as

$$C_1 = \lambda + \sqrt{\frac{4}{N_T} \left(d\log\frac{2eN_T}{d} + \log\frac{4}{\delta}\right)} + 4\sqrt{\frac{d\log(2N_T + \log(\frac{2}{\delta}))}{N_T}}$$
(6)

In addition, since $\epsilon_{\mathbb{D}_S^{K+1}}(h)$ and $\epsilon_{\mathbb{D}_T}(h)$ shares the same input space, we have $d_{\mathcal{H}}(\mathbb{D}_S^{K+1},\mathbb{D}_T) = 0$. With this property, we can get another form of constant C_1 with the following inequality

$$\epsilon_{\mathbb{D}_T}(h) \le \epsilon_{\mathbb{D}_S^{K+1}}(h) + \sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_T}(h) - \epsilon_{\mathbb{D}_S^{K+1}}(h)|$$
(7)

where $\sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_T}(h) - \epsilon_{\mathbb{D}_S^{K+1}}(h)|$ is the task risk gap between the target domain \mathbb{D}_T and the knowledge distillation domain \mathbb{D}_S^{K+1} . Substituting (5) into (7), we can get C_1 as

$$C_{1} = \sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_{T}}(h) - \epsilon_{\mathbb{D}_{S}^{K+1}}(h)|$$

$$\leq \sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_{T}}(h) - \hat{\epsilon}_{\mathbb{D}_{S}^{K+1}}(h)| + \sqrt{\frac{4}{N_{T}} (d \log \frac{2eN_{T}}{d} + \log \frac{4}{\delta})}$$

(8)

Combining (8) and (6), we can get the knowledge distillation bound with the following form for C_1 :

$$C_{1} = \min\{ \lambda + \sqrt{\frac{4}{N_{T}} (d \log \frac{2eN_{T}}{d} + \log \frac{4}{\delta})} + 4\sqrt{\frac{d \log(2N_{T} + \log(\frac{2}{\delta})}{N_{T}}}, \\ \sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_{T}}(h) - \hat{\epsilon}_{\mathbb{D}_{S}^{K+1}}(h)| + \sqrt{\frac{4}{N_{T}} (d \log \frac{2eN_{T}}{d} + \log \frac{4}{\delta})} \}$$

$$(9)$$

Appendix C

• •

Proposition 1 The knowledge distillation bound (2) is a tighter bound, if the task risk gap between the target domain \mathbb{D}_T and the knowledge distillation domain \mathbb{D}_S^{K+1} is small enough, i.e. $\sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_T}(h) - \epsilon_{\mathbb{D}_S^{K+1}}(h)| \to 0.$

Since $\epsilon_{\mathbb{D}_{S}^{K+1}}(h)$ and $\epsilon_{\mathbb{D}_{T}}(h)$ shares the same input space, we have $d_{\mathcal{H}}(\mathbb{D}_{S}^{K+1}, \mathbb{D}_{T}) = 0$. With the strong constraint $\sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_{T}}(h) - \epsilon_{\mathbb{D}_{S}^{K+1}}(h)| \to 0$, for all $\epsilon \ge 0$, $\forall h \in \mathcal{H}$, we have

$$\epsilon_{\mathbb{D}_T}(h) \le \epsilon_{\mathbb{D}_S^{K+1}}(h) + \epsilon \tag{10}$$

Then, it is apparent that the generalization bound is a tighter bound than others.

Moreover, since the condition $\sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_T}(h) - \epsilon_{\mathbb{D}_S^{K+1}}(h)| \to 0$ is too strong to satisfy, we can derive a looser constraint with the original bound in Theorem 1:

$$\epsilon_{\mathbb{D}_T}(h) \le \epsilon_{\mathbb{D}_{\tilde{S}}}(h) + d_{\mathcal{H}}(\mathbb{D}_{\tilde{S}}, \mathbb{D}_T) + C_0 \tag{11}$$

where $C_0 = \lambda(\mathbb{D}_{\tilde{S}}, \mathbb{D}_T)$ is the constant of the optimal model on the mixed source domain $\mathbb{D}_{\tilde{S}}$ and the target domain \mathbb{D}_T .

Methods	mt	mm	SV	syn	usps	Avg
Oracle	$99.5_{\pm 0.08}$	$95.4_{\pm 0.15}$	$92.3_{\pm 0.14}$	$98.7_{\pm 0.04}$	$99.2_{\pm 0.09}$	97.0
Source-only	$92.3_{\pm 0.91}$	$63.7_{\pm 0.83}$	$71.5_{\pm 0.75}$	$83.4_{\pm 0.79}$	$90.71_{\pm 0.54}$	80.3
DAN	$96.3_{\pm 0.54}$	$63.8_{\pm 0.71}$	$72.5_{\pm 0.72}$	$85.4_{\pm 0.77}$	$94.2_{\pm 0.87}$	82.4
M ³ SDA	$98.4_{\pm 0.68}$	$72.8_{\pm 1.13}$	$81.3_{\pm 0.86}$	$89.6_{\pm 0.56}$	$96.2_{\pm 0.81}$	87.7
DANN	$97.6_{\pm 0.75}$	$71.3_{\pm 0.56}$	$63.5_{\pm 0.79}$	$85.4_{\pm 0.84}$	$92.33_{\pm 0.85}$	82.1
DCTN	$96.2_{\pm 0.82}$	$70.5_{\pm 1.24}$	$77.6_{\pm 0.41}$	$86.8_{\pm 0.78}$	$92.8_{\pm 0.27}$	84.8
MoE	$97.1_{\pm 0.44}$	$70.8_{\pm 0.42}$	$78.7_{\pm 0.55}$	$87.6_{\pm 0.35}$	$95.2_{\pm 0.17}$	85.8
DSBN	$97.2_{\pm 0.34}$	$71.6_{\pm 0.22}$	$77.9_{\pm 0.53}$	$88.7_{\pm 0.54}$	$96.1_{\pm 0.17}$	86.3
FADA	$92.5_{\pm 0.9}$	$64.5_{\pm 0.7}$	$63.5_{\pm 0.3}$	$82.8_{\pm 0.5}$	$91.7_{\pm 1}$	86.2
SHOT	$98.2_{\pm 0.37}$	$80.2_{\pm 0.41}$	84.5 ± 0.32	$91.1_{\pm 0.23}$	$97.1_{\pm 0.28}$	90.2
KD3A	$99.2_{\pm 0.12}$	$87.3_{\pm 0.23}$	$85.6_{\pm 0.17}$	$89.4_{\pm 0.28}$	$98.5_{\pm 0.25}$	92.0

Table 4: UMDA accuracy (%) on the DigitFive. Our model KD3A achieves 92.0% accuracy and outperforms all other baselines.

Methods	А	С	D	W	Avg
Oracle	$99.7_{\pm 0.18}$	$98.4_{\pm 0.25}$	$99.8_{\pm 0.04}$	$99.7_{\pm 0.14}$	99.4
Source-only	$88.7_{\pm 0.11}$	$85.4_{\pm 0.03}$	$98.2_{\pm 0.05}$	$99.1_{\pm 0.09}$	92.9
DAN	$91.6_{\pm 0.04}$	$89.2_{\pm 0.11}$	$99.1_{\pm 0.12}$	$99.5_{\pm 0.07}$	94.8
M ³ SDA	$94.5_{\pm 0.08}$	$92.2_{\pm 0.03}$	$99.2_{\pm 0.06}$	$99.5_{\pm 0.06}$	96.4
DANN	$92.6_{\pm 0.05}$	$91.3_{\pm 0.06}$	$99.1_{\pm 0.09}$	$99.4_{\pm 0.04}$	95.6
DCTN	$93.2_{\pm 0.02}$	$91.5_{\pm 0.04}$	$99.1_{\pm 0.11}$	$99.2_{\pm 0.08}$	95.7
MoE	$94.1_{\pm 0.03}$	$95.8_{\pm 0.07}$	$99.1_{\pm 0.05}$	$99.6_{\pm 0.05}$	97.2
DSBN	$93.2_{\pm 0.06}$	$91.6_{\pm 0.09}$	$98.9_{\pm 0.05}$	$99.3_{\pm 0.04}$	95.8
FADA	$84.2_{\pm 0.5}$	$88.7_{\pm 0.5}$	$87.1_{\pm 0.6}$	$88.1_{\pm 0.4}$	87.1
SHOT	$96.4_{\pm 0.07}$	$96.2_{\pm 0.11}$	$98.5_{\pm 0.02}$	$99.7_{\pm 0.03}$	97.7
KD3A	$97.4_{\pm 0.08}$	$96.4_{\pm 0.11}$	$98.4_{\pm 0.08}$	$99.7_{\pm 0.02}$	97.9

Table 5: UMDA accuracy (%) on the Office-Caltech10.

To make the knowledge distillation bound (2) becomes a tighter bound than (11), the task risk gap should satisfy the following inequality

$$\epsilon_{\mathbb{D}_{S}^{K+1}}(h) + \sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_{T}}(h) - \epsilon_{\mathbb{D}_{S}^{K+1}}(h)|$$

$$\leq \epsilon_{\mathbb{D}_{\tilde{S}}}(h) + d_{\mathcal{H}}(\mathbb{D}_{\tilde{S}}, \mathbb{D}_{T}) + \lambda(\mathbb{D}_{\tilde{S}}, \mathbb{D}_{T})$$
(12)

Then we can get a looser constraint for the task risk gap as follows

$$\sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_{T}}(h) - \epsilon_{\mathbb{D}_{S}^{K+1}}(h)| \leq \sup_{h \in \mathcal{H}} |\epsilon_{\mathbb{D}_{\tilde{S}}}(h) - \epsilon_{\mathbb{D}_{S}^{K+1}}(h)| + d_{\mathcal{H}}(\mathbb{D}_{\tilde{S}}, \mathbb{D}_{T}) + \lambda(\mathbb{D}_{\tilde{S}}, \mathbb{D}_{T})$$
(13)

The tighter condition (13) for the knowledge distillation bound has the following meaning: to make the consensus knowledge work, we should control the task risk gap not too large with three components : (1) The task risk gap between the mixed source domains and the knowledge distillation domain. (2) The \mathcal{H} -divergence between the mixed source domains and the target domain. (3) The optimal task risk between the mixed source domains and the target domain.

Appendix D

We perform UMDA on those datasets with multiple domains. During experiments, we choose one domain as the target domain, and use the remained domains as source domains. Finally, we report the average UMDA results among all domains. In this section, we report the experiment results on **DigitFive** and **Office-Caltech10**. Digit-Five is a digit classification dataset including MNIST (mt), MNISTM(mm), SVHN (sv), Synthetic (syn), and USPS (up). Office-Caltech10 contains 10 object categories from four domains, i.e. Amazon (A), Caltech (C), DSLR (D).

Layer	Configuration
1	2D Convolution with kernel size 5*5 and output feature channels 64
2	BatchNorm, ReLU, MaxPool
3	2D Convolution with kernel size 5*5 and output feature channels 64
4	BatchNorm, ReLU, MaxPool
5	2D Convolution with kernel size 5*5 and output feature channels 128
6	BatchNorm, ReLU
7	Fully connection layer with output channels 10
8	Softmax

Table 6: The backbone for DigitFive.

and Webcam (W). The results on Table 4,5 show that our KD3A outperforms other UMDA methods and advanced decentralized UMDA methods.

Implementation details

The code, with which the most important results can be reproduced, is available at Github³. We also provide the code as well as the detailed documentation in "SourceCode.zip". In this section, we discuss the implementation details. Following previous settings (Peng et al. 2019), we use a 3layer CNN as backbone for DigitFive, as shown in Table 6, and use the pretrained ResNet101 for Office-Caltech10 and DomainNet. In all method comparison experiments, the backbones and training epochs are set to same. For DigitFive and Office-Caltech10, we train the model with the batchsize 64 and the total epoch 50. For DomainNet, we train the model with a mini batchsize 48 and the total epoch 80. In each epoch, we randomly select 30000 images from each domain and perform training, which makes each source domain equally important in sample size. In training process, We use the SGD as optimizer and take the cosine schedule to decay learning rate from high (i.e. 0.05 for Digit5 and 0.002 for Office-Caltech10 and DomainNet) to zero. For data augmentation strategies, we choose the widely-used mixup strategy (Zhang et al. 2017) and simply set $\beta = 2$ in all experiments.

³github.com/AAAI2021-255/KD3A