

# Quantum Entropic Causal Inference

Mohammad Ali Javidian, Vaneet Aggarwal, Fanglin Bao, Zubin Jacob

*School of Electrical and Computer Engineering*

*Purdue University*

{mjavidia,vaneet,baof,zjacob}@purdue.edu

## Abstract

As quantum computing and networking nodes scale up, important open questions arise on the causal influence of various sub-systems on the total system performance. A direct generalization of the existing causal inference techniques to the quantum domain is not possible due to super-position and entanglement. We put forth a new theoretical framework for merging quantum information science and causal inference by exploiting entropic principles. First, we build the fundamental connection between the celebrated quantum marginal problem and entropic causal inference. Second, inspired by the definition of geometric quantum discord, we fill the gap between classical conditional probabilities and quantum conditional density matrices. These fundamental theoretical advances are exploited to develop a scalable algorithmic approach for quantum entropic causal inference. We apply our proposed framework to an experimentally relevant scenario of identifying message senders on quantum noisy links. This successful inference on a synthetic quantum dataset can lay the foundations of identifying originators of malicious activity on future multi-node quantum networks. We unify classical and quantum causal inference in a principled way paving the way for future applications in quantum computing and networking.

## I. INTRODUCTION

The problem of determining causal relations in quantum systems has been gaining attention (Gill, 2014; Pienaar and Brukner, 2015; Allen et al., 2017), and new algorithms for quantum causal discovery have been designed (Fitzsimons et al., 2015; Ried et al., 2015; Giarmatzi, 2019; Chiribella and Ebler, 2019). However, none of these methods can be used without interventions from an experimentalist. In other words, they infer a causal model based on both observational and interventional data. Inferring causal relationships from observational data alone is a challenging task, and (Chaves et al., 2014a,b, 2015) made initial attempts for this problem using information theoretical generalization of Bell's inequalities and causal directed acyclic graphs (DAGs) in the quantum domain. Unfortunately, their approach does not differentiate between statistically equivalent DAGs, and in particular, cannot determine causal direction between two quantum systems since the two DAGs  $X \rightarrow Y$  and  $X \leftarrow Y$  are statistically equivalent where  $X$  and  $Y$  are two quantum systems. In this paper, we address the fundamental causal inference




Fig. 1. We develop a theoretical framework for quantum causality. We derive the conditions for various sub-systems of a large quantum system to causally influence each other.

problem that involves only two quantum systems  $X$  and  $Y$ , and is the first work to consider such a problem without any interventional data (Figure 1).

Classical statistics are not adequate for identification of cause–effect relations in quantum systems due to accessibility of a richer spectrum of causal relations in quantum scenarios. This problem is of both fundamental and practical interest since the characterization and benchmarking of quantum systems is intractable as they scale up. We emphasize that time series data is unavailable for quantum systems since the measurement process fundamentally alters the time evolution of quantum distributions. Thus quantum causal inference approaches can usher in a new generation of algorithms for tomographic reconstruction of the macroscopic wavefunction and optimizing connectivity of large engineered qubit systems, the reliable broadcasting of information across quantum networks, and speed-up of classical causal inference algorithms on quantum computers.

In this paper, we introduce a theoretical framework to merge quantum information science with causal inference using entropic principles. Classically, it has been proposed and tested that minimization of the information entropy of exogenous variables identifies the causal direction (Kocaoglu et al., 2017a,b). We will provide the first generalization of this result to the quantum domain. We emphasize that causal inference using entanglement entropy is a fundamentally new approach that also reduces to the classical causal inference method as expected. Our main contributions are as follows:

1. We show the connection between the celebrated quantum marginal problem and entropic causal inference. One of the fundamental problems in quantum information theory is characterizing the set of possible density matrices given the marginals, known as the *quantum marginal problem* (Zeng et al., 2019) which is also known as the  $N$ -representability problem in quantum chemistry (Klyachko, 2006; Liu et al., 2007). The general problem is of interest in many-body quantum simulation but is computationally intractable, even on a quantum computer (Liu, 2006). The simplest form of the quantum marginal problem can be stated as following: given density matrices

$\rho_A$  and  $\rho_B$ , the goal is to find the set of all density matrices  $\rho_{AB}$  such that  $\rho_A$  and  $\rho_B$  are reduced densities of  $\rho_{AB}$ . In this paper, we consider a natural question for the least entropy element of this set, which is the counterpart of the minimum-entropy coupling problem in the classical information theory. Although this problem is NP-hard in general, we adopt heuristic classical algorithms in the literature to the quantum domain for solving this problem. We formulate and numerically solve the *minimum-entropy quantum marginal* problem as an optimization problem (Section III-A), and we propose a scalable greedy minimization algorithm, as a counterpart of its classical version, to solve this problem in Section III-B. We believe this new methodology can help lower the barrier for information and quantum theory research community to solve the problem of dimension-reduction of stochastic processes,  $N$ -representability problem, among others.

2. We exploit a geometric measure of quantum discord to build our framework of entropic causal inference. In quantum information theory, *quantum discord* is a measure of nonclassical correlations between two subsystems of a quantum system. However, the quantum discord between two quantum systems is not trivial to calculate, and except for some special classes of states there is no closed form solution for quantum discord. To overcome this difficulty, (Dakić et al., 2010) introduced *geometric quantum discord* that is based on the Hilbert-Schmidt distance between the density matrix  $\rho_{AB}$  and its closest classical state. For this purpose, conditional density matrices for single qubits have been used to estimate *geometric discord* in the literature. We define the *instance conditional density matrices* as the extension of the conditional density matrices for a given joint density matrix  $\rho_{XY}$ , as the reduced density matrix  $\rho_X$  given the measurement  $Y = |y\rangle$  of the quantum system  $Y$ , denoting by  $\rho_{X|Y=|y\rangle}$  in Section IV-A. We show the crucial role of instance conditional density matrices in solving the quantum entropic causal inference.

3. Inferring causality from observational data alone is one of the most important and challenging problems in statistical inference. We propose a greedy algorithm, called QECI, for quantum entropic causal inference in Section IV-B. Our method unifies classical and quantum causal inference in a principled way. We discuss computational analysis and rotational invariance property of QECI in Section V.

4. We put forth an experimental scheme that can be used to confront our theoretical framework. We consider a minimalistic model of an unknown message (possibly encrypted) with unknown origin in a two-node quantum network. The two nodes are connected by a noisy channel (e.g., optical fiber) with unknown model of quantum disturbance. We prove that only using the joint density matrix, we can identify the originator of the message. To verify the validation of QECI, we use realistic quantum noisy links such as quantum symmetric channel and depolarizing channel (valid for quantum networking and quantum communications) (Section VI). Moreover, we show that entropic causal inference technique cannot be mapped directly from quantum to classical framework in general, and it may result in erroneous outcomes, as shown in Section VI. This specific approach can lay the foundations of identifying originators of malicious activity on multi-node quantum networks.

## II. CLASSICAL ENTROPIC CAUSAL INFERENCE

Consider that the joint distribution  $P(X, Y)$  between two observed variables is given. The aim of the entropic causal inference is to determine the causality relation between  $X$  and  $Y$ . The authors of (Kocaoglu et al., 2017a) proposed an approach to determine the causal direction by assuming that minimization of the information entropy of exogenous variable (i.e. one that is not caused by any others in the model) identifies the causal direction. The key assumption used for determining the causal direction in (Kocaoglu et al., 2017a) is given as follows.

**Assumption 1.** *Entropy of the exogenous variable  $E$  is small in the true causal direction. In other words, the exogenous variable has lower entropy in the true causal direction than the entropy in the wrong direction.*

However, in the causal graph  $X \rightarrow Y$ , where  $Y = f(X, E)$ , finding the exogenous variable  $E \perp\!\!\!\perp X$  (i.e.,  $E$  is marginally independent of  $X$ ) with minimum entropy is an NP hard problem due to the following argument. Assume that  $Y = f(X, E)$  and  $E \perp\!\!\!\perp X$ . Define the function  $f_x$  as  $\begin{cases} f_x : \mathcal{E} \rightarrow \mathcal{Y} \\ f_x(E) = f(x, E) \end{cases}$ . Using this definition and the fact that  $E \perp\!\!\!\perp X$ , we have:

$$\begin{aligned} p(Y = y|X = x) & \\ &= p(f_x(E) = y|X = x) && \text{by the definition of } f_x \\ &= p(f_x(E) = y) && \text{because } E \perp\!\!\!\perp X \end{aligned}$$

This means that the conditional distributions  $p(Y|X = x)$  can be considered and treated as distributions  $p(f_x(E))$  by applying the function  $f_x$  on an exogenous (unobserved) variable  $E$ . In other words, the problem of finding the exogenous variable  $E$  with minimum entropy given the joint distribution  $p(X, Y)$  is equivalent to the problem of finding the minimum entropy joint distribution of the random variables  $U_i = (Y|X = x_i)$ , given the marginal distributions  $p(Y|X = x_i)$  (Kocaoglu et al., 2017a). However, the problem of minimizing entropy subject to marginal constraints is non-convex and NP hard (Kovačević et al., 2015), and therefore it probably requires exponential time in the worst case. Importantly, however, the minimum entropy coupling problem can be tackled effectively using a heuristic search, as shown in (Kocaoglu et al., 2017b; Cicalese et al., 2017; Rossi, 2019).

The detailed algorithm for determining causal direction in (Kocaoglu et al., 2017a) is given in Algorithm 4 that uses Algorithm 5 for joint entropy minimization. The key steps in the algorithm include:

- 1) Computing marginal and conditional probability distributions from  $p(X, Y)$ : In this step, we compute  $p(X|Y)$  and  $p(Y|X)$ .
- 2) Compute minimum entropy of the exogenous variables from  $X$  to  $Y$  and from  $Y$  to  $X$ : This is where the problem of minimizing entropy subject to marginal constraints is used, and a greedy algorithm is provided for this problem. The greedy algorithm is provided in Algorithm 5. This algorithm has been shown to always finds

a *local minimum*, which is within an additive guaranteed gap from the unknown global optimum (Kocaoglu et al., 2017b).

- 3) Compare the minimum entropy from  $X$  to  $Y$  and from  $Y$  to  $X$ , and return the causal model with smaller entropy.

The second step finds the minimum joint entropy subject to marginal constraints, which we refer to as the *minimum entropy couplings* problem. This problem has a pivotal role in entropic causal inference, we take a look at this problem from quantum computing point of view in Section III.

### III. MINIMUM ENTROPY QUANTUM MARGINAL

In this section we formulate the problem of minimum-entropy quantum couplings (also known as quantum marginal problem) as an optimization problem. Then, we propose a greedy algorithm for solving this problem and show that for two quantum systems, it always finds a local optimum. Our proposed algorithm connects the problem of minimum-entropy couplings in classic context to the quantum marginal problem. In the next section we show the fundamental role of this connection in solving the problem of causal inference via an entropic approach.

#### A. Problem Formulation

Consider two quantum systems  $A$  and  $B$ . Assume that density matrices  $\rho_A$  and  $\rho_B$  are defined on Hilbert spaces  $\mathcal{H}_A$  and  $\mathcal{H}_B$ , respectively. Let  $\mathcal{C}(\rho_A, \rho_B)$  denotes the set of all density matrices  $\rho_{AB}$  on  $\mathcal{H}_A \otimes \mathcal{H}_B$  such that the states of the subsystems  $A$  and  $B$  can be characterized by the corresponding marginal density operators, that is,  $\rho_A = \text{Tr}_B(\rho_{AB})$  and  $\rho_B = \text{Tr}_A(\rho_{AB})$ , respectively, where  $\text{Tr}_B$  and  $\text{Tr}_A$  are the *partial traces* over the Hilbert spaces of subsystems  $B$  and  $A$ , respectively.  $\mathcal{C}(\rho_A, \rho_B)$  is the set of *quantum couplings* of  $\rho_A$  and  $\rho_B$ . Since the von Neumann entropy of a quantum state  $\rho$ , defined as  $S(\rho) = -\text{Tr}(\rho \log \rho)$ , is *non-negative* and *concave*, the minimum-entropy element of the convex set  $\mathcal{C}(\rho_A, \rho_B)$  will be attained at an *extreme point*. The extremal states in this set have been characterized in (Parthasarathy, 2005; Rudolph, 2004). Now, we formulate the minimum-entropy quantum marginal problem as a *minimization of a concave function subject to convex constraints* as follows.

**Problem 1** (Minimum Entropy Coupling Problem). *Given  $m \times m$  density matrix  $A$  and  $n \times n$  density matrix  $B$ , find a  $mn \times mn$  positive semidefinite matrix  $X = (X_{ij})$  of trace one with block matrices  $X_{ij} \in \mathbb{R}^{n \times n}$ ,  $1 \leq i, j \leq m$  such that the von Neumann entropy of  $X$ ,  $S(X)$ , is minimum and*

$$X_{11} + X_{22} + \cdots + X_{mm} = B \tag{1}$$

$$A = (A_{ij}), \text{ where } A_{ij} = \text{Tr}(X_{ij}), 1 \leq i, j \leq m \tag{2}$$

The set of positive semidefinite matrices is a *closed convex* set in the space of symmetric matrices (Lange, 2013). Also, the solution set of a system of linear equations is an affine space<sup>1</sup>, and as a result a convex set (Boyd and Vandenberghe, 2004). Thus, the three constraints  $\text{Tr}(X) = 1$ , Eq. (1), and Eq. (2) define convex constraints for Problem 1. This means that the minimum entropy quantum marginal problem is a concave minimization problem,  $\min_{X \in \mathcal{H}_A \otimes \mathcal{H}_B} S(X)$ , subject to convex constraints.

A large number of algorithms have been developed for solving concave minimization problems. A survey and comparison of methods can be found in (Heising-goodman, 1981; Pardalos and Rosen, 1986). Details concerning solution approaches to solve concave minimization problems can be found in (Pardalos and Rosen, 1987; Locatelli and Schoen, 2013; Horst and Tuy, 2013; Tuy, 2016). However, there are some important practical issues to use these approach for solving the minimum entropy quantum marginal: (1) *scalability*: This optimization problem is difficult to perform numerically because the boundary of the space of positive semidefinite matrices is hard to compute. (2) Most of optimization techniques do not guarantee global optimality, and it is quite possible to return a local optimum. In general, finding the global minimum for the minimum entropy quantum marginal is difficult (NP hard): analytical methods are not applicable, and the use of a numerical solution strategies often does not lead to optimal solutions in polynomial time. To overcome these difficulties we propose an alternative approach in the following subsection.

### B. A Greedy Entropy Minimization Algorithm for Quantum Marginal Problem

To succeed in dealing with the problems in solving the minimum-entropy quantum marginals, we propose a heuristic greedy algorithm that connects this problem to the classical minimum-entropy quantum couplings. In the next section, we show how to use this strategy for solving the problem of quantum causal inference. However, applicability of our proposed method goes beyond causal inference and can be used by the active community (Zeng et al., 2019; Schilling; Fritz and Chaves, 2012) that are working on quantum marginals. Given two density matrices  $\rho_A$  and  $\rho_B$  of two quantum systems  $A$  and  $B$  respectively, the minimum entropy quantum coupling problem is to find the minimum-entropy joint density matrix  $\rho_{AB}$  among all possible joint density matrices having  $\rho_A$  and  $\rho_B$  as partial traces. This problem is known to be NP-hard, even in the classical context (Kovačević et al., 2015). In this section, we propose an algorithm that provides a feasible solution to the quantum marginal problem.

Any density operator defines a classical probability distribution: its eigenvalues are a probability distribution on the set of its eigenvectors (Rieffel and Polak, 2011) ([Section10.1.2]), formally we have:

$$\rho_A = \sum_i p_i |v_i\rangle\langle v_i|, p_i \geq 0, \text{Tr}(\rho_A) = \sum_i p_i = 1, \quad (3)$$

$$\rho_B = \sum_j q_j |w_j\rangle\langle w_j|, q_j \geq 0, \text{Tr}(\rho_B) = \sum_j q_j = 1. \quad (4)$$

<sup>1</sup>An *affine space* is like a vector space, except that no special choice of origin is assumed.

Here  $|v_i\rangle$  denotes the normalized orthogonal eigenvectors of  $\rho_A$ , with  $|v_i\rangle\langle v_i|$  the corresponding orthogonal projector, and  $p_i$  its eigenvalues, such that  $\langle v_i|\rho_A|v_j\rangle = p_i\delta_{ij}$ , where  $\delta_{ij}$  is the Kronecker symbol ( $\delta_{ij} = 1$  for  $i = j$  and 0 otherwise). The eigenvalue  $p_i$  represents the probability of finding the system in the pure quantum state  $|v_i\rangle$ . Similar statement holds for  $|w_j\rangle$  and  $\rho_B$ .

Our proposed algorithm (pseudo-code in Algorithm 1) is composed of two steps. In the first step, we compute the eigenvalue decomposition of the given density matrices  $\rho_A$  and  $\rho_B$ . This helps give the eigenvectors  $|v_i\rangle, |w_j\rangle$  as well as the probabilities  $p_i$  and  $q_j$ . In the second step, we apply the greedy algorithm provided in (Kocaoglu et al., 2017b) on these probabilities  $p_i$  and  $q_j$  of the two random variables to determine the joint probabilities of the joint random variable. Let the joint probabilities returned by the algorithm be  $r_{i,j}$  corresponding to the first variable having probability  $p_i$  and the second variable having probability  $q_j$ . We note that the von Neumann entropy of  $A$  (resp.,  $B$ ) is  $H(p_1, \dots, p_m)$  (resp.,  $H(q_1, \dots, q_n)$ ). The joint entropy returned by the algorithm is  $H(r_{1,1}, \dots, r_{m,n})$ , where  $H(\cdot)$  is the Shannon entropy. We further note that the joint density matrix which has the entropy as above is

$$X = \sum_{i,j} r_{i,j} |v_i\rangle\langle w_j|(|v_i\rangle\langle w_j|)^\dagger \quad (5)$$

Since the above  $X$  can be easily shown to be a valid density matrix, with von Neumann entropy  $H(r_{1,1}, \dots, r_{m,n})$ , this  $X$  is a feasible solution for the joint coupling problem. We further note that the classical coupling problem is a special case of the quantum marginal problem where the pure states  $|v_i\rangle, |w_j\rangle$  are the possibilities of the classical variables. In this case, the quantum marginal problem results in the same joint entropy as in the classical coupling problem in (Kocaoglu et al., 2017b). Thus, the proposed approach results in a feasible joint density matrix with the constraints in (1) and (2) satisfied.

**Remark 1.** *In the step 2 of Algorithm 1 there are alternative greedy algorithms (Cicalese et al., 2017; Rossi, 2019) that can be used in this step. These algorithms provide different guarantees, i.e., solutions that are local minimum (Kocaoglu et al., 2017a) and 1-bit approximation (Cicalese et al., 2017). In (Rossi, 2019), the authors proved that the algorithm proposed in (Kocaoglu et al., 2017a) provides, in addition, a 1-bit approximation guarantee in the case of two variables.*

#### IV. PROPOSED APPROACH FOR QUANTUM ENTROPIC CAUSAL INFERENCE

In this section, we propose a quantum entropic causal inference approach, which is a generalization of the classical entropic causal inference, to the quantum domain by exploiting entanglement entropy of exogenous variables under the same assumption (Assumption 1). First, we introduce and develop the formalism of *quantum conditional density matrix*, which provides a solid framework for adapting the greedy entropy-based causal inference algorithm

---

**Algorithm 1:** Greedy Entropy Minimization Algorithm for Quantum Marginal

---

**Input:** Density matrices of quantum systems  $X$  and  $Y$  i.e.,  $\rho_X$  and  $\rho_Y$  of the size  $m$ -by- $m$  and  $n$ -by- $n$ , respectively.

**Output:** Minimum entropy  $H(e)$  of the joint density matrix.

```

/* Step 1: Compute eigenvalues of  $\rho_X$  and  $\rho_Y$  */
1  $p_X = \text{eig}(\rho_X)$ ;
2  $q_Y = \text{eig}(\rho_Y)$ ;
/* Step 2: Apply Joint Entropy Minimization Algorithm (Kocaoglu et al., 2017b) on  $p_X$  and  $q_Y$ . */
3  $e = [ ]$ ;
4 Initialize the matrix  $M_{ij} = 0, i = 1, \dots, m, j = 1, \dots, n$ ;
5 Initialize  $r = 1$ ;
6 while  $r > 0$  do
7    $e = [e, r]$ ;
8    $(\{p_X, q_Y\}, r) = \text{UpdateRoutine}(\{p_X, q_Y\}, r)$ 
9 end
10 UpdateRoutine( $\{p_X, q_Y\}, r$ ){
11  $i = \text{argmax}_k \{p_k\}$ ;
12  $j = \text{argmax}_k \{q_k\}$ ;
13  $M_{ij} = \min\{p_i, q_j\}$ ;
14  $p_i = p_i - M_{ij}$ ;
15  $q_j = q_j - M_{ij}$ ;
16  $r = r - M_{ij}$ ;
17 }
18  $H(e) = -\sum_k e_k \log(e_k)$ ;
19 return  $H(e)$ .

```

---

(Algorithm 4) to the quantum domain. Then, the proposed algorithm to determine the causal direction is described which uses the quantum conditional density matrix and the quantum marginal problem.

### A. Conditional Density Matrix

Quantum theory can be understood as a non-commutative generalization of classical probability theory wherein probability measures are replaced by density operators (Leifer and Spekkens, 2013). Analogies between the classical theory of Bayesian inference and the conditional states formalism for quantum theory are listed in Table I.

TABLE I  
ANALOGIES BETWEEN CLASSICAL AND QUANTUM FORMALISM

Classical Probability	Quantum Theory
probability distribution $p(X)$	density operator (matrix) $\rho_X$
joint distribution $p(X, Y)$	joint density $\rho_{XY}$
marginal distribution $p(X) = \sum_Y p(X, Y)$	partial trace $\rho_X = \text{Tr}_Y(\rho_{XY})$
conditional probability $p(X Y) = p(X, Y)/p(Y)$	conditional density $\rho_{X Y} = (\rho_Y^{-1} \otimes I) * \rho_{YX}$
instance conditional probability $p(X Y=y) = \frac{p(X, Y=y)}{\sum_x p(X, Y=y)}$	instance conditional density matrix $\rho_{X Y=y} = \frac{\text{Tr}_Y\{\rho_{YX} *  y\rangle\langle y \}}{\text{trace}\{\rho_{YX} *  y\rangle\langle y \}}$

Quantum conditional densities are a generalization of classical conditional probability distributions. However, to generalize conditional probabilities to the quantum case, several approaches have been proposed in the literature. The

three following generalizations are the best known in the literature of quantum information: (1) quantum conditional expectation (Umegaki, 1962), (2) quantum conditional amplitude operator (Cerf and Adami, 1997, 1999), and (3) quantum conditional states (Leifer, 2007; Leifer and Spekkens, 2013). Arguably, quantum conditional states are the most useful generalization of conditional probability from the point of view of practical applications.

Despite the elegance of the idea and decades of efforts, the analogy between quantum conditional densities and classical conditional probability as it has been developed so far is not complete. For example, consistent with the definition of conditional probability of events when  $A$  is the event  $X = x$  and  $B$  is the event  $Y = y$ , the conditional probability distribution of  $X$  given  $Y = y$  is defined as

$$p(X|Y = y) = \frac{p(X, Y = y)}{\sum_x p(X, Y = y)}$$

We will see that the quantum counterpart of this concept plays a significant role in the design of our entropic quantum causal inference algorithm. However, none of well-known generalizations of conditional probabilities in the literature of quantum computing has defined this notion where  $Y$  is in a given quantum state. For a given joint density matrix  $\rho_{XY}$ , the reduced density matrix  $\rho_X$  given the measurement  $Y = |y\rangle$  of the quantum system  $Y$ , denoting by  $\rho_{X|Y=|y\rangle}$ . This quantity was used in (Dakić et al., 2010) for defining an *alternative version of the mutual information* as follows:

$$Q_X(\rho_{XY}) = S(\rho_Y) - \min_{\{E_k\}} \sum_k p_k S(\rho_{Y|k}),$$

where  $\rho_{Y|k} = \text{Tr}(E_k \otimes \mathbb{1}_Y \rho_{XY}) / \text{Tr}(E_k \otimes \mathbb{1}_Y \rho_{XY})$  is the state of  $Y$  conditioned on outcome  $k$  in  $X$ , and  $\{E_k\}$  represents the set of positive operator valued measure elements (Dakić et al., 2010). Inspired by this work, we formally define the *instance conditional density matrices* for an arbitrary quantum system  $Y$  as follows.

**Definition 1** (Instance Conditional Density Matrix). *For a given joint density matrix  $\rho_{XY}$ , the reduced density matrix  $\rho_X$  given the measurement  $Y = |y\rangle$  of the quantum system  $Y$ , i.e.,  $\rho_{X|Y=|y\rangle}$ , is given as*

$$\rho_{X|Y=|y\rangle} = \frac{\text{Tr}_Y\{\rho_{YX} \star |y\rangle\langle y|\}}{\text{trace}\{\rho_{YX} \star |y\rangle\langle y|\}} \quad (6)$$

where the  $\star$ -product is defined by  $M \star N := (N^{1/2} \otimes I)M(N^{1/2} \otimes I)$ . Thus,  $\rho_{YX} \star |y\rangle\langle y| = ((|y\rangle\langle y|)^{1/2} \otimes I) \star \rho_{YX} \star ((|y\rangle\langle y|)^{1/2} \otimes I)$ .

**Theorem 1.** *The instance conditional density matrix  $\rho_{X|Y=|y\rangle}$ , defined in Definition 1, is a valid density matrix.*

*Proof.*  $\rho_{YX} \star |y\rangle\langle y|$  is a semidefinite positive operator because it is of the form  $AA^\dagger$ , where  $A = ((|y\rangle\langle y|)^{1/2} \otimes I)\rho_{YX}^{1/2}$ . Note that the partial trace of a positive semidefinite matrix is a positive semidefinite matrix (Filipiak et al., 2018). However, the numerator of  $\rho_{X|Y=|y\rangle}$  is not a density operator because it does not have trace one. Normalization guarantees that  $\rho_{X|Y=|y\rangle}$  is a valid density matrix.  $\square$

## B. QECI: Proposed Algorithm for Quantum Entropic Causal Inference

In this section, we propose an algorithm to generalize the classical entropic causal inference theory to quantum entropic causal inference using a density matrix approach. An overview of our **Quantum Entropic Causal Inference** (QECI) algorithm is shown in Figure 2, and Algorithm 2 summarizes the entire procedure of QECI.

**QECI Description.** For a given joint density matrix  $\rho_{XY}$ , QECI is able to discover the true causal direction between quantum systems  $X$  and  $Y$  in three phases:

**Phase 1.** In this phase we trace out  $Y$  and  $X$  to obtain  $\rho_X$  and  $\rho_Y$ , respectively (line 1-2). Then, we compute  $\rho_{YX}$  by reordering the entries of  $\rho_{XY}$ , appropriately (line 3).

**Phase 2.** Computing Eigenvectors and Conditional Densities: In this phase, we first find the eigenvectors of  $\rho_X$  and  $\rho_Y$  to determine the eigenstates. These eigenstates are  $|x_i\rangle$  and  $|y_j\rangle$ , respectively. These eigenstates provide a representation of the mixed states  $\rho_X$  and  $\rho_Y$  into superposition of pure states. Using these eigenstates, Definition 1 is used to find the instance conditional density matrices (line 4-11 and 14-21).

**Phase 3.** Solve Quantum Marginal Problem for the Conditional Densities: In this step, we use the quantum marginal problem to determine the minimum-entropy quantum coupling between the different  $\rho_{Y|X=|x_i\rangle}$  (line 12). Similarly, the quantum coupling between the different  $\rho_{X|Y=|y_j\rangle}$  is obtained (line 22).

**Phase 4.** Based on the minimum entropy coupling, we estimate minimum entropy  $H(X \rightarrow Y)$  and  $H(X \leftarrow Y)$ . Taking into account Assumption 1, if  $H(X \rightarrow Y) < H(X \leftarrow Y)$ , QECI returns that the causal model is of the form  $X \rightarrow Y$ , and  $X \leftarrow Y$  otherwise (line 24-28).




Fig. 2. An overview of QECI: an algorithm for Quantum Entropic Causal Inference.

**Algorithm 2:** QECI: Quantum Entropic Causal Inference

---

**Input:** The joint density matrix  $\rho_{XY}$  for a pair of quantum systems  $X$  and  $Y$ .  
**Output:** The cause-effect relationship between  $X$  and  $Y$ .

```

/* Phase 1: Compute reduced density matrices  $\rho_X$  and  $\rho_Y$  as well as density matrix  $\rho_{YX}$  from  $\rho_{XY}$ . */
1  $\rho_X = Tr_Y(\rho_{XY});$ 
2  $\rho_Y = Tr_X(\rho_{XY});$ 
3 Compute  $\rho_{YX}$  by reordering the entries of  $\rho_{XY}$ , appropriately;
/* Estimation of minimum entropy  $H(X \rightarrow Y)$  for the causal model  $Y = f(X, E)$ . */
/* Phase 2a: Compute eigenvalues and eigenvectors of  $\rho_X$ . */
4  $[V, D] = eig(\rho_X);$ 
/* Computes diagonal matrix  $D$  of eigenvalues and matrix  $V$  whose columns are the corresponding eigenvectors, so that  $\rho_X * V = V * D$ . */
5 for ( $d_i \in D$ ) do
/* Compute instance conditional density matrices. */
6  $|x_i\rangle\langle x_i| = e_i * e_i^T;$ 
/*  $e_i$  is the  $i$ 'th column of  $V$ , and  $e_i^T$  is the transpose of  $e_i$ . */
7  $\rho_i = Tr_X(\rho_{XY} * |x_i\rangle\langle x_i|);$ 
/*  $I$  is the identity matrix. */
8  $\rho_{Y||x_i}_X = \rho_i / trace(\rho_i);$ 
/* Compute marginal distributions. */
9  $B_i = eig(\rho_{Y||x_i}_X);$ 
10 Add  $B_i$  to the  $i$ 'th row of the matrix  $M$ 
11 end
/* Phase 3a: Apply Algorithm 5 to estimate joint entropy minimization. */
12  $H(E) = JointEntropyMinimization(M);$ 
13  $H(X \rightarrow Y) = S(X) + H(E);$ 
/* Estimation of minimum entropy  $H(X \leftarrow Y)$  for the causal model  $X = g(Y, E')$ . */
/* Phase 2b: Compute eigenvalues and eigenvectors of  $\rho_Y$ . */
14  $[V, D] = eig(\rho_Y);$ 
15 for ( $d_i \in D$ ) do
/* Compute instance conditional density matrices. */
16  $|y_i\rangle\langle y_i| = e_i * e_i^T;$ 
17  $\rho_i = Tr_Y(\rho_{YX} * |y_i\rangle\langle y_i|);$ 
18  $\rho_{X||y_i}_Y = \rho_i / trace(\rho_i);$ 
/* Compute marginal distributions. */
19  $B_i = eig(\rho_{X||y_i}_Y);$ 
20 Add  $B_i$  to the  $i$ 'th row of the matrix  $M$ ;
21 end
/* Phase 3b: Apply Algorithm 5 to estimate joint entropy minimization. */
22  $H(E') = JointEntropyMinimization(M);$ 
23  $H(X \leftarrow Y) = S(Y) + H(E');$ 
/* Phase 4: Compare the minimum entropy from  $X$  to  $Y$  and from  $Y$  to  $X$ . */
24 if ( $H(X \rightarrow Y) < H(X \leftarrow Y)$ ) then
25 | return The causal model is of the form  $X \rightarrow Y$ .
26 else
27 | return The causal model is of the form  $X \leftarrow Y$ .
28 end

```

---

## V. DISCUSSIONS

## A. Complexity Analysis of QECI.

First, we discuss the time complexity of QECI. Assume that  $\rho_X$  and  $\rho_Y$  of the size  $m$ -by- $m$  and  $n$ -by- $n$ , respectively. The most expensive parts of QECI are the computation of eigenvalues and eigenvectors as well as joint entropy minimization algorithm. So, we have:

- To compute eigenvalues and eigenvectors of  $\rho_X$ , i.e.,  $[V, D] = eig(\rho_X)$  (line 4), in the worst case scenario the time complexity is  $O(m^3)$  (Press et al., 1988).
- To compute  $B_i = eig(\rho_{Y||x_i}_X)$  ( $m$  times, line 5-11) the time complexity is  $O(m^2 \log(m))$  because for

symmetric tridiagonal eigenvalue problems all eigenvalues (without eigenvectors) can be computed numerically in time  $O(m \log(m))$ , using bisection on the characteristic polynomial (Coakley and Rokhlin, 2013).

- To apply joint entropy minimization algorithm (Algorithm 5) in line 12, the time complexity is  $O(m^4 \log(m))$ , it can easily be reduced to  $O(m^2 \log(m))$  by dropping the sorting step (Kocaoglu et al., 2017a).
- To compute eigenvalues and eigenvectors of  $\rho_Y$  i.e.,  $[V, D] = \text{eig}(\rho_Y)$  (line 14), in the worst case scenario the time complexity is  $O(n^3)$  (Press et al., 1988).
- To compute  $B_i = \text{eig}(\rho_{Y||x_i})$  ( $m$  times, line 15-21) the time complexity is  $O(n^2 \log(n))$ .
- To apply joint entropy minimization algorithm (Algorithm 5) in line 22, the time complexity is  $O(n^4 \log(n))$ , it can easily be reduced to  $O(n^2 \log(n))$  by dropping the sorting step (Kocaoglu et al., 2017a).

As a result the time complexity of QECI is  $O(\max(m^3, n^3))$ . It is not difficult to see that the space complexity of QECI is  $O(m^2 n^2)$  due to the size of  $\rho_{XY}$  and  $\rho_{YX}$ , i.e.,  $mn$ -by- $mn$ .

From the viewpoint of computational complexity, a concave minimization problem (e.g., Problem 1) is NP-hard (Horst and Tuy, 2013). Assume that  $\rho_X$  and  $\rho_Y$  are of the size  $m$ -by- $m$  and  $m$ -by- $m$ , respectively. So,  $\rho_{XY}$  is of the size  $mn$ -by- $mn$ , and all of  $m$  instance conditional density matrices  $\rho_{Y||x_i}, i = 1, \dots, m$  are of the size  $m$ -by- $m$ . This indicates that the solution of the minimum-entropy quantum marginal problem:  $\min S(\rho_{Y||x_1}, \dots, \rho_{Y||x_m})$  is a matrix of the size  $m^m$ -by- $m^m$ . Similarly, for the minimum-entropy quantum marginal problem:  $\min S(\rho_{X||y_1}, \dots, \rho_{X||y_n})$  is a matrix of the size  $n^n$ -by- $n^n$ . So, the total space complexity of the optimization approach is  $O(\max(m^m, n^n))$ . As a result this approach is impractical.

### B. Rotational Invariance of QECI

Let us assume that  $\rho_X$  is rotated using a unitary matrix  $U$ . Let us say  $\rho_Z = U \rho_X U^\dagger$ . Then, the causal direction between  $X$  and  $Y$  is the same as that between  $Z$  and  $Y$ . In order to see this, we note that the second phase of the QECI will result in  $|z_i\rangle = U|x_i\rangle$ . Further, we note that from the definition of conditional densities,  $\rho_{Z|Y=|y_j\rangle} = U \rho_{X|Y=|y_j\rangle} U^\dagger$  and  $\rho_{Y|X=|x_i\rangle} = \rho_{Y|Z=U|x_i\rangle}$ . Further, up to a rotation of the eigenstates in  $\rho_{Z|Y=|y_j\rangle}$ , the eigenvalues required for quantum marginal problem remain the same. Since these eigenvalues remain the same, the entropy of the quantum coupling remains the same. Since the entropy of the quantum density matrix is independent of rotations, the overall  $H(X \rightarrow Y)$  and  $H(Y \rightarrow X)$  are the same as  $H(Z \rightarrow Y)$  and  $H(Y \rightarrow Z)$ , respectively. By symmetry, the result also holds if  $Y$  is rotated by a unitary matrix.

### C. Classical vs Quantum Approach

We emphasize that causal inference using entanglement entropy of hidden variables is a fundamentally new approach that also reduces to the classical causal inference method as expected. In other words, QECI is a unified framework for classical and quantum causal inference. In fact, quantum entropic causal inference approach is a

generalization of the classical entropic causal inference because any classical probability distribution  $p : X \rightarrow [0, 1]$  can be written as a density matrix  $\rho_X$  by writing down a matrix with the probabilities along its diagonal. In fact, it does so in more than one way. However, for our purpose the diagonal approach is enough. For example, consider the following joint probability distribution  $p(X, Y)$ :

	$y_1$	$y_2$
$x_1$	$\frac{1}{16}$	$\frac{3}{16}$
$x_2$	$\frac{5}{16}$	$\frac{7}{16}$

Using the diagonal approach, we obtain the corresponding joint density matrix  $\rho_{XY}$ .

$$\rho_{XY} = \begin{bmatrix} \frac{1}{16} & 0 & 0 & 0 \\ 0 & \frac{3}{16} & 0 & 0 \\ 0 & 0 & \frac{5}{16} & 0 \\ 0 & 0 & 0 & \frac{7}{16} \end{bmatrix}$$

This means that QECI captures both the classical and quantum entropic causal inference in a unified framework. The parallels between classical and quantum entropic causal inference are illustrated in Figure 3. We now highlight similarities and differences between classical and quantum entropic causal inference.

**Key differences.** (1) Quantum entropic causal inference uses density matrices while the classical entropic causal inference uses probability distributions. (2) Quantum entropic causal inference uses partial traces while the classical entropic causal inference uses marginal probability distributions. (3) Quantum entropic causal inference uses instance conditional density matrices while the classical entropic causal inference uses conditional probability distributions. (4) Quantum entropic causal inference uses von Neumann entropy while the classical entropic causal inference uses Shannon entropy.

**Classical and quantum analogies.** (1) Both methods are built upon the assumption that the exogenous variable is *simple* (smaller) in the true causal direction (Assumption 1). (2) Both methods are built upon entropy as a measure of simplicity for the causal discovery task. (3) Both methods are built upon a greedy algorithm for searching minimum entropy of exogenous variables.

## VI. EVALUATION ON QUANTUM CAUSE-EFFECT SYNTHETIC DATA

Since there is no quantum cause-effect repository to verify the validity of our proposed algorithm, we put forward an experimental scheme that can be used to confront our theoretical framework. We consider a minimalistic model of an unknown message (possibly encrypted) with unknown origin in a two-node quantum network. The two nodes are connected by a noisy channel (e.g., an optical fiber) with unknown model of quantum disturbance, as depicted




Fig. 3. Entropic Causal Inference: Classical vs Quantum

in Figure 4. Consider a perfectly entangled system

$$\rho_{XY} = \sum_i p_i |X_i\rangle\langle X_i| \otimes (|X_i\rangle\langle X_i|)^\dagger,$$

for some  $p_i$  such that  $\sum_i p_i = 1$  and  $p_i > 0$ . Then, quantum system  $Y$  is communicated and encounters errors as a result of it. In this case, for any quantum noise model, we expect that  $X$  will be the cause of  $Y$ . We note that noise can arise in any quantum computation (Aggarwal et al., 2010), and is not just limited to communications. We prove that only using the joint density matrix, we can identify the originator of the message. To verify the validation of QECI, we use realistic quantum noisy links such as quantum symmetric channel and depolarizing channel (valid for

quantum networking and quantum communications). Our work can lay the foundations of identifying originators of malicious activity on multi-node quantum networks.




Fig. 4. Alice and Bob are connected by a noisy channel (e.g., an optical fiber) with unknown model of quantum disturbance.

In Appendix, we describe the Quantum Symmetric Channel (QSC), which is a quantum version of Binary Symmetric Channel. The proposed algorithm is run step-by-step to show that the output of the channel is the effect while the source is the cause, as expected. We consider a generalization of QSC in the example below. In this example, the phase of the qubit is reversed with certain probability.

**Model 1** (Generalized Quantum Symmetric Channel). *Assume that there are real numbers  $\alpha$  and  $\beta$  such that  $\alpha^2 + \beta^2 = 1$ , and  $X_1 = Y_1 = \alpha|0\rangle + \beta|1\rangle$ , and  $X_2 = Y_2 = \alpha|0\rangle - \beta|1\rangle$ . Let  $X$  be in state  $X_1$  with probability  $q$  and  $X_2$  with probability  $1 - q$ . Further, when input state is  $X_i$ , output is  $Y_i$  with probability  $1 - p$  and  $Y_{3-i}$  with probability  $p$  (indicating  $p$  as the probability of error). Thus, the joint density matrix of  $X$  and  $Y$  is the superposition of the following pure density matrices:*

$$\begin{aligned} \rho_{XY} = & q(1 - p) * (|X_1\rangle|Y_1\rangle)(|X_1\rangle|Y_1\rangle)^\dagger \\ & + qp * (|X_1\rangle|Y_2\rangle)(|X_1\rangle|Y_2\rangle)^\dagger \\ & + (1 - q)p * (|X_2\rangle|Y_1\rangle)(|X_2\rangle|Y_1\rangle)^\dagger \\ & + (1 - q)(1 - p) * (|X_2\rangle|Y_2\rangle)(|X_2\rangle|Y_2\rangle)^\dagger. \end{aligned}$$

We already know that  $X$  is the cause of  $Y$  in this scenario. To verify this using our proposed method QECI, assume that the joint density matrix  $\rho_{XY}$  is given with  $\alpha = \beta = 1/\sqrt{2}$ ,  $0 < p < 1$ , and  $q = 0.4$ .

Results are shown in Figure 5. Note that when  $p = 0.5$ ,  $H(X \rightarrow Y) = H(X \leftarrow Y) \simeq 1.97$ , which indicates that  $X$  and  $Y$  are uncorrelated in this case, as we expected. Further, for  $p = 0$  and  $p = 1$ ,  $X$  and  $Y$  are the symmetric and thus neither  $X$  causes  $Y$  or  $Y$  causes  $X$  in which case, the two are also the same. Thus, we see that other than  $p = 0, 0.5, 1$ ,  $H(X \rightarrow Y) < H(X \leftarrow Y)$  indicating the desired causal direction.




Fig. 5.  $H(X \rightarrow Y)$  vs  $H(X \leftarrow Y)$  for quantum symmetric channels in Model 1 with  $q = 0.4$ ,  $0 < p < 1$ , and  $\alpha = \beta = 1/\sqrt{2}$ .

**Model 2** (Depolarizing Channel). A quantum depolarizing channel (Nielsen and Chuang, 2002) is a model for quantum noise in quantum systems. In this channel, a quantum bit remains the same with probability  $1 - p$ , undergoes a bit-flip with probability  $p/3$ , a phase-flip with probability  $p/3$ , and a combination of bit-flip and phase-flip with probability  $p/3$ . Assume that there are real numbers  $\alpha$  and  $\beta$  such that  $\alpha^2 + \beta^2 = 1$ . Let the input  $X$  be in state  $\alpha|0\rangle + \beta|1\rangle$ . For  $0 \leq p \leq 1$ , the joint density operator  $\rho_{XY}^{\alpha,\beta}$  can be written as superposition of the following pure states:

$$\begin{cases} \alpha^2|00\rangle + \alpha\beta|01\rangle + \alpha\beta|10\rangle + \beta^2|11\rangle & 1 - p \\ \alpha^2|00\rangle - \alpha\beta|01\rangle + \alpha\beta|10\rangle - \beta^2|11\rangle & p/3 \\ \alpha\beta|00\rangle + \alpha^2|01\rangle + \beta^2|10\rangle + \alpha\beta|11\rangle & p/3 \\ -\alpha\beta|00\rangle + \alpha^2|01\rangle - \beta^2|10\rangle + \alpha\beta|11\rangle & p/3 \end{cases}$$

Figure 6 shows the  $\Delta(H) = H(X \leftarrow Y) - H(X \rightarrow Y)$  for different probability errors  $0 < p < 1$ , using QECI.




Fig. 6.  $\Delta(H) = H(X \leftarrow Y) - H(X \rightarrow Y)$  for depolarization channels in Model 2 with joint density matrix  $\rho_{XY} = 0.4 * \rho_{XY}^{0.6,0.8} + 0.6 * \rho_{XY}^{1/\sqrt{2},1/\sqrt{2}}$  is given for  $0 < p < 1$ .

**Why Should We Not Map Quantum to Classical Directly?** Here, we show why classical entropic causal inference do not directly apply to the quantum case. We emphasize that although a joint density operator (matrix)

can be converted to a joint probability distribution (as explained in Example 1), we *lose* some *quantum information* due to the loss of entanglement. The following example shows that converting a joint density matrix  $\rho_{XY}$  directly to a joint probability distribution  $p(X, Y)$ , and then applying classical entropic causal inference on  $p(X, Y)$  will not lead to the correct results.

**Example 1** (Counter Example). *Assume the depolarizing channel as described in Model 2. We already know that  $X$  causes  $Y$  in this model. To convert the joint density matrix  $\rho_{XY}$ , we use a rotational procedure explained as follows: Assume that  $\rho_{XY}$  is rotated using a unitary matrix  $U$ . Let us say  $\rho_{XY} = U\rho'_{XY}U^\dagger$ . So, the joint density matrix  $\rho'_{XY}$  is computed as  $\rho'_{XY} = U^\dagger\rho_{XY}U$ . To compute the unitary matrix  $U$  for a given  $\rho_{XY}$  we use the eigenspaces of  $\rho_X$  and  $\rho_Y$ , where  $\rho_X = \text{Tr}_Y(\rho_{XY})$  and  $\rho_Y = \text{Tr}_X(\rho_{XY})$  are computed by tracing out  $Y$  and  $X$ , respectively. This simple observation enables us to design a procedure that converts a joint density matrix  $\rho_{XY}$  to a joint probability distribution  $p(X, Y)$  in a way that it takes into account the rotation. This procedure is formally described in Algorithm 3.*

---

**Algorithm 3:** Rotational procedure for computing the joint probability distribution of a joint density matrix

---

**Input:** Joint density matrix of quantum systems  $X$  and  $Y$  i.e.,  $\rho_{XY}$ .  
**Output:** Joint probability distribution  $p(X, Y)$  corresponding to the joint density matrix  $\rho_{XY}$ .

```

/* Compute eigenvalues and eigenvectors of  $\rho_X$  */
1  $[V_1, D_1] = \text{eig}(\rho_X);$  */
/* Compute eigenvalues and eigenvectors of  $\rho_Y$  */
2  $[V_2, D_2] = \text{eig}(\rho_Y);$  */
/* Rotational procedure */
3  $U = V_1 \otimes V_2;$  */
4  $\rho'_{XY} = U^\dagger \rho_{XY} U;$ 
5 return  $p(X, Y)$  as the entries on the main diagonal of  $\rho'_{XY}$ .
```

---

*By converting the joint density matrix  $\rho_{XY}$  directly to a joint probability distribution  $p(X, Y)$ , using Algorithm 3, and then applying classical entropic causal inference, i.e., Algorithm 4 on  $p(X, Y)$  we obtain the results represented in Figure 7 which is opposite to the expected causal direction in all cases.*

## VII. DETAILED RELATED WORK

The contributions of this paper regarding a principled and unified entropic causal inference technique for classical and quantum cases intersect with various works in the literature as follows.

a) *Entropic Causal Inference: Classical Version.*: Classical entropic causal inference is a framework for inferring the causal direction between two ordinal or categorical variables from observational data was introduced in (Kocaoglu et al., 2017a). This approach is based on two main assumptions: (1) Every exogenous variable is a direct parent of at most one variable in the model (endogenous variable). This assumption is called *causal sufficiency* (Pearl, 2009). (2) In the true causal direction, the entropy of the exogenous variable is small. This assumption




Fig. 7.  $H(X \rightarrow Y)$  vs  $H(X \leftarrow Y)$  for depolarization channels in Model 2 with joint density matrix  $\rho_{XY} = 0.4 * \rho_{XY}^{0.6,0.8} + 0.6 * \rho_{XY}^{1/\sqrt{2},1/\sqrt{2}}$  is given for  $0 < p < 1$ .

(conjecture) was empirically validated in (Kocaoglu et al., 2017a). Recently, (Compton et al., 2020) prove a variant of this conjecture. In fact, they show that for almost all causal models where the exogenous variable has entropy that does not scale with the number of states of the observed variables, the causal direction is identifiable from observational data. The first assumption i.e., causal sufficiency was relaxed recently in (Kocaoglu et al., 2020). Our proposed framework is the quantum generalization of classical entropic causal inference that considers both assumptions (1) and (2).

*b) Minimum-Entropy Coupling Problem: Classical Version.:* The classical minimum-entropy coupling problem can be stated as follows. Given marginal distributions  $p(X)$  and  $p(Y)$ , what is the minimum entropy over all couplings  $p(X,Y)$  of  $p(X)$  and  $p(Y)$ ? This problem has been shown to be NP hard (Kovačević et al., 2015). Different greedy algorithms have been proposed in (Kocaoglu et al., 2017a,b; Cicalese et al., 2017; Rossi, 2019) to find the minimum-entropy joint distribution, given the marginals.

*c) Minimum-Entropy Coupling Problem: Quantum Version.:* The quantum marginal problem, in its simplest form, is the following: Given density matrices  $\rho_X$  and  $\rho_Y$ , on Hilbert spaces  $\mathcal{H}_1$  and  $\mathcal{H}_2$  respectively. The set of quantum couplings  $\mathcal{C}(\rho_X, \rho_Y)$  is the set of all density matrices  $\rho_{XY}$  on  $\mathcal{H} = \mathcal{H}_1 \otimes \mathcal{H}_2$  such that  $Tr_Y(\rho_{XY}) = \rho_X$  and  $Tr_X(\rho_{XY}) = \rho_Y$ . Characterizations of the extreme points of  $\mathcal{C}(\rho_X, \rho_Y)$  have been given in (Parthasarathy, 2005; Rudolph, 2004). In this paper we formulate the problem of minimum-entropy quantum marginal as an optimization problem, and we propose a greedy algorithm for solving this problem that for two quantum systems, it always finds a local optimum.

*d) Quantum Theory as a Theory of Bayesian Inference.:* The abstract formalism of quantum theory looks like a noncommutative generalization of classical probability. This view is discussed in many quantum mechanics references, particularly those concerned with the deeper mathematical aspects of the theory e.g., in (Kitaev et al., 2002; Rédei and Summers, 2007) among others. However, the generalization as it has been developed so far is not complete. One of the most challenging elements in this generalization is the notion of *conditional density*

*matrices* that can be considered as a counterpart for conditional probability distributions in classical probability (Umegaki, 1962; Cerf and Adami, 1997, 1999; Leifer, 2007; Leifer and Spekkens, 2013). In this paper we introduce and develop the formalism of *quantum conditional density matrix*, which provides a principled way for adapting classical greedy entropy-based causal inference algorithm to the quantum domain.

## VIII. CONCLUSIONS

This paper provides a novel approach for quantum entropic causal inference. As a part of the approach, an algorithmic greedy solution is provided for the minimum-entropy quantum marginal problem and a notion of instance conditional density matrices is developed. The approach is validated on quantum noisy link, where the approach detects the expected causal relation.

We note that the joint density matrix required in our analysis can be estimated from measurements using quantum tomography (D’Ariano et al., 2003), and is beyond the scope of this paper. The extension of the problem to general quantum causality graph relations between multiple variables is an open problem for the future.

## ACKNOWLEDGEMENTS

The authors would like to thank Xueji Wang for generating Figure 1 and Figure 4. This research was supported by the Defense Advanced Research Projects Agency (DARPA) Quantum Causality [Grant No. HR00112010008].

## REFERENCES

- V. Aggarwal, A. R. Calderbank, G. Gilbert, and Y. S. Weinstein, “Volume thresholds for quantum fault tolerance,” *Quantum Information Processing*, vol. 9, no. 5, pp. 541–549, 2010.
- J.-M. A. Allen, J. Barrett, D. C. Horsman, C. M. Lee, and R. W. Spekkens, “Quantum common causes and quantum causal models,” *Physical Review X*, vol. 7, no. 3, p. 031021, 2017.
- S. Boyd and L. Vandenberghe, *Convex optimization*. Cambridge university press, 2004.
- N. J. Cerf and C. Adami, “Negative entropy and information in quantum mechanics,” *Physical Review Letters*, vol. 79, no. 26, p. 5194, 1997.
- , “Quantum extension of conditional probability,” *Physical Review A*, vol. 60, no. 2, p. 893, 1999.
- R. Chaves, L. Luft, T. O. Maciel, D. Gross, D. Janzing, and B. Schölkopf, “Inferring latent structures via information inequalities,” ser. UAI’14. AUAI Press, 2014, p. 112–121.
- R. Chaves, L. Luft, and D. Gross, “Causal structures from entropic information: geometry and novel scenarios,” *New Journal of Physics*, vol. 16, no. 4, p. 043001, 2014.
- R. Chaves, C. Majenz, and D. Gross, “Information–theoretic implications of quantum causal structures,” *Nature communications*, vol. 6, no. 1, pp. 1–8, 2015.

- G. Chiribella and D. Ebler, “Quantum speedup in the identification of cause-effect relations,” *Nature communications*, vol. 10, no. 1, pp. 1–8, 2019.
- F. Cicalese, L. Gargano, and U. Vaccaro, “How to find a joint probability distribution of minimum entropy (almost) given the marginals,” in *2017 IEEE International Symposium on Information Theory (ISIT)*. IEEE, 2017, pp. 2173–2177.
- E. S. Coakley and V. Rokhlin, “A fast divide-and-conquer algorithm for computing the spectra of real symmetric tridiagonal matrices,” *Applied and Computational Harmonic Analysis*, vol. 34, no. 3, pp. 379–414, 2013.
- S. Compton, M. Kocaoglu, K. Greenewald, and D. Katz, “Entropic causal inference: Identifiability and finite sample results,” in *Advances in Neural Information Processing Systems*, 2020.
- B. Dakić, V. Vedral, and Č. Brukner, “Necessary and sufficient condition for nonzero quantum discord,” *Physical review letters*, vol. 105, no. 19, p. 190502, 2010.
- G. M. D’Ariano, M. G. Paris, and M. F. Sacchi, “Quantum tomography,” *Advances in Imaging and Electron Physics*, vol. 128, pp. 206–309, 2003.
- K. Filipiak, D. Klein, and E. Vojtková, “The properties of partial trace and block trace operators of partitioned matrices,” *The Electronic Journal of Linear Algebra*, vol. 33, pp. 3–15, 2018.
- J. F. Fitzsimons, J. A. Jones, and V. Vedral, “Quantum correlations which imply causation,” *Scientific reports*, vol. 5, no. 1, pp. 1–7, 2015.
- T. Fritz and R. Chaves, “Entropic inequalities and marginal problems,” *IEEE transactions on information theory*, vol. 59, no. 2, pp. 803–817, 2012.
- C. Giarmatzis, “A quantum causal discovery algorithm,” in *Rethinking Causality in Quantum Mechanics*. Springer, 2019, pp. 125–150.
- R. D. Gill, “Statistics, causality and Bell’s theorem,” *Statistical Science*, vol. 29, no. 4, pp. 512–528, 2014.
- C. D. Heising-goodman, “A survey of methodology for the global minimization of concave functions subject to convex constraints,” *Omega*, vol. 9, no. 3, pp. 313–319, 1981.
- R. Horst and H. Tuy, *Global optimization: Deterministic approaches*. Springer Science & Business Media, 2013.
- A. Y. Kitaev, A. Shen, M. N. Vyalyi, and M. N. Vyalyi, *Classical and quantum computation*. American Mathematical Soc., 2002, no. 47.
- A. A. Klyachko, “Quantum marginal problem and n-representability,” in *Journal of Physics: Conference Series*, vol. 36, no. 1. IOP Publishing, 2006, p. 014.
- M. Kocaoglu, A. G. Dimakis, S. Vishwanath, and B. Hassibi, “Entropic causal inference,” in *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence*, ser. AAAI’17. AAAI Press, 2017, p. 1156–1162.
- , “Entropic causality and greedy minimum entropy coupling,” in *2017 IEEE International Symposium on Information Theory (ISIT)*. IEEE, 2017, pp. 1465–1469.

- M. Kocaoglu, S. Shakkottai, A. Dimakis, C. Caramanis, and S. Vishwanath, “Applications of common entropy for causal inference,” in *Advances in Neural Information Processing Systems*, 2020.
- M. Kovačević, I. Stanojević, and V. Šenk, “On the entropy of couplings,” *Information and Computation*, vol. 242, pp. 369–382, 2015.
- K. Lange, *Optimization*, 2nd ed., ser. Springer Texts in Statistics. Springer, 2013.
- M. S. Leifer, “Conditional density operators and the subjectivity of quantum operations,” in *AIP Conference Proceedings*, vol. 889, no. 1. American Institute of Physics, 2007, pp. 172–186.
- M. S. Leifer and R. W. Spekkens, “Towards a formulation of quantum theory as a causally neutral theory of bayesian inference,” *Physical Review A*, vol. 88, no. 5, p. 052130, 2013.
- Y.-K. Liu, “Consistency of local density matrices is qma-complete,” in *Approximation, randomization, and combinatorial optimization. algorithms and techniques*. Springer, 2006, pp. 438–449.
- Y.-K. Liu, M. Christandl, and F. Verstraete, “Quantum computational complexity of the n-representability problem: Qma complete,” *Physical review letters*, vol. 98, no. 11, p. 110503, 2007.
- M. Locatelli and F. Schoen, *Global optimization: theory, algorithms, and applications*. SIAM, 2013.
- M. A. Nielsen and I. Chuang, *Quantum computation and quantum information*. American Association of Physics Teachers, 2002.
- P. M. Pardalos and J. B. Rosen, “Methods for global concave minimization: A bibliographic survey,” *Siam Review*, vol. 28, no. 3, pp. 367–379, 1986.
- , *Constrained global optimization: algorithms and applications*. Springer, 1987, vol. 268.
- K. Parthasarathy, “Extremal quantum states in coupled systems,” in *Annales de l’Institut Henri Poincaré (B) Probability and Statistics*, vol. 41, no. 3. Elsevier, 2005, pp. 257–268.
- J. Pearl, *Causality. Models, reasoning, and inference*. Cambridge University Press, 2009.
- J. Pienaar and Č. Brukner, “A graph-separation theorem for quantum causal models,” *New Journal of Physics*, vol. 17, no. 7, p. 073020, 2015.
- W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, *Numerical recipes in C*. Cambridge university press Cambridge, 1988.
- M. Rédei and S. J. Summers, “Quantum probability theory,” *Studies in History and Philosophy of Science Part B: Studies in History and Philosophy of Modern Physics*, vol. 38, no. 2, pp. 390–417, 2007.
- K. Ried, M. Agnew, L. Vermeyden, D. Janzing, R. W. Spekkens, and K. J. Resch, “A quantum advantage for inferring causal structure,” *Nature Physics*, vol. 11, no. 5, pp. 414–420, 2015.
- E. G. Rieffel and W. H. Polak, *Quantum computing: A gentle introduction*. MIT Press, 2011.
- M. Rossi, “Greedy additive approximation algorithms for minimum-entropy coupling problem,” in *2019 IEEE International Symposium on Information Theory (ISIT)*. IEEE, 2019, pp. 1127–1131.

- O. Rudolph, “On extremal quantum states of composite systems with fixed marginals,” *Journal of mathematical physics*, vol. 45, no. 11, pp. 4035–4041, 2004.
- C. Schilling, “Quantum marginal problem and its physical relevance (2015),” *arXiv preprint arXiv:1507.00299*.
- H. Tuy, *Convex Analysis and Global Optimization*, 2nd ed., ser. Springer optimization and its applications 110. Springer, 2016.
- H. Umegaki, “Conditional expectation in an operator algebra, IV (entropy and information),” in *Kodai Mathematical Seminar Reports*, vol. 14, no. 2, 1962, pp. 59–85.
- B. Zeng, X. Chen, D.-L. Zhou, and X.-G. Wen, *Quantum information meets quantum matter*. Springer, 2019.

## APPENDIX

**Algorithm 4:** Classical Entropic Causal Inference (Kocaoglu et al., 2017a)

---

**Input:** The joint probability distribution  $p(X, Y)$  for a pair of random variables  $X$  and  $Y$ .  
**Output:** The cause-effect relationship between  $X$  and  $Y$ .

```

/* Step 1: Compute marginal and conditional probability distributions from
   p(X, Y). */
1 Compute  $p(X)$  and  $p(Y)$ ;
2 Compute  $p(X|Y)$  and  $p(Y|X)$ ;
/* Step 2: Compute minimum entropy of the exogenous variables from X to Y
   and from Y to X. */
/* Estimation of minimum entropy  $H(E)$  for the causal model  $Y = f(X, E)$ . */
3  $M$  = the columns of the conditional probability distribution  $p(Y|X)$ ;
4  $H(E)$ =JointEntropyMinimization( $M$ );
5  $H(X \rightarrow Y) = H(X) + H(E)$ ;
/*  $H(\cdot)$  is the Shannon entropy i.e.,  $H(X) = -\sum_{i=1}^n p(X_i) \log(p(X_i))$  */
/* Estimation of minimum entropy  $H(E')$  for the causal model  $X = g(Y, E')$ . */
6  $M$  = the columns of the conditional probability distribution  $p(X|Y)$ ;
7  $H(E')$ =JointEntropyMinimization( $M$ );
/* Use Algorithm 5: Joint Entropy Minimization Algorithm */
8  $H(X \leftarrow Y) = H(Y) + H(E')$ ;
/* Step 3: Compare the minimum entropy from X to Y and from Y to X, and
   return the causal model with smaller entropy. */
9 if ( $H(X \rightarrow Y) < H(X \leftarrow Y)$ ) then
10 | return The causal model is of the form  $X \rightarrow Y$ .
11 else
12 | return The causal model is of the form  $X \leftarrow Y$ .
13 end

```

---

**Algorithm 5:** Joint Entropy Minimization Algorithm (Kocaoglu et al., 2017a)

---

**Input:** Marginal distributions of  $m$  variables each with  $n$  states, in matrix form  $M = [p_1^T; \dots; p_m^T]$ .  
**Output:** Minimum entropy  $e$  of the joint distributions.

```

1  $e = [ \ ]$ ;
2 Sort each row of  $M$  in decreasing order;
3 Find minimum of maximum of each row:  $r \leftarrow \min_i(p_i^T(1))$ ;
4 while  $r > 0$  do
5 |  $e \leftarrow [e, r]$ ;
6 | Update maximum of each row:  $p_i^T(1) \leftarrow p_i^T(1) - r, \forall i$ ;
7 | Sort each row of  $M$  in decreasing order;
8 |  $r \leftarrow \min_i(p_i^T(1))$ 
9 end
10 return  $e$ .

```

---

## DETAIL WORKOUT FOR QUANTUM SYMMETRIC CHANNEL

**Example 2** (Quantum Symmetric Channel). Consider the quantum qubit symmetric channel in Figure 8. Let the input qubit be in states either  $|0\rangle$  or  $|1\rangle$ . A quantum qubit symmetric channel with crossover probability  $p$ , denoted

by  $QSC_p$ , is a channel with qubit input  $X$  and qubit output  $Y$  and probability of error  $p$ . That is, if  $X$  is the transmitted qubit and  $Y$  the received qubit, then the channel is characterized by the conditional probabilities:

$$Pr(Y = |0\rangle|X = |0\rangle) = 1 - p$$

$$Pr(Y = |0\rangle|X = |1\rangle) = p$$

$$Pr(Y = |1\rangle|X = |0\rangle) = p$$

$$Pr(Y = |1\rangle|X = |1\rangle) = 1 - p$$




Fig. 8. Quantum symmetric channel

So, the joint density operator  $\rho_{XY}$  can be written as the superposition of the following density matrices, where  $q$  is the probability that  $X$  is in quantum state  $|0\rangle$  and  $1 - q$  is the probability that  $X$  is in quantum state  $|1\rangle$ .

$$\begin{aligned} \rho_{XY} &= q(1 - p) * (|00\rangle\langle 00|)(|00\rangle\langle 00|)^\dagger \\ &+ qp * (|01\rangle\langle 01|)(|01\rangle\langle 01|)^\dagger \\ &+ (1 - q)p * (|10\rangle\langle 10|)(|10\rangle\langle 10|)^\dagger \\ &+ (1 - q)(1 - p) * (|11\rangle\langle 11|)(|11\rangle\langle 11|)^\dagger. \end{aligned}$$

In this case we already know that  $X$  is the cause of  $Y$ . To verify this using our proposed method  $QECI$ , assume that the joint density matrix  $\rho_{XY}$  is given with  $p = 0.05$  and  $q = 0.4$ . So, we have:

$$\rho_{XY} = \begin{bmatrix} 0.38 & 0 & 0 & 0 \\ 0 & 0.02 & 0 & 0 \\ 0 & 0 & 0.03 & 0 \\ 0 & 0 & 0 & 0.57 \end{bmatrix}$$

Using  $QECI$  (Algorithm 2) we have (here we trace the algorithm line by line as follows):

1) Compute partial trace  $\rho_X = \text{Tr}_Y(\rho_{XY})$ :

$$\rho_X = \begin{bmatrix} 0.4 & 0 \\ 0 & 0.6 \end{bmatrix}$$

2) Compute partial trace  $\rho_Y = \text{Tr}_X(\rho_{XY})$ :

$$\rho_Y = \begin{bmatrix} 0.41 & 0 \\ 0 & 0.59 \end{bmatrix}$$

3) Compute  $\rho_{YX}$  by reordering the entries of  $\rho_{XY}$ , as follows:

$$\rho_{YX} = \begin{bmatrix} 0.38 & 0 & 0 & 0 \\ 0 & 0.03 & 0 & 0 \\ 0 & 0 & 0.02 & 0 \\ 0 & 0 & 0 & 0.57 \end{bmatrix}$$

4) Compute diagonal matrix  $D$  of eigenvalues and matrix  $V$  whose columns are the corresponding eigenvectors

for  $\rho_X$ , so that  $\rho_X * V = V * D$ :  $V = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$ , and  $D = \begin{bmatrix} 0.4 & 0 \\ 0 & 0.6 \end{bmatrix}$ .

5) For  $d_0 = 0.4, d_1 = 0.6$  do:

6) Compute pure states of eigenvectors  $e_0 = \begin{bmatrix} 1 & 0 \end{bmatrix}$  and  $e_1 = \begin{bmatrix} 0 & 1 \end{bmatrix}$  corresponding to the eigenvalues  $d_0 = 0.4, d_1 = 0.6$ , respectively, using the equation  $x_i = e_i * e_i^T$ , for  $i = 0, 1$ , where  $e_i^T$  is the transpose of  $e_i$ :

$$x_0 = \begin{bmatrix} 1 \\ 0 \end{bmatrix} * \begin{bmatrix} 1 & 0 \end{bmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix}$$

$$x_1 = \begin{bmatrix} 0 \\ 1 \end{bmatrix} * \begin{bmatrix} 0 & 1 \end{bmatrix} = \begin{bmatrix} 0 & 0 \\ 0 & 1 \end{bmatrix}$$

7) Compute instance conditionals as defined in Definition 1:

$$\rho_0 = \begin{bmatrix} 0.38 & 0 \\ 0 & 0.02 \end{bmatrix}, \text{ and } \rho_1 = \begin{bmatrix} 0.03 & 0 \\ 0 & 0.57 \end{bmatrix}$$

8) Compute instance conditional densities (normalizing by the trace of  $\rho_{Y||x_i\rangle_X}$ , for  $i = 0, 1$ ):  $\rho_{Y||x_0\rangle_X} =$

$$\begin{bmatrix} 0.95 & 0 \\ 0 & 0.05 \end{bmatrix}$$

$$\rho_{Y||x_1\rangle_X} = \begin{bmatrix} 0.05 & 0 \\ 0 & 0.95 \end{bmatrix}$$

9) Compute marginal distributions  $B_i = \text{eig}(\rho_{Y||x_i\rangle_X}$ , for  $i = 0, 1$ :

$$B_0 = \begin{bmatrix} 0.05 & 0.95 \end{bmatrix}, \text{ and } B_1 = \begin{bmatrix} 0.05 & 0.95 \end{bmatrix}$$

10) Add  $B_i$ 's to the  $i$ 'th row of the matrix  $M$ :

$$M = \begin{bmatrix} 0.05 & 0.95 \\ 0.05 & 0.95 \end{bmatrix}$$

11) **End of for loop.**

12) Apply Algorithm 5 to estimate joint entropy minimization:  $H(E) = 0.2864$

13) Compute  $H(X \rightarrow Y) = S(X) + H(E) = 0.2864 + 0.9710 = 1.2573$

14) Computes diagonal matrix  $D$  of eigenvalues and matrix  $V$  whose columns are the corresponding eigenvectors

for  $\rho_Y$ :

$$V = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, \text{ and } D = \begin{bmatrix} 0.41 & 0 \\ 0 & 0.59 \end{bmatrix}$$

15) **For**  $d_0 = 0.41, d_1 = 0.59$  **do**:

16) Compute pure states of eigenvectors  $e_0 = \begin{bmatrix} 1 & 0 \end{bmatrix}$  and  $e_1 = \begin{bmatrix} 0 & 1 \end{bmatrix}$  corresponding to the eigenvalues  $d_0 =$

$0.41, d_1 = 0.59$ , respectively:

$$y_0 = \begin{bmatrix} 1 \\ 0 \end{bmatrix} * \begin{bmatrix} 1 & 0 \end{bmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix}$$

$$y_1 = \begin{bmatrix} 0 \\ 1 \end{bmatrix} * \begin{bmatrix} 0 & 1 \end{bmatrix} = \begin{bmatrix} 0 & 0 \\ 0 & 1 \end{bmatrix}$$

17) Compute instance conditionals as defined in Definition 1:

$$\rho_0 = \begin{bmatrix} 0.38 & 0 \\ 0 & 0.03 \end{bmatrix}, \text{ and } \rho_1 = \begin{bmatrix} 0.02 & 0 \\ 0 & 0.57 \end{bmatrix}$$

18) Compute instance conditional density matrices (normalizing by the trace of  $\rho_{X||y_i\rangle_Y}$ , for  $i = 0, 1$ ):

$$\rho_{X||y_0\rangle_Y} = \begin{bmatrix} 0.9268 & 0 \\ 0 & 0.0732 \end{bmatrix}$$

$$\rho_{X||y_1\rangle_Y} = \begin{bmatrix} 0.0339 & 0 \\ 0 & 0.9661 \end{bmatrix}$$

19) Compute marginal distributions  $B_i = \text{eig}(\rho_{X||y_i\rangle_Y}$ , for  $i = 0, 1$ :

$$B_0 = \begin{bmatrix} 0.0732 & 0.9268 \end{bmatrix} \quad B_1 = \begin{bmatrix} 0.0339 & 0.9661 \end{bmatrix}$$

20) Add  $B_i$ 's to the  $i$ 'th row of the matrix  $M$ :

$$M = \begin{bmatrix} 0.0732 & 0.9268 \\ 0.0339 & 0.9661 \end{bmatrix}$$

21) **End of for loop.**

22) Apply Algorithm 5 to estimate joint entropy minimization:  $H(E') = 0.4505$

23) Compute  $H(X \leftarrow Y) = S(Y) + H(E') = 0.4505 + 0.9765 = 1.4270$

24) Compare  $H(X \rightarrow Y)$  and  $H(X \leftarrow Y)$ :  $H(X \rightarrow Y) < H(X \leftarrow Y)$

25) **return**: The causal model is of the form  $X \rightarrow Y$ .