

A MCMC-type simple probabilistic approach for determining optimal progressive censoring schemes

Ritwik Bhattacharya¹ and Narayanaswamy Balakrishnan²

¹*Department of Industrial Engineering, School of Engineering and Sciences, Tecnológico de Monterrey, Querétaro 76130, México*

¹*Department of Mathematics and Statistics, McMaster University, Hamilton, ON L8S 4K1, Canada*

Abstract

We present here a simple probabilistic approach for determining an optimal progressive censoring scheme by defining a probability structure on the set of feasible solutions. Given an initial solution, the new updated solution is computed within the probabilistic structure. This approach will be especially useful when the cardinality of the set of feasible solutions is large. The validation of the proposed approach is demonstrated by comparing the optimal scheme with these obtained by exhaustive numerical search.

Keywords: Life-testing experiment, Near-optimal solution, Optimal censoring, Quantile, Variance measure, cost criterion.

1 Introduction

Let us first consider the Type-II progressive censoring scheme. Suppose n test units are placed on a life-testing experiment. A pre-fixed integer m , representing the number of failures to be observed, is chosen before the experiment starts. At the time of first failure, denoted by $X_{1:m:n}$, R_1 units are randomly removed from the remaining $n - 1$ live units. At the time of second failure, denoted by $X_{2:m:n}$, R_2 units are randomly removed from the remaining $n - R_1 - 2$ live units, and so on. Finally, at the time of m th failure, denoted by $X_{m:m:n}$, all the remaining units $n - R_1 - \dots - R_{m-1} - m$ (say, R_m) are removed from the testing, terminating the experiment. Therefore, the integers R_1, \dots, R_m satisfy the identity

$$R_1 + \dots + R_m = n - m.$$

The quantities $X_{i:m:n}, i = 1, 2, \dots, m$, are called progressively Type-II censored ordered statistics; see [Balakrishnan and Cramer \(2014\)](#). A Type-II progressive censoring scheme is characterized by the parameters n, m and

(R_1, \dots, R_m) . Note that, for given n and m , there are many choices of R_i 's, and let us denote the set of all those choices by

$$\text{CS}(n, m) = \left\{ \mathcal{R} = (R_1, \dots, R_m) \in \mathcal{N}^m \mid \sum_{i=1}^m R_i = n - m, \mathcal{N} = \{0, 1, \dots, n - m\} \right\}.$$

The cardinality of the set $\text{CS}(n, m)$ is $\binom{n-1}{m-1}$ which becomes quite large even for moderate values of n and m . For instance, when $(n, m) = (30, 10)$, the cardinality is in fact 30045015. Therefore, our interest is then to find the optimal Type-II progressive censoring scheme under some suitable optimality criterion function $\psi : \text{CS}(n, m) \rightarrow [0, \infty)$. The problem of determining optimal progressive censoring scheme has been discussed considerably in the literature; see, [Balakrishnan and Cramer \(2014\)](#) for relevant details.

[Balakrishnan and Aggarwala \(2000\)](#) were the first to discuss optimal progressive censoring scheme by taking ψ to be the variance of the best linear unbiased estimators (BLUEs) of the model parameters and computed optimal scheme by minimizing it under normal and extreme value distributions. Due to the computational complexity, they presented the optimal schemes only up to $n = 50$ and $m = 3$ (see [Balakrishnan and Aggarwala, 2000](#), pages 197-204). Using the same optimality criterion, [Burkschat et al. \(2006, 2007\)](#) computed optimal censoring schemes for generalized Pareto distribution. Some more choices of ψ , such as total time on test, expected test duration and variance of the test time were considered by [Burkschat \(2008\)](#). Interestingly, in all these articles, optimal schemes mostly emerged as one-step progressive censoring, that is, censoring occurs only at one failure time (mathematically, exactly one R_i is positive). [Balakrishnan et al. \(2008\)](#) and [Ng et al. \(2004\)](#) also introduced three choices of ψ based on the asymptotic variance-covariance matrix and Fisher information, and computed optimal schemes under Weibull lifetime model. [Pradhan and Kundu \(2009, 2013\)](#) proposed criterion based on asymptotic variance of estimated p th quantile of the underlying lifetime distribution and obtained the optimal censoring schemes for generalized exponential and Birnbaum-Saunders distributions. [Bhattacharya et al. \(2016\)](#) introduced a meta-heuristic algorithm, called variable neighborhood search (VNS), for the determination of optimal censoring schemes. They showed that the VNS algorithm performs sufficiently well for moderate to large values of n and m . Recently, [Bhattacharya \(2020\)](#) introduced the notion of compound optimal design strategy under progressive censoring in a multi-criteria setup.

In this work, we propose a method based on a probabilistic structure through which optimal censoring schemes can be computed. The proposed al-

gorithm works in principle similar to the Markov Chain Monte Carlo (MCMC) technique; but, it is not a MCMC method as there is no target distribution. The algorithm is described in the subsequent sections along with some numerical results. For illustrative purpose, we consider a variance measure and a cost measure as optimality criterion. In fact, any optimality criteria can be utilized in the proposed method.

The rest of the paper is organized as follows. The main algorithm based on the probability structure is presented in Section 2. In Section 3, the algorithmic steps under three distributions, namely, multinomial, uniform and multivariate hypergeometric distributions, are discussed. Section 4 presents some numerical results for the proposed approach and some comparative results. Finally, some concluding remarks are made in Section 5.

2 Algorithm based on probability structure

Suppose the members of the set $CS(n, m)$ can be generated through a known probability distribution on \mathcal{R} , say, $\pi_{\mathcal{R}}(\cdot)$. This is analogous to the proposal density in MCMC technique. So, in analogy to target density in MCMC, we shall construct a monotone function $f_{\mathcal{R}|\psi(\mathcal{R})}(\cdot)$ of criterion $\psi(\mathcal{R})$. Depending on the minimization (or maximization) of the criterion function $\psi(\mathcal{R})$, the choice of $f_{\mathcal{R}|\psi(\mathcal{R})}(\cdot)$ will be monotone decreasing (or increasing) function. Then, the algorithm will simulate censoring schemes \mathcal{R} from $\pi_{\mathcal{R}}(\cdot)$ and the optimal scheme will be selected based on the following probability rule. Let \mathcal{R}^{old} be a candidate censoring scheme simulated from $\pi_{\mathcal{R}}(\cdot)$. A new candidate censoring scheme \mathcal{R}^{new} , obtained from the old candidate \mathcal{R}^{old} , will then be accepted with probability

$$\alpha = \min \left\{ 1, \frac{f_{\mathcal{R}|\psi(\mathcal{R})}(\mathcal{R}^{\text{new}}) \times \pi_{\mathcal{R}}(\mathcal{R}^{\text{old}})}{f_{\mathcal{R}|\psi(\mathcal{R})}(\mathcal{R}^{\text{old}}) \times \pi_{\mathcal{R}}(\mathcal{R}^{\text{new}})} \right\}.$$

Because of the monotonic structure of $f_{\mathcal{R}|\psi(\mathcal{R})}(\cdot)$, the algorithm will always try to accept better candidate censoring schemes with probability α . Consequently, starting with an initial simulated candidate \mathcal{R}^{old} from $\pi_{\mathcal{R}}(\cdot)$, the algorithm will tend to reach optimal censoring scheme after a number of simulation runs. It is important to note that this is not a MCMC because $f_{\mathcal{R}|\psi(\mathcal{R})}(\cdot)$ is no longer a probability structure. In particular, we choose

$$f_{\mathcal{R}|\psi(\mathcal{R})}(\psi(\mathcal{R})|\mathcal{R}) = e^{-\psi(\mathcal{R})}$$

for computational implementation purpose. Also, for the choice of $\pi_{\mathcal{R}}(\cdot)$, we choose multinomial, uniform and multivariate hypergeometric distributions.

Regarding the choices of optimality criterion $\psi(\mathcal{R})$, several options have been discussed in the literature, and a list of these options can be found in [Bhattacharya \(2020\)](#). In this work, we consider two optimality criteria. The first one is based on a variance measure given by

$$\psi(\mathcal{R}) = \int_0^1 \text{Var}[\ln \hat{X}_s] ds,$$

where \hat{X}_s represents the maximum likelihood estimate of X_s , the s th quantile of the underlying lifetime distribution. The aggregate variance of the log-quantile estimates over all quantile points get summarized under this measure. Moreover, the criterion is scale-invariant meaning that the optimal scheme computed by optimizing the criterion does not change if the time scale gets changed. This is a desirable property in an optimizing criterion used in life-testing experiments (see [Bhattacharya et al., 2016](#)). The second criterion is based on a cost measure given by

$$\psi(\mathcal{R}) = C_o + C_f m + C_t E[X_{m:m:n}],$$

where C_f is the cost per unit of failure, C_t is the cost per unit of duration of testing, and C_o is an overall fixed cost that does not depend on the design parameters of the test. This criterion is also scale-invariant.

A Weibull lifetime model with distribution function of the form

$$F(x; \beta, k) = 1 - e^{-(kx)^\beta},$$

where $\beta > 0$ and $k > 0$ are the shape and scale parameters, respectively, is considered for illustrative purpose. The required expressions of $\psi(\mathcal{R})$ under Weibull model are presented in the Appendix.

3 Different choices for $\pi_{\mathcal{R}}(\cdot)$

As mentioned in the last section, $\pi_{\mathcal{R}}(\cdot)$ needs to be specified with some known probability distribution, and then the censoring schemes will be simulated from this distribution. A complicated probability structure may increase the computational complexity of the algorithm. Here, we choose three known probability distributions for $\pi_{\mathcal{R}}(\cdot)$ and then assess the corresponding numerical results.

3.1 Multinomial distribution

Let us assume a multinomial distribution with probability mass function

$$\pi_{\mathcal{R}}(R_1, \dots, R_m; p_1, \dots, p_m) = \frac{(n-m)!}{R_1! \dots R_m!} p_1^{R_1} \dots p_m^{R_m}, \quad (1)$$

where $(n-m)$ and $p_i > 0, i = 1, \dots, m$, are the parameters; see [Johnson et al. \(1997\)](#) for various properties of this distribution. The simulation of a candidate from (1) is straightforward and any candidate generated from (1) automatically would satisfy the censoring constraint imposed by progressive censoring, namely, $R_1 + \dots + R_m = n - m$. Now, to run the algorithm, we adopt the following two steps:

Step 1 (Simulating \mathcal{R}_0) An initial candidate \mathcal{R}_0 can be simulated in the following manner. Generate m random numbers $u_i, i = 1, \dots, m$, from a uniform distribution $U[0, 1]$, and set

$$p_i = \frac{u_i}{\sum_{i=1}^m u_i}.$$

Then, \mathcal{R}_0 can be directly simulated from the multinomial distribution with parameters $n - m$ and (p_1, p_2, \dots, p_m) ;

Step 2 (Simulating \mathcal{R}_1 from \mathcal{R}_0) Now, given \mathcal{R}_0 , a new \mathcal{R}_1 can be randomly generated from \mathcal{R}_0 in the following manner. We randomly replace full/partial components of \mathcal{R}_0 with observations generated from a multinomial distribution. First, randomly choose $m_1 (0 < m_1 \leq m)$ positions of \mathcal{R}_0 . Let (R'_1, \dots, R'_{m_1}) and $(p_{R'_1}, \dots, p_{R'_{m_1}})$ denote the corresponding positions and probability values in \mathcal{R}_0 , respectively. Now, we recalculate the probabilities for these m_1 positions as

$$q_j = \frac{p_{R'_j}}{\sum_{j=1}^{m_1} p_{R'_j}},$$

where $j = 1, \dots, m_1$. We then simulate m_1 values from the multinomial distribution with parameters $\sum_{j=1}^{m_1} R'_j$ and (q_1, \dots, q_{m_1}) , and concatenate with \mathcal{R}_0 .

Following the above two steps, a new candidate will be accepted with probability

$$\min \left\{ 1, \frac{f_{\mathcal{R}|\psi(\mathcal{R})}(\psi(\mathcal{R}_1)|\mathcal{R}_1) \times \pi_{\mathcal{R}}(\mathcal{R}_0; p_1, p_2, \dots, p_m)}{f_{\mathcal{R}|\psi(\mathcal{R})}(\psi(\mathcal{R}_0)|\mathcal{R}_0) \times \pi_{\mathcal{R}}(\mathcal{R}_1; p_1, p_2, \dots, p_m)} \right\}.$$

At each time of acceptance of a candidate, a new updated optimal solution is obtained, and we would therefore expect to obtain the optimal solution after performing a number of simulation runs.

3.2 Uniform distribution

Let us consider a discrete uniform distribution to construct \mathcal{R}_0 , \mathcal{R}_1 and $\pi_{\mathcal{R}}(\cdot)$ in the following manner. First, generate a random number between 0 and $n - m$ and set it as R_1 . Then, generate another number between 0 and $n - m - R_1$ and set it as R_2 . Continue the process until all m positions are filled up. Thus, \mathcal{R}_0 gets generated and

$$\pi_{\mathcal{R}}(\mathcal{R}_0) = \frac{1}{(n - m)(n - m - R_1) \cdots (n - m - R_1 - \cdots - R_{m-1})}.$$

Next, we generate a new \mathcal{R}_1 from \mathcal{R}_0 as follows. Randomly choose a position in \mathcal{R}_0 and let the corresponding value at that position be r_0 . Then, first generate a number randomly between 0 and $n - m - r_0$ and set it as R_1 in \mathcal{R}_1 ; generate another number between 0 and $n - m - R_1$ and set it as R_2 in \mathcal{R}_1 ; and continue this process until all m positions are filled up. Thus, we can generate \mathcal{R}_1 and

$$\pi_{\mathcal{R}}(\mathcal{R}_1) = \frac{1}{(n - m - r_0)(n - m - R_1) \cdots (n - m - R_1 - \cdots - R_{m-1})}.$$

Thence, a new candidate will be accepted with probability

$$\min \left\{ 1, \frac{f_{\mathcal{R}|\psi(\mathcal{R})}(\psi(\mathcal{R}_1)|\mathcal{R}_1) \times \pi_{\mathcal{R}}(\mathcal{R}_0)}{f_{\mathcal{R}|\psi(\mathcal{R})}(\psi(\mathcal{R}_0)|\mathcal{R}_0) \times \pi_{\mathcal{R}}(\mathcal{R}_1)} \right\}.$$

3.3 Multivariate hypergeometric distribution

Let us assume a multivariate hypergeometric distribution with probability mass function

$$\pi_{\mathcal{R}}(R_1, \dots, R_m; M, (M_1, \dots, M_m), R) = \frac{\binom{M_1}{R_1} \cdots \binom{M_m}{R_m}}{\binom{M}{R}}, \quad (2)$$

where M , (M_1, \dots, M_m) and R are the parameters with $M_j = n - m$, for $j = 1, \dots, m$, $M = \sum_{j=1}^m M_j = m(n - m)$ and $R = \sum_{j=1}^m R_j = n - m$; see [Johnson et al. \(1997\)](#) for properties of this distribution. One may readily note that any candidate simulated from (2) would automatically satisfy the constraint imposed by progressive censoring. For given n and m , simulation of one candidate as \mathcal{R}_0 is straightforward. Next, we use the following steps to generate \mathcal{R}_1 from \mathcal{R}_0 . First, randomly choose m_1 ($0 < m_1 \leq m$) positions of \mathcal{R}_0 , and let (R'_1, \dots, R'_{m_1}) denote the corresponding positions. Next, simulate a candidate of length m_1 from a multivariate hypergeometric distribution with parameters $M_j = \sum_{j=1}^{m_1} R'_j$, $M = \sum_{j=1}^{m_1} M_j$ and $R = \sum_{j=1}^{m_1} R'_j$,

and concatenate with \mathcal{R}_0 . Then, proceeding as before, a new candidate will be accepted with probability

$$\min \left\{ 1, \frac{f_{\mathcal{R}|\psi(\mathcal{R})}(\psi(\mathcal{R}_1)|\mathcal{R}_1) \times \pi_{\mathcal{R}}(\mathcal{R}_0; M, (M_1, \dots, M_m), R)}{f_{\mathcal{R}|\psi(\mathcal{R})}(\psi(\mathcal{R}_0)|\mathcal{R}_0) \times \pi_{\mathcal{R}}(\mathcal{R}_1; M, (M_1, \dots, M_m), R)} \right\}.$$

4 Numerical results

We shall use Weibull distribution with parameters $(\beta, k)=(1, 0.5)$, $(1, 1)$ and $(1, 2)$ as the underlying lifetime model. We evaluate the performance of the proposed algorithm by comparing it with the optimal solution obtained through exhaustive search. Due to the large cardinality of the set $\text{CS}(n, m)$, exhaustive search is only possible for small value of n and m . For this reason, we set $(n, m)=(10, 5)$, $(15, 5)$, $(20, 5)$ and compared the optimal solutions by a relative efficiency measure defined as

$$\text{R.eff}_1 = \frac{\text{The value } \psi(\mathcal{R}^*) \text{ corresponding to optimal scheme } \mathcal{R}^* \text{ in exhaustive search}}{\text{The value } \psi(\mathcal{R}^\bullet) \text{ corresponding to optimal scheme } \mathcal{R}^\bullet \text{ in proposed approach}}.$$

The optimal schemes and the corresponding relative efficiencies so determined are presented in Table 1. These results show that even though the proposed approach does not achieve the true optimal scheme \mathcal{R}^* , but the corresponding relative efficiencies are very close to 1. For this reason, we refer to the obtained solution \mathcal{R}^\bullet as near-optimal censoring scheme. In addition, we have reported two quantities n_{it} and n_{ac} representing the number of simulation runs and accepted candidates, respectively. The corresponding results show the performance of multinomial distribution to be better than the uniform and multivariate hypergeometric distributions in that multinomial needs less number of accepted candidates than the other two distributions to reach near-optimal scheme with the same relative efficiency when the cardinality of the set $\text{CS}(n, m)$ is large.

As pointed out in [Bhattacharya et al. \(2016\)](#), the VNS algorithm provides near-optimal censoring schemes for large values of n and m . Therefore, we also compare the performance of the proposed approach with the VNS algorithm, and the corresponding results are reported in Table 2. We use the notation \mathcal{R}^\dagger to denote the near-optimal scheme obtained through the VNS algorithm, and we define a relative efficiency measure as

$$\text{R.eff}_2 = \frac{\text{The value of } \int_0^1 \text{Var}[\ln \hat{X}_s] ds \text{ corresponding to optimal scheme } \mathcal{R}^\dagger \text{ in VNS algorithm}}{\text{The value of } \int_0^1 \text{Var}[\ln \hat{X}_s] ds \text{ corresponding to optimal scheme } \mathcal{R}^\bullet \text{ in proposed approach}}.$$

The results in Table 2 show that, even though the near-optimal schemes are different, the corresponding $R.\text{eff}_2$ are always 1 indicating that the proposed approach performs well as compared to the VNS algorithm. While reporting the optimal schemes, we use the notation a^b to denote that a is repeated b times. For example, the scheme $((0^5, 20, 0^4))$ for the case $(n, m) = (30, 10)$ under VNS algorithm in Table 2 refers to the scheme $(0, 0, 0, 0, 0, 20, 0, 0, 0, 0)$. In a similar vein, the relative efficiency under cost criterion measure is defined as

$$R.\text{eff}_3 = \frac{\text{The value of } C_o + C_f m + C_t E[X_{m:m:n}] \text{ corresponding to optimal scheme } \mathcal{R}^\dagger \text{ in VNS algorithm}}{\text{The value of } C_o + C_f m + C_t E[X_{m:m:n}] \text{ corresponding to optimal scheme } \mathcal{R}^\bullet \text{ in proposed approach}}.$$

Although, the numerical results are not reported here, it is found that the efficiencies $R.\text{eff}_3$ are all once again close to one.

5 Conclusions

In this work, we have used a probability structure to develop a simple algorithm for the determination of optimal progressive censoring scheme. We have used three probability distributions for $\pi_{\mathcal{R}}(\cdot)$ for illustrative purpose. The comparisons made with a direct exhaustive search method and the VNS algorithm demonstrate the efficiency and good performance of the proposed method.

Appendix

Variance and cost measures under Weibull model

To derive explicit expressions for the two criteria used here, we first need the density of $X_{i:m:n}$, given by the Kamps-Cramer representation (see [Balakrishnan, 2007](#); [Balakrishnan and Cramer, 2014](#)), as

$$f_{X_{i:m:n}}(x; \theta) = \sigma_{i-1} \sum_{p=1}^i a_{p,i} \{1 - F(x; \theta)\}^{\gamma_p - 1} f(x; \theta), \quad \text{for } i = 1, \dots, m,$$

where $\gamma_r = m - r + 1 + \sum_{i=r}^m R_i$, for $r = 1, \dots, m$, $\sigma_{r-1} = \prod_{i=1}^r \gamma_i$, $a_{i,r} = \prod_{\substack{j=1 \\ j \neq i}}^r \frac{1}{\gamma_j - \gamma_i}$ for $1 \leq i \leq r \leq m$ with $a_{1,1} = 1$, and $f(x; \theta)$ is the probability

density function of X with $\theta = (\beta, k)$. From the above density function of $X_{i:m:n}$, $E[X_{m:m:n}]$ can be found to be

$$E[X_{m:m:n}] = \frac{1}{k} \Gamma \left(1 + \frac{1}{\beta} \right) \sigma_{m-1} \sum_{p=1}^m \frac{a_{p,m}}{\gamma_p^{1+\frac{1}{\beta}}}.$$

Finally, to derive an expression of the variance measure, we need the expression of Fisher information matrix about θ given by (see [Bhattacharya et al., 2016](#))

$$\mathcal{I}(\theta) = \begin{bmatrix} \mathcal{I}_{11}(\theta) & \mathcal{I}_{12}(\theta) \\ \mathcal{I}_{21}(\theta) & \mathcal{I}_{22}(\theta) \end{bmatrix},$$

where

$$\begin{aligned} \mathcal{I}_{11}(\theta) &= \frac{1}{\beta^2} \sum_{i=1}^m \sum_{j=1}^i \sigma_{i-1} \frac{a_{j,i}}{\gamma_j} \int_0^\infty \left(1 + \ln \left(\frac{z}{\gamma_j} \right) \right)^2 e^{-z} dz, \\ \mathcal{I}_{22}(\theta) &= \left(\frac{\beta}{k} \right)^2 \sum_{i=1}^m \sum_{j=1}^i \sigma_{i-1} \frac{a_{j,i}}{\gamma_j}, \\ \mathcal{I}_{12}(\theta) = \mathcal{I}_{21}(\theta) &= \frac{1}{k} \sum_{i=1}^m \sum_{j=1}^i \sigma_{i-1} \frac{a_{j,i}}{\gamma_j} \int_0^\infty \left(1 + \ln \left(\frac{z}{\gamma_j} \right) \right) e^{-z} dz. \end{aligned}$$

It is difficult to find the exact expression of $\int_0^1 \text{Var}[\ln \hat{X}_s] ds$. However, by using delta method, the asymptotic expression of $\text{Var}[\ln \hat{X}_s]$ can be found to be $\text{Var}[\ln \hat{X}_s] = (\mathcal{I}^{11}(\theta)/\beta^4) (g(s))^2 + (2\mathcal{I}^{12}(\theta)/\beta^2 k) g(s) + (\mathcal{I}^{22}(\theta)/k^2)$, where $g(s) = \ln\{-\ln(1-s)\}$, and $\mathcal{I}^{11}(\theta)$, $\mathcal{I}^{12}(\theta)$ and $\mathcal{I}^{22}(\theta)$ are the elements of the inverse of the Fisher information matrix given by

$$\mathcal{I}^{-1}(\theta) = \begin{bmatrix} \mathcal{I}^{11}(\theta) & \mathcal{I}^{12}(\theta) \\ \mathcal{I}^{21}(\theta) & \mathcal{I}^{22}(\theta) \end{bmatrix}.$$

Therefore, an asymptotic expression of $\int_0^1 \text{Var}[\ln \hat{X}_s] ds$ can be obtained readily as

$$\frac{\mathcal{I}^{11}(\theta)}{\beta^4} \int_0^1 (g(s))^2 ds + \frac{2\mathcal{I}^{12}(\theta)}{\beta^2 k} \int_0^1 g(s) ds + \frac{\mathcal{I}^{22}(\theta)}{k^2}.$$

References

Balakrishnan, N. (2007). Progressive censoring methodology: An appraisal. *Test*, **16**:211–296 (with discussions).

- Balakrishnan, N. and Aggarwala, R. (2000). *Progressive Censoring: Theory, Methods, and Applications*. Birkhäuser, Boston.
- Balakrishnan, N., Burkschat, M., Cramer, E., and Hofmann, G. (2008). Fisher information based progressive censoring plans. *Computational Statistics & Data Analysis*, **53**:366–380.
- Balakrishnan, N. and Cramer, E. (2014). *The Art of Progressive Censoring: Application to Reliability and Quality*. Birkhäuser, Boston.
- Bhattacharya, R. (2020). Implementation of compound optimal design strategy in censored life-testing experiment. *Test*, **29**:1029–1050.
- Bhattacharya, R., Pradhan, B., and Dewanji, A. (2016). On optimum life-testing plans under Type-II progressive censoring scheme using variable neighborhood search algorithm. *Test*, **25**:309–330.
- Burkschat, M. (2008). On optimality of extremal schemes in progressive Type II censoring. *Journal of Statistical Planning and Inference*, **138**:1647–1659.
- Burkschat, M., Cramer, E., and Kamps, U. (2006). On optimal schemes in progressive censoring. *Statistics & Probability Letters*, **76**:1032–1036.
- Burkschat, M., Cramer, E., and Kamps, U. (2007). Optimality criteria and optimal schemes in progressive censoring. *Communications in Statistics - Theory and Methods*, **36**:1419–1431.
- Johnson, N. L., Kotz, S., and Balakrishnan, N. (1997). *Discrete Multivariate Distributions*. John Wiley & Sons, New York.
- Ng, H. K. T., Chan, P. S., and Balakrishnan, N. (2004). Optimal progressive censoring plans for the Weibull distribution. *Technometrics*, **46**:470–481.
- Pradhan, B. and Kundu, D. (2009). On progressively censored generalized exponential distribution. *Test*, **18**:497–515.
- Pradhan, B. and Kundu, D. (2013). Inference and optimal censoring schemes for progressively censored Birnbaum-Saunders distribution. *Journal of Statistical Planning and Inference*, **143**:1098–1108.

Table 1: Comparison between the optimal censoring schemes obtained through exhaustive search and the proposed algorithm under the criterion $\psi(\mathcal{R}) = \int_0^1 \text{Var}[\ln \hat{X}_s] ds$ in the case of Weibull lifetime model.

Parameters (β, k)	(n, m)	Exhaustive search		Multinomial			
		\mathcal{R}^*	$\psi(\mathcal{R}^*)$	n_{it}	n_{ac}	\mathcal{R}^\bullet	R.eff ₁
(0.5, 1)	(10, 5)	(0, 4, 1, 0, 0)	2.4261	500	500	(0, 4, 0, 0, 1)	0.9995
				1000	1000	(0, 4, 0, 0, 1)	0.9995
				10000	8902	(0, 4, 0, 0, 1)	0.9995
				50000	18936	(0, 4, 0, 0, 1)	0.9995
				100000	99952	(0, 4, 0, 0, 1)	0.9995
Parameters (β, k)	(n, m)	Exhaustive search		Uniform			
		\mathcal{R}^*	$\psi(\mathcal{R}^*)$	n_{it}	n_{ac}	\mathcal{R}^\bullet	R.eff ₁
(0.5, 1)	(10, 5)	(0, 4, 1, 0, 0)	2.4261	500	412	(0, 4, 0, 0, 1)	0.9990
				1000	420	(0, 4, 0, 0, 1)	0.9990
				10000	9508	(0, 4, 0, 0, 1)	0.9990
				50000	47487	(0, 4, 0, 0, 1)	0.9990
				100000	49685	(0, 4, 0, 0, 1)	0.9990
Parameters (β, k)	(n, m)	Exhaustive search		Multivariate hypergeometric			
		\mathcal{R}^*	$\psi(\mathcal{R}^*)$	n_{it}	n_{ac}	\mathcal{R}^\bullet	R.eff ₁
(0.5, 1)	(10, 5)	(0, 4, 1, 0, 0)	2.4261	500	358	(1, 4, 0, 0, 0)	0.9995
				1000	600	(1, 4, 0, 0, 0)	0.9995
				10000	7016	(1, 1, 0, 2, 1)	0.9995
				50000	35566	(1, 1, 1, 0, 2)	0.9998
				100000	26463	(0, 0, 6, 3, 6)	0.9998
Parameters (β, k)	(n, m)	Exhaustive search		Multinomial			
		\mathcal{R}^*	$\psi(\mathcal{R}^*)$	n_{it}	n_{ac}	\mathcal{R}^\bullet	R.eff ₁
(1, 1)	(15, 5)	(0, 10, 0, 0, 0)	0.4983	500	310	(0, 0, 5, 5, 0)	0.9996
				1000	508	(0, 7, 2, 0, 1)	0.9996
				10000	5438	(0, 8, 1, 1, 0)	0.9996
				50000	26141	(0, 9, 1, 0, 0)	0.9996
				100000	45858	(0, 12, 3, 0, 0)	0.9998
Parameters (β, k)	(n, m)	Exhaustive search		Uniform			
		\mathcal{R}^*	$\psi(\mathcal{R}^*)$	n_{it}	n_{ac}	\mathcal{R}^\bullet	R.eff ₁
(1, 1)	(15, 5)	(0, 10, 0, 0, 0)	0.4983	500	500	(0, 9, 0, 0, 1)	0.9997
				1000	518	(0, 9, 0, 0, 1)	0.9997
				10000	8643	(0, 9, 0, 0, 1)	0.9997
				50000	49507	(0, 9, 0, 0, 1)	0.9997
				100000	49685	(0, 14, 0, 0, 1)	0.9998
Parameters (β, k)	(n, m)	Exhaustive search		Multivariate hypergeometric			
		\mathcal{R}^*	$\psi(\mathcal{R}^*)$	n_{it}	n_{ac}	\mathcal{R}^\bullet	R.eff ₁
(1, 1)	(15, 5)	(0, 10, 0, 0, 0)	0.4983	500	275	(2, 6, 2, 0, 0)	0.9996
				1000	575	(0, 5, 4, 0, 1)	0.9996
				10000	5933	(1, 1, 8, 0, 0)	0.9996
				50000	29809	(1, 8, 0, 0, 1)	0.9998
				100000	26463	(0, 0, 6, 3, 6)	0.9998
Parameters (β, k)	(n, m)	Exhaustive search		Multinomial			
		\mathcal{R}^*	$\psi(\mathcal{R}^*)$	n_{it}	n_{ac}	\mathcal{R}^\bullet	R.eff ₁
(2, 1)	(20, 5)	(0, 15, 0, 0, 0)	0.1113	500	244	(0, 0, 3, 10, 2)	0.9998
				1000	414	(0, 0, 3, 10, 2)	0.9998
				10000	4799	(0, 9, 6, 0, 0)	0.9998
				50000	24105	(0, 2, 13, 0, 0)	0.9998
				100000	45858	(0, 12, 3, 0, 0)	0.9998
Parameters (β, k)	(n, m)	Exhaustive search		Uniform			
		\mathcal{R}^*	$\psi(\mathcal{R}^*)$	n_{it}	n_{ac}	\mathcal{R}^\bullet	R.eff ₁
(2, 1)	(20, 5)	(0, 15, 0, 0, 0)	0.1113	500	440	(0, 14, 0, 0, 1)	0.9998
				1000	987	(0, 14, 0, 0, 1)	0.9998
				10000	8431	(0, 14, 0, 0, 1)	0.9998
				50000	28759	(0, 14, 0, 0, 1)	0.9998
				100000	49685	(0, 14, 0, 0, 1)	0.9998
Parameters (β, k)	(n, m)	Exhaustive search		Multivariate hypergeometric			
		\mathcal{R}^*	$\psi(\mathcal{R}^*)$	n_{it}	n_{ac}	\mathcal{R}^\bullet	R.eff ₁
(2, 1)	(20, 5)	(0, 15, 0, 0, 0)	0.1113	500	246	(4, 2, 0, 2, 7)	0.9998
				1000	581	(0, 1, 6, 2, 6)	0.9998
				10000	5387	(0, 1, 4, 8, 2)	0.9998
				50000	26835	(0, 3, 3, 6, 3)	0.9998
				100000	46463	(0, 0, 6, 3, 6)	0.9998

Table 2: Comparison of near-optimal censoring schemes (for large n and m) between the proposed approach and the VNS algorithm (Bhattacharya et al., 2016) under the criterion $\psi(\mathcal{R}) = \int_0^1 \text{Var}[\ln \hat{X}_s] ds$ in the case of Weibull lifetime model.

(n, m)	VNS algorithm		Multinomial		R.eff ₂
	\mathcal{R}^\dagger	$\psi(\mathcal{R}^\dagger)$	\mathcal{R}^\bullet	$\psi(\mathcal{R}^\bullet)$	
(30, 10)	$(0^5, 20, 0^4)$	0.2826	$(0^3, 1, 0, 2, 11, 3^2, 0)$	0.2826	1
(30, 15)	$(0^7, 15, 0^7)$	0.2505	$(0^5, 18, 2, 0^3)$	0.2826	1
(35, 10)	$(0^6, 25, 0^3)$	0.2664	$(0^4, 2, 5^2, 8, 4, 1)$	0.2664	1
(35, 15)	$(0^6, 20, 0^8)$	0.2342	$(0^6, 2, 0, 1^2, 2, 0, 5^2, 4)$	0.2342	1
(35, 20)	$(0^6, 15, 0^{14})$	0.2189	$(0^6, 4, 0, 2, 0^4, 2, 0, 2, 0, 2^2, 1)$	0.2189	1
(45, 10)	$(0^6, 35, 0^3)$	0.2442	$(0^3, 4, 11, 4, 9, 2, 3, 2)$	0.2442	1
(45, 15)	$(0^7, 2, 0^6, 28)$	0.2118	$(0^3, 1^2, 5^2, 0, 7, 0^2, 8, 2, 0, 1)$	0.2118	1
(45, 20)	$(0^{19}, 25)$	0.1964	$(0^5, 1, 0^2, 4, 1^2, 0, 1^2, 5, 1, 0, 2, 3, 5)$	0.1964	1
(n, m)	VNS algorithm		Uniform		R.eff ₂
	\mathcal{R}^\dagger	$\psi(\mathcal{R}^\dagger)$	\mathcal{R}^\bullet	$\psi(\mathcal{R}^\bullet)$	
(30, 10)	$(0^5, 20, 0^4)$	0.2826	$(0^4, 13, 6, 0^3, 1)$	0.2826	1
(30, 15)	$(0^7, 15, 0^7)$	0.2505	$(0^2, 5, 0, 4, 0, 1, 0^2, 3, 1, 0^3, 1)$	0.2505	1
(35, 10)	$(0^6, 25, 0^3)$	0.2664	$(0, 17, 14, 0, 2, 0^2, 1)$	0.2664	1
(35, 15)	$(0^6, 20, 0^8)$	0.2342	$(0^3, 15, 2, 1, 1, 0^7, 1)$	0.2342	1
(35, 20)	$(0^6, 15, 0^{14})$	0.2189	$(0^2, 1, 2, 7, 4, 0^{13}, 1)$	0.2189	1
(45, 10)	$(0^6, 35, 0^3)$	0.2442	$(0, 1, 1, 310, 3, 4, 3, 0^2, 1)$	0.2442	1
(45, 15)	$(0^7, 2, 0^6, 28)$	0.2118	$(0^2, 15, 5, 0, 2^2, 1, 4, 0^5, 1)$	0.2118	1
(45, 20)	$(0^{19}, 25)$	0.1964	$(0^2, 7, 14, 3, 0^{13}, 1)$	0.1964	1
(n, m)	VNS algorithm		Multivariate hypergeometric		R.eff ₂
	\mathcal{R}^\dagger	$\psi(\mathcal{R}^\dagger)$	\mathcal{R}^\bullet	$\psi(\mathcal{R}^\bullet)$	
(30, 10)	$(0^5, 20, 0^4)$	0.2826	$(0, 2, 0, 1, 3, 1, 1, 6, 1, 5)$	0.2826	1
(30, 15)	$(0^7, 15, 0^7)$	0.2505	$(0^3, 1, 0, 1, 0, 3, 0, 1, 0, 5, 2^2, 0)$	0.2505	1
(35, 10)	$(0^6, 25, 0^3)$	0.2664	$(1, 0, 5^2, 1, 2, 3^2, 5, 0)$	0.2664	1
(35, 15)	$(0^6, 20, 0^8)$	0.2342	$(0^4, 1, 0, 3^2, 2, 3, 0, 1, 3, 0, 4)$	0.2342	1
(35, 20)	$(0^6, 15, 0^{14})$	0.2189	$(0^6, 1, 2, 5, 1^2, 0, 4, 1, 0^6)$	0.2189	1
(45, 10)	$(0^6, 35, 0^3)$	0.2442	$(6, 2^2, 3, 4, 8, 4, 1, 4, 1)$	0.2442	1
(45, 15)	$(0^7, 2, 0^6, 28)$	0.2118	$(2, 0^3, 1, 2, 1, 4, 1, 7, 0, 7, 1, 2^2)$	0.2118	1
(45, 20)	$(0^{19}, 25)$	0.1964	$(2, 0^3, 1^2, 0^2, 1, 2, 0, 3, 0, 3, 2, 0, 3, 0, 2, 5)$	0.1964	1