MUAD: Multiple Uncertainties for Autonomous Driving benchmark for multiple

Gianni Franchi¹ gianni.franchi@ensta-paris.fr Xuanlong Yu^{2,1} xuanlong.yu@universite-paris-saclay.fr Andrei Bursuc³ andrei.bursuc@valeo.com Rémi Kazmierczak¹ remi.kazmierczak@ensta-paris.fr Séverine Dubuisson⁴ severine.dubuisson@lis-lab.fr Emanuel Aldea² manuel.aldea@universite-paris-saclay.fr Bavid Filliat¹ avid.filliat@ensta-paris.fr Predictive uncertainty estimation is real-world autonomous systems. Howe of uncertainty is non trivial in most da

- ¹ ENSTA Paris
- ² Paris-Saclay University

1

- ³ valeo.ai
- ⁴ Aix Marseille University

Abstract

Predictive uncertainty estimation is essential for deploying Deep Neural Networks in real-world autonomous systems. However, disentangling the different types and sources of uncertainty is non trivial in most datasets, especially since there is no ground truth for uncertainty. In addition, different degrees of weather conditions can disrupt neural networks, resulting in inconsistent training data quality. Thus, we introduce the MUAD dataset (Multiple Uncertainties for Autonomous Driving), consisting of 8,500 realistic synthetic images with diverse adverse weather conditions (night, fog, rain, snow), out-of-distribution objects and annotations for semantic segmentation, depth estimation, object and instance detection. MUAD allows to better assess the impact of different sources of uncertainty on model performance. We propose a study that shows the importance of having reliable Deep Neural Networks (DNNs) in multiple experiments, and will release our dataset to allow researchers to benchmark their algorithm methodically in adverse conditions. More information and the download link for MUAD are available at https://muad-dataset.github.io/.

1 Introduction

In recent years, Deep Neural Networks (DNNs) have achieved remarkable results in various computer vision tasks [8, 27, 57]. This has turned DNNs into an essential tool for effective

automatic perception. Although DNNs achieve outstanding performance across benchmarks and tasks, there are still a few major bottlenecks to solve before a widespread deployment. One of the most frequent and known criticisms of DNNs is related to their lack of reliability, and it became crucial to address this limitation. To achieve this task, we focus on studying the uncertainties of the DNN predictions for computer vision tasks, particularly autonomous driving tasks.

The predictive uncertainty of a DNN stems from two main types of uncertainty [22]: aleatoric uncertainty and epistemic uncertainty. The former is related to randomness, typically due to the noise in the data. The latter concerns finite size training datasets. The epistemic uncertainty captures the uncertainty in the DNN parameters and their lack of knowledge on the model that generated the training data. Uncertainty estimation and reliability are essential for deploying DNNs in real-world systems with different levels of autonomy, ranging from simple driving assistance functions to fully autonomous vehicles. In addition to excellent predictive performance, DNNs are also expected to address different types of uncertainty (noisy, ambiguous or out-of-distribution samples, distribution shift, etc.), while ensuring real-time computational performance. These key and challenging requirements have stimulated numerous solutions and research directions leading to significant progress in the estimation of DNNs uncertainty [2], [2], [2], [2], [3], [4], [5], [5], [6]]. However, evaluating such methods is not obvious as there is no ground truth for uncertainty. For most public datasets, it is difficult to easily separate the different sources of uncertainty as they are usually curated and perfectly annotated.

In this work, we introduce a new dataset to study the uncertainty estimation methods for the use-case of perception of autonomous vehicles. While most datasets for autonomous driving aim to improve the predictive performance of DNNs [1], [3], recent autonomous driving datasets, e.g., ACDC [3], Street Hazards [3], BDD anomaly [3], benchmark the robustness of DNNs under unseen weather conditions or objects. However, these datasets are either limited to only one task, typically semantic segmentation, or only focus on a single type of uncertainty, or are not being precise enough in the different levels of uncertainties. We address these limitations in our dataset that allows to quantify all levels on uncertainty in the same conditions. Our dataset (MUAD - Multiple Uncertainties for Autonomous Driving) is composed of 3420 images for training, 492 images for validation, and 6588 for testing.

To summarize, our contributions are as follows: (1) We introduce MUAD: a new automotive dataset with annotations for multiple tasks and multiple uncertainty sources. (2) We perform a wide range of baselines on MUAD dataset for multiple computer vision tasks and settings (semantic segmentation, depth estimation, object detection) to further support research in this area.



(a) No perturbation (b) With OOD instances (c) Level 1 perturbation (d) Level 2 perturbation Figure 1: **Snapshots from the MUAD dataset** showing different types of adverse conditions and events to evaluate perception models.

2 Related work

2.1 Datasets

A variety of real-world datasets for autonomous driving have been recently released [5, 0, 11, 11, 12, 12, 13, 13, 13, 14, 15]. They have enabled tremendous progress in the area but they typically focus on a main task, e.g., semantic segmentation [11, 14, 14, 15], object detection [5, 19, 11], motion prediction [10, 12] and do not have evaluation tracks for uncertainty and out-of-distribution detection. Synthetic datasets, e.g., GTA [153], SYNTHIA [159], virtual KITTI[16] can provide abundant training data alleviating the need for costly annotation of real images as well as privacy preservation concerns in the case of real data. Currently, they are mostly used for domain adaptation. A few datasets have emerged towards meeting the reliability requirement for self-driving vehicles [16, 16, 12], 12] and evaluate the capacity of semantic segmentation DNNs to react when encountering out-of-distribution objects (OOD). Other datasts investigate the robustness against different weather conditions, e.g., night [12], [13], [14], [15], rain [152], fog [151, [12], however they are often acquired in different locations and conditions leading to a performance decay that overlaps with the ones from the difficult weather conditions.

The predictive uncertainty of a DNN stems mainly from aleatoric uncertainty and epistemic uncertainty. For most datasets they are difficult to disentangle, as these datasets are either curated (non blurry images, clean labels) or come from a different domain than the one used for training. We propose MUAD that is focused on the study of different forms of uncertainty for various tasks, that allows to asses the performance of a model without changing domains, in similar conditions as the model was initially designed for.

2.2 Uncertainty

Several works address the two types of uncertainty, in particular for the classification task. Most approaches build upon Bayesian learning, frequently upon Bayesian Neural Networks (BNNs) [1, 12, 21, 51], which estimate the posterior distribution of the DNN weights to marginalize the likelihood distribution at inference time. Yet BNNs are difficult to train and scale to complex computer vision tasks. Deep Ensembles [22] achieve state-of-the-art performance on various tasks, yet require multiple training and forward passes at inference. Some approaches [23] formalize DNNs to output a parametric distribution, and their goal is to estimate the distribution parameters. These approaches can be applied to optical flow [23] and object detection [11], yet they mainly focus on aleatoric uncertainty. A recent and promising of methods is given by Deterministic Uncertainty Methods (DUMs) [11, 23, 53, 54, 54], 54] that allow to quantify the epistemic uncertainty in the DNNs with a single forward pass. These approaches are fast and appealing, yet so far they have been mostly applied to image classification.

Dataset	Adversarial annotations	Fog	Night	Rain	Snow	Classes	Out of distribution	Depth	Object detection 2D/3D	Instance segmentation
Foggy Driving[101	~	-	-	-	19	-	-	-	-
Foggy Zurich [40	~	-	-	-	19	-	-	-	-
Nighttime Driving [40	-	~	-	-	19	-	-	-	
Dark Zurich [201	-	~	-	-	19	-	-	-	-
Raincouver [326	-	~	\checkmark	-	3	-	-	-	-
WildDash [100]	226	~	~	~	~	19	-	-	-	-
BDD100K [1346	\checkmark	~	\checkmark	\checkmark	19	-	-	-	-
ACDC [4006	~	~	~	~	19	-	~	~	-
Fishyscapes [1]	373	-	-	-	-	19+2	~	-	-	-
LostAndFound [10]	1203	-	-	-	-	19+9	\checkmark	-	-	-
RoadObstacle21 [327	-	~	-	~	19+1	~	-	-	-
RoadAnomaly21 [100	-	-	-	\checkmark	19+1	\checkmark	-	-	-
Streethazard [6625	-	-	-	-	13+250	~	-	-	-
BDD anomaly [22]	810	~	~	\checkmark	\checkmark	17+2	~	-	-	-
MUAD	11564	~	~	\checkmark	\checkmark	16+9	~	~	√	~

Table 1: Comparative overview of the different datasets for uncertainty on autonomous driving.

3 Multiple Uncertainties for Autonomous Driving benchmark (MUAD)

3.1 Motivations

Datasets for autonomous driving contain real world and synthetic data used for object detection, semantic segmentation, depth estimation, etc. KITTI [1] and Cityscapes [1] were the first real datasets to challenge the deep learning algorithms. These two datasets are not ideally suited to quantify the two types of uncertainty, since the raw data and the high-quality annotations are curated and intended primarily for accuracy evaluation. Relying on simulators as for the GTA [5] or SYNTHIA [5] datasets provides a simple means to overcome a lack of diversity and to introduce environment settings or elements for challenging the models. In order to address the lack of diversity in real environments and to evaluate better the impact on the epistemic uncertainty, some works promoted the inpainting of virtual objects [2] or synthesised weather conditions[2]. In this setting however, questions may be raised about the veracity of the result; the recent ACDC dataset [2] includes multiple sources of aleatoric uncertainty, and is composed entirely of real images. However, not having any control on the noise level makes it harder to quantify the link between noise and uncertainty. Indeed, acquiring images with uncertainty corner cases is problematic as these cases are rare (long tail) and also costly to annotate, e.g., 3.3 h/image [2].

Given this scarcity, such images are better used for validation to assess the reliability of DNNs before deployment in a small test set. Usually, in the validation stage, DNNs undergo various stress tests, usually with corner cases. It is thus interesting even from a more applied standpoint to have a synthetic dataset that mimics these rare conditions with some good fidelity constraint to quantify the robustness of DNNs. Indeed, synthetic data is abundant and can allow us to measure finer drifts in the input distribution. In addition, classical datasets mainly focus on semantic segmentation. Here we propose to focus on multiple tasks (semantic segmentation, monocular depth, object detection, and instance segmentation). In Table 1 we provide a summary of the main existing uncertainty datasets. In this work, we propose a fully synthetic dataset, called MUAD, integrating different weather conditions with various intensities, and suitable for a multitude of vision tasks and for the comprehensive



Figure 2: Number of annotated pixels per class in MUAD.

characterisation of their uncertainty.

3.2 Uncertainty and Deep Learning

A DNN is a function f_{θ} parameterized by a set of parameters θ that takes input data x and outputs a prediction y. The DNN is trained on a training dataset composed of a set of $\mathcal{D} = \{x_i, y_i\}_{i=1}^N$ with N the number of data to optimize the parameters θ for a task. Once the DNN is trained, meaning that the optimization of θ on \mathcal{D} is completed, f_{θ} may be used for inference on new data x^* .

Uncertainty on deep learning may arise mainly from three factors [\square]. Firstly it can result from the data acquisition process. For example, there might be some noise during the acquisition of the training dataset. This might be due to the variability in real-world situations. For example, one records training data in certain weather conditions, which subsequently change during inferences. The measurement systems might also introduce errors as sensor noise. Secondly, uncertainty may result from the DNN building and training process. DNNs are random functions whose parameters θ are initialized randomly and whose training procedure relies on stochastic optimization. Therefore, the resulting neural network is a random function that is most of the time related to a local minimum of the expected loss function (which we denote as the risk). Hence this source of randomness might cause errors in the training procedure of the DNN. Thirdly, the last uncertainty factor is related to the DNN's prediction's uncertainty. Uncertainty could come from the lack of knowledge of the DNN and might be caused by unknown test data.

Based on these factors, we can divide the uncertainty into two kinds: the aleatoric uncertainty and the epistemic uncertainty. The aleatoric uncertainty can be subdivided into two kinds: In-domain uncertainty [2] and Domain-shift uncertainty [53]. In-domain uncertainty occurs when the test data is sampled from the training distribution and is related to the inability of the deep neural network to predict a proper confidence score about the quality of its predictions due to a lack of in-domain knowledge. Domain-shift uncertainty denotes the uncertainty related to an input drawn from a shifted version of the training distribution. Hence, it is caused by the fact the distribution of the training dataset might not encompass enough variability. These two kinds of uncertainty can be reduced by increasing the quality / number of the training dataset. Epistemic uncertainty denotes the uncertainty when the test data is sampled from a distribution that is different and far from the training distribution. Epistemic uncertainty can be categorized into two kinds namely [13]: approximation uncertainty and model uncertainty. The approximation uncertainty is linked to the fact that we optimize the empirical risk instead of the risk. Hence, we optimize an approximated loss function and the optimal DNN's parameter of this loss approximation of the true risk function. The model uncertainty is linked to the fact that our loss function provides us with a class of solutions that might not include the perfect predictor. For example, the DNN might have classes different between the training and testing set. Out of Distribution consists of having anomalies in the test set that are data from classes not present in the training set.

3.3 Uncertainty and MUAD

According to the summary and categorization of the uncertainty based on the previous works, we propose to use the dataset to better evaluate the results and uncertainty estimations given by the DNNs in the context of autonomous driving. In the scenario of autonomous driving, we believe that the aleatoric uncertainty of the DNNs will occur due to different weather conditions than the ones present in the training set. The epistemic uncertainty of the DNNs should arise when the class or the appearance of objects in the picture differ from those of the data provided in the training set. The design of MUAD dataset is based on the above discussion of the relationship between uncertainty and autonomous driving scenarios. In the next section, we will detail the composition of MUAD dataset.

3.4 MUAD overview

The goal of MUAD is to confront DNNs to uncertain environments and to characterize numerically their robustness in adverse conditions, more specifically in the presence of rain, fog and snow. Photorealism is essential for guaranteeing that synthetic datasets are challenging with respect to real-world conditions, and also for keeping them relevant for use in industrial applications. This is particularly important for accommodating weather artifacts [23, 14], 19]. Our dataset is generated using a pure spectral ray-tracing engine which computes the spectral radiance of every light beam interacting with materials in the scene, and which simulates lighting effects and materials at a close physical level. For each sample, the corresponding ground truth information contains the semantic segmentation, the depth map, and for some specific classes (pedestrian, car, van, traffic light, traffic sign) the instance segmentation with the corresponding bounding boxes. We follow the standard data split strategy, however the training and validation set contain only images with normal weather conditions and without some specific classes which are denoted as OOD. The test set is organized into seven subsets following the intensity of the adverse weather conditions:

- normal set: images without OOD objects nor adverse conditions, as in Figure 1.(a).
- **normal set no shadow:** images without OOD objects nor adverse conditions we simulate the sun like if it was 12:00 AM so the shadow is minimum.
- **OOD set:** images containing OOD objects and without adverse conditions, as in Figure 1.(b).
- **low adv. set:** images containing medium intensity adverse conditions (either fog, rain or snow).
- high adv. set: images containing high intensity adverse conditions (either fog, rain or snow).



Figure 3: Illustration of semantic segmentation images of MUAD dataset. The first row is composed of the original images of the high adv. set. The second row is their corresponding ground truth.



Figure 4: Illustration of instance segmentation images of MUAD dataset. The three images are selected from the high adv. set. We illustrated the fog (4(a)), the rain (4(b)), and the snow (4(c)) conditions.

- low adv. with OOD set: images containing both OOD objects and medium intensity adverse conditions (either fog, rain or snow), as in Figure 1.(c).
- high adv. with OOD set: images containing both OOD objects and high intensity adverse conditions (either fog, rain or snow), as in Figure 1.(d).

In Figure 3 and 4 we illustrate the instance segmentation and the semantic segmentation of 3 images. We observe that the adverse weather conditions are realistic and challenging as they bring a mix of difficult (unknown during training) environment conditions and perturbation of the visibility in the scene. We argue that such settings are helpful for autonomous driving since the autonomous system must face and be robust against a variety of weather conditions and situations.

3.5 MUAD statistics

Our dataset contains 3420 images in the train set, and 492 in the validation set. The test set is composed of 6588 images divided as follows: 551 in the **normal set**, 100 in the **normal set no shadow** 1664 in the **OOD set**, 600 in the **low adv. set** and 600 images in the **high adv. set** 1552 in the **low adv. with OOD set** and 1421 images in the **high adv. with OOD set**. All of these sets cover day and night conditions with 2/3 of day images and 1/3 of night images. Test datasets address diverse weather conditions (rain, snow, and fog with different levels), and various OOD objects.

The dataset aims to provide a general and consistent coverage for a typical urban and suburban environment under different times of day and weather conditions. Ego-vehicle poses are drawn randomly within a complex environment, and in a second stage the field

Cityscapes classes	MUAD classes	nb. of images with the annotations
Road	Bots, Tram Tracks, Crosswalk, Parking Area, Garbage - Road, Road Lines, Sewer Longitudinal Crack, Transversal Crack, Road, Asphalt Hole, Polished Aggregate, Vegetation - Road, Sewer - Road, Construction Concrete	9055
Sidewalk	Lane Bike, Kerb Stone, Sidewalk, Kerb Rising Edge	8948
Building	House, Construction Scaffold, Building, Air Conditioning, Construction Container, TV Antenna, Terrace, Water Tank, Pergola Garden, Stairs, Dog House, Sunshades, Railings, Construction Stock, Marquees, Hangar Airport	9089
Wall	Wall	1101
Fence	Construction Fence, Fences	8622
Pole	Traffic Signs Poles or Structure, Traffic Lights Poles, Street lights, Lamp	8984
Traffic light	Traffic Lights Head, Traffic Cameras, Traffic Lights Bulb (red, yellow, green)	8222
Traffic sign	Traffic Signs	2672
Vegetation	Vegetation	9072
Terrain	Terrain, Tree Pit	8377
Sky	Sky	8591
Person	Walker, All colors of Construction Helmet, All colors of Safety Vest, Umbrella, People	8843
Rider	Cyclist, Biker	3470
Car	Car, Beacon Light, Van, Ego Car	9026
Truck	Truck	5533
Bus	Bus	0
Train	Train, Subway	2240
Motorcycle	Motorcycle, Segway, Scooter Child	2615
Bicycle	Bicycle, Kickbike, Tricycle	2816
Animals	Cow, Bear, Deer, Moose	603
Objects anomalies	Stand Food, Trash Can, Garbage bag	352
Background	Others	-

Table 2: Overview of annotated classes

of view is populated stochastically with dynamic objects of interest following distributions in compliance with their expected behaviour. The pose and context changes as well as the variation of the models for the objects of interest ensure that content diversity is high, in addition to images being photorealistic. The simulator makes use of approximately 300 different person models and 150 different vehicle models, which are sampled while varying their visual characteristics.

3.6 Class labels

8

MUAD comprises 155 different classes that we have regrouped into 21 classes. The first 19 classes are similar CityScapes classes [1], then we added object anomalies and animals to have more diversity in the anomalies. In Table 2 one can see the classes' ontology. In addition to ensuring high content diversity, this ontology facilitates the mapping of MUAD to specific environments which require or impose a lower number of more generic classes. Consequently, trained models are easily transferable for existing datasets, and we provide the mapping towards the 21 classes widely used by the community, e.g., [1, 1], [2], [3], [3], [5]. The dataset statistics for the 21 classes is presented in Figure 2. For the evaluation of OOD detection, we have excluded nine classes (train, motorcycle, bicycle, bears, cow, deers, moose, Stand Food, Garbage bags) from the training and validation sets. These classes are present in the test set as OOD objects. DNNs that classify one of these nine classes are expected to have a low confidence score.

9

4 Experiments

In progress

References

- [1] Alexander A Alemi, Ian Fischer, and Joshua V Dillon. Uncertainty in the variational information bottleneck. *arXiv preprint arXiv:1807.00906*, 2018.
- [2] Arsenii Ashukha, Alexander Lyzhov, Dmitry Molchanov, and Dmitry Vetrov. Pitfalls of in-domain uncertainty estimation and ensembling in deep learning. *arXiv preprint arXiv:2002.06470*, 2020.
- [3] Hermann Blum, Paul-Edouard Sarlin, Juan Nieto, Roland Siegwart, and Cesar Cadena. Fishyscapes: A benchmark for safe semantic segmentation in autonomous driving. In *ICCVW*, 2019.
- [4] Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural network. In *ICML*, 2015.
- [5] Holger Caesar, Varun Bankiti, Alex H. Lang, Sourabh Vora, Venice Erin Liong, Qiang Xu, Anush Krishnan, Yu Pan, Giancarlo Baldan, and Oscar Beijbom. nuScenes: A multimodal dataset for autonomous driving. In *CVPR*, 2020.
- [6] Robin Chan, Krzysztof Lis, Svenja Uhlemeyer, Hermann Blum, Sina Honari, Roland Siegwart, Mathieu Salzmann, Pascal Fua, and Matthias Rottmann. Segmentmeifyoucan: A benchmark for anomaly segmentation. arXiv preprint arXiv:2104.14812, 2021.
- [7] Ming-Fang Chang, John Lambert, Patsorn Sangkloy, Jagjeet Singh, Slawomir Bak, Andrew Hartnett, De Wang, Peter Carr, Simon Lucey, Deva Ramanan, et al. Argoverse: 3d tracking and forecasting with rich maps. In *CVPR*, 2019.
- [8] Liang-Chieh Chen, George Papandreou, Iasonas Kokkinos, Kevin Murphy, and Alan L Yuille. Deeplab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected crfs. *IEEE transactions on pattern analysis and machine intelligence*, 40(4):834–848, 2017.
- [9] Yi-Hsin Chen, Wei-Yu Chen, Yu-Ting Chen, Bo-Cheng Tsai, Yu-Chiang Frank Wang, and Min Sun. No more discrimination: Cross city adaptation of road scene segmenters. In *ICCV*, 2017.
- [10] Jiwoong Choi, Dayoung Chun, Hyun Kim, and Hyuk-Jae Lee. Gaussian yolov3: An accurate and fast object detector using localization uncertainty for autonomous driving. In *ICCV*, 2019.
- [11] Marius Cordts, Mohamed Omran, Sebastian Ramos, Timo Rehfeld, Markus Enzweiler, Rodrigo Benenson, Uwe Franke, Stefan Roth, and Bernt Schiele. The cityscapes dataset for semantic urban scene understanding. In *CVPR*, 2016.
- [12] Dengxin Dai and Luc Van Gool. Dark model adaptation: Semantic image segmentation from daytime to nighttime. In *ITSC*, 2018.
- [13] Dengxin Dai, Christos Sakaridis, Simon Hecker, and Luc Van Gool. Curriculum model adaptation with synthetic and real data for semantic foggy scene understanding. *IJCV*, 2020.

- [14] Michael Dusenberry, Ghassen Jerfel, Yeming Wen, Yian Ma, Jasper Snoek, Katherine Heller, Balaji Lakshminarayanan, and Dustin Tran. Efficient and scalable bayesian neural nets with rank-1 factors. In *International conference on machine learning*, pages 2782–2792. PMLR, 2020.
- [15] Stanislav Fort, Huiyi Hu, and Balaji Lakshminarayanan. Deep ensembles: A loss landscape perspective. In arXiv, 2019.
- [16] Adrien Gaidon, Qiao Wang, Yohann Cabon, and Eleonora Vig. Virtual worlds as proxy for multi-object tracking analysis. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4340–4349, 2016.
- [17] Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *ICML*, 2016.
- [18] Jakob Gawlikowski, Cedrique Rovile Njieutcheu Tassi, Mohsin Ali, Jongseok Lee, Matthias Humt, Jianxiang Feng, Anna Kruspe, Rudolph Triebel, Peter Jung, Ribana Roscher, et al. A survey of uncertainty in deep neural networks. arXiv preprint arXiv:2107.03342, 2021.
- [19] Andreas Geiger, Philip Lenz, and Raquel Urtasun. Are we ready for autonomous driving? the kitti vision benchmark suite. In *CVPR*, 2012.
- [20] Dan Hendrycks, Steven Basart, Mantas Mazeika, Mohammadreza Mostajabi, Jacob Steinhardt, and Dawn Song. A benchmark for anomaly segmentation. In *arXiv*, 2019.
- [21] José Miguel Hernández-Lobato and Ryan Adams. Probabilistic backpropagation for scalable learning of bayesian neural networks. In *International conference on machine learning*, pages 1861–1869. PMLR, 2015.
- [22] Stephen C Hora. Aleatory and epistemic uncertainty in probability elicitation with an example from hazardous waste management. *Reliability Engineering & System Safety*, 54(2-3):217–223, 1996.
- [23] John Houston, Guido Zuidhof, Luca Bergamini, Yawei Ye, Long Chen, Ashesh Jain, Sammy Omari, Vladimir Iglovikov, and Peter Ondruska. One thousand and one hours: Self-driving motion prediction dataset. In *arXiv*, 2020.
- [24] Eddy Ilg, Ozgun Cicek, Silvio Galesso, Aaron Klein, Osama Makansi, Frank Hutter, and Thomas Brox. Uncertainty estimates and multi-hypotheses networks for optical flow. In ECCV, 2018.
- [25] Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision? In *NeurIPS*, 2017.
- [26] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25, 2012.
- [27] Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *NeurIPS*, 2017.

12 MUAD: DATASET WITH MULTIPLE UNCERTAINTIES FOR AUTONOMOUS DRIVING

- [28] Kunming Li, Yu Li, Shaodi You, and Nick Barnes. Photo-realistic simulation of road scene for data-driven methods in bad weather. In *ICCVW*, 2017.
- [29] Jeremiah Zhe Liu, Zi Lin, Shreyas Padhy, Dustin Tran, Tania Bedrax-Weiss, and Balaji Lakshminarayanan. Simple and principled uncertainty estimation with deterministic deep learning via distance awareness. In *NeurIPS*, 2020.
- [30] Andrey Malinin, Bruno Mlodozeniec, and Mark Gales. Ensemble distribution distillation. In *ICLR*, 2020.
- [31] Jishnu Mukhoti, Viveka Kulharia, Amartya Sanyal, Stuart Golodetz, Philip HS Torr, and Puneet K Dokania. Calibrating deep neural networks using focal loss. In *NeurIPS*, 2020.
- [32] Jishnu Mukhoti, Andreas Kirsch, Joost van Amersfoort, Philip HS Torr, and Yarin Gal. Deterministic neural networks with appropriate inductive biases capture epistemic and aleatoric uncertainty. In *arXiv*, 2021.
- [33] Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. *Advances in neural information processing systems*, 32, 2019.
- [34] Peter Pinggera, Sebastian Ramos, Stefan Gehrig, Uwe Franke, Carsten Rother, and Rudolf Mester. Lost and found: detecting small road hazards for self-driving vehicles. In *IROS*, 2016.
- [35] Janis Postels, Hermann Blum, Yannick Strümpler, Cesar Cadena, Roland Siegwart, Luc Van Gool, and Federico Tombari. The hidden uncertainty in a neural networks activations. In *arXiv*, 2020.
- [36] Vasili Ramanishka, Yi-Ting Chen, Teruhisa Misu, and Kate Saenko. Toward driving scene understanding: A dataset for learning driver behavior and causal reasoning. In *CVPR*, 2018.
- [37] Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards realtime object detection with region proposal networks. *Advances in neural information processing systems*, 28, 2015.
- [38] Stephan R Richter, Vibhav Vineet, Stefan Roth, and Vladlen Koltun. Playing for data: Ground truth from computer games. In *ECCV*, 2016.
- [39] German Ros, Laura Sellart, Joanna Materzynska, David Vazquez, and Antonio M Lopez. The synthia dataset: A large collection of synthetic images for semantic segmentation of urban scenes. In *CVPR*, 2016.
- [40] Christos Sakaridis, Dengxin Dai, and Luc Van Gool. Semantic foggy scene understanding with synthetic data. *IJCV*, 2018.
- [41] Christos Sakaridis, Dengxin Dai, and Luc Van Gool. Map-guided curriculum domain adaptation and uncertainty-aware evaluation for semantic nighttime image segmentation. arXiv preprint arXiv:2005.14553, 2020.

- [42] Christos Sakaridis, Dengxin Dai, and Luc Van Gool. Acdc: The adverse conditions dataset with correspondences for semantic driving scene understanding. In *ICCV*, 2021.
- [43] Pei Sun, Henrik Kretzschmar, Xerxes Dotiwalla, Aurelien Chouard, Vijaysai Patnaik, Paul Tsui, James Guo, Yin Zhou, Yuning Chai, Benjamin Caine, Vijay Vasudevan, Wei Han, Jiquan Ngiam, Hang Zhao, Aleksei Timofeev, Scott Ettinger, Maxim Krivokon, Amy Gao, Aditya Joshi, Yu Zhang, Jonathon Shlens, Zhifeng Chen, and Dragomir Anguelov. Scalability in perception for autonomous driving: Waymo open dataset. In *CVPR*, 2020.
- [44] Maxime Tremblay, Shirsendu Sukanta Halder, Raoul de Charette, and Jean-François Lalonde. Rain rendering for evaluating and improving robustness to bad weather. *ijcv*, 2021.
- [45] Omer Faruk Tuna, Ferhat Ozgur Catak, and M Taner Eskil. Exploiting epistemic uncertainty of the deep learning models to generate adversarial samples. *arXiv preprint arXiv:2102.04150*, 2021.
- [46] Frederick Tung, Jianhui Chen, Lili Meng, and James J Little. The raincouver scene parsing benchmark for self-driving in adverse weather and at night. 2017.
- [47] Joost van Amersfoort, Lewis Smith, Andrew Jesson, Oscar Key, and Yarin Gal. Improving deterministic uncertainty estimation in deep learning for classification and regression. arXiv preprint arXiv:2102.11409, 2021.
- [48] Girish Varma, Anbumani Subramanian, Anoop Namboodiri, Manmohan Chandraker, and CV Jawahar. Idd: A dataset for exploring problems of autonomous navigation in unconstrained environments. In WACV, 2019.
- [49] Alexander Von Bernuth, Georg Volk, and Oliver Bringmann. Simulating photo-realistic snow and fog on existing images for enhanced cnn training and evaluation. In *ITSC*, 2019.
- [50] Yeming Wen, Dustin Tran, and Jimmy Ba. Batchensemble: an alternative approach to efficient ensemble and lifelong learning. In *ICLR*, 2020.
- [51] Andrew Gordon Wilson and Pavel Izmailov. Bayesian deep learning and a probabilistic perspective of generalization. *arXiv preprint arXiv:2002.08791*, 2020.
- [52] Mike Wu and Noah Goodman. A simple framework for uncertainty in contrastive learning. *arXiv preprint arXiv:2010.02038*, 2020.
- [53] Fisher Yu, Haofeng Chen, Xin Wang, Wenqi Xian, Yingying Chen, Fangchen Liu, Vashisht Madhavan, and Trevor Darrell. Bdd100k: A diverse driving dataset for heterogeneous multitask learning. In CVPR, 2020.
- [54] Oliver Zendel, Katrin Honauer, Markus Murschitz, Daniel Steininger, and Gustavo Fernandez Dominguez. Wilddash-creating hazard-aware benchmarks. In ECCV, 2018.