# Efficiently Enumerating Answers to Ontology-Mediated Queries

Carsten Lutz Institute of Computer Science University of Leipzig Leipzig, Germany clu@informatik.uni-leipzig.de

# ABSTRACT

We study the enumeration of answers to ontology-mediated queries (OMQs) where the ontology is a set of guarded TGDs or formulated in the description logic  $\mathcal{ELI}$  and the query is a conjunctive query (CQ). In addition to the traditional notion of an answer, we propose and study two novel notions of partial answers that can take into account nulls generated by existential quantifiers in the ontology. Our main result is that enumeration of the traditional complete answers and of both kinds of partial answers is possible with linear-time preprocessing and constant delay for OMQs that are both acyclic and free-connex acyclic. We also provide partially matching lower bounds. Similar results are obtained for the related problems of testing a single answer in linear time and of testing multiple answers in constant time after linear time preprocessing. In both cases, the border between tractability and intractability is characterized by similar, but slightly different acyclicity properties.

# **1** INTRODUCTION

In knowledge representation, ontologies are an important means for injecting domain knowledge into an application. In the context of databases, they give rise to ontology-mediated queries (OMQs) which enrich a traditional database query such as a conjunctive query (CQ) with an ontology. OMQs aim at querying incomplete data, using the domain knowledge provided by the ontology to derive additional answers. In addition, they may enrich the vocabulary available for query formulation with relation symbols that are not used explicitly in the data. Popular choices for the ontology language include (restricted forms of) tuple-generating dependencies (TDGs), also dubbed existential rules [5] and Datalog<sup> $\pm$ </sup> [19], as well as various description logics [3].

The complexity of evaluating OMQs has been the subject of intense study, with a focus on *single-testing* as the mode of query evaluation: given an ontology-mediated query (OMQ) Q, a database D, and a candidate answer  $\bar{a}$ , decide whether  $\bar{a} \in Q(D)$  [2, 6, 13, 15]. In many applications, however, it is not realistic to assume that a candidate answer is available. This has led database theoreticians and practitioners to investigate more relevant modes of query evaluation such as *enumeration*: given Q and D, generate all answers in Q(D), one after the other and without repetition.

The first main aim of this paper is to initiate a study of efficiently enumerating answers to OMQs. We consider enumeration algorithms that have a preprocessing phase in which data structures are built that are used in the subsequent enumeration phase to produce the actual output. With 'efficient enumeration', we mean that preprocessing may only take time linear in O(||D||) while Marcin Przybyłko Institute of Computer Science University of Leipzig Leipzig, Germany przybyl@informatik.uni-leipzig.de

the delay between two answers must be constant, that is, independent of D. One may or may not impose the additional requirement that, in the enumeration phase, the algorithm may consume only a constant amount of memory on top of the data structures precomputed in the preprocessing phase. We refer to the resulting enumeration complexity classes as DelayClin and CDoLin, the former admitting unrestricted (polynomial) memory consumption; the use of these names in the literature is not consistent, we follow [22, 37]. Without ontologies, answer enumeration in CDoLin and in DelayC<sub>lin</sub> has received significant attention [4, 12, 16, 21–23, 26, 27, 37], see also the survey [11]. A landmark result is that a CQ  $q(\bar{x})$  admits enumeration in CDoLin if it is *acyclic* and *free-connex* acyclic where the former means that q has a join tree and the latter that the extension of *q* with an atom  $R(\bar{x})$  that 'guards' the answer variables is acyclic [4]. Partially matching lower bounds pertain to self-join free COs [4, 17].

The second aim of this paper is to introduce a novel notion of partial answers to OMQs. In the traditional *certain answers*,  $\bar{a} \in Q(D)$  if and only if  $\bar{a}$  is a tuple of constants from D such that  $\bar{a} \in Q(I)$  for every model I of D and the ontology O used in Q. In contrast, a *partial answer* may contain, apart from constants from D, also the wildcard symbol '\*' to indicate a constant that we know must exists, but whose identity is unknown. Such *labeled nulls* may be introduced by existential quantifiers in the ontology O. To avoid redundancy as in the partial answers (a, \*) and (a, b), we are interested in *minimal* partial answers that cannot be 'improved' by replacing a wildcard with a constant from D while still remaining a partial answers. The following simple example illustrates that minimal partial answers may provide useful information that is not provided by the traditional answers, from now called *complete answers*.

Example 1.1. Consider the ontology O that contains

Researcher(x)	$\rightarrow$	$\exists y \operatorname{HasOffice}(x, y)$
HasOffice(x, y)	$\rightarrow$	Office(y)
Office(x)	$\rightarrow$	$\exists y  \text{InBuilding}(x, y)$

and the CQ  $q(x_1, x_2, x_3) = \mathsf{HasOffice}(x_1, x_2) \land \mathsf{InBuilding}(x_2, x_3)$ giving rise to the OMQ  $Q(x_1, x_2, x_3)$ . Take the following database D:

Researcher(mary) Researcher(john) Researcher(mike) HasOffice(mary, room1) HasOffice(john, room4) InBuilding(room1, main1)

The minimal partial answers to Q on D are

(mary, room1, main1) (john, room4, \*) (mike, \*, \*).

We also introduce and study *minimal partial answers with multiple wildcards*  $*_1, *_2, \ldots$ . Distinct occurences of the same wildcard in an answer indicate the same null, while different wildcards may or may not correspond to different nulls. Multiple wildcards may thus be viewed as adding equality on wildcards, but not inequality. We note that there are certain similarities between minimal partial answer to OMQs and answers to SPARQL queries with the 'optional' operator [9, 33], but also many dissimilarities.

The third aim of this paper is to study two problems for OMQs that are closely related to constant delay enumeration: single-testing in linear time (in data complexity) and *all-testing* in CDoLin or DelayC<sub>lin</sub>. Note that for Boolean queries, single-testing in linear time coincides with enumeration in CDoLin and in DelayC<sub>lin</sub>. An all-testing algorithm has a prepocessing phase followed by a testing phase where it repeatedly receives candidate answers  $\bar{a}$  and returns 'yes' or 'no' depending on whether  $\bar{a} \in Q(D)$  [11]. All-testing in DelayC<sub>lin</sub> grants preprocessing time O(||D||) while the time spent per test must be independent of D, and all-testing in CDoLin is defined accordingly.

An ontology-mediated query takes the form  $Q(\bar{x}) = (O, S, q)$ where O is an ontology, S a schema for the databases on which Q is evaluated, and  $q(\bar{x})$  a conjunctive query. In this paper, we consider ontologies that are sets of guarded tuple-generating dependencies (TGDs) or formulated in the description logic  $\mathcal{ELI}$ . We remind the reader that a TGD takes the form  $\forall \bar{x} \forall \bar{y} (\phi(\bar{x}, \bar{y}) \rightarrow \exists \bar{z} \psi(\bar{x}, \bar{z}))$ where  $\phi$  and  $\psi$  are CQs, and that it is guarded if  $\phi$  has an atom that mentions all variables from  $\bar{x}$  and  $\bar{y}$ . Up to normalization, an  $\mathcal{ELI}$ -ontology may be viewed as a finite set of guarded TGDs of a restricted form, using in particular only unary and binary relation symbols. Both guarded TGDs and  $\mathcal{ELI}$  are natural and popular choices for the ontology language [3, 18, 20]. We use ( $\mathbb{G}, \mathbb{CQ}$ ) to denote the language of all OMQs that use a set of guarded TGDs as the ontology and a CQ as the actual query, and likewise for ( $\mathbb{ELI}, \mathbb{CQ}$ ) and  $\mathcal{ELI}$ -ontologies.

We next summarize our results. In Section 3, we start with showing that in  $(\mathbb{G}, \mathbb{CQ})$ , single-testing complete answers is in linear time for OMQs that are weakly acyclic. A CQ is weakly acyclic if it is acyclic after replacing the answer variables with constants and an OMQ is weakly acyclic if the CQ in it is; in what follows, we lift other properties of CQs to OMQs in the same way without further notice. Our proof relies on the construction of a 'query-directed' fragment of the chase and a reduction to the generation of minimal models of propositional Horn formulas. We also give a lower bound for OMQs from  $(\mathbb{ELI}, \mathbb{CQ})$  that are self-join free: every such OMQ that admits single-testing in linear time is weakly acyclic unless the triangle conjecture from fine-grained complexity theory fails. This generalizes a result for the case of CQs without ontologies [17]. We observe that it is not easily possible to replace ELI by  $\mathbb{G}$  in our lower bound as this would allow us to remove also 'self-join free' while it is open whether this is possible even in the case without ontologies. We also show that single-testing minimal partial answers with a single wildcard is in linear time for OMQs from  $(\mathbb{G}, \mathbb{CQ})$  that are acyclic and that the same is true for multiple wildcards and acyclic OMQs from  $(\mathbb{ELI}, \mathbb{CQ})$ . We also observe that these (stronger) requirements cannot easily be relaxed.

In Section 4, we turn to enumeration and all-testing of complete answers. We first show that in ( $\mathbb{G}$ ,  $\mathbb{CQ}$ ), enumerating complete answers is in CDoLin for OMQs that are acyclic and free-connex acyclic while all-testing complete answers is in CDoLin for OMQs that are free-connex acyclic (but not necessarily acyclic). The proof

again uses the careful chase construction and a reduction to the case without ontologies. The lower bound for single testing conditional on the triangle conjecture can be adapted to enumeration, with 'not weakly acyclic' replaced by 'not acyclic'. For enumeration, it thus remains to consider OMOs that are acvclic, but not free-connex acyclic. We show that for every self-join free OMQ from  $(\mathbb{ELI}, \mathbb{CQ})$  that is acyclic, connected, and admits enumeration in CDoLin, the query is free-connex acyclic, unless sparse Boolean matrix multiplication (BMM) is possible in time linear in the size of the input plus the size of the ouput; this would imply a considerable advance in algorithm theory and currently seems to be out of reach. We also show that it is not possible to drop the requirement that the query is connected, which is not present in the corresponding lower bound for the case without ontologies [4, 11]. We prove a similar lower bound for all-testing complete answers, subject to a condition regarding non-sparse BMM. All mentioned lower bounds also apply to both kinds of partial answers.

In Section 5, we then prove that enumerating minimal partial answers with a single wildcard is in  $\text{DelayC}_{\text{lin}}$  for OMQs from  $(\mathbb{G}, \mathbb{CQ})$  that are acyclic and free-connex acyclic. This is one of the main results of this paper, based on a non-trivial enumeration algorithm. Here, we only highlight two of its features. First, the algorithm precomputes certain data structures that describe 'excursions' that a homomorphism from *q* into the chase of *D* with *O* may make into the parts of the chase that has been generated by the existential quantifiers in the ontology. And second, it involves subtle sorting and pruning techniques to ensure that only *minimal* partial answers is less well-behaved than enumeration as there is an OMQ  $Q \in (\mathbb{ELI}, \mathbb{CQ})$  that is acyclic and free-connex acyclic, but for which all-testing is not in CDoLin unless the triangle conjecture fails.

Finally, Section 6 extends the upper bound from Section 5 to minimal partial answers with multiple wildcards. We first show that all-testing (not necessarily minimal!) partial answers with multiple wildcards is in  $DelayC_{lin}$  for OMQs that are acyclic and free-connex acyclic and then reduce enumeration of minimal partial answers with multiple wildcards to this, combined with the enumeration algorithm of minimal partial answers with a single wildcard obtained in the previous section.

Proof details are deferred to the appendix.

#### 2 PRELIMINARIES

**Relational Databases.** Fix countably infinite and disjoint sets of constants C and N. We refer to the constants in N as *nulls*. A *schema* S is a set of relation symbols *R* with associated arity  $ar(R) \ge 0$ . An S-*fact* is an expression of the form  $R(\bar{c})$ , where  $R \in S$ and  $\bar{c}$  is an ar(R)-tuple of constants from  $C \cup N$ . An S-*instance* is a set of S-facts and an S-*database* is a finite S-instance that uses only constants from C. We write adom(I) for the set of constants used in instance *I*. For a set  $S \subseteq C \cup N$ ,  $I_{|S}$  denotes the restriction of *I* to facts that mention only constants from *S*. A *homomorphism* from *I* to an instance *J* is a function  $h : adom(I) \rightarrow adom(J)$  such that  $R(h(\bar{c})) \in J$  for every  $R(\bar{c}) \in I$ . A set  $S \subseteq adom(I)$  is a *guarded set in I* if there is a fact  $R(\bar{c}) \in I$  such that all constants from *S* are in  $\bar{c}$ . The *Gaifman graph* of a database *D* is the undirected graph with Efficiently Enumerating Answers to Ontology-Mediated Queries

Figure 1: Different forms of acyclicity

vertices adom(D) and an edge  $\{c_1, c_2\}$  whenever  $c_1, c_2$  co-occur in a fact in D.

**Conjunctive Queries.** A *term* is a variable or a constant from C. A *conjunctive query* (CQ)  $q(\bar{x})$  over a schema S takes the form  $q(\bar{x}) \leftarrow \phi(\bar{x}, \bar{y})$  where  $\bar{x}$  and  $\bar{y}$  are tuples of variables,  $\phi$  is a conjunction of *relational atoms*  $R_i(\bar{t}_i)$  with  $R_i \in S$  and  $\bar{t}_i$  a tuple of terms of length  $\operatorname{ar}(R_i)$ . We refer to the variables in  $\bar{x}$  as the *answer variables* of q and to the variables in  $\bar{y}$  as the *quantified variables*. With  $\operatorname{var}(q)$ , we denote the set of all variables in q and with  $\operatorname{con}(q)$  the set of constants. Whenever convenient, we identify a conjunction of atoms with a set of atoms. The *arity* of q is defined as the number of its answer variables and q is Boolean if it is of arity 0. When we do not want to make  $\phi(\bar{x}, \bar{y})$  explicit, we may denote  $q(\bar{x}) \leftarrow \phi(\bar{x}, \bar{y})$  simply with  $q(\bar{x})$ . We say that  $q(\bar{x})$  is *self-join free* if no relation symbol occurs in more than one atom in it. We write  $\mathbb{CQ}$  for the class of CQs.

Every CQ  $q(\bar{x})$  can be naturally seen as a database  $D_q$ , known as the *canonical database* of q, obtained by viewing variables as constants from C. The *Gaifman graph* of q is that of  $D_q$ . A *homomorphism* h from q to an instance I is a homomorphism from  $D_q$ to I that is the identity on all constants that appear in q. A tuple  $\bar{c} \in \operatorname{adom}(I)^{|\bar{x}|}$  is an *answer* to q on I if there is a homomorphism h from q to I with  $h(\bar{x}) = \bar{c}$ . The *evaluation of*  $q(\bar{x})$  *on* I, denoted q(I), is the set of all answers to q on I.

For a CQ q, but also for any other syntactic object q, we use ||q|| to denote the number of symbols needed to write q as a word over a suitable alphabet.

**Acyclic CQs.** Let  $q(\bar{x}) \leftarrow \phi(\bar{x}, \bar{y})$  be a CQ. A *join tree* for  $q(\bar{x})$ is an undirected tree T = (V, E) where V is the set of atoms in  $\phi$ and for each variable  $x \in var(q)$ , the set  $\{\alpha \in V \mid x \text{ occurs in } \alpha\}$ is a connected subtree of T. Then  $q(\bar{x})$  is *acyclic* if it has a join tree. Note that constants need not satisfy the connectedness condition imposed on variables. We say that  $q(\bar{x})$  is weakly acyclic if q becomes acyclic after consistently replacing all answer variables with fresh constants. A CQ  $q(\bar{x})$  is *free-connex acyclic* if adding an atom  $R(\bar{x})$  that 'guards' the answer variables, where *R* is a relation symbol of arity  $|\bar{x}|$ , results in an acyclic CQ. Note that other authors have called a CQ q free-connex acyclic (or even just free-connex) if *q* is both acyclic and (in our sense) free-connex acyclic [11]. Acyclicity and free-connex acyclicity are independent properties, that is, neither of them implies the other. Each of them implies weak acyclicity while the converse is false. Figure 1 shows (the Gaifman graphs of) simple example CQs that illustrate the differences. Hollow nodes indicate quantified variables, ac stands for acyclic, fc for free-connex acyclic, and wac for weakly acyclic.

TGDs, Guardedness, Chase. A tuple-generating dependency (TGD) *T* over S is a first-order sentence  $\forall \bar{x} \forall \bar{y} (\phi(\bar{x}, \bar{y}) \rightarrow \exists \bar{z} \psi(\bar{x}, \bar{z}))$  such that  $q_{\phi}(\bar{x}) \leftarrow \phi(\bar{x}, \bar{y})$  and  $q_{\psi}(\bar{x}) \leftarrow \psi(\bar{x}, \bar{z})$  are CQs that do

Technical Report, arXiv version, 2022

not contain constants. We call  $\phi$  and  $\psi$  the *body* and *head* of *T*. The body may be the empty conjunction, i.e. logical truth, denoted by true. The variables in  $\bar{x}$  are the *frontier variables*. For simplicity, we write *T* as  $\phi(\bar{x}, \bar{y}) \rightarrow \exists \bar{z} \psi(\bar{x}, \bar{z})$ . An instance *I* over S satisfies *T*, denoted  $I \models T$ , if  $q_{\phi}(I) \subseteq q_{\psi}(I)$ . It satisfies a set of TGDs *O*, denoted  $I \models O$ , if  $I \models T$  for each  $T \in O$ . We then also say that *I* is a *model* of *O*. A TGD *T* is *guarded* if its body is true or contains a *guard atom*  $\alpha$  that contains all variables in the body [18]. We write TGD to denote the class of all TGDs and G for the class of guarded TGDs.

The well-known chase procedure makes explicit in an instance the consequences of a set of TGDs [18, 29, 31, 36]. Let I be an instance and O be a set of TGDs. A TGD  $T = \phi(\bar{x}, \bar{y}) \rightarrow \exists \bar{z} \psi(\bar{x}, \bar{z}) \in O$ is applicable to a tuple  $(\bar{c}, \bar{c}')$  of constants in I if  $\phi(\bar{c}, \bar{c}') \subseteq I$ . In this case, the *result of applying* T *in* I *at*  $(\bar{c}, \bar{c}')$  is the instance  $I \cup$  $\{\psi(\bar{c}, \bar{c}'')\}$  where  $\bar{c}''$  is the tuple obtained from  $\bar{z}$  by simultaneously replacing each variable z with a fresh distinct null that does not occur in I. We refer to such an application as a chase step. A chase sequence for I with O is a sequence of instances  $I_0, I_1, \ldots$  such that  $I_0 = I$  and each  $I_{i+1}$  is the result of applying some TGD from Oat some tuple  $(\bar{c}, \bar{c}')$  of constants in  $I_i$ . The *result* of this chase sequence is the instance  $J = \bigcup_{i>0} I_i$ . The chase sequence is *fair* if whenever a TGD  $T \in O$  is applicable to a tuple  $(\bar{c}, \bar{c}')$  in some  $I_i$ , then this application is a chase step in the sequence. Fair chase sequences are oblivious in that a TGD is eventually applied whenever its body is satisfied, even if also its head is already satisfied. As a consequence, every fair chase sequence for I with O leads to the same result, up to isomorphism. We denote this result with  $ch_O(I)$ .

**Ontology-Mediated Query, Description Logic.** An *ontology* is a finite set of TGDs. An *ontology-mediated query* (*OMQ*) takes the form Q = (O, S, q) where O is an ontology, S is a finite schema called the *data schema*, and q is a CQ. Both O and q can use symbols from S, but also additional symbols, and in particular O can 'introduce' symbols to enrich the vocabulary available for querying. We assume w.l.o.g. that S contains only relation symbols that occur in O or q. The *arity* of Q is defined as the arity of q. We write  $Q(\bar{x})$  to emphasize that the answer variables of q are  $\bar{x}$  and say that Q is *acyclic* if q is and likewise for *weakly acyclic*, *free-connex acyclic*, *self-join free*, and so on.

A tuple  $\overline{c} \in \operatorname{adom}(D)^{|\overline{x}|}$  is a *(certain)* answer to Q on D if  $\overline{c} \in q(I)$  for every model I of O with  $I \supseteq D$ . The evaluation of  $Q(\overline{x})$  over D, denoted Q(D), is the set of all answers to Q over D. Importantly,  $Q(D) = q(\operatorname{ch}_O(D))$  for every  $\operatorname{OMQ} Q = (O, S, q)$  and S-database D. When convenient, we may write  $D \cup O \models q(\overline{c})$  in place of  $\overline{c} \in Q(D)$ . We say that Q is *empty* if  $Q(D) = \emptyset$  for all S-databases D.

Let us remark that a CQ q can be semantically acyclic in the sense that it is equivalent to an acyclic CQ, but not acyclic itself [8, 25]. It is known that this is the case if and only if the homomorphism core of q is acyclic. An OMQ can be semantically acyclic (in the same sense) even if the homomorphism core of the CQ in it is not acyclic, that is, the ontology has an impact on semantic acyclicity; see [6, 7] for very similar effects that pertain to bounded treewidth. Since we are concerned with data complexity in this article, we can simply replace an OMQ with any equivalent one and thus w.l.o.g. refrain from considering semantic acyclicity.

We next introduce the widely known description logic  $\mathcal{ELI}$  [3]. Traditionally, description logics come with their own variable-free syntax. Here, we introduce  $\mathcal{ELI}$  using TGD syntax. A guarded TGD  $\phi(\bar{x}, \bar{y}) \rightarrow \exists \bar{z} \psi(\bar{x}, \bar{z})$  is an  $\mathcal{ELI}$  TGD if it uses only unary and binary relation symbols, has only a single frontier variable, contains no reflexive loops and multi-edges in body or head, and has a head that is acyclic and connected. Note that the original definition of  $\mathcal{ELI}$  is more liberal in that it restricts the body in the same way as the head in our definition, thus encompassing also unguarded TGDs. However, the restricted form used here can be attained by syntactic normalization [3]. Since the normalization of an ontology inside an OMQ does not affect query answers, all results in this paper apply also to the more liberal definition of  $\mathcal{ELI}$ . We use  $\mathbb{ELI}$  to denote the set of all  $\mathcal{ELI}$  TGDs.

An *OMQ* language is a class of OMQs. For a class of TGDs  $\mathbb{C}$  and a class of CQs  $\mathbb{Q}$ , we write ( $\mathbb{C}$ ,  $\mathbb{Q}$ ) to denote the OMQ language that consists of all OMQs (O, S, q) where O is a set of TGDs from  $\mathbb{C}$  and  $q \in \mathbb{Q}$ . For example, we may write ( $\mathbb{G}$ ,  $\mathbb{C}\mathbb{Q}$ ) and ( $\mathbb{ELI}$ ,  $\mathbb{C}\mathbb{Q}$ ).

Let  $Q_i(\bar{x}) = (O_i, S, q_i)$  for  $i \in \{1, 2\}$ . Then OMQ  $Q_1$  is contained in OMQ  $Q_2$ , written  $Q_1 \subseteq Q_2$ , if  $Q_1(D) \subseteq Q_2(D)$  for every Sdatabase *D*. Moreover,  $Q_1$  and  $Q_2$  are *equivalent*, written  $Q_1 \equiv Q_2$ , if  $Q_1 \subseteq Q_2$  and  $Q_2 \subseteq Q_1$ .

**Machine Model.** As our computational model, we use RAMs under the uniform cost model [24], see [30] for a formalization. Such a RAM has a one-way read-only input tape, a write-only output tape, and an unbounded number of registers that store nonnegative integers of  $O(\log n)$  bits, *n* the input size; this is called a DRAM in [30], used there to define the complexity class DLINEAR. Adding, subtracting, and comparing the values of two registers as well as bit shift takes time O(1). On a DRAM, sorting is possible in linear time and we can use and access lookup tables indexed by constants from adom(D) or by tuples of constants of length O(1) [30]. This model is standard in the context of constant delay enumeration, see also [4, 11, 21, 37] and the appendix for more details.

**Modes of Query Evaluation.** Single-testing means to decide, given an OMQ  $Q(\bar{x}) = (O, S, q)$ , an S-database D, and an answer candidate  $\bar{c} \in \text{adom}(D)^{|\bar{x}|}$ , whether  $\bar{c} \in Q(D)$ . We generally consider data complexity, where the OMQ Q is fixed and thus of constant size and the only remaining inputs are D and  $\bar{c}$ .

An enumeration algorithm for a class of OMQs  $\mathbb{C}$  is given as inputs an OMQ  $Q(\bar{x}) = (O, S, q) \in \mathbb{C}$  and an S-database *D*. In the preprocessing phase, it may produce data structures, but no output. In the subsequent enumeration phase, it enumerates all tuples from Q(D), without repetition, followed by an end of enumeration signal. An all-testing algorithm for  $\mathbb{C}$  is defined similarly. It takes the same two inputs, and has the same preprocessing phase, followed by a testing phase where it repeatedly receives tuples  $\bar{a} \in$  $\operatorname{adom}(D)^{|\bar{x}|}$  and returns 'yes' or 'no' depending on whether  $\bar{a} \in Q(D)$ .

Let  $(\mathbb{L}, \mathbb{Q})$  be an OMQ language. We say that answer enumeration for  $(\mathbb{L}, \mathbb{Q})$  is possible with linear preprocessing and constant delay, or in DelayC<sub>lin</sub> for short, if there is an enumeration algorithm for  $(\mathbb{L}, \mathbb{Q})$  in which preprocessing takes time  $f(||Q||) \cdot O(||D||)$ , fa computable function, while the delay between the output of two consecutive answers depends only on ||Q||, but not on ||D||. Enumeration in CDoLin is defined likewise, except that in the enumeration phase, the algorithm may consume only a constant amount of memory. Accessing the data structures computed in the preprocessing phase does not count as memory usage. It is not clear whether DelayC<sub>lin</sub> and CDoLin coincide or not, see e.g. [32]. The definition of DelayC<sub>lin</sub> and CDoLin for all-testing is analogous, except that the enumeration delay is replaced with the time needed for testing.

Partial Answers. We first introduce partial answers with a single wildcard symbol '\*' (that is not in  $C \cup N$ ). A wildcard tuple for an instance *I* takes the form  $(c_1, \ldots, c_n) \in (\operatorname{adom}(I) \cup \{*\})^n, n \ge 0$ . For wildcard tuples  $\bar{c} = (c_1, \ldots, c_n)$  and  $\bar{c}' = (c'_1, \ldots, c'_n)$ , we write  $\bar{c} \leq \bar{c}'$  if  $c'_i \in \{c_i, *\}$  for  $1 \leq i \leq n$ . Moreover,  $\bar{c} < \bar{c}'$  if  $\bar{c} \leq \bar{c}'$  and  $\bar{c} \neq \bar{c}'$ . For example,  $(a, b) \prec (a, *)$  and  $(a, *) \prec (*, *)$ . Informally,  $\bar{c} \prec \bar{c}'$  expresses that tuple  $\bar{c}$  is preferred over tuple  $\bar{c}'$  as it carries more information. A partial answer to OMQ  $Q(\bar{x}) = (O, S, q)$  on S-database D is a wildcard tuple  $\bar{c}$  for D of length  $|\bar{x}|$  such that for each model I of O with  $I \supseteq D$ , there is a  $\overline{c}' \in q(I)$  such that  $\bar{c}' \leq \bar{c}$ . Note that some positions in  $\bar{c}'$  may contain constants from  $adom(I) \setminus adom(D)$ , and that the corresponding position in  $\overline{c}$  must then have a wildcard. A partial answer  $\bar{c}$  to Q on S-database D is a *minimal partial answer* if there is no partial answer  $\bar{c}'$  to Q on D with  $\bar{c}' \prec \bar{c}$ . The partial evaluation of  $Q(\bar{x})$  on D, denoted  $Q(D)^*$ , is the set of all minimal partial answers to Q on D. Note that  $Q(D) \subseteq Q(D)^*$ . An illustrating example is provided in Section 1.

Minimal partial answers may provide valuable information not captured by complete answers. However, one might argue that complete answers are more important than minimal partial answers that contain a wildcard, and should thus be output first by an enumeration algorithm. We observe that this is always possible if we are interested in DelayC<sub>lin</sub> (whereas it is not clear whether an analogous statement for CDoLin holds).

PROPOSITION 2.1. Let  $Q \in (\mathbb{TGD}, \mathbb{CQ})$ . If minimal partial answers to Q can be enumerated in  $\mathsf{DelayC}_{\mathsf{lin}}$  and the same is true for complete answers, then there is a  $\mathsf{DelayC}_{\mathsf{lin}}$  enumeration algorithm for minimal partial answers to Q that produces the complete answers first.

We next introduce partial answers with multiple wildcards. Fix a countably infinite set of wildcards  $\mathcal{W} = \{*_1, *_2, ...\}$  (that are not in  $C \cup N$ ). A multi-wildcard tuple for an instance I is a tuple  $(c_1, ..., c_n) \in (\operatorname{adom}(I) \cup \mathcal{W})^n$ ,  $n \ge 0$ , such that if  $c_i = *_j$  with j > 1, then there is an i' < i with  $c_{i'} = *_{j-1}$ . Examples for multiwildcard tuples are  $(*_1, *_2)$  and  $(a, *_1, b, a, *_2, *_1, *_2)$  and a nonexample is  $(*_2, *_1)$ . Occurrences of the same wildcard represent occurrences of the same null while different wildcards represent nulls that may or may not be different. For multi-wildcard tuples  $\overline{c} = (c_1, ..., c_n)$  and  $\overline{c}' = (c'_1, ..., c'_n)$ , we write  $\overline{c} \le \overline{c}'$  if

(1) 
$$c_i = c'_i$$
 or  $\mathcal{W} \not\ni c_i \neq c'_i \in \mathcal{W}$  for  $1 \le i \le n$  and  
(2)  $c'_i = c'_i$  implies  $c_i = c_j$  for  $1 \le i, j \le n$ .

Moreover,  $\overline{c} < \overline{c}'$  if  $\overline{c} \leq \overline{c}'$  and  $\overline{c} \neq \overline{c}'$ . For example,  $(*_1, a) < (*_1, *_2)$  and  $(a, *_1, *_2, *_1) < (a, *_1, *_2, *_3)$ . Partial answers with multi-wildcards and minimal partial answers with multi-wildcards

are defined in exact analogy with (minimal) partial answers, but using multi-wildcard tuples in place of wildcard tuples. The *partial* evaluation of  $Q(\bar{x})$  with multi-wildcards on D, denoted  $Q(D)^W$ , is the set of all minimal partial answers with multi-wildcards to Q on D.

*Example 2.2.* Reconsider the ontology OMQ Q = (O, S, q) and database D from Example 1.1. Then  $Q(D)^{\mathcal{W}}$  contains the tuples

 $(\mathsf{mary},\mathsf{room1},\mathsf{main1}) \quad (\mathsf{john},\mathsf{room4},*_1) \quad (\mathsf{mike},*_1,*_2).$ 

Let the ontology O' be obtained from O by adding

 $Prof(x) \land HasOffice(x, y) \rightarrow LargeOffice(y)$ 

and  $\mathrm{S}'$  from  $\mathrm{S}$  by adding LargeOffice, consider the CQ

 $q'(x_1, x_2, x_3, x_4) = \text{HasOffice}(x_1, x_2) \land \text{LargeOffice}(x_2) \land$ HasOffice $(x_1, x_3) \land \text{InBuilding}(x_3, x_4),$ 

and let Q' = (O', S', q'). Moreover, let D' be D extended with fact

### Prof(mike).

Then  $Q'(D')^{W}$  contains, among others, the tuple (mike,  $*_1, *_1, *_2$ ), but not the tuple (mike,  $*_1, *_2, *_3$ ) which is a partial answer, but not a minimal one.

Finally, let the ontology O'' be obtained from O by adding

OfficeMate $(x, y) \rightarrow \exists z \operatorname{HasOffice}(x, z) \land \operatorname{HasOffice}(y, z)$ 

and  $\mathrm{S}^{\prime\prime}$  from  $\mathrm{S}$  by adding OfficeMate, consider the CQ

$$q''(x_1, x_2, x_3, x_4) = \exists y \operatorname{\mathsf{Hasoffice}}(x_1, x_3) \land \operatorname{\mathsf{Hasoffice}}(x_2, x_4) \land$$
  
InBuilding(x<sub>3</sub>, y)  $\land$  InBuilding(x<sub>4</sub>, y),

and set  $Q''(x_1, x_2, x_3, x_4) = (O'', S'', q'')$ . Moreover, let D'' be D extended with fact

OfficeMate(mary, mike).

 $Q''(D'')^W$  contains, among others, the tuple (mary, mike,  $*_1, *_1$ ).

It should not be surprising that minimal partial answers can equivalently be defined in terms of the chase. Let  $q(\bar{x})$  be a CQ and I an instance, possibly containing nulls. For an answer  $\bar{a} \in q(I)$ , we use  $\bar{a}_N^*$  to denote the (unique) wildcard tuple for I obtained from  $\bar{a}$  by replacing all nulls with '\*'. We call such an  $\bar{a}_N^*$  a *partial answer* to q on I and say that it is a *minimal* partial answer if there is no  $\bar{b} \in q(I)$  with  $\bar{b}_N^* < \bar{a}_N^*$ . We use  $q(I)_N^*$  to denote the set of minimal partial answers to q on I. Similarly, we use  $\bar{a}_N^W$  to denote the (unique) multi-wildcard tuple for I obtained by consistently replacing all nulls with wildcards from  $\mathcal{W} = \{*1, *2, \ldots\}$ . We then define *minimal partial answer with multi-wildcards* to q on I, denote  $q(D)_N^W$ , in the expected way.

LEMMA 2.3. Let  $Q(\bar{x}) = (O, S, q) \in (\mathbb{TGD}, \mathbb{CQ})$  and D be an S-database. Then  $Q(D)^* = q(ch_O(D))_N^*$  and  $Q(D)^W = q(ch_O(D))_N^W$ .

We remark that there is a subtlety here. In contrast to Lemma 2.3, the (not necessarily minimal) partial answers to  $Q(\bar{x}) = (O, S, q)$  on an S-database *D* need not coincide with the partial answers to *q* on  $ch_O(D)$ . In fact,  $(*, \dots, *)$  is a partial answer to  $Q(\bar{x}) = (O, S, q)$  on *D* if there is a partial answer at all, but this is not the case for the partial answers to *q* on  $ch_O(D)$ , e.g. when  $Q(x) = (\emptyset, \{A\}, A(x))$  and  $D = \{A(c)\}$ .

# **3 SINGLE-TESTING**

We consider the limits of single-testing in linear time for the OMQ languages ( $\mathbb{G}$ ,  $\mathbb{CQ}$ ) and ( $\mathbb{ELI}$ ,  $\mathbb{CQ}$ ). For complete answers, we establish a close link to weak acyclicity while minimal partial answers with a single wildcard are linked (in a more loose way) to acyclicity. The latter is also achieved for minimal partial answers with multiwildcards, but only when the ontology is from  $\mathbb{ELI}$ . To the best of our knowledge, these are the first results on linear time singletesting for ontology-mediated queries. Existing algorithms from the literature seem to require at least quadratic time (although authors typically do not analyse the degree of the polynomial explicitly).

THEOREM 3.1. Single-testing is in linear time for

- weakly acyclic OMQs from (G, CQ) in the case of complete answers;
- (2) acyclic OMQs from (G, CQ) in the case of minimal partial answers with single wildcards;
- (3) acyclic OMQs from (ELI, CQ) in the case of minimal partial answers with multi-wildcards.

To prove Theorem 3.1, we first show that for every OMQ  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  and S-database D, one can compute in time linear in ||D|| a (finite!) database  $ch_O^q(D)$  that enjoys all properties of the chase  $ch_O(D)$  which are important for enumerating answers to Q, both complete and partial. Informally,  $ch_O^q(D)$  contains only those parts of  $ch_O(D)$  that are 'relevant to q'. We refer to  $ch_O^q(D)$  as the *query-directed chase*, similar constructions have been used e.g. in [6, 14].

Let cl(Q) denote the set of CQs that are connected and use only relation symbols that occur in O, no constants, and only variables from a fixed set V whose cardinality is the maximum of |var(q)|and the arities of relation symbols in O. Note that the CQs in cl(Q)may have any arity, including zero, and that the number of CQs in cl(Q) is independent of D. The database  $ch_O^q(D)$  is obtained from D by adding, for every CQ  $p(\bar{y}) \in cl(Q)$  and every  $\bar{c} \in adom(D)^{|\bar{y}|}$ such that  $D \cup O \models p(\bar{c})$  and the constants in  $\bar{c}$  constitute a guarded set in D, a copy of  $D_p$  that uses the constants in  $\bar{c}$  in place of the answer variables  $\bar{y}$  of p and only fresh constants otherwise.

LEMMA 3.2. Let  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  and D be an S-database. Then  $Q(D) = q(\operatorname{ch}_{O}^{q}(D)) \cap \operatorname{adom}(D)^{|\bar{x}|}, Q(D)^{*} = q(\operatorname{ch}_{O}^{q}(D))_{\mathrm{N}}^{*},$ and  $Q(D)^{\mathcal{W}} = q(\operatorname{ch}_{O}^{q}(D))_{\mathrm{N}}^{\mathcal{W}}.$ 

As announced, the query-directed chase can be computed in linear time. Q is not required to be acyclic for this to hold.

PROPOSITION 3.3. Let  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  and let D be an S-database. Then  $ch_O^q(D)$  can be computed in time linear in ||D||, more precisely in time  $2^{2^{O(||Q||^2)}} \cdot ||D||$ .

To prove Proposition 3.3, we derive from D and Q a satisfiable Horn formula  $\theta$ , make use of the fact that a minimal model of  $\theta$  can be computed in linear time [28], and then read off  $ch_O^q(D)$  from the minimal model. We are not aware that such an approach has been used before.

For Point (1) of Theorem 3.1, we have to check whether  $\bar{c} \in Q(D)$  which can now be done in linear time a straightforward way.

First compute  $ch_O^q(D)$ . Then replace the answer variables in q by the constants from  $\bar{c}$ , turning the weakly acyclic q into an acyclic CQ. Finally, use an existing procedure such as Yannakakis' algorithm to single-test the resulting CQ in linear time [38]. Points (2) and (3) of Theorem 3.1 are proved by a (Turing) reduction to the case of complete answers. Details are provided in the appendix.

We next prove a lower bound that partially matches Theorem 3.1. As in the case without ontologies, we do not obtain a full dichotomy as the lower bound only applies to queries that are self-join free. In addition (and related to this), it only applies to OMQs where the ontology is formulated in the subclass  $\mathbb{ELI}$  of  $\mathbb{G}$ . The lower bound is conditional on the triangle conjecture, which we formulate next. *Triangle detection* is the problem to decide, given an undirected graph G = (V, E) as a list of edges, whether G contains a 3-clique. The triangle conjecture from fine-grained complexity theory [1] states that triangle detection cannot be solved in linear time.

THEOREM 3.4. Let  $Q \in (\mathbb{ELI}, \mathbb{CQ})$  be non-empty and self-join free. If Q is not weakly acyclic, single-testing complete answers to Q is not in linear time unless the triangle conjecture fails. The same is true for minimal partial answers and minimal partial answers with multiple wildcards.

The proof of Theorem 3.4 is an adaptation of the construction given in [11, 17] where no ontologies are considered. The challenge is to deal with the ontology and the fact that the ontology may contain relation symbols that are not admitted in the database. We address this by modifying the database construction from [11, 17] so that every constant *c* comes with fact A(c) for every unary relation symbol  $A \in S$  and has an incoming and an outgoing *R*-edge for every binary relation symbol  $R \in S$ . Informally, this ensures that everything that could possibly be implied by the ontology is indeed implied. Self-join freeness is important for this approach to work.

While it would be desirable to replace  $\mathbb{ELI}$  with  $\mathbb{G}$  in Theorem 3.4, this seems hard to achieve as it would also allow us to remove 'self-join free' from that theorem. Even in the case without ontologies, it is currently not known whether this is possible.

*Example 3.5.* Let  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  and let Q' = (O', S, q') be the OMQ that can be obtained from Q as follows: consider every atom  $R(\bar{z})$  in q, replace it with  $R_{\bar{z}}(\bar{z})$  where  $R_{\bar{z}}$  is a fresh relation symbol of the same arity as R, and add to O the TGDs

$$R(\bar{x}) \to R_{\bar{z}}(\bar{x})$$
 and  $R_{\bar{z}}(\bar{x}) \to R(\bar{x})$ 

where  $\bar{x}$  is a tuple of  $\operatorname{ar}(R)$  distinct variables. Then  $Q \equiv Q'$ , and Q' is self-join free. Moreover, Q' is weakly acyclic if and only if Q is.

More examples regarding Theorem 3.4 are given in the appendix. We close with noting that the prerequisites given in Theorem 3.1 for the case of minimal partial answers cannot easily be relaxed.

THEOREM 3.6. (1) There is a weakly acyclic  $OMQQ \in (\mathbb{ELI}, \mathbb{CQ})$ for which single-testing minimal partial answers is not in linear time unless the triangle conjecture fails and (2) an acyclic  $OMQQ \in (\mathbb{G}, \mathbb{CQ})$ for which single-testing minimal partial answers with multi-wildcards is not in linear time unless the triangle conjecture fails.

# 4 ENUMERATION AND ALL-TESTING: COMPLETE ANSWERS

We consider the limits of enumeration and all-testing of complete answers with constant delay for the OMQ languages ( $\mathbb{G}$ ,  $\mathbb{CQ}$ ) and ( $\mathbb{ELI}$ ,  $\mathbb{CQ}$ ). While enumeration is linked to the combination of acyclicity and free-connex acyclicity, we link all-testing to free-connex acyclicity only. In the lower bounds, we also consider minimal partial answers and minimal partial answers with multiple wildcards. We start with the upper bounds.

Theorem 4.1. In  $(\mathbb{G}, \mathbb{CQ})$ ,

- enumerating complete answers is in CDoLin for OMQs that are acyclic and free-connex acyclic;
- (2) all-testing complete answers is in CDoLin for OMQs that are free-connex acyclic.

Recall that for a CQ q to be free-connex acyclic, we do *not* require q to be acyclic. Thus, the requirement for all-testing in Theorem 4.1 is significantly weaker than that for enumeration and embraces, for example, every OMQ in which the CQ is full, that is, has no quantified variables. The proof of Point (1) of Theorem 4.1 uses the query-directed chase also employed in Section 3 and a reduction to the CDoLin enumeration of answers to CQs (without ontologies) that are acyclic and free-connex acyclic [4]. Point (2) can be proved in the same way using the following observation which, to our knowledge, is novel.

PROPOSITION 4.2. For CQs (without ontologies) that are free-connex acyclic, all-testing is in CDoLin.

To prove Proposition 4.2, we decompose the given CQ into CQs that are acyclic and free-connex acyclic, and then use CDoLin all-testing algorithms for those component CQs in parallel. In the appendix, we give a matching lower bound for self-join free CQs.

We next give lower bounds that partially match Theorem 4.1, starting with the requirement in Point (1) of Theorem 4.1 that OMQs must be acyclic. The following is a consequence of Theorem 3.4.

THEOREM 4.3. Let  $Q \in (\mathbb{ELL}, \mathbb{CQ})$  be non-empty, and self-join free. If Q is not acyclic, then enumerating complete answers to Q is not in  $\mathsf{DelayC}_{\mathsf{lin}}$  unless the triangle conjecture fails. The same is true for minimal partial answers and for minimal partial answers with multiple wildcards.

In Theorem 4.3 and all other lower bounds stated in this section,  $\mathbb{ELI}$  cannot easily be replaced by  $\mathbb{G}$ , see Example 3.5.

Staying with the requirements of Point (1) of Theorem 4.2, we next consider queries that are acyclic, but not free-connex acyclic. The lower bound that we establish is conditional on an assumption regarding the problem of Sparse Boolean matrix multiplication. A Boolean  $n \times n$  matrix is a function  $M : [n]^2 \rightarrow \{0, 1\}$  where [n] denotes the set  $\{1, \ldots, n\}$ . The *product* of two Boolean  $n \times n$  matrices  $M_1, M_2$  is the Boolean  $n \times n$  matrix  $M_1M_2 := \sum_{c=1}^n M_1(a,c) \cdot M_2(c,b)$  where sum and product are interpreted over the Boolean semiring. In (non-sparse) *Boolean matrix multiplication (BMM)*, one wants to compute  $M_1M_2$  given  $M_1$  and  $M_2$  as  $n \times n$  arrays. In *sparse Boolean matrix multiplication (spBMM)*, input and output matrices M are represented as lists of pairs (a, b) with M(a, b) = 1. Our lower bound is conditional on the assumption that spBMM is not

possible in time  $O(|M_1| + |M_2| + |M_1M_2|)$ , that is, in time linear in the size of the input and the output (represented as lists). While it is not ruled out that such a running time can be achieved, this would require dramatic progress in algorithm theory. Informally, the conditioning on spBMM should be read as 'currently out of reach'.

THEOREM 4.4. Let  $Q = (O, S, q) \in (\mathbb{ELI}, \mathbb{CQ})$  be acyclic, non-empty, self-join free, and connected. If Q is not free-connex acyclic, then enumerating complete answers to Q is not in DelayC<sub>lin</sub> unless spBMM is possible in time  $O(|M_1| + |M_2| + |M_1M_2|)$ . The same is true for minimal partial answers and for minimal partial answers with multiple wildcards.

There is a corresponding lower bound for CQs without ontologies, first proved conditional on the assumption that Boolean  $n \times n$ matrices cannot be multiplied in time  $O(n^2)$  [4] and then improved to the condition on spBMM used in Theorem 4.4 in [11]. To prove Theorem 4.4, we again have to deal with the fact that the ontology may contain relation symbols that are not admitted in the database. Here, this is done by first manipulating the input matrices  $M_1$  and  $M_2$  in a suitable way. Note that we require Q to be connected while this is not a precondition in the case without ontologies [11]. The following proposition shows that we cannot drop connectedness.

PROPOSITION 4.5. There is an  $OMQQ \in (\mathbb{ELI}, \mathbb{CQ})$  that is acyclic, non-empty, self-join free, but neither free-connex acyclic nor connected, such that complete answers to Q can be enumerated in  $DelayC_{lin}$ .

We next address the requirement in Point (2) of Theorem 4.2 that OMQs must be free-connex acyclic.

THEOREM 4.6. Let  $Q \in (\mathbb{ELI}, \mathbb{CQ})$  be non-empty and self-join free. If Q is not free-connex acyclic, then all-testing complete answers for Q is not in linear time unless the triangle conjecture fails or Boolean  $n \times n$  matrices can be multiplied in time  $O(n^2)$ . The same is true for minimal partial answers and minimal partial answers with multiple wildcards.

Note that Theorem 4.6 refers to the non-sparse version of BMM and that spBMM in time  $O(|M_1| + |M_2| + |M_1M_2|)$  implies BMM in time  $O(n^2)$  while the converse is unknown.

# 5 ENUMERATION WITH SINGLE WILDCARD

The main aim of this section is to prove that it is possible to enumerate in DelayC<sub>lin</sub> the minimal partial answers with a single wildcard to OMQs from ( $\mathbb{G}$ ,  $\mathbb{CQ}$ ) that are acyclic and free-connex acyclic. Thus, minimal partial answers are almost as well-behaved as complete answers, except that for the former it remains open whether enumeration is also possible in CDoLin. We start, however, with observing that all-testing of minimal partial answers is less wellbehaved. The following should be contrasted with Point (2) of Theorem 4.1.

THEOREM 5.1. There is an  $OMQQ \in (\mathbb{ELI}, \mathbb{CQ})$  that is acyclic and free-connex acyclic such that all-testing minimal partial answers to Q is not in  $DelayC_{lin}$  unless the triangle conjecture fails. The same is true for minimal partial answers with multiple wildcards.

Intuitively, all-testing of minimal partial answers is difficult because a single positive test for an answer that contains wildcards may imply a negative test for polynomially many complete answers. This is not a problem in enumeration where the 'problematic' wildcard answers will be output late and thus cannot be tested in linear time.

We now turn to the main result of this section.

THEOREM 5.2. Enumerating minimal partial answers is in DelayC<sub>lin</sub> for OMQs from ( $\mathbb{G}, \mathbb{CQ}$ ) that are acyclic and free-connex acyclic.

In the rest of this section, we prove Theorem 5.2 by developing an enumeration algorithm. We provide an example that illustrates important aspects of our algorithm in Appendix G. Fix an OMQ  $Q(\bar{x}) = (O, S, q_0) \in (\mathbb{G}, CQ)$  with  $q_0$  acyclic and free-connex acyclic, and let an S-database *D* be given as input.

**Preprocessing phase.** Recall from Section 3 that the querydirected chase  $ch_{O}^{q_0}(D)$  can be constructed in time linear in ||D||. This is the first step of the preprocessing phase. By Lemmas 2.3 and 3.2, we may enumerate  $q_0(ch_{O}^{q_0}(D))_N^*$  in place of  $Q(D)^*$ . For brevity, set  $D_0 := ch_{O}^{q_0}(D)$ .

We argue in the appendix that wean assume w.l.o.g. that the tuple  $\bar{x}$  has no repeated variables and that  $q_0$  contains no constants and is connected. As part of the preprocessing phase, we preprocess  $q_0$  and  $D_0$  in a way that resembles the first phase of the Yannakakis algorithm in which a join tree is traversed in a bottom-up fashion, computing a semi-join in each step [38]. The result is a CQ  $q_1(\bar{x})$  and database  $D_1$  that satisfy the following conditions:

- (i)  $q_1$  is self-join free, connected (since  $q_0$  is), acyclic, and has no quantified variables (thus is free-connex acyclic); it therefore has a join tree  $T_1 = (V_1, E_1)$ ; we choose a root in  $T_1$ allowing us to speak about predecessors and successors in  $T_1$ ;
- (ii) adom(D<sub>1</sub>) ⊆ adom(D<sub>0</sub>) and for every fact R(ā) ∈ D<sub>1</sub>, there is a fact S(b) ∈ D<sub>0</sub> such that ā and b contain exactly the same (database and null) constants;
- (iii)  $q_0(D_0) = q_1(D_1)$ , and thus  $q_0(D_0)_N^* = q_1(D_1)_N^*$ ;
- (iv) for all  $v = R(\bar{y}) \in V_1$ , facts  $R(\bar{a}) \in D_1$ , and successors  $v' = S(\bar{z})$  of v in  $T_1, D_1$  contains a fact  $S(\bar{b})$  such that if position i of  $\bar{y}$  has the same variable as position j of  $\bar{z}$ , then position i of  $\bar{a}$  has the same constant as position j of  $\bar{b}$ .

We refer to Condition (iv) as the *progress condition*. Informally, it makes sure that an enumeration algorithm that traverses  $T_1$  in a pre-order tree walk never gets 'stuck' in the sense that it can always extend the partial answer produced so far to a full answer. The construction of  $q_1$  and  $D_1$  is possible in time linear in  $||D_0||$ . It has been used many times in the context of enumerating answers to conjunctive queries (without ontologies) with constant delay. We give an outline in the appendix and refer to [11] for a very clear exposition of the full details. The construction of  $q_1$  and  $D_1$  also tells us whether  $q_0(D_0) = \emptyset$ . If this is the case, we stop without entering the enumeration phase.

We also use the preprocessing phase to compute data structures that are used in the enumeration phase. We start with some preliminaries. With a *predecessor variable* in an atom  $v \in V_1$ , we mean a variable that v shares with its predecessor in  $T_1$ . By definition, the root of  $T_1$  does not have any predecessor variables. A CQ q is a *subtree* of  $q_1$  if there is a subset  $V_q \subseteq V_1$  such that the subgraph  $T_q = (V_q, E_1|_{V_q \times V_q})$  of  $T_1$  induced by  $V_q$  is connected. Note that q must be connected since  $q_1$  is and that  $T_q$  is a join tree for q. We assume that  $T_q$  inherits the direction imposed on  $T_1$  and thus, for instance, may speak about its root.

A progress tree is a pair (q,g) with q a subtree of  $q_1$  and g: var $(q) \rightarrow (adom(D_1) \setminus N) \cup \{*\}$  a map such that the following conditions are satisfied:

- (1)  $g(x) \neq *$  for every predecessor variable *x* in the root of  $T_q$ ;
- (2) if v ∈ Vq and v' is a successor of v in T1, then v' ∈ Vq if and only if g(x) = \* for some predecessor variable x in v';
- (3) there is a homomorphism h from q to D<sub>1</sub> such that for all x ∈ var(q), h(x) ∈ N if g(x) = \* and h(x) = g(x) otherwise;
- (4) the constants in the range of g form a guarded set in  $D_1$ .

To explain the intuition of progress trees, consider a homomorphism *h* from  $q_1$  to  $D_1$  and an atom  $v = R(\bar{y}) \in V_1$  with predecessor variables  $\bar{z}$ . If  $h(\bar{y}) \cap N = \emptyset$ , then (v, g) is a (single atom) progress tree, *q* the restriction of *h* to the variables in  $\overline{y}$ . More interesting is the case where  $h(\bar{z}) \cap N = \emptyset$ , but  $h(\bar{y}) \cap N \neq \emptyset$ . Informally, under homomorphism h such an atom v 'crosses the boundary' between the 'database part' of  $D_1$  and the 'null part' of  $D_1$ . Let  $V_q \subseteq V_1$  be the smallest set that contains v and such that if  $u \in V_q$  and u' is a successor of *u* in  $T_1$  such that  $h(x) \in N$  for at least one predecessor variable in u', then  $u' \in V_q$ . This defines a subtree q of  $q_1$  and (q, g)is then a progress tree, where g is the restriction of h to the variables in q with constants from N replaced by \*. Informally, (q, g)thus describes an 'excursion' of the part q of  $q_1$  into the 'null part' of  $D_1$  and it turns out that properly dealing with such excursions is key to enumerating minimal partial answers. Note that the constants in the range of q form a guarded set in  $D_1$ , as required. This relies on  $q_1$  being connected as otherwise, it would be possible to cross the boundary to the null part of  $D_1$  at some guarded set, but return to the database part at a different guarded set.

Consider an atom v in  $q_1$  with predecessor variables  $\overline{z}$ . A predecessor map for v is a function  $h : \overline{z} \to \operatorname{adom}(D_1) \setminus N$  that extends to a homomorphism from v to  $D_1$ . We call such v and h relevant. For all relevant v and h, we compute a linked list trees(v, h) of all progress trees (q, g) with root v such that  $g(\overline{z}) = h(\overline{z})$ . We sort the list trees(v, h) so that it is in *database-preferring order*. This means that progress tree (q, g) is before progress tree (q', g') whenever  $(q, g) \prec_{db} (q', g')$ , which is the case if q and q' have the same root and  $V_q \subsetneq V_{q'}$ , or the following conditions are satisfied for all  $x \in \operatorname{var}(q)$ :

(a)  $V_q = V_{q'};$ 

- (b) q(x) = \* implies q'(x) = \*;
- (c)  $g(x) \neq *$  implies  $g'(x) \in \{g(x), *\};$
- (d) for some  $x \in var(q)$ , q'(x) = \* while  $q(x) \neq *$ .

The algorithm uses these lists as a global data structure that is both accessed and modified. We show in the appendix that the lists trees(v, h) can indeed be computed in linear time on a RAM.

LEMMA 5.3. The lists trees(v, h), for all relevant v and h, can be computed in overall time linear in  $||D_1||$ . Moreover, all these lists are non-empty.

Let  $v_0, \ldots, v_k$  be the ordering of the atoms in  $V_1$  generated by a pre-order traversal of  $T_1$ . For  $v_i \in \{v_0, \ldots, v_k\}$  and a partial map  $h : var(q_1) \rightarrow (adom(D_1) \setminus N) \cup \{*\}$ , we use nextat<sub>h</sub> $(v_i)$  to denote

 $v_j$  with j > i smallest such that h(x) is undefined for some variable x in  $v_j$ , if such j exists, and the special symbol eoa (*end of atoms*) otherwise. Clearly, computing nextat is independent of  $||D_1||$  and can thus be done in constant time.

**Enumeration Phase.** The enumeration phase of the algorithm is presented in Figure 1. In the **forall** loop in Line 10, we follow the database-preferring order imposed on the trees lists. It is straightforward to show the invariant that when a call enum(v, h) is made, then  $v, h|_{\overline{z}}$  used in Line 12 is relevant. The following is an important observation.

LEMMA 5.4. None of the lists trees(v, h), with v, h relevant, ever becomes empty.

Lemma 5.4 is important to achieve constant delay because it implies that that in each call enum(v, h), the **forall** loop in Line 10 makes at least one iteration and thus at least one recursive call in Line 12. Consequently, while traversing  $q_1$  we never backtrack without producing an output. Note that given v and  $h|_{\bar{z}}$ , we need to find the (first element of the) list trees(v,  $h|_{\bar{z}}$ ) in constant time. On a RAM, this can be achieved by a straightforward lookup table.

In the prune subprocedure, there are only constantly many progress trees (q,g) with  $(q,g) >_{db} (q,h|_{var(q)})$  and these can be found in constant time by starting with  $g = h|_{var(q)}$  and then choosing one or more variables  $x \in var(q)$  with  $g(x) \neq *$  and setting g(x) = \*. Note that the pair  $(q,h|_{var(q)})$  is neither required nor guaranteed to be a progress tree. To remove (q',g') from trees $(v,h|_{\bar{z}})$ , it is not possible to iterate over all progress trees in trees $(v,h|_{\bar{z}})$  in search of (q',g') as there may be linearly many trees in the list. This problem is also solved by a lookup table. When generating the trees lists in the preprocessing phase, we also generate a lookup table that takes as argument a progress tree and yields the memory location (register) where that tree is stored as part of a list trees(v,h). Note that every progress tree occurs in at most one such list. If the list is bidirectionally linked, it is then easy to locate and remove the tree in constant time.

In the appendix, we prove that the algorithm achieves its goal.

**PROPOSITION 5.5.** The algorithm outputs exactly the minimal partial answers to  $q_1$  on  $D_1$ , without repetition.

# 6 ENUMERATION WITH MULTI-WILDCARDS

We show that Theorem 5.2 lifts from the case of a single wildcard to the case of multi-wildcards.

THEOREM 6.1. Enumerating minimal partial answers with multiwildcards is in  $DelayC_{lin}$  for OMQs from (G, CQ) that are acyclic and free-connex acyclic.

Fix an OMQ  $Q(\bar{x}) = (O, S, q_0) \in (\mathbb{G}, \mathbb{CQ})$  with  $q_0$  acyclic and free-connex acyclic and let an S-database *D* be given as input. By Lemmas 2.3 and 3.2, we may enumerate  $q_0(\operatorname{ch}_O^{q_0}(D))_{\mathrm{N}}^{\mathcal{W}}$  in place of  $Q(D)^{\mathcal{W}}$ . For brevity, we from now on use *D* to denote  $\operatorname{ch}_O^{q_0}(D)$  (and we will never refer back to the original *D*).

Our general approach to enumerating  $Q^{\mathcal{W}}(D)$  is to combine the enumeration algorithm from Theorem 5.2, here called  $A_1$ , with a

Efficiently Enumerating Answers to Ontology-Mediated Queries

Algorithm 1 Enumeration of minimal partial answers.

	$h_0 = \emptyset;$		
	$enum(nextat_{h_0}(v_0), h_0);$		
	<b>function</b> enum $(v, h)$		
5:	if $v = eoa$ then		
	output $h(\bar{x})$ ;	$\%  ar{x}$ the variables in g	
	prune(h);	1	
	return		
	let $v = R(\bar{y})$ with predecessor v	variables $\bar{z}$ ;	
10:	for all $(q,g) \in \text{trees}(v,h _{\bar{z}})$ do		
	$h' = h \cup g;$		
	$enum(nextat_{h'}(v), h');$		
	return		
15:	<b>function</b> prune( <i>h</i> )		
	<b>for all</b> subtrees $q$ of $q_1$ <b>do</b>		
	let v be the root of q with predecessor variables $\overline{z}$ ;		
	<b>for all</b> progress trees $(q, g) >_{db} (q, h _{var(q)})$ <b>do</b>		
	remove $(q,g)$ from tree	$s(v,h _{\bar{z}})$	
20:	return		

 $\mathsf{DelayC}_{\mathsf{lin}}$  algorithm for all-testing (not necessarily minimal) partial answers with multi-wildcards. In fact, we develop such an algorithm  $A_2$  in the appendix, which is non-trivial. The algorithm involves a multi-wildcard version of progress trees and running in parallel  $\mathsf{DelayC}_{\mathsf{lin}}$  all-testing algorithms for complete answers to any subquery q' of q, that is, to any CQ q' that can be obtained from q by dropping atoms.

With that algorithm in place, a first implementation of the general approach could then be as follows. Use  $A_1$  to enumerate  $Q^*(D)$ . For each obtained answer  $\bar{a}^*$ , construct the *multi-wildcard ball of*  $\bar{a}^*$ , that is, the set  $B^{\mathcal{W}}(\bar{a}^*)$  of multi-wildcard tuples  $\bar{a}^{\mathcal{W}}$  such that replacing all occurrences of wildcards from  $\mathcal{W}$  in  $\bar{a}^{\mathcal{W}}$  by the single-wildcard '\*' results in  $\bar{a}^*$ . Notice that if the length of  $\bar{a}^*$  is bounded by a constant, then so is the cardinality of the multi-wildcard ball of  $\bar{a}^*$ . Discard from  $B^{\mathcal{W}}(\bar{a}^*)$  those tuples that are not partial answers using  $A_2$ , and then output those among the remaining tuples that are minimal w.r.t. '<'. This first implementation is incomplete.

*Example 6.2.* Let  $Q = (O, S, q_0)$  where

$$O = \{A(x) \to \exists y_1 \exists y_2 R(x, y_1) \land T(x, y_1) \land S(x, y_2)\},\$$

S contains all relation symbols in Q, and

$$q_0(x_0, x_1, x_2, x_3) = R(x_0, x_1) \wedge S(x_0, x_2) \wedge T(x_0, x_3).$$

Further let  $D = \{A(c), R(c, c')\}$ . Then  $Q^*(D) = \{(c, c', *, *)\}$  and  $Q^{W}(D) = \{(c, c', *_1, *_2), (c, *_1, *_2, *_1)\}$ . But we never consider (and thus do not output) the multi-wildcard tuple  $(c, *_1, *_2, *_1)$ .

The solution involves replacing the multi-wildcard ball  $B^{\mathcal{W}}(\bar{a}^*)$  with the *multi-wildcard cone* 

$$\operatorname{cone}^{\mathcal{W}}(\bar{a}^*) = \bigcup_{\bar{b}^*: \bar{a}^* \leq \bar{b}^*} B^{\mathcal{W}}(\bar{b}^*).$$

Technical Report, arXiv version, 2022

Algorithm 2 Enumeration of minimal partial answers with multi-
wildcards.
L = [];
for all $\bar{a}^* \in q(D)^*_N$ do
3: for all $\bar{a}^{\mathcal{W}} \in \operatorname{cone}^{\mathcal{W}}(\bar{a}^*) \cap q(D)_{N}^{\mathcal{W}, \bigstar}$ with $F(\bar{a}^{\mathcal{W}}) = 0$ do
$F(\bar{a}^{\mathcal{W}}) = 1;$
append $\bar{a}^{\mathcal{W}}$ to L;
6: prune $(\bar{a}^{\mathcal{W}})$
choose $\bar{a}^{\mathcal{W}} \in \min^{\prec}(B^{\mathcal{W}}(\bar{a}^*) \cap q(D)_{N}^{\mathcal{W}, \bigstar});$
output $\bar{a}^{\mathcal{W}}$ ;
9: remove $\bar{a}^{\mathcal{W}}$ from <i>L</i> ;
output all tuples in <i>L</i> ;
return
12:
<b>function</b> prune( $\bar{a}^{\mathcal{W}}$ )
for all multi-wildcard tuples $\bar{b}^{\mathcal{W}}$ such that $\bar{a}^{\mathcal{W}} \prec \bar{b}^{\mathcal{W}}$ do
15: $F(\bar{b}^{\mathcal{W}}) = 1;$
remove $\bar{b}^{\mathcal{W}}$ from <i>L</i> ;
return

Clearly, also the cardinality of  $\operatorname{cone}^{W}(\bar{a}^*)$  is bounded by a constant if the length of  $\bar{a}^*$  is. Regarding Example 6.2, note that  $(c, *_1, *_2, *_1) \notin B^W(c, c', *, *)$ , but  $(c, *_1, *_2, *_1) \in \operatorname{cone}^{W}(c, c', *, *)$ . However, the cones of different tuples  $\bar{a}^*, \bar{b}^* \in Q^*(D)$  might overlap and thus for some  $\bar{a}^* \in Q^*(D)$ , there might be no tuple in  $\operatorname{cone}^{W}(\bar{a}^*)$  that we haven't yet output, compromising constant delay. We address these issues by using a careful combination of balls, cones, and pruning.

We now describe our algorithm in full detail. The preprocessing phase consists of running the preprocessing phases of  $A_1$  and  $A_2$ . The enumeration phase is shown in Figure 2. With L, we denote a bidirectionally linked list in which we store multi-wildcard tuples and that is initialized as the empty list. In the **forall** loop in Line 2, we use algorithm  $A_1$  to iterate over all minimal partial answers in  $q(D)_{\rm N}^*$ . With  $q(D)_{\rm N}^{W,\star}$ , we denote the set of (not necessarily minimal) partial answers with multi-wildcards to CQ q on database D. The intersections with  $q(D)_{\rm N}^{W,\kappa}$  in Line 3 and 7 can be computed in constant time using algorithm  $A_2$ . F is a lookup table that stores a Boolean value for every multi-wildcard tuple of length  $|\bar{x}|$ , initialized with 0; this is done implicitly as all memory is initialized with 0 in our machine model. Informally,  $F(\bar{a}^{\mathcal{W}})$  is set to 1 if  $\bar{a}^{\mathcal{W}}$ has already been added to the list L or is not in  $q(D)_{N}^{W}$  (and thus does not need to be added to L). For a set of multi-wildcard tuples S, we use  $\min^{\prec}(S)$  to denote the tuples in S that are minimal w.r.t. '<'. To remove multi-wildcard tuples from L in constant time, we use another lookup table that stores, for every multi-wildcard tuple  $\bar{a}^{W}$  that we have added to *L*, the memory location of the list node representing  $\bar{a}^{W}$  on *L*. Since *L* is bidirectionally linked, this allows us to remove  $\bar{a}^{\mathcal{W}}$  from L in constant time. Since the arity of relation symbols is (implicitly) bounded by a constant, so is the number of iterations of the **forall** loop in Line 14. From what was said above, it follows that the preprocessing phase runs in linear time while the enumeration phase has only constant delay. Correctness is proved in the appendix.

LEMMA 6.3. The algorithm outputs exactly the minimal partial answers with multi-wildcards to q on D, without repetition.

# 7 CONCLUSIONS

As future work, it would be interesting to consider as the ontology language also description logics with functional roles such as  $\mathcal{ELIF}$ ; there should be a close connection to enumeration of answers to CQs in the presence of functional dependencies [21]. A much more daring extension would be to ( $\mathbb{G}, \mathbb{UCQ}$ ) or even to ( $\mathbb{FG}, (\mathbb{U})\mathbb{CQ}$ ) where  $\mathbb{UCQ}$  denotes unions of CQs and  $\mathbb{FG}$  denotes frontier-guarded TGDs. Note, however, that enumeration in CDoLin of answers to UCQs is not fully understood even in the case without ontologies [22]. Another interesting question is whether the enumeration problems placed in DelayC<sub>lin</sub> in the current paper actually fall within CDoLin, that is, whether the use of a polynomial amount of memory in the enumeration phase can be avoided.

Acknowledgement. We acknowledge support by the DFG project LU 1417/3-1 'QTEC'.

#### REFERENCES

- Amir Abboud and Virginia Vassilevska Williams. Popular conjectures imply strong lower bounds for dynamic problems. In *Proceedings of FOCS 2014*, pages 434–443. IEEE Computer Society, 2014. doi:10.1109/FOCS.2014.53.
- [2] Serge Abiteboul, Richard Hull, and Victor Vianu. Foundations of Databases. Addison-Wesley, 1995. URL: http://webdam.inria.fr/Alice/.
- [3] Franz Baader, Ian Horrocks, Carsten Lutz, and Ulrike Sattler. An Introduction to Description Logic. Cambridge University Press, 2017. doi:10.1017/9781139025355.
- [4] Guillaume Bagan, Arnaud Durand, and Etienne Grandjean. On acyclic conjunctive queries and constant delay enumeration. In *Proceedings of CSL 2007*, volume 4646, pages 208–222, 2007. doi:10.1007/978-3-540-74915-8\\_18.
- [5] Jean-François Baget, Marie-Laure Mugnier, Sebastian Rudolph, and Michaël Thomazo. Walking the complexity lines for generalized guarded existential rules. In *Proceedings of IJCAI 2011*, pages 712–717. IJCAI/AAAI, 2011. doi:10.5591/978-1-57735-516-8/JJCAI11-126.
- [6] Pablo Barceló, Victor Dalmau, Cristina Feier, Carsten Lutz, and Andreas Pieris. The limits of efficiency for open- and closed-world query evaluation under guarded TGDs. In *Proceedings of PODS 2020*, pages 259–270, 2020. doi:10.1145/3375395.3387653.
- [7] Pablo Barceló, Cristina Feier, Carsten Lutz, and Andreas Pieris. When is ontology-mediated querying efficient? In *Proceedings of LICS 2019*, pages 1–13, 2019. doi:10.1109/LICS.2019.8785823.
- [8] Pablo Barceló, Diego Figueira, Georg Gottlob, and Andreas Pieris. Semantic optimization of conjunctive queries. J. ACM, 67(6):34:1-34:60, 2020. doi:10.1145/3424908.
- [9] Pablo Barceló, Reinhard Pichler, and Sebastian Skritek. Efficient evaluation and approximation of well-designed pattern trees. In *Proceedings of PODS 2015*, pages 131–144. ACM, 2015. doi:10.1145/2745754.2745767.
- [10] Catriel Beeri, Ronald Fagin, David Maier, and Mihalis Yannakakis. On the desirability of acyclic database schemes. J. ACM, 30:479-513, 1983. doi:10.1145/2402.322389.
- [11] Christoph Berkholz, Fabian Gerhardt, and Nicole Schweikardt. Constant delay enumeration for conjunctive queries: a tutorial. ACM SIGLOG News, 7(1):4–33, 2020. doi:10.1145/3385634.3385636.
- [12] Christoph Berkholz and Nicole Schweikardt. Constant delay enumeration with fpt-preprocessing for conjunctive queries of bounded submodular width. In *Proceedings of MFCS 2019*, pages 58:1–58:15, 2019. doi:10.4230/LIPICS.MFCS.2019.58.
- [13] Meghyn Bienvenu and Magdalena Ortiz. Ontology-mediated query answering with data-tractable description logics. In *Proceedings of Reasoning Web*, pages 218–307, 2015. doi:10.1007/978-3-319-21768-0\\_9.
- [14] Meghyn Bienvenu, Magdalena Ortiz, Mantas Simkus, and Guohui Xiao. Tractable queries for lightweight description logics. In Proceedings of IJCAI 2013, pages 768–774. IJCAI/AAAI, 2013. URL: http://www.aaai.org/ocs/index.php/IJCAI/IJCAII3/paper/view/6908.
- [15] Meghyn Bienvenu, Balder ten Cate, Carsten Lutz, and Frank Wolter. Ontologybased data access: A study through disjunctive datalog, CSP, and MMSNP. ACM Trans. Database Syst., 39(4):33:1–33:44, 2014. doi:10.1145/2661643.

- [16] Endre Boros, Benny Kimelfeld, Reinhard Pichler, and Nicole Schweikardt. Enumeration in data management (Dagstuhl seminar 19211). Dagstuhl Reports, 9(5):89–109, 2019. doi:10.4230/DagRep.9.5.89.
- [17] Johann Brault-Baron. De la pertinence de l'énumération : complexité en logiques propositionnelle et du premier ordre. (On the relevance of enumeration: complexity of propositional and first-order logic). PhD thesis, University of Caen Normandy, France, 2013. URL: https://tel.archives-ouvertes.fr/tel-01081392.
- [18] Andrea Cali, Georg Gottlob, and Michael Kifer. Taming the infinite chase: Query answering under expressive relational constraints. J. Artif. Intell. Res., 48:115– 174, 2013. doi:10.1613/jair.3873.
- [19] Andrea Cali, Georg Gottlob, and Thomas Lukasiewicz. A general datalog-based framework for tractable query answering over ontologies. J. Web Semant., 14:57– 83, 2012. doi:10.1016/j.websem.2012.03.001.
- [20] Andrea Cali, Georg Gottlob, and Andreas Pieris. Towards more expressive ontology languages: The query answering problem. *Artif. Intell.*, 193:87–128, 2012. doi:10.1016/j.artint.2012.08.002.
- [21] Nofar Carmeli and Markus Kröll. Enumeration complexity of conjunctive queries with functional dependencies. *Theory Comput. Syst.*, 64(5):828–860, 2020. doi:10.1007/s00224-019-09937-9.
- [22] Nofar Carmeli and Markus Kröll. On the enumeration complexity of unions of conjunctive queries. ACM Trans. Database Syst., 46(2):5:1-5:41, 2021. doi:10.1145/3450263.
- [23] Nofar Carmeli, Shai Zeevi, Christoph Berkholz, Benny Kimelfeld, and Nicole Schweikardt. Answering (unions of) conjunctive queries using random access and random-order enumeration. In *Proceedings of PODS 2020*, pages 393–409, 2020. doi:10.1145/3375395.3387662.
- [24] Stephen A. Cook and Robert A. Reckhow. Time bounded random access machines. J. Comput. Syst. Sci., 7(4):354-375, 1973. doi:10.1016/S0022-0000(73)80029-7.
- [25] Víctor Dalmau, Phokion G. Kolaitis, and Moshe Y. Vardi. Constraint satisfaction, bounded treewidth, and finite-variable logics. In Proceedings of Principles and Practice of Constraint Programming - CP 2002, pages 310-326, 2002. doi:10.1007/3-540-46135-3\\_21.
- [26] Shaleen Deep, Xiao Hu, and Paraschos Koutris. Enumeration algorithms for conjunctive queries with projection. In *Proceedings of ICDT 2021*, pages 14:1– 14:17, 2021. doi:10.4230/LIPIcs.ICDT.2021.14.
- [27] Shaleen Deep and Paraschos Koutris. Ranked enumeration of conjunctive query results. In *Proceedings of ICDT 2021*, pages 5:1-5:19, 2021. doi:10.4230/LIPICS.ICDT.2021.5.
- [28] William F. Dowling and Jean H. Gallier. Linear-time algorithms for testing the satisfiability of propositional horn formulae. *The Journal of Logic Programming*, 1(3):267–284, 1984. doi:10.1016/0743-1066(84)90014-1.
- [29] Ronald Fagin, Phokion G. Kolaitis, Renée J. Miller, and Lucian Popa. Data exchange: semantics and query answering. J. Theor. Comput. Sci., 336(1):89–124, 2005. doi:10.1016/j.tcs.2004.10.033.
- [30] Etienne Grandjean. Sorting, linear time and the satisfiability problem. Annals of Mathematics and Artificial Intelligence, 16:183-236, 1996. doi:10.1007/BF02127798.
- [31] David S. Johnson and Anthony C. Klug. Testing containment of conjunctive queries under functional and inclusion dependencies. J. Comput. Syst. Sci., 28(1):167-189, 1984. doi:10.1016/0022-0000(84)90081-3.
- [32] Wojciech Kazana. Query evaluation with constant delay. (L'évaluation de requêtes avec un délai constant). PhD thesis, École normale supérieure de Cachan, Paris, France, 2013. URL: https://tel.archives-ouvertes.fr/tel-00919786.
- [33] Markus Kröll, Reinhard Pichler, and Sebastian Skritek. On the complexity of enumerating the answers to well-designed pattern trees. In *Proceedings of ICDT* 2016, pages 22:1–22:18, 2016. doi:10.4230/LIPIcs.ICDT.2016.22.
- [34] Andrea Lincoln, Virginia Vassilevska Williams, and R. Ryan Williams. Tight hardness for shortest cycles and paths in sparse graphs. In SODA 2018, pages 1236–1252. SIAM, 2018. doi:10.1137/1.9781611975031.80.
- [35] Carsten Lutz and Frank Wolter. Deciding inseparability and conservative extensions in the description logic & L. Journal of Symbolic Computation, 45(2):194– 228, 2010.
- [36] David Maier, Alberto O. Mendelzon, and Yehoshua Sagiv. Testing implications of data dependencies. ACM Trans. Database Syst., pages 455–469, 1979. doi:10.1145/320107.320115.
- [37] Luc Segoufin. Constant delay enumeration for conjunctive queries. SIGMOD Rec., 44(1):10–17, 2015. doi:10.1145/2783888.2783894.
- [38] Mihalis Yannakakis. Algorithms for acyclic database schemes. In Proceedings of the Seventh International Conference on Very Large Data Bases - Volume 7, pages 82–94, 1981.

Efficiently Enumerating Answers to Ontology-Mediated Queries

### **A ADDITIONAL PRELIMINARIES**

#### A.1 The RAM model

As our computational model, we assume RAMs under the uniform cost model [24], following [30] in the concrete formalization. Such a RAM has a one-way read-only input tape and a write-only output tape, as well as an unbounded number of registers that store nonnegative integers of  $O(\log n)$  bits, *n* the input size; this is called a DRAM in [30], used there to define the complexity class DLIN-EAR. Adding, subtracting, and comparing the values of two registers as well as bit shift takes time O(1). This model is a standard assumption in the context of enumerating the answers to queries [4, 11, 21, 37], although sometimes smaller registers are assumed that can only hold integers up to  $O(n/\log(n))$ . An input database D is given as a word on the input tape. Since we are interested in data complexity, there are only O(1) many relation symbols whose arity is O(1). We assume that constants in adom(D) are represented in binary, which requires at most  $\log(k)$  bits,  $k = |\mathsf{adom}(D)|$ . We can thus store a constant in a single register, and the same is true for facts in D.

We shall often be interested in lists of constants from adom(D) that are of length O(1), let us call this a *short list*. With every short list, we can associate a unique memory address (register) that can be computed from the short list in O(1) time using bit shifting and addition. This means that we can implement lookup tables indexed by such lists that can be accessed and updated in O(1) time.

Another crucial property of this model is that sorting is possible in linear time [30]. In fact, we shall be interested in sets of short lists equipped with a strict weak order. We summarize the approach from [30]. To sort a list  $L = l_1; l_2; \ldots; l_m$  of *m* short lists one first observes the following:

- we can sort a list of short words, by which we mean words of length  $O(\log ||L||)$ , in time O(||L||) using *counting sort*; indeed, there is no more than O(||L||) words of such length;
- we can use standard sorting algorithms to sort a list of long words, i.e. words of length  $\Omega(\log ||L||)$ , using  $O(n \log n)$  operations, where  $n \in O(\frac{||L||}{\log ||L||})$  is the number of elements of length  $\Omega(\log ||L||)$ .

To sort a list, it is thus enough to divide it into two disjoint lists: a list of short words and a list of long words. Then we sort those lists independently and join them into a single sorted list. Since the division and the join can be easily done in linear time, sorting can be performed in time  $O(||L||) + O(n \log n)$ . Since  $n \in O(\frac{||L||}{\log ||L||})$ , this gives the overall running time O(||L||). We also recall that sorting on a RAM in linear time is possible even under the less liberal *logarithmic cost measure* and when registers can only hold integers up to  $O(n/\log(n))$  [30].

#### A.2 More on the Chase

We provide some observations regarding chase procedure. The following is the central property of the chase.

LEMMA A.1. Let O be a finite set of TGDs and I an instance. Then for every model J of O with  $I \subseteq J$ , there is a homomorphism h from  $ch_O(I)$  to J that is the identity on adom(I). We next establish a technical lemma about the chase that may be viewed as a locality property. Let *I* be an instance and *O* a set of TGDs. With every guarded set *S* of *I*, we associate a subinstance  $ch_O(I)|_S^{\downarrow} \subseteq ch_O(I)$  such that every fact in  $ch_O(I)$  that contains at least one null is contained in exactly one such subinstance. We first identify with every fact  $R(\bar{c}) \in ch_O(I)$  that contains at least one null a unique 'source' fact source( $R(\bar{c})$ )  $\in I$ . Assume that  $R(\bar{c})$  was introduced by a chase step that applies a TGD *T* at a tuple ( $\bar{d}, \bar{d}'$ ), and let *R'* be the relation symbol in the guard atom in body(*T*). Then we set source( $R(\bar{c})$ ) =  $R'(\bar{d}, \bar{d}')$  if  $\bar{d} \cup \bar{d}' \subseteq adom(I)$  and source( $R(\bar{c})$ ) = source( $R'(\bar{d}, \bar{d}')$ ) otherwise. For any guarded set *S* of *I*, we now define  $ch_O(I)|_S^{\downarrow}$  to contain those facts  $R(\bar{c}) \in ch_O(I)$ such that

- (1)  $\bar{c} \subseteq S$  or
- (2)  $\bar{c}$  contains at least one null and source( $R(\bar{c})$ ) = *S*.

We shall actually consider such subinterpretations not only of the final result  $ch_O(I)$  of the chase, but also of the instances constructed as part of a chase sequence  $I_0, I_1, \ldots$  for I with O. In fact, we can define  $I_i|_S^{\downarrow}$  in exact analogy with  $ch_O(I)|_S^{\downarrow}$ , for all  $i \ge 0$ . We next observe that all facts in a subinstance  $I_i|_S^{\downarrow}$  of  $I_i$  can be obtained by starting from the (very small) subinstance  $I_i|_S$  and then chasing with O.

LEMMA A.2. Let I be an instance, O a set of guarded TGDs,  $I_0, I_1, \ldots$ a chase sequence of I with O,  $i \ge 0$ , and S a guarded set in I. Then there is a homomorphism from  $I_i|_S^{\downarrow}$  to  $ch_O(I_i|_S)$  that is the identity on all constants in S.

PROOF. The proof is by induction on *i*. The induction start holds as  $I_0|_S^{\downarrow} = I_0|_S \subseteq ch_O(I|_S)$ . For the induction step, assume that  $I_{i+1}$  was obtained from  $I_i$  by applying a TGD  $T = \phi(\bar{x}, \bar{y}) \rightarrow \exists \bar{z} \psi(\bar{x}, \bar{z})$  at a tuple  $(\bar{c}, \bar{c}')$ . Let R be the relation symbol used in the guard atom of  $\phi$ . Then  $R(\bar{c}, \bar{c}') \in I_i$ . Let S be a guarded set in I. If  $I_{i+1}|_S^{\downarrow} = I_i|_S^{\downarrow}$ , it suffices to use the induction hypothesis. Thus assume  $I_{i+1}|_S^{\downarrow} \neq I_i|_S^{\downarrow}$ .

First assume that  $S \neq \overline{c} \cup \overline{c'}$ . Then all facts in  $I_{i+1}|_{S}^{\downarrow} \setminus I_{i}|_{S}^{\downarrow}$  contain only constants in  $\overline{c}$ , but no nulls. By induction hypothesis, there is a homomorphism  $h_{i}$  from  $I_{i}|_{S}^{\downarrow}$  to  $ch_{O}(I_{i}|_{S})$  that is the identity on all constants in S. Clearly,  $h_{i}$  is also a homomorphism from  $I_{i+1}|_{S}^{\downarrow}$ to  $ch_{O}(I_{i+1}|_{S})$ .

Now assume that  $S = \overline{c} \cup \overline{c'}$ . Then  $I_{i+1}|_{S}^{\downarrow} \neq I_{i}|_{S}^{\downarrow} = \psi(\overline{c}, \overline{c''})$  where  $\overline{c''}$  consists of constants that do not occur in  $I_{i}$ . By induction hypothesis, there is a homomorphism  $h_{i}$  from  $I_{i}|_{S}^{\downarrow}$  to  $ch_{O}(I_{i}|_{S})$  that is the identity on all constants in *S*. Applicability of *T* at  $(\overline{c}, \overline{c'})$  implies  $\phi(\overline{c}, \overline{c'}) \subseteq I_{i}$  and thus  $\phi(h_{i}(\overline{c}), h_{i}(\overline{c'})) \subseteq ch_{O}(I_{i}|_{S})$ . It follows *T* has been applied at  $(h(\overline{c}), h(\overline{c'}))$  in (any fair chase sequence that produces)  $ch_{O}(I_{i}|_{S})$ . As a consequence, there are constants  $\overline{d}$  such that  $\psi(h(\overline{c}), \overline{d}) \subseteq ch_{O}(I_{i}|_{S})$ . We extend  $h_{i}$  to  $h_{i+1}$  so that  $h_{i+1}(\overline{c''}) = \overline{d}$ . Clearly,  $h_{i+1}$  is a homomorphism from  $I_{i+1}|_{S}^{\downarrow}$  to  $ch_{O}(I_{i+1}|_{S})$ .  $\Box$ 

#### A.3 $\mathcal{ELI}$ and Simulations

We introduce some preliminaries that are specific to  $\mathcal{ELI}$ . Recall that, in  $\mathcal{ELI}$ , relation symbols can only have arity 1 or 2. A CQ q

Technical Report, arXiv version, 2022

over such a schema gives rise to an undirected graph

$$G_q^{\mathsf{var}} = (\mathsf{var}(q), \{\{x, y\} \mid R(x, y) \in q \text{ with } x, y \in \mathsf{var}(q) \text{ and } x \neq y\}).$$

Note that in contrast to variables, constants in q do not serve as nodes in  $G_q^{\text{var}}$ . It is easy to see that q is acyclic if  $G_q^{\text{var}}$  is a disjoint union of trees. Of course, this admits reflexive loops and multiedges in q.

We now introduce the notion of a simulation, which is closely linked to the expressive power of  $\mathcal{ELI}$ . Let S be a schema that only contains relations of arity one and two, and let I and J be Sinstances. A simulation from I to J is a relation  $S \subseteq \operatorname{adom}(I) \times$ adom(I) such that

- (1)  $A(c) \in I$  and  $(c, c') \in S$  implies  $A(c') \in J$ ,
- (2)  $R(c_1, c_2) \in I$  and  $(c_1, c_1') \in S$  implies that there is a  $c_2' \in$
- adom(J) such that  $R(c'_1, c'_2) \in J$  and  $(c_2, c'_2) \in S$ , and (3)  $R(c_2, c_1) \in I$  and  $(c_1, c'_1) \in S$  implies that there is a  $c'_2 \in I$ adom(J) such that  $R(c'_2, c'_1) \in J$  and  $(c_2, c'_2) \in S$ .

If there is a simulation for *I* to *J* such that  $(c, c') \in S$ , then we write  $(I,c) \leq (J,c').$ 

A unary CQ q(x) is an *ELIQ* (which stands for *ELI* query) if it contains no constants and the undirected graph  $G_q^{\sf var}$  is a disjoint unions of trees and q contains no self-loops and multi-edges, where the latter means that for any  $x, y \in var(q)$ , q contains at most a single atom that mentions both *x* and y.<sup>1</sup> We use  $\mathbb{ELIQ}$  to denote the class of all ELIQs.

LEMMA A.3. Let  $Q(x) = (O, S, q) \in (\mathbb{ELI}, \mathbb{ELIQ}), D_1, D_2$  S-databases, and  $c_i \in \operatorname{adom}(D_i)$  for  $i \in \{1, 2\}$ . Then  $(D_1, c_1) \leq (D_2, c_2)$ and  $c_1 \in Q(D_1)$  implies  $c_2 \in Q(D_2)$ .

We start with recalling the following well-known fact, proved e.g. as Theorem 10 in [35].

LEMMA A.4. Let q(x) be an ELIQ,  $D_1$ ,  $D_2$  S-databases, and  $c_i \in$  $adom(D_i)$  for  $i \in \{1, 2\}$ . If  $(D_1, c_1) \leq (D_2, c_2)$  and  $c_1 \in q(D_1)$  then  $c_2 \in q(D_2).$ 

PROOF OF LEMMA A.3. Let  $D \supseteq D_2$  be a model of O. We have to show that  $c_2 \in q(D)$ . The following claim shall be essential.

*Claim.*  $(ch_{O}(D_{1}), c_{1}) \leq (ch_{O}(D_{2}), c_{2}).$ 

The chase constructs a sequence  $D_1 = I_0 \subseteq I_1 \subseteq \cdots$  such that  $ch_O(D_1) = \bigcup_{i>1} I_i$ . We construct a sequence of relations  $S = S_0 \subseteq$  $S_1 \subseteq \cdots \subseteq S_k$  such that

(†)  $S_i$  is a simulation from  $I_i$  to  $ch_O(D_2)$ .

Relation  $S_0$  is already defined. For the inductive step, let us assume that we have already defined  $S_i$ .

Assume that  $I_{i+1}$  was obtained from  $I_i$  by applying the TGD  $\varphi(x,\bar{y}) \to \psi(x,\bar{z}) \in O$  in  $I_i$  at  $(c,\bar{c}')$ . Since O is formulated in  $\mathcal{ELI}$ ,  $\varphi$  and  $\psi$  are ELIQ,  $c \in \varphi(I_i)$ , and  $I_{i+1}$  was obtained from  $I_i$ by adding a copy  $D'_{\psi}$  of  $D_{\psi}$  using the constant *c* in place of the answer variable of ELIQ  $\psi$  and the fresh constants from  $\bar{c}'$  in place of the quantified variables. Let us assume that for each quantified variable *z* in  $\psi$ , the corresponding constant in  $\overline{c}'$  is  $c_z$ .

Lutz and Przybyłko

To construct  $S_{i+1}$ , start with setting  $S_{i+1} = S_i$ . Then consider all  $(c, d) \in S_i$ . Since  $\varphi$  is an ELIQ,  $c \in \varphi(I_i)$  and Lemma A.4 yield  $d \in \varphi(\mathsf{ch}_Q(D_2))$ . It follows that the TGD  $\varphi(x, \bar{y}) \to \psi(x, \bar{z})$  is applicable in  $ch_{O}(D_{2})$  at d and was indeed applied during the construction of  $ch_{\mathcal{O}}(D_2)$ . Consequently,  $d \in \psi(ch_{\mathcal{O}}(D_2))$  and thus we find a homomorphism *h* from  $\psi(x)$  to  $ch_O(D_2)$  with h(x) = d. Extend  $S_{i+1}$  with  $(c_z, h(z))$  for each quantified variable z in  $\psi$ . It is easy to verify that  $S_{i+1}$  satisfies (†), as required. This finishes the proof of the claim.

Now back to the proof of Lemma A.3. Since  $c_1 \in Q(D_1)$ , there exists a homomorphism  $h_1$  from  $D_q(x)$  to  $ch_Q(D_1)$  such that h(x) = $c_1$ . Clearly, a homomorphism is also a simulation. Composing this simulation with a simulation S from  $ch_O(D_1)$  to  $ch_O(D_2)$  with  $(c_1, c_2) \in S$ , whose existence is guaranteed by the claim, we obtain a simulation S' from  $D_q$  to  $ch_O(D_2)$  with  $(x, c_2) \in S'$ . Since  $x \in q(D_q)$ , Lemma A.4 yields  $c_2 \in q(ch_O(D_2))$  and thus  $c_2 \in$  $Q(D_2)$ , as required. п

#### **PROOFS FOR SECTION 2** B

**PROPOSITION 2.1.** Let  $Q \in (\mathbb{TGD}, \mathbb{CQ})$ . If minimal partial answers to Q can be enumerated in  $DelayC_{lin}$  and the same is true for complete answers, then there is a DelayClin enumeration algorithm for minimal partial answers to Q that produces the complete answers first.

PROOF. Let  $A_{mpa}$  be the algorithm for enumerating minimal partial answers to Q in  $\mathsf{DelayC}_{\mathsf{lin}}$  and let  $A_{\mathsf{c}}$  be the algorithm for enumerating complete answers to Q in  $DelayC_{lin}$ . To obtain the desired enumeration algorithm that produces the complete answers first, we run  $A_c$  and  $A_{mpa}$  in parallel, starting with the preprocessing phase of both algorithms. In the enumeration phase, Ampa clearly outputs at least as many answers as Ac. We run the enumeration phase of both algorithms in parallel. As long as  $A_c$  still produces answers, we let both  $A_c$  and  $A_{mpa}$  produce their next answer, but output only the answer of  $A_c$ . The answer of  $A_{mpa}$  is diregarded if it is complete, and stored in a linked list otherwise. Once that  $A_{c}$  runs out of answers, we switch to only continueing the enumeration phase of  $A_{mpa}$ . If  $A_{mpa}$  produces an answer with a wildcard, we output it. If  $A_{mpa}$  produces a complete answer, we output one of the stored answers instead. Clearly, the number of complete answers to be replaced by a stored answer coincides exactly with the number of answers stored. 

LEMMA 2.3. Let  $Q(\bar{x}) = (O, S, q) \in (\mathbb{TGD}, \mathbb{CQ})$  and D be an S-database. Then  $Q(D)^* = q(\mathsf{ch}_O(D))^*_N$  and  $Q(D)^{\mathcal{W}} = q(\mathsf{ch}_O(D))^{\mathcal{W}}_N$ .

**PROOF.** We only consider  $Q(D)^*$  and  $q(ch_O(D))_N^*$ , the case of  $\cdot^{\mathcal{W}}$  is similar. First assume that  $\bar{c} \in Q(D)^*$ . Then for every model I of O with  $I \supseteq D$ , there is a  $\overline{c}' \in q(I)$  with  $\overline{c}' \leq \overline{c}$ . In particular, this is true for  $I = ch_{\mathcal{O}}(D)$ . We observe the following:

• If  $\bar{c}'$  has a constant from N in some position, then  $\bar{c}$  has '\*' in the same position.

This is because  $\bar{c}' \leq \bar{c}$  and  $\bar{c}$  may only contain elements from  $\operatorname{adom}(D) \cup \{*\}.$ 

• If  $\overline{c}'$  has a constant  $c \in adom(D)$  in some position, then  $\overline{c}$ has *c* in the same position.

<sup>&</sup>lt;sup>1</sup>In the literature, an ELIQ is often defined as a single tree, rather than a disjoint union thereof. We work with the more general definition as this turns our to be more convenient for our purposes.

From  $\overline{c}' \leq \overline{c}$ , it follows that  $\overline{c}$  has c or '\*' in the same position. Assume that there is at least one position i where  $\overline{c}'$  has a constant  $c \in \operatorname{adom}(D)$  and  $\overline{c}$  has '\*'. Let  $\overline{c}''$  be obtained from  $\overline{c}$  by replacing '\*' in position i with c. Then  $\overline{c}'' < \overline{c}$  and it follows from Lemma A.1 that  $\overline{c}''$  is a partial answer to Q on D, contradicting the fact that  $\overline{c}$  is a minimal partial answer to Q on D.

It follows that  $\bar{c} = (\bar{c}')_{\mathrm{N}}^* \in q(\mathsf{ch}_O(D))_{\mathrm{N}}^*$ .

Conversely, assume that  $\bar{c} \in q(ch_O(D))_N^*$ . By Lemma A.1, for every *I* of *O* with  $I \supseteq D$ , there is a  $\bar{c}' \in q(I)$  with  $\bar{c}' \leq \bar{c}$ . Thus,  $\bar{c}$ is a partial answer to *Q* on *D*. Assume to the contrary of what we want to show that it is not a minimal partial answer, that is, there is a  $\bar{c}' \in Q(D)^*$  with  $\bar{c}' < \bar{c}$ . Then there is a  $\bar{c}'' \in q(ch_O(D))$  with  $\bar{c}'' \leq \bar{c}'$ . We can show as above that  $\bar{c}' = (\bar{c}'')_N^* \in q(ch_O(D))_N^*$ . But now  $\bar{c}' < \bar{c}$  contradicts  $\bar{c} \in q(ch_O(D))_N^*$ .

# C PROOFS FOR SECTION 3

### C.1 Proof of Theorem 3.1

Our first aim is to prove Lemma 3.2. We start with observing the following.

LEMMA C.1. Let  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  and let D be an S-database. Further let  $q'(\bar{x}')$  be a CQ with  $|var(q')| \leq |var(q)|$  and  $\bar{c} \in \operatorname{adom}(D)^{|\bar{x}'|}$ . Then  $D \cup O \models q'(\bar{c})$  iff  $\bar{c} \in q'(\operatorname{ch}^q_O(D))$ .

PROOF. The 'if' direction is an immediate consequence of the definition of  $\operatorname{ch}_O^q(D)$ . For the 'only if' direction, assume that  $D \cup O \models q'(\bar{c})$ . Then there is a homomorphism h from q' to  $\operatorname{ch}_O(D)$  such that  $h(\bar{x}') = \bar{c}$ . For every guarded set S in D, let  $A_S$  denote the set of atoms  $R(\bar{t})$  in q' such that  $h(\bar{t})$  contains at least one null and source $(R(h(\bar{t}))) = S$  (as defined in Appendix A.2). Let  $\mathfrak{S}$  be the set of guarded sets S in D with  $A_S \neq \emptyset$ . For each  $S \in \mathfrak{S}$ , let  $q'_S(x'_S)$  denote the CQ obtained by first restricting q' to the atoms in  $A_S$  and then making a variable x an answer variable if  $h(x) \in \operatorname{adom}(D)$  and a quantified variable otherwise.

- To prove that  $D \cup O \models q'(\bar{c})$ , it suffices to show the following:
- (1)  $h(\bar{t}) \in q'(ch_O^q(D))$  for every atom  $R(\bar{t})$  in q' such that  $h(\bar{t})$  contains no null;
- (2)  $h(\bar{x}'_{S}) \in q'_{S}(\operatorname{ch}^{q}_{O}(D))$  for every  $S \in \mathfrak{S}$ .

In fact, composing homomorphism h with the homomorphisms into  $\operatorname{ch}_{O}^{q}(D)$  that witness (2), one can straightforwardly construct a homomorphism h' from q' to  $\operatorname{ch}_{O}^{q}(D)$  such that  $h'(q') = \bar{c}$ .

For Point (1), let  $R(\bar{t})$  be an atom in q' such that  $h(\bar{t})$  contains no null. Then  $D \cup O \models p(\bar{c}')$  for  $p = R(\bar{t})$  and  $\bar{c}' = h(\bar{t})$ , and  $\bar{c}'$  is a guarded set in D. Thus,  $R(h(\bar{t}))$  has been added to  $ch_O^q(D)$  during its construction.

For Point (2), let  $S \in \mathfrak{S}$ . Then  $D \cup O \models p(\overline{c}')$  for  $p = q'_S(\overline{x}'_S)$ and  $\overline{c}' = h(\overline{x}'_S)$ , and  $\overline{c}'$  is a guarded set in D. Thus, a copy of  $D_{q'_S}$ that uses the constants in  $\overline{c}'$  in place of the answer variable  $\overline{x}'_S$  of  $q'_S$  has been added to  $ch^q_O(D)$  during its construction.  $\Box$ 

LEMMA 3.2. Let  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  and D be an S-database. Then  $Q(D) = q(\operatorname{ch}^q_O(D)) \cap \operatorname{adom}(D)^{|\bar{x}|}, Q(D)^* = q(\operatorname{ch}^q_O(D))^*_N$ , and  $Q(D)^W = q(\operatorname{ch}^q_O(D))^W_N$ .

PROOF. Let  $Q(\bar{x}) = (O, S, q)$ , D and N be as in Lemma 3.2. It is an immediate consequence of Lemma C.1, instantiated with q' = q, that  $Q(D) = q(ch_O^q(D)) \cap adom(D)^{|\bar{x}|}$ . The cases  $Q(D)_N^* = q(ch_O^q(D))^*$  and  $Q(D)_N^W = q(ch_O^q(D))^W$  are very similar, we concentrate on the latter. It clearly suffices to prove that a tuple  $\bar{a}^W$  is a (not necessarily minimal) partial answer with multi-wildcards to q on  $ch_O^q(D)$  if and only if  $\bar{a}^W$  is a partial answer with multi-wildcards to Q on D.

Let  $\bar{x} = x_1, ..., x_n$ , let  $\bar{a}^W = a_1, ..., a_n$ , and let the wildcards from W that occur in  $\bar{a}^W$  be  $*_1, ..., *_{\ell}$ . Consider the CQ q' obtained from q in the following way:

- introduce fresh quantified variable  $z_1, \ldots, z_\ell$ ;
- if  $a_i = *_j$ , then replace in q' the answer variable  $x_i$  with quantified variable  $z_j$ .

Further let  $\bar{c}$  be obtained from  $\bar{a}^{\mathcal{W}}$  by removing all wildcards. It is easy to see that  $\bar{c} \in q'(ch_{\mathcal{O}}^{q}(D))$  iff  $\bar{a}^{\mathcal{W}}$  is a partial answer with multi-wildcards to q on  $ch_{\mathcal{O}}^{q}(D)$  and that  $D \cup \mathcal{O} \models q'(c)$  iff  $\bar{a}^{\mathcal{W}}$  is a partial answer with multi-wildcards to Q on D, both by definition of partial answers with multi-wildcards and by construction of q'. It thus remains to invoke Lemma C.1.

We next establish Proposition 3.3.

PROPOSITION 3.3. Let  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  and let D be an S-database. Then  $ch_O^q(D)$  can be computed in time linear in ||D||, more precisely in time  $2^{2^{O(||Q||^2)}} \cdot ||D||$ .

To prove Proposition 3.3, we make use of the fact that minimal models for propositional Horn formulas can be computed in linear time [28]. More precisely, we derive a satisfiable propositional Horn formula  $\theta$  from D and Q, compute a minimal model of  $\varphi$  in linear time, and then read off ch $_{O}^{q}(D)$  from that model.

Let  $\operatorname{sch}(O)$  denote the set of all relation symbols that occur in O. We introduce a propositional variable  $x_{p(\bar{c})}$  for every CQ  $p(\bar{y}) \in \operatorname{cl}(Q)$  and every  $\bar{c} \in \operatorname{adom}(D)^{|\bar{y}|}$  such that the constants in  $\bar{c}$  constitute a guarded set in D. Observe that the cardinality of  $\operatorname{cl}(Q)$  is bounded by  $2^{2^{O(||Q||^2)}}$ . Moreover, since Q is fixed and S only contains relation symbols that occur in O or on q, the arity of relation symbols in D is bounded by the constant ||Q||. Consequently, the number of guarded sets in D is bounded by  $2^{||Q||} \cdot ||D||$ and the number of variables  $x_{p(\bar{c})}$  is bounded by  $2^{2^{O(||Q||^2)}} \cdot ||D||$ .

Consider the Horn formula  $\theta$  that consists of the following conjuncts:

- (1)  $x_{R(\bar{c})}$  for every  $R(\bar{c}) \in D$ ;
- (2)  $\bigwedge_{S(\bar{d})\in D'} x_{S(\bar{d})} \to x_{p(\bar{c})}$  for every sch(*O*)-database *D'*, every CQ  $p(\bar{y}) \in cl(Q)$ , and every  $\bar{c} \in adom(D')^{|\bar{y}|}$  such that  $D' \cup O \models p(\bar{c})$  and adom(D') is a guarded set *S* in *D*.

The size of  $\theta$  is bounded by  $2^{2^{O(||Q||^2)}} \cdot ||D||$  and  $\theta$  can be constructed in time  $2^{2^{O(||Q||^2)}} \cdot ||D||$ . This again depends on the arity of relation symbols being (implicitly) bounded by a constant.

Since  $\theta$  contains no negative literals, it is clearly satisfiable and thus has a unique minimal model. Let *V* be the truth assignment that represents this minimal model. We construct a database  $D_{\theta}$ 

as follows. Start with *D*. Then iterate over all propositional variables  $x_{p(\bar{c})}$ . If  $V(x_{p(\bar{c})}) = 1$ , then take a copy  $D'_p$  of  $D_p$  that uses the constants in  $\bar{c}$  in place of the answer variables  $\bar{y}$  of p and only fresh constants otherwise, and take the union of the database constructed so far and  $D'_p$ . It is clear that the construction of  $D_\theta$  is in time  $2^{2^{O(||Q||^2)}} \cdot ||D||$ . Thus, the following implies Proposition C.1.

LEMMA C.2.  $D_{\theta} = \mathsf{ch}_{O}^{q}(D).$ 

PROOF. First assume that for some CQ  $p(\bar{y}) \in cl(Q)$  and tuple  $\bar{c} \in adom(D)^{|q|}$  such that the constants in  $\bar{c}$  constitute a guarded set in D, a copy  $D'_p$  of  $D_p$  has been added to  $D_\theta$  during the construction of this database. Then  $V(x_{p(\bar{c})}) = 1$ . We argue that this implies  $D \cup O \models p(\bar{c})$ . By construction of  $ch_O^q(D)$ , this means that  $D'_p$  has also been added during the construction of this database.

<sup>*r*</sup>Recall that the minimal model of a satisfiable propositional Horn formula can be computed (though not in linear time) through a straightforward algorithm that generates a least fixed point. Applied to  $\theta$ , the algorithm starts with the set of variables  $V_0$  from Point 1 of the definition of  $\theta$  and then exhaustively applies the rules from Point 2, which yields a sequence of variable sets  $V_0 \subseteq V_1 \subseteq$  $\cdots \subseteq V_k$  whose limit  $V_k$  is the minimal model V of  $\theta$ . It suffices to prove that  $x_{p'(\bar{c}')} \in V_i$ , with  $0 \le i \le k$ , implies  $D \cup O \models p'(\bar{c}')$ . This is straightforward be induction on i, using the definition of the Horn formula  $\theta$ .

Conversely, assume that for some CQ  $p(\bar{y}) \in cl(Q)$  and tuple  $\bar{c} \in adom(D)^{|q|}$  such that the constants in  $\bar{c}$  constitute a guarded set in D, a copy  $D'_p$  of  $D_p$  has been added to  $ch^q_O(D)$  during its construction. Then  $D \cup O \models p(\bar{c})$ .

Let  $D_0, D_1, \ldots$  be a chase sequence of D with O and let V be the minimal model of  $\theta$ . We first show that for all  $i \ge 0$ ,

(\*) if  $R(\bar{c}) \in D_i$  and  $\bar{c} \in \operatorname{adom}(D)^{\operatorname{ar}(R)}$ , then  $x_{R(\bar{c})} \in V$ .

The proof is by induction on *i* and the induction start holds since  $D_0 = D$  and by Point 1 of the definition of  $\theta$ .

For the induction step, let  $R(\bar{c}) \in D_i \setminus D_{i-1}$  with  $\bar{c} \in adom(D)^{ar(R)}$ and i > 0. Then  $R(\bar{c})$  was added by the chase step that produced  $D_i$ from  $D_{i-1}$ , by applying a TGD  $T = \phi(\bar{x}, \bar{y}) \rightarrow \exists \bar{z} \psi(\bar{x}, \bar{z})$  at a tuple  $(\bar{d}, \bar{d}')$ . Since the chase step has added  $R(\bar{c})$  and  $\bar{c} \in \mathsf{adom}(D)^{\mathsf{ar}(R)}$ , every constant that occurs in  $\bar{c}$  must also occur in  $\bar{d}$ . Consider the fact  $R'(\bar{d}, \bar{d}') \in \phi(\bar{d}, \bar{d}')$  that corresponds to the guard atom and let  $S = \overline{d} \cup \overline{d'}$  if all constants in  $\overline{d} \cup \overline{d'}$  are from adom(D) and  $S = \text{source}(R'(\bar{d}, \bar{d}'))$  otherwise. Then *S* is a guarded set in *D* that contains all constants from  $\bar{c}$ , and  $\phi(\bar{d}, \bar{d}') \subseteq D_i|_S^{\downarrow}$ . By Lemma A.2, there is a homomorphism h from  $D_i|_S^{\downarrow}$  to  $ch_O(D_i|_S)$  that is the identity on all constants in S. Thus  $\phi(h(\bar{d}), h(\bar{d}')) \subseteq ch_O(D_i|_S)$ and thus T was applied at (h(d), h(d')) during the construction of  $ch_{\mathcal{O}}(D_i|_S)$ , yielding  $R(\bar{c}) \in ch_{\mathcal{O}}(D_i|_S)$ . Consequently  $D_{I_i}|_S \cup \mathcal{O} \models$  $R(\bar{c})$ . Thus Point (2) from the definition of  $\theta$  includes the implication  $\bigwedge_{R'(\bar{e}) \in D_i|_S} x_{R'(\bar{e})} \to x_{R(\bar{e})}$ . From the induction hypothesis, we know that  $x_{R'(\bar{e})} \in V$  for all  $R'(\bar{e}) \in D_i|_S$ , and thus  $x_{R(\bar{e})} \in V$ as desired. This finishes the proof of (\*).

We now show that  $D'_p$  has also been added to  $D_\theta$  during the construction of this database. Since  $D \cup O \models p(\bar{c})$ , there is a homomorphism h from p to  $ch_O(D)|_S^{\downarrow}$  with  $h(\bar{y}) = \bar{c}$ . It follows that there is an  $i \ge 0$  such that h is also a homomorphism from p to

 $D_i|_{S}^{\downarrow}$ . Lemma A.2 implies that  $D_i|_{S} \cup O \models p(\bar{c})$ . Thus Point (2) from the definition of  $\theta$  includes the implication  $\bigwedge_{R'(\bar{e}) \in D_i|_{S}} x_{R'(\bar{e})} \rightarrow x_{p(\bar{c})}$ . By (\*),  $x_{R'(\bar{e})} \in V$  for all  $R'(\bar{e}) \in D_i|_{S}$  and thus  $x_{p(\bar{c})} \in V$ . By construction of  $D_{\theta}$ , it follows that  $D'_p$  has been added to this database.

For later use, we make explicit the structure of  $ch_O^q(D)$ . In fact,  $ch_O^q(D)$  can be obtained from D by grafting a database onto every guarded set in D, but the grafted databases are not connected other than through the guarded sets onto which they are grafted. Note that the size of a guarded set is bounded by a constant when we assume the OMQ to be fixed. To make this formal, we say that a database E is *chase-like* if there are databases  $D_1, \ldots, D_n$  such that

- $E = D_1 \cup \cdots \cup D_n$ ,
- *D<sub>i</sub>* contains exactly one fact that uses no nulls, and that fact contains all constants in adom(*D<sub>i</sub>*) \ N,
- $\operatorname{adom}(D_i) \cap \operatorname{adom}(D_j) \cap \mathbb{N} = \emptyset$  for  $1 \le i < j \le n$ .

We call  $D_1, \ldots, D_n$  a *witness* for *E* being chase-like.

LEMMA C.3.  $ch_{O}^{q}(D)$  is chase-like and there is a witness  $D_{1}, \ldots, D_{n}$  such that  $|adom(D_{i})|$  does not depend on D for  $1 \le i \le n$ .

We are now ready to prove Theorem 3.1.

THEOREM 3.1. Single-testing is in linear time for

- weakly acyclic OMQs from (G, CQ) in the case of complete answers;
- (2) acyclic OMQs from (G, CQ) in the case of minimal partial answers with single wildcards;
- (3) acyclic OMQs from (ELI, CQ) in the case of minimal partial answers with multi-wildcards.

Assume that we are given a weakly acyclic  $OMQQ(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$ , an S-database D, and a  $\bar{c} \in adom(D)^{|\bar{x}|}$ , and we have to decide whether  $\bar{c} \in Q(D)$  (complete answers case). We first compute  $ch_O^q(D)$  in time linear in ||D||. Introduce a fresh unary relation symbol  $P_{db}$ . We next extend  $ch_O^q(D)$  to a database D' by adding the fact  $P_{db}(c)$  for every  $c \in adom(D)$  and obtain the CQ  $q'(\bar{x})$  from q by adding the atom  $P_{db}(x)$  for every answer variable x. Note that since q is weakly acyclic, so is q'. It follows from Lemma C.1 that Q(D) = q'(D') and thus it suffices to check whether  $\bar{c} \in q'(D')$ . Construct the Boolean CQ q'' which is obtained from q' by replacing the answer variables with the constants from  $\bar{c}$ . Clearly, q'' is acyclic and we have to check whether  $() \in q''(D')$ . This can be done in linear time using existing procedures such as Yannakakis' algorithm [38].

Now for the case of minimal partial answers with a single wildcard. We start with observing that it suffices to show that, given an acyclic OMQ  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$ , an S-database *D*, and a  $\bar{c}^* \in (\operatorname{adom}(D) \cup \{*\})^{|\bar{x}|}$ , it can be decided in linear time whether  $\bar{c}^*$  is a (not necessarily minimal) partial answer to *Q* on *D*.

Assume that we have a linear time algorithm for this task. Given an acyclic OMQ  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$ , an S-database D, and a  $\bar{c}^* \in (\operatorname{adom}(D) \cup \{*\})^{|\bar{x}|}$ , we can then decide in linear time whether  $\bar{c}^* \in Q(D)^*$  in the following way. First, we check whether  $\bar{c}^*$  is a partial answer to Q on D and return 'no' if this is not the case. Next, let V be the set of all answer variables z in q such that the positions in  $\bar{c}^*$  that correspond to z are filled with '\*'. Introduce a fresh unary relation symbol  $P_{db}(c)$  and let D' be obtained from Dby adding the fact  $P_{db}(c)$  for every  $c \in adom(D)$ . For every  $z \in V$ , let  $Q_z(\bar{x}') = (O, S, q_z)$  where  $q_z$  is obtained from q by adding the atom  $P_{db}(z)$ . We then test whether  $\bar{c}^*$  is a partial answer to  $Q_z$ on D' and return 'no' if the check succeeds for any  $z \in V$  and 'yes' otherwise. To see that this is correct note that if  $\bar{c}^*$  is a partial answer to  $Q_z$  on D', then we also find a partial answer to Q on Din which all positions in  $\bar{c}^*$  that correspond to z are replaced with a constant from adom(D), thus  $\bar{c}^*$  is not a minimal partial answer.

We now show that the linear time algorithm for single-testing (not necessarily minimal) partial answers indeed exists. Assume that we are given an acyclic OMQ  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$ , an S-database D, and a  $\bar{c}^* \in (\operatorname{adom}(D) \cup \{*\})^{|\bar{x}|}$ , and we want to decide whether  $\bar{c}^*$  is a partial answer to Q on D. This can be done as follows. We first check whether  $\bar{c}^*$  is coherent with  $\bar{x}$  in the sense that  $x_i = x_j$  implies  $c_i = c_j$ , and return 'no' if this is not the case. Let  $Q'(\bar{x}') = (O, S, q')$  where  $q'(\bar{x}')$  is obtained from  $q(\bar{x})$  by quantifying all answer variables z such that  $x_i = z$  implies  $c_i = *$ , and let  $\bar{c}$  be obtained from  $\bar{c}^*$  by dropping all  $c_i$  with  $c_i = *$ . Note that q' is ayclic since q is acyclic (whereas q' would not be guaranteed to be weakly acyclic if q was only weakly acyclic). It then remains to check whether  $\bar{c} \in Q'(D)$ , using the algorithm for complete answers from above, which is the case if and only if  $\bar{c}^*$  is a partial answer to Q on D.

We next consider the case of minimal partial answers with multiwildcards. We first make the following observation.

Claim. Let  $Q(\bar{x}) = (O, S, q) \in (\mathbb{ELI}, \mathbb{CQ})$  be acyclic, D be an Sdatabase, and  $\bar{c}^{\mathcal{W}} \in Q(D)^{\mathcal{W}}$ . Further let  $\hat{q}$  be obtained from q by identifying any two answer variables  $x_1, x_2$  such that the corresponding positions in  $\bar{c}$  are filled with the same wildcard. Then  $\hat{q}$ is weakly acyclic.

To prove the claim, assume that  $Q, D, \bar{c}$ , and  $\hat{q}$  are as in the claim. Let  $\bar{x} = x_1 \cdots x_n$  and  $\bar{c}^{\mathcal{W}} = c_1 \cdots c_n$ . For every answer variable  $x_i$ , we use  $c(x_i)$  to denote  $c_i$ . Since  $\bar{c}^{\mathcal{W}}$  is a partial answer to Q on D, there is a homomorphism h from q to  $ch_O(D)$  such that for all answer variables  $x, x', c(x) \in \mathsf{adom}(D)$  implies h(x) = c(x), and  $c(x) = c(x') \in \mathcal{W}$  implies h(x) = h(x'). We prove that for all answer variables x, x' with  $c(x), c(x') \in \mathcal{W}$ ,

- (1)  $h(x) \notin adom(D)$  and
- (2)  $h(x_1) = h(x_2)$  iff  $c(x_1) = c(x_2)$ .

For Point 1, assume to the contrary that there is an answer variable x with  $h(x) \in adom(D)$ . Let  $\bar{c}'^W$  be obtained from  $\bar{c}^W$  by replacing  $c_i$  with h(x) whenever  $x_i = x$ . The homomorphism h witnesses that  $\bar{c}'^W$  is a partial answer to Q on D, but  $\bar{c}'^W < \bar{c}^W$  in contradiction to  $\bar{c}^W$  being a minimal partial answer. The 'if' direction of Point 2 is clear by choice of h. For the 'only if' direction, assume to the contrary that there are answer variables x, x' with  $c(x), c(x') \in W, c(x) \neq c(x')$ , and h(x) = h(x'). Let  $\bar{c}'^W$  be obtained from  $\bar{c}^W$  by choosing a fresh wildcard  $*_\ell$ , replacing  $c_i$  with  $*_\ell$  whenever  $c(x_i) \in \{c(x), c(x')\}$ , and then renaming wildcards to make them consecutive again. That is, the variables x, x' have distinct wildcards in  $\bar{c}^W$ , but the same wildcard in  $\bar{c}'^W$ . The homomorphism h witnesses that  $\bar{c}'^W$  is a partial answer to Q on D,

but  $\bar{c}'^{\mathcal{W}} \prec \bar{c}^{\mathcal{W}}$  in contradiction to  $\bar{c}^{\mathcal{W}}$  being a minimal partial answer.

To see that  $\widehat{q}$  is acyclic, first consider the restriction  $\widehat{q}_0$  of  $\widehat{q}$  to the answer variables x with  $c(x) \in \mathcal{W}$ . By construction of  $\widehat{q}_0$  and Point (2), h is a homomorphism from  $\widehat{q}_0$  to  $ch_O(D)$ . By Point (2) and since no wildcard occurs twice in  $\widehat{q}_0$  (which is due to the construction of  $\widehat{q}$ ), h as a homomorphism from  $\widehat{q}_0$  to  $ch_O(D)$  is injective. By Point (1) above, there is no variable x in  $\widehat{q}_0$  with  $h(x) \in \operatorname{adom}(D)$ . Since O is formulated in  $\mathcal{ELI}$ , however, the restriction of  $ch_O(D)$  to  $\operatorname{adom}(ch_O(D)) \setminus \operatorname{adom}(D)$  is acyclic. The injectivity of h thus implies that  $\widehat{q}_0$  is acyclic. Now consider the restriction  $\widehat{q}_1$  of  $\widehat{q}$  to the variables in  $\widehat{q}_0$  plus the quantified variables. Acyclicity of  $\widehat{q}_0$  and of the original query q implies that  $\widehat{q}_1$  is acyclic. This, in turn, clearly implies that  $\widehat{q}$  is weakly acyclic. This finishes the proof of the claim.

Now assume that we are given an acyclic OMQ  $Q(\bar{x}) = (O, S, q) \in$  $(\mathbb{ELL}, \mathbb{CQ})$ , an S-database D, and a  $\overline{c}^{\mathcal{W}} \in (\operatorname{adom}(D) \cup \mathcal{W})^{|\overline{x}|}$ , and that we want to decide whether  $\overline{c}^{\mathcal{W}} \in Q(D)^{\mathcal{W}}$ . We first verify that  $\bar{x} = x_1 \cdots x_n$  is coherent with  $\bar{c}^{\mathcal{W}} = c_1 \cdots c_n$  in the sense that  $x_i = x_j$  implies  $c_i = c_j$ , returning 'no' if this is not the case. For every answer variable  $x_i$ , we again use  $c(x_i)$  to denote  $c_i$ . We then construct  $\hat{q}$  as in the claim and check whether it is weakly acyclic, returning 'no' if this is not the case. Let  $\bar{c}^*$  be constructed from  $\bar{c}^{\mathcal{W}}$ by mirroring the construction of  $\hat{q}$ , that is, whenever two answer variables  $x_i, x_j$  are identified in  $\hat{q}$ , then the corresponding positions (which carry the same wildcard) are identified in  $\bar{c}^*$ . Clearly, every wildcard  $*_i$  occurs only once in  $\overline{c}^*$ . Thus, we can assume that all these wildcards are '\*' and  $\bar{c}^*$  is, in fact, a single-wildcard tuple. We check whether  $\bar{c}^*$  is a partial answer to Q on D using the procedure for single-testing partial answers with a single wildcard for  $(\mathbb{G}, \mathbb{CQ})$  given above. It can be verified that this is the case if and only if  $\overline{c}^{W}$  is a partial answer to Q on D, and thus we return 'no' if the check fails.

It remains to check whether there is a partial answer  $\bar{a}^{\mathcal{W}}$  to Q on D with  $\bar{a}^{\mathcal{W}} < \bar{c}^{\mathcal{W}}$ .Introduce a fresh unary relation symbol  $P_{db}(c)$  and let Q be the set of all pairs  $(p, \bar{b}^{\mathcal{W}})$  with p a CQ and  $\bar{b}^{\mathcal{W}}$  a tuple that can be obtained from q and  $\bar{c}^{\mathcal{W}}$  in the following way:

- choose a set *V* of answer variables *x* such that the corresponding positions in  $\bar{c}^{W}$  have a wildcard; then obtain *p* from *q* by adding  $P_{db}(x)$  for all  $x \in V$  and set  $\bar{b}^{W} = \bar{c}^{W}$ ;
- choose a partition  $S_1, \ldots, S_k$  of the set of indices of wildcards that occur in  $\overline{c}^{\mathcal{W}}$ ; then set p = q and obtain  $\overline{b}^{\mathcal{W}}$  from  $\overline{c}^{\mathcal{W}}$  by replacing, for  $1 \le i \le k$ , every wildcard ' $*_{\ell}$ ' with  $\ell \in S_i$  by ' $*_{\overline{\ell}}$ ' where  $\widehat{\ell} \in S_i$  is a chosen representative; then rename wildcards to make them consecutive again.

This is subject to the condition that *V* is non-empty or the partition  $S_1, \ldots, S_k$  contains at least one non-singleton set. Let *D'* be obtained from *D* by adding the fact  $P_{db}(c)$  for every  $c \in adom(D)$ . We then do the following for all  $(p, \overline{b}^W) \in Q$ :

- (1) if  $\hat{p}$  is not weakly acyclic, then skip;
- (2) otherwise, proceed as in the case of q to check whether b<sup>W</sup> is a partial answer to (O, S, p) on D' (by transitioning to p and the corresponding single-wildcard tuple b<sup>\*</sup> obtained

from  $\bar{b}^{\mathcal{W}}$  and using the algorithm for single-testing with single wildcards).

If any of the checks succeeds, then there is a partial answer  $\bar{a}^{\mathcal{W}}$  to Q on D such that  $\bar{a}^{\mathcal{W}} < \bar{c}^{\mathcal{W}}$ , and thus we answer 'no'. If, for example,  $(p, \bar{b}^{\mathcal{W}}) \in Q$  due to the choices V and  $S_1, \ldots, S_k$  with V non-empty, then we may obtain  $\bar{a}^{\mathcal{W}}$  from  $\bar{c}^{\mathcal{W}}$  by replacing all wildcard tuples in  $\bar{c}^{\mathcal{W}}$  that correspond to variables in V with constants from adom(D). Conversely, assume that there is a partial answer  $\bar{a}^{\mathcal{W}}$  to Q on D such that  $\bar{a}^{\mathcal{W}} < \bar{c}^{\mathcal{W}}$ . Then we may assume that  $\bar{a}^{\mathcal{W}}$  is a *minimal* partial answer. It should be clear that  $\bar{a}^{\mathcal{W}}$  induces a pair  $(p, \bar{b}^{\mathcal{W}}) \in Q$  by 'reading off' V and  $S_1, \ldots, S_k$  from  $\bar{a}^{\mathcal{W}}$ . By the claim,  $(p, \bar{b}^{\mathcal{W}})$  is not skipped in Step 1 above and the check in Step 2 succeeds, so the algorithm returns 'no', as desired.

# C.2 Proof of Theorem 3.4

THEOREM 3.4. Let  $Q \in (\mathbb{ELI}, \mathbb{CQ})$  be non-empty and self-join free. If Q is not weakly acyclic, single-testing complete answers to Q is not in linear time unless the triangle conjecture fails. The same is true for minimal partial answers and minimal partial answers with multiple wildcards.

To prove Theorem 3.4, it suffices to consider complete answers to Boolean OMQs that are not acyclic, non-empty and self-join free. To see this, first assume that there is an OMQ  $Q(\bar{x}) = (O, S, q) \in$  $(\mathbb{ELI}, \mathbb{CQ})$  that satisfies the conditions from Theorem 3.4 and such that single-testing complete answers to *Q* is possible in linear time. Since Q is non-empty, there is an S-database  $D_0$  and a tuple  $\bar{a} \in$  $Q(D_0)$ . Define the Boolean OMQ  $Q_{\bar{a}} := (O, S, q[\bar{a}/\bar{x}])$ . It is easy to see that  $Q_{\bar{a}}$  is not acyclic, non-empty and self-join free. In particular,  $D_0$  witnesses its non-emptiness. Moreover, single-testing for  $Q_{\bar{a}}$  is then also possible in linear time because ()  $\in Q_{\bar{a}}(D)$  iff  $\bar{a} \in Q(D)$ , for all S-databases D. If we have proved Theorem 3.4 for complete answers and the class of OMQs described above, of which  $Q_{\bar{a}}$  is a member, it thus follows that the triangle conjecture fails. Regarding minimal partial answers and minimal partial answers with multiple wildcards, it suffices to observe that these agree with complete answers for Boolean OMQs.

Let  $Q() = (O, S, q) \in (\mathbb{ELI}, \mathbb{CQ})$  be not acyclic, non-empty, and self-join free.<sup>2</sup> We show how to construct, given an undirected graph G = (V, E), an S-database D such that  $D \models Q$  if and only if G contains a triangle. When speaking about undirected graphs, we generally mean graphs without self loops and isolated vertices. Since Q is non-empty, there is an S-database  $D_0$  with  $D_0 \models Q$  and a homomorphism  $h_0$  from q to  $ch_O(D_0)$ . We are going to use  $D_0$ and  $h_0$  throughout the subsequent proof.

Since *q* is not acyclic, the undirected graph  $G_q^{\text{var}}$  contains a cycle  $x_1, \ldots, x_n$  of length at least three. We may assume w.l.o.g. that the cycle is chordless. To ease notation, set  $x_{n+1} := x_1$ . For  $1 \le i \le n$ , a binary relation *R* is an *i*-relation if *q* contains an atom  $R(x_i, x_{i+1})$  or  $R(x_{i+1}, x_i)$ . Note that no *R* can be an  $i_1$ -relation and an  $i_2$ -relation with  $i_1 \ne i_2$  since *q* is self-join free.

LEMMA C.4. If R is an i-relation,  $1 \le i \le n$ , then  $R \in S$ .

PROOF. The lemma follows from Q being non-empty and self-join free. In fact, assume to the contrary of what is to be shown that there is an *i*-relation R,  $1 \le i \le n$ , such that  $R \notin S$ . We have  $h_0(x_i) \in \operatorname{adom}(D_0)$  for  $1 \le i \le n$  since  $x_1, \ldots, x_n$  participate in a cycle in the self-join free CQ q, and the null part of  $\operatorname{ch}_O(D_0)$ consists of a disjoint union of trees without self loops and multiedges (because O is formulated in  $\mathcal{ELI}$ ). However, the restriction of  $\operatorname{ch}_O(D_0)$  to  $\operatorname{adom}(D_0)$  contains no R-edges with  $R \notin S$ , and thus all *i*-relations must be from S.

We now construct the S-database *D*. Let  $C = \{c_0, \ldots, c_{k-1}\}$  be a set of  $k = \max\{4, \operatorname{con}(q)\}$  constants with  $\operatorname{con}(q) \subseteq C$ . The active domain of the database *D* is

$$\mathsf{adom}(D) = V \cup C$$

and *D* contains the following facts:

- A(c) for every unary  $A \in S$  and every  $c \in adom(D)$ ;
- R(c, c) for every *i*-relation  $R, 3 < i \leq n$ , and every  $c \in adom(D)$ ;
- for every *i*-relation R,  $1 \le i \le 3$ :
  - R(u, v) for every edge  $\{u, v\} \in E$ ;
  - $R(c_i, c_{i+1 \mod k})$  for  $0 < i \le k$ .
- R(c, c),  $R(c, c_{\ell})$ , and  $R(c_{\ell}, c)$  for every binary  $R \in S$  that is not an *i*-relation for any *i*, all  $c' \in adom(D)$ , and  $1 \le \ell < k$ .

Due to Lemma C.4, D is indeed an S-database. The construction of D strongly relies on self-join freeness as this makes the interpretation of *i*-relations in D independent of each other for different *i*. It should be clear that D can be constructed in time linear in |E|.

We remark that *D* has two important properties. First, every  $c \in \operatorname{adom}(D)$  has both an incoming *R*-edge and an outgoing *R*-edge for every binary relation  $R \in S$ . And second, every triangle in *D* that only uses the relations  $R_1, R_2, R_3$  is in  $D|_V$ ; more precisely: if  $D' \subseteq D$  is an  $\{R_1, R_2, R_3\}$ -database such that  $|\operatorname{adom}(D')| = 3$  and the Gaifman graph of *D'* is a triangle, then  $\operatorname{adom}(D') \subseteq V$ . We refer to this as the *completeness property* and the *triangle property*, respectively. To complete the reduction, it suffices to show the following.

LEMMA C.5. *G* contains a triangle iff  $D \models Q$ .

**PROOF.** "if". Assume that  $D \models Q$ . Then there is a homomorphism h from q to  $ch_O(D)$ . Due to the interpretation of the *i*-relations in D with  $3 < i \leq n$ , we must have  $h(x_4) = \cdots = h(x_n) =$  $h(x_1)$ . Consequently, the Gaifman graph of  $ch_O(D)$  must contain the edge  $\{h(x_i), h(x_i)\}$  for  $1 \le i, j \le 3$ . By construction and since G has no self loops, D contains no reflexive  $R_i$ -edges for  $1 \leq i \leq 3$ . Since  $O \in \mathbb{ELI}$ , the same is then true for  $ch_O(D)$ . It follows that  $h(x_1), h(x_2), h(x_3)$  are all distinct and thus the restriction of  $ch_{\mathcal{O}}(D)$  to  $h(x_1), h(x_2), h(x_3)$  is a triangle. Due to the triangle property and since the chase with an ELI-ontology only adds to D trees without self loops and multi-edges, this implies that  $h(x_i) \in V$  for  $1 \le i \le 3$ . Since the chase adds no binary facts  $R(c_1, c_2)$  with  $c_1, c_2 \in \mathsf{adom}(D)$ , the restriction of D to  $h(x_1), h(x_2), h(x_3)$ is also a triangle. It now follows from the interpretation of the *i*relations in D with  $1 \le i \le 3$ ,  $h(x_1), h(x_2), h(x_3)$  is a triangle in *G*.

"only if". Assume that *G* contains a triangle that consists of the vertices  $v_1, v_2, v_3$ . Let  $q^-$  be q with all unary atoms dropped. We

 $<sup>^{2}</sup>$ We remark that the proof still goes through if *q* is self-join free only regarding the binary atoms, but not necessarily regarding the unary ones.

first construct a homomorphism h from  $q^-$  to  $ch_O(D)$  and then argue that it can be extended to a homomorphism from q to  $ch_O(D)$ .

We construct *h* by first mapping only some variables from *q* and then extending in several rounds. After each round, the constructed *h* will be a homomorphism from  $q^-|_h$  to  $ch_O(D)$  where  $q^-|_h$  is the restriction of  $q^-$  to the domain of *h*.

Start with setting  $h(x_1) = v_1$ ,  $h(x_2) = v_2$ , and  $h(x_3) = \cdots = h(x_n) = v_3$  and h(c) = c for all  $c \in \operatorname{con}(q)$ . It can be verified that h is a homomorphism from  $q^-|_h$  to D, thus also to  $\operatorname{ch}_O(D)$ . To see this, it helps to observe that q contains no atoms  $R(x_i, x_j)$  with  $x_j \notin \{x_{i-1}, x_i, x_{i+1}\}$  and that all binary atoms in  $q^-|_h$  use a relation from S. In fact, the former is a consequence of  $x_1, \ldots, x_n$  being a chordless cycle in  $G_q^{\operatorname{var}}$ . For the latter, recall that  $h_0$  is a homomorphism from q to  $\operatorname{ch}_O(D_0)$  that maps all variables  $x_1, \ldots, x_n$  to adom $(D_0)$ , established in the proof of Claim 1. But all binary facts in the restriction of  $\operatorname{ch}_O(D_0)$  to  $\operatorname{adom}(D_0)$  use relations from S.

To extend h, set  $h(x) = c_0$  for all  $x \in var(q)$  with h(x) not yet defined and  $h_0(x) \in adom(D_0)$  (any other constant would also work). It can be verified that h is still a homomorphism from  $q^-|_h$  to D. In particular, we can argue as above that all binary atoms in  $q^-|_h$  use a relation from S.

For the next extension of h, let q' be obtained from q by first dropping all atoms  $R(\bar{x})$  such that  $h_0(x) \in \operatorname{adom}(D_0)$  for all  $x \in \bar{x}$  and then identifying any variables  $x_1, x_2$  such that  $h_0(x_1) = h_0(x_2)$ . Consider all maximal connected components p of q'. We distinguish two cases.

First assume that p contains a variable x with h(x) already defined. It then only contains a single such variable, that is,  $h_0(x) \in$ adom $(D_0)$  and all  $y \neq x$  in p are mapped to the tree that the chase has generated below  $h_0(x)$ . Since the restriction of  $ch_O(D_0)$ to the nulls is a disjoint union of trees without reflexive loops and multi-edges, it follows that p(x) is an ELIQ. Moreover,  $D_0 \models$  $(O, S, p(x))(h_0(x))$ . The completeness property of D implies that  $(D_0, h_0(x)) \leq (D, h(x))$ , no matter what h(x) is. It thus follows from Lemma A.3 that  $D \models (O, S, p(x))(h(x))$ , and consequently there is a homomorphism g from p(x) to  $ch_O(D)$  with g(x) = h(x). We can extend h to p by setting  $h := h \cup q$ .

Now assume that p contains no variable x with h(x) already defined. Since p is connected, there is a  $c \in \operatorname{adom}(D_0)$  such that  $h_0(x)$  is in the tree that the chase has generated below c for all  $x \in \operatorname{var}(p)$ . Let  $\hat{p}(x)$  be the minimal prefix of that tree that contains  $h_0(x)$  for all  $x \in \operatorname{var}(p)$ , viewed as an ELIQ with c being the answer variable. There is a homomorphism g from p(x) to  $\hat{p}(x)$ ) with g(x) = x. We have  $D_0 \models (O, \mathrm{S}, \hat{p}(x))(c)$ . Take any constant  $c' \in \operatorname{adom}(D)$ . The completeness property of D implies that  $(D_0, c) \leq (D, c')$ . It thus follows from Lemma A.3 that  $D \models$  $(O, \mathrm{S}, \hat{p}(x))(c')$ , and consequently there is a homomorphism g'from  $\hat{p}(x)$  to  $\operatorname{ch}_O(D)$  with g'(x) = c'. We can extend h to p by setting  $h := h \cup (g \circ g')$ .

At this point, h is defined for all terms in var(q) and thus it is a homomorphism from  $q^-$  to  $ch_O(D)$ . Further extend h by setting h(x) to any constant in adom(D) if x does not occur in any binary atoms. It remains to argue that h satisfies all unary atoms A(x)in a. If  $A \in S$ , then this is clear by the interepretation of such symbols in D. Otherwise, we observe that  $A(h_0(x)) \in ch_O(D_0)$ . We can argue as above, using the ELIQ A(x) and Lemma A.3, that  $A(h(x)) \in ch_O(D)$ .

The next example illustrates another reason for why we cannot easily replace  $\mathbb{BLI}$  with  $\mathbb{G}$  in Theorem 3.4, unrelated to self-join freeness.

$$\begin{aligned} Example \ C.6. \ \text{Let } Q(x) &= (O, S, q) \in (\mathbb{G}, \mathbb{CQ}) \text{ where} \\ O &= \{A(x) \to \exists y \exists z \ R(x, y) \land S(y, z) \land T(z, x)\} \\ S &= \{A\} \\ q(x) &= R(x, y) \land S(y, z) \land T(z, x). \end{aligned}$$

Then *Q* is not acyclic and self-join free, yet single-testing *Q* is in linear time as  $Q \equiv (\emptyset, S, A(x))$ .

For CQs without ontologies, we are not aware of any examples which show that Theorem 3.4 fails when 'self-join free' is replaced with 'a homomorphism core'.<sup>3</sup> For ( $\mathbb{ELI}, \mathbb{CQ}$ ), however, such examples are not hard to find.

 $\begin{aligned} &Example \ C.7. \ \text{Let } Q = (O, S, q) \in (\mathbb{ELI}, \mathbb{CQ}) \text{ where} \\ &O = \{A(x) \to \exists y \exists z \ R(x, y) \land B_1(y) \land B_2(y) \land R(y, z)\} \\ &S = \{A\} \\ &q(x) = R(x, y_1) \land R(x, y_2) \land B_1(y_1) \land B_2(y_2) \land \\ &R(y_1, z) \land R(y_2, z). \end{aligned}$ 

Then *Q* is not acyclic and *q* is a homomorphism core, yet singletesting *Q* is in linear time as  $Q \equiv (\emptyset, S, A(x))$ .

# C.3 Proof of Theorem 3.6

THEOREM 3.6. (1) There is a weakly acyclic  $OMQ \ Q \in (\mathbb{ELI}, \mathbb{CQ})$ for which single-testing minimal partial answers is not in linear time unless the triangle conjecture fails and (2) an acyclic  $OMQQ \in (\mathbb{G}, \mathbb{CQ})$ for which single-testing minimal partial answers with multi-wildcards is not in linear time unless the triangle conjecture fails.

PROOF. First for weakly acyclic OMQs and minimal partial answers with a single wildcard. We start with showing the result for ( $\mathbb{G}$ ,  $\mathbb{CQ}$ ) in place of ( $\mathbb{ELI}$ ,  $\mathbb{CQ}$ ). Let *R* be a binary relation symbol and  $S = \{R\}$ . We may view an undirected graph G = (V, E) as the S-database

$$D_G = \{ R(v, v'), R(v', v) \mid \{v, v'\} \in E \}.$$

Consider the OMQ  $Q(x) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  where O contains the TGD

$$R(x_1, x_2) \rightarrow \exists y_1 \exists y_2 \exists y_3 R\{y_1, y_2\} \land R\{y_2, y_3\} \land R\{y_3, y_1\}$$

with  $R{x, y}$  an abbreviation for  $R(x, y) \land R(y, x)$  and with

$$q(x, y, z) = R\{x, y\} \land R\{y, z\} \land R\{z, x\}.$$

Note that *q* is weakly acyclic. Let G = (V, E) be an undirected graph. Then (\*, \*, \*) is a partial answer to *Q* on *D<sub>G</sub>*, but not necessarily a minimal partial answer. In fact, it is a minimal partial answer if and only if *G* contains no triangle. It clearly follows that single-testing minimal partial answers for *Q* is not in  $\text{DelayC}_{\text{lin}}$  unless the triangle hypothesis fails.

<sup>&</sup>lt;sup>3</sup>A CQ is a *homomorphism core* if every homomorphism from  $D_q$  to  $D_q$  is surjective. For every CQ, there is an equivalent CQ that is a homomorphism core.

Technical Report, arXiv version, 2022

The challenge in improving the construction to  $\mathbb{ELI}$  is that  $\mathcal{ELI}$  TGDs cannot introduce a triangle that consists of nulls. The solution is to construct *q*, *O*, and *D* in a more careful way. Let us start with *q*, which is now

$$q(x_1, x_2, x_3, x_4) = R(x_1, x_2) \land R(x_2, x_3) \land R(x_4, x_3) \land R(x_1, x_4)$$
$$\land A(x_1) \land B(x_2) \land B(x_3) \land A(x_4)$$

where *A*, *B*, *C* are additional unary relation symbols and the direction of the edges is chosen carefully. We choose *O* to contain the  $\mathcal{ELI}$  TGD

$$R(x_1, x_2) \rightarrow \exists y_1 \exists y_2 \exists y_3 R(x_1, y_2) \land R(y_2, y_3)$$
$$\land A(y_1) \land A(y_2) \land B(y_2) \land B(y_3).$$

Similarly to before, (\*, \*, \*, \*) is a partial answer to Q on any nonempty S-database, such as the databases  $D_G$ . It remains to modify  $D_G$  so that  $q(D_G)$  is non-empty if and only if G = (V, E) contains a triangle, as  $q(D_G)$  is empty if and only if (\*, \*, \*, \*) is a *minimal* partial answer. This is achieved by constructing  $D_G$  so that  $adom(D_G) = V \times [2]$  and  $D_G$  contains the following facts:

- R((v, 1), (v', 2)), R((v, 2), (v', 2)) for all  $\{v, v'\} \in E$ ;
- R((v, 1), (v, 1)), A(v, 1), B(v, 2) for all  $v \in V$ .

It thus remains to argue that  $q(D_G)$  is non-empty if and only if G = (V, E) contains a triangle. For the "if" direction, it suffices to observe that any triangle  $v_1, v_2, v_3$  in G gives rise to the answer  $((v_1, 1), (v_2, 2), (v_3, 2), (v_1, 1))$  in q(G). For the "only if" direction, let  $(c_1, c_2, c_3, c_4) \in q(G)$ . Due to the atoms  $A(x_1), R(x_1, x_4), A(x_4)$  in q, we must have  $c_1 = c_4 = (v_1, 1)$  for some  $v_1 \in V$ . Due to the atoms  $A(x_1), R(x_1, x_2), B(x_2)$  and  $A(x_4), R(x_4, x_3), B(x_3)$ , respectively, we must have  $c_2 = (v_2, 2)$  and  $c_3 = (v_3, 2)$  for some  $v_2, v_3 \in V$  such that  $v_1 \neq v_2, v_1 \neq v_3$ , and  $\{v_1, v_2\}, \{v_2, v_3\} \in G$ . Finally, the atoms  $B(x_2), R(x_2, x_3), B(x_3)$  ensure that  $v_2 \neq v_3$  and  $\{v_1, v_2\} \in G$ . Thus,  $v_1, v_2, v_3$  form a triangle in G.

We now turn towards acyclic OMQs and minimal partial answers with multi-wildcards. The general idea is similar to what was done above. In particular, with every undirected graph G = (V, E)we associate an S-database  $D_G = \{R(v, v'), R(v', v) \mid \{v, v'\} \in E\}$ . Consider the OMQ  $Q(x) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  where O contains the TGD

 $R(x_1, x_2) \rightarrow \exists y_1 \exists y_2 \exists y_3 R\{y_1, y_2\} \land R\{y_2, y_3\} \land R\{y_3, y_1\}$ 

with  $R{x, y}$  an abbreviation for  $R(x, y) \land R(y, x)$  and with

$$q(x_1, x_1', x_2, x_2', x_3, x_3') = R(x_1, x_1') \land R(x_2, x_2') \land R(x_3, x_3').$$

Note that q is acyclic and in fact of a very restricted shape. Let G = (V, E) be an undirected graph. Then  $(*_1, *_2, *_2, *_3, *_3, *_1)$  is a partial answer with multi-wildcards to Q on  $D_G$ . Moreover, it is a minimal partial answer if and only if  $D_G$  contains no triangle. It clearly follows that single-testing minimal partial answers with multi-wildcards for Q is not in DelayC<sub>lin</sub> unless the triangle hypothesis fails.

# **D PROOFS FOR SECTION 4**

PROPOSITION 4.2. For CQs (without ontologies) that are free-connex acyclic, all-testing is in CDoLin.

**PROOF.** Let  $q(\bar{x})$  be a CQ that is free-connex acyclic, over some schema S. Since q is free-connex acyclic, its extension  $q^+(\bar{x})$  with

atom  $R_0(\bar{x})$  is acyclic, where  $R_0$  is a fresh relation symbol of arity  $|\bar{x}|$ . Thus  $q^+$  has a join tree T = (V, E). When removing from T the node  $R_0(\bar{x})$ , we obtain a forest that consists of trees  $(V_1, E_1), \ldots, (V_k, E_k)$ . Let  $q_1(\bar{x}_1), \ldots, q_k(\bar{x}_k)$  be the corresponding CQs, that is,  $q_i$  contains exactly the atoms in  $V_i$ . It is clear that every  $q_i$  is acyclic since  $(V_i, E_i)$  is a join tree for  $q_i$ . It is also free-connex acyclic. In fact, let  $q_i^+(\bar{x}_i)$  be  $q_i$  extended with atom  $R_i(\bar{x}_i)$ . We obtain a join tree for  $q_i^+$  by starting with  $(V_i, E_i)$ , adding node  $R_i(\bar{x}_i)$ , and an edge between  $R_i(\bar{x}_i)$  and the node in  $V_i$  that is adjacent in T to  $R_0(\bar{x})$  (there must be a unique such node).

It is known that all-testing is in CDoLin for all CQs that are acyclic and free-connex acyclic [11]. There are thus CDoLin alltesting algorithms  $A_1, \ldots, A_k$  for  $q_1, \ldots, q_k$ . We devise a CDoLin all-testing algorithm for q by combining these. Let the S-database D be given as input. In the preprocessing phase, we run the preprocessing phases of algorithms  $A_1, \ldots, A_k$  on D. In the testing phase, we are given a tuple  $\bar{c} \in \mathsf{adom}(D)^{|\bar{x}|}$ . Let  $\bar{x} = x_1 \cdots x_n$  and  $\bar{c} = c_1 \cdots c_n$ . We first check whether  $x_i = x_j$  implies  $c_i = c_j$  and reject if this is not the case. We then use algorithms  $A_1, \ldots, A_k$ to test in constant time whether for  $1 \leq i \leq k$ , it holds that  $\bar{c}_i \in q_i(D)$  where  $\bar{c}_i$  is the 'projection' of tuple  $\bar{c}$  to the answer variables in  $q_i$ , that is, if  $x_{i_1}, \ldots, x_{i_\ell}$  are the answer variables in  $q_i$ , then  $c_i = c_{i_1}, \ldots, c_{i_\ell}$ . We answer 'yes' if all checks succeed and 'no' otherwise. Since  $q_1, \ldots, q_k$  is a partitioning of (the atoms of) qand distinct  $q_i$  do not share any quantified variables, the answer is clearly correct. 

Theorem 4.1. In  $(\mathbb{G}, \mathbb{CQ})$ ,

- enumerating complete answers is in CDoLin for OMQs that are acyclic and free-connex acyclic;
- (2) all-testing complete answers is in CDoLin for OMQs that are free-connex acyclic.

PROOF. Point (1) of Theorem 4.1 is easy to prove using the querydirected chase established in Section C.1 and the existing result stating that enumeration is in CDoLin for CQs that are acyclic and free-connex acyclic when no ontologies are present [4]. In fact, assume that an OMQ  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  that is acyclic and free-connex acyclic is given, as well as an S-database *D*. As a part of the preprocessing phase, we compute in linear time the query-directed chase  $ch^q(O)$ . As in the proof of Theorem 3.1, we introduce a fresh unary relation symbol  $P_{db}$ , extend  $ch_O^q(D)$  to a database *D'* by adding the fact  $P_{db}(c)$  for every  $c \in adom(D)$ , and obtain the CQ  $q'(\bar{x})$  from *q* by adding the atom  $P_{db}(x)$  for every answer variable *x*. Note that since *q* is acyclic and free-connex acyclic, so is *q'*. By Lemma C.1 Q(D) = q'(D') and thus we can use an existing procedure as a black box for enumerating q'(D')in CDoLin [4].

The argument for Point (2) is identical, based on Proposition 4.2.  $\hfill\square$ 

THEOREM 4.3. Let  $Q \in (\mathbb{ELI}, \mathbb{CQ})$  be non-empty, and self-join free. If Q is not acyclic, then enumerating complete answers to Q is not in  $\text{DelayC}_{\text{lin}}$  unless the triangle conjecture fails. The same is true for minimal partial answers and for minimal partial answers with multiple wildcards. PROOF. Let  $Q \in (\mathbb{ELI}, \mathbb{CQ})$  satisfy the conditions from Theorem 4.3. Assume that enumerating complete answers to Q is in DelayC<sub>lin</sub>. Let the Boolean OMQ Q' be obtained from Q by quantifying all answer variables. Then Q' satisfies the same conditions, that is, it is not acyclic, non-empty and self-join free. It is even weakly acyclic since acyclicity and weak acyclicity coincide for Boolean CQs. Moreover, single-testing for Q' is in linear time because given an S-database D, we can check whether  $() \in Q'(D)$  by enumerating Q on D, but accepting after the first ouput and rejecting if there was no output. It thus follows from Theorem 3.4 that the triangle conjecture fails. The same argument works for minimal partial answers and for minimal partial answers with multiple wildcards.

# D.1 Lower Bound for Proposition 4.2

We prove the following counterpart of Proposition 4.2. Note that it is not subsumed by Theorem 4.6 because, there, the arity of relation symbols is at most 2. As we are working without ontologies here, our proof follows closely the lines of corresponding lower bounds for enumeration given in [4, 11, 17]. For the same reason, we rely on the additional assumption stating that (k + 1, k)-hyperclique problem cannot be solved in time  $O(n^k)$ .

The (k + 1, k)-hyperclique problem is as follows. Given a k-uniform hypergraph with n vertices, i.e. every hyperedge consists of exactly k vertices, decide whether it contains a hyperclique of size k+1, i.e. a set of k+1 vertices where every subset of size k is a hyperedge. The hyperclique conjecture states that for all  $k \ge 3$  solving the (k + 1, k)-hyperclique problem requires  $n^{k+1-o(1)}$  time [34].

LEMMA D.1. Let  $q(\bar{x})$  be a self-join free CQ that is not free-connex acyclic. Then all-testing for q is not in  $DelayC_{lin}$  unless one of the following holds:

- (1) the triangle conjecture fails;
- (2) Boolean  $n \times n$  matrices can be multiplied in time  $O(n^2)$ ;
- (3) (k + 1, k)-hyperclique problem can be solved in time  $O(n^k)$ .

To prove Lemma D.1, we make use of the following well-known characterization of acyclicity.

THEOREM D.2 ([10]). A CQ q is acyclic iff it satisfies the following properties:

- q is conformal, i. e. for every clique of the Gaifman graph Gq of q there exists an atom that contains all variables in the clique;
- (2) q is chordal, i. e. every cycle of length at least 4 in G<sub>q</sub> has a chord. That is, G<sub>q</sub> contains an edge that is not part of the cycle but connects two vertices of the cycle.

We now prove Lemma D.1. Let q be as in the lemma and let us assume that all-testing for q is in  $DelayC_{lin}$ . We show that one of Points (1)-(3) applies.

Recall that  $\hat{q}(\bar{x})$  is the CQ  $q(\bar{x})$  with the additional atom  $\hat{R}(\bar{x})$  where  $\hat{R}$  is a fresh relation symbol. Since q is not free-connex acyclic,  $\hat{q}$  is not acyclic. Hence,  $\hat{q}$  is not conformal or not chordal.

Not chordal. If  $\hat{q}$  is not chordal, then there is a cordless cycle  $z_1, z_2, \ldots, z_m$  of length  $m \ge 4$  in the Gaifman graph of  $\hat{q}$ . Moreover, since there is an atom  $\hat{R}(\bar{x})$  in  $\hat{q}$ , there are no more than two answer variables in this cycle.

At most one answer variable in the cycle. If there is no more than one answer variable in the cycle, then also CQ q is not chordal, as the new edges in the Gaifman graph of  $\hat{q}$  are only those between answer variables. Hence, we can use the construction for the "not chordal" case form Section 6.2. in [11]. Given an undirected graph G, it constructs in time O(n) a database D such that  $q(D) \neq \emptyset$  if and only if G has a triangle.

Moreover, a careful analysis of the construction reveals that, in fact, we only need to test O(n) different tuples  $\bar{a} \in \operatorname{adom}(D)^{|\bar{x}|}$  to decide whether  $q(D) \neq \emptyset$ , and we can compute the set of those tuples in time O(n). Thus, assuming that all-testing is in  $\operatorname{DelayC_{lin}}$ , we can decide whether  $q(D) \neq \emptyset$  in time O(n). Indeed, the database D can be constructed in time O(n). Thus, the preprocessing phase can be done in O(n) time and testing can be carried out in time O(n). This gives overall running time O(n), and disproves the triangle conjecture.

Two answer variables in the cycle. If there are two answer variables in the cycle, then without loss of generality we can assume that they are  $x_1 = z_1$  and  $x_2 = z_m$ . Indeed, since there is an atom  $\hat{R}(\bar{x})$  in  $\hat{q}$  and the cycle is chordless, the answer variables have to be two consecutive vertices in the cycle. Thus, to obtain  $x_1 = z_1$  and  $x_2 = z_m$  we can simply rename some variables in q. Now we have two possibilities. Either there is an atom in q that contains both  $x_1$  and  $x_2$  or there is no such atom in q.

If there is no such atom, then we can use the construction for the "acyclic but not free-connex acyclic query" case form Section 6.1. in [11]. In the terminology of [11], applying the construction requires that there is a 'bad path' in q. This is the case when  $x_1, x_2$ do not co-occur in an atom in q. Given two  $n \times n$  Boolean matrices  $M_1, M_2$ , the construction creates in time  $O(n^2)$  a database D such that the set q(D) projected to the first two coordinates is the set  $M_1M_2$ .

Notice that the construction in [11] is used for queries that are not only free-connex acyclic, but also acyclic. However, acyclicity is only used to guarantee the existence of a bad path and not in the construction of the database *D*. It is easy to verify that the following claim is valid also in our setting.

CLAIM D.1. For every pair  $(i, j) \in [n]^2$  we have  $(i, j) \in M_1M_2$ if and only if there is a corresponding answer  $\bar{a}_{i,j}$  in q(D) where the tuple  $\bar{a}_{i,j}$  can be computed from (i, j) in constant time.

Hence, to compute  $M_1M_2$  we only need to test  $\bar{a}_{i,j} \in q(D)$  for all  $(i, j) \in [n]^2$ . If all-testing is in  $\text{DelayC}_{\text{lin}}$ , we can thus compute  $M_1M_2$  in time  $O(n^2)$ . Indeed, the database D can be constructed in time  $O(n^2)$ . Thus, the preprocessing phase can be done in  $O(n^2)$ time and testing can be carried out in time  $O(n^2)$ . This gives overall running time  $O(n^2)$ .

In the case that  $x_1$  and  $x_2$  are in an atom  $R'(\bar{w})$  in q, we slightly modify the construction by adding to the database D also the R'-facts that are total on  $x_1, x_2$  and use the unique constants for the remaining variables. Since the cycle is chordless, no other variables from the cycle appear in  $R'(\bar{w})$ . Thus, every such set of facts is of size  $n^2$  and the database can be constructed in time  $O(n^2)$ .

*Not conformal.* Now assume that  $\hat{q}$  is not conformal. Then there are k and a clique  $z_1, \ldots, z_{k+1}$  such that the clique is not covered by and atom and every proper subset of  $\{z_1, \ldots, z_{k+1}\}$  is. Indeed, it

Technical Report, arXiv version, 2022

is enough to take a minimal clique that is not covered by an atom. Let  $Z = \{z_1, \ldots, z_{k+1}\}.$ 

Again, we have two cases. Either every proper subset of Z can be covered by an atom that is not  $\hat{R}(\bar{x})$  or there is a proper subset of Z such that the only atom that covers it is  $\hat{R}(\bar{x})$ .

In the former case, q is not conformal and we can apply the construction for the "not conformal" case form Section 6.2. in [11]. Given a k-uniform hypergraph G, it creates in time  $O(n^k)$  a database D such that  $q(D) \neq \emptyset$  if and only if G contains a hyperclique of size k+1. A careful analysis of the construction reveals that, in fact, we only need to test  $O(n^k)$  different tuples  $\bar{a} \in \text{adom}(D)^{|\bar{x}|}$  to decide whether  $q(D) \neq \emptyset$  and that we can compute the set W of those tuples in time  $O(n^k)$ .

If there is an algorithm for all-testing in  $\text{DelayC}_{\text{lin}}$ , we can thus solve the hyperclique problem  $O(n^k)$ . Indeed, database D can be constructed in time  $O(n^k)$ , the preprocessing phase can be done in  $O(n^k)$  time, and testing all tuples from W can be carried out in time  $O(n^k)$ . This gives the overall running time  $O(n^k)$ .

Finally, for the case where there is a proper subset of Z such that the only atom that covers it is  $\hat{R}(\bar{x})$  we follow the same construction but using  $\hat{q}$  instead of q. Then we remove all  $\hat{R}$ -facts from the database D and adjust the set of tuples W so that it is consistent with the removed facts. It is easy to see that this adaptation can be done in time  $O(n^k)$  and does not change the results of the test. This ends the proof.

# D.2 Proof of Theorem 4.4

There are several characterizations of when an acyclic CQ is free-connex [11]. A characterization that we use in what follows is via bad paths. A *bad path* in a CQ *q* is a sequence of variables  $y_1, \ldots, y_n$ ,  $n \ge 3$ , such that  $y_1$  and  $y_n$  are distinct answer variables,  $y_2, \ldots, y_{n-1}$ are quantified variables, and  $\{y_i, y_{i+1}\}$  is an edge in the Gaifman graph of *q* while  $\{y_1, y_n\}$  is not. It was shown in [4] that an acyclic CQ is free-connex if and only if it has no bad path, see also [11].

THEOREM 4.4. Let  $Q = (O, S, q) \in (\mathbb{ELI}, \mathbb{CQ})$  be acyclic, non-empty, self-join free, and connected. If Q is not free-connex acyclic, then enumerating complete answers to Q is not in DelayC<sub>lin</sub> unless spBMM is possible in time  $O(|M_1| + |M_2| + |M_1M_2|)$ . The same is true for minimal partial answers and for minimal partial answers with multiple wildcards.

Before we prove the theorem, let us recall some basic relations between the sets of complete answers, minimal partial answers, and minimal partial answers with multiple wildcards.

CLAIM D.2. For every  $OMQ \ Q \in (\mathbb{G}, \mathbb{CQ})$  there is a constant K such that for every database D holds

$$|Q(D)| \le |Q(D)^*| \le |Q(D)^{\mathcal{W}}| \le K|Q(D)^*|.$$

Every complete answer is also a minimal partial answer (with multiple wildcards), thus  $Q(D) \subseteq Q(D)^*$  and  $Q(D) \subseteq Q(D)^W$ . Hence, the first inequality. The remaining inequalities are a consequence of Lemma F.5. By Point (1) of Lemma F.5, we have that  $|Q(D)^W| \leq K|Q(D)^*|$ , where K is some constant that depends only on Q. Indeed, every minimal partial answer with multiple wildcards is in a cone of some minimal partial answer. Since every cone has no more than  $k^{2^k}$  elements, where k is the number of Let  $Q = (O, S, q) \in (\mathbb{ELI}, \mathbb{CQ})$  be an OMQ as in the theorem. To prove Theorem 4.4 we show that if given a database D we can enumerate any of the sets Q(D),  $Q(D)^*$ , or  $Q(D)^W$  in  $\mathsf{DelayC}_{\mathsf{lin}}$ , then spBMM is possible in time  $O(|M_1| + |M_2| + |M_1M_2|)$ .

Assume that we are given Boolean matrices  $M_1$  and  $M_2$  of size  $n \times n$ . Recall that in sparse Boolean matrix multiplication (spBMM),  $M_1$  and  $M_2$  are given as lists of pairs (a, b) with  $M_i(a, b) = 1$  and also  $M_1M_2$  is output as such a list. For a pair (a, b) by  $\prod_{col}((a, b))$  we denote the column and by  $\prod_{row}((a, b))$  the row.

We use  $M_1$  and  $M_2$  to construct an S-database D such that enumerating Q(D) or  $Q(D)^*$  in DelayC<sub>lin</sub> allows us to construct  $M_1M_2$  within the desired time bound.

As a preliminary, we argue that we can w.l.o.g. assume  $M_1$  and  $M_2$  to satisfy a certain condition that shall prove to be useful in what follows. Let  $P_M$  denote the set of *productive indices* in  $n \times n$  matrix M, i.e.  $P_M = \{c \in [n] \mid \exists a M(a, c) = 1 \text{ or } M(c, a) = 1\}$ . Now the condition is:

(\*) for all  $c \in P_M$ , there are  $a_1, a_2 \in [n]$  with  $M(c, a_1) = 1$  and  $M(a_2, c) = 1$ .

In fact, we can construct from  $M_1, M_2$  in time  $O(|M_1| + |M_2|)$  two  $(n + 2) \times (n + 2)$  matrices  $\hat{M}_1, \hat{M}_2$  that satisfy (\*) and such that  $M_k(a, b) = 1$  if and only if  $\hat{M}_k(a+2, b+2) = 1$  for  $1 < a, b \le n$  and k = 1, 2, 3 where  $\hat{M}_3 = \hat{M}_1 \cdot \hat{M}_2$ . To construct  $\hat{M}_k$ , set

$\hat{M}_k(a+2,b+2) = M_k(a,b)$	for $0 < a, b \le n$
$\hat{M}_k(1,1) = \hat{M}_k(2,2) = 1$	
$\hat{M}_1(i+2,2) = 0$	for $1 \le i \le n$
$\hat{M}_2(1, i+2) = 0$	for $1 < i < n$

Note that quite a few entries in the first and second column and row  $\hat{M}_3(a+2,b+2)$ 

are yet undefined. Independently of how we define them,

Hence, we can use the remaining undefined positions to satisfy (\*). It clearly suffices to add at most  $2*|P_{M_1} \cup P_{M_2}|$  ones to each matrix and thus  $|\hat{M}_1| + |\hat{M}_2| \in O(|M_1| + |M_2|)$ . We can thus use  $\hat{M}_1$  and  $\hat{M}_2$  in place of  $M_1$  and  $M_2$ .

Recall that q is acyclic, but not free-connex acyclic and that, as discussed in the preliminaries, this implies that q contains a bad path, i.e. a sequence of variables a sequence of variables  $x_1, y_1, \ldots, y_\ell, x_2$ ,  $\ell \ge 1$ , with  $x_1, x_2$  answer variables and  $y_1, \ldots, y_\ell$  quantified variables such that any two consecutive variables form an edge in the Gaifman graph of q, but not two non-consecutive variables do. Since q is acyclic and connected, the undirected graph  $G_q^{\text{var}}$  is a disjoint union of trees (as the connectedness can be 'via' a constant). We can impose a direction on these trees. For the tree that contains  $x_1$ , we do this by choosing  $x_1$  as the root and call a variable in the tree a successor of another variable if it is further away from  $x_1$ , and likewise for descendants and ancestors. For the other trees we do the same, choosing a root as follows. If q contains an atom that contains a variable x from the tree and a constant, then choose such an x as the root. Otherwise choose the root arbitrarily. +

=

To present the reduction in a more transparent way, we make the following simplifying assumptions:

- (Dir) if *y* is a successor of *x* in  $G_q^{var}$ , then any binary atom in *q* that involves *x* and *y* is directed towards *y*, that is, it takes the form R(x, y); moreover, any binary atom in *q* that involves a variable *x* and a constant *c* is directed towards *c* if *x* is reachable from  $x_1$  in  $G_q^{var}$  and away from *c* otherwise;
- (Mult) *q* contain no non-reflexive multi-edges, that is, no two distinct non-reflexive binary atom that mention the same terms.

It is not difficult to get rid of these assumptions. In fact, this can be done as follows. Given q, first re-orient the edges and drop all edges but one from non-reflexive multi-edges, obtaining a CQ q'that satisfies (Dir) and (Mult). Then construct the S-database D as described below and obtain from it another S-database  $\hat{D}$  by reorienting edges back to their original direction and adding back multi-edges. Finally, show that every homomorphism from q to ch<sub>O</sub>( $\hat{D}$ ) is also a homomorphism from q' to ch<sub>O</sub>(D) and vice versa. We omit details.

We now turn towards the announced construction of the S-database D. Let  $R_0(x_1, y_1), R_1(y_1, y_2), \ldots, R_{\ell-1}(y_{\ell-1}, y_\ell), R_\ell(y_\ell, x_2)$  be the (unique) atoms in q that give rise to the bad path from  $x_1$  to  $x_2$ .

Lemma D.3.  $R_0, \ldots, R_\ell \in S$ .

PROOF. Assume to the contrary of what is to be shown that  $R_i \notin S$  for some  $R_i$ . Since Q is non-empty, there is an S-database  $D_0$  such that  $Q(D_0) \neq \emptyset$  and thus there is a homomorphism  $h_0$  from q to  $ch_O(D_0)$ . Since O is an  $\mathcal{ELI}$  ontology, the restriction of  $ch_O(D_0)$  to  $adom(D_0)$  does not contain any binary facts that use a relation symbol  $R \notin S$ . Since  $R_i \notin S$ ,  $h_0$  must thus map at least one of the variables on the bad path to a null. Since O is an  $\mathcal{ELI}$  ontology,  $ch_O(D_0)$  takes the shape of  $D_0$  with trees without multi-edges and self loops attached to every constant. Since  $h_0$  maps some variable on the bad path to a null and both  $x_1$  and  $x_2$  to  $adom(D_0)$ , there must be two distinct atoms in the bad path that are mapped to a fact that crosses from the database part of  $adom(D_0)$ , into the null part. This is impossible since q is self-join free.

Let  $C = \operatorname{con}(q)$  if  $\operatorname{con}(q)$  is non-empty and  $C = \{\bot\}$  otherwise,  $\bot$  a fresh constant. Moreover, let  $C_{\mathrm{S}} = \{\bot_R \mid R \in \mathrm{S} \text{ binary}\}$  where each  $\bot_R$  is a fresh constant. The active domain of the database Dthat we aim to construct is

$$\operatorname{adom}(D) = P_{M_1} \cup P_{M_2} \cup C \cup C_S$$

and D contains the following facts:

- A(c) for every unary  $A \in S$  and every  $c \in adom(D)$ ;
- For relation symbol *R*<sub>0</sub>:
  - $R_0(a, b)$  for all  $a, b \in [n]$  such that  $M_1(a, b) = 1$ ;
- $R_0(c, c)$  for all  $c \in C \cup C_S$ ;
- For relation symbol  $R_{\ell}$ :
  - $R_{\ell}(a, b)$  for all  $a, b \in [n]$  such that  $M_2(a, b) = 1$ ;
  - $R_{\ell}(c, c)$  for all  $c \in C \cup C_{S}$ ;
- For each relation symbol  $R_i$ ,  $0 < i < \ell$ :
- $R_i(a, a)$  for all  $a \in [n]$ ;
- For each relation symbol  $R \in S \setminus \{R_0, \ldots, R_\ell\}$ :
  - $R(\perp_R, a)$  for all  $a \in [n]$ ;
  - R(a, c), and R(c, c') for all  $a \in [n]$ , and  $c, c' \in C$ .
  - − R(a, a) for all  $a \in [n]$  if q contains reflexive atom R(z, z).

It should be clear that *D* can be constructed in time linear in  $|M_1| + |M_2|$ . Moreover, *D* satisfies the *completeness property* that every  $c \in adom(D)$  has an incoming and an outgoing edge for every  $R \in S$  since  $M_1$  and  $M_2$  satisfy Condition (\*) above. We next show how answers to *Q* on *D* are related to one entries in the matrix product  $M_1M_2$ .

LEMMA D.4. Let  $(a, b) \in [n]^2$ . Then  $M_1M_2(a, b) = 1$  if and only if there is a complete answer  $(a_1, a_2, \ldots, a_k) \in Q(D)$  such that  $a_1 = a$ and  $a_2 = b$ .

**PROOF.** "if". Let  $(a_1, a_2, ..., a_k) \in Q(D)$  so that  $a_1 = a$  and  $a_2 = b$ . Then there is a homomorphism h from q to  $ch_O(D)$  such that  $h(x_1) = a$  and  $h(x_2) = b$ . Consider the image of the path  $R_0(x_1, y_1), ..., R_\ell(y_\ell, x_2)$  under h in  $ch_O(D)$ . We first argue that this image is actually contained in D.

Recall the O is an  $\mathcal{ELI}$  ontology and  $ch_O(D)$  takes the shape of D with trees without multi-edges and self loops attached to each constant. It follows that none of  $h(y_1), \ldots, h(y_\ell)$  is a null as then the image of the path would start at a (in the database part), then cross to the null part and eventually cross back to end at b. But this is not possible because of the described form of  $ch_O(D)$  and since the relation symbols  $R_0, \ldots, R_\ell$  are all distinct (as q is self join free). Since the chase with an  $\mathcal{ELI}$  ontology does not add any facts  $R(c_1, c_2)$  with  $c_1, c_2 \in adom(D)$ , the image of the path must indeed by in D.

Considering the construction of D, it is now easy to see that  $h(y_1) = \cdots = h(y_\ell) = u$  for some  $u \in \{1, \ldots, n\}$ . In particular, note that the only  $R_0$ - and  $R_\ell$ -edges that originate at a constant from [n] also end at a constant from n, and that the relation symbols  $R_i$ ,  $1 \le i < \ell$ , only occur in reflexive facts. Thus, D contains atoms  $R_0(a, u)$ ,  $R_\ell(u, b)$ , which by the definition of D implies that  $M_1(a, u) = 1$  and  $M_2(u, b) = 1$ . Consequently,  $M_1M_2(a, b) = 1$ .

"only if". Let  $M_1M_2(a, b) = 1$ . Then we have  $M_1(a, u) = 1$  and  $M_2(u, b) = 1$  for some u with  $1 \le u \le n$ . Moreover, since Q is not empty, there is a database  $D_0$  and a homomorphism  $h_0$  from q to  $ch_Q(D_0)$  such that  $h_0(x_1), h_0(x_2) \in adom(D_0)$ .

We construct a homomorphism h from q to  $ch_O(D)$ . Start with setting h(c) = c for every constant c in q,  $h(x_1) = a$ ,  $h(x_2) = b$ , and  $h(y_v) = u$  for  $1 \le v \le \ell$ . We also choose a  $c_{\perp} \in C$  and set  $h(x) = c_{\perp}$  for all x such that h(x) was not previously defined and  $h_0(x) \in adom(D_0)$ .

It can be verified that h is a homomorphism from  $q|_h$  to  $ch_O(D)$  where  $q|_h$  is the restriction of q to the domain of h. We first argue that h respects all binary atoms in  $q|_h$  and the consider the unary atoms.

First note that *h* respects all binary atoms that involve any pair of variables  $(x_1, y_1)$ ,  $(y_i, y_{i+1})$  for  $1 \le i < \ell$ , and  $(y_\ell, x_2)$  by construction of *D* and due to (Mult). Reflexive binary atoms on a variable from the bad path are also defined by definition of *D*. There are no atoms that involve other combinations of variables on the bad path such as  $(x, y_2)$  since  $G_q^{\text{var}}$  is a disjoint union of trees. By definition of *D*, it is also clear that all binary atoms are respected that involve only constants and non-path variables for which *h* is defined. Finally, atoms that involve a path variable and a constant or a non-path variable are respected by (Dir) and construction of *D*. Now for the unary atoms A(x). If  $A \in S$ , then A(x) is satisfied since  $A(c) \in D$  for every  $c \in adom(D)$ . Thus let  $A \notin S$ . The completeness property of D implies that  $(D_0, h_0(x)) \leq (D, h(x))$ , no matter what h(x) is. It thus follows from Lemma A.3 that  $D \models (O, S, A(x))(h(x))$ .

We next extend h to all remaining variables in q. Assume that h(t) is defined, q contains an atom that uses term t and variable y, and h(y) is not yet defined. First assume that t is a constant c. Since h(y) is undefined,  $h_0(y)$  is a null. Due to (Dir) and (Mult), q contains a single atom R(y, c) that mentions y and c. Due to the self-join freeness of q,  $h_0$  maps all variables in the subtree of  $G_q^{\text{var}}$  rooted at y to a null, the exact argument for this is similar to the one used in the "if" direction. It follows that the CQ p(z), which is the restriction of q to the variables in the subtree of  $G_q^{\text{var}}$  rooted at y, extended with atom R(y, z), contains no multi-edges and reflexive loops, thus is an ELIQ. The completeness property of D implies that  $(D_0, h_0(z)) \leq (D, h(z))$ , no matter what h(z) is. It thus follows from Lemma A.3 that  $D \models (O, S, p(x))(h(x))$ , and consequently there is a homomorphism g from p(x) to ch<sub>O</sub>(D) with g(x) = h(x).

Now assume that *t* is a variable *z*. Then  $h_0(z)$  is not a null and  $h_0(y)$  is a null. Moreover, *y* is a successor of *z* in the direction that we have imposed on  $G_q^{\text{var}}$  because  $h_0(x_1)$  is non-null (as  $h_0$  witnesses non-emptiness w.r.t. *complete* answers). Due to the self-join freeness of *q*,  $h_0$  maps all variables in the subtree of  $G_q^{\text{var}}$  rooted at *y* to a null. It follows that the restriction p(z) of *q* to *z* and the variables in the subtree of  $G_q^{\text{var}}$  rooted at *y* contains no multi-edges and reflexive loops, thus is an ELIQ. We can proceed as in the case where *t* is a constant.

To finish the proof of Theorem 4.4 we use the following lemma and Claim D.5.

LEMMA D.5. The number of minimal partial answers  $Q(D)^*$  is bounded by  $O(|M_1| + |M_2| + |M_1M_2|)$ .

We can now prove Theorem 4.4 as follows. Assume that there is an algorithm that enumerates set Q(D) (or  $Q(D)^*$  or  $Q(D)^W$ ) in DelayC<sub>lin</sub>. Given matrices  $M_1, M_2$ , we can construct the database Din time  $O(|M_1| + |M_2|)$  and use and enumerate the answers in time  $O(|M_1| + |M_2| + |M_1M_2|)$ , cf. Lemma D.5. Finally, by Lemma D.4, the projection to the first two positions of the enumerated complete answers gives us a list representation of  $M_1M_2$  in total time  $O(|M_1| + |M_2| + |M_1M_2|)$ .

A central ingredient to the proof of Lemma D.5 is the following.

LEMMA D.6. Let h be a homomorphism from q to  $ch_O(D)$ . If there are two distinct answer variables  $x_i, x_j$  such that  $h(x_i), h(x_j) \in [n]$ , then  $\{x_i, x_j\} = \{x_1, x_2\}$ .

**PROOF.** Assume that  $x_i, x_j$  are distinct answer variables such that  $h(x_i), h(x_j) \in [n]$ . Due to the way in which we have oriented the edges in  $G_q^{\text{var}}$ , it must be the case that

(1)  $x_i$  and  $x_j$  are in the same tree in  $G_q^{\text{var}}$  as  $x_1$  and  $x_2$ .

In fact, assume to the contrary that  $x_i$  (or  $x_j$ ) is in a different tree in  $G_q^{\text{var}}$  than  $x_1$  and  $x_2$ . Then since q is connected, q must contain a binary atom that contains a constant c and a variable x from the tree. By the way we have imposed a direction on the trees in  $G_q^{\text{var}}$  and by (Dir), we even find such a *c* and an *x* such that all edges in the tree are oriented away from *x*. Also by (Dir), the edge between *c* and *x* is oriented towards *x*. Thus, there is a directed path in *q* from *c* to  $x_i$ . But there is no such (directed!) path from *c* to a constant in [*n*] in *D*. Since *O* is an  $\mathcal{ELI}$  ontology, the same holds for  $ch_O(D)$ . We have thus shown (\*).

We next observe that since q is connected and since all edges in  $G_q^{\text{var}}$  are oriented away from the roots of the trees, one of the following must hold:

- (2) there is a variable y such that x<sub>i</sub> and x<sub>j</sub> are both reachable in G<sub>a</sub><sup>var</sup> from y on a directed path;
- (3) x<sub>i</sub> and x<sub>j</sub> are in different trees in G<sub>q</sub><sup>var</sup>, but there is a constant c such that x<sub>i</sub> and x<sub>j</sub> are reachable in q from c on a (not necessarily directed) path.

Point (3), however, is ruled out by Point (1). We are thus left with Point (2). Consider the combined path from  $x_i$  to y to  $x_j$ . Since q is self-join free, all relation symbols on this path are distinct. Now take the image under h of the path in  $ch_O(D)$ . It starts and ends at a constant in [n]. Moreover, (i) the edge from  $x_i$  to the next variable y on the path must be directed towards  $x_i$  or (ii) the edge from the variable z before  $x_j$  on the path to  $x_j$  must be directed towards  $x_j$ . We only consider Case (i) as Case (ii) is completely symmetric.

In Case (i), the construction of *D* implies that h(y) can only be a null or of the form  $\perp_R$ . First assume the former. Then the *h*-image of the path crosses from the database part of  $ch_O(D)$  to the null part and eventually back to reach  $h(x_j) \in [n]$ . But since *O* is an  $\mathcal{ELI}$  ontology, the shape of  $ch_O(D)$  is that of *D* with trees without multi-edges and reflexive loops attached to each constant from adom(D). Thus, there is no path in  $ch_O(D)$  of the described form in which no relation symbol occurs twice.

Now assume that h(y) is of the form  $\perp_R$ . Then the *h*-image of the path starts at a constant of [n], then reaches a constant of the form  $\perp_R$ , and eventually again a constant of the form [n]. But by construction *D* contains no path of this form on which no relation symbol occurs twice. Since *O* is an  $\mathcal{ELI}$  ontology, the same is true for ch<sub>*O*</sub>(*D*).

PROOF OF LEMMA D.5. Let  $\bar{a} = (a_1, a_2, ..., a_k) \in Q(D)^*$  be a partial answer. By Lemma D.6, either  $\bar{a} \cap [n] = \{a_1, a_2\}$  or there is at most one value from [n] in  $\bar{a}$ , i.e.  $\{a\} = \bar{a} \cap [n]$  for some a.

In the former case, we observe that for every variable  $x_i$ ,  $1 \le i \le k$ , such that  $a_i \ne a$ , the value  $a_i$  can be chosen from at most  $|C|+|C_{\rm S}|+1$  possibilities. Since *k* is a fixed constant depending only on the query, we have  $O(|M_1| + |M_2|)$  answers of the former kind. Similarly, by Lemma D.4 we can conclude that the number of answers satisfying the latter case is bounded by  $O(|M_1M_2|)$ . Indeed, the number of possible pairs  $(a_1, a_2)$  is  $|M_1M_2|$  and the remaining undefined values in  $\bar{a}$  are chosen from a set of size O(|q|). This ends the proof the lemma.

We analyse separately the minimal partial answers  $(a_1, a_2, ..., a_k) \in Q(D)^*$  such that  $a_i \in [n]$  for some i > 2 and those for which  $a_i \in [n]$  only if  $i \in \{1, 2\}$ .

For answers of the former kind, Lemma D.6 implies that  $a_j \notin [n]$  for all  $j \in \{1, \ldots, i-1, i+1, k\}$ . Consequently, the number of answers of this kind is bounded by  $O(|M_1| + |M_2|)$ .

Now for answers of the latter kind. In this case, there are only constantly many choices for  $a_3, \ldots, a_k$  as we have at most  $|C|+|C_S|$ 

different possibilities for indices in  $i \in \{3, ..., k\}$ , and k is a constant. We may further distinguish between answers where at most one of  $a_1, a_2$  is from [n] and where both are. Due to the limited number of possible choices for  $a_3, ..., a_k$ , the number of answers of the former kind is bounded by  $O(|M_1| + |M_2|)$  and Lemma D.4 implies that the number of answers of the latter kind is bounded by  $O(|M_1M_2|)$ . This ends the proof of the conditional lower bound.

We give some remarks on (im)possible generalizations of Theorem 4.4. Replacing  $\mathbb{BLI}$  with  $\mathbb{G}$  in Theorem 4.4 would allow us to also remove 'self-join free' from Theorem 4.4, as in Example 3.5. But there are CQs (with self-joins) that are acyclic and not freeconnex acyclic, yet their answers can be enumerated in CDoLin (without ontologies) [11].

PROPOSITION 4.5. There is an  $OMQQ \in (\mathbb{ELI}, \mathbb{CQ})$  that is acyclic, non-empty, self-join free, but neither free-connex acyclic nor connected, such that complete answers to Q can be enumerated in  $DelayC_{lin}$ .

PROOF. Let

$$O = \{A_1(x) \to A_2(x), B_1(x) \to B_2(x), C_1(x) \to C_2(x)\}$$
  

$$S = \{A_1, B_1, C_1, L, R\}$$
  

$$q(x_1, z_1, x_2, y_2, z_2) = L(x_1, y_1) \land R(y_1, z_1) \land$$
  

$$A_1(x_1) \land B_1(y_1) \land C_1(z_1) \land$$
  

$$A_2(x_2) \land B_2(y_2) \land C_2(z_2).$$

Note that Q = (O, S, q) satisfies all properties listed in Proposition 4.5. We argue that complete answers to Q can be enumerated in DelayC<sub>lin</sub>. The idea is that the additional answer variables  $x_2, y_2, z_2$  enlarge the answer set, which gives additional computational power in the enumeration phase of the algorithm.

To make this precise, let *D* be an S-database and, by slight abuse of notation,  $A = \{c \in adom(D) \mid A(c) \in D\}$  for every unary relation symbol *A*, and |A| the size of set *A*. It is clear that  $Q(D) = p(D) \times A_1 \times B_1 \times C_1$  where

$$p(x_1, z_1) = L(x_1, y_1) \land R(y_1, z_1) \land A_1(x_1) \land B_1(y_1) \land C_1(z_1).$$

Since *q* is acyclic, we can find an answer  $(a_1, c_1, a_2, b_2, c_2) \in Q(D)$  in linear time during the preprocessing phase. In fact, we can compute  $ch_O(D)$  in linear time since the chase only needs to add unary relation symbols to existing constants, and then use the standard Yannakakis algorithm to find an answer to *q* on  $ch_O(D)$ . This actually reveals the  $|A_1| \cdot |B_1| \cdot |C_1|$  distinct answers in the set  $U = \{a_1\} \times \{c_1\} \times A_1 \times B_1 \times C_1$ . Now, while the algorithm enumerates the answers in *U* with constant delay, it can in parallel compute the set p(D) by simply checking all possible triples  $(a_1, b_1, b_2) \in A_1 \times B_1 \times C_1$ . After finishing the enumeration of *U*, it is then easy to enumerate the remaining answers with constant delay.

### D.3 Proof of Theorem 4.6

THEOREM 4.6. Let  $Q \in (\mathbb{ELI}, \mathbb{CQ})$  be non-empty and self-join free. If Q is not free-connex acyclic, then all-testing complete answers for Q is not in linear time unless the triangle conjecture fails or Boolean  $n \times n$  matrices can be multiplied in time  $O(n^2)$ . The same is true for minimal partial answers and minimal partial answers with multiple wildcards.

Let  $Q(\bar{x}) = (O, S, q)$ , and let  $\hat{q}(\bar{x})$  be the CQ obtained from q by adding an atom  $R(\bar{x})$  with R a fresh relation symbol. Since Q is not acyclic free-connex  $\hat{q}$  is not acyclic.

We observe the following consequence of Theorem D.2.

CLAIM D.3. There is a chordless cycle  $y_1, y_2, \ldots, y_\ell$  in  $G_{\hat{q}}$  that has no repeated vertices and no more than two answer variables.

Since  $\hat{q}$  is not acyclic, it is not conformal or not chordal. If it is not conformal, then there is a clique not contained in an atom. This clique has to have at least 3 vertices, since every clique of size 2 is an edge, and at least one quantified variable, as the clique of all answer variables is induced by the atom  $R(\bar{x})$ . To obtain the cycle, choose a triangle that contains this quantified variable.

If  $\hat{q}$  is not chordal, then there is a chordless cycle of length at least 4. Every such cycle has no more than two answer variables, as there is an edge between every two answer variables.

We distinguish three cases according to the number of answer variables in the cycle.

No answer variables in the cycle. If no variable in  $y_1, \ldots, y_\ell$  is an answer variable, then there is a cycle in q and, thus, q is not weakly acyclic.

Clearly, an algorithm for all-testing for Q in DelayC<sub>lin</sub> can be used to implement single-testing for Q in linear time. Thus, Theorem3.4 implies that the triangle conjecture fails.

One answer variable in the cycle. Without loss of generality, we can assume that  $x_1 = y_1$  is the single answer variable in the cycle  $y_1, \ldots, y_\ell$ . Hence the query  $q_0$  obtained from q by making  $x_1$  a quantified variable is not weakly acyclic.

If all-testing for Q is possible in  $\mathsf{DelayC}_{\mathsf{lin}}$ , then single-testing for  $Q_0 := (O, \mathsf{S}, q_0)$  is possible in linear time: given a candidate answer  $\bar{a}$  to  $Q_0$  on an S-database D, we use the all-testing algorithm to decide whether  $b\bar{a} \in Q(D)$  for any  $b \in \mathsf{adom}(D)$ , in overall linear time. By Theorem 3.4, this implies that the triangle conjecture fails.

Two answer variables in the cycle. We assume that  $x_1 = y_1$  and  $x_2 = y_\ell$  are the two answer variables in the cycle  $y_1, \ldots, y_\ell$ , it shall be clear how the proof can be adapted if the answer variables are located elsewhere on the cycle. We show that if all-testing for Q is in DelayC<sub>lin</sub>, then given the two  $n \times n$  Boolean matrices  $M_1, M_2$  we can compute  $M_1M_2$  in time  $O(n^2)$ .

We use a construction similar to that in the proof of Theorem 4.3. However, since Q may not be acyclic the construction needs to be suitably adapted.

As shown in proof of Theorem 4.4 we can assume that both  $M_1$  and  $M_2$  have 1 in every row and in every column. Also, we make the following observation.

CLAIM D.4. If R(x, y) is an atom in q where x and y are variables in the cycle  $y_1, \ldots, y_\ell$  then  $R \in S$ .

The proof follows the same pattern as the proof of Lemma D.3.

The active domain of the database *D* that we aim to construct is  $adom(D) = [n] \cup con(q)$  and *D* contains the following facts:

Technical Report, arXiv version, 2022

- A(c) for every unary  $A \in S$  and every  $c \in adom(D)$ ;
- for every relation symbol  $R \in S$  we add facts:
  - R(a, b) for all  $a, b \in [n]$  such that  $M_1(a, b) = 1$ , if  $R(x_1, y_2)$  is an atom in q;
  - R(b, a) for all  $a, b \in [n]$  such that  $M_1(a, b) = 1$ , if  $R(y_2, x_1)$  is an atom in q;
  - R(a, b) for all  $a, b \in [n]$  such that  $M_2(a, b) = 1$ , if  $R(y_{\ell-1}, x_2)$  is an atom in q;
  - $R(b, a) \text{ for all } a, b \in [n] \text{ such that } M_1(a, b) = 1,$ if  $R(x_2, y_{\ell-1})$  is an atom in q;
  - $\begin{array}{l} R(a,a) \text{ for all } a \in [n], \\ \quad \text{ if } R(y_i,y_{i+1}) \text{ is an atom in } q \text{ with } 2 \leq i \leq \ell-2; \end{array}$
  - R(a, b) for all  $a, b \in adom(D)$ ,

if R(x, y) is an atom in q and x and y are not both in the cycle;

- R(c, c) for every  $c \in \operatorname{con}(q)$ .

The database *D* can be constructed in time  $O(n^2)$ . Moreover, for every relation symbol  $R \in S$  and every element  $c \in adom(D)$  there are *a*, *b* such that  $R(a, c), R(c, b) \in D$ . Thus, as before, we will be able to extend a partial homomorphism from *q* to *D* to the atoms whose relation symbols are not present in the schema.

To end the reduction it is enough to show the following.

Claim D.5. Let  $(a, b) \in [n]^2$ . Then  $(a, b, 1, \dots, 1) \in Q(D)$  iff  $M_1M_2(a, b) = 1$ .

Indeed, assume that all-testing complete answers for Q is in  $\text{DelayC}_{\text{lin}}$ . Then given two matrices  $M_1, M_2$ , we can compute  $M_1M_2$  in time  $O(n^2)$  by first computing the database D in time  $O(n^2)$ , then executing the preprocessing phase of the all-testing algorithm in time linear in ||D||, which is  $O(n^2)$ , and finally testing the tuple  $(a, b, 1, \ldots, 1)$  for every pair  $(a, b) \in [n]^2$ .  $M_1M_2$  is the set of all pairs (a, b) for which the test succeeded.

All that is left is to prove the claim. The " $\Rightarrow$ " is proven the same way as in Lemma D.4. For the other direction we cannot use the proof of Lemma D.4 as the CQ may not be acyclic. We thus do the following. First, we define *h* only on  $\bar{x}$  so that  $h(\bar{x}) = (a, b, 1, ..., 1)$ . Then we argue as in the proof of Theorem 3.4 that it can be extended to a homomorphism *h* from *q* to ch<sub>*Q*</sub>(*D*). Details are left to the reader.

For the cases of minimal partial answers and minimal partial answers with multiple wildcards, recall that  $Q(D) \subseteq Q(D)^*$  and  $Q(D) \subseteq Q(D)^W$ . Thus, both the construction and the algorithm work with no modifications.

# **E PROOFS FOR SECTION 5**

THEOREM 5.1. There is an  $OMQQ \in (\mathbb{ELI}, \mathbb{CQ})$  that is acyclic and free-connex acyclic such that all-testing minimal partial answers to Q is not in  $DelayC_{lin}$  unless the triangle conjecture fails. The same is true for minimal partial answers with multiple wildcards.

PROOF. We start with showing the result for  $(\mathbb{G}, \mathbb{CQ})$  in place of  $(\mathbb{ELI}, \mathbb{CQ})$ . Let *R* be a binary relation symbol and  $S = \{R\}$ . We may view an undirected graph G = (V, E) as the S-database

$$D_G = \{ R(v, v'), R(v', v) \mid \{v, v'\} \in E \}.$$

Consider the OMQ  $Q(x) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  where O contains the TGD

 $R(x_1, x_2) \rightarrow \exists y_1 \exists y_2 R\{x_1, y_1\} \land R\{y_1, y_2\} \land R\{y_2, x_1\}$ 

with  $R{x, y}$  an abbreviation for  $R(x, y) \land R(y, x)$  and with

$$q(x, y, z, u) = R\{x, y\} \land R\{y, z\} \land R\{z, u\}$$

Let G = (V, E) be an undirected graph. Then (v, \*, \*, v) is a partial answer to Q on  $D_G$  for every  $v \in V$ , but not necessarily a minimal partial answer. In fact, it is a minimal partial answer if and only if v is not part of a triangle in G. It follows that all-testing for Q is not in DelayC<sub>lin</sub> unless the triangle hypothesis fails: to decide whether a given graph G = (V, E) contains a triangle, we can construct  $D_G$ in time linear in ||E||, then execute the preprocessing phase of alltesting for Q, and then iterate over all  $v \in V$  and test in constant time whether  $(v, *, *, v) \in Q(D)^*$ . We answer 'no' if this is the case for all v and 'yes' otherwise. The same arguments work in the multi-wildcard case, with (v, \*, \*, v) replaced by  $(v, *_1, *_1, v)$ .

The challenge in improving the construction to  $\mathbb{ELI}$  is that  $\mathcal{ELI}$  TGDs cannot introduce a triangle that consists of nulls. The solution is to construct q, O, and D in a more careful way. Let us start with q, which is now

$$q(x_1, x_2, x_3, x_4, x_5) = R(x_1, x_2) \land R(x_2, x_3) \land R(x_4, x_3) \land R(x_5, x_4),$$

that is, it is a path of length 4 rather than of length 3 and the direction of the edges is chosen carefully. We choose O to contain the  $\mathcal{ELI}$  TGD

$$R(x_1, x_2) \rightarrow \exists y_2 \exists y_3 R(x_1, y_2) \land R(y_2, y_3).$$

Similarly to before, (v, \*, \*, \*, v) is a partial answer to Q on any Sdatabase D such that every constant in D has an outgoing R-edge (in the multi-wildcard case, we use  $(v, *_1, *_2, *_1, v)$ . It remains to modify  $D_G$  so that  $q(D_G)$  contains a tuple  $(c_1, c_2, c_3, c_4, c_5)$  with  $c_1 = c_5$  if and only if G = (V, E) contains a triangle (as this makes at least one of the partial answers be not a minimal partial answer). This is achieved by constructing  $D_G$  so that  $adom(D_G) = V \times [4]$ and it contains the following facts, for each  $\{v, v'\} \in E$ :

$$R((v, 1), (v', 2)), R((v, 2), (v, 3)), R((v', 4), (v, 3)), R((v', 1), (v, 4)).$$

To finish the proof, it suffices to observe the following.

CLAIM.  $q(D_G)$  contains a tuple  $(c_1, c_2, c_3, c_4, c_5)$  with  $c_1 = c_5$  iff G contains a triangle.

For the "if" direction, assume that  $v_1, v_2, v_3$  is a triangle in G. Then the tuple

$$((v_1, 1), (v_2, 2), (v_2, 3), (v_3, 4), (v_1, 1))$$

is in  $q(D_G)$ .

"only if". Assume that  $q(D_G)$  contains a tuple  $(c_1, c_2, c_3, c_4, c_5)$ with  $c_1 = c_5$ . Consider  $c_3$ . Only constants of the form  $(v_1, 2)$  and  $(v_1, 4)$  have both incoming and outgoing *R*-edges in  $D_G$ , so  $c_2$ must be of one of these forms. Assume that  $c_2 = (v_1, 2)$ , the case  $c_2 = (v_1, 4)$  is symmetric. The construction of  $D_G$  yields the following. We must have  $c_3 = (v_1, 3)$ . The fact  $R(c_4, (v_1, 3)) \in D_G$ was introduced due to some edge  $\{v_2, v_1\} \in E$  and  $c_4$  must be of the form  $(v_2, 4)$ . The fact  $R(c_1, (v_1, 2)) \in D_G$  was introduced due to some edge  $\{v_3, v_1\} \in E$  and  $c_1$  must take the form  $(v_3, 1)$ ; likewise, the fact  $R(c_5, (v_2, 4))$  was introduced due to some edge

Lutz and Przybyłko

 $\{v_4, v_1\} \in E$  and  $c_5$  must take the form  $(v_4, 1)$ . Since  $c_1 = c_5$ , it follows that  $v_3 = v_4$ . Thus, the nodes  $v_1, v_2, v_3$  constitute a triangle in G. 

#### E.1 Missing Details for Proof of Theorem 5.2

In the main part of the paper, we have declared the goal to be the enumeration of  $q_0(\mathsf{ch}_Q^{q_0}(D))^*_N$ . Here, we actually prove something slightly more general (based on exactly the algorithm presented in the main part), as follows.

**PROPOSITION E.1.** For every CQ  $q(\bar{x})$  that is acyclic and free-connex ayclic, enumerating the answers  $q(D)_{N}^{*}$  is in  $\mathsf{DelayC}_{\mathsf{lin}}$  for databases D and sets of nulls  $N \subseteq adom(D)$  such that D is chase-like with witness  $D'_1, \ldots, D'_n$  where  $|\mathsf{adom}(D'_i)|$  does not depend on D for  $1 \le i \le i \le n$ n.

To prove Proposition E.1, let  $q_0(\bar{x})$  be a CQ that is acyclic and free-connex acyclic,  $D_0$  a database over the same schema as  $q_0$  that is chase-like with witness  $D'_1, \ldots, D'_n$  where  $|\mathsf{adom}(D'_i)|$  does not depend on *D* for  $1 \le i \le n$ . Note that this notation is completely compatible with the one used in the main part of the paper, only that there  $D_0$  is the concrete chase-like database  $ch_{\mathcal{O}}^{q_0}(D)$ .

We first note that we can assume w.l.o.g. that the tuple  $\bar{x}$  has no repeated variables and that  $q_0$  contains no constants. In fact, answer enumeration in the general case can be reduced in time linear in  $||D_0||$  to answer enumeration in this restricted case. We give the reduction for removing constants. For every atom  $R(\bar{t})$  in  $q_0$  where  $\bar{t}$  contains at least one constant, introduce a fresh relation symbol  $R_{\overline{t}}$  whose arity is the number of positions in  $\overline{t}$  that have a variable. Then replace  $R(\bar{t})$  in  $q_0$  with  $R_{\bar{t}}(\bar{y})$  where  $\bar{y}$  is obtained from  $\bar{t}$  by removing all constants. Furthermore, for each fact  $R(\bar{c})$ in  $D_0$  such that each constant *c* that occurs in some position *i* of  $\overline{t}$ also occurs in position *i* of  $\bar{c}$ , add to  $D_0$  the fact  $R_{\bar{t}}(\bar{c}')$  where  $\bar{c}'$  is obtained from  $\bar{c}$  by removing the constants in the positions where  $\overline{t}$  has a constant.

We can also assume  $q_0$  to be connected. For assume that we have found an enumeration algorithm for connected CQs that runs in  $\mathsf{DelayC}_{\mathsf{lin}}$ . We can then enumerate  $q_0(D_0)^*_{\mathsf{N}}$  in  $\mathsf{DelayC}_{\mathsf{lin}}$  when  $q_0$ has maximal connected components  $p_0, \ldots, p_k, k > 0$ , in the following way. We first do preprocessing for all  $p_0, \ldots, p_k$ . We then start an algorithm that enumerates the answers to  $p_0$ . After the first answer was found, it calls the enumeration algorithm for  $p_1$ , which upon finding an answer calls the enumeration algorithm for  $p_2$ , and so on. Only when the innermost algorithm found an answer to  $p_k$ , the answers are combined and output as an answer to *Q*. Note the algorithms for  $p_1, \ldots, p_k$  have to start from scratch multiple times which is problematic since the data structures computed in the preprocessing phase are modified in the enumeration phase and we cannot repeat preprocessing because that would introduce a linear time delay into the enumeration phase. An easy solution is as follows. When first enumerating the answers to  $p_k$ , we store all of them in the form of a linked list. When we need to enumerate the answers to  $p_k$  again, we can just use that list without any preprocessing. We do the same for the subqueries  $p_{k-1} \cup p_k$ ,  $p_{k-2} \cup p_{k-1} \cup p_k$ , and so on, which fixes the problem. The above argument requires a polynomial amount of memory during the enumeration phase. There is, however, an alternative approach that

avoids this. Our algorithm is such that the data structure S computed in the preprocessing phase is modified in the enumeration phase, resulting in a data structure S'. However, S' is such that it could have been used in place of S after the preprocessing phase without affecting the output of enumeration. This means that the preprocessing can simply be skipped before restarting the enumeration algorithm for a connected subquery.

Recall that from CQ  $q_0(\bar{x})$  and database  $D_0$ , we have to construct a CQ  $q_1(\bar{x})$  and a database  $D_1$  that satisfy Conditions (i) to (iv) from the main part of the paper. Note that Condition (ii) implies that  $D_1$  is chase-like with a witness  $D'_1, \ldots, D'_n$  (not necessarily the same as for  $D_0$  such that  $|\mathsf{adom}(D'_i)|$  does not depend on *D* for  $1 \le i \le n$ . he construction of  $q_1$  and  $D_1$  has been used many times in the context of enumerating answers to conjunctive queries (without ontologies) with constant delay. We give a rouch sketch and refer the interested reader to [11] for a very clear exposition of the details. Exploiting that  $q_0$  is acyclic and free-connex acyclic, it is possible to first construct a generalized hypertree decomposition (GHD) of  $q_0$  of width 1 in which the answer variables constitute a connected ('connex') prefix. Then a bottom-up pass over the GHD is made, manipulating both  $q_0$  and  $D_0$  in a synchronized way. In particular, one introduces a fresh relation symbol for each node of the GHD and duplicates facts in the database accordingly, thus achieving self-join freeness. Moreover, one achieves the progress condition by dropping facts from the database that violate it. This also turns the GHD into a join tree. Finally, the quantified variables can simply be dropped because the progress condition has already been achieved. If  $q_0(D_0)$  is empty, then we find this out during the construction of  $q_1$  and  $D_1$  as then all facts from the database that use the relation symbol from the root of the GHD have been dropped. We then return 'end of enumeration'. The construction only needs time linear in  $||D_0||$ .

LEMMA 5.3. The lists trees (v, h), for all relevant v and h, can be computed in overall time linear in  $||D_1||$ . Moreover, all these lists are non-empty.

**PROOF.** Recall that  $D_1$  is chase-like with witness  $D'_1, \ldots, D'_n$ . We iterate over i = 1, ..., n. For each i, set  $S = adom(D'_i) \setminus N$  and iterate over all pairs (q, g) with q a subtree of  $q_1$  and g:  $var(q) \rightarrow$  $S \cup \{*\}$ . Note that there are only constantly many such pairs: since the OMQ is fixed, there are only constantly many subtrees q of  $q_1$ , and the arity of relations in schema S is bounded by a constant; since S is a guarded set in  $D'_i$  (by definition of chase-likeness), it follows that the cardinality of S is bounded by a constant as well, implying that the same is true for the number of maps *q*.

We disregard pairs such that Conditions (1) or (2) of progress trees is violated. Note that this can clearly be checked in constant time, and that Condition (4) is in fact satisfied by choice of g. We then check whether there is a homomorphism  $\widehat{g}$  from q to  $D'_i$  such that for all  $x, y \in var(q)$ ,

- $\widehat{g}(x) \in N$  if g(x) = \* and  $\widehat{g}(x) = g(x)$  otherwise;  $\widehat{g}(x) = h(y)$  iff g(x) = g(y).

If this is not the case, we disregard (q, g). Otherwise, Condition (3) of progress trees is satisfied. Note that we can check the existence of *h* brute force as there are only constantly many potential targets because  $|\mathsf{adom}(D'_i)|$  does not depend on *D*. We then add (q, q) to trees(v, h) where v is the root of q and h is the restriction of g to the predecessor variables in v.

Regarding the correctness of this construction, there are two important observations. The first is that we really generate all progress trees despite considering only homomorphisms  $\hat{g}$  into the databases  $D'_i$  instead of into  $D_1$  as a whole, as required by Condition (3) of progress trees. This is guaranteed by the following claim.

CLAIM. Let (q, g) be a progress tree and let h be a homomorphism from q to  $D_1$  such that for all  $x \in var(q)$ ,  $h(x) \in N$  if g(x) = \* and h(x) = g(x) otherwise. Then h is a homomorphism from q to  $D'_i$ for some  $i \in \{1, ..., n\}$ .

*Proof of claim.* Let  $v_0 = R_0(\bar{y}_0)$  be the root of  $T_q$ . Then clearly there is an *i* such that  $R_0(h(\bar{y}_0)) \in D'_i$ . We show that *h* is a homomorphism from *q* to  $D'_i$ .

More precisely we prove by induction on the depth of v in  $T_q$  that that for all  $v = R(\bar{y}) \in V_q$ ,  $R(h(\bar{y})) \in D'_i$ . The induction start is trivial by choice of  $D'_i$ . So let  $v \in V_q$  be a non-root node. By Condition (2) of progress trees, v contains a predecessor variable x with g(x) = \*. Thus  $h(x) \in N$ . Let  $v' = R'(\bar{y}')$  be the predecessor of v in  $T_q$ . By induction hypothesis,  $R'(h(\bar{y}')) \in D'_i$ . Since by definition of 'chase-like'  $\operatorname{adom}(D'_i) \cap \operatorname{adom}(D'_j) \cap N = \emptyset$ , this and  $h(x) \in N$  yields  $R(h(\bar{y})) \in D'_i$ , as required. This finishes the proof of the claim.

The second observation is that we must be careful to avoid duplicates as the same (q, g) can be constructed for  $D_i$ ,  $D'_j$  with  $i \neq j$ , when  $adom(D'_i) \setminus N$  and  $adom(D'_j) \setminus N$  overlap. To identify duplicates, we use a lookup table that stores a Boolean value for every progress tree (q, g), indicating whether we have already seen this tree or not. Note that a progress tree (q, g) can essentially be represented by a list of constants from  $adom(D_1)$  of constant length, and by the remarks on RAMs under the uniform cost model in Section 2 we can access and modify such a table in constant time.

It remains to sort the lists trees(v, h), each of which is of length  $O(|\mathsf{adom}(\mathcal{D}_1)|)$ , into the desired order in overall linear time. Recall from Section 2 that sorting a list of short lists equipped with a strict weak order is possible on a RAM in linear time. Now, a progress tree (q, g) is essentially a short list. We can use q as the first element of the list (only constantly many choices), fix a total order  $z_1, \ldots, z_\ell$  on the variables in q, and use  $g(z_1), \ldots, g(z_\ell)$  as the remaining list. A strict weak order on progress trees is then defined by ' $\prec_{db}$ '. If we now sort the progress trees in trees(v, h) viewed as short lists, then we attain the required order, that is,  $(q,g) \prec_{db} (q',g')$  implies that (q,g) occurs before (q',g') in the list. There are linearly many lists trees(v, h) to be sorted, each in linear time, but we still attain overall linear time since each progress tree occurs in only one list and thus the total number of items to be sorted (across all lists) is bounded by  $O(||D_1||)$ .

It remains to prove the 'moreover' part. Let v and h be relevant. We have to show that there is a progress tree (q, g) with root v such that  $g(\bar{z}) = h(\bar{z})$ . We build this tree together with a homomorphism h' that witnesses Point (3) of the definition of progress trees. We start with q consisting only of the single node v. Since v and h are relevant, h extends to a homomorphism from v to  $D_1$ . We use this homomorphism both for (the initial) g and h'. We then exhaustively extend q, g, and h' as follows. If v' is an atom in q such that g maps at least one variable in v' to '\*' and v'' is a successor of v in  $T_1$ , then include v' in q. By the progress condition, we can extend the homomorphism h' to the extended q. Extend g accordingly, using '\*' in place of null constants. It can be verified that Conditions (1) to (4) of progress trees are satisfied. In particular, Condition (4) is: due to the shape of chase-like databases and since  $q_1$  is connected, all constants in the range of g are from the guarded set  $h(\bar{x})$ , with  $\bar{x}$  the variables in v.

LEMMA 5.4. None of the lists trees(v, h), with v, h relevant, ever becomes empty.

PROOF. Assume to the contrary that some list trees(v, h), with v, h relevant, becomes empty when prune(h') is called. Assume that among the progress trees removed during this call, (q,g) is a minimal progress tree regarding '<<sub>db</sub>'. Since (q,g) was still on trees(v, h) before the call prune(h'), no progress tree (q',g') with  $(q',g') <_{db} (q,g)$  was removed in any previous pruning step. To obtain a contradiction, it thus suffices to argue that the initial list trees(v, h) contains a progress tree (q',g') with  $(q',g') <_{db} (q,g)$ .

We extract the tree (q', g') from h'. Let  $q' \subseteq q_1$  be smallest so that  $v \in q'$  and if  $u \in q'$  and u' is a successor of u in  $T_1$  such that  $h(x) \in N$  for at least one predecessor variable in u', then  $u' \in q'$ . We define q' to be h' restricted to the variables in q'.

Note that we must have  $q' \subseteq q$ . If this is not the case, in fact, then by definition of q' and since q is a progress tree, there is an atom uin q such that g maps all predecessor variables in u to  $\operatorname{adom}(D_1)$ while g' maps at least one predecessor variable in u to '\*'. But this implies that the test ' $(q,g) >_{db} (q,h'|_{\operatorname{var}(q)})$ ' made in  $\operatorname{enum}(h')$ fails, in contradiction to (q,g) being removed during that call.

If  $q' \subsetneq q$ , then  $(q',g') <_{db} (q,g)$  and we are done. Otherwise, however, the test  $(q,g) >_{db} (q,h'|_{var(q)})$ ' made in enum(h') guarantees that Conditions (a)-(d) from the definition of  $(<_{db})$  are satisfied for (q',g') and (q,g), thus again  $(q',g') <_{db} (q,g)$ .  $\Box$ 

We now work towards a proof of Proposition 5.5. Every partial answer  $\bar{a}^*$  to  $q_1$  on  $D_1$  can be seen as a map  $h_{\bar{a}^*}$  :  $var(q_1) \rightarrow$  $(adom(D_1) \setminus N) \cup \{*\}$  in an obvious way and vice versa. Let  $\bar{a}^*$  be a partial answer. We say that a progress tree (q, g) is *realized* in  $\bar{a}^*$ if  $h_{\bar{a}^*}(x) = q(x)$  for all  $x \in var(q)$ .

LEMMA E.2. Without pruning, the algorithm outputs the (not necessarily minimal) partial answers to  $q_1$  on  $D_1$ , without repetition. Moreover, the enumeration order respects '<', that is, if partial answer  $\bar{a}^*$  is output before partial answer  $\bar{b}^*$ , then  $\bar{b}^* \not\prec \bar{a}^*$ .

**PROOF.** Let  $\bar{a}^*$  be a partial answer to  $q_1$  on  $D_1$ . We argue that there is a path in the recursion tree generated by the initial call enum(nextat<sub> $h_0$ </sub>( $v_0$ )) that leads to  $\bar{a}^*$  being output. This path can be identified by choosing, for each call enum(v, h), a recursive call made during it that identifies the successor on the path. Let enum(v, h) be such a call, and let  $h_{\bar{a}^*}(v) = R(\bar{c})$ . Using Condition (2) of progress trees, it can be shown in a straightforward way that the algorithm satisfies the following invariant:

(\*) In each call enum(v', h'), all predecessor variables in v' are mapped to database constants.

Hence, the same is true for all predecessor variables  $\overline{z}$  in v. We identify a candidate tree  $(q, g) \in \text{trees}(v, h|_{\overline{z}})$  as outlined after the

definition of candidate trees. More precisely, choose  $V_q \subseteq V_1$  to be the smallest set that contains v and such that if  $u \in V_q$  and u' is a successor of u in  $T_1$  such that  $h_{\bar{a}^*}(x) = *$  for at least one predecessor variable in u', then  $u' \in V_q$ . This defines a subtree qof  $q_1$ , and for g the restriction of  $h_{\bar{a}^*}$  to the variables in q, it can be verified that  $(q,g) \in \text{trees}(v,h|_{\bar{z}})$ . This identifies the recursive call made during enum(v, h) that we follow on the path towards the output of  $\bar{a}^*$ . It can be verified that the map h built up on this path is exactly  $h_{\bar{a}^*}$ , and thus  $\bar{a}^*$  is indeed output at the end of the path.

Now assume that the algorithm outputs a tuple  $\bar{a}^*$  and let  $h_{\bar{a}^*}$ :  $\operatorname{var}(q_1) \to (\operatorname{adom}(D_1) \setminus N) \cup \{*\}$  be the associated map. We argue that we can obtain from  $h_{\bar{a}^*}$  a homomorphism h from  $q_1$  to  $D_1$  such that for all  $x \in \overline{x}$ , (i)  $h_{\overline{a}^*}(x) \in \text{adom}(D_1)$  implies  $h(x) = h_{\overline{a}^*}(x)$ and (ii)  $h_{\bar{a}^*}(x) = *$  implies  $h(x) \in N$ . Consequently,  $\bar{a}^*$  is a partial answer to  $q_1$  on  $D_1$ . Let enum $(v_0, h_0), \ldots$ , enum $(v_{\ell-1}, h_{\ell-1})$  be the sequence of recursive calls that led to the output of  $\bar{a}^*$  (during the last call). Note that  $v_0, \ldots, v_{\ell-1}$  are not necessarily all nodes of  $V_1$ due to the use of progress trees and nextat. We define a sequence of partial mappings  $h'_0 \subseteq \cdots \subseteq h'_{\ell}$  from  $var(q_1)$  to  $adom(D_1)$  that for all  $x \in var(q_1)$  on which they are defined satisfy Conditions (i) and (ii). Then  $h'_{\ell}$  will be a total function and thus the desired homomorphism h from  $q_1$  to  $D_1$ . Start with setting  $h'_0 = \emptyset$ . Now assume that  $h'_i$  is already defined and consider the recursive call enum $(v_i, h_i)$ . By definition of the algorithm, there is a progress tree  $(q, q) \in \text{trees}(v_i, h_i | \overline{z})$ , with  $\overline{z}$  the predecessor variables of  $v_i$ , such that  $h_{\bar{a}^*}(z) = g(z)$  for all  $z \in var(q)$ . By Property (3) of progress trees, there is a homomorphism g' from q to  $D_1$  such that for all  $x \in var(q), g'(x) \in N$  if g(x) = \* and g'(x) = g(x) otherwise. We define  $h'_{i+1} = h'_i \cup g'$ . It can be verified that the map  $h = h'_{\ell}$  is indeed the desired homomorphism from  $q_1$  to  $D_1$ .

We next argue that there are no repetitions. Consider again the recursion tree generated by the initial call enum(nextat<sub> $h_0</sub>(v_0)$ , and</sub> consider two paths in the tree that lead to the output of partial answers  $\bar{a}_1^*$  and  $\bar{a}_2^*$ . Let enum(v, h) be the call in which the two paths diverge, that is,  $h_{\bar{a}_1^*}$  and  $h_{\bar{a}_2^*}$  both agree with h on the variables on which *h* is defined, but during the call enum(v, h) the two paths follow recursive calls made for different  $(p_1, g_1), (p_2, g_2) \in$ trees( $v, h|_{\bar{z}}$ ). We argue that then,  $h_{\bar{a}_1^*}$  and  $h_{\bar{a}_2^*}$  must also be different, and thus so are  $\bar{a}_1^*$  and  $\bar{a}_2^*$ . This is clear if  $p_1 = p_2$  as this implies  $g_1 \neq g_2$  and h is extended by setting  $h = h \cup g_1$  and  $h = h \cup g_2$ , respectively. Now assume that  $p_1 \neq p_2$ . Then there must be nodes u, u' in  $T_{q_1}$  with u' a successor of u and such that u is part of  $T_{p_1}$ and  $T_{p_2}$ , but u' is part of  $T_{p_1}$ , but not part of  $T_{p_2}$  (or vice versa). By Condition (2) of progress trees,  $g_1$  maps some predecessor variable of u' to \*, but  $g_2$  does not. Consequently, the extensions  $h = h \cup g_1$ and  $h = h \cup q_2$  differ on some variable on which they are both defined.

For the 'moreover' part, let  $\bar{a}^*, \bar{b}^*$  be partial answers with  $\bar{b}^* \prec \bar{a}^*$ . Since  $\bar{a}^*$  is a partial answer, there must be a homomorphism  $h_{\bar{a}}$  from  $q_1$  to  $D_1$  such that for all  $x \in var(q_1)$ ,  $h_{\bar{a}}(x) = h_{\bar{a}^*}(x)$  if  $h_{\bar{a}^*}(x) \notin N$  and  $h_{\bar{a}}(x) \in N$  if  $h_{\bar{a}^*}(x) = *$ , and analogously for  $\bar{b}^*$  and a homomorphism  $h_{\bar{b}}$ . Since  $\bar{b}^* \prec \bar{a}^*$ , there must further be a variable  $x_0$  with  $h_{\bar{b}^*}(x_0)$  a database constant and  $h_{\bar{a}^*}(x_0) = *$ . Let  $v \in V_1$  be the first atom that contains such an  $x_0$  in a pre-order tree walk over  $T_1$ . Let  $(q_a, g_a)$  be the progress tree realized in  $\bar{a}^*$ 

with  $v \in q_a$ , and let u be the root of  $q_a$ . Then  $h_{\bar{a}^*}(z) \neq *$  for all predecessor variables z in u. Since  $\bar{b}^* < \bar{a}^*$ , the same is true for  $h_{\bar{b}^*}$ . Due to Condition (2) of progress trees, it follows that there is a progress tree  $(q_b, g_b)$  realized in  $\bar{b}^*$  such that the root of q' is u. From  $\bar{b}^* < \bar{a}^*$ , it follows that  $V_{q_a} \subsetneq V_{q_b}$  or  $V_{q_a} = V_{q_b}$  and  $g_b(x) = *$  implies  $g_a(x) = *$  for all  $x \in var(q_a)$ . From  $h_{\bar{b}^*}(x_0) \neq *$  and  $h_{\bar{a}^*}(x_0) = *$ , it further follows that  $g_b(x_0) \neq *$  and  $g_a(x_0) = *$ . Consequently,  $(q_a, g_a)$  is before  $(q_b, g_b)$  in the list trees $(u, h_{\bar{z}})$  where  $h_{\bar{z}} = h_{\bar{b}^*}|_{\bar{z}} = h_{\bar{a}^*}|_{\bar{z}}$  and thus the recursive call that leads to the output of  $h_{\bar{b}^*}$ .

Let  $\bar{a}^*, \bar{b}^*$  be partial answers to  $q_1$  on  $D_1$ . We say that  $\bar{a}^*$  prunes  $\bar{b}^*$  if there is a node  $v = R(\bar{y}) \in V_1$  with predecessor variables  $\bar{z}$  and a progress tree  $(q, g) \in \text{trees}(v, h_{\bar{b}^*}|_{\bar{z}})$  that is realized in  $\bar{b}^*$  and removed from trees $(v, h_{\bar{b}^*}|_{\bar{z}})$  when  $\bar{a}^*$  is output.

**PROPOSITION 5.5.** The algorithm outputs exactly the minimal partial answers to  $q_1$  on  $D_1$ , without repetition.

PROOF. We first argue that whenever a partial answer is pruned, then it is not a minimal partial answer. Assume that partial answer  $\bar{a}^*$  prunes partial answer  $\bar{b}^*$ . Then there is a  $v \in V_1$  with predecessor variables  $\bar{z}$  and a progress tree  $(q,g) \in \text{trees}(v, h_{\bar{b}^*}|\bar{z})$  such that (q,g) is realized in  $\bar{b}^*$  and removed from  $\text{trees}(v, h_{\bar{b}^*}|\bar{z})$  when  $\bar{a}^*$  is output. Thus  $(q, h_{\bar{a}^*}|\bar{z}) \prec_{\text{db}} (q,g)$ . We call the variables in  $\bar{z}$  root variables of q. A fringe variable of q of is a variable x that occurs in a leaf u of  $T_q$  that has a successor u' in  $T_1$  in which x also occurs. We observe that

(\*) for all variables x that are root variables or fringe variables of q,  $h_{\overline{a}^*}(x) = g(x)$ .

In fact, this follows from  $(q, h_{\bar{a}^*}|_{\bar{z}}) <_{db} (q, g)$  and the fact that, by Conditions 1 and 2 of progress trees,  $g(x) \neq *$  for all variables x mentioned in (\*).

Let  $\bar{c}^*$  be obtained from  $\bar{b}^*$  by setting  $h_{\bar{c}^*}(x) = h_{\bar{a}^*}(x)$  for all  $x \in \operatorname{var}(q)$ . It can be verified that  $\bar{c}^*$  is a partial answer to  $q_1$  on  $D_1$ . In particular, there must be a homomorphism  $h_{\bar{b}}$  from  $q_1$  to  $D_1$  such that  $h_{\bar{b}^*}(x) = *$  iff  $h_{\bar{b}}(x) \in N$  for all  $x \in \operatorname{var}(q_1)$ . By Condition 3 of progress trees, there is a homomorphism h from q to  $D_1$  such that  $h(x) \in N$  if  $h_{\bar{b}^*} = *$  and  $h(x) = h_{\bar{b}^*}(x)$  otherwise. Let  $h_{\bar{c}}$  be obtained from  $h_{\bar{b}}$  by setting  $h_{\bar{c}}(x) = h(x)$  for all  $x \in \operatorname{var}(q)$ . Due to (\*),  $h_{\bar{c}}$  is a homomorphism, and thus  $\bar{c}^*$  is a partial answer to  $q_1$  on  $D_1$ . Moreover, the construction of  $\bar{c}^*$  yields  $\bar{c}^* <_{db} \bar{b}^*$ , and thus we have shown that  $\bar{b}^*$  is not a minimal partial answer.

We next show that if a partial answer is not a minimal partial answer, then it is pruned. Assume that  $\bar{b}^*$  is not a minimal partial answer. Then there is a minimal partial answer  $\bar{a}^*$  with  $\bar{a}^* < \bar{b}^*$ . We argue that  $\bar{a}^*$  prunes  $\bar{b}^*$ . By Lemma E.2,  $\bar{a}^*$  is output before  $\bar{b}^*$  when no pruning takes place. Since  $\bar{a}^* < \bar{b}^*$ , there is an  $x_0 \in var(q_1)$  with  $h_{\bar{a}^*}(x_0)$  a database constant and  $h_{\bar{b}^*}(x_0) = *$ . Let  $v \in V_1$  be the first node encountered in a pre-order tree walk over  $T_1$  that contains  $x_0$ , and let (q, g) be the progress tree realized in  $\bar{b}^*$  with  $v \in q$ . Further let u be the root of q and  $\bar{z}$  be the predecessor variables of u. It follows from  $\bar{a}^* < \bar{b}^*$  and the fact that  $x_0$  occurs in v occurs in q that  $(q,g) >_{db} (q, h_{\bar{a}^*}|_{var(q)})$ . Thus (g, q) is removed from  $(q,g) \in trees(u,h)$ , with  $h = h_{\bar{a}^*}|_{\bar{z}} = h_{\bar{b}^*}|_{\bar{z}}$ , when  $\bar{a}^*$  is output (which is the case since  $\bar{a}^*$  is a minimal partial answer and thus not pruned), and therefore  $\bar{a}^*$  prunes  $\bar{b}^*$ .

Technical Report, arXiv version, 2022

#### F PROOFS FOR SECTION 6

In the main part of the paper, we have declared the goal to be the enumeration of  $q_0(ch_Q^{q_0}(D))_N^W$ . Here, we actually prove something slightly more general, as follows (this parallels what is done in Appendix E.1).

**PROPOSITION F.1.** For every CQ  $q(\bar{x})$  that is acyclic and free-connex acyclic, enumerating the answers  $q(D)_N^{\boldsymbol{\mathcal{W}}}$  is in  $\mathsf{DelayC}_{\mathsf{lin}}$  for databases D and sets of nulls  $N \subseteq adom(D)$  such that D is chaselike with witness  $D_1, \ldots, D_n$  where  $|\mathsf{adom}(D_i)|$  does not depend on D for  $1 \leq i \leq n$ .

To prove Proposition F.1, we use as a blackbox the  $\mathsf{DelayC}_{\mathsf{lin}}$ algorithm for the enumeration of minimal partial answers with a single wildcard presented in the previous section. In addition, we use a  $\mathsf{DelayC}_{\mathsf{lin}}$  algorithm for all-testing of (not necessarily minimal) partial answers with multi-wildcards.

#### **All-Testing Partial Answers with F.1** Multi-Wildcards

We show that all-testing of (not necessarily minimal) partial answers with multi-wildcards is in DelayClin. The following proposition makes this precise.

**PROPOSITION F.2.** For every CQ  $q(\bar{x})$  that is acyclic and free-connex acyclic, all-testing of the answers  $q(D)_{N}^{\mathcal{W}, \bigstar}$  is in  $\mathsf{DelayC}_{\mathsf{lin}}$  for databases D and sets of nulls  $N \subseteq adom(D)$  such that D is chaselike with witness  $D_1, \ldots, D_n$  where  $|\mathsf{adom}(D_i)|$  does not depend on D for  $1 \leq i \leq n$ .

We remind the reader that when  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{C}Q)$ ,  $D = \operatorname{ch}_{O}^{q}(D_{0})$ , and  $N = \operatorname{adom}(D) \setminus \operatorname{adom}(D_{0})$ , then the set of partial answers with multi-wild cards to Q on  $D_0$  is not necessarily identical to  $q(D)_{N}^{\mathcal{W}, \bigstar}$ . In fact, one can show that for the former all-testing in  $DelayC_{lin}$  is not possible unless BMM can be done in quadratic time, and thus it is vital that we work with  $q(D)_{\rm N}^{\mathcal{W}, \bigstar}$ .

To prove Proposition F.2, fix a CQ  $q(\bar{x})$  over schema S that is acyclic and free-connex acyclic, and let D be an S-database and N a set of nulls satisfying the conditions from Proposition F.2. In time linear in ||D|| we can convert q and D into a CQ  $q'(\bar{x})$  without quantified variables and a database D' such that D and D'have the same Gaifman graph and q(D) = q'(D'), and thus also  $q(D)_{\rm N}^{\mathcal{W}, \star} = q'(D')_{\rm N}^{\mathcal{W}, \star}$ . Note that we achieve this as part of the preprocessing carried out in Section 5, an outline of how to do this is given in Appendix 5.2 and details are in [11]. Since D and D' have the same Gaifman graph, D' and N also satisfy the conditions from Proposition F.2 and we may in fact simply assume that q contains no quantified variables.

Let  $T_q = (V_q, E_q)$  be a join tree for q. A multi-progress tree is a pair (q', g) with q' a subtree of q (as defined in Section 5) and  $q: \operatorname{var}(q) \to (\operatorname{adom}(D) \setminus N) \cup \mathcal{W}$  a map such that the following conditions are satisfied:

- (1)  $g(x) \notin W$  for every predecessor variable x in the root of  $T_{q'}$ ;
- (2) if  $v \in V_{q'}$  and v' is a successor of v in  $T_q$ , then  $v' \in V_{q'}$  if and
- only if  $g(x) \in W$  for some predecessor variable x in v';
- (3) the constants in the range of g form a guarded set in D.

Recall that *D* is chase-like with witness  $D_1, \ldots, D_n$ . A set *S* =  $\{(q_1, g_1), \dots, (q_\ell, g_\ell)\}$  of multi-progress trees is *valid* if there is a homomorphism *h* from  $q_1 \cup \cdots \cup q_\ell$  to some database  $D_i$ , with  $1 \le i \le n$ , that is *compatible* with *g*, that is, for all  $x, y \in var(q_1) \cup i$  $\cdots \cup \operatorname{var}(q_\ell),$ 

- (a)  $h(x) \in N$  if  $g(x) \in W$  and h(x) = g(x) otherwise;
- (b) g(x) = g(y) implies h(x) = h(y).

Our DelayC<sub>lin</sub> algorithm for all-testing  $q(D)_{\mathrm{N}}^{\mathcal{W}, \star}$  uses as a black box a DelayC<sub>lin</sub> algorithm  $A_{q'}$  for all-testing of q'(D), for every subquery  $q'(\bar{x}')$  of  $q(\bar{x})$ , that is, for every CQ  $q'(\bar{x}')$  that can be obtained from q by dropping atoms. Note that all of these q' contain no quantified variables and are thus free-connex acyclic, implying that all-testing q'(D) is possible in  $\mathsf{DelayC}_{\mathsf{lin}}$  by Proposition 4.2. There are clearly only constantly many such subqueries.

In the preprocessing phase, we run the preprocessing phases of all the algorithms  $A_{q'}$ , q' a subquery of q. In addition, we precompute a lookup table nullhom that stores a Boolean value for all sets S of multi-progress trees that contain at most |var(q)| such trees. Let  $S = \{(q_1, g_1), \dots, (q_\ell, g_\ell)\}$ . The stored value is 1 if S is valid and 0 otherwise. Such a lookup table can be accessed and updated in O(1) time on a RAM. The proof of the following is similar to that of Lemma 5.3.

LEMMA F.3. The lookup table nullhom can be computed in time linear in ||D||.

**PROOF.** To compute the table, we iterate over the databases  $D_1, \ldots, D_n$ . For each  $D_i$ , set  $G = adom(D_i) \setminus N$  and iterate over all sets S of pairs (q', g) with q' a subtree of q and  $g : var(q') \to G \cup W$ , such that there are at most |q| pairs in S and Conditions (1) and (2) of multiprogress trees is satisfied for all pairs in S. Condition (3) is satisfied since G is a guarded set in  $D_i$ . This also implies that its cardinality is bounded by a constant and thus there are only constantly many pairs (q', g) of the described form and consequently also only constantly many sets S. Let  $S = \{(q_1, g_1), \dots, (q_\ell, g_\ell)\}$ . We then check whether there is a homomorphism *h* from  $q_1 \cup \cdots \cup q_\ell$ to  $D_i$  that is compatible with  $g_1, \ldots, g_\ell$ . If this is the case, we set nullhom(S) = 1. Otherwise, nullhom(S) = 1 as all memory is initialized with value 0 in our machine model. Note that we can check the existence of h brute force: there are only constantly many potential targets because  $|\mathsf{adom}(D_i)|$  does not depend on D. п

e now describe the testing phase of our algorithm. Assume that a multi-wildcard tuple  $\bar{a}^{W}$  of length  $|\bar{x}|$  is to be tested. We may first check whether wildcards are used in the required way and answer 'no' if this is not the case. More precisely, we check that the wildcards in  $\bar{a}^{\mathcal{W}}$  are a prefix of the ordered set  $\mathcal{W} = \{*_1, *_2, \dots\}$  and that multiple occurrences of the same variable in  $\bar{x}$  are matched by multiple occurrences of the same wildcard in  $\bar{a}^{\mathcal{W}}$ . If this is the case, we may view  $\bar{a}^{\mathcal{W}}$  as a map  $h_{\bar{a}^{\mathcal{W}}}$  : var $(q) \rightarrow (\operatorname{adom}(D) \setminus N) \cup \mathcal{W}$ in the obvious way. We may then check that the wildcards in  $\bar{a}^{\mathcal{W}}$ respect the order of the answer variables in  $\bar{x}$ , that is, if the first occurrence of *x* is before the first occurrence of *x'* in  $\bar{x}$ ,  $h_{\bar{a}W}(x) = *_i$ , and  $h_{\vec{a}W}(x') = *_j$ , then i < j.

We say that a multi-progress tree (q', g) is realized in  $\bar{a}^{W}$  if  $h_{\overline{a}^{W}}(x) = g(x)$  for all  $x \in var(q')$ . Let T be the set of all multiprogress trees realized in  $\bar{a}^{\mathcal{W}}$  and let ~ be the smallest equivalence relation on *T* such that  $(q_1, g_1) \sim (q_2, g_2)$  if there are variables  $x_1 \in var(q_1)$  and  $x_2 \in var(q_2)$  such that  $g_1(x_1) = g_2(x_2) \in \mathcal{W}$ . We consider each equivalence class  $S \subseteq T$  of ' $\sim$ ' and check whether *S* is valid by testing if nullhom(S) = 1. If any of the checks fails, we answer 'no'. Since at most |var(q)| (and thus only constantly many) multi-progress trees may be realized in  $\bar{a}^{\mathcal{W}}$ , the required checks can be done in constant time.

We then do one last check. Let q' be the subquery of q that consists of all atoms  $\alpha$  such that for all variables x in  $\alpha$ ,  $h_{\vec{a}^W}(x) \notin W$ . Further let  $\overline{a}$  be the tuple over  $\operatorname{adom}(D) \setminus N$  obtained from  $\overline{a}^W = (a_1^W, \ldots, a_{|\overline{x}|}^W)$  by dropping  $a_i^W$  whenever the *i*-th position in  $\overline{x}$  is an answer variable that is not in  $\operatorname{var}(q')$ . We then use algorithm  $A_{q'}$  to test whether  $\overline{a} \in q'(D)$  and return the result. The following lemma asserts that the returned answer is correct, which finishes the proof of Proposition 4.2.

LEMMA F.4. 
$$\bar{a}^{\mathcal{W}} \in q(D)_{\mathcal{N}}^{\mathcal{W}}$$
 iff the testing phase returns 'yes'.

PROOF. 'if'. Assume that the testing phase returns 'yes'. Then  $\bar{a} \in q'(D)$  and thus we may view  $\bar{a}$  as a homomorphism  $h_{\bar{a}}$  from q' to D in the obvious way. Note that the range of  $h_{\bar{a}}$  falls within  $\operatorname{adom}(D) \setminus N$  since all constants in  $\bar{a}$  are from this set. We next extend h by considering one equivalence class  $S \subseteq T$  of '~' at the time. Let  $S = \{(q_1, g_1), \ldots, (q_\ell, g_\ell)\}$ . Since the testing phase has returned 'yes', S is valid and thus there is a homomorphism  $h_S$  from  $q_1 \cup \cdots \cup q_\ell$  to some  $D_i$ , with  $1 \leq i \leq n$ , that is compatible with  $g = g_1 \cup \cdots \cup g_n$ . Taking the union of  $h_{\bar{a}}$  and all the homomorphisms  $h_S$  yields a homomorphism h from q to D that yields an answer  $\bar{b} \in q(D)$  such that  $\bar{a}^{\mathcal{W}}$  is obtained from  $\bar{b}$  by replacing nulls with wildcards from  $\mathcal{W}$ . Consequently,  $\bar{a}^{\mathcal{W}} \in q(D)_N^{\mathcal{W}}$ .

'only if'. Assume that  $\bar{a}^{W} \in q(D)_{N}^{W}$ . Then there is a homomorphism h from q to D that yields an answer  $\bar{b} \in q(D)$  such that  $\bar{a}^{W}$  is obtained from  $\bar{b}$  by replacing nulls with wildcards from W. Clearly, h is also a homomorphism from the subquery q' of q constructed during the testing phase to D. Consequently,  $\bar{a} \in q(D)$  where  $\bar{a}$  is the tuple over  $\operatorname{adom}(D) \setminus N$  constructed along with q', and thus the test for  $\bar{a} \in q(D)$  made in the testing phase succeeds. It remains to argue that every equivalence class  $S \subseteq T$  w.r.t. '~' is valid, and thus also the checks associated with that succeed. Let  $S = \{(q_1, g_1), \ldots, (q_\ell, g_\ell)\}$ . We first observe the following. The proof is identical to the proof of the analogous claim for single-wildcard progress trees in the proof of Lemma 5.3. Details are omitted.

CLAIM. Let (q', g) be a multiple-progress tree and let h be a homomorphism from q' to D such that for all  $x \in var(q')$ ,  $h(x) \in N$  if  $g(x) \in W$  and h(x) = g(x) otherwise. Then h is a homomorphism from q to  $D_i$  for some  $i \in \{1, ..., n\}$ .

Recall the definition of '~' via shared wildcards and the fact that  $\operatorname{adom}(D_i) \cap \operatorname{adom}(D_j) \cap N = \emptyset$  for  $1 \le i < j \le n$ , by definition of chase-like instances. From this and the claim it follows that there is a single  $D_i$ , with  $1 \le i \le n$ , such that h is a homomorphism from  $q_1 \cup \cdots \cup q_\ell$  to  $D_i$ . Moreover, h is clearly be compatible with  $g = g_1 \cup \cdots \cup g_\ell$  and thus S is valid.

#### F.2 Enumeration with Multi-Wildcards

We prove Proposition F.1 using exactly the algorithm described in the main part of the paper. Balls and cones play a crucial role in the algorithm. The following lemma explains how they link the set  $q(D)_{\rm N}^{\mathcal{W}}$  that we aim to enumerate to the set  $q(D)_{\rm N}^*$  that we enumerate in the outer **forall** loop. Note that, by Point (2), we can indeed choose an  $\bar{a}^{\mathcal{W}}$  with the required properties in the algorithm.

LEMMA F.5.  
(1) 
$$q(D)_{N}^{\mathcal{W}} \subseteq \bigcup_{\overline{a^{*}} \in q(D)_{N}^{*}} \operatorname{cone}^{\mathcal{W}}(\overline{a}^{*});$$
  
(2) for all  $\overline{a^{*}} \in q(D)_{N}^{*}, \emptyset \neq \min^{<}(B^{\mathcal{W}}(\overline{a^{*}}) \cap q(D)_{N}^{\mathcal{W}, \pounds}) \subseteq q(D)_{N}^{\mathcal{W}};$   
(3) for all distinct  $\overline{a^{*}}, \overline{b^{*}} \in q(D)_{N}^{*}, B^{\mathcal{W}}(\overline{a^{*}}) \cap \operatorname{cone}^{\mathcal{W}}(\overline{b^{*}}) = \emptyset.$ 

PROOF. For Point (1), let  $\bar{b}^{\mathcal{W}} \in q(D)_{\mathbb{N}}^{\mathcal{W}}$  and let  $\bar{b}^*$  be obtained from  $\bar{b}^{\mathcal{W}}$  by replacing every wildcard from  $\mathcal{W}$  by '\*'. Then  $\bar{b}^*$  is a partial answer to q on D, and thus there is an  $\bar{a}^* \in q(D)_{\mathbb{N}}^*$  such that  $\bar{a}^* \leq \bar{b}^*$ . It is easy to verify that  $\bar{b}^{\mathcal{W}} \in \operatorname{cone}^{\mathcal{W}}(\bar{a}^*)$ .

For Point (2), let  $\bar{a}^* \in q(D)_N^*$ . To prove that the set  $\min^{<}(B^{\mathcal{W}}(\bar{a}^*) \cap q(D)_N^{\mathcal{W}, \star})$  is non-empty, consider the multi-wildcard tuple  $\bar{a}^{\mathcal{W}}$  obtained from  $\bar{a}^*$  by replacing every occurrence of '\*' with a different wildcard from  $\mathcal{W}$ . It is clear that  $\bar{a}^{\mathcal{W}} \in B^{\mathcal{W}}(\bar{a}^*) \cap q(D)_N^{\mathcal{W}, \star}$  and thus this set is non-empty. Since it is finite (and in fact of constant size),  $\min^{<}(B^{\mathcal{W}}(\bar{a}^*) \cap q(D)_N^{\mathcal{W}, \star})$  is also non-empty. To show that this set is a subset of  $q(D)_N^{\mathcal{W}, \star}$  lis also non-empty. To show that this from  $q(D)_N^{\mathcal{W}, \star}$ . Now assume to the contrary of what is to be shown that there is a  $\bar{b}^{\mathcal{W}} \in q(D)_N^{\mathcal{W}, \star}$  with  $\bar{b}^{\mathcal{W}} < \bar{a}^{\mathcal{W}}$ . Then  $\bar{b}^{\mathcal{W}}$  cannot be in  $B^{\mathcal{W}}(\bar{a}^*)$  as otherwise  $\bar{a}^{\mathcal{W}}$  would not be minimal. This and  $\bar{b}^{\mathcal{W}} < \bar{a}^{\mathcal{W}}$  means that for  $\bar{a}^{\mathcal{W}} = (a_1, \ldots, a_{|\bar{x}|})$  and  $\bar{b}^{\mathcal{W}} = (b_1, \ldots, b_{|\bar{x}|})$ ,

(†) there is an  $i \in \{1, ..., |\bar{x}|\}$  with  $b_i \in \mathsf{adom}(D)$  and  $a_i \in \mathcal{W}$ . Let  $\bar{b}^*$  be  $\bar{b}^{\mathcal{W}}$  with every wildcard from  $\mathcal{W}$  replaced by '\*'. It is not hard to verify that  $\bar{b}^*$  is a partial answer to q on D and, using  $\bar{b}^{\mathcal{W}} < \bar{a}^{\mathcal{W}}$  and (†), that  $\bar{b}^* < \bar{a}^*$ , in contradiction to  $\bar{a}^* \in q(D)_{\mathbb{N}}^*$ .

We prove Point (3) by contradiction. Assume that  $\bar{a}^*, \bar{b}^* \in q_N^*(D)$ are distinct and that there is a multi-wildcard tuple  $\bar{a}^{\mathcal{W}} \in B^{\mathcal{W}}(\bar{a}^*) \cap$ cone<sup> $\mathcal{W}$ </sup>( $\bar{b}^*$ ). Then by definition of cones, there is a wildcard tuple  $\bar{c}^*$  such that  $\bar{a}^{\mathcal{W}} \in B^*(\bar{c}^*)$  and  $\bar{b}^* < \bar{c}^*$ . But, by definition of  $B^{\mathcal{W}}$ , we have that  $B^*(\bar{a}^{\mathcal{W}}) = \bar{a}^*$  and  $B^*(\bar{a}^{\mathcal{W}}) = \bar{c}^*$ . Thus,  $\bar{a}^* = \bar{c}^*$ .

Therefore  $\bar{b}^* \prec \bar{a}^*$  which is impossible as  $\bar{a}^W$  and  $\bar{b}^*$  are both minimal partial answers and, thus, incomparable.

LEMMA 6.3. The algorithm outputs exactly the minimal partial answers with multi-wildcards to q on D, without repetition.

PROOF. We first argue that all tuples output by the algorithm are from  $q(D)_{N}^{\mathcal{W}}$ . Indeed, tuples output during the **forall** loop are from  $q(D)_{N}^{\mathcal{W}}$  by Point (2) of Lemma F.5. It thus remains to consider tuples that were output because they remained on the list *L* after the execution of the **forall** loop. We first observe the following invariant, which follows from an easy analysis of the algorithm.

**Claim.** Throughout the run of the algorithm,  $F(\bar{a}^{\mathcal{W}}) = 1$  implies that  $\bar{a}^{\mathcal{W}}$  was already added to *L* or is not in  $q(D)_{N}^{\mathcal{W}}$ .

Now consider a tuple  $\bar{a}^W$  that was output after the execution of the **forall** loop and assume to the contrary of what is to be shown that there is a  $\bar{b}^W \in q(D)_N^W$  such that  $\bar{b}^W < \bar{a}^W$ . Let  $\bar{b}^*$  be obtained from  $\bar{b}^W$  by replacing every wildcard from W with '\*'. Then  $\bar{b}^*$  is a (not necessarily minimal) partial answer to q on D and thus there is a  $\bar{c}^* \in q(D)_N^*$  with  $\bar{c}^* \leq \bar{b}^*$ . Then  $\bar{b}^W \in \text{cone}^W(\bar{c}^*)$ . We next argue that at some point  $\bar{b}^W$  is appended to the list L. In fact, consider the iteration of the outer **forall** loop that processes  $\bar{c}^*$ . If  $F(\bar{b}^W) = 0$  at that point, then  $\bar{b}^W$  is appended to L. If  $F(\bar{b}^W) = 1$ , then by the claim  $\bar{b}^W$  was appended to L in a previous iteration. In both cases, when  $\bar{b}^W$  was added to L, prune $(\bar{b}^W)$  was called and  $\bar{a}^W$  was removed from L and  $F(\bar{a}^W)$  set to 1, ensuring that  $\bar{a}^W$  is never added back to L. This is a contradiction to  $\bar{a}^W$  being output because it remained on L.

We next argue that all tuples from  $q(D)_N^W$  are output. Let  $\bar{a}^W \in q(D)_N^W$ . By Point (1) of Lemma F.5, there is a  $\bar{b}^* \in q(D)_N^*$  with  $\bar{a}^W \in \operatorname{cone}^W(\bar{b}^*)$ . Consider the iteration of the outer **forall** loop that processes  $\bar{b}^*$ . If  $F(\bar{a}^W) = 0$  at that point, then  $\bar{a}^W$  is appended to *L*. If  $F(\bar{a}^W) = 1$ , then by the claim  $\bar{a}^W$  was appended to *L* in a previous iteration. Since  $\operatorname{prune}(\bar{c}^W)$  is only ever called for tuples  $\bar{c}^W \in q(D)_N^{W, \mathcal{K}}$ , the only way  $\bar{a}^W$  can be removed from *L* is when it is chosen to be output in the outer **forall** loop. If that never happens, it is still on *L* after that loop has terminated and thus also output.

Finally, we argue that there are no repetitions. This, however, is an immediate consequence of the use of the lookup table F to make sure that every multi-wildcard is appended to list L at most once and of the fact that when a tuple is output in the outer **forall** loop, then it is removed from L.

#### G ILLUSTRATING THE ALGORITHM

We give examples that showcase important aspects of the enumeration algorithm for minimal partial answers with a single wildcard presented in Section 5.

Assume that the enumeration algorithm is started on the OMQ  $Q(\bar{x}) = (O, S, q) \in (\mathbb{G}, \mathbb{CQ})$  where O consists of the TGDs

$$A(x) \quad \to \quad \exists y_1 \exists y_2 \ R(y_1, y_2) \land R(y_2, x) \land C(y_2)$$

$$B(x) \quad \to \quad \exists y_1 \exists y_2 \ R(y_1, x) \land R(y_2, x) \land C(y_1)$$

$$E(x) \rightarrow \exists y_1 R(x, y_1)$$

$$R(x, y) \rightarrow L(x, x) \wedge L(y, y),$$

the schema S is  $\{A, B, C, E, R\}$ , and where q is the CQ

$$\begin{array}{rcl} q(\bar{x}) & \leftarrow & \exists y_1 \exists y_5 \ L(y_1, x_1), R(x_1, x_2), R(x_2, x_3), \\ & & R(x_4, x_3), R(x_5, x_4), L(y_5, x_5), C(x_1). \end{array}$$

with  $\bar{x} = (x_1, x_2, x_3, x_4, x_5)$ . The CQ *q* is displayed in Figure 2. It is acyclic and free-connex acyclic, as witnessed by the join trees for *q* and its extension  $\hat{q}$  with the atom  $\hat{R}(x_1, \ldots, x_5)$ . The join tree for *q* is given in Figure 2. Note that the atoms that contain only answer variables constitute a connected prefix of the join tree of *q*. This can (almost<sup>4</sup>) always be achieved for CQs that are acyclic and free-connex acyclic and is exploited in the preprocessing phase.



Figure 2: CQ q and its join tree.



Figure 3: Database D and query-directed chase  $D_0$ . All edges represent relation R and every constant has an L-self-loop that is not shown.

Assume that the input database *D* is as depicted on the left-hand side of Figure 3, where all edges represent the relation symbol *R*.

*Preprocessing.* In the preprocessing phase, we modify the query q and database D to obtain the CQ  $q_2$  and database  $D_2$  that are used in the enumeration phase. This is done in several steps. In the very first step, we set  $q_0 = q$  and replace D with the query-directed chase  $D_0 = ch_O^q(D)$ , displayed on the right-hand side of Figure 3.

The next step is to construct from  $q_0$  and  $D_0$  a self-join free CQ  $q_1$  without quantified and a database  $D_1$  that has been adjusted accordingly. It is this step that exploits the special shape of the join tree of  $q_0$  mentioned above. In our case,  $q_1$  is

 $q_1(\bar{x}) \leftarrow R_1(x_1, x_2), R_2(x_2, x_3), R_4(x_4, x_3), R_5(x_5, x_4), C_1(x_1).$ 

Informally,  $q_1$  was obtained from q by renaming relation symbols to achieve self-join freeness and dropping atoms that involve a quantified variable. The join tree of  $q_1$  is the join tree of q except that relation symbols in atoms change and nodes/atoms that contain any of the variables  $y_1, y_5$  are removed.

The database  $D_1$  is shown in Figure 3 where, for better readability, we only show the index *i* of edge labels  $R_i$ . Observe that the constant  $n_8$  was removed and that edges are now multi-edges. To get an intuition of the construction of  $D_1$ , consider the fact  $R(n_2, n_1)$ in  $D_0$ . In principle, any of the four *R*-atoms in  $q_0$  can map to it, and in  $q_1$  the relation symbol *R* in those atoms has been renamed

<sup>&</sup>lt;sup>4</sup>It can always be achieved when using a generalized hypertree decomposition of width 1 in place of a join tree, see [11].

to  $R_1, R_2, R_4$ , and  $R_5$ , respectively. Thus, we should be prepared to include in  $D_1$  the fact  $R_i(n_2, n_1)$  for all  $i \in \{1, 2, 4, 5\}$ . However, a closer inspection shows that the atom  $R(x_2, x_3)$  in  $q_0$  cannot map to the fact  $R(n_2, n_1)$  in  $D_0$  since then  $x_1$  would have to be mapped to an *R*-predecessor of  $n_2$ , which does not exist. A similar observation holds for the atom  $R(x_4, x_3)$  in  $q_0$  and thus we only include in  $D_1$  the facts  $R_1(n_2, n_1)$  and  $R_5(n_2, n_1)$ . The 'right' facts to include are identified during a bottom-up walk over the join-tree of  $q_0$ . Note that the relation symbols *A*, *B*, have been dropped since they do not occur in  $q_0$ .



Figure 4: Database  $D_1$ . Edges are labeled with indices of the relation symbols  $R_1, R_2, R_4, R_5$  that constitute the edge.



Figure 5: Join tree of  $q_2$ . The predecessor variables of each atom are shown on the incoming edge of the atom.

Lists of progress trees. The last step of the preprocessing phase is to create the lists trees(v, h) of progress trees for each atom vin  $q_2$  and each predecessor map h for v. Recall that by the latter we mean a function  $h : \bar{z} \rightarrow \text{adom}(D_2) \setminus N$  whose range is a guarded set in  $D_2$ , and where  $\bar{z}$  are the predecessor variables in v. For brevity, we represent h in the form  $z_1 \cdots z_n \mapsto c_1 \cdots c_n$  when  $z_1, \ldots, z_n$  are the variables in  $\bar{z}$  and  $h(z_i) = c_i$  for  $1 \le i \le n$ ; this becomes  $\varepsilon \mapsto \varepsilon$  when  $\bar{z}$  is the empty tuple. For the join tree of  $q_1$ with marked predecessor variables, see Figure 5.

Also recall that a progress tree is a pair (q, g) with CQ q a subtree of  $q_2$  and g a function from var(q) to  $(adom(D_2) \setminus N) \cup \{*\}$  that must satisfy Conditions (1)-(4) given in Section 5. We represent the function g in the same way as predecessor maps. Examples of progress trees include

$$(R_1(x_1, x_2), x_1x_1x_2 \mapsto ba)$$

and

$$(R_2(x_2, x_3) \land R_1(x_1, x_2) \land C_1(x_1), x_1x_2x_3 \mapsto **a)$$

The reader is invited to verify that the relevant Conditions (1)-(4) are all satisfied for these progress trees. Intuitively, the second progress tree (q, g) above describes an 'excursion' of the part q of  $q_2$  into the 'null part' of  $D_2$ . This excursion consists of mapping  $x_1$  to  $n_2$ ,  $x_2$  to  $n_1$ , and  $x_3$  to a.

Let us review two non-examples progress trees, starting with

$$(R_4(x_4, x_3) \land R_5(x_5, x_4), x_3x_4x_5 \mapsto abc)$$

which is not a progress tree as the predecessor variable  $x_4$  of atom  $R_5(x_5, x_4)$  is mapped to '\*' and thus Condition (2) is violated. Next consider

$$(R_4(x_4, x_3) \land R_5(x_5, x_4), x_3x_4x_5 \mapsto a*c)$$

which is not a progress tree because there is no guarded set in  $D_2$  that contains *a* and *c*, and thus Condition (4) is violated.

We now give all the lists trees(v, h) that are computed in the preprocessing phase. For brevity, we represent progress trees (q, g) as the CQ q in which every variable x was replaced with g(x). List items are separated by ';'. The lists are:

- atom  $v = R_1(x_1, x_2)$  with a predecessor variable  $x_2$ 
  - trees( $v, x_2 \mapsto a$ ) = [ $R_1(b, a); R_1(d, a)$ ]

- trees(
$$v, x_2 \mapsto b$$
) = [ $R_1(*, b) \land C_1(*)$ ]

- trees( $v, x_2 \mapsto c$ ) = []
- trees $(v, x_2 \mapsto d) = [R_1(*, d) \land C_1(*)]$
- trees $(v, x_2 \mapsto e) = []$
- atom v = R<sub>2</sub>(x<sub>2</sub>, x<sub>3</sub>) no predecessor variables
   trees(v, ∅ ↦ ∅) = [R<sub>2</sub>(b, a); R<sub>2</sub>(d, a); R<sub>2</sub>(\*, a) ∧ R<sub>1</sub>(\*, \*) ∧ C<sub>1</sub>(\*); R<sub>2</sub>(a, \*) ∧ R<sub>4</sub>(a, \*)]
- atom  $v = R_4(x_4, x_3)$  with a predecessor variable  $x_3$
- $\begin{array}{l} \operatorname{trees}(v, x_3 \mapsto \beta) = [] \mbox{ for } \beta \in \{b, c, d, e\} \\ \operatorname{trees}(v, x_3 \mapsto c_0 a) = [R_4(b, a); R_4(d, a); \end{array}$
- $R_4(*, a) \land R_5(*, *)]$  atom  $v = R_5(x_5, x_4)$  with a predecessor variable  $x_4$ 
  - $-\operatorname{trees}(v, x_2 \mapsto c) = []$
  - trees(v, x<sub>2</sub> → a) = [R<sub>5</sub>(b, a); R<sub>5</sub>(d, a); R<sub>5</sub>(e, a)]
  - trees $(v, x_2 \mapsto b) = [R_5(c, b); R_5(*, b)]$
  - $-\operatorname{trees}(v, x_2 \mapsto d) = [R_5(*, d)]$
  - trees( $v, x_2 \mapsto e$ ) = []
- atom  $v = C_1(x_1)$  with a predecessor variable  $x_1$
- trees $(v, x_1 \mapsto \beta) = []$  for  $\beta \in \{a, c, d, e\}$
- trees( $v, x_1 \mapsto b$ ) = [ $C_1(b)$ ]

All the remaining lists are empty. The lists above are sorted in database preferring order, as required, and thus we are ready for the enumeration phase.

Enumeration and pruning. In the enumeration phase, we traverse the join tree of  $q_1$  in a depth-first fashion, assembling a minimal partial answer to  $q_1$  on  $D_1$ . Once such an answer is found, we output it and execute pruning, then backtrack in a systematic way and re-start answer assemblage to produce the next answer, and so on.

In our example, there are no complete answers. The first partial answer generated is  $\bar{c}^* = *babc$ . The answer  $\bar{c}^*$  is displayed on the left-hand side of Figure 6, inside the join tree for  $q_1$ . The blue boxes indicate the progress trees that have been used in assembling the answer  $\bar{c}^*$ .

Let us now consider pruning with  $\bar{c}^*$ . Informally, we consider all progress trees (q,g) such that q is some subtree of  $q_2$  and g



Figure 6: Three least partial answers, inside join tree of  $q_2$ .

can be obtained by starting with  $\bar{x} \mapsto \bar{c}^*$ , then restricting to the variables in var(q), and then switching at least one variable from a non-wildcard to a wildcard. One example of such a progress tree is

$$R_2(*, a) \wedge R_1(*, *) \wedge C_1(*).$$

Pruning removes this tree from trees  $(R_2(x_2, x_3), \emptyset \mapsto \emptyset)$ . One consequence of this pruning that the partial answer \*\*abc displayed on the right of Figure 6, which is not a minimal partial answer, is not output in the enumeration phase.

Minimal partial answers with multi-wildcards. We also briefly consider the enumeration algorithm for minimal partial answers with multi-wildcards from Section 6, illustrating in particular the necessity of using *cones*. Recall that a cone of a wildcard tuple  $\bar{a}^*$ 

is the set of all multi-wildcard tuples  $\bar{b}^{\mathcal{W}}$  such that the wildcard tuple  $\bar{b}^*$  obtained from  $\bar{b}^{\mathcal{W}}$  by replacing all named wildcards by \* satisfies  $\bar{a}^* \leq \bar{b}^*$ .

Intuitively, the enumeration algorithm for multiple wildcards starts the enumeration algorithm for a single wildcard as a black box procedure and whenever the black box generates a minimal partial answer  $\bar{a}^*$  then it outputs the multi-wildcard minimal partial answers from cone( $\bar{a}^*$ ), with some bookkeeping to prevent repetition.

Consider again the CQ  $q_1$  and database  $D_1$ . As mentioned before, the first generated answer is \*babc and pruning removes from trees( $R_2(x_2, x_3), \emptyset \mapsto \emptyset$ ) the progress tree  $R_2(*, a) \land R_1(*, *) \land$  $C_1(*)$ . Apart from preventing the partial answer \*\*abc to be output as noted above, this also suppresses the partial answer \*bab\*(which is correct, as it is not a minimal partial answer). In contrast, it is not hard to check that  $*_1bab*_1$  is a minimal partial answer and thus must be output by the enumeration procedure for multiwildcards.

A naive version of the procedure without cones would simply look at each minimal partial answer with a single wildcard  $\bar{c}^*$  output by the black box and then output all multi-wildcard answers  $\bar{c}^{\mathcal{W}}$  obtained from  $\bar{c}^*$  by replacing each occurrence of the wildcard with some wildcard from  $\mathcal{W}$ . Clearly, such a naive version would miss the minimal partial answer  $*_1bab*_1$ . However, \*babc < \*bab\* and thus  $*_1bab*_1 \in \operatorname{cone}(*babc)$ . Our more refined algorithm therefore adds  $*_1bab*_1$  to the list *L* when processing the tuple \*babc and outputs it at the end of its run along with the other tuples in *L*.