

Highlights

A multimodal model with Twitter FinBERT embeddings for extreme price movement prediction of Bitcoin

Yanzhao Zou, Dorien Herremans

- Proposes a multimodal model for Bitcoin extreme price movement prediction using Twitter contents, not just sentiment.
- Ablation study of the impact of different modalities on extreme price prediction accuracy.
- New publicly available dataset of 9,435,437 tweets over a period of years related to Bitcoin.
- Describes a profitable strategy with reduced risk exposure for Bitcoin trading using the proposed multimodal model.
- Demonstrates the influence of setting predictive thresholds on risk reduction of a trading strategy.

A multimodal model with Twitter FinBERT embeddings for extreme price movement prediction of Bitcoin

Yanzhao Zou^{a,*}, Dorien Herremans^a

^aSingapore University of Technology and Design, 8 Somapah Road, Singapore, 487372, Singapore, Singapore

ARTICLE INFO

Keywords:
Bitcoin
Twitter
NLP
BERT
Price
Prediction

ABSTRACT

Bitcoin, with its ever-growing popularity, has demonstrated extreme price volatility since its origin. This volatility, together with its decentralised nature, make Bitcoin highly subjective to speculative trading as compared to more traditional assets. In this paper, we propose a multimodal model for predicting extreme price fluctuations. This model takes as input a variety of correlated assets, technical indicators, as well as Twitter content. In an in-depth study, we explore whether social media discussions from the general public on Bitcoin have predictive power for extreme price movements. A dataset of 5,000 tweets per day containing the keyword 'Bitcoin' was collected from 2015 to 2021. This dataset, called PreBit, is made available online. In our hybrid model, we use sentence-level FinBERT embeddings, pretrained on financial lexicons, so as to capture the full contents of the tweets and feed it to the model in an understandable way. By combining these embeddings with a Convolutional Neural Network, we built a predictive model for significant market movements. The final multimodal ensemble model includes this NLP model together with a model based on candlestick data, technical indicators and correlated asset prices. In an ablation study, we explore the contribution of the individual modalities. Finally, we propose and backtest a trading strategy based on the predictions of our models with varying prediction threshold and show that it can be used to build a profitable trading strategy with a reduced risk over a 'hold' or moving average strategy.

1. Introduction


With cryptocurrencies gaining traction among both retail and institutional users over the past few years, the market cap of the cryptocurrencies grew significantly. Bitcoin is the most traded and largest cryptocurrency by market capitalisation. While trading activities of traditional assets are dominated by institutional investors, retail investors play a much bigger role in Bitcoin trading (see Goldman Sachs report by Nathan, Galbraith and Grimberg (2021)). Bitcoin is also a digital asset that does not derive its value from physical demands such as coal and iron ore. This makes the Bitcoin price more susceptible to be influenced by the market sentiment. For example, the price of Bitcoin rose by as much as 5.2 percent on 24 March 2021 when Elon Musk tweeted Tesla would accept Bitcoin for payments. It also crashed as much as 9.5 percent on 13 May 2021 when Elon Musk tweeted to question the energy consumption from Bitcoin mining. In this paper we examine and propose a multimodal model that can predict extreme Bitcoin price movements based on Twitter data as well as an extensive set of price data with technical indicators and related asset prices.

Research has shown that information from media sources is correlated to stock price movements (Pagolu, Reddy,

Panda and Majhi, 2016). This also applies to the relationship between social media and cryptocurrency prices. There exists some research that uses sentiment information from social media to try to predict cryptocurrency prices (Mohanty, Patel, Patel and Roy, 2018). We discuss the existing studies at length in Section 2. By just using sentiment information from social media posts, a lot of potentially useful information is ignored. In this research, we therefore leverage a state-of-the-art method to embed the entire tweet contents into a BERT model and use it as input to our predictive model. We further enhance our model using historical candlestick (OHLCV) data and technical indicators, together with correlated asset prices such as Ethereum and Gold.

When exploring existing studies that use social media data, we notice that most of the existing research uses derived measures from the media data source such as sentiments from the text, number of posts, and number of comments as the model input, rather than actual word embeddings. In addition, sentiments are often extracted using pretrained models such as VADER (Elbagir and Yang, 2019), Word2vec (Acosta, Lamaute, Luo, Finkelstein and Andreea, 2017), or BERT (Sun, Huang and Qiu, 2019a). Firstly, sentiment models pretrained for general purpose may not apply to financial language, for example, they may not accurately model or embed the words 'chart', 'hold', 'bull' or 'bear'. The context of the text is also lost when only the derived statistics are used. Utilising the full text of posts in the model retains more information and improve model performance. Hence, in this paper, we use the full text embeddings in our predictive model, in combination with a dedicated financial sentence embedding model, FinBERT (Araci, 2019). An additional challenge when doing this is that the number of words in the tweets gathered every day varies and a

*Corresponding author

 <yanzhao_zou@mymail.sutd.edu.sg> (Y. Zou);

dorien.herremans@sutd.edu.sg (D. Herremans)


 <https://github.com/YanzhaoZ/PreBit> (Y. Zou);

dorienherremans.com (D. Herremans)

ORCID(s): 0000-0001-8988-5981 (Y. Zou); 0000-0001-8607-1640 (D.

Herremans)

 <https://twitter.com/dorienherremans> (D. Herremans)

 <https://www.linkedin.com/profile/view?id=dorienherremans> (D.

Herremans)

neural network typically requires a constant input length. We propose a solution to this problem by concatenating the tweets and splitting them into larger blocks as explained in detail in Section 4. To the best of our knowledge, only one study (Lamon, Nielsen and Redondo, 2017) has tried to use text embeddings, not just sentiment, to predict Bitcoin prices, and none of these use an embedding model pretrained on financial texts, nor do they predict extreme movements or offer a backtested trading strategy with reduced market exposure risk. This research aims to fill this gap.

Most Bitcoin prediction models are formulated as a regression problem (see next section), whereby the exact price in the next bar is predicted. In this research, we opt to approach this as a classification problem, whereby we predict extreme price movement (up/down 2 or 5%) the next day. This way, the problem statement becomes directly useful for building trading strategies whereby the investor wants to either take advantage of an upcoming upwards price movement or avoid downwards volatility. We further experiment with moving the predictive threshold of our model and notice how risk exposure can be further minimised in our backtesting study.

In this paper, we propose a multimodal embedded model for predicting extreme price movements of Bitcoin and evaluate the impact of different modalities, including tweets represented through finBERT context embeddings. A new dataset is released consisting of tweets as well as candlestick data, related asset prices (Ethereum and Gold) and a selection of technical indicators from 1 January 2015 until 31 May 2021. In an ablation study, we explore the influence of different multimodal data. Finally, we show the usefulness of the model by proposing a simple trading strategy which was backtested with different predictive thresholds to optimally control risk exposure.

The next section provides a review of related literature. In Section 3, we describe the PreBit dataset in more detail. The proposed models are explained in the next section, followed by our experimental setup in Section 5. Finally, in Section 6, the results from the experiments are discussed followed by a conclusion.

2. Literature Review

Social media posts can have a dramatic and direct influence on the price of digital assets such as Bitcoin. An obvious example are the famed tweets by Elon Musk on accepting Bitcoin as payment for Tesla cars. On the same day, the price of Bitcoin rose by as much as 5.2 percent on 24 March 2021. In this work, we propose a model for predicting extreme price movements of Bitcoin using a multimodal model that includes technical indicators, related assets prices, as well as text from Twitter posts, and incorporate this in a simple trading strategy.

In this section, we will review some of the relevant research on price prediction models and identify how the current research addresses a unique gap. First, we will walk

through existing research that uses traditional price information and technical indicators for predicting Bitcoin's price. Then we provide a brief overview of models that use Natural Language Processing (NLP) in traditional stock price prediction models. Lastly, we explore how NLP has been used for cryptocurrency price prediction.

2.1. BTC price prediction with technical indicators

To predict price movements of any asset, a common approach is to look at historical price data together with technical analysis indicators. The same applies to Bitcoin trading. Most cryptocurrency exchanges provide Open-High-Low-Close-Volume (OHLCV) data for digital assets, much like stock exchanges do for traditional assets. This data is available on different time frames, e.g. 1 min, 5 min, 1 hour, 4 hours, daily, etc. Digital assets like Bitcoin do not have restricted trading hours like a traditional market such as Nasdaq. The daily OHLCV data is thus reset every day at 00:00:00 UTC.

The field of technical analysis (TA) focuses on using OHLCV data together with a range of technical indicators to build predictive models and trading strategies. For instance, Ślepaczuk, Zenkova et al. (2018) selected the daily top cryptocurrencies based on market cap, and filtered by moving average volume to construct their dataset. Utilising six technical features such as Momentum and Relative Strength Index, the authors trained a Support Vector Machine (SVM) model to predict whether each cryptocurrency belonged to the top or bottom quintile in terms of volatility-adjusted returns. However, their result did not show that the SVM strategy generated abnormal returns over simple Buy-and-Hold or Equal-Weight strategies. Sun, Zhou and Lin (2019b) used OHLCV data for Bitcoin and Ethereum with a 5-minute frequency. They calculated 16 technical indicators and fed this to a Random Forest model which predicts price change direction. The backtesting results for their strategy demonstrate the capability to capture trend change to a certain extent, but struggles with reversal periods.

With the success of neural networks over the past few years in fields such as Natural Language Processing (Devlin, Chang, Lee and Toutanova, 2018) and Computer Vision (He, Zhang, Ren and Sun, 2016), recent research has also explored the use of deep learning techniques for price prediction. Recurrent neural networks architectures, including Long-Short-Term-Memory (LSTM), are a widely adopted model in time-series prediction for their capability to capture temporal information (Mikolov, Karafiát, Burget, Cernocký and Khudanpur, 2010). For predicting digital asset prices, Kwon, Kim, Heo, Kim and Han (2019) used the OHLC and volume data of a basket of cryptocurrencies at a 10-min interval to construct a training dataset and predict price movement direction as a classification problem. The price time series data is processed into tensors and fed into a LSTM model, which achieved a better F1-score for this binary classification task, compared to a baseline gradient boosting model. LSTMs are a popular architecture for

time-series prediction, and other researchers have also used them to predict cryptocurrency prices using technical indicators (Aditya Pai, Devareddy, Hegde and Ramya, 2022), (Wu, Lu, Ma and Lu, 2018) (Shin, Mohaisen and Kim, 2021), (Felizardo, Oliveira, Del-Moral-Hernandez and Cozman, 2019). Using a different neural network architecture, Alonso-Monsalve, Suárez-Cetrulo, Cervantes and Quintana (2020) adopted Convolutional Neural Networks (CNNs) and compared their prediction results to a simple Multi-layer Perceptron (MLP), as well as an LSTM model. Using OHLC data and 18 derived technical indicators, the authors reported that an architecture that combined CNNs with an LSTM architecture outperformed the other models for Bitcoin, Litecoin and Ethereum price prediction on a 1-min interval from July 2018 to June 2019.

New deep learning techniques that capture the temporal relations between data include WaveNet (Oord, Dieleman, Zen, Simonyan, Vinyals, Graves, Kalchbrenner, Senior and Kavukcuoglu, 2016) and Transformer networks (Vaswani, Shazeer, Parmar, Uszkoreit, Jones, Gomez, Kaiser and Polosukhin, 2017). These have recently also been used for digital asset prediction. WaveNet is a network based upon the concept of Temporal CNNs with residual connections. Felizardo et al. (2019) did a comparison study between WaveNet, ARIMA, Random Forest, SVM, and LSTM to predict the future price of Bitcoin using OHLCV data. They found that the ARIMA model and the SVM equally outperformed the other models including WaveNet. One potential reason for this is that deeper models like Wavenet traditionally need a bigger dataset compared to models such as Support Vector Machines and ARIMA. Transformers, however, have demonstrated superior performance in the study conducted by Afteniy et al. (2021). Using only Bitcoin OHLC data on a 1-min interval for 2007 to 2021 as input, the authors reported 83% accuracy for a Transformer model versus the 67% accuracy for an LSTM architecture when performing directional price change prediction. The increased accuracy of the Transformer model may be due to the fact that working on a 1-min interval allows for the dataset to become much larger. Sridhar and Sanagavarapu (2021) also used the Transformer architecture with Time2vec on Dogecoin price data and reported a better result in terms of Mean Absolute Error (MAE) compared to an LSTM model (Shin et al., 2021), RNN model (Kavitha, Sinha and Jain, 2020), and a Linear neural network (Ali and Shatabda, 2020).

2.2. Stock price prediction with NLP

Looking at the stock market, there is a longstanding believe that sentiment and social influence has an impact on prices. For instance, the efficient market hypothesis states that assets are always trading at their fair value, thus leaving outperforming the market impossible (Malkiel, 1989). Provided an NLP model could capture all the knowledge of the world, we could in theory be able to predict the correct price. There are, however, limitations to this hypothesis: 1) markets may not really be efficient (Wang, 1985); 2) we cannot include all the information of the world in our model.

Researchers have tried to use cutting-edge natural language processing (NLP) techniques to include more information other than just OHLCV data and technical indicators in their models. Some common types of data include social media posts, newspaper articles / titles and related sentiment information. Wang, Xu and Zheng (2018) gathered Weibo (the Chinese Twitter-like social media) and A-share market data to predict the direction of movement of the Shanghai Stock Exchange Index. The authors obtained sentiment scores using a dictionary-based method and used it together with technical indicators as their model input. Their result reported over 14% increase in both F1-score and AUC value. While it is interesting to include sentiment into predictive models, feeding the actual text into the model may provide even more information to the model. With recent advances in NLP this has become more feasible.

The field of NLP made significant progress upon the introduction of the Word2vec embedding model (Mikolov, Sutskever, Chen, Corrado and Dean, 2013b). This has provided opportunities for financial models to better capture textual data and feed it to price prediction models. For instance, Pagolu et al. (2016) use both a Word2vec as well as an n-gram representation to train a sentiment analysis model on 3,216 tweets related to Microsoft. The trained model was then used on a larger dataset to show that the sentiments have a positive correlation to the Microsoft stock price.

The recent success of the Transformer based BERT model (Devlin et al., 2018) for multiple NLP tasks has attracted the attention of financial researchers as well. Combining the sentiment information extracted from BERT on carefully annotated Twitter data with stock OHLC price data, Dong, Yan, Almudaifer, Yan, Jiang and Zhou (2020) reported better results in terms of AUC for next-day price prediction compared to the state-of-the-art stock prediction model StockNet developed by (Xu and Cohen, 2018). Other similar work using BERT equally reported that their models outperformed others to various degrees (Sonkiya, Bajpai and Bansal, 2021; Chen, 2021). Based on these results, we have opted to use the state-of-the-art BERT model for this research, pretrained on a financial lexicon.

In general, we see many sources of text data used in stock prediction research, for instance, StockTwits (Jaggi, Mandal, Narang, Naseem and Khushi, 2021), Yahoo! Finance news (Schumaker and Chen, 2009), Reuters and Bloomberg news (Ding, Zhang, Liu and Duan, 2015), Twitter data (Bollen, Mao and Zeng, 2011; Si, Mukherjee, Liu, Li, Li and Deng, 2013; Das, Behera, Rath et al., 2018; Oliveira, Cortez and Areal, 2017; Groß-Klußmann, König and Ebner, 2019; Teti, Dallochio and Aniasi, 2019; Valle-Cruz, Fernandez-Cortez, López-Chau and Sandoval-Almazán, 2021), Dow Jones Newswire (Moniz and de Jong, 2014), and Bloomberg reports (Chan and Franklin, 2011). Given its popularity in financial circuits, we have opted to use Twitter data in this study. For a more complete overview of text-based methods for stock prediction, the reader is referred to the survey papers by De Fortuny, De Smedt, Martens and Daelemans

(2014); Kumar and Ravi (2016); Thakkar and Chaudhari (2021).

2.3. BTC price prediction with NLP

Just like stock prices are influenced by what people are saying on (social) media, so are digital asset prices. We see many sources of text data used in digital assets price prediction: Twitter data (Mohapatra, Ahmed and Alencar, 2019; Wołk, 2020; Raju and Tarif, 2020; Kim, Bock and Lee, 2021), Telegram (Smuts, 2019; Patel, Tanwar, Gupta and Kumar, 2020), Reddit (Ortu, Uras, Conversano, Bartolucci and Destefanis, 2022; Raju and Tarif, 2020), and more. Looking at existing literature, there are a number of models that again use the sentiment score derived from a text source as input to a predictive price model. Kim, Kim, Kim, Im, Kim, Kang and Kim (2016) used VADER (Valence Aware Dictionary for Sentiment Reasoning (Hutto and Gilbert, 2014)) to generate a sentiment score from comments and replies on the Bitcoin, Ethereum and Ripple community posts. Based on the result of a Granger causality test as well as two linear models, the authors concluded that the sentiments from the online community indeed have predictive value for price fluctuations as well as the number of transactions among users aforementioned digital assets. In a more recent study, Aharon, Demir, Lau and Zaremba (2022) examined the relationship between Twitter-based uncertainty and cryptocurrency returns. They used Twitter-Based Economic Uncertainty (TEU) and Twitter-Based Market Uncertainty (TMU), two indices generated by the Economic Policy Uncertainty website from 2011 to 2020 (Baker, Bloom, Davis and Renault, 2021), together with OHLCV data from CoinDesk. The authors documented a significant directional predictability from the TMU and TEU for Bitcoin based on a cross-quantile analysis. For more information on cross-quantile analysis, the reader is referred to Bouri, Gupta, Tiwari and Roubaud (2017); Demir, Gozgor, Lau and Vigne (2018); Wu, Tiwari, Gozgor and Leping (2021). Nghiem, Muric, Morstatter and Ferrara (2021) used historical posts from Telegram channels collected using PumpOlymp¹ which included keywords such as “pump”, “dump” and “signals” as part of their social media data. The authors built a model to predict ‘pumps’, which they define as follows: “Pump-and-dump is a type of fraud where scammers operate to lure unsuspecting traders to buy a cryptocurrency at an artificially inflated price (pump), then quickly sell their previous holdings to profit (dump).” OHLCV market data as well as statistics of social media data such as number of posts on Twitter, Facebook, Github repositories, number of comments, views and open issues were also used. A CNN, an LSTM and a combined model were built to predict whether a digital asset will become a “pump” target. Based on F1-score and MAPE, the authors concluded that the prediction error on an asset’s price during “pump” events is typically less than 5% away from the true price. Mohanty et al. (2018) used a Word2vec (Mikolov, Chen, Corrado and Dean, 2013a) model to extract sentiments from

tweets from February 2016 until January 2018. Using the sentiments as well as technical indicators as features, the authors reported marginally higher than 50% accuracy in predicting the next-ten-minute Bitcoin price change direction with their LSTM model. Passalis, Seficha, Tsantekidis and Tefas (2021) used FinBERT (Araci, 2019) to extract sentiments from a dataset with 223,000 news headlines collected by BDC consulting², ranging from 2015 until 2020. Using MLP, LSTM, and CNN models they predict the next-day Bitcoin price change direction. The paper reported the highest return (228% in profit) during the backtesting period 2019 to 2020 by using only sentiments with CNN, which slightly outperformed the CNN model using only OHLCV data at 219%, tied with the model using a combination of price and OHLCV data at 228%. Cruz and Silva (2021) use the BERT model to extract the sentiment of 10,111 news articles that contain keywords related to Bitcoin. An autoencoder model is developed that uses both the sentiment and the technical indicators as input. The authors reported 3.7 percent improvement in R^2 in predicting the next 4-hour Bitcoin price compared to models that did not use sentiment as input. Ortu et al. (2022) also utilised a BERT model to extract sentiments from 4,423 Github and 33,000 Reddit user comments. The authors reported a significantly improved accuracy when predicting the next-hour Bitcoin and Ethereum price change direction for all four models in their experiment: MLP, LSTM, Multivariate Attention LSTM with Fully Convolutional Network (MALSTM-FCN), and CNN.

Only a handful of studies directly use the actual text and feed it to a predictive model without first extracting the sentiment. Lamon et al. (2017) used a bag-of-words (BoW) to extract embeddings from news headlines from the *cryptocoin.com* website as well as 60 tweets daily on the topic of cryptocurrency. Experimenting with logistic regression, SVM, and Naive Bayes, the authors reported that logistic regression performed the best and was able to consistently achieve higher than 50% accuracy in predicting next-day Bitcoin price change direction. For a more comprehensive literature review on cryptocurrency trading research, the reader is referred to Fang, Ventre, Basios, Kong, Kanthan, Li, Martinez-Regoband and Wu (2020).

Most studies above use sentiment extracted from text sources to include in their price prediction models. To our knowledge, at the time of writing, only Lamon et al. (2017) uses a simple Bag of Words embedding. In the current study, we aim to optimally use social media content, beyond just using sentiment scores. We therefore leverage upon the positive results by Lamon et al. (2017) and improve their approach by using the more powerful BERT model which has shown to be effective on stock price prediction (Dong et al., 2020). To further enhance this model, we use a pretrained BERT on finance data: finBERT, which should be better able to capture financial content (Araci, 2019).

²<https://bdc.consulting/insights/cryptocurrency/analyzing-crypto-headlines>

¹<https://pumpolymp.com/>

Since Twitter is a preferred hangout for cryptocurrency traders, we opted to work with this data source. To further improve the accuracy of our model, we included not only NLP data, but also correlated assets such as Gold and Ethereum, as well as a variety of technical indicators. Our resulting multimodal dataset, PreBit, is made available online³.

In our experiments, we carefully examine the effectiveness of our proposed multimodal models on predicting extreme Bitcoin price movements, as well as study the individual influence of Twitter and technical analysis data. Contrary to many other research studies, we also propose a trading strategy based on the models and thoroughly backtest it to illustrate how such models may be used to decrease the downward risk of trading strategies.

3. Multimodal Dataset

We present a new dataset, PreBit, which consists of two modalities: daily price, correlated assets with technical analysis data for BTC (which we will refer to as TA data for simplicity), as well as the contents of a 5,000 of daily tweets. The dataset is available online⁴. In the next two subsections we will discuss these two modalities in more detail.

3.1. Twitter data

Collecting tweets The PreBit dataset consists of publicly available tweets containing the keyword ‘Bitcoin’ from 1 January 2015 until 31 May 2021. A total of 5,000 tweets (or the maximum available that day) were collected per day, starting at 23:59:59 GMT+0 and tracking backwards. This resulted in a total of 9,435,437 tweets over the entire period. In 2015 there are a few days with less than 5,000 tweets, which is due to the fact that Bitcoin was not yet as popular in these earlier years.

Each tweet contains the following attributes: username, timestamp in datetime format (minutes), number of retweets and favourites, tweet content, mentions (user names), hashtags, unique ID, and permalink. To protect user privacy, all information related to user identity was discarded. Although many of these attributes may be useful for future models, the current study focuses only on the tweet content.

Preprocessing To efficiently input tweet content into machine learning models in a way that is understandable, we first need to do preprocessing to clean the data and make it less noisy. This preprocessing step is a common practice in NLP models to ensure that the remaining word tokens are meaningful. Each tweet has gone through the following process in sequence:

1. Converted all English alphabet characters to lower case.

³<https://www.kaggle.com/datasets/zyz5557585/prebit-multimodal-dataset-for-bitcoin-price>

⁴<https://www.kaggle.com/datasets/zyz5557585/prebit-multimodal-dataset-for-bitcoin-price>




Figure 1: Top 20 most frequent words in the tweets in our dataset.

2. Removed all the URLs.
3. Removed the symbols ‘@’ and ‘#’.
4. Removed all the characters that are not in the English alphabet, to filter out numbers and non-English tweets using the library spaCy.
5. Removed sentences with only 1 word token left.

Figure 1 illustrates the 20 words with the highest occurrence frequency from the entire Twitter dataset. There are a total 36,639 unique words. Stopwords, ‘bitcoin’, ‘btc’ and ‘cryptocurrency’ have been excluded from the counting process, as unsurprisingly, they are the most frequent words given our search criteria when constructing the dataset. We notice two other cryptocurrencies were often mentioned together, ‘eth’ (Ethereum) and ‘xrp’(Ripple). Hence, we proceeded to include Ethereum price as part of the technical indicators for TA dataset. Action words such as ‘buy’ and ‘get’ also occurred with a high frequency.

3.2. TA data

For simplicity, we refer to the price related input data as TA data. It consists of three elements: candlestick data, related asset prices, and a few selected technical indicators. We will discuss each of these in more details below.

Candlestick data We included the daily Bitcoin OHLCV data from CryptoCompare⁵. As Bitcoin is traded on multiple exchanges, data from one exchange may not capture the full picture. Cryptocompare aggregates the trading volume and prices from different exchanges to provide a more comprehensive overview of market activities (also used by Alonso-Monsalve et al. (2020)). The data covers the period from 1 January 2015 until 31 May 2021, which is the same range as the collected Twitter data.

Technical indicators and correlated assets In addition to the basic OHLCV data collected directly from CryptoCompare, we have also calculated 13 standard technical indicators, including correlated asset prices. Figure 2 visualizes these indicators together with the Bitcoin close price. For better visibility, only the last year of our data is displayed.

- Moving Averages (5) - Moving average is a commonly used feature in technical analysis (Ellis and Parbery,

⁵cryptocompare.com

2005). We have included five different moving averages: the 7-day simple moving average, the 21-day simple moving average, and three exponential moving averages. The first exponential moving average uses a decay rate of 0.67. To support the calculation of Moving Average Convergence Divergence (MACD), we calculated 12-day and 26-day exponential moving average and kept them as indicators.

- Moving Average Convergence Divergence (MACD) (1) - this indicator is built upon moving averages. It compares the short-term moving average to the long-term moving average in order to identify the price movement momentum. If the short-term moving average is greater than the long-term moving average, it suggests that the recent price demonstrates an upward momentum. In our set-up, we have selected the 12-day and 26-day exponential moving averages to calculate the MACD.
- 20-day Standard Deviation of BTC Closing price (1)-this is a basic measure of the BTC price volatility, and used to calculate the Bollinger Bands.
- Bollinger Bands (2) - Bollinger Bands are volatility bands placed above and below the moving average of price. We have set up the band to be \pm two 20-day standard deviation of the price from the 21-day simple moving average. The band captures information on price volatility.
- High-Low Spread (1) - This is the distance between the highest and lowest price of the day. The indicator attempts to capture the price volatility of the day.
- ETH price (1) - the close price of Ethereum on the same day. Bitcoin and Ethereum currently the two cryptocurrencies with the two largest market caps (excluding USDT). Their price has historically shown correlation (Katsiampa, 2019; Beneki, Koulis, Kyriazis and Papadamou, 2019).
- Gold spot price (1) - Bitcoin is often referred to as a popular inflation hedge, or ‘digital gold’ (Kang, McIver and Hernandez, 2019), hence we have included the Gold price.
- Moving Average Indicator (1) - This feature is a binary representation which indicates whether the 7-day simple moving average price of the day is 5% higher than the current price.

Normalising Procedure The features that are directly related to the Bitcoin price were normalised as percentage change of the closing price of the previous day as per Equation 1. These include OHLC, moving averages, and Bollinger Bands. Other features including volume, ETH price and gold spot price were normalised as percentage change over their own value of the previous day as per

Table 1

Pearson Correlation coefficient of each feature with Bitcoin's next day closing price.

High	Low	Close	Volume
-0.017	-0.058	-0.056	0.013
Adj Close	ma7	ma21	ema
-0.056	-0.039	-0.032	-0.060
26ema	12ema	MACD	20sd
-0.034	-0.037	0.023	0.051
upper band	lower band	spread	ma feature
0.008	-0.065	0.033	-0.040
eth	gold		
-0.092	-0.020		

Equation 2; Lastly, for MACD, 20-day standard deviation and high-low spread, we normalised as percentages of the closing price of the previous day, as per Equation 3.

$$\text{feat_norm_btc}_t = \frac{\text{feat}_{(t)} - \text{price_BTC_close}_{(t-1)}}{\text{price_BTC_close}_{(t-1)}} \quad (1)$$

$$\text{feat_norm_self}_t = \frac{\text{feat}_{(t)} - \text{feat}_{(t-1)}}{\text{feat}_{(t-1)}} \quad (2)$$

$$\text{feat_norm_prev}_t = \frac{\text{feat}_{(t)}}{\text{price_BTC_close}_{(t-1)}} \quad (3)$$

The Pearson correlation between the above mentioned (normalized) technical indicators and the next day Bitcoin price is shown in the Figure 3 and Table 1. We notice that there is generally a low direct correlation between the features and the next day Bitcoin close price (normalized). The price of Ethereum has the highest correlation in terms of absolute value to the next day Bitcoin price. Volatility related indicators such as the 20-day standard deviation and lower Bollinger band show a stronger correlation as well. No one feature has an outspoken higher correlation with our predictive feature, hence we include all of them in our model.

3.3. Data labels

Our research aims to answer whether we can predict extreme price movements using a hybrid multimodal model. Therefore, the prediction class labels should serve to flag out extreme price movements. We created binary class labels based on whether the percentage change of the daily BTC close price is above a selected threshold θ for each experimental cases. The digital asset market generally has much higher volatility over the traditional market, therefore, we chose the work with the daily ‘high’ and ‘low’ values respectively for the up and down task. We explored four values for the threshold θ : $\pm 2\%$ and $\pm 5\%$. Being able to flag




Figure 2: Visualisation of selected TA features.

Table 2

Class distribution for different predictive tasks θ .

θ	+5 %			+2%			-5 %			-2%		
	T	F	True Ratio	T	F	True Ratio	T	F	True Ratio	T	F	True Ratio
Training Set	292	1680	14.84%	810	1162	41.08%	298	1674	15.11%	789	1183	40.01%
Test Set	60	305	16.44%	168	197	46.03%	60	305	16.44 %	175	190	47.95%

such large price movements may offer investors a warning sign protect their assets from downside volatility or profit from upcoming large price movements.

The $\pm 5\%$ thresholds will serve to alert investors of upcoming extreme volatility. Since these are extreme events, the positive and negative class ratio distribution ratio is around 1:5. With the $\pm 2\%$ thresholds, the class distribution ratio is around 2:3, which is a lot more balanced. Although a 2% move for Bitcoin might not be considered significant given the market volatility, the more balanced dataset distribution case could serve to provide additional perspective to our experiments, which will be discussed later in Section 6. The distribution of the labels can be found in Table 2.

4. Multimodal Price Extreme Movement Model

We propose a multimodal hybrid model that consists of two input modalities: Twitter content and TA data. A predictive model was built for each of these modalities and a fusion model was then added to the architecture to come to a joint prediction. The task of this model is to predict extreme price movement (up/down 2 or 5%) within the next one day (i.e. looking at high/low prices, not just closing price). Figure 4 shows an overview of the proposed architecture.

We will discuss the three parts of our model in the next subsections.

4.1. Twitter CNN model

For the Twitter model, we first represented the daily tweets as a dense embedding, and then we implemented two possible convolutional neural network (CNN) configurations which were evaluated in the results section.

4.1.1. FinBERT context embeddings

After the tweets are preprocessed (see Subsection 3.1), we represent them with efficient dense embeddings. There are various ways to obtain word embeddings, including Bag of Words (BoW), Term Frequency - Inverse Document Frequency (TF-IDF), Word2vec, Global Vectors for Word Representation (GloVe) (Pennington, Socher and Manning, 2014). Earlier embedding models such as BoW and TF-IDF in essence create a sparse matrix based on the (co-occurrence) frequency of words. GloVe (Pennington et al., 2014), a later model, uses a non-parametric and unsupervised learning algorithm that tries to capture the semantic similarities between words, and outputs them into a fixed-dimension feature representation. Word2vec embeddings are




Figure 3: Correlation matrix for the TA indicators.




Figure 4: Proposed multimodal hybrid model.

also much more dense and trained unsupervised by a simple neural network with one hidden layer (Mikolov et al., 2013b).

We opted to use the context (sentence) embeddings from the state-of-the-art FinBERT model (Araci, 2019) which

is built upon Bidirectional Encoder Representations from Transformers (BERT) (Devlin et al., 2018) to obtain our embeddings. When BERT was developed in 2018 it outperformed traditional embedding models on variety of language tasks (Devlin et al., 2018). FinBERT is in essence a BERT

model, finetuned on financial text datasets such as TRC2-financial⁶, a dataset provided by Thomson Reuters, which consists of 1.8 million news articles published between 2008 and 2009. Because FinBERT is trained on financial texts, it is better suited for any financial related task such as the one tackled in this research. The FinBERT model obtained a 10 to 20% increase in accuracy in Financial PhraseBank dataset classification tasks over the baseline models, and outperformed other state-of-the-art models in terms of both mean squared error (MSE) and R^2 on the FiQA sentiment dataset. These recent development incentivized us to use FinBERT in our model for embeddings.

The context embeddings for a given sentence generated by the FinBERT model are a 768-dimensional vector. As our dataset consists of 5,000 daily tweets across 6 years and 5 months, there would be over 9.5 million entries to process for the embeddings, resulting in a large amount (5,000) of embeddings per day. Considering the fact that tweets are very short (maximum 280 characters), and with computational efficiency in mind, we decided to concatenate multiple tweets into one longer text. Specifically, one day worth of tweets is concatenate to form text slices of 200 word tokens, with 50 overlapping tokens at the start of next text slice. Finally the embeddings are obtained for each of the text slices and fed into the Twitter CNN model. Each embedding has a dimension of 1×768 . Embeddings for tweets from the same day are stacked into a 2-dimensional vector of size $n \times 768$. Since the maximum number of text slices per day found in our dataset is 362, we used zero-padding on all the 2-dimensional input vectors to ensure a size of 362×768 .

4.1.2. CNN architectures

We experimented with two different convolutional neural network (CNN) architectures for the language-based model: a sequential CNN and a parallel CNN.

Parallel CNN Applying CNN on sentence classification has seen quite some research interest (Zhang and Wallace, 2015; Zhang, Roller and Wallace, 2016; Hsu, Moon, Jones and Samatova, 2017; Shin, Kim, Yoon and Jung, 2018). The popular work by Kim (2014) offered the basis for our model. In his work, Kim used the 300-dimensional Word2vec embedding for each token in a sentence, and fed them into a 1-D CNN model. This work highlighted the importance of well-trained unsupervised pretraining of word vectors, and also demonstrated that using a simple 1-layer convolution can produce high performance on a variety of tasks.

In our work, we are focused on capturing the collective discussions and views on Bitcoin from the tweets on a given day. The information behind a singular tweet can often be trivial and noisy. Therefore, our model input consists of multiple embeddings which together capture a full day of tweet sentences as opposed to just a sentence of tokens in Kim's model. The intuition for this parallel CNN architecture is that the model should first capture the most relevant information between sentences from the embedding, and then extract the

most relevant pieces of information from each of the 362 text slices (maximum number of daily text slices).

Our proposed parallel CNN model first applies 1-D convolution on the input (embedding) layer. This convolution operation uses three sets of filters of size: 3×768 , 4×768 , and 5×768 , but the filters move only in one direction. Afterwards, we apply 1-D max pooling on the 3 sets of feature maps resulting from the convolution operations, with the feature map length as the kernel size (resulting in one value per feature map), and concatenate the output. Then we pass the result through two fully connected layers followed by the classification layer. An overview is provided in Figure 5.

Sequential CNN A sequential CNN model (see Figure 6) was also implemented. This model essentially treats the embeddings as images of size 362×768 and applies a 2-D convolution operation on this input. This architecture is inspired by the LeNet-5 model (LeCun, Bottou, Bengio and Haffner, 1998). The main difference is that we added one extra convolutional layer and used a filter size of 5×5 , 4×4 , 3×3 respectively in each of the three convolution layers.

4.1.3. Implementation and hyperparameters

Loss function Two different loss functions were implemented for the Twitter CNN model: a conventional Binary Cross Entropy (CE) loss and a Focal Loss (Lin, Goyal, Girshick, He and Dollár, 2017) developed by Facebook AI Research. The CE loss is a staple in classification model training. Since our dataset is unbalanced (see Section 3, there is an incentive to use a loss function that takes this into account, i.e. Focal Loss (FL).

FL was proposed by Lin et al. (2017) to train dense object detectors. Below we show the formulas for the two loss functions for each output sample, in the case of a binary classification task (class $t = 1$ or $t = 0$), with p_t being the probability of a sample belonging to class t .

$$BCE(p_t) = -\log(p_t) \quad (4)$$

$$FL(p_t) = -\alpha_t(1 - p_t)^\gamma \log(p_t) \quad (5)$$

$$p_t = \begin{cases} p & \text{if } t=1 \\ 1 - p & \text{otherwise} \end{cases} \quad (6)$$

As we can see, FL differs from BCE through the additional factor $-\alpha_t(1 - p_t)^\gamma$. The parameter α ranges from 0 to 1 and attempts to tackle the class imbalance directly by amplifying the loss from the minority class. It is usually set as the inverse class frequency or tuned on the validation set. The parameter γ attempts to reduce the loss contributed by high confidence classifications, namely the easy examples, and generally is in the range from 0 to 5 to be effective. These parameters prevent the model from being overwhelmed by the easy negatives and enable the model to focus on the minority positives. Lin et al. (2017) reported that detectors trained with FL showed superior accuracy results compared to state-of-the-art detectors trained with BCE loss.

⁶<https://trc.nist.gov/data/reuters/reuters.html>




Figure 5: Parallel Twitter CNN model.




Figure 6: Sequential Twitter CNN model.

Hyperparameters The model was implemented in PyTorch, and we used the standard Adam optimiser with PyTorch default parameters. For the Sequential CNN model, we added L2 regularisation through the Adam optimizer’s *weight_decay* parameter set at 0.0005 to 0.001 to prevent overfitting. A ReLU activation is applied after each convolutional layer. A dropout of 0.5 is applied on the first fully connected layer. Additionally, ReLU activations are also applied after fully connected layers in the Sequential CNN model.

The performance of the sequential and parallel CNN models will be compared in the experiment section. We should note that the sequential CNN is computationally more expensive as the model has 7.6 million trainable parameters versus the 2.6 million in the parallel model, this may provide difficulties when training on small datasets. Yet, these layer, loss function, and kernel related hyperparameters were chosen based on best performance with trial-and-error on the validation set. The original training set was split into a (language) training set (90%) and a (language) validation set (10%).

4.2. TA model

The TA model takes as input all available TA data as described in Section , including candlestick data, and technical indicators including correlated assets, to predict extreme price movement (up/down 2-5%). We experimented with several simple models such as logistic regression, support vector machines (SVM), a feed-forward neural network, as well as a long-short term memory model (LSTM) with a range of feature set-ups. From these tests, we have selected the best performing model –SVM– to use as part of our model. While this model may seem simple, its performance makes sense given the limited size of our dataset.

Model Input This model will take as input all of the features described in Section 4.2: OHLCV data as well as 13 technical indicators, resulting in a total of 19 features per day. To provide additional historical price information, we concatenated this data in windows of 5 days. This resulted in a final input size of 1×95 . We experimented with Principle Component Analysis (PCA) values to reduce the dimension of the input, however, it did not produce better results. Thus, in the final version of the model, no PCA was applied.

The OHLCV SVM model was implemented with Scikit-learn. Based on trial-and-error, we opted to use the Radical

Basis Function (RBF) kernel. The RBF kernel has 2 input parameters: C and gamma. We performed a Grid Search to determine the optimal C and gamma. This search used 4-fold cross validation with the F1-score as the evaluation metric to guide the search. The reason for using F1-score as the evaluation criteria will be discussed further in Section 5.

4.3. Fusion Model

The proposed fusion model takes the prediction probabilities output by the Twitter and TA model as input and makes a final prediction about the extreme price movement. An overview of the Fusion model can be found in Figure 4.

Model Input The input to the Fusion model consists of the probabilities for the positive class from the Twitter model and TA model. More specifically, for the TA SVM model, we applied a sigmoid function to the decision function output. For Twitter model, we took the model output after the softmax function. The resulting probabilities from both models were concatenated so they were of size 1×2 . This small vector forms the input to the fusion model.

Model Architecture We experimented with several models such as feed-forward neural networks (FNN), logistic regression, SVM with RBF kernel and SVM with polynomial kernel. Except for the neural network models, who were implemented in PyTorch, we used Scikit-learn to implement all the models. Given the limited size of our input dataset, and the results from this trial-and-error experiment, we proceeded to use SVM in our final experiments. The parameter selection process was conducted similar to that of the TA SVM model.

5. Experimental Setup

We want to uncover which elements of our hybrid multimodal model contribute most to accurately predicting extreme BTC price movements. In particular, we are interested to explore if the model accuracy improves by incorporating a predictive model based on Twitter data in our hybrid architecture. To properly explore this question we have performed an ablation study for each of our four tasks: will the BTC price go up by 5%, down by 5%, up by 2%, and down by 2% on the next day. Separate models were trained for each task.

For each task, five models were evaluated in an ablation study to determine which input modality has the potential to improve predictions, and which CNN architecture is most efficient. These five models compared that were compared are the:

- TA SVM model;
- Twitter model (parallel);
- Twitter model (sequential);
- Fusion model (parallel) - using output from parallel CNN model as part of the input;
- Fusion model (sequential) - using output from sequential CNN model as part of the input.

5.1. Training-Test split

The dataset includes data from 1 January 2015 until 31 May 2021, and consists of a total of 2,337 entries after clean-up. For our experiments, we split the data into a training set and a test set. The latter consists of the last 1 year of our data, i.e. from 1 June 2020 until 31 May 2021, totalling 365 entries. This makes the split ratio around 5.4:1. The Bitcoin price during the test period includes a long bull run as well as a bear period (see Figure 9). Thus, we believed this to be as a good period to evaluate our model on. The non-stationary nature of the data makes it hard to generalize results, hence, we selected a test period with both types of markets to compensate as best as possible (De Prado, 2018). All of the hyperparameter tuning was done only on a validation set which was part of the original training set (see Table 2). For the Twitter CNN model, the training set was further split into a training and validation set with 9:1 ratio. We used the validation set to select the optimal hyperparameters including: FL parameters - α and γ , number of filters, number of layers and dropout ratio. For the TA and Fusion SVM models, 4-fold cross validation (on the training set) was used during the Grid Search for parameter tuning.

5.2. Evaluation metrics for predictive model

A very commonly used metric for any classification task is prediction accuracy. Although this provides an overview of the model performance, for datasets with noticeable class imbalance such as ours, accuracy alone is not enough. Therefore, we also include precision, recall, as well as F1-score. The latter is a comprehensive measure that accounts for both precision and recall rate for the prediction output as it is their harmonic mean. This means that both false positives as well as false negatives are considered. In addition, we report the confusion matrices to provide more complete insight into misclassifications. In our case this is particularly important as traders may be more interested to be absolutely certain of their model's predictions, and care less about missed opportunities, depending on their risk appetite, and hence want to focus on maximizing precision. We will illustrate this further in the backtesting section, whose setup is explained in the next subsection.

5.3. Trading strategy backtesting

To further evaluate how our model signals may be helpful in reducing risk during trading, we propose simple long-only trading strategies and analyse them with backtesting. The backtesting period is the same as the test set coverage, from 1 June 2020 until 31 May 2021. We assume no leverage, no transaction fees, complete liquidity and instant transactions without slippage.

Since our models performed best for Task 1 (predict up 5% BTC price), we have focused our trading strategy on this model. Both the TA and Fusion model (sequential) showed higher performance than the other models, they were used to construct the trading signals.

Trading strategy We implemented the following trading rules: if the model predicts a 5% upward price movement

for the next day, it flags a buy signal. We then buy 100% of all the cash holdings at the closing price of the day. The holding period is always set to one day, i.e., we always sell at the closing price the next day after buying. We limit the strategy to perform only one action per day, either buy, hold or sell. When there are consecutive days of buying signals, we only buy and hold during the first day. The occurrence of the aforementioned situation is rare during our test period, thus it has limited impact on the performance.

Baselines and metrics In addition to the TA SVM and Fusion model (sequential), we have included four other strategies for comparison in our backtesting:

- Buy and Hold - Buy on the first day and sell on the last. A commonly use baseline comparison.
- 7-D and 21-D Moving Average (MA) Cross - Buy when the 7-D MA goes above the 21-D MA, sell when 7-D MA dives below the 21-D MA. Sometimes it is referred to as the ‘Golden Cross’. It is a classic trading strategy capitalising on momentum Liu, Li, Li, Li and Xie (2021).
- Fusion model (sequential) with 0.95 prediction threshold - This is a variation on our Fusion model (sequential). The original Fusion model predicts between two classes by comparing the probability for each class to the default threshold 0.5. If the model’s output probability is greater than 0.5, the predicted class will be positive. In this variation, we have increased this threshold to 0.95, meaning that the model only predicts the positive class only if it has extremely high confidence. We explore the influence of this on reducing the risk of the trading strategy.
- Fusion model (sequential) with 0.99 prediction threshold - Similar to the above model, but with threshold set extremely high at 0.99.

To evaluate the backtesting results, we examine the following metrics:

- Profit % - The percentage of profit made. This reflects the overall performance of the strategy during the period.
- Sharpe Ratio - A risk-adjusted measure of the return (Sharpe, 1998). The risk-free interest rate is assumed to be 0 in our calculation.
- Sortino Ratio - A variation of the Sharpe ratio that only factors in the downside risk (Chaudhry and Johnson, 2008).
- Max Drawdown % - An indicator for downside risk over the full trading period. It measures the maximum observed loss of the portfolio.
- Win % - The ratio of profitable trades.

- Number of Trades - The number of trades made, which may be dependent upon the transaction costs. Note that in this low-frequency trading scenario, we omit the trading costs. For a more comprehensive analysis of more complex trading strategies this should be included in future work.

In the next section, the various results of our experiments are discussed.

6. Results

We ran a number of different experiments. First, an ablation study was conducted to examine the influence of the different parts of our proposed hybrid multimodal model on the prediction accuracy for each of the four tasks. Next, the best models were used to construct basic trading strategies for which we report the backtesting results and explore if they can be used to mitigate risk and exposure to volatility. When constructing the strategies, we also investigate the influence of probability thresholds on risk reduction.

6.1. Influence of different modalities

To explore the influence of each of the separate components of our multimodal model on the prediction accuracy, we performed an ablation study for each of the four predictive tasks. For each task, we report the best performing model in terms of the aforementioned evaluation criteria as well as the hyperparameters used in Tables 3, 4, 5, 6. The reported evaluation metrics include precision, recall, F1-score and overall accuracy on the test set. Given the class imbalance in our dataset, we pay special attention to the F1-score for positive class, weighted F1-score, the positive class precision as well as the recall rate. Positive class precision has practical significance because if a trading strategy is built upon the model predictions, higher precision indicates higher confidence which may be useful information when executing a buy or sell signal. While a positive class recall rate means that the proposed trading strategy would capture as many buy signals as possible, thus resulting in a lower opportunity cost for missing out.

Overall we observe a better performance by the Fusion models on the tasks related to upward price prediction compared to the TA SVM models, thus confirming the importance of incorporating Twitter content. For the Task Up 5%, (Table 3), the Fusion model (sequential) shows a higher positive class F1-score as well as a higher overall accuracy compared to the models based on individual modalities. Further breaking down the performance, we notice that the Fusion model traded off very slight positive class precision rate for a much higher positive class recall rate as indicated in the confusion matrices (Figure 7). The Fusion models were able to accurately predict around twice as many true positives for the Task Up 5%, all the while maintaining the performance in terms of precision. From a practical point of view, this means that a trading strategy based on these signals may have twice as many winning trades and thus incur less opportunity cost due to staying market neutral.

Table 3

Performance results for the Task Up 5%.

Models	Precision		Recall		F1-score			Accuracy	Parameters
	T	F	T	F	T	F	Weighted		
TA SVM	0.32	0.85	0.22	0.91	0.26	0.88	0.78	71.23	<i>RBF, C = 50, gamma = 0.5</i>
Twitter CNN (parallel)	0.20	0.86	0.47	0.62	0.28	0.72	0.65	59.22	$\alpha = 0.12, \gamma = 1$
Twitter CNN (sequential)	0.18	0.93	0.95	0.13	0.22	0.30	0.24	26.10	$\alpha = 0.12, \gamma = 1, L2weight = 0.0005$
Fusion model (parallel)	0.31	0.89	0.48	0.78	0.37	0.83	0.76	73.42	<i>polynomial, C = 500, gamma = 50</i>
Fusion model (sequential)	0.31	0.89	0.50	0.78	0.38	0.83	0.76	73.70	<i>polynomial, C = 30, gamma = 50</i>

Table 4

Performance results for the Task Up 2%.

Models	Precision		Recall		F1-score			Accuracy	Parameters
	T	F	T	F	T	F	Weighted		
TA SVM	0.61	0.63	0.49	0.73	0.54	0.67	0.61	61.91	<i>RBF, C = 500, gamma = 0.1</i>
Twitter CNN (parallel)	0.48	0.62	0.80	0.27	0.60	0.37	0.48	52.48	CE loss
Twitter CNN (sequential)	0.48	0.61	0.81	0.25	0.60	0.36	0.47	51.08	CE loss $L2weight = 0.001$
Fusion model (parallel)	0.62	0.67	0.60	0.68	0.61	0.67	0.64	64.38	Logistic regression
Fusion model (sequential)	0.54	0.66	0.70	0.50	0.61	0.57	0.59	58.90	Logistic regression

For Task Up 2% (Table 4), the good performance of the Fusion model (parallel) is even more apparent. Except for negative class recall rate, all other metrics show improvements compared to the other models. Looking at Task Down 5 and 2 % respectively (Tables 5 and 6), the models have a comparable performance and the improvements due to the Twitter model are less obvious. This may be due to the fact that the TA SVM model is already quite good, arguably because of the strong correlation between Bitcoin price and some of the model inputs like Ethereum price and 20-day standard deviation of price (see Figure 3). In future research, this effect may be increased by focusing on

tweets by influencers in the ‘Crypto-Twitter sphere’ instead of random tweets that mention Bitcoin, or by finetuning our word embedding representation to capture crypto- and Twitter-specific vocabulary.

When evaluating these models we should keep in mind the high class imbalance present in our dataset. In addition, since these predictions are quite directly translatable for use in a trading strategy, a resulting trading strategy could easily reach a win rate in the range of 50-60%. Such rates are considered quite promising and may obtain good returns. A full analysis of a naive trading strategy is provided in Section 6.3. Overall, our proposed models have a good performance,

Table 5

Performance results for the Task Down 5%.

Models	Precision		Recall		F1-score			Accuracy	Parameters
	T	F	T	F	T	F	Weighted		
TA SVM	0.40	0.87	0.28	0.92	0.33	0.89	0.80	81.36	<i>RBF, C = 1000, gamma = 0.1</i>
Twitter CNN (parallel)	0.20	0.94	0.90	0.31	0.33	0.46	0.44	40.63	$\alpha = 0.12, \gamma = 1$
Twitter CNN (sequential)	0.14	0.81	0.38	0.53	0.20	0.64	0.57	50.27	$\alpha = 0.12, \gamma = 1, L2weight = 0.0005$
Fusion model (parallel)	0.37	0.87	0.28	0.90	0.32	0.88	0.79	80.27	Logistic regression
Fusion model (sequential)	0.40	0.87	0.28	0.92	0.33	0.89	0.80	81.37	Logistic regression

Table 6

Performance results for the Task Down 2%.

Models	Precision		Recall		F1-score			Accuracy	Parameters
	T	F	T	F	T	F	Weighted		
TA SVM	0.55	0.56	0.43	0.67	0.49	0.63	0.56	56.71	<i>RBF, C = 1000, gamma = 0.1</i>
Twitter CNN (parallel)	0.50	0.67	0.91	0.17	0.65	0.28	0.45	53.85	CE loss
Twitter CNN (sequential)	0.44	0.42	0.66	0.23	0.53	0.29	0.41	43.34	CE loss $L2weight = 0.001$
Fusion model (parallel)	0.56	0.57	0.46	0.66	0.50	0.62	0.56	56.44	<i>polynomial, C = 10, gamma = 10</i>
Fusion model (sequential)	0.54	0.56	0.48	0.62	0.51	0.59	0.55	55.34	<i>polynomial, C = 10, gamma = 50</i>

		OHLCV SVM		Fusion model (parallel)		Fusion model (sequential)				
		Predicted		Predicted		Predicted				
		T	F	T	F	T	F			
+5%	Label	T	13	47	T	29	31	T	30	30
		F	27	278	F	66	239	F	66	239
+2%	Label	T	82	86	T	100	68	T	118	50
		F	52	145	F	62	135	F	99	98
-5%	Label	T	17	31	T	17	43	T	17	31
		F	25	279	F	29	276	F	25	279
-2%	Label	T	76	99	T	81	94	T	84	91
		F	62	128	F	64	126	F	72	118

Figure 7: Confusion Matrices.

with the upward extreme movement prediction models being successfully improved by adding Twitter models.

6.2. Predictive threshold tweaking

Before diving into an actual trading strategy that may be built upon our proposed models, it is important to consider the predictive threshold, especially since it has a direct influence on risk reduction. Our models were optimized based on F1-score, the harmonic mean of precision and recall rates, two metrics that can be traded off for one another by changing the predictive threshold.

The Fusion model's classification decisions are derived by comparing the SVM's output decision function to a threshold (0.5 as default). The parameters and decision functions for the SVM models have been optimized on the training dataset and fixed before getting the results on the testing set. Therefore, moving the threshold does not alter any model state, but only changes the reported classification results. If a higher precision rate (high-confidence positive class predictions) is desired, a higher threshold could be explored. (Yu, Mu, Sun, Yang, Yang and Zuo, 2015).

We report different confusion matrices based on a much higher decision threshold (0.95 and 0.99) in the best performing Fusion models for both Task Up 5% and 2% in Figure 8. For Task Up 5%, the Fusion model (sequential)'s precision rate for the positive class improved slightly. The confusion matrices report a quite different amount of true positives. The improvement is more evident for the Fusion model (parallel) for Task Up 2%, with a peak at the 0.95 threshold.

In the next section, we will uncover the full impact of this threshold tweaking on the trading strategy.

6.3. Backtesting results

Backtesting We implemented a simple, naive trading strategy based on the predicted classes for by our Fusion model as

explained in Subsection 5.3. Since the best overall predictive results (in terms for F1-score) were obtained for predicting a 5% increase in BTC price over the next day (see Table 3), we have opted to further evaluate our models' performance for this task with backtesting.

The backtesting statistics were calculated using the library `vectorbt`⁷. We report the results for our entire test period in Table 7. Whenever we are evaluating financial data, the non-stationarity of the data poses limitations and skews the metrics De Prado (2018). A rolling window test set may prove to be a slightly better representation, however, it would limit the amount of data we have to train our models. Hence, we ensured that our test period is long enough (1 entire year), and contains a steep upward (bull) as well as downward (bear) period. We report the results for the bull and bear periods separately in Tables 8, and 9.

Looking at the entire test period (Table 7), a Buy and Hold strategy achieves the highest Profit %. This is unsurprising given the rising trend in Bitcoin in the long run. This performance has a huge risk exposure, however, with a maximum drawdown (MDD) of 45.5%. Not many investors would be willing to risk almost half of their capital before seeing gains. Hence, we explore how our models can be used to provide a more market neutral strategy with lower risk exposure.

The Sortino ratio gives us an impression of risk free returns (excluding the upwards volatility, which is still included in the Sharpe ratio). Our proposed TA model achieves the highest Sortino ratio, followed closely by 7-D and 21-D MA Cross as well as the Fusion model with 0.99 threshold. The TA SVM model has a significantly lower maximum drawdown of 16% compared to the Buy and Hold drawdown of 45.5%, while still obtaining a nice 60% in returns with only 31 days of market exposure over the entire year. A

⁷<https://github.com/polakowo/vectorbt>




Figure 8: Confusion Matrices for Threshold Tuning.

Table 7

Backtesting results the full test period.

Strategies	Profit %	Sortino	Sharpe	Max Drawdown %	Win%	Num of Trades
Buy and Hold	249.3	3.28	2.08	45.5	N.A	N.A
7-D and 21-D MA Cross	199.7	3.60	2.17	37.7	40.0	10
TA SVM	60.4	3.62	1.56	16.0	58.0	31
Fusion model	1.4	0.26	0.18	12.4	56.0	50
Fusion model 0.95 threshold	49.9	3.02	1.39	14.9	55.6	36
Fusion model 0.99 threshold	56.6	3.45	1.49	16.0	56.6	30

similar result is obtained by the Fusion model with 0.5 and 0.99 threshold.

When comparing the result of the three Fusion models, we observe consistently better results with the 0.95 threshold over the default threshold (0.5). Raising the threshold from 0.95 to 0.99, however, does not always yield enhanced performance. Threshold tweaking based on the strategy in use is essential. In future research, the impact of threshold selection based on custom, more advanced trading strategies could be investigated.

Looking closer at the bull period (days 150-350) in Figure 9, we notice that, as expected, the Buy and Hold strategy performs very well, although still with a 25% MDD. The

proposed TA SVM and Fusion model with 0.95 threshold still achieve impressive performance in terms of Sortino ratio (4.65 and 5.97 respectively) and MDD (9.8% and 8.3% respectively), while sacrificing some profits for this reduced risk.

It is during bear periods that the usefulness of our proposed models really becomes apparent. Table 9 shows the trading results for the bear period (day 315 to day 365). During the bear period, both the TA SVM as well as the Fusion model with 0.95 and 0.99 threshold perform significantly better than the Buy and Hold and the MA Cross benchmark models. While the latter is down as much as -40.5% profit, the TA SVM and Fusion model with 0.99

Table 8

Backtesting results the bull period.

Strategies	Profit %	Sortino	Sharpe	Max Drawdown %	Win%	Num of Trades
Buy and Hold	345.5	8.10	4.50	25.1	N.A	N.A
7-D and 21-D MA Cross	96.0	4.16	2.43	29.9	75.0	5
TA SVM	36.6	4.65	1.90	9.8	63.2	19
Fusion model	12.9	1.72	1.09	12.4	57.1	28
Fusion model 0.95 threshold	50.4	5.97	2.40	8.3	68.2	22
Fusion model 0.99 threshold	33.4	4.32	1.77	9.9	61.1	18

Table 9
Backtesting results the bear period.

Strategies	Profit %	Sortino	Sharpe	Max Drawdown %	Win%	Num of Trades
Buy and Hold	-40.5	-4.27	-3.33	45.5	N.A	N.A
7-D and 21-D MA Cross	-6.3	-1.03	-0.86	16.0	0.0	1
TA SVM	32.0	12.72	4.30	6.3	85.7	7
Fusion model	-5.5	-1.54	-1.12	10.6	50.0	8
Fusion model 0.95 threshold	17.0	6.96	2.89	6.3	71.4	7
Fusion model 0.99 threshold	32.0	12.73	4.30	6.3	85.7	7




Figure 9: Bitcoin price during the entire test period.

threshold reaches 32% profit. This nicely illustrates the usefulness of our proposed strategy, because while Bitcoin has seen tremendous growth, it also goes through extensive bear periods where risk management is essential.

7. Conclusion

Bitcoin, and cryptocurrencies, are known for their volatile nature. We propose a cutting-edge multimodal model to predict extreme Bitcoin price movements (up/down 2 or 5 percent). In order to train our model, we created a new publicly available dataset, which includes 9,435,437 tweets that include the keyword ‘Bitcoin’ from 1 Jan 2015 until 31 May 2021. We also included based candlestick price/volume data, as well as selected technical indicators and correlated asset prices (Ethereum and gold). The resulting multimodal ensemble model uses normalized data, as well as the FinBERT context embeddings to provide a meaningful representation of our Twitter data.

In a thorough experiment, we perform an ablation study to compare the influence of adding the Twitter model or TA model to our hybrid model. This shows that adding prediction based on Twitter content improves the overall performance of the model for upward Bitcoin price prediction. Our proposed Fusion models demonstrate superior performance in positive class F1-score as well as overall accuracy in upward price prediction tasks compared to the TA SVM which uses only price and technical analysis data.

To further evaluate our model’s performance and demonstrate its practical use, we propose a simple (long only) trading strategy and reported the backtesting results for our models that predict Up 5% price movement. During




Figure 10: Trading strategy based on the TA model during the bear period.

this backtesting, we explored the influence of tweaking the predictive threshold on risk management. The results confirm the superior performance of our proposed TA SVM model as well as our multimodal Fusion model with 0.95 threshold in risk-adjusted measures such as Sortino ratio and maximum drawdown. While Buy and Hold strategies typically work well for Bitcoin and obtain huge profits, the risks can be substantial, with max. drawdown reaching 45.5% in our test period. Our models substantially reduce this risk while maintaining an impressive profit ratio.

The usefulness of our proposed approach becomes especially apparent during the bear market, when our Fusion strategy manages achieved 32% Profit (with long positions only), despite the fact that the Bitcoin price was down by -40.5%. We further observe that a carefully selected probability threshold can significantly improve the trading performance and lower the market exposure risk.

This work opens up many avenues for future research. For instance, the Twitter dataset could be more effective for predictions if it only includes tweets by influencers in the ‘crypto-Twitter sphere’, such as Elon Musk, CEOs of cryptocurrency exchanges, and many more. In addition, we may finetune the FinBERT model to better capture cryptocurrency-specific as well as Twitter-specific lingo. Finally, the resulting multimodal model’s prediction threshold may be further finetuned with a more complex trading strategy, possibly including the model’s class probability to size positions, to outperform the benchmark provided for our new dataset in this research.

CRedit authorship contribution statement

Yanzhao Zou: Development, lead author.. **Dorien Herremans:** Advisor, ideation, editing..

References

- Acosta, J., Lamaute, N., Luo, M., Finkelstein, E., Andreea, C., 2017. Sentiment analysis of twitter messages using word2vec. *Proceedings of Student-Faculty Research Day, CSIS, Pace University* 7, 1–7.
- Aditya Pai, B., Devareddy, L., Hegde, S., Ramya, B., 2022. A time series cryptocurrency price prediction using lstm, in: *Emerging Research in Computing, Information, Communication and Applications*. Springer, pp. 653–662.
- Afteniy, M., et al., 2021. Predicting time series with transformer .
- Aharon, D.Y., Demir, E., Lau, C.K.M., Zaremba, A., 2022. Twitter-based uncertainty and cryptocurrency returns. *Research in International Business and Finance* 59, 101546.
- Ali, M., Shatabda, S., 2020. A data selection methodology to train linear regression model to predict bitcoin price, in: *2020 2nd International Conference on Advanced Information and Communication Technology (ICAICT)*, IEEE. pp. 330–335.
- Alonso-Monsalve, S., Suárez-Cetrulo, A.L., Cervantes, A., Quintana, D., 2020. Convolution on neural networks for high-frequency trend prediction of cryptocurrency exchange rates using technical indicators. *Expert Systems with Applications* 149, 113250.
- Araci, D., 2019. Finbert: Financial sentiment analysis with pre-trained language models. *arXiv preprint arXiv:1908.10063* .
- Baker, S.R., Bloom, N., Davis, S., Renault, T., 2021. Twitter-derived measures of economic uncertainty.
- Beneki, C., Koulis, A., Kyriazis, N.A., Papadamou, S., 2019. Investigating volatility transmission and hedging properties between bitcoin and ethereum. *Research in International Business and Finance* 48, 219–227.
- Bollen, J., Mao, H., Zeng, X., 2011. Twitter mood predicts the stock market. *Journal of computational science* 2, 1–8.
- Bouri, E., Gupta, R., Tiwari, A.K., Roubaud, D., 2017. Does bitcoin hedge global uncertainty? evidence from wavelet-based quantile-in-quantile regressions. *Finance Research Letters* 23, 87–95.
- Chan, S.W., Franklin, J., 2011. A text-based decision support system for financial sequence prediction. *Decision Support Systems* 52, 189–198.
- Chaudhry, A., Johnson, H.L., 2008. The efficacy of the sortino ratio and other benchmarked performance measures under skewed return distributions. *Australian Journal of Management* 32, 485–502.
- Chen, Q., 2021. Stock movement prediction with financial news using contextualized embedding from bert. *arXiv:2107.08721* .
- Cruz, L.F.S.A., Silva, D.F., 2021. Financial time series forecasting enriched with textual information, in: *2021 20th IEEE International Conference on Machine Learning and Applications (ICMLA)*, IEEE. pp. 385–390.
- Das, S., Behera, R.K., Rath, S.K., et al., 2018. Real-time sentiment analysis of twitter streaming data for stock prediction. *Procedia computer science* 132, 956–964.
- De Fortuny, E.J., De Smedt, T., Martens, D., Daelemans, W., 2014. Evaluating and understanding text-based stock price prediction models. *Information Processing & Management* 50, 426–441.
- De Prado, M.L., 2018. *Advances in financial machine learning*. John Wiley & Sons.
- Demir, E., Gozgor, G., Lau, C.K.M., Vigne, S.A., 2018. Does economic policy uncertainty predict the bitcoin returns? an empirical investigation. *Finance Research Letters* 26, 145–149.
- Devlin, J., Chang, M.W., Lee, K., Toutanova, K., 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805* .
- Ding, X., Zhang, Y., Liu, T., Duan, J., 2015. Deep learning for event-driven stock prediction, in: *Twenty-fourth international joint conference on artificial intelligence*.
- Dong, Y., Yan, D., Almudaifer, A.I., Yan, S., Jiang, Z., Zhou, Y., 2020. Belt: A pipeline for stock price prediction using news, in: *2020 IEEE International Conference on Big Data (Big Data)*, IEEE. pp. 1137–1146.
- Elbagir, S., Yang, J., 2019. Twitter sentiment analysis using natural language toolkit and vader sentiment, in: *Proceedings of the international multicongress of engineers and computer scientists*, p. 16.
- Ellis, C.A., Parbery, S.A., 2005. Is smarter better? a comparison of adaptive, and simple moving average trading strategies. *Research in International Business and Finance* 19, 399–411.
- Fang, F., Ventre, C., Basios, M., Kong, H., Kanthan, L., Li, L., Martinez-Regoband, D., Wu, F., 2020. Cryptocurrency trading: a comprehensive survey. *arXiv preprint arXiv:2003.11352* .
- Felizardo, L., Oliveira, R., Del-Moral-Hernandez, E., Cozman, F., 2019. Comparative study of bitcoin price prediction using wavenets, recurrent neural networks and other machine learning methods, in: *2019 6th International Conference on Behavioral, Economic and Socio-Cultural Computing (BESC)*, IEEE. pp. 1–6.
- Groß-Klußmann, A., König, S., Ebner, M., 2019. Buzzwords build momentum: Global financial twitter sentiment and the aggregate stock market. *Expert Systems with Applications* 136, 171–186.
- He, K., Zhang, X., Ren, S., Sun, J., 2016. Deep residual learning for image recognition, in: *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778.
- Hsu, S.T., Moon, C., Jones, P., Samatova, N., 2017. A hybrid cnn-rnn alignment model for phrase-aware sentence classification, in: *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers*, pp. 443–449.
- Hutto, C., Gilbert, E., 2014. Vader: A parsimonious rule-based model for sentiment analysis of social media text, in: *Proceedings of the international AAAI conference on web and social media*, pp. 216–225.
- Jaggi, M., Mandal, P., Narang, S., Naseem, U., Khushi, M., 2021. Text mining of stocktwits data for predicting stock prices. *Applied System Innovation* 4, 13.
- Kang, S.H., McIver, R.P., Hernandez, J.A., 2019. Co-movements between bitcoin and gold: A wavelet coherence analysis. *Physica A: Statistical Mechanics and its Applications* 536, 120888.
- Katsiampa, P., 2019. Volatility co-movement between bitcoin and ether. *Finance Research Letters* 30, 221–227.
- Kavitha, H., Sinha, U.K., Jain, S.S., 2020. Performance evaluation of machine learning algorithms for bitcoin price prediction, in: *2020 Fourth International Conference on Inventive Systems and Control (ICISC)*, IEEE. pp. 110–114.
- Kim, H.M., Bock, G.W., Lee, G., 2021. Predicting ethereum prices with machine learning based on blockchain information. *Expert Systems with Applications* 184, 115480.
- Kim, Y., 2014. Convolutional neural networks for sentence classification, in: *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, Association for Computational Linguistics, Doha, Qatar. pp. 1746–1751. URL: <https://aclanthology.org/D14-1181>, doi:10.3115/v1/D14-1181.
- Kim, Y.B., Kim, J.G., Kim, W., Im, J.H., Kim, T.H., Kang, S.J., Kim, C.H., 2016. Predicting fluctuations in cryptocurrency transactions based on user comments and replies. *PLoS one* 11, e0161197.

- Kumar, B.S., Ravi, V., 2016. A survey of the applications of text mining in financial domain. *Knowledge-Based Systems* 114, 128–147.
- Kwon, D.H., Kim, J.B., Heo, J.S., Kim, C.M., Han, Y.H., 2019. Time series classification of cryptocurrency price trend based on a recurrent lstm neural network. *Journal of Information Processing Systems* 15, 694–706.
- Lamon, C., Nielsen, E., Redondo, E., 2017. Cryptocurrency price prediction using news and social media sentiment. *SMU Data Sci. Rev* 1, 1–22.
- LeCun, Y., Bottou, L., Bengio, Y., Haffner, P., 1998. Gradient-based learning applied to document recognition. *Proceedings of the IEEE* 86, 2278–2324.
- Lin, T.Y., Goyal, P., Girshick, R., He, K., Dollár, P., 2017. Focal loss for dense object detection, in: *Proceedings of the IEEE international conference on computer vision*, pp. 2980–2988.
- Liu, F., Li, Y., Li, B., Li, J., Xie, H., 2021. Bitcoin transaction strategy construction based on deep reinforcement learning. *Applied Soft Computing* 113, 107952.
- Malkiel, B.G., 1989. Efficient market hypothesis, in: *Finance*. Springer, pp. 127–134.
- Mikolov, T., Chen, K., Corrado, G., Dean, J., 2013a. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*.
- Mikolov, T., Karafiát, M., Burget, L., Cernocký, J., Khudanpur, S., 2010. Recurrent neural network based language model., in: *Interspeech*, Makuhari. pp. 1045–1048.
- Mikolov, T., Sutskever, I., Chen, K., Corrado, G.S., Dean, J., 2013b. Distributed representations of words and phrases and their compositionality. *Advances in neural information processing systems* 26.
- Mohanty, P., Patel, D., Patel, P., Roy, S., 2018. Predicting fluctuations in cryptocurrencies' price using users' comments and real-time prices, in: *2018 7th International Conference on Reliability, Infocom Technologies and Optimization (Trends and Future Directions)(ICRITO)*, IEEE. pp. 477–482.
- Mohapatra, S., Ahmed, N., Alencar, P., 2019. Kryptooracle: A real-time cryptocurrency price prediction platform using twitter sentiments, in: *2019 IEEE International Conference on Big Data (Big Data)*, IEEE. pp. 5544–5551.
- Moniz, A., de Jong, F., 2014. Classifying the influence of negative affect expressed by the financial media on investor behavior, in: *Proceedings of the 5th Information Interaction in Context Symposium*, pp. 275–278.
- Nathan, A., Galbraith, G.L., Grimberg, J., 2021. Crypto: a new asset class? Report - The Goldman Sachs Group Inc Issue 98. <https://www.goldmansachs.com/insights/pages/crypto-a-new-asset-class-f-report.pdf>.
- Nghiem, H., Muric, G., Morstatter, F., Ferrara, E., 2021. Detecting cryptocurrency pump-and-dump frauds using market and social signals. *Expert Systems with Applications*, 115284.
- Oliveira, N., Cortez, P., Areal, N., 2017. The impact of microblogging data for stock market prediction: Using twitter to predict returns, volatility, trading volume and survey sentiment indices. *Expert Systems with Applications* 73, 125–144.
- Oord, A.v.d., Dieleman, S., Zen, H., Simonyan, K., Vinyals, O., Graves, A., Kalchbrenner, N., Senior, A., Kavukcuoglu, K., 2016. Wavenet: A generative model for raw audio. *arXiv preprint arXiv:1609.03499*.
- Ortu, M., Uras, N., Conversano, C., Bartolucci, S., Destefanis, G., 2022. On technical trading and social media indicators for cryptocurrency price classification through deep learning. *Expert Systems with Applications*, 116804.
- Pagolu, V.S., Reddy, K.N., Panda, G., Majhi, B., 2016. Sentiment analysis of twitter data for predicting stock market movements, in: *2016 international conference on signal processing, communication, power and embedded system (SCOPES)*, IEEE. pp. 1345–1350.
- Passalis, N., Seficha, S., Tsantekidis, A., Tefas, A., 2021. Learning sentiment-aware trading strategies for bitcoin leveraging deep learning-based financial news analysis, in: *IFIP International Conference on Artificial Intelligence Applications and Innovations*, Springer. pp. 757–766.
- Patel, M.M., Tanwar, S., Gupta, R., Kumar, N., 2020. A deep learning-based cryptocurrency price prediction scheme for financial institutions. *Journal of information security and applications* 55, 102583.
- Pennington, J., Socher, R., Manning, C.D., 2014. Glove: Global vectors for word representation, in: *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pp. 1532–1543.
- Raju, S., Tarif, A.M., 2020. Real-time prediction of bitcoin price using machine learning techniques and public sentiment analysis. *arXiv preprint arXiv:2006.14473*.
- Schumaker, R.P., Chen, H., 2009. A quantitative stock prediction system based on financial news. *Information Processing & Management* 45, 571–583.
- Sharpe, W.F., 1998. The sharpe ratio. *Streetwise—the Best of the Journal of Portfolio Management*, 169–185.
- Shin, J., Kim, Y., Yoon, S., Jung, K., 2018. Contextual-cnn: A novel architecture capturing unified meaning for sentence classification, in: *2018 IEEE International Conference on Big Data and Smart Computing (BigComp)*, IEEE. pp. 491–494.
- Shin, M., Mohaisen, D., Kim, J., 2021. Bitcoin price forecasting via ensemble-based lstm deep learning networks, in: *2021 International Conference on Information Networking (ICOIN)*, IEEE. pp. 603–608.
- Si, J., Mukherjee, A., Liu, B., Li, Q., Li, H., Deng, X., 2013. Exploiting topic based twitter sentiment for stock prediction, in: *Proceedings of the 51st Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 24–29.
- Ślepaczuk, R., Zenkova, M., et al., 2018. Robustness of support vector machines in algorithmic trading on cryptocurrency market. *Central European Economic Journal* 5, 186–205.
- Smuts, N., 2019. What drives cryptocurrency prices? an investigation of google trends and telegram sentiment. *ACM SIGMETRICS Performance Evaluation Review* 46, 131–134.
- Sonkiya, P., Bajpai, V., Bansal, A., 2021. Stock price prediction using bert and gan. *arXiv preprint arXiv:2107.09055*.
- Sridhar, S., Sanagavarapu, S., 2021. Multi-head self-attention transformer for dogecoin price prediction, in: *2021 14th International Conference on Human System Interaction (HSI)*, IEEE. pp. 1–6.
- Sun, C., Huang, L., Qiu, X., 2019a. Utilizing bert for aspect-based sentiment analysis via constructing auxiliary sentence. *arXiv preprint arXiv:1903.09588*.
- Sun, J., Zhou, Y., Lin, J., 2019b. Using machine learning for cryptocurrency trading, in: *2019 IEEE International Conference on Industrial Cyber Physical Systems (ICPS)*, IEEE. pp. 647–652.
- Teti, E., Dallochio, M., Aniasi, A., 2019. The relationship between twitter and stock prices. evidence from the us technology industry. *Technological Forecasting and Social Change* 149, 119747.
- Thakkar, A., Chaudhari, K., 2021. Fusion in stock market prediction: a decade survey on the necessity, recent developments, and potential future directions. *Information Fusion* 65, 95–107.
- Valle-Cruz, D., Fernandez-Cortez, V., López-Chau, A., Sandoval-Almazán, R., 2021. Does twitter affect stock market decisions? financial sentiment analysis during pandemics: A comparative study of the h1n1 and the covid-19 periods. *Cognitive computation*, 1–16.
- Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A.N., Kaiser, Ł., Polosukhin, I., 2017. Attention is all you need. *Advances in neural information processing systems* 30.
- Wang, Q., Xu, W., Zheng, H., 2018. Combining the wisdom of crowds and technical analysis for financial market prediction using deep random subspace ensembles. *Neurocomputing* 299, 51–61.
- Wang, W.K., 1985. Some arguments that the stock market is not efficient. *UC Davis L. Rev.* 19, 341.
- Wolk, K., 2020. Advanced social media sentiment analysis for short-term cryptocurrency price prediction. *Expert Systems* 37, e12493.
- Wu, C.H., Lu, C.C., Ma, Y.F., Lu, R.S., 2018. A new forecasting framework for bitcoin price with lstm, in: *2018 IEEE International Conference on Data Mining Workshops (ICDMW)*, IEEE. pp. 168–175.
- Wu, W., Tiwari, A.K., Gozgor, G., Leping, H., 2021. Does economic policy uncertainty affect cryptocurrency markets? evidence from twitter-based uncertainty measures. *Research in International Business and Finance* 58, 101478.

- Xu, Y., Cohen, S.B., 2018. Stock movement prediction from tweets and historical prices, in: Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp. 1970–1979.
- Yu, H., Mu, C., Sun, C., Yang, W., Yang, X., Zuo, X., 2015. Support vector machine-based optimized decision threshold adjustment strategy for classifying imbalanced data. *Knowledge-Based Systems* 76, 67–78.
- Zhang, Y., Roller, S., Wallace, B.C., 2016. Mgnc-cnn: A simple approach to exploiting multiple word embeddings for sentence classification, in: Proceedings of NAACL-HLT, pp. 1522–1527.
- Zhang, Y., Wallace, B., 2015. A sensitivity analysis of (and practitioners' guide to) convolutional neural networks for sentence classification. arXiv preprint arXiv:1510.03820 .