Comparing Unit Trains versus Manifest Trains for the Risk of Rail

Transport of Hazardous Materials -

Part I: Risk Analysis Methodology

Di Kang^a, Jiaxi Zhao^b, C. Tyler Dick^b, Xiang Liu^{*a}, Zheyong Bian^c, Steven W. Kirkpatrick^d, Chen-Yu Lin^e

^a Department of Civil and Environmental Engineering, Rutgers, The State University of New Jersey, Piscataway, NJ.

^b Rail Transportation and Engineering Center – RailTEC, Department of Civil and Environmental Engineering, University of Illinois at Urbana Champaign, Urbana, IL

^c Department of Construction Management, University of Houston, Houston, TX.

^d Applied Research Associates, Inc., Los Altos, CA.

^e Department of Transportation and Logistics Management, National Yang Ming Chiao Tung University, Taipei, Taiwan.

Corresponding Author:

Xiang Liu, xiang.liu@rutgers.edu

Abstract: Transporting hazardous materials (hazmats) using tank cars has more significant economic benefits than other transportation modes. Although railway transportation is roughly four times more fuel-efficient than roadway transportation, a train derailment has greater potential to cause more disastrous consequences than a truck incident. Train types, such as unit train or manifest train (also called mixed train), can influence transport risks in several ways. For example, unit trains only experience risks on mainlines and when arriving at or departing from terminals, while manifest trains experience additional switching risks in yards. Based on prior studies and various data sources covering the years 1996-2018, this paper constructs event chains for line-haul risks on mainlines (for both unit trains and manifest trains), arrival/departure risks in terminals (for unit trains) and yards (for manifest trains), and yard switching risks for manifest trains using various probabilistic models, and finally determines expected casualties as the consequences of a potential train derailment and release incident. This is the first analysis to quantify the total risks a train may encounter throughout the shipment process, either on mainlines or in yards/terminals, distinguishing train types. It provides a methodology applicable to any train to calculate the expected risks (quantified as expected casualties in this paper) from an origin to a destination.

Keywords: risk analysis methodology; safety; freight railroads; hazardous material; mainlines; yard; terminal.

1. Introduction

The year 2021 has witnessed several train incidents on freight railways involving derailments and leaks of hazardous materials (hazmat): 47 cars of a train carrying combustible fertilizer and asphalt derailed in Sibley, Iowa; 27 cars derailed in Ames, Iowa; and 30 cars derailed in Newberry Township, Pennsylvania. The hazmat release poses a significant threat to surrounding people, property, and the environment. When transporting the same amount of hazmat using the same number of tank cars from the same origin to the same destination, service strategies play an important role in reducing the overall transportation risks. One possible strategy uses *unit trains*, usually consisting of 40-120 railcars, carrying the same commodity from the origin *terminal* to the destination terminal. Another possible service strategy uses *manifest trains*, in which railcars from multiple origins and destinations assemble and disassemble between trains at intermediate *classification yards*.

In the context of North American railroads, freight shipments carried by manifest trains require a process of assembling and dissembling, so that railcars bound for the same destination (or intermediate) classification yards re-sort into a new train. Railroad classification yards serve as hubs where loaded and empty railcars from various origins are grouped together into blocks of railcars headed for common destinations. These blocks of railcars are then further aggregated to form trains destined for different classification yards on other parts of the network or for local delivery to nearby shippers. The railcar sorting process requires numerous coupling and uncoupling events as groups of railcars are moved between multiple parallel tracks. In the highest-volume classification yards, sorting is accomplished by pushing railcars over small hills, or "humps." These events typically take place 1) in the main classification yard and its associated

tracks used for accumulating railcars into blocks by destination, 2) on the switching lead tracks used to actively sort the railcars and connect the receiving and departure tracks to the classification tracks, or 3) on other ancillary tracks used to process railcars as they pass through the classification yard. The sorting and switching process by destination in classification yards poses an additional risk of derailment and release.

In addition to the line-haul risk on mainlines, both unit and manifest trains encounter derailment and release risk during arrival and departure (A/D) events at loading and unloading terminals and classification yards. A/D events are operation processes similar to mainline operations but with a reduced speed on the non-mainline track. For unit trains at terminals, A/D events typically occur on loop or "balloon" tracks used to sequentially load or unload each railcar in the unit train as it advances at low speed or on the lead tracks connecting these facilities to the mainline. For manifest trains at classification yards, A/D events typically take place 1) in the receiving sub-yard where manifest trains arrive from the connection to the mainline, 2) in the departure sub-yard where manifest trains depart the classification yard to the mainline, or 3) on the lead and running tracks connecting the receiving and departure sub-yards to the mainline. Figure 1 depicts all types of risks using either unit or manifest trains transporting hazmat.



Figure 1 Types of risks encountered by different train configurations.

It is difficult to determine which service option experiences less risks than the other judging only based on train characteristics. The unit train provides economies of scale and short lead times, and it saves time and money by avoiding the complicated assembling and dissembling processes that pose additional risk in intermediate classification yards for manifest trains. However, since unit trains usually have more railcars on one shipment than manifest trains, unit train derailments result in more cars derailed per accident compared with manifest trains. Compared to unit train configurations, the placement of hazmat railcars in manifest trains, the switching approach, and the number and type of intermediate classification yards can affect hazmat transportation risks related to derailments and subsequent hazmat release for manifest trains. Previous work has explored transportation risks related to mainline and yard/terminal separately to some extent (Liu, 2017a; Zhao & Dick, 2022), factors that influence mainline and yard risks (Barkan et al., 2003),

and accident rates distinguishing mainline and yard (Anderson & Barkan, 2004). However, there is no comprehensive methodology that focuses on comparing the transportation risks between unit trains and manifest trains, with consideration to all mainline, yard, and terminal risk components.

By building the event-chain-based probabilistic risk analysis using multiple probabilistic models and the latest derailment rates analyzed based on data from 1996 to 2018 considering both mainline and yard/terminal operations, this paper proposes a comprehensive methodology comparing unit and manifest trains transporting a given amount of hazmat to answer the following question: given certain combinations of train lengths, tank car block size, operating speed, tank car placement in manifest trains, yard type, yard switching approach, and tank car design, will one train configuration experience less risk compared with the other?

The remainder of this paper is organized as follows: in this paper, Section 2 discusses previous work related to risk analyses of hazardous material trains. Section 3 presents the proposed methodology in detail, which considers both mainline and yard components. Section 4 concludes the whole paper.

2. Literature Review

Railroads in North America transported more than two million carloads of hazardous materials in 2018 (Bureau of Explosives, 2019). Although more than 99 percent of shipments reached their destinations safely and transportation of hazardous materials accounts for only 8.1 percent of rail traffic in the United States, this traffic is responsible for a major share of railroad liability and

insurance risk (Association of American Railroads, 2021). Over the past 20 years, railroads have decreased hazmat accident rates by 64 percent by increasing the safety design of tank cars carrying hazmat, choosing the safest routes to transport hazmat, and training first responders. However, a comprehensive risk analysis considering all possible risks a hazmat shipment might experience on both mainline and in yards/terminals is still lacking.

Existing studies have performed risk analyses of rail transport of hazardous material on mainlines based on the event chain. They have more or less explored the event chain towards the accident, and the risks have been quantified or modeled using different methodologies and historical datasets. To analyze the consequences of a train derailment involving the release of hazmat, the following elements have been studied in previous papers: the likelihood of a train derailment on a track segment (Dindar et al., 2018; Kaeeni et al., 2018; Lin et al., 2020; Nayak et al., 1983), the number of railcars derailed (Anderson, 2005; Bagheri, 2010; Martey & Attoh-Okine, 2019; Wang et al., 2020), the number of tank cars derailed (Bagheri et al., 2014; Kawprasert & Barkan, 2010; Saccomanno & El-Hage, 1991; Verma, 2011), the number of hazmat cars releasing contents (Barkan, 2008; Kawprasert & Barkan, 2010; Liu et al., 2014; Saat & Barkan, 2011), and the consequences (Branscomb et al., 2010; Glickman et al., 2007; Verma & Verter, 2007; Yoon et al., 2009). Bagheri et al. (2014) used the truncated geometric model to estimate the number of cars derailing and then multiplied the conditional probability of release to estimate the number of hazmat cars derailing and releasing. However, they did not consider different train configurations (especially manifest trains) or the probability distribution of release quantity. Liu (2017a) improved the model that Bagheri et al. (2014) developed by considering different derailing probabilities at different train positions. They focused on probability analysis of a release incident without accounting for the number of hazmat cars releasing contents or the consequences.

Typically, manifest trains carrying hazardous material shipments pass through numerous yards and are switched between trains several times during each trip. Despite the amount of time spent in classification yards, these facilities tend to be deemphasized or excluded in railway hazardous materials transportation risk assessments (Center for Chemical Process, 1995). Of the three aspects of the rail transportation process, the risk of the line-haul movement along mainline routes, intermediate yards, and loading/unloading captures the majority of attention when evaluating risk (Purdy et al., 1988). Glickman & Erkut (2007) argued that while the risk of movement through rail yards cannot be ignored, yard risk receives little attention due to the perception of it being a minor risk compared to the mainline and a lack of data to support analysis.

The rapid increase in crude oil transportation by rail in North America in recent years has led to more hazardous material being moved in dedicated unit trains of 80 to 100 railcars that transport a single commodity in a continuous movement from origin to destination (Dick & Brown, 2014). Moving large amounts of hazardous material in a single unit train may increase the risk of multiple-car releases and the disproportionately large consequences of large-release events (Liu, 2017a; Liu et al., 2014). However, these unit trains bypass intermediate classification yards and thus avoid the risk associated with sorting railcars in these facilities. On the other hand, if railcars are placed in the lowest-probability derailment positions as suggested in previous research (Bagheri, 2010; Bagheri et al., 2011), distributing them to multiple manifest trains would result in a lower risk level

(Liu, 2017b). Fully quantifying this risk trade-off requires a better understanding of the risk of handling hazardous material railcars both on mainlines and in classification yards/terminals.

Building a comprehensive risk assessment methodology considering potential risks on mainlines and in yards/terminals is also important for analyzing strategies, such as railcar placement, that are intended to reduce the line-haul risk of railway hazardous materials transportation (Liu et al., 2013). Railcar placement reduces risk by moving railcars carrying hazardous materials to the portion of the train with the lowest probability of release (Federal Railroad Administration, 2005). Achieving optimal car placement for safety requires deviating from conventional operating practices in classification yards that minimize the amount of railcar handling, thus introducing risk associated with additional car coupling events (Branscomb et al., 2010). Increased switching activity also increases the risk of railway employee injury (An et al., 2007). Previous studies of this approach have either ignored the risk in classification yards while focusing on the line-haul route risk or have only acknowledged a potential increase in risk associated with the classification yard train assembly process in a cursory manner as a subject for future research (Bagheri, 2010; Bagheri et al., 2011, 2012; Federal Railroad Administration, 2005).

Barkan et al. (2003) calculated railcar derailment rates for both mainlines and yards but concentrated on mainline accidents for subsequent research. Yard accidents were deemphasized since the yard incidents occurred at low speeds and were less likely to lead to hazardous material release (Anderson & Barkan, 2004). In making the decision to focus on mainline train accidents, since the risk of railroad hazardous materials transport is the product of the likelihood of a release event and its consequence (Saat et al., 2014), Barkan et al. (2003) only considered the likelihood

half of the risk equation. They did not fully consider the consequence of population exposure, implicitly assuming that it would be identical along mainline routes and surrounding yards and terminals. However, while many mainline route-miles are in remote, sparsely populated rural areas, most classification yards are located in urban areas that are moderately to densely populated, increasing human exposure to potential releases (Christou, 1999).

With less focus on railroad yard accident risk, there has been a lack of research analyzing risks throughout the shipment which considers both mainline and yard/terminal components. This twopart paper is the first study to build event chains for all line-haul risks, arrival/departure risks, and yard switching risks while considering train configuration. In this paper (Part I), yard types, train types, yard switching approaches, and a series of probability distributions for each event chain component are discussed in detail when building the probabilistic models. Instead of ignoring the potential risks caused by arrival/departure events and yard switching events as previous work did, this paper quantifies potential risks during these two events together with line-haul risks on mainlines. Additionally, the event chain for mainline risk analysis is also extended, modified, and improved. Risks are modeled as the total expected casualties considering route characterization, weather characterization, and evacuation response time. By considering risks on mainlines and yards/terminals for unit trains and manifest trains, this paper provides a solid approach for any train configuration transporting any amount of hazmat on any planned railroad. The proposed methodology can be used as a calculator to guide the operational arrangement in practice to reduce the total potential risks encountered.

3. Probabilistic Risk Analysis Methodology

The fundamental operating differences on mainlines and in yards/terminals determine the different components required to model the transportation risks by rail. Figure 2 shows the event chains for three different types of risks: line-haul risks on mainlines, A/D risks in yards (for manifest trains) or terminals (for unit trains), and yard switching risks (for manifest trains). In this section, three event chains for these three types of events will be elaborated component-by-component in the following subsections. All notations used in this paper are summarized in

Table 1.

Table 1 Notations for mainline risks and yard/terminal risks

$P_{i,c c\in\mathrm{TRM}}$	The probability that the derailment happens on mainline segment i and it is caused by a mainline train-mile-based cause.
$P_{i,c c\in \mathrm{TOM}}$	The probability that the derailment happens on mainline segment i and it is caused by a mainline ton-mile-based cause.
$P_{i,c c\in CM}$	The probability that the derailment happens on mainline segment i and it is caused by a mainline car-mile-based cause.
$d_{ m TRM}$	The number of mainline train derailments per million mainline train-miles.
$d_{ ext{TOM}}$	The number of mainline train derailments per billion mainline gross ton-miles.
d_{CM}	The number of mainline train derailments per billion mainline car- miles.
p_c	Percentage of mainline train derailments due to c^{th} cause in the total number of mainline derailments.
L	Train length, i.e., number of railcars in the train.
L_i	The length (in miles) of the track segment i where the train will travel from the origin to the destination.
GW	Gross tonnage of the train (including lightweight and lading).
$PTD_{i,main}$	The probability of a train derailment on mainline segment <i>i</i> .
TD	A train derailment, which can be a line-haul train derailment.

Notations related to risk components on mainlines

POD(k TD)	The conditional probability that the POD is at the k^{th} position in a train given a train derailment (which can be a line-haul incident).
POD	The point of derailment.
F(x)	The cumulative density distribution of the corresponding fitted NPOD distribution (i.e., best fitted Beta distributions).
$P_i(x POD=k)$	The conditional probability of derailing x cars given that the POD is at k^{th} position on segment i .
L_r	The number of railcars behind the point of derailment.
GT	The average gross tonnage per car.
EUT	If the train is an empty unit train, $EUT = 1$, otherwise $EUT = 0$.
LUT	If the train is a loaded unit train, $LUT = 1$, otherwise $LUT = 0$.
$PD_i(j TD)$	The conditional probability of derailing the car at j^{th} position on track segment <i>i</i> given a train derailment.
$R_i(j TD)$	The conditional probability of releasing the car at the j^{th} position in a train on segment <i>i</i> given a train derailment.
CPR	The base conditional probability of release for a tank car with a specific tank car type developed in Treichel et al. (2019).
$I_t(j)$	The 0-1 indicator, equals 1 if the car at the j^{th} position in a train is a tank car, and 0 otherwise.
${\mathcal Y}_i$	The occurrence of a train derailment at position j in a train.
$P_{\text{main,i,re}}(x_R TD)$	The conditional probability of releasing x_R tank cars on the mainline segment <i>i</i> given a train derailment.
$P_{\text{main,i,re}}(x_R)$	The probability of releasing x_R tank cars on the mainline segment <i>i</i> per shipment.
$P_{re}(x)$	The probability of releasing x gallons of contents in total from all releasing tank cars (from Section 3.5).
C(x,t)	The expected total casualties caused by releasing x gallons of content at response time t , and $t \in [0,120]$ in minutes (Figure 5).
TC(t)	The expected total casualties after t minutes caused by a releasing incident.
δ	The number of tank cars that need to be transported.
C _{unit}	The capacity of the unit train, i.e., the number of tank cars a unit train can carry.
$c_{ m manifest}$	The capacity of the manifest train, i.e., the number of tank cars a manifest train can carry.

Notations related to risk components in yard/terminal

$P_{c c\in ADTR}$	The probability that this freight consist train derails while arriving at or departing from a terminal or classification yard and the derailment is caused by a train-processed-based cause.
$P_{c c\in ADCA}$	The probability that this freight consist train derails while arriving at or departing from a terminal or classification yard and the derailment is caused by a car-processed-based cause.
$P_{\rm YS}$	The probability that this yard consist train derails while switching in yards.
$d_{ m ADTR}$	The number of A/D train derailments per million train A/D events.
$d_{ m ADCA}$	The number of A/D train derailments per billion car A/D events.
$d_{ m YS}$	The number of yard switching derailments per million cars processed in the yard.
p_c	Percentage of derailments of c^{th} cause in the total number of derailments while arriving at or departing from a terminal or classification yard.
L	Train length, i.e., number of railcars in the train.
n	The number of arrival/departure events that a shipment involves.
m	The number of intermediate yards that a manifest train shipment involves.
PTD _{ADI}	The probability of a train derailment per shipment during A/D events.
PTD _{YSI}	The probability of a train derailment per shipment during yard switching events.
TD	A train derailment, which can be an A/D train derailment.
POD(k TD)	The probability that POD is at the k^{th} position in a train given a train accident (which can be an A/D derailment).
POD	The point of derailment.
F(x)	The cumulative density distribution of the corresponding fitted NPOD distribution (i.e., best fitted Beta distributions).
$P_i(x POD=k)$	The conditional probability of derailing x cars given that the POD is at the k^{th} position in a train on segment i per A/D incidents.
f(x)	The probability mass functions of the best fitted generalized exponential distributions estimating the number of railcars derailed given the first car of derailment.
YSI	A yard switching incident.
$P_{\text{YardDeRail}}(x FCD = k)$	The conditional probability of derailing x railcars given that the first car of the derailment is at the k th position in the group of cars.

$PD_i(j)$	The conditional probability of derailing the car at j^{th} position on track segment <i>i</i> given a derailment.	
ADI	An arrival/departure incident in the yard/terminal.	
$P_{A/DDe}(x_{tank} ADI)$	The conditional probability of derailing x_{tank} tank cars given an A/D incident.	
$\delta_t(j)$	0-1 indicator, equals 1 if the car at the j^{th} position in the train is a tank car, and 0 otherwise.	
$P_{A/DRe}(x_{tank} ADI)$	The conditional probability that there are x_{tank} hazmat cars releasing contents given an A/D incident in yards/terminals.	
TT	The total number of tank cars in a yard switching event.	
CPR	The base conditional probability of release developed in Treichel et al. (2019).	
FCD(k YSI)	The probability that the first car of derailment is at the k^{th} position in the group of cars switched together given a yard switching incident (for yard switching incidents only).	
FCD	The position of the first car of derailment in the group of cars switched together.	
TCC	The total number of cars considered in a yard switching event. For "switched alone" approach, <i>TCC</i> is the number of tank cars, while it is the number of tank cars plus 19 non-tank cars for the "switched en masse" approach.	
$P_{\text{YardDeTank}}(x_{\text{tank}} YSI)$	The conditional probability of derailing x_{tank} tank cars given a yard switching incident.	
$P_{\text{terminal}}(x_{\text{tank}})$	The probability of releasing x_{tank} tank cars per shipment for a unit train in terminals.	
$P_{\rm yard}(x_{\rm tank})$	The probability of releasing x_{tank} tank cars per shipment for a manifest train in yards.	
PTD _{ADI,Unit}	The probability of a train derailment per shipment during A/D events in terminals using unit trains.	
PTD _{ADI,Manifest}	The probability of a train derailment per shipment during A/D events in the yard using manifest trains.	
PTD _{SWI}	The probability of a train derailment per shipment during yard switching events.	
$P_{\text{YardReTank}}(x_{\text{tank}} YSI)$	The conditional probability that there are x_{tank} hazmat cars releasing contents given a yard switching incident.	
$P_{\rm re}(x)$	The probability of releasing x gallons of contents in total from all releasing tank cars (from Section 3.5).	

C(x,t)	The expected total casualties caused by releasing x gallons of content at response time t, and $t \in [0,120]$ in minutes (Figure 5).
TC(t)	The expected total casualties after t minutes caused by a releasing incident.
δ	The number of tank cars that need to be transported.
C _{unit}	The capacity of the unit train, i.e., the number of tank cars a unit train can carry.
C _{manifest}	The capacity of the manifest train, i.e., the number of tank cars a manifest train can carry.

	Mainline incident	Yard or terminal: arrival/departure incident	Yard: switching incident
1	Probability of a line-haul incident on the mainline (Section 3.1.1)	Probability of an A/D incident in the yard or terminal (Section 3.1.2)	Probability of a yard switching incident (Section 3.1.2)
Step	Derailment causes Train configuration	Derailment causes Train configuration Yard type Number of intermediate yards	Derailment causes Train length Number of intermediate yards
01	Probability of derailing certain number of cars (Section 3.2.1)	Probability of derailing certain number of cars (Section 3.2.1)	Probability of derailing certain number of cars (Section 3.2.2)
Step 2	Train length Point of derailment Average gross tonnage Derailment speed Train configuration	- Point of derailment - Train length	 Train length Yard type The position of the first car of derailment in the group of cars switched together
	Probability of derailing at certain position (Section 3.3.1)	Probability of derailing certain number of tank cars (Section 3.3.2)	Probability of derailing certain number of tank cars (Section 3.3.3)
Step 3	Point of derailment Derailment severity given the point of derailment	 Point of derailment Position-dependent derailment probability Train length Train configuration Placement of tank cars 	 Switching approach Number of tank cars Number of non-tank cars switched together The position of the first car of the derailment in the group of cars switched together
	Probability of releasing at certain position (Section 3.3.1)	Probability of releasing certain number of tank cars (Section 3.3.2)	Probability of releasing certain number of tank cars (Section 3.3.3)
Step 4	 Conditional probability of release Tank car type Derailment speed Probability of derailment at certain position 	Conditional probability of release Probability distribution of the number of tank cars derailed	Conditional probability of release Probability distribution of the number of tank cars derailed
	Probability of releasing certain number of tank cars (Section 3.3.1)	Probability of releasing certain amount of content (Section 3.5)	Probability of releasing certain amount of content (Section 3.5)
Step 5	 Placement of tank cars in a train Probability of releasing at certain position 	- Tank car safety design - Derailment speed - Probability distribution of the number of tank cars releasing content	 Tank car safety design Derailment speed Probability distribution of the number of tank cars releasing content
	Probability of releasing certain amount of content (Section 3.5)	Consequence (Section 3.6)	Consequence (Section 3.6)
Step 6	 Tank car safety design Derailment speed Probability distribution of the number of tank cars releasing content 	Route characterization Weather characterization Response time	Route characterization Weather characterization Response time
	Consequence (Section 3.6)		
Step	Route characterization Weather characterization Response time		

Figure 2 Flow chart of event-chain-based risk analysis and the related risk components.

3.1 Train Derailment Probability

3.1.1 Derailments on Mainlines

According to Liu (2015), when traffic exposure is large and the derailment rate (i.e., the number of derailments normalized by the corresponding traffic volume) is relatively low, the probability of train derailment can be numerically approximated by multiplying the derailment rate by the mileage of the train shipment. Thus, the probability of train derailment can be estimated based on the train derailment rate using historical train derailment data and traffic data. The FRA has categorized more than 300 accident causes into five groups based on the circumstances and conditions of accidents (FRA, 2012). The hierarchically organized groups can be classified as track, equipment, human factors, signal, and miscellaneous, with each cause being assigned a unique cause code. In the 1990s, a study by Arthur D. Little, Inc (ADL) grouped similar FRA accident causes together based on experts' opinions, producing a variation on the FRA subgroups (Arthur D. Little, Inc. (ADL), 1996). Previous studies (Liu, 2015, 2016; Liu et al., 2012; Schafer & Barkan, 2008) found that the ADL cause groups could be more fine-grained, allowing for greater resolution for certain causes. For example, the FRA combines broken rails, joint bars, and rail anchors in the same subgroup, whereas the ADL grouping distinguishes between broken rail and joint bar defects. Thus, this study uses ADL cause groups to conduct its cause-specific railroad derailment analysis.

The traffic volume data used in this paper is obtained from Class I railroads¹ annual report financial data and Surface Transportation Board (STB) waybill sample data, which is available for the years

¹ As of 2019, the Surface Transportation Board defines a Class I as having operating revenues of, or exceeding, \$505 million annually. (Resource: https://en.wikipedia.org/wiki/Railroad_classes.)

between 1996 and 2018 at the time of this analysis (Dick et al., 2021). We count the number of accidents that occurred by their cause category. In total, there were 2,462 unit train derailments and 5,514 manifest train derailments on mainlines over these years. These accidents are classified into 46 cause groups. Table A.1 in Appendix A shows train derailment data from 1996 to 2018 by cause group and train type on Class I mainlines.

This study develops a cause-based train-derailment probability model. First, train derailment causes are classified into three categories: train miles, ton miles, and car miles (railcars only), respectively. For example, "broken wheels" could be associated with car miles traveled, and thus the probability of derailment caused by "broken wheels" should be calculated based on the traffic metric "car miles." In contrast, obstruction-caused accidents may be affected by the number of trains, and thus the probability of derailment caused by "obstruction" could be calculated based on the traffic metric "train miles."

Let *TRM* denote the set of train-mile-based derailment causes, *TOM* be the set of ton-mile-based derailment causes, and *CM* be the set of car-mile-based derailment causes. If a train has *L* railcars, its gross tonnage is denoted as *GW*, and it travels on a track segment *i* with length of L_i (in miles). The probability of train derailment due to the c^{th} cause can be calculated by:

$$P_{i,c|c\in\text{TRM}} \approx d_{\text{TRM}} / 1,000,000 \times L_i \times p_c \tag{1}$$

$$P_{i,c|c\in\text{TOM}} \approx d_{\text{TOM}} / 1,000,000,000 \times GW \times L_i \times p_c$$
(2)

$$P_{i,c|c \in CM} \approx d_{CM} / 1,000,000,000 \times L \times L_i \times p_c$$
(3)

where

 $P_{i,c|c \in \text{TRM}}$: the probability that the derailment happens on mainline segment *i* and it is caused by a mainline train-mile-based cause.

 $P_{i,c|c \in \text{TOM}}$: the probability that the derailment happens on mainline segment *i* and it is caused by a mainline ton-mile-based cause.

 $P_{i,c|c\in CM}$: the probability that the derailment happens on mainline segment *i* and it is caused by a mainline car-mile-based cause.

 d_{TRM} : the number of mainline train derailments per million mainline train-miles (Table 2).

 d_{TOM} : the number of mainline train derailments per billion mainline gross ton-miles (Table 2).

 d_{CM} : the number of mainline train derailments per billion mainline car-miles (Table 2).

 p_c : percentage of mainline train derailments due to c^{th} cause in the total number of mainline derailments (Table A.1 in Appendix A).

L: train length, i.e., number of railcars in the train.

 L_i : the length (in miles) of the track segment *i* where the train will travel from the origin to the destination.

GW: gross tonnage of the train (including lightweight and lading).

The derailment rate by traffic metric data shown in Table 2 is calculated by Zhang et al. (2022) using FRA-reportable Class I mainline train derailment data for the years 1996-2018. Since the train derailment probability per train shipment is very minimal, the probability of a train derailment on mainline segment i (denoted as $PTD_{i,main}$) can be estimated by:

$$PTD_{i,\text{main}} \approx \sum_{c \in \text{TRM}} P_{i,c|c \in \text{TRM}} + \sum_{c \in \text{TOM}} P_{i,c|c \in \text{TOM}} + \sum_{c \in \text{CM}} P_{i,c|c \in \text{CM}}$$
(4)

Table 2 Derailment rate on mainlines by traffic metric (Zhang et al., 2022)

Metric	Derailments
Derailments per million train-miles	0.85
Derailments per billion gross ton-miles	0.10
Derailments per billion car-miles	8.14

(a) Unit train

(b) Manifest train

Metric	Derailments
Derailments per million train-miles	0.67
Derailments per billion gross ton-miles	0.14
Derailments per billion car-miles	11.39

3.1.2 Derailments in Yards and Terminals

There are two types of events that can cause a derailment in the yard and terminal: the *arrival/departure event* (A/D event) for unit trains (or manifest trains) arriving at or departing from terminal facilities (or classification yards), and the *yard switching event* associated with the sorting, switching, assembling, and dissembling processes for manifest trains in classification yards. According to Zhao and Dick (2022), the A/D events are classified as either train-mile-based causes or car-mile-based causes. Thus, the probability of an A/D event is estimated by the cause-based train derailment model. Assume there is a manifest train with *L* cars (railcars only) and the

manifest train transverses m intermediate classification yards with n A/D events. The relationship between n and m for manifest trains is developed in Equation (5). Since each railcar is switched once at the origin yard and once at each intermediate yard, this manifest train has $(m + 1) \times L$ car switching movements. Similarly, by definition, a unit train with L railcars (railcars only) will have two A/D events (one at the origin yard and one at the destination yard). On the other hand, the yard switching derailment depends on the number of cars possessed.

The probability of an A/D train derailment due to the c^{th} cause can be calculated by Equation (6) if *c* is a train-mile-based cause and by Equation (7) if *c* is a car-processed-based cause. If the train derailment is due to a yard switching event (for manifest trains only), Equation (8) is used to calculate the probability of a train derailment.

$$n = 1 \text{ (origin yard)} + 2 \times m \text{ (intermediate yard)} +$$

$$1 \text{ (destination yard)}$$
(5)

$$P_{c|c\in ADTR} \approx d_{ADTR} / 1,000,000 \times n \times p_c \tag{6}$$

$$P_{c|c\in ADCA} \approx d_{ADCA} / 1,000,000,000 \times L \times n \times p_c \tag{7}$$

$$P_{\rm YS} \approx d_{\rm YS}/1,000,000 \times L \times (m+1)$$
 (8)

 $P_{c|c\in ADTR}$: the probability that this freight consist train derails while arriving at or departing from a terminal or classification yard and the derailment is caused by a train-processed-based cause. $P_{c|c\in ADCA}$: the probability that this freight consist train derails while arriving at or departing from a terminal or classification yard and the derailment is caused by a car-processed-based cause. P_{YS} : the probability that this yard consist train derails while switching in yards. d_{ADTR} : the number of A/D train derailments per million train A/D events (Table 3). d_{ADCA} : the number of A/D train derailments per billion car A/D events (Table 3). $d_{\rm YS}$: the number of yard switching derailments per million cars processed in the yard (Table 3).

 p_c : percentage of derailments of c^{th} cause in the total number of derailments while arriving at or

departing from a terminal or classification yard (Table B.1 in Appendix B).

L: train length, i.e., number of railcars in the train.

n: the number of arrival/departure events that a shipment involves.

m: the number of intermediate yards that a manifest train shipment involves.

Table 3 Derailment rates for various events, train configurations, yard types, and yard

	Arrival/Dep	Yard switching event	
			Derailments per
Group		Derauments per mution	million cars-processed in
	train arrivai/aepartures	car arrival/aepartures	classification yards
Manifest train	61.52	1.04	6.43
Flat yard	118.92	2.02	6.38
Hump yard	36.53	0.62	6.49
Unit train	76.95	0.74	N/A
Loaded unit	126.31	1.22	N/A

traffic metrics for years 1996-2018 (Zhao & Dick, 2022)

Combining risk components due to various causes, the probability of a train derailment per shipment during A/D events and during yard switching events, defined as PTD_{ADI} and PTD_{YSI} can be approximately estimated as follows:

$$PTD_{ADI} \approx \sum_{c \in ADTR} P_{c|c \in ADTR} + \sum_{c \in ADCA} P_{c|c \in ADCA}$$
(9)

$$PTD_{\rm YSI} \approx P_{\rm YS} \tag{10}$$

Note that the calculation of PTD_{ADI} and PTD_{YSI} can distinguish train types, yard types, and yard switching approaches by considering different derailment datasets.

3.2 Number of Railcars Derailed Per Train Derailment

3.2.1 Line-haul Incidents on Mainlines and A/D Incident in Yards/Terminals

Derailment severity, defined as the total number of railcars derailed given a mainline train derailment, can be affected by the point of derailment (POD), derailment speed, train type, train length (number of railcars), and average gross tonnage per car on mainlines. Since the arrival/departure process in a yard or terminal operates similarly to mainline freight operation with a reduced speed, the method to estimate the derailment severity of an A/D accident in yard and terminal is the same as it is on mainlines.

Normalized by the train length (the number of railcars), the normalized POD (denoted as NPOD) can be best predicted by Beta distributions of Beta(0.7549, 0.9582) for the unit train and Beta(0.7842, 1.1002) for the manifest train on mainlines using FRA train derailment data from 1996 to 2018. The "best fits" are Beta(0.5350, 0.9121) and Beta(0.7729, 0.9034) for the manifest train and the unit train in yard and terminal. The Beta distribution fits are consistent with

findings from prior research using older datasets (Saccomanno & El-Hage, 1989, Saccomanno & El-Hage, 1991, and Liu et al., 2014).

The probability that the train derails starting from the k^{th} position (for both mainline and A/D derailments) can be calculated by (Liu et al., 2014; Liu & Schlake, 2016):

$$POD(k|TD) = F\left(\frac{k}{L}\right) - F\left(\frac{k-1}{L}\right)$$
(11)

TD: a train derailment, which can be a line-haul train derailment or an A/D train derailment.

POD(k|TD): the probability that the POD is at the k^{th} position of a train given a train derailment. F(x): the cumulative density distribution of the corresponding fitted NPOD distribution (i.e., best fitted Beta distributions).

L: train length, i.e., number of railcars in the train.

As demonstrated by previous studies (Anderson & Barkan, 2005; Bagheri et al., 2011; Saccomanno & El-Hage, 1989, 1991), the conditional probability of derailing *x* railcars given that the point of derailment is at the k^{th} position on segment *i*, denoted as $P_i(x|\text{POD}=k)$ can be estimated by the Truncated Geometric Logistic model:

$$P_{i}(x|\text{POD}=k) = \begin{cases} \frac{\exp(z)}{1+\exp(z)} \times \frac{\exp(z)}{[1+\exp(z)]^{k-1}}, & \text{if } x = 1,2, \dots L_{r} \\ 1-\left[\frac{1}{1+\exp(z)}\right]^{L_{r}}, & \text{otherwise} \end{cases}$$
(12)

$$L_r = L - POD + 1 \tag{13}$$

where *z* takes different values for different derailment locations:

$$z_{\text{main}} = -0.952 - 0.0306 \times DS - 0.0018 \times L_r - 0.00239 \times GT$$
(14)

+
$$0.119 \times EUT - 0.339 \times LUT$$

 $z_{yard} = -1.595 - 0.0029 \times L$ (15)

$$z_{\text{term}} = -1.574 - 0.0016 \times L \tag{16}$$

where

 $P_i(x|\text{POD}=k)$: the conditional probability of derailing *x* railcars given that the POD is at the *k*th position on segment *i*.

L: train length, i.e., number of railcars in the train.

POD: point of derailment.

 L_r : the number of railcars behind the point of derailment, defined in Equation (13).

GT: average gross tonnage per car.

EUT: if the train is an empty unit train, EUT = 1, otherwise EUT = 0.

LUT: if the train is a loaded unit train, LUT = 1, otherwise LUT = 0.

On mainlines, the derailment severity can be estimated using Equations (12) - (14). The parameters used in Equation (14) are from Liu et al. (2022). When building this model, the manifest train is used as a reference. Thus, for manifest trains, variables *EUT* and *LUT* in Equation (14) are set to 0. In the yard, the derailment severity for a manifest train A/D incident is estimated by Equations (12), (13), and (15); in the terminal, the derailment severity for a loaded unit train A/D incident can be calculated by Equations (12), (13), and (16) (Liu et al., 2022).

3.2.2 Yard Switching Events

While the study of arrival/departure risk in the yard/terminal can consider the same unit train and manifest train consists studied on the mainline, by definition, the yard switching process will alter the arriving manifest train consist into new departing manifest train consists to the same destination yard. The yard switching process typically involves the movement of a single railcar, a cut of cars, or a portion of a train (potentially moving in reverse or as a shoving movement) at a reduced speed by a yard switching crew using a switch engine (not the mainline locomotive). Thus, the traditional definitions of a train consist and "point of derailment" described in Section 3.2.1 are not applicable, and a new risk analysis methodology for yard switching incidents should be developed.

Liu et al. (2022) examined 89 potential distribution models and found that the generalized exponential distribution best fits the empirical FRA Rail Equipment Accident (REA) yard derailment data for the years 1996-2018. The probability mass functions (denoted as f(x)) of the best fitted generalized exponential distributions for yard switching events are presented in Equation (17) for all yard types, in Equation (18) for flat yards, and in Equation (19) for hump yards.

$$f(x) = (1.44 + 1.37^{-7} \times (1 - e^{-1.1x})) \times \exp^{1.44x - 1.37^{-7}x + 1.25^{-7} \times (1 - e^{-1.1x})}$$
(17)

$$f(x) = (1.01 + 1.68^{-7} \times (1 - e^{-1.68x})) \times \exp^{1.01x - 1.68^{-7}x + 1.00^{-7} \times (1 - e^{-1.68x})}$$
(18)

$$f(x) = (5.05^{-8} \tag{19})$$

+ 2.40⁻⁵ × (1 –
$$e^{-3.12x}$$
))
× exp^{5.05⁻⁸x-2.40⁻⁵x+7.70⁻⁶×(1- $e^{-3.12x}$)}

This paper assumes that the derailment occurs when a cut of the group of railcars are switched together for yard switching incidents. The concept of "point of derailment" in Section 3.2.1 is defined from the perspective of root causes of the train derailment (for example, the derailment frequently happens from the head to the end of a train), while the "first car of derailment (FCD)" for yard switching incidents is defined only as a "label" referring to the first vehicle derailed in the cut of derailed vehicles. The main difference between POD and FCD is that POD is defined for a regular freight train consist, while FCD is defined for a yard switching events is not the same as that on mainlines.

Empirical data indicates that manifest trains infrequently derail more than 20 cars in a yard switching incident. Thus, it is necessary to truncate the generalized exponential distribution to fit the empirical data, the length of the train (number of railcars), and the known first car of derailment. The conditional probability of derailing *x* railcars in a yard switching incident given that the first car of the derailment is at the kth position in the group of cars, denoted as $P_{\text{YardDeRail}}(x|FCD = k)$, can be calculated by:

$$P_{\text{YardDeRail}}(x|FCD = k)$$

$$= \begin{cases} f(x), & \text{if } x < \min(20, L - k + 1) \\ \sum_{x=\min(20, L-k+1)}^{\infty} f(x), & \text{if } x = \min(20, L-k+1) \end{cases}$$
(20)

where

FCD: the position of the first car of the derailment in the group of cars switched together.

 $P_{\text{YardDeRail}}(x|FCD = k)$: the conditional probability of derailing *x* railcars given that the first car of the derailment is at the *k*th position in the group of cars.

f(x): the probability mass functions of the best fitted generalized exponential distributions defined in Equation (17) for all yard types, in Equation (18) for flat yards, and in Equation (19) for hump yards, respectively.

L: train length, i.e., number of railcars in the train.

3.3 Number of Hazmat Cars Releasing Contents Per Train Derailment

Different risk components (line-haul risks on mainlines, A/D risks in yards/terminals, and yard switching risks) follow different approaches to obtain the number of hazmat cars releasing contents. Before obtaining the probability distribution of the number of hazmat cars releasing contents, the analysis of line-haul risks on mainlines calculates the position-dependent releasing probability, while the analysis of A/D risks and the yard switching risks estimates the probability distribution of the number of the number of hazmat cars the probability distribution of the number of hazmat cars the probability distribution of the number of hazmat cars the probability distribution of the number of hazmat cars derailed first (see Figure 2).

3.3.1 Line-haul Events on Mainlines

Based on the calculated probability distribution of the total number of railcars derailed from Section 3.2.1, we can further calculate the conditional probability of the car at j^{th} position derailing on track segment *i* (defined as $PD_i(j|TD)$) given a train derailment on mainlines, which is the accordance to determine the train consist. Based on previous experience and historical data, it is assumed that if a train derailment occurs, cars will derail sequentially after the POD. For example, if there are three vehicles derailed, they are POD, POD+1, and POD+2. According to previous work by Liu et al. (2018), $PD_i(j|TD)$ can be calculated by:

$$PD_{i}(j|TD) = \sum_{k=1}^{j} \left[POD(k|TD) \times \sum_{x=j-k+1}^{L_{r}} P_{i}(x|POD = k) \right]$$
(21)

where

TD: a train derailment.

 $PD_i(j|TD)$: the conditional probability of derailing the car at j^{th} position on track segment *i* given a train derailment.

POD(k|TD): the probability that POD is at the k^{th} position in a train given a train derailment.

 $P_i(x|POD = k)$: the conditional probability of derailing *x* railcars given that the POD is at the k^{th} position in a train on segment *i*.

 $\sum_{x=j-k+1}^{L_r} P_i(x|POD = k)$ is the sum of the probability that the locomotive or the railcar at the *j*th position is derailed, given that the POD is at *k*th position.

In the next step, the position-dependent derailment probability is extended to the positiondependent tank car releasing probability, given a train derailment. Let $I_t(j)$ be the 0-1 indicator, which equals 1 if the car at j^{th} position of a train is a tank car, and 0 otherwise. We assume that the conditional probability of a derailed tank car releasing is the same given the same design and accident speed. It is also assumed that each tank car releases contents independently from others. These assumptions are made due to limited information regarding the relationship between the release probability of a derailed tank car and its position in a train. This paper calculates the probability of release (CPR) for a tank car using the results included in the RSI-AAR Tank Car Safety Project (Treichel et al., 2019).

For a car at j^{th} position of a train, the position-dependent tank car releasing probability on segment *i* given a train derailment, which is denoted as $R_i(j|TD)$, can be calculated as:

$$R_i(j|TD) = PD_i(j|TD) \times [I_t(j) \times CPR]$$
(22)

 $R_i(j|TD)$: the conditional probability of releasing of the car at the j^{th} position in a train on segment *i* given a train derailment.

 $PD_i(j|TD)$: the conditional probability of derailing the car at j^{th} position on track segment *i* given a train derailment.

CPR: the base conditional probability of release for a tank car with a specific tank car type developed in Treichel et al. (2019).

 $I_t(j)$: the 0-1 indicator, equal to 1 if the car at the j^{th} position in a train is a tank car, and 0 otherwise.

Based on the position-dependent tank car releasing probability given a train derailment, we can further calculate the probability distribution of the number of tank cars releasing contents. Let y_j represent whether the tank car at j^{th} position releases content, which is a 0-1 variable. For each car in a train, whether a tank car would release at j^{th} position is a Bernoulli variable with releasing probability of $R_i(j|TD)$, and the probability of releasing could vary by position in a train (due to the position-dependent car derailment probability):

$$y_i \sim Bernoulli(R_i(j|TD))$$
 (23)

For the entire train, the total number of tank cars releasing contents follows a Poisson Binomial distribution, which is the sum of independent Bernoulli random variables that are not necessarily identically distributed (Chen & Liu, 1997). The Poisson Binomial distribution is used to estimate the probability associated with a certain number of releasing tank cars in a group of derailed tank cars. Let x_R be the total number of tank cars releasing contents and L be the train length. For each tank car, whether it releases is a binary event (release or no release) with release probability $R_i(j|TD)$, $\forall j : y_j = 1$. x_R can be mathematically expressed as Equation (24). It follows the Poisson Binomial distribution with mean of $\sum_{j=1}^{L} R_i(j|TD)$ and variance of $\sum_{j=1}^{L} R_i(j|TD) \times (1 - R_i(j|TD))$.

$$x_R = \sum_{j=1}^{L} y_j \sim Poisson Binomial Distribution$$
(24)

3.3.2 Arrival/departure Events in Yards/Terminals

Section 3.2.1 calculates the probability that the point of derailment is at the k^{th} position in a train and the probability of derailing *x* railcars given the point of derailment is at the k^{th} position in a train. The probability of derailing x_{tank} tank cars given an A/D incident depends on train configuration and the placement of the block of tank cars in a manifest train, which can be calculated as:

$$P_{A/DDe}(x_{tank}|ADI) = \sum_{k=1}^{L} \sum_{\forall x: \ x_{tank} = \sum_{j=k}^{k+x} \delta_t(j)} POD(k|ADI) \times P_i(x|POD = k)$$
(25)

ADI: an arrival/departure incident in the yard/terminal.

 $P_{A/DDe}(x_{tank}|ADI)$: the conditional probability of derailing x_{tank} tank cars given an A/D incident. $\delta_t(j)$: 0-1 indicator; equals 1 if the car at the j^{th} position in the train is a tank car, and 0 otherwise. L: train length, i.e., the number of railcars in the train.

POD(k|ADI): the probability that POD is at the k^{th} position of a train given an A/D incident. $P_i(x|\text{POD} = k)$: the conditional probability of derailing x cars given that the POD is at k^{th} position in a train on segment *i*.

Due to lower yard/terminal operating speeds relative to mainline speeds, the conditional probability of a tank car releasing given an A/D incident is reduced by multiplying a factor of 0.35 to reflect the fact that most of the yard/terminal accidents have lower severity and chances of release than mainline accidents in general, for which the base CPR factors are developed (Treichel et al., 2019). Given that *y* tank cars derail in an A/D incident, the number of tank cars releasing contents follows a binomial distribution with *y* independent experiments and a success probability of $0.35 \times CPR$ for each experiment. Let $P_{A/DRe}(x_{tank}|ADI)$ denote the probability that there are x_{tank} hazmat cars releasing contents given an A/D incident in yards/terminals and *TT* denote the total number of tank cars in a train. Once the yard- or terminal-specific derailment rates (Section 3.1.2), the number of railcars derailed (Section 3.2.1), and the number of tank cars derailed (Equation (25)) are determined, the conditional probability of releasing x_{tank} tank cars can be determined as follow:

 $P_{A/DRe}(x_{tank}|ADI)$

$$= \sum_{y=x_{\text{tank}}}^{TT} {\binom{y}{x_{\text{tank}}}} (0.35 \times CPR)^{x_{\text{tank}}}$$

$$\times (1 - 0.35 \times CPR)^{y - x_{\text{tank}}} \times P_{A/\text{DDe}}(y|ADI)$$
(26)

where

ADI: an arrival/departure incident in the yard/terminal.

 $P_{A/DRe}(x_{tank}|ADI)$: the conditional probability that there are x_{tank} hazmat cars releasing contents. given an A/D incident in yards/terminals.

TT: the total number of tank cars in a train.

CPR: the base conditional probability of release developed in Treichel et al. (2019).

 $P_{A/DDe}(y|ADI)$: the conditional probability that there are y hazmat cars derailed in an A/D incident.

3.3.3 Yard Switching Events

Liu et al. (2022) declared that calculating the number of tank cars derailed in a yard switching incident distinguishes the yard switching approaches. Accordingly, this paper assumes that tank cars are grouped together as a block in yard switching events. Section 3.2.2 has explained that it is rare for manifest trains to derail more than 20 cars in a yard switching incident. Thus, in this study, the block of tank cars (no more than 20) can be analyzed 1) as being "*switched alone*" as an independent group of *TT* tank cars, or 2) as being "*switched en masse*" as a block of *TT* tank cars behind 19 other non-hazmat cars for a total switching "cut" of 19 + TT railcars. The analysis considers 19 non-hazmat railcars in front of the *TT* tank cars because, as mentioned, the

probability of derailing more than 20 railcars in a yard switching derailment is effectively zero. Assume 20 non-tank cars followed by 20 tank cars are switched together. Within this framework, in a yard switching derailment, if the first railcar (non-tank car) of the group derails and the resulting derailment spreads back through the railcars to derail the maximum amount of 20 railcars, none of the 20 tank cars will be derailed since the final car to derail is the last non-tank car immediately in front of the first tank car in the group. In other words, when the first car to derail is more than 19 cars away from the block of *TT* tank cars, there will be (almost) zero chance of derailing any tank cars and the scenario can be ignored (Figure 3). This paper considers the worst case (when there are at least 19 non-tank cars in front of the block of tank cars) from the conservative perspective for safety concerns. The total cut size of *TT* tank cars using the "switched alone" approach, or 19 + TT railcars using the "switched en masse" approach is considered to calculate the number of hazmat cars derailed in yard switching incidents.



Figure 3 Graphic explanation for the value of "19" in the "switched en masse" approach.

Again, this paper assumes that the derailment occurs as a cut of the group of railcars switched together. Thus, for both the "switched alone" and "switched en masse" approaches, the probability

that the first car of the derailment is at k^{th} position in the group of railcars switched together, when a yard switching incident has occurred, can be calculated as:

$$FCD(k|YSI) = \frac{1}{TCC}$$
(27)

where

Y: a yard switching incident.

FCD(k|YSI): the probability that the first car of the derailment is at the k^{th} position in the group of cars switched together given a yard switching incident.

TCC: the total number of cars considered in a yard switching event. For the "switched alone" approach, *TCC* is the number of tank cars, while it is the number of tank cars plus 19 non-tank cars for the "switched en masse" approach.

For the "switched alone" approach, since all cars switched together are tank cars, the probability of derailing x_{tank} tank cars given a yard switching incident can be estimated by:

$$P_{\text{YardDeTank}}(x_{\text{tank}}|YSI)$$

$$= \sum_{k=1}^{TCC-x_{\text{tank}}+1} FCD(k|YSI) \times P_{\text{YardDeRail}}(x_{\text{tank}}|FCD = k)$$
(28)

where

YSI: a yard switching incident.

 $P_{\text{YardDeTank}}(x_{\text{tank}}|YSI)$: the conditional probability of derailing x_{tank} tank cars given a yard switching incident.

FCD: the position of the first car of the derailment in the group of railcars.

FCD(k|YSI): the probability that the first car of the derailment is at the k^{th} position in the block of tank cars given a yard switching incident.

TCC: total cars considered. For the "switched alone" approach, *TCC* is the number of tank cars. $P_{\text{YardDeRail}}(x_{\text{tank}}|FCD = k)$: the conditional probability of derailing x_{tank} railcars given that the first car of the derailment is at the k^{th} position in the group of cars.

Note that in Equation (28), k sums from 1 to $TCC - x_{tank} + 1$ since the remaining cases are not able to derail x_{tank} tank cars.

For the "switched en masse" approach, the first car derailed can be any of 19 non-tank cars or the following block of tank cars. Thus, the probability of derailing x_{tank} tank cars given a yard switching incident using the "switched en masse" approach is:

 $P_{\text{YardDeTank}}(x_{\text{tank}}|YSI)$

$$= \sum_{k=x_{\text{tank}}}^{19} FCD(k|YSI)$$

$$\times P_{\text{YardDeRail}}(20 - k + x_{\text{tank}}|FCD = k)$$

$$+ \sum_{k=20}^{TCC-x_{\text{tank}}+1} FCD(k|YSI) \times P_{\text{YardDeRail}}(x_{\text{tank}}|FCD = k)$$
(29)

where

YSI: a yard switching incident.

 $P_{\text{YardDeTank}}(x_{\text{tank}}|YSI)$: the conditional probability of derailing x_{tank} tank cars given a yard switching incident.

FCD(k|YSI): the probability that the first car of the derailment is at the k^{th} position in the block of tank cars given a yard switching incident.

TCC: the total number of cars considered in a yard switching event. It is the number of tank cars plus 19 non-tank cars for the "switched en masse" approach.

 $P_{\text{YardDeRail}}(x_{\text{tank}}|FCD = k)$: the conditional probability of derailing x_{tank} railcars given that the first car of the derailment is at the k^{th} position in the group of cars.

In Equation (29) the first term on the right-hand side calculates the probability of releasing x_{tank} tank cars if the first car of the derailment is a non-tank car. The expression "20 – $k + x_{tank}$ ", in the term $P_{YardDeRail}(20 - k + x_{tank}|FCD = k)$, comes from the situation when the first car of the derailment is at k^{th} position; the non-tank cars (from k^{th} to 19th positions) and the first x_{tank} tank cars (from 20th to 19+ x_{tank} positions) are derailing to satisfy that there are exactly x_{tank} tank cars derailing, which is the condition that there are "19 – $k + 1 + x_{tank}$ " railcars derailed. The second term on the right-hand side of Equation (29) considers all cases if the first car of the derailment is a tank car. Knowing the probability distribution of the number of tank cars derailed, the probability of releasing x_{tank} tank cars given a yard switching incident (denoted as $P_{YardReTank}(x_{tank}|YSI)$) can be estimated by the same method as Equation (26).

3.4 Number of Hazmat Cars Releasing Contents Per Shipment

Section 3.2 and Section 3.3 calculate conditional probabilities given a certain type of train derailment. This section removes the "conditions" in the probability distributions developed in Section 3.3 and calculates the probability of releasing a certain number of hazmat cars per shipment.

3.4.1 Line-haul Incidents on Mainlines

Section 3.1.1 defined the probability of a line-haul incident per shipment on the mainline segment *i* as $PTD_{i,main}$, and Section 3.3.1 found that the probability of releasing x_R tank cars on the mainline segment *i* per train derailment (denoted as $P_{main,i,re}(x_R|TD)$) follows a Poisson Binomial distribution. Thus, the probability of releasing x_R tank cars on the mainline segment *i* per shipment is:

$$P_{\text{main,i,re}}(x_R) = P_{\text{main,i,re}}(x_R|TD) \times PTD_{i,\text{main}}$$
(30)

where

 $P_{\text{main,i,re}}(x_R)$: the probability of releasing x_R tank cars on the mainline segment *i* per shipment. $P_{\text{main,i,re}}(x_R|TD)$: the probability of releasing x_R tank cars on the mainline segment *i* per train derailment.

 $PTD_{i,main}$: the probability of a line-haul incident per shipment on the mainline segment *i*.

3.4.2 Unit Train Incidents in Terminals and Manifest Train Incidents in Yards

Section 3.1.2 calculated the likelihood of a train derailment per shipment during A/D events or yard switching events (PTD_{AD} and PTD_{SWI}). To distinguish train type (unit and manifest trains), PTD_{AD} is written as $PTD_{AD,Unit}$ and $PTD_{AD,Manifest}$ to represent the probability of a train derailment per shipment during A/D events in terminals for unit trains and in yards for manifest trains. Also, Section 3.3.2 and Section 3.3.3 built the probability distributions of the number of tank cars releasing contents given an A/D incident or a yard switching incident. Based on those calculations, for a unit train, the probability of releasing x_{tank} tank cars per shipment in terminals is:

$$P_{\text{terminal}}(x_{\text{tank}}) = P_{A/DRe}(x_{\text{tank}}|ADI) \times PTD_{ADI,\text{Unit}}$$
(31)

where

 $P_{\text{terminal}}(x_{\text{tank}})$: the probability of releasing x_{tank} tank cars per shipment for a unit train in terminals.

 $P_{A/DRe}(x_{tank}|ADI)$: the conditional probability that there are x_{tank} hazmat cars releasing contents given an A/D incident in terminal.

 $PTD_{ADI,Unit}$: the probability of a train derailment per shipment during A/D events in terminals using unit trains.

In contrast, for a manifest train, the probability of releasing x_{tank} tank cars per shipment in yards is:

$$P_{\text{yard}}(x_{\text{tank}}) = P_{\text{A/DRe}}(x_{\text{tank}}|ADI) \times PTD_{\text{ADI,Manifest}}$$
(32)
+
$$P_{\text{YardReTank}}(x_{\text{tank}}|YSI) \times PTD_{\text{SWI}}$$

where

 $P_{\text{yard}}(x_{\text{tank}})$: the probability of releasing x_{tank} tank cars per shipment for a manifest train in yards. $P_{A/DRe}(x_{\text{tank}}|ADI)$: the conditional probability that there are x_{tank} hazmat cars releasing contents given an A/D incident in yards.

 $PTD_{ADI,Manifest}$: the probability of a train derailment per shipment during A/D events in the yard using manifest trains.

 $P_{\text{YardReTank}}(x_{\text{tank}}|YSI)$: the conditional probability that there are x_{tank} hazmat cars releasing contents given a yard switching incident.

*PTD*_{SWI}: the probability of a train derailment per shipment during yard switching events.

3.5 Release Quantity

Using historical data from the Railway Supply Institute (RSI) and the Association of American Railroads (AAR) Tank Car Accident Database (TCAD), the RSI-AAR Railroad Tank Car Safety Research and Test Project (AAR-RSI, 2014) developed the probability distribution of release quantity from a single tank car. In this paper, the amount released from a single tank car is represented in terms of the percentage of car capacity loss based on a prior study (Treichel et al., 2019). Note that most of the non-pressure tank cars such as DOT 111s and DOT 117s have a gallon capacity of around 30,000-gallons. Table 4 presents the lading loss per car and the corresponding probability for a non-pressurized, 30,000-gallon tank car. This distribution is used to generate the amount released for all three types of risks on mainlines or in yards/terminals given the probability distributions of number of tank cars releasing contents derived from Section 3.4.

Table 4 Probability distribution of release quantity for a single non-pressurized tank car with a gallon capacity of around 30,000-gallons. (Treichel et al., 2019)

Quantity of Release	Average Quantity of	Lading Loss per Car	Deck -1:1:4	
(QR)	Release	(gallons)	Tiobaoliity	
0%-5%	2.50%	750	0.336	
5%-20%	12.50%	3,750	0.095	
20%-50%	35.00%	10,500	0.133	
50%-80%	65.00%	19,500	0.123	
80%-100%	90.00%	27,000	0.313	

Due to information constraints, the assumption is made that the release quantity of a tank car is independent of other tank cars. Hence, for multiple tank cars releasing contents, the total release quantity is an aggregation of the release quantity from multiple tank car releases. To be more specific, the potential release quantity for a release incident (with a specific number of releasing tank cars) is the combination of the five levels in Table 4. Each incident with a particular number of tank cars releasing contents has a probability distribution of release quantity. Take, for example, a situation where it is known that 20 tank cars are releasing. In such a case, there are 5^{20} possible combinations of amount released, which leads to a probability distribution of the total amount of hazmat release given 20 releasing tank cars. Summing up the probability distributions of the amount released for all possible values for "the number of tank cars releasing contents," we can obtain the probability distribution of the total amount released (let $P_{re}(x)$ denote the probability of releasing x gallons of contents in total from all releasing tank cars). For example, assume that there are 20 tank cars on a manifest train, and the probability of releasing 1, 2, 3, ..., 20 tank cars are all identical, and equal to 0.05. Thus, there are two possible cases resulting in releasing 4,500 gallons: 1) there are six tank cars releasing contents and each of them releases 750 gallons; or 2) there are two tank cars releasing contents: one of them releases 750 gallons, and the other tank car releases 3,750 gallons (note: there is a factor "2" reflecting that there are two ways to designate which car is releasing 750 or 3,750 gallons). Thus, according to Table 4, the probability of releasing 4,500 gallons can be calculated by:

P(*releasing* 4,500 *gallons hazmat*)

= P(there are six tank cars releasing contents) $\times P(a tank car releasing 750 gallons)^{6}$ + P(there are two tank cars releasing contents) $\times P(one tank car releasing 750 gallons)$ $\times P(one tank car releasing 3,750 gallons) \times 2$ $= 0.05 \times 0.336^{6} + 0.05 \times 0.336 \times 0.095 \times 2 = 0.0032$ (33)

The probability distribution of the total amount released for this 20-tank-car example is shown in

Figure 4.



Figure 4 Probability distribution of release quantity in gallons for the 20-tank-car example.

3.6 Releasing Consequences

Performing complete consequence analyses of train operations (to injuries/fatalities for all hazmat commodities, routes, etc.) is a very significant effort. Thus, this paper reduces the scope of the problem to limit the commodities carried by tank cars to flammable liquids (crude oil and ethanol), since crude oil and ethanol combined make up a significant majority of hazmat unit train shipments. The consequence analyses performed in this section demonstrate the approach to analyzing consequences resulting from shipments in unit trains versus manifest trains. One difficulty in performing consequence analyses is that the results are often controlled by the most severe events which are extremely rare, and the methodology makes it difficult to include consequences from conditions that have not been previously observed. A consequence analysis for rail transportation of flammable liquids performed prior to 2013 would likely not have considered that an event like the Lac-Mégantic rail disaster, which resulted in 47 fatalities and more than 30 buildings destroyed, was possible. One such type of severe consequence that has not been significantly considered for flammable liquids by rail is an uncontrolled fire spread.

This paper leverages the Hazard Prediction and Assessment Capability (HPAC) with its associated analysis modules and the Nuclear Capabilities Services (NuCS) framework to assess consequences of industrial accidents (e.g., hazmat spill fires). The proposed approach applies the HPAC and NuCS toolsets to analyze a series of derailment events (flammable liquid releases) at representative real-world locations with varying population densities and various release sizes. Three representative locations along a rail line (urban, suburban, and rural) in the NuCS database are selected for the derailment sites. The HPAC tool contains an OILSPILL model (a spreadsheet-based tool) that predicts the area and volume of contained and uncontained crude oil spills at selected locations with varying population densities and using various release sizes. The tool is geo-referenced and imports building, vegetation, and population data based on an input location. The amount of oil spilled can be estimated using railcar volumes, and this paper assumes that all fuel in the spill footprint will ignite for the conservative consideration. Then, the fuel spill distribution is mapped on the ground into the fuel files for the fire spread/casualty code (QUIC-FST) (Crepeau & Etheridge, 2019; Etheridge, 2020). The fire spread code is then run to provide a time-dependent map of the fuel consumed by fire, and the fire casualty model provides a time-dependent map of the casualties (fatalities and injuries) due to the propagating fire with a breakdown of casualties.

The fire spread/casualty code can be applied to a given region with a defined population to provide an estimate of fire casualties for that location and population. It calculates the probability of injury and fatality due to a thermal dose in each computational cell in the scene. Applying a random number generator and the probabilities to the population density, it arrives at an estimate of casualties (combined injuries and fatalities) for each computational cell. For a given spill, casualties are dependent on the vegetation and building distribution in the area.

Section 3.5 has built the probability distribution of release quantity for a unit train carrying 100 tank cars and a manifest train with a block of 20 tank cars. The results found that the probability of releasing more than 150,000 gallons of content in total is almost zero. Thus, for the consequence model in this paper, we focus on the total casualties caused by one, three, or five tank cars releasing contents, which represent small (30,000 gallons), medium (90,000 gallons), and large sizes

(150,000 gallons) of tank car release incidents, respectively. By performing a series of analyses with the above tool at a series of selected locations, we can develop a set of consequence curves (Figure 5) for casualties as a function of evacuation time with characterization values set in Table 5.

Figure 5 Casualties from fire spread in the QUIC-FST analyses

Table 5	Value	es set o	n calcu	lating	casua	lties
---------	-------	----------	---------	--------	-------	-------

Route characterization	
Urban track percentage	1%
Suburban track percentage	4%

Rural track percentage	95%
Weather characterization	
Low wind percentage	50%
Medium wind percentage	49%
High wind percentage	1%
Evacuation time	
Nearby building evacuation time	4 mins
Evacuation time for hazard zone	120 mins

We assume that there are no casualties when no tank cars release. Thus, we can piecewise-linearly interpolate casualties when the release quantity is between 0-30,000 gallons, 30,000-90,000 gallons, and 90,000-150,000 gallons. Equation (34) is the formula to calculate expected total casualties at a specific evacuation time (it applies to all three types of incidents).

$$TC(t) = \sum_{0 < x \le 150,000} P_{\rm re}(x) \times C(x,t)$$
(34)

where:

TC(t): the total casualties after t minutes caused by a releasing incident.

 $P_{re}(x)$: the probability of releasing x gallons of contents in total from all releasing tank cars (from Section 3.5).

C(x, t): the expected total casualties caused by releasing x gallons of content at response time t, and $t \in [0,120]$ in minutes (Figure 5).

Note that Equation (34) applies to all three types of derailments: the line-haul (mainline) train derailment, the A/D train derailment, and the yard switching train derailment. To distinguish train

types and derailment types, TC(t) is written as $TC_{main,i,Unit}(t)$ or $TC_{main,i,Manifest}(t)$ to represent total casualties per shipment on the mainline segment *i* using a unit train or a manifest train, $TC_{ADI,Unit}(t)$ to represent total casualties per shipment during A/D events using a unit train, and $TC_{Yard}(t)$ to represent total casualties per shipment considering both A/D events and yard switching events using a manifest train.

3.7 Summary

According to the above descriptions, the total expected casualties per train derailment caused by a flammable liquid release can be calculated following the event chain described in Sections 3.1 to 3.6. Let the operator [x] be the smallest integer greater than or equal to x. If there are δ tank cars that need to be transported, the number of shipments using unit trains (each unit train can carry c_{unit} tank cars) is $\left[\frac{\delta}{c_{\text{unit}}}\right]$, and the total expected casualties per traffic demand can be calculated by:

$$TC_{\text{Final}}(t) = \left(\sum_{\forall i} TC_{\text{main},i,\text{Unit}}(t) \times L_i + TC_{\text{ADI},\text{Unit}}(t)\right) \times \left[\frac{\delta}{c_{\text{unit}}}\right]$$
(35)

where:

 $TC_{\text{Final}}(t)$: total casualties if the evacuation process starts after *t* minutes of a releasing incident per traffic demand.

 δ : the number of tank cars that need to be transported.

 L_i : the length (in miles) of track segment *i*.

 c_{unit} : the capacity of the unit train, i.e., the number of tank cars a unit train can carry.

 $TC_{\text{main},i,\text{Unit}}(t)$: total casualties per shipment on the mainline segment *i* using a unit train (obtained by applying Equation (34) in Section 3.6).

 $TC_{ADI,Unit}(t)$: total casualties per shipment during A/D events using a unit train (obtained by applying Equation (34) in Section 3.6).

Using manifest trains (each manifest train can carry c_{manifest} tank cars) to perform the same service, the number of shipments needed is $\left[\frac{\delta}{c_{\text{manifest}}}\right]$, and the total casualties per traffic demand can be estimated by:

$$TC_{\text{Final}}(t) = \left(\sum_{\forall i} TC_{\text{main}, i, \text{Manifest}}(t) \times L_i + TC_{\text{Yard}}(t)\right) \times \left[\frac{\delta}{c_{\text{mainfest}}}\right]$$
(36)

where:

 $TC_{\text{Final}}(t)$: total casualties if the evacuation process starts after *t* minutes of a releasing incident per traffic demand.

 δ : the number of tank cars that need to be transported.

 L_i : the length (in miles) of track segment *i*.

 c_{manifest} : the capacity of the manifest train, i.e., the number of tank cars a manifest train can carry.

 $TC_{\text{main,i,Manifest}}(t)$: total casualties per shipment on the mainline segment *i* using a manifest train (obtained by applying Equation (34) in Section 3.6).

 $TC_{\text{Yard}}(t)$: total casualties per shipment during both A/D events and yard switching events using a manifest train (obtained by applying Equation (34) in Section 3.6).

4. Concluding Remarks

A large amount of effort has been made to mitigate the risk related to rail transportation of hazardous materials due to its devastating consequences. However, relatively limited prior research compared different service options (unit trains versus manifest trains) considering both mainline and yard risk components. This paper proposes a novel methodology quantifying the total risks as expected casualties for any service options knowing train configuration, tank car placement, yard type, and switching approach. There are two (three) types of risks that a unit train (manifest train) encounters per shipment. A unit train experiences arrival/departure risks in terminals and line-haul risks on mainlines, while a manifest train has additional risks during yard switching events. For each of these risks, multiple probabilistic models are built to conduct a comprehensive risk analysis of transporting hazmat by unit trains versus manifest trains. A variety of parameters are estimated for the unit train and the manifest train separately using historical derailment data for 1996-2018, considering the differences associated with various service options.

This comprehensive study is separated into Part I (methodology) and Part II (a practical case study). In the part II paper, a case study is conducted considering different levels of tank car positions, classification yard types, yard switching approaches, and train configurations. It compares unit trains and manifest trains by applying the methodology proposed in this paper. More practical insights will be discussed in the part II paper.

Acknowledgement

This research was funded through a contract by the Federal Railroad Administration (693JJ619C000017). However, all views, analyses, and errors are solely of the authors.

Appendix A

(a) Uni	t train derailments	
Cause group	Frequency	Percent of total
Broken Rails or Welds	440	17.87
Broken Wheels (Car)	230	9.34
Bearing Failure (Car)	182	7.39
Buckled Track	152	6.17
Other Axle/Journal Defects (Car)	152	6.17
Track Geometry (excl. Wide Gauge)	141	5.73
Obstructions	98	3.98
Wide Gauge	87	3.53
Roadbed Defects	71	2.88
Other Wheel Defects (Car)	70	2.84
Turnout Defects - Switches	65	2.64
Track-Train Interaction	58	2.36
Other Miscellaneous	56	2.27
Misc. Track and Structure Defects	50	2.03
Lading Problems	46	1.87
Joint Bar Defects	46	1.87
Coupler Defects (Car)	41	1.67
Other Rail and Joint Defects	40	1.62
Use of Switches	38	1.54
Sidebearing, Suspension Defects (Car)	36	1.46
Train Handling (excl. Brakes)	32	1.3
Non-Traffic, Weather Causes	31	1.26
Rail Defects at Bolted Joint	30	1.22
Train Speed	28	1.14
Truck Structure Defects (Car)	27	1.1
Centerplate/Carbody Defects (Car)	22	0.89
All Other Car Defects	22	0.89
Misc. Human Factors	21	0.85
Stiff Truck (Car)	15	0.61
Switching Rules	15	0.61
Failure to Obey/Display Signals	14	0.57
Other Brake Defect (Car)	14	0.57
Handbrake Operations	12	0.49
Brake Rigging Defect (Car)	12	0.49
Loco Electrical and Fires	11	0.45
Track/Train Interaction (Hunting) (Car)	10	0.41
Brake Operation (Main Line)	9	0.37

 Table A.1 FRA-reportable Class I mainline train derailment data, 1996-2018

Signal Failures80.32Loco Trucks/Bearings/Wheels80.32Turnout Defects - Frogs50.2All Other Locomotive Defects30.12Brake Operations (Other)20.08UDE (Car or Loco)10.04Employee Physical Condition10.04Air Hose Defect (Car)10.04Truth2462100	Mainline Rules	9	0.37
Loco Trucks/Bearings/Wheels80.32Turnout Defects - Frogs50.2All Other Locomotive Defects30.12Brake Operations (Other)20.08UDE (Car or Loco)10.04Employee Physical Condition10.04Air Hose Defect (Car)10.04Table2462100	Signal Failures	8	0.32
Turnout Defects - Frogs50.2All Other Locomotive Defects30.12Brake Operations (Other)20.08UDE (Car or Loco)10.04Employee Physical Condition10.04Air Hose Defect (Car)10.04Trivit2.462100	Loco Trucks/Bearings/Wheels	8	0.32
All Other Locomotive Defects30.12Brake Operations (Other)20.08UDE (Car or Loco)10.04Employee Physical Condition10.04Air Hose Defect (Car)10.04Table2.462100	Turnout Defects - Frogs	5	0.2
Brake Operations (Other)20.08UDE (Car or Loco)10.04Employee Physical Condition10.04Air Hose Defect (Car)10.04Truch2.462100	All Other Locomotive Defects	3	0.12
UDE (Car or Loco)10.04Employee Physical Condition10.04Air Hose Defect (Car)10.04Table2.462100	Brake Operations (Other)	2	0.08
Employee Physical Condition10.04Air Hose Defect (Car)10.04Truch2.462100	UDE (Car or Loco)	1	0.04
Air Hose Defect (Car)10.04Taskal2.462100	Employee Physical Condition	1	0.04
T_{-1} (100	Air Hose Defect (Car)	1	0.04
<u>100</u>	Total	2,462	100

(b) Manifest train derailments		
Cause group	Frequency	Percent of total
Broken Rails or Welds	639	11.59
Track Geometry (excl. Wide Gauge)	391	7.09
Bearing Failure (Car)	343	6.22
Train Handling (excl. Brakes)	324	5.88
Obstructions	243	4.41
Track-Train Interaction	212	3.84
Lading Problems	211	3.83
Wide Gauge	186	3.37
Coupler Defects (Car)	184	3.34
Use of Switches	182	3.30
Broken Wheels (Car)	173	3.14
Sidebearing, Suspension Defects (Car)	164	2.97
Other Wheel Defects (Car)	164	2.97
Brake Operation (Main Line)	163	2.96
Centerplate/Carbody Defects (Car)	148	2.68
Buckled Track	147	2.67
Other Miscellaneous	145	2.63
Turnout Defects - Switches	142	2.58
Misc. Track and Structure Defects	98	1.78
Train Speed	94	1.70
Stiff Truck (Car)	85	1.54
Roadbed Defects	82	1.49
Joint Bar Defects	70	1.27
Other Axle/Journal Defects (Car)	64	1.16
Other Brake Defect (Car)	64	1.16
Loco Trucks/Bearings/Wheels	63	1.14
All Other Car Defects	62	1.12
Track/Train Interaction (Hunting) (Car)	58	1.05
Misc. Human Factors	58	1.05

Switching Rules	55	1.00
Other Rail and Joint Defects	51	0.92
Rail Defects at Bolted Joint	51	0.92
Handbrake Operations	49	0.89
Non-Traffic, Weather Causes	44	0.80
Failure to Obey/Display Signals	39	0.71
Brake Rigging Defect (Car)	35	0.63
All Other Locomotive Defects	35	0.63
Signal Failures	35	0.63
Air Hose Defect (Car)	33	0.60
Truck Structure Defects (Car)	25	0.45
Loco Electrical and Fires	23	0.42
Mainline Rules	23	0.42
Turnout Defects - Frogs	20	0.36
Radio Communications Error	12	0.22
UDE (Car or Loco)	10	0.18
Brake Operations (Other)	6	0.11
TOFC/COFC Defects	5	0.09
Employee Physical Condition	2	0.04
Handbrake Defects (Car)	2	0.04
Total	5,514	100

Appendix B

Table B.1 FRA-reportable Class I yard train arrival/departure event derailment data,1996-2018 (Zhao & Dick, 2022)

(a) Unit train derailments		
Cause group	Frequency	Percent of total
Broken rails or welds	224	26.79
Wide gauge	106	12.68
Turnout defects: switches	105	12.56
Use of switches	79	9.45
Switching rules	42	5.02
Miscellaneous track and structure defects	29	3.47
Track geometry (excluding wide gauge)	27	3.23
Other miscellaneous	26	3.11
Other wheel defects (car)	19	2.27
Roadbed defects	18	2.15
Rail defects at bolted joint	13	1.56
Train handling (excluding brakes)	13	1.56
Train speed	12	1.44

Stiff truck (car)	12	1.44
Lading problems	11	1.32
Other rail and joint defects	10	1.20
Track-train interaction	9	1.08
Side bearing and suspension defects (car)	8	0.96
Miscellaneous human factors	8	0.96
Handbrake operations	7	0.84
Joint bar defects	7	0.84
Buckled track	6	0.72
Signal failures	5	0.60
Nontraffic, weather causes	5	0.60
Brake rigging defect (car)	4	0.48
Failure to obey or display signals	3	0.36
Locomotive trucks, bearings, and wheels	3	0.36
All other locomotive defects	3	0.36
All other car defects	3	0.36
Brake operation (main line)	2	0.24
Centerplate or car body defects (car)	2	0.24
Extreme weather	2	0.24
Bearing failure (car)	2	0.24
Turnout defects: frogs	2	0.24
Broken wheels (car)	2	0.24
Locomotive electrical and fires	2	0.24
Handbrake defects (car)	1	0.12
Brake operations (other)	1	0.12
UDE (car or locomotive)	1	0.12
Other brake defect (car)	1	0.12
Mainline rules	1	0.12
Total	836	100

(b) Manifest train derailments

(b) Mai		
Cause group	Frequency	Percent of total
Switching rules	908	15.45
Use of switches	766	13.03
Broken rails or welds	685	11.66
Wide gauge	625	10.63
Turnout defects: switches	486	8.27
Train handling (excluding brakes)	407	6.93
Other miscellaneous	206	3.51
Handbrake operations	195	3.32
Train speed	183	3.11
Miscellaneous track and structure defects	155	2.64
Track-train interaction	150	2.55

Track geometry (excluding wide gauge)	141	2.40
Brake operation (main line)	136	2.31
Lading problems	79	1.34
Other wheel defects (car)	70	1.19
Signal failures	63	1.07
Side bearing and suspension defects (car)	59	1.00
Coupler defects (car)	56	0.95
Stiff truck (car)	54	0.92
Roadbed defects	51	0.87
Radio communications error	48	0.82
Rail defects at bolted joint	37	0.63
Miscellaneous human factors	37	0.63
Centerplate or car body defects (car)	28	0.48
Turnout defects: frogs	28	0.48
Mainline rules	26	0.44
Nontraffic, weather causes	22	0.37
All other car defects	18	0.31
Other rail and joint defects	16	0.27
Brake operations (other)	15	0.26
Other brake defect (car)	15	0.26
Brake rigging defect (car)	14	0.24
Extreme weather	13	0.22
Locomotive trucks, bearings, and wheels	12	0.20
All other locomotive defects	12	0.20
Buckled track	11	0.19
Failure to obey or display signals	10	0.17
Joint bar defects	10	0.17
Broken wheels (car)	8	0.14
Obstructions	4	0.07
Handbrake defects (car)	4	0.07
Employee physical condition	4	0.07
Truck structure defects (car)	4	0.07
Air hose defect (car)	2	0.03
UDE (car or locomotive)	1	0.02
Bearing failure (car)	1	0.02
Locomotive electrical and fires	1	0.02
Track-train interaction (hunting) (car)	1	0.02
Total	5,877	100

Reference

- AAR-RSI. (2014). Preliminary distributions of quantities lost from tank cars releasing lading in accidents.
- An, M., Huang, S., & Baker, C. J. (2007). Railway risk assessment-the fuzzy reasoning approach and fuzzy analytic hierarchy process approaches: A case study of shunting at waterloo depot. *Proceedings of the Institution of Mechanical Engineers, Part F: Journal of Rail and Rapid Transit, 221*(3), 365–383.
- Anderson, R. T. (2005). *Quantitative analysis of factors affecting railroad accident probability and severity* [PhD Thesis]. University of Illinois at Urbana-Champaign.
- Anderson, R. T., & Barkan, C. P. (2004). Railroad accident rates for use in transportation risk analysis. *Transportation Research Record*, *1863*(1), 88–98.
- Anderson, R. T., & Barkan, C. P. (2005). Derailment probability analysis and modeling of mainline freight trains. *Proc.*, 8th International Heavy Haul Railway Conference.
- Arthur D. Little, Inc. (ADL). (1996). Risk assessment for the transportation of hazardous materials by rail, supplementary report: Railroad accident rate and risk reduction option effectiveness analysis and data.
- Association of American Railroads. (2021, August). *Freight railroads move hazardous materials safely*. https://www.aar.org/issue/freight-rail-hazmat-safety/
- Bagheri, M. (2010). Risk-based model for effective marshalling of dangerous goods railway cars.
- Bagheri, M., Saccomanno, F., Chenouri, S., & Fu, L. (2011). Reducing the threat of in-transit derailments involving dangerous goods through effective placement along the train consist. Accident Analysis & Prevention, 43(3), 613–620.

- Bagheri, M., Saccomanno, F., & Fu, L. (2012). Modeling hazardous materials risks for different train make-up plans. *Transportation Research Part E: Logistics and Transportation Review*, 48(5), 907–918.
- Bagheri, M., Verma, M., & Verter, V. (2014). Transport mode selection for toxic gases: Rail or road? *Risk Analysis*, 34(1), 168–186.
- Barkan, C. P. (2008). Improving the design of higher-capacity railway tank cars for hazardous materials transport: Optimizing the trade-off between weight and safety. *Journal of Hazardous Materials*, 160(1), 122–134.
- Barkan, C. P., Dick, C. T., & Anderson, R. (2003). Railroad derailment factors affecting hazardous materials transportation risk. *Transportation Research Record*, 1825(1), 64– 74.
- Branscomb, L., Fagan, M., Auerswald, P. E., Ellis, R., & Barcham, R. (2010). Rail transportation of toxic inhalation hazards: Policy responses to the safety and security externality. *Available at SSRN 2397482*.
- Bureau of Explosives. (2019). Annual Report of Hazardous Materials Transported by Rail: Calendar Year 2018. Association of American Railroads, Washington, DC, 2019.
- Center for Chemical Process. (1995). *Guidelines for chemical transportation risk analysis*. American Institute of Chemical Engineers, New York, 1995.
- Chen, S. X., & Liu, J. S. (1997). Statistical applications of the Poisson-binomial and conditional Bernoulli distributions. *Statistica Sinica*, 875–892.
- Christou, M. D. (1999). Analysis and control of major accidents from the intermediate temporary storage of dangerous substances in marshalling yards and port areas. *Journal of Loss Prevention in the Process Industries*, 12(1), 109–119.

- Crepeau, J., & Etheridge, M. (2019). Nuclear Capability Services, Quic-FST Verification and Validation (V&V) Report. *Defense Threat Reduction Agency (DTRA) Technical Report, Version 1.* July 12, 2019.
- Dick, C. T., & Brown, L. E. (2014). Design of bulk railway terminals for the shale oil and gas industry. In Shale Energy Engineering 2014: Technical Challenges, Environmental Issues, and Public Policy (pp. 704–714).
- Dick, C. T., Zhao, J., Liu, X., & Kirkpatrick, S. W. (2021). Quantifying Recent Trends in Class 1 Freight Railroad Train Length and Weight by Train Type. *Transportation Research Record*, 03611981211031534.
- Dindar, S., Kaewunruen, S., An, M., & Sussman, J. M. (2018). Bayesian Network-based probability analysis of train derailments caused by various extreme weather patterns on railway turnouts. *Safety Science*, *110*, 20–30.
- Etheridge, M. (2020). Nuclear Capability Services, Quick Urban and Industrial Complex (QUIC)—Fire Smoke Thermal (FST) Methodology Report. *Defense Threat Reduction Agency (DTRA) Technical Report, Version 4*. June 2020.
- Federal Railroad Administration. (2005). Safe placement of train cars: A report. In *Rep. To the Senate Committee on Commerce, Science and Transportation and the House Committee on Transportation and Infrastructure.*

FRA. (2012). FRA guide for preparing accident/incident reports.

Glickman, T. S., & Erkut, E. (2007). Assessment of hazardous material risks for rail yard safety. *Safety Science*, *45*(7), 813–822. https://doi.org/10.1016/j.ssci.2006.09.004

- Glickman, T. S., Erkut, E., & Zschocke, M. S. (2007). The cost and risk impacts of rerouting railroad shipments of hazardous materials. *Accident Analysis & Prevention*, 39(5), 1015– 1025.
- Kaeeni, S., Khalilian, M., & Mohammadzadeh, J. (2018). Derailment accident risk assessment based on ensemble classification method. *Safety Science*, *110*, 3–10.
- Kawprasert, A., & Barkan, C. P. (2010). Effect of train speed on risk analysis of transporting hazardous materials by rail. *Transportation Research Record*, *2159*(1), 59–68.
- Lin, C.-Y., Rapik Saat, M., & Barkan, C. P. (2020). Quantitative causal analysis of mainline passenger train accidents in the United States. *Proceedings of the Institution of Mechanical Engineers, Part F: Journal of Rail and Rapid Transit, 234*(8), 869–884.
- Liu, X. (2015). Statistical temporal analysis of freight train derailment rates in the United States: 2000 to 2012. *Transportation Research Record*, 2476(1), 119–125. https://doi.org/10.3141/2476-16
- Liu, X. (2016). Collision risk analysis of freight trains in the United States. *Transportation Research Record: Journal of the Transportation Research Board*, 2546, 121–128.
- Liu, X. (2017a). Risk comparison of transporting hazardous materials in unit trains versus mixed trains. *Transportation Research Record*, 2608(1), 134–142.
- Liu, X. (2017b). Risk comparison of transporting hazardous materials in unit trains versus mixed trains. *Transportation Research Record*, 2608(1), 134–142.
- Liu, X., Kang, D., Dick, C. T., Kirkpatrick, S., Zhao, J., Bian, Z., Lin, C.-Y., & Zhang, Z.
 (2022). Risk analysis methodology for hazardous material transportation in unit and manifest trains. Technical Report (Draft). (Washingtion D.C., the United States).

- Liu, X., Saat, M. R., & Barkan, C. P. (2012). Analysis of causes of major train derailment and their effect on accident rates. *Transportation Research Record*, 2289(1), 154–163.
- Liu, X., Saat, M. R., & Barkan, C. P. (2013). Integrated risk reduction framework to improve railway hazardous materials transportation safety. *Journal of Hazardous Materials*, 260, 131–140.
- Liu, X., Saat, M. R., & Barkan, C. P. (2014). Probability analysis of multiple-tank-car release incidents in railway hazardous materials transportation. *Journal of Hazardous Materials*, 276, 442–451.
- Liu, X., & Schlake, B. W. (2016). Probabilistic analysis of the release of liquefied natural gas (LNG) tenders due to freight-train derailments. *Transportation Research Part C: Emerging Technologies*, 72, 77–92.
- Liu, X., Turla, T., & Zhang, Z. (2018). Accident-cause-specific risk analysis of rail transport of hazardous materials. *Transportation Research Record*, 2672(10), 176–187.
- Martey, E. N., & Attoh-Okine, N. (2019). Analysis of train derailment severity using vine copula quantile regression modeling. *Transportation Research Part C: Emerging Technologies*, 105, 485–503. https://doi.org/10.1016/j.trc.2019.06.015
- Nayak, P. R., Rosenfield, D. B., & Hagopian, J. H. (1983). Event probabilities and impact zones for hazardous materials accidents on railroads. United States. Federal Railroad Administration.
- Purdy, G., Campbell, H. S., Grint, G. C., & Smith, L. M. (1988). An analysis of the risks arising from the transport of liquefied gases in Great Britain. *Journal of Hazardous Materials*, 20, 335–355.

- Saat, M. R., & Barkan, C. P. (2011). Generalized railway tank car safety design optimization for hazardous materials transport: Addressing the trade-off between transportation efficiency and safety. *Journal of Hazardous Materials*, 189(1–2), 62–68.
- Saat, M. R., Werth, C. J., Schaeffer, D., Yoon, H., & Barkan, C. P. (2014). Environmental risk analysis of hazardous material rail transportation. *Journal of Hazardous Materials*, 264, 560–569.
- Saccomanno, F. F., & El-Hage, S. (1989). Minimizing derailments of railcars carrying dangerous commodities through effective marshaling strategies. *Transportation Research Record*, 1245(34–51), 39–41.
- Saccomanno, F. F., & El-Hage, S. M. (1991). Establishing derailment profiles by position for corridor shipments of dangerous goods. *Canadian Journal of Civil Engineering*, 18(1), 67–75.
- Schafer, D. H., & Barkan, C. P. (2008). Relationship between train length and accident causes and rates. *Transportation Research Record*, *2043*(1), 73–82.
- Treichel, T., Ghosh, L., Saat, M. R., Barkan, C. P., Liu, X., Kirkpatrick, S., Song, J., & Zhou, X. (2019). Conditional probability of release (CPR) estimates for railroad tank cars in accidents. *RSI-AAR Railroad Tank Car Safety Research and Test Project Report RA-19-*01.
- Verma, M. (2011). Railroad transportation of dangerous goods: A conditional exposure approach to minimize transport risk. *Transportation Research Part C: Emerging Technologies*, 19(5), 790–802.
- Verma, M., & Verter, V. (2007). Railroad transportation of dangerous goods: Population exposure to airborne toxins. *Computers & Operations Research*, *34*(5), 1287–1303.

- Wang, B. Z., Barkan, C. P., & Rapik Saat, M. (2020). Quantitative analysis of changes in freight train derailment causes and rates. *Journal of Transportation Engineering, Part A: Systems*, 146(11), 04020127.
- Yoon, H., Werth, C. J., Barkan, C. P., Schaeffer, D. J., & Anand, P. (2009). An environmental screening model to assess the consequences to soil and groundwater from railroad-tankcar spills of light non-aqueous phase liquids. *Journal of Hazardous Materials*, 165(1–3), 332–344.
- Zhang, Z., Lin, C.-Y., Liu, X., Bian, Z., Dick, C. T., Zhao, J., & Kirkpatrick, S. (2022). An Empirical Analysis of Freight Train Derailment Rates for Unit Trains and Manifest Trains. *Journal of Rail and Rapid Transit*.
- Zhao, J., & Dick, C. T. (2022). Quantitative Derailment Rate Comparison of Unit Trains at Transload Terminals and Manifest Trains at Railroad Switching and Hump Classification Yards. *Transportation Research Record - 2022*.