

Consistent discretization of finite/fixed-time controllers

Andrey Polyakov*, Denis Efimov*, Xubin Ping†

Abstract

The paper proposes an algorithm for a discretization (sampled-time implementation) of a homogeneous control preserving the finite-time and nearly fixed-time stability property of the original (sampling-free) system. The sampling period is assumed to be constant. Both single-input and multiple-input cases are considered. The robustness (Input-to-State Stability) of the obtained sampled-time control system is studied as well. Theoretical results are supported by numerical simulations.

1 Introduction

By definition, the homogeneity is a dilation symmetry introduced by Leonhard Euler in 18th century as follows: $f(\lambda x) = \lambda^\nu f(x), \forall \lambda > 0$, where the coordinate transformation $x \mapsto \lambda x$ is known today as a standard (or Euler) dilation. A weighted (generalized) dilation is studied since 1950s. An introduction to stability theory of weighted homogeneous Ordinary Differential Equations (ODEs) can be found in [57]. Extensions of the homogeneity theory to various finite-dimensional and infinite-dimensional dynamical models are proposed in [25], [24], [13], [42]. Homogeneous differential equations/inclusions form an important class of control system models [48], [40], [3], [10], [45]. They appear as local approximations [17] or set-valued extensions [29] of nonlinear systems and include models of process control [54], mechanical systems with frictions [39], fluid dynamics [42], etc. Stability and stabilization problems were studied for both standard [56], [2] and weighted homogeneous [9], [18], [47], [50], [14], [37] systems which are the most popular today [39], [29], [40], [3], [45]. A homogeneous model predictive control is introduced in [8].

An asymptotically stable homogeneous system is finite-time stable in the case of negative homogeneity degree and nearly fixed-time stable in the case of the positive homogeneity degree (see, e.g. [36], [4], [3]). However, the finite/fixed-time stability is a fragile property, since an arbitrary small measurement delay or an improper discretization of a finite-time or a fixed-time stable ODE may

*Univ. Lille, Inria, CNRS, UMR 9189 CRISTAL, Centrale Lille, F-59000 Lille, France, andrey.polyakov(denis.efimov)@inria.fr

†Xidian University, Xi'an, Shaanxi, China, pingxubin@126.com

result in a chattering [1], [30] or even in a finite-time blow up [31]. Moreover, the explicit discretization (sampled-time implementation) of a finite-time control yields a chattering even if this control law is a continuous function of state [12], [23]. That is why the discretization issues are very important for practical implementation of finite/fixed-time control/estimation algorithms [1], [26], [32], [27], [21], [5], [34], [16].

The concept of consistent discretization introduced in [43] postulates that stability properties of a continuous-time system must be preserved in its discrete-time counterpart (approximation). Consistent discretizations for stable generalized homogeneous ODEs were developed in [43], [49] based on Lyapunov function theory. Some schemes with state dependent discretization step were given in [11]. Being efficient for numerical simulations, the mentioned schemes do not allow a consistent discretization (sampled-time implementation) of *finite-time controllers* in the general case. To the best of authors' knowledge, such implementations are developed only for first order ([1], [20]) and second order systems ([21], [6], [46]). This paper presents a consistent discretization for a homogeneous controller designed in [44], [55] for multidimensional linear plants. It is shown that the sampled-time implementation of the controller according to the developed scheme preserves the finite-time and nearly fixed-time stability property of the original closed-loop continuous-time system in the disturbance-free case. We also prove an Input-to-State Stability (ISS) of the obtained sampled-time control system with respect to bounded additive perturbations and measurement noises. Algorithms are developed for both single-input and multiple-input models. Numerical simulations show an efficiency of this scheme for complete rejection of the so-called *numerical chattering* [1] caused by a sampled-time implementation of a continuous-time control algorithm.

Notation: \mathbb{N} is the set of natural numbers including 0; \mathbb{R} is the field of real numbers; $\mathbb{R}_+ = \{\alpha \in \mathbb{R} : \alpha > 0\}$; \mathbb{C} is the field of complex numbers; $\mathbf{0}$ is the zero of a vector space (e.g., the zero vector in \mathbb{R}^n); $I_n \in \mathbb{R}^{n \times n}$ is the identity matrix; $e_i = (0, \dots, 0, 1, 0, \dots, 0)^\top \in \mathbb{R}^n$ is the i -th element of the canonical Euclidean basis; $W \succ 0$ denotes positive definiteness of a symmetric matrix $W = W^\top \in \mathbb{R}^{n \times n}$; $\lambda_{\max}(W)$ is a maximal eigenvalue of a symmetric matrix W ; $\|x\| = \sqrt{x^\top P x}$ denotes the weighted Euclidean norm in \mathbb{R}^n with a positive definite matrix $P \succ 0$ specified below in each case when P is not arbitrary; the matrix norm is defined as $\|A\| = \sup_{x \neq 0} \frac{\|Ax\|}{\|x\|}$; $S = \{x \in \mathbb{R}^n : \|x\| = 1\}$ is the unit sphere; \mathcal{K} denotes a class of strictly increasing positive definite continuous functions $[0, +\infty) \mapsto [0, +\infty)$; a function $\sigma \in \mathcal{K}$ is of the class \mathcal{K}_∞ if $\sigma(s) \rightarrow +\infty$ as $s \rightarrow +\infty$; a function $\sigma : [0, +\infty) \times [0, +\infty) \mapsto [0, +\infty)$ belongs to the class \mathcal{KL} if the function $s \mapsto \sigma(s, \tau)$ belongs to the class \mathcal{K} for any fixed $\tau \in [0, +\infty)$ and the function $\tau \mapsto \sigma(s, \tau)$ is monotonically decreasing to zero for any fixed $s \in [0, +\infty)$; $L^\infty(\mathbb{R}, \mathbb{R}^n)$ is the space of the essentially bounded measurable function $\mathbb{R} \mapsto \mathbb{R}^n$; $\|q\|_{L^\infty((a,b), \mathbb{R}^n)} = \text{ess sup}_{t \in (a,b)} \|q(t)\|$ for $q \in L^\infty(\mathbb{R}, \mathbb{R}^n)$; ℓ^∞ is a space uniformly bounded sequences in \mathbb{R}^n ; $\text{diag}\{a_1, \dots, a_n\} \in \mathbb{R}^{n \times n}$ is a diagonal matrix.

2 Problem Statement

Let us consider a linear control system

$$\dot{x}(t) = Ax(t) + Bu(t), \quad t \in \mathbb{R}_+, \quad x(0) = x_0 \in \mathbb{R}^n, \quad (1)$$

where $x(t) \in \mathbb{R}^n$ is the system state, $u(t) \in \mathbb{R}^m$ is the control input, $A \in \mathbb{R}^{n \times n}$, $B \in \mathbb{R}^{n \times m}$ are known matrices.

Definition 1 *Let the system (1) with a feedback $u \in C(\mathbb{R}^n \setminus \{\mathbf{0}\}, \mathbb{R}^m)$ be globally uniformly finite-time¹ (resp. nearly fixed-time) stable. A family of functions $\tilde{u}_h : \mathbb{R}^n \mapsto \mathbb{R}^m$ parameterized by a scalar $h > 0$ is said to be a consistent discretization of u if*

- **Consistency of Stability:** the system (1) with

$$u(t) = \tilde{u}_h(x(t_i)), \quad t \in [t_i, t_{i+1}), \quad t_i = ih, i \in \mathbb{N} \quad (2)$$

is globally uniformly finite-time (resp., nearly fixed-time) stable for any $h > 0$;

- **Control Approximation:** $\forall r_1 > 0, \forall r_2 > r_1, \exists \omega_r \in \mathcal{K} :$

$$\sup_{r_1 \leq \|x\| \leq r_2} \|\tilde{u}_h(x) - u(x)\| \leq \omega_r(h). \quad (3)$$

If the above properties are fulfilled for all $h \in (0, h_{\max})$ with $0 < h_{\max} < +\infty$ then the discretization is called conditionally consistent.

The first condition of Definition 1 asks that the sampled-time control system preserves the stability property of the original system for any fixed sampling period $h > 0$. The second condition guarantees that the control \tilde{u}_h is, indeed, an approximation of u , i.e., $\tilde{u}_h(x) \rightarrow u(x)$ as $h \rightarrow 0^+$ uniformly on compacts from $\mathbb{R}^n \setminus \{\mathbf{0}\}$. The origin is excluded since a finite-time stabilizing feedback is always non-smooth or even discontinuous at zero.

The aim of the paper is to develop a consistent discretization of a generalized homogeneous controllers introduced in [44], [45], [55]. First, we design a universal control discretization being a mixture of feedforward/feedback algorithms, which guarantees an exact tracking of the states of the original continuous-time closed-loop system at time instances $t_{nk}, k \in \mathbb{N}$. Next, we present a consistent (in the sense of the above definition) discretization scheme and study its robustness under the condition:

¹A system $\dot{x} = f(t, x), x(0) = x_0$ is globally uniformly

- *Lyapunov stable* if $\exists \sigma \in \mathcal{K}_\infty : \|x(t, x_0)\| \leq \sigma(\|x_0\|), \forall t \geq 0, \forall x_0 \in \mathbb{R}^n$ and for any solution $x(t, x_0)$ of the system;
- *finite-time stable* if it is globally uniformly Lyapunov stable and there exists a locally bounded function $T : \mathbb{R}^n \mapsto [0, +\infty)$ such that any trajectory of the system vanishes to zero in a finite time: $\|x(t, x_0)\| = 0, \forall t \geq T(x_0), \forall x_0 \in \mathbb{R}^n$;
- *nearly fixed-time stable* if it is globally uniformly Lyapunov stable and $\forall r > 0, \exists T_r > 0 : \|x(t, x_0)\| < r, \forall t \geq T_r, \forall x_0 \in \mathbb{R}^n$.

Assumption 1 *The pair $\{A, B\}$ is controllable, the matrix A is nilpotent and $m = 1$.*

Recall [55] that a linear system is generalized homogeneous of *non-zero degree* if and only if A is nilpotent.

Finally, we generalize both schemes to the multiple-input case assuming that the system can be decomposed into single-input subsystems satisfying Assumption 1.

Assumption 2 *Let us assume that*

$$A = \begin{bmatrix} A_1 & * & \dots & * & * \\ \mathbf{0} & A_2 & \dots & * & * \\ \dots & \dots & \dots & \dots & \dots \\ \mathbf{0} & \mathbf{0} & \dots & A_{m-1} & * \\ \mathbf{0} & \mathbf{0} & \dots & \mathbf{0} & A_m \end{bmatrix}, B = \begin{bmatrix} B_1 & \mathbf{0} & \dots & \mathbf{0} & \mathbf{0} \\ \mathbf{0} & B_2 & \dots & \mathbf{0} & \mathbf{0} \\ \dots & \dots & \dots & \dots & \dots \\ \mathbf{0} & \mathbf{0} & \dots & B_{m-1} & \mathbf{0} \\ \mathbf{0} & \mathbf{0} & \dots & \mathbf{0} & B_m \end{bmatrix}, \quad (4)$$

where $A_i \in \mathbb{R}^{n_i \times n_i}$, $B_i \in \mathbb{R}^{n_i}$, $n_i \geq 1$: $n_1 + n_2 + \dots + n_m = n$ and $*$ denotes (possibly) nonzero blocks. The pairs $\{A_i, B_i\}$ are controllable and the matrices A_i are nilpotent, $i = 1, \dots, m$.

If the pair $\{A, B\}$ is controllable and $\text{rank}(B) = m$ then there exists a coordinate transformation [33] of $\{A, B\}$ to a canonical form similar to (4). Assumption 2 asks that the pair $\{A, B\}$ is controllable, the matrix A is nilpotent, $\text{rank}(B) = m$ and the system admits a transformation to the block form (4).

3 Preliminaries: Homogeneous systems

3.1 Linear dilation and homogeneous norm

The so-called linear (geometric) dilation [42, Chapter 6] in \mathbb{R}^n is given by

$$\mathbf{d}(s) = e^{sG_{\mathbf{d}}} = \sum_{i=0}^{\infty} \frac{(sG_{\mathbf{d}})^i}{i!}, \quad s \in \mathbb{R}, \quad (5)$$

where $G_{\mathbf{d}} \in \mathbb{R}^{n \times n}$ is an anti-Hurwitz matrix² known as the *generator of linear dilation*. The latter guarantees that \mathbf{d} satisfies the limit property, $\|\mathbf{d}(s)x\| \rightarrow 0$ as $s \rightarrow -\infty$ and $\|\mathbf{d}(s)x\| \rightarrow +\infty$ as $s \rightarrow +\infty$, required for a group \mathbf{d} to be a dilation in \mathbb{R}^n (see, e.g., [24]). The linear dilation introduces an alternative norm topology in \mathbb{R}^n by means the so-called canonical homogeneous norm.

Definition 2 [42] *The function $\|\cdot\|_{\mathbf{d}} : \mathbb{R}^n \mapsto \mathbb{R}_+$ given by $\|x\|_{\mathbf{d}} = 0$ for $x = \mathbf{0}$ and*

$$\|x\|_{\mathbf{d}} = e^{s_x}, \quad \text{where } s_x \in \mathbb{R} : \|\mathbf{d}(-s_x)x\| = 1, \quad x \neq \mathbf{0} \quad (6)$$

is called the canonical homogeneous norm in \mathbb{R}^n , where \mathbf{d} is a linear monotone dilation³.

Notice that $\|x\| = 1$ (resp. $\|x\| \leq 1$) is equivalent to $\|x\|_{\mathbf{d}} = 1$ (resp. $\|x\|_{\mathbf{d}} \leq 1$). For the uniform dilation $\mathbf{d}(s) = e^s I_n$, $s \in \mathbb{R}$ we have $\|\cdot\| = \|\cdot\|_{\mathbf{d}}$.

²A matrix $G_{\mathbf{d}} \in \mathbb{R}^{n \times n}$ is anti-Hurwitz if $-G_{\mathbf{d}}$ is Hurwitz.

³A dilation in \mathbb{R}^n is monotone if for any $x \in \mathbb{R}^n \setminus \{\mathbf{0}\}$ the function $s \mapsto \|\mathbf{d}(s)x\|$, $s \in \mathbb{R}$ is strictly increasing.

Theorem 1 [41] *If \mathbf{d} is a monotone dilation and $\|x\| = \sqrt{x^\top Px}$ with a symmetric matrix $P \in \mathbb{R}^{n \times n}$ satisfying $PG_{\mathbf{d}} + G_{\mathbf{d}}^\top P \succ 0, P \succ 0$ then the canonical homogeneous norm $\|\cdot\|_{\mathbf{d}}$ is continuous on \mathbb{R}^n and smooth on $\mathbb{R}^n \setminus \{\mathbf{0}\}$:*

$$\frac{\partial \|x\|_{\mathbf{d}}}{\partial x} = \frac{\|x\|_{\mathbf{d}} x^\top \mathbf{d}^\top (-\ln \|x\|_{\mathbf{d}}) P \mathbf{d} (-\ln \|x\|_{\mathbf{d}})}{x^\top \mathbf{d}^\top (-\ln \|x\|_{\mathbf{d}}) P G_{\mathbf{d}} \mathbf{d} (-\ln \|x\|_{\mathbf{d}}) x}, \quad \forall x \neq \mathbf{0}; \quad (7)$$

Moreover, $\underline{\sigma}(\|x\|) \leq \|x\|_{\mathbf{d}} \leq \bar{\sigma}(\|x\|), \forall x \in \mathbb{R}^n$, with

$$\underline{\sigma}(r) = \begin{cases} r^{1/\alpha} & \text{if } r \geq 1, \\ r^{1/\beta} & \text{if } r < 1, \end{cases} \quad \bar{\sigma}(r) = \begin{cases} r^{1/\beta} & \text{if } r \geq 1, \\ r^{1/\alpha} & \text{if } r < 1, \end{cases}$$

where $\alpha = 0.5 \lambda_{\max}(P^{1/2} G_{\mathbf{d}} P^{-1/2} + P^{-1/2} G_{\mathbf{d}}^\top P^{1/2}) > 0$ and $\beta = 0.5 \lambda_{\min}(P^{1/2} G_{\mathbf{d}} P^{-1/2} + P^{-1/2} G_{\mathbf{d}}^\top P^{1/2}) > 0$.

Below the canonical homogeneous norm is utilized as a Lyapunov function for analysis and control design.

Remark 1 (On computation of $\|\cdot\|_{\mathbf{d}}$) *Since the canonical homogeneous norm is defined implicitly, a computational algorithm is required for its practical implementation. Issues of numerical estimation of $\|\cdot\|_{\mathbf{d}}$ are studied in [44], [45] based on a bisection method. In [42, Chapter 8] a scheme for an approximation of $\|\cdot\|_{\mathbf{d}}$ by an explicit homogeneous function is presented.*

3.2 Homogeneous continuous-time systems

Definition 3 [24] *A vector field $f : \mathbb{R}^n \mapsto \mathbb{R}^n$ (resp. a function $h : \mathbb{R}^n \mapsto \mathbb{R}$) is said to be \mathbf{d} -homogeneous of degree $\mu \in \mathbb{R}$ if $f(\mathbf{d}(s)x) = e^{\mu s} \mathbf{d}(s) f(x)$ (resp. $h(\mathbf{d}(s)x) = e^{\mu s} h(x)$), for all $x \in \mathbb{R}^n, s \in \mathbb{R}$.*

If f is \mathbf{d} -homogeneous of degree μ then solutions of $\dot{x} = f(x)$ are symmetric [24]: $x(e^{-\mu s} t, \mathbf{d}(s)x_0) = \mathbf{d}(s)x(t, x_0)$, where $x(t, z)$ denotes a solution with $x(0) = z$.

Example 1 [55] *The linear vector field $x \mapsto Ax, A \in \mathbb{R}^{n \times n}$ is \mathbf{d} -homogeneous of the degree $\mu \neq 0 \Leftrightarrow A$ is nilpotent $\Leftrightarrow AG_{\mathbf{d}} = (\mu I_n + G_{\mathbf{d}})A$.*

The homogeneity degree specifies the convergence rate.

Theorem 2 [4], [35] *Let $f : \mathbb{R}^n \mapsto \mathbb{R}^n$ be \mathbf{d} -homogeneous of a degree $\mu \in \mathbb{R}$. If the system $\dot{x} = f(x)$ is asymptotically stable then it is globally uniformly finite-time (nearly fixed-time) stable for $\mu < 0$ ($\mu > 0$).*

The homogeneous control systems are robust (ISS) with respect to a rather large class of perturbations [19], [3].

3.3 Homogeneous stabilization of linear plant

The following theorem merges results of [44], [55], [38].

Theorem 3 *Let a pair $\{A, B\}$ be controllable. Then*

1) any solution $Y_0 \in \mathbb{R}^{m \times n}$, $G_0 \in \mathbb{R}^{n \times n}$ of the linear algebraic equation

$$AG_0 - G_0A + BY_0 = A, \quad G_0B = \mathbf{0} \quad (8)$$

is such that the matrix $G_0 - I_n$ is invertible, the matrix $G_{\mathbf{d}} = I_n + \mu G_0$ is anti-Hurwitz for any $\mu \in [-1, 1/\tilde{n}]$, where \tilde{n} is a minimal natural number such that $\text{rank}[B, AB, \dots, A^{\tilde{n}-1}B] = n$, the matrix $A_0 = A + BY_0(G_0 - I_n)^{-1}$ satisfies the identity

$$A_0G_{\mathbf{d}} = (G_{\mathbf{d}} + \mu I_n)A_0, \quad G_{\mathbf{d}}B = B; \quad (9)$$

2) the linear algebraic system

$$\begin{aligned} A_0X + XA_0^\top + BY + Y^\top B^\top + \rho(G_{\mathbf{d}}X + XG_{\mathbf{d}}^\top) &= \mathbf{0}, \\ G_{\mathbf{d}}X + XG_{\mathbf{d}}^\top &> 0, \quad X = X^\top > 0 \end{aligned} \quad (10)$$

has a solution $X \in \mathbb{R}^{n \times n}$, $Y \in \mathbb{R}^{m \times n}$ for any $\rho \in \mathbb{R}_+$;

3) the canonical homogeneous norm $\|\cdot\|_{\mathbf{d}}$ induced by the weighted Euclidean norm $\|x\| = \sqrt{x^\top Px}$ with $P = X^{-1}$ is a Lyapunov function of the system

(1) with

$$u(x) = K_0x + \|x\|_{\mathbf{d}}^{1+\mu} K_{\mathbf{d}}(-\ln \|x\|_{\mathbf{d}})x, \quad (11)$$

$$K_0 = Y_0(G_0 - I_n)^{-1}, \quad K = YX^{-1}, \quad (12)$$

where \mathbf{d} is a dilation generated by $G_{\mathbf{d}}$; moreover,

$$\frac{d}{dt}\|x\|_{\mathbf{d}} = -\rho\|x\|_{\mathbf{d}}^{1+\mu}, \quad x \neq \mathbf{0}; \quad (13)$$

4) the feedback law u given by (11) is continuously differentiable on $\mathbb{R}^n \setminus \{\mathbf{0}\}$, u is continuous at zero if $\mu > -1$ and u is discontinuous at zero if $\mu = -1$;

5) the system (1), (11) is \mathbf{d} -homogeneous of degree μ .

Obviously, the closed-loop system (1),(11) is uniformly finite-time stable if $\mu < 0$ and it is nearly fixed-time stable if $\mu > 0$. For $\mu = 0$ the control (11) becomes $u = K_0x + Kx$. Such a control law (under some variations and/or simplifications) has been presented in the literature as a solution to a finite-time stabilization problem for linear plants [28], [47], [44].

Remark 2 Under Assumption 1, the equation (8) has a unique solution such that $Y_0 = \mathbf{0}$ (i.e., $A_0 = A$) and $\exists J \in \mathbb{R}^{n \times n} : J^{-1}G_0J = -\text{diag}\{n-1, \dots, 1, 0\}$. This follows from the fact then the system (1), in this case, is equivalent to a controlled integrator chain.

A topological equivalence of any stable \mathbf{d} -homogeneous system to a standard homogeneous one [41] allows an explicit representation of solution for (1), (11) to be derived.

Corollary 1 (Explicit representation of solutions) Under conditions of Theorem 3 with $\mu \neq 0$, a solution of the closed-loop system (1), (11) is unique and

$$x(t + \tau) = Q_\tau(\|x(t)\|_{\mathbf{d}})x(t), \quad (14)$$

where $\tau, t \geq 0$, $Q_\tau(0) = \mathbf{0}$ and for $r > 0$ one has

$$Q_\tau(r) = \begin{cases} e^{G_{\mathbf{d}} \ln r} \hat{Q} \left(\frac{\ln(1 + \mu \rho \tau r^\mu)}{\rho \mu} \right) e^{-G_{\mathbf{d}} \ln r} & \text{if } \frac{1}{r^\mu} > -\mu \rho \tau, \\ 0 & \text{if } \frac{1}{r^\mu} \leq -\mu \rho \tau, \end{cases} \quad (15)$$

$$\hat{Q}(\hat{s}) = e^{-\rho G_{\mathbf{d}} \hat{s}} e^{(A+B(K_0+K)+\rho G_{\mathbf{d}})\hat{s}}, \quad \hat{s} \geq 0. \quad (16)$$

The proof of this corollary, as well as the proofs of other main and auxiliary results, are given in the Appendix. The matrix-valued function $Q_{nh}(\cdot)$ can be easily computed, since elements of a matrix exponential e^{sM} can always be represented as polynomial functions of s , e^{ρ_i} , $\cos(\omega_i s)$ and $\sin(\omega_i s)$, where $\rho_i + i\omega_i$ are eigenvalues of the matrix $M \in \mathbb{R}^{n \times n}$. Moreover, if $A_0 = A + BK_0$, B, K, G_d satisfy (10) then the matrix $X^{1/2}(A_0 + BK + \rho G_d)X^{-1/2}$ is skew-symmetric and

$$e^{(A_0+BK+\rho G_d)\phi} = X^{-1/2}R(\phi)X^{1/2}, \quad (17)$$

where $R(\phi)$ is a rotation matrix for any $\phi \in \mathbb{R}$, i.e., $R(\phi)R^\top(\phi) = R^\top(\phi)R(\phi) = I_n$.

Corollary 2 (On cascade homogeneous control) *Let Assumption 2 be fulfilled. Let $G_{d_i} \in \mathbb{R}^{n_i \times n_i}$, $K_i \in \mathbb{R}^{1 \times n_i}$, $P_i \in \mathbb{R}^{n_i \times n_i}$ and the control $u_i(x_i)$ with $x_i \in \mathbb{R}^{n_i}$ be defined by Theorem 3 for the pairs $\{A_i, B_i\}$ and some $\mu_i \in \mathbb{R}$, $\rho_i > 0$, respectively. Then the system (1) with the control $u = (u_1, \dots, u_m)$ is globally uniformly finite-time stable if $\mu_i < 0$ (resp., nearly fixed-time stable if $\mu_i > 0$) for all $i = 1, 2, \dots, m$.*

4 Discretization of Homogeneous Control

4.1 Single-input case

Let us represent the system (1) with the sampled-time control $u(t) = u(t_k)$ for $t = [t_k, t_{k+1})$ in the form:

$$x_{k+1} = A_h x_k + B_h u(t_k), \quad k \in \mathbb{N}, \quad (18)$$

where $x_k = x(t_k)$, $t_k = kh$, $A_h = e^{hA}$ and $B_h = \int_0^h e^{sA} B ds$. The system (18) can be rewritten as follows:

$$x_{k+n} = B_h u(t_{k+n-1}) + \dots + A_h^{n-1} B_h u(t_k) + A_h^n x_k. \quad (19)$$

The controllability of the pair $\{A, B\}$ implies the controllability of the pair $\{A_h, B_h\}$ and the invertability of

$$W_h = [B_h, A_h B_h, \dots, A_h^{n-1} B_h] \quad (20)$$

(see the formulas (45), (44) and Lemma 5 in Appendix).

Let the parameters of a stabilizing homogeneous controller (11) be designed according to Theorem 3 for some $\mu \neq 0$. The case $\mu = 0$ is omitted since the control (11) is a well-known/studied linear feedback in this case. By Corollary 1, to track the trajectory of the continuous-time (sampling-free) closed-loop homogeneous system (1), (11), the sampled-time control just has to fulfill the following identity

$$Q_{nh}(\|x_k\|_d) x_k = B_h u(t_{k+n-1}) + \dots + A_h^{n-1} B_h u(t_k) + A_h^n x_k.$$

Indeed, if a sampled-time control is implemented as

$$\begin{bmatrix} u(t_{k+n-1}) \\ \vdots \\ u(t_k) \end{bmatrix} = W_h^{-1} (Q_{nh}(\|x_k\|_d) - A_h^n) x_k, \quad (21)$$

then the discrete-time system (18), (21) tracks any trajectory of the continuous-time system (1), (11) at time instances t_{kn} , where $k \in \mathbb{N}$.

Theorem 4 *The system (1) with the sampled-time control (21) is globally uniformly finite-time stable if $\mu < 0$ (nearly fixed-time stable if $\mu > 0$).*

Since $u(t_{k+i-1})$ depends on $x_k = x(t_k)$ but not on $x(t_{k+i-1})$, then the discretization (21) of the control (11) could be useful, for example, if the control sampling is n times faster than a measurement sampling. In other cases, the control (21) is a certain mixture of feedforward and feedback algorithms, where the state measurements $x(t_{k+i-1})$ for $i = 2, \dots, n-1$ are simply omitted during the control implementation. This could badly impact to a robustness and to a precision of the sampled-time controller. To avoid this drawback, let us consider the static feedback law

$$\tilde{u}_h(x_k) = \tilde{K}_h(\|x_k\|_{\mathbf{d}})x_k, \quad (22)$$

$$\tilde{K}_h(\|x_k\|_{\mathbf{d}}) = e_n^\top W_h^{-1} (Q_{nh}(\|x_k\|_{\mathbf{d}}) - A_h^n), \quad (23)$$

which is obtained from (21) selecting only $u(t_k)$.

Proposition 1 (Approximation property) *Let u be a homogeneous control (11) designed by Theorem 3 under Assumption 1. Then $\tilde{u}_h(x) \rightarrow u(x)$ as $h \rightarrow 0^+$ uniformly on compacts from $\mathbb{R}^n \setminus \{\mathbf{0}\}$.*

This proposition, in particular, implies that for a sufficiently small $h > 0$ the system (18), (22) behaves similarly to the continuous-time system (1), (11) at least on small intervals of time. Let us denote

$$L_h = B_h e_n^\top W_h^{-1}, \quad F_h = A_h - L_h A_h^n, \quad h > 0, \quad (24)$$

$$M_h(\|x\|_{\mathbf{d}})x = (F_h + L_h Q_{nh}(\|x\|_{\mathbf{d}}))x, \quad x \in \mathbb{R}^n, \quad (25)$$

and rewrite the discrete-time system (18), (22) as follows

$$x_{k+1} = z_h(x_k) := M_h(\|x_k\|_{\mathbf{d}})x_k. \quad (26)$$

Lemma 1 (Homogeneity of discretization) *The system (18), (22) is \mathbf{d} -homogeneous as follows :*

$$z_h(\mathbf{d}(s)x) = \mathbf{d}(s)z_{e^{\mu s}h}(x), \quad (27)$$

$$\tilde{u}_h(\mathbf{d}(s)x) = e^{s(1+\mu)}\tilde{u}_{e^{\mu s}h}(x), \quad (28)$$

for all $s \in \mathbb{R}$, for all $h > 0$ and for all $x \in \mathbb{R}^n$

The dilation symmetry established by Lemma 1 guarantees that a global asymptotic stability of the discrete-time system (18), (22) for some $h = \hat{h} > 0$ is equivalent to the global asymptotic stability of this system for any $h > 0$. For simplicity, we select

$$\hat{h} := (|\mu|\rho n)^{-1}. \quad (29)$$

As shown below, the key feature of the proposed control discretization is the nilpotence of the matrix F_h . Together with the properties of $Q_{nh}(\|x_k\|_{\mathbf{d}})x_k$, this allows the controller (22) to preserve stability properties of the original system.

Lemma 2 *Let u be a homogeneous control (11) designed by Theorem 3 under Assumption 1. Then the closed-loop discrete-time system (18), (22) is*

1) locally uniformly finite-time stable for $\mu < 0$ and

$$\forall x_0 \in \mathbb{R}^n : \|x_0\|_{\mathbf{d}} \leq \underline{r}^-(\hat{h}/h)^{1/\mu} \Rightarrow x_k = \mathbf{0}, \forall k \geq n,$$

where $\|x\|_{\mathbf{d}}$ is the canonical homogeneous norm induced by the weighted Euclidean norm $\|x\| = \sqrt{x^\top P x}$ with $P = X^{-1}$ and

$$\underline{r}^- > 0 : \max_{i \in \{1, \dots, n\}} \|F_{\hat{h}}^{i-1} \mathbf{d}(\ln \underline{r}^-)\| < 1;$$

2) globally practically⁴ finite-time stable for $\mu < 0$ and the set

$$\Omega^- = \left\{ x \in \mathbb{R}^n : \|x\|_{\mathbf{d}} \leq \bar{r}^-(\hat{h}/h)^{1/\mu} \right\}$$

is invariant and finite-time stable for some $\bar{r}^- \geq \underline{r}^-$;

3) globally practically fixed-time stable for $\mu > 0$:

$$\|x_k\|_{\mathbf{d}} \leq \bar{r}^+(\hat{h}/h)^{1/\mu}, \quad \forall k \geq n$$

for all $x_0 \in \mathbb{R}^n$, where $\bar{r}^+ > \max_{\|v_i\| \leq 1} \left\| \sum_{i=1}^n F_{\hat{h}}^{i-1} L_{\hat{h}} v_i \right\|_{\mathbf{d}}$;

4) locally asymptotically stable for $\mu > 0$ and the set

$$\Omega^+ = \left\{ x \in \mathbb{R}^n : \|x\|_{\mathbf{d}} \leq \underline{r}^+(\hat{h}/h)^{1/\mu} \right\}$$

is an invariant attraction domain for some $\underline{r}^+ \in (0, \bar{r}^+]$.

The latter lemma proves that the discretization (22) of the controller (11), indeed preserves a stability property of the original system at least locally. The discrete-time system with $h = \hat{h}$ behaves similarly to the continuous-time system for $\|x_k\|_{\mathbf{d}} < \underline{r}^\pm$ and $\|x_k\|_{\mathbf{d}} > \bar{r}^\pm$. If the set $\tilde{\Omega}^\pm = \{x : \underline{r}^\pm < \|x\|_{\mathbf{d}} < \bar{r}^\pm\}$ does not contain an invariant set of the discrete-time system then the discretization is globally consistent.

Let us consider a family of mappings $\Theta_k : (0, +\infty) \times S \mapsto \mathbb{R}^{n \times n}$ defined recursively as follows: $\Theta_0(\delta, v) = I_n$ and

$$\Theta_{k+1}(\delta, v) = M_{\delta \hat{h}}(\|\Theta_k(\delta, v)v\|_{\mathbf{d}}) \Theta_k(\delta, v), \quad k \in \mathbb{N}, \quad (30)$$

where $\delta \in \mathbb{R}, v \in S$, the parameter $\hat{h} > 0$ is defined by (29) and $S = \{x \in \mathbb{R}^n : \|x\| = 1\}$ is the unit sphere.

Lemma 3 Any solution of the discrete-time system (18), (22) with $h = \hat{h}$ and $x_0 \neq \mathbf{0}$ admits the representation

$$x_k = \mathbf{d}(\ln \|x_0\|_{\mathbf{d}}) \Theta_k(\|x_0\|_{\mathbf{d}}^\mu, v_0) v_0, \quad (31)$$

where $v_0 = \mathbf{d}(-\ln \|x_0\|_{\mathbf{d}}) x_0 \in S$.

The following theorem presents a necessary and sufficient condition of the consistency of the discretization (22) for the controller (11).

⁴Practical finite-time and fixed-time stability is introduced using the same definitions by replacing a norm (distance to $\mathbf{0}$) with a distance to a set being a neighborhood of zero.




Figure 1: The minimal eigenvalue of the matrix $\Delta(\delta)$ for $\mu = -1/2, \rho = 2$

Theorem 5 (Consistent discretization) *Let u be a homogeneous control (11) designed by Theorem 3 under Assumption 1 for $\mu \neq 0$. Then \tilde{u}_h given by (22) is a consistent discretization of the control u **if and only if** there exists $k^* \geq 1$ such that*

$$\|\Theta_{k^*}(\delta, v)v\|_{\mathbf{d}} < 1, \forall \delta \in (0, r^*], \quad \forall v \in S, \quad (32)$$

where $r^* = (\underline{r}^-)^\mu$ if $\mu < 0$ and $r^* = (\bar{r}^+)^\mu$ if $\mu > 0$.

Therefore, the discrete-time system (18), (22) is uniformly finite-time (or nearly fixed-time) stable if and only if the canonical homogeneous norm $\|\cdot\|_{\mathbf{d}}$ is a kind of a homogeneous Lyapunov function. Indeed, (31) and (32) simply means that $\|x_{k^*}\|_{\mathbf{d}} < \|x_0\|_{\mathbf{d}}, \forall x_0: \|x_0\|_{\mathbf{d}}^\mu \in (0, r^*)$.

Remark 3 (On feasibility of condition (32)) *For $k^* = 1$ the condition (32) is equivalent to the nonlinearly parameterized matrix inequality*

$$M_{\delta\hat{h}}(1)^\top X^{-1} M_{\delta\hat{h}}(1) < X^{-1}, \quad \forall \delta \in (0, r^*], \quad (33)$$

which can be checked numerically on a sufficiently dense grid in $(0, r^*]$ because of a continuous dependence of $M_{\delta\hat{h}}(1)$ on the parameter δ . Denoting $\Delta(\delta) = X^{-1} - M_{\delta\hat{h}}^\top(1)X^{-1}M_{\delta\hat{h}}(1)$ we conclude that the condition (33) is fulfilled if $\lambda_{\min}(\Delta(\delta)) > 0$ for all $\delta \in (0, r^*]$. For example, for $n = 2, \mu = -1, \rho = 2, A = \begin{bmatrix} 0 & 1 \\ 0 & 0 \end{bmatrix}, B = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$ Theorem 3 gives $G_{\mathbf{d}} = \text{diag}\{2, 1\}, K = YX^{-1}$ with $X = x_{11}\tilde{X}, x_{11} > 0, \tilde{X} = \begin{bmatrix} 1 & -\rho(1-\mu) \\ -\rho(1-\mu) & 7(2-\mu)^2\rho^2(1-\mu)/8 \end{bmatrix}, Y = \rho^2(2-\mu)(1-\mu)x_{11} \begin{bmatrix} \frac{8-7(2-\mu)}{8} & \frac{-7\rho(2-\mu)}{8} \end{bmatrix}$. In this case, we have $r^* = 1$ and Figure 1 depicts the evolution of the function $\delta \mapsto \lambda_{\min}(\Delta(\delta))$, which confirms that (33) is fulfilled. For $k^* > 1$ a similar (but a bit more complicated) numerical procedure can be developed.

4.2 Robustness analysis

It is well known [19], [3] that homogeneous systems are Input-to-State Stable (ISS) with respect to sufficiently large class of perturbations. Recall [51] that a system

$$\dot{x} = f(t, x, q), \quad t > t_0 \quad (34)$$

is practically ISS with respect to $q \in L^\infty(\mathbb{R}, \mathbb{R}^l)$ if there exist, $c > 0$, $\xi \in \mathcal{KL}$ and $\gamma \in \mathcal{K}$ such that

$$\|x(t)\| \leq c + \xi(\|x_0\|, t - t_0) + \gamma(\|q\|_{L^\infty((t_0, t), \mathbb{R}^l)}). \quad (35)$$

If $c = 0$ then the system is ISS. Local ISS restricts additionally the set of initial conditions $\|x_0\| \leq r_x$ and/or the maximal magnitude of the input $\|q\| \leq r_q$.

Let us consider the system

$$\begin{aligned} \dot{x}(t) &= Ax(t) + Bu(t) + q(t), & t > 0, \\ u(t) &= u(t_k), & t \in [t_k, t_{k+1}), \end{aligned} \quad (36)$$

where $u(t_k)$ is given by (21) and $q \in L^\infty(\mathbb{R}, \mathbb{R}^n)$ is an exogenous input.

Theorem 6 *The system (36) is 1) locally ISS; 2) practically fixed-time stable if $\mu > 0$; 3) ISS if $\mu > -\beta$, where $\beta > 0$ is defined in Theorem 1.*

The ISS can be established for consistent discretization of homogeneous controller. Let us consider the system

$$\begin{aligned} \dot{x}(t) &= Ax(t) + Bu(t) + q_p(t), & t > 0, \\ u(t) &= \tilde{u}_h(x(t_k) + q_m(t_k)), & t \in [t_k, t_{k+1}) \end{aligned} \quad (37)$$

where \tilde{u}_h given by (22) is a discretization of a control (11) designed by Theorem 3 under Assumption 1 and the exogenous input $q = (q_p^\top, q_m^\top)^\top \in L^\infty(\mathbb{R}, \mathbb{R}^{2n})$ is such that $\{q_m(t_k)\} \in \ell^\infty$. Here q_p models an external perturbation and q_m is a measurement noise.

Theorem 7 *The system (37) is 1) locally ISS; 2) practically fixed-time stable if $\mu > 0$; 3) practically ISS if $\mu > -\beta$; 4) ISS if $\mu > -\beta$ and the unperturbed system ($q=0$) is globally asymptotically stable.*

Notice that q may contain an output of another system. In this case, a stability analysis of a cascade system can be based on ISS [51], [7].

4.3 Multiple-input case

Let the control u be designed using Corollary 2 under Assumption 2. Since A_i is nilpotent then, as before, $K_0 = \mathbf{0}$ in Theorem 3 and in Corollary 1. Let $Q_{n_i h}(\cdot)$ be defined by the formula (15) for $A_i, B_i, K_i, G_{\mathbf{d}_i}, P_i, \mu_i$, $i = 1, \dots, m$. Let us denote

$$W_{h,i} = [B_{h,i}, A_{h,i}B_{h,i}, \dots, A_{h,i}^{n-1}B_{h,i}], \quad (38)$$

$A_{h,i} = e^{hA_i}$, $B_{h,i} = \int_0^h e^{\tau A_i} d\tau B$, and introduce the following discretization of the controllers u_i :

$$\begin{bmatrix} u_i(t_{k+n-1}) \\ \vdots \\ u_i(t_k) \end{bmatrix} = W_{h,i}^{-1} (Q_{n_i h}(\|x_i(t_k)\|_{\mathbf{d}}) - A_{h,i}^n x_i(t_k)). \quad (39)$$

Corollary 3 *Under Assumption 2, the system (18) with the control (39) is globally uniformly finite-time stable if $\mu_i < 0$ (nearly fixed-time stable if $\mu_i > 0$), $\forall i = 1, \dots, m$.*

Similarly to the single input case, a consistent discretization of the multiple-input control system is designed as

$$u_i(x_{k,i}) = \tilde{K}_i(\|x_{k,i}\|_{\mathbf{d}_i})x_{k,i}, \quad (40)$$

$$\tilde{K}_i(\|x_{k,i}\|_{\mathbf{d}_i}) = e_{n_i}^\top W_{h,i}^{-1} (Q_{nh,i}(\|x_{k,i}\|_{\mathbf{d}_i}) - A_{h,i}^n).$$

Corollary 4 *Let a control law u be designed by Corollary 2 under Assumption 2. Then (40) is a consistent discretization of u provided that conditions of Theorem 5 are fulfilled for $\mu_i < 0, \forall i = 1, \dots, m$ or $\mu_i > 0, \forall i = 1, \dots, m$.*

5 Numerical Examples

5.1 Single-input system

Let $n = 3$, $A = \begin{bmatrix} 0 & I_2 \\ 0 & 0 \end{bmatrix}$, $\mu = -0.25$, $\rho = 1$. By Theorem 3 we derive a finite-time homogeneous control (11) with parameters $K_0 = \mathbf{0}$, $G_{\mathbf{d}} = \begin{bmatrix} 1.5 & 0 \\ 0 & 1.25 \\ 0 & 0 \\ 0 & 1 \end{bmatrix}$ and $X = \begin{bmatrix} 1.0000 & -1.5000 & 0.6063 \\ -1.5000 & 3.5187 & -4.3984 \\ 0.6063 & -4.3984 & 49.3488 \end{bmatrix}$, $Y = [2.8828 \ -39.4523 \ -49.3488]$. Simulation results of the system (1) with the consistently discretized control (2), (40) for $x(0) = [1 \ -1 \ 0]^\top$, $h = 0.05$ are presented on Fig. 2 (right). The system states converges to zero in a finite time: $x(t) = \mathbf{0}, u(t) = \mathbf{0}$ for $t \geq 4.65$. The results for the *explicit discretization*

$$u(t) = \tilde{u}(x(t_k)), \quad t \in [t_k, t_{k+1}) \quad (41)$$

of the control (11) are depicted on Fig. 2 (left) for comparison reasons. The system (1) with the explicitly discretized homogeneous controller is not asymptotically stable and suffers of a chattering. For $\mu = 0.25$, $\rho = 1$ we similarly derive a nearly fixed-time homogeneous control (11) with parameters $K_0 = \mathbf{0}$, $G_{\mathbf{d}} = \begin{bmatrix} 0.5 & 0 \\ 0 & 0.75 \\ 0 & 0 \\ 0 & 1 \end{bmatrix}$ and $X = \begin{bmatrix} 1.0000 & -0.5000 & -0.8854 \\ -0.5000 & 1.5104 & -1.1328 \\ -0.8854 & -1.1328 & 8.5707 \end{bmatrix}$, $Y = [2.4609 \ -6.5883 \ -8.5707]$. The simulation results for the explicitly discretized controller with $x(0) = [110 \ -110]^\top$ are depicted in Fig. 3 (left). With this discretization, the system simply blows up for larger initial conditions. Simulations of the consistently discretized control were made for initial conditions with various magnitudes up to $\|x_0\| \approx 10^{10}$. They show that the nearly fixed-time stability of the closed-loop system is preserved as in Fig. 3 (right). ISS of both controllers (for $\mu = -0.25$ and $\mu = 0.25$) with respect to additive perturbations and measurement noises was also confirmed by simulations.

5.2 Multi-input system

For the multi-input case we consider the above single-input system ($n_1 = 3$) with the finite-time control ($\mu_1 = -0.25$) in the cascade with the second order system ($n_2 = 2$) with the finite-time control ($\mu_2 = -1$) considered in Remark




Figure 2: The simulation results for the system (1) with explicitly (left) and consistently (right) discretized finite-time control (11) for $n = 3, m = 1, \mu = -0.25, \rho = 1, h = 0.05$.




Figure 3: The simulation results for the system (1) with explicitly (left) and consistently (right) discretized fixed-time control (11) for $n = 3, m = 1, \mu = 0.25, \rho = 1, h = 0.2$.

3, i.e., $A = \begin{bmatrix} A_1 & A_{12} \\ \mathbf{0} & A_2 \end{bmatrix}, B = \begin{bmatrix} B_1 & \mathbf{0} \\ \mathbf{0} & B_2 \end{bmatrix}, A_1 = \begin{bmatrix} \mathbf{0} & I_2 \end{bmatrix}, A_{12} = \begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix}, A_2 = \begin{bmatrix} 0 & 1 \\ 0 & 0 \end{bmatrix}, B_1 = \begin{bmatrix} 0 \\ 1 \end{bmatrix}, B_2 = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$. The simulation results for the cascade system are shown on Fig. 4 for $x_1(0) = [1 \ -1 \ 0]^\top, x_2(0) = [1 \ 0]^\top$. They confirm finite-time stability of the closed-loop system with the consistently discretized control: $x_1(t) = \mathbf{0}, u_1(t) = 0, \forall t \geq 7.35$ and $x_2(t) = \mathbf{0}, u_2(t) = 0, \forall t \geq 4.2$.




Figure 4: The simulation results for the cascade system (1) with consistently discretized finite-time controllers with $n_1 = 3, n_2 = 2, \mu_1 = -0.25, \rho_1 = 1, \mu_2 = -1, \rho_2 = -1, h = 0.05$.

6 Conclusions

In the paper, two types of discretization (sampled-time implementation) schemes for a homogeneous control law are developed. Both preserves the finite/fixed-time stability properties of the original continuous-time closed-loop system. The first scheme gives a mixture of a feedforward and a feedback algorithms. It can be utilized if the control sampling is much faster than the sampling of measurements, or in the model-predictive framework. The second scheme (called consistent) provides a static feedback law, which always preserves the stability properties, at least, locally (close to zero and close to infinity). A necessary and sufficient condition of global consistency is presented. A particular sufficient condition is formalized in terms of a parametric LMI, which, by numerical simulations, is shown to be feasible in some cases. A development of numerical algorithms for control parameters tuning based on the obtained conditions of the consistency is an interesting problem for the future research.

7 Appendix

7.1 Auxiliary results

Lemma 4 [15, page 136] *If $Z_1 Z_2 - Z_2 Z_1 = q Z_2$ with $q \in \mathbb{R}$ and $Z_1, Z_2 \in \mathbb{R}^{n \times n}$ then $e^{Z_1} e^{Z_2} = e^{Z_1 + \frac{q}{1-e^{-q}} Z_2}$.*

Lemma 5 *If Assumption 1 is fulfilled and \mathbf{d} is a linear dilation defined in Theorem 3 then*

1) *for all $s \in \mathbb{R}$ the following identities hold:*

$$\mathbf{A} \mathbf{d}(s) = e^{\mu s} \mathbf{d}(s) \mathbf{A}, \quad \mathbf{d}(s) \mathbf{B} = e^s \mathbf{B}, \quad \mathbf{d}(s) e^{\tau \mathbf{A}} = e^{e^{-\mu s} \tau \mathbf{A}} \mathbf{d}(s), \quad (42)$$

$$\mathbf{d}(s) \int_0^h e^{\tau A} d\tau = e^{\mu s} \int_0^{e^{-\mu s} h} e^{\tau A} d\tau \mathbf{d}(s); \quad (43)$$

2) the matrix W_h given by (20) satisfies

$$W_h = \mathbf{d}_*(\ln h) \int_0^1 e^{\tau A} d\tau [B \ e^A B \ \dots \ e^{(n-1)A} B], \quad (44)$$

$$W_h^{-1} \mathbf{d}_*(\ln h) \int_0^n e^{\tau A} d\tau B = \begin{bmatrix} 1 \\ \vdots \\ 1 \end{bmatrix}, \quad (45)$$

where \mathbf{d}_* corresponds to \mathbf{d} with $\mu = -1$;

- the parameter β defined in Theorem 1 satisfy $\beta = 1$ for any $\mu < 0$.

Proof. 1) Under Assumption 1, Theorem 3 the dilation $\mathbf{d}(s) = e^{sG_{\mathbf{d}}}$ is uniquely defined such that $G_{\mathbf{d}}$ satisfies (9) with $A_0 = A$. We derive $\mathbf{Ad}(s) = A \sum_{i=0}^{+\infty} \frac{s^i G_{\mathbf{d}}^i}{i!} = \sum_{i=0}^{+\infty} \frac{s^i (\mu I_n + G_{\mathbf{d}})^i A}{i!} = e^{\mu s} \mathbf{d}(s) A$, $\mathbf{d}(s) B = \sum_{i=0}^{+\infty} \frac{s^i G_{\mathbf{d}}^i}{i!} B = \sum_{i=0}^{+\infty} \frac{s^i}{i!} B$,

$\forall s \in \mathbb{R}$. Hence, for all $s \in \mathbb{R}$ we have $\mathbf{d}(s) e^{\tau A} = \mathbf{d}(s) \sum_{i=0}^{n-1} \frac{h^i A^i}{i!} = \sum_{i=0}^{n-1} \frac{e^{-\mu i s} h^i A^i \mathbf{d}(s)}{i!} = e^{e^{-\mu s} \tau A} \mathbf{d}(s)$ and $\mathbf{d}(s) \int_0^h e^{\tau A} d\tau = \int_0^h e^{e^{-\mu s} \tau A} \mathbf{d}(s) d\tau$. and changing of the integration variable we derive (43). 2) On the one hand, since e^{sA} and $\int_0^h e^{\tau A} d\tau$ commute for any $s \in \mathbb{R}$ then taking into account $A_h^i = e^{ihA}$ we derive $W_h = [B_h \ A_h B \ A_h^2 B \ \dots \ A_h^{n-1} B_h] = \left(\int_0^h e^{sA} ds \right) \cdot [B; e^{hA} B \ e^{2hA} B \ \dots \ e^{(n-1)hA} B]$.

On the other hand, the homogeneity identities (42) imply $hB = \mathbf{d}_*(\ln h) B$ and $e^{ihA} \mathbf{d}_*(\ln h) = \mathbf{d}_*(\ln h) e^{iA}$, $\forall i \in \mathbb{N}$, $\forall h > 0$. Hence, we have

$W_h = \left(\frac{1}{h} \int_0^h e^{sA} ds \right) \mathbf{d}_*(\ln h) [B, e^A B, e^{2A} B, \dots, e^{(n-1)A} B]$. Using the identity (43) we derive

$$\mathbf{d}_*(-\ln h) \left(\frac{1}{h} \int_0^h e^{sA} ds \right) = \int_0^1 e^{sA} ds \mathbf{d}_*(-\ln h),$$

so the formula (44) holds. Finally, since $\int_0^n e^{\tau n A} d\tau = \sum_{i=0}^{n-1} \int_i^{i+1} e^{\tau A} d\tau = \int_0^1 e^{\tau A} d\tau \sum_{i=0}^{n-1} e^{iA}$ then $W_h^{-1} \mathbf{d}_*(\ln h) \cdot \int_0^n e^{\tau n A} d\tau B = [B e^A B \ \dots \ e^{(n-1)A} B]^{-1} \sum_{i=0}^{n-1} e^{iA} B = \sum_{i=0}^{n-1} e_i$.

3) For $m = 1$, under conditions of Theorem 3, we have $G_{\mathbf{d}} = U^{-1} \text{diag}\{1 - \mu(n-1), \dots, 1\} U$ for some non-singular matrix $U \in \mathbb{R}^{n \times n}$. The latter means that $\beta = 1$

Lemma 6 The function $V : \mathbb{R}^n \mapsto [0, +\infty)$ defined as $V(x) = \bar{\sigma}^{-1}(\|x\|_{\mathbf{d}})$, $x \in \mathbb{R}^n$ is positive definite radially unbounded and globally Lipschitz continuous with the Lipschitz constant 1, where $\bar{\sigma} \in \mathcal{K}_{\infty}$ is as in Theorem 1.

Proof. The Lipschitz continuity for $\|x\| \geq 1$ follows from [41, Proposition 1]. For $\|x\| \leq 1$ this fact can be proven similarly (just replacing β with α). All other properties of V are obvious.

Lemma 7 For any $C_* > 0$ and any $\varepsilon \in (0, 1)$ there exist $C > 0$ and $r > 0$ such that

$$\|u(x) - u_{\tilde{h}}(\tilde{x})\| \leq C \min\{\|x\|_{\mathbf{d}}^{1+2\mu}, \|\tilde{x}\|^{1+2\mu}\}, \quad (46)$$

for all x, \tilde{x} satisfying $(1-\varepsilon)\|\tilde{x}\|_{\mathbf{d}} \leq \|x\|_{\mathbf{d}} \leq (1+\varepsilon)\|\tilde{x}\|_{\mathbf{d}}$, $\|x\|_{\mathbf{d}}^{\mu} \leq r$, $\|\mathbf{d}(-\ln \|x\|_{\mathbf{d}})(x - \tilde{x})\| \leq C_* \|x\|^{\mu}$.

Proof. Using approximation of $\tilde{u}_{\tilde{h}}$ (see, the proof of Proposition 1) we conclude $\exists h_0 \in (0, 1), \exists C_0 > 0$ such that $\sup_{y \in S} |u(y) - \tilde{u}_{\tilde{h}}(y)| \leq C_0 \tilde{h}, \forall \tilde{h} < h_0$. Since u is locally Lipschitz continuous on $\mathbb{R}^n \setminus \{\mathbf{0}\}$ then for any $\delta \in (0, 1)$ there exists C_1 such that $|u(y) - u(z)| \leq C_1 \|y - z\|, \forall y \in S$ and $\forall z : \|y - z\| \leq \delta$. Using the Lipschitz condition and the dilation symmetry of u and $\tilde{u}_{\tilde{h}}$ (see (28)) we derive

$$\begin{aligned} & |u(x) - \tilde{u}_{\tilde{h}}(\tilde{x})| \leq |u(x) - u(\tilde{x})| + |u(\tilde{x}) - \tilde{u}_{\tilde{h}}(\tilde{x})| = \\ & \|x\|_{\mathbf{d}}^{1+\mu} |u(\mathbf{d}(-\ln \|x\|_{\mathbf{d}})x) - u(\mathbf{d}(-\ln \|\tilde{x}\|_{\mathbf{d}})\tilde{x})| + \\ & \|\tilde{x}\|_{\mathbf{d}}^{1+\mu} |u(\mathbf{d}(-\ln \|\tilde{x}\|_{\mathbf{d}})\tilde{x}) - u_{\|\tilde{x}\|_{\mathbf{d}}^{\mu} \tilde{h}}(\mathbf{d}(-\ln \|\tilde{x}\|_{\mathbf{d}})\tilde{x})| \leq \\ & C_1 \|x\|_{\mathbf{d}}^{1+\mu} \|\mathbf{d}(-\ln \|x\|_{\mathbf{d}})x - \mathbf{d}(-\ln \|\tilde{x}\|_{\mathbf{d}})\tilde{x}\| + \|\tilde{x}\|_{\mathbf{d}}^{1+\mu} C_0 \|\tilde{x}\|_{\mathbf{d}}^{\mu} \hat{h} = \\ & C_1 \|x\|_{\mathbf{d}}^{1+\mu} \|\mathbf{d}(-\ln \|x\|_{\mathbf{d}})x - \mathbf{d}(-\ln \|\tilde{x}\|_{\mathbf{d}})\tilde{x}\| + C_2 \|\tilde{x}\|_{\mathbf{d}}^{1+2\mu} \end{aligned}$$

provided that $\|\mathbf{d}(-\ln \|x\|_{\mathbf{d}})x - \mathbf{d}(-\ln \|\tilde{x}\|_{\mathbf{d}})\tilde{x}\| \leq \delta$ and $\|\tilde{x}\|_{\mathbf{d}}^{\mu} \leq h_0/\hat{h}$, where $C_2 = C_0 \hat{h}$. Taking $r \leq \left(\frac{1-\varepsilon}{1+\varepsilon}\right)^{\mu} \min\left\{\frac{\delta}{C_*}, \frac{h_0}{\hat{h}}\right\}$ and $C = (C_1 C_* + C_2) \left(\frac{1+\varepsilon}{1-\varepsilon}\right)^{1+2|\mu|}$ we complete the proof.

7.2 The proof of Corollary 1

Denoting $y = \|x\|_{\mathbf{d}} \mathbf{d}(-\ln \|x\|_{\mathbf{d}})x$, we derive $\|y\| = \|x\|_{\mathbf{d}} \|\mathbf{d}(-\ln \|x\|_{\mathbf{d}})x\| = \|x\|_{\mathbf{d}}$ and conclude that the closed-loop system (1), (11) is topologically equivalent (homeomorphic on \mathbb{R}^n and diffeomorphic on $\mathbb{R}^n \setminus \{\mathbf{0}\}$, see [41]) to the standard homogeneous system:

$$\dot{y} = \|y\|^{\mu} (A_0 + BK + \rho(G_{\mathbf{d}} - I_n))y,$$

where the identities $\mathbf{d}(s)A_0 = e^{-\mu s}A_0\mathbf{d}(s)$ and $\mathbf{d}(s)B = e^s B, \forall s \in \mathbb{R}$ are utilized on the last step. In this case, using (10) we conclude

$$\frac{d}{dt} \|y(t)\| = -\rho \|y(t)\|^{\mu+1}$$

and $\|y(t + \tau)\|^{-\mu} = \|y(t)\|^{-\mu} + \mu\rho\tau$, for $\|y(t)\|^{-\mu} + \mu\rho\tau \geq 0$. Obviously, $\|y(t + \tau)\| = 0$ if $\|y(t)\|^{-\mu} + \mu\rho\tau \leq 0$. The latter corresponds to the negative homogeneity degree $\tilde{\mu} < 0$ and the finite-time stability of the closed-loop system. Hence, denoting $\tilde{A} = A_0 + BK + \rho G_{\mathbf{d}}$ we obtain

$$\begin{aligned} y(t + \tau) &= e^{(\tilde{A} - \rho I_n) \int_0^{\tau} \|y(t+\sigma)\|^{\mu} d\sigma} y(t) \\ &= e^{(\tilde{A} - \rho I_n) \frac{1}{\mu\rho} \ln(1 + \mu\rho\tau \|y(t)\|^{\mu})} y(t). \end{aligned}$$

Since $\|y(t)\| = \|x(t)\|_{\mathbf{d}}$ then returning to the original coordinates we derive

$$x(t + \tau) = \mathbf{d}(\ln \|y(t + \tau)\|) \frac{y(t + \tau)}{\|y(t + \tau)\|} = Q_{\tau}(\|x(t)\|_{\mathbf{d}})x(t)$$

for all $t \geq 0$ and all $\tau \geq 0$.

7.3 The proof of Corollary 2

Under Assumption 2, the model (1) is a system of interconnected systems with state vectors $x_i \in \mathbb{R}^{n_i}$ and control inputs $u_i \in \mathbb{R}$. By the formula (7), we derive

$$\begin{aligned} & \frac{d}{dt} \|x_i\|_{\mathbf{d}_i} = -\rho_i \|x_i\|_{\mathbf{d}_i}^{1+\mu_i} + \\ & \|x_i\|_{\mathbf{d}_i} \frac{x_i^{\top} \mathbf{d}_i^{\top} (-\ln \|x_i\|_{\mathbf{d}_i}) P_i \mathbf{d}_i (-\ln \|x_i\|_{\mathbf{d}_i}) \sum_{j=i+1}^m A_{ij} x_j}{x_i^{\top} \mathbf{d}_i^{\top} (-\ln \|x_i\|_{\mathbf{d}_i}) P_i G_{\mathbf{d}_i} \mathbf{d}_i (-\ln \|x_i\|_{\mathbf{d}_i}) x_i}, \end{aligned}$$

where A_{ij} are over diagonal blocks of the matrix A . By Theorem 3 the norm in \mathbb{R}^{n_i} is defined as $\|z\| = \sqrt{z^\top P_i z}$, $z \in \mathbb{R}^{n_i}$ and $\|\mathbf{d}_i(-\|x_i\|_{\mathbf{d}_i})x_i\| = 1$. Taking into account $P_i G_{\mathbf{d}_i} + G_{\mathbf{d}_i}^\top P_i \succ 0$ we derive

$$x_i^\top \mathbf{d}_i^\top (-\ln \|x_i\|_{\mathbf{d}_i}) P_i G_{\mathbf{d}_i} \mathbf{d}_i (-\ln \|x_i\|_{\mathbf{d}_i}) x_i \geq \beta_i > 0,$$

where $\beta_i = 0.5 \lambda_{\min}(P_i^{1/2} G_{\mathbf{d}_i} P^{-1/2} + P_i^{-1/2} G_{\mathbf{d}_i}^\top P^{1/2})$. Applying the Cauchy-Schwartz inequality we obtain

$$\frac{x_i^\top \mathbf{d}_i^\top (-\ln \|x_i\|_{\mathbf{d}_i}) P_i \mathbf{d}_i (-\ln \|x_i\|_{\mathbf{d}_i}) \sum_{j=i+1}^m A_{ij} x_j}{x_i^\top \mathbf{d}_i^\top (-\ln \|x_i\|_{\mathbf{d}_i}) P_i G_{\mathbf{d}_i} \mathbf{d}_i (-\ln \|x_i\|_{\mathbf{d}_i}) x_i} \leq$$

$$\frac{1}{\beta_i} \left\| \mathbf{d}_i (-\ln \|x_i\|_{\mathbf{d}_i}) \sum_{j=i+1}^m A_{ij} x_j \right\| \leq \frac{\left\| \sum_{j=i+1}^m A_{ij} x_j \right\|}{\beta_i \sigma_i (\|x_i\|_{\mathbf{d}_i})},$$

where $\sigma_i = \bar{\sigma}^{-1}$ and $\bar{\sigma}$ is given in Theorem 1 with $\alpha = \alpha_i = 0.5 \lambda_{\max}(P_i^{1/2} G_{\mathbf{d}_i} P^{-1/2} + P_i^{-1/2} G_{\mathbf{d}_i}^\top P^{1/2})$ and $\beta = \beta_i$. The estimate obtained for $\frac{d}{dt} \|x_i\|_{\mathbf{d}_i}$, the stability of the m -subsystem and the cascade structure imply the forward completeness of the whole system.

If $V_i(x_i) = \sigma_i (\|x_i\|_{\mathbf{d}_i})$ then for $\|x_i\|_{\mathbf{d}_i} > 1$ we have

$$\frac{dV_i}{dt} = \beta_i \frac{V_i \cdot \frac{d}{dt} \|x_i\|_{\mathbf{d}_i}}{\|x_i\|_{\mathbf{d}_i}} \leq -\beta_i \rho_i V_i^{1+\frac{\mu_i}{\beta_i}} + \left\| \sum_{j=i+1}^m A_{ij} x_j \right\|.$$

For $0 < \|x_i\|_{\mathbf{d}_i} < 1$ we derive

$$\frac{dV_i}{dt} = \alpha_i \frac{V_i \cdot \frac{d}{dt} \|x_i\|_{\mathbf{d}_i}}{\|x_i\|_{\mathbf{d}_i}} \leq -\alpha_i \rho_i V_i^{1+\frac{\mu_i}{\alpha_i}} + \frac{\alpha_i}{\beta_i} \left\| \sum_{j=i+1}^m A_{ij} x_j \right\|$$

Since V_i locally Lipschitz continuous on $\mathbb{R}^{n_i} \setminus \{\mathbf{0}\}$ then using the Clarke's gradient for $\|x_i\|_{\mathbf{d}_i} = 1$ we have

$$\frac{dV_i}{dt} \leq -\lambda_i(x_i) \alpha_i \rho_i V_i^{1+\frac{\mu_i}{\alpha_i}} - (1 - \lambda_i(x_i)) \beta_i \rho_i V_i^{1+\frac{\mu_i}{\beta_i}}$$

$$+ \left(\lambda_i(x_i) \frac{\alpha_i}{\beta_i} + 1 - \lambda_i(x_i) \right) \left\| \sum_{j=i+1}^m A_{ij} x_j \right\|$$

with some $\lambda(x_i) \in [0, 1]$. The latter means that $x_i \mapsto V_i(x_i)$ is an ISS Lyapunov function [53] of the i -th subsystem with respect to the input $\sum_{j=i+1}^m A_{ij} x_j$ provided that $\mu_i > -\beta_i$. Since the m -th subsystem is globally uniformly asymptotically stable then using the cascade structure and the ISS property of each subsystem we conclude that the whole system is globally uniformly asymptotically stable as well. Moreover, the obtained estimate of $\frac{d}{dt} \|x_i\|_{\mathbf{d}_i}$ implies that the finite-time, exponential and nearly fixed-time convergence rates are preserved as well dependently of the sign of μ_i for all $i = 1, \dots, m$. If $\mu_i \leq -\beta_i$, then the each subsystem with the zero input is finite-time stable. Taking into account forward completeness and the cascade structure we conclude that the whole system is finite-time stable too.

7.4 The proof of Theorem 4

On the one hand, since $x_{k+n} = Q_{nh}(\|x_k\|_{\mathbf{d}})x_k$ then, in the view of Corollary 1, the states of the discrete-time system (18) with the control (21) coincides with the states of the original continuous-time system (1), (11) at time instances $t_{kn}, k = 0, 1, \dots$. In this case, if the discrete-time system is globally Lyapunov

stable then the finite-time or nearly fixed-time stability property of the original continuous-time system is preserved.

On the one hand, in the view of Theorem 3 and Corollary 1, we have $\|Q_\tau(\|x\|_{\mathbf{d}})x\|_{\mathbf{d}}^{-\mu} = \|x\|_{\mathbf{d}}^{-\mu} + \mu\rho\tau$ for all $x \in \mathbb{R}^n : \|x\|_{\mathbf{d}}^{-\mu} + \mu\rho\tau \geq 0$ and $\forall \tau > 0$, and $Q_\tau(\|x\|_{\mathbf{d}})x = \mathbf{0}$ otherwise. Hence, we conclude

$$\|Q_\tau(\|x\|_{\mathbf{d}})x\|_{\mathbf{d}} = (\|x\|_{\mathbf{d}}^{-\mu} + \mu\rho\tau)^{-1/\mu} \leq \|x\|_{\mathbf{d}} \leq \bar{\sigma}(\|x\|),$$

where $\bar{\sigma} \in \mathcal{K}_\infty$ is defined in Theorem 1. In this case, there exists $\xi \in \mathcal{K}_\infty$ such that $|u(t_{k+j})| \leq \xi(\|x_{k+j}\|)$, $j = 0, 1, \dots, n-1$ and there exists $\sigma_1 \in \mathcal{K}_\infty$ such that $\|x_{k+j+1}\|_{\mathbf{d}} \leq \sigma_1(\|x_{k+j}\|_{\mathbf{d}})$, $j = 0, 1, \dots, n-1$. Consequently, there exists $\sigma_n \in \mathcal{K}_\infty$ such that $\|x_{k+n}\|_{\mathbf{d}} \leq \sigma_n(\|x_k\|_{\mathbf{d}}), \forall k \in \mathbb{N}$. On the other hand, by construction, we have $x_{k+n} = Q_{nh}(\|x_k\|_{\mathbf{d}})x_k$, so, taking into account $\|Q_{nh}(\|x_k\|_{\mathbf{d}})x_k\|_{\mathbf{d}} \leq \|x_k\|_{\mathbf{d}}$, we derive $\|x_{k+n}\|_{\mathbf{d}} \leq \min\{\|x_k\|_{\mathbf{d}}, \sigma_n(\|x_k\|_{\mathbf{d}})\}$ and $\|x_k\|_{\mathbf{d}} \leq \min\{\|x_0\|_{\mathbf{d}}, \sigma_n(\|x_0\|_{\mathbf{d}})\}, \forall k \geq 0$. Using Theorem 1 we substantiated the global Lyapunov stability of the system (18) (as well as the system (1)) with the sampled-time control (21).

7.5 The proof of Proposition 1

First of all, notice that under Assumption 1 we have $K_0 = \mathbf{0}$ and $A_0 = A$ (see Theorem 3). Let us denote $s_h = \ln(1 + \mu\rho nh r^\mu)^{1/(\rho\mu)}$ with $r = \|x\|_{\mathbf{d}}$ and show $\tilde{K}_h(r) \rightarrow r^{1+\mu}K\mathbf{d}(-\ln r)$ as $h \rightarrow 0$.

On the one hand, if $\mathbf{d}_*(s)$ is defined by Lemma 5 then

$$\begin{aligned} \mathbf{d}_*(-\ln h)e^{(A+BK+\rho G_{\mathbf{d}})s_h} &= \sum_{i=0}^{\infty} \frac{s_h^i \mathbf{d}_*(-\ln h)(A+BK+\rho G_{\mathbf{d}})^i}{i!} = \\ &= \sum_{i=0}^{\infty} \frac{s_h^i (A+BK\mathbf{d}_*(\ln h) + \rho h G_{\mathbf{d}})^i \mathbf{d}_*(-\ln h)}{h^i i!} = \\ &= e^{\frac{s_h(A+\rho h G_{\mathbf{d}})}{h}} \mathbf{d}_*(-\ln h) + \sum_{i=1}^{n-1} \frac{s_h^i}{h^i i!} A^{i-1} BK + O(h). \end{aligned}$$

Indeed, for $i = 2$ we have

$$(A + BK\mathbf{d}_*(\ln h) + \rho h G_{\mathbf{d}})^2 \mathbf{d}_*(-\ln h) = (A + \rho h G_{\mathbf{d}})^2 \mathbf{d}_*(-\ln h) + ABK + O(h),$$

for $i = 3$ we derive

$$\begin{aligned} (A + BK\mathbf{d}_*(\ln h) + \rho h G_{\mathbf{d}})^3 \mathbf{d}_*(-\ln h) &= \\ (A + BK\mathbf{d}_*(\ln h) + \rho h G_{\mathbf{d}}) \{ (A + \rho h G_{\mathbf{d}})^2 \mathbf{d}_*(-\ln h) + ABK + O(h) \} &= \\ (A + \rho h G_{\mathbf{d}})^3 \mathbf{d}_*(-\ln h) + A^2 BK + O(h) & \end{aligned}$$

and, by induction, we conclude $(A + BK\mathbf{d}_*(\ln h) + \rho h G_{\mathbf{d}})^i \mathbf{d}_*(-\ln h) = (A + \rho h G_{\mathbf{d}})^i \mathbf{d}_*(-\ln h) + A^{i-1} BK + O(h)$. Since A is nilpotent then for $i \geq n+1$ we have $A^{i-1} = \mathbf{0}$ and $(A+BK\mathbf{d}_*(\ln h) + \rho h G_{\mathbf{d}})^i \mathbf{d}_*(-\ln h) = (A + \rho h G_{\mathbf{d}})^i \mathbf{d}_*(-\ln h) + O(h)$.

On the other hand, since $\mathbf{d}(-s)A\mathbf{d}(s) = e^{\mu s}A$ then $\mathbf{d}(-s)e^{\tau A}\mathbf{d}(s) = e^{e^{\mu\tau}A}$ for all $s, \tau \in \mathbb{R}$ and $Q_{nh}(r) - A_h^n = \mathbf{d}(\ln r)\hat{Q}(s_h)\mathbf{d}(-\ln r) - e^{nhA} = \mathbf{d}(\ln r)(\hat{Q}(s_h) - e^{nhr^\mu A})\mathbf{d}(-\ln r)$ where $\hat{Q}(s_h)$ is given by (16). Since $\mathbf{d}^*(s)$ commutes with $\mathbf{d}(\tau)$,

$\forall s, \tau \in \mathbb{R}$ then using the identities (42) and the estimate of $\mathbf{d}_*(-\ln h)e^{(A+BK+\rho G_{\mathbf{d}})s_h}$ we derive

$$\begin{aligned} & \mathbf{d}_*(-\ln h) \left(e^{(A+BK+\rho G_{\mathbf{d}})s_h} - e^{\rho s_h G_{\mathbf{d}}} e^{nr^\mu A} \right) = \\ & \mathbf{d}_*(-\ln h) e^{(A+BK+\rho G_{\mathbf{d}})s_h} - e^{\rho s_h G_{\mathbf{d}}} e^{nr^\mu A} \mathbf{d}_*(-\ln h) = \\ & \sum_{i=0}^{n-1} \frac{s_h^i A^{i-1} BK}{h^i i!} + \left(e^{\frac{s_h(A+\rho h G_{\mathbf{d}})}{h}} - e^{\rho s_h G_{\mathbf{d}}} e^{nr^\mu A} \right) \mathbf{d}_*(-\ln h) + O(h). \end{aligned}$$

If $Z_1 = \rho s_h G_{\mathbf{d}}$, $Z_2 = nr^\mu A$, $q = -\mu \rho s_h$ then the condition $Z_1 Z_2 - Z_2 Z_1 = q Z_2$ of Lemma 4 is fulfilled, so $e^{Z_1} e^{Z_2} = e^{Z_1 + \frac{q}{1-e^{-q}} Z_2}$ or, equivalently, $e^{\rho s_h G_{\mathbf{d}}} e^{nr^\mu A} = e^{\rho s_h G_{\mathbf{d}} + \frac{s_h}{h} A}$. Therefore, since $s_h = \frac{\ln(1+\mu \rho n h r^\mu)}{\rho \mu} = \frac{\mu \rho n h r^\mu - \frac{(\mu \rho 2 h r^\mu)^2}{2} + O(h^3)}{\rho \mu} = h n r^\mu + O(h^2)$ then $\mathbf{d}_*(-\ln h) \left(e^{(A+BK+\rho G_{\mathbf{d}})s_h} - e^{\rho s_h G_{\mathbf{d}}} e^{nr^\mu A} \right) = \sum_{i=0}^{n-1} \frac{s_h^i A^{i-1} BK}{h^i i!} + O(h) = \sum_{i=0}^{n-1} \frac{(nr^\mu)^i A^{i-1} BK}{i!} + O(h) = \int_0^{nr^\mu} e^{\tau A} d\tau BK + O(h)$. Since $\mathbf{d}(s) = e^{s G_{\mathbf{d}}}$ then

$$\begin{aligned} & \mathbf{d}_*(-\ln h) (Q_{nh}(r) - A_h^n) = \\ & \mathbf{d}(\ln r) e^{-\rho s_h G_{\mathbf{d}}} \int_0^{nr^\mu} e^{\tau A} d\tau BK \mathbf{d}(-\ln r) + O(h) = \\ & \int_0^{nr^\mu} \mathbf{d}(\ln r - \rho s_h) e^{\tau A} d\tau BK \mathbf{d}(-\ln r) + O(h) = \\ & \int_0^{nr^\mu} e^{-\mu(\ln r - \rho s_h) \tau A} d\tau \mathbf{d}(\ln r - \rho s_h) BK \mathbf{d}(-\ln r) + O(h) = \\ & \int_0^{nr^\mu} e^{\frac{1+\mu \rho n h r^\mu}{r^\mu} \tau A} d\tau \frac{r}{(1+\mu \rho n h r^\mu)^{1/\mu}} BK \mathbf{d}(-\ln r) + O(h) = \\ & \int_0^{nr^\mu} e^{\frac{1}{r^\mu} \tau A} d\tau B r K \mathbf{d}(-\ln r) + O(h) = \\ & \int_0^n e^{\tau A} d\tau B r^{1+\mu} K \mathbf{d}(-\ln r) + O(h). \end{aligned}$$

Therefore, using Lemma 5 and Remark 2 we conclude

$$\begin{aligned} & \tilde{K}_h(r) = e_n^\top W_n^{-1} (Q_{nh}(s_h) - A_h^n) = \\ & e_n^\top W_n^{-1} \mathbf{d}_*(\ln h) \left(\int_0^n e^{\tau A} d\tau B r^{1+\mu} K \mathbf{d}(-\ln r) + O(h) \right) = \\ & r^{1+\mu} K \mathbf{d}(-\ln r) + O(h^2), \end{aligned}$$

and $\tilde{K}_h(r) \rightarrow r^{1+\mu} K \mathbf{d}(-\ln r)$ as $h \rightarrow 0$ uniformly on r from compacts belonging to $(0, +\infty)$.

7.6 The proof of Lemma 1

Let us show that (27) holds. Indeed, on the one hand, since $\|\mathbf{d}(s)x\|_{\mathbf{d}} = e^s \|x\|_{\mathbf{d}}$ then

$$\hat{Q} \left(\frac{\ln(1+\mu \rho n h e^{-\mu s} \|\mathbf{d}(s)x\|_{\mathbf{d}}^\mu)}{\rho \mu} \right) = \hat{Q} \left(\frac{\ln(1+\mu \rho n h \|x\|_{\mathbf{d}}^\mu)}{\rho \mu} \right)$$

and $\forall s \in \mathbb{R}, \forall x \in \mathbb{R}^n$ we have

$$Q_{nh} e^{-\mu s} (\|\mathbf{d}(s)x\|_{\mathbf{d}}) = \mathbf{d}(s) Q_{nh} (\|x\|_{\mathbf{d}}) \mathbf{d}(-s).$$

On the other hand, using Lemma 5 we derive

$$\begin{aligned} & W_{e^{-\mu s} h} = \mathbf{d}_*(-\mu s) W_h, \quad B_{e^{-\mu s} h} = e^{-\mu s - s} \mathbf{d}(s) B_h, \\ & L_{e^{-\mu s} h} \mathbf{d}(s) = \mathbf{d}(s) L_h, \quad \mathbf{d}(s) F_h = F_{e^{-\mu s} h} \mathbf{d}(s), \end{aligned}$$

for all $s \in \mathbb{R}$ and for all $h > 0$, where the identities $\mathbf{d}_*(\tau) = e^{\tau I_n + \tau G_0}$ and $\mathbf{d}(s) = e^{s I_n - s \mu G_0}$ are utilized for the analysis L_h in order to conclude that $e^{-s - \mu s} \mathbf{d}_*(\mu s) \mathbf{d}(s) = I_n$, where G_0 is defined in Theorem 3. Hence, we derive (27). The identity (28) can be obtained in the same way.

7.7 The proof of Lemma 2

1) Local Finite-Time Stability for $\mu < 0$. Let us show that the matrix F_h is nilpotent. Notice that F_h can be rewritten as follows

$$\begin{aligned} F_h &= (I_n - [\mathbf{0} \ \mathbf{0} \ \dots \ \mathbf{0} \ B_h]W_h^{-1}A_h^{n-1})A_h = \\ &= (A_h^{1-n}W_hW_h^{-1}A_h^{n-1} - [\mathbf{0} \ \mathbf{0} \ \dots \ \mathbf{0} \ B_h]W_h^{-1}A_h^{n-1})A_h = \\ &= A_h^{1-n}(W_h - [\mathbf{0} \ \mathbf{0} \ \dots \ \mathbf{0} \ A_h^{n-1}B_h])W_h^{-1}A_h^n = \\ &= A_h^{1-n}[B_h \ A_hB_h \ \dots \ A_h^{n-2}B_h \ \mathbf{0}]W_h^{-1}A_h^n \end{aligned}$$

Since $W_h^{-1}[A_hB_h \ \dots \ A_h^{n-1}B_h \ \mathbf{0}] = [e_2 \ \dots \ e_n \ \mathbf{0}]$ then

$$\begin{aligned} F_h^2 &= A_h^{1-n}[B_h \ A_hB_h \ \dots \ A_h^{n-2}B_h \ \mathbf{0}][e_2 \ e_3 \ \dots \ e_n \ \mathbf{0}]W_h^{-1}A_h^n = \\ &= A_h^{1-n}[A_hB_h \ \dots \ A_h^{n-2}B_h \ \mathbf{0}]W_h^{-1}A_h^n. \end{aligned}$$

Continuing the same considerations we derive $F_h^n = \mathbf{0}$. On the one hand, since for $\mu < 0$ we have $Q(\|x\|_{\mathbf{d}}) = \mathbf{0}$ if $\|x\|_{\mathbf{d}} \leq (-\mu\rho nh)^{-1/\mu}$ then the closed-loop system becomes linear $x_{k+1} = F_h x_k$ for $\|x_k\|_{\mathbf{d}} \leq (-\mu\rho nh)^{-1/\mu} = (\hat{h}/h)^{1/\mu}$. On the other hand, the inequality $\|F_h^i x_0\|_{\mathbf{d}} \leq (\hat{h}/h)^{1/\mu}$ is equivalent to $\left\| \mathbf{d} \left(\frac{1}{\mu} \ln \frac{h}{\hat{h}} \right) F_h^i x_0 \right\| = \left\| F_h^i \mathbf{d} \left(\frac{1}{\mu} \ln \frac{h}{\hat{h}} \right) x_0 \right\| \leq 1$, and the inequality $\|x_0\|_{\mathbf{d}} \leq \underline{r}^- \left(\frac{\hat{h}}{h} \right)^{1/\mu}$ is equivalent to $\left\| \mathbf{d}(-\ln \underline{r}^-) \mathbf{d} \left(\frac{1}{\mu} \ln \frac{h}{\hat{h}} \right) x_0 \right\| \leq 1$. Therefore, the inequality $\|F_h^i \mathbf{d}(\ln \underline{r}^-)\| \leq 1$ yields $\left\| F_h^i \mathbf{d} \left(\frac{1}{\mu} \ln \frac{h}{\hat{h}} \right) x_0 \right\| \leq \left\| \mathbf{d}(-\ln \underline{r}^-) \mathbf{d} \left(\frac{1}{\mu} \ln \frac{h}{\hat{h}} \right) x_0 \right\|$. Hence, we derive $\|x_i\|_{\mathbf{d}} = \|F_h^i x_0\|_{\mathbf{d}} \leq \left(\frac{\hat{h}}{h} \right)^{1/\mu}$ for $i = 1, \dots, n-1$ provided that $\|x_0\|_{\mathbf{d}} \leq \underline{r}^- \left(\frac{\hat{h}}{h} \right)^{1/\mu}$. Taking into account the nilpotence of F_h , the latter implies local Lyapunov stability of the closed-loop system and the finite-time convergence of solutions to zero.

2) Practical Finite-time Stability for $\mu < 0$. The proof repeats the proof of Theorem 7, the case 1) for $q = \mathbf{0}$ and gives $\frac{d\|x\|_{\mathbf{d}}}{dt} \leq -0.5\rho\|x\|_{\mathbf{d}}^{1+\mu}$ for all $x : \|x\|_{\mathbf{d}}^{-\mu} \geq \tilde{r}$. Using Lemma 1 we derive Ω^- for $h \neq \hat{h}$ with $\bar{r}^- = \tilde{r}^{-1/\mu}$, where \tilde{r} is defined in the proof of Theorem 7.

3) Practical Fixed-time Stability for $\mu > 0$ Let us prove, now, the practical fixed-time stability. On the one hand, since, by Theorem 3 the canonical homogeneous norm is a Lyapunov function of the system satisfying

$$\frac{d}{dt}\|x(t)\|_{\mathbf{d}} = -\rho\|x(t)\|_{\mathbf{d}}^{1+\mu},$$

then $\|x(t+nh)\|_{\mathbf{d}}^{-\mu} = \|x(t)\|_{\mathbf{d}}^{-\mu} + \mu\rho nh$, and for $\mu > 0$ we have $\|x(t+nh)\|_{\mathbf{d}} < (\mu\rho nh)^{-1/\mu} = \left(\frac{\hat{h}}{h} \right)^{1/\mu}$ independently of $x(t)$. On the other hand, by Corollary 1,

we have $x(t+nh) = Q_{nh}(\|x(t)\|_{\mathbf{d}})x(t)$, so $\|Q_{nh}(\|\tilde{x}\|_{\mathbf{d}})\tilde{x}\|_{\mathbf{d}} \leq \left(\frac{\hat{h}}{h} \right)^{1/\mu}$, $\forall \tilde{x} \in \mathbb{R}^n$.

Since the right-hand side of the system can be represented as follows

$$z_h(x) = F_h x + L_h Q_{nh}(\|x\|_{\mathbf{d}})x, \quad L_h := B_h e_n^\top W_h^{-1},$$

then, for any $x_0 \in \mathbb{R}^n$ the solution $x_k, k = 0, 1, 2, \dots$ of the discrete-time system (18), (22) satisfies

$$\begin{aligned}
x_1 &= F_h x_0 + L_h y_1, \\
x_2 &= F_h^2 x_0 + F_h L_h y_1 + L_h y_2, \\
&\dots \\
x_n &= F_h^n x_0 + F_h^{n-1} L_h y_1 + F_h^{n-2} L_h y_2 + \dots + L_h y_n,
\end{aligned}$$

where $y_i = Q_{nh}(\|x_{i-1}\|_{\mathbf{d}})x_{i-1}$, $i = 1, 2, \dots$. Since the matrix F_h is nilpotent then $F_h^n = \mathbf{0}$ and

$$x_k = F_h^{n-1} L_h y_{k-n+1} + F_h^{n-2} L_h y_{k-n+2} + \dots + L_h y_k, \forall k \geq n.$$

Since $\|y_i\|_{\mathbf{d}} \leq \left(\frac{\hat{h}}{h}\right)^{\frac{1}{\mu}} \Leftrightarrow \left\| \mathbf{d} \left(\frac{1}{\mu} \ln \frac{\hat{h}}{h} \right) y_i \right\|_{\mathbf{d}} \leq 1 \Leftrightarrow \left\| \mathbf{d} \left(\frac{1}{\mu} \ln \frac{\hat{h}}{h} \right) y_i \right\| \leq 1$ then

$$\left\| \mathbf{d} \left(\frac{1}{\mu} \ln \frac{\hat{h}}{h} \right) x_k \right\|_{\mathbf{d}} = \left\| \sum_{i=1}^n \mathbf{d} \left(\frac{1}{\mu} \ln \frac{\hat{h}}{h} \right) F_h^{i-1} L_h \mathbf{d} \left(-\frac{1}{\mu} \ln \frac{\hat{h}}{h} \right) v_i \right\|_{\mathbf{d}},$$

where $v_i = \mathbf{d} \left(\frac{1}{\mu} \ln \frac{\hat{h}}{h} \right) y_{k+n-i}$. Taking into account $F_{\hat{h}} = \mathbf{d} \left(\frac{1}{\mu} \ln \frac{\hat{h}}{h} \right) F_h \mathbf{d} \left(-\frac{1}{\mu} \ln \frac{\hat{h}}{h} \right)$, $L_{\hat{h}} = \mathbf{d} \left(\frac{1}{\mu} \ln \frac{\hat{h}}{h} \right) L_h \mathbf{d} \left(-\frac{1}{\mu} \ln \frac{\hat{h}}{h} \right)$ and $\|v_i\| \leq 1$ we derive $\left\| \mathbf{d} \left(\frac{1}{\mu} \ln \frac{\hat{h}}{h} \right) x_k \right\|_{\mathbf{d}} < \tilde{r}^+$, $\forall k \geq n$.

4) Local Asymptotic Stability for $\mu > 0$. Since $\frac{d\|x\|_{\mathbf{d}}}{dt} \leq -0.5\rho\|x\|_{\mathbf{d}}^{1+\mu}$ for all $x : \|x\|_{\mathbf{d}}^{\mu} \leq \tilde{r}^{-1}$ then for $\mu > 0$ the closed-loop system is locally asymptotically stable. Using Lemma 1 we derive Ω^+ with $\underline{r}^+ = \tilde{r}^{-1/\mu}$.

7.8 The proof of Lemma 3

The symmetry proven by Lemma 1 yields

$$M_h(\|x\|_{\mathbf{d}})x = \mathbf{d}(s)M_{e^{\mu s}h}(\|\mathbf{d}(-s)x\|_{\mathbf{d}})\mathbf{d}(-s)x$$

for all $x \in \mathbb{R}^n$, for all $s \in \mathbb{R}$ and $\forall h > 0$. Hence, for any $x_0 \in \mathbb{R}^n \setminus \{\mathbf{0}\}$ we have $x_1 = M_h(\|x_0\|_{\mathbf{d}})x_0 = \mathbf{d}(\ln \|x_0\|_{\mathbf{d}})\Theta_1(\|x_0\|_{\mathbf{d}}^{\mu}\hat{h}, v_0)v_0$. Since $\|x_1\|_{\mathbf{d}} = \|x_0\|_{\mathbf{d}} \|\Theta_1(\|x_0\|_{\mathbf{d}}^{\mu}, v_0)v_0\|_{\mathbf{d}}$ then

$$\begin{aligned}
x_2 &= M_h(\|x_1\|_{\mathbf{d}})x_1 = M_h(\|x_1\|_{\mathbf{d}})\mathbf{d}(\ln \|x_0\|_{\mathbf{d}})\Theta_1(\|x_1\|_{\mathbf{d}}\hat{h}, v_0)v_0 \\
&= \mathbf{d}(\ln \|x_0\|_{\mathbf{d}})M_{\|x_0\|_{\mathbf{d}}^{\mu}\hat{h}}(\|x_1\|_{\mathbf{d}}/\|x_0\|_{\mathbf{d}})\Theta_1(\|x_0\|_{\mathbf{d}}^{\mu}, v_0)v_0 \\
&= \mathbf{d}(\ln \|x_0\|_{\mathbf{d}})\Theta_2(\|x_0\|_{\mathbf{d}}^{\mu}, v_0)v_0. \text{ Repeating the above considerations we derive} \\
&(31).
\end{aligned}$$

7.9 The proof of Theorem 5

The approximation property is proven by Proposition 1. Let us prove the consistency of stability properties. If the discrete-time system (26) is globally uniformly finite-time stable for some $h > 0$ then due to dilation symmetry (see Lemma 1) it is globally uniformly finite-time stable for any $h > 0$, in particular, for $h = \hat{h}$.

Necessity. Let us consider **the case** $\mu < 0$. The uniformity of the finite-time stability and Lemma 2 guarantee that there exists $k^* \geq 1$ such that for any $x_0 : \|x_0\|_{\mathbf{d}} \geq \underline{r}^-$ we have $\|x_{k^*}\|_{\mathbf{d}} < \|x_0\|_{\mathbf{d}}$. The latter means that $\|x_0\|_{\mathbf{d}}\|\Theta_{k^*}(\|x_0\|_{\mathbf{d}}^{\mu}, v_0)v_0\|_{\mathbf{d}} < \|x_0\|_{\mathbf{d}}$ and

$$\|\Theta_{k^*}(\underline{r}^{\mu}, v_0)v_0\|_{\mathbf{d}} < 1, \forall \underline{r} \geq \underline{r}^-, \forall v_0 \in S.$$

Denoting $\delta = r^\mu$ for $\mu < 0$ we derive the inequality (32). **The case $\mu > 0$** can be treated similarly.

Sufficiency. Let us denote $r_* = (\bar{r}^-)^\mu$ for $\mu < 0$ and $r_* = (\underline{r}^+)^\mu$ for $\mu > 0$. Let us consider the candidate Lyapunov function $V : \mathbb{R}^n \mapsto [0, +\infty)$ defined as follows

$$V(x) = \begin{cases} \|\mathbf{d}(-\mu^{-1} \ln r_*)x\|_{\mathbf{d}}^p & \text{if } \|x\|_{\mathbf{d}}^\mu \leq r_*, \\ \|\mathbf{d}(-\mu^{-1} \ln r_*)x\| & \text{if } \|x\|_{\mathbf{d}}^\mu \geq r_*, \end{cases} \quad (47)$$

where $p = \beta$ if $\mu < 0$ and $p = \alpha$ if $\mu > 0$, where α, β are given by Theorem 1. By construction, V is positive definite, radially unbounded and globally Lipschitz continuous with the Lipschitz constant $L = \|\mathbf{d}(-\mu^{-1} \ln r_*)\|$ and Lemma 6.

a) Let us show that V is a Lyapunov function for $\|x_0\|_{\mathbf{d}}^\mu \in [r_*, r^*]$. Since $(\delta, v) \mapsto \|\Theta_{k^*}(\delta, v)v\|_{\mathbf{d}}$ is a continuous function on the compact $[r_*, r^*] \times S$ then using (32) we derive $\gamma = \max_{\delta \in [r_*, r^*]} \|\Theta_{k^*}(\delta, v)v\|_{\mathbf{d}} < 1$ and for $\|x_0\|_{\mathbf{d}}^\mu \in [r_*, r^*]$ we have $\|x_{k^*}\|_{\mathbf{d}} \leq \gamma \|x_0\|_{\mathbf{d}}$. Since $\|x_{k^*}\|_{\mathbf{d}} \leq \gamma \|x_0\|_{\mathbf{d}} \Leftrightarrow \|\mathbf{d}(s)x_{k^*}\|_{\mathbf{d}} \leq \gamma \|\mathbf{d}(s)x_0\|_{\mathbf{d}}, \forall s \in \mathbb{R}$ then $V(x_{k^*}) \leq \gamma^p V(x_0)$ for $\|x_0\|_{\mathbf{d}}^\mu \in [r_*, r^*]$.

b) Let us show that V is a Lyapunov function for $\|x_0\|_{\mathbf{d}}^\mu \leq r_*$. Since $\frac{d\|x\|_{\mathbf{d}}}{dt} \leq -0.5\rho\|x\|_{\mathbf{d}}^{1+\mu}$ for all $x : \|x\|_{\mathbf{d}}^\mu \leq r_*$ (see the proof of Lemma 2, case 2), then $\|x_1\|_{\mathbf{d}} \leq \gamma_*(\|x_0\|_{\mathbf{d}}^\mu)\|x_0\|_{\mathbf{d}}, \forall x_0 : \|x_0\|_{\mathbf{d}}^\mu \leq r_*$, or equivalently, $V(x_1) \leq \gamma_*^p(\|x_0\|_{\mathbf{d}}^\mu)V(x_0), \forall x_0 : \|x_0\|_{\mathbf{d}}^\mu \leq r_*$, where $\gamma_*(s) = (1 + 0.5\rho\mu s)^{-1/\mu}$ with $s > 0$.

c) Let us show that V is a Lyapunov function for $\|x_0\|_{\mathbf{d}}^\mu \geq r^*$. If $\|x_0\|_{\mathbf{d}}^\mu > r^*$ then for all $k \geq n$ we have $\|x_k\| = 0$ if $\mu < 0$ and $\|\mathbf{d}(-\mu^{-1} \ln r_*)x_k\| < 1$ if $\mu > 0$ (see the proof of Lemma 2). This means that there exist $\gamma^* \in (0, 1)$ such that $V(x_k) \leq \gamma^* V(x_0), \|x_0\|_{\mathbf{d}}^\mu > r^*$. Without loss of generality we may assume that $k^* \geq n$ (otherwise we just take nk^* instead of k^* in all above considerations).

d) Therefore, for any $\bar{r}_* \in (0, r_*)$ and for any finite $\bar{r}^* > r_*$ there exists $\bar{\gamma} \in (0, 1)$ such that

$$V(x_{k^*}) \leq \bar{\gamma} V(x_0), \quad \forall x_0 : \bar{r}_* \leq \|x_0\|_{\mathbf{d}}^\mu \leq \bar{r}^*.$$

Taking into account local finite-time (resp., asymptotic) stability and practical finite-time (resp., fixed-time) stability proven by Lemma 2 for $\mu < 0$ (resp., $\mu > 0$) we complete the proof.

7.10 The proof of Theorem 6

In a discrete time, the system (36) can be rewritten as

$$x_{k+n}^q = Q_{nh}(\|x_k^q\|_{\mathbf{d}})x_k^q + \sum_{i=0}^{n-1} A_h^{n-i} \tilde{q}_{k+i}$$

where $\tilde{q}_k = \int_0^h e^{A(h-\tau)} q_p(t_k + \tau) d\tau$ is the sampled-time realization of the external perturbation, so $\{\tilde{q}_k\} \in \ell^\infty$ for any $h > 0$. Let V be defined as in Lemma 6. Since $\|Q_{nh}(\|x\|_{\mathbf{d}})x\|_{\mathbf{d}}^{-\mu} = \|x\|_{\mathbf{d}}^{-\mu} + \mu\rho nh$ for all $x \in \mathbb{R}^n : \|x\|_{\mathbf{d}}^{-\mu} + \mu\rho nh \geq 0$ then $\|x_{k+n}^q - \bar{q}_k\|_{\mathbf{d}}^{-\mu} = \|x_k^q\|_{\mathbf{d}}^{-\mu} + \mu\rho nh$, where $\bar{q}_k = \sum_{i=0}^{n-1} A_h^{n-i} \tilde{q}_{k+i}$. Moreover, since \bar{q}_k is uniformly bounded, then for $\mu > 0$ it guarantees a practical fixed-time stability. In this case, we derive

$$\begin{aligned}
V(x_{k+n}^q) - V(x_k^q) &= V(x_{k+n}^q) - V(x_{k+n}^q - \tilde{q}_k) + V(x_{k+n}^q - \tilde{q}_k) - V(x_k^q) \\
&\leq \|\tilde{q}_k\| + V(x_{k+n}^q - \tilde{q}_k) - V(x_k^q) = \|\tilde{q}_k\| + \bar{\sigma}^{-1}(\|x_k^q - \tilde{q}_k\|_{\mathbf{d}}) - V(x_k^q) \\
&= \|\tilde{q}_k\| + W(V(x_k^q)),
\end{aligned}$$

where $W(V) = \bar{\sigma}^{-1}(\bar{\sigma}(V)^{-\mu} + \mu\rho nh)^{-1/\mu} - V$. For $\mu > -\beta$ we have $W \in \mathcal{K}_\infty$ and V is an ISS Lyapunov function [22].

7.11 The proof of Theorem 7

In a discrete time, the system (37) can be rewritten as

$$x_{k+1}^q = A_h x_k^q + B_h \tilde{K}_h(\|x_k^q + \hat{q}_k\|)(x_k^q + \hat{q}_k) + \tilde{q}_k, \quad (48)$$

where $\{\hat{q}_k\}, \{\tilde{q}_k\} \in \ell^\infty$ for any $h > 0$, $\hat{q}_k = q_m(t_k)$ is the sampled-time realization of the measurement noise and $\tilde{q}_k = \int_0^h e^{A(h-\tau)} q_p(t_k + \tau) d\tau$ is the sampled-time realization of the external perturbation. Denote $q_k = (\tilde{q}_k^\top, \hat{q}_k^\top)$. Due to the dilation symmetry proven by Lemma 1 it is sufficient to analyze ISS of (48) for $h = \hat{h}$.

1) Let us prove local ISS and practical ISS of (37). If $x = e^{Ah_t} x_k^q + B_{h_t} \tilde{u}_{\hat{h}}(x_k^q + \hat{q}_k) + \tilde{q}_{h_t}$, $h_t = t - t_k$ and $\tilde{q}_{h_t} = \int_0^{h_t} e^{A(h_t-\tau)} q_p(t_k + \tau) d\tau$ then x corresponds to a solution of the system (37) for $t \in [t_k, t_k + \hat{h})$. Let us denote $q_k^1 = \mathbf{d}(-\ln \|x_k^q\|_{\mathbf{d}}) \hat{q}_k$, $q_k^2 = \mathbf{d}(-\ln \|x_k^q\|_{\mathbf{d}}) \tilde{q}_{h_t}$. a) Let us show that $\|x_k^q\|_{\mathbf{d}}$ is close to $\|x\|_{\mathbf{d}}$ for a sufficiently large $\|x_k^q\|_{\mathbf{d}}^{-\mu}$ and sufficiently small q_k^i , $i = 1, 2$. Using dilation symmetry (see (28)) we derive $x = \mathbf{d}(\ln \|x_k^q\|_{\mathbf{d}}) (e^{A h_t \|x_k^q\|_{\mathbf{d}}^\mu} v_k + B_{h_t \|x_k^q\|_{\mathbf{d}}^\mu} \tilde{u}_{\hat{h}} \|x_k^q\|_{\mathbf{d}}^\mu (v_k + q_k^1) + q_k^2)$, with $v_k = \mathbf{d}(-\ln \|x_k^q\|_{\mathbf{d}}) x_k^q \in S$. Since $e^{A h_t s} \rightarrow I_n$ as $s \rightarrow 0$ and $B_{h_t s} \rightarrow \mathbf{0}$ as $s \rightarrow 0$ then for any $\varepsilon \in (0, 1)$ there exist $r_\varepsilon > 0$ and $\delta_\varepsilon > 0$ such that

$$\left\| e^{A h_t \|x_k^q\|_{\mathbf{d}}^\mu} v_k + B_{h_t \|x_k^q\|_{\mathbf{d}}^\mu} \tilde{u}_{\hat{h}} (v_k + q_k^1) + q_k^2 \Big|_{\mathbf{d}} - 1 \right\| \leq \varepsilon$$

for $\|x_k^q\|_{\mathbf{d}}^{-\mu} > r_\varepsilon$ and $\|q_k^i\| \leq \delta_\varepsilon$, $i = 1, 2$. Hence, we have $(1 - \varepsilon) \|x_k^q\|_{\mathbf{d}} \leq \|x\|_{\mathbf{d}} \leq (1 + \varepsilon) \|x_k^q\|_{\mathbf{d}}$ and $\exists \tilde{C}_0, \tilde{C}_1 > 0 : \|\mathbf{d}(-\ln \|x\|_{\mathbf{d}}) \hat{q}_k\| = \left\| \mathbf{d} \left(-\ln \frac{\|x\|_{\mathbf{d}}}{\|x_k^q\|_{\mathbf{d}}} \right) q_k^1 \right\| \leq \tilde{C}_0 \|q_k^1\|$ and $\|\mathbf{d}(-\ln \|x\|_{\mathbf{d}}) x_k^q\| < \tilde{C}_1$ for $\|x_k^q\|_{\mathbf{d}}^{-\mu} > r_\varepsilon$ and $\|q_k^i\| \leq \delta_\varepsilon$.

b) Let us show that $u_h(x_k^q + \hat{q}_k)$ is close to $u(x)$ for a sufficiently large $\|x_k^q\|_{\mathbf{d}}^{-\mu}$ and sufficiently small $\|q_k^i\|$. Using Lemma 5 and the identity $x_k^q = e^{-Ah_t} x - e^{-Ah_t} B_{h_t} \tilde{u}_{\hat{h}}(x_k^q + \hat{q}_k) - e^{-Ah_t} \tilde{q}_{h_t}$ we derive

$$\begin{aligned}
&\mathbf{d}(-\ln \|x\|_{\mathbf{d}}) x - \mathbf{d}(-\ln \|x\|_{\mathbf{d}}) (x_k^q + \hat{q}_k) = \\
&\mathbf{d}(-\ln \|x\|_{\mathbf{d}}) (I_n - e^{-Ah_t}) x + \mathbf{d}(-\ln \|x\|_{\mathbf{d}}) e^{-Ah_t} B_{h_t} \tilde{u}_{\hat{h}}(x_k^q + \hat{q}_k) \\
&\quad + \mathbf{d}(-\ln \|x\|_{\mathbf{d}}) e^{-Ah_t} \tilde{q}_{h_t} + \mathbf{d}(-\ln \|x\|_{\mathbf{d}}) \hat{q}_k = \\
&-\mathbf{d}(-\ln \|x\|_{\mathbf{d}}) \int_0^{h_t} A e^{A\tau} d\tau x + e^{-Ah_t} \|x\|_{\mathbf{d}}^\mu \mathbf{d}(-\ln \|x\|_{\mathbf{d}}) B_{h_t} \tilde{u}_{\hat{h}}(x_k^q + \hat{q}_k) \\
&\quad + e^{-Ah_t} \|x\|_{\mathbf{d}}^\mu \mathbf{d}(-\ln \|x\|_{\mathbf{d}}) \tilde{q}_{h_t} + \mathbf{d}(-\ln \|x\|_{\mathbf{d}}) \hat{q}_k = \\
&\quad - \int_0^{h_t} \|x\|_{\mathbf{d}}^\mu A e^{A\tau} d\tau \mathbf{d}(-\ln \|x\|_{\mathbf{d}}) x \\
&+ e^{-Ah_t} \|x\|_{\mathbf{d}}^\mu \cdot B_{h_t} \|x\|_{\mathbf{d}}^\mu \cdot \tilde{u}_{\|x\|_{\mathbf{d}}^\mu \hat{h}} (\mathbf{d}(-\ln(\|x\|_{\mathbf{d}}/\|x_k^q\|_{\mathbf{d}})) (v_k + q_k^1)) \\
&\quad + e^{-Ah_t} \|x\|_{\mathbf{d}}^\mu \mathbf{d}(-\ln(\|x\|_{\mathbf{d}}/\|x_k^q\|_{\mathbf{d}})) q_k^2 + \mathbf{d}(-\ln \|x\|_{\mathbf{d}}) \hat{q}_k.
\end{aligned}$$

Since $\exists \tilde{C}_2 > 0 : \left\| \int_0^{h_t} \|x\|_{\mathbf{d}}^\mu A e^{A\tau} d\tau \right\| \leq \tilde{C}_2 \|x\|_{\mathbf{d}}^\mu$ and $\exists \tilde{C}_3 > 0 : \left\| B_{\hat{h}} \|x\|_{\mathbf{d}}^\mu \right\| = \left\| \int_0^{h_t} \|x\|_{\mathbf{d}}^\mu e^{A\tau} d\tau B \right\| \leq \tilde{C}_3 \|x\|_{\mathbf{d}}^\mu$ then for any $\tilde{C}_4 > 0$ there exist $C_3 > 0$ such that

$\|\mathbf{d}(-\ln\|x\|_{\mathbf{d}})x - \mathbf{d}(-\ln\|x\|_{\mathbf{d}})(x_k^q + \hat{q}_k)\| \leq C_3\|x\|_{\mathbf{d}}^\mu$ for $\|x\|_{\mathbf{d}}^{-\mu} \geq \tilde{r}_\varepsilon = (\frac{1+\varepsilon}{1-\varepsilon})^{|\mu|}r_\varepsilon$, $\|q_k^i\| \leq \delta_\varepsilon$ and $\|\mathbf{d}(-\ln\|x\|_{\mathbf{d}})\hat{q}_k\| \leq \tilde{C}_4\|x\|_{\mathbf{d}}^\mu$. In this case, by Lemma 7 there exists $C > 0$ and $r > 0$ such that $\|\tilde{u}_{\hat{h}}(x_k^q + \hat{q}_k) - u(x)\| \leq C\|x\|_{\mathbf{d}}^{1+2\mu}$. for $\|x\|_{\mathbf{d}}^{-\mu} \geq \max\{\tilde{r}_\varepsilon, r^{-1}\}$, all $t \in [t_i, t_{i+1})$ and $\|q_k^i\| \leq \delta_\varepsilon$ and $\|\mathbf{d}(-\ln\|x\|_{\mathbf{d}})\hat{q}_k\| \leq \tilde{C}_4\|x\|_{\mathbf{d}}^\mu$.

c) Adding and subtracting $u(x)$ we derive

$$\begin{aligned} \frac{d\|x\|_{\mathbf{d}}}{dt} &= \frac{\|x\|_{\mathbf{d}}x^\top \mathbf{d}^\top (-\ln\|x\|_{\mathbf{d}}) P \mathbf{d} (-\ln\|x\|_{\mathbf{d}}) (Ax + B\tilde{u}_{\hat{h}}(x_k + \hat{q}_k) + q_p)}{x^\top \mathbf{d}^\top (-\ln\|x\|_{\mathbf{d}}) P G_{\mathbf{d}} \mathbf{d} (-\ln\|x\|_{\mathbf{d}}) x} = \\ &= \frac{x^\top \mathbf{d}^\top (-\ln\|x\|_{\mathbf{d}}) P (B(\tilde{u}_{\hat{h}}(x_k + \hat{q}_k) - u(x)) + \|x\|_{\mathbf{d}} \mathbf{d} (-\ln\|x\|_{\mathbf{d}}) q_p)}{x^\top \mathbf{d}^\top (-\ln\|x\|_{\mathbf{d}}) P G_{\mathbf{d}} \mathbf{d} (-\ln\|x\|_{\mathbf{d}}) x} - \rho \|x\|_{\mathbf{d}}^{1+\mu} \\ &\leq \beta \|B(\tilde{u}_{\hat{h}}(x_k + \hat{q}_k) - u(x))\| + \beta \|x\|_{\mathbf{d}} \|\mathbf{d}(-\ln\|x\|_{\mathbf{d}}) q_p\| - \rho \|x\|_{\mathbf{d}}^{1+\mu} \\ &\leq \|x\|_{\mathbf{d}}^{1+\mu} (\beta \|B\| C \|x\|_{\mathbf{d}}^\mu - \rho) + \beta \|x\|_{\mathbf{d}} \|\mathbf{d}(-\ln\|x\|_{\mathbf{d}}) q_p\| \end{aligned}$$

that for $\|x\|_{\mathbf{d}}^{-\mu} \geq r' = \max\{\tilde{r}_\varepsilon, r^{-1}\}$, $t \in [t_i, t_{i+1})$, $\|q_k^i\| \leq \delta_\varepsilon$ and $\|\mathbf{d}(-\ln\|x\|_{\mathbf{d}})\hat{q}_k\| \leq \tilde{C}_4\|x\|_{\mathbf{d}}^\mu$.

d) Let us show that $\|\cdot\|_{\mathbf{d}}$ is an ISS Lyapunov function (close to zero for $\mu > 0$ and close to infinity for $-\beta < \mu < 0$). Let $\sigma(s) = s^\mu \bar{\sigma}^{-1}(s)$, where $\bar{\sigma} \in \mathcal{K}_\infty$ is given in Theorem 1 and $s \geq 0$. For $\|q_p\| \leq 0.25\beta^{-1}\rho\sigma(\|x\|_{\mathbf{d}})$ we derive $\beta\|x\|_{\mathbf{d}}\|\mathbf{d}(-\ln\|x\|_{\mathbf{d}})q_p\| \leq 0.25\rho\|x\|_{\mathbf{d}}^{1+\mu}$. Notice that $\|q_m\| \leq \delta_\varepsilon \bar{\sigma}^{-1}(\|x\|_{\mathbf{d}})$ implies $\|q_k^1\| \leq \delta_\varepsilon$, $\|q_m\| \leq \delta_0\sigma(\|x\|_{\mathbf{d}})$ with $\delta_0 = \tilde{C}_0^{-1} \left(\frac{1-\varepsilon}{1+\varepsilon}\right)^{|\mu|}$ implies $C_0\|q_k^1\| \leq \left(\frac{1-\varepsilon}{1+\varepsilon}\right)^{|\mu|} \|x_k^q\|_{\mathbf{d}}^\mu$ and $\|\mathbf{d}(-\ln\|x\|_{\mathbf{d}})\hat{q}_k\| \leq \|x\|_{\mathbf{d}}^\mu$ for $\|x\|_{\mathbf{d}}^{-\mu} \geq r'$. For a sufficiently small $\delta' > 0$ the inequalities $\|x_k^q\|_{\mathbf{d}}^{-\mu} \geq r_\varepsilon$ (or, equivalently, $\|x\|_{\mathbf{d}}^{-\mu} \geq \tilde{r}_\varepsilon$) and $\|q_p\| \leq \delta'\sigma(\|x\|_{\mathbf{d}})$ imply $\|q_k^2\| \leq \delta_\varepsilon$.

Selecting $\tilde{r} = \max\{r', 0.5\rho(\beta\|B\|C)^{-1}\}$ we derive $\frac{d\|x\|_{\mathbf{d}}}{dt} \leq -0.25\rho\|x\|_{\mathbf{d}}^{1+\mu}$ for $\|x\|_{\mathbf{d}}^{-\mu} \geq \tilde{r}$, $\|q_p\| \leq \tilde{\delta}\sigma(\|x\|_{\mathbf{d}})$, $\|q_m\| \leq \delta_0\sigma(\|x\|_{\mathbf{d}})$ and $\|q_m\| \leq \delta_\varepsilon \bar{\sigma}(\|x\|_{\mathbf{d}})$, where $\tilde{\delta} = \min\{0.25\beta^{-1}\rho, \delta'\}$. The function σ belongs to the class \mathcal{K}_∞ if $\mu > -\beta$. Therefore, the system (37) is practically ISS if $-\beta < \mu < 0$ and locally ISS if $\mu > 0$ even when the conditions of Theorem 5 do not hold.

e) Let us show that the system (37) is practically fixed-time stable and practically ISS for $\mu > 0$. Since $F_{\hat{h}}^n = \mathbf{0}$ (see the proof of Lemma 2) then

$$\begin{aligned} x_1^q &= F_{\hat{h}} x_0^q + L_{\hat{h}} y_1 + \bar{q}_1, & \bar{q}_1 &= \tilde{q}_0 - L_{\hat{h}} A_{\hat{h}}^n \tilde{q}_0, \\ x_2^q &= F_{\hat{h}}^2 x_0^q + F_{\hat{h}} L_{\hat{h}} y_1 + L_{\hat{h}} y_2 + \bar{q}_1, & \bar{q}_2 &= F_{\hat{h}} \bar{q}_1 + \tilde{q}_1 - L_{\hat{h}} A_{\hat{h}}^n \tilde{q}_1, \\ \dots & & \dots & \\ x_n^q &= F_{\hat{h}}^{n-1} L_{\hat{h}} y_1 + \dots + L_{\hat{h}} y_n + \bar{q}_n, & \bar{q}_n &= F_{\hat{h}} \bar{q}_{n-1} + \tilde{q}_{n-1} - L_{\hat{h}} A_{\hat{h}}^n \tilde{q}_{n-1}, \end{aligned}$$

where $y_{i+1} = Q_{n\hat{h}}(\|x_i^q + \hat{q}_i\|_{\mathbf{d}})(x_i^q + \hat{q}_i)$, $i = 0, \dots, n-1$. Since for $\mu > 0$ we have $\|y_{k+i}\| \leq 1$ (see the proof of Lemma 2, case 3) and $\|\bar{q}_i\| \leq C \max_{j=0, \dots, i-1} \|q_j\|$ for some $C > 0$, then the system (37) with $\mu > 0$ is practically fixed-time stable and practically ISS.

f) Let us show that the system (37) is locally ISS for $\mu \geq -1$. For $\|x_k^q + \hat{q}_k\|_{\mathbf{d}} \leq r^-$ we have $x_{k+1}^q = F_{\hat{h}} x_k^q + \tilde{q}_k - L_{\hat{h}} A_{\hat{h}}^n \hat{q}_k$, where $F_{\hat{h}}$ is a Schur stable nilpotent matrix. Since an asymptotically stable linear system is ISS with respect to additive perturbations then the system (37) is locally ISS.

2) Let us show that the system (37) is ISS for $\mu > -\beta$ provided that the unperturbed system is globally asymptotically stable. Our goal is to show a discrete-time system:

$$x_{(p+1)k^*}^q = \Xi(x_{pk^*}^q, q_{pk^*}, \dots, q_{(p+1)k^*-1}), \quad p=0, 1, \dots \quad (49)$$

which describes evolution of (48) with the discrete step k^* , is ISS. The latter would imply ISS of (37). Notice that the local and practical ISS of (37) guarantees the local and practical ISS of the system (49). Let $k^* \geq 1$, V , \bar{r}_* , \bar{r}^* , $\bar{\gamma} \in (0, 1)$, $L = \|\mathbf{d}(-\mu^{-1} \ln r^*)\|$ be defined as in the proof of Theorem 5. Let $x_k \in \mathbb{R}^n$ denote a solution of the non-perturbed system with $x_0 = x_0^q$.

a) Let us show there exists $\omega_{k^*} \in \mathcal{K}_\infty$:

$$\|x_{k^*}^q - x_{k^*}\| \leq \omega_{k^*}(\max\{\|q_0\|, \dots, \|q_{k^*-1}\|\})$$

for $\bar{r}_* \leq \|x_0\|_{\mathbf{d}}^\mu \leq \bar{r}^*$. Since the system (37) is practically ISS then for any $\tilde{\sigma} \in \mathcal{K}_\infty$ there exists a compact set $\tilde{\Omega} \subset \mathbb{R}^n$ such that $x_i^q \in \tilde{\Omega}$ for all $i \in 0, \dots, k^*$ provided that $\bar{r}_* \leq \|x_0\|_{\mathbf{d}}^\mu \leq \bar{r}^*$ and $\max_{j=0, \dots, k^*-1} \|q_j\| \leq \tilde{\sigma}(\|x_0\|_{\mathbf{d}})$. Denoting $\bar{q}_0 = \mathbf{0}$ and $\bar{q}_k = F_h \bar{q}_{k-1} + \tilde{q}_k + L_h(Q_{n\hat{h}}(\|x_{k-1} + \bar{q}_{k-1} + \hat{q}_k\|_{\mathbf{d}})(x_{k-1} + \bar{q}_{k-1} + \hat{q}_k) - Q_{n\hat{h}}(\|x_{k-1}\|_{\mathbf{d}})x_{k-1})$ for $k \geq 1$ we derive $x_k^q = x_k + \bar{q}_k$. Since the function $x \mapsto Q_\tau(\|x\|_{\mathbf{d}})x$ is continuous on \mathbb{R}^n then by Heine-Cantor Theorem it is uniformly continuous on $\tilde{\Omega}$ and there exists $\omega_0 \in \mathcal{K}_\infty$ such that $\|Q_\tau(\|z_1\|_{\mathbf{d}})z_1 - Q_\tau(\|z_2\|_{\mathbf{d}})z_2\| \leq \omega_0(\|z_1 - z_2\|)$ for all $z_1, z_2 \in \tilde{\Omega}$ and

$$\|\bar{q}_1\| \leq \|\tilde{q}_0\| + \|L_h\| \omega_0(\|\hat{q}_0\|).$$

Repeating the above consideration, on k^* -th step, we derive that $\exists \omega_{k^*} \in \mathcal{K}_\infty$: $\|\bar{q}_{k^*}\| \leq \omega_{k^*}(\max_{j=0, \dots, k^*-1} \|q_j\|)$ for $\bar{r}_* \leq \|x_0\|_{\mathbf{d}}^\mu \leq \bar{r}^*$ and $\max_{j=0, \dots, k^*-1} \|q_j\| \leq \tilde{\sigma}(\|x_0\|_{\mathbf{d}})$. Since $V(x_{k^*}^q) = V(x_{k^*}^q) - V(x_k) + V(x_k) \leq L\|\bar{q}_{k^*}\| + \bar{\gamma}V(x_0) \leq \frac{\bar{\gamma}+1}{2}V(x_0^q)$ for $\bar{r}_* \leq \|x_0\|_{\mathbf{d}}^\mu \leq \bar{r}^*$ and $\|\bar{q}_{k^*}\| \leq \frac{1-\bar{\gamma}}{2L}V(x_0)$ then $V(x_{k^*}^q) \leq \frac{\bar{\gamma}+1}{2}V(x_0^q)$ for $\bar{r}_* \leq \|x_0\|_{\mathbf{d}}^\mu \leq \bar{r}^*$ and $\max_{j=0, \dots, k^*-1} \|q_j\| \leq \min\{\tilde{\sigma}(\|x_0\|_{\mathbf{d}}), \omega_{k^*}^{-1}(\frac{1-\bar{\gamma}}{2L}V(x_0))\}$. Taking into account the local and practical ISS proven above, the latter guarantees global ISS of (49) in the view of [22]. The proof is complete.

7.12 The proof of Corollaries 3 and 4

Denote $\delta_i(t) = \sum_{j=i+1}^m A_{ij}x_j(t)$, where $i = 1, \dots, m$ is a number of subsystem in the system (1), (2), (39) and the matrices A_{ij} are defined in the proof of Corollary 2. By Theorem 4, each subsystem with $\delta_i = 0$ is finite-time (for $\mu_i < 0$) or nearly fixed-time (for $\mu_i > 0$) stable. Moreover, it is forward complete⁵ if δ_i is uniformly bounded. **The case $\mu_i < 0$.** Since the m -th subsystem is finite-time stable then $\exists T_m > 0$ such that $\delta_{m-1}(t) = \mathbf{0}$ for all $t \geq T_m$. Considering subsequently the systems $m-1, m-2, \dots, 1$ we conclude that the system (18), (39) is finite-time stable. **The case $\mu_i > 0$.** Since the m -th subsystem is fixed-time stable then d_{m-1} is uniformly bounded and $(m-1)$ -th subsystem practically fixed-time stable (see Theorem 6), but the ISS property guarantees its global uniform asymptotic stability [52]. Using the cascade structure of the system we complete the proof of Corollary 3. The proof of Corollary 4 is literally the same but it uses Theorems 5 and 7 instead of Theorem 4 and 6, respectively.

⁵A system is forward complete if all its solutions are defined globally in the forward time.

References

- [1] V. Acary and B. Brogliato. Implicit euler numerical scheme and chattering-free implementation of sliding mode systems. *Systems & Control Letters*, 59(5):284–293, 2010.
- [2] A. Andreini, A. Bacciotti, and G. Stefani. Global stabilizability of homogeneous vector fields of odd degree. *Systems & Control Letters*, 10:251–256, 1988.
- [3] V. Andrieu, L. Praly, and A. Astolfi. Homogeneous Approximation, Recursive Observer Design, and Output Feedback. *SIAM Journal of Control and Optimization*, 47(4):1814–1850, 2008.
- [4] S. P. Bhat and D. S. Bernstein. Geometric homogeneity with applications to finite-time stability. *Mathematics of Control, Signals and Systems*, 17:101–127, 2005.
- [5] B. Brogliato and A. Polyakov. Digital implementation of sliding-mode control via the implicit method: A tutorial. *International Journal of Robust and Nonlinear Control*, 31:3528–3586, 2021.
- [6] B. Brogliato, A. Polyakov, and D. Efimov. The implicit discretization of the super-twisting sliding-mode control algorithm. *IEEE Transactions on Automatic Control*, 65(8):3707–3713, 2020.
- [7] A. Chaillet, D. Angeli, and H. Ito. Combining iiss and iss with respect to small inputs: the strong iiss property. *IEEE Transactions on Automatic Control*, 59(9):2518–2524, 2014.
- [8] J.-M. Coron, L. Grüne, and K. Worthmann. Model predictive control, cost controllability, and homogeneity. *SIAM Journal on Control and Optimization*, 58(5):2979–2996, 2020.
- [9] J.-M. Coron and L. Praly. Adding an integrator for the stabilization problem. *Systems & Control Letters*, 17(2):89–104, 1991.
- [10] D. Efimov and W. Perruquetti. Oscillations conditions in homogenous systems. In *Proc. IFAC NOLCOS Symp.*, pages 1379–1384, 2010.
- [11] D. Efimov, A. Polyakov, and A. Aleksandrov. Discretization of homogeneous systems using euler method with a state-dependent step. *Automatica*, 109(11):108546, 2019.
- [12] D. Efimov, A. Polyakov, A. Levant, and W. Perruquetti. Realization and discretization of asymptotically stable homogeneous systems. *IEEE Transactions on Automatic Control*, 62(11):5962–5969, 2017.
- [13] G. Folland. Subelliptic estimates and function spaces on nilpotent Lie groups. *Arkiv for Matematik*, 13(1-2):161–207, 1975.

- [14] L. Grüne. Homogeneous state feedback stabilization of homogeneous systems. *SIAM Journal of Control and Optimization*, 38(4):1288–1308, 2000.
- [15] B.C. Hall. *Lie Groups, Lie Algebras, and Representations*. Springer, 2015.
- [16] A. Hanan, A. Jbara, and A. Levant. Low-chattering discretization of sliding mode control. In *the 60th IEEE Conference on Decision and Control*, 2021.
- [17] H. Hermes. Nilpotent approximations of control systems and distributions. *SIAM Journal of Control and Optimization*, 24(4):731, 1986.
- [18] H. Hermes. Homogeneous feedback controls for homogeneous systems. *Systems & Control Letters*, 24:7–11, 1995.
- [19] Y. Hong. H_∞ control, stabilization, and input-output stability of nonlinear systems with homogeneous properties. *Automatica*, 37(7):819–829, 2001.
- [20] O. Huber, V. Acary, and B. Brogliato. Lyapunov stability and performance analysis of the implicit discrete sliding mode control. *IEEE Transactions on Automatic Control*, 61(10):3016–3030, 2016.
- [21] O. Huber, V. Acary, and B. Brogliato. Lyapunov stability analysis of the implicit discrete-time twisting control algorithm. *IEEE Transactions on Automatic Control*, 65(6):2619–2626, 2020.
- [22] Z.-P. Jiang and Y. Wang. Input-to-state stability for discrete-time nonlinear systems. *Automatica*, 37(6):856–869, 2001.
- [23] F. Josse, E. Bernuau, E. Moulay, and P. Coirault. Robustness of sampled-data homogeneous systems. *Automatica*, 123:109345, 2021.
- [24] M. Kawski. Families of dilations and asymptotic stability. *Analysis of Controlled Dynamical Systems*, pages 285–294, 1991.
- [25] V. V. Khomenuk. On systems of ordinary differential equations with generalized homogenous right-hand sides. *Izvestia vuzov. Mathematica (in Russian)*, 3(22):157–164, 1961.
- [26] R. Kikuuwe, S. Yasukouchi, H. Fujimoto, and M. Yamamoto. Proxy-based sliding mode control: A safer extension of pid position control. *IEEE Transactions on Robotics*, 26(4):670–683, 2010.
- [27] S. Koch, M. Reichhartinger, M. Horn, and L. Fridman. Discrete-time implementation of homogeneous differentiators. *IEEE Transactions on Automatic Control*, 65(2):757–762, 2019.
- [28] V.I. Korobov. A solution of the synthesis problem using controlability function. *Doklady Akademii Nauk SSSR*, 248:1051–1063, 1979.
- [29] A. Levant. Homogeneity approach to high-order sliding mode design. *Automatica*, 41(5):823–830, 2005.

- [30] A. Levant. Chattering analysis. *IEEE Transactions on Automatic Control*, 55(6):1380–1389, 2010.
- [31] A. Levant. On fixed and finite time stability in sliding mode control. In *IEEE Conference on Decision and Control*, pages 4260–4265, 2013.
- [32] M. Livne and A. Levant. Proper discretization of homogeneous differentiators. *Automatica*, 50(8):2007–2014, 2014.
- [33] D. Luenberger. Canonical forms for linear multivariable systems. *IEEE Transactions on Automatic Control*, 12(3):290–293, 1967.
- [34] L. Michel, M. Chanes, F. Plestan, J. Aoustin, and J.-P. Barbot. A noise less-sensing semi-implicit discretization of a homogeneous differentiator : principle and application. In *European Control Conference (ECC)*, 2021.
- [35] H. Nakamura. Positive definiteness of generalized homogeneous functions. In *9th Symposium on Nonlinear Control Systems, Toulouse, France,,* pages 552–557, 4-6 September 2013.
- [36] H. Nakamura, Y. Yamashita, and H. Nishitani. Smooth Lyapunov functions for homogeneous differential inclusions. In *Proceedings of the 41st SICE Annual Conference*, pages 1974–1979, 2002.
- [37] N. Nakamura, H. Nakamura, and Y. Yamashita. Homogeneous stabilization for input-affine homogeneous systems. In *Conference on Decision and Control*, pages 80–85, 2007.
- [38] A. Nekhoroshikh, D. Efimov, A. Polyakov, W. Perruquetti, and I. Furtat. Finite-time stabilization under state constraints. In *Conference on Decision and Control*, 2021.
- [39] Y. Orlov. Finite time stability and robust control synthesis of uncertain switched systems. *SIAM Journal of Control and Optimization*, 43(4):1253–1271, 2005.
- [40] W. Perruquetti, T. Floquet, and E. Moulay. Finite-time observers: application to secure communication. *IEEE Transactions on Automatic Control*, 53(1):356–360, 2008.
- [41] A. Polyakov. Sliding mode control design using canonical homogeneous norm. *International Journal of Robust and Nonlinear Control*, 29(3):682–701, 2018.
- [42] A. Polyakov. *Generalized Homogeneity in Systems and Control*. Springer, 2020.
- [43] A. Polyakov, D. Efimov, and B. Brogliato. Consistent discretization of finite-time and fixed-time stable systems. *SIAM Journal of Control and Optimization*, 57(1):78–103, 2019.

- [44] A. Polyakov, D. Efimov, and W. Perruquetti. Finite-time and fixed-time stabilization: Implicit Lyapunov function approach. *Automatica*, 51(1):332–340, 2015.
- [45] A. Polyakov, D. Efimov, and W. Perruquetti. Robust stabilization of MIMO systems in finite/fixed time. *International Journal of Robust and Nonlinear Control*, 26(1):69–90, 2016.
- [46] A. Polyakov, D. Efimov, and X. Ping. Consistent discretization of a homogeneous finite-time control for a double integrator. In *IEEE Conference on Decision and Control*, 2022 (submitted).
- [47] L. Praly. Generalized weighted homogeneity and state dependent time scale for linear controllable systems. In *Proc. IEEE Conference on Decision and Control*, pages 4342–4347, San Diego, USA, 1997.
- [48] L. Rosier. Homogeneous Lyapunov function for homogeneous continuous vector field. *Systems & Control Letters*, 19:467–473, 1992.
- [49] T. Sanchez, A. Polyakov, and D. Efimov. Lyapunov-based consistent discretisation of stable homogeneous systems. *International Journal of Robust and Nonlinear Control*, 31(9):3587–3605, 2021.
- [50] R. Sepulchre and D. Aeyels. Homogeneous Lyapunov Functions and Necessary Conditions for Stabilization. *Mathematics of Control, Signals and Systems*, 9:34–58, 1996.
- [51] E.D. Sontag. Smooth stabilization implies coprime factorization. *IEEE Transactions on Automatic Control*, 34:435–443, 1989.
- [52] E.D. Sontag and A. Teel. Changing supply functions in input-state stable systems. *IEEE Transaction on Automatic Control*, 40(8):1476–1478, 1995.
- [53] E.D. Sontag and Y. Wang. On characterizations of the input-to-state stability property. *Systems & Control Letters*, 24(5):351–359, 1996.
- [54] K. Zimenko, D. Efimov, A. Polyakov, and W. Perruquetti. A note on delay robustness for homogeneous systems with negative degree. *Automatica*, 79(5):178–184, 2017.
- [55] K. Zimenko, A. Polyakov, D. Efimov, and W. Perruquetti. Robust feedback stabilization of linear mimo systems using generalized homogenization. *IEEE Transactions on Automatic Control*, 2020.
- [56] V. I. Zubov. *Methods of A.M. Lyapunov and Their Applications*. Noordhoff, Leiden (Translated from Russian: V.I. Zubov, Metody Lyapunova i ih primeneniye, Leningrad: LGU, 1957), 1964.
- [57] V.I. Zubov. On systems of ordinary differential equations with generalized homogenous right-hand sides. *Izvestia vuzov. Mathematica (in Russian)*, 1:80–88, 1958.