
FunQG: Molecular Representation Learning Via Quotient Graphs

Hossein Hajiabolhassan^{*,†,§}, Zahra Taheri^{†,§}, Ali Hojatinia^{‡,§}, Yavar Taheri Yeganeh^{‡,§}

July 19, 2022

ABSTRACT

Learning expressive molecular representations is crucial to facilitate the accurate prediction of molecular properties. Despite the significant advancement of graph neural networks (GNNs) in molecular representation learning, they generally face limitations such as neighbors-explosion, under-reaching, over-smoothing, and over-squashing. Also, GNNs usually have high computational complexity because of the large-scale number of parameters. Typically, such limitations emerge or increase when facing relatively large-size graphs or using a deeper GNN model architecture. An idea to overcome these problems is to simplify a molecular graph into a small, rich, and informative one, which is more efficient and less challenging to train GNNs. To this end, we propose a novel molecular graph coarsening framework named **FunQG** utilizing **F**unctional groups, as influential building blocks of a molecule to determine its properties, based on a graph-theoretic concept called **Q**uotient **G**raph. By experiments, we show that the resulting informative graphs are much smaller than the molecular graphs and thus are good candidates for training GNNs. We apply the FunQG on popular molecular property prediction benchmarks and then compare the performance of a GNN architecture on the obtained datasets with several state-of-the-art baselines on the original datasets. By experiments, this method significantly outperforms previous baselines on various datasets, besides its dramatic reduction in the number of parameters and low computational complexity. Therefore, the FunQG can be used as a simple, cost-effective, and robust method for solving the molecular representation learning problem.

Keywords Deep learning; Molecular representation; Molecular property; Graph neural network; Quotient graph; Functional group

1 Introduction

Drug discovery and development are often fraught with problems such as high costs and time-consuming processes, e.g., the production of a drug by traditional methods costs an average of 2.6 billion USD and can take more than 12 years [8]. Innovative approaches are essential to reduce the cost and accelerate the accurate development of a new drug. Computational methods can improve the drug discovery process due to their rapid and accurate prediction. The field of quantitative structure-activity relationship (QSAR) modeling was founded as a powerful computational approach to screen large libraries of molecules with desired properties [9]. Artificial intelligence based methods are a kind of solution to the current problems of drug development, especially in predicting molecular properties [60], drug-drug interaction [49], and drug-target interaction [1]. The performance of these methods relies heavily on finding the expressive representations of molecular structures [66]. In the early works, molecular representations are based on fixed expert-designed molecular descriptors or fingerprints, such as Dragon descriptors or Morgan (ECFP) fingerprints [39, 47]. On the other hand, domain-specific expertise is used to select or engineer molecular descriptors and improve the performance of previous approaches [7, 13, 41].

* Corresponding author: Department of Mathematics and Information Technology, Chair of Information Technology, Montanuniversität Leoben, Franz-Josef-Strasse 18, A-8700 Leoben, Austria. E-mail: hossein.hajiabolhassan@unileoben.ac.at

§ Machine Learning and Graph Mining Lab, Department of Applied Mathematics, Faculty of Mathematical Sciences, Shahid Beheshti University, 19839-69411, Tehran, Iran.

†,‡ These two authors have contributed equally to this work and their names are listed alphabetically.

One of the most significant advances in QSAR analysis has come from utilizing deep learning. The highly flexible architecture of neural networks enables them to adapt to various problems and achieve remarkable gains by extracting complex relationships. Instead of relying on features compiled by an expert, neural models can learn expressive representations directly from raw data [10, 14, 25].

Graph neural networks (GNNs), which have been developed as a powerful candidate for graph-structured data modeling [19, 40, 51], are among the hottest topics in recent years [14, 22, 65]. A molecule can be represented naturally as a graph wherein atoms (nodes) connect by chemical bonds (edges). It has been shown in numerous studies that graph-based molecular property prediction can be more accurate than traditional descriptor-based methods [10, 14, 18, 25, 64]. On the other hand, some other studies have shown that utilizing only computed descriptors achieved better results than graph-based models [24]. Therefore, each has its own benefits [66]. Accordingly, some works that have followed a hybrid approach, incorporating easily computed descriptors with a graph-based model, have shown promising performance in drug discovery over non-neural models [57, 66].

The key idea of GNN and its variants is the use of a neural message passing process, in which message vectors of the nodes' neighbors (or edges' neighbors) are aggregated through neural networks to update node (and/or edge) representations [18, 26, 59, 66]. Therefore, a GNN layer combines the independent information of each node (and/or edge) with the structural information obtained from its neighbors. However, most learning problems require multiple GNN layers to exchange information between nodes (and/or edges) that are not directly connected.

Although existing GNN architectures have made good progress in various fields, such as drug discovery, they also face limitations that need further investigation. Some of such limitations are common problems observed in neural networks, such as overfitting due to a large number of GNNs parameters as well as the small size of datasets, which is a significant problem in drug discovery. Others are structural limitations specific to graphs that typically emerge when the scale of the graph increases or the GNN model architecture goes deeper. The process of recursive aggregation of neighborhoods in GNNs causes the explosion of the number of neighbors and thus leads to exponentially-growing computation complexity due to the use of multiple GNN layers. This problem which is described as *neighbors-explosion* results in serious memory and computation bottlenecks, especially in working with large-size graphs [3]. On the other hand, if the number of GNN layers is less than the diameter of the graph, then nodes that are farther away than the number of GNN layers are unable to receive information from each other [4]. Alon et al. [2] refer to this limitation as *under-reaching*. Another limitation is due to the *over-smoothing* phenomenon, in which the node representations become almost indistinguishable by increasing the number of GNN layers [29, 43, 62]. However, over-smoothing is more common in short-range problems, such as prediction tasks on social networks [28], citation networks [53], and product recommendations [54]. The efficiency in such cases usually depends only on short-range information from each node's local neighborhood and does not improve by adding distant information. In contrast, *over-squashing* of information from exponentially many neighbors into fixed-size vectors is a performance bottleneck in tasks that require long-range interaction and so more number of GNN layers [2], such as molecular property prediction tasks, which may depend on the combination of atoms that reside in the molecule's opposite sides [38]. To avoid under-reaching, the number of GNN layers should be as many as the range of interactions. But as the depth of GNNs increases, the neighbors-explosion, over-smoothing, and over-squashing become more likely. Using GNNs whose number of layers was more than the diameter of the graphs, experimentally on chemical property prediction tasks, Alon et al. [2] show that over-squashing is the cause of the poor performance of such neural networks, not under-reaching.

There are several ways to approach improving the performance of GNNs in molecular property prediction tasks. Common strategies include proposing a new GNN variant, self-supervised pre-training, and pre-processing raw input data. Each of such approaches has its advantages and disadvantages. For example, despite acceptable performances of self-supervised pre-training methods [16, 30, 36, 48], these methods have high computational costs and require rich hardware resources. The main focus of this paper is proposing a specific type of pre-processing method for molecular data that not only focuses on solving the above issues of GNNs in property prediction tasks but also reduces computational costs. In order to achieve this goal, an idea is to simplify the graphs in such a way that by using fewer GNN layers to the resulting small graphs, not only memory and computational costs are reduced but also significant performances are achieved. Typical approaches for simplifying graphs can be divided into two major categories. In the first category, graph edge *sparsification methods* approximate a graph to a sparse graph by reducing the number of edges [45, 55, 56]. In the second category, graph *coarsening methods* reduce the number of nodes to a subset of the original node set [5, 6, 33, 34]. In this paper, we propose a novel molecular graph coarsening method, which reduces the number of nodes by contracting nodes in certain subgraphs. Such subgraphs are obtained from a partition of the molecular graph. Our approach is based on a concept of graph theory called *quotient graph* (see Definition 1), and the resulting coarsened graph is named *molecular quotient graph*.

Although there are various methods for graph coarsening, most are not data-driven or even domain-specific [6]. Also, the purpose of most existing graph coarsening algorithms is to maintain some graph properties such as principal




Figure 1: The overview of FunQG framework. The left figure (A) illustrates the application of the FunQG framework to a molecule to find its corresponding coarsened graph, named molecular quotient graph. The right figure (B) shows the application of a GNN architecture to the graph obtained from the FunQG to predict the property of the molecule.

eigenvalues [33], which may be suboptimal. The main focus of this paper is to propose a coarsening method specific to molecular graphs. Specifically, we aim to miniaturize the molecular graph into a rich and informative one such that GNNs with fewer layers trained on the resulting small graphs have great efficiency and even better performance than GNNs with more layers trained on the molecular graphs.

Since the process of constructing quotient graphs is prone to information loss, selecting appropriate graph partitions is crucial to maintaining information in the resulting quotient graphs. Different methods can be considered to partition the node set of a molecular graph. But based on our experiments, we have decided to use the domain knowledge of chemistry for this case. On the other hand, unlike a molecule, a graph is a 2-dimensional structure with no spatial relationship between its elements. Yet, some 3-dimensional information of a molecule and the information resulting from its 3-dimensional structure, such as stereochemistry, can be encoded in its feature vectors of the nodes and edges [12]. In this paper, to produce an expressive molecular representation and avoid data loss, information in feature vectors of the nodes and edges of a molecular graph are maintained in the feature vectors of the nodes and edges of its molecular quotient graph by an appropriate local aggregation method.

It is known that a molecule may consist of many atomic groups, while certain atomic groups, called *functional groups* (FGs), determine the properties and reactivity of the parent molecule [15, 42]. Despite the importance of FGs in predicting molecular properties, most existing GNN models completely ignore them. Various substructure features are often used in cheminformatics to predict molecules' biological activity or properties. These features are usually

generated based on fragments or local properties of atoms and bonds. In general, the fragments are strongly overlapping and are generated for all parts of a molecule without considering their potential chemical role [15]. Therefore, these features do not describe functional groups. In this paper, we propose a framework for the molecular graph coarsening, named *FunQG*, which firstly partitions the molecular graph’s nodes based on functional groups and then contracts the nodes of each partition in such a way that information is preserved in the new nodes and edges. This pre-processing method is independent of GNN architectures. Therefore, we can apply each of the different GNN model architectures to the resulting graphs and then compare its efficiency with the efficiency of the GNN applied on the main molecular graphs. By our experiments, the resulting informative molecular quotient graphs are much smaller than the molecular graphs (see Supplementary Section 4). Because many of the problems of GNNs are rooted in working with relatively large-size graphs, the resulting small molecular quotient graphs are good candidates to be used more efficiently and with fewer challenges for training various GNN architectures. As far as we know, this molecular graph coarsening framework is the first approach that uses information about functional groups to find more expressive molecular representations for predicting molecular properties by deep learning. The experimental results on 9 molecular property prediction benchmarks using the FunQG graph coarsening framework and the DMPNN model architecture [66], named *FunQG-DMPNN*, indicate the effectiveness of the proposed framework on different molecular datasets and show that the FunQG-DMPNN advances the state-of-the-art performances on multiple drug discovery tasks. In summary, FunQG is ready to be used as a powerful and cost-effective framework to overcome the problems of molecular representation learning.

2 Materials and Methods

2.1 Preliminaries

Throughout this paper, suppose that graphs are finite, undirected (or equivalently, directed in which the reverse of every edge is also an edge), and simple (loopless with no parallel edges). Also, if G is a graph, then the node set of G is denoted by $V(G)$, and its edge set is denoted by $E(G)$. If two nodes v and w are adjacent in G , then it is denoted by $vw \in E(G)$ (or equivalently by $(v, w) \in E(G)$ as a directed edge from v to w). Furthermore, the set of neighbors of a node v is denoted by $N(v)$.

A molecule \mathcal{M} can be represented as a graph $G_{\mathcal{M}}$ wherein every node v is corresponding to an atom v in \mathcal{M} , and for all $v, w \in V(G_{\mathcal{M}})$, $vw \in E(G_{\mathcal{M}})$ if and only if there exists a chemical bond between atoms v and w in \mathcal{M} . The initial features of a node v is denoted by \mathbf{x}_v , and the initial features of an edge (v, w) is denoted by \mathbf{e}_{vw} . For initial feature extraction, we follow the same protocol as Wu et al. [63] and Yang et al. [66]. The detailed feature extraction process and initial atom and bond features can be found in the Supplementary Section 3. In graph based molecular property prediction tasks, the goal is to predict the property y of the molecule \mathcal{M} according to the embedding $e_{\mathcal{M}}$ of the graph $G_{\mathcal{M}}$.

2.1.1 Message Passing Neural Networks

Graph neural networks (GNNs) have been developed as a powerful candidate to learn representations of graph data, e.g., molecular structures. *Message passing neural networks* utilize the notion of messages in GNNs. Considering the node and edge features along with the graph structure as inputs, such a GNN uses a neural message passing process to learn the representation vector of the nodes. More precisely, in the message passing phase, the independent information of each node v with the structural information of its neighbors are combined iteratively to obtain a representation vector h_v of the node. Then in the readout phase, the representation vector h_G of the graph is obtained by pooling over the final representation vectors of its nodes to make predictions about the properties of interest.

MPNN. An *MPNN* [18] operates on an undirected graph G . On each step $t \in \{0, 1, \dots, T-1\}$ of the message passing phase, for all nodes v , the hidden states h_v^t and the messages m_v^t are updated as follows

$$m_v^{t+1} = \sum_{w \in N(v)} M_t(h_v^t, h_w^t, e_{vw}),$$

$$h_v^{t+1} = U_t(h_v^t, m_v^{t+1}),$$

where M_t , U_t , and h_v^0 are respectively a message function, a vertex update function, and a function of the initial node features \mathbf{x}_v . Afterwards, in the readout phase, a readout function R is used to predict the property $\hat{y} = R(\{h_v^T | v \in V(G)\})$.

Directed MPNN. Unlike MPNN, in *Directed MPNN (DMPNN)* [11, 66] messages are propagated via directed edges in a way that prevents *totters* [37], i. e., messages passed along a path of the form $v_1 v_2 \dots v_n$ where $v_i = v_{i+2}$ for some i ,




Figure 2: G/\mathcal{P} is the quotient graph of G under the equivalence relation specified by the partition $\mathcal{P} = \{V_1, V_2, V_3\}$ of $V(G)$, where $V(G) = \{1, 2, \dots, 6\}$, $V_1 = \{3, 4, 5\}$, $V_2 = \{1, 6\}$, and $V_3 = \{2\}$.

because such paths are likely to introduce noise to the graph representation. This is achieved by updating messages m_{vw} of the directed edge (v, w) using all hidden states of the incoming edges h_{kv} , where $k \in N(v) \setminus w$.

The learnable parameters of the DMPNN [66] are the weight matrices $W_i \in \mathbb{R}^{h \times (n_i + e_i)}$, $W_m \in \mathbb{R}^{h \times h}$, and $W_o \in \mathbb{R}^{h \times (h + n_i)}$, where n_i is the initial node features size, e_i is the initial edge features size, and h is called the *hidden size*. In the message passing phase, the hidden states of an edge (v, w) is initialized as

$$h_{vw}^0 = \tau(W_i \text{cat}(\mathbf{x}_v, \mathbf{e}_{vw})),$$

where $\text{cat}(\mathbf{x}_v, \mathbf{e}_{vw}) \in \mathbb{R}^{(n_i + e_i)}$ is the concatenation of the initial node features \mathbf{x}_v and the initial edge features \mathbf{e}_{vw} , and τ is the *ReLU* activation function. Then on each step $t \in \{0, 1, \dots, T - 1\}$ of the message passing phase, for all directed edges (v, w) , the hidden states h_{vw}^t and the messages m_{vw}^t are updated as follows

$$m_{vw}^{t+1} = \sum_{k \in N(v) \setminus w} h_{kv}^t, \quad (1)$$

$$h_{vw}^{t+1} = \tau(h_{vw}^0 + W_m m_{vw}^{t+1}). \quad (2)$$

Afterwards, node representations h_v can be obtained by summing up all the incoming edge representations, as follows

$$m_v = \sum_{w \in N(v)} h_{vw}^T, \quad (3)$$

$$h_v = \tau(W_o \text{cat}(\mathbf{x}_v, m_v)). \quad (4)$$

Then, in the readout phase, a representation h_G of the graph is obtained by summing or averaging the node representations. Finally, a feed-forward neural network f is used to generate property predictions $\hat{y} = f(h_G)$.

2.1.2 Quotient Graphs

Definition 1 [20] *The quotient graph G/\mathcal{P} of a graph G under the equivalence relation specified by the partition set $\mathcal{P} = \{V_1, V_2, \dots, V_k\}$ of $V(G)$ is a graph with the node set $V(G/\mathcal{P}) = \mathcal{P}$, such that for all distinct $i, j \in \{1, 2, \dots, k\}$, $V_i V_j \in E(G/\mathcal{P})$ if and only if there exists $(v, v') \in (V_i, V_j)$ such that $vv' \in E(G)$. Each node V_i of G/\mathcal{P} is called a contracted node from the set of nodes V_i of G . Also, each edge $V_i V_j$ of G/\mathcal{P} is called a contracted edge from the set of edges $\{vv' \in E(G) : (v, v') \in (V_i, V_j)\}$.*

Figure 2 gives an example for Definition 1.

2.2 The FunQG Framework

It is known that functional groups (FGs) are sets of connected atoms that determine the properties and reactivity of the parent molecule [15]. So, the physical and chemical properties of compounds that contain a particular functional group tend to be similar [23]. Therefore by most theoretical studies, FGs are considered as keys to hierarchically classifying molecules [17]. However, most existing machine learning models which are based on cheminformatics have paid no attention to FGs.

Let \mathcal{M} be a molecule and $G_{\mathcal{M}}$ be its corresponding molecular graph. In this paper, a molecular graph coarsening framework, named **FunQG**, is proposed. This framework firstly constructs a partition set \mathcal{P} of the node set $V(G_{\mathcal{M}})$




Figure 3: Over-squashing bottleneck of graph neural networks [2]

based on **functional groups** of \mathcal{M} , and then considers the **quotient graph** of $G_{\mathcal{M}}$ under the equivalence relation specified by \mathcal{P} as the molecular quotient graph of G . To avoid loss of information, the FunQG aggregates node and edge features of the original graph in their corresponding new nodes and edges, respectively, of the quotient graph.

There are slightly different definitions for FGs by medicinal chemists. Also, extracting functional groups from molecules may have high computational costs. Here, we utilize a relatively simple algorithm presented by Ertl [15] to identify all functional groups in organic molecules. This algorithm enables us to analyze FGs in large chemical databases very quickly and with low computational costs, which was not possible using other approaches. In this work, we utilize an open-source Python version of this algorithm [21].

2.2.1 FunQG and Molecular Quotient Graphs

Let \mathcal{M} be a molecule and $G_{\mathcal{M}}$ be its molecular graph. Suppose that there exist m functional groups in \mathcal{M} , and $\mathcal{FG} = \{S_1, S_2, \dots, S_m\}$ is the set of all subgraphs of $G_{\mathcal{M}}$ induced by functional groups of \mathcal{M} , i. e., for every functional group \mathcal{G} of \mathcal{M} with corresponding atom set $A_{\mathcal{G}}$, there exists a unique $i \in \{1, 2, \dots, m\}$ such that the molecular subgraph induced by $A_{\mathcal{G}}$ is S_i . Then, the steps for applying the FunQG framework to \mathcal{M} are as follows:

1. Find $E_{cut} \subseteq E(G_{\mathcal{M}})$ such that $vw \in E_{cut}$ if and only if there exists an $i \in \{1, 2, \dots, m\}$ such that either v or w is a node in S_i .
2. Let G_{cut} be the subgraph of $G_{\mathcal{M}}$ obtained from deletion of E_{cut} from $E(G_{\mathcal{M}})$. Let $\{G_1, G_2, \dots, G_c\}$ be the set of all connected components of G_{cut} . Consider $\{V(G_1), V(G_2), \dots, V(G_c)\}$ as the partition set \mathcal{P} of $V(G_{\mathcal{M}})$.
3. Let f be an aggregation function, e.g., sum, mean, etc. Find the quotient graph $G_{\mathcal{M}}/\mathcal{P}$ of the graph $G_{\mathcal{M}}$ under the equivalence relation specified by the partition set \mathcal{P} of $V(G_{\mathcal{M}})$, such that the node features of each contracted node $V(G_i)$ in $G_{\mathcal{M}}/\mathcal{P}$ is equal to the output of f on the set of all node features of $V(G_i)$ in $G_{\mathcal{M}}$. Also, the edge features of each contracted edge $V(G_i)V(G_j) \in E(G_{\mathcal{M}}/\mathcal{P})$ is equal to the output of f on the set of all edge features of $\{vv' \in E_{cut} | (v, v') \in (V(G_i), V(G_j))\}$. The graph $G_{\mathcal{M}}/\mathcal{P}$ with the above properties is named the molecular quotient graph of \mathcal{M} .

2.2.2 Details About The FunQG

The following facts are true about the FunQG framework:

1. By the definition of FGs in the Ertl's algorithm [15], two different FGs in a molecule have no atoms in common. Therefore, in the first step of the FunQG, if v is a node in S_i , then there exists no $j \in \{1, 2, \dots, m\} \setminus \{i\}$ such that v is a node in S_j .
2. By the definition of FGs in the Ertl's algorithm, for all $i \in \{1, 2, \dots, m\}$, S_i is a connected subgraph of $G_{\mathcal{M}}$.
3. By items 1 and 2, $\mathcal{FG} \subseteq \{G_1, G_2, \dots, G_c\}$, and so $\mathcal{P}_{\mathcal{FG}} = \{V(S_1), V(S_2), \dots, V(S_m)\} \subseteq \mathcal{P}$. So, we have $\mathcal{P} = \mathcal{P}_{\mathcal{FG}} \cup \mathcal{P}_{\text{non-}\mathcal{FG}}$, where $\mathcal{P}_{\text{non-}\mathcal{FG}} = \mathcal{P} \setminus \mathcal{P}_{\mathcal{FG}}$. Let $V(\mathcal{FG}) = \cup_{i \in \{1, 2, \dots, m\}} V(S_i)$ and $V(\text{non-}\mathcal{FG}) = V(G_{\mathcal{M}}) \setminus V(\mathcal{FG})$. By the definition of FGs in the Ertl's algorithm, each node in $V(\text{non-}\mathcal{FG})$ corresponds to a carbon atom.
4. By item 3, since $\mathcal{P} = \mathcal{P}_{\mathcal{FG}} \cup \mathcal{P}_{\text{non-}\mathcal{FG}}$, the third step of the FunQG can be decomposed into two consecutive steps as follows:




Figure 4: Application of the FunQG to the molecule \mathcal{M} with the SMILES string Cc1cc(N)c2ccccc2[n+]1CCCCCCCCC[n+]1c(C)cc(N)c2ccccc21 from the Tox21 dataset results in the molecular quotient graph $G_{\mathcal{M}}/\mathcal{P}$.

- (a) *Quotient by non-FGs:* An aggregation function f_1 is considered and the third step of the FunQG is executed for f_1 and the partition set $\mathcal{P}' = \mathcal{P}_{\text{non-FG}} \cup \{\{v\} | v \in V(\mathcal{FG})\}$, to find the quotient graph $G_{\mathcal{M}}/\mathcal{P}'$ of $G_{\mathcal{M}}$.
 - (b) *Quotient by FGs:* An aggregation function f_2 is considered and the third step of the FunQG is executed for f_2 and the partition set $\mathcal{P}'' = \mathcal{P}_{\mathcal{FG}} \cup \{\{v\} | v \in V(G_{\mathcal{M}}/\mathcal{P}') \setminus V(\mathcal{FG})\}$ to find the quotient graph $(G_{\mathcal{M}}/\mathcal{P}')/\mathcal{P}''$ of $G_{\mathcal{M}}/\mathcal{P}'$, where by $V(\mathcal{FG})$ here we mean the nodes of $G_{\mathcal{M}}/\mathcal{P}'$ corresponding to the nodes in $V(\mathcal{FG})$. Note that the quotient graph $(G_{\mathcal{M}}/\mathcal{P}')/\mathcal{P}''$ is equal to the quotient graph $G_{\mathcal{M}}/\mathcal{P}$ of $G_{\mathcal{M}}$.
5. By item 4, the aggregation function f_1 may be different from the aggregation function f_2 . In this paper, we utilize the mean aggregation function as f_1 (because by item 3, all nodes in $V(\text{non-FG})$ correspond to carbon atoms) and the sum aggregation function as f_2 . However, some of our experiments considering other combinations of the mean and sum aggregators provided relatively similar results.
 6. By our experiments on multiple molecular property prediction benchmarks from the MoleculeNet [63], on average, the resulting molecular quotient graphs are much smaller than the molecular graphs. For a molecular dataset, let the *abstraction ratio* be the total number of nodes in molecular quotient graphs divided by the total number of nodes in molecular graphs. It can be seen that for each dataset of our experiment, the abstraction ratio is at most 0.38. In Section 3, we see that applying the FunQG framework to molecular property prediction benchmarks not only reduces the required memory and computational costs of GNNs but also achieves significant performance. More details about the size of the molecular graphs, the size of the molecular quotient graphs, and functional groups of the datasets can be found in the Supplementary Section 4.

Figures 1 and 4 give two illustrative examples for the FunQG framework. In these two figures, edges in E_{cut} are drawn in red.

Alon et al. [2] show that over-squashing of information from exponentially many neighbors into fixed-size vectors is a performance bottleneck in tasks that require long-range interaction and so more number of GNN layers, such as molecular property prediction tasks, which may depend on the combination of atoms that reside in the molecule’s opposite sides (Figure 3). The molecular graph $G_{\mathcal{M}}$ in Figure 4 is an example of a graph that may suffer the over-squashing issue during a message passing process. Figure 4 is a good example to show how using the FunQG for graph coarsening can alleviate the over-squashing issue of GNNs.

3 Results

To evaluate the performance of the FunQG, we apply it on multiple molecular property prediction benchmarks and then compare the performance of a GNN model architecture on the obtained datasets with several state-of-the-art baselines on the original datasets. To show the capability of our proposed framework and maintain the simplicity of the method to

reduce computational costs, we utilize the DMPNN architecture as a simple GNN baseline for predicting molecular properties, which needs no attention layers or pre-training. Other GNN variants can also be considered in conjunction with the FunQG in a similar manner. We denote this combination of the FunQG and the DMPNN by FunQG-DMPNN.

3.1 Datasets and Splitting Method

We conduct experiments on 9 popular benchmark datasets from MoleculeNet, including both classification and regression tasks [63]. More details about the datasets can be found in the Supplementary Section 1.

Although *scaffold splitting* is more challenging than *random splitting*, using it for molecular property prediction tasks can better evaluate out-of-distribution generalisation abilities of the models [63]. Following the previous works, e.g., [30, 48], we perform three independent executions on three randomly seeded scaffold splittings with the ratio of 80:10:10 for the training/validation/test sets, and then report the means and standard deviations of the evaluation metrics. More details about this splitting method can be found in the Supplementary Section 2.

3.2 Baselines

We compare the performance of the proposed method with various popular baselines. Among these baselines, ECFP [47] and TF_Robust [46] are non-graph models taking the molecular fingerprints as inputs. But, GraphConv [26], Weave [25], SchNet [52], MPNN [18], DMPNN [66], MGCN [35], AttentiveFP [64] and TrimNet [31] are GNN-based models. More specifically, GraphConv, Weave and SchNet are graph convolutional models, while MPNN, DMPNN, MGCN, AttentiveFP and TrimNet are GNN models considering the edge features during message passing. Furthermore, AttentiveFP and TrimNet are variants of the graph attention networks. The performances of the baselines are taken from GROVER [48] and MPG [30].

3.3 Evaluation Metrics

Following the evaluation metrics suggested by the MoleculeNet [63] and used by the baselines, in this paper, all classification models are evaluated by *ROC-AUC* (area under the receiver operating characteristic curve), and regression models are evaluated by *RMSE* (root-mean-square error).

3.4 Experiments Settings

3.4.1 GNN Architecture

In our experiments, firstly, we apply the FunQG to a molecular dataset. Then, we use the DMPNN as a GNN architecture on the obtained dataset to evaluate the performance of the proposed graph coarsening framework. In details, we use the aggregation and update steps defined in equations (1), (2), (3) and (4). Also, ReLU is utilized as the activation function τ . In the readout phase, we use average pooling to obtain the graphs representations. Then, a feed-forward neural network with two hidden layers and the activation function ReLU is utilized to generate property predictions.

3.4.2 Training and Hyperparameters Details

We utilize the gradient descent and back-propagation algorithms by PyTorch [44] and DGL [61] libraries to implement the models. Specifically, we use the *Adam* optimizer to update the parameters in both training and hyperparameter tuning procedures. Also, we utilize three regularization techniques, including dropout, early stopping, and max-norm to prevent overfitting issues. More details about the training are deferred to the Supplementary Section 5.

The resulting graphs of the FunQG are much smaller than the molecular graphs (Supplementary Section 4). Therefore, a GNN model architecture requires much less depth in working with resulting graphs compared to working with molecular graphs. Thus, using FunQG reduces the computational complexity compared to working with molecular graphs. We utilize one *Intel (R) Xeon (R) E5-2699 v4 @ 2.20GHz* CPU for training, testing, and hyperparameter tuning of the FunQG-DMPNN on each dataset in a relatively short time. For all tasks, Figure 5 compares the total number of parameters of the best models of the FunQG-DMPNN and the DMPNN. Information about the models of the DMPNN are taken from [58].

We perform *Bayesian optimization* using the Ray Tune [32] Python package to find the optimal hyperparameters for the FunQG-DMPNN. More details about the hyperparameters optimization process can be found in the Supplementary Section 5.

Table 1: Performance comparison on 9 benchmarks

	Classification (higher is better)						Regression (lower is better)		
	Tox21 7831	ToxCast 8576	ClinTox 1478	SIDER 1427	BBBP 2039	BACE 1513	FreeSolv 642	ESOL 1128	Lipophilicity 4200
ECFP [47]	0.760(0.009)	0.615(0.017)	0.673(0.031)	0.630(0.019)	0.783(0.050)	0.861(0.024)	5.275(0.751)	2.359(0.454)	1.188(0.061)
TF_Robust [46]	0.698(0.012)	0.585(0.031)	0.765(0.085)	0.607(0.033)	0.860(0.087)	0.824(0.022)	4.122(0.085)	1.722(0.038)	0.909(0.060)
GraphConv [26]	0.772(0.041)	0.650(0.025)	0.845(0.051)	0.593(0.035)	0.877(0.036)	0.854(0.011)	2.900(0.135)	1.068(0.050)	0.712(0.049)
Weave [25]	0.741(0.044)	0.678(0.024)	0.823(0.023)	0.543(0.034)	0.837(0.065)	0.791(0.008)	2.398(0.250)	1.158(0.055)	0.813(0.042)
SchNet [52]	0.767(0.025)	0.679(0.021)	0.717(0.042)	0.545(0.038)	0.847(0.024)	0.750(0.033)	3.215(0.755)	1.045(0.064)	0.909(0.098)
MPNN [18]	0.808(0.024)	0.691(0.013)	0.879(0.054)	0.595(0.030)	0.913(0.041)	0.815(0.044)	2.185(0.952)	1.167(0.430)	0.672(0.051)
DMPNN [66]	0.826(0.023)	0.718(0.011)	0.897(0.040)	0.632(0.023)	0.919(0.030)	0.852(0.053)	2.177(0.914)	0.980(0.258)	0.653(0.046)
MGCN [35]	0.707(0.016)	0.663(0.009)	0.634(0.042)	0.552(0.018)	0.850(0.064)	0.734(0.030)	3.349(0.097)	1.266(0.147)	1.113(0.041)
AttentiveFP [64]	0.807(0.020)	0.579(0.001)	0.933(0.020)	0.605(0.060)	0.908(0.050)	0.863(0.015)	2.030(0.420)	0.853(0.060)	0.650(0.030)
TrimNet [31]	0.812(0.019)	0.652(0.032)	0.906(0.017)	0.606(0.006)	0.892(0.025)	0.843(0.025)	2.529(0.111)	1.282(0.029)	0.702(0.008)
FunQG-DMPNN	0.845(0.008)	0.721(0.009)	0.841(0.037)	0.642(0.034)	0.914(0.010)	0.862(0.047)	1.501(0.376)	0.818(0.047)	0.622(0.028)

We report the mean of three independent executions on three randomly seeded scaffold splittings with the ratio of 80:10:10 for the training/validation/test sets. The numbers in brackets are the standard deviations, and the best result in each dataset is written in bold.

3.5 Experiments Results

Table 1 summarizes the performance of our proposed method alongside various baseline methods. This table indicates that the FunQG-DMPNN outperforms popular baselines on 6 of the 9 datasets, besides its low computational complexity. Specifically, compared to the DMPNN, the FunQG-DMPNN performs better in 7 out of 9 studied benchmarks despite the significant reduction of parameters. Also, relatively small standard deviations indicate the robustness of our method.

4 Conclusion and Future Work

In this paper, we have proposed a novel molecular graph coarsening framework named FunQG for more efficient learning of molecular representations. Our method focuses on obtaining richer, more effective, and less challenging graphs for training graph neural networks from molecular graphs. To achieve this goal, we used a concept of graph theory called quotient graphs along with important molecular substructures called functional groups. Since selecting appropriate graph partitions is crucial to avoid information loss in constructing quotient graphs, we utilized FGs for this purpose. A direction for future research is to consider other domain knowledge or graph-theoretic information about the molecular graphs to partition their node sets. On the other hand, medicinal chemists have relatively different definitions of FGs. In this paper, we employed a relatively simple algorithm to identify FGs in large chemical databases very quickly and with low computational costs. Another future research direction is to use other definitions and algorithms to determine FGs. Also, we respectively utilized mean and sum functions to aggregate local information of molecular graphs into the nodes and edges of the quotient graphs to avoid data loss. One can use other combinations of aggregation functions in a similar manner. Through experiments, we showed that the resulting informative graphs are much smaller than the molecular graphs and thus are good candidates for making GNNs more efficient for finding molecular representations. Since the FunQG framework is model-independent, one can try different models on the resulting graphs to find an optimal model architecture. To demonstrate the efficiency of the FunQG and maintain the simplicity and cost-effectiveness of the method, we used the DMPNN architecture as a simple state-of-the-art baseline GNN with no attention layers and no need for pre-training. According to our experiments, this method significantly outperforms previous baselines on various popular molecular property prediction benchmarks despite its simplicity and low computational complexity. This work has focused on the problem of molecular representation learning, but the proposed framework is general and adjustable to other areas of graph representation learning.

5 Data and Code Availability

The molecular datasets are available on the website of MoleculeNet at <http://moleculenet.ai>. The source code and other data underlying this work are available in GitHub at <https://github.com/hhaji/funqg>.




Figure 5: A comparison between the total number of parameters of the best models of the FunQG-DMPNN and the DMPNN

6 Competing interests

The authors declare no competing financial interest.

7 Funding

Hossein Hajiabolhassan was supported by a grant from the National Natural Science Foundation of China (NSFC U20A2068). Also, Zahra Taheri was supported by a grant from Basic Sciences Research Fund (No. BSRF-math-399-06).

References

- [1] Abbasi, K., Razzaghi, P., Poso, A., Ghanbari-Ara, S. and Masoudi-Nejad, A., 2021. Deep Learning in Drug Target Interaction Prediction: Current and Future Perspectives. *Current Medicinal Chemistry*, 28(11), pp.2100–2113.
- [2] Alon, U. and Yahav, E., 2020, September. On the Bottleneck of Graph Neural Networks and its Practical Implications. In *International Conference on Learning Representations*.
- [3] Bai, J., Ren, Y. and Zhang, J., 2021, July. Ripple walk training: A subgraph-based training framework for large and deep graph neural network. In *2021 International Joint Conference on Neural Networks (IJCNN)* (pp. 1–8). IEEE.
- [4] Barceló, P., Kostylev, E., Monet, M., Pérez, J., Reutter, J. and Silva, J.P., 2020, April. The logical expressiveness of graph neural networks. In *8th International Conference on Learning Representations (ICLR 2020)*.
- [5] Bravo Hermsdorff, G. and Gunderson, L., 2019. A Unifying Framework for Spectrum-Preserving Graph Sparsification and Coarsening. *Advances in Neural Information Processing Systems*, 32, pp.7736–7747.
- [6] Cai, C., Wang, D. and Wang, Y., 2020, September. Graph Coarsening with Neural Networks. In *International Conference on Learning Representations*.
- [7] Cao, D.S., Xu, Q.S., Hu, Q.N. and Liang, Y.Z., 2013. ChemoPy: freely available python package for computational biology and chemoinformatics. *Bioinformatics*, 29(8), pp.1092–1094.
- [8] Chan, H.S., Shan, H., Dahoun, T., Vogel, H. and Yuan, S., 2019. Advancing drug discovery via artificial intelligence. *Trends in pharmacological sciences*, 40(8), pp.592–604.
- [9] Cherkasov, A., Muratov, E.N., Fourches, D., Varnek, A., Baskin, I.I., Cronin, M., Dearden, J., Gramatica, P., Martin, Y.C., Todeschini, R. and Consonni, V., 2014. QSAR modeling: where have you been? Where are you going to?. *Journal of medicinal chemistry*, 57(12), pp.4977–5010.

- [10] Coley, C.W., Barzilay, R., Green, W.H., Jaakkola, T.S. and Jensen, K.F., 2017. Convolutional embedding of attributed molecular graphs for physical property prediction. *Journal of chemical information and modeling*, 57(8), pp.1757–1772.
- [11] Dai, H., Dai, B. and Song, L., 2016, June. Discriminative embeddings of latent variable models for structured data. In *International conference on machine learning* (pp. 2702–2711). PMLR.
- [12] David, L., Thakkar, A., Mercado, R. and Engkvist, O., 2020. Molecular representations in AI-driven drug discovery: a review and practical guide. *Journal of Cheminformatics*, 12(1), pp.1-22.
- [13] Durant, J.L., Leland, B.A., Henry, D.R. and Nourse, J.G., 2002. Reoptimization of MDL keys for use in drug discovery. *Journal of chemical information and computer sciences*, 42(6), pp.1273–1280.
- [14] Duvenaud, D.K., Maclaurin, D., Iparraguirre, J., Bombarell, R., Hirzel, T., Aspuru-Guzik, A. and Adams, R.P., 2015. Convolutional Networks on Graphs for Learning Molecular Fingerprints. *Advances in Neural Information Processing Systems*, 28, pp.2224–2232.
- [15] Ertl, P., 2017. An algorithm to identify functional groups in organic molecules. *Journal of cheminformatics*, 9(1), pp.1–7.
- [16] Fang, X., Liu, L., Lei, J., He, D., Zhang, S., Zhou, J., Wang, F., Wu, H. and Wang, H., 2022. Geometry-enhanced molecular representation learning for property prediction. *Nature Machine Intelligence*, 4(2), pp.127-134.
- [17] Feldman, H.J., Dumontier, M., Ling, S., Haider, N. and Hogue, C.W., 2005. CO: A chemical ontology for identification of functional groups and semantic comparison of small molecules. *FEBS letters*, 579(21), pp.4685–4691.
- [18] Gilmer, J., Schoenholz, S.S., Riley, P.F., Vinyals, O. and Dahl, G.E., 2017, July. Neural message passing for quantum chemistry. In *International conference on machine learning* (pp. 1263–1272). PMLR.
- [19] Gori, M., Monfardini, G. and Scarselli, F., 2005, July. A new model for learning in graph domains. In *Proceedings. 2005 IEEE International Joint Conference on Neural Networks*, 2005. (Vol. 2, pp. 729–734). IEEE.
- [20] Hahn, G. and Sabidussi, G. eds., 2013. *Graph symmetry: algebraic methods and applications* (Vol. 497). Springer Science and Business Media.
- [21] Hall, R., 2017. Implementation of an algorithm to identify functional groups in organic molecules. <https://github.com/rdkit/rdkit/tree/master/Contrib/IFG> (accessed 2022-04-16).
- [22] Hamilton, W.L., Ying, R. and Leskovec, J., 2017, December. Inductive representation learning on large graphs. In *Proceedings of the 31st International Conference on Neural Information Processing Systems* (pp. 1025–1035).
- [23] Headley, A. D., 2020, *Organic Chemistry: Concepts and Applications*. United Kingdom, Wiley.
- [24] Jiang, D., Wu, Z., Hsieh, C.Y., Chen, G., Liao, B., Wang, Z., Shen, C., Cao, D., Wu, J. and Hou, T., 2021. Could graph neural networks learn better molecular representation for drug discovery? A comparison study of descriptor-based and graph-based models. *Journal of cheminformatics*, 13(1), pp.1-23.
- [25] Kearnes, S., McCloskey, K., Berndl, M., Pande, V. and Riley, P., 2016. Molecular graph convolutions: moving beyond fingerprints. *Journal of computer-aided molecular design*, 30(8), pp.595–608.
- [26] Kipf, T.N. and Welling, M., 2017. Semi-supervised classification with graph convolutional networks. In *Proceedings of the 5th International Conference on Learning Representations, ICLR’17, Toulon, France, April 24–26*.
- [27] Landrum, G., 2006. RDKit: Open-source cheminformatics. <https://www.rdkit.org> (accessed 2022-04-16).
- [28] Leskovec, J. and McAuley, J., 2012. Learning to Discover Social Circles in Ego Networks. *Advances in Neural Information Processing Systems*, 25, pp.539–547.
- [29] Li, Q., Han, Z. and Wu, X.M., 2018, April. Deeper insights into graph convolutional networks for semi-supervised learning. In *Thirty-Second AAAI conference on artificial intelligence*.
- [30] Li, P., Wang, J., Qiao, Y., Chen, H., Yu, Y., Yao, X., Gao, P., Xie, G. and Song, S., 2021. An effective self-supervised framework for learning expressive molecular global representations to drug discovery. *Briefings in Bioinformatics*, 22(6), p.bbab109.
- [31] Li, P., Li, Y., Hsieh, C.Y., Zhang, S., Liu, X., Liu, H., Song, S. and Yao, X., 2021. TrimNet: learning molecular representation from triplet messages for biomedicine. *Briefings in Bioinformatics*, 22(4), p.bbba266.
- [32] Liaw, R., Liang, E., Nishihara, R., Moritz, P., Gonzalez, J.E. and Stoica, I., 2018. Tune: A research platform for distributed model selection and training. *arXiv preprint arXiv:1807.05118*. <https://docs.ray.io/en/latest/tune/index.html> (accessed 2022-05-10).

- [33] Loukas, A. and Vandenbroucke, P., 2018, July. Spectrally approximating large graphs with smaller graphs. In International Conference on Machine Learning (pp. 3237–3246). PMLR.
- [34] Loukas, A., 2019. Graph Reduction with Spectral and Cut Guarantees. *J. Mach. Learn. Res.*, 20(116), pp.1–42.
- [35] Lu, C., Liu, Q., Wang, C., Huang, Z., Lin, P. and He, L., 2019, July. Molecular property prediction: A multilevel quantum interactions modeling perspective. In Proceedings of the AAAI Conference on Artificial Intelligence (Vol. 33, No. 01, pp. 1052–1060).
- [36] Ma, H., Bian, Y., Rong, Y., Huang, W., Xu, T., Xie, W., Ye, G. and Huang, J., 2022. Cross-dependent graph neural networks for molecular property prediction. *Bioinformatics*, 38(7), pp.2003–2009.
- [37] Mahć, P., Ueda, N., Akutsu, T., Perret, J.L. and Vert, J.P., 2004, July. Extensions of marginalized graph kernels. In Proceedings of the twenty-first international conference on Machine learning (p. 70).
- [38] Matlock, M.K., Datta, A., Le Dang, N., Jiang, K. and Swamidass, S.J., 2019, July. Deep learning long-range information in undirected graphs with wave networks. In 2019 International Joint Conference on Neural Networks (IJCNN) (pp. 1–8). IEEE.
- [39] Mauri, A., Consonni, V., Pavan, M. and Todeschini, R., 2006. Dragon software: An easy approach to molecular descriptor calculations. *Match*, 56(2), pp.237–248.
- [40] Micheli, A., 2009. Neural network for graphs: A contextual constructive approach. *IEEE Transactions on Neural Networks*, 20(3), pp.498–511.
- [41] Moriwaki, H., Tian, Y.S., Kawashita, N. and Takagi, T., 2018. Mordred: a molecular descriptor calculator. *Journal of cheminformatics*, 10(1), pp.1–14.
- [42] Muller, P., 1994. Glossary of terms used in physical organic chemistry (IUPAC Recommendations 1994). *Pure and Applied Chemistry*, 66(5), pp.1077–1184.
- [43] Oono, K. and Suzuki, T., 2019, September. Graph Neural Networks Exponentially Lose Expressive Power for Node Classification. In International Conference on Learning Representations.
- [44] Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L. and Desmaison, A., 2019. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32.
- [45] Peleg, D. and Schäffer, A.A., 1989. Graph spanners. *Journal of graph theory*, 13(1), pp.99–116.
- [46] Ramsundar, B., Kearnes, S., Riley, P., Webster, D., Konerding, D. and Pande, V., 2015. Massively multitask networks for drug discovery. *arXiv preprint arXiv:1502.02072*.
- [47] Rogers, D. and Hahn, M., 2010. Extended-connectivity fingerprints. *Journal of chemical information and modeling*, 50(5), pp.742–754.
- [48] Rong, Y., Bian, Y., Xu, T., Xie, W., Wei, Y., Huang, W. and Huang, J., 2020. Self-supervised graph transformer on large-scale molecular data. *Advances in Neural Information Processing Systems*, 33, pp.12559–12571.
- [49] Ryu, J.Y., Kim, H.U. and Lee, S.Y., 2018. Deep learning improves prediction of drug–drug and drug–food interactions. *Proceedings of the National Academy of Sciences*, 115(18), pp.E4304–E4311.
- [50] Sanders, P. and Schulz, C., 2012. High quality graph partitioning. *Graph Partitioning and Graph Clustering*, 588(1), pp.1–17.
- [51] Scarselli, F., Gori, M., Tsoi, A.C., Hagenbuchner, M. and Monfardini, G., 2008. The graph neural network model. *IEEE transactions on neural networks*, 20(1), pp.61–80.
- [52] Schütt, K.T., Kindermans, P.J., Sauceda, H.E., Chmiela, S., Tkatchenko, A. and Müller, K.R., 2017. SchNet: A continuous-filter convolutional neural network for modeling quantum interactions. *Advances in Neural Information Processing Systems*, 2017, pp.992–1002.
- [53] Sen, P., Namata, G., Bilgic, M., Getoor, L., Galligher, B. and Eliassi-Rad, T., 2008. Collective classification in network data. *AI magazine*, 29(3), pp.93–93.
- [54] Shchur, O., Mumme, M., Bojchevski, A. and Günnemann, S., 2018. Pitfalls of graph neural network evaluation. *Relational Representation Learning Workshop, NeurIPS 2018*.
- [55] Spielman, D.A. and Teng, S.H., 2011. Spectral sparsification of graphs. *SIAM Journal on Computing*, 40(4), pp.981–1025.
- [56] Spielman, D.A. and Srivastava, N., 2011. Graph sparsification by effective resistances. *SIAM Journal on Computing*, 40(6), pp.1913–1926.

- [57] Stokes, J.M., Yang, K., Swanson, K., Jin, W., Cubillos-Ruiz, A., Donghia, N.M., MacNair, C.R., French, S., Carfrae, L.A., Bloom-Ackermann, Z. and Tran, V.M., 2020. A deep learning approach to antibiotic discovery. *Cell*, 180(4), pp.688–702.
- [58] Swanson, K., 2019. Message passing neural networks for molecular property prediction (Doctoral dissertation, Massachusetts Institute of Technology).
- [59] Veličković, P., Cucurull, G., Casanova, A., Romero, A., Liò, P. and Bengio, Y., 2018, February. Graph Attention Networks. In *Proceedings of 6th International Conference on Learning Representations*. Vancouver, Canada.
- [60] Walters, W.P. and Barzilay, R., 2020. Applications of deep learning in molecule generation and molecular property prediction. *Accounts of Chemical Research*, 54(2), pp.263–270.
- [61] Wang, M., Zheng, D., Ye, Z., Gan, Q., Li, M., Song, X., Zhou, J., Ma, C., Yu, L., Gai, Y. and Xiao, T., 2019. Deep graph library: A graph-centric, highly-performant package for graph neural networks. *arXiv preprint arXiv:1909.01315*.
- [62] Wu, Z., Pan, S., Chen, F., Long, G., Zhang, C. and Philip, S.Y., 2020. A comprehensive survey on graph neural networks. *IEEE transactions on neural networks and learning systems*, 32(1), pp.4–24.
- [63] Wu, Z., Ramsundar, B., Feinberg, E.N., Gomes, J., Geniesse, C., Pappu, A.S., Leswing, K. and Pande, V., 2018. MoleculeNet: a benchmark for molecular machine learning. *Chemical science*, 9(2), pp.513–530.
- [64] Xiong, Z., Wang, D., Liu, X., Zhong, F., Wan, X., Li, X., Li, Z., Luo, X., Chen, K., Jiang, H. and Zheng, M., 2019. Pushing the boundaries of molecular representation for drug discovery with the graph attention mechanism. *Journal of medicinal chemistry*, 63(16), pp.8749–8760.
- [65] Xu, K., Hu, W., Leskovec, J. and Jegelka, S., 2018, September. How Powerful are Graph Neural Networks?. In *International Conference on Learning Representations*.
- [66] Yang, K., Swanson, K., Jin, W., Coley, C., Eiden, P., Gao, H., Guzman-Perez, A., Hopper, T., Kelley, B., Mathea, M. and Palmer, A., 2019. Analyzing learned molecular representations for property prediction. *Journal of chemical information and modeling*, 59(8), pp.3370–3388.