# On the Expressiveness of a Logic of Separated Relations

Radu Iosif<sup>1</sup> and Florian Zuleger<sup>2</sup>

Institute of Logic and Computation, Technische Universität Wien, Austria

Abstract. We compare the model-theoretic expressiveness of the existential fragment of Separation Logic over unrestricted relational signatures (SLR) — with only separating conjunction as logical connective and higher-order inductive definitions, traditionally known as the symbolic heap fragment — with the expressiveness of (Monadic) Second Order Logic ((M)SO). While SLR and MSO are incomparable on structures of unbounded treewidth, it turns out that SLR can be embedded in SO, in general, and that MSO becomes a strict subset of SLR, when the treewidth of the models is bounded by a parameter given as input. We also discuss the problem of defining a fragment of SLR that is equivalent to MSO over models of bounded treewidth. Such a fragment would then become the most general Separation Logic with a decidable entailment problem, a key ingredient of practical verification methods for self-adapting (reconfigurable) component-based and distributed systems.

## 1 Introduction

Separation Logic [36,28] (SL) is used to write proofs of programs that perform low-level memory updates via pointer manipulations. The main feature of SL is the separating conjunction connective \*, that is associative, commutative but not idempotent i.e.,  $\phi * \phi$  is not the same as  $\phi$ . The lack of idempotency, traditionally recognized as a natural property of boolean connectives, became a rather useful tool in reasoning about *resources* that can be accumulated, split or shared among the members of a given population (see [34] for a survey of resource logics and their semantics).

Since, merely a decade ago, computers were still standalone systems (though parallel and interconnected), the most important resource of a computing device was its embedded memory. More recently, with the advent of complex heterogeneous systems, such as mobile networks and cloud computing, this view is drifting towards component-based and distributed computing, where resources are mostly understood as components (of possibly different nature e.g., discrete and continuous as in a cyberphysical system) and network nodes (executing processes in disjoint memory spaces), respectively.

The modeling and verification of complex component-based and distributed systems have been only recently addressed by logicians, see e.g., [3,33]. Driven by the needs of reasoning about such systems, we have developed dialects of SL tailored for modeling and verification of hierarchical component-based [5] and self-adapting (dynamically reconfigurable) distributed systems [2,4]. To this end, the original signature of SL has been extended from a single atomic proposition  $x \mapsto (y_1, \ldots, y_k)$  interpreted as an allocated memory cell x that *points-to* other non-allocated cells  $y_1, \ldots, y_k$ , to a *relational signature*, that contains relation symbols (of arity greater or equal to one) and

no other function symbols than constants (function symbols of arity zero). Whereas SL formulæ are interpreted over *heaps* (i.e., partial functions with finite domain) of a fixed arity, the formulæ of the *Separation Logic of Relations* (SLR) are interpreted over generic *relational structures*. In particular, the interpretation of an atomic proposition  $R(x_1, ..., x_n)$  is the relation consisting of a single tuple, given by the store values of  $x_1, ..., x_n$ , respectively.

Whereas the SL formula  $x \mapsto (y_1, \dots, y_k) * u \mapsto (v_1, \dots, v_k)$  constrains x and u to refer to distinct memory cells (i.e.,  $x \neq u$ ), the SLR formula  $R(x_1, \dots, x_n) * R(u_1, \dots, u_n)$  means that the interpretation of the relation symbol R consists of two distinct tuples (i.e.,  $x_i \neq u_i$  for at least one index  $1 \leq i \leq n$ ). If we restrict the formulæ to contain only separation conjunctions (i.e., no boolean conjunctions or negations), the relational dialect of SL is more general than the original, because each points-to atom  $x \mapsto (y_1, \dots, y_k)$  can be encoded by a formula  $D(x) * H(x, y_1, \dots, y_k)$  in a signature with two symbols D and D and D and the graph D of the heap, respectively D.

Despite a large body of work on the use of inductive definitions in SL to reason about (mainly) recursive datastructures [7,8,18,22,23,17,30] and (recently) about architectures of component-based and distributed systems [2,4], little is known about the expressive power of these logics. This paper fills this gap by pursueing a model-theoretic comparison of SLR with the classical Monadic Second Order (MSO) and Second Order (SO) logics. We compare SLR with (M)SO on structures defined over relational signatures with and without a bound on their treewidth. The main results (see Table 1 for a summary) are that:

- 1. SLR and MSO are incomparable on structures of unbounded treewidth i.e., there are formulæ in each of the logics that do not have an equivalent in the other in terms of the families of structures they define,
- 2. SLR is strictly contained in SO, when considering structures of unbounded treewidth,
- 3. MSO is strictly contained in SLR, when considering structures of bounded treewidth. The third result is probably the most interesting, as it gives a sense of the expressive power of SLR (and implicitly of standard SL), emphasizing the importance of the treewidth parameter.

Because the inclusion of MSO into SLR is strict over structures of bounded treewidth, it is natural to ask for a fragment of SLR that has the same expressive power as MSO, over such structures. This is motivated by the need for a general fragment of SL, with a decidable entailment problem (asking if every model of a formula  $\phi$  is also a model of another formula  $\psi$ , when the predicates are interpreted by a given set of inductive definitions) useful in designing automated program analyses. Unfortunately, this definition is challenging because the MSO-definability of the set of models of an SLR formula is undecidable, whereas the boundedness of the treewidth for such sets remains an open problem.

**Motivation.** In this paragraph, we shortly sketch our earlier work that motivated the study of SLR. Earlier versions of SLR [2,4] have been used to describe components

<sup>&</sup>lt;sup>1</sup> This is not true if we allow boolean connectives because e.g.,  $(x \mapsto (y) * \text{true}) \land (x \mapsto (y') * \text{true}) \land y \neq y'$  is unsatisfiable, whereas  $(D(x) * H(x,y) * \text{true}) \land (D(x) * H(x,y') * \text{true}) \land y = y'$  remains satisfiable.

in a component-based system (resp. network nodes in a distributed system) by unary relation symbols and interactions (resp. communication channels in a distributed system) involving n participants by relation symbols of arity  $n \ge 2$ . Moreover, recent work emphasized similarities between recursive datastructures (e.g., lists, trees, etc.) and distributed networks (e.g., datacenters) for instance, splay trees [38] are used to design reconfiguration algorithms that minimize network traffic [31,32]. Taking this idea one step further, we describe concisely distributed networks of unbounded sizes, that share the same architectural style (e.g., a ring, star, tree, etc.) in similar way as recursive datastructures are described in SL [36], using sets of inductive definitions [4,5,2]. For instance, a system consisting of a finite but unbounded number of components (processes) placed in a ring, such that each component interacts only with its left and right neighbour, can be described by the following inductive rules:

$$\mathsf{Ring}() \leftarrow \exists x \exists y \ . \ I(x,y) * \mathsf{Chain}(y,x)$$
 
$$\mathsf{Chain}(x,y) \leftarrow \exists z \ . \ C(x) * I(x,z) * \mathsf{Chain}(z,y) \mid \mathsf{emp} * x = y$$

where I(x,y) denotes a single interaction between nodes with identifiers x and y, C(x) denotes a single component with identifier x and emp denotes an empty structure. The predicate symbols Ring() and Chain(x,y) are interpreted as the components of the pointwise smallest solution of the system of recursive constraints above, with  $\leftarrow$  interpreted as right-to-left inclusion between sets of structures. Equivalently, any model of Ring() is a model of a formula without predicate symbols, obtained by an exhaustive unfolding of the above definitions:

$$\mathsf{Ring}() \Rightarrow \exists x \exists y \,.\, I(x,y) * \mathsf{Chain}(y,x) \Rightarrow \exists x \exists y \exists z \,.\, I(x,y) * C(y) * I(y,z) * \mathsf{Chain}(z,x) \Rightarrow \ldots$$

**Related Work.** The problem of comparing the expressiveness of SL [36], the most prominent among the dialects of the calculus of Bunched Implications [29], with that of classical logics received a fair amount of attention in the past. For instance, the first proof of undecidability of the satisfiability problem for first-order SL [10] is based on a reduction to Trakhtenbrot's undecidability result for first-order logic on finite models [15]. This proof was reviewed with certain criticism, given that the only construction specific to SL is the intuitionistic binary points-to formula used to encode arbitrary binary relations as  $R(x,y) \stackrel{\text{def}}{=} \exists z \cdot z \hookrightarrow (x,y)$ , where  $z \hookrightarrow (x,y)$  stands for  $z \mapsto (x,y) *$  true. A more refined proof of undecidability for unary points-to relations  $x \mapsto y$  was given by Brochenin, Demri and Lozes [6]. In particular, they show that SO over heaps with one record field has the same expressivity as SL with unary points-to predicates.

A related line of work, pioneered by Lozes [25], is the translation of quantifier-free SL formulæ into boolean combinations of *core formulæ*, belonging to a small set of very simple patterns. This enables a straightforward translation of the quantifier-free fragment of SL into first-order logic, over unrestricted signatures with both relation and function symbols, that was subsequently extended to two quantified variables [13] and restricted quantifier prefixes [16]. Moreover, a translation of quantifier-free SL into first-order logic, based on the small model property of the former, has been described in [9].

Unlike our work, the above references focus exclusively on fragments of SL without inductively defined predicates, but with arbitrary combinations of boolean (conjunction,

implication) and multiplicative (separating conjunction, magic wand) connectives. A non-trivial attempt of generalizing the technique of translating SL into boolean combinations of core formulæ to *reachability* and *list segment* predicates is given in [14]. Moreover, an in-depth comparison between the expressiveness of various models of separation i.e., spatial, as in SL, and contextual, as in ambient logics, can be found in [27].

To the best of our knowledge, the results reported in this paper constitute the first model-theoretic comparison of a Separation Logic with *arbitrary inductive predicates*, written using a generalized relational signature and interpreted over logical structures (instead of heaps) with the (M)SO logics. Previous work along this line concerns a fairly general fragment of SL, defined using syntactic restrictions on the rules used to interpret the predicates, that translates into MSO formlæ and has models of bounded treewidth [20]. This fragment has also been studied in [22,30], where an alternative decision procedure based on types has been developed. Our result showing the embedding of MSO into SLR, on models of bounded treewidth, based on the refinement of a generic SID for bounded treewidth structures by MSOtypes, is dual and opens the (hard) problem of defining a fragment of SLR with the same expressivity as MSO. The approach of refining SIDs has previously been exploited for the study of robustness properties [21] but not for the comparison of SL and MSO.

### 2 Definitions

For a set A, we denote by pow(A) its powerset and  $A^1 \stackrel{\mathsf{def}}{=} A$ ,  $A^{i+1} \stackrel{\mathsf{def}}{=} A^i \times A$ , for all  $i \ge 1$ , where  $\times$  is the Cartesian product, and  $A^+ \stackrel{\mathsf{def}}{=} \bigcup_{i \ge 1} A^i$ . The cardinality of a finite set A is denoted by  $\|A\|$ . Given integers i and j, we write [i,j] for the set  $\{i,i+1,\ldots,j\}$ , assumed to be empty if i > j.

**Signatures and Structures** Let  $\Sigma = \{R_1, \dots, R_N, c_1, \dots, c_M\}$  be a finite *signature*, where  $R_i$  denote relation symbols of arity  $\#R_i$  and  $c_j$  denote constant symbols (i.e., nullary function symbols). Since there are no function symbols of arity more than zero, these signatures are said to be *relational* in the literature, see e.g., [12].

A structure is a pair  $(\mathbb{U},\sigma)$ , where  $\mathbb{U}$  is an infinite countable set, called *universe*, and  $\sigma: \Sigma \to \mathbb{U} \cup \text{pow}(\mathbb{U}^+)$  is a function that maps each relation symbol  $\mathsf{R}_i$  to a relation  $\sigma(\mathsf{R}_i) \subseteq \mathbb{U}^{\#\mathsf{R}_i}$  and each constant  $\mathsf{c}_j$  to an element of the universe. We define the sets  $\mathsf{Rel}(\sigma) \stackrel{\mathsf{def}}{=} \{u_k \mid \langle u_1, \dots, u_{\#\mathsf{R}_i} \rangle \in \sigma(\mathsf{R}_i), \ i \in [1,N], \ k \in [1,\#\mathsf{R}_i] \}$  and  $\mathsf{Dom}(\sigma) \stackrel{\mathsf{def}}{=} \mathsf{Rel}(\sigma) \cup \{\sigma(\mathsf{c}_1), \dots, \sigma(\mathsf{c}_M) \}$  of elements that belong to the interpretation of a relation symbols or a constant from  $\Sigma$ , respectively. Unless stated otherwise (as in e.g., §7), we consider the signature  $\Sigma$  and the countably infinite universe  $\mathbb U$  to be fixed, for all structures considered in the rest of this paper. Hence we denote structures simply by  $\sigma$ , in the following.

Remark 1. The standard notion of structure from the literature encapsulates the universe (sometimes called *domain*), such that two different structures may have different universes (see e.g., [15] for the standard definitions). By considering that all structures share the same universe we deviate from the standard definition. This is important for the definition of a composition operation on structures that extends naturally the union

of heaps with disjoint domains, defined over the same set of memory locations, from the semantics of SL [36]. Moreover, standard structures may have a finite universe, whereas here we consider a countably infinite universe, in analogy with the set of memory locations

**Definition 1.** Two structures  $\sigma_1$  and  $\sigma_2$  are disjoint if and only if  $\sigma_1(R_i) \cap \sigma_2(R_i) = \emptyset$ , for all  $i \in [1,N]$  and compatible if and only if  $\sigma_1(c_j) = \sigma_2(c_j)$ , for all  $j \in [1,M]$ . The composition of two disjoint and compatible structures is the structure  $\sigma_1 \bullet \sigma_2$ , such that  $(\sigma_1 \bullet \sigma_2)(R_i) = \sigma_1(R_i) \cup \sigma_2(R_i)$  and  $(\sigma_1 \bullet \sigma_2)(c_j) = \sigma_1(c_j) = \sigma_2(c_j)$ , for all  $i \in [1,N]$  and  $j \in [1,M]$ . The composition is undefined for structures that are not disjoint or not compatible.

In the rest of this paper, we will identify structures that differ by a renaming of elements from the universe and consider only classes of structures that are closed under isomorphism:

**Definition 2.** Two structures  $\sigma_1$  and  $\sigma_2$  are isomorphic, denoted  $\sigma_1 \simeq \sigma_2$  if and only if there exists a bijection  $h: \mathbb{U} \to \mathbb{U}$ , such that:

- 1. for each  $i \in [1,N]$  and  $\langle u_1,\ldots,u_{\#R_i} \rangle \in \mathbb{U}^{\#R_i}$ , we have  $\langle u_1,\ldots,u_{\#R_i} \rangle \in \sigma_1(\mathsf{R}) \iff \langle h(u_1),\ldots,h(u_{\#R_i}) \rangle \in \sigma_2(\mathsf{R})$ ,
- 2. for each  $j \in [1,M]$ , we have  $h(\sigma_1(c_j)) = \sigma_2(c_j)$ .

**Graphs, Cliques, Trees and Grids** A graph is a pair  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , such that  $\mathcal{V} \subseteq \mathbb{U}$  is a finite set of *vertices* and  $\mathcal{E} \subseteq \mathcal{V} \times \mathcal{V}$  is a set of *edges*. All graphs considered in this paper are directed i.e.,  $\mathcal{E}$  is not a symmetric relation. The following definition relates graphs and structures.

**Definition 3.** Each graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$  can be viewed as a structure  $\sigma_{\mathcal{G}}$  over the signature  $\Gamma \stackrel{\text{def}}{=} \{V, E\}$ , where #V = 1 and #E = 2, such that  $\sigma_{\mathcal{G}}(V) = \mathcal{V}$  and  $\sigma_{\mathcal{G}}(\mathcal{E}) = E$ .

A *path* in  $\mathcal{G}$  is a sequence of pairwise distinct vertices  $v_1, \ldots, v_n \in \mathcal{V}$ , such that  $(v_i, v_{i+1}) \in \mathcal{E}$  or  $(v_{i+1}, v_i) \in \mathcal{E}$ , for all  $i \in [1, n-1]$ . A set of vertices  $V \subseteq \mathcal{V}$  is *connected in*  $\mathcal{G}$  if and only if there is path in  $\mathcal{G}$  between any two vertices in V. A graph  $\mathcal{G}$  is *connected* if and only if  $\mathcal{V}$  is connected in  $\mathcal{G}$ . A *clique* is a graph such that there exists an edge between each two nodes. We denote by  $\mathcal{K}_n$  the set of (pairwise isomorphic) cliques with n nodes.

A *tree* is a tuple  $\mathcal{T}=(\mathcal{N},\mathcal{F},r,\lambda)$ , where  $(\mathcal{N},\mathcal{F})$  is a graph,  $r\in\mathcal{N}$  is a designated vertex called the *root*, such that there exists a path in  $(\mathcal{N},\mathcal{F})$  from r to any other vertex  $v\in\mathcal{N},r$  has no incoming edge  $(p,r)\in\mathcal{F}$  and no vertex  $n\in\mathcal{N}$  has two incoming edges  $(m,n),(p,n)\in\mathcal{F}$ , for  $m\neq p$ . The mapping  $\lambda:\mathcal{N}\to\Lambda$  associates each vertex of the tree with a *label* from a given set  $\Lambda$ .

A  $n \times m$  grid is a graph  $(\mathcal{V}, \mathcal{E})$ , such that there exists a bijective function  $g : \mathcal{V} \to [1,n] \times [1,m]$  and, for each edge  $(u,v) \in \mathcal{E}$ , such that g(u) = (i,j), either i < n and g(v) = (i+1,j), or j < m and g(v) = (i,j+1). A grid is *square* if and only if n = m, and we denote by  $\mathcal{H}_n$  the set of (pairwise isomorphic)  $n \times n$  square grids.

**Treewidth** We define a measure on structures indicating how close a structure is to a tree:

**Definition 4.** A tree decomposition of a structure  $\sigma$  over the signature  $\Sigma$  is a tree  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$  labeled with subsets of  $\mathbb{U}$ , such that the following hold:

- 1. for each relation symbol  $R \in \Sigma$  and each tuple  $\langle u_1, ..., u_{\#R} \rangle \in \sigma(R)$  there exists  $n \in \mathcal{N}$ , such that  $\{u_1, ..., u_{\#R}\} \subseteq \lambda(n)$ , and
- 2. for each  $u \in Dom(\sigma)$ , the set  $\{n \in \mathcal{N} \mid u \in \lambda(n)\}$  is non-empty and connected in  $(\mathcal{N}, \mathcal{F})$ .

The width of the tree decomposition is  $\operatorname{tw}(\mathcal{T}) \stackrel{\text{def}}{=} \max_{n \in \mathcal{N}} \|\lambda(n)\| - 1$ . The treewidth of the structure  $\sigma$  is  $\operatorname{tw}(\sigma) \stackrel{\text{def}}{=} \min\{\operatorname{tw}(\mathcal{T}) \mid \mathcal{T} \text{ is a tree decomposition of } \sigma\}$ .

It is clear that two isomorphic structures have the same treewidth. In the following, we consider indexed families of structures that are closed under isomorphism. Such a family is *treewidth-bounded* if and only if the set of corresponding treewidths is finite and *treewidth-unbounded* otherwise. A family is *strictly treewidth-unbounded* if and only if it is treewidth-unbounded and any infinite subfamily is treewidth-unbounded. The following result can be found in several textbooks (see e.g., [12]) and is restated here for self-containment:

**Proposition 1.** The indexed families  $\{ \mathcal{K}_n \mid n \in \mathbb{N} \}$  and  $\{ \mathcal{H}_n \mid n \in \mathbb{N} \}$  are strictly treewidth-unbounded.

*Proof.* 1. Let  $\mathcal{K}_u \stackrel{\text{def}}{=} (\mathcal{V}, \mathcal{E})$ , modulo isomorphism. We prove that  $\operatorname{tw}(\mathcal{K}_u) = n-1$ , for all  $n \geq 2$ , by showing that, in every tree decomposition  $(\mathcal{N}, \mathcal{F}, r, \lambda)$  of  $\mathcal{K}_u \stackrel{\text{def}}{=} (\mathcal{V}, \mathcal{E})$  there is a node  $p \in \mathcal{N}$ , such that  $\lambda(p) = \mathcal{V}$ . By induction on  $n \geq 2$ , the base case n = 2 follows immediately from point (1) of Def. 4. For the inductive step n > 2, let  $u \in \mathcal{V}$  be a vertex and let  $p \in \mathcal{N}$  be the node of least depth, such that  $u \in \lambda(p)$ . By point (2) of Def. 4, this node is unique. Let  $\{v_1, \ldots, v_{n-1}\} \stackrel{\text{def}}{=} \mathcal{V} \setminus \{u\}$ . By the inductive hypothesis, there exists a node  $m \in \mathcal{N}$ , such that  $\lambda(m) = \{v_1, \ldots, v_{n-1}\}$ , because the restriction of  $(\mathcal{V}, \mathcal{E})$  to  $\{v_1, \ldots, v_{n-1}\}$  is a clique and  $(\mathcal{N}, \mathcal{F}, r, \lambda)$  is also a tree decomposition of that clique. Since  $(u, v_1), \ldots, (u, v_{n-1}) \in \mathcal{E}$ , by point (1) of Def. 4, there exists nodes  $q_1, \ldots, q_{n-1} \in \mathcal{N}$ , such that  $u, v_i \in \lambda(q_i)$ , for all  $i \in [1, n-1]$ . By the choice of p, these nodes are all descendants of p, because  $u \in \lambda(q_i)$ , for all  $i \in [1, n-1]$  and p has the lowest depth among all such nodes. We distinguish two cases:

- m is not a descendant of p, then let q be the deepest common ancestor of m and p. Since  $v_i \in \lambda(q_i) \cap \lambda(m)$ , we obtain  $v_i \in \lambda(q)$ , for all  $i \in [1, n-1]$ , by point (2) of Def. 4. This leads to  $u, v_1, \dots, v_{n-1} \in \lambda(p)$ , by the same argument.
- m is a descendant of p and let  $q_i', \ldots, q_{n-1}'$  be the deepest common ancestors of m and  $q_1, \ldots, q_{n-1}$ , respectively. Since  $v_i \in \lambda(q_i) \cap \lambda(m)$ , we obtain  $v_i \in \lambda(q_i')$ , for all  $i \in [1, n-1]$ , by point (2) of Def. 4. Since  $q_1', \ldots, q_{n-1}'$  are all ancestors of m, they are linearly ordered by the ancestor relation and let  $q_k'$  be the deepest such node. Then we obtain  $u, v_1, \ldots, v_{n-1} \in \lambda(q_k')$ , by point (2) of Def. 4.
- 2. Let  $\mathcal{H}_n \stackrel{\text{def}}{=} (\mathcal{V}, \mathcal{E})$ . Consider the k-cops and robber game on  $(\mathcal{V}, \mathcal{E})$ , defined as follows. A position in the game is a pair (C, r), where  $C \subseteq \mathcal{V}$ , ||C|| = k and  $r \in \mathcal{V} \setminus C$ . The game can move from  $(C_i, r_i)$  to  $(C_{i+1}, r_{i+1})$  if there exists a path between  $r_i$  and  $r_{i+1}$  in the restriction of  $(\mathcal{V}, \mathcal{E})$  to  $\mathcal{V} \setminus C_i \cap C_{i+1}$ . We say that k cops catch the robber if and only if every sequence of moves in the game is finite. It is known that, if  $\operatorname{tw}(\mathcal{G}) \leq k$  then

k+1 cops catch the robber on a graph  $\mathcal{G}$  [37]. Since n-1 cops do not catch the robber (which can always move to the intersection of a cop-free row and a cop-free column) it follows that  $\operatorname{tw}(\mathcal{H}_n) \geq n-1$ .

### 3 Logics

We introduce two logics for reasoning about structures over a (fixed) relational signature  $\Sigma = \{R_1, \dots, R_N, c_1, \dots, c_M\}$ . The first such logic, called the *Separation Logic of Relations* (SLR), uses a set of *first-order variables*  $\mathbb{V}^{(1)} = \{x, y, \dots\}$  and a set of *predicates*  $\mathbb{A} = \{A, B, \dots\}$  of arities #A, #B, etc. We use the symbols  $\xi, \chi \in \mathbb{V}^{(1)} \cup \{c_1, \dots, c_M\}$  to denote *terms* i.e., either first-order variables or constants. The formulæ of SLR are defined by the syntax:

$$\phi := \mathsf{emp} \mid \xi = \chi \mid \xi \neq \chi \mid \mathsf{R}(\xi_1, \dots, \xi_{\mathsf{\#R}}) \mid \mathsf{A}(\xi_1, \dots, \xi_{\mathsf{\#A}}) \mid \phi * \phi \mid \exists x \: . \: \phi$$

The formulæ  $\xi = \chi$  and  $\xi \neq \chi$  are called *equalities* and *disequalities*,  $R(\xi_1, \dots, \xi_{\#R})$  and  $A(\xi_1, \dots, \xi_{\#A})$  are called *relation* and *predicate atoms*, respectively. By *atom* we mean either emp or any of the above atomic formulæ.

A formula with no occurrences of predicate atoms (resp. existential quantifiers) is called *predicate-free* (resp. *quantifier-free*). A variable is *free* if it does not occur within the scope of an existential quantifier and let  $fv(\phi)$  be the set of free variables of  $\phi$ . A *sentence* is a formula with no free variables. A *substitution*  $\phi[x_1/\xi_1...x_n/\xi_n]$  replaces simultaneously every occurrence of the free variable  $x_i$  by the term  $\xi_i$  in  $\phi$ , for all  $i \in [1,n]$ . Before defining the semantics of SLR formulæ, we consider definitions that assign meaning to predicates:

**Definition 5.** A set of inductive definitions (SID)  $\Delta$  consists of rules  $A(x_1, ..., x_{\#A}) \leftarrow \phi$ , where  $x_1, ..., x_{\#A}$  are pairwise distinct variables, called parameters, such that  $fv(\phi) \subseteq \{x_1, ..., x_{\#A}\}$ . An atom  $\alpha$  occurs in a rule  $A(x_1, ..., x_{\#A}) \leftarrow \phi$  if and only if it occurs in  $\phi$ . We say that the rule  $A(x_1, ..., x_{\#A}) \leftarrow \phi$  defines A. We denote by  $def_{\Delta}(A)$  the set of rules from  $\Delta$  that define A and by  $def(\Delta)$  the set of predicates defined by some rule in  $\Delta$ .

Note that having distinct parameters in a rule is without loss of generality, as e.g., a rule  $A(x_1,x_1) \leftarrow \phi$  can be equivalently written as  $A(x_1,x_2) \leftarrow x_1 = x_2 * \phi$ . As a convention, we shall always use the names  $x_1, \dots, x_{\#A}$  for the parameters of a rule that defines A.

The semantics of SLR formulæ is given by the satisfaction relation  $(\sigma, \mathbf{v}) \models_{\Delta} \phi$  between structures and formulæ. This relation is parameterized by a *store*  $\mathbf{v} : \mathbb{V}^{(1)} \to \mathbb{U}$  mapping the free variables of a formula into elements of the universe and an SID  $\Delta$ . We write  $\mathbf{v}[x \leftarrow u]$  for the store that maps x into u and agrees with  $\mathbf{v}$  on all variables other than x. For a term  $\xi$ , we denote by  $(\sigma, \mathbf{v})(\xi)$  the value  $\sigma(\xi)$  if  $\xi$  is a constant, or  $\mathbf{v}(\xi)$  if  $\xi$  is a first-order variable. The satisfaction relation is defined by induction on the structure

of formulæ, as follows:

```
 \begin{array}{lll} (\sigma,\nu) \models_{\Delta} \mathsf{emp} & \iff \sigma(\mathsf{R}) = \emptyset, \, \mathsf{for} \, \mathsf{all} \, \mathsf{R} \in \Sigma \\ (\sigma,\nu) \models_{\Delta} \xi \bowtie \chi & \iff (\sigma,\nu) \models \mathsf{emp} \, \mathsf{and} \, (\sigma,\nu)(\xi) \bowtie (\sigma,\nu)(\chi), \, \mathsf{for} \, \mathsf{all} \, \bowtie \in \{=,\neq\} \\ (\sigma,\nu) \models_{\Delta} \mathsf{R}(\xi_1,\ldots,\xi_{\#\mathsf{R}}) & \iff \sigma(\mathsf{R}) = \{\langle (\sigma,\nu)(\xi_1),\ldots,(\sigma,\nu)(\xi_{\#\mathsf{R}}) \rangle\} \, \mathsf{and} \, \sigma(\mathsf{R}') = \emptyset, \\ & \quad \mathsf{for} \, \mathsf{all} \, \mathsf{R}' \in \Sigma \setminus \{\mathsf{R}\} \\ (\sigma,\nu) \models_{\Delta} \mathsf{A}(\xi_1,\ldots,\xi_{\#\mathsf{A}}) & \iff (\sigma,\nu) \models_{\Delta} \varphi[x_1/\xi_1,\ldots,x_{\#\mathsf{A}}/\xi_{\#\mathsf{A}}], \, \mathsf{for} \, \mathsf{some} \, \mathsf{rule} \\ & \quad \mathsf{A}(x_1,\ldots,x_{\#\mathsf{A}}) \leftarrow \varphi \, \mathsf{from} \, \Delta \\ (\sigma,\nu) \models_{\Delta} \varphi_1 \ast \varphi_2 & \iff \mathsf{there} \, \mathsf{exist} \, \mathsf{structures} \, \sigma_1 \, \mathsf{and} \, \sigma_2, \, \mathsf{such} \, \mathsf{that} \\ & \quad \sigma = \sigma_1 \bullet \sigma_2 \, \mathsf{and} \, (\sigma_i,\nu) \models_{\Delta} \varphi_i, \, \mathsf{for} \, \mathsf{all} \, i = 1,2 \\ (\sigma,\nu) \models_{\Delta} \exists x \, . \, \varphi & \iff (\sigma,\nu[x \leftarrow u]) \models_{\Delta} \varphi, \, \mathsf{for} \, \mathsf{some} \, u \in \mathbb{U} \\ \end{array}
```

If  $\phi$  is a sentence, the satisfaction relation  $(\sigma, v) \models_{\Delta} \phi$  does not depend on the store, written  $\sigma \models_{\Delta} \phi$ , in which case we say that  $\sigma$  is a *model* of  $\phi$ . If  $\phi$  is a predicate-free formula, the satisfaction relation does not depend on the SID, written  $(\sigma, v) \models \phi$ . We say that a pair  $(\phi, \Delta)$ , consisting of a sentence  $\phi$  and an SID  $\Delta$ , SLR-*defines* a set S of structures if and only if  $\sigma \models_{\Delta} \phi \iff \sigma \in S$ . By the result below, every set of SLR-defined structures is a union of equivalence classes of isomorphism (Def. 2):

**Proposition 2.** Given structures  $\sigma \simeq \sigma'$ , for any sentence  $\phi$  of SLR and any SID  $\Delta$ , we have  $\sigma \models_{\Delta} \phi \iff \sigma' \models_{\Delta} \phi$ .

*Proof.* By induction on the definition of the satisfaction relation  $\models_{\Delta}$ , we show that  $(\sigma, v) \models_{\Delta} \psi \iff (\sigma', h \circ v) \models_{\Delta} \psi$ , for any store v and any bijection  $h : \mathbb{U} \to \mathbb{U}$ , such that, for any relation symbol  $R \in \Sigma$ , we have  $\langle u_1, \dots, u_n \rangle \in \sigma(R) \iff \langle h(u_1), \dots, h(u_n) \rangle \in \sigma'(R)$  and, for any constant  $c \in \Sigma$ , we have  $h(\sigma(c)) = \sigma'(c)$ , as in Def. 2. We consider the following cases:

- $\phi$  = emp: for all  $R \in \Sigma$ , we have  $\sigma(R) = \emptyset \iff \sigma'(R) = \emptyset$ , by the existence of h.
- $\phi = \xi \bowtie \chi, \text{ for } \bowtie \in \{=, \neq\}: \text{ we prove only the case where } \xi \in \mathbb{V}^{(1)} \text{ and } \chi \in \{c_1, \ldots, c_M\}, \text{ the other cases being similar. By the above point, for all } \bowtie \in \{=, \neq\}, \text{ we have } \sigma \models \text{emp} \iff \sigma' \models \text{emp and } \nu(\xi) \bowtie \sigma(\chi) \iff h(\nu(\xi)) \bowtie h(\sigma(\chi)) \iff (h \circ \nu)(\xi) \bowtie \sigma'(\chi).$
- $$\begin{split} &- \phi = R(\xi_1, \dots, \xi_{\#R}) \colon \langle (\sigma, \nu)(\xi_1), \dots, (\sigma, \nu)(\xi_{\#R}) \rangle \in \sigma(R) \iff \langle h((\sigma, \nu)(\xi_1)), \dots, h((\sigma, \nu)(\xi_{\#R})) \rangle \in \\ &\sigma'(R). \text{ If } \xi_1, \dots, \xi_{\#R} \in \mathbb{V}^{(1)}, \text{ the latter condition is } \langle (h \circ \nu)(\xi_1), \dots, (h \circ \nu)(\xi_{\#R}) \rangle \in \\ &\sigma'(R). \text{ Else, if } \xi_1, \dots, \xi_{\#R} \in \{c_1, \dots, c_M\}, \text{ the condition is } \langle h(\sigma(\xi_1)), \dots, h(\sigma(\xi_{\#R})) \rangle \in \\ &\sigma'(R). \text{ The general case } \xi_1, \dots, \xi_{\#R} \in \mathbb{V}^{(1)} \cup \{c_1, \dots, c_M\} \text{ is a combination of the above cases.} \end{split}$$
- $\phi = A(\xi_1, \dots, \xi_{\#A})$ : this case follows by the induction hypothesis.
- $\phi = \phi_1 * \phi_2$ :  $(\sigma, v) \models_{\Delta} \phi_1 * \phi_2$  if and only if there exists disjoint and compatible structures  $\sigma_1 \bullet \sigma_2 = \sigma$ , such that  $(\sigma_i, v) \models_{\Delta} \phi_i$ , for all i = 1, 2. We define the structures  $\sigma'_1$  and  $\sigma'_2$  as follows, for i = 1, 2::
  - $\sigma'_i(R) = \{ \langle h(u_1), \dots, h(u_{\#R}) \rangle \mid \langle u_1, \dots, u_{\#R} \rangle \in \sigma_i(R) \}$ , for all relation symbols  $R \in \Sigma$ ,
  - $\sigma'_i(c) = h(\sigma_i(c))$ , for all constants  $c \in \Sigma$ .

Then  $\sigma'_1$  and  $\sigma'_2$  are disjoint and compatible and  $\sigma' = \sigma'_1 \bullet \sigma'_2$ . Moreover, by the inductive hypothesis, we have  $(\sigma'_i, v) \models_{\Delta} \phi_i$ , for all i = 1, 2, leading to  $(\sigma', v) \models_{\Delta} \phi_1 * \phi_2$ .

$\subseteq \subseteq^k$	SLR		MSO		SO	
SLR	<b>√</b>	?	× (§4)	× (§4)	<b>√</b> (§6)	<b>√</b> (§8)
MSO	× (§5)	<b>√</b> (§7)	✓	<b>√</b> (§8)	✓	<b>√</b> (§8)
SO	× (§5)	?	$\times$ (§8)	$\times$ (§8)	✓	<b>√</b> (§8)

Table 1: A comparison of SLR, MSO and SO in terms of expressiveness, where  $\checkmark$  means that the inclusion holds,  $\times$  means it does not and? denotes an open problem.

$$- \phi = \exists x . \psi$$
: by the inductive hypothesis, we obtain  $(\sigma, v[x \leftarrow u]) \models_{\Delta} \psi \iff (\sigma', h \circ (v[x \leftarrow u])) \models_{\Delta} \psi \iff (\sigma', (h \circ v)[x \leftarrow h(u)]) \models_{\Delta} \psi \iff (\sigma', h \circ v) \models_{\Delta} \exists x . \psi$ .

The other logic is *Second Order Logic* (SO) defined using a set of *second-order variables*  $\mathbb{V}^{(2)} = \{X, Y, \ldots\}$ , in addition to first-order variables. As usual, we denote by #X the arity of a second-order variable X. Terms and atoms are defined in the same way as in SLR. The formulæ of SO are defined by the following syntax:

$$\psi := \xi = \chi \mid \mathsf{R}(\xi_1, \dots, \xi_{\#\mathsf{R}}) \mid X(\xi_1, \dots, \xi_{\#X}) \mid \neg \psi \mid \psi \land \psi \mid \exists x . \psi \mid \exists X . \psi$$

As usual, we write  $\xi \neq \chi \stackrel{\text{def}}{=} \neg \xi = \chi$ ,  $\psi_1 \lor \psi_2 \stackrel{\text{def}}{=} \neg (\neg \psi_1 \land \neg \psi_2)$ ,  $\psi_1 \to \psi_2 \stackrel{\text{def}}{=} \neg \psi_1 \lor \psi_2$ ,  $\forall x . \psi \stackrel{\text{def}}{=} \neg \exists x . \neg \psi$  and  $\forall X . \psi \stackrel{\text{def}}{=} \neg \exists X . \neg \psi$ . We denote by MSO the fragment of SO restricted to using only second-order variables of arity one.

The semantics of SO is given by the relation  $(\sigma, \mathbf{v}) \Vdash \psi$ , where the store  $\mathbf{v} : \mathbb{V}^{(1)} \cup \mathbb{V}^{(2)} \to \mathbb{U} \cup \bigcup_{k \geq 1} \mathrm{pow}(\mathbb{U}^k)$  maps each first-order variable  $x \in \mathbb{V}^{(1)}$  to an element of the universe  $\mathbf{v}(x) \in \mathbb{U}$  and each second-order variable  $X \in \mathbb{V}^{(2)}$  to a relation  $\mathbf{v}(X) \subseteq \mathbb{U}^{\#X}$ . The satisfaction relation is defined inductively on the structure of formulæ:

$$(\sigma, \nu) \Vdash \xi = \chi \qquad \iff (\sigma, \nu)(\xi) = (\sigma, \nu)(\chi)$$

$$(\sigma, \nu) \Vdash R(\xi_1, \dots, \xi_{\#R}) \iff \langle (\sigma, \nu)(\xi_1), \dots, (\sigma, \nu)(\xi_{\#R}) \rangle \in \sigma(R)$$

$$(\sigma, \nu) \Vdash X(\xi_1, \dots, \xi_{\#X}) \iff \langle (\sigma, \nu)(\xi_1), \dots, (\sigma, \nu)(\xi_{\#X}) \rangle \in \nu(X)$$

$$(\sigma, \nu) \Vdash \neg \psi \qquad \iff (\sigma, \nu) \not\Vdash \psi$$

$$(\sigma, \nu) \Vdash \psi_1 \wedge \psi_2 \qquad \iff (\sigma, \nu) \Vdash \psi_i, \text{ for all } i = 1, 2$$

$$(\sigma, \nu) \Vdash \exists X \cdot \psi \qquad \iff (\sigma, \nu[X \leftarrow u]) \Vdash \psi, \text{ for some } u \in \mathbb{U}$$

$$(\sigma, \nu) \Vdash \exists X \cdot \psi \qquad \iff (\sigma, \nu[X \leftarrow u]) \Vdash \psi, \text{ for some } u \subseteq \mathbb{U}^{\#X}$$

We write  $\sigma \Vdash \phi$  whenever  $\phi$  is a sentence. A sentence  $\phi$  SO-*defines* a set of structures  $\mathcal{S}$  if and only if  $\sigma \Vdash \phi \iff \sigma \in \mathcal{S}$ . It is well-known (see e.g., [15]) that the sets of SO-defined structures are unions of equivalence classes of isomorphism (Def. 2).

In this paper we are concerned with the following definability problems:

**Definition 6.**  $SLR \subseteq (M)SO$ : Let  $\phi$  and  $\Delta$  be a SLR sentence and SID, respectively. Does there exist a (M)SO sentence  $\psi$  such that the family of structures SLR-defined by  $(\phi, \Delta)$  is also SO-defined by  $\psi$ ?

(M)SO  $\subseteq$  SLR: Let  $\psi$  be a (M)SO sentence. Does there exist a SLR sentence  $\phi$  and a SID  $\Delta$ , such that the family of structures SO-defined by  $\psi$  is SLR-defined by  $(\phi, \Delta)$ ?

Additionally, we consider the *treewidth-bounded* versions of the above problems:

**Definition 7.**  $SLR \subseteq^k (M)SO$ : Let  $\phi$  and  $\Delta$  be a SLR sentence and SID, respectively and  $k \ge 1$  be an integer. Does there exist a (M)SO sentence  $\psi$  such that the family of structures of treewidth at most k SLR-defined by  $(\phi, \Delta)$  is SO-defined by  $\psi$ ?

(M)SO  $\subseteq^k$  SLR: Let  $\psi$  be a (M)SO sentence and  $k \ge 1$  be an integer. Does there exist a SLR sentence  $\phi$  and an SID  $\Delta$ , such that the family of structures of treewidth at most k that is (M)SO-defined by  $\psi$  is SLR-defined by  $(\phi, \Delta)$ ?

For symmetry, we consider also the problems MSO  $\subseteq^{(k)}$  SO, SO  $\subseteq^{(k)}$  MSO. Table 1 summarizes our results, with references to the sections in the paper where the proofs (for the non-trivial ones) can be found, and the remaining open problems.

# 4 SLR $\not\subseteq^{(k)}$ MSO

We prove that SLR  $\not\subseteq^k$  MSO, by exhibiting an SLR-definable family of structures of treewidth k=1 that is not MSO-definable. Note that this also implies that SLR  $\not\subseteq$  MSO, in general.

The main idea is to encode words over a binary alphabet  $\mathcal{A} = \{a,b\}$  by lists (connected acyclic graphs in which each vertex has at most one incoming and at most one outgoing edge) whose vertices are labeled by symbols from  $\mathcal{A}$ . We encode a language L as a family of  $\mathcal{A}$ -labeled lists, using the intuitive encoding of a word  $w = a_1 \dots a_n$  by the structure  $\sigma_w$ , over the signature  $\{V, E, P_a, P_b, b, e\}$ , such that  $\sigma_w(V) = \{v_1, \dots, v_n\}$ ,  $\sigma_w(E) = \{(v_i, v_{i+1}) \mid i \in [1, n-1]\}$ ,  $\sigma_w(P_\alpha) = \{v_i \mid i \in [1, n], a_i = \alpha\}$ , for all  $\alpha \in \mathcal{A}$ ,  $\sigma_w(b) = v_1$  and  $\sigma_w(e) = v_n$ . Note that  $\operatorname{tw}(\sigma_w) = 1$ , for any word  $w \in \mathcal{A}^*$ .

A context-free grammar  $G = (N, X, \Delta)$  consists of a finite set N of nonterminals, a start symbol  $X \in N$  and a finite set  $\Delta$  of productions of the form  $\mathcal{Y} \to w$ , where  $\mathcal{Y} \in N$  and  $w \in (N \cup \mathcal{A})^*$ . Given finite strings  $u, v \in (N \cup \mathcal{A})^*$ , the relation  $u \rhd v$  replaces a nonterminal  $\mathcal{Y}$  of u by the right-hand side w of a production  $\mathcal{Y} \to w$  and  $\rhd^*$  denotes the reflexive and transitive closure of  $\rhd$ . The language of G is the set  $\mathcal{L}(G) \stackrel{\text{def}}{=} \{w \in \mathcal{A}^* \mid \mathcal{X} \rhd^* w\}$ . A language L is context-free if and only if there exists a context-free grammar G, such that  $L = \mathcal{L}(G)$ .

A language L is recognizable if and only if  $L=h^{-1}(C)$ , where  $C\subseteq \mathcal{M}$  and h is a monoid morphism between the monoid  $(\mathcal{A}^*,\cdot)$  of words with concatenation and a finite monoid  $(\mathcal{M},\odot)$ . It is known that a language is recognizable if and only if it is definable by an WS1S formula, i.e. an MSO formula over the signature  $\{\mathfrak{p}_a,\mathfrak{p}_b,\mathfrak{s}\}$ , where  $\mathfrak{p}_a$ ,  $\mathfrak{p}_b$  are unary predicates interpreted in every word w of length n as the subsets of [1,n] consisting of the positions in the word labeled by a and b, respectively and  $\mathfrak{s}$  is a function symbol interpreted in every word as the successor in  $\mathbb{N}$  (i.e.,  $\mathfrak{s}(n)=n+1$ ) (see e.g., [24] for a textbook presentation of this result). It is also well-known that every recognizable language is context-free but not viceversa e.g.,  $\{a^nb^n\mid n\in\mathbb{N}\}$  is context-free but not recognizable.

**Proposition 3.** Given a context-free grammar  $G = (N, X, \Delta)$ , there exists an SID  $\Delta_G$  and a binary predicate symbol  $A_X \in def(\Delta_G)$ , such that  $w \in \mathcal{L}(G) \iff \sigma_w \models_{\Delta_G} A_X(b,e)$ , for all  $w \in \mathcal{A}^*$ .

*Proof.* Assume w.l.o.g that the context-free grammar G does not produce the empty word and that it is in Greibach normal form i.e., contains only production rules of the form  $\mathcal{Y}_0 \to \alpha \mathcal{Y}_1 \dots \mathcal{Y}_i$ , where  $\mathcal{Y}_0, \dots, \mathcal{Y}_i \in N$ , for some  $i \geq 0$  and some  $\alpha \in \mathcal{A}$ . For

each nonterminal  $\mathcal{Y}$ , we consider a binary relation symbol  $A_{\mathcal{Y}}(x_1, x_2)$  and for each production rule as above, we consider a rule:

$$A_{\gamma_0}(x_1, x_2) \leftarrow \exists y_1 \dots \exists y_i . V(x_1) * P_{\alpha}(x_1) * E(x_1, y_1) * A_{\gamma_1}(y_1, y_2) * E(y_2, y_3) * \dots * E(y_{i-1}, y_i) * A_{\gamma_i}(y_i, x_2)$$

if  $i \ge 1$  and  $A_{\mathcal{J}_0}(x_1, x_2) \leftarrow V(x_1) * P_{\alpha}(x_1)$ , if i = 0. Let  $\Delta$  be the set of the rules above and let  $\mathcal{L}_{\mathcal{J}}(G) \stackrel{\text{def}}{=} \{w \in \mathcal{A}^* \mid \mathcal{J} \rhd^* w\}$ , for all  $\mathcal{J} \in N$ . Let  $w = a_1 \dots a_n \in \mathcal{A}^*$  be any word and  $\sigma_w$  be the structure over the signature  $\{V, E, P_a, P_b, b, e\}$ , such that  $\sigma_w(V) = \{v_1, \dots, v_n\}$ ,  $\sigma_w(E) = \{(v_j, v_{j+1}) \mid j \in [1, n-1]\}$ ,  $\sigma_w(P_{\alpha}) = \{v_j \mid j \in [1, n], \ a_j = \alpha\}$ , for all  $\alpha \in \mathcal{A}$ ,  $\sigma_w(b) = v_1$  and  $\sigma_w(e) = v_n$ . We prove that  $\mathcal{J} \rhd^* w \iff (\sigma_w, v) \models_{\Delta} A_{\mathcal{J}}(x, y)$ , for any word  $w \in \mathcal{A}^*$  and any nonterminal  $\mathcal{J} \in N$ , where v is any store such that  $v(x) = \sigma_w(b)$  and  $v(y) = \sigma_w(e)$ .

" $\Rightarrow$ " By induction on the length  $n \ge 1$  of the derivation of w from  $\mathcal{Y}$ . The base case n = 1 corresponds to a production rule  $\mathcal{Y} \to \alpha$  in G that yields the rule  $A_{\mathcal{Y}}(x_1, x_2) \leftarrow V(x_1) * P_{\alpha}(x_1)$  in  $\Delta$  and  $\sigma_{\alpha} \models_{\Delta} A_{\mathcal{Y}}(b, e)$  follows. For the inductive step n > 1, we assume w.l.o.g. that the derivation is ordered such that each nonterminal is fully expanded before another nonterminal from the same rule (every derivation of a context-free grammar can be reordered in this way). Let  $\mathcal{Y}_0 \to \alpha \mathcal{Y}_1 \dots \mathcal{Y}_i$  be the first rule of the derivation and let  $\mathcal{Y}_j \rhd^* w_j$  be the sub-derivations of  $\mathcal{Y}_1, \dots, \mathcal{Y}_i$ , respectively. Then  $w = \alpha w_1 \dots w_i$ . We can now choose structures  $\sigma_j$ , with  $0 \le j \le i$ , such that

- $\sigma_w = \sigma_0 \bullet \sigma_1 \bullet \cdots \bullet \sigma_i,$
- $\sigma_0$  is a structure with  $\sigma_0(V) = \{v_0\}$ ,  $\sigma_0(P_\alpha) = \{v_0\}$ ,  $\sigma_0(E) = \{(v_j, v_{j+1}) \mid j \in [0, n-1]\}$ ,  $\sigma_0(R) = \emptyset$ , for all  $R \notin \{V, P_\alpha, E\}$ ,  $\sigma_0(b) = v_0$  and  $\sigma_0(e) = v_n$  for some set of pairwise different nodes  $\{v_0, \dots, v_n\}$ .

We denote by  $\sigma'_j$ , for  $1 \le j \le i$ , the structure that is identical to  $\sigma_j$  except that we set  $\sigma'_j(b) = v_j$  and  $\sigma'_j(e) = v_{j+1}$ , where we set  $v_{n+1} = \sigma_w(e)$ . We recognize that  $\sigma'_j$  is isomorphic to  $\sigma_{w_j}$ . By the inductive hypothesis, we have  $\sigma_{w_j} \models_{\Delta} A_{\mathcal{I}_j}(b,e)$  for all  $1 \le j \le i$ . By Prop. 2 we get that  $\sigma'_j \models_{\Delta} A_{\mathcal{I}_j}(b,e)$ . Let v be a store with  $v(y_j) = v_j$  for all  $1 \le j \le i$ . We now recognize that

$$(\sigma_0 \bullet \sigma_1 \bullet \ldots \bullet \sigma_i, V) \models_{\alpha} V(b) * P_{\alpha}(b) * E(b, y_1) * A_{\gamma_i}(y_1, y_2) * E(y_2, y_3) * \ldots * E(y_{i-1}, y_i) * A_{\gamma_i}(y_i, e).$$

Hence,  $\sigma_w \models_{\Delta} A_{\gamma}(b, e)$ .

" $\Leftarrow$ " By induction on the definition of the satisfaction relation. In the base case, we have  $\sigma_{\alpha} \models V(b) * P_{\alpha}(b)$ , leading to  $\mathcal{Y} \rhd^* \alpha$ , for a rule  $\mathcal{Y} \to \alpha$  of G. For the inductive step, assume that

$$(\sigma_w, v) \models_{\Delta} V(b) * P_{\alpha}(b) * E(b, y_1) * A_{\gamma_1}(y_1, y_2) * E(y_2, y_3) * \dots * E(y_{i-1}, y_i) * A_{\gamma_i}(y_i, e)$$

for some store v with  $dom(v) = \{y_1, \dots, y_i\}$ , where  $A_{\mathcal{Y}_0}(x_1, x_2) \leftarrow \exists y_1 \dots \exists y_i \ . \ V(x_1) * P_{\alpha}(x_1) * E(x_1, y_1) * A_{\mathcal{Y}_1}(y_1, y_2) * E(y_2, y_3) * \dots * E(y_{i-1}, y_i) * A_{\mathcal{Y}_i}(y_i, x_2) \text{ is a rule of } \Delta, \text{ for some } i \geq 1. \text{ Then } G \text{ has a rule } \mathcal{Y} \rightarrow \alpha \mathcal{Y}_1 \dots \mathcal{Y}_i. \text{ Moreover, there exist structures } \sigma_j \text{ with } \sigma_0 \bullet \sigma_1 \bullet \dots \bullet \sigma_i = \sigma_w, \ (\sigma_0, v) \models V(b) * P_{\alpha}(b) * E(b, y_1) * E(y_2, y_3) * \dots * E(y_{i-1}, y_i), \ (\sigma_j, v) \models_{\Delta} A_{\mathcal{Y}_i}(y_j, y_{j+1}) \text{ for all } j \in [1, i-1] \text{ and } (\sigma_i, v) \models_{\Delta} A_{\mathcal{Y}_i}(y_i, e). \text{ Let } \sigma'_j \text{ be the } v \in \mathcal{Y}_i \cap \mathcal{Y}_i.$ 

structures that agree with  $\sigma_j$ , except that  $\sigma'_j(b) = v'(y_j)$ ,  $\sigma'_j(e) = v(y_{j+1})$ , for all  $j \in [1, i-1]$ , and  $\sigma'_i(e) = \sigma_w(e)$ . It is easy to show that there exist words  $w_1, \ldots, w_i$ , such that  $w = \alpha w_1 \ldots w_i$  and  $\sigma_{w_j} \simeq \sigma'_j$ , for all  $j \in [1, i]$ . By Prop. 2, we obtain  $\sigma_{w_j} \models_{\Delta} A_{\mathcal{I}_j}(b, e)$ , hence  $\mathcal{I}_j \rhd^* w_j$ , by the inductive hypothesis, thus leading to  $\mathcal{I}_j \rhd^* w_j$ .

Let L be a non-recognizable context-free language and suppose that there exists an MSO formula  $\phi_L$ , over the signature  $\{V, E, P_a, P_b, b, e\}$ , that defines the family  $\mathcal{S}_L \stackrel{\text{def}}{=} \{\sigma_w \mid w \in L\}$ . Then there exists also a WS1S formula  $\psi_L$  that defines L. Note that  $\psi_L$  can be obtained directly from  $\phi_L$  by replacing each atom  $E(\xi, \chi)$  by  $\mathfrak{s}(\xi) = \chi$  and each atom  $P_\alpha(\xi)$  by  $\mathfrak{p}_\alpha(\xi)$ . But then the language L is recognizable, which contradicts with the choice of L. Moreover, we have  $\{\operatorname{tw}(\sigma) \mid \sigma \in \mathcal{S}_L\} = \{1\}$ , proving that SLR  $\not\subseteq^k$  MSO, for any given  $k \geq 1$ .

### 5 MSO ⊈ SLR

We prove that the MSO-definable indexed family of cliques  $\{\mathcal{K}_u \mid n \in \mathbb{N}\}$  is not SLR-definable. Because MSO is a fragment of SO, this also implies SO  $\not\subseteq$  SLR. First, observe that  $\{\mathcal{K}_u \mid n \in \mathbb{N}\}$  is defined by the MSO formula  $\forall x \forall y$ .  $V(x) \land V(y) \land x \neq y \rightarrow E(x,y)$ . The definition of square grids in MSO is given in [12, §5.2.3]. As shown in Proposition 1, this family is strictly treewidth-unbounded. We prove that SLR cannot define strictly treewidth-unbounded families of structures, by showing the existence of an integer  $k \geq 1$ , depending only on  $\phi$  and  $\Delta$ , such that for each model of  $\phi$  there exists another model of  $\phi$  of greater or equal size and treewidth bounded by k (Proposition 4). This is a consequence of the fact that each SID can be transformed into an equivalent SID in which the variables that occur existentially quantified in the rules of  $\Delta$  are not constrained by equalities.

**Definition 8.** A rule  $A(x_1,...,x_{\#A}) \leftarrow \exists y_1...\exists y_n \ . \ \psi$ , where  $\psi$  is a quantifier-free formula, is normalized if and only if no equality atom x = y occurs in  $\psi$ , for distinct variables  $x, y \in \{x_1,...,x_{\#A}\} \cup \{y_1,...,y_n\}$ . An SID is normalized if and only if it contains only normalized rules.

**Lemma 1.** Given an SID  $\Delta$ , one can build a normalized SID  $\Delta'$  such that  $def(\Delta) \subseteq def(\Delta')$  and for each structure  $\sigma$  and each predicate atom  $A(\xi_1, \ldots, \xi_{\#A})$ , we have  $\sigma \models_{\Delta} \exists \xi_{i_1} \ldots \exists \xi_{i_n} . A(\xi_1, \ldots, \xi_{\#A}), \text{ where } \{\xi_{i_1}, \ldots, \xi_{i_n}\} = \{\xi_1, \ldots, \xi_{\#A}\} \cap \mathbb{V}^{(1)}$ .

*Proof.* Let  $\Delta$  be an SID. For each predicate  $A \in \text{def}(\Delta)$  and each partition  $\{I_1, \dots, I_k\}$  of [1, #A], we consider a fresh predicate  $A_{I_1, \dots, I_k}$  of arity  $k \ge 1$ , not in  $\text{def}(\Delta)$ . Let  $\Delta'$  be the SID obtained from  $\Delta$  by introducing, for each rule:

$$\mathsf{A}(x_1,\ldots,x_{\mathsf{\#A}}) \leftarrow \exists y_1 \ldots \exists y_m \ . \ \phi * \bigstar^h_{\ell=1} \mathsf{B}^\ell(z_{\ell,1},\ldots,z_{\ell,\mathsf{\#B}^\ell}) \in \Delta \tag{1}$$

where  $\phi$  is a quantifier- and predicate-free formula and for each equivalence relation  $\approx$  on the set of variables  $\{x_1, \dots, x_{\#A}\} \cup \{y_1, \dots, y_m\}$  that is compatible with all equalities

in  $\phi$  i.e., x = y occurs in  $\phi$  only if  $x \approx y$ , the following rules:

$$\mathsf{A}_{I_{1},...,I_{k}}(x_{1},...,x_{k}) \leftarrow \left(\exists y_{j_{1}} ... \exists y_{j_{n}} . \psi * \bigstar_{\ell=1}^{k} \mathsf{B}_{J_{1}^{\ell},...,J_{s^{\ell}}^{\ell}}^{\ell}(z_{r_{\ell,1}},...,z_{r_{\ell,s^{\ell}}})\right)$$
(2)  
$$[x_{i_{1}}/x_{1},...,x_{i_{k}}/x_{k}]$$

$$A(x_1,\ldots,x_{\#A}) \leftarrow A_{I_1,\ldots,I_k}(x_{i_1},\ldots,x_{i_k}) \tag{3}$$

where:

- ≈ induces the partitions  $\{I_1, ..., I_k\}$  of [1, #A] and  $\{J_1^{\ell}, ..., J_{s^{\ell}}^{\ell}\}$  of  $[1, \#B^{\ell}]$ , for each  $\ell \in [1, k]$ ,
- $x_{i_j}$  and  $z_{r_{\ell,s^\ell}}$  are the first in their  $\approx$ -equivalence classes, respectively, in the total order  $x_1 < \ldots < x_{\#A} < y_1 < \ldots < y_m$ ,
- $\psi$  is obtained from  $\phi$  by replacing each variable x, such that  $x \approx x_{i_j}$  with  $x_{i_j}$ , respectively each z, such that  $z \approx z_{r_{\ell,x^j}}$  with  $z_{r_{\ell,x^j}}$ , and removing the trivial equalities of the form x = x,
- the quantifier prefix  $\exists y_{j_1} \dots \exists y_{j_n}$  is the result of eliminating from  $\exists y_1 \dots \exists y_m$  the variables that do not occur in  $fv(\psi) \cup \bigcup_{\ell=1}^h \{z_{\ell,r_1}, \dots, z_{r_{\ell,\ell}}\}$ .

In particular, one can remove from  $\Delta'$  the rules containing unsatisfiable disequalities of the form  $x \neq x$ , obtained from the above transformations. We are left with proving the equivalence from the statement.

"\(\Rightarrow\)" Assume that  $(\sigma, v) \models_{\Delta} A(\xi_1, \dots, \xi_{\#A})$  for a store v, and let  $\approx$  be the equivalence relation over  $x_1 < \dots < x_{\#A}$  defined as  $\xi_i \approx \xi_j \iff (\sigma, v)(\xi_i) = (\sigma, v)(\xi_j)$ . We now prove by induction that  $(\sigma, v) \models_{\Delta} A(\xi_1, \dots, \xi_{\#A})$  implies  $(\sigma, v) \models_{\Delta'} A_{I_1, \dots, I_k}(\xi_{i_1}, \dots, \xi_{i_k})$ , where  $\{I_1, \dots, I_k\}$  are the partitions of [1, #A] induced by  $\approx$  and the  $\xi_{i_j}$  are minimal representatives of  $I_j$ . Since  $(\sigma, v) \models_{\Delta} A(\xi_1, \dots, \xi_{\#A})$ , there is a rule (1) in  $\Delta$ , a store v', that agrees with v over  $\xi_1, \dots, \xi_{\#A}$  and structures  $\sigma_0 \bullet \dots \bullet \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\Delta} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\sigma} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\sigma} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\sigma} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\sigma} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\sigma} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\sigma} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\sigma} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\sigma} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\sigma} \sigma_0 \circ \dots \circ \sigma_h = \sigma$ , such that  $(\sigma_0, v') \models_{\sigma}$ 

"\(\infty\)" Assume that  $(\sigma, v) \models_{\Delta'} A(\xi_1, \dots, \xi_{\#A})$ . Then, by a rule of type (3) from  $\Delta'$ , we must have  $(\sigma, v) \models_{\Delta'} A_{I_1, \dots, I_k}(\xi_{i_1}, \dots, \xi_{i_k})$ . We now prove by induction that  $(\sigma, v) \models_{\Delta'} A_{I_1, \dots, I_k}(\xi_{i_1}, \dots, \xi_{i_k})$  implies that  $(\sigma, v') \models_{\Delta} A(\xi_1, \dots, \xi_{\#A})$ , where v' is the store that maps each  $\xi_j \in \mathbb{V}^{(1)}$ , such that  $j \in I_j$ , into  $(\sigma, v)(\xi_{i_j})$ . Assume that  $(\sigma, v'') \models_{\Delta'} (\psi * \star^h_{\ell=1} \mathsf{B}^\ell_{J^\ell_1, \dots, J^\ell_{\xi'}_\ell}(z_{r_{\ell,1}}, \dots, z_{r_{\ell,\xi'}}))\overline{s}$ , by a rule of type (2), where v'' is a store that agrees with

v over  $\xi_{i_1}, \ldots, \xi_{i_k}$  and  $\overline{s} \stackrel{\text{def}}{=} [x_1/\xi_{i_1}, \ldots, x_k/\xi_{i_k}]$  is a substitution. Then there exists structures  $\sigma_0 \bullet \ldots \bullet \sigma_h = \sigma$ , such that  $(\sigma_0, \nu'') \models \psi \overline{s}$  and  $(\sigma_\ell, \nu'') \models_{\Delta'} \mathsf{B}^\ell_{J_1^\ell, \ldots, J_{s^\ell}}(z_{r_{\ell, 1}}, \ldots, z_{r_{\ell, s^\ell}})\overline{s}$ , for all  $\ell \in [1, h]$ . By the definition of  $\Delta'$ , there exists a rule of type (1) in  $\Delta$  and a corresponding equivalence relation  $\approx \operatorname{over} x_1 < \ldots < x_{\#A} < y_1 < \ldots < y_m$ , which induces the partitions  $\{I_1, \ldots, I_k\}$  of [1, #A] and  $\{J_1^\ell, \ldots, J_{s^\ell}^\ell\}$  of  $[1, \#B^\ell]$ , for each  $\ell \in [1, k]$ , and

 $x_{i_j}$  and  $z_{r_{\ell,s^\ell}}$  are the first in their  $\approx$ -equivalence classes. We can now choose a store v''', such that:

 $- (\sigma, \nu''')(\xi_j) = (\sigma, \nu'')(\xi_{i_j}), \text{ for all } j \in [1, k], \text{ and }$   $- (\sigma, \nu''')(z_j \overline{s}) = (\sigma, \nu'')(z_{r_{\ell,q}} \overline{s}) \text{ if } j \in J_q^\ell, \text{ for all } \ell \in [1, h] \text{ and } q \in [1, s^\ell].$ By the definition of  $\psi$ , we have  $(\sigma_0, \nu''') \models \phi$ . By the inductive hypothesis, we obtain

By the definition of  $\psi$ , we have  $(\sigma_0, v''') \models \phi$ . By the inductive hypothesis, we obtain  $(\sigma_\ell, v''') \models_{\Delta} B^\ell(z_{\ell,1}, \dots, z_{\ell,\#B^\ell})$ , for all  $\ell \in [1, h]$ . Hence  $(\sigma, v''') \models_{\Delta} A(\xi_1, \dots, \xi_{\#A})$ , by a rule of type (1).

A consequence of the above result is that, in the absence of equality constraints in a normalized SID, each existentially quantified variable instantiated by the inductive definition of the satisfaction relation can be assigned a distinct element of the universe. We write  $(\sigma, v) \models_{\Delta}^{U} \phi$  if and only if the satisfaction relation  $(\sigma, v) \models_{\Delta} \phi$  can be established by considering stores that are injective over the interpretation of existentially quantified variables and map these variables into elements from an infinite set  $U \subseteq \mathbb{U}$ . More precisely, the inductive definition of  $\models_{\Delta}^{U}$  is the same as the definition of  $\models_{\Delta}$ , except for the following cases:

$$(\sigma, \mathsf{v}) \models^U_\Delta \quad \phi_1 * \phi_2 \iff \text{there exist structures } \sigma_1 \bullet \sigma_2 = \sigma \text{ and infinite sets} \\ U_1 \cap U_2 = \emptyset, \ U_1 \cup U_2 \subseteq U, \text{ such that } (\sigma_i, \mathsf{v}) \models^{U_i}_\Delta \ \phi_i, \\ \text{for all } i = 1, 2 \\ (\sigma, \mathsf{v}) \models^U_\Delta \quad \exists x \ . \ \phi \iff (\sigma, \mathsf{v}[x \leftarrow u]) \models_\Delta \phi, \text{ for some } u \in U \setminus \mathsf{v}(\mathsf{fv}(\phi) \setminus \{x\})$$

**Lemma 2.** Given a normalized SID  $\Delta$ , a predicate atom  $A(\xi_1, ..., \xi_{\#A})$  and an infinite set  $U \subseteq \mathbb{U}$ , for each structure-store pair  $(\sigma, v)$ , such that  $(\sigma, v) \models_{\Delta} A(\xi_1, ..., \xi_{\#A})$ , there exists a structure  $\sigma'$ , such that  $(\sigma', v) \models_{\Delta} A(\xi_1, ..., \xi_{\#A})$  and  $\|Dom(\sigma)\| \leq \|Dom(\sigma')\|$ .

*Proof.* The structure  $\sigma'$  is built inductively on the definition of the satisfaction relation  $(\sigma, v) \models_{\Delta} A(x_1, \dots, x_{\#A})$ . Since no existentially quantified variable is constrained by equality during this derivation, one can use the definition of  $\models^U_{\Delta}$  instead, thus ensuring that  $(\sigma', v) \models^U_{\Delta} A(x_1, \dots, x_{\#A})$ . Moreover, since the values of all existentially quantified variables are pairwise distinct in  $\sigma'$ , it follows that  $\|\mathrm{Dom}(\sigma)\| \leq \|\mathrm{Dom}(\sigma')\|$ .

We show that the models defined on injective stores have bounded treewidth:

**Lemma 3.** Given a normalized SID  $\Delta$  and a predicate atom  $A(\xi_1, \ldots, \xi_{\#A})$ , we have  $tw(\sigma) \leq k$ , for each structure-store pair  $(\sigma, v)$  such that  $(\sigma, v) \models_{\Delta}^{U} A(\xi_1, \ldots, \xi_{\#A})$ , for some infinite set  $U \subseteq \mathbb{U}$ , where  $k \geq 1$  is a constant depending only on  $\Delta$ .

*Proof.* Let k be the maximal number of variables that occurs free or bound in the right-hand side of a rule from  $\Delta$ . Given an infinite set  $U \subseteq \mathbb{U}$ , we build a tree decomposition  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$  of  $\sigma$ , inductively on the definition of the satisfaction relation  $(\sigma, v) \models_{\Delta}^{U} A(\xi_{1}, \ldots, \xi_{\#A})$ , such that  $\bigcup_{n \in \mathcal{N}} \lambda(n) \subseteq U \cup \{(\sigma, v)(\xi_{1}), \ldots, (\sigma, v)(\xi_{\#A})\}$ . Assume that  $(\sigma, v) \models_{\Delta}^{U} A(\xi_{1}, \ldots, \xi_{\#A})$  is the consequence of a rule  $A(x_{1}, \ldots, x_{\#A}) \leftarrow \exists y_{1} \ldots \exists y_{m} \ . \ \psi * * \underset{\ell=1}{k} B_{\ell}(z_{1}^{\ell}, \ldots, z_{\#B_{\ell}}^{\ell})$  from  $\Delta$ , where  $\psi$  is a quantifier- and predicate-free formula, such that:

$$(\sigma, \mathbf{v}') \models^{U}_{\Delta} \exists y_{1} \dots \exists y_{m} . \psi * * \underset{\ell=1}{k} \mathsf{B}_{\ell}(z_{1}^{\ell}, \dots, z_{\mathsf{\#B}_{\ell}}^{\ell})$$

where  $\mathbf{v}'$  is the store that maps  $x_i$  into  $\mathbf{v}(\xi_i)$ , for all  $i \in [1, \#A]$ . Then there exists a store  $\mathbf{v}''$  that agrees with  $\mathbf{v}'$  over  $x_1, \ldots, x_{\#A}$ , such that  $\mathbf{v}''(y_1), \ldots, \mathbf{v}''(y_m) \in U$  are pairwise distinct, and structures  $\sigma_0 \bullet \sigma_1 \bullet \ldots \bullet \sigma_k = \sigma$ , such that  $(\sigma_0, \mathbf{v}'') \models \psi$  and  $(\sigma_\ell, \mathbf{v}'') \models_{\Delta}^{U_\ell} \mathsf{B}_\ell(z_1^\ell, \ldots, z_{\#B_\ell}^\ell)$ , for all  $\ell \in [1, k]$ , where  $U_1, \ldots, U_k$  is a partition of U into infinite sets. Note that, because U is infinite, such a partition always exists. By the inductive hypothesis, there exists a tree decomposition  $\mathcal{T}_\ell = (\mathcal{N}_\ell, \mathcal{F}_\ell, r_\ell, \lambda_\ell)$  of  $\sigma_\ell$ , such that  $\mathsf{tw}(\mathcal{T}_\ell) \leq k$  and  $\bigcup_{n \in \mathcal{N}_\ell} \lambda_\ell(n) \subseteq U_\ell \cup \{\mathbf{v}''(z_1^\ell), \ldots, \mathbf{v}''(z_{\#B_\ell}^\ell)\}$ , for each  $\ell \in [1, k]$ .

We define the tree decomposition  $\mathcal{T}=(\mathcal{N},\mathcal{F},r,\lambda)$  such that the subtrees rooted in the children of the root are  $\mathcal{T}_1,\ldots,\mathcal{T}_k$  and  $\lambda(r)=\{\mathbf{v}''(x_1),\ldots,\mathbf{v}''(x_{\mathsf{HA}})\}\cup\{\mathbf{v}''(y_1),\ldots,\mathbf{v}''(y_m)\}$ . Then, for each relation atom  $\mathsf{R}(z_1,\ldots,z_{\mathsf{HR}})$  that occurs in  $\psi$ , the set  $\{\mathbf{v}''(z_1),\ldots,\mathbf{v}''(z_{\mathsf{HR}})\}$  is a subset of the label of the root, thus fulfilling point (1) of Def. 4. To check point (2) of Def. 4, let  $u\in\lambda_i(n_i)\cap\lambda_j(n_j)$ , where  $n_i\in\mathcal{N}_i$  and  $n_j\in\mathcal{N}_j$ , for some  $1\leq i< j\leq k$ . Since  $(\sigma_i,\mathbf{v}'')\models^{U_i}_{\Delta}$   $\mathsf{B}_i(z_1^i,\ldots,z_{\mathsf{HB}_i}^i)$ ,  $(\sigma_j,\mathbf{v}'')\models^{U_j}_{\Delta}$   $\mathsf{B}_j(z_1^j,\ldots,z_{\mathsf{HB}_j}^j)$  and  $U_i\cap U_j=\emptyset$ , we obtain that u is not the image of an existentially quantified variable via  $\mathbf{v}''$ , hence  $u=\mathbf{v}''(z)$ , for some  $z\in\{z_1^i,\ldots,z_{\mathsf{HB}_i}^i\}\cap\{z_1^j,\ldots,z_{\mathsf{HB}_j}^j\}\subseteq\{\xi_1,\ldots,\xi_{\mathsf{HA}}\}\cup\{y_1,\ldots,y_m\}$ . Then  $u\in\lambda(r)$ , thus fulfilling point (2) of Def. 4.

The proof of MSO  $\not\subseteq$  SLR relies on the following result:

**Proposition 4.** Given an SID  $\Delta$  and a SLR sentence  $\phi$ , the family  $\{\sigma \mid \sigma \models_{\Delta} \phi\}$  is either finite or it has an infinite subfamily of bounded treewidth.

*Proof.* Given a sentence  $\phi$ , we introduce a fresh predicate  $A_{\phi}$  of arity zero and consider the rule  $A_{\phi}() \leftarrow \phi$ . Then, for each structure  $\sigma$ , we have  $\sigma \models_{\Delta} \phi$  if and only if  $\sigma \models_{\Delta_{\phi}} A_{\phi}()$ , where  $\Delta_{\phi} \stackrel{\text{def}}{=} \Delta \cup \{A_{\phi}() \leftarrow \phi\}$ . Let  $\Delta_{\phi}'$  be the normalized SID, such that  $\sigma \models_{\Delta_{\phi}'} A_{\phi}()$ , by Lemma 1. Given an infinite subset U of  $\mathbb{U}$ , there exists a structure  $\sigma'$ , such that  $\sigma' \models_{\Delta_{\phi}'}^U A_{\phi}()$  and  $\|\text{Dom}(\sigma)\| \leq \|\text{Dom}(\sigma')\|$ , by Lemma 2. By Lemma 3, we also obtain  $\text{tw}(\sigma') \leq k$ , where k depends only of  $\Delta_{\phi}'$  and hence of  $\Delta$  and  $\phi$ . If  $A_{\phi}()$  has finitely many models, there is nothing to prove. Otherwise, consider an infinite sequence  $\sigma_1, \sigma_2, \ldots$  of models of  $A_{\phi}()$ , such that  $\|\text{Dom}(\sigma_i)\| < \|\text{Dom}(\sigma_{i+1})\|$ , for all  $i \geq 1$ . Then there exists a sequence of models  $\sigma_1', \sigma_2', \ldots$  of  $A_{\phi}()$ , such that  $\|\text{Dom}(\sigma_i)\| \leq \|\text{Dom}(\sigma_i')\|$  and  $\text{tw}(\sigma_i') \leq k$ , for all  $i \geq 1$ . By going to a subsequence, if necessary, one can retrieve an infinite treewidth-bounded family of models of  $\phi$ .

### **6** SLR ⊂ SO

Since SLR and MSO have incomparable expressivities (at least on unbounded sets of structures), it is natural to ask for a logic that subsumes them both. In this section, we prove that SO is such a logic. Since MSO is a syntactic subset of SO, we have MSO  $\subseteq$  SO trivially.

In the rest of this section, we show that  $SLR \subseteq SO$ , using the fact that each model of a predicate atom in SLR is built according to an *unfolding tree* indicating the partial order in which the rules of the SID are used in the inductive definition of the satisfaction relation<sup>2</sup>. More precisely, the model can be decomposed into pairwise disjoint

<sup>&</sup>lt;sup>2</sup> Unfolding trees are for SIDs what derivation trees are for context-free grammars.

substructures, each being the model of the quantifier- and predicate-free subformula of a rule in the SID, such that there is a one-to-one mapping between the nodes of the tree and the decomposition of the model. We use second-order variables to define the unfolding tree and the mapping between the nodes of the unfolding tree and the tuples in the interpretation of the relation symbols from the model. Finally, these second-order variables are existentially quantified and the resulting SO formula describes the model alone, without the unfolding tree that witnesses its decomposition according to the rules of the SID.

In the following, let  $\Sigma \stackrel{\text{def}}{=} \{R_1, \dots, R_N, c_1, \dots, c_M\}$  be the signature of SLR and let  $\Delta \stackrel{\text{def}}{=} \{r_1, \dots, r_R\}$  be a given SID. Without loss of generality, for each relation symbol  $R_i \in \Sigma$ , we assume that there is at most one occurrence of a relation atom  $R_i(y_1, \dots, y_{\#R_i})$  in each rule from  $\Delta$ . If this is not the case, we split the rule by introducing a new predicate symbol for each relation atom with relation symbol  $R_i$ , until the condition is satisfied.

We define unfolding trees formally. For a tree  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$  and a vertex  $n \in \mathcal{N}$ , we denote by  $\mathcal{T}\downarrow_n$  the subtree of  $\mathcal{T}$  whose root is n. For a quantifier- and predicate-free formula  $\phi$ , we denote by  $\phi^n$  the formula in which every relation atom  $R(x_1, \ldots, x_{\#R})$  is annotated as  $R^n(x_1, \ldots, x_{\#R})$ . Atoms  $R^n(x_1, \ldots, x_{\#R})$  (and consequently formulas  $\phi^n$ ) have the same semantics as atoms  $R(x_1, \ldots, x_{\#R})$  (resp. formulas  $\phi$ ); the annotations  $x_n$ 0 purely serve as explanatory devices in our construction (see the proof of Proposition 5) by tracking the node of the unfolding tree where a given relation atom is introduced.

**Definition 9.** An unfolding tree for a predicate atom  $A(\xi_1, ..., \xi_{\#A})$  is a tree  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$  with labeling mapping  $\lambda : \mathcal{N} \to \Delta$ , such that  $\lambda(r) \in def_{\Delta}(A)$  and, for each vertex  $n \in \mathcal{N}$ , if  $B_1(z_{1,1}, ..., z_{1,\#B_1}), ..., B_h(z_{h,1}, ..., z_{h,\#B_h})$  are the predicate atoms that occur in  $\lambda(n)$ , then  $p_1, ..., p_h$  are the children of n in  $\mathcal{T}$ , such that  $\lambda(p_\ell) \in def_{\Delta}(B_\ell)$ , for all  $\ell \in [1,h]$ .

An unfolding tree  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$  for a predicate atom  $A(\xi_1, \dots, \xi_{\#A})$  gives rise to a predicate-free formula defined inductively as follows:

$$\Theta(\mathcal{T},\mathsf{A}(\xi_1,\ldots,\xi_{\text{\#A}})) \stackrel{\mathsf{def}}{=}$$

$$\left(\exists y_1 \ldots \exists y_m \ . \ \psi^r * \bigstar^h_{\ell=1} \Theta(\mathcal{T} \downarrow_{p_\ell}, \mathsf{B}_\ell(z_{\ell,1}, \ldots, z_{\ell, \#\mathsf{B}_\ell}))\right) [x_1/\xi_1, \ldots, x_{\#\mathsf{A}}/\xi_{\#\mathsf{A}}],$$

where  $\lambda(r) = A(x_1, \dots, x_{\#A}) \leftarrow \exists y_1 \dots \exists y_m . \ \psi * \bigstar_{\ell=1}^h B_\ell(z_{\ell,1}, \dots, z_{\ell,\#B_\ell})$ , for a quantifierand predicate-free formula  $\psi$ ,  $p_1, \dots, p_h$  are the children of the root r in  $\mathcal{T}$ , corresponding to the predicate atoms  $B_1(z_{1,1}, \dots, z_{1,\#B_1}), \dots, B_h(z_{h,1}, \dots, z_{h,\#B_h})$ , respectively.

The unfolding trees of a predicate atom describe the set of models of that predicate atom. The following lemma is standard and we include it for self-containment reasons:

**Lemma 4.** For any structure-store pair 
$$(\sigma, v)$$
, we have  $(\sigma, v) \models_{\Delta} A(\xi_1, ..., \xi_{\#A}) \iff (\sigma, v) \models_{\Theta} (\mathcal{T}, A(\xi_1, ..., \xi_{\#A}))$ , where  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$  is an unfolding tree for  $A(\xi_1, ..., \xi_{\#A})$ .

*Proof.* (We omit the annotations  $\cdot^n$ , as in  $\phi^n$ , in this proof and simply write  $\phi$  because the annotations are not relevant for this proof.)

" $\Rightarrow$ " By induction on the definition of the satisfaction relation  $(\sigma, \nu) \models_{\Delta} A(\xi_1, \dots, \xi_{\#A})$ . Assume the relation holds because:

$$(\sigma, \mathbf{v}') \models_{\Delta} \psi \overline{s} * \star_{\ell=1}^{h} \mathsf{B}_{\ell}(z_{\ell,1}, \dots, z_{\ell, \# \mathsf{B}_{\ell}}) \overline{s}$$

for a rule  $\mathbf{r}: \mathsf{A}(x_1,\ldots,x_{\#\mathsf{A}}) \leftarrow \exists y_1\ldots\exists y_m \ .\ \psi* * \bigwedge_{\ell=1}^h \mathsf{B}_\ell(z_{\ell,1},\ldots,z_{\ell,\#\mathsf{B}_\ell})$  from  $\Delta$ , where  $\psi$  is a quantifier- and predicate-free formula,  $\overline{s} \stackrel{\text{def}}{=} [x_1/\xi_1,\ldots,x_{\#\mathsf{A}}/\xi_{\#\mathsf{A}}]$  is a substitution and  $\mathbf{v}'$  is a store that agrees with  $\mathbf{v}$  over  $\{\xi_1,\ldots,\xi_{\#\mathsf{A}}\}\cap \mathbb{V}^{(1)}$ . Then there exist structures  $\sigma_0\bullet\sigma_1\bullet\ldots\bullet\sigma_h=\sigma$ , such that  $(\sigma_0,\mathbf{v}')\models\psi\overline{s}$  and  $(\sigma_\ell,\mathbf{v}')\models_\Delta\mathsf{B}_\ell(z_{\ell,1},\ldots,z_{\ell,\#\mathsf{B}_\ell})\overline{s}$ , for all  $\ell\in[1,h]$ . By the induction hypothesis, there exist unfolding trees  $\mathcal{T}_\ell=(\mathcal{N}_\ell,\mathcal{F}_\ell,r_\ell,\lambda_\ell)$  for  $\mathsf{B}_\ell(z_{\ell,1},\ldots,z_{\ell,\#\mathsf{B}_\ell})\overline{s}$ , such that  $(\sigma_\ell,\mathbf{v}')\models_\Delta\mathsf{\Theta}(\mathcal{T}_\ell,\mathsf{B}_\ell(z_{\ell,1},\ldots,z_{\ell,\#\mathsf{B}_\ell})\overline{s})$ , for all  $\ell\in[1,h]$ . Then  $\mathcal{T}=(\mathcal{N},\mathcal{F},r,\lambda)$  is defined as  $\mathcal{N}\stackrel{\text{def}}{=} \{r\}\cup\bigcup_{\ell=1}^h \mathcal{N}_\ell,\mathcal{F}\stackrel{\text{def}}{=} \{(r,r_\ell)\mid\ell\in[1,h]\}\cup\bigcup_{\ell=1}^h \mathcal{F}_\ell$  and  $\lambda=\{(r,r)\}\cup\bigcup_{\ell=1}^h \lambda_\ell$ , assuming w.l.o.g. that  $\mathcal{N}_\ell\cap\mathcal{N}_k=\emptyset$ , for all  $1\leq\ell< k\leq h$  and  $r\not\in\bigcup_{\ell=1}^h \mathcal{N}_\ell$ . The check that  $(\sigma,\mathbf{v})\models\mathsf{\Theta}(\mathcal{T},\mathsf{A}(\xi_1,\ldots,\xi_{\#\mathsf{A}}))$  is routine. " $\Leftarrow$ " By induction on the structure of  $\mathcal{T}$ . Let  $p_1,\ldots,p_h$  be the children of r in  $\mathcal{T}$ . By Def. 9, we have:

$$(\sigma, \mathbf{v}') \models \psi \overline{s} * \bigstar_{\ell=1}^h \Theta(\mathcal{T}\downarrow_{p_{\ell}}, \mathsf{B}_{\ell}(z_{\ell,1}, \dots, z_{\ell, \#\mathsf{B}_{\ell}})) \overline{s}$$

where  $\overline{s} \stackrel{\text{def}}{=} [x_1/\xi_1, \dots, x_{\#A}/\xi_{\#A}]$  is a substitution,  $\mathbf{v}'$  is a store that agrees with  $\mathbf{v}$  over  $\{\xi_1, \dots, \xi_{\#A}\} \cap \mathbb{V}^{(1)}$  and  $\lambda(r) = \mathsf{A}(x_1, \dots, x_{\#A}) \leftarrow \exists y_1 \dots \exists y_m \ . \ \psi * \bigstar_{\ell=1}^h \mathsf{B}_\ell(z_{\ell,1}, \dots, z_{\ell,\#B_\ell})$  is a rule from  $\Delta$ . Then there exist structures  $\sigma_0 \bullet \sigma_1 \bullet \dots \bullet \sigma_h = \sigma$ , such that  $(\sigma_0, \mathbf{v}') \models \psi \overline{s}$  and  $(\sigma_\ell, \mathbf{v}') \models \Theta(\mathcal{T}_{\downarrow p_\ell}, \mathsf{B}_\ell(z_{\ell,1}, \dots, z_{\ell,\#B_\ell}))\overline{s}$ , for all  $\ell \in [1, h]$ . Since  $\mathcal{T}_{\downarrow p_\ell}$  is an unfolding tree for  $\mathsf{B}_\ell(z_{\ell,1}, \dots, z_{\ell,\#B_\ell})\overline{s}$ , by the inductive hypothesis, we obtain  $(\sigma_\ell, \mathbf{v}') \models_{\Delta} \mathsf{B}_\ell(z_{\ell,1}, \dots, z_{\ell,\#B_\ell})\overline{s}$ , for all  $\ell \in [1, h]$ . Then, we have  $(\sigma, \mathbf{v}') \models_{\Delta} \psi \overline{s} * \bigstar_{\ell=1}^h \mathsf{B}_\ell(z_{\ell,1}, \dots, z_{\ell,\#B_\ell})\overline{s}$ , leading to  $(\sigma, \mathbf{v}) \models_{\Delta} \mathsf{A}(\xi_1, \dots, \xi_{\#A})$ .

To build a SO formula that defines the models of a SLR sentence  $\phi$ , we first add a rule  $A_{\phi}() \leftarrow \phi$  to  $\Delta$  and describe a formula that asserts the existence of an unfolding tree for  $A_{\phi}()$  in the SID  $\Delta_{\phi} \stackrel{\text{def}}{=} \Delta \cup \{A_{\phi}() \leftarrow \phi\}$ . Let P be the maximum number of occurrences of predicate atoms in a rule from  $\Delta_{\phi}$ . We use second-order variables  $Y_1, \ldots, Y_P$  of arity 2, for the edges of the tree and  $X_1, \ldots, X_R$  of arity 1, for the labels of the nodes in the tree i.e., the rules of  $\Delta$ . Then the SO formula  $\mathfrak{T}(x, \{X_i\}_{i=1}^R, \{Y_j\}_{j=1}^P)$  is defined as the conjunction of SO formulæ that describe the following facts:

- 1. the root x belongs to  $X_i$ , for some rule  $r_i$  that defines the predicate  $A_{\phi}$ ,
- 2. the sets  $X_1, \ldots, X_R$  are pairwise disjoint,
- 3. each vertex in  $X_1 \cup ... \cup X_R$  is reachable from x by a path of edges  $Y_1, ..., Y_P$ ,
- 4. each vertex in  $X_1 \cup ... \cup X_R$ , except for x, has exactly one incoming edge and x has no incoming edge,
- 5. each vertex from  $X_i$  has exactly h outgoing edges  $Y_1, \ldots, Y_h$ , each to a vertex from  $X_{j_\ell}$ , respectively, such that  $\mathsf{r}_{j_\ell}$  defines the predicate  $\mathsf{B}_\ell$ , for all  $\ell \in [1,h]$ , where  $\mathsf{B}_1(z_{1,1},\ldots,z_{1,\#\mathsf{B}_1}),\ldots,\mathsf{B}_h(z_{h,1},\ldots,z_{h,\#\mathsf{B}_h})$  are the predicate atoms that occur in  $\mathsf{r}_i$ .

We now state a SO formula  $\mathfrak{F}(\xi_1,\ldots,\xi_{\mathtt{\#A}},x,\{X_i\}_{i=1}^R,\{Y_j\}_{j=1}^P,\{\{Z_{k,\ell}\}_{\ell=1}^{\mathtt{\#R}_k}\}_{k=1}^N)$  that fixes the relationship between the unfolding tree  $\mathcal{T}$  and the relations  $\sigma(\mathsf{R}_i)$ . We recall that by construction for every node n of  $\mathcal{T}$  and every relation atom  $\mathsf{R}$  there is at most one annotated relation atom  $\mathsf{R}_k^n(\xi_1,\ldots,\xi_{\mathtt{\#R}_i})$  in  $\Theta(\mathcal{T},\mathsf{A}(\xi_1,\ldots,\xi_{\mathtt{\#A}}))$ . The formula  $\mathfrak{F}$  now uses second-order variables  $Z_{k,\ell}$ , of arity 2, in order to encode (partial) functions mapping a tree vertex n to the value of  $\xi_\ell$  for the (unique) annotated atom  $\mathsf{R}_k^n(\xi_1,\ldots,\xi_{\mathtt{\#R}_i})$  (in case such an atom exists). The formula  $\mathfrak{F}$  is the conjunction of following SO-definable facts:

(i) each second-order variable  $Z_{k,\ell}$  denotes a functional binary relation:

$$\bigwedge_{k \in [1,N]} \bigwedge_{\ell \in [1,\#\mathsf{R}_k]} \forall y \forall z \forall z' \ . \ Z_{k,\ell}(y,z) \wedge Z_{k,\ell}(y,z') \to z = z'$$

(ii) for each relation atom with relation symbol  $R_k$  that occurs in a rule  $r_i$ , the  $R_k$ -relation contains a tuple:

$$\bigwedge_{i \in [1,R]} \bigwedge_{\mathsf{R}_k \text{ occurs in } \mathsf{r}_i} \forall y . X_i(y) \to \exists z_1 \dots \exists z_{\mathsf{\#R}_k} . \mathsf{R}_k(z_1,\dots,z_{\mathsf{\#R}_k}) \land \bigwedge_{\ell \in [1,\mathsf{\#R}_k]} Z_{k,\ell}(y,z_\ell)$$

(iii) for any two (not necessarily distinct) rules  $r_i$  and  $r_j$  such that an atom with relation symbol  $R_k$  occurs in both, the tuples introduced by the two atoms are distinct:

$$\bigwedge_{i,j\in[1,R]} \bigwedge_{\mathsf{R}_k \text{ occurs in } \mathsf{r}_i,\mathsf{r}_j} \forall y \forall y' \forall z_1 \forall z'_1 \dots \forall z_{\mathsf{\#R}_k} \forall z'_{\mathsf{\#R}_k} .$$

$$\left( X_i(y) \wedge X_j(y') \wedge \bigwedge_{\ell\in[1,\mathsf{\#R}_k]} (Z_{k,\ell}(y,z_\ell) \wedge Z_{k,\ell}(y',z'_\ell)) \right) \to \bigvee_{\ell\in[1,\mathsf{\#R}_k]} z_\ell \neq z'_\ell$$

(iv) each tuple from a  $R_k$ -relation must have been introduced by a relation atom with relation symbol  $R_k$  that occurs in a rule  $r_i$ :

$$\bigwedge_{k \in [1,N]} \forall z_1 \ldots \forall z_{\#\mathsf{R}_k} \ . \ \mathsf{R}_k(z_1,\ldots,z_{\#\mathsf{R}_k}) \to \exists y \ . \bigvee_{\mathsf{R}_k \ \text{occurs in } \mathsf{r}_i} \left( X_i(y) \ \land \bigwedge_{\ell \in [1,\#\mathsf{R}_k]} Z_{k,\ell}(y,z_\ell) \right)$$

(v) two terms  $\xi_m$  and  $\chi_n$  that occur within two relation atoms  $R_k(\xi_1, ..., \xi_{\#R_k})$  and  $R_\ell(\chi_1, ..., \chi_{\#R_\ell})$  within rules  $r_i$  and  $r_j$ , respectively, and are constrained to be equal (i.e., via equalities and parameter passing), must be equated:

The formula  $isEq_{k,\ell,m,n}(y,y',\{X_i\}_{i=1}^R,\{Y_j\}_{j=1}^P)$  asserts that there is a path in the unfolding tree between the store values (i.e., vertices of the tree) of y and y', such that the m-th and n-th variables of the relation atoms  $\mathsf{R}_k(z_1,\ldots,z_{\mathsf{HR}_k})$  and  $\mathsf{R}_\ell(z_1',\ldots,z_{\mathsf{HR}_\ell}')$  are bound to the same value.

(vi) a disequality  $\xi \neq \chi$  that occurs in a rule  $r_i$  is propagated throughout the tree to each pair of variables that occur within two relation atoms  $R_k(\xi_1, \dots, \xi_{\#R_k})$  and  $R_\ell(\chi_1, \dots, \chi_{\#R_\ell})$  in rules  $r_{j_k}$  and  $r_{j_\ell}$ , respectively, such that  $\xi$  is bound  $\xi_r$  and  $\chi$  to  $\chi_s$  by equality atoms and parameter passing:

$$\begin{split} & \bigwedge_{\substack{\mathsf{R}_{\ell} \text{ occurs in } r_{i} \\ \mathsf{R}_{\ell} \text{ occurs in } r_{j_{k}} \\ \mathsf{R}_{\ell} \text{ occurs in } r_{j_{\ell}} \\ & \left(X_{i}(y) \wedge X_{j_{k}}(y') \wedge X_{j_{\ell}}(y'') \wedge Z_{k,r}(y',z') \wedge Z_{\ell,s}(y'',z'') \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{k}}(y') \wedge X_{j_{\ell}}(y''') \wedge Z_{k,r}(y',z') \wedge Z_{\ell,s}(y'',z'') \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{k}}(y') \wedge X_{j_{\ell}}(y''') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{k}}(y') \wedge X_{j_{\ell}}(y''') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{k}}(y') \wedge X_{j_{\ell}}(y''') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{k}}(y') \wedge X_{j_{\ell}}(y''') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right) \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{k}}(y') \wedge X_{j_{\ell}}(y''') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right) \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{k}}(y') \wedge X_{j_{\ell}}(y''') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right) \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{k}}(y') \wedge X_{j_{\ell}}(y''') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right) \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{k}}(y') \wedge X_{j_{\ell}}(y'') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right) \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{k}}(y'') \wedge X_{j_{\ell}}(y''') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right) \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{\ell}}(y'') \wedge X_{j_{\ell}}(y'') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right) \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{\ell}}(y'') \wedge X_{j_{\ell}}(y'') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right. \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{\ell}}(y'') \wedge X_{j_{\ell}}(y'') \wedge Z_{k,r}(y',z'') \wedge Z_{\ell,s}(y'',z'') \right. \right. \\ & \left. \left(X_{i}(y) \wedge X_{j_{\ell}}(y'') \wedge X_{i}(y'',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \right. \right. \\ & \left. \left(X_{i}(y) \wedge X_{i}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \right. \right. \\ & \left. \left(X_{i}(y) \wedge X_{i}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \right) \right. \\ & \left. \left(X_{i}(y) \wedge X_{i}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \right. \right. \\ & \left. \left(X_{i}(y) \wedge X_{i}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \right. \right. \\ & \left. \left(X_{i}(y) \wedge X_{i}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \wedge Z_{k,r}(y',z'') \right. \right. \\ & \left. \left(X_{i}(y) \wedge X_{i$$

The formula  $varEq_{\xi,k,r}(x,y,\{X_i\}_{i=1}^R,\{Y_j\}_{j=1}^P)$  states that the variable  $\xi$  occurring in the label of the unfolding tree vertex x is bound to the variable  $z_r$  that occurs in a relation atom  $\mathsf{R}_k(z_1,\ldots,z_{\mathsf{HR}_i})$  in the label of the vertex y.

(vii) each top-level variable in  $A(\xi_1, ..., \xi_{\#A})$  that is bound to a variable from a relation atom  $R_k(z_1, ..., z_{\#R_k})$  in the unfolding, must be equated to that variable:

atom 
$$\mathsf{R}_k(z_1,\ldots,z_{\mathsf{HR}_k})$$
 in the unfolding, must be equated to that variable: 
$$\bigwedge_{r_i\in \mathsf{def}_\Delta(\mathsf{A})} \bigwedge_{j\in[1,\mathsf{\#A}]} \forall y\forall z\,.\, X_i(x) \wedge varEq_{\xi_j,k,r}(x,y,\{X_i\}_{i=1}^R,\{Y_j\}_{j=1}^P) \wedge Z_{k,r}(y,z) \to \xi_j = z$$

The formulæ  $isEq_{k,\ell,m,n}(x,y,\{X_i\}_{i=1}^R,\{Y_j\}_{j=1}^P)$  and  $varEq_{\xi,k,r}(x,y,\{X_i\}_{i=1}^R,\{Y_j\}_{j=1}^P)$  above are definable in MSO, using standard tree automata construction techniques, similar to the definition of MSO formulæ that track parameters in an unfolding tree for SL, with edges definable by MSO formulæ over the signature of SL [20]. To avoid clutter, we defer such definitions to a long version of this paper.

Summing up, the SO formula defining the models of the predicate atom  $A(\xi_1, \dots, \xi_{\#A})$  with respect to the SID  $\Delta$  is the following:

$$\mathfrak{A}^{\mathsf{A}}_{\Delta}(\xi_{1},\ldots,\xi_{\mathsf{\#A}}) \stackrel{\mathsf{def}}{=} \exists x \exists \{X_{i}\}_{i=1}^{R} \exists \{Y_{j}\}_{j=1}^{P} \exists \{Z_{1,\ell}\}_{\ell=1}^{\mathsf{\#R}_{1}} \ldots \exists \{Z_{K,\ell}\}_{\ell=1}^{\mathsf{\#R}_{K}} .$$

$$\mathfrak{T}(x,\{X_{i}\}_{i=1}^{R},\{Y_{j}\}_{j=1}^{P}) \wedge \mathfrak{F}(\xi_{1},\ldots,\xi_{\mathsf{\#A}},x,\{X_{i}\}_{i=1}^{R},\{Y_{j}\}_{j=1}^{P},\{\{Z_{k,\ell}\}_{\ell=1}^{\mathsf{\#R}_{k}}\}_{k=1}^{N})$$

The correctness of the construction is asserted by the following proposition, that also proves  $SLR \subseteq SO$ , using a similar reduction of sentences to predicate atoms as in Proposition 4:

**Proposition 5.** Given an SID  $\Delta$  and a predicate atom  $A(\xi_1, ..., \xi_{\#A})$ , for each structure  $\sigma$  and store v, we have  $(\sigma, v) \models_{\Delta} A(\xi_1, ..., \xi_{\#A}) \iff (\sigma, v) \models_{\Delta} A(\xi_1, ..., \xi_{\#A})$ .

*Proof.* " $\Rightarrow$ " By Lemma 4, there exists an unfolding tree  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$  of  $A(\xi_1, \ldots, \xi_{\# A})$ , such that  $(\sigma, v) \models \Theta(\mathcal{T}, A(\xi_1, \ldots, \xi_{\# A}))$ . Let  $\Theta(\mathcal{T}, A(\xi_1, \ldots, \xi_{\# A})) = \exists y_1 \ldots \exists y_K \cdot \Phi$ , where  $\Phi$  is a quantifier- and predicate-free formula. Note that, by Def. 9, no second-order variables occur in  $\Theta(\mathcal{T}, A(\xi_1, \ldots, \xi_{\# A}))$ . Hence there exists a store v' that agrees with v over  $\xi_1, \ldots, \xi_{\# A}$ , such that  $(\sigma, v') \models \Phi$ . We define another store v'', that agrees with v and v' over  $\xi_1, \ldots, \xi_{\# A}$  such that, moreover, we have:

- v''(x) = r
- $-\mathbf{v}''(X_i) = \{n \in \mathcal{N} \mid \lambda(n) = r_i\}, \text{ for all } i \in [1, R],$
- $\mathbf{v}''(Y_j) = \{(n,m) \in \mathcal{N} \times \mathcal{N} \mid m \text{ is the } j\text{-th child of } n\}$ , for all  $j \in [1,P]$ ; we consider that the order between the children of a vertex in an unfolding tree is the syntactic order of their corresponding predicate atoms, in the sense of Def. 9,
- $\mathbf{v}''(Z_{k,\ell})$  = {(n,(σ, $\mathbf{v}'$ )( $ξ_{\ell}$ )) | n ∈  $\mathcal{N}$ ,  $\mathsf{R}_{k}^{n}(ξ_{1},...,ξ_{\mathsf{\#R}_{k}})$  occurs in Φ}, for all k ∈ [1,N] and  $\ell$  ∈ [1, $\mathsf{\#R}_{k}$ ].

We have  $(\sigma, v'') \Vdash \mathfrak{T}(x, \{X_i\}_{i=1}^R, \{Y_j\}_{j=1}^P)$  because  $\mathcal{T}$  is an unfolding tree for  $A(\xi_1, \ldots, \xi_{\#A})$ , by Def. 9. The proof of  $(\sigma, v'') \Vdash \mathfrak{F}(\xi_1, \ldots, \xi_{\#A}, x, \{X_i\}_{i=1}^R, \{Y_j\}_{j=1}^P, \{\{Z_{k,\ell}\}_{\ell=1}^{\#R_k}\}_{k=1}^N)$  follows from  $(\sigma, v') \models \Phi$  and the definition of v'', by the points (i-vii) from the definition of  $\mathfrak{F}$ . We obtain  $(\sigma, v) \Vdash \mathfrak{A}_{\Delta}^A(\xi_1, \ldots, \xi_{\#A})$  from the definition of  $\mathfrak{A}_{\Delta}^A$ .

"\( = " \text{ There exists a store } \nu ' \text{ that agrees with } \nu \text{ over } \xi\_1, \ldots, \xi\_{\pma A}, \text{ such that:}

$$(\sigma, \mathsf{v}') \Vdash \mathfrak{T}(x, \{X_i\}_{i=1}^R, \{Y_i\}_{i=1}^P) \tag{4}$$

$$(\sigma, \mathbf{v}') \Vdash \mathfrak{F}(\xi_1, \dots, \xi_{\mathsf{\#A}}, x, \{X_i\}_{i=1}^R, \{Y_j\}_{j=1}^P, \{\{Z_{k,\ell}\}_{\ell=1}^{\mathsf{\#R}_k}\}_{k=1}^N)$$
 (5)

By (4) we obtain an unfolding tree  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$  for  $A(\xi_1, \dots, \xi_{\#A})$ , such that:

-  $\mathcal{N} = \bigcup_{j=1}^{R} \mathbf{v}'(X_i)$ , -  $\mathcal{F} = \bigcup_{j=1}^{P} \mathbf{v}'(Y_j)$ , -  $\lambda(n) = \mathbf{r}_i \iff n \in \mathbf{v}'(X_i)$ , for all  $n \in \mathcal{N}$  and  $i \in [1, R]$ .

Let  $\Theta(\mathcal{T}, \mathsf{A}(\xi_1, \dots, \xi_{\#A})) = \exists y_1 \dots \exists y_K \cdot \Phi$ , where  $\Phi$  is a quantifier- and predicate-free formula (Def. 9). By Lemma 4, it is sufficient to show the existence of a store  $\mathbf{v}''$  that agrees with  $\mathbf{v}$  over  $\xi_1, \dots, \xi_{\#A}$ , such that  $(\sigma, \mathbf{v}'') \models \Phi$ . Let  $f_{k,\ell}$  denote the partial mapping defined by  $\mathbf{v}'(Z_{k,\ell})$ , for each  $k \in [1,N]$  and  $\ell \in [1,\#R]$ , by point (i) of the definition of  $\mathfrak{F}$ . For each  $r \in [1,K]$ , we define  $\mathbf{v}''(y_r) \stackrel{\text{def}}{=} f_{k,\ell}(n)$  if  $y_r$  occurs in or is constrained to be equal to a term  $\xi_\ell$  that occurs in an annotated relation atom  $\mathsf{R}_k^n(\xi_1, \dots, \xi_{\#R_k})$  from  $\Phi$ . Note that there can by at most one such relation atom in  $\Phi$ , because of the assumption that in each rule from  $\Phi$  at most one relation atom  $\mathsf{R}_k(z_1, \dots, z_{\#R_k})$  occurs. Otherwise, if  $y_r$  is not constrained in  $\Phi$  to be equal to a term that occurs in a relation atom,  $\mathbf{v}''(y_r)$  is given an arbitrary fresh value. Because the equalities and disequalities from  $\Phi$  are taken care of by points (v) and (vi) from the definition of  $\mathfrak{F}$ , it remains to check the satisfaction of the relation atoms from  $\Phi$ . To this end, we define a decomposition  $\sigma = \Phi_{n \in \mathcal{N}, k \in [1,N]} \sigma_{n,k}$  such that  $(\sigma_{n,k}, \mathbf{v}'') \models \mathsf{R}_k(\xi_1, \dots, \xi_{\#R_k})$ , for all relation atoms  $\mathsf{R}_k^n(\xi_1, \dots, \xi_{\#R_k})$  from  $\Phi$ . Such a decomposition is possible due to points (ii-iv) from the definition of  $\mathfrak{F}$ .

# 7 MSO $\subseteq^k$ SLR

We prove that, for any MSO sentence  $\phi$  and any integer  $k \ge 1$ , there exists an SID  $\Delta(k, \phi)$  that defines a predicate  $A_{k,\phi}$  of arity zero, such that the set of models of  $\phi$  of treewidth at most k corresponds to the set of structures SLR-defined by the pair  $(A_{k,\phi}(), \Delta(k,\phi))$ . Our proof leverages from a result of Courcelle [11], stating that the set of models of bounded treewidth of a given MSO sentence can be described by a set of recursive equations, written using an algebra of operations on structures. This result follows up in a long-standing line of work (known as Feferman-Vaught theorems [26]) that reduces the evaluation of an MSO sentence on the result of an algebraic operation to the evaluation of several related sentences in the arguments of the respective operation.

### 7.1 Courcelle's Theorem

In order to exlpain our construction (given in §7.2), we recall first a result of Courcelle on the characterization of the structures of bounded treewidth that satisfy a given MSO formula  $\phi$  by an effectively constructible set of recursive equations. The equation set uses two operations on structures, namely *glue* and  $fgcst_j$ , that are lifted to sets of structures, as usual. The result is developed in two steps: the first step builds a generic equation set, that characterizes all structures of bounded treewidth, which is then refined to describe only those structures that satisfy  $\phi$ , in the second step.

Standard Structures Given a signature  $\Sigma$ , a standard structure  $S = (D_S, \sigma_S)$  consists of a domain  $D_S$  and an interpretation  $\sigma_S$  of the relation and constant symbols from  $\Sigma$  as tuples and elements from  $D_S$ , respectively. Note that the structures S considered in the semantics of SLR correspond to the particular case  $D_S = \mathbb{U}$ , for a countably infinite set  $\mathbb{U}$ , whereas in general,  $D_S$  might be finite or even uncountable. The interpretation of (M)SO formulæ and the notion of treewidth are defined for standard structures in the

same way as for structures  $(\mathbb{U}, \sigma)$ . We denote by  $Str(\Sigma)$  the set of standard structures over the signature  $\Sigma$ . We sometimes abuse notation and write  $\sigma \in Str(\Sigma)$  instead of  $(\mathbb{U}, \sigma) \in Str(\Sigma)$ .

Operations Let  $\Sigma = \{R_1, \dots, R_N, c_1, \dots, c_M\}$  and  $\Sigma' = \{R'_1, \dots, R'_{N'}, c'_1, \dots, c'_{M'}\}$  be two (possibly overlapping) signatures. The *glueing* operation *glue*:  $Str(\Sigma) \times Str(\Sigma') \to Str(\Sigma \cup \Sigma')$  is the disjoint union of structures, followed by the fusion of constants. Formally, given  $S_i = (D_i, \sigma_i)$ , for i = 1, 2, such that  $D_1 \cap D_2 = \emptyset$ , let  $\sim$  be the least equivalence relation on  $D_1 \cup D_2$  such that  $\sigma_1(c) \sim \sigma_2(c)$ , for all  $c \in \Sigma \cap \Sigma'$ . We denote by [d] the equivalence class of an element  $d \in D_1 \cup D_2$  w.r.t. the  $\sim$  relation. Then  $glue(S_1, S_2) \stackrel{\text{def}}{=} (D, \sigma)$ , where  $D \stackrel{\text{def}}{=} \{[d] \mid d \in D_1 \cup D_2\}$  and the interpretation of relation symbols and constants follows:

$$\sigma(\mathsf{R}) \stackrel{\mathsf{def}}{=} \begin{cases} \{\langle [d_1], \dots [d_{\mathsf{\#R}}] \rangle \mid \langle d_1, \dots, d_{\mathsf{\#R}} \rangle \in \sigma_1(\mathsf{R}) \}, & \text{if } \mathsf{R} \in \Sigma \setminus \Sigma' \\ \{\langle [d_1], \dots [d_{\mathsf{\#R}}] \rangle \mid \langle d_1, \dots, d_{\mathsf{\#R}} \rangle \in \sigma_2(\mathsf{R}) \}, & \text{if } \mathsf{R} \in \Sigma' \setminus \Sigma \\ \{\langle [d_1], \dots [d_{\mathsf{\#R}}] \rangle \mid \langle d_1, \dots, d_{\mathsf{\#R}} \rangle \in \sigma_1(\mathsf{R}) \cup \sigma_2(\mathsf{R}) \}, & \text{if } \mathsf{R} \in \Sigma \cap \Sigma \end{cases}$$

$$\sigma(\mathsf{c}) \stackrel{\mathsf{def}}{=} \begin{cases} [\sigma_1(\mathsf{c})], & \text{if } \mathsf{c} \in \Sigma \\ [\sigma_2(\mathsf{c})], & \text{if } \mathsf{c} \in \Sigma' \setminus \Sigma \end{cases}$$

Since we identify isomorphic structures, the nature of the elements of D (i.e., equivalence classes of the  $\sim$  relation) is not important. The *forget* operation  $fgcst_j: Str(\Sigma) \rightarrow Str(\Sigma \setminus \{c_j\})$  simply drops the constant  $c_j$  from the domain of its argument, for any  $j \in [1,M]$ .

**Structures of Bounded Treewidth** Let  $k \ge 1$  be an integer,  $\Sigma = \{R_1, \dots, R_N, c_1, \dots, c_M\}$  be a signature and  $\Pi = \{c_{M+1}, \dots, c_{M+k+1}\}$  be a set of constants disjoint from  $\Sigma$ , called *ports*. We consider variables  $Y_i$ , for all subsets  $\Pi_i \subseteq \Pi$ , denoting sets of structures over the signature  $\Sigma \cup \Pi_i$ . The equation system now consists of recursive equations of the form  $Y_0 \supseteq f(Y_1, \dots, Y_n)$ , where each f is either  $glue, fgcst_{M+j}$ , for any  $j \in [1, k+1]$ , or a relation  $\overline{R}_i$  of type  $R_i$ , consisting of one tuple with at most k+1 distinct elements, for any  $i \in [1, N]$ . We denote this set of equations by Tw(k). The structures of treewidth at most k correspond to a component of the least solution of Tw(k), in the domain of tuples of sets ordered by pointwise inclusion, see e.g., [12, Theorem 2.83].

Refinement to Models of MSO We recall that the *quantifier rank*  $qr(\phi)$  of an MSO formula  $\phi$  is the maximal depth of nested quantifiers i.e.,  $qr(\phi) \stackrel{\text{def}}{=} 0$  if  $\phi$  is an atom,  $qr(\neg \phi_1) \stackrel{\text{def}}{=} qr(\phi_1)$ ,  $qr(\phi_1 \land \phi_2) \stackrel{\text{def}}{=} \max(qr(\phi_1), qr(\phi_2))$  and  $qr(\exists x . \phi_1) = qr(\exists X . \phi_1) \stackrel{\text{def}}{=} qr(\phi_1) + 1$ . We denote by  $\mathbb{F}^r_{\text{MSO}}$  the set of MSO sentences of quantifier rank at most r; this set is finite, up to logical equivalence. For a standard structure S, we define its r-type as  $type^r(S) \stackrel{\text{def}}{=} \{\phi \in \mathbb{F}^r_{\text{MSO}} \mid S \Vdash \phi\}$ . We assume the sentences in  $type^r(S)$  to use the signature over which S is defined; this signature will be clear from the context in the following.

**Definition 10.** An operation  $f: Str(\Sigma_1) \times ... \times Str(\Sigma_n) \to Str(\Sigma_{n+1})$  is said to be (effectively) MSO-compatible<sup>3</sup> iff  $type^r(f(S_1,...,S_n))$  depends only on (and can be computed from)  $type^r(S_1),...,type^r(S_n)$  by an abstract operation  $f^{\sharp}: (pow(\mathbb{F}^r_{MSO}))^n \to pow(\mathbb{F}^r_{MSO})$ .

<sup>&</sup>lt;sup>3</sup> Also referred to as *smooth* in [26].

Courcelle establishes that glueing and forgetting of constants are effectively MSO-compatible and computable by abstract operations  $glue^{\sharp}$  and  $fgcst^{\sharp}_{M+i}$ , for  $i \in [1, k+1]$ . Then, one can build, from Tw(k) a set of recursive equations  $Tw^{\sharp}(k)$  of the form  $Y_0^{\tau_0} = f(Y_1^{\tau_1}, \ldots, Y_n^{\tau_n})$ , where  $Y_0 = f(Y_1, \ldots, Y_n)$  is an equation from Tw(k) and  $\tau_0, \ldots, \tau_n$  are  $qr(\phi)$ -types such that  $\tau_0 = f^{\sharp}(\tau_1, \ldots, \tau_n)$ . Intuitively, each annotated variable  $Y^{\tau}$  denotes denotes the set of structures whose  $qr(\phi)$ -type is  $\tau$ , from the Y-component of the the least solution of Tw(k). Then, the set of models of  $\phi$  of treewidth at most k is the union of the  $Y^{\tau}$ -components of the least solution of  $Tw^{\sharp}(k)$ , such that  $\phi \in \tau$ , see e.g., [11, Theorem 3.6].

### 7.2 Encoding Types with SIDs

We now give the details of MSO  $\subseteq^k$  SLR. Instead of using the set of recursive equations Tw(k) from the previous subsection, we give an SID  $\Delta(k)$  that also characterizes the structures of bounded treewidth (Figure 1a). The idea is to use the separating conjunction for simulating the glueing operation. However, the separating conjunction does not necessarily guarantee disjointness of the structures, as required by the glueing operation. In order to enforce disjointness with the separating conjunction, we introduce a new relation symbol  $\mathfrak{D} \notin \Sigma$ , that "collects" the values assigned to the existentially quantified variables created by rule (7) and the top-level rule (9) during the unraveling. In particular, the relation symbol  $\mathfrak D$  ensures that (i) the variables of a predicate atom  $A(x_1, \dots, x_{\#A})$  are mapped to pairwise distinct values and (ii) the composition  $\sigma_1 \bullet \sigma_2$  of two structures  $\sigma_1$  and  $\sigma_2$  over  $\Sigma \cup \{\mathfrak{D}\}$  behaves like glueing the standard structures  $(Dom(\sigma_1), \sigma_1)$  and  $(Dom(\sigma_2), \sigma_2)$ . Formally, we establish a correspondence between structures over  $\Sigma$  and  $\Sigma \cup \{\mathfrak{D}\}$ : given a structure  $\sigma \in Str(\Sigma)$ , we say that  $\sigma' \in Str(\Sigma \cup \{\mathfrak{D}\})$  is a  $\mathfrak{D}$ -extension of  $\sigma$  if and only if  $\sigma'(\mathfrak{D}) \supseteq Rel(\sigma)$  and  $\sigma'$  agrees with  $\sigma$  over  $\Sigma$ . Below we prove that  $\Delta(k)$  (Figure 1a) fulfills the purpose of defining the structures of bounded treewidth:

**Definition 11.** A tree decomposition  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$  of a structure  $\sigma$  is said to be reduced if and only if the following hold:

- 1. for each  $R \in \Sigma$  and each  $\langle u_1, ..., u_{\#R} \rangle \in \sigma(R)$  there exists a leaf  $n \in \mathcal{N}$  such that  $\{u_1, ..., u_{\#R}\} \subseteq \lambda(n)$ , called the witness of  $\langle u_1, ..., u_{\#R} \rangle \in \sigma(R)$ ,
- 2. every leaf witnesses exactly one tuple  $\langle u_1, \dots, u_{\#R} \rangle \in \sigma(R)$ ,
- 3. T is a binary tree i.e., a tree where each node has at most two children,
- 4. if  $n \in \mathcal{N}$  has two children  $m_1, m_2 \in \mathcal{N}$  then  $\lambda(n) = \lambda(m_1) = \lambda(m_2)$ ,
- 5. if  $n \in \mathcal{N}$  has one child  $m \in \mathcal{N}$  then either  $\lambda(n) = \lambda(m)$  and m witnesses a tuple  $\langle u_1, \ldots, u_{\#R} \rangle \in \sigma(R)$ , or  $\|\lambda(n) \setminus \lambda(m)\| = \|\lambda(m) \setminus \lambda(n)\| = 1$ ,
- 6.  $\|\lambda(n)\| = k+1$ , for all  $n \in \mathcal{N}$ .

**Lemma 5.** If a structure  $\sigma$  has a tree decomposition of width k, then it also has a reduced tree decomposition of width k.

*Proof.* The properties (1-6) can be proven directly from Definition 4. The main tool is the introduction of intermediate nodes into the tree decomposition. We list some of the cases. For (1), if a node witnesses more than one tuple, then we introduce an

$$\begin{array}{ll} \mathsf{A}(x_{1},\ldots,x_{k+1}) \leftarrow \mathsf{A}(x_{1},\ldots,x_{k+1}) * \mathsf{A}(x_{1},\ldots,x_{k+1}) & (6) \\ \mathsf{A}(x_{1},\ldots,x_{k+1}) \leftarrow \exists y \ . \ \mathfrak{D}(y) * \mathsf{A}(x_{1},\ldots,x_{k+1})[x_{i}/y], \text{ for all } i \in [1,k+1] & (7) \\ \mathsf{A}(x_{1},\ldots,x_{k+1}) \leftarrow \mathsf{R}(y_{1},\ldots,y_{\#R}), \text{ for all } \mathsf{R} \in \Sigma \text{ and } y_{1},\ldots,y_{\#R} \in \{x_{1},\ldots,x_{k+1}\} & (8) \\ \mathsf{A}_{k}() \leftarrow \exists x_{1} \ldots \exists x_{k+1} \ . \ \mathfrak{D}(x_{1}) * \ldots * \mathfrak{D}(x_{k+1}) * \mathsf{A}(x_{1},\ldots,x_{k+1}) & (9) \\ & (a) &$$

Fig. 1: The SID  $\Delta(k)$  defining structures of treewidth at most k (a) and its annotation  $\Delta(k, \phi)$  defining the models of an MSO sentence  $\phi$ , of treewidth at most k (b)

intermediate node between itself and its parent that is labeled by the same set of vertices. The intermediate node then becomes the witness for the this tuple. This process can be iterated until every node witnesses at most one tuple. For (3), if a node  $n_0$  has children  $m_0, \dots, m_l$  we can introduce new nodes  $n_1, \dots, n_{l-1}$  with  $\lambda(m_0) = \lambda(m_i)$ , and create a new tree decomposition which agrees with the old tree decomposition except that we remove the edges from  $n_0$  to the children  $m_0, \dots, m_l$  and add edges from  $n_i$  to  $m_i$  and  $n_{i+1}$  for all i < l-1 and edges from  $n_{l-1}$  to  $m_{l-1}$  and  $m_l$ . For (6), note that we always consider structures over some infinite universe. Hence, we can always extend the labels of the tree-decomposition with some fresh vertices from the universe.

**Lemma 6.** Let 
$$\sigma \in Str(\Sigma \cup \{\mathfrak{D}\})$$
 be a structure and  $v$  be a store, such that  $(\sigma, v) \models_{\Delta(k)} A(x_1, \ldots, x_{k+1})$  and  $v(x_i) \notin \sigma(\mathfrak{D})$ , for all  $1 \le i \le k+1$ . Then, there exists a reduced tree decomposition  $\mathcal{T} = (\mathfrak{N}, \mathcal{F}, r, \lambda)$  of  $\sigma$ , such that  $tw(\mathcal{T}) = k$ ,  $\lambda(r) = \{v(x_1), \ldots, v(x_{k+1})\}$  and  $\lambda(n) \subseteq \sigma(\mathfrak{D}) \cup \{v(x_1), \ldots, v(x_{k+1})\}$ , for all  $n \in \mathcal{N}$ .

*Proof.* We prove the claim by induction on the number of rule applications. The claim clearly holds for the base case, by rule (8). We now consider the rule (6) i.e., we assume that  $(\sigma, v) \models_{\Delta(k)} A(x_1, \dots, x_{k+1}) * A(x_1, \dots, x_{k+1})$ . Then, there exist structures  $\sigma_1$  and  $\sigma_2$ , such that  $(\sigma_i, v) \models_{\Delta(k)} A(x_1, \dots, x_{k+1})$ , for i = 1, 2 and  $\sigma_1 \bullet \sigma_2 = \sigma$ . We note that the latter implies that  $\sigma_1(\mathfrak{D}) \cap \sigma_2(\mathfrak{D}) = \emptyset$  (†). We now apply the inductive hypothesis and obtain reduced tree decompositions  $\mathcal{T}_i$  for  $\sigma_i$  whose respective roots are labelled by  $\{v(x_1), \dots, v(x_{k+1})\}$  and  $\lambda(n) \subseteq \sigma(\mathfrak{D}) \cup \{v(x_1), \dots, v(x_{k+1})\}$ , for all

nodes n of  $\mathcal{T}_i$  and all i=1,2. We obtain a reduced tree decomposition for  $\sigma$  by composing  $\mathcal{T}_1$  and  $\mathcal{T}_2$  with a fresh root node labelled by  $\{v(x_1), \dots, v(x_{k+1})\}$ . Note that  $\mathcal{T}$  is indeed a tree decomposition because the only elements that may appear in labels of both  $\mathcal{T}_1$  and  $\mathcal{T}_2$  must belong to  $\{v(x_1), \dots, v(x_{k+1})\}$ , by  $(\dagger)$ . Clearly, we have  $\lambda(n) \subseteq \sigma_1(\mathfrak{D}) \cup \sigma_2(\mathfrak{D}) \cup \{v(x_1), \dots, v(x_{k+1})\} = \sigma(\mathfrak{D}) \cup \{v(x_1), \dots, v(x_{k+1})\}, \text{ for all }$ nodes n of the resulting tree decomposition  $\mathcal{T}$ . We now consider the rule (7) i.e., we assume that  $(\sigma, \mathbf{v}) \models_{\Delta(k)} \exists y : \mathfrak{D}(y) * \mathsf{A}(x_1, \dots, x_{k+1})[x_i/y]$ . Then, there is an element  $u \notin \{v(x_1), \dots, v(x_{k+1})\}$  such that  $(\sigma', v[x_i \leftarrow u]) \models_{\Delta(k)} A(x_1, \dots, x_{k+1})$ , where the structure  $\sigma'$  agrees with  $\sigma$ , except that  $\sigma(\mathfrak{D}) = \sigma'(\mathfrak{D}) \setminus \{u\}$ . We now apply the inductive hypothesis and obtain a reduced tree decomposition  $T_1$  for  $\sigma'$  whose root is labelled by  $\{\{v(x_1),\ldots,v(x_{k+1})\}\setminus\{v(x_i)\}\}\cup\{u\}$  and  $\lambda(n)\subseteq((\sigma'(\mathfrak{D})\cup\{v(x_1),\ldots,v(x_{k+1})\})\setminus\{v(x_i)\}\cup\{v(x_i$  $\{v(x_i)\}\cup\{u\}$ , for all nodes n of  $\mathcal{T}_1$  (‡). We can now obtain a reduced tree decomposition  $\mathcal{T}$  for  $\sigma$  by composing  $\mathcal{T}_1$  with an additional root labelled by  $\{v(x_1), \dots, v(x_{k+1})\}$ . Note that  $\mathcal{T}$  is indeed a tree decomposition because  $v(x_i) \notin \lambda(n)$  for every node n of  $\mathcal{T}_1$ , because of  $(\ddagger)$ ,  $u \neq v(x_i)$  and the assumption that  $v(x_i) \notin \sigma(\mathfrak{D})$ . We have  $\lambda(n) \subseteq$  $\sigma'(\mathfrak{D}) \cup \{v(x_1), \dots, v(x_{k+1})\} \cup \{u\} = \sigma(\mathfrak{D}) \cup \{v(x_1), \dots, v(x_{k+1})\}$  for all nodes n of the resulting tree decomposition  $\mathcal{T}$ .

**Definition 12.** If  $\mathcal{T} = (\mathfrak{N}, \mathcal{F}, r, \lambda)$  is a tree decomposition of a structure  $\sigma \in Str(\Sigma)$ , we denote by  $add_{\mathfrak{D}}^{\mathcal{T}}(\sigma) \in Str(\Sigma \cup \{\mathfrak{D}\})$  the structure that agrees with  $\sigma$  over  $\Sigma$ , such that, moreover,  $(add_{\mathfrak{D}}^{\mathcal{T}}(\sigma))(\mathfrak{D}) = (\bigcup_{n \in \mathcal{N}} \lambda(n)) \setminus \lambda(r)$ .

**Lemma 7.** Let  $\sigma$  be a structure with  $\operatorname{tw}(\sigma) \leq k$  witnessed by some reduced tree decomposition  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$ , such that  $\lambda(r) = \{u_1, \dots, u_{k+1}\}$  and let  $\nu$  be a store with  $\nu(x_i) = u_i$ , for all  $i \in [1, k+1]$ . Then, we have  $(\operatorname{add}_{\mathfrak{D}}^{\mathcal{T}}(\sigma), \nu) \models_{\Delta(k)} A(x_1, \dots, x_{k+1})$ .

*Proof.* The proof goes by induction on the structure of  $\mathcal{T}$ . The claim clearly holds for the base case, where  $\mathcal{T}$  consists of a single leaf, by rule (8). Consider first the case where the root of  $\mathcal{T}$  has two children. The subtrees  $\mathcal{T}_1$  and  $\mathcal{T}_2$  rooted in the two children induce substructures  $\sigma_1$  and  $\sigma_2$  of  $\sigma$ , where  $\langle v_1, \dots, v_{\#R} \rangle \in \sigma_i(R)$  iff  $\langle v_1, \dots, v_{\#R} \rangle$ is witnessed by some leaf of  $T_i$ , for i = 1, 2. Because T is a reduced tree decomposition, there is at most one leaf that witnesses a tuple  $\langle v_1, \dots, v_{\#R} \rangle \in \sigma_i(R)$ . Hence, we have  $\sigma = \sigma_1 \bullet \sigma_2$ . Because the only elements that can appear as labels in both  $T_1$  and  $\mathcal{T}_2$  are  $\{u_1,\ldots,u_{k+1}\}$ , we also get that  $add_{\mathfrak{D}}^{\mathcal{T}}(\sigma)=add_{\mathfrak{D}}^{\mathcal{T}_1}(\sigma_1)\bullet add_{\mathfrak{D}}^{\mathcal{T}_2}(\sigma_2)$ . From the inductive hypothesis we obtain  $(add_{\mathfrak{D}}^{T_i}(\sigma_i), \mathbf{v}) \models_{\Delta(k)} \mathsf{A}(x_1, \dots, x_{k+1})$ , for i = 1, 2. Hence  $(add_{\mathfrak{D}}^{\prime 2_1}(\sigma_1) \bullet add_{\mathfrak{D}}^{\prime 2_2}(\sigma_2), \mathbf{v}) \models_{\Delta(k)} \mathsf{A}(x_1, \dots, x_{k+1}) * \mathsf{A}(x_1, \dots, x_{k+1}), \text{ thus } (add_{\mathfrak{D}}^T(\sigma), \mathbf{v}) \models_{\Delta(k)} \mathsf{A}(x_1, \dots, x_{k+1}) * \mathsf{A}(x_1, \dots, x_{k+1}), \mathsf{A}(x_1, \dots, x_{k+1})$  $A(x_1, \dots, x_{k+1})$ , by rule (6). Consider now the case where the root of  $\mathcal{T}$  has a single child which is not a leaf and consider the subtree  $\mathcal{T}_1$  rooted at this child. Then, there is an element  $u \notin \{u_1, \dots, u_{k+1}\}$ , such that the root of  $\mathcal{T}_1$  is labeled by  $\{u_1, \dots, u_{i-1}, u, u_{i+1}, \dots, u_{k+1}\}$ . By the inductive hypothesis, we obtain  $(add_{\mathfrak{D}}^{T_1}(\sigma), v[x_i \leftarrow u]) \models_{\Delta(k)} A(x_1, \dots, x_{k+1})$ . We recognize that  $add_{\mathfrak{D}}^{\mathcal{T}_1}(\sigma)$  agrees with  $add_{\mathfrak{D}}^{\mathcal{T}}(\sigma)$  except that  $u \in (add_{\mathfrak{D}}^{\mathcal{T}}(\sigma))(\mathfrak{D})$ . Hence,  $(add_{\mathfrak{D}}^{T}(\sigma), \mathbf{v}) \models_{\Delta(k)} \exists \mathbf{y} \cdot \mathfrak{D}(\mathbf{y}) * \mathsf{A}(x_{1}, \dots, x_{k+1})[x_{i}/\mathbf{y}], \text{ thus } (add_{\mathfrak{D}}^{T}(\sigma), \mathbf{v}) \models_{\Delta(k)} \mathsf{A}(x_{1}, \dots, x_{k+1}),$ by rule (7).

**Lemma 8.** For any structure  $\sigma \in Str(\Sigma)$ , we have  $tw(\sigma) \le k$  if and only if there is a  $\mathfrak{D}$ -extension  $\sigma'$  of  $\sigma$  with  $\sigma' \models_{\Lambda(k)} A_k()$ .

*Proof.* " $\Rightarrow$ " If  $\sigma$  has tree decomposition of width at most k, then it also has a reduced tree decomposition  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$  of width k, by Lemma 5. Let  $\lambda(r) = \{u_1, \dots, u_{k+1}\}$  and  $\nu$  be a store such that  $\nu(x_i) = u_i$ , for all  $i \in [1, k+1]$ . By Lemma 7,  $(add_{\mathfrak{D}}^{\mathcal{T}}(\sigma), \nu) \models_{\Delta(k)} A(x_1, \dots, x_{k+1})$ . By adding  $\{u_1, \dots, u_{k+1}\}$  to the interpretation of  $\mathfrak{D}$  in  $add_{\mathfrak{D}}^{\mathcal{T}}(\sigma)$ , we obtain a  $\mathfrak{D}$ -extension  $\sigma'$  of  $\sigma$  that satisfies  $\sigma' \models_{\Delta(k)} A_k()$ , by rule (9).

" $\Leftarrow$ " Let  $\sigma'$  be a  $\mathfrak{D}$ -extension of  $\sigma$  with  $\sigma' \models_{\Delta(k)} \mathsf{A}_k()$ . By rule (9), there exists a  $\mathfrak{D}$ -extension  $\sigma''$  of  $\sigma$  and a store  $\mathsf{v}$ , with  $\mathsf{v}(x_i) \neq \mathsf{v}(x_j)$ , for all  $i \neq j \in [1, k+1]$  and  $\mathsf{v}(x_1), \ldots \mathsf{v}(x_{k+1}) \not\in \sigma''(\mathfrak{D})$ , such that  $(\sigma'', \mathsf{v}) \models_{\Delta(k)} \mathsf{A}(x_1, \ldots, x_{k+1})$ . By Lemma 6, there exists a reduced tree decomposition  $\mathscr{T}$  of  $\sigma''$  of width k. Thus  $\mathsf{tw}(\sigma) \leq k$ , because  $\sigma$  is a substructure of  $\sigma''$ .

The second step of our construction is the annotation of the rules in  $\Delta(k)$  with  $\operatorname{qr}(\phi)$ -types, in order to obtain an SID  $\Delta(k,\phi)$  describing the models of an MSO sentence  $\phi$ , of treewidth at most k. For this, we consider the set of ports  $\Pi = \{c_{M+1}, \ldots, c_{M+k+1}\}$  disjoint from  $\Sigma$ , used to encode the values of the variables  $x_1, \ldots, x_{k+1}$ :

**Definition 13.** Let  $\Sigma = \{R_1, \dots, R_N, c_1, \dots, c_M\}$  be a signature and  $\Pi = \{c_{M+1}, \dots, c_{M+k+1}\}$  be constants not in  $\Sigma$ . For a structure  $\sigma \in Str(\Sigma)$  and a store  $v : \{x_1, \dots, x_m\} \to \mathbb{U}$ , we denote by  $encode(\sigma, v) \in Str(\Sigma \cup \{c_{M+1}, \dots, c_{M+k+1}\})$  the structure that agrees with  $\sigma$  over  $\Sigma$  and maps  $c_{M+i}$  to  $v(x_i)$ , for all  $i \in [1, k+1]$ .

The correctness of our construction will rely on the fact that the disjoint union behaves like glueing for two structures that only overlap at the ports:

**Lemma 9.** Given an integer  $r \ge 0$ , a store  $\nu$  and disjoint compatible structures  $\sigma_1, \sigma_2 \in Str(\Sigma)$  with  $Rel(\sigma_1) \cap Rel(\sigma_2) \subseteq {\{\nu(x_1), \dots, \nu(x_{k+1})\}}$ , we have  $type^r(encode(\sigma_1 \bullet \sigma_2, \nu)) = glue^{\sharp}(type^r(encode(\sigma_1, \nu)), type^r(encode(\sigma_2, \nu)))$ .

*Proof.* Let us consider  $\sigma_1' = encode(\sigma_1, v)$  and  $\sigma_2' = encode(\sigma_2, v)$ . In order to apply glueing we will now consider two standard structures isomorphic to  $\sigma_1'$  and  $\sigma_2'$ , respectively. We note that  $Dom(\sigma_1') \cap Dom(\sigma_2') \subseteq \{\sigma_2'(c_{M_1}), \ldots, \sigma_2'(c_{M+k+1})\}$  because of our assumption that  $Rel(\sigma_1) \cap Rel(\sigma_2) \subseteq \{v(x_1), \ldots, v(x_{k+1})\}$ . We further note that  $\sigma_1'(c_{M_i}) = \sigma_2'(c_{M_i})$ , for all  $i \in [1, M+k+1]$ , because  $\sigma_1$  and  $\sigma_2$  are compatible and the interpretation of the additional constants  $c_{M+1}, \ldots, c_{M+k+1}$  has been chosen w.r.t. the same store v. Hence, we can choose some partitioning  $\mathcal{U}_1 \uplus \mathcal{U}_2 = \mathbb{U}$  such that  $\mathcal{U}_1$  and  $\mathcal{U}_2$  are countably infinite,  $Dom(\sigma_1') \subseteq \mathcal{U}_1$  and  $Dom(\sigma_2') \setminus \{\sigma_2'(c_1), \ldots, \sigma_2'(c_{M+k+1})\} \subseteq \mathcal{U}_2$ . We can now choose a structure  $\sigma_2''$  with  $Dom(\sigma_2'') \subseteq \mathcal{U}_2$  that is isomorphic to  $\sigma_2'$  and that agrees with  $\sigma_2'$  except for  $c_1, \ldots c_{M+k+1}$ , whose interpretation is chosen as  $\sigma_2''(c_1), \ldots, \sigma_2''(c_{M+k+1}) \in \mathcal{U}_2 \setminus (Dom(\sigma_1') \cup Dom(\sigma_2'))$ . Then,  $(\mathcal{U}_1, \sigma_1')$  [resp.  $(\mathcal{U}_2, \sigma_2'')$ ] is isomorphic to  $(\mathbb{U}, \sigma_1)$  [resp.  $(\mathbb{U}, \sigma_2)$ ]. In particular, they have the same type i.e.,  $type^r(\mathcal{U}_1, \sigma_1') = type^r(\mathbb{U}, \sigma_1')$  and  $type^r(\mathcal{U}_2, \sigma_2'') = type^r(\mathbb{U}, \sigma_2')$ . Moreover, we have  $glue((\mathcal{U}_1, \sigma_1'), (\mathcal{U}_2, \sigma_2'')) = type^r(\mathcal{U}_1, \sigma_1') = type^r(\mathbb{U}, \sigma_1')$  and  $type^r(\mathcal{U}_2, \sigma_2'') = type^r(\mathbb{U}, \sigma_2')$ . Moreover, we have  $glue((\mathcal{U}_1, \sigma_1'), (\mathcal{U}_2, \sigma_2'')) = type^r(\mathcal{U}_1, \sigma_1')$  and  $type^r(\mathcal{U}_2, \sigma_2'') = type^r(\mathbb{U}, \sigma_2')$ . Moreover, we have  $glue((\mathcal{U}_1, \sigma_1'), (\mathcal{U}_2, \sigma_2'')) = type^r(\mathcal{U}_1, \sigma_1')$ .

```
encode(\sigma_1 \bullet \sigma_2, v). We compute:
```

```
 \begin{array}{l} \mathit{type}^r(\mathit{encode}(\sigma_1 \bullet \sigma_2, \nu)) = \\ \mathit{type}^r(\mathit{glue}((\mathcal{U}_1, \sigma_1'), (\mathcal{U}_2, \sigma_2''))) = \\ \mathit{glue}^\sharp(\mathit{type}^r((\mathcal{U}_1, \sigma_1')), \mathit{type}^r((\mathcal{U}_2, \sigma_2''))) = \\ \mathit{glue}^\sharp(\mathit{type}^r((\mathbb{U}, \sigma_1')), \mathit{type}^r((\mathbb{U}, \sigma_2'))) = \\ \mathit{glue}^\sharp(\mathit{type}^r(\mathit{encode}(\sigma_1, \nu)), \mathit{type}^r(\mathit{encode}(\sigma_2, \nu))) \end{array}
```

**Lemma 10.** Let  $k \ge 1$  be an integer,  $\phi$  be an MSO sentence,  $\sigma \in Str(\Sigma \cup \{\mathfrak{D}\})$  be a structure and v be a store such that  $(\sigma, v) \models_{\Delta(k, \phi)} A^{\tau}(x_1, \dots, x_{k+1}), v(x_i) \notin \sigma(\mathfrak{D})$  for all  $i \in [1, k+1]$ , and  $v(x_i) \ne v(x_j)$  for all  $i \ne j$ . Then,  $type^{qr(\phi)}(encode(rem_{\mathfrak{D}}(\sigma), v)) = \tau$ , where  $rem_{\mathfrak{D}}(\sigma) \in Str(\Sigma)$  is the restriction of  $\sigma$  to  $\Sigma$ .

*Proof.* We prove the claim by induction on the number of rule applications. The claim clearly holds for the base case, by a rule of type (12). We now consider a rule of type (10), i.e., we have  $(\sigma, v) \models_{\Delta(k,\phi)} A^{\tau_1}(x_1, \dots, x_{k+1}) * A^{\tau_2}(x_1, \dots, x_{k+1})$ , such that  $\tau = glue^{\sharp}(\tau_1, \tau_2)$ . Then, there are structures  $\sigma_1$  and  $\sigma_2$  with  $(\sigma_i, v) \models_{\Delta(k,\phi)} A^{\tau_i}(x_1, \dots, x_{k+1})$ , for i = 1, 2 and  $\sigma_1 \bullet \sigma_2 = \sigma$ . By the inductive hypothesis, we have that  $type^{qr(\phi)}(encode(rem_{\mathfrak{D}}(\sigma_i), v)) = \tau_i$ , for i = 1, 2. Because every derivation of  $\Delta(k,\phi)$  is also a derivation of  $\Delta(k)$ , obtained by removing the type annotations from the rules in  $\Delta(k,\phi)$ , we get that  $(\sigma_i, v) \models_{\Delta(k)} A(x_1, \dots, x_{k+1})$ , for i = 1, 2. By Lemma 6 we have that  $Rel(\sigma_i) \subseteq \sigma_i(\mathfrak{D}) \cup \{v(x_1), \dots, v(x_{k+1})\}$ , for i = 1, 2. Since  $\sigma = \sigma_1 \bullet \sigma_2$ , we have that  $\sigma_1(\mathfrak{D}) \cap \sigma_2(\mathfrak{D}) = \emptyset$  and  $rem_{\mathfrak{D}}(encode(\sigma, v)) = rem_{\mathfrak{D}}(encode(\sigma_1, v)) \bullet rem_{\mathfrak{D}}(encode(\sigma_2, v))$ . We compute

```
 \begin{array}{l} \textit{type}^{qr(\phi)}(\textit{encode}(\textit{rem}_{\mathfrak{D}}(\sigma), \nu)) = \\ \textit{glue}^{\sharp}(\textit{type}^{qr(\phi)}(\textit{encode}(\textit{rem}_{\mathfrak{D}}(\sigma_{1}), \nu)), \textit{type}^{qr(\phi)}(\textit{encode}(\textit{rem}_{\mathfrak{D}}(\sigma_{2}), \nu))) = \\ \textit{glue}^{\sharp}(\tau_{1}, \tau_{2}) = \tau \end{array}
```

by Lemma 9. We now consider rules of type (11) i.e., we have  $(\sigma, v) \models_{\Delta(k, \phi)} \exists y . \mathfrak{D}(y) *$   $\mathsf{A}^{\tau_1}(x_1, \dots, x_{k+1})[x_i/y]$ , for some  $i \in [1, k+1]$ , such that  $\tau = glue^\sharp(fgcst^\sharp_{M+i}(\tau_1), \rho_i)$  for the type  $\rho_i$  of a standard structure  $S \in Str(\{c_{M+i}\})$  with a singleton universe, for  $i \in [1, k+1]$ . Then, there is an element  $u \in \mathbb{U}$ , such that  $(\sigma', v[x_i \leftarrow u]) \models_{\Delta(k, \phi)} \mathsf{A}^{\tau_1}(x_1, \dots, x_{k+1})$ , where the structure  $\sigma'$  agrees with  $\sigma$ , except that  $\mathfrak{D}$  does not hold for u in  $\sigma'$ . By the inductive hypothesis,  $type^{\operatorname{qr}(\phi)}(encode(rem_{\mathfrak{D}}(\sigma'), v[x_i \leftarrow u])) = \tau_1$ . Because every derivation of  $\Delta(k, \phi)$  is also a derivation of  $\Delta(k)$ , obtained by removing the type annotations from the rules in  $\Delta(k, \phi)$ , we get that  $(\sigma_i, v) \models_{\Delta(k)} \mathsf{A}(x_1, \dots, x_{k+1})$ , for i = 1, 2. By Lemma 6 we have that  $\operatorname{Rel}(\sigma') \subseteq \sigma'(\mathfrak{D}) \cup \{v(x_1), \dots, v(x_{k+1})\} \setminus \{v(x_i)\} \cup \{u\}$ . Because of  $v(x_i) \neq u$  (due to the assumption  $v(x_i) \notin \sigma(\mathfrak{D})$ ) and because of  $v(x_i) \neq v(x_j)$  for all  $i \neq j$ , we get that  $encode(rem_{\mathfrak{D}}(\sigma), v) = glue(fgcst_{M+i}(encode(rem_{\mathfrak{D}}(\sigma'), v[x_i \leftarrow u])), S')$ , where  $S' \in Str(\{c_{M+i}\})$  is the standard structure with singleton universe  $\{v(x_i)\}$ . Because S is isomorphic to S', we obtain:

```
 \begin{split} &type^{\operatorname{qr}(\phi)}(encode(rem_{\mathfrak{D}}(\sigma), \mathsf{v})) = \\ &type^{\operatorname{qr}(\phi)}(glue(fgcst_{M+i}(encode(rem_{\mathfrak{D}}(\sigma'), \mathsf{v}[x_i \leftarrow u])), S')) = \\ &glue^{\sharp}(type^{\operatorname{qr}(\phi)}(fgcst_{M+i}(encode(rem_{\mathfrak{D}}(\sigma'), \mathsf{v}[x_i \leftarrow u]))), type^{\operatorname{qr}(\phi)}(S')) = \\ &glue^{\sharp}(fgcst_{M+i}^{\sharp}(type^{\operatorname{qr}(\phi)}(encode(rem_{\mathfrak{D}}(\sigma'), \mathsf{v}[x_i \leftarrow u]))), type^{\operatorname{qr}(\phi)}(S)) = \\ &glue^{\sharp}(fgcst_{M+i}^{\sharp}(\tau_1), \rho_i) = \tau \end{split}
```

**Lemma 11.** Let  $k \ge 1$  be an integer,  $\phi$  be an MSO sentence,  $\sigma \in Str(\Sigma)$  be a structure of treewidth  $tw(\sigma) \le k$ , witnessed by some reduced tree decomposition  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$ , and v be a store with  $\lambda(r) = \{v(x_1), \dots, v(k+1)\}$  and  $v(x_i) \ne v(x_j)$  for all  $i \ne j$ , such that  $type^{qr(\phi)}(encode(\sigma, v)) = \tau$  and  $\phi \in \tau$ . Then, we have  $(add_{\mathfrak{D}}^{\mathcal{T}}(\sigma), v) \models_{\Delta(k, \phi)} A^{\tau}(x_1, \dots, x_{k+1})$ .

*Proof.* The proof proceeds by induction on the structure of  $\mathcal{T}$ . Clearly the claim holds for the base case, by a rule of type (12). For the inductive step, we assume first that the root of  $\mathcal{T}$  has two children. The subtrees  $\mathcal{T}_1$  and  $\mathcal{T}_2$  rooted in the two children induce substructures  $\sigma_1$  and  $\sigma_2$  of  $\sigma$ , where  $\langle v_1, \ldots, v_{\#R} \rangle \in \sigma_i(R)$  if and only if  $\langle v_1, \ldots, v_{\#R} \rangle$  is witnessed by some leaf of the respective subtree. Because  $\mathcal{T}$  is a reduced tree decomposition, there is at most one leaf that witnesses a tuple  $\langle v_1, \ldots, v_{\#R} \rangle \in \sigma_i(R)$ . Hence, we have  $\sigma = \sigma_1 \bullet \sigma_2$  and  $encode(\sigma, v) = encode(\sigma_1, v) \bullet encode(\sigma_2, v)$ . Because the only elements that can appear as labels in  $\mathcal{T}_1$  and  $\mathcal{T}_2$  are  $v(x_1), \ldots, v(x_{k+1})$  (as these are the labels of the root of the tree decomposition), we get that  $Rel(\sigma_1) \cap Rel(\sigma_2) \subseteq \{v(x_1), \ldots, v(x_{k+1})\}$ . Let  $\tau_i = type^{qr(\phi)}(encode(\sigma_i, v))$ , for i = 1, 2. From the inductive hypothesis, we obtain  $(add_{\mathfrak{D}}^{\mathcal{T}_i}(\sigma_i), v) \models_{\Delta(k,\phi)} A^{\tau_i}(x_1, \ldots, x_{k+1})$ , for i = 1, 2. Let  $\tau \stackrel{\text{def}}{=} glue^{\sharp}(\tau_1, \tau_2)$ . By Lemma 9, we obtain:

```
 \begin{aligned} \textit{type}^{qr(\phi)}(\textit{encode}(\sigma, \nu)) &= \textit{type}^{qr(\phi)}(\textit{encode}(\sigma_1, \nu) \bullet \textit{encode}(\sigma_2, \nu)) = \\ \textit{glue}^{\sharp}(\textit{type}^{qr(\phi)}(\textit{encode}(\sigma_1, \nu)), \textit{type}^{qr(\phi)}(\textit{encode}(\sigma_2, \nu))) &= \textit{glue}^{\sharp}(\tau_1, \tau_2) = \tau \end{aligned}
```

Hence, we now get that  $(add_{\mathfrak{D}}^{\mathcal{T}}(\sigma), \mathbf{v}) \models_{\Delta(k,\phi)} \mathsf{A}^{\tau}(x_1, \dots, x_{k+1})$ , by a rule of type (10). We now assume that the root of  $\mathcal{T}$  has a single child which is not a leaf. We consider the subtree  $\mathcal{T}_1$  rooted at this child. Then, there is an element  $u \notin \{\mathbf{v}(x_1), \dots, \mathbf{v}(x_{k+1})\}$ , such that the root of  $\mathcal{T}_1$  is labeled by  $\{\mathbf{v}(x_1), \dots, \mathbf{v}(x_{i-1}), u, \mathbf{v}(x_{i+1}), \dots, \mathbf{v}(x_{k+1})\}$ . Let  $\tau_1 \stackrel{\text{def}}{=} type^{\operatorname{qr}(\phi)}(encode(\sigma, \mathbf{v}[x_i \leftarrow u]))$ . By the inductive hypothesis, we obtain that  $(add_{\mathfrak{D}}^{\mathcal{T}_1}(\sigma), \mathbf{v}[x_i \leftarrow u]) \models_{\Delta(k,\phi)} \mathsf{A}^{\tau_1}(x_1, \dots, x_{k+1})$ . Let  $\tau \stackrel{\text{def}}{=} glue^{\sharp}(fgcst^{\sharp}_{M+i}(\tau_1), \rho_i)$  for the type  $\rho_i$  of a structure  $S \in Str(\{c_{M+i}\})$  with singleton universe  $\{\mathbf{v}(x_i)\}$ . Because of  $\mathbf{v}(x_i) \neq u$  and because of  $\mathbf{v}(x_i) \neq v(x_j)$  for all  $i \neq j$ , we get that  $encode(rem_{\mathfrak{D}}(\sigma), \mathbf{v}) = glue(fgcst_{M+i}(encode(rem_{\mathfrak{D}}(\sigma'), \mathbf{v}[x_i \leftarrow u])), S)$ . We compute:

```
 \begin{split} &type^{\operatorname{qr}(\phi)}(encode(rem_{\mathfrak{D}}(\sigma), \mathsf{v})) = \\ &type^{\operatorname{qr}(\phi)}(glue(fgcst_{M+i}(encode(rem_{\mathfrak{D}}(\sigma'), \mathsf{v}[x_i \leftarrow u])), S)) = \\ &glue^{\sharp}(type^{\operatorname{qr}(\phi)}(fgcst_{M+i}(encode(rem_{\mathfrak{D}}(\sigma'), \mathsf{v}[x_i \leftarrow u]))), type^{\operatorname{qr}(\phi)}(S)) = \\ &glue^{\sharp}(fgcst_{M+i}^{\sharp}(type^{\operatorname{qr}(\phi)}(encode(rem_{\mathfrak{D}}(\sigma'), \mathsf{v}[x_i \leftarrow u]))), type^{\operatorname{qr}(\phi)}(S)) = \\ &glue^{\sharp}(fgcst_{M+i}^{\sharp}(\tau_1), \rho_i) = \tau \end{split}
```

We now recognize that  $add_{\mathfrak{D}}^{\mathcal{T}_1}(\sigma)$  agrees with  $add_{\mathfrak{D}}^{\mathcal{T}}(\sigma)$  except that  $add_{\mathfrak{D}}^{\mathcal{T}}(\sigma)(\mathfrak{D}) = add_{\mathfrak{D}}^{\mathcal{T}_1}(\sigma)(\mathfrak{D}) \cup \{u\}$ . Hence, we get that  $(add_{\mathfrak{D}}^{\mathcal{T}}(\sigma), \mathbf{v}) \models_{\Delta(k,\phi)} \exists y . \mathfrak{D}(y) * \mathsf{A}_{\tau}(x_1, \dots, x_{k+1})[x_i/y]$  i.e., that  $(add_{\mathfrak{D}}^{\mathcal{T}}(\sigma), \mathbf{v}) \models_{\Delta(k,\phi)} \mathsf{A}^{\tau}(x_1, \dots, x_{k+1})$  by a rule of type (11).

Then  $\Delta(k, \phi)$  is the set of rules from Figure 1 (b), whose property is stated below:

**Proposition 6.** Given  $k \ge 1$  and an MSO sentence  $\phi$ , for any structure  $\sigma \in Str(\Sigma)$ , the following are equivalent: (1)  $\sigma \Vdash \phi$  and  $tw(\sigma) \le k$ , and (2) there is a  $\mathfrak{D}$ -extension  $\sigma'$  of  $\sigma$  with  $\sigma' \models_{\Delta(k,\phi)} \mathsf{A}_{k,\phi}()$ .

*Proof.* "(1)  $\Rightarrow$  (2)" Since  $\operatorname{tw}(\sigma) \leq k$ , there exists a reduced tree decomposition  $\mathcal{T} = (\mathcal{N}, \mathcal{F}, r, \lambda)$  of width k, by Lemma 5. Let v be a store such that  $\lambda(r) = \{v(x_1), \dots, v(x_{k+1})\}$  and  $v(x_i) \neq v(x_j)$  for all  $i \neq j \in [1, k+1]$ . Thus, we obtain  $(add_{\mathfrak{D}}^T(\sigma), v) \models_{\Delta(k, \phi)} A^{\tau}(x_1, \dots, x_{k+1})$ , by Lemma 11, for  $\tau \stackrel{\text{def}}{=} type^{\operatorname{qr}(\phi)}(encode(\sigma, v))$ . Since, moreover, we have assumed that  $\sigma \Vdash \phi$ , we have  $\phi \in \tau \stackrel{\text{def}}{=} type^{\operatorname{qr}(\phi)}(encode(\sigma, v))$ . Let  $\sigma'$  be the  $\mathfrak{D}$ -extension obtained from  $add_{\mathfrak{D}}^T(\sigma)$  by setting  $\sigma'(\mathfrak{D}) = add_{\mathfrak{D}}^T(\sigma)(\mathfrak{D}) \cup \{v(x_1), \dots, v(x_{k+1})\}$ . Then, we obtain  $\sigma' \models_{\Delta(k, \phi)} A_{k, \phi}()$ , by a rule of type (13).

tain  $\sigma' \models_{\Delta(k,\phi)} A_{k,\phi}()$ , by a rule of type (13). "(2)  $\Rightarrow$  (1)" Let  $\sigma'$  be a  $\mathfrak{D}$ -extension of  $\sigma$  with  $\sigma' \models_{\Delta(k,\phi)} A_{k,\phi}()$ . Since  $\sigma' \models_{\Delta(k,\phi)} A_{k,\phi}()$ , there exists a  $\mathfrak{D}$ -extension  $\sigma''$  of  $\sigma$  and a store  $\nu$  with  $\nu(x_i) \neq \nu(x_j)$  for all  $i \neq j \in [1, k+1]$ , such that  $(\sigma'', \nu) \models_{\Delta(k,\phi)} A^{\tau}(x_1, \dots, x_{k+1})$ , for some type  $\tau$ , such that  $\phi \in \tau$ , by a rule of type (13). By Lemma 10, we obtain  $type^{qr(\phi)}(encode(\sigma, \nu')) = \tau$ , thus  $encode(\sigma, \nu') \Vdash \phi$ , leading to  $\sigma \Vdash \phi$ . Moreover, we have  $tw(\sigma) \leq k$ , by Lemma 8, because each derivation of  $\sigma' \models_{\Delta(k,\phi)} A_{k,\phi}()$  corresponds to a derivation of  $\sigma' \models_{\Delta(k)} A_k()$ , obtained by removing the type annotations from the rules in  $\Delta(k,\phi)$ .

The above result shows that SLR can define the models  $\sigma \in Str(\Sigma)$  of a given MSO formula whose treewidth is bounded by a given integer, up to extending the signature  $\Sigma$  with a monadic relation symbol  $\mathfrak{D}$ , whose interpretation subsumes the set  $Rel(\sigma)$  of elements that occur in some tuple from  $\sigma(R)$ , for some relation symbol  $R \in \Sigma$ . It is unclear, for the moment, how to prove MSO  $\subseteq^k$  SLR without introducing this gadget.

**Effectiveness of the Construction.** The above construction of the SID  $\Delta(k,\phi)$  is effective apart from rule 12, where one needs to determine the type of a structure S with infinite universe. However, we argue in the following that determining this type can be reduced to computing the type of a finite structure; the type of such a structure can in turn be determined by solving finitely many MSO model checking problems on finite structures, each of which being known to be PSPACE-complete [39].

Given an integer  $k \ge 0$  and a structure  $S = (\mathbb{U}, \sigma) \in Str(\Sigma)$ , we define the finite structure  $S^k = (D^k, \sigma)$ , where  $D^k \stackrel{\text{def}}{=} \text{Dom}(\sigma) \cup \{u_1, \dots, u_k\}$ , for pairwise distinct elements  $u_1, \dots, u_k \in \mathbb{U} \setminus \text{Dom}(\sigma)$ . Then, for any quantifier rank r, the structures S and  $S^{2^r}$  have the same r-type, as shown below:

**Lemma 12.** Given 
$$r \ge 0$$
 and  $S = (\mathbb{U}, \sigma) \in Str(\Sigma)$ , we have  $type^r(S) = type^r(S^{2^r})$ .

*Proof.* We consider the *r*-round MSO Ehrenfeucht-Fraïssé game: In every round, Spoiler picks a vertex u or a set of vertices U in S or  $S^{2^r}$  and Duplicator answers with a vertex or a set of vertices in the other structure. Duplicator wins iff after *r*-rounds the substructures induced by the selected vertices are isomorphic. We now sketch a winning strategy for Duplicator (as the argument is standard, we leave the details to the reader): For vertices in  $Dom(\sigma)$  the Duplicator plays the same vertices in the respective other structure (this applies to single vertices as well as sets of vertices). For the vertices that do not belong to  $Dom(\sigma)$  in the other structure such that the selected vertices belong to the same subsets played in the previous rounds; care has to be taken for the involved cardinalities, if playing in  $S^{2^r}$  the Duplicator limits himself to at most  $2^{r-k-1}$  vertices that belong to any combination of previously played subsets or the complement of these subsets, where k is the

number of previously played rounds; this choice is sufficient such that after r-rounds the substructures induced by the selected vertices are isomorphic.

## 8 The Remaining Cases

We present the results for the problems from Table 1, not already covered in §4, §5 and §6.

**SO**  $\not\subseteq^{(k)}$  **MSO** First, SO  $\not\subseteq^k$  MSO is a consequence of the fact that any non-recognizable context-free word language, corresponding to a non-MSO-definable family of structures can be defined in SLR. Since SLR  $\subseteq$  SO, we obtain that SO  $\not\subseteq^k$  MSO. Moreover, SO  $\not\subseteq$  MSO follows from the fact that our counterexample involves only structures of treewidth 1 (i.e., lists encoding words as in §4).

**SLR**  $\subseteq^k$  **SO** By applying the translation of SLR to SO from §6 to  $\Delta(k)$  (Fig. 1a) and to a given SID  $\Delta$  defining a predicate A of zero arity, respectively, and taking the conjunction of the results, we obtain an SO formula that defines the SLR models of  $(A(),\Delta)$  of treewidth at most k, thus proving SLR  $\subseteq^k$  SO.

**(M)SO**  $\subseteq^k$  **(M)SO** For each given  $k \ge 1$ , there exists an MSO formula  $\theta_k$  that defines the structures of treewidth at most k [12, Proposition 5.11]. This is a consequence of the Graph Minor Theorem proved by Robertson and Seymour [35], combined with the fact that bounded treewidth graphs are closed under taking minors and that the property of having a given finite minor is MSO-definable<sup>4</sup>. Then, for any given (M)SO formula  $\phi$ , the (M)SO formula  $\phi \land \theta_k$  defines the models of  $\phi$  of treewidth at most k.

**Open Problems** The following problems from Table 1 are currently open:  $SLR \subseteq {}^k$  SLR and  $SO \subseteq {}^k$  SLR, both conjectured to have a negative answer. In particular, the difficulty concerning  $SLR \subseteq {}^k$  SLR is that, in order to ensure treewidth boundedness, it seems necessary to force the composition of structures to behave like glueing (see the definition of  $\Delta(k)$  in Fig. 1a), which is however difficult to ensure without an additional predicate symbol.

Since MSO  $\subseteq^k$  SLR but MSO  $\not\subseteq$  SLR, it is natural to ask for the existence of a fragment of SLR that describes only MSO-definable families of structures of bounded treewidth. Moreover, in earlier work [20], we showed that a significant fragment of SL, given by three restrictions on the syntax of the rules, can be embedded in MSO and defines only structures of bounded treewidth. Unfortunately, since SLR can define context-free languages (Prop. 3), the MSO-definability of the set of models of a SLR formula is undecidable, as a consequence of the undecidability of the recognizability of context-free languages [19]. On the other hand, the treewidth-boundedness of the set of models of a SLR formula is an open problem, related to the open problem SLR  $\subseteq^k$  SLR above.

<sup>&</sup>lt;sup>4</sup> The original proof of Robertson and Seymour does not build  $\theta_k$  effectively, see [1] for an effective proof.

### 9 Conclusions and Future Work

We have compared the expressiveness of SLR, MSO and SO, in general and for models of bounded treewidth. Interestingly, we found that SLR and MSO are, in general, incomparable and subsumed by SO, whereas the models of bounded treewidth of MSO can be defined by SLR, modulo augmenting the signature with a unary relation symbol used to store the elements that occur in the original structure.

Future work concerns answering the open problems of the SLR-definability of structures defined by either an SLR or SO formula, of treewidth bounded by a given integer. A cornerstone is deciding whether a given SID defines only structures of bounded treewidth. Answering these questions would help the definition of SLR fragments with a decidable entailment problem, useful for system verification.

#### References

- I. Adler, M. Grohe, and S. Kreutzer. Computing excluded minors. In *Proceedings of the Nineteenth Annual ACM-SIAM Symposium on Discrete Algorithms*, SODA '08, page 641–650, USA, 2008. Society for Industrial and Applied Mathematics.
- 2. E. Ahrens, M. Bozga, R. Iosif, and J. Katoen. Reasoning about distributed reconfigurable systems. In *Object-Oriented Programming, Systems, Languages and Applications (OOP-SLA)*, volume To appear, 2022.
- B. Bollig, P. Bouyer, and F. Reiter. Identifiers in registers describing network algorithms with logic. In M. Bojanczyk and A. Simpson, editors, Foundations of Software Science and Computation Structures - 22nd International Conference, FOSSACS 2019, Held as Part of the European Joint Conferences on Theory and Practice of Software, ETAPS 2019, Prague, Czech Republic, April 6-11, 2019, Proceedings, volume 11425 of Lecture Notes in Computer Science, pages 115–132. Springer, 2019.
- 4. M. Bozga, L. Bueri, and R. Iosif. Decision problems in a logic for reasoning about reconfigurable distributed systems. In *International Joint Conference on Automated Reasoning*, volume to appear, 2022.
- M. Bozga, R. Iosif, and J. Sifakis. Verification of component-based systems with recursive architectures. CoRR, abs/2112.08292, 2021.
- R. Brochenin, S. Demri, and É. Lozes. On the almighty wand. *Inf. Comput.*, 211:106–137, 2012.
- J. Brotherston, D. Distefano, and R. L. Petersen. Automated cyclic entailment proofs in separation logic. In N. Bjørner and V. Sofronie-Stokkermans, editors, Automated Deduction - CADE-23 - 23rd International Conference on Automated Deduction, Wroclaw, Poland, July 31 - August 5, 2011. Proceedings, volume 6803 of Lecture Notes in Computer Science, pages 131–146. Springer, 2011.
- J. Brotherston, C. Fuhs, J. A. N. Pérez, and N. Gorogiannis. A decision procedure for satisfiability in separation logic with inductive predicates. In CSL-LICS, pages 25:1–25:10. ACM, 2014.
- C. Calcagno, P. Gardner, and M. Hague. From separation logic to first-order logic. In *Foundations of Software Science and Computational Structures*, pages 395

  –409, Berlin, Heidelberg, 2005. Springer Berlin Heidelberg.
- C. Calcagno, H. Yang, and P. W. O'Hearn. Computability and complexity results for a spatial assertion language for data structures. In R. Hariharan, M. Mukund, and V. Vinay, editors, FST TCS 2001: Foundations of Software Technology and Theoretical Computer Science, 21st

- Conference, Bangalore, India, December 13-15, 2001, Proceedings, volume 2245 of Lecture Notes in Computer Science, pages 108–119. Springer, 2001.
- 11. B. Courcelle. The monadic second-order logic of graphs VII: graphs as relational structures. *Theor. Comput. Sci.*, 101(1):3–33, 1992.
- B. Courcelle and J. Engelfriet. Graph Structure and Monadic Second-Order Logic: A Language-Theoretic Approach. Encyclopedia of Mathematics and its Applications. Cambridge University Press, 2012.
- 13. S. Demri and M. Deters. Expressive completeness of separation logic with two variables and no separating conjunction. *ACM Trans. Comput. Log.*, 17(2):12, 2016.
- 14. S. Demri, É. Lozes, and A. Mansutti. The effects of adding reachability predicates in quantifier-free separation logic. *ACM Trans. Comput. Log.*, 22(2):14:1–14:56, 2021.
- 15. H. Ebbinghaus and J. Flum. *Finite model theory*. Perspectives in Mathematical Logic. Springer, 1995.
- 16. M. Echenim, R. Iosif, and N. Peltier. The bernays-schönfinkel-ramsey class of separation logic with uninterpreted predicates. *ACM Trans. Comput. Log.*, 21(3):19:1–19:46, 2020.
- 17. M. Echenim, R. Iosif, and N. Peltier. Unifying decidable entailments in separation logic with inductive definitions. In A. Platzer and G. Sutcliffe, editors, *Automated Deduction CADE 28 28th International Conference on Automated Deduction, Virtual Event, July 12-15, 2021, Proceedings*, volume 12699 of *Lecture Notes in Computer Science*, pages 183–199. Springer, 2021.
- 18. C. Enea, M. Sighireanu, and Z. Wu. On automated lemma generation for separation logic with inductive definitions. In B. Finkbeiner, G. Pu, and L. Zhang, editors, *Automated Technology for Verification and Analysis 13th International Symposium, ATVA 2015, Shanghai, China, October 12-15, 2015, Proceedings*, volume 9364 of *Lecture Notes in Computer Science*, pages 80–96. Springer, 2015.
- 19. S. Greibach. A note on undecidable properties of formal languages. *Math. Systems Theory*, 2:1–6, 1968.
- 20. R. Iosif, A. Rogalewicz, and J. Simácek. The tree width of separation logic with recursive definitions. In M. P. Bonacina, editor, *Automated Deduction CADE-24 24th International Conference on Automated Deduction, Lake Placid, NY, USA, June 9-14, 2013. Proceedings*, volume 7898 of *Lecture Notes in Computer Science*, pages 21–38. Springer, 2013.
- C. Jansen, J. Katelaan, C. Matheja, T. Noll, and F. Zuleger. Unified reasoning about robustness properties of symbolic-heap separation logic. In H. Yang, editor, *ESOP*, volume 10201 of *Lecture Notes in Computer Science*, pages 611–638. Springer, 2017.
- 22. J. Katelaan, C. Matheja, and F. Zuleger. Effective entailment checking for separation logic with inductive definitions. In *TACAS* (2), volume 11428 of *Lecture Notes in Computer Science*, pages 319–336. Springer, 2019.
- 23. J. Katelaan and F. Zuleger. Beyond symbolic heaps: Deciding separation logic with inductive definitions. In E. Albert and L. Kovács, editors, LPAR 2020: 23rd International Conference on Logic for Programming, Artificial Intelligence and Reasoning, Alicante, Spain, May 22-27, 2020, volume 73 of EPiC Series in Computing, pages 390–408. EasyChair, 2020.
- B. Khoussainov and A. Nerode. Automata Theory and Its Applications. Birkhauser Boston, Inc., 2001.
- É. Lozes. Expressivité des logiques spatiales. Thèse de doctorat, Laboratoire de l'Informatique du Parallélisme, ENS Lyon, France, Nov. 2004.
- 26. J. A. Makowsky. Algorithmic uses of the feferman-vaught theorem. *Ann. Pure Appl. Log.*, 126(1-3):159–213, 2004.
- A. Mansutti. Logiques de séparation: complexité, expressivité, calculs. (Reasoning with separation logics: complexity, expressive power, proof systems). PhD thesis, University of Paris-Saclay, France, 2020.

- 28. P. W. O'Hearn. Separation logic. Commun. ACM, 62(2):86-95, 2019.
- 29. P. W. O'Hearn and D. J. Pym. The logic of bunched implications. *Bull. Symb. Log.*, 5(2):215–244, 1999.
- J. Pagel, C. Matheja, and F. Zuleger. A decision procedure for guarded separation logic. *Transactions on Computational Logic*, to appear. See "Complete Entailment Checking for Separation Logic with Inductive Definitions", abs/2002.01202, CoRR for pre-print.
- 31. B. Peres, O. A. d. O. Souza, O. Goussevskaia, C. Avin, and S. Schmid. Distributed self-adjusting tree networks. In *IEEE INFOCOM 2019 IEEE Conference on Computer Communications*, pages 145–153, 2019.
- 32. B. S. Peres, O. A. de Oliveira Souza, O. Goussevskaia, C. Avin, and S. Schmid. Distributed self-adjusting tree networks. In 2019 IEEE Conference on Computer Communications, IN-FOCOM 2019, Paris, France, April 29 May 2, 2019, pages 145–153. IEEE, 2019.
- 33. D. Pym and W. Venters. Modelling interfaces in the decentralized internet of things. In *International Conference on Information Systems (ICIS)*, 2020.
- 34. D. J. Pym. Resource semantics: logic as a modelling technology. *ACM SIGLOG News*, 6(2):5–41, 2019.
- 35. M. R. F. R. G. Downey. Parameterized Complexity. Springer New York, NY, 1999.
- J. C. Reynolds. Separation logic: A logic for shared mutable data structures. In 17th IEEE Symposium on Logic in Computer Science (LICS 2002), 22-25 July 2002, Copenhagen, Denmark, Proceedings, pages 55-74. IEEE Computer Society, 2002.
- 37. P. Seymour and R. Thomas. Graph searching and a min-max theorem for tree-width. *Journal of Combinatorial Theory, Series B*, 58(1):22–33, 1993.
- 38. D. D. Sleator and R. E. Tarjan. Self-adjusting binary search trees. *J. ACM*, 32(3):652–686, July 1985.
- 39. M. Y. Vardi. The complexity of relational query languages (extended abstract). In *Proceedings of the 14th Annual ACM Symposium on Theory of Computing, May 5-7, 1982, San Francisco, California, USA*, pages 137–146. ACM, 1982.