

Quantum Register Algebra: the mathematical language for quantum computing*

Hrdina, J.¹[0000-0003-2460-7571], Hildenbrand D.²[0000-0002-6384-4345],
 Návrat A.¹[0000-0002-8100-4032], Steinmetz C.⁴[⁻],
 Alves R.³[0000-0002-3171-9339], Lavor C.⁴[0000-0002-8105-3627],
 Vašík P.¹[0000-0001-6725-7378], and Eryganov I.¹[0000-0003-2203-882X]

¹ Brno University of Technology, Czech Republic

{hrdina, navrat.a, vasik}@fme.vutbr.cz, xperya00@vutbr.cz

² Technische Universität Darmstadt, Darmstadt, 64297, Germany
 dietmar.hildenbrand@gmail.com

³ Federal University of ABC, Sao Bernardo, Brazil alves.rafael@ufabc.edu.br

⁴ :em engineering methods AG, Darmstadt, Germany
 christian.steinmetz@e-mail.de

⁵ University of Campinas, Campinas, Brazil clavor@unicamp.br

Abstract. We introduce Quantum Register Algebra (QRA) as an efficient tool for quantum computing. We show the direct link between QRA and Dirac formalism. We present GAALOP (Geometric Algebra Algorithms Optimizer) implementation of our approach. Using the QRA basis vectors definitions given in Section 4 and the framework based on the de Witt basis presented in Section 5, we are able to fully describe and compute with QRA in GAALOP using the geometric product. We illustrate the intuitiveness of this computation by presenting the QRA form for the well known SWAP operation on a two qubit register.

Keywords: quantum computing · geometric algebra · quantum register algebra

1 Introduction

Geometric Algebra proved in recent years that it is a mathematical system covering many other mathematical systems as conventionally used in engineering and physical science, [4,5,6,9]. Examples are linear algebra, quaternions, Dirac and Pauli matrices, Plucker coordinates to mention only a few. This means, the big advantage of Geometric Algebra is that you do not have to learn different mathematical systems in order to handle various application areas. You simply have to learn only one mathematical system to handle them. Another simplification based on Geometric Algebra is that both objects and operations are handled in one algebra, means you do not have to distinguish, for instance, between points or vectors as objects and matrices for the description of operations on them.

* Supported by FAPESP and CNPq.

Now, the question is: can Geometric Algebra also advantageously be used for quantum computing? Quantum computing, currently, is based on working with complex numbers, matrices of complex numbers and tensor computing in order to handle operations with arbitrary numbers of qubits.

Some papers on geometric algebras and quantum computing demonstrate application of geometric algebras $\mathbb{G}_{4,1}$ (relativistic case) and $\mathbb{G}_{3,0}$ (nonrelativistic case), [3], geometric algebra $\mathbb{G}_{n,n}$, [1] and finally a complex Clifford algebra \mathbb{C}_n , [2].

In this paper, we show that quantum computing can simply be based on a Geometric Algebra called QRA (quantum register algebra). In Sect. 2, we show that complex numbers can easily be identified within Geometric Algebra.

The Dirac formalism is a very useful formalism to describe quantum computing. Although it is originally based on complex matrices (see Sect. 3), we show in our definition of QRA according to Sect. 4 and Sect. 5, that it can still be used with QRA.

In order to compute with QRA, we use GAALOP, a stand alone geometric algebra algorithm optimizer [Ref for GAALOP]. We extended the GAALOP tool presented in [1] for the QRA support based on the definitions presented in Sections 4 and 5. The full implementation is shown in Sect. 6. In order to simplify the computing as much as possible, we also integrated it in our online tool GAALOPWeb. In Sect. 7, we present how easy it is to compute with QRA using GAALOP, for this we present the QRA form for the SWAP gate. The big advantage for quantum computing beginners is that they only have to know Geometric Algebra in order to describe the objects and operations of quantum computing.

2 From complex numbers to geometric algebras and back again

The algebra of complex numbers \mathbb{C} is an essential tool for quantum computing. Qubits are realised by vectors in complex vector space \mathbb{C}^n and the gates by matrices $n \times n$ over the complex numbers. In our approach, the complex linear algebra is the language for quantum computing. More precisely, we are using the natural concept of complex geometric algebras with the complex numbers as one of their instances. In the sequel, we investigate these concepts in a more detailed way.

Formally, geometric algebra $\mathbb{G}_{p,q}$ is a free, associative, distributive and unitary algebra over the set of abstract elements $\{e_1, \dots, e_n\}$ endowed with the following identities:

$$\begin{aligned} e_i e_j &= -e_j e_i, \text{ where } i \neq j, \\ e_i^2 &= 1, \text{ where } i = 1, \dots, p, \\ e_i^2 &= -1, \text{ where } i = p + 1, \dots, n. \end{aligned} \tag{1}$$

In computer science notation, we understand $\mathbb{G}_{p,q}$ as a vector space where vectors are built as words over the alphabet $\{e_1, \dots, e_n\}$, including an empty word,

using the following equivalency. Two words are equivalent (they are different representations of the same object) if the first can be rewritten into the second and vice versa with the help of identities (1), distributivity and associativity.

For example, let us consider geometric algebra $\mathbb{G}_{1,1}$, so we have words over the alphabet $\{e_1, e_2\}$ and identities $e_1^2 = 1$, $e_2^2 = -1$ together with anti-commutativity $e_1e_2 = -e_2e_1$. Then the vector space basis is of the form

$$\{1, e_1, e_2, e_1e_2\}. \quad (2)$$

Hence, for example the word $e_2e_1e_2e_1e_1e_2e_2$ can be rewritten to $-e_1$ with the help of identities (1) in the following way:

$$e_2e_1e_2e_1e_1e_2e_2 = e_2e_1e_2(1)(-1) = e_1e_2e_2 = e_1(-1) = -e_1.$$

The element e_1 is in the basis (2). We can see that the elements of geometric algebra $\mathbb{G}_{1,1}$ are the linear combinations over the basis (2), i.e.

$$\mathbb{G}_{1,1} = \{x_1 + x_2e_1 + x_3e_2 + x_4e_1e_2 | x_i \in \mathbb{R}\} \quad (3)$$

together with multiplication given by identities (1). For example

$$\begin{aligned} (e_1 + 2e_1e_2)(1 + e_1 - 3e_2) &= e_1(1 + e_1 - 3e_2) + 2e_1e_2(1 + e_1 - 3e_2) \\ &= e_1 + e_1e_1 - e_13e_2 + 2e_1e_2 + 2e_1e_2e_1 - 2e_1e_23e_2 \\ &= e_1 + (1) - 3e_1e_2 + 2e_1e_2 - 2e_2e_1e_1 - 6e_1(-1) \\ &= 1 + e_1 - e_1e_2 - 2e_2(1) + 6e_1 \\ &= 1 + 7e_1 - 2e_2 - e_1e_2 \in \mathbb{G}_{1,1}. \end{aligned}$$

In any geometric algebra $\mathbb{G}(p, q)$ such that $p > 1$ or $q > 1$ we can find a subalgebra isomorphically equivalent to \mathbb{C} in the following way: if $p > 1$ we have two elements $e, f \in \mathbb{G}(p, q)$ such that $e^2 = f^2 = 1$ and $ef = -fe$, so

$$(ef)^2 = efef = -eeff = -e^2f^2 = -1$$

and

$$\mathbb{C} \cong \bar{\mathbb{C}} = \{a + b(ef) | a, b \in \mathbb{R}\} \subset \mathbb{G}(p, q).$$

In the same way, if we have $q > 1$ then we have two elements e, f such that $e^2 = f^2 = -1$ and $ef = -fe$, so

$$(ef)^2 = efef = -eeff = -e^2f^2 = -1(-1)(-1) = -1.$$

Note that the element ef commutes with the other basis elements in both cases.

Remark 1. The complex numbers \mathbb{C} are in fact isomorphically equivalent geometric algebra $\mathbb{G}_{0,1}$. Indeed, $\mathbb{G}_{0,1}$ is a space

$$\mathbb{G}_{0,1} = \{x_1 + x_2e_1 | x_i \in \mathbb{R}\} \quad (4)$$

such that $e_1^2 = -1$ which is the vector space isomorphically equivalent to \mathbb{C} . The specific concept for the imaginary unit used in QRA is described in Sect. 4.

3 Matrices vs. Dirac formalism

In this section, we show the direct link between Dirac formalism and geometric algebras. Original quantum mechanics is based on Dirac formalism, but quantum computing can be built up of matrices because the Hilbert space of qubits' states is finite. We briefly recall the link between matrices and Dirac formalism, [10].

– the n -qubit (ket)

$$|i\rangle = |a_1 \cdots a_{n-1} a_n\rangle, \text{ where } a_i \in \{0, 1\} \text{ and } i = a_1 2^{n-1} + \cdots + a_n 2^0$$

$$\iff \begin{pmatrix} 0 \\ \vdots \\ 1 \\ \vdots \\ 0 \end{pmatrix}, \text{ where 1 is on } i+1 \text{ position, 0 otherwise.}$$

– the dual n -qubit (bra)

$$\langle i| = \langle a_1 \cdots a_{n-1} a_n|, \text{ where } a_i \in \{0, 1\} \text{ and } i = a_1 2^{n-1} + \cdots + a_n 2^0$$

$$\iff (0 \cdots 1 \cdots 0), \text{ where 1 is on } i+1 \text{ position, 0 otherwise.}$$

The n -qubit gates are matrices $A = (a_{ij})$, where $i, j = 1, \dots, 2^n$. So if a matrix A acts on coordinates in canonical basis, then its element a_{ij} sends the j -th element of canonical basis to i -th element of canonical basis in the same way as Dirac expression $|i-1\rangle\langle j-1|$, so

$$\begin{pmatrix} a_{11} & \cdots & a_{1n} \\ \vdots & & \vdots \\ a_{n1} & \cdots & a_{nn} \end{pmatrix} \iff \sum_{i,j=1}^n a_{ij} |i-1\rangle\langle j-1|.$$

For example, the representations of 1-qubits (ket and bra) are

$$|0\rangle \iff \begin{pmatrix} 1 \\ 0 \end{pmatrix}, |1\rangle \iff \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \langle 0| \iff (1 \ 0), \langle 1| \iff (0 \ 1)$$

and the NOT gate is of the form

$$\begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix} \iff |0\rangle\langle 1| + |1\rangle\langle 0|.$$

4 Definition of QRA

Recall that a Geometric Algebra $\mathbb{G}_n = \mathbb{G}_{n,0}$ is a free, associative, unitary algebra over the set of anti-commuting generators $\{e_1, \dots, e_n\}$ such that $e_i^2 = 1, i \in \{1, \dots, n\}$. Now we finally define the Quantum Register Algebra (QRA). First,

let us consider a geometric algebra \mathbb{G}_{n+2} with its basis elements $\{e_1, \dots, e_n, r_1, r_2\}$ together with the following identities

$$e_1^2 = e_2^2 = \dots = e_n^2 = r_1^2 = r_2^2 = 1. \quad (5)$$

Then we define a bivector

$$\iota = r_1 r_2$$

and show that the set $\tilde{\mathbb{C}} = \{a + b\iota | a, b \in \mathbb{R}\}$ is isomorphic to an algebra \mathbb{C} , so ι plays the role of a complex unit. The set $\tilde{\mathbb{C}}$ is closed with respect to addition and multiplication. The element ι is in square equal to -1 . Indeed,

$$\iota^2 = r_1 r_2 r_1 r_2 = -r_1^2 r_2^2 = -1,$$

so $\tilde{\mathbb{C}} \cong \mathbb{C}$. Now we define QRA as a geometric subalgebra \mathbb{G}_n with the coefficients in $\tilde{\mathbb{C}}$, i.e.

$$\text{QRA} = \{a_0 g_0 + \dots + a_n g_n | a_i \in \tilde{\mathbb{C}}, g_i \in \mathbb{G}_n\} \subset \mathbb{G}_{n+2}.$$

Hence for any element $A \in \mathbb{G}_n$ we have $\iota A = A \iota$ because ι is a bivector and $\iota \notin \mathbb{G}_n$.

5 QC in the QRA framework

To use QRA to model quantum computing we choose a different basis of QRA based on geometric algebra \mathbb{G}_{2n} . This basis is called Witt basis and it is formed by elements $\{f_1, f_1^\dagger, \dots, f_n, f_n^\dagger\}$ satisfying

$$f_i = \frac{1}{2}(e_i + \iota e_{i+n}), \quad (6)$$

$$f_i^\dagger = \frac{1}{2}(e_i - \iota e_{i+n}), \quad (7)$$

where $\iota = r_1 r_2$. Now, we define an element $I = f_1 f_1^\dagger \dots f_n f_n^\dagger$ satisfying

$$I^2 = I, \quad (8)$$

$$f_i I = 0, \quad (9)$$

$$f_i f_i^\dagger I = I \quad (10)$$

then we have a straightforward identification of bra and ket vectors with the elements of QRA as follows:

$$\langle a_1 \dots a_n | \mapsto I (f_n)_{a_n} \dots (f_1)_{a_1}, \text{ where } a_i \in \{0, 1\}, \quad (11)$$

$$|a_1 \dots a_n\rangle \mapsto (f_1^\dagger)^{a_1} \dots (f_n^\dagger)^{a_n} I, \text{ where } a_i \in \{0, 1\}. \quad (12)$$

For example, let us consider the space of 2-qubit states. Then the identification (11) and (12) for the ket vectors reads

$$\begin{aligned} |00\rangle &\mapsto (f_1^\dagger)^0 (f_2^\dagger)^0 I = I, \\ |01\rangle &\mapsto (f_1^\dagger)^0 (f_2^\dagger)^1 I = f_2^\dagger I, \\ |10\rangle &\mapsto (f_1^\dagger)^1 (f_2^\dagger)^0 I = f_1^\dagger I, \\ |11\rangle &\mapsto (f_1^\dagger)^1 (f_2^\dagger)^1 I = f_1^\dagger f_2^\dagger I. \end{aligned} \quad (13)$$

So the ket vectors in 2-qubit state space are linear combinations of the basis $\{f_1, f_1^\dagger, \dots, f_n, f_n^\dagger\}$ elements:

$$|\psi\rangle = (\psi_{00} + \psi_{01}f_2^\dagger + \psi_{10}f_1^\dagger + \psi_{11}f_1^\dagger f_2^\dagger)I. \quad (14)$$

To define the quantum gates we have to identify the bra vectors in the similar way:

$$\begin{aligned} \langle 00| &\mapsto I(f_2)^0(f_1)^0 = I, \\ \langle 01| &\mapsto I(f_2)^1(f_1)^0 = If_2, \\ \langle 10| &\mapsto I(f_2)^0(f_1)^1 = If_1, \\ \langle 11| &\mapsto I(f_2)^1(f_1)^1 = -If_1f_2. \end{aligned} \quad (15)$$

Thus the bra vectors in 2-qubit state space are combinations of the basis $\{f_1, f_1^\dagger, \dots, f_n, f_n^\dagger\}$ elements as follows:

$$\langle\psi| = I(\psi_{00} + \psi_{10}f_1 + \psi_{01}f_2 - \psi_{11}f_1f_2).$$

To demonstrate our approach we show the design of the SWAP gate [8]. Recall that in Dirac notation, the SWAP gate is represented by

$$|00\rangle\langle 00| + |01\rangle\langle 10| + |10\rangle\langle 01| + |11\rangle\langle 11|.$$

Using the identification (13) and (15), the SWAP gate may be rewritten as:

$$\begin{aligned} \text{SWAP} &= |00\rangle\langle 00| + |01\rangle\langle 10| + |10\rangle\langle 01| + |11\rangle\langle 11| \\ &= f_1f_1^\dagger f_2f_2^\dagger + f_1^\dagger f_2 - f_1f_2^\dagger + f_1^\dagger f_1 f_2^\dagger f_2. \end{aligned} \quad (16)$$

Before we present how the gate acts on 2-qubits, let us mention the rules for calculations with the Witt basis $\{f_i, f_i^\dagger\}$ elements in the form of a list of properties which can be verified by straightforward computations:

$$(f_i)^2 = (f_i^\dagger)^2 = 0 \quad (17)$$

$$f_i f_j = -f_j f_i, \quad f_i^\dagger f_j^\dagger = -f_j^\dagger f_i^\dagger \quad (18)$$

$$f_i f_i^\dagger f_i = f_i, \quad f_i^\dagger f_i f_i^\dagger = f_i^\dagger \quad (19)$$

We present the SWAP gate functionality on 2-qubits step by step. Thus we can calculate:

$$\begin{aligned}
 \text{SWAP}|\psi\rangle &= \\
 &= (f_1 f_1^\dagger f_2 f_2^\dagger + f_1^\dagger f_2 - f_1 f_2^\dagger + f_1^\dagger f_1 f_2^\dagger f_2)(\psi_{00} + \psi_{01} f_2^\dagger + \psi_{10} f_1^\dagger + \psi_{11} f_1^\dagger f_2^\dagger)I \\
 &= f_1 f_1^\dagger f_2 f_2^\dagger (\psi_{00} + \cancel{\psi_{01} f_2^\dagger} + \cancel{\psi_{10} f_1^\dagger} + \cancel{\psi_{11} f_1^\dagger f_2^\dagger})I \text{ by (17)} \\
 &\quad + f_1^\dagger f_2 (\psi_{00} + \cancel{\psi_{01} f_2^\dagger} + \cancel{\psi_{10} f_1^\dagger} + \cancel{\psi_{11} f_1^\dagger f_2^\dagger})I \text{ by (9) and (17)} \\
 &\quad - f_1 f_2^\dagger (\psi_{00} + \cancel{\psi_{01} f_2^\dagger} + \cancel{\psi_{10} f_1^\dagger} + \cancel{\psi_{11} f_1^\dagger f_2^\dagger})I \text{ by (9) and (17)} \\
 &\quad + f_1^\dagger f_1 f_2^\dagger f_2 (\psi_{00} + \cancel{\psi_{01} f_2^\dagger} + \cancel{\psi_{10} f_1^\dagger} + \psi_{11} f_1^\dagger f_2^\dagger)I \text{ by (9) and (17)} \\
 &= (\underline{f_1 f_1^\dagger f_2 f_2^\dagger})(\psi_{00})I + (f_1^\dagger f_2)(\psi_{01} f_2^\dagger)I \text{ by (10)} \\
 &\quad + f_2^\dagger f_1 \psi_{10} f_1^\dagger I + (f_1^\dagger f_1 f_2^\dagger f_2)(\psi_{11} f_1^\dagger f_2^\dagger)I \\
 &= (\psi_{00} + \psi_{01} f_1^\dagger + \psi_{10} f_2^\dagger + \psi_{11} (f_1^\dagger f_1 f_1^\dagger)(f_2^\dagger f_2 f_2^\dagger))I \text{ the last step by (10)} \\
 &= (\psi_{00} + \psi_{01} f_1^\dagger + \psi_{10} f_2^\dagger + \psi_{11} f_1^\dagger f_2^\dagger)I,
 \end{aligned}$$

where \overline{g} and \underline{g} stand for $g = 0$ and $g = 1$. Finally, by means of (13), the final 2-qubit can be rewritten in Dirac notation as

$$(\psi_{00}|00\rangle + \psi_{01}|10\rangle + \psi_{10}|01\rangle + \psi_{11}|11\rangle)I$$

which is the expected result.

The other gates may be interpreted in the very same way and thus we showed how quantum computation in QRA is realized. We used the Witt basis axioms (17)–(19) together with additional axioms (9) and (10). The use of the additional axioms may seem redundant and complicated but they only simplify the written form of calculations and thus the functionality is easier for demonstration. Indeed, these rules may be avoided completely for which we point out the following two reasons:

- If we interpret the element I as $f_1 f_1^\dagger \cdots f_n f_n^\dagger$, the rules (9) and (10) do not apply because they are simple consequences of (17)–(19). Only the expressions will be longer.
- We are using the axioms (17)–(19) for calculations in the Witt basis which naturally corresponds to Dirac formalism. But Witt basis is just a different set of generators for QRA elements. Thus the axioms (17)–(19) are derived from geometric algebra axioms (5) which are very simple.

Our approach is based on the fact that QRA and the Witt basis provide nice language for written QC schemes. The expressions are very similar to Dirac formalism, so they are very simple to understand for people not familiar with geometric algebra. But unlike abstract Dirac formalism, our objects are elements of QRA which is a geometric algebra based on very simple axioms and, furthermore, it is very easy for implementation as shown in the following section.

6 GAALOP implementation

The integration of QRA into GAALOP is done based on the file Definition.csv according to Chapt. 9 of [7]. Listing 1.1 shows the file for the definition of one qubit.

Listing 1.1. Definition.csv for QRA for one qubit

```

1 | 1 , e1 , e2 , er1 , er2
2 |
3 | 1 , e1 , e2 , er1 , er2
4 | e1=1 , e2=1 , er1=1 , er2=1

```

In general, this file consists of 5 lines for the definition of the algebra. In the case of QRA, the lines 2 and 5 are left blank since the used basis in Line 1 and the standard basis in Line 3 are the same and no transformations between the two bases are needed. The basis is defined by the basis vectors e1, e2, er1 and er2 according to e_1, e_2, r_1, r_2 as defined in the previous sections. All their squares are defined to 1 according to line 4.

For each additional qubit we need two additional basis vectors, while er1 and er2 are always the same. The definition of a register with two qubits is shown in Listing 1.2.

Listing 1.2. Definition.csv for QRA based on two qubits

```

1 | 1 , e1 , e2 , e3 , e4 , er1 , er2
2 |
3 | 1 , e1 , e2 , e3 , e4 , er1 , er2
4 | e1=1 , e2=1 , e3=1 , e4=1 , er1=1 , er2=1

```

For the second qubit we need the additional basis vectors e3 and e4. For this paper, we also made a new version of GAALOPWeb⁶. It allows online computations with a number of n qubits without the installation of a specific software.

7 Example in GAALOP

As an example we implemented the SWAP gate on GAALOP for a register with two qubits. Following the Equations (6) and (7), the vectors f_i and f_i^+ as

$$\begin{aligned}
 f_1 &= \frac{1}{2}(e_1 + \iota e_3), & f_1^\dagger &= \frac{1}{2}(e_1 - \iota e_3) \\
 f_2 &= \frac{1}{2}(e_2 + \iota e_4), & f_2^\dagger &= \frac{1}{2}(e_2 + \iota e_4),
 \end{aligned}$$

where $\iota = r_1 r_2$. Then, we use the definitions in (13) to implement the basis elements, Equation (14) for $|\psi\rangle$ and (16) to define the operator of the SWAP gate. We apply the SWAP operator on the element $|\psi\rangle$. But first, let us see the coordinates of each ket vector basis when they are multiplied by I separately:

⁶ <http://www.gaalop.de/gaalopweb/>

Listing 1.3. SWAP gate in QRA for two qubits.

```

1 // Imaginary unit
2 i = er1*er2;
3 // Witt basis
4 f1 = 0.5*(e1+i*e3);
5 f1T = 0.5*(e1-i*e3);
6 f2 = 0.5*(e2+i*e4);
7 f2T = 0.5*(e2-i*e4);
8 // Element "I"
9 Id = f1*f1T*f2*f2T;
10 // ket basis vectors multiplied by "Id"
11 ?ket00 = 1*Id;
12 ?ket01 = f2T*Id;
13 ?ket10 = f1T*Id;
14 ?ket11 = f1T*f2T*Id;

```

This is important to show which coordinates correspond to each vector in order to see the amplitudes interchanging when SWAP is applied to some linear combination of these vectors. The output for this code is shown below:

Listing 1.4. Basic elements multiplied by I .

```

1 ket00[0] = 0.25; // 1.0
2 ket00[42] = 0.25; // e1 ^ (e2 ^ (e3 ^ e4))
3 ket00[50] = -0.25; // e1 ^ (e3 ^ (er1 ^ er2))
4 ket00[55] = -0.25; // e2 ^ (e4 ^ (er1 ^ er2))
5 ket01[2] = 0.25; // e2
6 ket01[26] = -0.25; // e1 ^ (e3 ^ e4)
7 ket01[41] = -0.25; // e4 ^ (er1 ^ er2)
8 ket01[59] = 0.25; // e1 ^ (e2 ^ (e3 ^ (er1 ^ er2)))
9 ket10[1] = 0.25; // e1
10 ket10[32] = 0.25; // e2 ^ (e3 ^ e4)
11 ket10[40] = -0.25; // e3 ^ (er1 ^ er2)
12 ket10[60] = -0.25; // e1 ^ (e2 ^ (e4 ^ (er1 ^ er2)))
13 ket11[7] = 0.25; // e1 ^ e2
14 ket11[16] = -0.25; // e3 ^ e4
15 ket11[51] = -0.25; // e1 ^ (e4 ^ (er1 ^ er2))
16 ket11[54] = 0.25; // e2 ^ (e3 ^ (er1 ^ er2))

```

We remark that all identities given in (17)-(10) can be observed in GAALOP. Now, let us choose a vector $|\psi\rangle$ ⁷ given by:

$$\begin{aligned}
|\psi\rangle &= (|00\rangle + 2|01\rangle + 3|10\rangle + 4|11\rangle)I \\
&= (1 + 3f_2^\dagger + 3f_1^\dagger + 4f_1^\dagger f_2^\dagger)I,
\end{aligned}$$

⁷ The vector $|\psi\rangle$ is not normalized, so the final result should be divided by $\sqrt{29}$.

and apply the SWAP gate on it. The expected result is given by:

$$\begin{aligned} |\bar{\psi}\rangle &= (1 + 3f_2^\dagger + 2f_1^\dagger + 4f_1^\dagger f_2^\dagger)I \\ &= (|00\rangle + 3|01\rangle + 2|10\rangle + 4|11\rangle)I. \end{aligned}$$

We add 3 lines to the code in 1.3:

Listing 1.5. Definition and application of the SWAP gate on GAALOP.

```

1 //SWAP
2 SWAP=(f1*f1T*f2*f2T)+(f1T*f2)-(f1*f2T)+(f1T*f1*f2T*f2);
3 ?psi = ket00 + 2*ket01 + 3*ket10 + 4*ket11;
4 ?SwapPsi = SWAP*psi;

```

The output is shown below and then we analyze the result.

Listing 1.6. Output of the application of the SWAP gate on GAALOP.

```

1 psi[0] = 0.25; // 1.0
2 psi[1] = 0.75; // e1
3 psi[2] = 0.5; // e2
4 psi[7] = 1.0; // e1 ^ e2
5 psi[16] = -1.0; // e3 ^ e4
6 psi[26] = -0.5; // e1 ^ (e3 ^ e4)
7 psi[32] = 0.75; // e2 ^ (e3 ^ e4)
8 psi[40] = -0.75; // e3 ^ (er1 ^ er2)
9 psi[41] = -0.5; // e4 ^ (er1 ^ er2)
10 psi[42] = 0.25; // e1 ^ (e2 ^ (e3 ^ e4))
11 psi[50] = -0.25; // e1 ^ (e3 ^ (er1 ^ er2))
12 psi[51] = -1.0; // e1 ^ (e4 ^ (er1 ^ er2))
13 psi[54] = 1.0; // e2 ^ (e3 ^ (er1 ^ er2))
14 psi[55] = -0.25; // e2 ^ (e4 ^ (er1 ^ er2))
15 psi[59] = 0.5; // e1 ^ (e2 ^ (e3 ^ (er1 ^ er2)))
16 psi[60] = -0.75; // e1 ^ (e2 ^ (e4 ^ (er1 ^ er2)))
17 SwapPsi[0] = 0.25; // 1.0
18 SwapPsi[1] = 0.5; // e1
19 SwapPsi[2] = 0.75; // e2
20 SwapPsi[7] = 1.0; // e1 ^ e2
21 SwapPsi[16] = -1.0; // e3 ^ e4
22 SwapPsi[26] = -0.75; // e1 ^ (e3 ^ e4)
23 SwapPsi[32] = 0.5; // e2 ^ (e3 ^ e4)
24 SwapPsi[40] = -0.5; // e3 ^ (er1 ^ er2)
25 SwapPsi[41] = -0.75; // e4 ^ (er1 ^ er2)
26 SwapPsi[42] = 0.25; // e1 ^ (e2 ^ (e3 ^ e4))
27 SwapPsi[50] = -0.25; // e1 ^ (e3 ^ (er1 ^ er2))
28 SwapPsi[51] = -1.0; // e1 ^ (e4 ^ (er1 ^ er2))
29 SwapPsi[54] = 1.0; // e2 ^ (e3 ^ (er1 ^ er2))
30 SwapPsi[55] = -0.25; // e2 ^ (e4 ^ (er1 ^ er2))
31 SwapPsi[59] = 0.75; // e1 ^ (e2 ^ (e3 ^ (er1 ^ er2)))
32 SwapPsi[60] = -0.5; // e1 ^ (e2 ^ (e4 ^ (er1 ^ er2)))

```

Note that the groups of coordinates $\{0, 42, 50, 55\}$ and $\{7, 16, 51, 54\}$, which refer to the coefficients of $|00\rangle$ and $|11\rangle$ respectively, remained unchanged from `psi` to `SwapPsi`, as expected. However, note that the coefficients in the coordinates $\{2, 26, 41, 59\}$ of `psi` that corresponds to $|01\rangle$ was exactly 2 times the coefficients of `ket01` given by 1.4 and, in `SwapPsi`, they became 3 times those same coefficients. On the other hand, the coordinates $\{1, 32, 40, 60\}$ changed from 3 (in `psi`) to 2 (in `SwapPsi`) times the coefficients of `ket10` in 1.4, that corresponds to $|10\rangle$. So, the output vector `SwapPsi` is exactly the vector $|\bar{\psi}\rangle$.

8 Conclusion

In this paper, we presented how natural Geometric Algebra can be used for quantum computing. Based on the newly developed QRA and its support by the extended GAALOP tool, the handling of quantum computing is strongly simplified, especially for beginners. The big advantage for quantum computing beginners is that they only have to know Geometric Algebra in order to describe the objects and operations of quantum computing. We hope that this can be the reason for Geometric Algebra to become "the" language for quantum computing in the future.

References

1. Alves, R., Hildenbrand, D., Hrdina, J. et al.: *An Online Calculator for Quantum Computing Operations Based on Geometric Algebra* Adv. Appl. Clifford Algebras 32, 4 (2022) (cited on p. 2)
2. Hrdina J., Navrat A., Vasik P.: *Quantum computing based on complex Clifford algebras*, accepted in Quantum Information Processing, arXiv(quant-ph):2201.02246 (2022) (cited on p. 2)
3. Cafaro, C., Mancini, S. *A Geometric Algebra Perspective on Quantum Computational Gates and Universality in Quantum Computing*. Adv. Appl. Clifford Algebras 21, 493–519 (2011). <https://doi.org/10.1007/s00006-010-0269-x> (cited on p. 2)
4. Chris Doran, Anthony Lasenby, *Geometric Algebra for Physicists*, Cambridge University Press (2003) DOI:<https://doi.org/10.1017/CBO9780511807497> (cited on p. 1)
5. Dorst, L.: *Geometric Algebra for Computer Science, An Object-Oriented Approach to Geometry*. Morgan Kaufmann, San Francisco (2007). (cited on p. 1)
6. Hildenbrand, D.: *Foundations of Geometric Algebra Computing*. Springer Science & Business Media (2013). (cited on p. 1)
7. Hildenbrand, D.: *The Power of Geometric Algebra Computing*. CRC Press, Taylor & Francis Group, (2022). (cited on p. 8)
8. Nielsen, M., Chuang, I.: *Quantum Computation and Quantum Information: 10th Anniversary Edition*. Cambridge: Cambridge University Press (2010) doi:10.1017/CBO9780511976667 (cited on p. 6)
9. Perwass, Ch.: *Geometric Algebra with Applications in Engineering* (1st edn). Springer Verlag, (2009). (cited on p. 1)
10. de Lima Marquezino Franklin, Portugal R., Lavor C.: *A Primer on Quantum Computing*. Springer Publishing Company (2019) (cited on p. 4)