

Adapting the LodView RDF Browser for Navigation over the Multilingual Linguistic Linked Open Data Cloud

Alexander Kirillovich
Kazan Federal University,
Joint Supercomputer Center
of the Russian Academy of Sciences
Kazan, Russia
al.kirillovich@gmail.com

Konstantin Nikolaev
Kazan Federal University,
Joint Supercomputer Center
of the Russian Academy of Sciences
Kazan, Russia
konnikolaeff@yandex.ru

Abstract—The paper is dedicated to the use of LodView for navigation over the multilingual Linguistic Linked Open Data cloud. First, we define the class of Pubby-like tools, that LodView belongs to, and clarify the relation of this class to the classes of URI dereferenciation tools, RDF browsers and LOD visualization tools. Second, we reveal several limitations of LodView that impede its use for the designated purpose, and propose improvements to be made for fixing these limitations. These improvements are: 1) resolution of Cyrillic URIs; 2) decoding Cyrillic URIs in Turtle representations of resources; 3) support of Cyrillic literals; 4) user-friendly URLs for RDF representations of resources; 5) support of hash URIs; 6) expanding nested resources; 7) support of RDF collections; 8) pagination of resource property values; and 9) support of \LaTeX math notation. Third, we partially implement several of the proposed improvements.

Index Terms—LodView, Pubby-class tool, RDF browser, dereferenciation tool, Linked Data visualization, Linguistic LOD

I. INTRODUCTION

Digital language resources are key to linguistics research and natural language processing. Among these resources are corpora, thesauri, lexicons, grammatical dictionaries, valence dictionaries, linguistic data categories registers, and other.

Publishing linguistic resources according to the principles of Linked Open Data (LOD) [1]–[3] is a recently established trend, that has led to the emergence of the fast-growing Linguistic Linked Open Data (LLOD) cloud [4], [5]. It offers a number of advantages, including structural and conceptual interoperability, and integration of heterogeneous linguistic resources to solve a common problem.

As a part of the global LLOD project we are working on developing the fragment of the LLOD cloud for Russian and minority languages of Russia. This fragment integrates several resources such as the RuThes [6], TatThes [7], TatWordNet [8],




Figure 1. The place of Pubby-class tools among other LOD applications.

TatVerbBank, the Russian corpus “OpenCorpora” [9], the Tatar national corpus “Tugan Tel” [10]–[12], the parallel informal/formal corpus of educational mathematical texts in Russian [13], the linguistic layer of the educational mathematical ontology OntoMath^{Edu} [14]–[16] and other.

In accordance with Linked Open Data best practices, the integrated resources have to be available via RDF dumps, SPARQL endpoints and dereferenceable URIs. For navigation over the LOD cloud via dereferenceable URIs, a specialized tool is required. One of the most popular navigation tools is the LodView RDF browser.

LodView (<https://github.com/dvcama/LodView>) is a web application for dereferencing URIs of the RDF resources stored in the SPARQL-exposed datasets. When a human user requests the URI of an RDF resource, LodView retrieves information of the resource in the dataset and visualizes this information as a human-readable HTML page. On the page, the resource properties are represented in a tabular form. Each row represents a property-value pair; the first cell of the row contains the property name and the second contains the property value or values. If a property value is the URI of an another resource,

Please, cite as: Alexander Kirillovich and Konstantin Nikolaev. Adapting the LodView RDF Browser for Navigation over the Multilingual Linguistic Linked Open Data Cloud // Proceedings of the 9th IEEE International Conference on Sciences of Electronics, Technologies of Information and Telecommunications (SETIT 2022), Genova, Italy & Sfax, Tunisia, 28-30 May 2022. IEEE, 2022. Pp. 143–149 [revised version]. <https://arxiv.org/abs/2208.13295>




Figure 2. Visualization of the ‘автомобиль’ (‘automobile’) lexical entry in LodView

this value is rendered as a link. A user may follow the link and get representation of the another resource, thus navigating over RDF dataset. The HTML page also contains links to the RDF documents with machine-readable representation of the resource (in different serialization format, including N-Triples, Turtle, RDF/XML and JSON-LD). When the URI is requested not by human but by a software agent, LodView immediately returns the machine-readable RDF representation.

Fig. 1. shows the place of LodView among other LOD applications.

Fig. 2 represents an example how LodView visualizes the ‘автомобиль’ (‘automobile’) lexical entry.

However, LodView has several limitations that impede its use for navigation over the multilingual LLOD cloud. In this paper, we continue the work initiated in [17], [18] and present the first version of our LodView fork, adapted to address these limitations.

The rest of the paper is organized as following. In Section 2 we define the class of Pubby-like tools that LodView belongs to and outline the relationships of this class with other classes of LOD applications. In Section 3 we list the limitations of LodViews and propose improvements to be made for fixing these limitations. Section 4 describes the improvements, that have already been made by us. In Conclusion, we outline the directions of future work.

II. RELATED WORKS

In this section we clarify the place of LodView among other LOD applications.

LodView belongs to a class of tools, that we called the Pubby class after its first prominent representative. We define a Pubby-class tool as a LOD application which is:

- 1) a URI dereferenciation tool, i.e. when a client requests the URI of an RDF resource via HTTP protocol, the tool handles the request and responds with a resource representation;
- 2) a LOD visualization tool, i.e. it represents the resource in human-friendly visual form;
- 3) a Linked Data or RDF browser, i.e. it allows a user to navigate between RDF resources of an RDF dataset or the entire LOD cloud, by following links in resource representations;
- 4) and a SPARQL endpoint interface, i.e. it retrieves information about resources from a SPARQL-exposed dataset.

Conceptually, these four classes are independent and so it is possible for example to conceive a URI dereferenciation tool that doesn’t allow a user to follow links or even doesn’t visualize a resource at all, dereferencing it just as a source RDF file in some textual serialization format. However, in practice,

every known URI dereferencing tool is an RDF browser, and every known RDF browser is a LOD visualization tool (see the relationships between the classes at Fig. 1).

Pubby-class tools. Besides LodView, the Pubby class includes the following tools:

- Pubby¹. A Java web application. Was used for publishing a lot of LOD datasets, including DBpedia. However, it hadn't been updated in more than 10 years and now its GitHub repository is officially archived.
- LODDY². A Java web application. Is used for publishing the AGROVOC Linked Dataset.
- Zazuko Trifid³. A Node.js-based web application. Is used in two open data platforms of Swiss Confederation.
- RDFBrowser⁴. A PHP web application. Is used by the OpenBudgets.eu platform.
- LODI⁵. A Node.js-based web application. Is used by two Spanish open data portals.

Other Linked Data and RDF browsers. While almost all Pubby-class tools are Linked Data browsers, there are Linked Data browsers that are not Pubby-class tools. Among the first such Linked Data browsers the well-known ones are Haystack [19], Disco⁶ and Tabulator⁷ [20]. Examples of the more recent developments are Phuzzy.link⁸ [21] and RDFSurveyor⁹ [22].

Besides Linked Data browsers, there are many LOD visualization tools of several other types, including graph-based and ontology visualization tools.

Graph-based visualization tools. While RDF browsers mainly work on the level of single RDF resources, graph-based tools work on the level of entire RDF graphs. One of the earliest tools in this category is IsaViz¹⁰, a desktop application for authoring and visualizing RDF models, represented as relatively small local RDF files. In contrast, graphVizdb¹¹ [23] enables the user to navigate over very-large RDF graphs. LodLive¹² [24] and LODmilla¹³ [25], [26] provide incremental graph visualization. RelFinder¹⁴ [27] and WiSP¹⁵ [28] are intended to identify and visualize the paths between two selected RDF resources.

Ontology visualization tools. Examples of these tools are OWLPropViz, WebVOWL¹⁶ [29] and OWLGrEd¹⁷ [30].

For a book length overview of LOD visualization tools, we refer the interested reader to [31].

¹<http://wifo5-03.informatik.uni-mannheim.de/pubby/>

²<https://bitbucket.org/art-uniroma2/loddy/src/master/>

³<https://github.com/zazuko/trifid>

⁴<https://github.com/okgreece/RDFBrowser>

⁵<https://github.com/marfeser/LODI>

⁶<http://wifo5-03.informatik.uni-mannheim.de/bizer/ng4j/disco/>

⁷<https://github.com/linkedata/tabulator>

⁸<https://github.com/blake-regalia/phuzzy.link>

⁹<https://github.com/guiveg/rdfsurveyor>

¹⁰<https://www.w3.org/2001/11/IsaViz/>

¹¹<http://www.graphvizdb.com/>

¹²<https://github.com/LodLive/LodLive>

¹³<https://github.com/dsd-sztaki-hu/LODmilla-frontend>

¹⁴<http://www.visualdataweb.org/relfinder.php>

¹⁵<https://github.com/GTartari/Weighted-Shortest-Paths>

¹⁶<https://github.com/VisualDataWeb/WebVOWL>

¹⁷<http://owlgred.lumii.lv/>

III. REQUIRED IMPROVEMENTS OF LODVIEW

In this section, we list the limitations of LodViews and propose improvements to be made to fix these limitations.




Figure 3. Error occurred while resolving a URI that contains Cyrillic characters.

1) Resolution of Cyrillic URIs. In a LLOD dataset, the URI of an RDF resource may contain Cyrillic characters. For example, in the RuThes Cloud dataset, the URI of the lexical entry 'машина' ('car') is `<http://lod.ruthes.org/resource/entry/RU-машина-n>`. However, in some environments, resolving Cyrillic URIs by LodView leads to an error (see Fig. 3). LodView must resolve Cyrillic URIs in all environments.

2) Decoding Cyrillic URIs in Turtle representations of resources. In a machine-readable RDF representation of a resource in the Turtle serialization format, Cyrillic URIs are presented in an encoded form. Fig. 4A shows a fragment of the Turtle representation of the *Automobile* concept, that contains encoded URIs. Encoded URIs hinder readability of Turtle documents. In the Turtle representation of a resource, URIs must be presented in a decoded form (for example, as in Fig. 4B).

A) Encoded URIs:

```
<resource/concept/154>
  a skos:Concept;
  ontolex:lexicalizedSense
  <resource/sense/154-%D0%BC%D0%B0%D1%88%D0%B8%D0%BD%D0%B0-n-0>,
  <resource/sense/154-
  %D0%B0%D0%B2%D1%82%D0%BE%D0%BC%D0%BE%D0%B1%D0%B8%D0%BB%D1%8C-n-0>,
  <...>.
```

B) Decoded URIs:

```
<resource/concept/154>
  a skos:Concept;
  ontolex:lexicalizedSense
  <resource/sense/154-машина-n-0>,
  <resource/sense/154-автомобиль-n-0>,
  <...>.
```

Figure 4. Fragment of a Turtle representation of a resource with encoded and decoded URIs.




Figure 9. Example of deploying an embedded resource using an iframe.




Figure 10. Blank node, located in the cell with the property value.

appended just near its URI (see Fig. 9). Also, we are going to implement more flexible solution, that doesn't use an iframe.

The descriptions of blank nodes are simply moved from the bottom of the HTML page to the cells with the IDs of these nodes. For example, Fig. 10 represents the *cat* synset. For this synset, the value of the `wn:definition` property is a blank node. This blank node is represented not only by its ID, but also by its description, i.e. a table of its own properties.

Issue #9 (Support of \LaTeX math notation). In order to solve this problem, we have developed a special plugin, based on the well-known MathJax library¹⁸ [32] (see Fig. 11).

V. CONCLUSION

We reveal several limitations of LodView that impede its use for navigation over the multilingual Linguistic Linked Open Data cloud. For fixing these limitations, we propose the following improvements: 1) resolution of Cyrillic URIs; 2) decoding Cyrillic URIs in Turtle representations of resources; 3) support of Cyrillic literals; 4) user-friendly URLs for RDF representations of resources; 5) support of hash URIs; 6) expanding nested resources; 7) support of RDF collections; 8) pagination of resource property values; and 9) support of \LaTeX math notation.

¹⁸<https://www.mathjax.org/>




Figure 11. Visualization of math notation with rendering.

At the moment, we have implemented the improvements #1–4 and #9, and partially the improvements #5 and #6. Our fork of LodView is available on GitHub: https://github.com/ManlyMan1/LodView_Cyrillic.

Currently, we are working on the remaining issues. After that, we are going to send a pull request to the main LodView repository.

Acknowledgment. The work was initiated for navigation over LLOD cloud at KFU where was funded by RSF according to the project no. 19-71-10056, and then adapted for navigation over specialized \LaTeX -based math collections at JSC RAS.

REFERENCES

- [1] Christian Bizer, Tom Heath, and Tim Berners-Lee. Linked Data – The Story So Far. *International Journal on Semantic Web and Information Systems*, 5(3):1–22, July 2009. doi:10.4018/jswis.2009081901.
- [2] Tom Heath and Christian Bizer. *Linked Data: Evolving the Web into a Global Data Space*. Morgan & Claypool, 2011. URL: <http://linkeddatabook.com/editions/1.0/>.
- [3] Aidan Hogan. *The Web of Data*. Springer, 2020. doi:10.1007/978-3-030-51580-5.
- [4] John Philip McCrae et al. The Open Linguistics Working Group: Developing the Linguistic Linked Open Data Cloud. In Nicoletta Calzolari et al., editors, *Proceedings of the 10th International Conference on Language Resources and Evaluation (LREC'16), Portorož, Slovenia, May 23–28, 2016*, pages 2435–2441. European Language Resources Association, 2016. URL: <https://www.aclweb.org/anthology/L16-1386>.
- [5] Philipp Cimiano, Christian Chiarcos, John P. McCrae, and Jorge Gracia. *Linguistic Linked Data: Representation, Generation and Applications*. Springer, 2020. doi:10.1007/978-3-030-30225-2_3.
- [6] Alexander Kirillovich, Olga Nevzorova, Emil Gimadiev, and Natalia Loukachevitch. RuThes Cloud: Towards a Multilevel Linguistic Linked Open Data Resource for Russian. In Przemysław Różewski and Christoph Lange, editors, *Proceedings of the 8th International Conference on Knowledge Engineering and Semantic Web (KESW 2017), Szczecin, Poland, November 8–10, 2017*, Communications in Computer and Information Science, vol. 786, pages 38–52. Springer, 2017. doi:10.1007/978-3-319-69548-8_4.
- [7] Alfiya Galieva, Alexander Kirillovich, Bulat Khakimov, Natalia Loukachevitch, Olga Nevzorova, and Dzhavdet Suleymanov. Toward Domain-Specific Russian-Tatar Thesaurus Construction. In Radomir Bolgov et al., editors, *Proceedings of the International Conference IMS-2017, St. Petersburg, Russia, 21–24 June 2017*, ACM International Conference Proceeding Series, pages 120–124. ACM Press, New York, 2017. doi:10.1145/3143699.3143716.
- [8] Alexander Kirillovich, Marat Shaekhov, Alfiya Galieva, Olga Nevzorova, Dmitry Ilvovsky, and Natalia Loukachevitch. TatWordNet: A Linguistic Linked Open Data-Integrated WordNet Resource for Tatar. In Dagmar Gromann et al., editors, *Proceedings of the 3rd Conference on Language, Data and Knowledge (LDK 2021), Zaragoza, Spain, 1–3 Sep 2021*, OpenAccess Series in Informatics, vol. 93, pages 16:1–16:12. Schloss Dagstuhl, 2021. doi:10.4230/OASIS.LDK.2021.16.

- [9] Alexander Kirillovich, Natalia Loukachevitch, Maksim Kulaev, Angelina Bolshina, and Dmitry Ilvovsky. Sense-Annotated Corpus for Russian. In *Proceedings of the 5th International Conference on Computational Linguistics in Bulgaria (CLIB 2022)*, Sofia, Bulgaria, 8–9 September 2022, in press.
- [10] Damir Mukhamedshin, Olga Nevzorova, and Alexander Kirillovich. Using FLOSS for Storing, Processing and Linking Corpus Data. In Vladimir Ivanov et al., editors, *Proceedings of the 16th IFIP WG 2.13 International Conference on Open Source Systems (OSS 2020)*, Innopolis, Russia, 12–14 May 2020, IFIP Advances in Information and Communication Technology, vol. 582, page 177–182. Springer, 2020. doi:10.1007/978-3-030-47240-5_17.
- [11] Damir Mukhamedshin, Dzhavdet Suleymanov, and Olga Nevzorova. Choosing the Right Storage Solution for the Corpus Management System (Analytical Overview and Experiments). In Med Salim Bouhlef and Stefano Rovetta, editors, *Proceedings of the 8th International Conference on Sciences of Electronics, Technologies of Information and Telecommunications (SETIT'18)*, Genoa-Italy & Hammamet-Tunisia, December 18-20, 2018, Smart Innovation, Systems and Technologies, vol. 146, pages 105–114. Springer, 2020. doi:10.1007/978-3-030-21005-2_10.
- [12] O. Nevzorova, D. Mukhamedshin, A. Galieva, R. Gataullin, O. Nevzorova, and R. Gataullin. Corpus management system: Semantic aspects of representation and processing of search queries. In *Proceedings of the 7th International Conference on Sciences of Electronics, Technologies of Information and Telecommunications (SETIT 2016)*, Hammamet, Tunisia, 18–20 December, 2016, pages 285–290. IEEE, 2016. doi:10.1109/SETIT.2016.7939881.
- [13] Alexander Kirillovich, Olga Nevzorova, Konstantin Nikolaev, and Kamilla Galiaskarova. Towards a Parallel Informal-Formal Corpus of Educational Mathematical Texts in Russian. In Zhengbing Hu et al., editors, *Proceedings of the 2019 International Symposium on Computer Science, Digital Economy and Intelligent Systems (CSDEIS 2019)*, Advances in Intelligent Systems and Computing, vol. 1127, page 325–334. Springer, 2020. doi:10.1007/978-3-030-39216-1_29.
- [14] Alexander Kirillovich, Olga Nevzorova, Marina Falileeva, Eugeny Lipachev, and Liliana Shakirova. OntoMath^{Edu}: Towards an Educational Mathematical Ontology. In Edwin Brady et al., editors, *Workshop Papers at 12th Conference on Intelligent Computer Mathematics (CICM-WS 2019)*, Prague, Czech Republic, 8–12 July 2019, CEUR Workshop Proceedings, vol. 2634. CEUR-WS, 2020. URL: <http://ceur-ws.org/Vol-2634/WiP1.pdf>.
- [15] Alexander Kirillovich, Olga Nevzorova, Marina Falileeva, Eugeny Lipachev, and Liliana Shakirova. OntoMath^{Edu}: A Linguistically Grounded Educational Mathematical Ontology. In Christoph Benzmlüller and Bruce Miller, editors, *Proceedings of the 13th International Conference on Intelligent Computer Mathematics (CICM 2020)*, Bertinoro, Italy, July 26–31, 2020, Lecture Notes in Computer Science, vol. 12236, pages 157–172. Springer, 2020. doi:10.1007/978-3-030-53518-6_10.
- [16] Alexander Kirillovich, Marina Falileeva, Olga Nevzorova, Evgeny Lipachev, Anastasiya Dyupina, and Liliana Shakirova. Prerequisite Relationships of the OntoMath^{Edu} Educational Mathematical Ontology. In Juan Carlos Figueroa-García et al., editors, *Proceedings of the 8th Workshop on Engineering Applications (WEA 2021)*, Medellín, Colombia, October 6–8, 2021, Communications in Computer and Information Science, vol. 1431, page 517–524. Springer, 2021. doi:10.1007/978-3-030-86702-7_44.
- [17] А. Кириллович и К. Николаев. Инструмент навигации по облаку Лингвистических Открытых Связанных Данных для русского языка и языков народов России. ИТНОУ, 1(15):49–56, 2020.
- [18] Alexander Kirillovich and Konstantin Nikolaev. Adapting the LodView RDF Browser for Navigation over the Linguistic Linked Open Data Cloud in Russian and the Languages of Russia. In Bernhard K. Thalheim et al., editors, *Supplementary Proceedings of the XXII International Conference on Data Analytics and Management in Data Intensive Domains (DAMDID/RCDL 2020)*, CEUR Workshop Proceedings, vol. 2790, pages 350–361. CEUR-WS, 2020.
- [19] Dennis Quan and David R. Karger. How to Make a Semantic Web Browser. In Stuart I. Feldman et al., editors, *Proceedings of the 13th international conference on World Wide Web (WWW 2004)*, New York, USA, May 17-20, 2004, pages 255–265. ACM, 2004. doi:10.1145/988672.988707.
- [20] Tim Berners-Lee, Yuhsin Chen, Lydia Chilton, Dan Connolly, Ruth Dhanaraj, James Hollenbach, Adam Lerer, and David Sheets. Tabulator: Exploring and Analyzing linked data on the Semantic Web. In *Proceedings of the 3rd International Semantic Web User Interaction Workshop (SWUI 2006)*, November 6, 2006, Athens, Georgia, USA, 2006. URL: <https://web.archive.org/web/20071213214206/http://swui.semanticweb.org/swui06/program.html>.
- [21] Blake Regalia, Krzysztof Janowicz, and Gengchen Mai. Phuzzy.link: A SPARQL-powered Client-Sided Extensible Semantic Web Browser. In Valentina Ivanova et al., editors, *Proceedings of the 3rd International Workshop on Visualization and Interaction for Ontologies and Linked Data (VOILA 2017)*, Vienna, Austria, October 22, 2017, CEUR Workshop Proceedings, vol. 1947, pages 34–44. CEUR-WS, 2017. URL: <http://ceur-ws.org/Vol-1947/paper04.pdf>.
- [22] Guillermo Vega-Gorgojo, Laura Slaughter, Björn Marius von Zernichow, Nikolay Nikolov, and Dumitru Roman. Linked Data Exploration With RDF Surveyor. *IEEE Access*, 7:172199–172213, 2019. doi:10.1109/ACCESS.2019.2956345.
- [23] Nikos Bikakis, John Liagouris, Maria Krommyda, George Papastefanatos, and Timos Sellis. graphvizdb: A scalable platform for interactive large graph visualization. In *Proceedings of the 32nd IEEE International Conference on Data Engineering (ICDE 2016)*, Helsinki, Finland, May 16-20, 2016, pages 1342–1345. IEEE, 2016. doi:10.1109/ICDE.2016.7498340.
- [24] Diego Valerio Camarda, Silvia Mazzini, and Alessandro Antonuccio. Lodlive, exploring the web of data. In Harald Sack and Tassilo Pellegrini, editors, *Proceedings of the 8th International Conference on Semantic Systems (I-SEMANTICS 2012)*, Graz, Austria, September 5–7, 2012, pages 197–200. ACM, 2012. doi:10.1145/2362499.2362532.
- [25] András Micsik, Zoltán Tóth, and Sándor Turbucz. LODmilla: Shared Visualization of Linked Open Data. In Łukasz Bolikowski et al., editors, *Revised Selected Workshops Papers of the International Conference on Theory and Practice of Digital Libraries (TPDL 2013 Selected Workshops)*, Valletta, Malta, September 22-26, 2013, Communications in Computer and Information Science, vol. 416, pages 89–100. Springer, 2014. doi:10.1007/978-3-319-08425-1_9.
- [26] András Micsik, Sándor Turbucz, and Zoltán Tóth. Exploring publication metadata graphs with the LODmilla browser and editor. *International Journal on Digital Libraries*, 16(1):15–24, July 2015. doi:10.1007/s00799-014-0130-2.
- [27] Philipp Heim, Steffen Lohmann, and Timo Stegemann. Interactive Relationship Discovery via the Semantic Web. In Lora Aroyo et al., editors, *Proceedings of the 7th Extended Semantic Web Conference (ESWC 2010)*, Heraklion, Crete, Greece, May 30 – June 2, 2010, Lecture Notes in Computer Science, vol. 6088, page 303–317. Springer, 2010. doi:10.1007/978-3-642-13486-9_21.
- [28] Gonzalo Tartari and Aidan Hogan. WiSP: Weighted Shortest Paths for RDF Graphs. In Valentina Ivanova et al., editors, *Proceedings of the 4th International Workshop on Visualization and Interaction for Ontologies and Linked Data (VOILA 2018) co-located with the 17th International Semantic Web Conference (ISWC 2018)*, Monterey, CA, USA, October 8, 2018, CEUR Workshop Proceedings, vol. 2187, pages 37–52. CEUR-WS, 2018. URL: <http://ceur-ws.org/Vol-2187/paper4.pdf>.
- [29] Steffen Lohmann, Vincent Link, Eduard Marbach, and Stefan Negru. WebVOWL: Web-based Visualization of Ontologies. In Patrick Lambrix et al., editors, *Revised Selected Papers of the 19th International Conference on Knowledge Engineering and Knowledge Management (EKAW 2014) Satellite Events, Linköping, Sweden, November 24-28, 2014*, Lecture Notes in Computer Science, vol. 8982, pages 154–158. Springer, 2014. doi:10.1007/978-3-319-17966-7_21.
- [30] Renārs Liepiņš, Mikus Grasmanis, and Uldis Bojārs. OWLGrEd Ontology Visualizer. In Ruben Verborgh and Erik Mannens, editors, *Proceedings of the ISWC Developers Workshop 2014 (ISWC-DEV 2014) co-located with the 13th International Semantic Web Conference (ISWC 2014)*, Riva del Garda, Italy, October 19, 2014, CEUR Workshop Proceedings, vol. 1268, pages 37–42. CEUR-WS, 2014. URL: <http://ceur-ws.org/Vol-1268/paper7.pdf>.
- [31] Laura Po, Nikos Bikakis, Federico Desimoni, and George Papastefanatos. *Linked Data Visualization: Techniques, Tools, and Big Data*. Morgan & Claypool Publishers, 2020.
- [32] Davide Cervone. MathJax: A Platform for Mathematics on the Web. *Notices of the AMS*, 59(2):312–316, 2012. doi:10.1090/noti794.