# Drone Deployment Optimization for Direct Delivery with Time Windows and Battery Replacements

Tanveer Hossain Bhuiyan\* <sup>a,b</sup>, Mohammad Roni, <sup>a</sup> and Victor Walker<sup>a</sup>

<sup>a</sup> Energy and Environment Science & Technology Department, Idaho National Laboratory, Idaho, USA

<sup>b</sup> Department of Mechanical Engineering, The University of Texas at San Antonio, TX, USA

\*Corresponding author email: tanveer.bhuiyan@utsa.edu

#### Abstract

Aerial drones offer a distinct potential to reduce the delivery time and energy consumption for the delivery of time-sensitive and small products. However, there is still a need in the relevant industry to understand the performance of drone-based delivery under different business needs and drone operating conditions. We studied a drone deployment optimization problem for direct delivery of goods to customers maintaining a specified time window. This paper presents a new mathematical optimization-based decision-making methodology to help business owners optimally route their drone fleet minimizing the total energy consumption, required fleet size, and the required number of additional batteries. A realistic feature of the optimization method is that instead of replacing the drone battery after each return to the depot, it keeps track of the remaining energy in the drone battery and decides on battery replacements accounting for the drone routing and the user-specified minimum required battery energy. Numerical results based on real drone flight tests and delivery data provide insights into the effect of different drone operating parameters on the energy consumption, required fleet size, and the required number of battery replacements. Results from a case study show that the total energy consumption, required fleet size, and the required number of battery replacements increase by 72.22%, 22.2%, and 200%, respectively, as the drones fly over the road networks compared to flying in a straight path. Additionally, results show that using a mixed fleet of hexacopter and quadcopter drones reduces the total energy consumption by 48.52% compared to using a homogeneous fleet of only hexacopters.

**Keywords:** Drone routing, Drone energy consumption, Mixed-integer program, Minimum required battery energy, Mixed fleet of drones

### 1 Introduction

This paper studies a drone deployment optimization problem for direct delivery of goods from a retail business location (e.g., store) to customer locations. The objective of the decision-maker (i.e., business owner) is to find the optimal routing of drones that minimizes the investment (e.g., drone fleet and battery costs) and operating (e.g., energy, labor, and maintenance costs) costs in delivering customer orders within a specified time window. Specifically, the goal of this study is to (1) develop a mathematical optimization-based decision-making model that retail business owners can use to optimally deploy a fleet of drones in delivering customer orders with a minimum required fleet size (i.e., number of drones), required number of additional batteries, and total energy consumption; (2) understand the effect of different business and drone operating conditions on total energy consumption, required fleet size, and required number of additional batteries; and (3) provide numerical results and managerial insights based on real drone flight test data to help business owners better understand the potential of drones in goods delivery and evaluate alternative decisions.

### 1.1 Motivation

Unmanned aerial vehicles (UAVs), also known as drones, have gained abundant attention from businesses and consumers. For instance, Amazon and several other companies (e.g., Google, DHL) have developed their own drone delivery systems [1]. Drones possess several advantages compared to other vehicles, such as low capital and operating costs, the capability of taking off and landing in a limited space without requiring expensive infrastructure, and eliminating the necessity of an operator on board [2]. Due to these advantages, drones offer a great benefit in numerous transportation and logistics activities including but not limited to traffic surveillance [3], consumer product delivery [4], emergency medical supplies [2], and agriculture and forest fire surveillance [5].

Specifically, drones offer a distinct potential to improve the delivery of goods in the last-mile, especially for time-sensitive, small, and localized deliveries. In recent years, general e-commerce and retail online deliveries are growing, and in some areas they are approaching a critical stage, such as in New York City, where over 1.5 million daily deliveries are putting a strain on the road networks and curb resources [6]. In addition, local business-to-consumer deliveries are growing quickly for time-sensitive products, such as prepared food, medicine, and groceries. With the growing online retail business, cost-efficient and timely delivery of products from stores to the customers' homes is becoming a challenge for business owners, especially in a densely populated urban environment due to congestion in the road networks. Moreover, current delivery services are also expensive, costing restaurants up to 30% of each order's value for food delivery [7]. In these circumstances, drone-based delivery can significantly reduce traffic congestion by avoiding the use of road networks, as well as increase the delivery range, market reach, and sales volume for the retail business owners by reducing the cost and delivery time of the current system of using ground vehicles. Moreover, McKinsey has suggested that 80% of last-mile deliveries will be done by autonomous vehicles within 8 years [8], and that drones will likely be the chosen method for a very large segment of the population, especially for suburban and rural consumers

needing same-day and speedy deliveries.

Despite the great potential and benefit, drone-based delivery suffers from a major limitation—limited battery capacity—that limits the drone delivery range. Therefore, in a drone routing problem, battery capacity, energy consumption, and battery replacement decisions (i.e., swapping the depleted battery with a fully-charged one) need to be incorporated to ensure safe deliveries of products. Most research studies on drone deployment and operations assume a fixed flight duration to reflect the battery capacity [1], whereas some studies consider the drone energy consumption to be a function of only drone speed, or package weight. But, in practice, drone energy consumption, and thus, the battery capacity is affected by several drone operating factors—speed, package weight, battery weight, distance traveled, and duration of flight components (e.g., ascend, descend, hover). Therefore, all these factors need to be accounted for while computing the drone energy consumption and in the drone routing decisions. Also, depending on the type of products, delivery locations, and customer preferences, business owners may need to use different delivery methods, such as landing with the package on the ground, or hovering above the ground and delivering the product through a winch. Different delivery methods cause different amounts of energy consumption, which can also affect the drone range. Therefore, practitioners (e.g., business owners) need to get insight into the question: how much do the package weight, drone speed, and delivery method affect the drone energy consumption, required fleet size (i.e., number of drones), and the required number of battery replacements?

In the drone routing literature on direct delivery from business to customers, all the studies assume that drones always fly in a straight path. However, in some areas, especially in densely populated urban areas, drones may not be able to fly in a straight path due to the presence of no-fly zones in the flight path, such as schools, large buildings, and restricted private property. To avoid these no-fly zones, flying over the road networks is a viable option as they are public property, resulting in a higher amount of energy consumption and delivery time. Therefore, how does the drone flight path (e.g., straight vs. over the road networks) affect the drone delivery range, energy consumption, required fleet size, and the required number of battery replacements in delivering all customer orders?

Also, all existing studies on direct delivery from business to customer consider that each drone delivers packages to multiple customers in a single trip before returning to the depot, which is not always possible, especially for rotary drones, such as quadcopters and hexacopters. Moreover, in current drone-delivery systems, such as Amazon Prime Air press releases [9] demonstrate drones delivering packages to a single customer on each trip. In case of delivering a single customer order on each trip, replacing the drone battery after each return to the depot is not practical. Because it is likely that there is a sufficient amount of energy remaining in the drone battery to make an additional delivery to another customer. Therefore, replacing the battery after each return can lead to an unnecessarily large number of battery replacements and less drone utilization, causing the business owner to have a large number of additional batteries and battery charging infrastructure, as well as a larger number of drones in the fleet to maintain a desired delivery time window for customers. Therefore, the question remains on how the drones be routed to minimize the required fleet size? How should drones be routed to minimize the required number of battery replacements? Most studies assume a homogeneous fleet of drones, where all drones are identical. But, customers are usually located at different distances from the business location (e.g., store) and their orders have different weights. Therefore, different drones may be suitable for different customer orders in terms of energy-efficiency. Therefore, how much is the benefit of using a mixed (heterogeneous) fleet of drones compared to using a homogeneous fleet?

The above-mentioned questions need to be answered quantitatively using real data for the retail business owners to demonstrate the potential of drones in the direct delivery of products to customers. Motivated by these needs, we study a drone routing problem for direct delivery of goods and proposed a mathematical optimization-based approach that incorporates realistic drone operating conditions and provides insights to the questions based on real drone flight test data. Specifically, our proposed mathematical optimization approach can provide insights into the effect of different operating parameters—drone speed, package weight, flight path, delivery method, fleet type—on the delivery range, required fleet size, required number of battery replacements, and energy consumption.

### 1.2 Related Literature

Drone routing optimization has been gaining a lot of attention to researchers recently. Several research teams have conducted comprehensive review of the recent studies on drone delivery and operations. Rojas et al. [10] and Marcina et al. [11] provide a review of the research on generic drone routing problems and for parcel delivery, respectively. Boysen et al. [12] provides a review of the operations research methods used for solving the last-mile delivery problems with drones. Otto et al. [13], Coutinho et al. [14], and Chung et al. [15] provide comprehensive reviews of the optimization approaches—models and algorithms—used for drone routing problems, where Chung et al. [15] focuses on drone and drone-truck combined routing applications, and Otto et al. [13] focuses on the civilian applications (e.g., medical supplies and disaster management) of drones. Meanwhile, Barmpounakis et al. [16] provides a review of the studies on using drones for surveillance in transportation and traffic engineering.

In the drone-based product delivery literature, combined drone and ground vehicle routing problems have been mostly studied, where ground vehicles (e.g., trucks, delivery van) carry one or multiple drones to perform localized deliveries. Researchers have studied a different variants of this combined drone-truck delivery problem: (1) drone and truck both deliver packages to customers [17, 18]; and (2) packages are delivered by drone only, whereas the trucks act as a mobile depot to carry drones to a longer distance [19] and provide drone battery recharging/replacement services [20]. Wang et al. [18] were the first to model a combined drone-truck parcel delivery problem seeking to reduce the total delivery time, where drones are carried by trucks. This proposed model ignores several realistic features of the problems, including the limitation of drone battery life, cost, and different distance metrics for drones and trucks. However, this study presents a comparison of the delivery time between a truck-only fleet and a drone-truck combined fleet. The Wang et al. [18] study was extended by Poikonen et al. [17] by incorporating the limited drone battery life and distance metrics for trucks and drones. Di Puglia Pugliese and Guerriero [21] extended the work of Wang et al. [18] and Poikonen et al. [17]

to minimize the overall travel cost. These authors made numerical comparisons between the use of a combined drone-truck fleet and a truck-only fleet in terms of transportation cost and total delivery time for last-mile delivery.

Murray and Chu [4] were the first to introduce two different variations of the drone-truck delivery problem, where in one variant, truck and drones work synchronously in delivering the package, whereas in the second variant, both the truck and drones independently deliver packages to the customers. However, in this routing problem, the authors only considered a single truck with multiple drones. Ham [22] and Murray and Raj [23] extended the drone-truck routing model of Murray and Chu [4] by introducing multiple drones and trucks. These studies were further extended in [24], where the drones can fly from a delivery truck and land on another truck, adding more flexibility to the delivery problem. Heimfarth et al. [25] extended the independent drone truck delivery problem accounting for the customer preferences in delivery time window requirement for each delivery, where the customer is provided a rebate if the time window is violated. There also exist studies where ground vehicles are used only as a carrier for drones (e.g., [26, 2]). Huang et al. [26] proposed a drone routing model for parcel delivery utilizing public transportation to carry drones to a longer distance.

However, none of the above-mentioned studies modeled drone battery replacements or charging phenomena, rather they made a limiting assumption that a drone battery is enough to complete each trip. Also, these studies mostly considered identical drones in the fleet. However, using a mixed fleet of drones is beneficial in making energy-efficient delivery. Gentili et al. [2] studied the problem of locating mobile depots (e.g., ground vehicles) and routing drones for providing emergency medical supplies to disaster-affected areas aiming to minimize the total disutility of the demand locations. The authors considered a mixed fleet, consisting of two types of drones—short-range and long-range. In their routing problem, each drone carries a single package to the demand point and returns back to the mobile depot. The authors did not explicitly model the battery replacement and resuming of the drone energy level, rather just added a fixed amount of time for package loading and battery replacement each time a drone returned to the depot. However, replacing the drone battery at each return is not realistic as there may be energy remaining in the drone battery to make the next trip. Therefore, this solution can lead to a larger number of unnecessary battery replacements, which results in a larger number of additional batteries and battery charging infrastructure. In the drone-truck hybrid delivery literature, none of the above studies explicitly modeled the drone battery replacement to minimize the required number of battery replacements, neither did they evaluate the impact of no-fly zones on fleet sizing decisions, delivery time, and energy consumptions. Only Jeong et al. [27] incorporated no-fly zones in the drone flight path in a drone-truck hybrid parcel delivery problem and evaluated the effect of no-fly zones on delivery time. However, these authors did not model the battery replacements and mixed fleet of drones.

Compared to truck-drone hybrid delivery, relatively less work has been done on deploying drones for the direct delivery of products to customers. Yadav and Narasimhamurthy [28] studied a UAV routing problem seeking to minimize the total time for delivery of all customer orders, where multiple drones can be used to deliver the demand of a single customer. However, the authors made an impractical assumption that drones can fly indefinitely in delivering customer orders. But, in practice, battery energy capacity is the major limitation of the drone-based deliveries that limits the drone delivery range. A Genetic algorithm-based procedure was presented by San et al. [29] for assigning drones to deliver packages to customer locations. Later, Song et al. [30] modeled the UAV delivery problem as a mixed-integer program and solved using a heuristics algorithm. Unlike Yadav and Narasimhamurthy [28] and San et al. [29], the authors considered the effect of package weight on the flight time of UAVs to reflect the limited battery capacity. However, they did not account for the other factors (e.g., drone speed, flight path) in computing the energy consumption, neither did they explicitly model battery energy consumption or battery replacements.

Dorling et al. [31] modeled the battery energy consumption as a function of drone battery and package weight. The authors proposed mixed-integer linear programming formulations for two variants of a drone routing problem with the objective functions of minimizing the total delivery time and the total cost, respectively. The model assumes that each drone can deliver multiple packages to different customers in a single trip and ensures that the battery capacity is enough to make a trip before the trip starts. The drone battery is replaced after each trip. However, this study does not explicitly model the minimum energy requirement to determine battery replacement, neither does it seek to minimize the number of battery replacements. Rabta et al. [32] modeled a drone routing problem in addition to drone battery charging location decisions for delivering disaster relief packages as a mixed-integer program. Like Dorling et al. [31], each drone can deliver multiple packages in a single trip and battery consumption is a function of package weight. Their model tracks the remaining drone battery energy in the model using a variable to determine the charging need. But the battery charging was not modeled explicitly accounting for the charging time or rate.

Some studies incorporated a time window for customer deliveries in the drone routing problem and optimize the fleet size in delivering customer orders. Troudi et al. [33] modeled a capacitated vehicle routing problem with time windows as a mixed-integer program to minimize the required number of drones and batteries. Similar to Dorling et al. [31], the authors assumed that each drone carries multiple packages in a single trip, and that the battery is replaced after each trip. Exploiting these assumptions, the authors minimized the number of batteries used by minimizing the number of trips. Cheng et al. [1] studied another multi-trip (i.e., each drone performs multiple trips starting and ending at the depot) drone routing problem with time windows aiming to minimize the travel cost and electricity consumption cost related to the drone battery. The authors considered drone energy consumption as a function of package weight and distance traveled. However, they used theoretical power consumption during hovering to approximate the forward flight energy consumption, which is not realistic. Another multi-trip drone delivery problem with time windows was studied by Kong et al. [34] to minimize the total routing distance in delivering all parcels to customers. Considering energy consumption as a function of package weight, Choi and Schonfeld [35] studied an automated drone delivery system to minimize the total cost by optimizing fleet size. The authors demonstrated the sensitivity of the drone speed and battery capacity on the system cost and fleet size, respectively. All the above-mentioned studies assume the drone fleet is homogeneous.

Coelho et al. [36] studied a drone routing problem for a mixed fleet of drones, containing six different types of drones, with the objectives of minimizing the total distance, total delivery time, and the number of drones used. However, the authors considered drone energy consumption as a function of drone speed only. But the drone energy consumption is affected by several other operating parameters—package weight, drone body and battery weight, distance traveled, and duration of different flight segments (e.g., ascend, descend, hover). In addition to Coelho et al. [36], all the above-mentioned studies on drone-only delivery modeled the drone routing problem assuming each drone delivers packages to multiple customers in a single trip, and that the battery is replaced after each trip. Under this assumption, the routing problem is modeled just to ensure the battery energy is enough to complete each trip in visiting the customers. But, in practice, many drones—especially rotary drones—are designed to carry a single package on a trip. In this case when a drone visits only a single customer on each trip, replacing the drone battery after each return to the depot will lead to an unnecessarily large number of battery replacements and less drone utilization, which can eventually result in a large number of additional batteries or charging infrastructure and the larger number of drones to maintain the same delivery time window. Additionally, all the above studies on drone routing assume drones fly in a straight path, which may not be always possible, especially in a dense urban environment.

There exist other studies on drone routing focused on the effect of drone delivery on carbon emission (e.g., [37, 38]) and locating drone deployment and charging facilities to improve demand coverage (e.g., [39, 40]).

#### **1.3** Contributions

In summary, existing studies have not simultaneously considered the different factors (e.g., drone speed, package weight, distance traveled, duration of ascend, descend, hover) affecting drone energy consumption and delivery range. A lack of studies exist analyzing the improvement in the energy-efficiency of the drone fleet due to using a mixed fleet of drones compared to a homogeneous fleet. In the direct delivery of goods from business to customers, no research has explicitly modeled the drone battery replacement decisions accounting for the remaining energy in drone battery, user-specified minimum required energy in drone battery, and drone routing when each drone visits a single customer on each trip. Existing studies assume that each drone battery after each return to the depot, which can lead to an unnecessarily large number of battery replacements when each drone visits a single customer in each trip, eventually necessitating a large number of additional batteries and drones. Additionally, no research has analyzed the effect of routing drones over the road networks—due to avoiding restricted and no-fly zones—on total energy consumption, required fleet size (i.e., number of drones), and the required number of battery replacements.

Therefore, to fill the gaps in the literature, we studied a drone deployment optimization problem for direct delivery of goods that accounts for the different factors (e.g., drone speed, package weight, distance traveled, duration of ascend, descend, hover) affecting drone energy consumption, pickup time window for customer orders, and battery replacement decisions to evaluate the performance of drone-based delivery under different drone operating parameters—speed, flight path (e.g., straight vs. over the road networks), fleet type (e.g., homogeneous vs. mixed fleet), and package delivery method (e.g., landing vs. package dropping). This is the first study to (1) model the drone routing problem where the drone battery is not replaced after each return to the depot, rather a battery replacement is decided by the optimization model accounting for the remaining battery energy, minimum required energy for safe operation, and drone routing to minimize the number of battery replacements needed; and (2) evaluate the effect of several key drone operating parameters—flight path, fleet type, and minimum required energy in the drone battery—on the delivery range, energy consumption, required fleet size, and the number of times battery needs to be replaced.

Our paper extends the drone routing literature by introducing a new mathematical optimization approach that incorporates real-life drone operating characteristics and presents new insights based on real drone flight test data. Specifically, in this paper, we made the following contributions: (1) developed new mathematical optimization models that incorporate the business limitations and drone operating conditions and seek to optimally route the drones to minimize the total energy consumption, required fleet size, and the required number of battery replacements in delivering a set of customer orders; (2) proposed two valid inequalities to improve the computational efficiency of the mathematical model; and (3) provided numerical results and new insights based on real data into the effect of drone speed, package weight, flight path, minimum required energy, delivery method, fleet type, and pickup time window on the drone delivery range, total energy consumption, required fleet size, and the required number of battery replacements.

### 2 Problem Description

In this paper, we study the problem of a retail business owner (e.g., grocery stores, restaurants) seeking to efficiently deploy drones to directly deliver goods to a set of customer locations that minimizes the total energy consumption, the required fleet size, and the required number of battery replacements. We assume that the business owner owns the drone fleet and that all drones are stationed at the business location that acts as a central depot for the drones. The drone fleet may consists of the same type (i.e., homogeneous fleet) or different types (i.e., mixed fleet) of drones. The customers are geographically located around the central depot. The business owner whows the geographic location (i.e., latitude and longitude) from where each customer order originates, as well as the time stamp of order placement. In this business scenario (see Figure 1), each drone carries a single package in a flight from the depot to a delivery (i.e., customer) location and then returns to the depot before flying to the next delivery location.

Depending on the business and product types, customers may have different preferences on the time window (e.g., 2 minutes for Starbucks coffee vs. 30 minutes for a grocery item) they are willing to allow for drones to pick up the products once they are ready for delivery. To account for this realistic customer preference criterion in retail business, we consider a pickup time window for each customer order within which a drone must pick up the product from the depot. This time window for each customer order is defined by the package ready time (i.e., earliest possible pickup time) and the maximum permissible delayed pickup time. The travel



Figure 1: Business scenario.

time of a drone from the depot to a delivery location consists of the time required to ascend to the flying height, forward flight time to reach the delivery location, short hovering duration required to ensure the correct landing location, and the time required to descend to the ground. We also consider the time required to load and unload the packages to/from the drone at the depot and the delivery locations, respectively, as these package loading and unloading times affect drone operation and satisfying the customer order pickup time windows.

We consider that each drone starts with a fully-charged battery at the beginning of the planning horizon. As the drones continue to deliver packages to the customer locations, energy in the drone battery gets consumed, and thus, the remaining energy in the drone battery gradually decreases. The energy consumption during drone operation depends on several operating parameters, such as drone speed, package weight, distance traveled, duration of flight segments (i.e., ascend, descend, hover), and delivery method. To ensure safe operation of the drones, prior to leaving the depot for the next delivery location, we need to ensure that the drone battery would have at least a minimum required amount of energy remaining after returning from that delivery location. Therefore, before leaving the depot for the next delivery location, we need to compute the potential remaining energy in the drone battery after returning from the next location. If the potential remaining energy is less than the minimum required energy, the current battery needs to be replaced with one that is fully-charged before leaving for the next delivery location.

However, despite starting with a fully-charged battery to deliver a package to a delivery location, if the potential remaining energy in the drone battery drops below the minimum required energy, then it is not possible for the drones to deliver a package to that particular location. We refer this particular delivery location to be outside the *delivery range* of the drone. This *delivery range* of a drone varies with different operating parameters—drone speed, package weight, drone flight path, delivery method, and minimum required energy. A drone cannot be assigned to serve a location that is outside its delivery range. In addition, each drone has a maximum weight carrying capacity that cannot be exceeded, meaning that the drone cannot be used to deliver a package that weighs more than the maximum allowable weight.

### 3 Methods

To solve the drone deployment problem discussed in Section 2, we formulate the problem as a mixed-integer program. In this section, we present the mathematical formulations of the drone deployment problem for both homogeneous and mixed fleets of drones. We lists the necessary sets, parameters, and variables that support the mathematical formulations in Table 1.

### Table 1: Notation.

(a)	Sets
-----	------

Sets	Description
I	Set of delivery locations $i$
$\mathcal{I}'$	Set of delivery locations including the dummy source 0 and sink $S$
$\mathcal{D}$	Set of drone types $d$

(b)	Parameters
-----	------------

Parameters	Description
$C_d$	Amortized cost of the drone type $d$
$C_{bat}^d$	Amortized cost of the battery of drone type $d$
v	Drone speed
$C_E$	Cost of per unit of energy
$C_L$	Wage of a drone operator
$n_d$	Number of drones of type $d$ a drone operator can operate simultaneously
$C_d^M$	Maintenance cost of a drone of type $d$
$L_i^a$	Distance of delivery location $i$ from depot
$t_{Hi} = \frac{L_i}{v}$	Time required for drone to arrive at delivery location $i$
U	from depot
$t_{iH} = \frac{L_i}{v}$	Time required for drone to return from delivery location $i$
U	to depot
$t_d^{bat}$	Time required to replace the battery of drone type $d$
$\ddot{e}_i$	Earliest possible pickup time
$\Delta$	Maximum permissible delay
$ch_d^0$	Initial energy in the battery of drone type $d$
$ch_d^{min}$	Minimum remaining energy required in the battery of
	drone type $d$
$E_{dHi}$	Energy consumption by a drone of type $d$ to arrive at
	delivery location $i$ from depot with a package
$E_{diH}$	Energy consumption by drone of type $d$ to return empty
	from delivery location $i$ to the depot
$c_{ij}^d$	Energy consumption by a drone of type $d$ to fly from
~	location i to j, i.e., $c_{ij}^d = E_{diH} + E_{dHj}$
$M_d^{max}$	Maximum package weight carrying capacity of drone type $d$
$M_i$	Package weight for delivery location $i$

(c)	Variables
-----	-----------

Variables	Description
$\overline{z_{ij}}$	1 if delivery location $i$ is served immediately before $j$ by a
	drone, 0 otherwise
$y_i$	1 if drone battery is replaced after returning from delivery
	location $i$ , 0 otherwise
$g_i$	Remaining battery energy of a drone after returning from
	delivery location $i$
$g'_i$	Auxiliary variable storing the remaining battery energy
	after returning from delivery location $i$
$f_i$	Timing of when a drone picks-up the package for delivery
	location $i$ at depot
$x_{di}$	1 if drone type $d$ is assigned to deliver a package to location
	i, 0 otherwise

#### 3.1 Model for Homogeneous Fleet of Drones

In this subsection, we assume that the drone fleet is homogeneous, meaning that the drones are identical. Taking advantage of this assumption, we can develop the drone deployment model as a two-index formulation, similar to the vehicle routing literature (e.g., [41]). As mentioned in Section 2, in the retail business scenario studied in this paper, each drone directly flies from the depot to a delivery location and returns to the depot before flying to the next location. To model this drone routing problem as a network optimization problem (an example network is shown in Figure 2), we add a dummy source (0) and a sink (S) to the set of delivery locations  $\mathcal{I}$ , resulting in a new set  $\mathcal{I}'$ . In Figure 2, the path 0 - 1 - 2 - 4 - S indicates that a drone starts with delivering a package to location 1 and returns to the depot, then visits location 2 and returns to the depot again, before making its last delivery to location 4. We define a variable  $z_{ij}$  that represents whether a drone visits location j after returning from location i or not. The corresponding parameter to this variable,  $c_{ij}^d$ , denotes the energy consumed by the drone to return empty to the depot from location i and then arrive at location j with the package. The variable  $z_{0i}$  represents an outgoing arc from the dummy source (0), as well as the beginning of a sequence of delivery locations visited by a drone. Therefore, adding a large penalty to the corresponding energy consumption parameter,  $c_{oj}$ , we can minimize the number of outgoing arcs (i.e., routes) from the source, and thus minimize the required fleet size, which is the number of drones used to deliver packages to all locations.



Figure 2: An example network representation of the original problem.

The mixed-integer programming (MIP) formulation of the drone deployment optimization problem is presented below.

#### **Objective Function**

The goal of our drone deployment optimization problem is to find the optimal drone routing that minimizes both investment and operating costs in delivering all customer orders within a specified planning horizon. The investment cost includes the drone and battery costs, whereas the operating cost includes the energy consumption, drone operator, and maintenance costs.

$$\min C_E\left(\sum_{i\in\mathcal{I}'}\sum_{j\in\mathcal{I}'}c_{ij}^d z_{ij}\right) + \left(C_d + \frac{C_L}{n_d} + C_d^M\right)\sum_{j\in\mathcal{I}'}z_{0j} + C_{bat}^d\left(\sum_{i\in\mathcal{I}'}y_i\right)$$
(1)

The objective function (1) seeks to minimize the total energy consumption cost (component 1), total investment and operating costs of the drones (component 2), and investment costs of the batteries (component 3) in delivering all customer orders maintaining the specified pickup time windows within the planning horizon. As the costs of drones and batteries are functions of the number of drones required and the number of times battery needs to be replaced, respectively, an optimal solution to this drone routing MIP model provides the minimum required fleet size (i.e., required number of drones) and the minimum required number of battery replacements, which is also the minimum required additional batteries, to deliver all customer orders satisfying the specified time windows.

### Assignment and Flow Balance Constraints

As mentioned earlier, in this drone routing problem, each customer order is delivered once by only one drone and the drones return to the depot after delivering a package to each location before visiting the next location.

$$\sum_{i \in \mathcal{I}'} z_{ij} = 1 \qquad \forall j \in \mathcal{I}$$
<sup>(2)</sup>

$$\sum_{j \in \mathcal{I}'} z_{ij} = 1 \qquad \forall i \in \mathcal{I}$$
(3)

$$\sum_{i \in \mathcal{I}'} z_{ij} = \sum_{i \in \mathcal{I}'} z_{ji} \qquad \forall j \in \mathcal{I}$$
(4)

$$\sum_{j \in \mathcal{I}} z_{0j} = \sum_{j \in \mathcal{I}} z_{jS} \tag{5}$$

Constraints (2)–(3) ensure that each customer order is delivered once by only one drone. Constraints (4) and (5) are the flow balance constraints for the customer locations, and dummy source-sink pair, respectively, ensuring that if a drone visits a location *i*, it must return to depot from that location to visit the next location in the delivery sequence until the drone completes its route.

### Package Weight and Delivery Range Constraints

As mentioned in Section 2, a drone cannot be used to deliver a package to a location that is out of its delivery range. Constraints (6) represent this delivery range limitation. In addition, a drone cannot be used to deliver a customer order if the package weight exceeds the maximum weight carrying capacity, which is enforced by constraints (7).

$$\sum_{i \in \mathcal{I}'} \left( E_{dHj} + E_{djH} \right) z_{ij} \le \left( ch_d^0 - ch_d^{min} \right) \qquad \forall j \in \mathcal{I}$$
(6)

$$M_j \sum_{i \in \mathcal{I}'} z_{ij} \le M_d^{max} \quad \forall j \in \mathcal{I}$$
 (7)

#### **Pickup Time Window Constraints**

Constraints (8) ensure that the pickup time of the packages for the delivery locations are computed consistently accounting for the sequence in which each drone visits the locations. Constraints (9) enforce the time windows within which each package must be picked-up for the delivery locations by the drones.

$$f_j \ge f_i + (t_\ell + t_{Hi} + t_u + t_{iH}) + t_d^{bat} y_i - M(1 - z_{ij}) \qquad \forall i, j \in \mathcal{I}', i \neq j$$
(8)

$$e_i \le f_i \le \ell_i \qquad \forall i \in \mathcal{I} \tag{9}$$

Here,  $\ell_i = e_i + \Delta$  is the maximum permissible delayed pickup time for delivery location *i* and *M* is a large positive number.

#### **Battery Replacement Constraints**

To ensure safe operation of the drones, before visiting the next location, we need to compute how much energy would be remaining in the drone's battery after returning to the depot from its delivery location and replace the battery if needed. Constraints (10) compute the potential remaining energy in the drones' batteries after returning from the first delivery location in each delivery sequence (i.e., route). Each constraint (11) computes the potential remaining energy in the drone's battery after returning from each delivery location except for the first location in each delivery sequence. This constraint ensures the potential remaining energy in the drone's battery is computed consistently accounting for the sequence in which the delivery locations are visited by the drone. For example, if location 4 is visited after location 3 (i.e.,  $z_{34} = 1$ ), then the potential remaining energy after returning from delivery location  $4 (E_{dH4} + E_{d4H})$  from the remaining energy after returning from location 3 (g<sub>3</sub>), i.e.,  $g'_4 \leq g_3 - (E_{dH4} + E_{d4H})$ .

$$g'_{j} \le ch_{d}^{0} - (E_{dHj} + E_{djH}) + M(1 - z_{0j}) \qquad \forall j \in \mathcal{I}'$$
(10)

$$g'_{j} \leq g_{i} - (E_{dHj} + E_{djH}) + M(1 - z_{ij}) \qquad \forall i, j \in \mathcal{I}', i \neq j$$

$$\tag{11}$$

If the potential remaining energy after returning from a delivery location j is less than the minimum required energy (i.e.,  $g'_j < ch_d^{min}$ ), then we need to replace the current battery with a fully-charged one (i.e.,  $y_i = 1$ ) before the drone leaves the depot to visit location j. This condition is represented by constraints (12). But, if the potential remaining energy after returning from delivery location j is higher than the minimum required energy (i.e.,  $g'_j \ge ch_d^{min}$ ), then the battery must not be replaced before visiting j, and thus, the drone should continue its operation with the remaining energy  $(g_i)$  after returning from its previous location i. Constraints (13) enforce this condition. Here,  $M_u$  and  $M_\ell$  are the upper and lower bounds of  $(g'_j - ch_d^{min})$ , respectively.

$$g'_{i} - ch_{d}^{min} \ge M_{\ell} y_{i} + M(z_{ij} - 1) \quad \forall i \in \mathcal{I}', j \in \mathcal{I}' \setminus \{0\}, i \neq j$$

$$\tag{12}$$

$$g'_j - ch_d^{\min} \le M_u(1 - y_i) + M(1 - z_{ij}) \quad \forall i \in \mathcal{I}', j \in \mathcal{I}' \setminus \{0\}, i \neq j$$

$$\tag{13}$$

Depending on whether the battery is replaced or not before visiting the next location j, we need to compute the actual energy remaining after returning from location j. If the current battery is replaced with a fully-charged one after returning from location i (or before visiting location j), then the battery energy is resumed to the initial energy level  $ch_d^0$ . Therefore, if the battery is replaced before visiting location j (i.e.,  $y_i = 1$ ), then the energy remaining after returning from location j is computed by subtracting the total energy consumption due to round-trip travel to location j from the initial battery energy, i.e.,  $g_j \leq ch_d^0 - (E_{dHj} + E_{djH})$ . Constraints (14) represent this condition. If the drone's battery is not replaced before visiting location j (i.e.,  $y_i = 0$ ), the energy remaining after returning from location j is computed based on the remaining energy  $(g_i)$  after returning from its previous location i as  $g_j \leq g_i - (E_{dHj} + E_{djH})$ . This condition is represented by constraints (15). Each constraint (16) computes the actual energy remaining after returning from the first location in each delivery sequence. Here,  $Q_u$  is the upper of  $(ch_d^0 - g_j)$ .

$$g_j \le ch_d^0 - (E_{dHj} + E_{djH}) + Q_u(1 - y_i) + M(1 - z_{ij}) \quad \forall i, j \in \mathcal{I}', i \ne j$$
(14)

$$g_j \le g_i - (E_{dHj} + E_{djH}) + Q_u y_i + M(1 - z_{ij}) \quad \forall i \in \mathcal{I}' \setminus \{0\}, j \in \mathcal{I}', i \ne j$$

$$(15)$$

$$g_j \le ch_d^0 - (E_{dHj} + E_{djH}) + Q_u y_0 + M(1 - z_{0j}) \quad \forall j \in \mathcal{I}'$$
(16)

#### Sign Restriction Constraints

Constraints (17)-(20) represent the binary nature and sign restrictions of the variables.

$$z_{ij} \in \{0, 1\} \qquad \forall i, j \in \mathcal{I}', i \neq j \tag{17}$$

$$g_i \ge 0 \qquad \forall i \in \mathcal{I}' \tag{18}$$

$$g'_i \ge -ch_d^{\min} \qquad \forall i \in \mathcal{I}' \tag{19}$$

$$f_i \ge 0 \qquad \forall i \in \mathcal{I}' \tag{20}$$

### 3.2 Model for Mixed Fleet of Drones

We propose a two-phase modeling approach to solve the drone deployment optimization problem for a mixed fleet of drones, which contains different types of drones in the fleet. In the first phase, we develop an integer programming model to find the energy-efficient assignment of the different types of drones to deliver packages to the delivery locations. This drone assignment model (21) accounts for the limitations of battery energy and package weight carrying capacity for different types of drones and provides the optimal assignment of drone types to the delivery locations.

min 
$$\sum_{i \in \mathcal{I}} \sum_{d \in \mathcal{D}} \left( E_{dHi} + E_{diH} \right) x_{di}$$
(21a)

s.t., 
$$\sum_{d \in \mathcal{D}} x_{di} = 1$$
  $\forall i \in \mathcal{I}$  (21b)

$$(E_{dHi} + E_{diH}) x_{di} \le \left(ch_d^0 - ch_d^{min}\right) \qquad \forall d \in \mathcal{D}, i \in \mathcal{I}$$
(21c)

$$M_i x_{di} \le M_d^{max} \quad \forall i \in \mathcal{I}, d \in \mathcal{D}$$
 (21d)

$$x_{di} \in \{0, 1\} \qquad \forall i \in \mathcal{I}, d \in \mathcal{D}$$
 (21e)

The objective function (21a) seeks to optimally assign drone types to the delivery locations that minimizes the total energy consumption in delivering packages to all locations. Each constraint (21b) ensures that only one type of drone can be assigned to deliver a package to a location. A drone type d cannot be assigned to deliver a package to a location i if that drone type consumes more energy than the maximum allowable energy consumption (i.e.,  $ch_d^0 - ch_d^{min}$ ) in delivering the package to that location. Constraints (21c) enforce this battery energy limitations for the drone types. Each constraint (21d) represents that a drone type d cannot be assigned to deliver a package to a location i if the package weight for that delivery,  $M_i$ , exceeds the maximum weight carrying capacity,  $M_d^{max}$ , of that drone type. Constraints (21e) represent the binary nature of the assignment decision variables.

The output of this first-phase modeling is the subsets of delivery locations and their corresponding drone types. We use the MIP model for homogeneous fleet of drones presented in Section (3.1) for each subset of delivery locations and the corresponding drone type d to obtain the required number of drones of type d, the total energy consumption in delivering packages to the locations in that subset, and the required number of battery replacements. Combining the results from each subset and drone type, we obtain the minimum total number of drones of different types required in the fleet, which is the required fleet size, and the total energy consumption by all drones in delivering all packages. A flowchart of this two-phase modeling approach is demonstrated in Figure A.1 (see Appendix A) to clarify the modeling concept.

#### **3.3** Acceleration Techniques

We observed that the number of  $z_{ij}$  variables in the developed drone deployment MIP model increases by  $|\mathcal{I}'|$  for each additional delivery location in the data. A large number of constraints are also added in the model for each additional delivery location. Therefore, as the number of delivery locations in our drone deployment problem increases, the computational complexity of the MIP model increases exponentially. To alleviate the computational burden in solving the MIP model, we implement two problem-specific valid inequalities that substantially reduce the number of  $z_{ij}$  variables. We observed that in the optimal solution, most of the  $z_{ij}$  variables are zero. Therefore, we implement the following two valid inequalities to remove those unnecessary  $z_{ij}$  variables from the candidate solutions:

1. A drone cannot pick up the package for delivery location j immediately after serving

location *i*, if the maximum permissible delayed pickup time for j ( $\ell_j$ ) is earlier than the earliest time the drone can return to the depot after serving location *i*. Each constraint (22) removes the  $z_{ij}$  variables from the candidate solutions for which this condition holds.

if 
$$e_i + t_\ell + t_{Hi} + t_u + t_{iH} > \ell_j$$
  
then  $z_{ij} = 0 \quad \forall i, j \in \mathcal{I}$  (22)

2. If the time difference between the maximum delayed pickup time for delivery location j and returning from location i is longer than the time required for a drone to serve the furthest location, then the drone will not wait for such a long duration to pick up the package for location j after returning from location i. This is because, the objective of our model is to minimize the total number of drones required to deliver packages to all customer orders. Therefore, the drone will deliver a package to another location k after returning from location i, meaning  $z_{ij} = 0$ . Constraints (23) remove the  $z_{ij}$  variables from the candidate solutions for which this condition holds.

if 
$$\ell_j > \ell_i + t_{Hi} + t_{iH} + 2(t_\ell + t_u + 2t_{Range})$$
  
then  $z_{ij} = 0 \quad \forall i, j \in \mathcal{I}$  (23)

### 4 Case Study Results and Managerial Insights

We used our mathematical models described in Section 3 to provide insights into the following questions:

- 1. How do the drone operating parameters—speed, package weight, flight path, minimum required energy in the battery—affect the delivery range?
- 2. How does the drone speed, package weight, delivery method, flight path affect the total and average energy consumption in delivering packages to customer locations?
- 3. How does the required fleet size (i.e., number of drones required) changes with the drone speed, package weight, and flight path?
- 4. How sensitive is the required fleet size to changes in the pickup time window?
- 5. How frequently do batteries needs to be replaced as the drone speed, package weight, flight path, and minimum required energy change?
- 6. How does the use of a mixture of drones in the fleet affect the delivery range, total energy consumption, and the required fleet size?

### 4.1 Experimental Setup

We implemented the drone deployment optimization models described in Section 3 using Python 3.7 with Cplex optimizer 12.10 [42]. We conducted numerical experiments using a one-hour

Spatio-temporal prepared food delivery data from the San Francisco Bay Area in California. This delivery data contains the business provider and 126 customers' geographic locations (i.e., latitude and longitude) and the timing of when a package is ready for pick up. We synthetically generated the package weight for each customer order or delivery location. We conducted drone flight tests using two rotary drones—DJI Matrice 600 Pro and Tarot 650—for different operating conditions—drone speed, flight path (e.g., straight, over the road networks), and package weight. DJI Matrice 600 Pro is a rotary hexacopter that has higher package weight carrying capacity at a longer distance than the Tarot 650, which is a rotary quadcopter. Table 2 lists the parameters and their values that are kept fixed in all numerical experiments. While designing and conducting the drone flight tests, we used United States Customery System (USCS) units. Therefore, in Tables 2 and 3, we provided the parameter values both in USCS and SI units. We used the amortized hourly costs of the drones and batteries to run our numerical experiments.

Demometers	DJI Matrice 600 Pro Values		Tarot 650 Values	
Farameters	USCS	SI Unit	USCS	SI Unit
	$\mathbf{Unit}$		$\mathbf{Unit}$	
Initial battery energy (fully-charged), $ch^0$	600 watt-hour	2.16 Mega-Joule (MJ)	177.6 watt-hour	0.639 Mega-Joule (MJ)
Package loading time, $t_{\ell}$	5 minutes	5 minutes	5 minutes	5 minutes
Package unloading time (landing), $t_u$	30 seconds	30 seconds	30 seconds	30 seconds
Battery replacement time, $t_d^{bat}$	5 minutes	5 minutes	5 minutes	5 minutes
Flying height	200 feet	60.96	200  feet	60.96
		meters		meters
Hovering duration while delivering package (landing)	5 seconds	5 seconds	5 seconds	5 seconds
while returning to	5 seconds	5 seconds	5 seconds	5 seconds
Cost of a drone battery	\$8000 \$1200	\$8000 \$1200	\$4000 \$200	\$4000 \$200
Labor (drone operator) cost	60/hour	60/hour	60/hour	60/hour
Number of drones operated by an operator	5	5	5	5

Table 2: Fixed parameter values.

We conducted numerical experiments for different combinations of the parameters shown in Table 3 to analyze the effects these parameters on total and average energy consumption, the required number of drones, and the required number of battery replacements. It is to be noted that we used the same package weight for all customer orders in each model run to demonstrate the individual effect of package weight on the delivery range, energy consumption, required number of drones, and battery replacements.

Paramotors	Values			
I al ameters	USCS Unit	SI Unit		
Drone speed	15, 30  (mph)	$6.71, 13.41 \ (m/s)$		
Package delivery method	Landing, Package	Landing, Package		
	dropping	dropping		
Minimum required battery energy,				
$ch^{min}$	10,  15,  20,  25	10,  15,  20,  25		
(%  of initial battery energy)				
Package weight	2.5, 5.0, 10.0 (lb)	1.13, 2.27, 4.54 (Kg)		
Hovering duration in package dropping	30, 60, 90, 120 (seconds)	30, 60, 90, 120 (seconds)		
Pick up time window	1, 5, 10, 15, 20, 25, 30,	1, 5, 10, 15, 20, 25, 30,		
	35  (minutes)	35  (minutes)		

Table 3: Parameters for sensitivity analysis.

In the numerical experiments, we used the power consumption and flight time data from our drone flight tests. The power consumption and flight time data of the DJI Matrice 600 Pro drone corresponding to the flight segments—ascend, forward flight, hover, and descend—for different package weights and drone speeds are provided in Table B.1 and B.2, respectively in Appendix B. Tables B.3 and B.4 in Appendix B show the power consumption and flight time data of the Tarot 650 drone, respectively. Using these power consumption and flight time data, we computed the energy consumption for each flight segment to use in the numerical experiments. To obtain the total time required and energy consumed by a drone to arrive with a package at a customer location (i) from the depot (H), we used the time and energy of the flight segments as shown in Figure 3a. Taking summation of the time of these flight segments, we obtained the model parameter  $t_{Hi}$ , whereas the summation of the energy of these segments provides the parameter  $E_{dHi}$ . Figure 3b demonstrates the flight segments when the drone returns to depot (H) from the delivery location (i). Combining the time and energy consumption of these segments provides the parameters  $t_{iH}$  and  $E_{diH}$ , respectively. Figure 3 demonstrates the flight segments when the drone is delivering packages by landing to the ground. Another delivery method is package dropping, when the drones hover at 20 feet (6.096 meters) above the ground and drops the package via a winch.



(a) Drone flight segments when delivering the (b) Drone flight segments when returning to package to a customer location

the depot

Figure 3: Drone flight segments.

### 4.2 Effect of Drone Speed and Package Weight on Delivery Range, Energy Consumption, Required Fleet Size, and Battery Replacements

The delivery range of a drone is limited by the drone's battery energy and the fact that we need to ensure a minimum required energy remains in the drone battery upon returning to the depot for its safe operation. We conducted numerical experiments to evaluate the effect of drone speed and package weight on the delivery range. In this analysis, we used the DJI Matrice 600 Pro drone for which we used the minimum required battery energy as 324 Kilo-Joule (KJ), which is 15% of the initial battery energy of 2.16 Mega-Joule (MJ). Therefore, the delivery locations for which the DJI drone consumes more energy than 1.836 MJ (= 2.16 - 0.324) to deliver the package and return, are considered to be outside the drone delivery range. As mentioned earlier, the delivery range is defined by the number of locations that are outside the range of drone delivery. Table 4 demonstrates the number of locations that are outside the drone range for two different drone speeds and three different package weights.

Drone Speed	Package Weight (Kg)		
(m/s)	1.13	2.27	4.54
13.41	0	0	0
6.71	27	29	45

Table 4: Number of locations outside drone delivery range.

We see from Table 4 that the DJI Matrice 600 Pro can deliver packages to all 126 customer locations when flying at 13.41 meter per second (m/s) speed. However, the drone cannot deliver packages to all locations when flying at 6.71 m/s. This is because, despite the average power consumption is less at a slower speed (6.71 m/s), the drone stays in the air for a much longer duration at 6.71 m/s speed to travel the same distance, resulting in a much larger total energy consumption as compared to 13.41 m/s speed in delivering a package. Due to this much larger consumption of energy, it is not possible for the drone to safely deliver packages to far away locations and return to the depot while flying at 6.71 m/s speed. The drone energy consumption increases as the package weight increases. Therefore, we see from Table 4 that more locations fall outside the delivery range when the weights of all customer orders increases from 1.13 Kg to 2.27 Kg and 4.54 Kg. As we see that 45 locations are outside the delivery range of the DJI drones with 6.71 m/s speed, we excluded these 45 locations for the other analysis in this subsection to ensure a fair comparison in the required fleet size (i.e., required number of drones), required number of battery replacements, and the total and average energy consumption between these two speeds.

Figure 4 demonstrates the variation in the required number of drones to deliver all customer orders as the speed changes from 13.41 m/s to 6.71 m/s. In this experiments, we used the pickup time window to be 15 minutes for the customer orders. We see that across all three package weights, more drones are needed with 6.71 m/s speed as compared to 13.41 m/s. The percentage increase in the required number of drones are 22.2%, 27.7%, and 20% corresponding to package weights of 1.13 Kg, 2.27 Kg, and 4.54 Kg, respectively, as the drone speed reduces from 13.41 m/s to 6.71 m/s. This is because, with a slower speed (i.e., 6.71 m/s), it is not possible to maintain the same pickup time window with the same number of drones as in 13.41 m/s. However, we

see that the package weight does not have much impact on the required number of drones. This is because, drone speed and travel time are not affected by the package weight. One or two additional drones are required as the package weight increases from 1.13 Kg due to the fact that a higher number of battery replacements are needed with a larger package weight. Due to this additional battery replacement time, additional drones are needed to maintain the same time window.



Effect of Drone Speed and Package Weight on Number of Drones Required

Figure 4: Effect of drone speed and package weight on the required number of drones.

Figures 5a and 5b demonstrate the effect of drone speed and package weight on the total energy consumption in delivering all customer orders and on the average energy consumption per delivery, respectively. We see that the total and average energy consumption increases as the drone speed reduces from 13.41 m/s to 6.71 m/s across all three package weights. As mentioned earlier, the average power consumption by a drone is lower at a slower speed, but the drone stays in the air for a longer duration to travel the same distance at a slower speed. Therefore, compared to the 13.41 m/s speed, flying at 6.71 m/s results in a much larger energy consumption in delivering each customer order, eventually increasing the total and average energy consumption. We have observed that the total energy consumption increases by 47.96%, 45.78%, and 53.82% corresponding to the package weights of 1.13 Kg, 2.27 Kg, and 4.54 Kg, respectively, as the drone speed reduces from 13.41 m/s to 6.71 m/s. The percentage changes in the average energy consumption per delivery also demonstrates the same trend and magnitude. It is evident from Figures 5a and 5b that the energy consumption increases as the drones carry larger package weight at both speed levels, which is very intuitive. The percentage increase in total energy consumption are 10.03% and 23.45% as the package weight of all customer orders increases from 1.13 Kg to 2.27 Kg and 4.54 Kg, respectively, at 13.41 m/s drone speed. We see a similar effect with an increase in the package weight on energy consumption when the drone speed is 6.71 m/s.

Figure 6 demonstrates the effect of drone speed and package weight on the required number of battery replacements in delivering all 81 customer orders. We see that the drone battery needs



Figure 5: Effect of drone speed and package weight on energy consumption.

to be replaced a substantially larger number of times in delivering all customer orders at 6.71 m/s speed as compared to 13.41 m/s speed. This is due to an increased energy consumption at 6.71 m/s speed as discussed earlier. As the energy consumption at 6.71 m/s speed is higher than at 13.41 m/s speed in delivering a customer order, the minimum required battery energy is reached more frequently at a slower speed, thus necessitating more battery replacements.



Effect of Drone Speed and Package Weight on Battery Replacement Instance

Figure 6: Effect of drone speed and package weight on the required number of battery replacements.

The required number of battery replacements also increases as the package weight increases at the same speed level. Table 5 demonstrates the percentage increase in the number of battery replacements as the package weight of all customer orders increases from 1.13 kg for the two speed levels.

### 4.3 Effect of Delivery Method on Energy Consumption

While delivering a package to a customer location, the drone can either land on the ground, as shown in Figure 3 or hover 20 feet (6.096 meters) above the ground and drop the package via

Package Weight	Percentage Increase in Number of Battery Replacements		
(Kg)	Speed: 13.41 $m/s$	Speed: 6.71 $m/s$	
2.27	25.0	23.33	
4.54	56.25	56.67	

Table 5: Effect of package weight on the number of battery replacements.

a winch. As the hovering operation is energy-intensive, we compare the energy consumption between these two delivery methods—package dropping and landing with a package to the ground. Depending on the type of product, the hovering duration while package dropping can be different, ranging from 30 seconds to several minutes. Therefore, we compared the total energy consumption in delivering all customer orders via landing with four different package dropping methods where the hovering durations are 30 seconds, 1 minute, 1.5 minutes, and 2 minutes. In this analysis, we used the data for the DJI Matrice 600 Pro drone flying at a speed of 13.41 m/s while carrying a package weight of 1.13 Kg.

We would like to note that compared to landing, the drones save some amount of ascend and descend energy while package dropping by not descending to the ground, as well as not ascending from the ground while returning. Table 6 demonstrates the percentage increase in the total energy consumption for using the different package dropping methods as compared to landing. We see that when the hovering duration in package dropping is short (e.g., 30 seconds), the percentage increase in the total energy consumption is not significant compared to energy consumption in landing. As such, the package dropping also saves some energy by avoiding to land and ascend from the ground. However, as the hover duration becomes longer, drones consume a much higher amount of energy while delivering a package via dropping as compared to landing.

Delivery Method	Hovering	% Increase in Energy
Delivery Method	Duration	Consumption
Package dropping 1	30 seconds	1.45
Package dropping 2	$1  \mathrm{minute}$	6.0
Package dropping 3	1.5 minutes	12.48
Package dropping 4	2 minutes	14.98

Table 6: Comparison of energy consumption between landing and package dropping.

### 4.4 Effect of Minimum Required Battery Energy on Delivery Range and Battery Replacements

We mentioned earlier that a minimum specified amount of energy should be remaining in the drone battery each time a drone returns to the depot to ensure the safe operation of the drones. This is because, if the remaining energy in the drone battery drops below a critical level, the drone will be grounded while flying. This critical minimum required amount of energy for our DJI Matrice 600 Pro is 10% of the initial battery energy of 2.16 MJ. However, business owners may choose a larger value of this minimum required energy than 10% to ensure the safe operation of the drones under adverse conditions, such as flying in the opposite direction of

strong wind. Different business owners can have different levels of risk preferences and set the minimum required amount of energy to different levels. Therefore, we analyzed the effect of different values of this minimum required energy on the delivery range and the required number of battery replacements in delivering all customer orders.

Table 7 demonstrates the number of delivery locations out of drone range for four different values of minimum required levels of battery energy—10%, 15%, 20%, and 25% of the initial battery energy—and three different package weights—1.13 Kg, 2.27 Kg, and 4.54 Kg. We see that more locations fall outside the delivery range as the minimum required battery energy increases with the same package weight. This is because as the requirement for remaining energy in the drone battery after returning from each delivery location increases, this increased threshold cannot be met for a higher number of locations. Therefore, with this increased minimum required amount of energy, the number of customer locations that drones cannot safely deliver packages to increases. In addition, the number of locations outside the delivery range increases as the package weight increases within the same minimum required battery energy level. This is because the energy consumption increases with the package weight; thus, the minimum required energy threshold cannot be met for a larger number of locations and fall outside the delivery range.

Minimum Required	Number of Locations Outside Delivery Range			
Battery Energy (KJ)	m = 1.13	m = 2.27	m = 4.54	
	Kg	$\mathbf{K}\mathbf{g}$	Kg	
216 (10%)	0	0	6	
324~(15%)	0	0	10	
432~(20%)	0	7	12	
540~(25%)	2	10	14	

Table 7: Effect of minimum required battery energy on delivery range.  $\mathbf{m}$  denotes the package weight.

This minimum required amount of battery energy also affects the required number of battery replacements in delivering packages to customer locations. To demonstrate this effect, we conducted numerical analysis for the four different values of minimum required battery energy with 1.13 Kg package weight and excluding the two locations outside the delivery range, as shown in Table 7. Figure 7 demonstrates that the required number of battery replacements in delivering packages to all 124 customer locations increases as the minimum required battery energy increases. As the minimum required battery energy is set to a higher level, the minimum threshold is reached more quickly during drone operations, which increases the frequency of replacing the drone batteries. We see from Figure 7 that the required number of battery replacements increases substantially (i.e., 34%) as the minimum required energy increases from 10% to 25% of the initial battery energy.

#### 4.5 Effect of Time Window on the Required Fleet Size

We analyzed the impact of a pickup time window requirement of customer orders on the minimum required drone fleet size (i.e., required number of drones) to deliver all customer orders. As mentioned in Section 2, we considered a pickup time window in which a customer wants a drone



Effect of Minimum Required Battery Energy on Battery Replacement Instance

Figure 7: Effect of minimum required battery energy on the required number of battery replacements.

to pick the product up for delivery to them. This time window requirement is different for different products and business types (e.g., 2 minutes for Starbucks coffee vs. 30 minutes for grocery items from Walmart). Our drone deployment optimization model accounts for this time window preference of customers while finding the optimal solution—minimum required fleet size, required number of battery replacements, and energy consumption.

Figure 8 demonstrates the variation in the required number of drones as the pickup time window increases from 1 to 35 minutes. We see that the required number of drones in delivering all customer orders decreases as the time window increases. In a real-life business environment, multiple customer orders are placed at the same time or their order placement times very close to each other, which is reflected in the real-life delivery data we used in our case study. In this real-life business environment, with a more flexible pickup time window, the same drone can be used to deliver packages to a larger number of customer orders by meeting the time window. But, while satisfying a very short time window, it is not possible for a drone to pick up the packages for multiple customer orders having order placement time close to each other. Therefore, the required number of drones to deliver all customer orders increases as the pickup time window decreases. For instance, the required number of drones (i.e., fleet size) increases by 48% as the time window reduces from 35 minutes to 1 minute.

Therefore, depending on the business and product type, the minimum required drone fleet size can vary. Business owners can use our model on their delivery data to determine the minimum required drone fleet size based on the time window requirements of their business and product types.

#### 4.6Effect of Drone Flight Path on the Delivery Range, Energy Consumption, Fleet Size, and Battery Replacements

In real-life operations of drones, it may not always be possible to fly the drones in a straight path from the business provider's location to customer locations due to the presence of no-fly



Figure 8: Effect of time window on the required number of drones.

zones (e.g., schools, large buildings, and restricted private property) in the flight path. Flying over the road networks is a viable option to avoid these no-fly zones. But, as compared to a straight path, flying over the road networks requires the drones to travel longer distances and consume higher amounts of energy in delivering customer orders. Our hypothesis is that this increased distance and energy consumption affects drone delivery range, as well as the required fleet size (i.e., number of drones) and the number of battery replacements. Therefore, using our drone deployment optimization model, we evaluated the impact of drone flight path (i.e., straight vs. over the road networks) on the delivery range, minimum number of drones and battery replacements needed.

To incorporate the road network flight path of the drones in our optimization model, we used the Open Source Routing Machine (OSRM) API [43] to obtain the road distance traveled and the number of turns a drone makes to change direction while traveling to each customer location. Based on our DJI Matrice 600 Pro drone flight test, we consider that a drone hovers 7 seconds on average to change direction (including the time for deceleration and acceleration) while flying over the road networks. Using these road distances and turns, we compute the energy consumed by the DJI Matrice 600 Pro drones and travel times for all customer locations that are used in the optimization model. We used the minimum required battery energy as 324 Kilo-Joule (KJ), which is 15% of the initial battery energy of 2.16 Mega-Joule (MJ) in all the analyses presented in this subsection, where we used a 15 minute pickup time window.

Table 8 shows the number of locations out of delivery range of the DJI Matrice 600 Pro for two different flight paths (i.e., straight and over the road networks), two different speed levels (i.e., 6.71 m/s and 13.41 m/s), and three different package weights (i.e., 1.13 Kg, 2.27 Kg, and 4.54 Kg). We see that within the same package weight and speed level, a larger number of customer locations are out of the drone delivery range as the drones fly over the road networks as compared to the straight path. This is because the drones consume substantially higher energy while flying over the road networks. Therefore, given the battery energy limitation, it is not possible for the drones to safely deliver packages and return to the depot for a larger number of locations. Compared to 13.41 m/s, flying over the road networks at the slower speed (i.e., 6.71 m/s) substantially limits the drone delivery range. For instance, 82 of the 126 locations fall outside the delivery range when drones fly over the road networks at 6.71 m/s speed. Therefore, in the remaining analysis in this subsection, we excluded these 82 locations from the delivery data to compare the results for both speed levels and flight paths.

Drone Speed	Flight Path	Number of Locations Outside Delivery Range				
(m/s)	r ngnt 1 atn	m = 1.13	m = 2.27	m = 4.54		
		$\mathbf{K}\mathbf{g}$	$\mathbf{K}\mathbf{g}$	Kg		
12 /1	Straight	0	0	10		
13.41	Over Road	15	02	27		
	Network	10	20	51		
6 71	Straight	27	29	45		
0.71	Over Road	40	57	00		
	Network	49	07	04		

Table 8: Effect of flight path on delivery range. m denotes the package weight.

Figures 9a and 9b demonstrate the effect of flight path and package weight on the required fleet size (i.e., required number of drones) to deliver packages to all customer locations with drone speeds of 13.41 m/s and 6.71 m/s, respectively. We see that a larger number of drones are needed as the drones fly over the road networks as compared to the straight path at both speed levels. This is because, as compared to the straight path, while flying over the road networks, drones travel much longer distances to deliver packages to customer locations, increasing the travel time. With this increased travel time over the road networks for each delivery, it is not possible to meet the pickup time window with the same number of drones as in flying in the straight path with shorter distance and travel time. Therefore, a larger number of drones are needed to deliver the packages meeting the time window requirement while flying over the road networks. When the DJI Matrice 600 Pro drones are flying over the road networks at 13.41 m/s speed, the percentage increase in the required number of drones across the three different package weights are 22.2%, 22.2%, and 33.3% as compared to flying in the straight path. For the 6.71 m/s drone speed, the percentage increase in the required number of drones are 40.0%, 27.3%, and 25.0% as compared to flying in the straight path corresponding to the three different package weights. However, it is evident from Figures 9a and 9b that the package weight does not have much noticeable impact on the number of drones as the package weight does not affect drone speed and travel time.

Figures 10a and 10b demonstrate the effect of flight path and package weight on the total energy consumption in delivering all customer orders at the drone speeds of 13.41 m/s and 6.71 m/s, respectively. We see that the total energy consumption increases substantially as the drones fly over the road networks as compared to flying in a straight path at both speed levels across all three package weights. This is because flying over the road networks requires the drones to travel a longer distance and stay in the air for a longer amount of time, resulting in an increased energy consumption. We have observed that the total energy consumption increases by 72.22%, 71.24%, and 70.54% corresponding to the package weights of 1.13 Kg, 2.27 Kg, and



,

m/s

Figure 9: Effect of flight path and package weight on the required number of drones.

4.54 Kg, respectively, as the drones fly over the road networks than in the straight paths at 13.41 m/s speed. The percentage increase in the total energy consumption due to flying over the road networks at 6.71 m/s speed are 64.85%, 64.14%, and 64.87% across three different package weights. The average energy consumption per delivery also demonstrate the same trend and magnitude (see Figure C.2 in Appendix C). It is evident from Figures 10a and 10b that the energy consumption increases as the drones carry larger package weight at both speed levels, which is very intuitive.



(a) Total energy consumption for drone speed of 13.41 m/s
 (b) Total energy consumption for drone speed of 6.71 m/s
 Figure 10: Effect of flight path and package weight on total energy consumption.

Figures 11a and 11b demonstrate that the required number of battery replacements increases substantially as the drones fly over the road networks as compared to a straight path for both speed levels. For instance, the required number of battery replacements increases by 200% as the drones fly over the road networks compared to flying in a straight path at 13.41 m/s speed and all customer orders weigh 1.13 Kg. This is due to the increased energy consumption while flying over the road networks as explained earlier. As more energy is consumed in delivering each customer order, the minimum required battery energy is reached more frequently, resulting in a larger number of battery replacements.



(a) Required number of battery replacements for drone (b) Required number of battery replacements for drone speed of 13.41 m/s.

Figure 11: Effect of flight path and package weight on the required number of battery replacements.

### 4.7 Effect of Mixed Drone Fleet on Energy Consumption and Required Number of Drones

We observed that due to its small size and limited battery capacity, the delivery range and package weight carrying capacity of the Tarot 650 drone (rotary quadcopter) is much smaller compared to the DJI Matrice 600 Pro (rotary hexacopter). But our drone flight test data shows that the Tarot 650 drone is more energy-efficient than the DJI Matrice 600 Pro drone while carrying the same package weight for the same distance. Therefore, our assumption is that business owners can substantially reduce energy consumption by using a mixed fleet of drones consisting of these both types of drones such that the Tarot 650 drones are used to deliver smaller packages to shorter distances whereas larger packages are delivered longer distances using the DJI Matrice 600 Pro drones.

Using the modeling approach presented in Section 3.2, we evaluated the effect of using both Tarot and DJI drones in a mixed fleet on the number of locations served, energy consumption, and the required number of drones of each type. As the maximum weight carrying capacity of the Tarot 650 drone is 1.13 Kg, we used the package weight of 1.13 Kg for both types of drones in the analysis. Table 9 demonstrates that 113 of the 126 locations are served using the Tarot drones, whereas only 13 locations are served using DJI drones when all drones are operated at 13.41 m/s speed. We see that the Tarot drones contribute 61.95% to the total energy consumption in delivering packages to 113 locations, whereas the DJI drones contribute 38.05% despite delivering packages to only 13 locations. DJI drones are only used to deliver packages to locations outside the delivery range of Tarot. We see a similar pattern in the number of locations served at 6.71 m/s speed, as shown in Table 9, which also demonstrates the optimal number of drones required for each type of drone in the mixed fleet.

We analyzed how much does total energy consumption decreased due to using a mixed fleet of drones compared to using a homogeneous fleet with only DJI drones. Figure 12 demonstrates the total energy consumption by the mixed fleet of drones and the homogeneous fleet with only

Drone	DJI Matrice 600 Pro				Tarot 650	
Speed	Number	% of Total	Required	Number	% of Total	Required
(m/s)	$\mathbf{of}$	Energy	Numbers	of	Energy	Numbers
	Locations	Consump-	of Dronos	Locations	Congump	of Dropos
	Locations	Consump-	of Diones	LUCations	Consump-	of Drones
	Served	tion	of Diolles	Served	tion	of Drones
13.41	Served 13	tion 38.05	5	Served 113	tion 61.95	30 30

Table 9: Number of locations served, percentage of total energy consumption, and the required number of drones for different drone types in a mixed fleet.



Figure 12: Comparison of total energy consumption between different fleet types.

DJI drones when all drones are operated at 13.41 m/s speed. We see that using a mixed fleet with both Tarot and DJI drones substantially reduces the energy consumption in delivering customer orders compared to the homogeneous fleet with only DJI drones. For instance, when the drones are operated at 13.41 m/s speed, using a mixed fleet of drones reduces the total energy consumption by 48.52% compared to the homogeneous fleet with only DJI drones.

### 5 Conclusion

We studied a drone deployment optimization problem for direct delivery of goods from a retail business location that acts as the central depot to customer locations, where each drone visits a single customer location on each trip and returns to the depot before visiting the next customer. In this problem, the goal of the business owner is to optimally route the drones that minimizes the total energy consumption, the required fleet size (i.e., required number of drones), and the required number of battery replacements in delivering customer orders maintaining a specified pickup time window. We proposed a new mathematical optimization approach to solve the problem for both homogeneous and mixed fleets of drones. The mathematical model incorporates the specified time window, factors affecting the drone energy consumption, and the drone operating parameters (e.g., drone speed, package weight, flight path, the minimum required battery energy, and fleet type) and optimally decides the routing of drones so that the minimum number of drones are used, the number of times drone battery is replaced is minimum and the total energy consumption is minimum in delivering customer orders. We also proposed two valid inequalities to improve the computational efficiency of the mathematical optimization models.

We conducted numerical experiments using real drone flight test data to provide new insights into the effect of different drone operating conditions on the performance of drone-based delivery. Results demonstrate that the total and average energy consumption increases as the drones fly at a slower speed due to staying in the air for a longer time. For instance, the total energy consumption for DJI drones (i.e., rotary hexacopter) increases by 47.96% as the drone speed reduces from 13.41 m/s to 6.71 m/s when all customer orders weigh 1.13 Kg. Energy consumption increases substantially as the drones fly over the road network as compared to a straight path; the total energy consumption for DJI drones increases by 72.22% as the drones fly over the road networks compared to the straight path with all customers weighing 1.13 Kg. Drone energy consumption also increases with package weight and package dropping delivery method that requires a longer hover duration. Results demonstrate that using a mixed fleet of drones (i.e., a fleet containing both rotary hexacopters and quadcopters) reduces the total energy consumption by 48.52% compared to the homogeneous fleet with only hexacopter drones when all drones are operated at 13.41 m/s speed. The delivery range of drones decreases as the package weight increases, drone speed decreases, and the minimum required battery energy increases.

The required fleet size increases as the pickup time window of the customer orders decreases, as a higher number of drones are needed to pick up the products within a shorter time window. The number of drones required increases by 48% as the time window reduces from 35 minutes to 1 minute. The required number of drones increases as the drone speed decreases, as a higher number of drones are required to maintain the same pickup time window when the drones are flying at a slower speed. A higher number of drones are needed when the drones fly over the road networks compared to flying in a straight path; the required number of drones increases by 22.2% as the drones fly over the road networks as compared to flying in a straight path.

The required number of battery replacements increases as the package weight and minimum required battery energy increases and speed decreases. As the drones fly over the road networks, the drone battery needs to be replaced a substantially larger number of times as compared to flying in a straight path. This is mainly because of the higher energy consumption due to traveling long distances over the road network. The required number of battery replacements increases by 200% as the drones fly over the road network compared to flying in a straight path when all customer orders weigh 1.13 Kg and drones fly at 13.41 m/s speed. Therefore, business owners need to have a substantially larger number of additional drone batteries when their drones need to be flown over the road networks as compared to flying in a straight path.

The managerial insights drawn from the numerical results based on real drone flight tests and delivery data will help retail business owners better understand the potential of drones under different conditions. Another practical implication of our research is that retail business owners can use our proposed optimization method to make investment and operating decisions in using their drones to deliver customer orders. Specifically, a retail business owner can use our optimization method with their drone energy profile and delivery data to decide on the minimum required fleet size (i.e., the required number of drones) and the number of drones in each type for a mixed fleet under different conditions (e.g., time window requirement, flight path, drone speed). The business owners can compute the number of additional batteries they need to have to operate the drone fleet depending on their drone operating conditions. Additionally, business owners can evaluate how different drone operating parameters specific to their business and products affect the total energy consumption.

### Acknowledgments

We thank the U.S. Department of Energy Vehicle Technology Office (VTO) for funding and supporting this work. This work is supported by the U.S. Department of Energy under Department of Energy Idaho Operations Office Contract No. DE-AC07-05ID14517.

### References

- Chun Cheng, Yossiri Adulyasak, and Louis-Martin Rousseau. Drone routing with energy function: Formulation and exact algorithm. *Transportation Research Part B: Methodologi*cal, 139:364–387, 2020.
- [2] Monica Gentili, Pitu B Mirchandani, Alessandro Agnetis, and Zabih Ghelichi. Locating platforms and scheduling a fleet of drones for emergency delivery of perishable items. *Computers & Industrial Engineering*, 168:108057, 2022.
- [3] Joseph YJ Chow. Dynamic uav-based traffic monitoring under uncertainty as a stochastic arc-inventory routing policy. International Journal of Transportation Science and Technology, 5(3):167–185, 2016.
- [4] Chase C Murray and Amanda G Chu. The flying sidekick traveling salesman problem: Optimization of drone-assisted parcel delivery. *Transportation Research Part C: Emerging Technologies*, 54:86–109, 2015.
- [5] Roger Clarke. Understanding the drone epidemic. Computer Law & Security Review, 30(3):230-246, 2014.
- [6] New York Times. 1.5 Million Packages a Day: The Internet Brings Chaos to N.Y. Streets, 2019. Accessed 7/21/2019.
- [7] Accenture. Faster, saferand greener. https://storage.googleapis.com/wing-staticus/us/DallasFebruary 2021.
- [8] McKinsey and Company. Parcel Delivery: The future of last mile, 2019. Accessed 7/21/2019.
- [9] Amazon.com Inc. Amazon prime air prepares for drone deliveries. https://www.aboutamazon.com/news/transportation/amazon-prime-air-prepares-fordrone-deliveries, June 2022.
- [10] Daniela Rojas Viloria, Elyn L Solano-Charris, Andrés Muñoz-Villamizar, and Jairo R Montoya-Torres. Unmanned aerial vehicles/drones in vehicle routing problems: a literature review. International Transactions in Operational Research, 28(4):1626–1657, 2021.
- [11] Giusy Macrina, Luigi Di Puglia Pugliese, Francesca Guerriero, and Gilbert Laporte. Drone-

aided routing: A literature review. *Transportation Research Part C: Emerging Technologies*, 120:102762, 2020.

- [12] Nils Boysen, Stefan Fedtke, and Stefan Schwerdfeger. Last-mile delivery concepts: a survey from an operational research perspective. OR Spectrum, 43(1):1–58, 2021.
- [13] Alena Otto, Niels Agatz, James Campbell, Bruce Golden, and Erwin Pesch. Optimization approaches for civil applications of unmanned aerial vehicles (uavs) or aerial drones: A survey. *Networks*, 72(4):411–458, 2018.
- [14] Walton Pereira Coutinho, Maria Battarra, and Jörg Fliege. The unmanned aerial vehicle routing and trajectory optimisation problem, a taxonomic review. *Computers & Industrial Engineering*, 120:116–128, 2018.
- [15] Sung Hoon Chung, Bhawesh Sah, and Jinkun Lee. Optimization for drone and drone-truck combined operations: A review of the state of the art and future directions. *Computers & Operations Research*, 123:105004, 2020.
- [16] Emmanouil N Barmpounakis, Eleni I Vlahogianni, and John C Golias. Unmanned aerial aircraft systems for transportation engineering: Current practice and future challenges. International Journal of Transportation Science and Technology, 5(3):111–122, 2016.
- [17] Stefan Poikonen, Xingyin Wang, and Bruce Golden. The vehicle routing problem with drones: Extended models and connections. *Networks*, 70(1):34–43, 2017.
- [18] Xingyin Wang, Stefan Poikonen, and Bruce Golden. The vehicle routing problem with drones: several worst-case results. *Optimization Letters*, 11(4):679–697, 2017.
- [19] Neil Mathew, Stephen L Smith, and Steven L Waslander. Planning paths for package delivery in heterogeneous multirobot teams. *IEEE Transactions on Automation Science* and Engineering, 12(4):1298–1308, 2015.
- [20] Pratap Tokekar, Joshua Vander Hook, David Mulla, and Volkan Isler. Sensor planning for a symbiotic uav and ugv system for precision agriculture. *IEEE Transactions on Robotics*, 32(6):1498–1511, 2016.
- [21] Luigi Di Puglia Pugliese and Francesca Guerriero. Last-mile deliveries by using drones and classical vehicles. In A. Sforza and C. Sterle, editors, *International Conference on Optimization and Decision Science*, volume 217, pages 557–565, 2017.
- [22] Andy M Ham. Integrated scheduling of m-truck, m-drone, and m-depot constrained by timewindow, drop-pickup, and m-visit using constraint programming. *Transportation Research Part C: Emerging Technologies*, 91:1–14, 2018.
- [23] Chase C Murray and Ritwik Raj. The multiple flying sidekicks traveling salesman problem: Parcel delivery with multiple drones. *Transportation Research Part C: Emerging Technolo-gies*, 110:368–398, 2020.
- [24] Patchara Kitjacharoenchai, Mario Ventresca, Mohammad Moshref-Javadi, Seokcheon Lee, Jose MA Tanchoco, and Patrick A Brunese. Multiple traveling salesman problem with drones: Mathematical model and heuristic approach. *Computers & Industrial Engineering*, 129:14–30, 2019.
- [25] Andreas Heimfarth, Manuel Ostermeier, and Alexander Hübner. A mixed truck and robot delivery approach for the daily supply of customers. *European Journal of Operational Research*, In Press, 2022.

- [26] Hailong Huang, Andrey V Savkin, and Chao Huang. Round trip routing for energy-efficient drone delivery based on a public transportation network. *IEEE Transactions on Transportation Electrification*, 6(3):1368–1376, 2020.
- [27] Ho Young Jeong, Byung Duk Song, and Seokcheon Lee. Truck-drone hybrid delivery routing: Payload-energy dependency and no-fly zones. International Journal of Production Economics, 214:220–233, 2019.
- [28] Vivek Yadav and Anand Narasimhamurthy. A heuristics based approach for optimizing delivery schedule of an unmanned aerial vehicle (drone) based delivery system. In 2017 Ninth International Conference on Advances in Pattern Recognition (ICAPR), pages 1–6. IEEE, 2017.
- [29] Khin Thida San, Eun Young Lee, and Yoon Seok Chang. The delivery assignment solution for swarms of uave dealing with multi-dimensional chromosome representation of genetic algorithm. In 2016 IEEE 7th Annual Ubiquitous Computing, Electronics & Mobile Communication Conference (UEMCON), pages 1–7. IEEE, 2016.
- [30] Byung Duk Song, Kyungsu Park, and Jonghoe Kim. Persistent uav delivery logistics: Milp formulation and efficient heuristic. Computers & Industrial Engineering, 120:418–428, 2018.
- [31] Kevin Dorling, Jordan Heinrichs, Geoffrey G Messier, and Sebastian Magierowski. Vehicle routing problems for drone delivery. *IEEE Transactions on Systems, Man, and Cybernetics:* Systems, 47(1):70–85, 2016.
- [32] Boualem Rabta, Christian Wankmüller, and Gerald Reiner. A drone fleet model for last-mile distribution in disaster relief operations. *International Journal of Disaster Risk Reduction*, 28:107–112, 2018.
- [33] Asma Troudi, Sid-Ali Addouche, Sofiene Dellagi, and Abderrahman El Mhamedi. Sizing of the drone delivery fleet considering energy autonomy. *Sustainability*, 10(9):3344, 2018.
- [34] Fanhui Kong, Jianqiang Li, Bin Jiang, Huihui Wang, and Houbing Song. Trajectory optimization for drone logistics delivery via attention-based pointer network. *IEEE Transactions* on Intelligent Transportation Systems, pages 1 – 13, 2022.
- [35] Youngmin Choi and Paul M Schonfeld. Optimization of multi-package drone deliveries considering battery capacity. In Proceedings of the 96th Annual Meeting of the Transportation Research Board, Washington, DC, USA, pages 8–12, 2017.
- [36] Bruno N Coelho, Vitor N Coelho, Igor M Coelho, Luiz S Ochi, Roozbeh Haghnazar, Demetrius Zuidema, Milton SF Lima, and Adilson R da Costa. A multi-objective green uav routing problem. Computers & Operations Research, 88:306–315, 2017.
- [37] Wen-Chyuan Chiang, Yuyu Li, Jennifer Shang, and Timothy L Urban. Impact of drone delivery on sustainability and cost: Realizing the uav potential through vehicle routing optimization. Applied Energy, 242:1164–1175, 2019.
- [38] Miguel A Figliozzi. Lifecycle modeling and assessment of unmanned aerial vehicles (drones) co2e emissions. Transportation Research Part D: Transport and Environment, 57:251–261, 2017.
- [39] Darshan Chauhan, Avinash Unnikrishnan, and Miguel Figliozzi. Maximum coverage capacitated facility location problem with range constrained drones. *Transportation Research Part C: Emerging Technologies*, 99:1–18, 2019.

- [40] Angelo Trotta, Marco Di Felice, Federico Montori, Kaushik R Chowdhury, and Luciano Bononi. Joint coverage, connectivity, and charging strategies for distributed uav networks. *IEEE Transactions on Robotics*, 34(4):883–900, 2018.
- [41] Maria Gabriela S Furtado, Pedro Munari, and Reinaldo Morabito. Pickup and delivery problem with time windows: a new compact two-index formulation. Operations Research Letters, 45(4):334–341, 2017.
- [42] IBM. Ilog cplex optimization studio. http://www.ibm.com/software/commerce/optimization/cplexoptimizer/, December 2019.
- [43] Vaclav Dekanovsky. Driving distance between two or more places in python. https://towardsdatascience.com/driving-distance-between-two-or-more-places-in-python-89779d691def, December 2020.

# Appendices

## A Flowchart of the Mixed Fleet of Drones Modeling

Figure A.1 demonstrates the two-phase modeling approach proposed to solve the drone deployment optimization problem for a mixed fleet of drones.



Figure A.1: Two-phase modeling approach for mixed fleet of drones.

### **B** Energy Consumption and Flight Time Data

Table B.1 presents the average power consumption data for different flight segments of our DJI Matrice 600 Pro drone at two different speed levels and four different package weights.

Drone Speed	Package	Average Power (Joule per Second) in Flight Segments				
(m/s)	Weight (Kg)	Ascend	Descend	Forward	Hover	
				$\mathbf{Flight}$		
13.41	0	1351.4456	1023.8680	1186.5048	1039.2542	
	1.13	1487.3006	1104.4719	1479.2276	1211.6308	
	2.27	1746.2067	1422.7263	1718.7145	1406.6182	
	4.54	2233.5910	1738.2538	2044.0478	1759.3900	
6.71	0	1351.4456	1023.8680	1052.5789	1039.2542	
	1.13	1487.3006	1104.4719	1232.8998	1211.6308	
	2.27	1746.2067	1422.7263	1401.8190	1406.6182	
	4.54	2233.5910	1738.2538	1878.1490	1759.3900	

Table B.1: Power consumption of the DJI Matrice 600 Pro drone for the flight segments.

Table B.2 presents the flight time of different flight segments of our DJI Matrice 600 Pro drone test at two different speed levels. Flight durations are the same for different package weights at the same speed level.

Table B.3 presents the average power consumption data for different flight segments of our Tarot 650 drone test at two different speed levels and two different package weights.

Table B.4 presents the flight time of different flight segments of our Tarot 650 drone test at two different speed levels. Flight durations are the same for different package weights at the same speed level.

### C Effect of Drone Flight Path on Average Energy Consumption

Figures C.2a and C.2b demonstrate the effect of flight path and package weight on the average energy consumption per delivery of the DJI Matrice 600 Pro drone at drone speeds of 13.41 m/s and 6.71 m/s, respectively. The average energy consumption increases by 72.22%, 71.25%, and 70.54% corresponding to the package weights of 1.13 Kg, 2.27 Kg, and 4.54 Kg, respectively, as the drones fly over the road networks than the straight paths at 13.41 m/s speed. The percentage increase in the average energy consumption due to flying over the road networks at 6.71 m/s speed are 64.48%, 64.13%, and 64.87% across three different package weights.

$egin{array}{c} { m Drone Speed} & - \ ({ m m/s}) \end{array}$	Duration (Seconds) of Flight Segments				
	Ascend	Descend	Forward Flight		Hovor
			Time/mile	Time/kilor	leter
13.41	24.6	41.80	125.0	78.125	5.0
6.71	24.6	41.80	245.0	153.125	5.0

Table B.2: Flight time of the DJI Matrice 600 Pro drone for the flight segments.

Drone Speed	Package	Package Average Power (Joule per Second) in Flight Se					
(m/s)	Weight $(Kg)$	Ascend	Descend	Forward	Hover		
				$\mathbf{Flight}$			
13.41	0	419.9395	370.3456	389.3249	369.2475		
	1.13	638.3887	589.3817	596.6649	564.6385		
6.71	0	419.9395	370.3456	381.6552	369.2475		
	1.13	638.3887	589.3817	580.4716	564.6385		

Table B.3: Power consumption of the Tarot 650 drone for the flight segments.

Table B.4: Flight time of the Tarot 650 drone for the flight segments.

$\begin{array}{c} \textbf{Drone Speed} \\ \textbf{(m/s)} \end{array}$	Duration (Seconds) of Flight Segments				
	Ascend	Descend	Forward Flight		Hovor
			Time/mile	Time/kilor	neter
13.41	32.56	38.31	130.0	80.78	5.0
6.71	32.56	38.31	250.0	155.34	5.0



(a) Average energy consumption for drone speed of 13.41 (b) Average energy consumption for drone speed of 6.71 m/s.

Figure C.2: Effect of flight path and package weight on the average energy consumption per delivery.