

MonoByte: A Pool of Monolingual Byte-level Language Models

Hugo Abonizio

FEEC, UNICAMP, Brazil

NeuralMind, Brazil

hugo.abonizio@gmail.com

Leandro Rodrigues de Souza

FEEC, UNICAMP, Brazil

l231250@g.unicamp.br

Roberto Lotufo

FEEC, UNICAMP, Brazil

NeuralMind, Brazil

lotufo@unicamp.br

Rodrigo Nogueira

FEEC, UNICAMP, Brazil

NeuralMind, Brazil

rfn@unicamp.br

Abstract

The zero-shot cross-lingual ability of models pretrained on multilingual and even monolingual corpora has spurred many hypotheses to explain this intriguing empirical result. However, due to the costs of pretraining, most research uses public models whose pretraining methodology, such as the choice of tokenization, corpus size, and computational budget, might differ drastically. When researchers pre-train their own models, they often do so under a constrained budget, and the resulting models might underperform significantly compared to SOTA models. These experimental differences led to various inconsistent conclusions about the nature of the cross-lingual ability of these models. To help further research on the topic, we released 10 monolingual byte-level models¹ rigorously pretrained under the same configuration with a large compute budget (equivalent to 420 days on a V100) and corpora that are 4 times larger than the original BERT’s. Because they are tokenizer-free, the problem of unseen token embeddings is eliminated, thus allowing researchers to try a wider range of cross-lingual experiments in languages with different scripts. Additionally, we release two models pretrained on non-natural language texts that can be used in sanity-check experiments. Experiments on QA and NLI tasks show that our monolingual models achieve competitive performance to the multilingual one, and hence can be served to strengthen our understanding of cross-lingual transferability in language models.

1 Introduction

Shortly after the publication of BERT (Devlin et al., 2019), researchers showed that multilingual models

pretrained on the masked language modeling objective can achieve remarkable zero-shot cross-lingual performance on various NLP tasks (i.e., a multilingual model finetuned on a high-resource language and directly evaluated in other languages) (Conneau et al., 2019; Hu et al., 2020).

These empirical results triggered a wave of research that aimed to explain this behavior. Pires et al. (2019) raised the “anchor tokens” hypothesis, i.e., that tokens shared between two languages act as a reference point so models can learn similar concepts. Artetxe et al. (2020) and Conneau et al. (2020) questioned these findings and pointed out that, even without a shared vocabulary, models achieve great cross-lingual transfer performance by leveraging shared parameters only.

Perhaps even more surprising is the performance of *monolingual* models in a cross-lingual setting. For instance, models pretrained and finetuned only on English can perform well in French tasks (Oladipo et al., 2022). de Souza et al. (2021) also show that monolingual models finetuned on a foreign language (i.e., a language that differs from pretraining) achieve comparable results to models finetuned on their language.

Recent work investigates properties of the pretraining corpora that contribute to the model’s performance on natural language tasks. Models are pretrained on non-natural language corpora, such as code, music, proteins, and artificial languages and their performances are compared with natural language models (Papadimitriou and Jurafsky, 2020; Chiang and yi Lee, 2020; Lu et al., 2021; Ri and Tsuruoka, 2022). Evidence shows that pretraining on a corpus that contains artificial recursive or hierarchical structure between tokens results in a similar performance when compared to models

¹<https://huggingface.co/monobyte>

pretrained on a natural language.

However, an outstanding problem is that these experiments are made either 1) using models pretrained by different research groups, whose pre-training configuration differs widely, or 2) using models pretrained under a compute budget or pre-training corpus that are orders of magnitude smaller than the ones used by SOTA models. For instance, [Chiang and yi Lee \(2020\)](#) pretrain their models on a dataset 200 times smaller than BERT’s. This is problematic because certain skills are learned only when corpus size and training budget are large enough ([Zhang et al., 2020](#)).

These differences in the pretraining methodology and undertrained models make it difficult to draw a conclusion about the nature of the cross-lingual ability of such models. Additionally, since most models use subword tokenization, it is difficult to experiment with languages that do not have a significant subword vocabulary overlap. For example, if a model is pretrained and finetuned on English, it cannot be tested in Chinese because there is very little token overlap in their vocabularies, and hence, Chinese token embeddings are not learned. This is a problem even for languages with the same script. For example, many Spanish embeddings are not learned in an English-only pre-training, and hence it is difficult to tell whether a model’s inability to learn cross-lingual representations is due only to tokenization issues ([Rust et al., 2021](#)).

Following [Bommasani et al. \(2021\)](#), who advocate for the release of pretraining models, corpus, and script as a way to strengthen the field, we release byte-level models pretrained on large corpora from the same domain and using exactly the same training setup and compute budget. Because they rely only on bytes to represent strings, they can be used to compare languages that use different scripts.

Each model takes approximately 210 hours of pretraining, resulting in more than three months of TPU computing. The models are available at <https://huggingface.co/monobyte> and the code used for finetuning can be found at <https://github.com/lersouza/lang-agnostic>.

2 Related work

In the last years, many monolingual versions of BERT ([Devlin et al., 2019](#); [Souza et al., 2020](#); [Chan et al., 2020](#); [Martin et al., 2020](#); [Antoun et al., 2020](#);

[Lee et al., 2021](#); [Nguyen and Tuan Nguyen, 2020](#); [Cañete et al., 2020](#); [Bhattacharjee et al., 2021](#)) and T5 ([Raffel et al., 2020](#); [Carmo et al., 2020](#); [Sarti and Nissim, 2022](#)) have been released. The authors often claim that these versions outperform multilingual models in their languages. [Rust et al. \(2021\)](#) showed that the tokenizer plays a critical role in achieving those results. More recently, [Xue et al. \(2021a\)](#) released the ByT5 model, which would overcome this issue by leveraging a byte-level vocabulary. This model is pretrained on several languages and achieves great results when compared to mT5 ([Xue et al., 2021b](#)). However, no monolingual version of ByT5 has been released, which makes it difficult to conduct further investigation on the model’s pretraining and cross-lingual performance that is not impacted by the tokenization in different languages.

Current research on the properties of pretraining often relies on monolingual models or models pretrained on artificial languages. Researchers often rely on models released by other groups ([de Souza et al., 2021](#)) or pretrain models in a very controlled setup ([Artetxe et al., 2020](#); [Papadimitriou and Jurafsky, 2020](#); [Fujinuma et al., 2022](#)). In both cases, it is not clear if the results suffer from these different methodologies or undertrained models. [Blevins and Zettlemoyer \(2022\)](#), for instance, suggests that language contamination (i.e., a monolingual corpus composed of sentences in more languages) is the reason for monolingual zero-shot effectiveness. The same happens with models pretrained on non-natural language corpora ([Chiang and yi Lee, 2020](#); [Lu et al., 2021](#); [Ri and Tsuruoka, 2022](#)), where the corpus size differs from the ones trained on natural language, which might affect the conclusions drawn from the experiments. We hope to bridge this gap by releasing the set of monolingual models presented in this paper.

3 Pretraining

To train our monolingual models, we used mC4 ([Xue et al., 2021b](#)), the same corpus used to train mT5 and ByT5, which comprises 101 natural languages extracted from the Common Crawl web scrape. For each model, we selected only the documents written in the specific language, which was originally identified using `cl_d3` by [Xue et al. \(2021b\)](#). The mC4 is a large corpus with different language distributions, with some being more represented than others. Thus, we trimmed each pre-

training corpus in approximately 65 billion UTF-8 bytes for all languages. The only exception was Bengali, which was trimmed on 32 billion bytes, corresponding to its total size.

The pretraining was conducted on a TPU VM v3-8 using Flax (Heek et al., 2020) library and the pretraining script for T5-like span-masked language modeling available on HuggingFace Transformers library.² We chose the smaller architecture of ByT5, with 300 million parameters, and used similar hyper-parameters as reported on ByT5 (Xue et al., 2021a) and mT5 (Xue et al., 2021b) papers. We did not experiment with larger models due to their computational cost. We set the sequence length to 1024 tokens (UTF-8 bytes) and train for 1 million steps with a batch of 2^{16} bytes, resulting in approximately 65 billion bytes. Since we could only fit a batch of 8 examples per device, we used gradient accumulation of 128 steps to achieve a larger batch size. The learning rate starts at 10^{-3} and decays linearly throughout the pretraining.

In comparison with the original ByT5, our models are pretrained on a 16 times smaller corpus. However, our pretraining corpus is 4 times larger than BERT’s, which was trained on 3,300M words (Devlin et al., 2019) — i.e., approximately 16 billion characters, considering an average of 5 characters per word in English (Bochkarev et al., 2015). In comparison with GPT-2, our corpus is 1.6 times larger (Radford et al., 2019).

Compared with other monolingual models research, Rust et al. (2021) pretrained on a corpus of approximately 77GB, according to the reported number of steps and tokens per batch. Ri and Tsuruoka (2022) pretrained on a corpus of 1.2GB of artificially generated text. A more extensive comparison to other work is presented in Table 1 and demonstrates that our pretraining is comparable to SOTA monolingual models and much larger than corpora used in the majority of monolingual studies.

To sanity-check and validate the performance of our pretrained models, we compared their results with different baselines proposed in the literature. The first synthetic pretraining strategy, called nesting parentheses, was proposed by Papadimitriou and Jurafsky (2020), which recursively generates random symbols respecting a hierarchical structure. This was proposed to evaluate how this recursion

²https://github.com/huggingface/transformers/blob/main/examples/flax/language-modeling/run_t5_mlm_flax.py

Model name	Language	Size
PTT5 (Carmo et al., 2020)	pt	15
BERT (Devlin et al., 2019)	en	16
BERTimbau (Souza et al., 2020)	pt	17
PhoBERT (Nguyen and Tuan Nguyen, 2020)	vi	20
AraBERT (Antoun et al., 2020)	ar	24
BanglaBERT (Bhattacharjee et al., 2021)	bn	35
KoreALBERT (Lee et al., 2021)	ko	43
North ByT5 (Kummervold, 2022)	no	45
CamemBERT (Martin et al., 2020)	fr	138
IT5 (Sarti and Nissim, 2022)	it	215
Chiang and yi Lee, 2020	en, artificial	0.08
Papadimitriou and Jurafsky, 2020	many, artif.	0.5
Deshpande et al., 2021	many	0.5
Ri and Tsuruoka, 2022	many, artif.	1.2
Rust et al., 2021	many	77
MonoByte (ours, each model)	many	65

Table 1: Comparison of pretraining corpus sizes in GB of monolingual models. Models which does not explicitly report the corpus size were estimated based on the reported amount of tokens.

structure of the pretraining corpus transfers into modeling real languages. Their work showed that the models pretrained on the synthetic hierarchical corpus were able to predict human language far better than other baselines (e.g., random, music, and code), with a perplexity comparable to real languages.

We used the code released by the authors, with the vocabulary being the 50,000 most frequent words based on the first one million documents of the Spanish mC4 corpus, and their sampling probability based on the Zipf distribution over the same Spanish corpus.³ We generated examples until reaching the same size as our natural languages corpora sizes to make a fair comparison.

The second pretraining baseline was proposed by Krishna et al. (2021), dubbed nonsense, where the authors explored the knowledge transfer hypothesis of the downstream performance improvement of transfer learning. The authors pretrained on documents consisting of random n-grams and achieve similar performance on summarization over different datasets when compared to pretraining on real language. We generated examples using the original code⁴ to match the same corpus size of our natural language models.

³<https://github.com/toizzy/tilt-transfer/>

⁴<https://github.com/acmi-lab/pretraining-with-nonsense/>

	de	en	es	pt	ru	vi	zh	avg.
Nonsense	33.33	33.55	33.27	50.00	33.33	33.57	34.19	35.89
Hierarchical	66.01	69.32	68.04	65.65	62.12	64.49	62.83	65.49
Monolingual	70.85	76.76	75.07	83.40	67.39	70.37	69.91	73.39
Multilingual	76.02	80.55	78.39	67.73	73.58	73.01	73.39	74.67
$\Delta(\text{multi} - \text{mono})$	5.16	3.80	3.32	-15.67	6.19	2.64	3.48	1.28

Table 2: Results (accuracy) for Natural Language Inference in each language.

	ar	bn	en	ko	pt	ru	avg.
Nonsense	0.22	0.00	0.45	0.00	0.26	0.27	0.20
Hierarchical	67.23	0.38	28.03	9.99	3.63	32.85	23.68
Monolingual	78.17	53.89	60.15	51.17	64.88	58.26	61.09
Multilingual	81.81	70.28	68.51	54.70	42.37	72.97	65.11
$\Delta(\text{multi} - \text{mono})$	3.65	16.39	8.36	3.54	-22.51	14.71	4.02

Table 3: Results (F1 Score) for Question Answering in each language.

4 Experiments

Our models are evaluated on two downstream tasks: Natural Language Inference (NLI) and Question Answering (QA). We use a similar setting as the *In-language model*, described by Hu et al. (2020), where the model is finetuned and evaluated in the subset of the task that corresponds to its pretraining language. The following subsections provide details about the datasets used and the results. The monolingual models are compared to the ByT5 Small checkpoint. The latter is expected to perform better since it is pretrained on a much larger set of a more diverse corpus, as investigated by Fujinuma et al. (2022). For additional information on the finetuning procedure, please refer to Appendix A.

Natural Language Inference. The XNLI⁵ dataset (Conneau et al., 2018) is used for finetuning and evaluating our German, English, Spanish, Russian, Vietnamese, and Chinese models. For the Portuguese model, we select the Recognizing Textual Entailment (RTE) task of the ASSIN2 dataset (Real et al., 2020). Performance is measured by using the accuracy metric.

Results are reported in Table 2. Compared to the multilingual ByT5, our models achieve competitive performance. The difference in accuracy is about 1.28 on average. The results in Russian represent the largest gap (6.19 points), while those in Vietnamese represent the smallest (2.64 points). Non-

sense achieves a near random performance, while Hierarchical approaches the models pretrained on natural language, as also evidenced by Papadimitriou and Jurafsky (2020) and Chiang and yi Lee (2020).

Question Answering. The gold passage version of the TydiQA (Clark et al., 2020) dataset (**TydiQA-GoldP**) is selected for finetuning and evaluating the Arabic, Bengali, English, Korean and Russian models. For finetuning the Portuguese model, we use the FaQuAD (Sayama et al., 2019). Performance is measured by the F1 Score metric as described by Rajpurkar et al. (2016).

Results are reported in Table 3. For Portuguese, our model outperforms the Multilingual checkpoint by 22.51 points, while, for Bengali, it stays 16.39 points behind. Our monolingual models stay, on average, 4 points behind the multilingual model released by Google. Looking at the difference between monolingual and multilingual models for every language, we see a higher variation. Nonsense and Hierarchical results are very distant. Question answering is a more difficult task (Vania et al., 2021) and a good benchmark for model quality. We hypothesize that this difference in task complexity requires more from the model. Pretraining with token structure emphasis only may not provide the required knowledge for good performance.

5 Conclusion

In this work, we introduced a pool of 10 tokenizer-free language models pretrained on large monolingual corpora. We demonstrated that our monolin-

⁵We use the machine-translated version of XNLI for training in different languages. Available at <https://dl.fbaipublicfiles.com/XNLI/XNLI-MT-1.0.zip>

gual models can achieve competitive results to the multilingual ByT5, although having a smaller and less diverse pretraining — single language, compared to all languages concatenated.

The main goal of our work was to release a set of monolingual models that carefully follow the same pretraining methodology to support the research of monolingual language models, pretraining properties, and cross-linguality. We hope that by releasing our models, we bridge this gap of having a more controlled and reproducible setup for rigorous experiments.

Acknowledgments

This research was partially funded by grants 2020/09753-5 and 2022/01640-2 from Fundação de Amparo à Pesquisa do Estado de São Paulo (FAPESP). We also would like to thank Google Cloud for credits to support this work.

References

- Wissam Antoun, Fady Baly, and Hazem Hajj. 2020. [AraBERT: Transformer-based model for Arabic language understanding](#). In *Proceedings of the 4th Workshop on Open-Source Arabic Corpora and Processing Tools, with a Shared Task on Offensive Language Detection*, pages 9–15, Marseille, France. European Language Resource Association.
- Mikel Artetxe, Sebastian Ruder, and Dani Yogatama. 2020. [On the cross-lingual transferability of monolingual representations](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4623–4637, Online. Association for Computational Linguistics.
- Abhik Bhattacharjee, Tahmid Hasan, Wasi Uddin Ahmad, Kazi Samin, Md Saiful Islam, Anindya Iqbal, M. Sohel Rahman, and Rifat Shahriyar. 2021. [Banglabert: Language model pretraining and benchmarks for low-resource language understanding evaluation in bangla](#).
- Terra Blevins and Luke Zettlemoyer. 2022. [Language contamination explains the cross-lingual capabilities of english pretrained models](#).
- Vladimir V Bochkarev, Anna V Shevlyakova, and Valery D Solovyev. 2015. The average word length dynamics as an indicator of cultural changes in society. *Social Evolution and History*, 14(2):153–175.
- Rishi Bommasani, Drew A. Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S. Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, Erik Brynjolfsson, Shyamal Buch, Dallas Card, Rodrigo Castellon, Niladri S. Chatterji, Annie S. Chen, Kathleen Creel, Jared Quincy Davis, Dorottya Demszky, Chris Donahue, Moussa Doumbouya, Esin Durmus, Stefano Ermon, John Etchemendy, Kawin Ethayarajh, Li Fei-Fei, Chelsea Finn, Trevor Gale, Lauren Gillespie, Karan Goel, Noah D. Goodman, Shelby Grossman, Neel Guha, Tatsunori Hashimoto, Peter Henderson, John Hewitt, Daniel E. Ho, Jenny Hong, Kyle Hsu, Jing Huang, Thomas Icard, Saahil Jain, Dan Jurafsky, Pratyusha Kalluri, Siddharth Karamcheti, Geoff Keeling, Fereshthe Khani, Omar Khattab, Pang Wei Koh, Mark S. Krass, Ranjay Krishna, Rohith Kudipudi, and et al. 2021. [On the opportunities and risks of foundation models](#). *CoRR*, abs/2108.07258.
- Diedre Carmo, Marcos Piau, Israel Campiotti, Rodrigo Nogueira, and Roberto Lotufo. 2020. [Pt5: Pre-training and validating the t5 model on brazilian portuguese data](#).
- José Cañete, Gabriel Chaperon, Rodrigo Fuentes, Jou-Hui Ho, Hojin Kang, and Jorge Pérez. 2020. [Spanish pre-trained bert model and evaluation data](#). In *PMLADC at ICLR 2020*.
- Branden Chan, Stefan Schweter, and Timo Möller. 2020. [German’s next language model](#). In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 6788–6796, Barcelona, Spain (Online). International Committee on Computational Linguistics.
- Cheng-Han Chiang and Hung yi Lee. 2020. [Pre-training a language model without human language](#).
- Jonathan H. Clark, Eunsol Choi, Michael Collins, Dan Garrette, Tom Kwiatkowski, Vitaly Nikolaev, and Jennimaria Palomaki. 2020. Tydi qa: A benchmark for information-seeking question answering in typologically diverse languages. *Transactions of the Association for Computational Linguistics*.
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2019. [Unsupervised cross-lingual representation learning at scale](#). *CoRR*, abs/1911.02116.
- Alexis Conneau, Ruty Rinott, Guillaume Lample, Adina Williams, Samuel R. Bowman, Holger Schwenk, and Veselin Stoyanov. 2018. "XNLI: Evaluating Cross-lingual Sentence Representations". In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics.
- Alexis Conneau, Shijie Wu, Haoran Li, Luke Zettlemoyer, and Veselin Stoyanov. 2020. [Emerging cross-lingual structure in pretrained language models](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 6022–6034, Online. Association for Computational Linguistics.

- Leandro Rodrigues de Souza, Rodrigo Nogueira, and Roberto Lotufo. 2021. [On the ability of monolingual models to learn language-agnostic representations](#).
- Ameet Deshpande, Partha Talukdar, and Karthik Narasimhan. 2021. When is bert multilingual? isolating crucial ingredients for cross-lingual transfer. *arXiv preprint arXiv:2110.14782*.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. [BERT: Pre-training of deep bidirectional transformers for language understanding](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Yoshinari Fujinuma, Jordan Boyd-Graber, and Katharina Kann. 2022. [Match the script, adapt if multilingual: Analyzing the effect of multilingual pretraining on cross-lingual transferability](#).
- Jonathan Heek, Anselm Levskaya, Avital Oliver, Marvin Ritter, Bertrand Rondepierre, Andreas Steiner, and Marc van Zee. 2020. [Flax: A neural network library and ecosystem for JAX](#).
- Junjie Hu, Sebastian Ruder, Aditya Siddhant, Graham Neubig, Orhan Firat, and Melvin Johnson. 2020. XTREME: A Massively Multilingual Multi-task Benchmark for Evaluating Cross-lingual Generalisation. In *International Conference on Machine Learning*, pages 4411–4421. PMLR.
- Kundan Krishna, Jeffrey Bigham, and Zachary C. Lipton. 2021. [Does pretraining for summarization require knowledge transfer?](#) In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 3178–3189, Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Per E Kummervold. 2022. North T5. <https://github.com/peregilk/north-t5>.
- Hyunjae Lee, Jaewoong Yoon, Bonggyu Hwang, Seongho Joe, Seungjai Min, and Youngjune Gwon. 2021. [Korealbert: Pretraining a lite bert model for korean language understanding](#).
- Kevin Lu, Pieter Abbeel, Aditya Grover, Igor Mordatch, and Google Brain. 2021. [Pretrained transformers as universal computation engines](#).
- Louis Martin, Benjamin Muller, Pedro Javier Ortiz Suárez, Yoann Dupont, Laurent Romary, Éric de la Clergerie, Djamel Seddah, and Benoît Sagot. 2020. [CamemBERT: a tasty French language model](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7203–7219, Online. Association for Computational Linguistics.
- Dat Quoc Nguyen and Anh Tuan Nguyen. 2020. [PhoBERT: Pre-trained language models for Vietnamese](#). In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 1037–1042, Online. Association for Computational Linguistics.
- Akintunde Oladipo, Odunayo Ogundepo, Kelechi Ogueji, and Jimmy Lin. 2022. [An exploration of vocabulary size and transfer effects in multilingual language models for african languages](#). In *3rd Workshop on African Natural Language Processing*.
- Isabel Papadimitriou and Dan Jurafsky. 2020. [Learning Music Helps You Read: Using transfer to study linguistic structure in language models](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6829–6839, Online. Association for Computational Linguistics.
- Telmo Pires, Eva Schlinger, and Dan Garrette. 2019. [How multilingual is Multilingual BERT?](#) *ACL 2019 - 57th Annual Meeting of the Association for Computational Linguistics, Proceedings of the Conference*, pages 4996–5001.
- Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. [Exploring the limits of transfer learning with a unified text-to-text transformer](#). *Journal of Machine Learning Research*, 21(140):1–67.
- Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. 2016. [SQuAD: 100,000+ Questions for Machine Comprehension of Text](#).
- Livy Real, Erick Fonseca, and Hugo Gonçalo Oliveira. 2020. The assin 2 shared task: A quick overview. In *Computational Processing of the Portuguese Language*, pages 406–412, Cham. Springer International Publishing.
- Ryokan Ri and Yoshimasa Tsuruoka. 2022. [Pretraining with artificial language: Studying transferable knowledge in language models](#).
- Phillip Rust, Jonas Pfeiffer, Ivan Vulić, Sebastian Ruder, and Iryna Gurevych. 2021. [How good is your tokenizer? on the monolingual performance of multilingual language models](#). In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 3118–3135, Online. Association for Computational Linguistics.
- Gabriele Sarti and Malvina Nissim. 2022. [It5: Large-scale text-to-text pretraining for italian language understanding and generation](#).

- H. F. Sayama, A. V. Araujo, and E. R. Fernandes. 2019. FaQuAD: Reading Comprehension Dataset in the Domain of Brazilian Higher Education. In *2019 8th Brazilian Conference on Intelligent Systems (BRACIS)*, pages 443–448.
- Noam Shazeer and Mitchell Stern. 2018. [Adafactor: Adaptive learning rates with sublinear memory cost](#).
- Fábio Souza, Rodrigo Nogueira, and Roberto Lotufo. 2020. [Bertimbau: Pretrained bert models for brazilian portuguese](#). *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 12319 LNAI:403–417.
- Clara Vania, Phu Mon Htut, William Huang, Dhara Mungra, Richard Yuanzhe Pang, Jason Phang, Haokun Liu, Kyunghyun Cho, and Samuel R. Bowman. 2021. [Comparing test sets with item response theory](#). *ACL-IJCNLP 2021 - 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing, Proceedings of the Conference*, pages 1141–1158.
- Linting Xue, Aditya Barua, Noah Constant, Rami Al-Rfou, Sharan Narang, Mihir Kale, Adam Roberts, and Colin Raffel. 2021a. [Byt5: Towards a token-free future with pre-trained byte-to-byte models](#).
- Linting Xue, Noah Constant, Adam Roberts, Mihir Kale, Rami Al-Rfou, Aditya Siddhant, Aditya Barua, and Colin Raffel. 2021b. [mT5: A massively multilingual pre-trained text-to-text transformer](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 483–498, Online. Association for Computational Linguistics.
- Yian Zhang, Alex Warstadt, Haau-Sing Li, and Samuel R. Bowman. 2020. [When do you need billions of words of pretraining data?](#)

A Finetuning Details

The experiments were carried out in a single NVIDIA A100 80GB GPU. We use the Adafactor optimizer (Shazeer and Stern, 2018) with a constant learning rate of 10^{-4} . The models were finetuned using three different seeds, and we report an average of the results. We have chosen hyperparameters based on preliminary experiments with the ByT5 Small checkpoint⁶ on both XNLI and TydiQA datasets. We do not perform any exhaustive hyperparameter search, and use the same settings (per-task) for all models.

Natural Language Inference. For all NLI experiments, we use a batch size of 16, accumulating gradients for 4 steps. The maximum input length was 1024, trimmed by batch. We train the model to output the class identifier (a number). We train for 10 epochs and evaluate every 0.2 epoch. We also perform early stopping with patience of 5 evaluations and select the best model on the validation set of each task. The results are reported against the test set of each dataset.

Question Answering. For QA, the selected batch size is 6, accumulating gradients for 4 steps. The maximum input length was 2048 (question and context concatenated), trimmed by batch. We train the model to output an answer to the question with a maximum length of 768 bytes. We train for 10 epochs and evaluate at the end of each epoch. We also perform early stopping with patience of 3 and select the best model on the validation set of each task.

⁶Available at: <https://huggingface.co/google/byt5-small>