Transformer-based Text Classification on Unified Bangla Multi-class Emotion Corpus

Md Sakib Ullah Sourav¹ · Huidong Wang¹

Received: date / Accepted: date

Abstract

Because of its importance in studying people's thoughts on various Web 2.0 services, emotion classification (EC) is an important undertaking. Existing research, on the other hand, is mostly focused on the English language, with little work on low-resource languages. Though sentiment analysis, particularly the EC in English, has received a lot of attention in recent years, little study has been done in the context of Bangla, one of the world's most widely spoken languages. We propose a complete set of approaches for identifying and extracting emotions from Bangla texts in this research. We provide Bangla emotion classifier for six classes (anger, disgust, fear, joy, sadness, and surprise) from Bangla words, using transformer-based models which exhibit phenomenal results in recent days especially for high resource languages. The "Unified Bangla Multi-class Emotion Corpus (UBMEC)" is used to assess the performance of our models. UBMEC was created by combining two previously released manually labeled datasets of Bangla comments on 6-emotion classes with fresh manually tagged Bangla comments created by us. The corpus dataset and code we used in this work is publicly available.

Keywords Bangla corpus \cdot Bangla emotion analysis \cdot Text classification \cdot Multi-class emotion classification \cdot Natural language processing.

1 Introduction

A sufficient amount of work has been done by researchers to detect emotion from facial and audio information whereas recognizing emotions from textual data is still a fresh and hot research area. Blogs, Emails, Instant Messages, Chatting, Forums, Reviews, and other Web 2.0 platforms, such as WeChat, Twitter, YouTube, Instagram, and Facebook, have lately emerged as the most essential venues for social communication amongst varied individuals [1, 2]. More individuals are utilizing the internet for worldwide communication, online shopping, sharing their experiences and opinions, remote education, and correspondence on a variety of topics as technology and awareness improve [3-5]. Users are increasingly using social networks (SNs) to interact and express feelings, ideas, opinions, and thoughts, as well as to engage in discussion groups [6]. The invisible nature of the internet has allowed a single user to participate in aggressive SNs speech data, which has made text conversation [7, 8] or, more precisely, emotion classification (EC) crucial to understanding people's actions [9-15].

Huidong Wang huidong.wang@ia.ac.cn

¹ School of Management Science and Engineering, Shandong University of Finance and Economics, Jinan, China

EC is a subset of sentiment analysis (SC). Text-based SC usually classified into two types: opinionbased and emotion-based. Text polarity, which divides text/sentences into positive, negative, or neutral feelings, is used to classify opinions [18, 19]. EC is a technique for extracting fine-grained emotions from speech/voice, picture, or text data [20]. With an increasing number of people on virtual platforms creating online material at a rapid rate, understanding emotion or sentiment behind a certain activity or trend in online content is of significant value to businesses, consumers, corporate leaders, governments, and other interested parties [16]. Text classification is also important in various human-computer interaction (HCI) applications where text is the primary mode of communication in the SNs indicated above. As interest in EC rises, businesses are keen to run campaigns, attract more customers, fix their problems, and employ successful marketing techniques. Politicians and their political parties are likewise curious about how they come across to the public. EC's focus has shifted to social media data analysis due to the recent increase in SNs. Computational linguistics, machine learning (ML), and deep learning (DL) are usually used nowadays to analyze the feelings or sensations expressed in user-written comments. Classifying emotion detection in text is one of the most challenging tasks in natural language processing (NLP), which involves an understanding of natural language [17].

The fifth most extensively used native language in the world is Bangla. Worldwide, 228 million people speak Bangla as their mother tongue, and another 37 million do so as a second language [21]. Data storage on the web has grown significantly in recent years as a result of the growth of Web 2.0 apps and related services in Bangla. Reviews, opinions, suggestions, ratings, comments, and feedback are just a few examples of the unstructured textual formats in which this data is most commonly presented. The supervised nature of classification techniques means that ML models need to be trained on much larger amounts of labeled data in order to produce usable results. However, there is a lack of high-quality tagged data in many fields. For resource-constrained languages such as Bangla, analyzing these massive volumes of data using NLP to identify underlying sentiment or emotions is a difficult research topic [22, 23]. English and other Western dialects are acknowledged as rich dialects in terms of linguistics and technology. SentiWordNet is one of numerous English-language sentiment lexicons. The intricacy is exacerbated by a number of limitations, including a dearth of tools, a scarcity of benchmark corpora, and learning approaches. In addition, due to the Indo-Aryan language's highly inflected features, which include more than 160 distinct inflected verb forms, 36 different noun forms, and 24 different pronoun forms made EC in Bangla particularly challenging. BNEmo [24] and BEmoC [25] are two Bangla emotion corpuses that include 6327 and 7000 tagged reviews, respectively, and are divided into six groups (anger, disgust, fear, joy, sorrow, and surprise). However, the development of an automated emotion classifier for Bangla literature requires a comparatively larger amount of emotion corpus.

As a result, we thrive to do the EC of Bangla phrases in this study, [26] is the source of motivation of our purposed model. A detailed assessment of transformer-based models for emotion detection in texts utilizing pre-trained Bidirectional Encoder Representations from Transformers (BERT) word embeddings was published in the mentioned study. Transformer-based deep neural network architectural models and variations have recently demonstrated effectiveness in a variety of downstream natural language processing applications, particularly for resource-rich languages like English. Because a few previous research has been done on Bangla EC, we wished to evaluate it using the most effective and reliable way available.

The objective of this research study is to answer the following questions:

• Is it possible to utilize a transformer-based DL model to identify the emotion expressed by a social network user in Bangla?

• Does the DL approach with BERT word embeddings effective than the ML-based approaches to EC for the Bangla language?

The use of pre-trained word embeddings for EC of Bangla language reviews is examined to solve the first study question. Unlike ML-based techniques, Multilingual BERT is a DL model based on pre-trained word embedding that is used to examine semantic links between words. The DL models were compared to Bangla EC's ML-based approaches to answer the second question.

The main contributions of our research are as follows:

- A new, larger, unified 6-class (anger, disgust, fear, joy, sadness, and surprise) EC dataset named Unified Bangla Multi-class Emotion Corpus (UBMEC) has been constructed for Bangla language based on user reviews. It amalgamates two previously published publicly available Bangla emotion corpuses BNEmo [24] and BEmoC [25], as well as with additional manually tagged corpus by us those results in an adequately developed Bangla emotion corpus. It is gathered from various domains such as food, software, entertainments, politics, sports and others.
- Fine-tuning a multilingual variant of BERT (m-BERT) model for Bangla EC that has been trained on 104 languages, including Bangla, and is based on a BERT base with 12 layers, 768 hidden heads, and 110M parameters.
- A set of baseline results of ML models (LR, NB, XGBoost) to create a benchmark for multi-class EC in Bangla.

The remainder of the paper is laid out as follows. The section "Related work" describes EC's related work. The recommended technique is presented in the section "Methodology." The "Results and Discussions" section examines the experimental findings and assessment criteria. The paper's final section is titled "Conclusions."

2 Related Works

2.1 Transformer Models in Text-based Emotion Classification (EC)

Researchers put their efforts in building state of the art transformer models detecting emotions from text in rich resource languages, mostly in English. Huang et al. [27] used an F1 score of 81.5 and 88.5 for the Friends and Emotion-Push datasets, respectively, to examine BERT's emotion identification abilities. There are four emotion classifications in both datasets [28]. They altered BERT and created two models, FriendsBERT and Chat-BERT, for the Friends and EmotionPush datasets, respectively, using various pretraining tasks before the official training procedure. Using a modified BERT model, Huang et al. [29] achieved 0.7709 on four categories (Angry, Sad, Happy, and Others) using Twitter data. Malte and Ratadiya [30] constructed the BERT model on three classes (overtly aggressive, covertly aggressive and non-aggressive) to detect cyber abuse in English and Hindi texts, which received an F1 score of 0.6244 and 0.6596, respectively. Using BERT-large on three datasets: ISEAR, SemEval, and Emobank, Park et al. [31] categorised emotions categorically and predicted the Valence-Arousal-Dominance (VAD) scores of dimensional emotions. For categorically identifying texts in the ISEAR and SemEval data, their model received micro F1 values of 0.688 and 0.695, respectively, and VAD scores of 0.659, 0.327, and 0.287. To identify emotions and propaganda, Vlad et al. [32] presented an ensemble of BERT, bi-LSTM, and Capsule models that received a micro F1 score of 0.5868. Kazameini et al. [33] used BERT word embeddings with bagged SVM to predict author personality attributes. They were 59.03 percent accurate on average.

Subsequently, when it comes to Bangla language using transformer models, there is only a single earlier work based on transformer models till this date. Avishek el at. [43] assessed three transformer models: m-BERT, Bangla-BERT, and XLM-R on their own developed Bangla corpus BEmoC along with several ML and DL models. Among all the models in their work, they got highest weighted F1-score of 69.73%. Tripto et al. [39] performed emotion detection of six classes in their custom made dataset containing 2890 comments from different types YouTube videos in Bangla, English and Romanized Bangla language. Using DL models such as LSTM and CNN and ML models NB and SVM, the best model gives a weighted F1-score of 53.54%.

2.2 Datasets for Text-based Emotion Classification (EC)

There are enormous publicly available large-scale English datasets on various emotion classes from different domains. The EmotionLines dataset [28] consisting of two data subsets (i.e., the Friends and EmotionPush datasets) was released for the challenge; emotions were classified into four labels (i.e., neutral, joy, sadness, and anger to classify emotion from texts in English. Each subset includes1,000 English dialogues. EmoBank [34] is another corpus of 10,000 English sentences balancing multiple genres, annotated with dimensional emotion metadata in the VAD representation format. EmoBank excels with a bi-perspectival and bi-representational design. ISEAR (International Survey on Emotion Antecedents and Reactions) is another widely renowned dataset contains 7,665 sentences. Over a period of many years during the 1990s, a large group of psychologists all over the world collected data in the ISEAR project, directed by Klaus R. Scherer and Harald Wallbott [35]. Student respondents, both psychologists and non-psychologists, were asked to report situations in which they had experienced all of 7 major emotions (joy, fear, anger, sadness, disgust, shame, and guilt). In each case, the questions covered the way they had appraised the situation and how they reacted. The final data set thus contained reports on seven emotions each by close to 3,000 respondents in 37 countries on all 5 continents. SemEval-2017 Task 4 [36] is a dataset contains 1,250 texts obtained from Twitter, news headlines, Google news and other sources that were annotated for Ekman's 6 basic emotions [38]. Saif M. Mohammad and Felipe Bravo-Marquez [37] developed a small dataset named "WASSA-2017 Emotion Intensities (EmoInt)" with 4 emotion classes (fear joy, sadness and anger) which caught much attention to the NLP researchers.

Corpus	Publicly available	Classes	Total data (reviews)
BEmoC [25]	Yes	6	7000
BNEmo [24]	Yes	6	6327
Bangla Youtube Comments [39]	No	6	2890

Table 1. Summary of existing Bangla Emotion Datasets

On the other hand, only two publicly available datasets on Bangla emotion classes has been published so far (Table.1). Ataur Rahman and Hanif Seddiqui [24] presented a manually annotated Bangla emotion corpus named BNEmo which incorporates the diversity of fine-grained emotion labels such as Sadness, Happiness, Disgust, Surprise, Fear and Anger. They collected a large amount of raw text data from the user's comments on two different Facebook groups (Ekattor TV and Airport Magistrates) and from the public post of a popular blogger and activist Dr. Imran H Sarker. A total of 6,327 comments/reviews were annotated into the six categories. Another recent work by Asif Iqbal et al. [25] named BEmoC, they labeled a total of 7,000 Bangla texts into six basic emotion categories from various sources like-

Facebook and YouTube comments/posts, online blog posts, Bangla story books, Bangla novels, text conversations, and newspapers.

We consider EC is as important for Bangla dialects as it is for any other dialect. Hence our focus is to build a BERT-based model that can classify Bangla emotion from texts.

3 Methods

3.1 Model and Architecture

In this section, we present the implementation details of our experimental setup. We fine-tuned m-BERT (Fig.1), BERT-base-multilingual-uncased¹, as this is one of the well-structured backbone especially for low resource languages and there is a lack of such robust monolingual Bangla models and it is the only model that was trained with Bangla language up until performing our experiment. The m-BERT is trained on more than 100 languages with the largest Wikipedia corpus. Embeddings from *BERTbase* have 768 hidden units. The BERT configuration model takes a sequence of words/tokens at a maximum length of 512 and produces an encoded representation of dimensionality 768. When fine-tuned on the downstream sentence classification task, a very few changes are applied to the *BERTbase* configuration. In this architecture, only the [CLS] (classification) token output provided by BERT is used. The [CLS] output is the output of the 12th transformer encoder with a dimensionality of 768. It is given as input to a fully connected neural network, and the Softmax activation function is applied to the neural network to classify the given sentence. Thus, BERT learns to predict whether a sentence can be classified as any of the six emotion classes.



Fig.1. BERT model for emotion classification in Bangla texts.

3.2 Dataset Creation & Preprocessing

We considered two publicly available Bangla corpuses on 6 major emotion classes named BNEmo [24] and BEmoC [25] for our work. We combined these two datasets and external manually annotated addition reviews. We took the reviews from the public YouTube comments on famous Bangla novelist and writer Humayun Ahmed's dramas named "কোখাও কেউ লেই", "বহুৱীহি", "লক্ষত্রের রাত্ত" and comments from BBC

¹ https://github.com/google-research/BERT/blob/master/multilingual.md

Bangla's various Facebook posts on contemporary issues, for instance - war, suicide, hatred, women abuse and similar kinds.

In BNEmo dataset, the six emotion classes were named as- "sad", "happy", "disgust", "surprise", "fear" and "angry". We changed "sad" to "sadness", "happy to "joy" and "angry" to "anger" to keep all the labels similar with BEmoC dataset.

We performed quite a few operations as part of the preprocessing step. For instance, stopwords. Stopwords are used to remove unnecessary words, fostering programs deal with the crucial ones. Plus, we performed duplicate drop function if any review is mistakenly added in more than any review in the above two datasets. After performing such cleaning operations, we finally got 6125 out of 6327 reviews from BNEmo and 6838 out of 7000 reviews from BEmoC (Fig.2). With our manually annotated reviews we constructed the Unified Bangla Multi-class Emotion Corpus (UBMEC) that accumulates a total of 13072 reviews. The data length of UBMEC is 268298 words. The rest of the data are shown in Table.2.



Fig.2. Total number of reviews from different sources in development of UBMEC

Table 2. Description of UBMEC Dataset

UBMEC		
Data length	268298 words	
Data Class	6 (anger, disgust, fear, joy, sadness, and surprise)	
Total Reviews	13072	
Size on disk	1100 KB	
Train-test data split	9150, 3922	
Maximum words in a single review	218	
Minimum words in a single review	6	

The UBMEC dataset consists of 3290 "joy" reviews, 2622 "sadness" reviews, 2422 "anger" reviews, 2049 "disgust" reviews, 1348 "fear" reviews and 1341 "surprise" reviews (Fig.3).



Fig.3. Distribution of 6 classes in UBMEC Dataset.

As mentioned by the authors in [40], the human emotions can be further categorized into just four classes: joy, sadness, fear/surprise, and anger/disgust. As the semantic meaning of a sentence from fear/surprise and anger/disgust are very close to each other. Hence, we split the dataset into 4 classes to see how it results when our model classifies the emotion classes.

After splitting, we got 3290 "joy" reviews, 2622 "sadness" reviews, 4460 "anger/disgust" reviews, and 2687 "fear/surprise" reviews (Fig.4).



Fig.4. Distribution of 4 classes in UBMEC Dataset.

From Table.3 we can see sample annotated reviews in UBMEC dataset for each of six emotion classes in Bangla sentences.

Emotion	Meaning	Text Sample
Class		
Joy	When a writing expresses happy feelings derived from both new and familiar experiences, it is classified as joyful. [41]	এরকম লাটক বারবার দেখেও বিরক্ত লাগে লা, এমল লেখক আর দ্বিতীয় একজন হবে লা, যার লাম হুমায়ুল আহমেদ
Sadness	If a text communicates a response to loss, it falls into the grief category, and feeling sad helps us convince others that we need aid. [41]	সত্যের জয় সবসময় হয় নাহ্! এমন হাজারও বাকের আছে মিথ্যের কারণে চলে যেতো হয়! সত্যি কোখাও কেউ নেই!
Anger	A letter is considered angry if it expresses unjust treatment of us or others. [41]	দেশ যখন মানুষরুপী শুয়োরেরা চালায়।
Disgust	When a text conveys a disappointed sensation about anything bad or unpleasant that occurs physically or psychologically, it falls into the Disgust category. [41]	জনগণের ক্রিটিকাল থিংকিং এবিলিটি প্রয়োজনীয়তার তলানিরও নিচে। আই ওয়াশ আর সার্কাজমে এরা বেশি উৎসাহী।
Fear	When a literature depicts threats or dangers to our safety or existence, it expresses terror. [41]	দেশে হিন্দু মুসলিমদের দাঙ্গা লাগানোর চেষ্টা চলছে।
Surprise	A writing is considered surprising if it describes an unexpected or surprising incident that occurred unexpectedly. [41]	সুইসাইড করাকে জাস্টিফাই করছেল?!

Table 3. Sample annotated reviews in UBMEC dataset

3.3 Model Training and Fine-Tuning

The pre-training of the m-BERT language model took place in the first phase of the complete emotion classification m-BERT model's training, and the fine-tuning of the outermost classification layer took place in the second phase. The Bangla Wikipedia has served as the primary source of pre-training for the m-BERT. The training set of the proposed UBMEC dataset, which consists of labeled user evaluations, was used to fine-tune the m-BERT model. This method has been used to train the fully connected classification layer in particular. Wikipedia items vary in quantity across languages, so data is sampled using an exponentially smoothed weighting (with a factor 0.7). This ensures that high resource languages like English are under-sampled compared to low resource languages. Word counts are also sampled in a similar manner so that low resource languages have sufficient words in the vocabulary. During training, categorical cross-entropy was utilized as the loss function. Table.4 presents the lists of hyper-parameters adopted for this research.

Table.4 m-BERT model hyper-parameters.

Hyper-parameter	Value
Learning rate	2e-5
Batch size	64
Number of epochs	5
Adam epsilon	1e-8
Gradient accumulation steps	1
Hidden size	768
Hidden layers	12
Maximum sequence length	64
Parameters	110 M

4 Results and Discussions

4.1 Result of Machine Learning Models and m-BERT model

Here, we compared the results of m-BERT model with other ML algorithms. First we see the results of Logistic Regression (LR), Naïve Bayes (NB), XGBoost on datasets- BNEmo, BEmoC and on our proposed UBMEC dataset (Fig.5). The train-test split made same in both m-BERT model and ML models. The results of these three dataset using different ML models are given in Table.5 in detailed form. From the table, we get to see that among all ML models, LR gave the best result. In BEmoC dataset, LR gives 47% accuracy. While the UBMEC dataset exhibits 44% accuracy through LR method. Among all the ML models, it is evident that the three datasets along with our proposed one perform consistently. This also validates the correctness of the formation of UBMEC dataset.



Fig.5 Accuracy of Different Machine Learning Models on Three Emotion Corpus.

ML models have fewer trainable parameters on average than deep neural networks, which explains why they learn so rapidly. Instead than using semantic information, these classifiers use the discriminative power of words in respect to their classes to create class margins. Furthermore, LR outperforms all other ML algorithms since it not only deduces maximum margin hyper planes, but it also handles outliers substantially better than other ML algorithms.

On the other hand, DL algorithms are substantially more capable of extracting hidden patterns than ML learning classifiers, not simply because they automate the feature engineering process. Quite often ML algorithms are generally found less successful than DL algorithms in this regard.

Dataset	Models	Accuracy	Weighted F1-score
BNEmo	LR	0.41	0.45
	NB	0.40	0.47
	XGBoost	0.38	0.44
BEmoC	LR	0.47	0.47
	NB	0.44	0.48
	XGBoost	0.41	0.42
	LR	0.44	0.45
UBMEC	NB	0.39	0.44
	XGBoost	0.39	0.42
	m-BERT	0.61	0.7103

Table.5 Six Emotion Class Results using Machine Learning and m-BERT Models

In view of getting a different insight, along with six class EC, we further performed four class (joy, sadness, fear/surprise, and anger/disgust) EC. For this purpose, we splitted the UBMEC dataset into traintest data split of 9141 and 3918. This time we get the data length of UBMEC dataset is 267847 words. Total reviews, (Before cleaning, after cleaning) = (13436, 13059).

Table.6 shows the result on 4 classes EC results in different ML and m-BERT models. The performance metrics indicate the enhancement of results in classifying 4 Bangla emotion classes.

Table.6 Four Emotion Classes Results using Machine Learning and m-BERT Models

Dataset	ML model	Accuracy	Weighted F1-score
UBMEC	LR	0.53	0.55
	NB	0.51	0.56
	XGBoost	0.49	0.53
	m-BERT	0.69	0.76

From the table.5 and 6, it is observable that the m-BERT model performs well in compared to the ML approaches. For six classes Bangla emotion classification it shows a highest weighted f1-score of 71% and that of 76% for four classes. Since the training of m-BERT models take significant amounts of time, we restricted the training to only seven epochs. It is obvious that if we train the model with more epochs it can perform even better. As well as, other approaches can be made. Eor example, [42] is being made to construct monolingual BERT models dedicated for Bangla language by enthusiastic Bangla NLP researchers around the world. Hence, more sophisticated BERT-based text classification models for Bangla EC can be constructed as potential future work of this research that will surely enrich the Bangla NLP research domain.

4.2 Performance Comparison with Previous Models

By assessing the performance in F1-score, we compare the effectiveness of our m-BERT model with the prior techniques [39, 43]. A summary of the comparison is shown in Table.8. The findings demonstrate that proposed m-BERT model performed better than previous approaches classifying six emotion classes in Bangla by obtaining the greatest F1-score (71.03%).

Table.8 Model Performance Comparison

Methods	Weighted F1 (%)
Word2Vec + LSTM [39]	53.54
XLM-R [43]	69.73
m-BERT (proposed)	71.03

As previously indicated, research on applying BERT techniques to evaluate Bangla emotion is limited. In this domain, few papers have been published, all of which mostly employed ML or DL classifiers on a small dataset with constrained domains. Our dataset, on the other hand, comprises more user ratings than previous research and covers numerous genres with six categorization classes: anger, disgust, fear, joy, sadness, and surprise.

5 Conclusions

It appears difficult to determine someone's emotional state from their textual communication. Understanding the text's emotions is crucial for human-computer interaction (HCI). In this work, we employed multilingual-BERT (m-BERT) and pre-trained BERT for emotion categorization for Bangla, a language with limited resources. By comparing the outcomes between two earlier, smaller Bangla emotion datasets and our newly created unified dataset using ML and m-BERT classification models, we were able to verify the high quality of our generated dataset. In comparison to conventional word-based ML techniques, our analysis demonstrated that employing the pre-trained BERT and m-BERT models and fine-tuning it for downstream Bangla emotion text classification tasks produced higher weighted F1-score and accuracy metrics.

Declarations

Funding None.

Conflicts of interest/Competing interests The authors declare that they have no conflicts of interest/ competing interests.

Ethics Approval Not applicable.

Consent to participate Not applicable.

Availability of data The dataset we constructed in this paper is available at <u>https://github.com/Sakibsourav019/UBMEC-Unified-Bangla-Multi-class-Emotion-Corpus-/blob/main/UBMEC%20Corpus_Sakib(updated).xlsx</u>

Code availability The source code is available at <u>https://github.com/Sakibsourav019/UBMEC-Unified-Bangla-Multi-class-Emotion-Corpus-</u>

Authors' contribution MSU Sourav and H. Wang contributed the central idea, analyzed most of the data, and wrote the initial draft of the paper. Both of them contributed to refining the ideas and revised the manuscript. The authors reviewed the results and approved the final version of the manuscript.

References

- 1. Liu, Y. et al. (2019). Identifying social roles using heterogeneous features in online social networks. J. Assoc. Inf. Sci. Technol. 70, 660–674
- 2. Lytos, A., Lagkas, T., Sarigiannidis, P. & Bontcheva, K. (2019). The evolution of argumentation mining: From models to social media and emerging tools. *Inf. Process. Manage*.56, 102055
- 3. Vuong, T., Saastamoinen, M., Jacucci, G. & Ruotsalo, T. (2019). Understanding user behavior in naturalistic information search tasks. *J. Assoc. Inf. Sci. Technol.* 70, 1248–1261
- 4. Amjad, A., Khan, L. & Chang, H.-T. (2021). Effect on speech emotion classification of a feature selection approach using a convolutional neural network. *PeerJ Comput.Sci.* 7, e766
- 5. Amjad, A., Khan, L. & Chang, H.-T. (2021). Semi-natural and spontaneous speech recognition using deep neural networks with hybrid features unification. *Processes* 9, 2286
- Al-Smadi, M., Al-Ayyoub, M., Jararweh, Y. & Qawasmeh, O. (2019). Enhancing aspect-based sentiment analysis of Arabic hotels' reviews using morphological, syntactic and semantic features. *Inf. Process. Manage*. 56, 308–319
- 7. Hassan, S.-U., Safder, I., Akram, A. & Kamiran, F. (2018). A novel machine-learning approach to measuring scientific knowledge flows using citation context analysis. *Scientometrics* 116, 973–996
- 8. Ashraf, M. et al. (2018). A study on usability awareness in local it industry. Int. J. Adv. Comput. Sci. Appl 9, 427-432
- 9. Shardlow, M. et al. (2018). Identification of research hypotheses and new knowledge from scientific literature. *BMC Med. Inform. Decis. Mak.* 18, 1–13
- 10. Tompson, P., Nawaz, R., McNaught, J. & Ananiadou, S. (2017). Enriching news events with meta-knowledge information. *Lang. Resour.Eval.* 51, 409–438
- 11. Mateen, A., Khalid, A., Khan, L., Majeed, S. & Akhtar, T. (2016). Vigorous algorithms to control urban vehicle traffic. In 2016 *IEEE/ACIS 15th International Conference on Computer and Information Science (ICIS)*, 1–5
- 12. Bashir, F., Ashraf, N., Yaqoob, A., Rafiq, A. & Mustafa, R. U. (2019). Human aggressiveness and reactions towards uncertain decisions. *Int. J. Adv. Appl. Sci.* 6, 112–116
- Mustafa, R. U. et al. (2020). A multiclass depression detection in social media based on sentiment analysis. In Latifi, S. (ed.) 17th International Conference on Information Technology–New Generations (ITNG 2020), 659– 662
- 14. Ameer, I., Ashraf, N., Sidorov, G. & Gómez Adorno, H. (2020). Multi-label emotion classification using content-based features in Twitter. *Comput. Sist.* 24, 25
- 15. Ashraf, N. et al. (2022). Youtube based religious hate speech and extremism detection dataset with machine learning baselines. *J. Intell. Fuzzy Syst.* 20:1–9
- Luo, Z., Huang, S. & Zhu, K. Q. (2019). Knowledge empowered prominent aspect extraction from product reviews. *Inf. Process. Manage.* 56, 408–423
- 17. Anusha, Vajrapu, and Banda Sandhya. (2015). "A learning based emotion classifier with semantic text processing." *In Advances in intelligent informatics, Springer, Cham*, 371-382
- Hossain E, Sharif O, Hoque MM, Sarker IH. (2020). Sentilstm: a deep learning approach for sentiment analysis of restaurant reviews. *In: hybrid intelligent systems: 20th international conference on hybrid intelligent systems* (HIS 2020), springer nature, 1375:193–203
- 19. Liu B, et al. (2010). Sentiment analysis and subjectivity. Handb Nat Lang Process. 2010;2 627-66

- Garg K, Lobiyal DK. (2020). Hindi emotionnet: a scalable emotion lexicon for sentiment classification of Hindi text. ACM Trans Asian Low-Resour Lang Inf Process. 19(4):1–35
- 21. Bangla language. 202. https:// en.wikipedia.org/ wiki/Bangla_language. Accessed 2 Mar 2022.
- Das A, Iqbal MA, Sharif O, Hoque MM. (2021). Bemod: development of Bangla emotion dataset for classifying expressions of emotion in texts. In: Vasant P, Zelinka I, Weber GW, editors. *Intelligent computing and optimization. Cham: Springer International Publishing*, 1124–36
- 23. Al-Ayyoub, M., Khamaiseh, A. A., Jararweh, Y. & Al-Kabi, M. N. (2019). A comprehensive survey of Arabic sentiment analysis. *Inf. Process. Manage*. 56, 320–342
- 24. Rahman, Md Ataur; Seddiqui, Md. Hanif, (2020). "BanglaEmotion: A Benchmark Dataset for Bangla Textual Emotion Analysis", *Mendeley Data*, V1, doi: 10.17632/24xd7w7dhp.1
- Iqbal, M.A., Das, A., Sharif, O. et al. (2022). BEmoC: A Corpus for Identifying Emotion in Bangla Texts. SN COMPUT. SCI. 3, 135 https://doi.org/10.1007/s42979-022-01028-w
- Acheampong, Francisca Adoma, Henry Nunoo-Mensah, and Wenyu Chen. (2021). "Transformer models for text-based emotion detection: a review of BERT-based approaches." *Artificial Intelligence Review* 54.8, 5789-5829,
- 27. Y.-H. Huang, S.-R. Lee, M.-Y. Ma, Y.-H. Chen, Y.-W. Yu, and Y.-S. Chen, (2019). "Emotionx-idea: Emotion BERT-an affectional model for conversation," arXiv preprint arXiv:1908.06264, p. 6,
- S. Y. Chen, C. C. Hsu, C. C. Kuo, K. Huang, and L. W. Ku, (2019). "Emotionlines: An emotion corpus of multi-party conversations," in 11th International Conference on Language Resources and Evaluation, LREC 2018, 1597–1601, European Language Resources Association (ELRA),
- 29. C. Huang, A. Trabelsi, and O. R. Zaiane, (2019). "Ana at semeval-2019 task 3: Contextual emotion detection in conversations through hierarchical lstms and BERT," *in Proceedings of the 13th International Workshop on Semantic Evaluation*, 49–53,
- A. Malte and P. Ratadiya, (2019). "Multilingual cyber abuse detection using advanced trans- former architecture," in TENCON 2019-2019 IEEE Region 10 Conference (TEN-CON), 784–789
- S. Park, J. Kim, J. Jeon, H. Park, and A. Oh, (2019). "Toward dimensional emotion detection from categorical emotion annotations," arXiv preprint arXiv: 1911.02499, 11
- 32. G.-A. Vlad, M.-A. Tanase, C. Onose, and D.-C. Cercel, (2019). "Sentence-level propaganda detection in news articles with transfer learning and BERT-bilstm-capsule model," in Proceedings of the Second Workshop on Natural Language Processing for Internet Freedom: Censorship, Disinformation, and Propaganda, 148–154
- 33. A. Kazameini, S. Fatehi, Y. Mehta, S. Eetemadi, and E. Cambria, (2020). "Personality trait detection using bagged svm over BERT word embedding ensembles," arXiv preprint arXiv:2010.01309, p. 4
- Buechel, Sven, and Udo Hahn. (2017). "Readers vs. writers vs. texts: Coping with different perspectives of text understanding in emotion annotation." In Proceedings of the 11th Linguistic Annotation Workshop, 1-12.
- 35. Scherer, K.R. and Wallbott, H.G., (1994). Evidence for universality and cultural variation of differential emotion response patterning. *Journal of personality and social psychology*, 66(2), 310.
- Rosenthal, Sara, Noura Farra, and Preslav Nakov. (2019). "SemEval-2017 task 4: Sentiment analysis in Twitter." arXiv preprint arXiv:1912.00741
- Mohammad, Saif M., and Felipe Bravo-Marquez. (2017). "WASSA-2017 shared task on emotion intensity." arXiv preprint arXiv:1708.03700
- Ekman P. (1972). Universal and cultural differences in facial expression of emotion. *Nebraska Symp Motiv*. 19:207–84
- N. Irtiza Tripto and M. Eunus Ali, (2018). "Detecting Multilabel Sentiment and Emotions from Bangla YouTube Comments," 2018 International Conference on Bangla Speech and Language Processing (ICBSLP), 1-6, (2018) doi: 10.1109/ICBSLP.2018.8554875
- 40. R. E. Jack, O. G. Garrod, and P. G. Schyns, (2014). "Dynamic facial expressions of emotion transmit an evolving hierarchy of signals over time," *Current biology*, vol. 24, no. 2, 187–192
- 41. Ekman P. 16 (1999). Basic emotions. Handbook of cog-nition and emotion. 98(45-60):

- 42. Bhattacharjee, Abhik, Tahmid Hasan, Kazi Samin, M. Sohel Rahman, Anindya Iqbal, and Rifat Shahriyar. (2021). "BanglaBERT: Combating embedding barrier for low-resource language understanding." arXiv preprint arXiv:2101.00204
- 43. Das, A., Sharif, O., Hoque, M. M., & Sarker, I. H. (2021). Emotion classification in a resource constrained language using transformer-based approach. *arXiv preprint arXiv:2104.08613*.