Online Matching with Cancellation Costs

Farbod Ekbatani

University of Chicago Booth School of Business, Chicago, IL, fekbatan@chicagobooth.edu

Yiding Feng

Microsoft Research New England, Cambridge, MA, yidingfeng@microsoft.com

Rad Niazadeh

University of Chicago Booth School of Business, Chicago, IL, rad.niazadeh@chicagobooth.edu

Motivated by applications in cloud computing spot markets and selling banner ads on popular websites, we study the online resource allocation problem with overbooking and cancellation costs, also known as the buyback setting. To model this problem, we consider a variation of the classic edge-weighted online matching problem in which the decision maker can reclaim any fraction of an offline resource that is pre-allocated to an earlier online vertex; however, by doing so not only the decision maker loses the previously allocated edge-weight, it also has to pay a non-negative constant factor f of this edge-weight as an extra penalty. Parameterizing the problem by the buyback factor f, our main result is obtaining optimal competitive algorithms for all possible values of f through a novel primal-dual family of algorithms. We establish the optimality of our results by obtaining separate lower-bounds for each of small and large buyback factor regimes, and showing how our primal-dual algorithm exactly matches this lower-bound by appropriately tuning a parameter as a function of f. Interestingly, our result shows a phase transition: for small buyback regime $(f < \frac{e-2}{2})$ the optimal competitive ratio is $\frac{e}{e-(1+f)}$, and for large buyback regime $(f \ge \frac{e-2}{2})$, the competitive ratio is $-W_{-1}\left(\frac{-1}{e(1+f)}\right)$. We further study the lower and upper bounds on the competitive ratio in variants of this model, such as matching with deterministic integral allocations or single-resource with different demand sizes. For deterministic integral matching, our results again show a phase transition: for small buyback regime $(f < \frac{1}{3})$, the optimal competitive ratio is $\frac{2}{1-f}$, and for the large buyback regime $(f \ge \frac{1}{3})$, the competitive ratio is $1 + 2f + 2\sqrt{f(1+f)}$. We show how algorithms in our unifying family of primal-dual algorithms can obtain the exact optimal competitive ratio in all of these variants — which, in turn, demonstrates the power of our algorithmic framework for online resource allocations with costly cancellations.

Key words: online resource allocation, overbooking, buyback problem, callable resources, online matching, primal-dual analysis

1. Introduction

Revenue management strategies play a pivotal role in driving profitability and ensuring optimal resource utilization. One such strategy that has garnered significant attention is overbooking, a prevalent practice in classic applications such as airline seat reservations (Rothstein, 1971) and hotel booking (Liberman and Yechiali, 1978) where businesses intentionally accept more reservations or orders than their available capacity as customers arrive. By doing so, businesses can hedge against early commitments to low-paying customers by denying service after allocation, and also mitigate losses from no-shows and cancellations, ultimately leading to increased revenue.

To address customer satisfaction upon service denial, one approach is to implement a *buyback* contract. This contract allows the platform to reclaim any pre-allocated resource from a customer during the allocation horizon, but only after providing full refund of the original fee along with an additional compensation fee, often determined by a simple function of the original payment. With the advent of modern online marketplaces, this paradigm has found intriguing applications. An example is assigning servers to arriving jobs in cloud computing spot markets (e.g., AWS EC2 spot instances), where the platform can recall servers after a full refund and an extra fee paid to the owner of the revoked job.¹ Similarly, for negotiated yearly contracts selling banner advertisements on popular websites (e.g., displayed ads on Microsoft Network), the platform must make online admission and costly revocation decisions as advertisers with heterogeneous willingness-to-pay arrive over the ad campaign horizon.² Adopting the buyback strategy enables such platforms to effectively manage overbooking, and optimize resource allocation in dynamic market environments.

Motivated by the above paradigm, we investigate the problem of online resource allocations with buyback. Existing work has mainly focused on single-resource scenarios (Gallego et al., 2008; Babaioff et al., 2009), but modern applications involve richer environments with multiple resources of different types (e.g., servers with varying computational power). The objective is to find a matching between demand and supply. We model this as an edge-weighted online bipartite matching problem, where online nodes arrive sequentially and reveal their edge-weights to the offline side (Karp et al., 1990; Feldman et al., 2009). The decision maker must determine how to match each arriving online node to offline nodes (with capacity constraints) either fractionally or integrally. The decision maker is allowed to allocate more than the capacity to an offline node, but should revoke the overbooked allocations by paying a buyback cost. We consider a simple linear model where the buyback cost is a non-negative constant f times the pre-allocated reward.³

¹ For more details on this application, see AWS's website.

² For more details on this application, see MSN's display ad website.

³ The modeling choice of the fixed linear compensation scheme is partially motivated by applications in which buyback contracts cannot be personalized and should have simple and interpretable forms. More complicated compensation schemes are still interesting to be studied, but are not captured by our simple model.

The decision maker's goal is to maximize the total weight of the matching minus the buyback cost at the end. Our focus is on developing robust online algorithms to handle non-stationary demand arrivals, motivated in part by relevant applications. Building on the seminal work of Karp et al. (1990) in the computer science literature and Ball and Queyranne (2009) in the revenue management literature, we adopt a framework that considers adversarial arrival for the online nodes. Parameterizing the problem by the *buyback factor* f, we measure the performance of our online algorithms by their competitive ratio, which is the worst-case ratio of the objective of an omniscient offline benchmark to that of the algorithm. We then ask the following research questions:

(i) Can we design simple (fractional) online algorithms for the above problem to achieve the optimal competitive ratio for <u>all the parameter choices</u> of the buyback factor f? (ii) What if we restrict our attention to the simpler class of deterministic integral online algorithms?

Our main contributions. We answer both of the above questions in affirmative by hitting two birds with one stone: we design and analyze a unifying parametric family of primal-dual online algorithms that are optimal competitive in both settings with fractional allocations and with deterministic integral allocations (after tuning their parameters). We also show by applying randomized rounding techniques any fractional algorithm can be converted into a randomized integral algorithm with almost no loss under large capacities — hence our set of results provide a complete picture for designing optimal competitive online algorithms in the online resource allocation problem with buyback under large capacities. To show these results, our contribution is two-fold:

(i) Lower-bounds in different parameter regimes. We first establish separate lower-bounds of $\Gamma_{gen}(f)$ and $\Gamma_{det-int}(f)$ on the optimal competitive ratios for the general setting and the deterministic integral setting, respectively. These lower-bounds (below) are drawn in Figure 1; here, $W_{-1}: [-1/e, 0) \rightarrow (-\infty, -1]$ is the non-principal branch of the Lambert W function:⁴

$$\Gamma_{\text{gen}}(f) \triangleq \begin{cases} \frac{e}{e-(1+f)} & \text{if } f \leq \frac{e-2}{2} \\ \\ -W_{-1}\left(\frac{-1}{e(1+f)}\right) & \text{if } f \geq \frac{e-2}{2} \end{cases} , \quad \Gamma_{\text{det-int}}(f) \triangleq \begin{cases} \frac{2}{1-f} & \text{if } f \leq \frac{1}{3} \\ \\ 1+2f+2\sqrt{f(1+f)} & \text{if } f \geq \frac{1}{3} \end{cases}$$

To obtain the above lower-bounds, we identify two sources of uncertainty preventing an online algorithm to perform as well as the optimum offline: the *edge-wise uncertainty* and the *weight-wise uncertainty*. Intuitively speaking, the edge-wise uncertainty is related to the multi-resource aspect of our model and captures the information-theoretic difficulty of identifying the right offline node to be matched to an arriving online node given the future uncertainty (hence it is still present even when f = 0). On the contrary, the weight-wise uncertainty is related to the buyback aspect of

⁴ In mathematics, the Lambert W function, also called the omega function or product logarithm, is the converse relation of the function $y(x) = x \cdot e^x$. The non-principal branch $x = W_{-1}(y)$ is the inverse relation when $x \leq -1$.

our model and captures the information-theoretic difficulty of identifying the edge with the largest weight among all edges adjacent to an offline node given the future uncertainty (hence it is still present even in the special case with a single resource). Notably, as f increases, the weight-wise uncertainty starts playing a more important role than the edge-wise uncertainty, and vice versa.

We use novel constructions in our worst-case instances to exploit the trade-off between the above two sources of uncertainty. Interestingly, we observe a phase transition in both fractional and deterministic integral settings in terms of the behavior of the worst-case instance for the competitive ratio: there is the small buyback cost regime where $f < \hat{f}$ and the worst-case instance heavily relies on the multi-resource aspect of the model, and the large buyback cost regime where $f > \hat{f}$ and the worst-case instance heavily relies on the buyback aspect of our model and is indeed *exactly* the same as the worst-case instance of the single-resource environment. The phase transition thresholds are different for the two settings. Specifically, $\hat{f} = \frac{e-2}{2}$ for the general setting and $\hat{f} = \frac{1}{3}$ for the deterministic integral setting. In the large buyback cost regime, our lower-bounds for the general algorithms and deterministic integral algorithms match the bounds in Badanidiyuru and Kleinberg (2009) and Babaioff et al. (2009), respectively, established for the single-resource environment. Moreover, as $f \to 0$ in the extreme case of the small buyback cost regime, the lower-bound $\Gamma_{gen}(f)$ converges to $\frac{e}{e-1}$ and $\Gamma_{det-int}(f)$ converges to 2, which are indeed the worst-case competitive ratios of the edge-weighted online bipartite matching with free-disposal (Karp et al., 1990; Feldman et al., 2009) for general algorithms and deterministic integral algorithms, respectively. This problem is a special case of our model when f = 0.



Figure 1 Competitive ratio as the function of buyback factor f: Black solid (dashed) curve is the optimal competitive ratio $\Gamma_{\text{gen}}(f)$ for the matching environment (single-resource environment). Gray solid (dashed) curve is the optimal competitive ratio $\Gamma_{\text{det-int}}(f)$ of deterministic integral algorithms for the matching environment (single-resource environment). Black solid curve and black dashed curve coincide for buyback factor $f \geq \frac{e-2}{2} \approx 0.359$. Gray solid curve and gray dashed curve coincide for buyback factor $f \geq \frac{1}{3}$.

(ii) Upper-bounds via primal-dual in all parameter regimes. Second, we establish *exact* matching upper-bounds by introducing a novel primal-dual family of online algorithms for this problem. The primal-dual framework has demonstrated its efficacy in designing and analyzing online bipartite allocation algorithms with irrevocable allocations or free cancellations in various contexts.⁵ However, until now, this framework has not been applied to cases where cancellation is costly, and it remained uncertain whether it could be beneficial in such settings.

The main challenge arises from the fact that the optimal offline benchmark does not involve buybacks (incurring no buyback cost). Consequently, the linear program for the optimum offline solution *does not* capture any aspects of the buyback feature in our problem. Prior work on singleresource buyback (Babaioff et al., 2009; Badanidiyuru and Kleinberg, 2009) does not propose systematic approaches to address the problem; instead, they either rely on simple variations of the naive greedy algorithm or adhoc randomized schemes (for rounding weights) to obtain competitive online algorithms. It remains unclear whether any of these adhoc ideas can be extended to the matching environment. This gap in understanding the buyback problem from prior literature makes developing the optimal competitive online algorithm for edge-weighted online matching with costly cancellation/buyback highly challenging.

In a nutshell, our main technical (and conceptual) contribution is bridging the gap in the existing literature by establishing a new connection between the primal-dual framework for online bipartite resource allocation problems and the buyback problem. This newfound understanding allows us to derive optimal competitive algorithms for all the regimes of the buyback parameter f. We begin our investigation by re-visiting the single-resource buyback problem through the systematic lens of the primal-dual framework. Equipped with this systematic approach, we can recover a new optimal competitive online algorithm for the fractional (and integral) single-resource buyback. More interestingly, we show how to naturally extend our primal-dual fractional algorithm to the matching environment to obtain our main result. We also show how natural adaptations of this approach to the integral setting obtain optimal competitive ratios for deterministic integral algorithms.

Our techniques. We summarize our technical findings below. The complete technical story in this paper is elaborate and we refer the reader for the details to Sections 3, 4, and 5.

⁵ Examples of such applications include the well-celebrated online bipartite matching problem with or without vertex weights (Karp et al., 1990; Aggarwal et al., 2011), online budgeted allocation (Adwords) problem (Mehta et al., 2007; Buchbinder et al., 2009), online assortment optimization with or without reusable resources (Golrezaei et al., 2014; Feng et al., 2019; Goyal et al., 2020), and the special case of our problem when f = 0, which is the online edge-weighted bipartite matching with free disposal (Feldman et al., 2009; Devanur et al., 2016).

Single-resource: weight continuum, canonical allocations & lemon juice. For the single-resource environment with only one offline node, inspired by our lower-bound result, we first focus on instances with infinitely many arriving online nodes whose weights form a continuum. A key concept central to the design and analysis of all our algorithms is the notion of allocation distributions. When a new online node arrives, we consider all past (fractional) allocations of this offline node that will not be revoked at the end, effectively capturing the complete state of the allocation for this offline node by recording the distribution of these non-revoked weights.⁶ Interestingly, we have identified natural and concrete invariant properties, namely scale invariance" (defined in Definition 3) and greedily buyback" (defined in Definition 4) in Section 3.1, that should be preserved by the allocation distribution of the optimal competitive online algorithm for the class of continuum weight instances. Leveraging these properties, we precisely characterize a canonical allocation distribution induced by any algorithm satisfying these invariants and demonstrate that it implies the competitive optimality of the resulting algorithm under continuum weight instances.

Furthermore, we show through a reduction that we can treat general instances similar to a continuum of weights by filling the gaps in the arriving weight sequence — roughly speaking the same way that one makes lemon water by mixing lemon juice and water. See more details in Section 3 (and for our reduction see Section 3.3). Finally, to complement our results, we show how to round this algorithm without any loss to an online randomized integral algorithm (see Section EC.4.1 for the details of our lossless online randomized rounding approach).

Primal-dual for matching environment: the general exponential penalty functions. Building on the insights from our previous investigation and its resulting characterization, we propose a family of primal-dual online algorithms. We first introduce our algorithm in the single-resource environment and show it satisfies the above mentioned invariants (almost by construction). We then consider its natural extension to the matching environment and develop a direct primal-dual analysis for its competitive ratio. At a high level, our algorithm maintains a dual assignment β_j for each offline node j, fractionally allocates the arriving online node to the offline node with the maximum edge-weight minus the dual assignment (following the complementary slackness of the LP), and greedily recalls the smallest edge-weight assigned to this offline node by paying the buyback cost. The main remaining algorithmic construct is how dual assignments are updated (and what information is needed for this update).

⁶ When overbooking occurs, it is optimal to perform buybacks from the smallest allocated weight until the capacity is no longer exceeded. Although this buyback process typically takes place at the end, it can be viewed equivalently as an online procedure that continuously performs buybacks from the smallest weight whenever the total allocation surpasses the capacity. As a result, the allocation distribution, could be tracked in an online fashion.

There are two key technical ingredients in the way we update the dual variables. First, we use allocation distributions of each offline node (in particular, their quantile functions). This information helps us to capture an "importance score" (i.e., the dual assignment) for each offline node via their entire state of allocation (and not via any other compressed statistics such as total allocated weight). Second, we use a parametric family of *general exponential penalty functions*:

$$\Psi(y) = \tau \cdot (\lambda^y - 1) ,$$

which are parametric by $\lambda, \tau \geq 0$. Such a penalty function summarizes the allocation (quantile) function of each offline node to a score (after a proper integration; see the exact formula for the dual assignment β_j in our algorithms, i.e., Algorithm 1, Algorithm 3, and Algorithm 4). Intuitively speaking, these functions, with proper choice of their parameters τ and λ as a function of the buyback factor f, enable us to *indirectly* incorporate the history of buybacking cost of each offline node in its importance score. Moreover, although neither buybacking decisions nor their cost appear in the standard linear program for edge-weighted bipartite matching, the properties of the general exponential function enable us to bring buybacking cost into the primal-dual analysis of our algorithms — in our view, this feature has been a major missing technical piece to connect the buyback problem with other online bipartite allocation problems. See more details in Section 4.

Primal-dual for deterministic integral setting: simpler algorithms. Notably, our resulting family of primal-dual algorithms is simple, easy-to-interpret, and optimal competitive, i.e., with competitive ratio equal to $\Gamma_{\text{gen}}(f)$ when its parameters are picked properly. Moreover, for the special case of integral allocations, they have a much simpler form as only the choice of $\Psi(1)$ matters: a naive greedy algorithm matches the arriving online node to the offline node with the maximum edgeweight and is unbounded competitive; however, our resulting integral algorithm discounts each edge-weight by subtracting a fraction $\hat{\tau}(f) \equiv \Psi(1)$ of the buyback weight and then runs greedy. By proper choice of $\hat{\tau}$ as a function of f, the competitive ratio of such an algorithm exactly matches the earlier lower-bound $\Gamma_{\text{det-int}}(f)$ for deterministic integral algorithms. See the details in Section 5.

1.1. Further related work

Single-resource online allocation with buyback. As we mentioned earlier, Babaioff et al. (2009) consider the single resource allocation with costly cancellations, which is a special case of our model. They identify the optimal deterministic integral algorithm and generalize it to matriod environments as well as knapsack environments (with an inflated capacity constraint). In three follow-up works, Badanidiyuru and Kleinberg (2009) identify the optimal randomized algorithm for the single resource setting and then generalize it to the matroid environments; Badandiyuru (2011) identifies the optimal deterministic algorithm for the intersection of general matriod environments;

Han et al. (2014) identify the optimal deterministic algorithm for knapsack environments with identical weights. Constantin et al. (2009) study the online resource allocation with buyback under transversal matroid. They further assume that the online demand requests are strategic and thus focus on incentive compatible, individual rational mechanisms.

Online matching with free disposal. Feldman et al. (2009); Devanur et al. (2016) study the online edge-weighted matching with free disposal (i.e., a special case of of our model with f = 0), and identify the optimal competitive fractional algorithm. Under the same model, Fahrbach et al. (2020) identify a randomized integral algorithm whose competitive ratio beats the naive greedy algorithm. Devanur and Jain (2012) study online matching with concave return. In their model, each offline node does not have a hard capacity constraint, but is associated with a concave function, which maps the total reward collected in this offline node to the utility of this offline node. They identify the optimal competitive fractional algorithm in this model. As a comparison, in our model, the profit of each offline node depends not only the total reward, but also the whole allocation history (which determines the buyback costs). Finally, Buchbinder et al. (2014) study the online submodular maximization with free disposal, which again cannot capture the buyback cost.

Robust revenue management. Our model makes no assumption on the customer sequence arriving in the future (e.g., no need for stochastic knowledge, having identical rewards, etc). Similar adversarial arrival models have been considered in various robust revenue management problems: online booking (e.g., Ball and Queyranne, 2009), assortment (e.g., Golrezaei et al., 2014; Gong et al., 2022), allocation (e.g., Balseiro et al., 2022), and pricing (e.g., Lobel et al., 2018).

Dynamic revenue management with soft inventory constraint. Our work is also conceptually related to dynamic revenue management where the offline supplies have a soft inventory constraint. Examples include dynamic revenue management with cancellation (on the demand side) and overbooking (e.g., Rothstein, 1971; Erdelyi and Topaloglu, 2010; Freund and Zhao, 2021); and also dynamic inventory control problems (e.g., Levi et al., 2007; Mostagir, 2010; Besbes and Muharremoglu, 2013; Qin et al., 2022).

Revenue management with callable products. Motivated by applications in the airline industry, Gallego et al. (2008) introduce the revenue management problem with callable products. They study a two-period model, where low-fare consumers arrive in the first period, and are able to grant the capacity provider an option to "call" the capacity at a prespective recall price; then high-fare consumers arrive in the second period and the capacity provider decides how many callable products to exercise. The authors identify the optimal policy in this model. In two follow-up works, Gallego and Lee (2018) study an extension with multi-fare consumers, and develop heuristic policies; Gallego and Lee (2020) study online assortment with callable products, and characterize the optimal policy for both general choice model as well as multinomial-logit model.

Organization. We start by formalizing the model and providing necessary preliminaries and notations in Section 2. In Section 3 we revisit the single-resource buyback problem and design new primal-dual algorithms which attain the optimal competitive ratio. In Section 4 we generalize the primal-dual algorithms in the single-resource environment to the matching environment and obtain the optimal competitive ratio that matches our lower-bound for all choices of the buyback factor. In Section 5, we identify the optimal competitive deterministic integral algorithm. Finally, we summarize our results and provide a short list of directions for future research in Section 6.

Organization of electronic companion. In Section EC.1, we provide separate worst-case instances establishing our tight competitive ratio lower-bounds for all parameter regimes of the buyback factor f, for both general algorithms and deterministic integral algorithms. In Section EC.2 we provide the omitted proofs from the main body. In Section EC.3 we provide two polynomial-time implementation of our optimal competitive fractional algorithm. In Section EC.4 we provide a collection of subsidiary results by studying the design of (i) optimal competitive randomized integral algorithms for single-resource buyback problem à la Badandiyuru (2011) (Section EC.4.1), (ii) optimal competitive fractional algorithm for single-resource with non-uniform demand and non-uniform supply (Section EC.4.2), and (iii) (asymptotically) optimal competitive integral online matching algorithms under large capacities using randomized rounding (Section EC.4.3). Finally, we provide numerical simulations on synthetic data in Section EC.5, demonstrating improved empirical performance guarantees by our proposed algorithms on practical instances of the online matching problem with costly cancellations.

2. Preliminaries

We study two-sided online allocations with cancellation costs. In this section, we first describe the base model and the decision maker's problem — which we refer to as the *edge-weighted online matching with buyback* — as well as some special cases and variations of our base model. We then formalize the type of performance guarantee we are considering in this paper. We finally detail some basic algorithmic constructs that we heavily use in the rest of the paper.

Base model. An instance of our problem consists of a bipartite graph G = (U, V, E), where V is the set of resources (i.e., supply) indexed by $[n] \equiv 1, ..., n, U$ is the set of requests (i.e., demand) indexed by $[T] \equiv 1, ..., T$, and $E \subseteq U \times V$ is a set of edges denoting the allocation compatibility of each pair (i, j) of requests and resources. Moreover, each edge $(i, j) \in E$ is associated with a non-negative weight w_{ij} — if there is no edge between i and j we define $w_{ij} = 0$, and hence, without loss of generality, we assume $E = U \times V$ throughout the paper. The resources V are available and known to the decision maker upfront, hence referred to as offline nodes. The requests arrive in an online fashion over discrete times 1, ..., T, hence referred to as online nodes. Once an online node *i* arrives, it reveals the edge-weights w_{ij} to every offline node $j \in V$. Given this information, the decision maker should make an online allocation decision to fractionally match *i* (with a total of one unit of demand) to the offline nodes *V*. In contrast to a typical online allocation problem, these allocations are *not* irrevocable, as we explain next.

Each offline node j has a total of one unit of capacity,⁷ meaning that no more than one unit of this resource in total can be considered as allocated to the set of online nodes U at any point during times $1, \ldots, T$. By allocating dx amount of offline node $j \in V$ to online node i upon its arrival, the decision maker collects $w_{ij}dx$ amount of reward. Furthermore, to preserve the capacity constraints, she can also revoke (i.e., buyback) any fraction of an earlier allocation to any previous online node i' < i by paying a linear buyback cost. Specifically, should she decide to buyback dx amount of allocation between offline node $j \in V$ and previous online node i', she will not only lose the reward $w_{i'j}dx$ of this allocation, but she will also pay an extra cost of $f \cdot w_{i'j}dx$ due to buybacks, where $f \geq 0$ is called the buyback factor.⁸ The goal of the decision maker is to run an online algorithm for determining fractional allocations and buybacks at each time, so as to maximize her total profit, i.e., the total reward from non-revoked allocations minus the total costs due to buybacks.

Overbooking with offline buyback. In the base model, the buyback decision is made simultaneously with the allocation decision in a fully online fashion. It is important to note that the base model is equivalent to an alternative model where the decision maker allows overbooking and can postpone the buyback decision to an offline stage, i.e., after the end of the allocation horizon T.

In this alternative offline buyback model, the decision maker handles each online node's arrival by determining its fractional allocation without imposing unit-capacity constraints on the offline side. Subsequently, after all T online nodes have arrived, the decision maker addresses the unit-capacity constraints through the buyback decision. At first glance, this alternative model appears to grant the decision maker greater control. Nevertheless, two models are indeed equivalent. Specifically, given the linear buyback cost structure, the globally optimal strategy (given any sequence of future online nodes) for the decision maker is to perform online buybacks greedily, thereby always revoking allocation with the smallest edge weight.

Single resource buyback problem & extensions. We also consider a special case of our model where there is only a single resource with unit capacity. In this case, we simplify the notation and drop the index j from our notations. Notably, this simple model is introduced and studied for first in Babaioff et al. (2009); Badanidiyuru and Kleinberg (2009). We also consider an extension of this model where each arriving node i has a demand of $d_i \ge 0$ (not necessarily one) and the resource has a capacity of s (not necessarily one).

⁷ As we show later in Appendix EC.4.2, this assumption is indeed without loss of generality for fractional allocations, both in the matching environment and the special case of the single resource environment.

⁸ In the special case when f = 0, our model boils down to online allocations with *free disposal* (Feldman et al., 2009).

Deterministic integral allocation. We mostly focus on the model that allows for fractional allocations and buybacks. Later in Section 5 we also consider the model when allocations and buybacks are forced to be integral and deterministic. It is important to mention that our fractional algorithms can be converted into integral algorithms in the asymptotic regime when capacities are large (with almost no loss in performance);⁹ however, our integral deterministic algorithm and its performance guarantee work even with unit capacities — which is the relevant scenario in some applications.

Performance guarantee. To benchmark the performance of our online algorithms, we compare them with an optimum omniscient algorithm that knows the entire problem instance, referred to as optimum offline. Note that the optimum offline pays zero buyback cost (since buyback is not necessary if the entire instance is known) and essentially picks the maximum edge-weighted matching (or simply the online node with the maximum weight in the special case of single resource). Fixing a buyback factor $f \ge 0$, we then measure the performance of our online algorithms by their competitive ratio, which basically compares the (expected) total profit of the online algorithm with the optimum offline under the worst-case instance for the buyback factor f.

DEFINITION 1 (COMPETITIVE RATIO). Given buyback factor f, an online algorithm ALG is $\Gamma(f)$ -competitive against the optimum offline benchmark within a class of problem instances \mathcal{I} if:

$$\sup_{I \in \mathcal{I}} \; \frac{\mathsf{OPT}(I)}{\mathsf{ALG}(I)} \leq \Gamma(f)$$

where ALG(I) and OPT(I) are the expected total profit of the online algorithm ALG and the total profit of the optimum offline solution, respectively.

Allocation distribution. A crucial construct in the design and analysis of our online algorithms is keeping track of a separate allocation distribution for each offline node $j \in V$. Since each offline node j has a unit capacity for the total allocation, we can consider a probability distribution over different weights for this offline node to capture how the weights of past non-revoked allocations of this offline node are distributed.¹⁰ Note that such a distribution fully captures the "current state" of allocation of its corresponding resource. For each offline node $j \in V$, we define the allocation (probability) density function $x_j : \mathbb{R}_+ \to \mathbb{R}_+$, where $x_j(w)$ denote the density (fraction) of offline node j allocated at edge-weight equal to w in the current matching. We also define allocation quantile function $y_j : \mathbb{R}_+ \to [0, 1]$, where $y_j(w) = \int_w^\infty x_j(t) dt$ is the fraction of offline node j allocated at edge-weights no smaller than w in the current matching.

⁹ This conversion in the large capacity regime is quite straightforward and can be done by using standard independent randomized rounding techniques based on concentration bounds (e.g., see Feng and Niazadeh, 2021). See the details of the randomized rounding in Section EC.4.3.

¹⁰ We initialize the allocation distribution of each offline node by a point-mass distribution at weight zero.

3. Warmup: Optimal Competitive Algorithm for Single Resource

To introduce our technique and pave the path to explain the main result of this paper in Section 4 — which is an optimal competitive online algorithm for the edge-weighted online matching with buyback — we revisit the single-resource buyback problem. Although this is a fairly simple special case of our problem, still obtaining the optimal (or even a constant) competitive online algorithm is highly non-trivial. To see the challenge, consider the following example demonstrating that the naive greedy algorithm's competitive ratio is unbounded.

EXAMPLE 1. Consider the greedy algorithm that (fractionally) allocates the offline resource (and buyback if it is necessary) as long as the immediate profit is nonnegative. Consider an instance with a single offline node, T online nodes and buyback factor f = 1. Each online node $i \in [T]$ has weight $w_i = 2^i$. The total profit of the optimum offline benchmark is 2^T (i.e., allocates the offline node to the last online node T and collects reward 2^T). In contrast, the greedy algorithm allocates the offline node to each online node $i \in [T]$ with reward 2^i (and buybacks from the previous online node i - 1 with cost $2 \cdot 2^{i-1}$ if i > 1). In the end, the total profit of the greedy algorithm is 2. By letting T going to infinity, the competitive ratio of the greedy algorithm becomes unbounded.

The above example illustrates that an online algorithm should handle the trade-off between the immediate collected reward and the potential cost due to the uncertainty of online nodes in the future. As mentioned earlier, Babaioff et al. (2009) study this trade-off and show the optimal competitive ratio that can be achieved by a deterministic integral algorithm in the single-resource buyback problem. Then, the followup work of Badanidiyuru and Kleinberg (2009) show an optimal competitive randomized integral algorithm for this problem (and hence an optimal competitive fractional algorithm); however, their algorithm is quite ad-hoc and it is not clear at all how to extend neither its design nor its performance analysis to the more general matching case.

To fill the above gap, so that we have an algorithm that can be extended to the matching case, we take a completely different approach in this warm up section. We aim to design a systematic framework, based on the primal-dual algorithm design and analysis, to gradually build a fractional optimal competitive algorithm for single resource buyback. Our approach heavily relies on keeping track of the allocation distribution of the single offline node, and trying to maintain a "canonical" form for this distribution. We then show how this objective leads to a primal-dual algorithm that can then be generalized to the matching case in Section 4.

In Section 3.1, we first restrict our attention to a subclass of instances (i.e., truncated weight continuum instances), and identify two natural properties of the allocation distribution of a "good" algorithm for these instances. In Section 3.2, we present a class of primal-dual algorithms which all satisfy the properties identified above. Finally, we discuss how to extend these primal-dual

algorithms to general instances through a reduction in Section 3.3. Throughout this section, we drop subscript j for the single offline node in our notations, e.g., replacing weight w_{ij} with w_i , and allocation density/quantile function x_j , y_j with x, y, respectively.

3.1. Truncated weight continuum and the canonical allocation

In this subsection, with a slight abuse of the model,¹¹ we focus on designing an optimal competitive algorithm within the class of *truncated weight continuum instances* \mathcal{I}_{cont} defined as follows.

DEFINITION 2 (TRUNCATED WEIGHT CONTINUUM INSTANCE). A truncated weight continuum instance I_T parameterized by $T \in \mathbb{R}_+$ contains a single offline node (resource) and a continuum population of online nodes (i.e., U = [0, T]), where each online node $w \in U$ has weight exactly equal to w. We denote the set of all such instances as $\mathcal{I}_{\text{cont}} = \{I_T\}_{T \in \mathbb{R}_+}$.

As a sanity check, the competitive ratio of the naive greedy algorithm (illustrated in Example 1) remains unbounded even within the class of instances \mathcal{I}_{cont} .

Suppose we track the allocation distribution of an optimal competitive online algorithm within the class $\mathcal{I}_{\text{cont}}$. We start our investigation by guessing two natural properties that we expect to be satisfied by the allocation distribution of such an algorithm (or in some sense, by the allocation distribution of any good candidate algorithm for our problem). We show given these invariants, we can exactly characterize the family of allocation density/quantile functions satisfying those.

To explain the first property, we start with the following intuitive observation: from the perspective of any given online algorithm, every truncated weight continuum instance $I_T \in \mathcal{I}_{\text{cont}}$ looks exactly the same before its termination (i.e., the departure of the last online node T), and any truncated weight continuum instance $I_T \in \mathcal{I}_{\text{cont}}$ can be seen as a stretched/compressed version of any other instance $I_{T'} \in \mathcal{I}_{\text{cont}}$ after re-scaling the arrival times (or equivalently the weights) by a factor of $\frac{T}{T'}$. Hence, intuitively speaking, the optimal competitive online algorithm should treat these instances equally after an appropriate re-scaling. As for some extra notation to help with formalizing this intuition, let $y^{(w^{\dagger})}(\cdot)$ denote the allocation quantile function $y(\cdot)$ of an online algorithm after it finishes processing online node w^{\dagger} in a truncated weight continuum instance I_T for any $T > w^{\dagger}$.¹² We then have the following definition.

DEFINITION 3 (SCALE INVARIANCE). An online algorithm satisfies the *Scale Invariance* (SI) property if its allocation quantile function $y(\cdot)$ satisfies the following equality:

$$\forall w^{\dagger}, w \in \mathbb{R}_{+}: \quad y^{(w^{\dagger})}(w) = y^{(1)}\left(\frac{w}{w^{\dagger}}\right) \tag{SI}$$

 $^{^{11}}$ It is clear that each truncated weight continuum instance can be approximated by instances in our base model with arbitrary precision.

¹² Equivalently, notation $y^{(w^{\dagger})}(\cdot)$ can be defined as the allocation quantile function $y(\cdot)$ generated from running the online algorithm on the truncated continuum weight instance $I_{w^{\dagger}} \in \mathcal{I}_{\text{cont}}$.

Note that equality (SI) in Definition 3 follows from the earlier observation regarding the weight re-scaling interpretation of different truncated weight continuum instances: the allocation quantile function $y^{(w^{\dagger})}$ after processing online node w^{\dagger} is a stretched/compressed version of the allocation quantile function $y^{(1)}$ after processing online node 1 by a re-scaling factor of $\frac{w^{\dagger}}{1}$.

The second property echos the simple intuition behind the equivalence between the base model and the alternative model of overbooking with offline buyback (Section 2): whenever an online algorithm requires to buyback a fraction of an offline node, it is optimal (given any sequence of future online nodes) to greedily buyback from a previously allocated online node which has the smallest weight. To formalize this intuition, define $\underline{w}^{(w^{\dagger})} \triangleq \inf\{w \in \mathbb{R}_{+} : y^{(w^{\dagger})}(w) < 1\}$ to be the smallest allocated weight when the online algorithm finishes processing online node w^{\dagger} in a truncated weight continuum instance I_T for any $T > w^{\dagger}$. We then have the following definition.

DEFINITION 4 (GREEDILY BUYBACK). An online algorithm satisfies the *Greedily Buyback (GB)* property if its allocation quantile function $y(\cdot)$ satisfies the following equality:

$$\forall w^{\dagger} \in [\underline{w}^{(1)}, 1], w \in [\underline{w}^{(1)}, w^{\dagger}]: \quad y^{(1)}(w) = y^{(w^{\dagger})}(w) + 1 - y^{(w^{\dagger})}\left(\underline{w}^{(1)}\right) \tag{GB}$$

Again, note that equality (GB) in Definition 4 follows from the other earlier observation regarding buybacking the fraction with the smallest weight: consider the allocations and buybacks happened between arrival of online node $w^{\dagger} \in [\underline{w}^{(1)}, 1]$ and online node 1. First, the definition of $\underline{w}^{(1)}$ implies that the online algorithm has boughtback all allocated fraction with weight smaller than $\underline{w}^{(1)}$ (with a total of $1 - y^{(w^{\dagger})}(\underline{w}^{(1)})$) and reallocated them to new arriving weights between $[w^{\dagger}, 1]$; Second, suppose the online algorithm always greedily buybacks the fraction with the smallest weight; then no allocated fraction with weight between $[\underline{w}^{(1)}, w^{\dagger}]$ has been boughtback during arrival of weights $[w^{\dagger}, 1]$. Combining these two facts, we know that the increment from $y^{(w^{\dagger})}(w)$ to $y^{(1)}(w)$ is exactly equal to $1 - y^{(w^{\dagger})}(\underline{w}^{(1)})$ for every weight $w \in [\underline{w}^{(1)}, w^{\dagger}]$, and thus quality (GB) holds.

Before proceeding further, we define the concept of "canonical allocation", which is the key to obtain our characterization of the allocation density/quantile functions of the optimal algorithm.

DEFINITION 5 (CANONICAL ALLOCATION). The canonical allocation density function $\hat{x} : \mathbb{R}_+ \to \mathbb{R}_+$, parameterized by $\hat{w} \ge 1$, is equal to

$$\hat{x}(w) \triangleq \frac{1}{w} \frac{1}{\log(\hat{w})}$$

for every $w \in \mathbb{R}_+$.

We say an algorithm follows the canonical allocation (parameterized by \hat{w}) if it allocates to each online node $w \in \mathbb{R}$ with density $\hat{x}(w)$. Note that the algorithm has a total of one unit of the offline node to allocate (so always maintains a distribution), and that

$$\int_{\frac{w^{\dagger}}{\hat{w}}}^{w^{\dagger}} \hat{x}(w) dw = 1$$





Figure 2 Canonical allocation: Gray dashed curve is the canonical allocation density, quantile functions $\hat{x}(\cdot)$, $\hat{y}(\cdot)$, respectively, parameterized by \hat{w} . Black solid curve are the allocation density/quantile functions after processing online node w^{\dagger} when following canonical allocation.

for every $w^{\dagger} \in \mathbb{R}_+$. Thus, if an algorithm follows the canonical allocation function in a (truncated) continuum weight instance, its allocation density will be equal to zero outside of the interval $\left[\frac{w^{\dagger}}{\hat{w}}, w^{\dagger}\right]$ when it finishes processing weight w^{\dagger} . See Figure 2(a). As a simple corollary, the allocation quantile function of such an algorithm after it finishes processing w^{\dagger} is equal to $y^{(w^{\dagger})}(w) = \hat{y}\left(\hat{w} \cdot \frac{w}{w^{\dagger}}\right)$ for every $w \in \mathbb{R}_+$, where \hat{y} is defined as (see Figure 2(b)):

$$\hat{y}(w) \triangleq \begin{cases} 1 & w \in [0,1] \\ 1 - \frac{\log(w)}{\log(\hat{w})} & w \in [1,\hat{w}] \\ 0 & w \in [\hat{w},\infty) \end{cases}$$

Now, consider a family of (fractional) online algorithms that satisfy both the scale invariance (Definition 3, SI) and the greedily buyback (Definition 4, GB) properties. Moreover, suppose their allocation quantile functions $y(\cdot)$ always remain continuous in (0,T] for any truncated weight continuum instance $I_T \in \mathcal{I}_{\text{cont}}$. Given these properties, we have the following closed-form characterization based on the canonical allocation function in Proposition 1, part (i). We postpone its

proof to Appendix EC.2.4. Using this characterization, we show how to establish an upper-bound on the competitive ratio within the class \mathcal{I}_{cont} in Proposition 1, part (ii).

PROPOSITION 1. In the single-resource environment, for any online algorithm ALG that satisfies both scale invariance property (SI) and greedily buyback property (GB), there exists $\hat{w} \ge 1$ such that the online algorithm ALG (i) follows canonical allocation parameterized by $\hat{w} \triangleq (\underline{w}^{(1)})^{-1}$; and (ii) achieves competitive ratio $\frac{\hat{w}\log(\hat{w})}{\hat{w}-1-f}$ within the class of truncated weight continuum instances \mathcal{I}_{cont} .

Proof of part (ii). Consider an arbitrary truncated weight continuum instance $I_T \in \mathcal{I}_{\text{cont}}$. Due to part (i) of Proposition 1, online algorithm allocates $\hat{x}(w)$ density of the offline node to each weight $w \in [0, T]$. Furthermore, every weight $w \in [0, T/\hat{w}]$ has been boughtback. Therefore, the total profit of ALG is

$$\mathsf{ALG}(I_T) = \int_0^T w \cdot \hat{x}(w) \, dw - (1+f) \int_0^{\frac{T}{\hat{w}}} w \cdot \hat{x}(w) \, dw = \frac{\hat{w} - 1 - f}{\hat{w} \log(\hat{w})} \cdot T$$

On the other side, the optimum offline benchmark is $OPT(I_T) = T$.

The competitive ratio formula $\frac{\hat{w}\log(\hat{w})}{\hat{w}-1-f}$ in Proposition 1 attains its minimum $\min_{\hat{w}\geq 1} \frac{\hat{w}\log(\hat{w})}{\hat{w}-1-f} = -W_{-1}\left(\frac{-1}{e(1+f)}\right)$ at $\hat{w} = -(1+f)W_{-1}\left(\frac{-1}{e(1+f)}\right)$, which *exactly* matches the lower bound of the competitive ratio for the single-resource environment within *all* problem instances (Theorem EC.3 in Section EC.1.1.2). Interestingly, as we will illustrate out in Section EC.1.1, the lower-bound instance in Theorem EC.3 belongs to the class of truncated weight continuum instances $\mathcal{I}_{\text{cont}}$; thus, following the canonical allocation with parameter $\hat{w} = -(1+f)W_{-1}\left(\frac{-1}{e(1+f)}\right)$ achieves the optimal competitive ratio within the class $\mathcal{I}_{\text{cont}}$ as well.

3.2. A family of optimal primal-dual algorithms under truncated weight continuum Now we exactly pinned down the properties needed to be satisfied by an optimal competitive algorithm for truncated weight continuum instances, namely scale invariance (SI) and greedily buyback (GB). The question left to answer is whether we can also identify a natural family of algorithms satisfying these properties. Ideally, our algorithms should have the possibility of getting extended to the more complicated matching environment.

Online primal-dual algorithm design framework has proved to be quite powerful in designing competitive online algorithms for online bipartite matching and its variants (c.f., Mehta et al., 2013). Inspired by this, we introduce a parametric family of primal-dual algorithms (Algorithm 1). We then show that they satisfy our two properties of the previous subsection for instances in \mathcal{I}_{cont} ; thus, they follow the canonical allocation and by appropriately picking their parameter can achieve the optimal competitive ratio.

The main idea behind the primal-dual algorithm (Algorithm 1) is simple. The algorithm is parameterized by a *penalty scalar* $\tau \geq 1$ and a *penalty function* Ψ which is a weakly increasing mapping from [0,1] to [0,1] satisfying $\Psi(0) = 0$, $\Psi(1) = 1$. Consider the following (trivial) linear program and its dual for the optimum offline of the instance $I_T \in \mathcal{I}_{cont}$:

$$\begin{split} \max & \int_0^T w \cdot x(w) dw \quad \text{s.t.} \quad \min \quad \beta \qquad \text{s.t.} \\ & \int_0^T x(w) dw \leq 1 \qquad \qquad \beta \geq w \ , \ w \in [0,T] \\ & x(w) \geq 0 \ , \qquad w \in [0,T] \qquad \beta \geq 0 \end{split}$$

Our primal-dual algorithm maintains a feasible offline dual assignment β for the above LP throughout. This assignment is coupled with the current allocation quantile function as follows:

$$\beta = \int_0^\infty \tau \cdot \Psi(y(w)) \, dw$$

To maintain the dual feasibility of the assignment β , once a new online node $w \in \mathbb{R}_+$ arrives, the algorithm keeps allocating the offline node continuously to this online node (and greedily buybacks the fraction with the smallest allocated weight) until the dual assignment equals to the weight, i.e., $\beta = w$. Since $\Psi(1) = 1$ and $\tau \ge 1$, this continuous allocation procedure is well-defined (i.e., the stopping condition $\beta = w$ will be satisfied eventually) for truncated weight continuum instances. We formalize this description in Algorithm 1.

Algorithm 1: Primal-dual allocation for truncated weight continuum

input : penalty function Ψ , penalty scalar τ

1 initialize
$$\beta \leftarrow 0$$
, and $\forall w \in \mathbb{R}_+ : x(w) \leftarrow \delta_0(w), y(w) \leftarrow \mathbb{1} \{w = 0\}$

/* $\delta_0(\cdot)$ is the Dirac delta function. */

- **2** for each online node $w \in [0,T]$ do
- 3 | while $\beta < w$ do

4 buyback dx amount from the smallest allocated weight \underline{w} , i.e., $x(\underline{w}) \leftarrow x(\underline{w}) - dx$ /* by definition, $\underline{w} = \inf\{w' \in \mathbb{R}_+ : y(w') < 1\}$ */ 5 allocate dx amount to online node w, i.e., $x(w) \leftarrow x(w) + dx$ 6 update allocation quantile function $y(w) \leftarrow \int_w^\infty x(t) dt$ 7 update $\beta \leftarrow \int_0^\infty \tau \cdot \Psi(y(w)) dw$

PROPOSITION 2. In the single-resource buyback with truncated weight continuum instances \mathcal{I}_{cont} , for any monotone increasing function $\Psi : [0,1] \to [0,1]$ with $\Psi(0) = 0$, $\Psi(1) = 1$ and constant $\tau \ge 1$, Algorithm 1 with penalty function Ψ and penalty scalar τ follows the canonical allocation. *Proof.* By construction, Algorithm 1 satisfies greedily buyback (GB). To see why it satisfies scale invariance (SI) note that:

$$\beta > w \leftrightarrow \int_0^\infty \tau \cdot \Psi\left(y(w)\right) dw > w \leftrightarrow \int_0^\infty \tau \cdot \Psi\left(y\left(\frac{w}{w'}\right)\right) dw > \frac{w}{w'}$$

and hence by stretching the weight continuum instance by a factor of w', the allocation distribution function of Algorithm 1 keeps having the same shape but will be re-scaled by a factor of w'. Given these two properties, invoking Proposition 1 finishes the proof.

Note that given any penalty function Ψ , we can pin down the relation between τ and \hat{w} through the following equation (which is basically the termination condition after online node \hat{w} arrives):

$$\hat{w} = \int_0^\infty \tau \cdot \Psi\left(y^{(\hat{w})}(w)\right) \, dw \; .$$

The above relation can then be simplified as (since the algorithm follows the canonical allocation):

$$\hat{w} = \tau \cdot \left(1 + \int_1^{\hat{w}} \Psi\left(1 - \frac{\log(w)}{\log(\hat{w})}\right) dw\right) .$$

As it can be seen, for any monotone increasing penalty function Ψ satisfying $\Psi(0) = 0$ and $\Psi(1) = 1$, as long as the penalty scalar τ is equal to 1, the parameter \hat{w} of the canonical allocation followed by the Algorithm 1 (with Ψ and τ) is equal to 1; thus the algorithm is degenerated to the greedy algorithm (which ignores the buyback cost). When we fix a penalty function Ψ and increase the penalty scalar τ to be strictly greater than 1, the parameter \hat{w} increases as well. See the following remark for the relation between τ and \hat{w} for the linear and the exponential penalty functions.

REMARK 1. For any $\hat{w} \geq 1$, Algorithm 1 with the linear penalty $\Psi(y) = y$ (resp. exponential penalty $\Psi(y) = \frac{e^y - 1}{e^{-1}}$), and the penalty scalar $\tau = \frac{\hat{w} \log(\hat{w})}{\hat{w} - 1}$ (resp. $\tau = \frac{\hat{w} \log(\hat{w}) - \hat{w}}{\hat{w} - e}$) follows the canonical allocation parameterized by \hat{w} for every truncated weight continuum instance $I_T \in \mathcal{I}_{\text{cont}}$.

3.3. An algorithmic reduction framework for general instances

In this subsection, we present an algorithmic reduction framework (Theorem 1) that converts online algorithms for truncated weight continuum instances to online algorithms for general instances. By combining this framework with our results in Section 3.1 and Section 3.2 for truncated weight continuum instances \mathcal{I}_{cont} , we obtain the optimal fractional competitive algorithm within the entire class of problem instances \mathcal{I} .

THEOREM 1. In the single-resource environment, for any online algorithm ALG with the competitive ratio Γ within the truncated weight continuum instances \mathcal{I}_{cont} , Algorithm 2 (with ALG as input) is valid and has a competitive ratio of Γ within the class of all problem instances \mathcal{I} . Algorithm 2: Reduction from general instances to truncated-weight continuum

input : algorithm ALG for truncated weight continuum instances $\mathcal{I}_{\mathrm{cont}}$

```
1 initialize w_{\max} \leftarrow 0
```

2 for each online node $i \in U$ do

3 if $w_i > w_{\max}$ then

4	for each $w \in (w_{\max}, w_i]$ do
5	present a proxy online node w to ALG
6	if ALG allocates x of offline node to proxy online node w then
7	allocate $\frac{w}{w_i}x$ amount to online node i
8	preserve capacity constraint by greedily buybacking
9	update $w_{\max} \leftarrow w_i$

At a high level, the proof of Theorem 1 relies on the following two-step argument. Firstly, we introduce a variant model (Definition 7) where, in addition to allocation and buyback decisions, the decision maker has the ability to specify a *discounted per-unit price* (which is weakly smaller than the current edge weight) for each allocation. We demonstrate that it is straightforward to convert online algorithms for truncated weight continuum instances in the base model to online algorithms for general instances in the discounted-allocation model. In the second step, we establish an equivalence between the base model and discounted-allocation model for general instances. See the full proof in Appendix A.

3.4. Auxiliary results for single resource

We end this section with three auxiliary results. First, we present a lossless online rounding in the single resource environment, i.e., we show any fractional online algorithm can be converted to a randomized integral online algorithm with the same competitive ratio in this environment. Second, it is interesting to note that by choosing the fractional online algorithm to be the online algorithm that follows the canonical allocation, and by using a slightly different loss-less online randomized rounding scheme, we can recover the direct randomized integral online algorithm that was proposed by Badanidiyuru and Kleinberg (2009) for the single resource buyback problem. See the details for the first two auxiliary results in Appendix EC.4.1. Finally, we consider a simple generalization of the single-resource environment, where demand sizes are non-unitary and the capacity of the offline resource is not necessarily equal to one. By providing a simple reduction, we basically show the optimal competitive ratio in this setting matches that of the single resource buyback environment. See the details in Appendix EC.4.2.

4. Optimal Competitive Primal-Dual Algorithm

In this section, we present the main result of this paper — an optimal competitive online algorithm for the edge-weighted online matching with buyback. Our algorithm (Algorithm 3) is a natural generalization of our primal-dual algorithm for the single-resource environment (Algorithm 1), which was proposed and analyzed before in Section 3.

4.1. Algorithm description

Similar to the primal-dual algorithms in the single-resource environment, Algorithm 3 maintains an offline dual assignment $\beta_j = \int_0^\infty \Psi(y(w)) dw$ for each offline node j. In this section, we change our notation a bit and drop the penalty scalar parameter τ ; instead, we directly consider the penalty function Ψ , which is a weakly increasing mapping from [0,1] to $\mathbb{R}_{\geq 0}$ satisfying $\Psi(0) = 0$, $\Psi(1) \geq 1$. Once a new online node i arrives, the algorithm continuously allocates this online node (with a unit total demand) to offline node j^* with the largest $w_{ij^*} - \beta_{j^*}$ (i.e., $j^* = \arg \max_{j \in V} w_{ij} - \beta_j$), and hence updates only β_{j^*} accordingly, until the unit demand of online node i is exhausted or $w_{ij} - \beta_j$ is negative for every offline node $j \in V$. Note that the choice of j^* changes during this continuous process every time a new offline node j maximizes $w_{ij} - \beta_j$. As before, if needed, the algorithm greedily buybacks the fraction of the offline node j^* with the smallest allocated weight as it continuously allocates.¹³

Algorithm 3: Primal-dual allocation for matching with buyback

input : penalty function Ψ

1 initialize $\beta_i \leftarrow 0$, and $\forall w \in \mathbb{R}_+ : x_i(w) \leftarrow \delta_0(w), y_i(w) \leftarrow \mathbb{1} \{w = 0\}$ for every $j \in V$.

- /* $\delta_0(\cdot)$ is the Dirac delta function. */
- **2** for each online node $i \in U$ do

while capacity of online node *i* is not exhausted and there exists $j \in V$ s.t. $\beta_j < w_{ij}$ do let $j^* \leftarrow \arg \max_{j \in V} w_{ij} - \beta_j$ buyback dx amount of offline node j^* from the smallest allocated weight \underline{w} , i.e., $x_{j^*}(\underline{w}) \leftarrow x_{j^*}(\underline{w}) - dx$ /* by definition, $\underline{w} = \inf\{w' \in \mathbb{R}_+ : y_{j^*}(w') < 1\}$ */ allocate dx amount of offline node j^* to online node *i*, i.e., $x_{j^*}(w_{ij^*}) \leftarrow x_{j^*}(w_{ij^*}) + dx$ update allocation quantile function $y_{j^*}(w) \leftarrow \int_w^\infty x_{j^*}(t) dt$ **a** update $\beta_{j^*} \leftarrow \int_0^\infty \Psi_{j^*}(y(w)) dw$

 $^{^{13}\,\}mathrm{As}$ a sanity check, when there is a single offline node, Algorithm 3 boils down to Algorithm 1.

A few notes are in order regarding running Algorithm 3. First, although this algorithm is described as a continuous allocation procedure (due to the while loop from line 3 to 8), it is straightforward to see that the allocation for each online node eventually terminates by construction. Second, this algorithm can be implemented in polynomial-time. See Section EC.3 for two polynomial-time implementations of this algorithm based on a direct approach and a convexprogramming based approach.

As we saw in Section 3.2, in the single-resource buyback problem any choice of the penalty function $\Psi : [0,1] \rightarrow [0,1]$ would lead to the optimal competitive algorithm as long as Ψ is monotone increasing, $\Psi(0) = 0$, and $\Psi(1) = 1$. On the contrary, there are new challenges in achieving optimal competitive ratio in the matching environment, and therefore the choice of the penalty function plays a critical role. In what follows, we discuss how a particular choice of the penalty function in Algorithm 3 results in the optimal competitive algorithm.

4.2. Optimal Competitive ratio via generalized exponential penalty function

Although our new primal-dual algorithm for the matching environment is a natural generalization of our earlier algorithm for the single-resource, new challenges arise in its analysis — to handle the uncertainty about both future weights across different offline nodes as well as future weights of the same offline node across time.

Recall that in the single-resource environment, we first analyze the competitive ratio of Algorithm 1 within the truncated weight continuum instances $\mathcal{I}_{\text{cont}}$ and then generalize the algorithm as well as its competitive ratio guarantee within general instances through a reduction. Unfortunately, neither the truncated weight continuum instances nor the reduction admit natural extensions to the matching environment. To shed some lights on this difficulty, note that in the single-resource environment, it is sufficient to consider online algorithms which ignore (i.e., allocate nothing to) any online node $i \in U$ whose weight w_{i1} is not the largest among all arrived online nodes so far. This property is crucial for our reduction (see Section 3.3), as it enables us to convert general instances to truncated weight continuum instances after filling the gap between two consecutive arriving weights. In contrast, in the matching environment, if an online algorithm ignores an edge w_{ij} whenever there exists i' < i such that $w_{ij} \leq w_{i'j}$, its competitive ratio can be unbounded.

In the single-resource environment, by restricting our attention to the truncated weight continuum instances, we obtained a clean closed-form characterization of the allocation distribution of the family of our primal-dual algorithms (i.e., the canonical allocation in Definition 5). As a consequence, this characterization enabled us to analyze the competitive ratio in a straightforward fashion. In the matching environment, in order to follow the same proof strategy to analyze the competitive ratio of the primal-dual algorithm with a general penalty function Ψ , a detailed characterization of the allocation quantile function y seems necessary. However, in the matching environment, because of what we mentioned above, this seems intractable.

To bypass these challenges and analyze the competitive ratio directly, in the remaining of this section, we restrict our attention to a subclass of parametric penalty functions — generalized exponential functions. As the main benefits of restricting to this subclass of penalty functions, (i) we are able to analyze the competitive ratio with almost no characterization of allocation quantile function y needed, and (ii) the subclass is rich enough so that the optimal competitive ratio can be achieved by picking the proper parameter choices for our penalty function in this subclass.

DEFINITION 6. Given any $\lambda, \tau \ge 0$, the generalized exponential penalty function $\Psi : [0,1] \to \mathbb{R}_{\ge 0}$ parameterized by (λ, τ) is defined as $\Psi(y) = \tau(\lambda^y - 1)$ for every $y \in [0,1]$.

We summarize the competitive ratio of Algorithm 3 with the generalized exponential penalty function in Theorem 2. At a high-level, the proof of this theorem is a new LP-based primal-dual analysis that, somewhat surprisingly, incorporates the buyback cost *indirectly* into the proof. In fact, buyback cost plays a role in this analysis thanks to properties of the general exponential function — although neither buybacking decisions nor their cost appear in the linear program.

THEOREM 2. For every $\lambda \ge e$ and $\tau \ge \frac{1+f}{\lambda-1}$, Algorithm 3 with generalized exponential penalty function $\Psi(y) = \tau(\lambda^y - 1)$ has competitive ratio at most $\Gamma_{(\lambda,\tau)}(f)$, where

$$\Gamma_{(\lambda,\tau)}(f) \triangleq \max_{w \ge 1+f} \frac{(\tau+1)\log(\lambda)w - \tau\lambda\log(\lambda)}{w - (1+f)}$$

Proof. Consider the linear program of maximum edge-weighted bipartite matching in complete bipartite graph G = (U, V) as the primal linear program, and its dual:

$$\max \sum_{i \in U} \sum_{j \in V} z_{ij} w_{ij} \quad \text{s.t.} \qquad \min \sum_{i \in U} \alpha_i + \sum_{j \in V} \beta_j \quad \text{s.t.} \\ \sum_{j \in V} z_{ij} \leq 1 \qquad i \in U , \qquad \alpha_i + \beta_j \geq w_{ij} \quad i \in U, j \in V , \\ \sum_{i \in U} z_{ij} \leq 1 \qquad j \in V , \qquad \alpha_i \geq 0 \qquad i \in U , \\ z_{ij} \geq 0 \qquad i \in U, j \in V . \qquad \beta_j \geq 0 \qquad j \in V .$$

We construct a dual assignment based on the allocation decision made in Algorithm 3 (denoted by ALG throughout the proof) as follows. First, set $\alpha_i \leftarrow 0$ and $\beta_j \leftarrow 0$ for all $i \in U, j \in V$. Now consider every allocation (and buybacking) decision in ALG. Whenever ALG buybacks dx amount of offline node j from online node i' and then re-allocates this dx amount of offline node j to online node i, update the dual variables as follows:

$$\alpha_i \leftarrow \alpha_i + \log(\lambda) \left(w_{ij} - \beta_j \right) dx$$
 and $\beta_j \leftarrow \beta_j + \left(\int_{w_{i'j}}^{w_{ij}} \psi(y_j(w)) dw \right) dx$,

where $\psi(\cdot)$ is the first-order derivative of penalty function $\Psi(\cdot)$, i.e., $\psi(y) = \frac{\partial}{\partial y}\Psi(y)$, and $y_j(\cdot)$ is the allocation density function of offline node j at that time. By construction, the invariant $\beta_j \equiv \int_0^\infty \Psi(y_j(w)) \, dw$ holds throughout ALG.

The rest of the proof is done in two steps:

[Step i] Checking the feasibility of dual. We first show that the constructed dual assignment is feasible. By construction, whenever ALG allocates dx amount of offline node j to online node i, we know that $w_{ij} - \beta_j \ge 0$. Thus, $\alpha_i \ge 0$ and $\beta_j \ge 0$ for all $i \in U, j \in V$. Next, we show the feasibility of dual constraint $\alpha_i + \beta_j \ge w_{ij}$ by considering two cases.

- Case I ALG does not exhaust the unit capacity of online node i: By construction, after the departure of online node i, $\beta_{j'} \ge w_{ij'}$ for every offline node $j' \in V$. Thus, the dual constraint is satisfied.
- <u>Case II</u> ALG exhausts the unit capacity of online node *i*: By construction, each dx amount is allocated to an offline node j' such that $w_{ij'} - \beta_{j'} \ge w_{ij} - \beta_j$. Thus, the dual variable α_i can be lowerbounded as

$$\alpha_i \ge \int_0^1 \log(\lambda) (w_{ij} - \beta_j^{(i,x)}) dx \ge \log(\lambda) (w_{ij} - \beta_j^{(i,1)}) \ge w_{ij} - \beta_j$$

where $\beta_j^{(i,x)}$ is the value of dual variable β_j after x fraction of online node i is matched with offline nodes, and the last inequality holds since $\lambda \ge e$ and β_j is increasing throughout ALG.

[Step ii] Comparing objective values in primal and dual. Here we show that the total profit of ALG is a $\Gamma_{(\lambda,\tau)}(f)$ -approximation of the objective value of the above dual assignment. To show this, we consider every allocation (and buybacking) decision in ALG and its impact on the total profit as well as the objective value of the dual assignment.

Suppose ALG buybacks dx amount of offline node j from an earlier arrived online node i' and then re-allocates this dx amount to the currently arriving online node i. The change in the profit (i.e., the net change in the primal objective *after* we incorporate buyback cost) is

$$\Delta(\text{Primal}) = (w_{ij} - (1+f)w_{i'j}) \, dx$$

and the change in the dual objective is

$$\begin{split} \Delta(\mathrm{Dual}) &= \left(\log(\lambda) \left(w_{ij} - \int_0^\infty \Psi(y_j(w)) \, dw \right) + \int_{w_{i'j}}^{w_{ij}} \psi(y_j(w)) \, dw \right) dx \\ &\stackrel{(a)}{\leq} \left(\log(\lambda) \left(w_{ij} - \int_0^{w_{i'j}} \Psi(1) \, dw - \int_{w_{i'j}}^{w_{ij}} \Psi(y_j(w)) \, dw \right) + \int_{w_{i'j}}^{w_{ij}} \psi(y_j(w)) \, dw \right) dx \\ &= \left(\log(\lambda) \left(w_{ij} - \tau \left(\lambda - 1 \right) w_{i'j} - \int_{w_{i'j}}^{w_{ij}} \tau \left(\lambda^{y_j(w)} - 1 \right) \, dw \right) + \int_{w_{i'j}}^{w_{ij}} \log(\lambda) \tau \lambda^{y_j(w)} \, dw \right) dx \\ &= (\tau + 1) \log(\lambda) w_{ij} - \tau \lambda \log(\lambda) w_{i'j} \quad , \end{split}$$

where inequality (a) holds by dropping $\int_{w_{ij}}^{\infty} \Psi(y_j(w)) dw$ and the fact that $y_j(w) = 1$ for every $w \le w_{i'j}$. To see why $\Delta(\text{Dual}) \le \Gamma_{(\lambda,\tau)}(f) \cdot \Delta(\text{Primal})$, it remains to argue $w_{ij} \ge (1+f)w_{i'j}$. Note that

$$w_{ij} \ge \int_0^\infty \Psi(y_j(w)) \, dw \ge \int_0^{w_{i'j}} \Psi(y_j(w)) \, dw = \Psi(1) w_{i'j} \ge (1+f) w_{i'j}$$

where the last inequality holds since $\tau \geq \frac{1+f}{\lambda-1}$. By summing $\Delta(\text{Dual})$ and $\Delta(\text{Primal})$ over all allocations and buybacks throughout the horizon, we obtain:

$$\operatorname{total-profit}(\mathtt{ALG}) \triangleq \mathtt{Primal} \geq \frac{1}{\Gamma_{(\lambda,\tau)}(f)} \cdot \mathtt{Dual}$$

Finally, by weak duality of the linear program, $Dual \ge profit(OPT)$, which finishes the proof.

REMARK 2. In the proof of Theorem 2, when we analyze the objective value of the constructed dual assignment, the terms related to allocation quantile function $y(\cdot)$ cancel out due to the specific form of the generalized exponential function $\Psi(y) = \tau(\lambda^y - 1)$.

Given Theorem 2, we are now ready to obtain the optimal competitive algorithm by properly picking the values of (λ, τ) in the generalized exponential function $\Psi(y) = \tau(\lambda^y - 1)$. As we discussed in the introduction, we use two different values for (λ, τ) , depending on the buyback factor f, and show the resulting algorithm obtains the competitive ratio of $\Gamma_{\text{gen}}(f)$ (see Figure 1) in both the small buyback cost regime (i.e., $f \leq \frac{e-2}{2}$) and the large buyback cost regime (i.e., $f \geq \frac{e-2}{2}$). Later in Section EC.1.1 we provide tight lower-bound instances matching this upper-bound, proving that Algorithm 3 with proper choices of its parameter is optimal competitive for all parameters f.

COROLLARY 1 (Optimal competitive ratio in the small buyback cost regime). For every buyback factor $f \leq \frac{e-2}{2}$, Algorithm 3 with the generalized exponential penalty function $\Psi(y) = \frac{1+f}{e-(1+f)}(e^y - 1)$ has competitive ratio at most $\frac{e}{e-(1+f)}$.

Proof. Let $\lambda = e$ and $\tau = \frac{1+f}{e^{-(1+f)}}$. By construction, $\tau \ge \frac{1+f}{\lambda-1}$. Invoking Theorem 2, the competitive ratio is at most

$$\max_{w \ge 1+f} \frac{(\tau+1)\log(\lambda)w - \tau\lambda\log(\lambda)}{w - (1+f)} = \max_{w \ge 1+f} \frac{\left(\frac{1+f}{e^{-(1+f)}} + 1\right)w - \frac{1+f}{e^{-(1+f)}}e}{w - (1+f)}$$
$$= \max_{w \ge 1+f} \frac{\frac{e}{e^{-(1+f)}}w - \frac{e}{e^{-(1+f)}}(1+f)}{w - (1+f)}$$
$$= \frac{e}{e - (1+f)} ,$$

as desired.

COROLLARY 2 (Optimal competitive ratio in the large buyback cost regime.). For every buyback factor $f \ge \frac{e-2}{2}$, let $\hat{w} = -(1+f)W_{-1}\left(\frac{-1}{e(1+f)}\right)$, Algorithm 3 with the generalized exponential penalty function $\Psi(y) = \frac{1}{\log(\hat{w})}(\hat{w}^y - 1)$ has competitive ratio at most $-W_{-1}\left(\frac{-1}{e(1+f)}\right)$.

Proof. By definition, we have $1 + f = \frac{\hat{w}}{\log(\hat{w})+1}$. Let $\lambda = \hat{w}$ and $\tau = \frac{1}{\log(\hat{w})}$. By construction $\tau > \frac{1+f}{\lambda-1}$ and $\lambda \ge e$ for every $f \ge \frac{e-2}{2}$. Invoking Theorem 2, the competitive ratio is at most

$$\begin{split} \max_{w \ge 1+f} \frac{(\tau+1)\log(\lambda)w - \tau\lambda\log(\lambda)}{w - (1+f)} &= \max_{w \ge 1+f} \frac{\left(\frac{1}{\log(\hat{w})} + 1\right)\log(\hat{w})w - \frac{1}{\log(\hat{w})}\hat{w}\log(\hat{w})}{w - \frac{\hat{w}}{\log(\hat{w}) + 1}} \\ &= \max_{w \ge 1+f} \frac{(\log(\hat{w}) + 1)w - \hat{w}}{\frac{(\log(\hat{w}) + 1)w - \hat{w}}{\log(\hat{w}) + 1}} \\ &= \log(\hat{w}) + 1 \\ &= -W_{-1}\left(\frac{-1}{e(1+f)}\right) \quad, \end{split}$$

as desired.

The value assignment for (λ, τ) in the generalized exponential function $\Psi(y) = \tau(\lambda^y - 1)$ also indicates the phase transition point $\hat{f} = \frac{e-2}{2}$ of the buyback factor f in the optimal competitive ratio (as discussed in the introduction). It also shows why the optimal competitive ratio in the matching environment is *strictly worse* than the one in the single-resource environment. In particular, the constructed $\lambda = -(1+f)W_{-1}\left(\frac{-1}{e(1+f)}\right)$ becomes strictly smaller than e when $f < \frac{e-2}{2}$. However, Theorem 2 requires $\lambda \geq e$ to ensure the dual feasibility.

We finish this section by two remarks about Algorithm 3, one related to rounding this algorithm and one related to running this algorithm when f is not known to the algorithm, but either it has a known upper-bound or is a random variable drawn from a distribution with a known mean.

REMARK 3. Algorithm 3 is indeed a fractional online algorithm; however it can be shown that under large capacities (i.e., when all capacities s_i are at least s_{\min} for large enough s_{\min}), any online fractional algorithm with competitive ratio Γ can be converted into an integral randomized online algorithm with competitive ratio $\hat{\Gamma}(s_{\min})$, where $\lim_{s_{\min}\to+\infty}\hat{\Gamma}(s_{\min}) = \Gamma$. For more details, see Proposition EC.2 in Section EC.4.3.

REMARK 4. First, note that Algorithm 3 achieves a competitive ratio of at most $\Gamma_{gen}(f)$ even when the buyback cost is not equal to f but it is guaranteed to be no more than f. In particular, if the exact value of f is unknown to the algorithm, running the algorithm on a known upper bound \bar{f} guarantees a competitive ratio of $\Gamma_{gen}(\bar{f})$. Second, consider the case of stochastic f, where the buyback parameter will be drawn from a (possibly unknown) distribution F every time a buyback happens. Given the linearity of the total weight minus the buyback cost objective, the algorithm which knows the mean of distribution F (and uses $\mathbb{E}[f]$ as its buyback parameter) obtains a competitive ratio of at most $\Gamma_{gen}(\mathbb{E}[f])$ in expectation by linearity of the expectations.

5. Optimal Competitive Deterministic Integral Algorithm

In this section, we consider the model where allocations and buybacks are forced to be integral, i.e., (i) the algorithm should maintain an integral matching at each time, and (ii) should it decide

to buyback an edge-weight, it can only buyback the entire edge. In Section 5.1, we present the optimal competitive deterministic integral algorithm (Algorithm 4). Both the algorithm as well as its competitive ratio analysis are natural modifications of the primal-dual algorithm and the primal-dual analysis in Section 4 for fractional allocations. We show the optimality of our algorithm by providing the matching lower bound on the optimal competitive ratio in Section EC.1.2.

5.1. Upper-bound via primal-dual

In this subsection, we present the optimal competitive deterministic integral algorithm. The algorithm is parameterized by a penalty scalar $\tau \geq f$. It keeps track of the currently allocated weight \underline{w}_j for every offline node $j \in V$.¹⁴ Once a new online node $i \in U$ arrives, the algorithm allocates online node i to offline node j^* with the largest $w_{ij^*} - \tau \cdot \underline{w}_{j^*}$ (i.e., $j^* = \arg \max_{j \in V} w_{ij} - \tau \cdot \underline{w}_j$) unless $w_{ij} - \tau \cdot \underline{w}_j$ is negative for every offline node $j \in V$. In that case, it leave i unmatched. The formal description of the algorithm can be found in Algorithm 4.

Algorithm 4: Primal-dual deterministic integral allocation for matching with buyback		
in	put : penalty scalar $ au$	
1 initialize $\underline{w}_j \leftarrow 0$ for every offline node $j \in V$.		
a for each online node $i \in U$ do		
2 101		
3	if there exists $j \in V$ s.t. $\tau \cdot \underline{w}_j < w_{ij}$ then	
4	let $j^* \leftarrow \arg \max_{j \in V} w_{ij} - \tau \cdot \underline{w}_j$	
5	buyback offline node j^* from the previously allocated online node i' with $w_{i'j^*} \equiv \underline{w}_{j^*}$	
6	allocate offline node j^* to online node i	

7 $\[update \underline{w}_{j^*} \leftarrow w_{ij^*}\]$

REMARK 5. Algorithm 4 is equivalent to our primal-dual family of algorithms in Section 4 (Algorithm 3), when they are forced to make integral allocations. In particular, consider the algorithm which maintains an offline dual assignment $\beta_j = \int_0^\infty \tau \cdot \Psi(y(w)) dw$ for each offline node $j \in V$. Once a new online node i arrives, the algorithm allocates online node i to the offline node j^* which maximizes $w_{ij^*} - \beta_{j^*}$ if this difference is positive, and buybacks j^* from an earlier online node i' with $w_{i'j^*} = \underline{w}_{j^*}$ Namely, it differs from Algorithm 3 by replacing the continuous fractional allocation with a (deterministic) integral allocation. As a consequence, the allocation quantile function becomes a step function and thus $\beta_j = \int_0^{\underline{w}_j} \tau \Psi(1) dw \equiv \tau \cdot \underline{w}_j$, which shows the equivalence.

¹⁴ Because of integrality of allocation, \underline{w}_i is also the weight needed to be boughtback when a new allocation is made.

We present the competitive ratio of Algorithm 4 in Theorem 3. The proof is a simple adaptation of our previous primal-dual proof of Theorem 2 for the integral setting.

THEOREM 3. For every $\tau \ge 1 + f$, Algorithm 4 with penalty scalar τ has competitive ratio at most $\hat{\Gamma}_{\tau}(f)$, where

$$\hat{\Gamma}_{\tau}(f) \triangleq \max_{w \ge \tau} \frac{(\tau+1)w - 2\tau}{w - (1+f)}$$

Proof. Recall the linear program of maximum edge-weighted bipartite matching in complete bipartite graph G = (U, V) as the primal linear program, and its dual in \mathcal{P}_{OPT} . We construct a dual assignment based on the allocation decisions of Algorithm 4 (denoted by ALG throughout the proof). First, set $\alpha_i \leftarrow 0$ and $\beta_j \leftarrow 0$ for all $i \in U, j \in V$. Now consider every allocation (and buybacking) decision in ALG. Whenever ALG buybacks offline node j from online node i' (with weight $w_{i'j} \equiv \underline{w}_j$) and re-allocates offline node j to online node i, update the dual variables as follows:

$$\alpha_i \leftarrow w_{ij} - \tau \cdot \underline{w}_j \quad \text{and} \quad \beta_j \leftarrow \beta_j + \tau (w_{ij} - \underline{w}_j)$$

By construction, the invariant $\beta_j \equiv \tau \cdot \underline{w}_j$ holds throughout ALG. Similar to our earlier primal-dual proof of Theorem 2, the rest of this proof is also done in two steps:

[Step i] Checking the feasibility of dual. We first show that the constructed dual assignment is feasible. By construction, whenever ALG allocates offline node j to online node i, we know that $w_{ij} - \tau \cdot \underline{w}_j \ge 0$. Thus, $\alpha_i \ge 0$ and $\beta_j \ge 0$ for all $i \in U, j \in V$. Next, we show the feasibility of the dual constraint $\alpha_i + \beta_j \ge w_{ij}$ by considering two cases:

- Case I ALG does not allocate online node *i* to any offline node: By construction, we know that this happens only if $\beta_j = \tau \cdot \underline{w}_j \ge w_{ij}$. Thus, the dual constraint is satisfied.
- Case II ALG allocates online node *i* to offline node *j'*: By construction, ALG greedily allocates online node *i* to offline node *j*^{*} which maximizes $w_{ij^*} \beta_{j^*}$, meaning that $w_{ij} \tau \cdot \underline{w}_j \leq w_{ij'} \tau \cdot \underline{w}_{j'}$. Thus, the dual constraint is satisfied.

[Step ii] Comparing objective values in primal and dual. Here we show that the total profit of ALG is a $\hat{\Gamma}_{\tau}(f)$ -approximation of the objective value of the above dual assignment. To show this, we consider every allocation (and buybacking) decision in ALG and its impact on the total profit as well as the objective value of the dual assignment.

Now suppose ALG buybacks offline node j from online node i' (with weight $w_{i'j} \equiv \underline{w}_j$) and then re-allocates this offline node j to online node i. The change in the profit (i.e., the net change in the primal objective *after* we incorporate buyback cost) is

$$\Delta(\text{Primal}) = \left(w_{ij} - (1+f)\underline{w}_{i}\right)dx \quad ,$$

and the change in the dual objective is

$$\Delta(\text{Dual}) = w_{ij} - \tau \cdot \underline{w}_j + \tau (w_{ij} - \underline{w}_j) = (\tau + 1)w_{ij} - 2\tau \underline{w}_j$$

Combining with the fact $w_{ij} \ge \tau \cdot \underline{w}_j$, we have that $\Delta(\text{Dual}) \le \hat{\Gamma}_{\tau}(f) \cdot \Delta(\text{Primal})$. Again, by summing Δ (Dual) and Δ (Primal) over the entire horizon, we obtain:

$$ext{total-profit}(\texttt{ALG}) riangle extsf{Primal} \geq rac{1}{\hat{\Gamma}_{ au}(f)} \cdot extsf{Dual}$$

Finally, by weak duality of the linear program, $Dual \geq profit(OPT)$, which finishes the proof.

Given Theorem 3, we are ready to obtain the optimal competitive deterministic integral algorithm by properly picking the value of τ in Algorithm 4. Similar to the fractional matching settings in Section 4, we use two different value assignment of τ , depending on the buyback factor f.

COROLLARY 3 (Competitive ratio $\Gamma_{det-int}(f)$ in the small buyback cost regime). For every buyback factor $f \leq \frac{1}{3}$, Algorithm 4 with $\tau = \frac{1+f}{1-f}$ has competitive ratio at most $\frac{2}{1-f}$.

Proof. By construction, $\tau \ge 1 + f$. Invoking Theorem 3, the competitive ratio is at most

$$\begin{split} \max_{w \ge \tau} \frac{(\tau+1)w - 2\tau}{w - (1+f)} &= \max_{w \ge \tau} \frac{\left(\frac{1+f}{1-f} + 1\right)w - 2 \cdot \frac{1+f}{1-f}}{w - (1+f)} \\ &= \max_{w \ge \tau} \frac{\frac{2}{1-f}w - \frac{2}{1-f}(1+f)}{w - (1+f)} \\ &= \frac{2}{1-f} \quad , \end{split}$$

as desired.

COROLLARY 4 (Competitive ratio $\Gamma_{det-int}(f)$ in the large buyback cost regime). For every buyback factor $f \ge \frac{1}{3}$, Algorithm 4 with $\tau = 1 + f + \sqrt{f(1+f)}$ has competitive ratio at most $1 + 2f + 2\sqrt{f(1+f)}.$

Proof. By construction $\tau > 1 + f$. Invoking Theorem 3, the competitive ratio is at most

$$\max_{w \ge \tau} \frac{(\tau+1)w - 2\tau}{w - (1+f)} = \max_{w \ge \tau} \frac{\left(2 + f + \sqrt{f(1+f)}\right)w - 2\left(1 + f + \sqrt{f(1+f)}\right)}{w - (1+f)}$$

Thus, it is sufficient to show that for every $w \ge 1 + f + \sqrt{f(1+f)}$,

$$\left(2 + f + \sqrt{f(1+f)}\right)w - 2\left(1 + f + \sqrt{f(1+f)}\right) \ge \left(1 + 2f + 2\sqrt{f(1+f)}\right)(w - (1+f)) \quad ,$$

which can be simplified as

$$\left(f - 1 + \sqrt{f(1+f)}\right) \left(w - \left(1 + f + \sqrt{f(1+f)}\right)\right) \ge 0 \quad ,$$

which is true for every $f \ge \frac{1}{3}$.

6. Conclusion and Future Directions

Inspired by applications in modern online marketplaces such as cloud computing and banner advertising, we study online resource allocation of products with the possibility of booking and costly cancellations, where cancellation costs are linear with fixed slope f in the previous weight. Our main result is a full characterization of (both upper and lower bounds on) the optimal competitive ratio in the adversarial model and under all parameter regimes of the buyback factor f. We make a fundamental connection between the celebrated primal-dual framework and the buyback problem, and show how this connection can be used to obtain optimal competitive algorithms. As for future research, one can consider digging deeper into the primal-dual connection and extending it to other problems that consider costly cancellations. Another future direction is considering more complicated ways of augmenting the current matching by paying an appropriate cost. Finally, we can consider a general class of resource allocation where the reward from each offline resource is a high-dimensional function of its allocation distribution. Whether such models are amenable to constant competitive algorithms is an interesting yet challenging problem.

Appendix A: Proof of Theorem 1.

As discussed in the proof sketch in Section 3.3, our proof is a two-step argument.

Step 1- Reduction from general instances in the discounted-allocation model. Consider the following variant of edge-weighted online matching with buyback.

DEFINITION 7 (DISCOUNTED-ALLOCATION MODEL). In the discounted-allocation model, once an online node $i \in U$ with edge weights $\{w_{ij}\}_{j\in V}$ arrives, for each dx amount of offline node j allocated to online node i, the decision maker also immediately and irrevocably specifies a discounted per-unit price p which is weakly smaller than edge weight w_{ij} , and collects $p \cdot dx$ amount of reward. The buyback cost depends linearly on the allocated per-unit prices. In particular, when the decision maker buybacks dx amount of allocation with previously specified per-unit discounted price p', she loses the reward $p' \cdot dx$ and pays an extra cost of $f \cdot p' \cdot dx$ due to buybacks.

It is straightforward to see that the optimum offline benchmark is the same for the base model and the discounted-allocation model, since the optimum offline never buybacks and always sets discounted per-unit prices equal to edge weights. Similarly, every online algorithm in the base model is well-defined in the discounted-allocation model (by setting discounted per-unit prices equal to the edge weights).

Now we present the main claim in the first step of our argument.

LEMMA 1. In the single-resource environment, for any online algorithm ALG with the competitive ratio Γ within the truncated weight continuum instances \mathcal{I}_{cont} in the base model, there exists an online algorithm ALG[†] that has a competitive ratio of Γ within the class of all problem instances \mathcal{I} in the discounted-allocation model.

Proof. The idea behind this claim is a simple simulation approach. Consider any online algorithm ALG for the truncated weight continuum instances $\mathcal{I}_{\text{cont}}$ in the base model, and any general problem instance

 $I \in \mathcal{I}$ with T online nodes. For simplicity, suppose $w_1 \leq w_2 \leq \cdots \leq w_T$.¹⁵ When online node $i \in [T]$ arrives, We present all weights in the interval $[w_{i-1}, w_i]$ as proxy online nodes with a weight continuum to the online algorithm ALG. From the perspective of online algorithm ALG, it is executed on a truncated weight continuum instance I_{w_i} . We then mimic the allocation and buyback decisions of ALG by considering discounted per-unit prices in $[w_{i-1}, w_i]$, which is valid since the decision maker can choose any discounted per-unit price (as long as it is smaller than the current weight w_i) in the discounted-allocation model. By construction, the total profit under this simulation procedure for the original instance is the same as the total profit in ALG on truncated weight continuum instance I_{w_T} . Furthermore, since the optimum offline benchmarks are the same, this simulation procedure (given ALG as its guidance) obtains the same competitive ratio as ALG. This completes the proof of the claim.

Step 2- Reduction from general instances in the base model. Recall that every online algorithm in the base model is also well-defined in the discounted-allocation model (by setting discounted per-unit prices equal to the edge weights). In this step, we argue that the reverse also holds, and thus two models are equivalent.

LEMMA 2 (Lemon juice equivalence). For any online algorithm ALG in the base (resp. discountedallocation) model, there exists an online algorithm ALG^{\dagger} in the discounted-allocation (resp. base) model such that for any instance $I \in \mathcal{I}$, the expected profit in ALG is the same as the expected profit in ALG^{\dagger} , i.e., $ALG(I) = ALG^{\dagger}(I)$.¹⁶

Proof. Fix any online algorithm ALG in the base mode; note that it is by definition a valid online algorithm in the discounted-allocation model.

Fix any online algorithm ALG in the discounted-allocation model. We construct a valid online algorithm ALG^{\dagger} in the base model as follows. For each online node $i \in U$, suppose dx amount is allocated by ALG from offline node $j \in V$ with discounted per-unit price p. By definition, the discounted per-unit price p is weakly smaller than the edge weight w_{ij} , i.e., $p \leq w_{ij}$. We let ALG^{\dagger} allocate $\frac{p}{w_{ij}} \cdot dx$ amount of offline node j to online node i. Similarly, suppose ALG buybacks dx amount of allocation between online node i' and offline node j' with discounted per-unit price p' (with buyback $\cot(1+f)p'$). By construction, there is $\frac{p'}{w_{i'j'}} \cdot dx$ amount of offline node j' allocated to online node i' in ALG^{\dagger} . Thus, we let ALG^{\dagger} buyback this $\frac{p'}{w_{i'j'}} \cdot dx$ amount of offline node j' from online node i' (with buyback $\cot(1+f)w_{i'j'} \cdot \frac{p'}{w_{i'j'}} \cdot dx$). By construction, after the departure of each online node, (i) the buyback $\cot(1+f)w_{i'j'} \cdot \frac{p'}{w_{i'j'}} \cdot dx$). By construction, after the departure of allocation between online i and offline node j with discounted per-unit price p (and thus reward of $p \cdot dx$) in ALG, there exists $\frac{p}{w_{ij}} \cdot dx$ amount of offline node j allocated to online node j allocated to online node j allocated to online node i (and thus the same reward of $w_{ij} \cdot \frac{p}{w_{ij}} \cdot dx$) in ALG[†]. Since the discounted per-unit price is weakly smaller than the edge weight, i.e., $p \leq w_{ij}$, the constructed online algorithm ALG[†] is valid. Moreover, the profit in ALG[†] is the same as the profit in ALG, which concludes the proof.

¹⁵ Otherwise, we can consider another weight sequence $\{w'_i\}$ where $w'_i = \max_{\ell \leq i} w_i$. The rest of the argument holds in a straightforward fashion.

¹⁶ We have picked the name "lemon juice" since converting online algorithms in base model to online algorithms in discounted-allocation model is similar to making lemon water by adding water into lemon juice.

Combining Lemmas 1 and 2, we finish the proof of Theorem 1. Furthermore, it can be verified that Algorithm 2 is indeed the algorithmic construction in the proof of Lemmas 1 and 2.

Given the lemon juice equivalence between the base model and the discounted-allocation model, it is sufficient for us to present Algorithm 2, which converts any online algorithm (e.g., Algorithm 1) for the truncated weight continuum instances $\mathcal{I}_{\text{cont}}$ (in base model) to an online algorithm with the same competitive ratio guarantee in the discounted-allocation model.

References

Amazon EC2 spot instances. https://aws.amazon.com/ec2/spot/. Accessed: 08-01-2022.

- Microsoft display advertising network for online marketing. https://about.ads.microsoft.com/en-us/solutions/ ad-products/display-advertising-for-search-marketers. Accessed: 08-01-2022.
- Gagan Aggarwal, Gagan Goel, Chinmay Karande, and Aranyak Mehta. Online vertex-weighted bipartite matching and single-bid budgeted allocations. In Proceedings of the twenty-second annual ACM-SIAM symposium on Discrete Algorithms, pages 1253–1264. SIAM, 2011.
- Moshe Babaioff, Jason D Hartline, and Robert D Kleinberg. Selling ad campaigns: online algorithms with cancellations. In *Proceedings of the 10th ACM conference on Electronic commerce*, pages 61–70, 2009.
- Ashwinkumar Badandiyuru. Buyback problem-approximate matroid intersection with cancellation costs. In International Colloquium on Automata, Languages, and Programming, pages 379–390. Springer, 2011.
- Ashwinkumar Badanidiyuru and Robert Kleinberg. Randomized online algorithms for the buyback problem. In International Workshop on Internet and Network Economics, pages 529–536. Springer, 2009.
- Michael O Ball and Maurice Queyranne. Toward robust revenue management: Competitive analysis of online booking. Operations Research, 57(4):950–963, 2009.
- Santiago R Balseiro, Haihao Lu, and Vahab Mirrokni. The best of many worlds: Dual mirror descent for online allocation problems. *Operations Research*, 2022.
- Omar Besbes and Alp Muharremoglu. On implications of demand censoring in the newsvendor problem. *Management Science*, 59(6):1407–1424, 2013.
- Niv Buchbinder, Joseph Seffi Naor, et al. The design of competitive online algorithms via a primal-dual approach. Foundations and Trends in Theoretical Computer Science, 3(2-3):93-263, 2009.
- Niv Buchbinder, Moran Feldman, and Roy Schwartz. Online submodular maximization with preemption. In Proceedings of the twenty-sixth annual ACM-SIAM symposium on Discrete algorithms, pages 1202–1216. SIAM, 2014.
- Herman Chernoff et al. A measure of asymptotic efficiency for tests of a hypothesis based on the sum of observations. The Annals of Mathematical Statistics, 23(4):493–507, 1952.
- Florin Constantin, Jon Feldman, S Muthukrishnan, and Martin Pál. An online mechanism for ad slot reservations with cancellations. In *Proceedings of the twentieth annual ACM-SIAM symposium on discrete algorithms*, pages 1265–1274. SIAM, 2009.
- Nikhil R Devanur and Kamal Jain. Online matching with concave returns. In Proceedings of the forty-fourth annual ACM symposium on Theory of computing, pages 137–144, 2012.
- Nikhil R Devanur, Zhiyi Huang, Nitish Korula, Vahab S Mirrokni, and Qiqi Yan. Whole-page optimization and submodular welfare maximization with online bidders. ACM Transactions on Economics and Computation (TEAC), 4(3):1–20, 2016.
- Alexander Erdelyi and Huseyin Topaloglu. A dynamic programming decomposition method for making overbooking decisions over an airline network. *INFORMS Journal on Computing*, 22(3):443–456, 2010.

- Matthew Fahrbach, Zhiyi Huang, Runzhou Tao, and Morteza Zadimoghaddam. Edge-weighted online bipartite matching. In 2020 IEEE 61st Annual Symposium on Foundations of Computer Science (FOCS), pages 412–423. IEEE, 2020.
- Jon Feldman, Nitish Korula, Vahab Mirrokni, Shanmugavelayutham Muthukrishnan, and Martin Pál. Online ad assignment with free disposal. In *International workshop on internet and network economics*, pages 374–385. Springer, 2009.
- Yiding Feng and Rad Niazadeh. Batching and optimal multi-stage bipartite allocations. In 12th Innovations in Theoretical Computer Science Conference (ITCS 2021). Schloss Dagstuhl-Leibniz-Zentrum f
 ür Informatik, 2021.
- Yiding Feng, Rad Niazadeh, and Amin Saberi. Linear programming based online policies for real-time assortment of reusable resources. *Chicago Booth Research Paper*, (20-25), 2019.
- Daniel Freund and Jiayu Zhao. Overbooking with bounded loss. In Proceedings of the 22nd ACM Conference on Economics and Computation, pages 477–478, 2021.
- G Gallego and H Lee. Callable products with early exercise and overbooking. Proceedings of the AGIFORS Revenue Management Study Group, 2018.
- Guillermo Gallego and Haengju Lee. Callable products with dependent demands. Naval Research Logistics (NRL), 67(3):185–200, 2020.
- Guillermo Gallego, Steve G Kou, and Robert Phillips. Revenue management of callable products. Management Science, 54(3):550–564, 2008.
- Negin Golrezaei, Hamid Nazerzadeh, and Paat Rusmevichientong. Real-time optimization of personalized assortments. *Management Science*, 60(6):1532–1551, 2014.
- Xiao-Yue Gong, Vineet Goyal, Garud N Iyengar, David Simchi-Levi, Rajan Udwani, and Shuangyu Wang. Online assortment optimization with reusable resources. *Management Science*, 68(7):4772–4785, 2022.
- Vineet Goyal, Garud Iyengar, and Rajan Udwani. Online allocation of reusable resources via algorithms guided by fluid approximations. arXiv preprint arXiv:2010.03983, 2020.
- Xin Han, Yasushi Kawase, and Kazuhisa Makino. Online unweighted knapsack problem with removal cost. Algorithmica, 70(1):76–91, 2014.
- Richard M Karp, Umesh V Vazirani, and Vijay V Vazirani. An optimal algorithm for on-line bipartite matching. In Proceedings of the twenty-second annual ACM symposium on Theory of computing, pages 352–358, 1990.
- Retsef Levi, Robin O Roundy, and David B Shmoys. Provably near-optimal sampling-based policies for stochastic inventory control models. *Mathematics of Operations Research*, 32(4):821–839, 2007.
- Varda Liberman and Uri Yechiali. On the hotel overbooking problem—an inventory system with stochastic cancellations. Management Science, 24(11):1117–1126, 1978.
- Ilan Lobel, Renato Paes Leme, and Adrian Vladu. Multidimensional binary search for contextual decision-making. Operations Research, 66(5):1346–1361, 2018.
- Aranyak Mehta, Amin Saberi, Umesh Vazirani, and Vijay Vazirani. Adwords and generalized online matching. Journal of the ACM (JACM), 54(5):22–es, 2007.
- Aranyak Mehta et al. Online matching and ad allocation. Foundations and Trends® in Theoretical Computer Science, 8(4):265–368, 2013.
- Mohamed Mostagir. Optimal delivery in display advertising. In 2010 48th Annual Allerton Conference on Communication, Control, and Computing (Allerton), pages 577–583. IEEE, 2010.
- Hanzhang Qin, David Simchi-Levi, and Li Wang. Data-driven approximation schemes for joint pricing and inventory control models. *Management Science*, 2022.
- Marvin Rothstein. An airline overbooking model. Transportation Science, 5(2):180–192, 1971.

This page is intentionally blank. Proper e-companion title page, with INFORMS branding and exact metadata of the main paper, will be produced by the INFORMS office when the issue is being assembled.

Appendix EC.1: Competitive Ratio Lower-bounds

In this section we provide worst-case instances and prove tight competitive ratio lower-bounds in both the general setting (i.e., when fractional allocations and randomization are allowed) and the deterministic integral setting, for all choices of the buyback parameter f.

EC.1.1. General Setting

In this section, we present our lower-bounds on the optimal competitive ratio of general algorithms. Later in Section EC.1.2 we discuss lower-bounds for deterministic integral algorithms.

THEOREM EC.1. In the matching environment, the optimal competitive ratio $\Gamma_{gen}(f)$ is at least $\frac{e}{e^{-(1+f)}}$ for every buyback factor $f \leq \frac{e-2}{2}$, and $-W_{-1}\left(\frac{-1}{e^{(1+f)}}\right)$ for every buyback factor $f \geq \frac{e-2}{2}$.¹⁷

At a high level, in our problem, there are two sources of uncertainty preventing the optimal online algorithm to perform as well as the optimum offline benchmark (or even better than a certain approximation of this benchmark). We refer to these sources the *edge-wise* uncertainty and the *weight-wise* uncertainty, respectively:

• Edge-wise uncertainty: this source of uncertainty is related to the matching feature of our model. To better understand its effect, consider an extreme case where f = 0 (i.e., no buyback cost) and the edge-weights w_{ij} take values of either 0 or 1 for $i \in U, j \in V$. Note that this special case is indeed the classic unweighted online bipartite matching model studied in Karp et al. (1990). In this case, there exists no online algorithm, neither integral nor fractional, performing better than 1-1/e fraction of the optimum offline benchmark due to the uncertainty in the future edges of the graph. Instances establishing this bounds are simple: online nodes and offline nodes are indexed by $1, \ldots, n$, and online node i is only connected to offline nodes [i:n]. Such an instance basically pushes the online algorithm to fully hedge against the future uncertainty in the future sub-graph, while optimum offline just picks the right edge for each online node.

• Weight-wise uncertainty: this source is related to the buyback feature of our model. Consider an extreme case where f > 0 (i.e., costly cancellations) and there is a single offline node (i.e., the single-resource environment). Even in this case, there exists no online algorithm performing as well as the optimum offline benchmark due to the uncertainty of the future weights and the cost of buyback. In fact, as shown in Badanidiyuru and Kleinberg (2009), no randomized integral algorithm can perform better than $1/\left(-W_{-1}\left(\frac{-1}{e(1+f)}\right)\right)$ fraction of optimum offline. Again, instances establishing this bound are simple: in short, an increasing sequence of weights (with certain structures) is

¹⁷ As a sanity check, $\frac{e}{e-(1+f)} \ge -W_{-1}\left(\frac{-1}{e(1+f)}\right)$ for every $f \le \frac{e-2}{2}$, and the equality holds when $f = \frac{e-2}{2}$.

presented to the online algorithm. Now the algorithm does not know when to stop and is pushed to fully hedge against the future uncertainty in the arriving weights, while the optimum offline just stops right at end of the sequence and picks the maximum weight.

To establish lower-bounds on the optimal competitive ratio of the buyback problem in the matching environment, we construct (randomized) worst-case instances which exploit both of these aforementioned uncertainty sources by borrowing ideas from both lower-bound instances. As mentioned earlier, we observe a phase transition in terms of the behaviour of those instances for the competitive ratio. Specifically, in Section EC.1.1.1, we present the competitive ratio lower-bound for the small buyback cost regime (i.e., $f \leq \frac{e-2}{2}$), through a worst-case instance which mainly utilizes the edge-wise uncertainty in the matching environment. In Section EC.1.1.2, we present the competitive ratio lower-bound for the large buyback cost regime (i.e., $f \geq \frac{e-2}{2}$), through a worst-case instance which utilizes the weight-wise uncertainty in the single-resource environment. Combining both lower-bound results, we obtain Theorem EC.1.

EC.1.1.1. Matching environment under small buyback factor In this section, we present a randomized instance (Example EC.1) in the matching environment, which utilizes the edge-wise uncertainty to derive the competitive ratio lower-bound in the small buyback cost regime, i.e., $f \leq \frac{e-2}{2}$.

EXAMPLE EC.1. Fix an arbitrary $K \in \mathbb{N}$. Let $\pi : [K] \to [K]$ be a uniform random permutation over [K]. Consider a randomized instance with bipartite graph G = (U, V, E) where

$$U \leftarrow [K] \qquad V \leftarrow [K] \qquad E \leftarrow [K] \times [K] ,$$

and edge-weights $\{w_{ij}\}_{i,j\in[K]}$ are as follows,

$$\forall i \in [K], j \in [K]: \qquad w_{ij} \leftarrow \frac{1}{K - i + 1} \cdot \mathbbm{1}\left\{\pi(j) \ge i\right\}$$

In Example EC.1, conditioning on a realized permutation π , each online node $i \in [K]$ has edgeweights $\frac{1}{K-i+1}$ for (K-i+1) offline nodes, and zero edge-weight for the remaining offline nodes. Furthermore, for every online nodes i and i+1, the set of offline nodes with non-zero edge-weights are nested, i.e., $\{j \in [K] : w_{ij} > 0\} \equiv \{j \in [K] : w_{i+1,j} > 0\} \cup \{\pi^{-1}(i)\}$.¹⁸ By construction, it is straightforward to verify that the optimum offline matches each online node i to offline node $\pi^{-1}(i)$ and collects total profit $\sum_{i \in [K]} 1/i$, which we summarize as the following lemma.

LEMMA EC.1. In Example EC.1, the expected profit in the optimum offline benchmark is $\sum_{\ell \in [K]} 1/\ell.$

 18 Here $\pi^{-1}(\cdot)$ is the inverse of permutation $\pi,$ i.e., $\pi(i)=j \leftrightarrow i=\pi^{-1}(j)$

Next we characterize the optimal competitive online algorithm in Example EC.1. We start with a simple and intuitive observation that when f = 0 (i.e., no buyback cost), since the (non-zero) edge-weights are weakly increasing in Example EC.1, it is optimal (given any sequence of future online nodes) to allocate the whole unit of online node i to offline nodes j with non-zero edgeweights. As the main technical ingredient of this lower-bound result, we prove that this observation for f = 0 approximately holds in the small buyback cost regime (i.e., $f \leq \frac{e-2}{2}$). Specifically, we show that for any buyback factor $f \leq \frac{e-2}{2}$, there exists $K_0(f) \in \mathbb{N}$ (independent of K) such that for every online node $i \leq K - K_0(f)$, the optimal online algorithm allocates the whole unit of online node ito offline nodes j with non-zero edge-weights. Additionally, due to the ex-ante symmetry (over the randomness in π), we also show that optimal online algorithm allocates equal fractions of a given online node to each offline node with non-zero edge-weights. We summarize the characterization of this optimal competitive algorithm in Lemma EC.2, and defer its formal proof to Appendix EC.2.1.

LEMMA EC.2. In Example EC.1, for any buyback factor $f \leq \frac{e-2}{2}$, the optimal online algorithm satisfies

- 1. <u>Symmetric-allocation</u>: for each online node $i \in [K]$, the algorithm allocates equal fractions of online node i to all offline nodes with non-zero edge-weights.
- 2. <u>Fully-allocation</u>: there exists $K_0(f) \in \mathbb{N}$ such that for each online node $i \in [K K_0(f)]$, the algorithm allocates the whole unit of online node i to offline nodes with non-zero edge-weights.

Given the characterizations of both the optimum offline benchmark as well as the optimal online algorithm, we obtain the following competitive ratio lower-bound through Example EC.1. We defer its formal proof to Appendix EC.2.2.

THEOREM EC.2. In the matching environment, for any buyback factor $f \leq \frac{e-2}{2}$, the optimal competitive ratio $\Gamma_{gen}(f)$ is at least $\frac{e}{e-(1+f)}$.

EC.1.1.2. Matching environment under large buyback factor When buyback factor f is close to zero, it is intuitive that the edge-wise uncertainty (rather than the weight-wise uncertainty) becomes the main source preventing any online algorithm to perform as well as the optimum offline benchmark. However, it is not clear whether the edge-wise uncertainty or the weight-wise uncertainty becomes the dominant (or equally important) source when buyback factor f becomes large.

In this subsection, we revisit the lower-bound for randomized integral algorithms in the singleresource environment, established first in Badanidiyuru and Kleinberg (2009). We show this lowerbound can be transformed into a lower-bound for fractional allocations. This holds as we show any fractional algorithm can be rounded without any loss (in expectation) to an integral algorithm by a standard (yet clever) randomized rounding. Notably, by definition, such a lower-bound serves as a lower-bound for the (fractional allocations) in the matching environment as well. Quite surprisingly, as we show later in Section 4, this particular lower-bound becomes the *tightest* lower-bound for the matching environment in the large buyback cost regime (i.e., $f \ge \frac{e-2}{2}$) — indicating that weight-wise uncertainty dominates the edge-wise uncertainly in this regime.¹⁹

THEOREM EC.3 (Adopted from Badanidiyuru and Kleinberg, 2009). In the singleresource environment, for any buyback factor $f \ge 0$, the optimal competitive ratio of fractional online algorithms $\Gamma_{gen}(f)$ is at least $-W_{-1}\left(\frac{-1}{e(1+f)}\right)$.

For completeness, we provide a formal proof of Theorem EC.3 in Appendix EC.2.3. At the core of this proof, we introduce and analyze a loss-less rounding rounding algorithm for online factional algorithms for single-resource buyback problem. We present such a rounding algorithm for certain class of instances helpful for establishing this lower-bound, and later generalize them to arbitrary instances in Section EC.4.1.

In the remaining of this subsection, we explain the lower-bound instance used in the above theorem and provide some intuitions on why it plays the role of a worst-case example in the singleresource buyback. The lower-bound instance in Theorem EC.3 has a particular structure. With a slight abuse of the model, consider an instance I_T in the single-resource environment where there is a continuum population of online nodes (i.e., U = [0, T]), and each node $w \in U$ has weight exactly equal to w. We refer to this instance as a *truncated weight continuum* instance. Let $\mathcal{I}_{\text{cont}} = \{I_T\}_{T \in \mathbb{R}_+}$ be the class of all such instances. In the proof of Theorem EC.3, we consider a randomized instance based on the truncated weight continuum instances as follows.

EXAMPLE EC.2. Fix an arbitrary $T_0 \in \mathbb{R}_+$. Consider a randomized truncated weight continuum instance $I_T \in \mathcal{I}_{\text{cont}}$ where T is selected with density $1/T^2$ for every $T \in [0, T_0]$, and with remaining probability $1/T_0$ for $T = T_0$.

Since Example EC.2 only contains a single offline node, there exists no edge-wise uncertainty. The only source preventing any online algorithm to perform as well as the optimum offline benchmark is the weight-wise uncertainty. In fact, due to this uncertainty, the optimal competitive online algorithm in Example EC.2 does not fully allocate some online nodes even though such allocation leads to strictly positive immediate profit (i.e., in some sense, it reserves the capacity for possibly higher-weight online nodes in future).²⁰

¹⁹ We provide an online algorithm which matches this lower-bound in the large buyback cost regime for the matching environment in Section 4.

 $^{^{20}}$ As a comparison, in Example EC.1 which utilizes the edge-wise uncertainty, the optimal online algorithm fully allocates almost every online node.

We would like to end this section by mentioning that the truncated continuum instances $\mathcal{I}_{\text{cont}}$ turns out to be an important subclass of instances. Not only it is used as the main building block of the lower-bound result (Theorem EC.3), it also serves as a key concept for us to design optimal competitive algorithm in Section 3 and Section 4.

EC.1.2. Deterministic Integral Setting

In this section, we show our upper bound in Theorem 3 for deterministic integral algorithms is tight by studying two problem instances. As discussed in Section EC.1.1, there are two uncertainties preventing the online algorithm to does as good as the optimum offline benchmark, edge-wise uncertainty and weight-wise uncertainty. First in Theorem EC.4 by analyzing Example EC.3 (originally suggested in Babaioff et al., 2009), we show a lower-bound for the single resource environment. Similar to the general setting, the lower-bound for the single-resource environment is tight for the matching environment when the weight-wise uncertainty is dominant (i.e., buyback factor is large). For small buyback factors on the other hand, adversary will also exploit the edge-wise uncertainty. In Theorem EC.5 we show a better lower-bound for matching environments when $f < \frac{1}{3}$. Formal proofs are deferred to Appendices EC.2.5 and EC.2.6.

EXAMPLE EC.3. Let n = 1. Given an arbitrary online algorithm ALG and positive number w_0 , let $\{w_i\}_{i=1}^{\infty}$ be the increasing sequence such that w_i is the infimum weight w the algorithm sells to given that the weight of previous arrivals are $\{w_0, w_1, ..., w_{i-1}\}$.

THEOREM EC.4 (Adopted from Babaioff et al., 2009). In Example EC.3, for any buyback factor $f \ge 0$, the optimal competitive ratio of deterministic integral online algorithm $\Gamma_{det-int}(f)$ is at least $1 + 2f + 2\sqrt{f(1+f)}$.

EXAMPLE EC.4. Set an arbitrary online algorithm ALG and let n = 2. Without loss of generality assume ALG allocates the first arrived online node to the offline node number 1 if $w_{11} = w_{12} \equiv w_0$ (if ALG decides not to allocate, CR will be unbounded as the adversary can just terminate the instance). Let $\{w_i\}_{i=1}^{\infty}$ be the increasing sequence such that w_i is the infimum weight w the algorithm accepts, i.e., allocates the offline node to the arriving online node and buybacks the previously allocated one, given that the weight of previous arrivals are $\{(w_0, w_0), (w_1, 0), ..., (w_{i-1}, 0)\}$.

THEOREM EC.5. In Example EC.4, for any buyback factor $f < \frac{1}{3}$, the optimal competitive ratio of deterministic integral online algorithm $\Gamma_{det-int}(f)$ is at least $\frac{2}{1-f}$.

Appendix EC.2: Missing Proofs EC.2.1. Proof of Lemma EC.2

LEMMA EC.2. In Example EC.1, for any buyback factor $f \leq \frac{e-2}{2}$, the optimal online algorithm satisfies

- 1. <u>Symmetric-allocation</u>: for each online node $i \in [K]$, the algorithm allocates equal fractions of online node i to all offline nodes with non-zero edge-weights.
- 2. <u>Fully-allocation</u>: there exists $K_0(f) \in \mathbb{N}$ such that for each online node $i \in [K K_0(f)]$, the algorithm allocates the whole unit of online node i to offline nodes with non-zero edge-weights.

To prove Lemma EC.2, we introduce two auxiliary functions and prove one related technical lemma which will be used in the final analysis. Define function $pre : \mathbb{N} \to \mathbb{N}$ and function $suc : \mathbb{N} \to \mathbb{N}$ where:

$$\forall i \in \mathbb{N}: \qquad \texttt{pre}(i) = \max\left\{i' \in \mathbb{N}: \sum_{\ell=i'}^{i} \frac{1}{\ell} > 1\right\} \qquad \text{and} \qquad \texttt{suc}(i) = \min\left\{i' \in \mathbb{N}: \sum_{\ell=i}^{i'} \frac{1}{\ell} > 1\right\} \quad .$$

As a sanity check, note that **pre** is the inverse function of **suc** by definition. Now we have the following lemma regarding the asymptotic behaviours of these two functions.

LEMMA EC.3. $\lim_{i \to \infty} \frac{\operatorname{pre}(i)}{i} = \frac{1}{e}, \ \lim_{i \to \infty} \frac{\operatorname{suc}(i)}{i} = e, \ and \ \lim_{i \to \infty} \sum_{i' = \operatorname{pre}(i)+1}^{i} \frac{1}{\operatorname{suc}(i')} \leq \frac{1}{e} \ .$

Proof. We first show $\lim_{i \to \infty} \frac{\operatorname{pre}(i)}{i} = \frac{1}{e}$, which is equivalent to $\lim_{i \to \infty} \frac{i}{\operatorname{pre}(i)} = e$. On one hand,

$$\log\left(\frac{i}{\operatorname{pre}(i)-1}\right) = \int_{\operatorname{pre}(i)-1}^{i} \frac{1}{\ell} \, d\ell \ge \sum_{\ell=\operatorname{pre}(i)}^{i} \frac{1}{\ell} \ge 1 \quad .$$

Similarly,

$$\log\left(\frac{i+1}{\operatorname{pre}(i)}\right) = \int_{\operatorname{pre}(i)}^{i+1} \frac{1}{\ell} \, d\ell \le \sum_{\ell = \operatorname{pre}(i)+1}^{i} \frac{1}{\ell} < 1 \quad .$$

Combining the above inequalities with the fact that

$$\lim_{i \to \infty} \frac{i}{\operatorname{pre}(i)} = \lim_{i \to \infty} \frac{i+1}{\operatorname{pre}(i)} = \lim_{i \to \infty} \frac{i}{\operatorname{pre}(i) - 1} ,$$

we prove $\lim_{i\to\infty} \frac{\operatorname{pre}(i)}{i} = \frac{1}{e}$ by the sandwich theorem, as desired. Since suc is the inverse function of pre, we have $\lim_{i\to\infty} \frac{\operatorname{suc}(i)}{i} = e$ as well.

Finally, we show $\lim_{i\to\infty}\sum_{i'=\operatorname{pre}(i)+1}^{i}\frac{1}{\operatorname{suc}(i')}\leq \frac{1}{e}$. As we shown above, for every $\varepsilon > 0$, there exists $N \in \mathbb{N}$ such that $\frac{\operatorname{suc}(i)}{i} \geq \frac{1}{\frac{1}{e}+\varepsilon}$ for every $i \geq N$. Therefore,

$$\lim_{i \to \infty} \sum_{i' = \operatorname{pre}(i)+1}^{i} \frac{1}{\operatorname{suc}(i')} \leq \lim_{i \to \infty} \sum_{i' = \operatorname{pre}(i)+1}^{i} \left(\frac{1}{e} + \varepsilon\right) \frac{1}{i} \leq \frac{1}{e} + \varepsilon$$

Letting ε goes to zero finishes the proof.

Now we are ready to prove Lemma EC.2.

Proof of Lemma EC.2. We first show the symmetric-allocation property. In particular, we show how to convert an arbitrary online algorithm ALG to an online algorithm ALG[†] that satisfies the symmetric-allocation property and achieves the same profit: Fix an arbitrary online algorithm ALG. Let z_{ij}^{π} be the expected allocation between online node *i* and offline node *j* under permutation π in ALG. Note that for every $i, j, j' \in [K]$

$$\mathbf{E}_{\pi} \left[z_{ij}^{\pi} \mid w_{ij} > 0 \right] = \mathbf{E}_{\pi} \left[z_{ij'}^{\pi} \mid w_{ij'} > 0 \right]$$

which holds due to the symmetry of our bipartite graph construction, i.e., conditioned on the event $[w_{ij} > 0 \land w_{ij'} > 0]$, it is an automorphism that exchanges j and j'. Therefore, we construct algorithm ALG[†] by simulating algorithm ALG. For each online node i, let ALG[†] allocates $\mathbf{E}_{\pi}[z_{ij}^{\pi} | w_{ij} > 0]$ to each offline node j with non-zero edge weight, and allocates nothing to each offline node j with zero edge weight. By construction, it is straightforward to verify that ALG[†] satisfies the symmetric-allocation property and achieves the same profit as ALG.

Next, we show the fully-allocation property. Fix an arbitrary online node $i \in [K]$. Let $k \triangleq K - i+1$. Note that there are k offline nodes j with non-zero edge weight $w_{ij} > 0$. Suppose the optimal online algorithm allocates $k \cdot dx$ amount of online node i to offline nodes. By the symmetricallocation property, each offline node j with non-zero edge weight receives dx amount. Given the definition of function $\mathbf{pre}(\cdot)$ and the fact that the optimal algorithm always greedily buybacks the smallest allocated weight, there are $\mathbf{pre}(k)$ offline nodes with non-zero edge weight, each of which has total allocation exceeding one in the future.²¹ Thus, these $\mathbf{pre}(k)$ offline nodes are the ones which the algorithm may buyback their dx amount of online node i in the future. As a consequence, by allocating this $k \cdot dx$ amount of online node i, the algorithm incurs an additional buyback cost at most $\mathbf{pre}(k) \cdot \left(\frac{f}{k}\right) dx$.²² On the other hand, each of the remaining $k - \mathbf{pre}(k)$ offline nodes in the end, the algorithm makes a marginal profit of at least $\sum_{\ell=\mathbf{pre}(k)+1}^{k} \left(\frac{1}{k} - \frac{1+f}{\operatorname{suc}(\ell)}\right) dx$. Putting all pieces together, the increase of the final profit by allocating extra $k \cdot dx$ amount of online node i is at least

$$-\mathtt{pre}(k) \cdot \left(\frac{f}{k}\right) dx + \sum_{\ell = \mathtt{pre}(k)+1}^{k} \left(\frac{1}{k} - \frac{1+f}{\mathtt{suc}(\ell)}\right) dx$$

²¹ Namely, suppose the algorithm fully allocates each future online node i' > i with equal fractions to offline nodes with non-zero edge weight, then the total amount allocated to offline node j > K - pre(k) exceeds one.

²² There are pre(k) offline nodes which may be buyback in the future. Each offline node receives dx amount of online node with edge weight $\frac{1}{k}$.

By algebra, this increase of the final profit is non-negative if

$$1 - (1+f)\left(\frac{\operatorname{pre}(k)}{k} + \sum_{\ell = \operatorname{pre}(k)+1}^k \frac{1}{\operatorname{suc}(\ell)}\right) \ge 0$$

Invoking Lemma EC.3, for every $\varepsilon > 0$, there exists $N(\varepsilon) \in \mathbb{N}$ such that for every $k \ge N(\varepsilon)$, $\left(\frac{\operatorname{pre}(k)}{k} + \sum_{\ell=\operatorname{pre}(k)+1}^{k} \frac{1}{\operatorname{suc}(\ell)}\right) \le \frac{2+\varepsilon}{e}$. Thus, for every buyback factor $f < \frac{e-2}{2}$, let $\varepsilon(f)$ be the number such that $f \le \frac{e-2-\varepsilon(f)}{2+\varepsilon(f)}$. Setting $K_0(f) \triangleq N(\varepsilon(f))$ finishes the proof. \Box

EC.2.2. Proof of Theorem EC.2

THEOREM EC.2. In the matching environment, for any buyback factor $f \leq \frac{e-2}{2}$, the optimal competitive ratio $\Gamma_{gen}(f)$ is at least $\frac{e}{e-(1+f)}$.

Proof. Consider the optimum offline benchmark and the optimal competitive online algorithm in Example EC.1. By Lemma EC.1, the expected total profit of the optimum offline benchmark is

$$\texttt{OPT}(\text{Example EC.1}) = \sum_{\ell \in [K]} \frac{1}{\ell}$$

By Lemma EC.2, in the optimal online algorithm, for every online node $i \in [K - K_0(f)]$, the algorithms allocates $\frac{1}{K-i+1}$ to each of K - i + 1 offline nodes with non-zero edge weights. Therefore, the total profit induced by every online node $i \in [K - \operatorname{suc}(K_0(f))]$ is at most $\frac{1}{K-i+1} \left(1 - (1+f) \frac{\operatorname{pre}(K-i+1)}{K-i+1}\right)^{23}$ The total profit induced by every online node $i \in [K - \operatorname{suc}(K_0(f)) + 1:K]$ is at most $\frac{1}{K-i+1}$. Putting two pieces together, the expected total profit of the optimal online algorithm ALG^{*} is at most

$$\begin{aligned} \text{ALG}^{*}(\text{Example EC.1}) &\leq \sum_{i \in [K- \text{suc}(K_{0}(f))]} \frac{1}{K - i + 1} \left(1 - (1 + f) \frac{\text{pre}(K - i + 1)}{K - i + 1} \right) + \sum_{i \in [K- \text{suc}(K_{0}(f)) + 1:K]} \frac{1}{K - i + 1} \\ &= \sum_{\ell=1}^{\text{suc}(K_{0}(f))} \frac{1}{\ell} + \sum_{\ell=\text{suc}(K_{0}(f))}^{K} \frac{1}{\ell} \left(1 - (1 + f) \frac{\text{pre}(\ell)}{\ell} \right) \\ &\leq \sum_{\ell=1}^{\text{suc}(K_{1}(f,\varepsilon))} \frac{1}{\ell} + \sum_{\ell=\text{suc}(K_{1}(f,\varepsilon))}^{K} \frac{1}{\ell} \left(1 - (1 + f) \left(\frac{1}{e} - \varepsilon \right) \right) \end{aligned}$$

where $\varepsilon > 0$ is an arbitrary positive constant, and $K_1(f,\varepsilon) \ge K_0(f)$ is a constant such that $\frac{\operatorname{pre}(\ell)}{\ell} \ge \frac{1}{e} - \varepsilon$ for every $\ell \ge K_1(f,\varepsilon)$. The existence of constant $K_1(f,\varepsilon)$ is guaranteed by Lemma EC.3. Notably, constant $K_1(f,\varepsilon)$ is independent of K.

²³ The weight of online node *i* is $\frac{1}{K-i+1}$. There are pre(K-i+1) offline nodes *j*, which the algorithm will buyback its allocation from online node *i* to offline node *j* in the future.

Finally, to lowerbound the optimal competitive ratio $\Gamma_{gen}(f)$, note that

$$\frac{1}{\Gamma_{\text{gen}}(f)} \leq \frac{\text{ALG}^{*}(\text{Example EC.1})}{\text{OPT}(\text{Example EC.1})} \\
\leq \frac{\sum_{\ell=1}^{\text{suc}(K_{1}(f,\varepsilon))} \frac{1}{\ell} + \sum_{\ell=\text{suc}(K_{1}(f,\varepsilon))}^{K} \frac{1}{\ell} \left(1 - (1+f)\left(\frac{1}{e} - \varepsilon\right)\right)}{\sum_{\ell \in [K]} \frac{1}{\ell}} \\
\leq o(1) + 1 - (1+f)\left(\frac{1}{e} - \varepsilon\right)$$

where the last inequality holds since $\frac{\sum_{\ell=\operatorname{suc}(K_1(f,\varepsilon))}^K \frac{1}{\ell}}{\sum_{\ell\in[K]} \frac{1}{\ell}} = o(1)$ when we let K go to infinite and hold $K_1(f,\varepsilon)$ as constant.

EC.2.3. Proof of Theorem EC.3

THEOREM EC.3 (Adopted from Badanidiyuru and Kleinberg, 2009). In the singleresource environment, for any buyback factor $f \ge 0$, the optimal competitive ratio of fractional online algorithms $\Gamma_{gen}(f)$ is at least $-W_{-1}\left(\frac{-1}{e(1+f)}\right)$.

To prove Theorem EC.3, we first use a lemma in Badanidiyuru and Kleinberg (2009) to establish the same lower-bound on competitive ratio of integral algorithms using a randomized truncated weight continuum instance (Example EC.2). We later show in that we can extend it to online fractional algorithms by combining it with the fractional-to-integral rounding for truncated weight continuum instances.

LEMMA EC.4 (Badanidiyuru and Kleinberg, 2009). In Example EC.2, the expected profit in the optimum offline benchmark is $\log(T_0) + 1$, and the expected profit in the optimal integral algorithm is $\max_{w\geq 1} 1 + (k(w) - 1) \cdot \frac{w - (1+f)}{w}$ where $k(w) = \max\{\ell \in \mathbb{N} : w^{\ell-1} \leq T_0\}$.

LEMMA EC.5. In the single-resource environment, for any online algorithm ALG with the competitive ratio Γ within the truncated weight continuum instances \mathcal{I}_{cont} , there exists a randomized integral online algorithm ALG[†] with the same competitive ratio Γ within the truncated weight continuum instances \mathcal{I}_{cont} .

Proof. Fix an arbitrary online algorithm ALG for the truncated weight continuum instances $\mathcal{I}_{\text{cont}}$. Note that every truncated weight continuum instance I_T looks exactly the same before its termination. Thus, let $\tilde{x}(w)$ be the allocated density/fraction when online node $w \in \mathbb{R}_+$ arrives in algorithm ALG. For any $\eta \in [0, 1]$, define function $w_\eta : \mathbb{N} \to \mathbb{R}_+$ where for every $\ell \in \mathbb{N}$, $w_\eta(\ell)$ is the solution w such that $\int_0^w \tilde{x}(t) dt = \ell + \eta - 1.^{24}$

Now we construct a randomized integral algorithm ALG^{\dagger} as follows. The algorithm samples η from [0,1] uniformly at random. Then it allocates the offline node to each online node $w \in \{w_{\eta}(\ell) : \ell \in \mathbb{N}\}$.

²⁴ If there exists no w such that $\int_0^w \tilde{x}(t) dt = \ell + \eta - 1$, we let $w_\eta(\ell) = \infty$.

By construction, $\operatorname{ALG}^{\dagger}$ is a randomized integral algorithm. We just need to prove the probability that $\operatorname{ALG}^{\dagger}$ allocates the offline node to an online node in the interval $[\underline{w}, \overline{w}]$ is exactly $\min(1, \int_{\underline{w}}^{\overline{w}} \tilde{x}(w) \, dw)$ for each truncated weight continuum instance I_T with $T \geq \overline{w}$. First of all if $\int_{\underline{w}}^{\overline{w}} \tilde{x}(w) \, dw > 1$ it means that there exists a $w \in [\underline{w}, \overline{w}]$ and $\ell \in \mathbb{N}$ such that $\int_0^w \tilde{x}(t) \, dt = \ell + \eta - 1$. Which means $\operatorname{ALG}^{\dagger}$ always allocate to the online node $w \in [\underline{w}, \overline{w}]$. Otherwise, $\operatorname{ALG}^{\dagger}$ allocates to an online node in the interval $[\underline{w}, \overline{w}]$ if and only if there exists an $\ell \in \mathbb{N}$ with $\int_0^w \tilde{x}(w) \, dw < \ell + \eta - 1 < \int_0^{\overline{w}} \tilde{x}(w) \, dw$. Since η is uniformly sampled, this happens with probability $\int_0^{\overline{w}} \tilde{x}(w) \, dw - \int_0^w \tilde{x}(w) \, dw = \int_{\underline{w}}^w \tilde{x}(w) \, dw$. Furthermore, notice that in both cases the arrival w is bought back if and only if $\int_w^T \tilde{x}(w) \, dw \ge 1$. Thus, the competitive ratio (within truncated weight continuum instances $\mathcal{I}_{\text{cont}}$) of the constructed randomized integral online algorithm $\operatorname{ALG}^{\dagger}$ is the same as algorithm ALG.

Now we are ready to prove Theorem EC.3.

Proof of Theorem EC.3. To lower-bound the competitive ratio $\Gamma_{\text{gen}}(f)$, by Lemma EC.5, it is enough to find a lower-bound on the competitive ratio of integral algorithms within the class of truncated weight continuum instances. Now consider Example EC.2 which is in this class. By Lemma EC.4, the expected total profit of the optimum offline benchmark as well as the optimal online integral algorithm ALG^{*} is

$$\begin{aligned} & \mathsf{OPT}(\mathsf{Example EC.2}) = \log(T_0) + 1 \\ & \mathsf{ALG}^*(\mathsf{Example EC.2}) = \max_{w \ge 1} 1 + (k(w) - 1) \cdot \frac{w - (1 + f)}{w} \end{aligned}$$

where $k(w) = \max\{\ell \in \mathbb{N} : w^{\ell-1} \leq T_0\}$. Let $w^* \triangleq \arg \max_{w \geq 1} \max_{w \geq 1} 1 + (k(w) - 1) \cdot \frac{w - (1+f)}{w}$, and $k^* \triangleq k(w^*)$. Now note that

$$\begin{split} \frac{1}{\Gamma_{\text{gen}}(f)} &\leq \frac{\text{ALG}^*(\text{Example EC.2})}{\text{OPT}(\text{Example EC.2})} \\ &= \frac{1 + (k^* - 1) \cdot \frac{w^* - (1+f)}{w^*}}{\log(T_0) + 1} \\ &\leq \frac{1}{\log(T_0)} + \frac{(k^* - 1) \cdot \frac{w^* - (1+f)}{w^*}}{(k^* - 1)\log(w^*)} \\ &\leq \frac{1}{\log(T_0)} + \max_{a \geq 1} \frac{a - (1+f)}{a\log(a)} \\ &\leq \frac{1}{\log(T_0)} - \frac{1}{W_{-1}\left(\frac{-1}{e(1+f)}\right)} \end{split}$$

Finally, letting T_0 go to infinite finishes the proof.

EC.2.4. Proof Proposition 1

PROPOSITION 1. In the single-resource environment, for any online algorithm ALG that satisfies both scale invariance property (SI) and greedily buyback property (GB), there exists $\hat{w} \geq 1$ such that

the online algorithm ALG (i) follows canonical allocation parameterized by $\hat{w} \triangleq \left(\underline{w}^{(1)}\right)^{-1}$; and (ii) achieves competitive ratio $\frac{\hat{w}\log(\hat{w})}{\hat{w}-1-f}$ within the class of truncated weight continuum instances \mathcal{I}_{cont} .

Proof of part (i). First, we consider the case where $\underline{w}^{(1)} = 1$. In this case, by definition $y^{(1)}(w) = \mathbb{1} \{ w \leq 1 \}$. Invoking the scale invariance property (SI), $y^{(w^{\dagger})}(w) = \mathbb{1} \{ w \leq w^{\dagger} \}$, and thus the algorithm follows canonical allocation with $\hat{w} = 1$.

Now, consider the case where $\underline{w}^{(1)} < 1$. The greedily buyback property (GB) ensures that for every $w^{\dagger} \in [\underline{w}^{(1)}, 1]$,

$$y^{(1)}(w^{\dagger}) = y^{(w^{\dagger})}(w^{\dagger}) + 1 - y^{(w^{\dagger})}(\underline{w}^{(1)})$$

Plugging the scale invariance property (SI), the equation

$$y^{(1)}(w^{\dagger}) = y^{(1)}\left(\frac{w^{\dagger}}{w^{\dagger}}\right) + 1 - y^{(1)}\left(\frac{\underline{w}^{(1)}}{w^{\dagger}}\right)$$

holds for every $w^{\dagger} \in [\underline{w}^{(1)}, 1]$. Thus, considering the derivative of both hand sides with respect to w^{\dagger} , we obtain equation

$$x^{(1)}(w^{\dagger}) = \frac{\underline{w}^{(1)}}{(w^{\dagger})^2} \cdot x^{(1)} \left(\frac{\underline{w}^{(1)}}{w^{\dagger}}\right)$$

which holds for every $w^{\dagger} \in [\underline{w}^{(1)}, 1]$. This equation admits a unique form (up to a constant K) as follows,

$$\forall w \in [\underline{w}^{(1)}, 1]: \qquad x^{(1)}(w) = \frac{K}{w}$$

Plugging the boundary condition where $y^{(1)}(\underline{w}^{(1)}) = 1$ and $y^{(1)}(1) = 0$, we have $K = \frac{1}{-\log(\underline{w}^{(1)})} = \frac{1}{\log(\widehat{w})}$. Finally, invoking the scale invariance property, we have $x^{(w^{\dagger})}(w^{\dagger}) = \hat{x}(w^{\dagger})$ with $\hat{w} = \frac{1}{\underline{w}^{(1)}}$ for every $w^{\dagger} \in \mathbb{R}_+$, which finishes the proof.

EC.2.5. Proof of Theorem EC.4

THEOREM EC.4 (Adopted from Babaioff et al., 2009). In Example EC.3, for any buyback factor $f \ge 0$, the optimal competitive ratio of deterministic integral online algorithm $\Gamma_{det-int}(f)$ is at least $1 + 2f + 2\sqrt{f(1+f)}$.

Proof. Suppose an algorithm has a competitive ratio Γ less than $1 + 2f + 2\sqrt{f(1+f)}$. We have

$$\frac{w_i}{w_{i-1} - f(w_0 + w_1 + \dots + w_{i-2})} \le \Gamma$$

Let j be the first index such that left hand side is strictly smaller. Let $\rho = \frac{w_j}{\Gamma(w_{j-1} - f(w_0 + w_1 + \dots + w_{j-2}))}$. Define a new sequence $\{z_i\}_{i=0}^{\infty}$ such that $z_i = \rho w_i$ for i < j and $z_i = w_i$ otherwise. This new sequence still satisfies

$$\frac{z_i}{z_{i-1} - f(z_0 + z_1 + \dots + z_{i-2})} \le \Gamma$$

For all and *i* but for $i \leq j$ we have

$$\frac{z_i}{z_{i-1} - f(z_0 + z_1 + \dots + z_{i-2})} = \Gamma$$

Then for all positive number M one can find a sequence $\{z_i\}_{i=0}^M$ such that

$$\frac{z_n}{z_{n-1} - f(z_0 + z_1 + \dots + z_{n-2})} = \mathbf{I}$$

This means:

$$z_n = (\Gamma + 1)z_{n-1} - \Gamma(1+f)z_{n-2}$$

Solving this we get:

$$z_n = C_1 \left(\frac{\Gamma + 1 + \sqrt{(\Gamma + 1)^2 - 4\Gamma(1 + f)}}{2} \right)^n + C_2 \left(\frac{\Gamma + 1 - \sqrt{(\Gamma + 1)^2 - 4\Gamma(1 + f)}}{2} \right)^n$$

since $1 < \Gamma < 1 + 2f + 2\sqrt{f(1+f)}$ both roots are non-real complex numbers. Using the fact that $z_i \in \mathbb{R}$ we can get $\bar{C}_1 = C_2$ the equation can be rewritten as:

$$z_n = ar^n e^{in\theta} + \bar{a}r^n e^{-in\theta} = 2r^n \Re(ae^{in\theta}) = 2|a|r^n \cos(\phi + n\theta)$$

Where $0 < \theta < \pi$. Let $M > \frac{2\pi}{\theta}$ then there will be at least one positive number n < M with $(2m + \frac{1}{2})\pi < \phi + n\theta < (2m + \frac{3}{2})\pi$ which means $z_n < 0$. This contradicts our assumption about existing of an increasing sequence $\{z_i\}_{i=0}^{\infty}$.

EC.2.6. Proof of Theorem EC.5

THEOREM EC.5. In Example EC.4, for any buyback factor $f < \frac{1}{3}$, the optimal competitive ratio of deterministic integral online algorithm $\Gamma_{det-int}(f)$ is at least $\frac{2}{1-f}$.

Proof. By way of contradiction assume ALG has a competitive ratio better than Γ where $1 + 2f + 2\sqrt{f(1+f)} < \Gamma < \frac{2}{1-f}$. Then for all *i* we know

$$\frac{w_i + w_0}{w_{i-1} - f(w_0 + w_1 + \dots + w_{i-2})} \le \Gamma$$

Let l be the first index such that left hand side is strictly smaller. Let $\rho = \frac{w_l + w_0}{\Gamma(w_{l-1} - f(w_0 + w_1 + ... + w_{l-2}))}$. Define a new sequence $\{z_i\}_{i=0}^{\infty}$ such that $z_i = \rho w_i$ for i < l and $z_i = w_i$ otherwise. This new sequence still satisfies

$$\frac{z_i + z_0}{z_{i-1} - f(z_0 + z_1 + \dots + z_{i-2})} \le \Gamma$$

For all and *i* but for $i \leq l$ we have

$$\frac{z_i + z_0}{z_{i-1} - f(z_0 + z_1 + \dots + z_{i-2})} = \Gamma$$

Continuing this process for all positive number M one can find a sequence $\{z_i\}_{i=0}^M$ such that

$$\frac{z_i + z_0}{z_{i-1} - f(z_0 + z_1 + \dots + z_{i-2})} = \mathbf{I}$$

Or

$$z_i = (\Gamma + 1)z_{i-1} - \Gamma(1+f)z_{i-2}$$

Solving this we get:

$$z_{i} = C_{1} \left(\frac{\Gamma + 1 + \sqrt{(\Gamma + 1)^{2} - 4\Gamma(1 + f)}}{2} \right)^{i} + C_{2} \left(\frac{\Gamma + 1 - \sqrt{(\Gamma + 1)^{2} - 4\Gamma(1 + f)}}{2} \right)$$

Given that $\Gamma > 1 + 2f + 2\sqrt{f(1+f)}$ both roots are real and positive numbers. Looking at the first terms:

$$z_0 = C_1 + C_2$$

(\Gamma - 1)z_0 = z_1 = (C_1 + C_2) \frac{\Gamma + 1}{2} + (C_1 - C_2) \frac{\sqrt{(\Gamma + 1)^2 - 4\Gamma(1 + f)}}{2}

We can normalize the sequence by setting $z_0 = 1$. Then

$$C_1 = \frac{\Gamma - 3}{2\sqrt{(\Gamma + 1)^2 - 4\Gamma(1 + f)}} + \frac{1}{2}$$

Since $f < \frac{1}{3}$ then $\Gamma < 3$ so

$$C_1 \ge 0 \iff 1 \ge \frac{3-\Gamma}{\sqrt{(\Gamma+1)^2 - 4\Gamma(1+f)}} \iff \Gamma \ge \frac{2}{1-f}$$

Which means $C_1 < 0$ in our setting. But we know

$$z_i \ge 0 \iff C_1 + C_2 \left(\frac{\Gamma + 1 - \sqrt{(\Gamma + 1)^2 - 4\Gamma(1 + f)}}{\Gamma + 1 + \sqrt{(\Gamma + 1)^2 - 4\Gamma(1 + f)}} \right)^i \ge 0$$

Which this obviously cannot hold when $i \to \infty$.

Appendix EC.3: Implementation of Algorithm 3

Recall that Algorithm 3 is described as a continuous procedure. In this section, we present two approaches to efficiently implement it with polynomial running time.

Water-filling method. The first method utilizes the simple observation that for each online node i, Algorithm 3 is essentially increasing "water level" β_j with identical $d\beta$ for every offline node $j \in \arg \max_j w_{ij} - \beta_j$. Therefore, the continuous allocation procedure for online node i can be divided into at most m = |V| critical discrete time stamps where either (i) the set $\arg \max_j w_{ij} - \beta_j$ increases, or (ii) the termination condition, i.e., the capacity of online node i exhausts or $\beta_j \ge w_{ij}$ for all j, is satisfied. Between each pair of adjacent time stamps, we can binary search the increment $\Delta\beta$ of water level β_j for every offline node $j \in \arg \max_j w_{ij} - \beta_j$ and then compute the increment of allocation $\Delta x_j(w_{ij})$ based on $\Delta\beta$ accordingly. It is straightforward to verify that both $\Delta\beta$ and $\Delta x_j(w_{ij})$ can be computed in polynomial time.

i

Convex-programming method. In this method, we determine the fractional allocation $\{z_{ij}\}_{j \in V}$ for each online node *i* by solving the following convex program:

where $\hat{\Psi}(x) \triangleq \int_0^x \Psi(t) dt$, variable z_{ij} specifies the fractional allocation between online node i and offline node j, and $x_j(w) - \eta_j(w)$ specifies the fractional buyback of offline node j from weight w. Since allocation probability function $x_j(\cdot)$ has at most i strictly positive entries upon the arrival of online node i, it suffices to consider variable $\eta_j(\cdot)$ for those entries. Therefore, program $\mathcal{P}_{\text{Convex}}(i)$ is a convex program with a polynomial number of variables and constraints. Consequently, it can be solved in polynomial time using classic approaches such as the Frank-Wolfe algorithm, projected gradient ascent, or mirror descent.

Finally, it suffices to argue that the optimal solution $\{z_{ij}^*\}_{j \in V}$ coincides with the continuous allocation procedure described in Algorithm 3. This follows a similar argument as the one in Feng and Niazadeh (2021) where the authors introduce the convex-programming-based online algorithm for the online edge-weighted bipartite matching with free disposal under batch arrival. At a high level, by analyzing the KKT condition of program $\mathcal{P}_{\text{Convex}}(i)$, the following two claims can be shown: (i) $\{\eta_j^*(w)\}_{j \in V, w \in [0,\infty)}$ follows greedy buyback; and (ii) if $z_{ij}^* > 0$ then $w_{ij} - \beta_j^* \ge w_{ij'} - \beta_{j'}^*$ for every $j' \in V$ and $w_{ij} - \beta_j^* \ge 0$ where β_j^* and $\beta_{j'}^*$ are updated based on $\{z_{ij}^*\}_{j \in V}$. The proof of the second claim relies on the first claim, and the second claim itself implies $\{z_{ij}^*\}_{j \in V}$ coincides with the continuous allocation procedure described in Algorithm 3 as desired. For the detailed proofs of these two claims, check Lemmas 2 and 3 in Feng and Niazadeh (2021).

Appendix EC.4: Extensions EC.4.1. Randomized rounding for single resource

In this subsection, we present a lossless online rounding in the single resource environment, i.e., we show any fractional online algorithm can be converted to a randomized integral online algorithm with the same competitive ratio in this environment.

LEMMA EC.6. In the single-resource environment, any online fractional algorithm ALG with the competitive ratio Γ can be converted into a randomized integral online algorithm ALG[†] with the same competitive ratio Γ .

Proof. Fix an arbitrary online algorithm ALG and an instance I. Let $\tilde{x}(i)$ be the allocated density/fraction when online node i arrives in algorithm ALG. For any $\eta \in [0, 1]$, define function t_{η} : $\mathbb{N} \to \mathbb{R}_+$ where for every $\ell \in \mathbb{N}$, $t_{\eta}(\ell)$ is the solution t such that $\sum_{i=1}^{t-1} \tilde{x}(i) \leq \ell + \eta - 1 < \sum_{i=1}^{t} \tilde{x}(i)$.²⁵

Now we construct a randomized integral algorithm ALG^{\dagger} as follows. The algorithm samples η from [0, 1] uniformly at random and allocates the offline node to each online node $t \in \{t_{\eta}(\ell) : \ell \in \mathbb{N}\}$. Allocating to $t_{\eta}(\ell)$ the algorithm needs to buy back from $t_{\eta}(\ell-1)$.

By construction, ALG^{\dagger} is a randomized integral algorithm. ALG^{\dagger} allocates to an online node t if and only if there exists an $\ell \in \mathbb{N}$ with $\sum_{i=1}^{t-1} \tilde{x}(i) \leq \ell + \eta - 1 < \sum_{i=1}^{t} \tilde{x}(i)$. Since η is uniformly sampled, this happens with probability $\sum_{i=1}^{t} \tilde{x}(i) - \sum_{i=1}^{t-1} \tilde{x}(i) = \tilde{x}(t)$.

The only thing left to prove is that the probability of buyback is also the same.

- 1. if $\sum_{i=t}^{T} \tilde{x}(i) < 1$ none of ALG and ALG[†] will buy back online node t.
- 2. When $\sum_{i=t+1}^{T} \tilde{x}(i) > 1$ that online node is fully bought back in both cases.
- 3. In case $\sum_{i=t}^{T} \tilde{x}(i) \ge 1 \ge \sum_{i=t+1}^{T} \tilde{x}(i)$, ALG will buy back $\sum_{i=t}^{T} \tilde{x}(i) 1$ fraction of online node t and ALG[†] will buy back with probability $\frac{\sum_{i=t}^{T} \tilde{x}(i) 1}{\tilde{x}(t)}$.

Thus, the competitive ratio of the constructed randomized integral online algorithm ALG^{\dagger} is the same as algorithm ALG as desired.

Direct randomized algorithm of Badanidiyuru and Kleinberg (2009) for single resource We also investigate the connection between the randomized integral online algorithm proposed in Badanidiyuru and Kleinberg (2009) and our canonical allocation. We will show how one can start from the canonical allocation for weight-continuum instances, and through several steps transform it into a randomized integral algorithm with weakly better performance compared to the online fractional algorithm that follows the canonical allocation.

Without loss of generality assume the lowest weight arriving is greater than 1. Pick a uniform random number η from the interval [0, 1]. For all $\ell \in \mathbb{N}$ let $w_{\eta}(\ell)$ be the solution to:

$$\int_1^{w_\eta(\ell)} \hat{x}(w) dw = \eta + \ell - 2$$

Since $\hat{x}(w) = \frac{1}{w} \frac{1}{\log \hat{w}}$ it can easily be seen that $w_{\eta}(\ell) = \hat{w}^{\eta+\ell-2}$

LEMMA EC.7. Selling at $w_{\eta}(\ell)$ for all ℓ gives us the same expected allocation as the canonical allocation.

Proof. Let T_{-1} be the solution to $\int_{T_{-1}}^{T} \hat{x}(w) dw = 1$. Notice that both the canonical allocation and the new algorithm buyback the weights less than T_{-1} .

Now we just need to prove that the expected allocation are equal. Since η is uniformly distributed, the probability of selling an item in the interval $[\underline{w}, \overline{w}]$ is $\min\{\int_{\underline{w}}^{\overline{w}} \hat{x}(w)dw, 1\}$ which if less than one, is the allocated density of the canonical allocation. \Box

²⁵ If there exists no such t we let $t_n(\ell) = \infty$.

Now we present an algorithm based on this definition of $w_{\eta}(\ell)$.

Algorithm 5: Randomized Algorithm

```
input : random seed \eta
1 initialize \ell_{\max} = 0.
2 for each online node i \in U do
       Observe w_i.
3
       Find the largest \ell \in \mathbb{N} such that w_{\eta}(\ell) \leq w_i
\mathbf{4}
       if \ell > \ell_{max} then
\mathbf{5}
            Randomly sample x_i = 1 with probability \frac{w_\eta(\ell)}{w_i}, else x_i = 0.
6
            if x_i = 1 then
7
              Sell to w_i and buyback the last allocated weight if any.
8
            \ell_{\max} = \ell.
9
```

LEMMA EC.8. Algorithm 5 is as good as the canonical allocation.

Proof. Let ℓ^* be the largest integer satisfying $w_\eta(\ell^*) \leq w_{\text{max}}$. By fixing $w_\eta(\ell^*)$, the expected revenue of the algorithm is $\frac{w_\eta(\ell^*)}{w}w = w_\eta(\ell^*)^{26}$. Since $w_\eta(\ell^*)$ can be any number in the interval $\left[\frac{w_{\text{max}}}{\hat{w}}, w_{\text{max}}\right]$ the expected revenue of the algorithm is at least:

$$\int_{\frac{w_{\max}}{\hat{w}}}^{w_{\max}} w \hat{x}(w) dw$$

This is exactly equal to canonical allocation expected revenue.

On the other hand, the buyback cost of this algorithm is at most

$$f\int_{1}^{\frac{w_{\max}}{\hat{w}}}w\hat{x}(w)dw$$

Which is equal to the buyback cost of the canonical allocation. Using both of these two observations we can conclude:

$$\mathbb{E}[\mathtt{ALG}_6] \ge \int_{\frac{w_{\max}}{\hat{w}}}^{w_{\max}} w \hat{x}(w) dw - f \int_0^{\frac{w_{\max}}{\hat{w}}} w \hat{x}(w) dw = \mathbb{E}[\mathtt{ALG}_{Canonical}]$$

as desired.

REMARK EC.1. This algorithm is identical to the algorithm proposed in Badanidiyuru and Kleinberg, 2009. The only difference is that Algorithm 5 only buys back when there is a demand.

 $^{^{26}}w$ is the first online node exceeding $w_{\eta}(\ell^*)$. It is not necessarily w_{\max}

EC.4.2. Single resource with non-uniform demand and supply

Throughout the paper we assumed the offline node has capacity s = 1 and $d_i = 1$ for all i. In the following section we prove our single resource algorithm also works for the general case when s and d_i can be positive numbers other than 1. Without loss of generality, we do the normalization such that s = 1 and $d_i \leq 1$ for every online node $i \in U$.

Let K be a large positive integer. At a high-level the algorithm breaks the offline node into K infinitesimal mini nodes with capacity $\frac{1}{K}$ and run the algorithm 2 for $\lfloor Kd_i \rfloor$ of them.

Algorithm 6: Reduction from non-uniform demand to uniform demand in single-resource environment

input : integer K, algorithm ALG for single-resource environment with uniform demand

1 for each $j \in [K]$ do \lfloor initialize $\psi_j \leftarrow 0$ 3 for each online node $i \in U$ do $\begin{vmatrix} \text{for each } \lfloor Kd_i \rfloor \text{ mini nodes with smallest } \psi \text{ like } j \text{ do} \end{vmatrix}$ $\begin{vmatrix} \text{allocate to mini node } j \frac{1}{K} \text{ as much ALG will allocate if } w_{\max} \text{ was equal to } \psi_j. \end{vmatrix}$ $\begin{vmatrix} \psi_j \leftarrow \max(w_i, \psi_j). \end{vmatrix}$

PROPOSITION EC.1. Assume there is a positive ϵ such that for all *i* we have $d_i > \epsilon$, then Algorithm 6 achieves the same competitive ratio as algorithm 2.

Proof. Assume the optimal offline has allocation density function x(w).

$$\mathsf{OPT} = \sum_{w: x(w) > 0} x(w) w$$

Each of the online nodes with positive x(w) were showed to at least $\lfloor Kx(w) \rfloor$ mini nodes then from those mini nodes we get profit $\frac{1}{K} \frac{w}{cR}$. Given the priority queue nature of the allocation (Algorithm 6 line 4) these mini nodes are all different nodes.

$$\operatorname{ALG} \geq \frac{1}{K} \sum_{w:x(w)>0} \lfloor Kx(w) \rfloor \frac{w}{\operatorname{CR}} = \frac{\operatorname{OPT}}{\operatorname{CR}} - \sum_{w:x(w)>0} \frac{\{Kx(w)\}}{K} \frac{w}{\operatorname{CR}} \geq \frac{\operatorname{OPT}}{\operatorname{CR}} - \sum_{w:x(w)>0} \frac{1}{K} \frac{w}{\operatorname{CR}} = \frac{\operatorname{OPT}}{\operatorname{CR}} + \frac{$$

The second term goes to zero as $K \to \infty$.

EC.4.3. Randomized rounding in the matching environment for large inventory

In this subsection, we focus on a variant model where each offline node j has a large initial capacity (inventory) $s_j \in \mathbb{R}_+$. We present a near-optimal online rounding, i.e., we show any fractional online algorithm can be converted to a randomized integral online algorithm whose competitive ratio suffers an additional multiplicative factor $(1 - (1 + f) \cdot O(\sqrt{\log(s_{\min})/s_{\min}}))^{-1}$ where $s_{\min} \triangleq \min_{j \in V} s_j$ is the smallest initial capacity.

PROPOSITION EC.2. In the matching environment, any online fractional algorithm ALG with the competitive ratio Γ can be converted into a randomized integral online algorithm ALG[†] with competitive ratio $\frac{\Gamma}{1-(1+f)\cdot O(\sqrt{\log(s_{\min})/s_{\min}})}$.

Proof. Let $\kappa \triangleq O\left(\sqrt{\log(s_{\min})/s_{\min}}\right)$. Without loss of generality, we assume ALG always greedily buybacks, and its profit from each offline node is non-negative. We construct a randomized integral online algorithm ALG^{\dagger} following the fractional allocation decision in ALG as follows: For each online node $i \in U$, let $\{z_{ij}\}_{j \in V}$ be the fractional allocation between online node i and each offline node jin algorithm ALG. The randomized integral algorithm ALG^{\dagger} samples an offline node $j^* = j$ with probability $(1 - \kappa) \cdot z_{ij}$ for each offline node j, and $j^* = \emptyset$ otherwise. If j^* is not \emptyset , algorithm ALG^{\dagger} matches online node i with offline node j^* , and greedily buybacks (when it is necessary). Importantly, the sampled offline nodes for each online node in algorithm ALG^{\dagger} are independent.

Now we analyze the competitive ratio of algorithm ALG^{\dagger} . It suffices to show for each offline node j, the profit in algorithm ALG^{\dagger} is an $(1 - (1 + f)\kappa)$ -approximation of the profit in algorithm ALG. Fix an arbitrary offline node j. Recall that z_{ij} is the fractional allocation between online node i and each offline node j in algorithm ALG. Let \tilde{z}_{ij} be the fractional buyback between online node i and each offline node j in algorithm ALG. As a sanity check, the profit from offline node j in algorithm ALG. As a sanity check, the profit from offline node j in algorithm ALG.

$$\sum_{i \in U} w_{ij} z_{ij} - (1+f) \cdot \sum_{i \in U} w_{ij} \tilde{z}_{ij}$$

Let $\hat{U}_j \triangleq \{i \in U : z_{ij} > \tilde{z}_{ij}\}$ and $\tilde{U}_j \triangleq U \setminus \hat{U}_j$. By definition, $\sum_{j \in \hat{U}_j} z_{ij} - \tilde{z}_{ij} \leq s_j$. Moreover, since algorithm ALG greedily buybacks, we have $\sum_{j \in \hat{U}_j} z_{ij} \leq s_j + 1$

Let Z_{ij}^{\dagger} be the event that algorithm ALG^{\dagger} matches online node *i* with offline node *j*. By definition, $\mathbf{Pr}[Z_{ij}] = (1 - \kappa) \cdot z_{ij}$. Similarly, let \tilde{Z}_{ij}^{\dagger} be the event that algorithm ALG^{\dagger} buybacks offline node *j* from online node *i*. For each online node $i \in \tilde{U}_j$, it guarantees that

$$\mathbf{Pr}\left[\tilde{Z}_{ij}\right] \leq \mathbf{Pr}[Z_{ij}] = (1-\kappa) \cdot z_{ij} = (1-\kappa) \cdot \tilde{z}_{ij}$$

where the last equality holds since $i \in \tilde{U}_i$. For each online node $i \in \hat{U}_i$, it guarantees that

$$\mathbf{Pr}\Big[\tilde{Z}_{ij}\Big] \stackrel{(a)}{\leq} \mathbf{Pr}[Z_{ij}] \cdot \mathbf{Pr}\left[\sum_{i' \in \tilde{U}_j : i' \neq i} \mathbb{1}\left\{Z_{ij}\right\} \ge s_j\right]$$
$$\stackrel{(b)}{\leq} (1-\kappa) \cdot z_{ij} \cdot \kappa$$
$$= \kappa \cdot z_{ij}$$

where inequality (a) holds since both algorithm ALG and ALG[†] greedily buyback; and inequality (b) holds due to the multiplicative form of the Chernoff bound (Chernoff et al., 1952). Putting all pieces together, the profit from offline node j in algorithm ALG is

$$\sum_{i \in U} w_{ij} \mathbf{Pr} [Z_{ij}^{\dagger}] - f \cdot \sum_{i \in U} w_{ij} \mathbf{Pr} \Big[\tilde{Z}_{ij}^{\dagger} \Big]$$

$$\geq \sum_{i \in \tilde{U}_j} w_{ij} (1-\kappa) z_{ij} - (1+f) \sum_{i \in \tilde{U}_j} w_{ij} (1-\kappa) \tilde{z}_{ij} + \sum_{i \in \hat{U}_j} w_{ij} (1-\kappa) z_{ij} - (1+f) \sum_{i \in \hat{U}_j} w_{ij} \kappa z_{ij}$$

$$\geq (1 - (1+f)\kappa) \cdot \left(\sum_{i \in U} w_{ij} z_{ij} - (1+f) \cdot \sum_{i \in U} w_{ij} \tilde{z}_{ij} \right)$$

which is an $(1 - (1 + f)\kappa)$ -approximation to the profit in algorithm ALG as desired.

Appendix EC.5: Numerical Experiments

In this section we run numerical simulations on synthetic instances to measure the empirical performance of our proposed algorithms and compare them with alternative methods. We utilize the concept of a performance gap, represented as $\frac{ALG(I)}{OPT(I)}$ to measure the effectiveness of an algorithm on each problem instance *I*. This metric serves as a measure of how well the algorithm performs in comparison to the optimal solution for a given problem instance.

Experimental setup. We consider a cloud market setting in which customers who are willing to pay for the service arrive over time (online nodes) and should be matched to available servers (offline nodes). As for the offline nodes, there are 10 servers with independent qualities randomly drawn from U[0,1]. On the online side, there are 100 customers arriving over time with different willingness to pay. The willingness to pay v_i of the customers are increasing over time and its increment is drawn from U[0,1]. In particular, $v_i = \sum_{j=1}^i u_j$ where $u_j \sim U[0,1]$. We define the value on an edge to be the product of server's quality and customer's willingness to pay v_i only accepts an offline node with quality greater than $\frac{v_i}{100}$. To put it another way, $w_{ij} = 0$ if willingness to pay of the customer is greater than 100 times the quality of the offline node. Note that in such an instance, more valuable and less flexible customers arrive later in the sequence — hence it is critical for the online algorithm to protect the inventory to avoid paying large amounts of cancellation/buyback cost.

Algorithms. In the experiments, we consider 4 different algorithms.

- 1. Fractional algorithm (Algorithm 3)
- 2. Integral-Deterministic algorithm (Algorithm 4)
- 3. Greedy algorithm: An integral algorithm which allocates online node i to the offline node j with largest positive marginal profit.

$$\operatorname*{arg\,max}_{j} w_{ij} - (1+f)w_j$$



Figure EC.1 Numerical experiment results: blue and orange solid curves are the worst case guarantee of our algorithms parameterized by f for fractional and integral-deterministic algorithm respectively. The vertical lines are the 95% confidence interval and the dots are the mean for each algorithm and each f

4. Free-disposal algorithm: The algorithm which does not take into account the buyback cost. This is in fact Algorithm 3 for f = 0, which was introduced in the earlier work of Devanur et al. (2016).

Result. We generate 20 sample instances for each $f \in \{0, 0.25, ..., 3\}$ and compare the profit generated by each algorithm with the optimal offline using performance gap. We then calculate the confidence interval for these performance gaps for each f. The result of this simulation can be seen in fig. EC.1.