

# E2E Refined Dataset

Keisuke Toyama Katsuhito Sudoh Satoshi Nakamura

Nara Institute of Science and Technology, Japan

{toyama.keisuke.tb5, sudoh, s-nakamura}@is.naist.jp

## Abstract

Although the well-known MR-to-text E2E dataset has been used by many researchers, its MR-text pairs include many deletion/insertion/substitution errors. Since such errors affect the quality of MR-to-text systems, they must be fixed as much as possible. Therefore, we developed a refined dataset and some python programs that convert the original E2E dataset into a refined dataset.

## 1 Introduction

The E2E dataset (Novikova et al., 2017), which was used in the E2E NLG Challenge (Dušek et al., 2020), is a very popular dataset for natural language generation (NLG) from meaning representation (MR): MR-to-text. The dataset consists of a set of pairs of a British English sentence and a corresponding MR with eight attributes (name, eatType, food, priceRange, customer rating, area, familyFriendly, and near) in a restaurant recommendation domain (Table 1). However, some of the MR-text pairs suffer from the following errors: deletion (an MR is not reflected in the text), insertion (an MR whose value is empty appears in the text with an unintended value), and substitution (an MR value is replaced in the text) (Table 2).

To properly control the content of a sentence by MR-to-text, such incorrect data must be removed from the dataset. Although there have been some updates to the E2E dataset to rectify its errors (Dušek et al., 2019; Castro Ferreira et al., 2021), the updated datasets still include such deletion/insertion/substitution errors. The specific number of errors that we identified is shown in Table 3. In this work, we further refine the E2E dataset by additional manual annotation of the MR values. We fixed the errors in the MR-text correspondences and removed inappropriate data.

We also provided the following additional annotations:

MR	name	The Wrestlers
	eatType	restaurant
	food	Italian
	priceRange	moderate
	customer rating	(empty)
	area	city centre
	familyFriendly	yes
	near	Raja Indian Cuisine
Text	The Wrestlers is a moderately priced restaurant that serves Italian food. It is located in the city centre near Raja Indian Cuisine. Great place to bring your family.	

Table 1: Example of the E2E dataset

MR	name	The Punter
	eatType	coffee shop
	food	<b>English</b>
	priceRange	<i>moderate</i>
	customer rating	1 out of 5
	area	(empty)
	familyFriendly	yes
	near	Café Sicilia
Text	The Punter is a <i>cheap</i> family friendly coffee shop located in City Centre near Café Sicilia. 1 out of 5 customer rating.	

Table 2: Example of MR errors in the E2E dataset: `food` is deleted (“**English**”), `area` is inserted (“city centre”), and `priceRange` is replaced (“*moderate*” → “*cheap*”) in the text.

**MR order:** The order of the mentions of MR values in corresponding sentences

**Number of sentences:** The number of sentences included in the text part

**Sentence indexes:** An index of the sentences that include the corresponding MR values

Finally, the dataset consists of 40,560 examples for training, 4,489 for validation, and 4,555 for test. We named it the *E2E refined dataset*. An example from it is shown in Table 6.

## 2 Text Refinement

### 2.1 Error Correction

We corrected the following types of errors in the original E2E dataset. Some examples are shown

Error type	E2E dataset			Cleaned dataset (Dušek et al., 2019)			Enriched dataset (Castro Ferreira et al., 2021)		
	Training	Validation	Test	Training	Validation	Test	Training	Validation	Test
Deletion	10,931	1,096	1,315	23	1	1	1,262	145	89
Insertion	10,028	263	16	4,475	471	745	25,570	2,724	3,082
Substitution	9,290	794	945	5,795	616	666	4,172	413	395

Table 3: Number of MR labelling errors in each dataset

Refinement type	Text examples
Irregular MR values	The <b>Cotto</b> ranges between twenty and twenty-five pounds with a high customer rating. <b>The Portland Arms</b> serves Italian food near the riverside.
Overlap	The Golden Curry served English food, <b>is adult only</b> , is in the city centre, <b>is adult only</b> , has a customer rating of 5 out of 5 and is near the Cafe Rouge.
Indefinite article	For <b>an</b> child friendly, average coffee shop serving fast food try The Eagle, riverside near Burger King.
Typos	A kid friendly Strada has moderate price range and customer rating of 1 <b>of of</b> 5.
British English	Alimentum providing fast food less than £20 price range. It is located in city <b>center</b> .
Currency mark	Close to Yippee Noodle Bar in the city centre a French restaurant, Alimentum, has low ratings but the price is less than <b>20lb</b> .
Symbol	Browns Cambridge sells Indian food, and is kids friendly,, it is in riverside area near The Sorrento

Table 4: Examples of text refinement

in Table 4. Note that although our corrections may not be exhaustive, they will support future studies.

**Irregular MR Values:** Each attribute of an MR should have only one value or be empty. However, some MR data have two values for the `name` and `near` attributes. We removed such irrelevant data from the dataset.

**Overlaps:** We removed a phrase that appears twice in a sentence.

**Indefinite Articles:** We corrected usage mistakes in the indefinite articles of “a” and “an.”

**Typos:** We corrected over 3,700 typos in the MR values and sentences.

## 2.2 Normalization

**British English:** Since the E2E dataset is based on British English, we replaced such words with American spellings as “center”, “flavor”, “organize”, and “traveling” with “centre”, “flavour”, “organise”, and “travelling.”

**Prices:** `priceRange` is categorized into “cheap”, “moderate”, “expensive”, “lower than £20”, “£20-25”, and “more than £30” (Table 5). In that case, “£23” should be labelled as “£20-25”. However, the value of such prices as “£23”, “£22”, “£24”, and “from £20 to £25” in the sentences cannot be determined uniquely from the label “£20-25”. To avoid this issue, we replaced all of the price values that should be labelled as “£20-25”

with “£20-25”. The same idea was also applied to “lower than £20” and “more than £30” labels.

**Currency Expressions:** To simplify the expressions of currency units, we use “£20” instead of “20 pounds”, “20gbp”, “20lb”, “20 quid” and so on.

**Symbols:** We normalized such symbols as periods, commas, white spaces, etc.

**Quotation Marks:** We use single quotation marks instead of double quotations in the refined dataset.

**Capital Letters:** We fixed the capitalization errors in proper nouns and words that begin sentences.

## 3 MR Refinement

### 3.1 Label Names

We replaced “high” with “expensive” for the `priceRange` attribute. For the `food` attribute, we defined additional labels: “American”, “Canadian”, “Indian”, and “Thai”. The refined labels are listed in Table 5.

### 3.2 Labelling Errors

We manually corrected the MR labelling errors throughout the E2E dataset.

### 3.3 MR Order

We annotated the order of the mentions of the MR values in the corresponding sentences in Table 6.

Attribute	# Variations	MR values (delexicalized)
Name	1	NAME
eatType	4	(empty), coffee shop, pub, restaurant
food	11	(empty), American, Canadian, Chinese, English, fast food, French, Indian, Italian, Japanese, Thai
priceRange	7	(empty), £20-25, cheap, expensive, less than £20, moderate, more than £30
customer rating	7	(empty), 1 out of 5, 3 out of 5, 5 out of 5, average, high, low
area	3	(empty), city centre, riverside
familyFriendly	3	(empty), no, yes
near	2	(empty), NEAR

Table 5: All variations of MR values in the E2E refined dataset

	Attribute	Value	Order	Sentence index
MR	name	NAME (THE WRESTLERS)	1	1
	eatType	restaurant	3	1
	food	Italian	4	1
	priceRange	moderate	2	1
	customer rating	(empty)	0	0
	area	city centre	5	2
	familyFriendly	yes	7	3
	near	NEAR (RAJA INDIAN CUISINE)	6	2
Number of sentences	3			
Text	THE WRESTLERS is a moderately priced restaurant that serves Italian food. It is located in the city centre near RAJA INDIAN CUISINE. Great place to bring your family.			
Text (delexicalized)	NAME is a moderately priced restaurant that serves Italian food. It is located in the city centre near NEAR. Great place to bring your family.			

Table 6: Example of the E2E refined dataset: Original sample of the E2E dataset is shown in Table 1.

If the MR value is empty, the order is represented by “0”.

### 3.4 Number of Sentences

We put the number of sentences in the text part, as shown in Table 6. We simply found the number of sentences using periods (“.”) and question marks (“?”). Since the example in Table 6 shows that the text part includes three periods, we set its number of sentences to “3”.

### 3.5 Sentence Indexes

We also annotated each MR value with its appearance in the text by sentence-level indexes (Table 6). The example in Table 6 shows that the values of eatType, area, and familyFriendly appear in the first, second, and third sentences, respectively. The index is set to “0” when an MR value is empty.

## 4 Others

**Delexicalization:** Because all of the name and near values appear as-is in the sentences, we replaced such values in the text and MR values with “NAME” and “NEAR” to standardize the data. The

original values are stored to keep the original information, although the standardized forms are still useful for training MR-to-text models.

**Deduplication:** We conducted deduplication of the MR-text pairs and excluded about 1,500 pairs from the dataset.

## 5 Limitations

Although we modified the E2E dataset for the development of MR-to-text models, the following limitations remain:

- As mentioned in Section 2.1, we removed the data that had irregular MR values. However, multiple values may be allowed under different formulations of MR-to-text problems for more complex situations.
- We currently ignored referring expressions, although generally they should be allowed.
- We regard attributes other than name as modifiers of a name. However, an attribute sometimes modifies near. Our current formulation ignores such relationships.

## 6 Conclusion

We described our E2E refined dataset. We reduced the deletion/insertion/substitution errors in the original E2E dataset and refined it by correcting errors and normalizing some expressions to simplify the sentences. We also refined the annotation of the MR values and annotated the MR order, the number of sentences, and the sentence indexes as additional information. The dataset and the data conversion programs in Python are publicly available at <https://github.com/KSKTYM/E2E-refined-dataset>. We believe that this dataset will support future studies in related research fields.

## References

- Thiago Castro Ferreira, Helena Vaz, Brian Davis, and Adriana Pagano. 2021. [Enriching the E2E dataset](#). In *Proceedings of the 14th International Conference on Natural Language Generation*, pages 177–183, Aberdeen, Scotland, UK. Association for Computational Linguistics.
- Ondřej Dušek, David M. Howcroft, and Verena Rieser. 2019. [Semantic noise matters for neural natural language generation](#). In *Proc. of the 12th International Conference on Natural Language Generation*, pages 421–426, Tokyo, Japan. Association for Computational Linguistics.
- Ondřej Dušek, Jekaterina Novikova, and Verena Rieser. 2020. [Evaluating the State-of-the-Art of End-to-End Natural Language Generation: The E2E NLG Challenge](#). *Computer Speech & Language*, 59:123–156.
- Jekaterina Novikova, Ondřej Dušek, and Verena Rieser. 2017. [The E2E dataset: New challenges for end-to-end generation](#). In *Proceedings of the 18th Annual Meeting of the Special Interest Group on Discourse and Dialogue*, Saarbrücken, Germany. ArXiv:1706.09254.