# A Survey of Deep Graph Clustering: Taxonomy, Challenge, Application, and Open Resource

Yue Liu, Jun Xia, Sihang Zhou, Xihong Yang, Ke Liang, Chenchen Fan, Yan Zhuang, Stan Z. Li, *Fellow, IEEE*, Xinwang Liu<sup>†</sup>, *Senior Member, IEEE*, Kunlun He<sup>†</sup>

**Abstract**—Graph clustering, which aims to divide nodes in the graph into several distinct clusters, is a fundamental yet challenging task. Benefiting from the powerful representation capability of deep learning, deep graph clustering methods have achieved great success in recent years. However, the corresponding survey paper is relatively scarce, and it is imminent to make a summary of this field. From this motivation, we conduct a comprehensive survey of deep graph clustering. Firstly, we introduce formulaic definition, evaluation, and development in this field. Secondly, the taxonomy of deep graph clustering methods is presented based on four different criteria, including graph type, network architecture, learning paradigm, and clustering method. Thirdly, we carefully analyze the existing methods via extensive experiments and summarize the challenges and opportunities from five perspectives, including graph data quality, stability, scalability, discriminative capability, and unknown cluster number. Besides, the applications of deep graph clustering methods in six domains, including computer vision, natural language processing, recommendation systems, social network analyses, bioinformatics, and medical science, are presented. Last but not least, this paper provides open resource supports, including 1) a collection (https://github.com/yueliu1999/Awesome-Deep-Graph-Clustering) of state-of-the-art deep graph clustering methods (papers, codes, and datasets) and 2) a unified framework (https://github.com/Marigoldwu/A-Unified-Framework-for-Deep-Attribute-Graph-Clustering) of deep graph clustering. We hope this work can serve as a quick guide and help researchers overcome challenges in this vibrant field.

Index Terms—Deep Graph Clustering, Graph Neural Network, Self-Supervised Learning, Clustering Analysis.

# 1 INTRODUCTION

G Raph clustering is an important and challenging task to separate nodes of the graph into different clusters in an unsupervised manner. In recent years, benefiting from the strong representation capability of deep learning [1], especially graph neural networks (GNNs) [2], [3], [4], [5], [6], [7], [8], deep graph clustering has witnessed fruitful advances. However, unlike the deep clustering area [9], [10], [11], [12], the survey paper of deep graph clustering [13] is relatively scarce. For example, [14], [15] mainly survey the papers about community detection with deep learning. To better assist researchers in reviewing, summarizing, and planning for the future, a comprehensive survey of deep graph clustering is expected. From this motivation, we make a comprehensive survey of deep graph clustering in this paper.



Figure 1: The general pipeline of deep graph clustering.

Firstly, we demonstrate the general pipeline of deep graph clustering. As shown in Figure 1, the encoding neural network  ${\cal F}$ 

is trained in a self-supervised manner to embed the nodes into the latent space. After encoding, the clustering method C separates the node embeddings  $\mathbf{Z}$  into several disjoint clusters. The formulaic definitions and the important baselines of deep graph clustering are deliberated in Section 2.



Figure 2: The taxonomy of deep graph clustering.

Secondly, as shown in Figure 2, we contribute a structured taxonomy to provide a broad overview of this field, categorizing existing works from four perspectives: graph type, network architecture, learning paradigm, and clustering method. More specifically, the input graph type can be classified into four distinct categories: pure structure graph, attribute graph, heterogeneous graph, and dynamic graph. We analyze the characteristics of each graph type and introduce the corresponding processing methods. Besides, for the network architecture, the existing deep graph clustering methods are grouped into multi-layer perceptron-based

<sup>•</sup> Y. Liu, S. Zhou, X. Yang, K. Liang, and X. Liu are with National University of Defense Technology, Changsha, China. (E-mail: yueliu19990731@163.com). J. Xia and Stan Z. Li are with Westlake University, Hangzhou, China. C. Fan and Y. Zhuang are with Big Data Research Center, Chinese PLA General Hospital, Beijing, China.

<sup>•</sup> *†*: Corresponding author.

(MLP-based) methods, graph-neural network-based (GNN-based) methods, and hybrid methods. The benefits and drawbacks of each type are carefully discussed. Moreover, the learning paradigms are classified into reconstructive, adversarial, contrastive, and hybrid paradigms. For each learning paradigm, the general pipeline is summarized in detail. In addition, the clustering methods are separated into traditional clustering methods and neural clustering methods. The advantages and disadvantages of traditional clustering are analyzed, and the technological evolution of neural clustering is summarized in depth. We elaborate on the taxonomy of deep graph clustering in Section 3.

Despite the remarkable progress, this fast-growing field is still fraught with several crucial challenges. Therefore, we conduct comprehensive experiments to summarize and analyze the challenges of deep graph clustering. In addition, we carefully discuss the potential opportunities to solve the challenges in this field. Specifically, Figure 3 demonstrates the problems of graph data quality, stability, scalability, discriminative capability, and unknown cluster number. The detailed analysis and the potential solutions are provided in Section 4.



Figure 3: The challenges in deep graph clustering.

Moreover, in recent years, deep graph clustering methods have been successfully applied to numerous domains, such as social network analysis, recommendation systems, computer vision, natural language processing, bioinformatics, medical science, etc. The detailed information refers to Section 5. The main contributions of this paper are summarized as follows.

- We present a comprehensive survey paper in deep graph clustering domain to help researchers review, summarize, solve challenges, and plan for future.
- We design a taxonomy of recent deep graph clustering methods based on four aspects, i.e., graph type, network architecture, learning paradigm, and clustering method.
- We conduct extensive experiments to summarize the challenges in the deep graph clustering field from five perspectives, including graph data quality, stability, scalability, discriminative capability, and unknown cluster number. Besides, through the careful analyses, we provide the potential promising technical solutions.
- We share two practical open resources, including a collection of state-of-the-art deep graph clustering methods and a unified framework of deep graph clustering.

Table 1: Basic notation summary.

Notations	Meanings
$\mathcal{G}_{\mathrm{S}}$	Pure structure graph
$\mathcal{G}_{\mathrm{A}}$	Attribute graph
$\mathcal{G}_{\mathrm{H}}$	Heterogeneous graph
$\mathcal{G}_{\mathrm{D}}$	Dynamic graph
$\mathcal{V}$	Set of nodes
${\mathcal E}$	Set of edges
${\cal F}$	Encoding network
$\mathcal{C}$	Clustering method
$\mathcal{M}$	Evaluation method
$n \in \mathbb{R}$	Sample number
$d' \in \mathbb{R}$	Attribute number
$d \in \mathbb{R}$	Dimension number of learned feature
$k \in \mathbb{R}$	Cluster number
$s \in \mathbb{R}$	Clustering score
$\mathbf{y} \in \mathbb{R}^n$	Ground truth label vector
$\hat{\mathbf{y}} \in \mathbb{R}^n$	Predicted cluster-ID vector
$\mathbf{X} \in \mathbb{R}^{n  imes d'}$	Node attribute matrix
$\mathbf{A} \in \mathbb{R}^{n  imes n}$	Original adjacency matrix
$\mathbf{Z} \in \mathbb{R}^{n  imes d}$	Node embeddings
$\mathbf{C} \in \mathbb{R}^{k  imes d}$	Cluster center embeddings
$\mathbf{Q} \in \mathbb{R}^{n  imes k}$	Soft clustering assignment matrix
$\mathbf{P} \in \mathbb{R}^{n  imes k}$	High confidence clustering assignment matrix

# 2 DEEP GRAPH CLUSTERING

In this section, we first introduce the basic notation and the formulaic definition of deep graph clustering. Then the critical deep graph clustering baselines are deliberated.

#### 2.1 Notation

The basic notations in this paper are summarized in Table 1. First, we take the attribute graph as an example input of the deep graph clustering methods. Given an attribute graph  $\mathcal{G}_A = \{\mathcal{V}, \mathcal{E}, \mathbf{X}\}, \mathcal{V} = \{v_1, v_2, \ldots, v_n\}$  denotes a node set, which contains k classes of n nodes. Besides,  $\mathcal{E}$  denotes a set of edges that link nodes. In addition, each node in the graph attaches d'-dimension attributes. In matrix form,  $\mathbf{X} \in \mathbb{R}^{n \times d'}$  denotes the node attribute matrix and  $\mathbf{A} \in \mathbb{R}^{n \times n}$  denotes the adjacency matrix.  $\mathbf{y} \in \mathbb{R}^n$  denotes ground truth labels of nodes. We introduce other types of the input graph in Section 3.1.

#### 2.2 Task Definition

The target of deep graph clustering is to encode nodes in the graph with the neural networks and divide them into different clusters. Figure 1 demonstrates this process. In formulaic, the self-supervised neural network  $\mathcal{F}$  first encodes the nodes of the attribute graph  $\mathcal{G}_A$  as follows.

$$\mathbf{Z} = \mathcal{F}(\mathcal{G}_{\mathbf{A}}) = \mathcal{F}(\mathbf{X}, \mathbf{A}), \tag{1}$$

where  $\mathbf{X} \in \mathbb{R}^{n \times d'}$  denotes the node attribute matrix,  $\mathbf{A} \in \mathbb{R}^{n \times n}$ denotes the adjacency matrix, and  $\mathbf{Z} \in \mathbb{R}^{n \times d}$  denotes the learned node embeddings. Generally, the self-supervised neural network  $\mathcal{F}$  is trained with pre-text tasks like structure reconstruction, attribute reconstruction, contrastive learning, adversarial learning, etc. Details about network architecture and learning paradigm are introduced in Section 3.2 and Section 3.3, respectively. After encoding, the clustering method  $\mathcal{C}$  groups the nodes into several disjoint clusters as follows.



Figure 4: Time line of the important baselines in deep graph clustering field.

$$\hat{\mathbf{y}} = \mathcal{C}(\mathbf{Z}, k),\tag{2}$$

where k denotes the cluster number and  $\hat{\mathbf{y}} \in \mathbb{R}^n$  denotes predicted cluster-ID vector. We deliberate the details of the clustering method C in Section 3.4. After the clustering process, evaluation method  $\mathcal{M}$  tests the clustering performance with various metrics as follows.

$$s = \mathcal{M}(\mathbf{y}, \hat{\mathbf{y}}), \tag{3}$$

where  $s \in \mathbb{R}$  denotes the clustering score and  $\mathbf{y} \in \mathbb{R}^n$  denotes the ground truth label vector. In the next section, we introduce the development of deep graph clustering.

#### 2.3 Development

**Overview.** In this section, we introduce the development of deep graph clustering methods. At first, as shown in Figure 4, we summarize the essential baselines in the deep graph clustering field. These papers promote the crucial development of deep graph clustering and gradually become the milestones in this field. Additionally, these research papers have been published in influential international conferences or high-quality journals in artificial intelligence, machine learning, data mining, computer vision, multimedia, etc. In Figure 4, the important baselines are displayed according to the publish time. Besides, in order to highlight the development trend of deep graph clustering, we roughly categorize the methods into four classes according to the learning paradigm. The blue, red, yellow, and green boxes indicate the reconstructive methods, adversarial methods, contrastive methods, and other methods. We find that most of the early methods are based on the reconstructive and adversarial learning paradigms. Recently, contrastive deep graph clustering methods become popular and mainstream. Next, we introduce the development of deep graph clustering methods in detail.

**Stage I: graph clustering via deep neural networks.** At the early stage, motivated by the great success of deep learning, researchers aim to endow the graph clustering methods with strong representation capability of deep neural networks. Concretely, the pioneers [16] adopt the sparse auto-encoder [17] to learn

the non-linear node representations and then perform k-means [18] to separate the node embeddings into disjoint clusters in the GraphEncoder model. After that, DNGR [19] is developed to capture graph structural information by the random surfing model. Although verified effectiveness, the previous methods merely learn the graph structure information while ignoring the node attributes. GAE/VGAE [4] is proposed with the graph convolutional encoder [2] and a simple inner product decoder to learn both attribute and structural information. Meanwhile, to handle the heterogeneous graphs, [20] develop a deep heterogeneous graph embedding algorithm termed HNE for five downstream tasks. Motivated by GAE/VGAE [4], [21] propose MGAE to learn node representations with the graph auto-encoder and then group the nodes into clusters with the spectral clustering algorithm [22].

Stage II: introduce adversarial mechanism. Subsequently, motivated by the generative adversarial mechanism [23], several adversarial deep graph clustering methods are proposed. For example, [24], [25] propose ARGA/ARVGA by enforcing the latent representations to align a prior distribution in an adversarial learning manner. Similarly, ProGAN [26] and CommnityGAN [27] also utilize generative adversarial networks to generate proximities and optimize embeddings, respectively.

Stage III: unified framework & data fusion. Although promising performance has been achieved, [28] indicates that the previous methods are not designed for the specific clustering task. To design a clustering-directed method, [28] propose a unified framework termed DAEGC with the attention-based graph encoder and clustering alignment loss adopted in deep clustering methods [29], [30]. In the same year, [31] designed a new symmetric graph auto-encoder architecture named GALA based on the Laplacian sharpening. Besides, [32] proposes AGC model with an adaptive graph convolution to capture the clustering information in different neighbor hops. Subsequently, SDCN [33] and DFCN [34] verify the effectiveness of integrating structural information and attribute information by the delivery operator and the information fusion module, respectively. Then, to avoid the expensive costs of spectral clustering, [35] formulate a continuous relaxation of the normalized minCUT problem and optimize the clustering objective with the GNN. It is worth mentioning that some graph pooling methods [36], [37], [38] also contribute to this field. Then, O2MAC [39] and MAGCN [40] make attempts to exploit deep neural networks for attributed multi-view graph clustering via the multiple graph view reconstruction and the view-consistency information learning, respectively. Besides, a self-supervised method SGCMC [41] utilizes the clustering labels to guide the network learning, thus improving clustering performance. R-GAE [42] rethink the graph-auto-encoder-based deep graph clustering methods by considering feature randomness and feature drift. And scTAG [43] apply the graph-auto-encoder-based methods to the single-cell RNA sequencing.

**Stage IV: apply contrastive learning**. More recently, contrastive learning has become the mainstream paradigm in the domains of vision [44], [45], [46], [47], [48], [49], [50] and graph [51], [52], [53], [54], [55], [56], [57], and contrastive deep graph clustering methods are increasingly proposed. Specifically, in the AGE model, [58] first filters the high-frequency noises in node attributes and then trains the encoder by adaptively discriminating the positive and negative samples. In the same year, MVGRL [59] generates an augmented structural view and contrasts node embeddings from one view with graph embeddings of another view and vice versa. Following up, MCGC [60] and HeCo [61] extend the contrastive paradigm to multi-view clustering and heterogeneous graph learning.

Stage V: improve contrastive learning. Although the effectiveness of the contrastive learning paradigm has been verified, there are still many open technical problems. Specifically, [62] proposes GDCL to correct sampling bias in contrastive deep graph clustering. Besides, to avoid the semantic drift caused by inappropriate data augmentations, AFGRL [63] is proposed by replacing data augmentations with node discovery. Differently, Liu et al. [64] propose an augmentation-free contrastive deep graph clustering method by designing the parameter-unshared encoders. Then, to refine the noisy connections in the graph, [65] propose SUBLIME by generating the sketched graph view with unsupervised structure learning. Moreover, [66], [67] design the dual correlation reduction strategy in the DCRN model to alleviate the representation collapse problem in deep graph clustering. To further enhance the discriminative capability of networks, Liu et al. [68] guide the networks to learn the hard sample pairs. CCGC [69] propose a new positive and negative sample pairs construction method.

Stage VI: scale to large graphs & apply to more complex scenarios. However, previous methods fail to scale to the large graphs, easily leading to the out-of-memory and long running time problem. To this end, Devvrit et al. [70] scale the contrastive deep graph clustering to large-scale graphs. Additionally, Dink-Net [71] unified the representation learning and clustering optimization into an end-to-end framework on large-scale graphs via dilation and shrink cluster loss functions. Besides, Shiao et al. [72] utilize the node clustering method to accelerate graph representation learning. Besides, Sun et al. [73] rethink the graph clustering problem from a geometric perspective and introduce the heterogeneous curvature space into deep graph clustering. To adapt deep graph clustering methods to both homophily and heterophily graphs, DGCN [74] is proposed by designing the mixed graph filter and the dual encoders. And Wen et al. [75] propose a framework to match the unpaired multi-view graphs.

# 2.4 Evaluation

This section introduces the evaluation of deep graph clustering. Deep graph clustering is a purely unsupervised task. Therefore it is hard to evaluate the clustering performance of deep graph clustering methods without the ground truth. Generally, an excellent deep graph clustering algorithm can learn the clustering distribution that has small with-cluster variance and significant between-cluster variance. The mainstream metrics can be categorized into two classes [76], i.e., extrinsic metrics and intrinsic metrics. Calculating extrinsic metrics requires the ground truth while calculating the intrinsic metrics does not require labels. In the research track, researchers conduct experiments on graph data with human annotations, thus the extrinsic metrics of clustering are more common. However, in the industry scenario, labels of nodes are always scarce, therefore the intrinsic metrics are more practical.

Firstly, we introduce four extrinsic metrics, including accuracy (ACC) [77], normalized mutual information (NMI) [78], adjust rand index (ARI) [79], and F1 score. These metrics need the ground truth labels, therefore the typical pre-process operation is to map the cluster-ID to the class-ID by the Kuhn-Munkres algorithm [80]. Then the metrics can be calculated. Specifically, accuracy (ACC) is calculated as follows:

$$ACC = \sum_{i=1}^{n} \frac{\phi(y_i, \operatorname{map}(\hat{y}_i))}{n}, \qquad (4)$$

where  $\hat{y}_i$  and  $y_i$  denote the predicted cluster-ID and the ground truth label of the *i*-th sample, respectively. Besides, map( $\cdot$ ) denotes the Kuhn-Munkres algorithm [80], which maps the predicted cluster-ID to the class-ID.  $\phi(\cdot)$  is an indicator function as formulated:

$$\phi(y_i, \max(\hat{y}_i)) = \begin{cases} 1 & \text{if } y_i = \max(\hat{y}_i), \\ 0 & \text{otherwise.} \end{cases}$$
(5)

In addition, the F1-score also evaluates the clustering performance. It is a balance of precision and recall, calculated as follows.

$$F1 = 2 \cdot \frac{\text{precision} \cdot \text{recall}}{\text{precision} + \text{recall}},$$
(6)

precision = 
$$\frac{TP}{TP + FP}$$
, recall =  $\frac{TP}{TP + FN}$ , (7)

where TP, FP, and FN denote true positive samples, false positive samples, and false negative samples, respectively. Further, the calculation of Normalized Mutual Information (NMI) is based on mutual information. It is more robust to the unbalanced sample distribution. It can be formulated as follows.

$$\mathbf{NMI} = -\frac{2\sum_{\hat{y}}\sum_{y} p(\hat{y}, y) \log \frac{p(y, y)}{p(\hat{y})p(y)}}{\sum_{i} p(\hat{y}_{i}) \log(p(\hat{y}_{i})) + \sum_{j} p(y_{j}) \log(p(y_{j}))}, \quad (8)$$

where  $p(\hat{y})$ , p(y), and  $p(\hat{y}, y)$  denotes the distribution of the predicted results, distribution of the ground truth, and joint distribution of them, respectively. Differently, another metric named Adjust Rand Index (ARI) is based on the pairwise similarity between predicted labels and ground truth labels. It is formulated as follows:

$$ARI = \frac{RI - expectedRI}{\max(RI) - expectedRI},$$
(9)

where RI denote rand index [79] and expectedRI [79] denote the expected rand index. ARI equals 0 indicates real and modeled

clustering do not agree on pairing, and ARI equals 1 indicates real and modeled clustering both represent the same clusters.

Secondly, we introduce three intrinsic metrics, including Silhouette Coefficient (SC) [81], Calinski-Harabasz Index (CHI) [82], and Davies-Bouldin Index (DBI) [83]. Different from previous extrinsic metrics, the intrinsic metrics are more piratical for real-world data since they get rid of the ground truth labels. Concretely, Silhouette Coefficient (SC) can be calculated as follows.

$$SC = \frac{dis - dis'}{\max(dis, dis')},$$
(10)

where dis' denotes the average distance between the node and all other nodes in the same cluster while dis denotes the average distance between the node and all other points in the next nearest cluster. SC is intuitive and easy to understand and has a range of [-1, 1]. Additionally, Calinski-Harabasz Index can be calculated as follows.

$$b = \sum_{i=1}^{\kappa} \mathbf{m}_i (\mathbf{c}_i - \hat{\mathbf{c}}) (\mathbf{c}_i - \hat{\mathbf{c}})^{\mathrm{T}}, \qquad (11)$$

$$w = \sum_{i=1}^{k} \sum_{\mathbf{x} \in i \text{-th cluster}} (\mathbf{x} - \mathbf{c}_i) (\mathbf{x} - \mathbf{c}_i)^{\mathrm{T}}, \qquad (12)$$

$$CHI = \frac{b}{w} \times \frac{n-k}{k-1},$$
(13)

where b denotes the between-cluster dispersion, and w denotes the within-cluster dispersion. n is the number of all nodes, k is the cluster number, and  $\mathbf{m}_i$  is the number of nodes in the *i*th cluster. Besides,  $\hat{\mathbf{c}}$  denote the cluster center of all samples, and  $\mathbf{c}_i$  denote the *i*-th cluster center. CHI measures the betweencluster dispersion against within-cluster ones. The higher score indicates better clusters. Unlike CHI, Davies-Bouldin Index (DBI) can measure the cluster size against the average distance between clusters. And the lower score indicates better clusters. DBI can be calculated as follows.

$$r_{ij} = \frac{s_i + s_j}{s'_{ij}}, \text{ DBI} = \frac{1}{k} \sum_{i=1}^k \max_{i \neq j} r_{ij},$$
 (14)

where  $s_i$  denotes the average distance between each nodes in the *i*-th cluster to the *i*-th cluster center  $\mathbf{c}_i$ .  $s'_{ij}$  denotes the distance between the *i*-th cluster center  $\mathbf{c}_i$  to the *j*-th cluster center  $\mathbf{c}_j$ . In this paper, the used datasets are open benchmarks, which have the ground truth of the nodes. Therefore, we adopt four extrinsic metrics, including ACC, NMI, ARI, and F1 score in our experiments.

# 3 TAXONOMY

We contribute a structured taxonomy to provide a broad overview of this field. Concretely, this section introduces the taxonomy of deep graph clustering methods from the following four perspectives: graph type, network architecture, learning paradigm, and clustering method. The surveyed paper are categorized based these criteria in Table 2 (part I) and Table 3 (part II). Next, we present taxonomy criteria in detail.

# 3.1 Graph Type

First of all, we begin with the input of deep graph clustering. The input graphs of existing deep graph clustering methods are mainly categorized into four types. Figure 5 demonstrates the details of these four types of graphs. In what follows, we provide the detailed definitions of these graph types.



Figure 5: The demonstrations of pure structure graph  $\mathcal{G}_{S}$ , attribute graph  $\mathcal{G}_{A}$ , heterogeneous graph  $\mathcal{G}_{H}$ , and dynamic graph  $\mathcal{G}_{D}$ . The pure structure graph merely contains the connected edges between nodes. In addition, each node in the attribute graph attaches attributes. Moreover, in heterogeneous graphs, the node types and edge types are multiple. Furthermore, the nodes and edges of dynamic graphs will change over time.

# 3.1.1 Pure Structure Graph

In a pure structure graph  $\mathcal{G}_{S} = \{\mathcal{V}, \mathcal{E}\}, \mathcal{V} = \{v_{1}, v_{2}, \dots, v_{n}\}$  denotes the node set, which contain n nodes of k categories. Besides,  $\mathcal{E}$  denotes the edge set, which contains l edges. With the matrix form, the pure structure graph can be represented by the adjacency matrix  $\mathbf{A} \in \mathbb{R}^{n \times n}$ . Here,  $a_{ij} = 1$  indicates that *i*-th node is linked to *j*-th node while  $a_{ij} = 0$  indicates that *i*-th node is not linked to *j*-th node in the graph.

#### 3.1.2 Attribute Graph

Compared with the pure structure graph  $\mathcal{G}_S$ , the attribute graph  $\mathcal{G}_A = \{\mathcal{V}, \mathcal{E}, \mathbf{X}\}$  is more complex. Specifically, each node in  $\mathcal{G}_A$  attaches the *d'*-dimension attributes.  $\mathbf{X} \in \mathbb{R}^{n \times d'}$  is denoted as the node attribute matrix, where *d'* is the dimension number of node attributes. In the matrix form,  $\mathcal{G}_A$  is represented by the adjacency matrix  $\mathbf{A} \in \mathbb{R}^{n \times n}$  and node attribute matrix  $\mathbf{X}$ .

#### 3.1.3 Heterogeneous Graph

The heterogeneous graph at least contains more than one type of node or more than one type of edge. Formally, we first denote the type number of nodes and edges as  $T_n$  and  $T_e$ . Then a heterogeneous graph  $\mathcal{G}_H$  satisfies  $T_n + T_e > 2$ , i.e., it contains multiple types of nodes or/and multiple types of edges. Otherwise, the graph is homogeneous.

# 3.1.4 Dynamic Graph

Different from the static graph, the dynamic graph  $\mathcal{G}_{\rm D} = \{\mathcal{G}_{\rm D}^{(1)}, ..., \mathcal{G}_{\rm D}^{(t)}, ..., \mathcal{G}_{\rm D}^{(T)}\}$  will dynamically change over time, where *t* denotes the time step. The changes in dynamic graphs include changing the linkages between nodes, adding or deleting nodes, modifying the node features, etc.

#### 3.1.5 Processing Techniques

The first type of graph, the pure structure graph, is relatively easy to process since it merely contains structural information. For example, in early works, [16] encodes the structural embeddings

Table 2: Taxonomy table of deep g	graph clustering	methods: part I	. The criteria	contain four	aspects: g	graph type,	network	architecture
learning paradigm, and clustering r	method.							

Methods	Graph Type	Network Architecture	Learning Paradigm	Clustering Method
GraphEncoder [16]	Pure Structure Graph	MLP	Reconstructive	Traditional Clustering
DNGR [19]	Pure Structure Graph	MLP	Reconstructive	Traditional Clustering
CommunityGAN [27]	Pure Structure Graph	MLP	Adversarial	Neural Clustering
NetVAE [84]	Attribute Graph	MLP	Reconstructive	Traditional Clustering
DGCN [74]	Attribute Graph	MLP	Reconstructive	Neural Clustering
GRACE [85]	Attribute Graph	MLP	Reconstructive	Neural Clustering
ProGAN [26]	Attribute Graph	MLP	Adversarial	Traditional Clustering
AGE [58]	Attribute Graph	MLP	Contrastive	Traditional Clustering
SCGC [64]	Attribute Graph	MLP	Contrastive	Traditional Clustering
CCGC [69]	Attribute Graph	MLP	Contrastive	Traditional Clustering
HSAN [68]	Attribute Graph	MLP	Contrastive	Traditional Clustering
RGC [86]	Attribute Graph	MLP	Contrastive	Traditional Clustering
CONVERT [87]	Attribute Graph	MLP	Contrastive	Traditional Clustering
GCC-LDA [88]	Attribute Graph	MLP	Contrastive	Traditional Clustering
GALA [31]	Attribute Graph	GNN	Reconstructive	Traditional Clustering
MGAE [21]	Attribute Graph	GNN	Reconstructive	Traditional Clustering
CGCN [89]	Attribute Graph	GNN	Reconstructive	Traditional Clustering
GCLN [90]	Attribute Graph	GNN	Reconstructive	Traditional Clustering
AHGAE [91]	Attribute Graph	GNN	Reconstructive	Traditional Clustering
RWR-GAE [92]	Attribute Graph	GNN	Reconstructive	Traditional Clustering
EGAE [93]	Attribute Graph	GNN	Reconstructive	Traditional Clustering
DGCSF [94]	Attribute Graph	GNN	Reconstructive	Traditional Clustering
DAEGC [28]	Attribute Graph	GNN	Reconstructive	Neural Clustering
DGVAE [95]	Attribute Graph	GNN	Reconstructive	Neural Clustering
CDRS [96]	Attribute Graph	GNN	Reconstructive	Neural Clustering
GCC [97]	Attribute Graph	GNN	Reconstructive	Neural Clustering
GC-SEE [98]	Attribute Graph	GNN	Reconstructive	Neural Clustering
FT-VGAE [99]	Attribute Graph	GNN	Reconstructive	Neural Clustering
scTAG [43]	Attribute Graph	GNN	Reconstructive	Neural Clustering
GC-VAE [100]	Attribute Graph	GNN	Reconstructive	Neural Clustering
DNENC [101]	Attribute Graph	GNN	Reconstructive	Neural Clustering
JANE [102]	Attribute Graph	GNN	Adversarial	Traditional Clustering
SAIL [103]	Attribute Graph	GNN	Contrastive	Traditional Clustering
AFGRL [63]	Attribute Graph	GNN	Contrastive	Traditional Clustering
S <sup>3</sup> GC [70]	Attribute Graph	GNN	Contrastive	Traditional Clustering
CONGREGATE [73]	Attribute Graph	GNN	Contrastive	Traditional Clustering
SCAGC [104]	Attribute Graph	GNN	Contrastive	Neural Clustering
CommDGI [105]	Attribute Graph	GNN	Contrastive	Neural Clustering
CARL-G [72]	Attribute Graph	GNN	Contrastive	Neural Clustering

with the sparse auto-encoders [17]. Besides, [19] apply random surfing in the graph and embed the graph structure with the stacked denoising auto-encoder. For attribute graphs, the additional attribute information always brings more process operations and performance improvement. For instance, [21] integrates the attributes and the graph structure with the graph convolutional operation [2]. Also, [33] transfers the attribute embeddings to the GCN layer with the delivery operator. Moreover, [34], [111] demonstrate the effectiveness of the attribute-structure fusion mechanism. The heterogeneous graph is more complex since it may contain different types of nodes and edges. To handle these graphs, [61] adopts the meta-path technology while [39] treats them as multi-view graphs. Different from the aforementioned static graphs, dynamic graphs change over time, increasing the difficulty of clustering. To solve this problem, [120] performs graph clustering in an incremental learning fashion. [118] adopt the variant of gated recurrent unit (GRU) [121] to capture the temporal information. Liu et al. [119] present a general framework for temporal deep graph clustering and [122] collect several datasets for temporal deep graph clustering.

#### 3.2 Network Architecture

For the network architecture, the mainstream deep graph clustering methods can roughly be categorized into three classes: MLP-based method, GNN-based method, and hybrid methods.

6

#### 3.2.1 MLP-based Methods

The MLP-based methods utilize the multi-layer perceptrons (MLPs) [123] to exact the informative features in the graphs. For example, GraphEncoder [16] and DNGR [19] encode the graph structure with the auto-encoders. Subsequently, in ProGAN [26] and CommunityGAN [27], the authors adopt MLPs to design the generative adversarial networks. Moreover, based on MLPs, AGE [58] and SCGC [64] design the adaptive encoder and the parameter un-shared encoders to embed the smoothed node features into the latent space. Although the effectiveness of these methods has been demonstrated, it is difficult for MLPs to capture non-euclidean structural information in graphs. Thus, GNN-based methods have been increasingly proposed in recent years.

Table 3: Taxonomy table of deep graph clustering methods: part II. The criteria contain four aspects: graph type, network architecture, learning paradigm, and clustering method.

Methods	Graph Type	Network Architecture	Learning Paradigm	Clustering Method
AGAE [106]	Attribute Graph	GNN	Reconstructive+Adversarial	Traditional Clustering
ARGA [25]	Attribute Graph	GNN	Reconstructive+Adversarial	Traditional Clustering
WARGA [107]	Attribute Graph	GNN	Reconstructive+Adversarial	Traditional Clustering
GCI [108]	Attribute Graph	GNN	Reconstructive+Adversarial	Traditional Clustering
NCAGC [109]	Attribute Graph	GNN	Reconstructive+Contrastive	Neural Clustering
GEC-CSD [110]	Attribute Graph	GNN	Reconstructive+Adversarial	Neural Clustering
SDCN [33]	Attribute Graph	MLP+GNN	Reconstructive	Neural Clustering
DFCN [34]	Attribute Graph	MLP+GNN	Reconstructive	Neural Clustering
AGCN [111]	Attribute Graph	MLP+GNN	Reconstructive	Neural Clustering
R-GAE [42]	Attribute Graph	MLP+GNN	Reconstructive	Neural Clustering
DAGC [112]	Attribute Graph	MLP+GNN	Reconstructive	Neural Clustering
MVGRL [59]	Attribute Graph	MLP+GNN	Contrastive	Traditional Clustering
SUBLIME [65]	Attribute Graph	MLP+GNN	Contrastive	Traditional Clustering
GDCL [62]	Attribute Graph	MLP+GNN	Contrastive	Neural Clustering
Dink-Net [71]	Attribute Graph	MLP+GNN	Contrastive	Neural Clustering
SELENE [113]	Attribute Graph	MLP+GNN	Reconstructive+Contrastive	Traditional Clustering
DCRN [66]	Attribute Graph	MLP+GNN	Reconstructive+Contrastive	Neural Clustering
IDCRN [67]	Attribute Graph	MLP+GNN	Reconstructive+Contrastive	Neural Clustering
SCGC [114]	Attribute Graph	MLP+GNN	Reconstructive+Contrastive	Neural Clustering
AGC-DRR [115]	Attribute Graph	MLP+GNN	Adversarial+Contrastive	Neural Clustering
DMGC [116]	Heterogeneous Graph	MLP	Reconstructive	Traditional Clustering
MAGCN [40]	Heterogeneous Graph	GNN	Reconstructive	Neural Clustering
O2MAC [39]	Heterogeneous Graph	GNN	Reconstructive	Neural Clustering
HeCo [61]	Heterogeneous Graph	GNN	Contrastive	Traditional Clustering
SGCMC [41]	Heterogeneous Graph	GNN	Reconstructive+Contrastive	Neural Clustering
VaCA-HINE [117]	Heterogeneous Graph	GNN	Reconstructive+Contrastive	Traditional Clustering
HNE [20]	Heterogeneous Graph	MLP+CNN	Reconstructive	Traditional Clustering
VGRGMM [118]	Dynamic Graph	GNN	Reconstructive	Traditional Clustering
TGC [119]	Dynamic Graph	MLP	Reconstructive	Neural Clustering
CGC [120]	Dynamic Graph	GNN	Contrastive	Traditional Clustering

# 3.2.2 GNN-based Methods

The GNN-based methods model the non-euclidean graph data with the GNN encoders like graph convolutional network [2], graph attention network [3], graph auto-encoder [4], etc. Benefiting from the strong graph structure representation capability, GNN-based methods have achieved promising performance. For instance, MGAE [21] is proposed to learn the node attribute and graph structure with the designed graph auto-encoder. In addition, [31] design a novel symmetric graph auto-encoder named GALA. Furthermore, the GNNs are also applied to the heterogeneous graphs in O2MAC [39], MAGCN [40], SGCMC [41], and HeCo [61]. However, the entanglement of transformation and propagation in GNNs will incur heavy computational overhead. Thus, SCGC [64] is proposed to improve the efficiency and scalability of the existing deep graph clustering methods by decoupling these two operations.

# 3.2.3 Hybrid Methods

More recently, some researchers have considered integrating the advantages of both MLP-based and GNN-based methods. Concretely, [33] transfers the embeddings from the auto-encoder to the GCN layer with a designed delivery operator. In addition, AGCN [111] and DFCN [34] demonstrate the effectiveness of the fusion of the node attribute feature and the topological graph feature with the combination of auto-encoder and GCN. Moreover, some contrastive deep graph clustering methods [59], [62], [65], [66], [69], [87], [88], [115] also adopt the hybrid architecture of MLPs and GNNs as the backbones.

#### 3.3 Learning paradigm

Based on the learning paradigm, the surveyed methods contain four categories: reconstructive methods, adversarial methods, contrastive methods, and hybrid methods. Taking the attribute graph as the input graph, we elaborate on these learning paradigms of deep graph clustering methods as follows.



Figure 6: The general pipeline of the reconstructive deep graph clustering methods. Firstly, the nodes of the input graph are encoded into the node embeddings  $\mathbf{Z}$  via a designed Encoder. Subsequently, with the reconstruction pre-text tasks like attribute reconstruction or link reconstruction, the decoder aims to recover the graph information from the learned embeddings  $\mathbf{Z}$ . Eventually, in the latent space, the clustering method  $\mathcal{C}$  groups the nodes into different clusters.

#### 3.3.1 Reconstructive Methods

The core idea of the reconstructive methods is forcing the network to encode the features in the graph and then recovering (part of) the graph information from the learned embeddings. Thus, the reconstructive methods focus on the intra-data information in the graph and adopt the node attributes and graph structure as the self-supervision signals. The general pipeline of reconstructive deep graph clustering methods is illustrated in Figure 6. The core designs of the reconstructive methods are the encoder architecture, decoder architecture, and reconstructed objective functions. Researchers improve reconstructive methods from these perspectives.

#### 3.3.2 Adversarial Methods

The adversarial deep graph clustering methods aim to improve the quality of features by creating a zero-sum game between the generator and the discriminator. Specifically, the discriminator is trained to recognize whether learned features are from the real data distribution, while the generator aims to generate confusing embeddings to cheat the discriminator. In these settings, the generation and discrimination operations provide effective selfsupervision signals, guiding the network to learn high-quality embeddings. Figure 7 demonstrates the general pipeline of the adversarial deep graph clustering methods. The core technologies determining the quality of adversarial methods contain generator designs, discriminator designs, noise generation, and discriminative loss functions. Several works aim to improve the performance of adversarial methods from these aspects.



Figure 7: The general pipeline of adversarial deep graph clustering. Firstly, the Generator aims to generate high-quality node embeddings  $\mathbf{Z}$  from the input graph. Subsequently, the Discriminator is trained to distinguish the fake information and the learned features. After the self-supervised training, the clustering method C separates the learned node embeddings into several clusters.

#### 3.3.3 Contrastive Methods

The critical idea in contrastive deep graph clustering methods is to improve the discriminativeness of features by pulling together the positive samples while pushing away the negative ones. Thus, contrastive methods focus on the inter-data information and construct the self-supervision signals via meaningful relationships between samples. The general pipeline of contrastive methods can be found in Figure 8. The main techniques in contrastive methods include graph data augmentations, siamese encoder designs, positive and negative sample pair construction, negative sampling, counteractive learning loss functions, etc. These aspects are carefully modified to enhance the discriminative capability of contrastive learning methods.

# 3.3.4 Hybrid Methods

In recent years, some papers have demonstrated the effectiveness of combining different learning paradigms. For example, in ARGA [25], Pan et al. adopt both the reconstructive and adversarial



Figure 8: The general pipeline of contrastive deep graph clustering methods. At first, the augmented graph is generated via data augmentations, and nodes are embedded into the latent space by the encoders. Subsequently, the networks are guided to pull together positive samples and push away negative samples. Finally, the node embeddings from different views are fused and grouped into distinct clusters via the clustering method C.

learning paradigms. Besides, researchers [41], [66] also verified the effectiveness of the combination of reconstructive and contrastive learning paradigms. Moreover, in AGC-DRR [115], the researchers show that an adversarial mechanism is a new option for data augmentation in contrastive learning. How to better optimize multiple self-supervised tasks and make them cooperate with each other is another crucial research topic [124], [125].

# 3.4 Clustering Method

The clustering methods in deep graph clustering aim to separate the learned node embeddings into different clusters in a purely unsupervised manner. They roughly can be categorized into two classes: traditional clustering and neural clustering.

### 3.4.1 Traditional Clustering

The traditional clustering methods [18], [22], [126], [127], [128], [129] can be directly performed on the learned node embeddings to group them into disjoint clusters in many early deep graph clustering methods [16], [19], [21], [25], [31], [58], [59], [106]. Although they efficiently achieve promising performance, the traditional clustering methods have two drawbacks as follows: 1) First, the clustering process can not benefit from the strong representation capability of deep neural networks, thus limiting the discriminative capability of the samples. 2) Second, in these methods, the node representation learning and the clustering learning cannot be jointly optimized in an end-to-end manner, therefore leading to sub-optimal performance. 3) These methods are not easy to adopt batch training and batch inference techniques, limiting the model scalability on large graphs.

#### 3.4.2 Neural Clustering

To alleviate the aforementioned issues of traditional clustering methods, the neural clustering methods are designed to group the samples into different clusters with deep neural networks. Concretely, in the neural clustering methods, the clustering process and the deep neural network are jointly optimized by the gradient descent algorithms [130], [131].

For example, in many two-stage neural clustering methods [28], [33], [34], [39], [40], [62], [66], [96], [111], a widely-used



Figure 9: The clustering distribution alignment loss  $\mathcal{L}_{KL}$  in the neural clustering methods. In the first step, the graph encoder  $\mathcal{F}$  is trained in a self-supervised manner. Then, the clustering method obtains the initial clustering distribution  $\mathbf{Q}$ . In the second step, the model sharpens the clustering distribution  $\mathbf{Q}$  and gains the sharpened distribution  $\mathbf{P}$ , which represents a clustering distribution with more confidence. The model will be fine-tuned by aligning the original distribution and sharpened distribution via the KL divergence loss function.

clustering distribution alignment loss is introduced to network optimization as shown in Figure 9. Specifically, in the first stage, these methods pre-train the encoders  $\mathcal{F}$  in a self-supervised manner. After that, they initialize the cluster center embeddings  $\mathbf{C} \in \mathbb{R}^{k \times d}$  by the traditional clustering algorithms on the learned node embeddings  $\mathbf{Z} \in \mathbb{R}^{n \times d}$ , where n, k, and d denotes the node number, cluster number, latent feature dimension, respectively. Note that the cluster center embeddings  $\mathbf{C}$  are set to the learnable parameters of the deep neural networks, i.e., the tensors with gradients. In the second stage, a soft assignment between the node embeddings  $\mathbf{Z}$  and the cluster center embeddings  $\mathbf{C}$  is calculated as formulated:

$$Q_{ij} = \frac{(1 + \|\mathbf{z}_i - \mathbf{c}_j\|^2 / \alpha)^{-\frac{\alpha+1}{2}}}{\sum_{j'} (1 + \|\mathbf{z}_i - \mathbf{c}_j\|^2 / \alpha)^{-\frac{\alpha+1}{2}}}.$$
 (15)

Here, the similarity between *i*-th node embedding  $\mathbf{z}_i$  and *j*-th cluster center embedding  $\mathbf{c}_j$  is measured by the Student's *t*-distribution kernel.  $\alpha$  is the freedom degree of Student's *t*-distribution.  $Q_{ij}$  can be considered as the probability of assigning *i*-th node to *j*-th cluster, namely a soft assignment. Subsequently, the clustering distribution is promoted by aligning the soft assignment  $Q_{ij}$  with the high confidence assignments  $P_{ij}$  as follows.

$$\mathcal{L}_{\text{KL}} = \text{KL}(P||Q) = \sum_{i} \sum_{j} P_{ij} \log(\frac{P_{ij}}{Q_{ij}}), \quad (16)$$

where the high confidence (target) assignments  $P_{ij}$  can be calculated by first raising  $Q_{ij}$  to the second pow and then normalizing by the frequency per cluster as formulated:

$$P_{ij} = \frac{Q_{ij}^2 / \sum_i Q_{ij}}{\sum_{j'} Q_{ij'}^2 / \sum_i Q_{ij'}}.$$
(17)

Here, the distribution  $\mathbf{P}$  is considered the sharpened clustering distribution, which contains more high-confidence clustering information. By aligning the original clustering distribution  $\mathbf{Q}$  and sharpened clustering distribution  $\mathbf{P}$ , the clusters are iteratively refined, therefore improving clustering performance.

Similarly, in other two-stage neural clustering methods [41], [62], [67], [96], [104], the high confidence clustering pseudo labels are adopted as the supervision signal for better clustering as



Figure 10: The clustering pseudo label technology in the neural clustering methods. In the first step, the encoder  $\mathcal{F}$  is trained by the self-supervised pre-text tasks to obtain the discriminative node embeddings  $\mathbf{Z}$ . Then the clustering method  $\mathcal{C}$  is performed on the learned node embeddings. In the second step, high-confidence samples are selected as the pseudo labels. These pseudo labels serve as the supervision signal to further fine-tune the encoder  $\mathcal{F}$ .

shown in Figure 10. For instance, in GDCL, [62] debias the false negative sampling of contrastive learning with the pseudo clustering labels. Besides, [104] proposes SCAGC to maximize the similarities of intra-cluster nodes while minimizing the similarities of inter-cluster nodes. Moreover, in IDCRN, [67] utilizes the high confidence pseudo labels to refine the adjacency matrix and guide the learned embeddings to recover the affinity matrix even across views. In addition, [41] design a cross-entropy based objective function to guide the network to classify the clustering pseudo labels in the SGCMC model. Furthermore, [96] collaborates the pseudo node classification task with clustering and augments a pseudo-label set to further improve the clustering performance.

Although previous methods achieve promising performance, the scalability of the KL divergence loss and pseudo-label promoting is limited. We analyze the complexity of the KL divergence loss in Eq. (16) as follows. This KL divergence loss function optimizes the clustering distribution with the whole data, therefore leading to high time and space costs. The time complexity and space complexity of calculating the KL divergence loss is O(nkd)and  $\mathcal{O}(nk + nd + kd)$ , where n denotes the node number, k denotes the cluster number and d denotes the dimension number of latent features. On the large graphs, the node number n becomes very large, e.g., 111 million nodes on ogbn-papers100M [132]. Therefore the KL divergence loss easily leads to the out-ofmemory error or the long running time problem. To alleviate these problems, Dink-Net [71] is proposed by the idea of cluster dilation and cluster shrink. Concretely, the graph encoders are first pretrained with a discriminative pre-text task. Then the cluster centers are initialized on the learned node embeddings in the k-means++ manner [18]. Note that these cluster centers are assigned as the tensors with gradient, thus can be optimized with gradient descent algorithms [130], [131]. Furthermore, the clustering distribution is optimized by minimizing the cluster dilation and cluster shrink loss functions as follows.

$$\mathcal{L}_{\text{dilation}} = \frac{-1}{(k-1)k} \sum_{i=1}^{k} \sum_{j=1, j \neq i}^{k} \|\mathbf{c}_{i} - \mathbf{c}_{j}\|^{2}, \qquad (18)$$

$$\mathcal{L}_{\text{shrink}} = \frac{1}{bk} \sum_{i=1}^{b} \sum_{j=1}^{k} \|\mathbf{z}_{i} - \mathbf{c}_{j}\|^{2}, \qquad (19)$$

Table 4: The statistical information of eleven attribute graph datasets. "# Nodes" denotes the number of nodes, "# Edges" denotes the number of edges, "# Feature Dims" denotes the feature dimension number, and "# Classes" denotes the number of categories.

Dataset	# Nodes	# Edges	# Feature Dims	# Classes
BAT	131	81	1,038	4
EAT	399	203	5,994	4
UAT	1,190	239	13,599	4
Cora	2,708	5,278	1,433	7
CoraFull	19,793	63,421	8,710	70
CiteSeer	3,327	4,614	3,703	6
ACM	3,025	1,870	13,128	3
DBLP	4,057	334	3,528	4
Amazon-Photo	7,650	119,081	745	8
ogbn-arxiv	169,343	1,166,243	128	40
Reddit	232,965	23,213,838	602	41
ogbn-products	2,449,029	61,859,140	100	47
ogbn-papers100M	111,059,956	1,615,685,872	128	172

$$\mathcal{L}_{\text{Dink-Net}} = \mathcal{L}_{\text{dilation}} + \mathcal{L}_{\text{shrink}},\tag{20}$$

where the first term  $\mathcal{L}_{dilation}$  denotes the cluster dilation loss, and the second term  $\mathcal{L}_{shrink}$  denotes the cluster shrink loss. Besides,  $\mathbf{Z} \in \mathbb{R}^{n \times d}, \mathbf{C} \in \mathbb{R}^{k,d}, n, k, b, d$  denotes the node embeddings, cluster center embeddings, node number, cluster number, and hidden feature dimension. In Eq. 18, the cluster dilation loss aims to learn the network to push away different cluster centers. In addition, in Eq. 19, the cluster shrink loss aims to pull the samples to the cluster centers. Note that the cluster shrink loss pulls batch samples to the cluster centers and easily scales to large graphs. Besides, each sample will be pulled to all cluster centers rather than the corresponding nearest cluster centers. The authors claim this design alleviates the confirmation bias problem [133]. The time complexity and space complexity of calculating  $\mathcal{L}_{\text{Dink-Net}}$  is  $\mathcal{O}(bkd + k^2d + bd)$  and  $\mathcal{O}(bk + bd + kd)$ , respectively.

Although verified effective, the two-stage neural clustering methods heavily depend on the excellent initialization of cluster centers. And the precise cluster center initialization relies on the promising network pre-training and the auxiliary of traditional clustering methods like k-Means, leading to high training and deployment costs. To overcome this shortcoming, many onestage methods [64], [97], [115] have been gradually proposed recently. For example, [64] proposes a new method termed SCGC with Laplacian smoothing and neighborhood-orient contrastive learning. Besides, in AGC-DRR [115], the clustering sub-network is developed to directly predict the probabilities of cluster-ID for each sample. Moreover, rather than dealing with clustering as a downstream task, [97] proposes a unified framework termed GCC by minimizing the difference between node embeddings and reconstructed cluster embeddings. The one-stage neural clustering will be a promising future direction. In the next section, we analyze and summarize the technical challenges and opportunities in the deep graph clustering field in detail.

# 4 CHALLENGE & OPPORTUNITY

In recent years, we have witnessed the fast growth of deep graph clustering. More and more methods have been proposed and achieved promising performance. However, most methods are under some perfect assumption, and there are still many challenges in the field of deep graph clustering. From this motivation, this section aims to summarize the main technical challenges. As shown in Figure 3, the main challenges in deep graph clustering contain five aspects, i.e., graph data quality, stability, scalability, discriminative capability, and unknown cluster number. In the following five sub-sections, we will analyze these challenges via experiments and provide potential solutions and opportunities.

# 4.1 Graph Data Quality

The existing conventional deep graph clustering methods always are under the assumption that the input graphs are perfectly correct, namely, the connections between nodes are complete and correct and the node information is also complete and precise. However, these assumptions do not always hold, especially in the industrial scenario. The real-world graph data are always of low quality. The noises come from two aspects, i.e., nodes and edges. Firstly, for the nodes in graphs, the node attributes may contain error information or incomplete information. To be specific, for the error information, they are caused by error records and easily spreads in the whole graph during the message-passing process. In addition, incomplete information contains two types, i.e., partly attribute missing and completely attribute missing. The latter one is more difficult to process. Secondly, for the edges in graphs, they may also contain the error information and incomplete information. Concretely, the error information denotes the error connections between nodes, while the incomplete information denotes the missing edges, which should exist in the correct graph. Besides, the conventional graph convolutional network encoders [2], [134] are based on the homophily assumption [135], i.e., the connected nodes contain similar semantics. However, in the realworld scenario, the connected nodes may not have similar features. For example, in the heterophily graphs [136] such as fraudulent networks, the hackers and regular users will construct dense connections, but they do not share similar underlying semantics.

To verify this challenge in deep graph clustering, we conduct experiments on one of the representative state-of-the-art methods, HSAN [68], on five datasets, including Cora, CiteSeer, BAT, EAT, and UAT. The detailed information of the datasets can be found in Table 4. The experimental results are demonstrated in Table 5 and Table 6.

In Table 5, we evaluate the clustering performance of HSAN [68] with missing data. The missing information contains node attributes and edges. And the drop rates are set to 10%, 30%, 50%, 70%, and 90%, respectively. From the experimental results, three conclusions are drawn. Firstly, when the information on graphs is missing, the deep graph clustering method can not achieve promising performance. Secondly, the clustering performance drops when the drop rate increases. Thirdly, the node attributes are more critical to the clustering performance on some citation graphs, such as the CiteSeer dataset, while the edges are more critical to the clustering performance on some airport activity graphs, such as the BAT dataset.

In addition, in Table 6, the performance of HSAN [68] with noisy information is tested. Similarly, the noised information contains the noised node attribute and noised edges. Concretely, for the node attributes, we add the Gaussian noises to them, and the standard deviations are set to 0.01, 0.1, 1, and 10, respectively. Besides, for the edges in the graph, we add the Gaussian noises to the adjacency matrix, and the standard deviations are set to 0.01, 0.1, 1, and 10, respectively. We have two conclusions from the experimental results. Firstly, the noises in attributes and edges limit the clustering performance. Secondly, when the noise rate increases, the performance drops significantly.

Table 5: Graph data quality testing experiments. Clustering performance of HSAN [68] on five datasets with missing information including dropped node attributes and dropped edges. Experimental results are the mean value of ten runs.

		Onicin		Attrik	oute Droj	o Rate		Edg	ge Drop I	Rate		
		Origin	10%	30%	50%	70%	90%	10%	30%	50%	70%	90%
	ACC	77.73	75.22	74.00	68.07	63.74	46.16	77.13	75.00	71.53	62.96	48.81
Como	NMI	59.45	57.93	54.73	48.26	40.62	21.21	59.55	56.74	51.69	42.54	29.54
Cora	ARI	57.62	54.76	51.72	42.05	36.01	16.42	58.03	53.81	47.31	38.10	18.98
	F1	76.16	73.70	72.78	67.72	62.91	45.39	74.97	72.09	68.48	59.34	47.12
	ACC	71.36	69.64	64.52	62.26	51.21	36.13	70.83	67.66	62.48	53.64	55.06
CitoSoor	NMI	45.03	42.01	35.56	32.33	19.83	8.66	44.53	42.12	35.30	26.80	27.50
CheSeer	ARI	46.81	43.94	36.19	32.23	19.74	8.02	45.95	38.75	31.38	22.38	23.50
	F1	63.63	62.25	56.98	54.09	45.08	28.75	63.44	59.53	56.06	49.59	48.84
	ACC	77.86	77.61	75.32	74.30	76.08	70.74	65.90	56.74	49.87	48.35	51.15
DAT	NMI	53.00	53.34	50.19	49.40	50.96	45.29	41.70	30.36	22.33	24.82	22.75
DAI	ARI	51.16	51.26	47.42	46.25	48.61	42.26	36.32	23.94	15.40	15.42	17.09
	F1	77.80	77.48	75.15	74.02	75.85	69.40	62.71	53.10	45.43	43.00	50.50
	ACC	57.73	57.73	58.15	58.06	57.39	55.97	55.22	52.88	47.70	44.78	45.36
FAT	NMI	34.12	34.35	34.86	33.83	33.00	31.73	33.10	29.38	22.26	16.79	17.88
LAI	ARI	27.22	27.37	28.17	27.33	26.99	25.58	26.16	22.89	15.57	11.40	13.69
	F1	58.09	57.98	58.31	58.21	57.20	55.85	51.02	47.87	45.79	44.43	43.42
	ACC	56.16	56.89	55.18	55.29	54.45	55.77	52.55	46.69	42.86	42.94	47.90
TIAT	NMI	26.89	26.60	25.51	23.55	23.77	24.68	20.30	14.58	13.57	15.04	19.06
UAI	ARI	25.21	24.49	23.11	23.23	22.77	24.79	19.40	13.82	09.63	11.98	16.28
	F1	55.99	54.33	51.46	53.86	51.91	55.05	49.60	43.53	40.65	38.13	44.13

Table 6: Graph data quality testing experiments. Clustering performance of HSAN [68] on five datasets with noisy information including noised node attributes and noised edges. Experimental results are the mean value of ten runs.

		Origin	Standa	rd Devia	tion of At	tribute Noises	Standa	rd Devia	tion of E	dge Noises
		Origin	0.01	0.1	1	10	0.01	0.1	1	10
Cora	ACC	77.73	77.31	76.53	46.82	36.15	37.20	21.25	30.24	30.24
Com	NMI	59.45	59.04	58.37	22.18	13.53	11.16	0.51	0.40	0.40
Cora	ARI	57.62	59.16	56.43	17.44	8.95,	8.53	0.48	0.02	0.02
	F1	76.16	74.76	74.76	46.34	37.19	34.4	15.61	6.84	6.84
	ACC	71.36	70.39	68.79	37.47	27.35	28.27	21.57	21.07	21.07
CitoSoom	NMI	45.03	44.54	41.85	8.44	3.52	3.70	0.35	0.29	0.29
Cheseel	ARI	46.81	46.16	43.64	8.06	1.55	2.21	0.20	0.00	0.00
	F1	63.63	64.12	62.40	30.49	17.70	21.85	15.53	5.91	5.91
	ACC	77.86	78.37	78.37	66.41	58.52	66.41	52.67	27.48	27.48
ват	NMI	53.00	54.15	53.07	46.50	40.53	38.86	23.62	4.36	4.36
DAI	ARI	51.16	52.27	52.33	42.14	31.70	34.02	18.13	0.15,	0.15
BAT	F1	77.80	78.30	78.19	62.76	56.32	66.12	52.45	12.25	12.25
	ACC	57.73	57.98	56.64	53.22	50.71	55.81	50.71	26.07	26.07
FAT	NMI	34.12	34.36	33.59	32.13	32.17	31.58	23.27	1.46	1.46
LAI	ARI	27.22	28.06	25.92	25.64	23.73	24.07	17.30	0.01	0.01
	F1	58.09	58.11	57.12	48.54	45.92	56.37	51.62	11.24	11.24
	ACC	56.16	55.57	56.97	53.39	54.17	47.00	40.25	25.38	25.38
UAT	NMI	26.89	25.59	26.23	24.33	24.88	15.72	9.26	0.50	0.50
UAI	ARI	25.21	25.41	25.60	22.02	23.88	15.41	9.10	0.00	0.00
	F1	55.99	54.86	53.64	47.29	52.79	45.42	36.97	10.56	10.56

Next, we discuss the potential solutions. Firstly, for the incomplete node attributes or edges, the imputation networks [137], [138] can help alleviate the information missing issue. Besides, for the error information, the denoising technologies [139], [140], [141] might effectively remove the noises in the node attributes and edges. Additionally, to solve the homophily and heterophily problems, researchers propose various methods [74], [136].

# 4.2 Stability

The stability of deep graph clustering algorithms is essential, especially in sensitive domains such as financial risk control, social network anomaly detection, etc. Different from the supervised methods or the semi-supervised methods, deep graph clustering methods group the nodes into disjoint clusters in a purely unsupervised manner, i.e., without any human annotations. Therefore, without the guidance of ground truth, the stability of deep graph clustering models is relatively weak. For example, for the classical clustering method such as k-Means [18], its promising performance highly relies on the quality of the initial cluster centers. Similarly, the performance of deep clustering techniques [29], [30] is also sensitive to the initialization of the neural networks and trainable cluster centers. Next, we systematically analyze the randomness in the deep graph clustering methods. It mainly consists of two parts as follows. Firstly, one of the key factors in achieving promising clustering performance is the excellent representation capability of the learned node embeddings. Thus, the initialization and training processes of the embedding networks influence the stability of deep graph clustering methods. Secondly, a clustering method with strong discriminative capability is another critical factor. Therefore, initialization and optimization processes of the neural cluster centers also easily affect the stability of deep graph clustering methods.

Table 7: Stability testing of deep graph clustering methods. Average clustering performance of eleven methods on six datasets. The experimental results are obtained with ten runs and presented with standard deviation.

Dataset	Metric	k-Means	AE	DEC	IDEC	GAE	DAEGC	ARGA	SDCN	MVGRL	DFCN	DCRN
	ACC	0.65	0.35	0.56	0.62	1.22	0.48	0.59	1.81	1.02	0.80	0.25
DDI D	NMI	0.38	0.16	0.28	0.50	0.91	0.45	0.92	1.34	0.63	1.00	0.44
DBLP	ARI	0.39	0.43	0.39	0.60	1.40	0.52	0.91	2.01	0.50	1.50	0.46
	F1	0.27	0.36	0.51	0.56	2.23	0.67	0.66	1.51	1.51	0.80	0.26
	ACC	3.17	0.13	0.20	1.42	0.80	1.39	0.49	0.31	0.36	0.20	0.18
CitoSoor	NMI	3.22	0.08	0.30	2.40	0.65	0.86	0.71	0.32	0.40	0.20	0.35
Citeseei	ARI	3.02	0.14	0.36	2.65	1.18	1.24	0.70	0.43	0.73	0.30	0.30
	F1	3.53	0.11	0.17	1.39	0.82	1.32	0.31	0.24	0.39	0.20	0.21
	ACC	0.71	0.08	0.76	0.52	1.44	2.83	0.36	0.18	0.76	0.20	0.20
ACM	NMI	0.46	0.16	1.51	1.16	1.92	4.15	0.82	0.25	1.40	0.40	0.61
ACM	ARI	0.69	0.16	1.87	1.50	3.10	3.89	0.86	0.40	1.76	0.40	0.52
	F1	0.74	0.08	0.74	0.48	1.33	2.79	0.35	0.19	0.72	0.20	0.20
	ACC	0.76	0.08	0.08	0.08	2.48	0.01	2.30	0.81	1.79	0.80	0.13
Amozon Photo	NMI	1.33	0.30	0.05	0.08	2.79	0.03	2.76	0.83	1.31	1.00	0.24
Amazon-r noto	ARI	0.44	0.47	0.04	0.07	4.57	0.02	4.41	1.23	0.47	0.84	0.20
	F1	0.51	0.20	0.12	0.11	1.76	0.02	1.95	1.49	2.39	0.31	0.12
	ACC	0.01	0.31	0.09	0.34	0.81	0.03	0.12	1.30	0.52	0.07	0.07
PubMed	NMI	0.02	0.57	0.14	0.29	3.54	0.03	0.17	2.04	1.45	0.13	0.08
rubivieu	ARI	0.01	0.67	0.13	0.39	1.39	0.04	0.17	2.07	1.06	0.11	0.12
	F1	0.01	0.29	0.10	0.32	0.85	0.02	0.13	1.21	0.36	0.07	0.08
	ACC	1.10	0.19	0.45	0.31	0.81	1.00	0.43	0.40	2.95	0.81	0.60
CoroFILL	NMI	0.84	0.25	0.24	0.28	0.75	0.73	0.25	0.39	3.95	0.41	0.35
CularULL	ARI	0.57	0.27	0.29	0.22	0.86	0.47	0.24	0.27	2.63	0.48	0.49
	F1	1.09	0.30	0.58	0.41	0.75	1.33	0.41	0.43	2.87	0.87	0.76

We conduct experiments to test the stability of existing deep graph clustering methods on six datasets, including DBLP, CiteSeer, ACM, Amazon-Photo, PubMed, and CoraFULL. The compared methods include DCRN [66], DFCN [34], MVGRL [59], DAEGC [28], , SDCN [33], ARGA [25], GAE [4], DEC [29], IDEC [30], AE [142], k-Means [18]. All experimental results are obtained with ten runs. And the results are reported with standard deviation. The experimental results indicate that the stability of recent methods seems good. However, there are various problems with their implementation. Firstly, the classical method k-Means initializes the cluster centers various times to find excellent initialization. Secondly, most of the existing methods such as DEC [29], IDEC [30], DAEGC [28], ARGA [25], SDCN [33], MVGRL [59], DFCN [34], and DCRN [66] rely on the well pre-trained node embeddings and cluster center embeddings. And the manual trial processes of network pre-training and center initialization seem to increase the stability of deep graph clustering methods. However, in the real-world scenario, implementing these procedures is costly. Thus, we consider that the stability of the existing deep graph clustering methods is overestimated. It will be a promising direction to improve the robustness and stability of deep graph clustering methods.

In the existing studies, researchers conduct ten runs with different random seeds to alleviate the randomness influence on the experimental results. We consider that some optimization strategies [143], [144] might enhance the stability of deep graph clustering.

# 4.3 Scalability

In this section, we discuss the scalability of deep graph clustering methods. Although achieving promising performance, most previous deep graph clustering methods can not scale to large-scale graph datasets, such as ogbn-papers100M [132]. The heavy time and memory costs mainly come from two parts, as follows. Firstly, the graph encoders need to be trained on large-scale graphs.

Secondly, the clustering algorithms need to group a large number of nodes into separate clusters.

For the first part, batch training [145] will be a good solution. Concretely, researchers can partition the large graph into a minibatch graph via sub-graph extraction technology like random walk [146] and then train the networks on the sub-graphs. Here, unlike images or texts, one of the essential characteristics of graph data is the relational connections between nodes. Thus, keeping the original connection information after the graph partition is vital for the model's performance.

For the second part, given the learned node embeddings  $\mathbf{Z} \in \mathbb{R}^{n \times d}$ , the classical k-Means clustering algorithm will take  $\mathcal{O}(tknd)$  time complexity and  $\mathcal{O}(nd + kd)$  space complexity. Here, n, k, and d are the node number, cluster number, and feature dimension number, respectively. Besides, t is the iteration number of k-Means. On the large graph, the node number n is very large, such as 111M node number on ogbn-paper100M dataset [132], easily leading to out-of-memory on GPU or the long calculation time on CPU.

To demonstrate this challenge in deep graph clustering methods, we conduct experiments and theoretical analyses including comparison experiments, running cost evaluation, and complexity analyses. As shown in Table 8. Concretely, fifteen important baselines are tested on four large graph datasets, including ogbnarXiv, ogbn-products, Reddit, and ogbn-papers100M. The detailed statistics of datasets are summarized in Table 4. The baselines contain k-Means [18], DEC [29], DCN [147], node2vec [148], DGI [51], AGE [58], MinCutPool [35], MVGRL [59], BGRL [55], GRACE [52], ProGCL [149], AGC-DRR [115], DCRN [66], S<sup>3</sup>GC [70], and Dink-Net [71]. From these experimental results, three conclusions are obtained as follows. Firstly, the classical method k-Means can scale to large graphs with million of nodes but can not achieve promising performance since the representation learning capability is limited. Secondly, most of the deep graph clustering methods like MVGRL [59], AGE [58], GRACE [52], and DCRN [66] fail to run on large graphs. The reasons

Dataset	Metric	k-Means	DEC	DCN	node2vec	DGI	AGE	MVGRL	BGRL	GRACE	ProGCL	AGC-DRR	DCRN	S <sup>3</sup> GC	Dink-Net
ogbn-arXiv	ACC NMI ARI F1	18.11 22.13 7.43 12.94	21.25 25.14 10.28 15.57	19.91 23.81 8.25 13.06	29.00 40.60 19.00 22.00	31.40 41.20 22.30 23.00	OOM	OOM	22.70 32.10 13.00 16.60	OOM	29.86 37.51 25.74 21.79	OOM	ООМ	35.00 46.30 27.00 23.00	43.68 43.73 35.22 26.92
ogbn- products	ACC NMI ARI F1	18.11 22.13 7.43 12.94	23.79 24.47 9.05 13.54	24.50 21.92 10.96 13.95	35.70 48.90 17.00 24.70	32.00 46.70 17.40 19.20	OOM	OOM	ООМ	OOM	35.21 46.59 19.87 21.55	ООМ	ООМ	40.20 53.60 23.00 25.00	41.09 50.78 21.08 25.15
Reddit	ACC NMI ARI F1	8.90 11.40 2.90 6.80	ООМ	ООМ	70.90 79.20 64.00 55.10	22.40 30.60 17.00 18.30	ООМ	OOM	ООМ	ООМ	65.41 70.48 63.42 51.45	ООМ	ООМ	73.60 80.70 74.50 56.00	76.03 78.91 71.34 67.95
ogbn- papers100M	ACC NMI ARI F1	14.60 37.33 7.54 10.45	ООМ	ООМ	17.50 38.00 11.20 11.10	15.10 41.60 9.60 11.10	ООМ	OOM	ООМ	OOM	OOM	OOM	ООМ	17.30 45.30 11.00 11.80	26.67 54.92 18.01 19.48

Table 9: Efficiency analyses of eight deep graph clustering methods. The left two columns denote the time and space complexity analyses. The right two columns denote the GPU and time costs. Experimental results obtained on the Cora dataset. n, b, k, l, g, d', and d denote node number, batch size, cluster number, edge number, average degree of graph, attribute dimension, and latent feature dimension.

Method	Time Complexity (per iteration)	Space Complexity	GPU Memory Cost (MB)	Time Cost (s)
DEC	$\mathcal{O}(nkd)$	$\mathcal{O}(nk + nd + kd)$	1294	14.59
node2vec	$\hat{\mathcal{O}}(bd)$	$\mathcal{O}(nd)$	-	111.03
DGI	$\mathcal{O}(ld'+nd^2)$	$\mathcal{O}(l+nd+d^2)$	3798	19.03
MVGRL	$\mathcal{O}(n^2d + nd^2)$	$\mathcal{O}(n^2 + nd + d^2)$	9466	168.20
GRACE	$\mathcal{O}(n^2d + ld + d^2)$	$\mathcal{O}(l+nd)$	1292	44.77
BGRL	$\mathcal{O}(ld+nd^2)$	$\mathcal{O}(l+nd+d^2)$	1258	44.18
S <sup>3</sup> GC	$\mathcal{O}(ngd^2)$	$\mathcal{O}(nd + bgd + d^2)$	1474	508.21
Dink-Net	$\mathcal{O}(nkd + k^2d + bd)$	$\mathcal{O}(bk + bd + kd)$	1248	35.09

are that they either process the graph diffusion matrix or do not adopt batch training techniques. Thirdly, the scalable deep graph clustering methods  $S^3GC$  [70] and Dink-Net [71] can run on large graphs like ogbn-papers100M [132] with 111 million nodes and achieve promising performance.  $S^3GC$  [70] conducts contrastive learning on the graph and performs k-Means on the learned node embeddings. In addition, Dink-Net [71] unifies the representation learning and clustering optimization via cluster dilation and cluster shrink loss functions. Besides, in Table 9, we analyze the time complexity and space complexity, and test the GPU memory costs and time costs of six deep graph clustering methods, including DEC [29], node2vec [148], DGI [51], MVGRL [59], BGRL [55],  $S^3GC$  [70], and Dink-Net [71].

Next, we discuss the potential techniques to improve the scalability of deep graph clustering methods. For the first part, i.e., encoder training on the large-scale graph, the possible techniques include the better sub-graph extraction method, more efficient batch training strategy, etc. For the second part, i.e., node clustering on the large-scale graph, the potential solutions contain the mini-batch k-Means [150], finding cluster centers via the neural network [71], calculating the clustering assignments in a mini-batch manner [71], and bi-part graph clustering [151], [152], etc.

# 4.4 Discriminative Capability

One key factor of promising clustering performance is to learn discriminative node embeddings, which help the clustering methods better group nodes into different clusters. Therefore, the discriminative capability of the network is vital in self-supervised learning. [66] observe the representation collapse problem, i.e., the encoder tends to embed all samples into the same cluster in deep graph clustering methods. To demonstrate this problem, we conduct extensive experiments, including three types: performance comparison experiments, similarity visualization experiments, and embedding visualization experiments.

At first, as shown in Table 10, we conduct performance comparison experiments on six datasets, including DBLP, Cite-Seer, ACM, Amazon-Photo, PubMed, and CoraFull datasets. The detailed information of these datasets is listed in Table 4. We compare thirteen state-of-the-art methods including DEC [29], GAE [4], DAEGC [28], ARGA [25], SDCN [33], DFCN [34], MVGRL [59], MCGC [60], SCAGC [104], SCGC [64], AGC-DDR [115], DCRN [66], and IDCRN [67]. From these experimental results, we have three observations as follows. Firstly, the performance of deep clustering methods such as DEC [29] is limited since it omits the graph structure of graph data. Secondly, various deep reconstructive graph clustering methods such as GAE [4], DAEGC [28], SDCN [33], DFCN [34] significantly improve the clustering performance since they reconstruct the graph information and improve the discriminative capability of networks. Thirdly, the recent contrastive methods like MVGRL [59], SCGC [64], and DCRN [66] further enhance the sample discriminative capability via pulling together positive sample pairs and pushing away the negative sample pairs, achieving the most promising performance.

In addition, to intuitively demonstrate this challenge, we conduct the t-SNE visualization on the learned node embeddings. As shown in Figure 11, Three observations can be found as follows.

Table 10: Discriminative capability testing experiments. Clustering performance of thirteen methods on six datasets

Dataset	Metric	DEC	GAE	DAEGC	ARGA	SDCN	DFCN	MVGRL	MCGC	SCAGC	SCGC	AGC-DDR	DCRN	IDCRN
DBLP	ACC	58.16	61.21	62.05	64.83	68.05	76.00	42.73	58.92	79.42	67.25	80.41	79.66	82.08
	NMI	29.51	30.80	32.49	29.42	39.50	43.70	15.41	33.69	49.05	38.64	49.77	48.95	52.70
	ARI	23.92	22.02	21.03	27.99	39.15	47.00	8.22	25.97	54.04	35.95	55.39	53.60	58.81
	F1	59.38	61.41	61.75	64.97	67.71	75.70	40.52	50.39	78.88	67.06	79.90	79.28	81.47
	ACC	55.89	61.35	64.54	61.07	65.96	69.50	68.66	64.76	61.16	71.02	68.32	70.86	71.40
CitoSoor	NMI	28.34	34.63	36.41	34.40	38.71	43.90	43.66	39.11	32.83	45.25	43.28	45.86	46.77
CheSeel	ARI	28.12	33.55	37.78	34.32	40.17	45.50	44.27	37.54	31.17	46.29	45.34	47.64	48.67
	F1	52.62	57.36	62.20	58.23	63.62	64.30	63.71	59.64	56.82	62.24	64.82	65.83	66.27
	ACC	84.33	84.52	86.94	86.29	90.45	90.90	86.73	91.64	91.83	89.80	92.55	91.93	92.58
ACM	NMI	54.54	55.38	56.18	56.21	68.31	69.40	60.87	70.71	71.28	66.60	72.89	71.56	73.17
ACM	ARI	60.64	59.46	59.35	63.37	73.91	74.90	65.07	76.63	77.29	72.37	79.08	77.56	79.18
	F1	84.51	84.65	87.07	86.31	90.42	90.80	86.85	91.70	91.84	89.74	92.55	91.94	92.60
	ACC	47.22	71.57	76.44	69.28	53.44	76.88	45.19	OOM	75.25	77.48	78.11	79.94	80.17
Amazon-Photo	NMI	37.35	62.13	65.57	58.36	44.85	69.21	36.89	OOM	67.18	67.67	72.21	73.70	74.32
Amazon-1 noto	ARI	18.59	48.82	59.39	44.18	31.21	58.98	18.79	OOM	56.86	58.48	61.15	63.69	64.10
	F1	46.71	68.08	69.97	64.30	50.66	71.58	39.65	OOM	72.77	72.22	72.72	73.82	74.01
	ACC	60.14	62.09	68.73	65.26	64.20	68.89	67.01	60.97	OOM	63.14	-	69.87	70.02
DubMod	NMI	22.44	23.84	28.26	24.80	22.87	31.43	31.59	33.39	OOM	27.77	-	32.20	33.29
rubivieu	ARI	19.55	20.62	29.84	24.35	22.30	30.64	29.42	29.25	OOM	24.73	-	31.41	32.67
	F1	61.49	61.37	68.23	65.69	65.01	68.10	67.07	59.84	OOM	62.27	-	68.94	69.19
	ACC	31.92	29.60	34.35	22.07	26.67	37.51	31.52	29.08	OOM	OOM	-	38.80	39.45
CoroFULI	NMI	41.67	45.82	49.16	41.28	37.38	51.30	48.99	36.86	OOM	OOM	-	51.91	52.83
CULAFULL	ARI	16.98	17.84	22.60	12.38	13.63	24.46	19.11	13.15	OOM	OOM	-	25.25	25.97
	F1	27.71	25.95	26.96	18.85	22.14	31.22	26.51	22.90	OOM	OOM	-	31.68	32.58



Figure 11: Discriminative capability testing experiments. *t*-SNE visualization of node embeddings. The compared methods include DEC [29], GAE [4], ARGA [25], DFCN [34], and IDCRN [67]. The first and second row is the result on ACM and DBLP dataset.



Figure 12: Discriminative capability testing experiments. Visualization of pairwise sample similarity. The compared methods are GAE [4], MVGRL [59], SDCN [33], and IDCRN [67]. The first row and second row is the result on ACM and CiteSeer dataset.

Firstly, in the raw data, we can not observe any cluster shape in the latent space. Secondly, the deep clustering method DEC [29], reconstructive deep graph clustering [4], [34], and adversarial deep graph clustering method ARGA [25] can reveal part of the clus-

tering distribution. Thirdly, the sample discriminative capability of the contrastive methods IDCRN [67] is strong, revealing the clustering distribution well. We consider visualizing the learned node embeddings as one of the intuitive ways to evaluate the discriminative capability of deep graph clustering methods.

Furthermore, we calculate and visualize the pair-wise similarity of the learned node embeddings. The results are demonstrated in Figure 12. Here, we reorder the nodes and gather the nodes with the same labels on the same side. Besides, the red pixel denotes the high similarity, and the blue pixel denotes the low similarity. From the figure, two conclusions are drawn. Firstly, GAE [4] and MVGRL [59] have a trend to the representation collapse problem since all paired sample similarities are high. Secondly, SDCN [33] and IDCRN [67] alleviate the representation collapse problem via the delivery operator and dual correlation reduction. As shown in Figure 12 (c) and Figure 12 (d), the similarities between the samples in the same cluster are relatively high. In contrast, the similarities between the samples in different clusters are relatively low. We think this similarity visualization method can be an excellent tool to test the sample discriminative capability of the deep graph clustering method.

Recently, we have witnessed the fast development of selfsupervised learning on graphs [153]. The reconstructive deep graph clustering methods [4], [28], [33], [34], [39] reconstruct the graph information such as node attribute and graph structure. Besides, the adversarial methods [25], [106], [115] generate the adversarial samples and discriminate them from the real samples. In addition, the contrastive methods [66], [71], [104], [115] pull together the positive sample pairs while pushing away the negative sample pairs. Previous researchers designed different promising pre-text tasks to enhance the sample discriminative capability of networks. In the future, to further enhance the discriminative capability, the hard sample mining strategies [68], [149] will be an exciting future direction.

#### 4.5 Unknown Cluster Number

Most of the existing deep graph clustering methods consider the cluster number as a given value, which is usually the same as the classes of the ground truth. Benefiting from this setting, recent deep graph clustering methods can achieve promising performance. The remarkable success of recent deep graph clustering algorithms relies on the pre-defined cluster number. However, in most real-world scenarios, the cluster number is an unknown value. For example, in Internet social networks, the users can be grouped into several clusters, but we can not know the specific number of user groups. In addition, the number of user groups is the most important in the user grouping algorithm. Therefore, we think the clustering performance of the existing deep graph clustering methods is overestimated.



Figure 13: Unknown cluster number experiments. Clustering performance of DCRN [66] with different cluster numbers  $K \in [2, 10]$  on Cora and CiteSeer datasets.

In order to verify our suspect, we conduct experiments on two datasets, including DBLP and CiteSeer. Concretely, we adopt DCRN [66] as the baseline and evaluate its clustering performance with NMI and ARI metrics using different cluster numbers ranging from 2 to 10. The experimental results are demonstrated in Figure 13. We carefully analyze the results the draw two conclusions as follows. Firstly, the baseline DCRN achieves promising and best performance when the cluster number equals the class number of ground truth. Here, the sample class number of the DBLP dataset is 4, and the sample class number of CiteSeer is 6. Secondly, other cluster numbers will lead to performance degeneration. When the cluster number reduces, many clusters will collapse into one cluster. Besides, when the cluster number increases, the large cluster will be split into many small clusters. Therefore, the cluster number is crucial for the clustering performance, and designing the deep graph clustering methods without the pre-defined cluster number will be a challenging and meaningful direction.

To solve this problem, one potential solution is to perform clustering based on density [154]. Concretely, the clustering network should be designed to assign the high-density data area as the cluster centers and regard the low-density data area as the decision borders. Besides, another potential solution technology is deep reinforcement learning [86], [155]. To be specific, in an unsupervised scenario, recognizing the cluster number in the graph data can be modeled as the Markov decision process and be handled with deep reinforcement neural networks. More cluster number determination methods refer to [156]. In the next section, we will introduce the applications of deep graph clustering in four domains.

# 5 APPLICATION & OPEN RESOURCE

# 5.1 Application

In recent years, we have witnessed the fast growth of deep graph clustering. Thanks to the researchers in this field, promising deep graph clustering methods are increasingly proposed. Benefiting from the strong data partitioning capability, deep graph clustering has been applied to various real-world application domains, such as natural language processing, computer vision, social network analyses, recommendation systems, bioinformatics, medical science, etc. The applications are demonstrated in Figure 14.

Next, we introduce the applications in detail. In the computer vision domain, deep graph clustering methods are applied to face analysis [157], [158], co-saliency detection [159] and video analyses [160]. Besides, document mining [161], speech separation [162], and large language models [163] are essential applications of deep graph clustering in the natural language processing area. In addition, deep graph clustering is crucial for social network analyses. It can be used to conduct community detection [164], [165], [166], [167] and anomaly detection [168], [169]. Similarly, deep graph clustering demonstrates the high application values in the recommendation systems. To be specific, it can help user grouping recommendations and user intent extraction [170]. Apart from social data mining, deep graph clustering is also vital to bioinformatics and medical science. Concretely, the applications in the bioinformatics field include molecular mining [171], [172], metagenomic binning [173], single-cell RNA sequencing [43], etc. Also, in the medical science domain, deep graph clustering methods are adopted in disease analyses [174], medical big data [175], and medical image [176]. In the future, we hope the researchers will further solve the challenges and apply deep graph clustering methods to a broader range and more significant fields.

# 5.2 Open Resource

In order to construct an open, active, and collaborative research & engineering atmosphere in the deep graph clustering field, we make efforts to the open-source projects of deep graph clustering. Concretely, we make a deep graph clustering collection and build a unified framework of deep graph clustering methods. We hope these open resources will help the researchers quickly startup, solve critical problems, and apply deep graph clustering methods to a boarder range of applications. Next, we introduce these two GitHub repositories in detail.

#### 5.2.1 Awesome Deep Graph Clustering

Awesome Deep Graph Clustering (ADGC) is a collection of state-of-the-art, novel deep graph clustering methods, including papers, codes, and datasets. In addition, this project



Figure 14: Applications of deep graph clustering in six domains: natural language processing, computer vision, social network analyses, recommendation systems, bioinformatics, and medical science.

open-sources some common data processing, clustering, metric calculation, and visualization functions. The project address can be found at GitHub (https://github.com/yueliu1999/ Awesome-Deep-Graph-Clustering). Up to this paper submission time, we have collected about 130 papers and codes and about 20 datasets. Besides, this GitHub repository has gained about 500 stars and 100 forks. We welcome any issues, pull requests, contributions, discussions, etc.

#### 5.2.2 A Unified Framework of Deep Graph Clustering

A-Unified-Framework-for-Deep-Attribute-Graph-Clustering aims to build а unified framework for the deep graph clustering methods. The project address can found at GitHub (https://github.com/Marigoldwu/ be A-Unified-Framework-for-Deep-Attribute-Graph-Clustering). This project redesigns the architecture of the codes of ADGC so that helps researchers conduct experiments easily. The tool classes and functions are defined to simplify the codes and clarify the settings configuration.

# 6 CONCLUSION

In this work, we make a comprehensive survey about deep graph clustering to help researchers review, summarize, and plan for the future. Concretely, we first demonstrate the general pipeline of deep graph clustering and give a formal definition. Besides, we introduce the critical development and evaluation of deep graph clustering. Secondly, a structured taxonomy is provided from four perspectives, including graph type, network architecture, learning paradigm, and clustering method. Moreover, through extensive experiments, we analyze and summarize the challenges in this domain, such as the problems of graph data quality, stability, scalability, discriminative capability, and unknown cluster number. Also, the potential technical solutions are carefully discussed. Thirdly, we introduce the applications of deep graph clustering in six domains, including social network analysis, recommendation systems, computer vision, natural language processing, bioinformatics, and medical science. More importantly, we contribute two open resources on the GitHub platform. Among them, Awesome Deep Graph Clustering is a comprehensive collection of deep graph clustering, including papers, codes, and datasets. Besides, A-Unified-Framework-for-Deep-Attribute-Graph-Clustering is a unified framework of deep graph clustering. We hope this work becomes a quick guide for the researchers and motivates them to solve significant problems in deep graph clustering.

#### ACKNOWLEDGMENTS

This work was supported by the National Key R&D Program of China (project no. 2020AAA0107100, 2021ZD0140406, 2022ZD0115100), the National Natural Science Foundation of China (project no, 62325604, 62276271, U21A20427, 62006237, 61922088, 61906020 and 61773392), the Research Center for Industries of the Future (Project WU2022C043), and the Competitive Research Fund (Project WU2022A009) from the Westlake Center for Synthetic Biology and Integrated Bioengineering. Besides, we thank Benyu Wu (https://marigoldwu.github.io/) for his significant contributions to A-Unified-Framework-for-Deep-Attribute-Graph-Clustering project.

#### REFERENCES

- [1] Y. LeCun, Y. Bengio, and G. Hinton, "Deep learning," nature, 2015.
- [2] T. N. Kipf and M. Welling, "Semi-supervised classification with graph convolutional networks," in *Proc. of ICLR*, 2017.
- [3] P. Veličković, G. Cucurull, A. Casanova, A. Romero, P. Liò, and Y. Bengio, "Graph attention networks," in *Proc. of ICLR*, 2018.
- [4] T. N. Kipf and M. Welling, "Variational graph auto-encoders," arXiv preprint arXiv:1611.07308, 2016.
- [5] X. Yang, Y. Liu, S. Zhou, X. Liu, and E. Zhu, "Mixed graph contrastive network for semi-supervised node classification," *arXiv preprint arXiv:2206.02796*, 2022.
- [6] K. Liang, L. Meng, M. Liu, Y. Liu, W. Tu, S. Wang, S. Zhou, and X. Liu, "Learn from relational correlations and periodic events for temporal knowledge graph reasoning," in *Proc. of SIGIR*, 2023.
- [7] K. Liang, L. Meng, S. Zhou, S. Wang, W. Tu, Y. Liu, M. Liu, and X. Liu, "Message intercommunication for inductive relation reasoning," *arXiv preprint arXiv:2305.14074*, 2023.

- [8] K. Liang, J. Tan, D. Zeng, Y. Huang, X. Huang, and G. Tan, "Abslearn: a gnn-based framework for aliasing and buffer-size information retrieval," *Pattern Analysis and Applications*, 2023.
- [9] S. Zhou, H. Xu, Z. Zheng, J. Chen, J. Bu, J. Wu, X. Wang, W. Zhu, M. Ester *et al.*, "A comprehensive survey on deep clustering: Taxonomy, challenges, and future directions," *arXiv preprint arXiv:2206.07579*, 2022.
- [10] Y. Ren, J. Pu, Z. Yang, J. Xu, G. Li, X. Pu, P. S. Yu, and L. He, "Deep clustering: A comprehensive survey," *arXiv preprint arXiv:2210.04142*, 2022.
- [11] E. Aljalbout, V. Golkov, Y. Siddiqui, M. Strobel, and D. Cremers, "Clustering with deep learning: Taxonomy and new methods," *arXiv* preprint arXiv:1801.07648, 2018.
- [12] E. Min, X. Guo, Q. Liu, G. Zhang, J. Cui, and J. Long, "A survey of clustering with deep learning: From the perspective of network architecture," *IEEE Access*, 2018.
- [13] S. Wang, J. Yang, J. Yao, Y. Bai, and W. Zhu, "An overview of advanced deep graph node clustering," *IEEE Transactions on Computational Social Systems*, 2023.
- [14] S. Xing, X. Shan, L. Fanzhen, W. Jia, Y. Jian, Z. Chuan, H. Wenbin, P. Cecile, N. Surya, J. Di *et al.*, "A comprehensive survey on community detection with deep learning," *IEEE Trans. Neural Netw. Learn. Syst*, 2022.
- [15] F. Liu, S. Xue, J. Wu, C. Zhou, W. Hu, C. Paris, S. Nepal, J. Yang, and P. S. Yu, "Deep learning for community detection: progress, challenges and opportunities," in *Proceedings of the Twenty-Ninth International Conference on International Joint Conferences on Artificial Intelli*gence, 2021.
- [16] F. Tian, B. Gao, Q. Cui, E. Chen, and T.-Y. Liu, "Learning deep representations for graph clustering," in *Proc. of AAAI*, 2014.
- [17] A. Ng et al., "Sparse autoencoder," CS294A Lecture notes, 2011.
- [18] J. A. Hartigan and M. A. Wong, "Algorithm as 136: A k-means clustering algorithm," *Journal of the royal statistical society. series c* (applied statistics), 1979.
- [19] S. Cao, W. Lu, and Q. Xu, "Deep neural networks for learning graph representations," in *Proc. of AAAI*, 2016.
- [20] S. Chang, W. Han, J. Tang, G.-J. Qi, C. C. Aggarwal, and T. S. Huang, "Heterogeneous network embedding via deep architectures," in *Proc. of KDD*, 2015.
- [21] C. Wang, S. Pan, G. Long, X. Zhu, and J. Jiang, "Mgae: Marginalized graph autoencoder for graph clustering," in *Proceedings of the 2017* ACM on Conference on Information and Knowledge Management, 2017.
- [22] U. Von Luxburg, "A tutorial on spectral clustering," *Statistics and computing*, 2007.
- [23] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio, "Generative adversarial nets," *Proc. of NeurIPS*, 2014.
- [24] S. Pan, R. Hu, G. Long, J. Jiang, L. Yao, and C. Zhang, "Adversarially regularized graph autoencoder for graph embedding," in *Proc. of IJCAI*, 2018.
- [25] S. Pan, R. Hu, S.-f. Fung, G. Long, J. Jiang, and C. Zhang, "Learning graph embedding with adversarial training methods," *IEEE transactions* on cybernetics, 2019.
- [26] H. Gao, J. Pei, and H. Huang, "Progan: Network embedding via proximity generative adversarial network," in *Proc. of KDD*, 2019.
- [27] Y. Jia, Q. Zhang, W. Zhang, and X. Wang, "Communitygan: Community detection with generative adversarial nets," in *Proc. of WWW*, 2019.
- [28] C. Wang, S. Pan, R. Hu, G. Long, J. Jiang, and C. Zhang, "Attributed graph clustering: A deep attentional embedding approach," *arXiv preprint arXiv:1906.06532*, 2019.
- [29] J. Xie, R. Girshick, and A. Farhadi, "Unsupervised deep embedding for clustering analysis," in *Proc. of ICML*, 2016.
- [30] X. Guo, L. Gao, X. Liu, and J. Yin, "Improved deep embedded clustering with local structure preservation." in *Proc. of IJCAI*, 2017.
- [31] J. Park, M. Lee, H. J. Chang, K. Lee, and J. Y. Choi, "Symmetric graph convolutional autoencoder for unsupervised graph representation learning," in *Proc. of ICCV*, 2019.
- [32] X. Zhang, H. Liu, Q. Li, and X.-M. Wu, "Attributed graph clustering via adaptive graph convolution," in *Proc. of IJCAI*, 2019.
- [33] D. Bo, X. Wang, C. Shi, M. Zhu, E. Lu, and P. Cui, "Structural deep clustering network," in *Proc. of WWW*, 2020.
- [34] W. Tu, S. Zhou, X. Liu, X. Guo, Z. Cai, J. Cheng *et al.*, "Deep fusion clustering network," *arXiv preprint arXiv:2012.09600*, 2020.
- [35] F. M. Bianchi, D. Grattarola, and C. Alippi, "Spectral clustering with graph neural networks for graph pooling," in *Proc. of ICML*, 2020.

- [36] A. Tsitsulin, J. Palowitch, B. Perozzi, and E. Müller, "Graph clustering with graph neural networks," *Journal of Machine Learning Research*, 2023.
- [37] Z. Ying, J. You, C. Morris, X. Ren, W. Hamilton, and J. Leskovec, "Hierarchical graph representation learning with differentiable pooling," *Proc. of NeurIPS*, 2018.
- [38] J. Lee, I. Lee, and J. Kang, "Self-attention graph pooling," in *Proc. of ICML*, 2019.
- [39] S. Fan, X. Wang, C. Shi, E. Lu, K. Lin, and B. Wang, "One2multi graph autoencoder for multi-view graph clustering," in *Proc. of WWW*, 2020.
- [40] J. Cheng, Q. Wang, Z. Tao, D. Xie, and Q. Gao, "Multi-view attribute graph convolution networks for clustering," in *Proceedings of the Twenty-Ninth International Conference on International Joint Conferences on Artificial Intelligence*, 2021.
- [41] W. Xia, Q. Wang, Q. Gao, X. Zhang, and X. Gao, "Self-supervised graph convolutional network for multi-view clustering," *IEEE Trans. Multim.*, 2022.
- [42] N. Mrabah, M. Bouguessa, M. F. Touati, and R. Ksantini, "Rethinking graph auto-encoder models for attributed graph clustering," *IEEE Transactions on Knowledge and Data Engineering*, 2022.
- [43] Z. Yu, Y. Lu, Y. Wang, F. Tang, K.-C. Wong, and X. Li, "Zinb-based graph embedding autoencoder for single-cell rna-seq interpretations," in *Proc. of AAAI*, 2022.
- [44] R. D. Hjelm, A. Fedorov, S. Lavoie-Marchildon, K. Grewal, P. Bachman, A. Trischler, and Y. Bengio, "Learning deep representations by mutual information estimation and maximization," in *Proc. of ICLR*, 2018.
- [45] K. He, H. Fan, Y. Wu, S. Xie, and R. Girshick, "Momentum contrast for unsupervised visual representation learning," in *Proc. of CVPR*, 2020.
- [46] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton, "A simple framework for contrastive learning of visual representations," in *Proc. of ICML*, 2020.
- [47] J.-B. Grill, F. Strub, F. Altché, C. Tallec, P. H. Richemond, E. Buchatskaya, C. Doersch, B. A. Pires, Z. D. Guo, M. G. Azar et al., "Bootstrap your own latent: A new approach to self-supervised learning," arXiv preprint arXiv:2006.07733, 2020.
- [48] J. Zbontar, L. Jing, I. Misra, Y. LeCun, and S. Deny, "Barlow twins: Self-supervised learning via redundancy reduction," *arXiv preprint* arXiv:2103.03230, 2021.
- [49] X. Yang, X. Hu, S. Zhou, X. Liu, and E. Zhu, "Interpolation-based contrastive learning for few-label semi-supervised learning," *IEEE Transactions on Neural Networks and Learning Systems*, 2022.
- [50] X. Yang, J. Jin, S. Wang, K. Liang, Y. Liu, Y. Wen, S. Liu, S. Zhou, X. Liu, and E. Zhu, "Dealmvc: Dual contrastive calibration for multiview clustering," arXiv preprint arXiv:2308.09000, 2023.
- [51] P. Velickovic, W. Fedus, W. L. Hamilton, P. Liò, Y. Bengio, and R. D. Hjelm, "Deep graph infomax." *ICLR (Poster)*, 2019.
- [52] Y. Zhu, Y. Xu, F. Yu, Q. Liu, S. Wu, and L. Wang, "Deep Graph Contrastive Representation Learning," in *ICML Workshop on Graph Representation Learning and Beyond*, 2020.
- [53] J. Xia, L. Wu, J. Chen, B. Hu, and S. Z. Li, "Simgrace: A simple framework for graph contrastive learning without data augmentation," *arXiv preprint arXiv:2202.03104*, 2022.
- [54] Y. You, T. Chen, Y. Sui, T. Chen, Z. Wang, and Y. Shen, "Graph contrastive learning with augmentations," *Proc. of NeurIPS*, 2020.
- [55] S. Thakoor, C. Tallec, M. G. Azar, R. Munos, P. Veličković, and M. Valko, "Bootstrapped representation learning on graphs," in *ICLR* 2021 Workshop on Geometrical and Topological Representation Learning, 2021.
- [56] K. Liang, Y. Liu, S. Zhou, X. Liu, and W. Tu, "Relational symmetry based knowledge graph contrastive learning," 2022.
- [57] Y. Zhu, Y. Xu, Q. Liu, and S. Wu, "An empirical study of graph contrastive learning," arXiv preprint arXiv:2109.01116, 2021.
- [58] G. Cui, J. Zhou, C. Yang, and Z. Liu, "Adaptive graph encoder for attributed graph embedding," in *Proc. of KDD*, 2020.
- [59] K. Hassani and A. H. Khasahmadi, "Contrastive multi-view representation learning on graphs," in *Proc. of ICML*, 2020.
- [60] E. Pan and Z. Kang, "Multi-view contrastive graph clustering," Proc. of NeurIPS, 2021.
- [61] X. Wang, N. Liu, H. Han, and C. Shi, "Self-supervised heterogeneous graph neural network with co-contrastive learning," in *Proc. of KDD*, 2021.
- [62] H. Zhao, X. Yang, Z. Wang, E. Yang, and C. Deng, "Graph debiased contrastive learning with joint representation clustering," in *Proc. of IJCAI*, 2021.
- [63] N. Lee, J. Lee, and C. Park, "Augmentation-free self-supervised learning on graphs," arXiv preprint arXiv:2112.02472, 2021.

- [64] Y. Liu, X. Yang, S. Zhou, and X. Liu, "Simple contrastive graph clustering," *IEEE Transactions on Neural Networks and Learning Systems*, 2023.
- [65] Y. Liu, Y. Zheng, D. Zhang, H. Chen, H. Peng, and S. Pan, "Towards unsupervised deep graph structure learning," in *Proceedings of the ACM Web Conference 2022*, 2022.
- [66] Y. Liu, W. Tu, S. Zhou, X. Liu, L. Song, X. Yang, and E. Zhu, "Deep graph clustering via dual correlation reduction," in *Proc. of AAAI*, 2022.
- [67] Y. Liu, S. Zhou, X. Liu, W. Tu, and X. Yang, "Improved dual correlation reduction network," arXiv preprint arXiv:2202.12533, 2022.
- [68] Y. Liu, X. Yang, S. Zhou, X. Liu, Z. Wang, K. Liang, W. Tu, L. Li, J. Duan, and C. Chen, "Hard sample aware network for contrastive deep graph clustering," in *Proc. of AAAI*, 2023.
- [69] X. Yang, Y. Liu, S. Zhou, S. Wang, W. Tu, Q. Zheng, X. Liu, L. Fang, and E. Zhu, "Cluster-guided contrastive graph clustering network," in *Proc. of AAAI*, 2023.
- [70] F. Devvrit, A. Sinha, I. Dhillon, and P. Jain, "S3gc: Scalable selfsupervised graph clustering," 2022.
- [71] Y. Liu, K. Liang, J. Xia, S. Zhou, X. Yang, X. Liu, and S. Z. Li, "Dinknet: Neural clustering on large graphs," in *Proc. of ICML*, 2023.
- [72] W. Shiao, U. S. Saini, Y. Liu, T. Zhao, N. Shah, and E. E. Papalexakis, "Carl-g: Clustering-accelerated representation learning on graphs," ACM SIGKDD Explorations Newsletter, 2023.
- [73] L. Sun, F. Wang, J. Ye, H. Peng, and P. S. Yu, "Contrastive graph clustering in curvature spaces," 2023.
- [74] E. Pan and Z. Kang, "Beyond homophily: Reconstructing structure for graph-agnostic clustering," 2023.
- [75] Y. Wen, S. Wang, Q. Liao, W. Liang, K. Liang, X. Wan, and X. Liu, "Unpaired multi-view graph clustering with cross-view structure matching," *IEEE Transactions on Neural Networks and Learning Systems*, 2023.
- [76] J.-O. Palacio-Niño and F. Berzal, "Evaluation metrics for unsupervised learning algorithms," arXiv preprint arXiv:1905.05667, 2019.
- [77] A. Lutov, M. Khayati, and P. Cudré-Mauroux, "Accuracy evaluation of overlapping and multi-resolution clustering algorithms on large datasets," in 2019 IEEE International Conference on Big Data and Smart Computing (BigComp), 2019.
- [78] A. F. McDaid, D. Greene, and N. Hurley, "Normalized mutual information to evaluate overlapping community finding algorithms," *arXiv* preprint arXiv:1110.2515, 2011.
- [79] K. Y. Yeung and W. L. Ruzzo, "Details of the adjusted rand index and clustering algorithms, supplement to the paper an empirical study on principal component analysis for clustering gene expression data," *Bioinformatics*, 2001.
- [80] M. D. Plummer and L. Lovász, Matching theory. Elsevier, 1986.
- [81] S. Aranganayagi and K. Thangavel, "Clustering categorical data using silhouette coefficient as a relocating measure," in *International conference on computational intelligence and multimedia applications* (ICCIMA 2007), 2007.
- [82] X. Wang and Y. Xu, "An improved index for clustering validation based on silhouette index and calinski-harabasz index," in *IOP Conference Series: Materials Science and Engineering*, 2019.
- [83] S. Petrovic, "A comparison between the silhouette index and the daviesbouldin index in labelling ids clusters," in *Proceedings of the 11th Nordic workshop of secure IT systems*, 2006.
- [84] D. Jin, B. Li, P. Jiao, D. He, and W. Zhang, "Network-specific variational auto-encoder for embedding in attribute networks." in *Proc. of IJCAI*, 2019.
- [85] C. Yang, M. Liu, Z. Wang, L. Liu, and J. Han, "Graph clustering with dynamic embedding," arXiv preprint arXiv:1712.08249, 2017.
- [86] Y. Liu, K. Liang, J. Xia, X. Yang, S. Zhou, M. Liu, X. Liu, and S. Z. Li, "Reinforcement graph clustering with unknown cluster number," 2023.
- [87] X. Yang, C. Tan, Y. Liu, K. Liang, S. Wang, S. Zhou, J. Xia, S. Z. Li, X. Liu, and E. Zhu, "Convert: Contrastive graph clustering with reliable augmentation," *arXiv preprint arXiv:2308.08963*, 2023.
- [88] X. Yang, Y. Liu, S. Zhou, S. Wang, X. Liu, and E. Zhu, "Contrastive deep graph clustering with learnable augmentation," *arXiv preprint arXiv:2212.03559*, 2022.
- [89] B. Hui, P. Zhu, and Q. Hu, "Collaborative graph convolutional networks: Unsupervised learning meets semi-supervised learning," in *Proc. of* AAAI, 2020.
- [90] R. Hu, S. Pan, G. Long, Q. Lu, L. Zhu, and J. Jiang, "Going deep: Graph convolutional ladder-shape networks," in *Proc. of AAAI*, 2020.
- [91] Y. Hu, X. Li, Y. Wang, Y. Wu, Y. Zhao, C. Yan, J. Yin, and Y. Gao, "Adaptive hypergraph auto-encoder for relational data clustering," *IEEE Transactions on Knowledge and Data Engineering*, 2021.

- [92] P.-Y. Huang, R. Frederking *et al.*, "Rwr-gae: Random walk regularization for graph auto encoders," *arXiv preprint arXiv:1908.04003*, 2019.
- [93] H. Zhang, P. Li, R. Zhang, and X. Li, "Embedding graph auto-encoder for graph clustering," *IEEE Transactions on Neural Networks and Learning Systems*, 2022.
- [94] W. Li, S. Wang, X. Guo, and E. Zhu, "Deep graph clustering with multi-level subspace fusion," *Pattern Recognition*, 2023.
- [95] J. Li, J. Yu, J. Li, H. Zhang, K. Zhao, Y. Rong, H. Cheng, and J. Huang, "Dirichlet graph variational autoencoder," *Proc. of NeurIPS*, 2020.
- [96] P. Zhu, J. Li, Y. Wang, B. Xiao, S. Zhao, and Q. Hu, "Collaborative decision-reinforced self-supervision for attributed graph clustering," *IEEE Transactions on Neural Networks and Learning Systems*, 2022.
- [97] H. Zhong, J. Wu, C. Chen, J. Huang, M. Deng, L. Nie, Z. Lin, and X.-S. Hua, "Graph contrastive clustering," in *Proc. of ICCV*, 2021.
- [98] S. Ding, B. Wu, X. Xu, L. Guo, and L. Ding, "Graph clustering network with structure embedding enhanced," *Pattern Recognition*, 2023.
- [99] N. Mrabah, M. Bouguessa, and R. Ksantini, "Escaping feature twist: A variational graph auto-encoder for node clustering," *Proceedings of the* 31st IJCAI.
- [100] L. Guo and Q. Dai, "Graph clustering via variational graph embedding," Pattern Recognition, 2022.
- [101] C. Wang, S. Pan, P. Y. Celina, R. Hu, G. Long, and C. Zhang, "Deep neighbor-aware embedding for node clustering in attributed graphs," *Pattern Recognition*, 2022.
- [102] L. Yang, Y. Wang, J. Gu, C. Wang, X. Cao, and Y. Guo, "Jane: Jointly adversarial network embedding." in *Proc. of IJCAI*, 2020.
- [103] L. Yu, S. Pei, L. Ding, J. Zhou, L. Li, C. Zhang, and X. Zhang, "Sail: Self-augmented graph contrastive learning," in *Proc. of AAAI*, 2022.
- [104] W. Xia, Q. Wang, Q. Gao, M. Yang, and X. Gao, "Self-consistent contrastive attributed graph clustering with pseudo-label prompt," *IEEE Transactions on Multimedia*, 2022.
- [105] T. Zhang, Y. Xiong, J. Zhang, Y. Zhang, Y. Jiao, and Y. Zhu, "Commdgi: community detection oriented deep graph infomax," in *Proc. of CIKM*, 2020.
- [106] Z. Tao, H. Liu, J. Li, Z. Wang, and Y. Fu, "Adversarial graph embedding for ensemble clustering," in *International Joint Conferences on Artificial Intelligence Organization*, 2019.
- [107] H. Liang and J. Gao, "Wasserstein adversarially regularized graph autoencoder," *Neurocomputing*, 2023.
- [108] H. Sun, Y. Li, B. Lv, W. Yan, L. He, S. Qiao, and J. Huang, "Graph community infomax," ACM Transactions on Knowledge Discovery from Data (TKDD), 2021.
- [109] T. Wang, G. Yang, Q. He, Z. Zhang, and J. Wu, "Ncagc: A neighborhood contrast framework for attributed graph clustering," *arXiv preprint* arXiv:2206.07897, 2022.
- [110] H. Xu, W. Xia, Q. Gao, J. Han, and X. Gao, "Graph embedding clustering: Graph attention auto-encoder with cluster-specificity distribution," *Neural Networks*, 2021.
- [111] Z. Peng, H. Liu, Y. Jia, and J. Hou, "Attention-driven graph clustering network," in *Proc. of ACM MM*, 2021.
- [112] —, "Deep attention-guided graph clustering with dual selfsupervision," *IEEE Transactions on Circuits and Systems for Video Technology*, 2022.
- [113] Z. Zhong, G. Gonzalez, D. Grattarola, and J. Pang, "Unsupervised network embedding beyond homophily," *Transactions on Machine Learning Research*, 2022.
- [114] G. K. Kulatilleke, M. Portmann, and S. S. Chandra, "Scgc: Self-supervised contrastive graph clustering," arXiv preprint arXiv:2204.12656, 2022.
- [115] L. Gong, S. Zhou, X. Liu, and W. Tu, "Attributed graph clustering with dual redundancy reduction," in *Proc. of IJCAI*, 2022.
- [116] D. Luo, J. Ni, S. Wang, Y. Bian, X. Yu, and X. Zhang, "Deep multigraph clustering via attentive cross-graph association," in *Proceedings* of the 13th international conference on web search and data mining, 2020.
- [117] R. A. Khan and M. Kleinsteuber, "Cluster-aware heterogeneous information network embedding," in *Proc. of WSDM*, 2022.
- [118] T. Li, W. Wang, P. Jiao, Y. Wang, R. Ding, H. Wu, L. Pan, and D. Jin, "Exploring temporal community structure via network embedding," *IEEE Transactions on Cybernetics*, 2022.
- [119] M. Liu, Y. Liu, K. Liang, S. Wang, S. Zhou, and X. Liu, "Deep temporal graph clustering," arXiv preprint arXiv:2305.10738, 2023.
- [120] N. Park, R. Rossi, E. Koh, I. A. Burhanuddin, S. Kim, F. Du, N. Ahmed, and C. Faloutsos, "Cgc: Contrastive graph clustering forcommunity detection and tracking," in *Proceedings of the ACM Web Conference* 2022, 2022.

- [121] J. Chung, C. Gulcehre, K. Cho, and Y. Bengio, "Empirical evaluation of gated recurrent neural networks on sequence modeling," *arXiv preprint* arXiv:1412.3555, 2014.
- [122] M. Liu, K. Liang, Y. Liu, S. Wang, S. Zhou, and X. Liu, "arxiv4tgc: Large-scale datasets for temporal graph clustering," *arXiv preprint* arXiv:2306.04962, 2023.
- [123] S. K. Pal and S. Mitra, "Multilayer perceptron, fuzzy sets, classifiaction," 1992.
- [124] W. Jin, X. Liu, X. Zhao, Y. Ma, N. Shah, and J. Tang, "Automated self-supervised learning for graphs," in *Proc. of ICLR*, 2021.
- [125] M. Ju, T. Zhao, Q. Wen, W. Yu, N. Shah, Y. Ye, and C. Zhang, "Multi-task self-supervised graph neural networks enable strongefr task generalization," in *Proc. of ICLR*, 2022.
- [126] D. A. Reynolds, "Gaussian mixture models." Encyclopedia of biometrics, 2009.
- [127] L. Li, S. Wang, X. Liu, E. Zhu, L. Shen, K. Li, and K. Li, "Local sample-weighted multiple kernel clustering with consensus discriminative graph," *IEEE Trans. Neural Networks*, 2022.
- [128] J. Zhang, L. Li, S. Wang, J. Liu, Y. Liu, X. Liu, and E. Zhu, "Multiple kernel clustering with dual noise minimization," in *Proc. of the 30-th* ACM Int. Conf. Multimedia, Lisboa, Portugal, 2022.
- [129] L. Li, J. Zhang, S. Wang, X. Liu, K. Li, and K. Li, "Multi-view bipartite graph clustering with coupled noisy feature filter," *IEEE Trans. Knowl. Data Eng.*, 2023.
- [130] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," arXiv preprint arXiv:1412.6980, 2014.
- [131] L. Bottou, "Large-scale machine learning with stochastic gradient descent," in *Proceedings of COMPSTAT'2010*, 2010.
- [132] W. Hu, M. Fey, M. Zitnik, Y. Dong, H. Ren, B. Liu, M. Catasta, and J. Leskovec, "Open graph benchmark: Datasets for machine learning on graphs," *Proc. of NeurIPS*, 2020.
- [133] R. S. Nickerson, "Confirmation bias: A ubiquitous phenomenon in many guises," *Review of general psychology*, 1998.
- [134] W. Hamilton, Z. Ying, and J. Leskovec, "Inductive representation learning on large graphs," *Proc. of NeurIPS*, 2017.
- [135] C. R. Shalizi and A. C. Thomas, "Homophily and contagion are generically confounded in observational social network studies," *Sociological methods & research*, 2011.
- [136] X. Zheng, Y. Liu, S. Pan, M. Zhang, D. Jin, and P. S. Yu, "Graph neural networks for graphs with heterophily: A survey," *arXiv preprint arXiv:2202.07082*, 2022.
- [137] W. Tu, S. Zhou, X. Liu, Y. Liu, Z. Cai, E. Zhu, Z. Changwang, and J. Cheng, "Initializing then refining: A simple graph attribute imputation network," *IJCAI*, pages, 2022.
- [138] X. Chen, S. Chen, J. Yao, H. Zheng, Y. Zhang, and I. W. Tsang, "Learning on attribute-missing graphs," *IEEE transactions on pattern* analysis and machine intelligence, 2020.
- [139] S. Chen and Y. C. Eldar, "Graph signal denoising via unrolling networks," in *Proc. of ICASSP*, 2021.
- [140] T. H. Do, D. M. Nguyen, and N. Deligiannis, "Graph auto-encoder for graph signal denoising," in *Proc. of ICASSP*, 2020.
- [141] J. Xia, H. Lin, Y. Xu, L. Wu, Z. Gao, S. Li, and S. Z. Li, "Towards robust graph neural networks against label noise," 2020.
- [142] P. Baldi, "Autoencoders, unsupervised learning, and deep architectures," in Proceedings of ICML workshop on unsupervised and transfer learning, 2012.
- [143] S. Zheng, Y. Song, T. Leung, and I. Goodfellow, "Improving the robustness of deep neural networks via stability training," in *Proc. of CVPR*, 2016.
- [144] A. Rozsa, M. Gunther, and T. E. Boult, "Towards robust deep neural networks with bang," arXiv preprint arXiv:1612.00138, 2016.
- [145] M. Li, T. Zhang, Y. Chen, and A. J. Smola, "Efficient mini-batch training for stochastic optimization," in *Proc. of KDD*, 2014.
- [146] L. Lovász, "Random walks on graphs," Combinatorics, Paul erdos is eighty, 1993.
- [147] B. Yang, X. Fu, N. D. Sidiropoulos, and M. Hong, "Towards k-meansfriendly spaces: Simultaneous deep learning and clustering," in *Proc. of ICML*, 2017.
- [148] A. Grover and J. Leskovec, "node2vec: Scalable feature learning for networks," in *Proc. of KDD*, 2016.
- [149] J. Xia, L. Wu, G. Wang, J. Chen, and S. Z. Li, "Progcl: Rethinking hard negative mining in graph contrastive learning," in *Proc. of ICML*, 2022.
- [150] J. Newling and F. Fleuret, "Nested mini-batch k-means," Proc. of NeurIPS, 2016.
- [151] S. Wang, X. Liu, L. Liu, W. Tu, X. Zhu, J. Liu, S. Zhou, and E. Zhu, "Highly-efficient incomplete large-scale multi-view clustering with consensus bipartite graph," in *Proc. of CVPR*, 2022.

- [152] W. Xia, Q. Gao, Q. Wang, X. Gao, C. Ding, and D. Tao, "Tensorized bipartite graph learning for multi-view clustering," *IEEE Transactions* on Pattern Analysis and Machine Intelligence, 2022.
- [153] Y. Liu, M. Jin, S. Pan, C. Zhou, Y. Zheng, F. Xia, and S. Y. Philip, "Graph self-supervised learning: A survey," *IEEE Transactions on Knowledge and Data Engineering*, 2022.
- [154] A. Rodriguez and A. Laio, "Clustering by fast search and find of density peaks," *science*, 2014.
- [155] K. Arulkumaran, M. P. Deisenroth, M. Brundage, and A. A. Bharath, "Deep reinforcement learning: A brief survey," *IEEE Signal Processing Magazine*, 2017.
- [156] P. Makwana, T. Kodinariya, and P. Makwana, "Review on determining of cluster in k-means clustering review on determining number of cluster in k-means clustering," *International Journal of Advance Research in Computer Science and Management Studies*, 2013.
- [157] Z. Wang, L. Zheng, Y. Li, and S. Wang, "Linkage based face clustering via graph convolution network," in *Proc. of CVPR*, 2019.
- [158] Y. Wang, Y. Zhang, F. Zhang, S. Wang, M. Lin, Y. Zhang, and X. Sun, "Ada-nets: Face clustering via adaptive neighbour discovery in the structure space," *arXiv preprint arXiv:2202.03800*, 2022.
- [159] K. Zhang, T. Li, S. Shen, B. Liu, J. Chen, and Q. Liu, "Adaptive graph convolutional network with attention graph clustering for co-saliency detection," in *Proc. of CVPR*, 2020.
- [160] H. Alwassel, D. Mahajan, B. Korbar, L. Torresani, B. Ghanem, and D. Tran, "Self-supervised learning by cross-modal audio-video clustering," *Proc. of NeurIPS*, 2020.
- [161] B. Chiu, S. K. Sahu, D. Thomas, N. Sengupta, and M. Mahdy, "Autoencoding keyword correlation graph for document clustering," in *Proc. of ACL*, 2020.
- [162] S. Qin, T. Jiang, S. Wu, N. Wang, and X. Zhao, "Graph convolutionbased deep clustering for speech separation," *IEEE Access*, 2020.
- [163] Y. Zhang, Z. Wang, and J. Shang, "Clusterllm: Large language models as a guide for text clustering," arXiv preprint arXiv:2305.14871, 2023.
- [164] S. Cavallari, V. W. Zheng, H. Cai, K. C.-C. Chang, and E. Cambria, "Learning community embedding with community detection and node embedding on graphs," in *Proceedings of the 2017 ACM on Conference* on Information and Knowledge Management, 2017.
- [165] B. Rozemberczki, R. Davies, R. Sarkar, and C. Sutton, "Gemsec: Graph embedding with self clustering," in *Proceedings of the 2019 IEEE/ACM international conference on advances in social networks analysis and mining*, 2019.
- [166] C. Tu, X. Zeng, H. Wang, Z. Zhang, Z. Liu, M. Sun, B. Zhang, and L. Lin, "A unified framework for community detection and network representation learning," *IEEE Transactions on Knowledge and Data Engineering*, 2018.
- [167] F. Liu, S. Xue, J. Wu, C. Zhou, W. Hu, C. Paris, S. Nepal, J. Yang, and P. S. Yu, "Deep learning for community detection: progress, challenges and opportunities," *arXiv preprint arXiv:2005.08225*, 2020.
- [168] I. Ahmed, T. Galoppo, X. Hu, and Y. Ding, "Graph regularized autoencoder and its application in unsupervised anomaly detection," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.
- [169] X. Ma, J. Wu, S. Xue, J. Yang, C. Zhou, Q. Z. Sheng, H. Xiong, and L. Akoglu, "A comprehensive survey on graph anomaly detection with deep learning," *IEEE Transactions on Knowledge and Data Engineering*, 2021.
- [170] Y. Chen, Z. Liu, J. Li, J. McAuley, and C. Xiong, "Intent contrastive learning for sequential recommendation," in *Proceedings of the ACM Web Conference 2022*, 2022.
- [171] G. Grunig, N. Durmus, Y. Zhang, Y. Lu, S. Pehlivan, Y. Wang, K. Doo, M. L. Cotrina-Vidal, R. Goldring, K. I. Berger *et al.*, "Molecular clustering analysis of blood biomarkers in world trade center exposed community members with persistent lower respiratory symptoms," *International journal of environmental research and public health*, 2022.
- [172] J. Xia, Y. Zhu, Y. Du, Y. Liu, and S. Z. Li, "A systematic survey of molecular pre-trained models," arXiv preprint arXiv:2210.16484, 2022.
- [173] H. Xue, V. Mallawaarachchi, Y. Zhang, V. Rajan, and Y. Lin, "Repbin: Constraint-based graph representation learning for metagenomic binning," in *Proc. of AAAI*, 2022.
- [174] H. Alashwal, M. El Halaby, J. J. Crouse, A. Abdalla, and A. A. Moustafa, "The application of unsupervised clustering methods to alzheimer's disease," *Frontiers in computational neuroscience*, 2019.
- [175] R. Jiang, S. Han, Y. Yu, and W. Ding, "An access control model for medical big data based on clustering and risk," *Information Sciences*, 2023.
- [176] R. Dhaundiyal, A. Tripathi, K. Joshi, M. Diwakar, and P. Singh, "Clustering based multi-modality medical image fusion," in *Journal of Physics: Conference Series*, 2020.



Yue Liu is a computer science master's student at National University of Dense Technology (NUDT). His research interests include selfsupervised learning, deep graph clustering, and knowledge graphs. He has published 10+ peerreviewed papers, including ICLR, ICML, AAAI, IJCAI, ACM MM, SIGIR, IEEE T-KDE, and IEEE T-NNLS. More detailed information is listed on his homepage: https://yueliu1999.github.io/.



**Chenchen Fan** is a postdoctoral researcher at the Chinese PLA General Hospital. Prior to this, he obtained his PhD from the Institute of Automation, Chinese Academy of Sciences and his bachelor's degree from the Beijing University of Chemical Technology. His research interests include medical artificial intelligence, medical image processing, etc.



Jun Xia received the B. Eng honour degree from Central South University (CSU), Changsha, China in 2020. He is currently pursuing Ph.D. degree at Westlake University and Zhejiang University (ZJU), Hangzhou, China, supervised by Chair Professor Stan Z.Li (IEEE Fellow). His research interests include graph neural networks and AI for scientific discovery. He has published 20+ papers in top-tier conferences such as IEEE T-KDE, ICML, ICLR, CVPR, WWW, ACL, IJCAI, ACM Multimedia, ECML-PKDD, etc.



Yan Zhuang is now a senior engineer at Medical Big Data Research Center, Chinese PLA General Hospital. He has rich experience in hospital informatization and research, expertized in medical big data and artificial intelligence technologies. He has published 20+ papers as the first author and 90+ collaborative papers in the field of medical big data. In addition, He was honored with the Best Paper Award at CIKM 2017.



Sihang Zhou received his PhD degree from School of Computer, National University of Defense Technology (NUDT), China. He is now lecturer at College of Intelligence Science and Technology, NUDT. His current research interests include machine learning and medical image analysis. Dr. Zhou has published 40+ peerreviewed papers, including IEEE T-IP, IEEE T-NNLS, IEEE T-MI, Information Fusion, Medical Image Analysis, AAAI, MICCAI, etc.



**Stan Z. Li** received Ph.D. degree from Surrey University, United Kingdom. He is currently a chair professor and the director of Center for Artificial Intelligence Research and Innovation (CAIRI), School of Engineering, Westlake University. His research interests include pattern recognition, machine learning, image processing, face recognition, biometrics, and intelligent video surveillance. He has published 400+ papers in international journals and conferences and authored and edited eight books. He was an

associate editor of the IEEE T-PAMI. He was elevated to IEEE fellow for his contributions to face recognition, pattern recognition, and computer vision, and he is a member of the IEEE Computer Society.



Xihong Yang is pursuing his Ph.D. at National University of Defense Technology (NUDT), China. His current research interests include semi-supervised learning, self-supervised learning, and graph neural networks. He has published several papers in top journals and conferences, such as IEEE T-NNLS, IEEE T-KDE, IEEE T-AI, AAAI, ICML, ACM MM, etc.



Xinwang Liu received his PhD degree from National University of Defense Technology (NUDT), China. He is now Professor of School of Computer, NUDT. His current research interests include kernel learning and unsupervised feature learning. Dr. Liu has published 60+ peerreviewed papers, including those in highly regarded journals and conferences such as IEEE T-PAMI, IEEE T-KDE, IEEE T-IP, IEEE T-NNLS, IEEE T-MM, IEEE T-IFS, ICML, NeurIPS, ICCV, CVPR, AAAI, IJCAI, etc. He serves as the asso-

ciated editor of T-NNLS, T-CYB and Information Fusion Journal. More information can be found at https://xinwangliu.github.io/.



Ke Liang is currently pursuing a Ph.D. degree at the National University of Defense Technology (NUDT). Before joining NUDT, he got BSc degree from Beihang University (BUAA) in 2017 and MSc degree from Pennsylvania State University (PSU) in 2021. His research interests include knowledge graphs, graph learning, healthcare AI, and urban computing. He has published several top-tier journal and conference papers, *e.g.*, IEEE T-KDE, IEEE T-NNLS, SIGIR, AAAI, ICML, ACM MM, etc.



**Kunlun He** received his M.D. degree from The 3rd Military Medical University, Chongqing, China, in 1988, and Ph.D. degree in Cardiology from Chinese PLA Medical School, Beijing, China, in 1999. He worked as a postdoctoral research fellow at the Division of circulatory physiology of Columbia University from 1999 to 2003. He is the director and professor of Medical Big Data Research Center, Chinese PLA General Hospital, Beijing, China. His research interests include medical big data and artificial

intelligence for cardiovascular disease.