

Neural activity as vector fields

Siddharth Kackar^{1,2}

1 - Department of Physics, Imperial College London, London, United Kingdom

2 - Institute of Ophthalmology, University College London, London, United Kingdom

Abstract

We consider the information transmission problem in neurons and its possible implications for learning in neural networks. Our approach is based on recent developments in statistical physics and complexity science. We also develop a method to try and select significant neural responses from the background activity and consider its wider applications. This would support temporal coding theory as a model for neural coding.

The aggregate activity of neurons

In order to understand the transfer of information in the nervous system, we need to understand the relationship between a stimulus and the response it evokes in a single or network of neurons. In addition, we also need to understand how that stimulus is represented or coded in the neuron and how that representation relates to observed behavior. Neural coding is concerned with the study of these two aspects of information flow. I want to use our current knowledge of neural coding and information theory to study how the brain perceives the statistical features of the input and encodes them to form representations of our world. Also, I want to study how the brain stores this information in the longer term i.e., how it learns from probabilistic stimuli. Ultimately, we want to contribute toward a unified understanding of perception and learning. This will require the combined efforts of electrophysiologists, molecular biologists, and cognitive scientists and we want to contribute to this problem from a computational/theoretical standpoint.

While much progress has been made in mapping neural correlates of sensory or motor variables, we still have a very limited understanding of how the microarchitecture of brain circuitry supports cognitive processes underlying thinking, memory, and decision-making. A particularly important challenge is to clarify the operating principles governing how information processing is coordinated over time across large spatial scales. The human brain is far “smarter” than a current generation supercomputer yet consumes 100,000-fold less space and energy (Sterling & Laughlin, 2015). Neural dynamics have been observed to show a temporal mode of emergence. There are long periods of quiescence followed by sudden bursts of activity (Tagliazucchi et al., 2012). This pattern of activity may be associated with consciousness (Paradisi et al., 2013). Principles from statistical physics and information theory may provide powerful tools for revealing these operating principles.

In recent years, the statistical physics of avalanches – as observed in earthquakes, sandpiles, and forest fires – has been used to explain the dynamics of bursts of neuronal activity observed spontaneously in brain tissue in culture and in vivo (Beggs & Plenz, 2003; Hahn et al., 2010; Petermann et al., 2009). It is well known that brain dynamics at the neuronal level usually involve intermittent bursts of activity in the form of avalanche-like phenomena spanning a wide range of spatiotemporal scales. However, there is an important knowledge gap in establishing how this intermittent phenomenon underpins higher brain function. Aligning with the theory of critical branching processes, the propagation of these bursts follows a power law with an exponent of $-3/2$ for event sizes, with a branching parameter close to the critical value of 1 (Christensen & Moloney, 2005; Jensen, 1998, 2022). This has been suggested to optimize information transmission in networks, while preventing runaway network excitation, with such avalanches providing a signature of a multiscale self-organizing process. The precise operating point, near to criticality, used by neural circuits remains a matter of debate. Slice physiology indicates the balance of excitation and inhibition found in vivo seems to favor self-organized criticality (Shew et al., 2011). It has also been conjectured that it may be advantageous for brain networks to operate just below criticality (Beggs, 2022; Williams-García et al., 2014).

However, a crucial unanswered question is how neuronal avalanches affect behavior, and in particular cognitive phenomena such as memory and decision-making which we might expect to be driven by internal processes. Altered avalanche dynamics have been implicated in cognitive dysfunction caused by schizophrenia (Seshadri et al., 2018). The emergence of technology for simultaneously monitoring up to tens of thousands of neurons across the brain (Demas et al., 2021; Stringer et al., 2021) makes it timely, and crucially important, to develop theoretical approaches to make sense of the brain-scale coordination of information processing critical to understanding cognitive function.

Practitioners in the finance industry, where the log-normal distribution occurs frequently, have been working on using Monte Carlo simulations to predict rare events (Taleb, 2005). There is experimental evidence for the log-normal distribution of neural responses (Buzsáki & Mizuseki, 2014; Koulakov et al., 2009). Topological vector fields have also been used to model neural activity (Curto, 2017).

We wrote a MATLAB function that selects neurons responding to specific stimuli using paired t-tests between the firing rates before and after the stimulus event. A modified Bonferroni correction with the alpha equal to the square root of the number of terms works best. It implies that neurons encode information as aggregates. This would support temporal coding theory as a model for neural coding, as it is the fluctuations in the firing rate from the baseline that encode information about the stimulus.

Information theory and neural coding

Information theory provides mathematically rigorous tools to quantify the precision of information transmission, setting theoretical limits on maximum information capacity (Borst & Theunissen, 1999). The three central questions in the field of neural coding are to find out:

1. What is being encoded? For example, whether the information is encoded in the amplitude of spikes or the change in amplitude?
2. How is it being encoded? The question of rate vs temporal coding has seen conflicting reports, with conventional studies supporting rate coding as standard (Adrian & Zotterman, 1926), but more recent studies reporting examples of temporal coding (Stein et al., 2005).
3. With what precision is it being encoded? What is the degree of variability in the responses?

Neuroscientists have traditionally addressed the first two questions by studying stimulus-response curves and changing the stimulus ensembles and response measures. Error bars were used to assess the variability. Information theory, on the other hand, provides mathematically rigorous tools to quantify the precision of information transmission, setting theoretical limits on maximum information capacity. The theory can be applied to study neural coding in the following ways:

1. Estimating the maximum information capacity (channel capacity) of a neuron and the actual information transmitted, to quantify efficiency.
2. Compare the upper bound of information transmitted with that of an optimal linear model, to test for non-linearities and find out how a neuron transforms our data.
3. Determining the limiting temporal precision of code i.e., the minimal timescale in which information is contained, to find out if there is any information in the precise timings of the spikes.

To calculate maximal information transfer, a new quantity was introduced, called entropy. Entropy characterizes how many free states a variable can assume and the probability of each i.e., the variability. Entropy is the information needed to eliminate all uncertainty about a variable. In fact, information can be considered as a reduction in entropy. There are three common approaches used for estimating the mutual information between the stimulus and response, the direct method, which calculates the exact value of information, and the upper and lower bound methods. Factors such as the experimental parameters and quality of stimulus ensembles determine our choice of method. Generally, a combination of all three is used as an optimal linear model.

Another area of application of information theory is population coding. Population coding is defined as a method to represent stimuli from multiple neurons. The response of each neuron has a probabilistic distribution over a set of stimuli, which is considered together with other neurons to characterize certain features of the input. Population analysis is reported to have several advantages over single-neuron recordings in reducing uncertainty due to neuronal variability and the ability to represent different attributes of the stimulus simultaneously.

Studies have suggested using linear decoding algorithms for population recordings in conjunction with information-theoretic tools as mutual information gives a more comprehensive quantification of the information contained in a neuronal population, by evaluating the reduction of uncertainty about the stimuli that can be obtained from the neuronal responses (Quiñero & Panzeri, 2009). Representing uncertainty is important for decisions involving risks and may be fundamental for neuronal computations that take place in the presence of both sensory and neural noise.

The information bottleneck method

The information bottleneck method (Tishby et al., 2000) tries to answer how much relevant information survives a communication. Suppose there is an input variable X with a hidden characteristic Y . In order to transfer relevant information about Y from X to the output state T , we try to maximize the mutual information between Y and T , which is bounded above by the mutual information between X and T (by the data processing theorem), which we are trying to minimize. What this means is that we are trying to preserve the maximum amount of relevant information about Y , while letting go of the unnecessary parts of X . This creates the “information bottleneck” in the T - X - Y Markov chain.

Experiments on the H1 motion-sensitive neuron of the fly visual system tried to characterize the neural “dictionary” containing the relevant stimuli and their respective responses, using the information bottleneck (Schneidman et al., 2001). They tried to quantify the compressibility of said dictionary i.e., they tried to find out which features of the stimuli are relevant. They found that the stimulus code was highly compressible meaning the neuron was sensitive to only a few significant features. This feature of compressibility was preserved in different flies.

The information bottleneck method also has applications in understanding deep learning. Each layer of a deep neural network can be treated as input and output points for the surrounding layers, requiring analysis of information compression by the bottleneck method (Schwartz-Ziv & Tishby, 2017; Tishby & Zaslavsky, 2015). However, recent studies have argued against this method being used to explain deep learning saying that the results of Schwartz-Ziv and Tishby are particular to their setup and do not hold true in the general case (Saxe et al., 2019). Thus, this is an area of intense interest in both neuroscience and machine learning communities.

Information bottleneck and the renormalization group

In the context of neuroscience, both the information bottleneck and the renormalization group are coarse-graining methods used to analyze the flow of information between the layers of a neural network (Meshulam et al., 2019). In another paper published the same year, they presented the renormalization group and the information bottleneck in a unified framework (Tan et al., 2019). Their renormalization procedure achieves a coarse-graining where they can choose which relevant features they want to keep, for example, by keeping information about long-range interactions while removing local information. Other studies have drawn parallels between the coarse-graining performed by neural networks and renormalization group procedures (Iso et al., 2018), found similarities in the notion of “relevance” in renormalization and the information bottleneck (Gordon et al., 2021), and have devised a self-supervised learning method based on combining the renormalization group and the information bottleneck (Ngampruetikorn et al., 2020).

If aggregates of neurons are the functional units of information storage, then I believe that there is an inherent limit of resolution to our attempts to model it. So, when we use coarse-graining methods to zoom in or zoom out, there is an inherent component of uncertainty or noise. As these methods are approximating a very noisy process, they may belong to the same universality class.

Future directions

Speculating further, we would want to study how these ideas relate to Alfred North Whitehead’s process philosophy (Lowe, 2020; Sherburne, 1966; Whitehead, 2010) and quantum computation in the brain (Penrose & Mermin, 1998). It may be that neurons encode information as aggregates of bits. Then, measurement is the unit process of a bit being defined in either of the two states +1 or -1 in unit time. The limit of resolution that is imposed on the system seems to be like the measurement problem in quantum mechanics. This would mean that a qubit is just two bits entangled by gravity, which is the simplest form of interaction between them. “Spooky action at a distance” could be just gravity.

If successful, then maybe this work can be extended to other complex systems, with the connecting link being the statistics of rare events. These could include studying prime numbers through the Erdős-Kac theorem, and Fermat’s last theorem through integrability and maybe even information encoding in black holes through the holographic principle. A couple of (simpler?) situations are considered here as examples.

It seems to us that the trains on the London tube network are grouped together in clusters (like bursts of neural activity). When we arrive on the platform, and there is a train already there, for

example, if I just miss it, then the next one is only 1 minute away (mostly, sometimes it is 2 minutes). But, if there is no train on the platform when I arrive, then we must wait for 3/4/5 minutes. An exception to this may be when the train on the platform is the last train of a cluster and so the next one arrives a bit later. We could also explore applications of ideas from criticality to game theoretic situations where information is encoded in aggregates, such as opinion formation.

We are essentially studying an information transmission problem in neurons. The function we wrote, sigSort, can be viewed as preventing false alarms i.e. preventing the neurons from responding to noise / false stimuli. If this can be developed further along the lines of correlation measures and correlated systems, it may be applied to design or improve technology like correlated or clustered detonation systems, which may even have nuclear applications. Such technology may also be used for long-distance space travel.

References

- Adrian, E. D., & Zotterman, Y. (1926). The impulses produced by sensory nerve endings: Part 3. Impulses set up by Touch and Pressure. *The Journal of Physiology*, 61(4), 465.
<https://doi.org/10.1113/JPHYSIOL.1926.SP002308>
- Beggs, J. M. (2022). *The Cortex and the Critical Point: Understanding the Power of Emergence*. MIT Press.
- Beggs, J. M., & Plenz, D. (2003). Neuronal Avalanches in Neocortical Circuits. *Journal of Neuroscience*, 23(35), 11167–11177. <https://doi.org/10.1523/JNEUROSCI.23-35-11167.2003>
- Borst, A., & Theunissen, F. E. (1999). Information theory and neural coding. *Nature Neuroscience* 1999 2:11, 2(11), 947–957. <https://doi.org/10.1038/14731>
- Buzsáki, G., & Mizuseki, K. (2014). The log-dynamic brain: how skewed distributions affect network operations. *Nature Reviews Neuroscience* 2014 15:4, 15(4), 264–278.
<https://doi.org/10.1038/nrn3687>
- Christensen, K., & Moloney, N. R. (2005). *Complexity and criticality* (Vol. 1). World Scientific Publishing Company.
- Curto, C. (2017). What can topology tell us about the neural code? *Bulletin of the American Mathematical Society*, 54(1), 63–78. <https://doi.org/10.1090/BULL/1554>
- Demas, J., Manley, J., Tejera, F., Barber, K., Kim, H., Traub, F. M., Chen, B., & Vaziri, A. (2021). High-speed, cortex-wide volumetric recording of neuroactivity at cellular resolution using light beads microscopy. *Nature Methods* 2021 18:9, 18(9), 1103–1111.
<https://doi.org/10.1038/s41592-021-01239-8>
- Gordon, A., Banerjee, A., Koch-Janusz, M., & Ringel, Z. (2021). Relevance in the Renormalization Group and in Information Theory. *Physical Review Letters*, 126(24), 240601.
<https://doi.org/10.1103/PHYSREVLETT.126.240601/FIGURES/3/MEDIUM>
- Hahn, G., Petermann, T., Havenith, M. N., Yu, S., Singer, W., Plenz, D., & Nikolić, D. (2010). Neuronal avalanches in spontaneous activity in vivo. *Journal of Neurophysiology*, 104(6), 3312–3322.
<https://doi.org/10.1152/JN.00953.2009/ASSET/IMAGES/LARGE/Z9K0091003280008.JPEG>
- Iso, S., Shiba, S., & Yokoo, S. (2018). Scale-invariant feature extraction of neural network and renormalization group flow. *Physical Review E*, 97(5), 053304.
<https://doi.org/10.1103/PHYSREVE.97.053304/FIGURES/18/MEDIUM>
- Jensen, H. J. (1998). *Self-organized criticality: emergent complex behavior in physical and biological systems* (Vol. 10). Cambridge university press.
- Jensen, H. J. (2022). *Complexity Science: The Study of Emergence*. Cambridge University Press.
- Koulakov, A. A., Hromádka, T., & Zador, A. M. (2009). Correlated Connectivity and the Distribution of Firing Rates in the Neocortex. *Journal of Neuroscience*, 29(12), 3685–3694.
<https://doi.org/10.1523/JNEUROSCI.4500-08.2009>
- Lowe, V. (2020). *Understanding Whitehead*. JHU Press.

- Meshulam, L., Gauthier, J. L., Brody, C. D., Tank, D. W., & Bialek, W. (2019). Coarse graining, fixed points, and scaling in a large population of neurons. *Physical Review Letters*, *123*(17), 178103. <https://doi.org/10.1103/PHYSREVLETT.123.178103>/FIGURES/5/MEDIUM
- Ngampruetikorn, V., Bialek, W., & Schwab, D. (2020). Information-bottleneck renormalization group for self-supervised representation learning. *Bulletin of the American Physical Society*, *Volume 65*, Number 1.
- Paradisi, P., Allegrini, P., Gemignani, A., Laurino, M., Menicucci, D., & Piarulli, A. (2013). Scaling and intermittency of brain events as a manifestation of consciousness. *AIP Conference Proceedings*, *1510*(1), 151. <https://doi.org/10.1063/1.4776519>
- Penrose, R., & Mermin, N. D. (1998). The Emperor's New Mind: Concerning Computers, Minds, and the Laws of Physics. *American Journal of Physics*, *58*(12), 1214. <https://doi.org/10.1119/1.16207>
- Petermann, T., Thiagarajan, T. C., Lebedev, M. A., Nicolelis, M. A. L., Chialvo, D. R., & Plenz, D. (2009). Spontaneous cortical activity in awake monkeys composed of neuronal avalanches. *Proceedings of the National Academy of Sciences of the United States of America*, *106*(37), 15921–15926. <https://doi.org/10.1073/PNAS.0904089106>
- Quiari Quiroga, R., & Panzeri, S. (2009). Extracting information from neuronal populations: information theory and decoding approaches. *Nature Reviews Neuroscience* *2009 10:3*, *10*(3), 173–185. <https://doi.org/10.1038/nrn2578>
- Saxe, A. M., Bansal, Y., Dapello, J., Advani, M., Kolchinsky, A., Tracey, B. D., & Cox, D. D. (2019). On the information bottleneck theory of deep learning*. *Journal of Statistical Mechanics: Theory and Experiment*, *2019*(12), 124020. <https://doi.org/10.1088/1742-5468/AB3985>
- Schneidman, E., Slonim, N., Tishby, N., van Steveninck, R. deRuyter, & Bialek, W. (2001). Analyzing neural codes using the information bottleneck method. *Advances in Neural Information Processing Systems, NIPS*.
- Schwartz-Ziv, R., & Tishby, N. (2017). *Opening the Black Box of Deep Neural Networks via Information*. <https://doi.org/10.48550/arxiv.1703.00810>
- Seshadri, S., Klaus, A., Winkowski, D. E., Kanold, P. O., & Plenz, D. (2018). Altered avalanche dynamics in a developmental NMDAR hypofunction model of cognitive impairment. *Translational Psychiatry* *2017 8:1*, *8*(1), 1–12. <https://doi.org/10.1038/s41398-017-0060-z>
- Sherburne, D. W. (1966). *A key to Whitehead's process and reality*.
- Shew, W. L., Yang, H., Yu, S., Roy, R., & Plenz, D. (2011). Information Capacity and Transmission Are Maximized in Balanced Cortical Networks with Neuronal Avalanches. *Journal of Neuroscience*, *31*(1), 55–63. <https://doi.org/10.1523/JNEUROSCI.4637-10.2011>
- Stein, R. B., Gossen, E. R., & Jones, K. E. (2005). Neuronal variability: noise or part of the signal? *Nature Reviews Neuroscience* *2005 6:5*, *6*(5), 389–397. <https://doi.org/10.1038/nrn1668>
- Sterling, P., & Laughlin, S. (2015). *Principles of neural design*. MIT press.
- Stringer, C., Michaelos, M., Tsyboulski, D., Lindo, S. E., & Pachitariu, M. (2021). High-precision coding in visual cortex. *Cell*, *184*(10), 2767–2778.e15. <https://doi.org/10.1016/J.CELL.2021.03.042>

- Tagliazucchi, E., Balenzuela, P., Fraiman, D., & Chialvo, D. R. (2012). Criticality in large-scale brain fmri dynamics unveiled by a novel point process analysis. *Frontiers in Physiology*, 3 FEB, 15. <https://doi.org/10.3389/FPHYS.2012.00015/BIBTEX>
- Taleb, N. (2005). *The black swan: Why don't we learn that we don't learn*. NY: Random House, 1145.
- Tan, A., Meshulam, L., Bialek, W., Schwab, D., Tan, A., Meshulam, L., Bialek, W., & Schwab, D. (2019). The renormalization group and information bottleneck: a unified framework. *APS*, 2019, F66.007. <https://ui.adsabs.harvard.edu/abs/2019APS..MARF66007T/abstract>
- Tishby, N., Pereira, F. C., & Bialek, W. (2000). *The information bottleneck method*.
- Tishby, N., & Zaslavsky, N. (2015). Deep learning and the information bottleneck principle. 2015 *IEEE Information Theory Workshop, ITW 2015*. <https://doi.org/10.1109/ITW.2015.7133169>
- Whitehead, A. N. (2010). *Process and reality*. Simon and Schuster.
- Williams-García, R. V., Moore, M., Beggs, J. M., & Ortiz, G. (2014). Quasicritical brain dynamics on a nonequilibrium Widom line. *Physical Review E - Statistical, Nonlinear, and Soft Matter Physics*, 90(6), 062714. <https://doi.org/10.1103/PHYSREVE.90.062714/FIGURES/7/MEDIUM>