AQSA ASHRAF MAKHDOMI and IQRA ALTAF GILLANI, NIT Srinagar, India

In recent years, ridesharing platforms have become a prominent mode of transportation for the residents of urban areas. One of the fundamental challenges faced by these platforms is providing efficient route recommendations to drivers. Existing studies in this direction have primarily focused on recommending routes based on the expected passenger demand. Despite the existing works, statistics have suggested that these services cause increased greenhouse emissions as they do not utilize the vehicle capacity efficiently. To address this, we propose to recommend routes that will fetch multiple passengers simultaneously which will result in increased vehicle utilization and decrease the effect of these systems on environment. We establish that route recommendation is NP-hard and develop a k-hop-based sliding window to reduce the search space from the entire road network to a window. We further show that maximizing expected passenger requests within a window is submodular which provides greedy algorithms as a solution to optimize the objective function. In addition to route recommendation, we address the challenge of determining the minimum number of vehicles required to fulfill all passenger requests in a given area. Extensive simulations on the datasets of New York City and Washington DC demonstrate superior performance by our proposed model.

 $\label{eq:ccs} \texttt{CCS Concepts:} \bullet \textbf{Information systems} \to \texttt{Spatial-temporal systems}; \bullet \textbf{Applied computing} \to \texttt{Transportation}.$ 

Additional Key Words and Phrases: Route recommendation, ridesharing, heuristics, greedy approach, submodular, fleet size.

#### **ACM Reference Format:**

Aqsa Ashraf Makhdomi and Iqra Altaf Gillani. 2024. A Greedy Approach for Increased Vehicle Utilization in Ridesharing Platforms. *ACM Trans. Inf. Syst.* 1, 1 (January 2024), 30 pages. https://doi.org/10.1145/nnnnnnnnnnnnnnn

# **1 INTRODUCTION**

Due to the prominent development of internet and GPS-enabled services, the dynamics of ridehailing platforms have changed completely. People have now become used to travelling over these services for their day-to-day activities. However, this increased surge has resulted in their shortage over peak hours. In order to avoid the absence of vehicles during peak hours and provide efficient utilization of vehicles, ridesharing has been proposed as a solution wherein the different users with similar routes share a single vehicle. This potentially brings up many benefits for an urban city and results in alleviating traffic congestion, providing eco-friendly rides, and reducing the waiting time of passengers [3]. Owing to the benefits made by these platforms, they have received significant attention from researchers around the globe. Various methods have been proposed for effective matching [15], route planning [29], and route recommendation [39] in ridesharing platforms.

Authors' address: Aqsa Ashraf Makhdomi, makhdoomiaqsa@gmail.com; Iqra Altaf Gillani, iqraaltaf@nitsri.ac.in, NIT Srinagar, Hazratbal, Srinagar, Jammu & Kashmir, India, 190020.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

https://doi.org/10.1145/nnnnnnnnnnn

<sup>© 2024</sup> Association for Computing Machinery.

<sup>1046-8188/2024/1-</sup>ART \$15.00

Despite their popularity, it has been found that the ridesharing services do not utilize the available vehicle capacity in an efficient manner. Statistics have suggested that ridesharing platforms share only 15% of their rides [19] whereas 73% of rides can be shared with a slight increase in waiting time of passengers [4] which can result in the efficient utilization of vehicles. Therefore, it becomes important to design effective recommendation systems that predict future requests and pair up multiple passengers with similar schedules in a single vehicle which will reduce the fossil fuel consumption that contributes both to local air pollution and climate change.

Existing works in this direction have recommended the routes with higher expected passenger demand [39]. These works have predicted the number of passenger requests that arrive at different locations and directed the routes with the highest number of expected requests to the drivers. However, passenger mobility patterns can be better analyzed if the origin (the place from where the passenger request arrives), as well as the destination (the place to which the passenger wants to travel) of requests, can be predicted in advance. When the origin and destination locations of passenger requests are predicted, ridesharing platforms gain the ability to identify passengers with similar or overlapping travel routes. As a result, it can recommend routes to drivers where multiple passengers have similar routes and a single vehicle can accommodate them, which reduces the overall number of vehicles required to serve the same number of passengers. To the best of our knowledge, none of the existing works so far have recommended the routes to ridesharing platforms keeping in consideration the origin and destination of requests.

We demonstrate that the problem of route recommendation using the origin and destination of passenger requests is NP-Hard, and no polynomial time algorithm exists that can solve it on a deterministic machine. In order to overcome it, we develop a *k*-hop-based sliding window approach that will reduce the search space from the entire road network to a window and thereby improve the time complexity of the model. Moreover, the underlying objective function of the proposed function, which utilizes the origin and destination of requests, is submodular and greedy algorithms are known to provide well-known approximation guarantees for these functions and we have applied them to maximize our objective function within the corresponding window.

After applying the greedy strategy, we determine the optimal fleet size required by the ridesharing companies. The optimal fleet size represents the minimum number of vehicles that ridesharing companies must possess to effectively service all passenger requests within a specific city. The determination of the optimal fleet size establishes a lower limit on the vehicle count necessary to fulfil the requests within the designated area and gives ridesharing companies an overview of resources required over different time instants. It is determined by converting the graph that stores the origin and destination of requests, into a vehicle count graph, and applying minimum path cover on it.

In this paper, we develop an eco-friendly route recommendation system for ridesharing platforms that decreases the extra miles travelled by vehicles by predicting the origin and destination of passenger requests and thereby pairs these requests effectively in a single vehicle. The proposed approach utilizes a k-hop window, to decrease the complexity of route recommendation from the road network to a small area and slides this window forward in the direction of expected passenger requests. Through this approach, we calculate the fleet size required by our proposed model to cover the entire area which determines the resource utilization of ridesharing platforms over different time periods of the day.

Our key contributions can be summarized as follows:

• We propose an eco-friendly route recommendation system for the drivers of the ridesharing platforms which reduces pollution and promotes sustainability.

- We show that the proposed problem of route recommendation is NP-hard. We overcome the computational complexity by developing a *k*-hop-based sliding window algorithm that reduces the exponential search space from all possible paths in the entire road network to a window.
- We demonstrate that the underlying objective function of our proposed model is submodular and thereby greedy algorithms can be used to optimize them, as they are known to provide well-known approximation bounds for submodular functions.
- A vehicle count graph is constructed to determine the minimum fleet size required to cover the requests that arrive in the ridesharing platforms. This is done by reducing the origin-destination request arrival graph and applying the minimum path cover to it.
- We evaluate the performance of our proposed model extensively on real-world datasets from New York and Washington DC across different metrics. The experimental results demonstrate that our proposed route recommendation system improves vehicle utilization, and decreases the count of vehicles on the road.

# 2 RELATED WORK

The eco-friendly nature of route recommendation systems can be reviewed from two aspects: 1) Effective vehicle utilization, and 2) Optimal fleet size.

# 2.1 Route recommendation

Ride-hailing platforms have received considerable attention in the research community, with numerous efforts focused on optimizing their functionality. Existing studies in this direction have designed matching algorithms [24–26, 37] which match the passenger requests with drivers, route planning frameworks [6, 29, 30, 33] which insert a new request into the existing route of drivers without changing the origin and destination of passengers already in the vehicle, and route recommendation systems [11, 13, 17, 23, 26, 27, 38, 39] that recommend routes to drivers to ensure they get passengers quickly. In our proposed model, we provide the design of a route recommendation system.

The current route recommendation systems aim to achieve diverse objectives, such as reducing the cruising distance of drivers without having a rider in the vehicle [11, 39], decreasing the waiting time of passengers [13, 38], and increasing the profit of drivers [9, 11, 12, 14, 21, 22, 32, 39]. These works have predicted the passenger demand using various deep learning frameworks [35, 36] and recommended the routes with the highest passenger demand. Some of these works [23, 26, 27, 39] have enabled ridesharing and paired multiple riders in a single vehicle.

Despite the prior research, statistical analysis reveals that ridesharing platforms currently share a mere 15% of their rides [19], while a significant 73% of rides could be shared with a slight increase in the waiting time of passengers [4]. This suggests that there is considerable room for enhancing the utilization of vehicles through the effective design of recommendation systems. Our proposed model overcomes this problem and utilizes the vehicle capacity efficiently by predicting the origin and destination of requests and thereupon pairs the passengers in a vehicle based on their shared routes.

## 2.2 Optimal fleet size.

The determination of the optimal fleet size plays a pivotal role in comprehending resource utilization within ride-hailing platforms. It offers valuable insights to ride-hailing companies regarding the number of vehicles needed to effectively service passenger requests in a specific geographic area. Extensive research has been conducted to determine the optimal fleet size, predominantly employing simulation-based methodologies [1, 2, 5, 10]. However, these simulation-based approaches have

certain limitations. They heavily depend on initial driver positioning and necessitate multiple rounds of simulations to arrive at the optimal fleet size. Recognizing this challenge, Vazifeh *et al.* [31] introduced a network flow-based model to determine the optimal fleet size for ride-hailing platforms. Their proposed model formulated the optimal request calculation as a minimum path cover on a graph and determined the minimum number of vehicles required to effectively service passengers operating in ride-hailing (solo) mode. However, their model did not consider vehicle sharing and focused solely on the one passenger-one vehicle scenario. To address the limitations of previous models, Qu *et al.* [20] designed an optimal vehicle-sharing model specifically for ridesharing platforms (when multiple passengers share a vehicle). However, their model is designed for driver-passenger matching and does not explicitly consider route recommendation. In contrast, our proposed model determines the optimal fleet size for ridesharing platforms and it considers the sharing of vehicles among passengers when routes are recommended to drivers. We aim to calculate the number of vehicles required to efficiently service passengers by reducing the origin-destination request arrival graph to a vehicle count graph and thereafter applying minimum path cover (MPC) to it.

## **3 PROBLEM FORMULATION**

In this section, we will introduce definitions and formulate our problem.

**DEFINITION 1** (GRID). The road network is divided into a grid which is a collection of *n* nonoverlapping grid cells and is represented as  $g = \{g_1, g_2, ..., g_n\}$ .

Within a grid, two grid cells are said to be connected if they are adjacent to each other. Figure 1 displays the part of the road network divided into a grid. The road network is a combination of 576 grid cells and the grid cell  $g_1$  is adjacent to grid cells  $g_2, g_{25}$ , and  $g_{26}$ .

			And in case of	
<b>9</b> 2	<b>g</b> 3	•	924	
<b>9</b> 26	<b>9</b> 27	•	<b>9</b> 48	
950	<b>9</b> 61	•	<b>9</b> 72	
		•	•	
<b>9554</b>	<b>9</b> 555		9576	
	92 926 950 9554	92         93           926         927           950         951           .         .           9354         9565	92         93         .           926         927         .           960         961         .           .         .         .           984         9885         .	

Fig. 1. Road network represented in the form of a grid

**DEFINITION** 2 (ROUTE). A route corresponds to a path on the graph and it is a sequence of connected grid cells  $P = \langle g_1, g_2, ..., g_l \rangle$ , where  $l \leq n$ .

**DEFINITION** 3 (RIDE-ORDER). A ride-order o is represented as  $< o_s, o_d, o^t >$  where  $o_s, o_d$  denote the origin (source) and destination of ride-order respectively and  $o^t$  denotes the time at which the ride-order is made.

In this text, we have used ride-order, passenger request and request interchangeably.

#### 3.1 Graphical modelling

Our proposed model is represented by a family of subgraphs  $G = \bigcup_{k \in \{R,Q,T\}} G^k = \bigcup_{k \in \{R,Q,T\}} (V, E^k, w^k)$ 

where the nodes V in all the subgraphs represent the grid cells, and the edges  $E^k$  of subgraph k determine connections between various nodes. We have used the terms nodes or grid cells interchangeably. One of the subgraphs  $G^k = G^R$ , called the road subgraph is used to represent the structure of the road. The road network is assumed to be divided into a grid with *n* non-overlapping grid cells as shown in Figure 1. The vertices V of the subgraph  $G^R$  represent the grid cells, and the



Fig. 2. A particular instance of the road graph  $G^R$ . In this graph, the vertices represent the grid cells and the edge weight represents the distance between grid cells. The distance is measured between the center points of grid cells.





(a) A particular instance of the request graph  $G^Q$ .



Fig. 3. In these graphs, the vertices represent grid cells, edges represent the direction of requests, and the edge weight represents the (a) predicted and (b) actual number of requests between the grid cells. For simplicity, we have ignored the edges with 0 weight.

edges  $E^R$  determine connections between adjacent grid cells. The weight of an edge denoted by  $w^R$  represents the distance between the central points of adjacent grid cells. Figure 2 shows the part of the road network in terms of the road graph. In this graph, vertices  $\{g_1, g_2, g_3, g_{25}, g_{26}, g_{27}\}$  represent grid cells and the edges exist between grid cells if they are adjacent. For instance, vertices  $g_1$  and  $g_{27}$  are not adjacent, so there is no edge between them. The grid cells  $g_1$  and  $g_2$  are adjacent, so an edge exists between them with the weight of edge set equal to the distance between the central points of the grid cells.

The other subgraph is the request graph  $G^k = G^Q$  which represents the expected passenger requests that arrive in the ridesharing platforms and these requests are predicted through the GNN based architecture described in [18]. Each expected request has an origin (the place from which the request arrives) and destination (the place to which the request is headed). The origin and destination of these predicted requests appear on the grid cells and they are represented through

the vertices V of the request graph. The edges  $E^Q$  of request graph represent the direction of predicted requests i.e, if there is an edge between grid cells  $g_i$  and  $g_j$ , it implies that the passenger has to travel from  $g_i$  (origin) to  $g_j$  (destination). Each edge is associated with an edge weight  $w^Q$ that represents the expected number of passenger requests between the grid cells. Apart from the request graph, there is a target graph  $G^k = G^T$  that contains the actual number of requests between any two grid cells. Its vertices V represent the grid cells, edges  $E^T$  represent the flow of requests, and the edge weight  $w^T$  represents the actual number of requests between the grid cells. The target graph is not available to the ride-hailing companies beforehand, as these companies do not know the number of requests that will arrive between any two grid cells. This graph is used for monitoring the performance of the proposed model and determining the optimal fleet size as will be discussed in Section 5.6. The request graph contains the expected number of passenger requests which are predicted through the GNN-based model described in [18], and it is used for recommending the routes with the highest expected passenger requests to the drivers.

Figures 3a and 3b show the request graph and the corresponding target graph. These graphs are complete graphs as the requests can appear between any pair of vertices. For clarity, we have ignored the edges with weight 0 in both of these subgraphs. As can be seen through these figures, the edge weights of target graph are similar to that of request graph, except the edge  $(g_1, g_{26})$  which has a value of 1 in the target graph and 0 in the request graph. It displays that there was 1 request between the grid cells  $g_1$  and  $g_{26}$  but the Graph Neural Network-based architecture described in [18] misclassified it and predicted that no request will arrive between grid cells  $g_1$  and  $g_{26}$ .

**DEFINITION 4** (DETOUR RATIO AND ORDER SET). The detour ratio is the ratio of the distance travelled between the grid cells  $o_s$  and  $o_d$  ( $|P_{G^R}(o_s, o_d)|$ ), to the distance of the shortest path between these grid cells. It is mathematically represented as:

$$\alpha(P_{G^{R}}, o_{s}, o_{d}) = \frac{|P_{G^{R}}(o_{s}, o_{d})|}{|SP_{G^{R}}(o_{s}, o_{d})|}$$
(1)

where  $|P_{G^R}(o_s, o_d)|$  denotes the distance travelled when traversing through path P on subgraph  $G^R$  with end vertices  $o_s$  and  $o_d$  and  $|SP_{G^R}(o_s, o_d)|$  denotes the distance of the shortest path between the grid cells  $o_s$  and  $o_d$ .

When the routes are recommended to a driver it can't pick up all the passenger requests on the route. This is because the requests have different destinations, and reaching each destination would likely require a deviation from the original route, resulting in increased travel distance for the passengers. In order to ensure passengers are satisfied and the distance travelled by them is bounded within a specified value, we add a constraint that specifies the detour ratio of all the passenger orders taken, should not exceed a threshold value t.

$$\forall_{o_s} \alpha(P_{G^R}, o_s, o_d) \le t \tag{2}$$

This constraint ensures that only those ride-orders are taken whose paths are similar and the distance travelled by each ride order beyond its shortest path is bounded. The orders that can be paired in a single vehicle without violating the detour constraints are denoted by the order set  $\mathbb{O}$ . In order to understand the detour ratio and order set consider the following example.

**EXAMPLE 1 :** Consider the road network shown in Figure 4. The nodes represent grid cells and the edge weights represent the distance between the center points of different grid cells. A vehicle is at node  $g_1$  and is currently servicing a passenger o whose source  $(o_s)$  and destination  $(o_d)$  are  $g_1$  and  $g_4$  respectively. The current order set  $\mathbb{O}$  of the vehicle is  $\mathbb{O} = \{o\}$  where  $o = \langle g_1, g_4, o^t \rangle$ . Meanwhile, the request for 2 orders arrives while the vehicle is in transit and has not yet reached their starting point.  $o_1$  arrives at  $g_6$   $(o_{1s})$  and wants to go to  $g_4$   $(o_{1d})$ ,  $o_2$  arrives at  $g_7$   $(o_{2s})$  and wants to travel to  $g_4$   $(o_{2d})$ . These orders are represented as  $o_1 = \langle g_6, g_4, o^t \rangle$  and  $o_2 = \langle g_7, g_4, o^t \rangle$  respectively. Assume



Fig. 4. A particular instance of the road network with the driver and passenger orders. The nodes represent grid cells and the edge weight represents the distance between the center points of grid cells. The vehicle is at grid cell  $g_1$  and servicing the passenger who has to travel from  $g_1$  to  $g_4$ . Meanwhile, the requests for two orders arrive at  $g_6$  and  $g_7$ , and they have to reach  $g_4$ .

the detour ratio is 1.5. In order to determine whether the order  $o_1$  can be taken by the platform, we need to ensure the detour ratio of passenger o who has to travel from  $g_1$  to  $g_4$  is not violated by taking the order  $o_1$ . If order  $o_1$  is taken, the path followed by the vehicle will be  $P = \{q_1, q_5, g_6, g_4\}$ . We need to determine if the detour ratio of order *o* gets violated through this modified path which incorporates  $o_1$ . The detour ratio of order o is the ratio of the distance travelled in the current path P (after incorporating order  $o_1$ ) to the distance of the shortest path between the grid cells  $g_1$ and  $g_4$ . The distance travelled with the modified path P after incorporating  $o_1$  is 8 (sum of edge weights in the path *P*), and the distance of the shortest path between  $g_1$  and  $g_4$  is 6 (through the path  $\{g_1, g_2, g_3, g_4\}$ ). So the detour ratio of passenger *o* is  $\alpha = \frac{8}{6} = 1.33$  which is less than the threshold value of 1.5. Thus the order  $o_1$  is accepted by the platform, as it does not violate the detour ratio of passenger *o* which is already in the vehicle. The order set gets modified as  $\mathbb{O} = \{o, o_1\}$ . Similarly, to determine whether the order  $o_2$  can be taken by the driver we check the detour constraints of both the ride-orders o and  $o_1$  in the vehicle. The path that would be followed by the driver if  $o_2$  is taken is  $\{q_1, q_5, q_6, q_7, q_8, q_4\}$ . Let's first determine the detour ratio of  $o_1$  and see if it gets violated by taking  $o_2$ . The path followed by ride-order  $o_1$  if  $o_2$  is taken will be  $\{g_6, g_7, g_8, g_4\}$ . The distance corresponding to this path is 6 and the distance of the shortest path between  $g_6$  and  $g_4$  is 3 (through path  $\{g_6, g_4\}$ ). The detour ratio of ride-order  $o_1$  is  $\frac{6}{3} = 2$  which is greater than the threshold of 1.5. Thus the detour constraint of the order  $o_1$  which is already in the vehicle is violated if we take the new order  $o_2$ . The order  $o_2$  is thereby not accepted by the platform and the order set remains  $\mathbb{O} = \{o, o_1\}$ .

## 3.2 Computing the origin and destination of passenger requests

The requests in ridesharing platforms follow a specific pattern and depend upon requests originating from subsequent areas (spatial dependencies) or on previous request patterns (temporal dependencies). To model these spatio-temporal dependencies and predict the future origin and destination of requests, we use a Graph Neural Network (GNN)-based model described in [18] which analyzes the passenger mobility patterns and predicts the requests that can arrive in the future. Though there have been various approaches that have predicted the origin and destination of passenger requests [35, 36], however, the GNN-based model captures the non-recurring trends in data apart from the other recurring trends that have been predicted by previous studies. This results in efficient prediction and allows our proposed model to recommend the route with the highest number of passengers.

## 3.3 Problem Statement

The main objective of our proposed model is to develop an eco-friendly route recommendation system that reduces the hazardous emissions of ridesharing platforms by predicting the origin and destination of requests and utilizing them to make efficient use of vehicles. In order to utilize the vehicles all the way, the proposed approach recommends the route that has the higher number of expected passenger demand (origin of requests) on its way. However, while recommending routes with more passengers, the vehicle can deviate too much from the shortest path of passengers and cause inconvenience to them. In order to ensure that vehicle does not deviate and passengers on board are satisfied by the platform service, the detour ratio which is the ratio of the length of the path taken by the passengers in the vehicle to the length of the shortest path between their origin and destination should be bounded by a threshold. Thus the objective of our proposed approach is to select a route that has the highest number of expected passengers with a constraint that the detour ratio of all the passengers is satisfied. Moreover, there is a constraint on the number of passengers a driver can take since the capacity of the vehicle is limited. The problem can be described mathematically as:

$$P_{GQ}^* = \arg\max_{P_{GQ}} \{ \mathbb{E}[|P_{GQ}|] \}$$
(3)

subject to

$$\forall_{o_s} \alpha(P_{G^R}, o_s, o_d) \le t \tag{4}$$

$$|P_{G^T}| \le c \tag{5}$$

where

$$|P_{GQ}| = \sum_{g_i \in P} \sum_{g_j \in \mathcal{F}} w_{ij}^Q \tag{6}$$

$$|P_{G^T}| = \sum_{g_i \in P} \sum_{g_j \in \mathcal{F}} w_{ij}^T$$
(7)

Eq. (3) denotes the objective function of our proposed model which is to select a path P from the request graph  $G^Q$  that has the highest number of expected passenger requests. The expected number of requests in a path is calculated through the summation of edge weights  $w_{ij}^Q$  from all the grid cells  $g_i$  in the path P i.e.,  $(g_i \in P)$  to the set of their forward nodes  $(g_j \in \mathcal{F})$  which lie on the path to the destination, as is defined through Eq. (6). For instance, the expected number of requests in path  $\{g_1, g_2, g_{26}\}$  in Figure 3a is  $w_{(1)(2)}^Q + w_{(1)(26)}^Q + w_{(2)(26)}^Q = 3 + 0 + 1 = 4$ . While selecting the path with the maximum expected requests there is a constraint specified by Eq. (4) which states that for each ride order taken, its detour ratio should be bounded by a threshold (t) in order to ensure they are satisfied. Moreover, there is a constraint on the vehicle side denoted by Eq. (5) which states that the number of passengers taken  $|P_{G^T}|$  should not be more than the capacity cof the vehicle. The total number of passengers in a vehicle is calculated through the summation of edge weights of the target graph  $w_{ij}^T$  from all the grid cells  $g_i$  in the path P i.e.,  $(g_i \in P)$  to the set of their forward nodes ( $g_i \in \mathcal{F}$ ) which lie on the path to the destination, as is defined through Eq. (7).

## 4 BASELINES

In this section, we will discuss the existing works, identify their limitations and highlight how our proposed model overcomes them.

#### 4.1 Existing Works

There are three baselines for our proposed model. One of the baselines is the trivial baseline that recommends the route with the shortest distance between the source and destination. This approach does not involve any element of prediction and traverses a sequence of vertices where the distance between the source and destination vertices is the shortest. The other baselines are SHARE [39], and insertion-based route planning framework [29] which predict the passenger demand on the road and recommend the routes that may be slightly longer than the shortest path but have high expected demand.

#### 4.2 Limitations

The shortest path algorithm does not consider the expected number of requests. Whenever a request arrives, this approach recommends the shortest path between the source and destination locations of the request. It results in inefficient utilization of vehicles since there is a small probability of having another request on the shortest path between source and destination.

SHARE and the route planning-based frameworks, predict future requests and recommend routes that may be slightly longer than the shortest path, but they have a higher probability of finding more passengers. However, these methods only predict the origin of requests, which is also called demand prediction, and not where they are headed towards. This could result in the recommendation of routes that do not utilize the vehicle capacity efficiently. Consider the part of the road network captured through Figure 5, where the nodes represent grid cells and the node weight determines the expected number of passengers that may arrive at that node. In this road network, we have to recommend a route between grid cells  $g_1$  and  $g_4$ , and there is already a passenger in the vehicle who has to travel between these grid cells. The expected demand between the grid cells  $q_1$  and  $q_4$  is maximum along the path  $P = \{g_1, g_5, g_6, g_4\}$  and is equal to the summation of node weights in the path *P* i.e., 1 + 2 + 2 + 0 = 5. This path would be recommended by the optimal demand prediction algorithm. However as can be seen through the origin and destination of requests (represented by  $o_{si}$  and  $o_{di}$  for *i*<sup>th</sup> request), the corresponding destination of requests originating from nodes  $g_5$ are  $g_1$ , and the destination of requests from  $g_6$  are  $g_2$  and none of the requests is directed towards  $g_4$ . Thus the path P would contain only one passenger who has to travel from  $q_1$  to  $q_4$ , and will not utilize the vehicle capacity efficiently. On the other hand, the origin and destination of requests displays that the requests from  $q_2$  and  $q_3$  are directed towards  $q_4$ . Thus the optimal path between nodes  $q_1$  and  $q_4$  is  $\{q_1, q_2, q_3, q_4\}$  which contains 3 requests and they have their destination at  $q_4$ , and this path can be recommended by utilizing the origin and destination of requests and not only their origins as was done in the existing baselines.

From the above explanation, we can follow that passenger mobility patterns are better exploited by using the origin as well as the destination of requests and we provide a route recommendation system for ridesharing platforms that anticipates the passenger's origin and destination and overcomes the limitation of previous models. We will describe it next.

#### 5 OUR PROPOSED MODEL

In this section, we will describe the working of our proposed model.



Fig. 5. Performance of demand and origin-destination prediction. In this graph, nodes represent grid cells and the node weight represents the expected number of passengers on the grid cell. The origin and destination of passenger i are denoted as  $o_{is}$  and  $o_{id}$  respectively.

## 5.1 Complexity analysis

Our proposed model recommends routes to drivers that will maximize the expected number of passengers on the way and utilize the vehicle effectively. In order to recommend a route, the algorithm needs to analyze all the expected requests between the source and the destination. This problem is NP Hard as it can be reduced from the Longest Path problem.

Longest Path problem:

Given a weighted graph G = (V, E, w) with non-negative edge weights, the Longest Path problem is to find the longest simple path from the source vertex (*s*) to the destination vertex (*d*).

## Max-Request Path problem

Given a weighted complete graph G = (V, E, w) with non-negative edge weights, the Max-Request Path problem is to find a simple path with the maximum number of expected requests from the source vertex (*s*) to the destination vertex (*d*).

Route recommendation for ridesharing platforms is actually Max-Request Path problem, where the weight of each edge w is the expected number of passengers that can arrive between the source vertex s and destination vertex d. The route which has the highest number of expected passengers is the Max-Req path. The Longest Path problem is known to be NP-hard as it can be reduced from the Hamiltonian path [8].

Theorem: Finding Max-Request path is NP-Hard

*Proof:* Given an arbitrary instance of the Longest Path Problem, we reduce it to an instance of the Max-Request Path problem through the following procedure. Consider the given graph G = (V, E, w) in the Longest Path problem, we design a graph G' = (V', E', w') such that  $\forall v \in V$ , we have a vertex v' in V' and  $\forall e = (u, v) \in E$  we have an edge  $e' = (u', v') \in E'$  with edge weight w' = w. For the edges  $(u, v) \notin E$  in G, we have the edge (u', v') in G' with the edge weight w' = 0. In G' the Max-Request problem is to identify the path from a source s to a destination d with the maximum number of expected requests. Since each edge  $e' = (u, v) \in E$  with weight w' selected in the path in G' corresponds to selecting the edge  $e = (u, v) \in E$  with weight w, if the Max-Request problem is solved, the resultant path is the longest path from s to d in a graph G and hence we would have solved the Longest Path Problem.

Considering the NP-Hardness optimal algorithms are not possible. Thus we apply heuristics to solve the problem at hand.

#### 5.2 Heuristic

In order to reduce the exponential nature of the problem, we use a k-hop-based sliding window approach, where the route is recommended in the reduced space whose size is determined by the hop count k of the window. In this space, there are few requests and they can be analyzed and paired up effectively. The route that maximizes the expected number of requests and satisfies the detour constraints is recommended within the window. The window is then slid forward in the subsequent steps and the route is recommended from thereon until the destination point is reached.

5.2.1 How sliding window-based route recommendation algorithm works. In this subsection, we will describe the working of *k*-hop based sliding window. The driver wants a recommendation mechanism from the place where he is currently located, and without loss of generality, we assume there is already a passenger in his vehicle who has to travel between the specified source and destination points. The driver can follow the shortest path between the source and destination points of the passenger who is in the vehicle, but there is a small probability that the shortest path will contain any other request. This will result in inefficient utilization of the vehicle as there will be only one passenger in the vehicle whereas the vehicle can be filled up to its capacity *c*. In order to utilize the vehicle capacity, the recommendation mechanism will provide a route to the driver that might be slightly longer than the shortest path but it will have a higher probability of finding passengers. This will result in the efficient utilization of vehicles and contribute to eco-friendly rides.

In order to recommend a route with the highest number of expected passengers between the source and destination points of the passenger who is already in the vehicle while satisfying the detour constraints, we need to search the entire search space and find the best-constrained route among all the possible routes that exist in the graph. This results in exponential complexity as was proved in subsection 5.1. To reduce the complexity of route recommendation, the proposed approach uses a window to create a small area around the source node (the point at which the request of passenger who is the vehicle arrived) and recommends the optimal path within this area which reduces the complexity of recommendation from an exponential frame to a smaller area. The window is then slid forward in the direction of the destination(s) of the passenger(s) already in the vehicle, and the highest expected requests within the window that satisfies the detour constraints of passengers are checked till the window reaches the destination point of the last passenger in the vehicle.

To understand this point, consider Figure 6. The driver is at grid cell  $g_{51}$  and it has a passenger in it whose destination is  $g_{176}$ . The shortest path between these grid cells is  $\{g_{51}, g_{76}, g_{101}, g_{126}, g_{151}, g_{176}\}$ . The proposed model selects a path that might be slightly longer than the shortest path but will have a higher number of expected passengers. In order to select a path with the highest number of expected passengers, the window is created around the source node which is the point where the first request arrives and it is  $g_{51}$  here (highlighted in orange). The middle point of the window is placed at the source node  $g_{51}$ . The window is assumed to be 2- hop, which means the two neighbors from each side are taken, as displayed through Figure 6 (window is highlighted in blue). By using this window, we constrain the search space around the source node to this window of 2 hop and see the maximum expected request path within this window. Let's assume the highest expected request path in this window is  $\{g_{51}, g_{75}, g_{100}, g_{101}\}$  (how this path is obtained will be described later on). Since the maximum expected request path within the window is achieved, the window is slid forward with the destination point of this window which is  $g_{101}$  as the source point of the next

Makhdomi, Gillani

<b>9</b> 1	<b>g</b> 2	<b>9</b> 3	<b>g</b> 4	<b>9</b> 5	ge	<b>9</b> 7	<b>9</b> 8		<b>9</b> 1	<b>g</b> 2	<b>9</b> 3	<b>g</b> 4	<b>9</b> 5	<b>9</b> 6	<b>9</b> 7	<b>9</b> 8
<mark>9</mark> 25	<b>9</b> 26	<b>9</b> 27	<b>9</b> 28	g <sub>29</sub>	<b>9</b> 30	<b>9</b> 31	<b>g</b> 32		<b>9</b> 25	926	<b>9</b> 27	<b>9</b> 28	<b>g</b> 29	<b>9</b> 30	<b>9</b> 31	<b>9</b> 32
<b>9</b> 49	<b>9</b> 50	<b>9</b> 51	<b>9</b> 52	<b>9</b> 53	<b>9</b> 54	<b>9</b> 55	<b>9</b> 56		g49	<b>9</b> 50	961	<b>9</b> 52	<b>9</b> 53	<b>9</b> 54	<b>9</b> 55	<b>9</b> 56
<b>9</b> 73	<b>9</b> 74	<b>9</b> 75	<b>9</b> 76	<b>9</b> 77	<b>9</b> 78	<b>g</b> 79	<b>9</b> 80	$\Rightarrow$	<b>9</b> 73	<b>9</b> 74	<b>9</b> 75	<b>9</b> 76	<b>9</b> 77	<b>9</b> 78	<b>9</b> 79	980
<b>9</b> 97	<b>9</b> 98	<b>9</b> 99	<b>9</b> 100	<b>9</b> 101	<b>9</b> 102	<b>9</b> 103	9104		<b>9</b> 97	<b>9</b> 98	<b>9</b> 99	<b>9</b> 100	<b>9</b> 101	<b>9</b> 102	<b>9</b> 103	<b>9104</b>
g121	<b>9</b> 122	<b>9</b> 123	<b>9</b> 124	g <sub>125</sub>	<b>9</b> 126	<b>9</b> 127	<b>9</b> 128		9121	<b>9</b> 122	<b>9</b> 123	<b>9</b> 124	<b>9</b> 125	<b>9</b> 126	<b>9</b> 127	<b>9</b> 128
<mark>9145</mark>	<b>9</b> 146	<b>9</b> 147	<mark>9148</mark>	<b>9</b> 149	<b>9</b> 150	<mark>9151</mark>	<b>9</b> 152		<b>9</b> 145	<b>9</b> 146	<b>9</b> 147	<b>9</b> 148	<b>9</b> 149	<b>9</b> 150	<b>9</b> 151	<b>9</b> 152
<b>9</b> 169	<b>9</b> 170	<b>9</b> 171	<b>9</b> 172	<b>9</b> 173	<b>9</b> 174	<b>9</b> 175	<b>9</b> 176		<b>9</b> 169	<b>9</b> 170	<b>9</b> 171	<b>9</b> 172	<b>9</b> 173	<b>9</b> 174	<b>9</b> 175	<b>9</b> 176
<b>9</b> 193	<b>9</b> 194	<b>9</b> 195	<b>9</b> 196	<b>9</b> 197	<b>9</b> 198	<b>9</b> 199	9 <sub>200</sub>		<b>9</b> 193	<b>9</b> 194	<b>9</b> 195	<b>9</b> 196	<b>9</b> 197	<b>9</b> 198	<b>9</b> 199	<b>g</b> 200

Fig. 6. Road network represented in terms of a window that is slid in the direction of passengers already in the vehicle. The road network is replicated 2 times to show how the window moves at each step. Initially, the window (highlighted in blue) is created around  $g_{51}$  (highlighted in orange) which is the source node. The window is then slid and the next window is created around grid cell  $g_{101}$ .

window, as is shown by Figure 6. The window after sliding is centred around  $g_{101}$  and the highest expected request path within its 2 hop neighbours is chosen. The window continues moving until the destination point of the passenger already in the vehicle, which is  $g_{176}$  is reached. Thus, by applying the window we reduce the search space from the entire road network which has an exponential complexity to a set of neighborhood grids around a node and move this window at each step in the direction of the destination of passengers already in the vehicle.

Till now, we have described the mechanism for reducing the search space from the road network to a window. Next, we need to determine how the highest expected request path is obtained within the window. We can use a brute-force approach to determine the optimal path in a window and slide the window towards the destination in the next step. However, the brute force approach leads to an exponential search space in the size of the number of elements e in the window ( $2^e$ ), which implies that the number of elements needs to be very small. We need to apply an algorithm that finds the route within a window in an efficient manner. To determine the route in the window we analyze the structure of our objective function and see if it can be solved effectively without the use of a brute force approach that is impractical for large window size. We analyze our objective function in the next subsection.

## 5.3 Analysis of Objective function

Eq. (3) determines the objective function of our proposed model. It states that we want to recommend a path that has the highest number of expected passenger requests. As can be seen clearly from Eq. (6), this function is a linear combination of edge weights in a path and we know that linear functions are *submodular* in nature.

5.3.1 Submodular. A function is said to be submodular if the addition of an element leads to decreasing difference in the incremental value of the function. Let Z be a finite set. A function  $f: 2^Z \rightarrow R$  is said to be submodular if for all subsets  $X \subseteq Y \subseteq Z$  and  $\forall a \in Z \setminus Y$ :

$$f(X \cup \{a\}) - f(X) \ge f(Y \cup \{a\}) - f(Y)$$
(8)

In simple words, submodular functions state that the marginal benefit of adding an element to the smaller set is at least as high as the marginal benefit of adding it to a bigger set. Apart from being submodular, our objective function is also monotone.

*5.3.2 Monotone.* A function is monotone if  $f(A) \le f(B)$  implies  $A \subseteq B$ . We know that our objective function is linear which adds the requests repeatedly after each iteration. Since the request

value is non-negative, when an element is added to a set it cannot decrease the value of the set. By this argument, we can say that our function is monotone.

*5.3.3 Optimization of monotone submodular functions.* The greedy algorithm has proved to be a natural method for maximizing a monotone submodular function subject to certain constraints. In various settings, the approximation ratios provided by greedy algorithms are best-known [7]. Further, the simplicity of greedy algorithms makes them useful in route recommendation systems and their performance has been found to be at par with other algorithms [16].

As our objective function determines the route followed by the vehicle based on the expected requests that arise within that route, and it is submodular and monotone, greedy provides an obvious choice for our proposed system. Within a window, in order to recommend a path among exponential paths, we switch from the brute force approach to the greedy approach due to the submodular and monotone nature of our objective function. While directing the route, two key factors need to be taken into account: the expected passenger requests in the path and the detour constraints of the passengers in the vehicle. Now, as the subgraph instance is reduced to the size of a window, we need to find the path in this window with the above objective and constraints through the greedy strategy. Firstly, we will describe the simple greedy strategy wherein the node with the maximum expected requests is selected among the neighborhood nodes and we will show that it does not utilize the window appropriately. After that, we will propose two variants of the greedy approach.

# 5.4 Simple Greedy

The simple greedy approach finds a route with the highest expected requests that satisfies the detour constraints of passengers by looking only at the directly connected nodes. As the name suggests this approach looks for local optimum at each step and selects the adjacent node with the highest expected requests from the current node. The process continues until the driver wants the recommendation mechanism. If we consider the road network displayed by Figure 6, and assume the driver is at grid cell  $g_{51}$ , the simple greedy approach will select the highest expected requests among the 8 neighborhood nodes of  $g_{51}$  which are { $g_{26}, g_{27}, g_{28}, g_{50}, g_{52}, g_{74}, g_{75}, g_{76}$ }. Suppose the request graph  $G^Q$  displays that the highest expected requests are from  $g_{51}$  to  $g_{76}$ . The proposed approach will move the window to  $g_{76}$  and select the highest expected requests from  $g_{76}$  among its 8 adjacent nodes. This process will continue until the point driver wants the recommendation mechanism.

If we carefully analyze the procedure we can see that this approach does not violate the detour constraints of any passenger. This is because at each step the source and destination of passengers are one grid cell away, as we look for maximum expected requests from a grid cell among its neighbors and move directly towards that grid cell. However, the main drawback of this approach is that it only considers the directly connected nodes for selecting the path and does not utilize the window size properly. Even if the window covers the whole road network this approach will still look at the directly connected nodes to determine whether the route has the higher flow of requests or not.

## 5.5 Greedy Variants

With the simple greedy approach, we look at the neighborhood nodes in order to get the maximum request path. This reduces the search space to 1 hop and does not utilize the origin and destination of the majority of requests in the window. In order to utilize the origin-destination of requests appropriately, we use two variants of the greedy algorithm which consider the entire window in

their initial step, with a view to obtain the maximum request path, and subsequently, consider the neighborhood nodes in order to keep the road segments connected.

In both of these approaches, we consider the driver's starting position as the point on a graph from which the route is to be recommended. After that, we select the node or location within the window that will have the maximum number of expected requests from the starting location. This step utilizes the full window and selects the node with the maximum expected requests from the source node as the destination or endpoint of the window i.e., the route recommended in the window has the source as the drivers starting location and the destination as the point from which the source has the maximum expected requests. Since the route needs to be connected, we need to check if the destination selected in the window is directly connected to the source point of the window. If that is the case, then the path in the window is complete and the window is moved forward. If the destination is not connected to the source, then we need to find a set of connected nodes between the source and destination of the window, and the connected nodes should have high expected requests and the detour of passengers onboard should not be violated. There are two approaches to selecting the set of connected nodes between source and destination, namely Backward Greedy and Forward Greedy. These approaches select the nodes between the source and destination either through backtracking from the destination point of the window until the source is reached or by following the path from source to destination respectively. They are described in detail in the next subsections.

5.5.1 Backward Greedy (BG). After selecting the node that has the maximum expected requests from the source as the destination point of the window, we need to select the set of connected nodes between these points and this set of nodes should have higher expected requests within the detour constraints of the passengers onboard. The first approach to selecting these nodes is Backward Greedy, and as the name suggests this approach selects the set of nodes greedily in backward direction i.e., after the source and destination points of the window are fixed, this approach checks the nodes that are directly connected to the destination and greedily returns the one that has the highest expected requests to the destination. If the selected node that has the highest expected requests to the destination is connected, then the procedure is repeated and the nodes with maximum expected requests to the already connected nodes with the destination are returned. In this way, we continue till the source node is reached. Thus in this approach, we backtrack from the destination until we reach the source node with the connected set of nodes.

Consider the sliding window shown in Figure 6. In this figure, we will show how the route is recommended by using the backward greedy approach within a window when the driver is at the grid cell  $g_{51}$ . Initially, we consider all the expected requests that can arrive from the starting point of the driver and return the one with the maximum value in the window. For instance, in the above window, if the request graph  $G^Q$  displays that the maximum expected requests from  $g_{51}$  are towards  $g_{101}$ , we will consider  $g_{101}$  as the destination node of the current window. As the route needs to be connected, we check the maximum expected requests from the directly connected nodes of  $g_{101}$  in the window i.e., { $g_{76}, g_{77}, g_{100}$ } to  $g_{101}$ . In this case, if the expected requests to  $g_{101}$  are highest from  $g_{76}$ , then the path is returned and the window is slid as  $g_{76}$  is directly connected to the source node  $g_{51}$ . However, if the highest expected requests come out from  $g_{77}$  or  $g_{100}$  then we need to continue backtracking until we reach the source node, i.e., we need to find the highest expected requests to these nodes ( $g_{77}$  or  $g_{100}$ ) among their directly connected nodes, and continue this procedure till the nodes directly connected to the source are returned.

It can be seen from the above procedure that the origin and destination of all expected requests except the source and destination points of the window are just a 1 hop away. This can be followed

directly, as the first step utilizes the full window size and looks for the maximum expected requests from the source within the window, and the subsequent steps keep the path connected and look for expected requests among the directly connected nodes. From the above analysis, we can follow that the detour ratio of the requests that are directly connected will not be violated as their source

Algorithm 1: Backward greedy approach for finding the highest expected request path within the detour constraints of passengers onboard through *k*-hop sliding window approach

- 1: **Input:** Drivers starting location  $o_s$ , detour ratio  $\alpha$ , number of hops k, request graph  $G^Q$ , road graph  $G^R$
- 2: **Output:** Highest expected requests path  $p^*$  within the detour constraints of all the passengers in the vehicle

3:  $p^* = []$ 

- 4: *b* = []
- 5:  $p^* \leftarrow o_s$
- 6: while destination is not reached do
- 7: Create a k-hop-window with  $o_s$  as the middle point of the window
- 8: Calculate requests from the source node  $o_s$  to all other nodes in the window
- 9: Select the node with maximum requests  $(o_d)$  from the source  $(o_s)$  as the endpoint of the current window

```
10: b \leftarrow o_d
```

11: **if**  $o_d$  is directly connected to source **then** 

- 12:  $p^* \leftarrow reverse(b)$
- 13:  $o_s \leftarrow o_d$
- 14: Slide the window
- 15: **else**
- 16: **while**  $o_d$  is not equal to  $o_s$  **do**
- 17: Find the maximum directly connected element  $o_j$  from endpoint  $o_d$  that satisfies detour ratio

```
18:b \leftarrow o_j19:o_d \leftarrow o_j20:end while21:end if
```

```
22: end while
```

and destination are just 1 hop away and our proposed model will always move to subsequent grid cells directly without any detour. However, the detour ratio of the passenger on board who has to travel from the source point of the window and reach the destination point in the same window can be violated if we explore nodes from destination to source without taking into consideration the extra distance travelled at each step.

In order to ensure that the detour ratio of the passenger who has to travel between the source  $g_i$  and destination  $g_j$  points of the window is satisfied the ratio of extra distance travelled by him when the set of connected nodes is selected between these points, to the distance of the shortest path between these points should be bounded by a threshold value. If the driver is assumed to be at grid cell  $g_k$ , and the distance of  $g_k$  from the destination point  $g_j$  is  $d_{jk}$ , and the maximum expected passenger requests among the adjacent grid cells of  $g_k$  arrive at  $g_l$  (see Figure 7), then the driver can move to grid cell  $g_l$  from  $g_k$  if the extra distance travelled by moving through the modified path (which incorporates  $g_l$ ) does not violate the detour ratio of a passenger who has to travel from



Fig. 7. Road network in the form of a window. The driver is assumed to be at  $g_k$  and its adjacent grid cell  $g_l$  is checked for inclusion in the path between  $g_i$  and  $g_j$ .

 $g_i$  to  $g_j$  i.e.,

$$\alpha(P_{G^R}, g_i, g_j) \le t \tag{9}$$

We know the detour ratio of the passenger is the length of the path travelled by the vehicle between its source and destination points to the length of the shortest path between those points. The length of the shortest path between the grid cells  $g_i$  and  $g_j$  is denoted by  $|SP(g_i, g_j)|$ . The length of the path taken by the vehicle between grid cells  $g_i$  and  $g_j$  changes when the driver is assumed to be at grid cell  $g_k$  and its adjacent grid cell  $g_l$  is checked if it could be taken in the path, and it becomes  $d_{jk} + w_{k,l}^R + |SP(g_l, g_i)|$ , where  $d_{jk}$  is the distance travelled by vehicle between the destination point  $g_j$  and the point at which driver is currently located  $g_k$ ,  $w_{k,l}^R$  is the distance between the current position of the driver which is  $g_k$  and its adjacent grid cell  $g_l$ , and  $|SP(g_l, g_i)|$  is the length of the shortest path between the grid cells  $g_l$  and  $g_i$ . The detour constraint specifies that the length of the modified path to the original path should be bounded by threshold t i.e.,

$$\frac{d_{jk} + w_{k,l}^{R} + |SP(g_l, g_i)|}{|SP(g_l, g_j)|} \le t$$
(10)

This constraint states that the driver can move to grid cell  $g_l$  if the distance between the current position of driver  $g_k$  and the grid cell  $g_l$  which is denoted by  $w_{k,l}^R$ , is less than  $t \cdot |SP(g_i, g_j)| - d_{jk} - |SP(g_l, g_i)|$ . After the route in the window is complete, the window is slid and the same process is repeated with the destination point of the previous window as the source of the next window. This process continues until the last passenger in the vehicle reaches his destination.

Algorithm 1 presents the pseudocode of the Backward Greedy algorithm. After creating the k-hop window around the source node  $o_s$ , the node with maximum expected requests from the source node is returned ( $o_d$ ) as the destination point of the window and added to the backtrack array b (lines 5-8). If  $o_d$  is directly connected to the source then the source is updated and the path is returned by backtracking from the destination point to the source through the array b, and the window is slid (lines 9-12), else we will loop till the nodes connected to the destination point are directly connected to the source node  $o_s$  and keep appending them to the backtrack array b (lines 13-17). This procedure is repeated till the last passenger in the vehicle reaches his destination.

*5.5.2 Forward Greedy (FG).* Forward Greedy has an approach similar to the Backward Greedy variant with a slight change in procedure. This change occurs in the selection of nodes between the source and destination. While the Backward Greedy selects the directly connected nodes from the destination node and backtracks to the source node, the Forward Greedy does the reverse and follows the path from the source to the destination. In this approach after selecting the source and destination, instead of looking at the requests from the nodes connected to the destination,

ACM Trans. Inf. Syst., Vol. 1, No. 1, Article . Publication date: January 2024.

we look at the requests from the source node and continue the procedure till the destination node of the window is reached. Initially, we check the adjacent nodes of the source and return the one which has the highest number of expected requests directed from the source node. After that, we check if the node connected to the source that has the maximum requests from the source is connected directly with the destination node of the window. If that is the case, we move the window forward. However, if that is not the case we repeat the procedure until we get a node that is directly connected to the destination. After the route in the window is complete, we move the window with the destination of the current window as the source of the next window. In this way, we continue until the final destination point is reached.

Like Backward Greedy, this approach does not violate the detour ratio of directly connected requests but can violate the constraints of requests that have to travel from the source point to the destination point. In order to ensure the distance travelled by the passenger is bounded when the highest expected request path is selected between its source and destination points, it should satisfy the following detour constraint:

$$\frac{d_{ik} + w_{k,l}^R + |SP(g_l, g_j)|}{|SP(g_i, g_j)|} \le t$$
(11)

where  $d_{ik}$  represents the distance between the source grid cell  $g_i$  and the grid cell  $g_k$  at which the driver is located,  $w_{k,l}^R$  represents the distance between grid cell  $g_k$  and the grid cell  $g_l$  that needs to be checked for detour constraint, and  $|SP(g_l, g_j)|$  represents the distance of the shortest path between grid cells  $g_l$  and  $g_j$ . According to this constraint, the driver is permitted to move to grid cell  $g_l$  only if the distance between its current position which is grid cell  $g_k$  and the target grid cell  $g_l$  (represented by  $w_{k,l}^R$ ) is less than  $t \cdot |SP(g_i, g_j)| - d_{ik} - |SP(g_l, g_j)|$ .

In both the forward and backward greedy approaches, the proposed approach recommends a route between the source and destination points of the window that has the highest expected requests and satisfies the detour constraints of the passenger on board who has to travel from the source to destination points of the window. However, apart from the passenger who has to travel from source to destination points of window, there is another passenger who is already in the vehicle whose source and destination points can lie outside the window. The proposed model needs to ensure that while selecting the highest request path, the detour constraints of the passenger who is already in the vehicle lies below the threshold value. It ensures that through the use of equations (10) and (11), where  $g_i$  and  $g_j$  now correspond to the source and destination points of the passenger who is already in the vehicle.

5.5.3 Complexity analysis. The complexity of our proposed model depends upon the following two factors: 1) the time required to execute the operations performed within the window, and 2) the number of times the window slides between the source and destination points of the passenger. Within the window, the proposed model selects the source node and finds the node that has the highest expected requests from the source node as the destination node of the window. This operation determines finding the maximum element within the window and its complexity will depend upon the number of elements in the window. Let *e* denote the number of elements in the window, then the complexity of finding the maximum element in the window is O(e). After selecting the maximum request point as the destination nodes. In the worst case, the proposed model can visit each and every element within the window which leads to the complexity of O(e). So the complexity of executing the operations within the window is  $O(e^2)$ . We know *e* denotes the number of elements within a window and its count depends upon the number of hops *k* i.e.,  $e = 8(1 + \sum_{i=2}^{k}(i-1) + 1)$ . Thus, the number of elements *e* is of the order of  $k^2$  and the time

complexity within a window is  $O(k^4)$ . The second factor which determines the complexity is the number of times the window is slid. In the worst case, the window is slid over each and every grid cell. If we assume there are *n* grid cells, the complexity of the sliding window between source and destination points will be O(n). The overall complexity of the proposed approach depends upon the number of times the window is slid and the time required to execute instructions per window and it is  $O(nk^4)$ . The hop count *k* is determined through experimental evaluation and it is usually a small constant as the performance of the system improves quadratically initially with the increase in the hop count *k* and stabilizes after some time (see Section 6). Its value is usually smaller than 6. So we can say the proposed model runs in linear time.

#### 5.6 Fleet size

In this subsection, we will describe the process of obtaining the fleet size. The fleet size is a crucial factor that determines the number of vehicles required to effectively service all passenger requests that arrive within a given time frame. There are two cases that arise in the determination of fleet size: 1) the fleet size required by our proposed model, which predicts the origin and destination of requests through GNN based architecture described in [18] and thereafter utilizes the greedy-based sliding window approach to recommend the routes, and 2) the optimal fleet size, which occurs when the arrival of passenger requests is known beforehand.

To determine the fleet size of our proposed model, we employ a random sampling technique where we allocate an imaginary set of vehicles to various grid cells. These vehicles are then assigned routes using the greedy-based sliding window approach described in the previous subsection. After allocating routes to all the imaginary vehicles, we count the number of vehicles that were actually assigned to the passengers. This count represents the fleet size required by our proposed model to service all passengers within a given area and time frame effectively.

The second case involves determining the optimal fleet size, which represents the *minimum* number of vehicles required by the ridesharing platforms to accommodate all passenger requests when the passenger arrival sequence is known *in advance*. Although this scenario rarely occurs in practice, as companies typically do not possess precise knowledge of passenger arrival sequences beforehand, it serves as a benchmark for evaluating the optimal number of vehicles needed by ridesharing platforms. To derive the optimal fleet size in the offline case, we utilize the *target graph*  $G^T$  that accurately captures the arrival sequence of passenger requests for the ridesharing platforms. The target graph incorporates all the requests that can arrive within a particular time frame. This graph contains some requests which can be merged into the same vehicle without violating their detour constraints. It also contains certain requests which can be serviced by the same vehicle consecutively i.e., after dropping off some passengers, the vehicle arrives at the starting point of the next passenger before his waiting time is over. We need to handle these two cases and consider the number of vehicles required by the ridesharing platforms when some requests can be serviced by the same vehicle. While considering these two cases, we need to take into account the vehicle capacity, as there is a maximum limit on the number of requests a vehicle can accommodate.

In order to derive the fleet size with the above two cases and capacity constraints, we transform the target graph which contains the request arrival sequence known in advance, into the vehicle count graph. The target graph  $G^T = (V, E^T, w^T)$ , being a complete graph, encompasses all possible requests between any pair of grid cells. This graph is transformed into the vehicle count graph  $G^C = (V^C, E^C, w^C)$ , which specifically denotes the requests that can be serviced by the same vehicle. The transformation process is described next.

The vertices  $V^C$  of the vehicle count graph represent the edges  $E^T$  of the target graph in terms of the vehicle capacity i.e, if the edge weight  $w_{ii}^T$  between any two grid cells  $g_i$  and  $g_j$  in the target



Fig. 8. Vehicle count graph

graph is less than or equal to the vehicle capacity c, these edges appear directly as vertices in the vehicle count graph with the vertex weight in vehicle count graph set equal to the edge weight in the target graph. However, if the edge weight  $w_{ij}^T$  between the grid cells  $g_i$  and  $g_j$  of target graph is more than the vehicle capacity than the number of vertices in the vehicle count graph will be  $\left[\frac{w_{ij}^T}{c}\right]$ , and the vertex weight of  $\left[\frac{w_{ij}^T}{c}\right]$  vertices will be equal to the vehicle capacity, and one vertex will have a weight of  $w_{ij}^T - \left[\frac{w_{ij}^T}{c}\right] \cdot c$ . In order to understand this point consider Figures 3b and 8 which show the target graph and its vehicle count graph. Let's assume the vehicle capacity is 2 i.e., the vehicle can at maximum carry 2 passengers in a single run. The edge  $(g_1, g_{26})$  of target graph has a weight of 1 which is less than the vehicle capacity of 2, so it directly appears as the vertex  $g_{1}g_{26}$  in vehicle count graph with vertex weight being equal to the corresponding edge weight in the target graph i.e., 1. The edge  $(g_1, g_2)$  of the target graph has a weight of 3 which is more than the vehicle capacity of 2, so there are  $\left\lceil \frac{3}{2} \right\rceil$  vertices in vehicle capacity of 2, and one vertex weight of  $\left\lfloor \frac{3}{2} \right\rfloor$  i.e., 1 vertex will be equal to the vehicle capacity of 2, and one vertex weight of  $\left\lfloor \frac{3}{2} \right\rfloor$  i.e., 1 vertex will be equal to the vehicle capacity of 2, and one vertex weight of  $\left\lfloor \frac{3}{2} \right\rfloor$  i.e., 1 vertex will be equal to the vehicle capacity of 2, and one vertex weight of  $\left\lfloor \frac{3}{2} \right\rfloor$ .

Now, that we have defined the vertices of the vehicle count graph, we will describe the formation of the edges of this graph. The edges of the vehicle count graph connect the vertices that can be serviced through a single vehicle. A single vehicle can service multiple requests either if it is running with more than one passenger in it, or if it reaches the starting point of next passenger after dropping previous. For the first case which confers to the efficient pairing of passengers in a single vehicle when it is operating, we check the vertices of the vehicle count graph with vertex weight less than the vehicle capacity *c*, and connect them through an edge if they can be merged in a single vehicle without violating the detour constraints of any of them. For the second case, in which the vehicle can service the passengers consecutively, we connect the vertices through the edge only if the vehicle arrives at the next passenger's place (grid cell) before its waiting time is over. Figure 8 displays the vehicle count graph corresponding to the target graph shown in Figure 3b. The purple edges represent the vertices that can be serviced through the same vehicle in the sharing mode, and the black-coloured edges connect the vertices which can be serviced by the same vehicle one after the other.

After formulating the vehicle count graph, we need to determine the minimum number of vehicles required to service all the passenger requests in this graph. The vertices that are isolated i.e., those vertices which are not connected with any other vertex through an edge require a single vehicle. Each isolated vertex represents a passenger request that couldn't be paired with any other passenger due to detour constraints or the unavailability of a suitable vehicle that could reach within the waiting time constraints of the passenger. On the other hand, vertices that are connected through an edge will result in a decrease in vehicle count and the connected vertices will require a single vehicle to service them. Determining the minimum fleet size on this graph is reduced to finding the minimum number of the edge sequences such that each vertex precisely belongs to only one sequence, which is equivalent to finding the minimum path cover on the vehicle count graph. For example, referring to Figure 8, the vehicle count graph exhibits 3 edge sequences that cover the graph, ensuring that each vertex is part of exactly one sequence. Therefore, the minimum number of vehicles required is 3.

# 6 EXPERIMENTS AND RESULTS

In this section, we determine through experimental evaluation that our proposed model is ecofriendly, scalable, and can be used by ridesharing platforms for effective route recommendation.

## 6.1 Experimental setup

All the experiments are implemented in Python and performed on a machine with Intel(R) Core(TM) i9-12900 CPU 2.40 GHz with 32 GB RAM.

Datasets	New York	Washington DC			
Time Span	1 month	1 month			
Grid cell size	$2 * 2 km^2$	$2 * 2 km^2$			
Size	20024124	1389234			
Number of grid cells	576	99			
Time slot granularity	15 minutes	15 minutes			

Table 1. A Summary of Datasets used

6.1.1 Datasets. To evaluate the performance of our proposed model, we conducted experiments using two real-world datasets obtained from New York and Washington DC. These datasets contain different passenger distribution patterns and determine the functioning of the system in varied environments. They were collected for February 2016 and 2017 respectively. Table 1 provides a brief overview of the datasets utilized in our experimental analysis. The datasets were divided into grid cells with a size of 2 km and a time interval of 15 minutes. The rows of the dataset are of the form pick-up time, pick-up latitude and longitude, drop-off latitude and longitude, and passenger count. This data about passengers' origin and destination is provided as input to the GNN-based model described in [18], which predicts the number of requests that can arrive between any two grid cells within the next 15 minutes. The predicted data is fed as input to the request graph  $G^Q$  which is used for recommending routes to the drivers. As can be seen from Table 1 the size of the dataset is massive and thereupon we have utilized the greedy-based sliding window approach to decrease the search space considerably and speed up the recommendation process.

*6.1.2 Rationale for Grid-based Approach.* The grid-based approach provides a simplified representation of the road network, facilitating the modelling of complex transportation systems. It divides the road into geographical zones, allowing the proposed model to recommend zones with a higher flow of passenger requests efficiently. This approach has gained popularity in various studies on route recommendation and matching algorithms, as evidenced by works such as [25, 28, 29, 34].

When implementing a grid-based approach, the size of the grid cell becomes an important parameter. If the size is small, there will be an increase in the computational complexity of the model. On the other hand, if the size is large, a single grid cell covers a substantial number of road segments, which oversimplifies the road network and ignores the important details. Informed by insights from previous studies [28, 34], we have set the size of the grid cell as 2 km. This size strikes a balance, aiming to capture relevant details of the road network while maintaining computational feasibility.

It is important to note that while the grid-based approach simplifies the representation of road networks, this system can be easily applied in practical settings. In these cases, the vertices are redefined to represent actual road intersections, and the edges connecting these vertices denote the road segments, enabling a transition from a grid-centric model to one that more accurately mirrors the intricacies of real-world road networks. This adaptability enhances the generalizability of the proposed model, allowing it to be integrated into diverse real-world scenarios with different levels of road network complexity.

*6.1.3 Evaluation Framework.* To evaluate the performance of our proposed model, we divide the dataset into training data and test data. The training dataset contains 75% and the rest is used for testing. The model is learned on training data and its performance is evaluated on the test dataset. The data generated by the test set is used as input by the route recommendation algorithm to provide optimal routes to the driver. Thereafter, the performance of the route recommendation system is measured by using the actual data of passengers' origin and destination of the corresponding place. The working of the proposed route recommendation system depends upon the output of the deep learning model applied for predicting the origin and destination of passengers requests. Although we have used the GNN-based model proposed in [18] for predicting the passengers' origin and destination, any deep learning model can be applied to do the prediction task.

*6.1.4 Baselines.* We compare the performance of our proposed model with the following baselines: **Shortest path (SP):** The shortest path algorithm recommends the shortest path between the source and destination points.

**SHARE [39]:** We evaluate SHARE which predicts the demand at various nodes and recommends the routes with the highest expected demand without violating the detour constraints of passengers in the vehicle.

**Unified route planning (URP) [29]:** It is a route planning approach that uses historical data to analyze areas with high demand. Whenever requests appear dynamically it modifies the original route of the driver to incorporate the new request through its insertion operation.

6.1.5 *Metrics.* The performance of our proposed model is measured by the following metrics:

**Percentage of orders with ridesharing :** This metric quantifies the proportion of ride orders that were executed in sharing mode, reflecting the effectiveness of our proposed model in pairing multiple passengers based on their origin and destination information. A higher value of this metric indicates better performance of the route recommendation system in terms of maximizing shared rides.

**Passengers per grid :** This metric measures the occupancy level of the vehicle per grid. Its value should be higher for better performance of the system.

**Vehicle Utilization:** This metric measures the effective utilization of the vehicle. It is defined as,  $VU = \frac{u}{c}$ , where *c* is the vehicle's capacity, and *u* is the number of passengers in the vehicle i.e., this metric determines the utilized capacity of the vehicle. The value of *VU* can range between 0 and 1, where the value 0 indicates no passenger in the vehicle and the value 1 indicates that the vehicle was filled completely.



Fig. 9. Evaluation of different metrics on New York (NY) and Washington (DC) dataset by Forward Greedy (FG) and Backward Greedy (BG) approaches based upon the number of hops (k)

**Waiting time:** Customers are the primary stakeholders of any platform, and the performance of the system depends upon its ability to meet their needs effectively. In ride-hailing platforms, when the passengers book a ride, they should get it quickly from the platform and their waiting time should be low. To ensure passenger satisfaction, we evaluate this metric and see how its value gets affected by incorporating greener rides.

*6.1.6 Parameter.* Our proposed model has one parameter k which determines the size of window and needs to be estimated for complexity and accuracy. Its value is determined through experimental evaluation under different conditions. The default value of k is 5.

# 6.2 Results and Discussion

In this subsection, we will analyze the performance of our proposed model on the range of metrics, and the parameter specified above.

6.2.1 Impact of k. The hop count k determines the size of window used for recommending routes to drivers. Figure 9 shows the performance of our proposed model on vehicle utilization, percentage of orders with ridesharing, passengers per grid, and waiting time with the increase in k. As can be seen through the figures, New York City has higher values of vehicle utilization, passengers per grid, and percentage of orders with ridesharing, than Washington DC. This is because of the difference in demand between the two cities. The higher demand in New York City leads to better utilization of vehicle capacity and is reflected in the metrics displayed in the figure. However, the higher demand leads to more waiting time for passengers in New York City than in Washington DC. When the demand is high, even with effective vehicle utilization all the passengers are not able to access the ride quickly which displays in their higher waiting times.

These figures also display the improvement in the performance of the proposed model with the increase in the number of hops. When the number of hops increases, the search space increases



(a) New York dataset

(b) Washington DC dataset





Fig. 11. Percentage of orders with ridesharing with increase in detour ratio ( $\alpha$ )

which implies that the origin-destination pairs of multiple passengers can be matched effectively which leads to the improvement in the performance of the model. Moreover, it can be seen from the figure performance continues to improve with the increase in the number of hops in Washington DC, whereas the performance remains constant after the number of hops increases beyond 3 in New York. This is because of the request arrival patterns in these cities. New York City has a higher request count which leads to good performance even with the low hop size, and this performance remains nearly about the same with the increase in hop count after 3. Whereas Washington DC has fewer requests, and the performance continues to improve with the hop count, as the higher hop count will result in the pairing of more requests.

6.2.2 Impact of detour ratio on the performance of the system and existing baselines. The detour ratio determines the distance that can be travelled beyond the shortest path of passengers in the vehicle. Figures 10, 11, 12, and 13 show the performance of Forward Greedy (FG) and Backward Greedy (BG) approaches based upon the detour ratio on the New York and Washington DC datasets. The performance improvement of Forward Greedy with an increase in the detour ratio is found to be similar to Backward Greedy on the New York dataset. However, on the Washington dataset, the Backward Greedy is found to perform better. Intuitively, both the Forward Greedy and Backward Greedy should perform similarly. The superior performance of Backward Greedy on the Washington DC dataset can be attributed to the distribution pattern of requests which helps Backward Greedy. These figures also display that the performance of the proposed system continues to improve with the increase in detour ratio. This follows through intuitive reasoning, as the increase in detour ratio displays that the passengers are willing to travel higher distances beyond their shortest paths which results in searching for routes with higher expected passenger count more effectively and



Fig. 12. Passenger per grid with increase in detour ratio ( $\alpha$ )



Fig. 13. Waiting time with increase in detour ratio ( $\alpha$ )

increases the vehicle utilization, passengers per grid, and percentage of orders with ridesharing. It also decreases the waiting time of passengers as effective vehicle utilization results in the reaching of drivers at the passenger areas quickly.

Apart from comparing the performance of Forward Greedy and Backward Greedy approaches, Figures 10, 11, 12, and 13 also display the performance of the proposed model and the existing baselines: Unified Route Planning (URP) [29], SHARE [39], and Shortest Path (SP). The proposed model is found to perform better on all the evaluation metrics and surpasses the existing baselines. This is because we have used the passenger data effectively and experimented with the origin and destination of requests. The proposed model's objective function after incorporating the origin and destination of requests comes out to be submodular on which greedy algorithms are known to provide wellknown approximation guarantees, which results in improved performance by the proposed model.

6.2.3 Time-frames. Figures 14 and 15 display the performance of the proposed model and the existing baselines over different time periods of the day. The performance is evaluated over the night hour (0 - 1) when the demand is low, morning rush hour (7 - 8) when people are moving from their homes to offices, day hour (12 - 13) when the demand is scattered around different places, and the evening rush hour (16 - 17) when people are coming to their homes from respective offices. During the morning and evening rush hours, the proposed model and existing baselines perform well for all the parameters. However, the proposed models' performance is superior due to the prediction of origin and destination of requests which results in the effective functioning of the system. The performance improvement of the proposed model is particularly high during the morning rush hours than that of the evening rush hour. The analysis behind this functioning can be



Fig. 14. Improvement of the proposed model over the existing baselines over different time periods of the day on the New York dataset



Fig. 15. Improvement of the proposed model over the existing baselines over different time periods of the day on the Washington DC dataset



Fig. 16. Window movements at (a) different distances and (b) over different times

that during the morning hours, people prefer speed and efficiency and try to reach their offices as quickly as possible, which results in effective vehicle utilization, whereas during the evening hours, people prefer convenience and can follow the preferred routes which results in less utilization than the morning rush hour. The values of different metrics are relatively low during the night hour due to the low demand over those time periods. They are also slightly lower in the day hours which can be attributed to the demand scattered over different places during these hours. Overall, the proposed model exhibits superior performance during different time frames of the day with varying demands which shows its adaptability in different environments.

Window movement. The proposed model constrains the search space within which the 6.2.4 route is recommended by creating a window around the source node and slides this window until the destination node is reached. The number of times window is slid is an important factor that determines the complexity of the proposed approach. Theoretically, the movements are of the order of *n*, where *n* denotes the number of grid cells. In this section, we display through experiments the movement of windows over different time frames and with different distances. Figure 16a displays the movement of the window over different distances (distance between source and destination of passengers) in New York and Washington DC datasets. The default value of k is kept as 5. When the distance between source and destination points is less than 8 km, i.e., the passenger has to travel within 8 km, these points lie within the same window, and in this case window is not slid forward or backward. When the distance between source and destination points increases the window movement increases. With the same distance, the window movement is more in Washington DC than in New York. This is because of the difference in demand arrival patterns in these two cities. In New York City, the requests are higher and the routes with the highest expected requests are found within the window frequently which results in fewer movements of the window whereas in Washington DC the requests are scattered around different places which shows up in the higher movement of the window. Apart from distance, the window movement also depends upon the time of the day. Figure 16b shows the movement of the window over different times of the day. During the night the demand is less, which results in the less movement of the window. The demand increases during the morning hours which results in a higher movement of window in order to cover the demand at different places. Its movement further increases during the day hours. The reason behind this is attributed to the demand scattered around different places which results in the frequent movement of the window in order to cover the demand over different places. Although the demand is near about the same in the morning and evening rush hours, the window movement is much higher in the evening rush hours than that of morning hours. The analysis behind this functioning of model is the difference in travelling behavior of people. During morning rush hours people prioritize speed over convenience and try to reach their destination quickly. Whereas



Fig. 17. Approximation ratio at different times of the day

during evening hours, people usually prefer to follow the desired routes which results in the higher movement of the window. Moreover, the figure displays that window movement is higher in New York than in Washington DC. This is mainly because the area covered by the New York dataset is higher than the Washington DC. There are 576 grid cells in New York, whereas Washington DC contains only 99 grid cells. The higher area leads to higher movement of window in New York than in Washington DC. With similar distances, the window movement was higher in Washington DC due to demand spread over the grid cells as was displayed through Figure 16a. However, due to the higher area, the movement of window is more frequent in New York than in Washington DC.

6.2.5 Approximation ratio. The proposed model approximates the highest expected request path by using the sliding window based greedy algorithm which is submodular. To determine the approximation quality, we plot the approximation ratio over different times of the day. The approximation ratio is quantified as  $\frac{vu_{prop}}{vu^*}$ , where  $vu_{prop}$  denotes the vehicle utilization of the proposed model, and  $vu^*$  denotes the optimal vehicle utilization. Since computing  $vu^*$  is NP-Hard, we perform the computation on a smaller area of 6 \* 6 km on both datasets. Figure 17 shows the approximation ratio over different times of the day. It can be seen that the proposed model works effectively during different times of the day and its approximation value lies within 1.3 times the optimal value. The approximation value is high during the day hours (12 - 13) which can be attributed to the demand scattered over different grid cells. Over the other times, the proposed model performs well which is displayed through the approximation ratio being close to 1 over those times.

6.2.6 Fleet Size estimation. The fleet size determines the number of vehicles required by ridesharing companies to service passenger requests over different time periods of the day. Figures 18a and 18b show the fleet size of the proposed model considering the backward greedy approach, existing baselines, and the optimal fleet size over different hours of the day in New York City and Washington DC. These figures illustrate the dynamic nature of fleet size throughout the day. Notably, during late-night hours (from 2 to 7), the fleet size remains relatively low, while it experiences an increase during the morning rush hours (from 7 to 11) and the evening rush hours (from 16 to 20). This variation in fleet size is directly influenced by the fluctuating demand throughout the day. During late-night hours, the demand decreases as most people have already reached their respective homes. Conversely, the demand surges during the morning and evening rush hours as people commute from their homes to offices in the morning and vice versa in the evening. This can be verified through Figures 19a and 19b, which plot the number of vehicles required over different times of the day with the demand over different time frames. For instance, the data point (0 - 1, 5000, 3000)signifies that between 12 am and 1 am, there were 5000 passenger requests, and our proposed model utilized 3000 vehicles to service those requests. This graph displays that the demand is different over different time periods of the day and the vehicle count changes accordingly.

Through these figures, it can be seen that the proposed model uses fewer vehicles in comparison to the existing baselines. This is primarily due to the reason that the proposed model effectively



Fig. 18. Fleet size at different times of the day



(a) New York dataset

(b) Washington DC dataset

Fig. 19. Evaluation of fleet size over different times of the day with different demands

utilizes the available vehicle capacity which results in a decrease in the count of vehicles on the road.



Fig. 20. Scalability of the proposed model

*6.2.7 Discussion.* After examining the performance of the proposed model over different detours, time frames, and examining the other aspects of the system like the window movements we can conclude that our proposed model is:

**Eco-friendly and Cost-efficient:** As the proposed model is found to perform better on all the evaluation metrics in comparison to the existing baselines, it displays that the drivers are provided with a route that has higher passenger density which makes them cruise for passengers less and

ACM Trans. Inf. Syst., Vol. 1, No. 1, Article . Publication date: January 2024.

utilize the vehicle in an efficient manner. This results in eco-friendly rides and it also increases the profit of drivers as they are provided with the passengers earlier on the road.

**Reduces fleet size:** Since the proposed model recommends the routes that have higher count of passengers, it results in the efficient utilization of vehicle and decreases the number of vehicles on the road.

**Scalable:** As can be seen through Figure 20, our proposed model responds to any query in nearly about 1.1 seconds which makes it useful for real-time recommendation.

## 7 CONCLUSION

In this paper, we establish that it is possible to use the origin-destination request patterns for route recommendation systems. The proposed approach does this by applying a greedy-based algorithm to maximize the underlying objective function. Further, it overcomes the scalability challenges posed by the NP-Hard nature of these problems, by reducing the search space to a k-hop-based sliding window. Through this novel approach, the proposed model achieves better performance than the state-of-the-art techniques and reduces the fleet size on the real network taxi datasets generated from New York City and Washington DC. Moreover, it overcomes the computational complexity and runs the simulations in 1.1 seconds which implies the model can be run in real time.

#### REFERENCES

- 2018. Analyzing the dynamic ride-sharing potential for shared autonomous vehicle fleets using cellphone data from Orlando, Florida. Computers, Environment and Urban Systems 71 (2018), 177–185.
- [2] 2019. Shared autonomous vehicle simulation and service design. Transportation Research Part C: Emerging Technologies 107 (2019), 15–33.
- [3] Javier Alonso-Mora, Samitha Samaranayake, Alex Wallar, Emilio Frazzoli, and Daniela Rus. 2017. On-demand highcapacity ride-sharing via dynamic trip-vehicle assignment. *Proceedings of the National Academy of Sciences* 114, 3 (2017), 462–467.
- [4] Hua Cai, Xi Wang, Peter Adriaens, and Ming Xu. 2019. Environmental benefits of taxi ride sharing in Beijing. Energy 174 (2019), 503–508.
- [5] Michal Cáp and Javier Alonso Mora. 2018. Multi-objective analysis of ridesharing in automated mobility-on-demand. Proceedings of RSS 2018: Robotics-Science and Systems XIV (2018).
- [6] Peng Cheng, Hao Xin, and Lei Chen. 2017. Utility-Aware Ridesharing on Road Networks. In Proceedings of the 2017 ACM International Conference on Management of Data (Chicago, Illinois, USA) (SIGMOD '17). Association for Computing Machinery, New York, NY, USA, 1197–1210.
- [7] Michele Conforti and Gérard Cornuéjols. 1984. Submodular set functions, matroids and the greedy algorithm: Tight worst-case bounds and some generalizations of the Rado-Edmonds theorem. *Discrete Applied Mathematics* 7, 3 (1984), 251–274.
- [8] Thomas H Cormen, Charles E Leiserson, Ronald L Rivest, and Clifford Stein. 2022. Introduction to algorithms. MIT press.
- [9] Ye Ding, Siyuan Liu, Jiansu Pu, and Lionel M. Ni. 2013. HUNTS: A Trajectory Recommendation System for Effective and Efficient Hunting of Taxi Passengers. In 2013 IEEE 14th International Conference on Mobile Data Management, Vol. 1. 107–116.
- [10] Daniel J Fagnant and Kara M Kockelman. 2018. Dynamic ride-sharing and fleet sizing for a system of shared autonomous vehicles in Austin, Texas. *Transportation* 45 (2018), 143–158.
- [11] Nandani Garg and Sayan Ranu. 2018. Route Recommendations for Idle Taxi Drivers: Find Me the Shortest Route to a Customer!. In Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (KDD '18). Association for Computing Machinery, New York, NY, USA, 1425–1434.
- [12] Pengzhan Guo, Keli Xiao, Zeyang Ye, and Wei Zhu. 2021. Route Optimization via Environment-Aware Deep Network and Reinforcement Learning. ACM Trans. Intell. Syst. Technol. 12, 6, Article 74 (dec 2021), 21 pages.
- [13] Shenggong Ji, Zhaoyuan Wang, Tianrui Li, and Yu Zheng. 2020. Spatio-temporal feature fusion for dynamic taxi route recommendation via deep reinforcement learning. *Knowledge-Based Systems* 205 (2020), 106302.
- [14] Xiaoting Jiang, Yanyan Shen, and Yanmin Zhu. 2018. Cruising or Waiting: A Shared Recommender System for Taxi Drivers. In Advances in Knowledge Discovery and Data Mining, Dinh Phung, Vincent S. Tseng, Geoffrey I. Webb, Bao

Ho, Mohadeseh Ganji, and Lida Rashidi (Eds.). Springer International Publishing, Cham, 418-430.

- [15] Yuanyuan Li, Yang Liu, and Jun Xie. 2020. A path-based equilibrium model for ridesharing matching. Transportation Research Part B: Methodological 138 (2020), 373–405.
- [16] Hongwei Liang and Ke Wang. 2018. Top-k Route Search through Submodularity Modeling of Recurrent POI Features. In *The 41st International ACM SIGIR Conference on Research & Conference on Re*
- [17] Linfeng Liu, Yaoze Zhou, and Jia Xu. 2023. A Cloud-edge-end Collaboration Framework for Cruising Route Recommendation of Vacant Taxis. *IEEE Transactions on Mobile Computing* (2023), 1–16.
- [18] Aqsa Ashraf Makhdomi and Iqra Altaf Gillani. 2023. GNN-based passenger request prediction. Transportation Letters 0, 0 (2023), 1–15. https://doi.org/10.1080/19427867.2023.2283949
- [19] Yoann Le Petit. 2020. Uber pollutes more than the cars it replaces-US scientists. https://www.transportenvironment. org/discover/uber-pollutes-more-cars-it-replaces-us-scientists/. Accessed: 2022-02-28.
- [20] Boting Qu, Linran Mao, Zhenzhou Xu, Jun Feng, and Xin Wang. 2022. How Many Vehicles Do We Need? Fleet Sizing for Shared Autonomous Vehicles With Ridesharing. *IEEE Transactions on Intelligent Transportation Systems* 23, 9 (Sep. 2022), 14594–14607.
- [21] Boting Qu, Wenxin Yang, Ge Cui, and Xin Wang. 2020. Profitable Taxi Travel Route Recommendation Based on Big Taxi Trajectory Data. IEEE Transactions on Intelligent Transportation Systems 21, 2 (Feb 2020), 653–668.
- [22] Meng Qu, Hengshu Zhu, Junming Liu, Guannan Liu, and Hui Xiong. 2014. A Cost-Effective Recommender System for Taxi Drivers. In Proceedings of the 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (New York, New York, USA) (KDD '14). Association for Computing Machinery, New York, NY, USA, 45–54.
- [23] Maximilian Schreieck, Hazem Safetli, Sajjad Ali Siddiqui, Christoph Pflügler, Manuel Wiesche, and Helmut Krcmar. 2016. A Matching Algorithm for Dynamic Ridesharing. *Transportation Research Procedia* 19 (2016), 272–285.
- [24] Dingyuan Shi, Yongxin Tong, Zimu Zhou, Bingchen Song, Weifeng Lv, and Qiang Yang. 2021. Learning to Assign: Towards Fair Task Assignment in Large-Scale Ride Hailing. In Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining (KDD '21). Association for Computing Machinery, New York, NY, USA, 3549–3557.
- [25] Jiahui Sun, Haiming Jin, Zhaoxing Yang, Lu Su, and Xinbing Wang. 2022. Optimizing Long-Term Efficiency and Fairness in Ride-Hailing via Joint Order Dispatching and Driver Repositioning. In Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining. 3950–3960.
- [26] Na Ta, Guoliang Li, Tianyu Zhao, Jianhua Feng, Hanchao Ma, and Zhiguo Gong. 2018. An Efficient Ride-Sharing Framework for Maximizing Shared Route. *IEEE Transactions on Knowledge and Data Engineering* 30, 2 (2018), 219–233.
- [27] Raja Subramaniam Thangaraj, Koyel Mukherjee, Gurulingesh Raravi, Asmita Metrewar, Narendra Annamaneni, and Koushik Chattopadhyay. 2017. Xhare-a-Ride: A Search Optimized Dynamic Ride Sharing System with Approximation Guarantee. In 2017 IEEE 33rd International Conference on Data Engineering (ICDE). 1117–1128.
- [28] Yongxin Tong, Libin Wang, Zhou Zimu, Bolin Ding, Lei Chen, Jieping Ye, and Ke Xu. 2017. Flexible online task assignment in real-time spatial data. *Proceedings of the VLDB Endowment* 10, 11 (2017), 1334–1345.
- [29] Yongxin Tong, Yuxiang Zeng, Zimu Zhou, Lei Chen, and Ke Xu. 2022. Unified Route Planning for Shared Mobility: An Insertion-Based Framework. ACM Trans. Database Syst. 47, 1, Article 2 (may 2022), 48 pages.
- [30] Yongxin Tong, Yuxiang Zeng, Zimu Zhou, Lei Chen, Jieping Ye, and Ke Xu. 2018. A unified approach to route planning for shared mobility. *Proceedings of the VLDB Endowment* 11, 11 (2018), 1633.
- [31] Mohammad M Vazifeh, Paolo Santi, Giovanni Resta, Steven H Strogatz, and Carlo Ratti. 2018. Addressing the minimum fleet problem in on-demand urban mobility. *Nature* 557, 7706 (2018), 534–538.
- [32] Tanvi Verma, Pradeep Varakantham, Sarit Kraus, and Hoong Chuin Lau. 2017. Augmenting decisions of taxi drivers through reinforcement learning for improving revenues. In *Proceedings of the International Conference on Automated Planning and Scheduling*, Vol. 27. 409–417.
- [33] Jiachuan Wang, Peng Cheng, Libin Zheng, Lei Chen, and Wenjie Zhang. 2022. Online Ridesharing with Meeting Points. Proceedings of the VLDB Endowment 15, 13 (2022), 3963–3975.
- [34] Jiachuan Wang, Peng Cheng, Libin Zheng, Chao Feng, Lei Chen, Xuemin Lin, and Zheng Wang. 2020. Demand-Aware Route Planning for Shared Mobility Services. Proc. VLDB Endow. 13, 7 (mar 2020), 979–991.
- [35] Yuandong Wang, Hongzhi Yin, Hongxu Chen, Tianyu Wo, Jie Xu, and Kai Zheng. 2019. Origin-Destination Matrix Prediction via Graph Convolution: A New Perspective of Passenger Demand Modeling. In Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (Anchorage, AK, USA) (KDD '19). Association for Computing Machinery, New York, NY, USA, 1227–1235.
- [36] Yuandong Wang, Hongzhi Yin, Tong Chen, Chunyang Liu, Ben Wang, Tianyu Wo, and Jie Xu. 2021. Passenger Mobility Prediction via Representation Learning for Dynamic Directed and Weighted Graphs. ACM Trans. Intell. Syst. Technol. 13, 1, Article 2 (nov 2021), 25 pages.
- [37] Yixin Xu, Jianzhong Qi, Renata Borovica-Gajic, and Lars Kulik. 2020. Geoprune: Efficiently matching trips in ridesharing through geometric properties. In 32nd International Conference on Scientific and Statistical Database Management.

1 - 12.

- [38] Armin Sadeghi Yengejeh and Stephen L. Smith. 2021. Rebalancing Self-Interested Drivers in Ride-Sharing Networks to Improve Customer Wait-Time. IEEE Transactions on Control of Network Systems 8, 4 (Dec 2021), 1637–1648.
- [39] Chak Fai Yuen, Abhishek Pratap Singh, Sagar Goyal, Sayan Ranu, and Amitabha Bagchi. 2019. Beyond Shortest Paths: Route Recommendations for Ride-Sharing. In *The World Wide Web Conference (WWW '19)*. Association for Computing Machinery, New York, NY, USA, 2258–2269.