Implementing Dynamic Programming in Computability Logic Web

Keehang Kwon Dept. of Computer Engineering, DongA University khkwon@dau.ac.kr

We present a novel definition of an algorithm and its corresponding algorithm language called CoLweb. The merit of CoLweb[1] is that it makes algorithm design so versatile. That is, it forces us to a high-level, proof-carrying, distributed-style approach to algorithm design for both non-distributed computing and distributed one. We argue that this approach simplifies algorithm design. In addition, it unifies other approaches including recursive logical/functional algorithms, imperative algorithms, object-oriented imperative algorithms, neural-nets, interaction nets, proof-carrying code, etc.

As an application, we refine Horn clause definitions into two kinds: blinduniverally-quantified (BUQ) ones and parallel-universally-quantified (PUQ) ones. BUQ definitions corresponds to the traditional ones such as those in Prolog where knowledgebase is *not* expanding and its proof procedure is based on the backward chaining. On the other hand, in PUQ definitions, knowledgebase is *expanding* and its proof procedure leads to forward chaining and *automatic memoization*.

1 CoLweb as a unifying framework

Computer science lacks a unifying computing model. It consists of diverse models such as pseudocode, petri-net, interaction net, web languages, etc. Computability-logic web (CoLweb) is a recent attempt to provide a unifying computing model for distributed computing with the following principle:

computation as game playing

In particular, it integrates all the concepts widely used in AI as well as in everyday life – strategies, tactics, proofs, interactions, etc.

In this paper, we slightly extends CoLweb with class agents. A *class* agent is a cluster of agents in a compressed form. It is useful for applications such as dynamic programming.

We show that CoLweb, if scaled down, is also a candidate unifying model for a single, non-distributed computing. That is, it is an appealing alternative to pseudocode. This is not so surprising, because a block of memory cell within a single machine can be seen as an (local) agent. From this view, a machine with local memories can be seen as a multi-agent system where each agent shares a CPU.

2 Implementing Dynamic Programming

In the traditional logic programming approaches such as Prolog, their knowledgebase is *not* expanding and their underlying proof procedure is based on the backward chaining such as uniform proof. For example, a fib function is specified as:

$$\begin{split} &fib(0) = 1\\ &fib(1) = 1\\ &\forall x, y, z[(fib(x, y) \land fib(x+1, z)) \rightarrow fib(x+2, y+z)]. \end{split}$$

Note that the third definition – called *blind-universally-quantified defini*tion in [1] – is true independent of x. For example, to compute $\Box x fib(3, x)$, the machine simply returns 3 without expanding the BUQ-definition.

However, this procedure discards lemmas which are generated as new instances of the existing knowledgebase. Often these lemmas are useful and discarding them often leads to clumsy code when it deals with dynamic programming.

There have been different approaches to this topic such as tabled logic programming. These approaches, however, lead to slow performance. In this paper, we introduce a novel approach which is based on PUQs. As we shall see from the semantics of \wedge , its proof mechanism is required to add lemmas to the program, rather than discards them. These lemmas play a role similar to automatic memoization.

For example, a fib relation is specified as:

$$\begin{array}{l} fib(0,1) \\ fib(1,1) \\ \wedge x,y,z \; [(fib(x,y) \wedge fib(x+1,z) \rightarrow fib(x+2,y+z)] \end{array}$$

Note that the third definition – which we call PUQ definition – is compressed and needs to be *expanded* during execution. For example, to compute fib(3,3), our proof procedure adds the following:

$$fib(0,1) \wedge fib(1,1) \rightarrow fib(2,2)$$

$$fib(1,1) \wedge fib(2,2) \rightarrow fib(3,3).$$

One consequence of our approach is that it supports dynamic programming in a clean code.

3 CoLweb Algorithms

Although algorithm is one of the central subjects, there have been little common understandings of what an algorithm is. We believe the following definition is a simple yet quite compelling definition:

An algorithm for an agent d who can perform a task T, written as d = T, is defined recursively as follows:

Algorithm alg(d = T)

Step 1: Identify a set of agents $c_1 = T_1, \ldots, c_n = T_n$ such that they can collectively perform T.

Step 2. Call recursively each of the following: $alg(c_1 = T_1), \ldots, alg(c_n = T_n)$.

Note that Step 2 is missing from the traditional definition of algorithms, i.e., algorithm as a sequence of instructions to perform a task. We view instructions something that are not fixed and Step 2 is added for manipulating the instructions. It turns out that Step 2 is the key idea which makes algorithm design so interesting, compared to the traditional definition. In other words, our approach corresponds to n-level-deep algorithms, while the traditional one to 1-level-deep.

In the above, c = T represents an agent c who can do task T. In the traditional developments of declarative algorithms, T is limited to simple tasks such as recursive functions or Horn clauses. Most complex tasks such as interactive ones are not permitted. In our algorithm design, however, interactive tasks are allowed.

To define the class of computable tasks, we need a specification language. An ideal language would support an optimal translation of the tasks. Computability logic(CoL)[1] is exactly what we need here.

4 Preliminaries

In this section a brief overview of CoL is given.

There are two players: the machine \top and the environment \perp .

There are two sorts of atoms: *elementary* atoms p, q, \ldots to represent elementary games, and *general atoms* P, Q, \ldots to represent any, not-necessarily-elementary, games.

- **Constant elementary games** \top is always a true proposition, and \perp is always a false proposition.
- **Negation** \neg is a role-switch operation: For example, $\neg(0 = 1)$ is true, while (0 = 1) is false.
- **Choice operations** The choice group of operations: \Box , \sqcup , \forall and \exists are defined below.

 $\Box xA(x)$ is the game where, in the initial position, only \bot has a legal move which consists in choosing a value for x. After \bot makes a move $c \in \{0, 1, \ldots\}$, the game continues as A(c). $\forall xA(x)$ is similar, only here the value of x is invisible. \sqcup and \exists are symmetric to \Box and \forall , with the difference that now it is \top who makes an initial move.

Parallel operations Playing $A_1 \wedge \ldots \wedge A_n$ means playing the *n* games concurrently. In order to win, \top needs to win in each of *n* games. Playing $A_1 \vee \ldots \vee A_n$ also means playing the *n* games concurrently. In order to win, \top needs to win one of the games. To indicate that a given move is made in the *i*th component, the player should prefix it with the string "*i*.". The operations $\land A$ means an infinite parallel game $A \wedge \ldots \wedge A \wedge \ldots$. To indicate that a given move is made in the i(i > 1)th component, we assume the player should first replicate *A* and then prefix it with the string "*i*.".

In addition, we use the following notation:

$$\wedge x_m^n A =_{def} A(m/x) \wedge \ldots \wedge A(n/x).$$

Reduction $A \to B$ is defined by $\neg A \lor B$. Intuitively, $A \to B$ is the problem of reducing B (*consequent*) to A (*antecedent*).

5 CoLweb

CoLweb is a multi-agent version of computability logic. It consists of a set of agent declarations. An example looks like the following form:

$$\alpha_1 = F_1$$

$$\alpha_2 = F_2$$

$$\alpha_3 = F_3^{\alpha_1} \wedge F_4^{\alpha_1, \alpha_2}$$

$$\alpha_4 = \alpha_2^{\alpha_1}$$

$$\wedge x \ \alpha(x) = F(x)$$

Here α_1 is an agent name and F_1 is called the knowledge of α_1 . Similarly for F_2 is the knowledge of α_2 .

The agent α_3 has F_3 and F_4 as its knowledge, provided that F_3 is a logical consequence of α_1 and F_4 a logical consequence of α_1, α_2 combined. If F_3 is not logical consequence of α_1 , the above will be converted to:

$$\alpha_3 = \top \wedge F_4^{\alpha_1, \alpha_2}.$$

In α_4 , α_2 is a macro call, meaning that

$$\alpha_4 = F_2^{\alpha_1}.$$

The agent $\wedge x\alpha(x) = F(x)$ is a *class agent* which means the following:

$$(\alpha(1) = F(1)) \land (\alpha(2) = F(2)) \land \ldots \land \ldots$$

As an example, consider the following CoLweb:

$$/m(0) = q$$

 $\wedge x / m(x') = p \wedge / m(x)$

Given this definition, $p \wedge (p \wedge (p \wedge q))$ can be represented simply as /m(0'''). We assume in the above that ' is the number-successor function.

6 Example

Recursive algorithms focuses on designing algorithms with only one agent. On the contrary, in the multi-agent (or object-oriented) approach, there is no limit regarding the number of agents involved in developing an algorithm. Therefore, the main virtue of the multi-agent approach is that much more diverse algorithms are possible.

To support multi-agent programming, computability logic allows the introduction of a *location/agent/object* for knowledgebases. We called this computability logic web (CoLweb) in our previous works. For example, assume that fib(X, Y) is stored at a location /a[X] and the rule

$$\forall y \forall z (fib(X, y) \land fib(X+1, z)) \rightarrow fib(X+2, y+z)$$

is stored at b[X+2]. Then *fib* can be rewritten as:

$$\begin{split} &\wedge x_0^{\infty} \ /b[x+2] = \forall y \forall z [(fib(x,y) \land fib(x+1,z)) \rightarrow fib(x+2,y+z)] \\ &/a[1] = fib(1,1) \\ &/a[2] = fib(2,1) \\ &\wedge x_0^{\infty} \ /a[x+2] = (\sqcup y fib(x+2,y))^{/a[x],/a[x+1],b[x+2]} \\ &/fib = \sqcap n(\sqcup y fib(n,y)^{/a[n]}) \\ &/query = \sqcup y fib(4,y)^{/fib} \end{split}$$

Now consider an expression /query. This expression tries to solve $\Box yfib(4, y)$ relative to /fib. It then executes fib by trying to solve $\Box yfib(4, y)$ relative to /a[4]. It eventually creates the following which is a form of memoization:

$$\begin{aligned} &/a[3] = fib(3,2) \\ &/a[4] = fib(4,3) \\ &\wedge x_3^{\infty} / a[x+2] = (\sqcup yfib(x+2,y))^{/a[x],/a[x+1],b[x+2]} \end{aligned}$$

Similarly for the class agent /b. Note also that the above code is nothing but an object-oriented programming in a distilled form. That is, in objectoriented terms, /a[1], /a[2] are regular objects and /a[x+2], /b[x+2] are class objects.

7 Some Variation

The Fibonacci implementation in the previous section is quite complex and is hard to prove its correctness. We will present a simpler version.

z))

$$\begin{split} /b &= \forall x \forall y \forall z (fib(x,y) \land fib(x+1,z)) \to fib(x+2,y+1) \\ /a[1] &= fib(1,1) \\ /a[2] &= fib(2,1) \\ \land x_0^{\infty} /a[x+2] &= (\sqcup y (fib(x+2,y))^{/a[x],/a[x+1],/b} \\ /fib &= \sqcap n ((\sqcup y fib(n,y))^{/a[n]}) \\ /query &= (\sqcup y fib(4,y))^{/fib} \end{split}$$

The above is somewhat different from the old version in that the agent b is not a class agent anymore. The agent eliminates \wedge in favor of \forall -quantifier. One consequence is that b is not expanding anymore.

Now consider an expression /query. This expression tries to solve $\Box yfib(4, y)$ relative to /fib. It then executes fib by trying to solve $\Box yfib(4, y)$ relative to /a[4]. It eventually creates the following which is a form of memoization:

 $\begin{array}{l} /a[3] = fib(3,2) \\ /a[4] = fib(4,3) \\ \wedge x_3^{\infty} \ /a[x+2] = (\sqcup y(fib(x+2,y))^{/a[x],/a[x+1],/b} \end{array}$

8 Algorithm Design via CoLweb

There are traditional approaches to algorithm design (for small-size problems) and software design (for big- size ones):

algorithm design = pseudocode, etc

software design = UML

We propose an alternative approach:

$$algorithm design = CoLweb$$

software design = CoLweb

We compare some approaches.

- 1. CoLweb algorithms
- 2. imperative algorithms
- 3. object-oriented imperative algorithms
- 4. logical/recursive algorithms

(1) is a high-level, lemma-based approach to algorithm design and has the following features: (a) consists of a sequence of *big* steps (b) execution from bottom-up, (c) support parallelism, and (d) support proof-carrying codes. We consider this approach the best, leading to clean, versatile yet efficient codes.

Both (2),(3) are inferior versions of (1) and can be seen as a sequence of *small* steps, execution from top-down, support no correct and support no parallel codes. These leads to non-parallel, efficient yet messy and incorrect code.

(4) is simply a high-level approach without any use of lemmas and can be seen as an empty sequence. We consider this the worst, leading to clean yet inefficient code.

9 Conclusion

Note that we introduce an interesting kind of agents called class agents. A class agent is a collection of agents in a compressed form.

Our ultimate goal is to implement the computability logic web[1, 2] which is a promising approach to reaching general AI. New ideas in this paper will be useful for organizing agents and their knowledgebases in CoLweb.

We now discuss how the machine executes CoLweb. An important point is that it must first check the *validity* of CoLweb given by the programmer. This is not an easy task which may require new, sophisticated inductions. In this sense, it is a *proof-carrying* code.

References

- [1] G. Japaridze, "Introduction to computability logic", Annals of Pure and Applied Logic, vol.123, pp.1–99, 2003.
- [2] G. Japaridze, "Sequential operators in computability logic", Information and Computation, vol.206, No.12, pp.1443-1475, 2008.
- [3] D. Miller, "A logical analysis of modules in logic programming", Journal of Logic Programming, vol.6, pp.79–108, 1989.