DSVAE: Interpretable Disentangled Representation for Synthetic Speech Detection

Amit Kumar Singh Yadav[†]

Kratika Bhagtani[†] Ziyue Xiang[†] Edward J. Delp[†]

Paolo Bestagini[‡]

Stefano Tubaro[‡]

[†]Video and Image Processing Lab (VIPER), School of Electrical and Computer Engineering,

Purdue University, West Lafayette, Indiana, USA

[‡]Dipartimento di Elettronica, Informazione e Bioingegneria, Politecnico di Milano, Milano, Italy

Abstract—Tools to generate high quality synthetic speech that is perceptually indistinguishable from speech recorded from human speakers are easily available. Many incidents report misuse of synthetic speech for spreading misinformation and committing financial fraud. Several approaches have been proposed for detecting synthetic speech. Many of these approaches use deep learning methods without providing reasoning for the decisions they make. This limits the explainability of these approaches. In this paper, we use disentangled representation learning for developing a synthetic speech detector. We propose Disentangled Spectrogram Variational Auto Encoder (DSVAE) which is a two staged trained variational autoencoder that processes spectrograms of speech to generate features that disentangle synthetic and bona fide speech. We evaluated DSVAE using the ASVspoof2019 dataset. Our experimental results show high accuracy (> 98%) on detecting synthetic speech from 6 known and 10 out of 11 unknown speech synthesizers. Further, the visualization of disentangled features obtained from DSVAE provides reasoning behind the working principle of DSVAE, improving explainability of our method. DSVAE performs well compared to several existing methods. Additionally, DSVAE works in practical scenarios such as detecting synthetic speech uploaded on social platforms and against simple attacks such as removing silence regions.

Index Terms-disentangled representation learning, synthetic speech detection, explainable AI, autoencoder

I. INTRODUCTION

Generating perceptually human-like synthetic speech has been of interest for a long time. Traditional synthetic speech methods either use source modeling or simple waveform cut-paste techniques to generate synthetic speech [1]-[3]. Recent deep learning methods can generate high-quality and semantically consistent long-duration speech signals [4]-[6]. Some deep learning methods can generate synthetic speech that can mimic language accents and impersonate persons using 3 seconds of their speech [7]–[9]. The diminishing perceptual difference between synthetic speech and bona fide human speech is useful in applications such as voice assistants, games, and e-learning [10]-[12]. However, several incidents have reported misuse of synthetic speech for spreading misinformation [13], committing financial fraud [14], and using for impersonation attacks [9]. To prevent such misuse of synthetic speech, there is a need for development of methods that can detect synthetic speech.

Several methods have been proposed for detecting synthetic speech [15]-[21]. These methods have shown promising detection accuracy but lack in interpretability/explainability. By interpretability we mean that the method provides reasoning for the decision it makes [22]. Kien et al. argued that representations produced by a neural network are interpretable by humans only if they are discriminative w.r.t one attribute (characteristic) [23]. For example, in speech synthesis, if one of the representation controls only the accent of the speech signal and a different instance of this representation generates a different accent in speech, then the representation is discriminative w.r.t only one attribute *i.e.*, accent.

Disentangled representation learning has been proposed as an approach to learn interpretable representations from a neural network [24]-[27]. This approach separates the network's latent representations into different components. Tang et al. used disentangled representation learning to control certain regions while generating synthetic images [28]. Disentangled representation learning has also been used to generate interpretable representations for face anti-spoofing [26], [27]. The disentangled representation learnt for face anti-spoofing will be independent of the content in image and will be different depending on only one attribute *i.e.*, whether face image is spoofed or is pristine. For example, two images with identical faces/content in them will have different/farther representations if one image is spoofed and other image is pristine. So, visualization of the disentangled representation will show evident discrimination between representations of pristine and spoofed face images. Such a visualization can provide forensic analysts with reasoning behind working of the detector making it more explainable. Disentangling the representation improves the method's ability to generalize to unseen face-spoofing attacks [25], [27].

Generalization to unseen attacks is also important for synthetic speech detectors. One major challenge involved in synthetic speech detection is the increasing number of synthesizers which makes it practically infeasible to include synthetic speech from all possible speech synthesizers during training. This demands that synthetic speech detection methods should generalize to unknown synthesizers that were not included in training. Motivated by the success of disentangled representation learning in face anti-spoofing [24]-[27], controlled image generation [28], voice conversion [29], [30], and speech generation tasks [31], we propose a method to use it for developing a detector for synthetic speech detection.

The contributions of our paper are as follows. (a) We propose Disentangled Spectrogram Variational Auto Encoder (DSVAE), a dual stage network using speech spectrogram for synthetic speech detection. (b) The disentangled representations obtained from DSVAE when visualized provide explanation behind the decision made by the detector and enable generalization of our method to 10/11 unknown synthesizers. (c) We use disentangled representation and generate an activation map to highlight regions in the spectrogram that help to make the decision. (d) DSVAE performs better than several existing methods using spectrogram and baselines provided in the ASVspoof2019 Challenge. (e) We also investigate performance of DSVAE in two practical scenarios: when synthetic speech is uploaded on social platforms and during simple attacks like silence removal from speech. DSVAE performs well in these scenarios.

The rest of the paper is organized as follows. In Section II we discuss existing methods for synthetic speech detection and disentangled representation learning. Section III describes Disentangled Spectrogram Variational Auto Encoder (DSVAE). Section IV describes the dataset used in our experiments and the implementation details. Section V discusses our experimental results. Finally, Section VI concludes the paper with our last remarks.

II. RELATED WORK

In this section we describe existing work in synthetic speech detection and disentangled representation learning.

A. Synthetic Speech Detection

Some methods for synthetic speech detection use hand crafted features such as cepstral coefficients to detect synthetic speech [21], [32]–[35]. These hand crafted features include temporal and spectral features such as Constant Q Cepstral Coefficients (CQCCs) [33], Mel Frequency Cepstral Coefficients (MFCCs) [34], Constant-Q Transform (CQT) [21], and Linear Frequency Cepstral Coefficients (LFCCs) [21]. Since feature selection procedure can be tedious, other approaches process the time-domain speech signal as a sequence [15] using Recurrent Neural Network (RNN) [36]. The Fourier Transform can be used to convert a time domain speech signal into an image representation known as a spectrogram [37]. The spectrogram has been used for speech forensics using a transformer neural network [38] or a Convolutional Neural Network (CNN) [18], [19], [39]–[41].

These methods for synthetic speech detection lack interpretability [22], [42], *i.e.*, they do not provide any reasoning behind how a detector produces its output. Some work has been done in providing explanations for synthetic speech detectors output [43]–[47]. For example, Ge *et al.* [46] analyzed the detector behaviour using Shapley Additive Explanations [48] and Chettri *et al.* [44] used Local Interpretable Model-Agnostic Explanations [49] to provide artifacts that contribute most to synthetic speech detectors output. Tak *et al.* in [43] analyzed different sub-band components of the spectrum of a speech signal obtained using Fourier transform to explain which sub-band contributes most to synthetic speech artifacts. These methods mainly focus on post analysis of detectors to add explanation behind its working.

In this paper, we examine spectrogram representations of speech to obtain disentangled representations using a Variational Auto Encoder network. These disentangled representations when visualized provide explanation behind working of detector.

B. Disentangled Representation Learning

Disentangled representation learning methods leverage the idea that it is possible to divide learned representations into multiple explainable components [23], [24]. This concept has been used in generative networks for image generation to control regions of synthetic images [28], [50]. Some methods have also used disentangled representation learning for voice conversion, and voice style transfer during speech synthesis [29], [30], [51], [52].

The use of disentangled representation learning in forensic applications is mostly limited to face anti-spoofing systems [26], [27]. Zhang *et al.* proposed a one stage disentanglement network using autoencoder for face anti-spoofing [26]. Wang *et al.* also used an autoencoder neural network but with a two stage training strategy to generalize performance to unseen face spoofing attacks [25]. Two stage disentanglement autoencoder proposed in [25] showed better generalization to detect unknown face spoofing attacks. We propose a variational autoencoder architecture and use two stage training to learn disentangled representation for speech forensics.

III. PROPOSED METHOD

In this paper we propose Disentangled Spectrogram Variational Auto Encoder (DSVAE) to detect if a speech signal under analysis is bona fide or synthetically generated. We do so by exploiting variational autoencoders that provide disentangled representation of the input speech signal. We refer to these representations as disentangled because they depend on only one characteristic of speech signal *i.e.*, whether speech signal is bona fide or synthetic. Hence, these representations disentangle when visualized for bona fide and synthetic speech adding explanation behind the working of detector. The disentangled representation is also used to compute an activation map that highlights which regions of the input are used for classification. Together with disentangled representation and an activation map DSVAE sheds light on the working principle of the detector, making it more explainable.

In this section, we first provide an overview of the overall proposed method. Then we report additional details about the training procedure.

A. Overall Approach

An autoencoder maps an input data point to a representation vector. A variational autoencoder maps input to a distribution from which the data point could have been generated [53]. Wang *et al.* and Zhang *et al.* used autoencoder network for face anti-spoofing [25], [26]. We modified their autoencoder

architecture, added stochastic variational inference and learning [53], and optimized the obtained variational autoencoder for processing spectrograms. Contrary to face images, spectrograms are 2-D single channel inputs and require different number of layers, kernel size, and dimension of representation vector. The architecture of our optimized variational autoencoder can be found in our code.

Given a time domain speech signal x, we compute the magnitude of its Short Time Fourier Transform (STFT) using a Hanning window of size 25 ms with a shift of 10 ms to obtain the spectrogram [37]. We used these parameters following previous methods which use spectrogram for general audio classification and speech forensics tasks [54], [55]. We convert the frequency axis of the spectrogram from the Hertz scale to the mel-scale [56]. The mel-scale correlates better with the human auditory system as compared to the Hertz scale [56]. The conversion between the Hertz frequency scale $f_{\rm Hz}$ and the mel frequency scale $f_{\rm mel}$ [56] is obtained by

$$f_{\rm mel} = 2595 \cdot \log_{10} \left(1 + \frac{f_{\rm Hz}}{700} \right)$$
 (1)

We represent the mel-scale spectrogram by X. Our claim is that the mel-spectrogram X can be decomposed into two parts that contain complementary pieces of information about the speech signal. The first type of information is general speech information which is common in both bona fide and synthetic speech signals. We denote this by \mathbf{F}_{G} (see Fig. 1 and Fig. 2) and refer to it as the general speech representation. The second type of information discriminates bona fide speech from synthetic speech. We denote it by \mathbf{F}_{D} (see Fig. 2) and refer to it as the disentangled representation. The disentangled representation discriminates w.r.t whether the speech signal is bona fide or synthetic.

We use a two stage training approach to obtain \mathbf{F}_{G} and \mathbf{F}_{D} . In Training Stage 1, we use the General Representation Network described in Section III-B (Fig. 1) to obtain \mathbf{F}_{G} . Once we obtain \mathbf{F}_{G} , we fix the weights of the encoder E_{G} that provides general speech representation *i.e.*, \mathbf{F}_{G} in Fig. 2 and then train the Disentangled Representation Network and the Unsupervised Activation Generation Network described in Section III-C (Fig. 2) to obtain \mathbf{F}_{D} and an activation map \mathbf{A}_{map} . \mathbf{A}_{map} shows regions of spectrogram that contain discriminative features for detecting synthetic speech.

During evaluation/inference, we do not need to obtain the general speech representation *i.e.*, \mathbf{F}_{G} . We need the disentangled representation *i.e.*, \mathbf{F}_{D} to decide whether a speech signal is synthetic or bona fide. The block diagram for our evaluation/inference stage is shown in Fig. 3.

B. Training Stage 1

In the first training stage, we train the General Representation Network shown in Fig. 1 for the self-supervised task of reconstructing the input spectrogram that contains the common speech information [25], [53]. We do not use any synthetic speech signals during this stage. We train only on real speech signals. This ensures that the method does not learn any discriminative features during this stage.

The variational autoencoder consists of an encoder E_G and a decoder D. The Encoder E_G produces a general speech feature vector \mathbf{F}_G from the spectrogram \mathbf{X} . The Decoder Duses \mathbf{F}_G to reconstruct the spectrogram of the common speech information. We denote the reconstructed spectrogram by $\tilde{\mathbf{X}}$, where $\tilde{\mathbf{X}} = D(E_G(\mathbf{X}))$.

We train the network using a weighted average of two loss functions: the reconstruction loss; the Kullback-Leibler (KL)-divergence loss. The reconstruction loss \mathcal{L}_{recon} is defined as

$$\mathcal{L}_{recon} = E[||\mathbf{X} - \tilde{\mathbf{X}}||_2^2], \qquad (2)$$

where E is the expected value/mean of the square error between the input \mathbf{X} and the output $\tilde{\mathbf{X}}$. The KL-divergence loss \mathcal{L}_{KL1} is the typical loss function used for variational autoencoders and is defined as

$$\mathcal{L}_{KL1} = \sum_{i} KL(q_i^g(z^g|x)) || p(z^g|x))$$
(3)

Here, q^g is the distribution learned by encoder E_G , p is the true prior distribution, x is an instance of input spectrogram **X**, and z^g is an instance *i.e.*, **F**_G sampled from the learned distribution. We followed reparameterization mentioned in [53] for variational autoencoder E_G and \mathcal{L}_{KL1} .

C. Training Stage 2

In the second training stage, we train the Disentangled Representation Network and the Unsupervised Activation Generation Network shown in Fig. 2 to obtain the disentangled representation and the activation map. The Disentangled Representation Network processes the spectrogram \mathbf{X} using two identical variational autoencoders E_G and E_D to obtain a general speech representation \mathbf{F}_G and a disentangled representation \mathbf{F}_D . The goal of the second training stage is to learn interpretable features that differentiate/disentangle bona fide speech from synthetic speech.

We fix the weights of E_G to the weights obtained from Training Stage 1 (Section III-B). Fixing the weights of E_G fixes the network used for obtaining the general speech representation from the input speech signal. Note that we hypothesize that both bona fide and synthetic speech have these general features and they are common for both classes. We concatenate the general feature vector \mathbf{F}_G and the disentangled feature vector \mathbf{F}_D to form \mathbf{F} . We process \mathbf{F} using a decoder D_{rec} to reconstruct the spectrogram. We denote the reconstructed spectrogram as $\hat{\mathbf{X}}$ (see Fig. 2). Note that while learning the general speech representation in Training Stage 1 we used a different decoder D (see Fig. 1).

To train this network we minimize a weighted average of multiple loss terms. To generate spectrograms similar to the original input spectrograms, we use the reconstruction loss \mathcal{L}_{recon} described in Section III-B. We also use the KL-divergence loss \mathcal{L}_{KL2} for the encoder E_D defined as

$$\mathcal{L}_{KL2} = \sum_{i} KL(q_i^d(z^d|x)) || p(z^d|x))$$
(4)



Fig. 1: Block diagram of DSVAE for Training Stage 1: The General Representation Network.



Fig. 2: Block diagram of DSVAE for Training Stage 2: The Disentangled Representation Network and The Unsupervised Activation Generation Network.



Fig. 3: Block diagram of DSVAE for evaluation/inference.

Here, q^d is the distribution learned by encoder E_D , p is the true prior distribution, x is an instance of input spectrogram **X**, and z^d is an instance *i.e.*, **F**_D sampled from the learned

distribution. To disentangle \mathbf{F}_{D} for bona fide and synthetic speech signal we use the CosFace loss \mathcal{L}_{cos} proposed in [57]. This loss minimizes intra-class variance of \mathbf{F}_{D} and maximizes

inter-class variance by maximizing the decision margin in the angular space [57].

The Unsupervised Activation Generation Network further processes the disentangled feature \mathbf{F}_{D} to generate an activation map that highlights the spectrogram region that is captured by the disentangled representation. We denote the activation map by \mathbf{A}_{map} . DSVAE processes \mathbf{F}_{D} using the Decoder D_{map} to create the activation map \mathbf{A}_{map} . Following [25], to avoid trivial identity activation map, we impose L_1 regularization on the activation map for bona fide speech signal. We refer this loss as \mathcal{L}_{con} and it is defined as

$$\mathcal{L}_{con} = E[||\mathbf{A}_{\mathrm{map}}||_1] \tag{5}$$

where E is the expected value from all bona fide speech signals. This loss helps to ensure that the activation map is not an identity map activating all regions of spectrogram. We take dot product of the activation map \mathbf{A}_{map} and the spectrogram \mathbf{X} to obtain the activated spectrogram map \mathbf{X}_{map} . Following previous work in face anti-spoofing [25], [26], we process \mathbf{X}_{map} using a classifier C to obtain probability of the speech signal being synthetic which is used to determine the prediction label *i.e.*, \hat{y} . To train the classifier C, we use the binary cross entropy loss \mathcal{L}_{bce} defined as

$$\mathcal{L}_{bce} = E[-y \cdot \log(\hat{y}) + (1-y) \cdot \log(1-\hat{y})] \tag{6}$$

where E is expected value from all speech signal, \hat{y} is the prediction label from classifier C and y is ground truth label *i.e.*, equal to 1 for synthetic speech and 0 for bona fide speech.

IV. EXPERIMENTS

In this section, we describe the dataset used for our experiments, the objective metrics, and the parameters used in our implementation.

A. Dataset

We use the Logical Access (LA) part of the ASVspoof2019 dataset [32], [58]. This dataset contains approximately 121.5k speech signals. These signals are divided into a training set D_{tr} , a validation set D_{dev} , and an evaluation set D_{eval} [32] in the approximate ratio of 1:1:3. Each set is highly unbalanced w.r.t the number of bona fide and synthetic speech signals. There are approximately 89% synthetic speech signals and 11% bona fide speech signals in each set. These speech signals are encoded using the Free Lossless Audio Codec (FLAC) format [59].

We select this dataset for evaluation because it contains synthetic speech signals from unknown synthesizers in the evaluation set D_{eval} . Investigating this dataset helps us to identify if our disentangled representation generalizes to unknown synthesizers. The dataset contains synthetic speech signals from 19 speech synthesizers A01 to A19. Two pairs of synthesizers namely (A04, A16), and (A06, A19) have the same underlying architectures but are trained on different datasets. Therefore, overall there are only 17 different speech synthesizers. All 17 speech synthesizers can be categorized into one of the three categories based on the type of generation: neural networks, vocoders, and waveform concatenation [58]. There are 63.9k synthetic speech signals in the D_{eval} set, out of which 61.5k synthetic speech signals are generated from 11 unknown synthesizers A07 to A18 (except A16) that are not present in D_{tr} or D_{dev} . The training and validation sets contain synthetic speech signals from methods A01 to A06. The bona fide speech signals in the training, validation, and testing sets are recorded from human speakers which do not overlap among the three sets.

B. Evaluation Metrics

We use Equal Error Rate (EER) as our performance metric for evaluation. It is the recommended metric for comparison in the ASVspoof2019 Challenge [32], [58]. We obtain EER from Receiver Operating Characteristics (ROC) by finding the rate where False Negative Rate (FNR) and False Positive Rate (FPR) are equal. Lower the EER, the better is the performance of a method. We also report detection accuracy [60] which is percentage of total correct classifications out of all the classifications made.

C. Implementation Details

For Training Stage 1 (*i.e.*, to find the general speech representation) we use speech signals from the Audioset dataset [61]. We fixed the dimension of general speech representation vector (*i.e.*, \mathbf{F}_{G}) to 512 dimensions. We use the Adam optimizer [62] with an initial learning rate of 10^{-3} , a decay rate of 5×10^{-7} and trained the network using a batch size of 256. We trained the network for \approx 333K iterations until convergence (the loss is not changing and is below 0.37). We use \mathcal{L}_{rec} and KL-divergence loss \mathcal{L}_{KL1} described in Section III-B for training the variational encoder E_G . Therefore, the loss for Training Stage 1 (\mathcal{L}_{stage1}) is given by

$$\mathcal{L}_{stage1} = \mathcal{L}_{recon} + \mathcal{L}_{KL1} \tag{7}$$

For the second stage of training we use the AdamW [63] optimizer with an initial learning rate of 10^{-4} and a weight decay of 10^{-3} for training. We fixed the dimension of disentangled speech representation vector (*i.e.*, \mathbf{F}_D) to 512 dimensions. We fixed the weights of the variational encoder E_G and trained using the sum of five losses- \mathcal{L}_{bce} , \mathcal{L}_{cos} , \mathcal{L}_{con} , \mathcal{L}_{KL2} , and \mathcal{L}_{recon} . These losses are defined in Section III-B and Section III-C. Therefore the loss for Training Stage 2 (L_{stage2}) is

$$\mathcal{L}_{stage2} = \mathcal{L}_{recon} + \mathcal{L}_{cos} + \mathcal{L}_{con} + \mathcal{L}_{KL2} + \mathcal{L}_{bce} \qquad (8)$$

We trained the second stage for 100 epochs with a batch size of 100 on the training set D_{tr} from ASVspoof2019 [32]. We select the model with the best balanced accuracy on validation set D_{dev} for evaluation.

V. EXPERIMENTAL RESULTS

This section describes the results of our experiments.



Fig. 4: Detection accuracy of DSVAE on bona fide speech signal (blue), and synthetic speech from known (green) and unknown (orange) synthesizers in the of the ASVspoof2019 dataset. A16 and A19 have same architecture as A04 and A06.



Fig. 5: 2-D t-SNE visualization of general speech representation (\mathbf{F}_{G}) and disentangled representation (\mathbf{F}_{D}) obtained by DSVAE for A01 to A06 speech synthesizers in validation set and A07 to A19 speech synthesizers in the evaluation set of the ASVspoof2019 dataset. '**d**' is the Mahalanobis distance between the distribution of bona fide speech representation and synthetic speech representation from a synthesizer. '**d**' in green is obtained from \mathbf{F}_{G} and '**d**' in brown is obtained from \mathbf{F}_{D} .

A. Synthetic Speech Detection

In this experiment, we evaluated the ability of Disentangled Spectrogram Variational Auto Encoder (DSVAE) to distinguish between bona fide and synthetic speech. We take synthetic speech signals from all the synthesizers in D_{dev} and D_{eval} set of the ASVspoof2019 dataset [32]. The synthetic speech signals are generated from 19 synthesizers (from A01 to A19), out of which synthetic speech signals from 6 synthesizers (from A01 to A06) were present in the training set. Synthesizer A16 and synthesizer A19 have same underlying architecture as synthesizer A04 and A06, respectively. Therefore there are 17 different synthesizers, 6 known and 11 unknown synthesizers. For bona fide class we used the union of bona fide speech signals from D_{dev} and D_{eval} set. These are from 58 different human speakers that do not overlap with the speakers from the training set.

Fig. 4 shows the detection accuracy of DSVAE on speech belonging to each one of the synthesizers as well as bona

fide speech. In total there are approximately 10k bona fide speech signals and about 86k synthetic speech signals. We observe from Fig. 4 that DSVAE has perfect detection accuracy for all known and unknown synthesizers and bona fide speech except for the unknown synthesizer A17. Synthesizer A17 belongs to the most challenging class according to the ASVspoof2019 Challenge result [64]. A significant portion in the starting of the signal is non speech segment (silence). For example, the silence in the start covers on average around 26% duration of the total duration for each signal from synthesizer A17. Speech signal from other unknown synthesizers such as synthesizer A14 have on average same total duration but the the silence in the start covers on average around 8% of the total duration. The accuracy reported in Fig. 4 for synthesizer A17 corresponds to the one obtained after removing silence segment from the start of the signal generated from A17. With the silence segment the detection accuracy for synthetic speech signal from synthesizer A17 was less than 10%. Therefore, removing silence segment from starting improved performance of DSVAE on A17 class. However, it is still less comparative to other classes. A possible reason could be after removing non-speech (silent) segment from starting, DSVAE had on average duration of only 2.5 seconds. Hence, there is less speech segment to analyze and that might be the reason for lower performance of DSVAE on class A17.

B. Visualizing General and Disentangled Features

In this experiment, we visualized the general speech representations \mathbf{F}_G and disentangled representations \mathbf{F}_D learnt by DSVAE. \mathbf{F}_G represents those features that are common to both bona fide and synthetic speech, hence during visualization we expect overlapping of \mathbf{F}_G for synthetic and bona fide speech signals. \mathbf{F}_D represents those features that differentiate synthetic speech from bona fide speech, hence during visualization we expect either very minimal or no overlapping of \mathbf{F}_D for synthetic and bona fide speech signals.

For 2D visualization of the feature vectors \mathbf{F}_{G} and \mathbf{F}_{D} , we first projected them from 512-D to 2-D using T-distributed Stochastic Neighbor Embedding (t-SNE) [65]. Fig. 5 shows a visualization for both \mathbf{F}_{G} and \mathbf{F}_{D} for each of the synthesizers present in the ASVspoof2019 dataset. The red color corresponds to synthetic speech while the blue color corresponds to bona fide speech. In Fig. 5, we can observe that the general speech representations overlap and the disentangled representations do not overlap except for very few speech samples. This is true for all the known synthesizers and 10 out of 11 unknown synthesizers. The disentanglement can also be shown quantitatively. We compute the Mahalanobis distance [66] (denoted by **d**) between the distribution of bona fide and synthetic speech representation for each of the synthesizer. Larger Mahalanobis distance indicates the two distributions are more dissimilar. Fig. 5 shows that the Mahalanobis distance obtained from \mathbf{F}_{D} (in brown) is very large compared to Mahalanobis distance obtained from \mathbf{F}_{G} (in green). Therefore, feature \mathbf{F}_{D} disentangle synthetic speech from bona fide speech. For synthesizer A17, visualization of \mathbf{F}_{G} representation is as expected and d obtained from F_G is also low. But visualization of \mathbf{F}_{D} representation shows that many of the synthetic speech signals are not disentangling from bona fide speech signal. Notice that disentangled representation \mathbf{F}_{D} for several



Fig. 6: 2-D t-SNE visualization showing general speech representation learnt by DSVAE is different from disentangled representation.

TABLE I: EER% of DSVAE and 16 other methods for synthetic speech detection using the ASVspoof2019 dataset.

Method Name	Feature	Network	EER
B01	CQCC	GMM	8.09%
B02	LFCC	GMM	9.57%
S01	Spectrogram	VGG	10.52%
S02	Log-Spectrogram	MesoInception	10.02%
S03	Spectrogram	CNN	9.57%
S04	Spectrogram+CQT	VGG+SincNet	8.01%
S05	Spectrogram _{CQOST}	DNN	8.04%
S06	Spectrogram _{ICQCC}	DNN	7.70%
S07	Spectrogram _{CQT}	Transformer	7.50%
S08	Spectrogram _{CQT}	MesoNet	7.42%
S09	Spectrogram _{CQT}	LSTM	7.16%
S10	Spectrogram _{CQT}	LCNN-Attention	6.76%
S11	Spectrogram _{CQT}	ResNet18	6.55%
S12	Spectrogram _{CQT}	LCNN	6.35%
S13	Spectrogram _{CQT}	LCNN+LSTM	6.23%
S14	Mel-Spectrogram	PaSST	5.26%
DSVAE	Mel-Spectrogram	VAE	2.16%

synthetic speech signals from synthesizer A17 are on top of the cluster created by disentangled representation $\mathbf{F}_{\rm D}$ of bona fide speech. This is also reflected by low detection accuracy on synthesizer A17 in Fig. 4 and lower value of **d** obtained from $\mathbf{F}_{\rm D}$ for synthesizer A17. Therefore, low detection accuracy for any unknown synthesizer can directly be attributed to overlapping in disentangled representation $\mathbf{F}_{\rm D}$ and lower value of **d** obtained from $\mathbf{F}_{\rm D}$. We observe that visualizing disentangled features adds reasoning to the decision made by DSVAE.

Some of the previous methods proposed for disentanglement representation learning have argued that it is important to verify that feature vectors \mathbf{F}_{G} and \mathbf{F}_{D} do not overlap and are different to ensure robust disentangled representation learning [25], [27]. This ensures that learned disentangled representation are different from general speech representation. In Fig. 6, we show that feature vectors \mathbf{F}_{G} and \mathbf{F}_{D} do not overlap and are different.

C. Comparison with Existing Methods

In this experiment, we compare the performance of our method with 16 other methods for synthetic speech detection. The proposed Disentangled Spectrogram Variational Auto Encoder (DSVAE) uses spectrogram to detect synthetic speech. Therefore, for comparison, we only include methods that either use spectrogram or features obtained from spectrogram or are proposed in ASVspoof2019 Challenge as baselines [32]. The methods proposed in the ASVspoof2019 Challenge as baselines [32] are methods B01 and B02 [32]. Both of these methods use Gaussian Mixture Model (GMM) for processing hand-crafted features such as LFCCs, and CQCCs. The remaining 14 methods (S01 to S14) that we use for comparison either process spectrogram or features obtained from spectrogram using different neural networks.

We can obtain spectrogram by processing time domain signal using either Short Time Fourier Transform (STFT)



Fig. 7: Visualization of input spectrogram: \mathbf{X} , reconstructed spectrogram: \mathbf{X} , and activated region: \mathbf{X}_{map} .

or using CQT. In Table I, Spectrogram denotes the one obtained using STFT and Spectrogram_{CQT} denotes the one obtained using CQT. S05 uses Spectrogram_{CQOST} and S06uses Spectrogram_{ICQCC} [67]. These features are obtained by using octave sub-banding and applying Discrete Cosine Transform (DCT) to either Spectrogram_{COT} or inverted Spectrogram_{CQT}. S02 [68] and S14 [69] map the spectrogram obtained using STFT to logarithmic and mel scale, respectively. S01 [19] uses VGG and S02 [68] uses Inception neural network to process features [70]. Method S03 [40] process Spectrogram using a CNN. S04 [19] uses fusion of two features, namely, Spectrogram and CQT [37] to detect synthetic speech (refer as Spectrogram+CQT in Table I). S05 and S06 [67] use Deep Neural Network (DNN) to process Spectrogram_{COOST} and Spectrogram_{ICOCC} feature, respectively. There are several version of method S02, and S07 to S13. Each version is trained on a different feature derived from spectrogram (e.g., Spectrogram_{CQT} and Log-Spectrogram). In our comparison, we report the EER of the best performing version. More details about methods S02, S07 to S13 and their different versions can be found in proposed several transformer neural [68]. Bartusiak *et al.* networks to process Mel-Spectrogram and detect synthetic speech in [69]. Method S14 is the best individual performing transformer neural network in [69]. Similar to DSVAE, S14 also processes Mel-Spectrogram. S14 is first trained using self-supervision on a large audio dataset *i.e.*, Audioset [61]. For inferencing, it uses 85.3M parameters, almost twice the number of parameters used by DSVAE.

Table I summarizes our results. We can notice that S14 with Patchout faSt Spectrogram Transformer (PaSST) [54] has better performance among all the comparison methods. DSVAE has better performance than all the 16 methods. DSVAE provides an improvement of more than 3 percentage points in EER from S14 which has twice the number of parameters. There is around 6 percentage points and 7 percentage

points improvement in EER from baseline methods B01 and B02, respectively. Overall the working principle of DSVAE is more understandable by visualizing the disentangled features and it has a significant improvement in EER than several existing methods such as S04.

D. Performance in practical scenarios

First, we investigate performance of DSVAE when synthetic speech is uploaded on social platforms. Different social platforms use different compression standards. For this evaluation we use around 534K speech signals from the evaluation part of the ASVspoof2021 DeepFake (DF) dataset [64]. It contains speech signals from the evaluation set of ASVspoof2019 dataset [32] and 2018 and 2020 Voice Conversion Challenge (VCC) datasets [71], [72]. Speech signals consist of uncompressed, single compressed and double compressed speech signals. Single compression is done using MP3, AAC, and OGG compression standards [73]-[75] at both high and low variable bit rate. Double compression is done from two standards MP3 and OGG at low variable bit rate to AAC standard at high variable bit rate. Yadav et al. showed that detectors with EER less than 5% on uncompressed speech have almost random accuracy (EER 50%) when tested on compressed speech [76]. DSVAE has detection accuracy of 92.25% with an EER of 32.28% on the evaluated dataset with compressed speech and hence DSVAE can detect synthetic speech uploaded to different social platforms.

Some existing methods trained on ASVspoof2019 have been shown to use silence region for detecting synthetic speech [77]. A simple attack such as removing silence can lead to failure and random performance of such detectors. Therefore, secondly, we investigate the performance of DSVAE when non speech elements *i.e.*, silence regions are removed from each speech signal. For this we use the hidden part of the ASVspoof2021 DeepFake (DF) dataset [64]. It consists of 18.5K speech signal randomly selected from evaluation set of ASVspoof2019 [58] and 2018 and 2020 Voice Conversion Challenge (VCC) datasets [71], [72]. DSVAE has detection accuracy of 84.09% on hidden part with an EER of 38.28%. Hence, DSVAE is robust to simple attacks such as removing silence.

E. Reconstructed Spectrograms and Attention

We randomly select 7 speech signals from the evaluation set of the ASVspoof2019 dataset. In Fig. 7, we show their spectrograms **X**, the spectrograms reconstructed by D_{rec} using feature vector **F**, and the spectrogram attention maps \mathbf{X}_{map} obtained by doing a dot product of \mathbf{A}_{map} with the input spectrogram **X**. The \mathbf{X}_{map} highlights the regions of the spectrogram that contributed to the decision made by DSVAE. We can observe that the reconstructed spectrograms $\hat{\mathbf{X}}$ do not capture all the fine details of the original input spectrograms **X**. They rather identify the regions and frequency bins that are more energetic. From the observation of \mathbf{X}_{map} we can see that the detector tends to take its decisions based on mainly energetic frequency bands. These most likely contain information related to the speech being bona fide or synthetic.

VI. CONCLUSIONS AND FUTURE WORK

In this paper we propose Disentangled Spectrogram Variational Auto Encoder (DSVAE) that uses disentangled representation learning to detect synthetic speech. Visualizing disentangled features and activation map helps to understand the working of the detector. DSVAE showed high performance compared to several existing approaches on ASVspoof2019 dataset. In future work, we plan to replace the used variational autoencoder with a transformer neural network, as in several existing works these networks have shown better performance than variational autoencoder to learn general speech representations. We also plan to evaluate DSVAE on detecting noisy synthetic speech signals. Lastly, currently we create unsupervised activation map, we plan to investigate supervised learning for synthetic speech localization.

ACKNOWLEDGMENTS

This material is based on research sponsored by the Defense Advanced Research Projects Agency (DARPA) and the Air Force Research Laboratory (AFRL) under agreement number FA8750-20-2-1004. The U.S. Government is authorized to reproduce and distribute reprints for Governmental purposes notwithstanding any copyright notation thereon. The views and conclusions contained herein are those of the authors and should not be interpreted as necessarily representing the official policies or endorsements, either expressed or implied, of DARPA, AFRL or the U.S. Government. Address all correspondence to Edward J. Delp, ace@purdue.edu.

REFERENCES

- D. H. Klatt, "Review of Text-to-Speech Conversion for English," *The Journal of the Acoustical Society of America*, vol. 82, no. 3, p. 737–793, May 1987.
- [2] M. Zakariah, M. K. Khan, and H. Malik, "Digital Multimedia Audio Forensics: Past, Present and Future," *Multimedia Tools and Applications*, vol. 77, no. 1, pp. 1009–1040, January 2017.

- [3] K. Bhagtani, A. K. S. Yadav, E. R. Bartusiak, Z. Xiang, R. Shao, S. Baireddy, and E. J. Delp, "An Overview of Recent Work in Multimedia Forensics," *Proceedings of the IEEE Conference on Multimedia Information Processing and Retrieval*, pp. 324–329, August 2022, Virtual.
- [4] J. Kim, J. Kong, and J. Son, "Conditional Variational Autoencoder with Adversarial Learning for End-to-End Text-to-Speech," *Proceedings* of the International Conference on Machine Learning, vol. 139, pp. 5530–5540, July 2021, Virtual. [Online]. Available: https: //proceedings.mlr.press/v139/kim21f.html
- [5] Y. Ren, C. Hu, X. Tan, T. Qin, S. Zhao, Z. Zhao, and T.-Y. Liu, "FastSpeech 2: Fast and High-Quality End-to-End Text to Speech," *Proceedings of the International Conference on Learning Representations*, pp. 1–15, May 2021, Virtual. [Online]. Available: https://openreview.net/forum?id=piLPYqxtWuA
- [6] V. Popov, I. Vovk, V. Gogoryan, T. Sadekova, and M. Kudinov, "Grad-TTS: A Diffusion Probabilistic Model for Text-to-Speech," *Proceedings of the International Conference on Machine Learning*, vol. 139, pp. 8599–8608, July 2021, Virtual. [Online]. Available: http://proceedings.mlr.press/v139/popov21a/popov21a.pdf
- [7] WellSaid Labs, Inc. 2022, "WELLSAID: AI Voice Over for Commercials," 2022. [Online]. Available: https://wellsaidlabs.com/aivoice-over
- [8] C. Wang, S. Chen, Y. Wu, Z. Zhang, L. Zhou, S. Liu, Z. Chen, Y. Liu, H. Wang, J. Li, L. He, S. Zhao, and F. Wei, "Neural Codec Language Models are Zero-Shot Text to Speech Synthesizers," *arXiv preprint* arXiv:2301.02111, January 2023.
- [9] Y. Gao, R. Singh, and B. Raj, "Voice Impersonation Using Generative Adversarial Networks," *Proceedings of the IEEE International Conference on Acoustics, Speech and Signal Processing*, pp. 2506–2510, April 2018, Calgary, Canada.
- [10] M. B. Hoy, "Alexa, Siri, Cortana, and More: An Introduction to Voice Assistants," *Medical Reference Services Quarterly*, vol. 37, no. 1, pp. 81–88, 2018.
- [11] Microsoft, "Your personal productivity assistant in Microsoft 365," *Microsoft.com*, 2021, https://www.microsoft.com/en-us/cortana.
- [12] BBC News Services, "Star Wars: James Earl Jones steps back from Darth Vader role," 2022. [Online]. Available: https://www.bbc.com/ news/entertainment-arts-63032248
- [13] B. Allyn, "Deepfake Video of Zelenskyy Could be 'Tip of the Iceberg' in Info War, Experts Warn," https://www.npr.org/2022/03/16/1087062648/ deepfake-video-zelenskyy-experts-war-manipulation-ukraine-russia, March 2022.
- [14] B. Smith, "Goldman Sachs, Ozy Media and a \$40 Million Conference Call Gone Wrong," *The New York Times*, September 2021. [Online]. Available: https://www.nytimes.com/2021/09/26/business/ media/ozy-media-goldman-sachs.html
- [15] G. Hua, A. B. J. Teoh, and H. Zhang, "Towards End-to-End Synthetic Speech Detection," *IEEE Signal Processing Letters*, vol. 28, pp. 1265– 1269, June 2021.
- [16] J. Yang, R. K. Das, and H. Li, "Significance of Subband Features for Synthetic Speech Detection," *IEEE Transactions on Information Forensics and Security*, vol. 15, pp. 2160–2170, November 2020.
- [17] R. K. Das, J. Yang, and H. Li, "Long Range Acoustic and Deep Features Perspective on ASVspoof 2019," *Proceedings of the IEEE Automatic Speech Recognition and Understanding Workshop*, pp. 1018– 1025, December 2019, Singapore.
- [18] C.-I. Lai, N. Chen, J. Villalba, and N. Dehak, "Assert: Anti-spoofing with squeeze-excitation and residual networks," *Proceedings of the Interspeech*, September 2019, Graz, Austria.
- [19] H. Zeinali, T. Stafylakis, G. Athanasopoulou, J. Rohdin, I. Gkinis, L. Burget, and J. Černocký, "Detecting Spoofing Attacks Using VGG and SincNet: BUT-Omilia Submission to ASVspoof 2019 Challenge," *Proceedings of the Interspeech*, pp. 1073–1077, September 2019, Graz, Austria.
- [20] G. Lavrentyeva, S. Novoselov, A. Tseren, M. Volkova, A. Gorlanov, and A. Kozlov, "Stc antispoofing systems for the asvspoof2019 challenge," *Proceedings of the Interspeech*, pp. 1033–1037, September 2019, Graz, Austria.
- [21] X. Li, N. Li, C. Weng, X. Liu, D. Su, D. Yu, and H. Meng, "Replay and Synthetic Speech Detection with Res2Net Architecture," *Proceedings* of the IEEE International Conference on Acoustics, Speech and Signal Processing, pp. 6354–6358, June 2021, Toronto, Canada.

- [22] V. Vishwarupe, P. M. Joshi, N. Mathias, S. Maheshwari, S. Mhaisalkar, and V. Pawar, "Explainable ai and interpretable machine learning: A case study in perspective," *Procedia Computer Science*, vol. 204, pp. 869–876, 2022.
- [23] K. Do and T. Tran, "Theory and evaluation metrics for learning disentangled representations," arXiv preprint arXiv:1908.09961, 2019.
- [24] X. Zhu, C. Xu, and D. Tao, "Where and What? Examining Interpretable Disentangled Representations," *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5861–5870, June 2021, Nashville, Tennessee.
- [25] Y.-C. Wang, C.-Y. Wang, and S.-H. Lai, "Disentangled Representation with Dual-stage Feature Learning for Face Anti-spoofing," *Proceedings* of the IEEE/CVF Winter Conference on Applications of Computer Vision, pp. 1234–1243, January 2022, Waikoloa, Hawaii.
- [26] K.-Y. Zhang, T. Yao, J. Zhang, Y. Tai, S. Ding, J. Li, F. Huang, H. Song, and L. Ma, "Face Anti-Spoofing via Disentangled Representation Learning," *Proceedings of the European Conference on Computer Vision*, pp. 641–657, August 2020, Glasgow, United Kingdom.
- [27] Y. Liu, J. Stehouwer, and X. Liu, "On Disentangling Spoof Trace for Generic Face Anti-spoofing," *Proceedings of the European Conference* on Computer Vision, pp. 406–422, August 2020, Glasgow, United Kingdom.
- [28] S. Tang, X. Zhou, X. He, and Y. Ma, "Disentangled Representation Learning for Controllable Image Synthesis: An Information-Theoretic Perspective," *Proceedings of the International Conference on Pattern Recognition*, pp. 10042–10049, January 2021, Milan, Italy.
- [29] Y.-J. Zhang, S. Pan, L. He, and Z.-H. Ling, "Learning Latent Representations for Style Control and Transfer in End-to-end Speech Synthesis," *Proceedings of the IEEE International Conference on Acoustics, Speech* and Signal Processing, pp. 6945–6949, May 2019, Brighton.
- [30] R. Aloufi, H. Haddadi, and D. Boyle, "Privacy-Preserving Voice Analysis via Disentangled Representations," *Proceedings of the ACM SIGSAC Conference on Cloud Computing Security Workshop*, p. 1–14, 2020, Virtual Event, USA.
- [31] G. Sun, Y. Zhang, R. J. Weiss, Y. Cao, H. Zen, and Y. Wu, "Fully-Hierarchical Fine-Grained Prosody Modeling For Interpretable Speech Synthesis," *Proceedings of the IEEE International Conference on Acoustics, Speech and Signal Processing*, pp. 6264–6268, May 2020, Barcelona.
- [32] M. Todisco, X. Wang, V. Vestman, M. Sahidullah, H. Delgado, A. Nautsch, J. Yamagishi, N. Evans, T. Kinnunen, and K. A. Lee, "ASVspoof 2019: Future Horizons in Spoofed and Fake Audio Detection," *Proceedings of the Interspeech*, pp. 1008–1012, September 2019, Graz, Austria.
- [33] M. Todisco, H. Delgado, and N. Evans, "Constant Q Cepstral Coefficients: A Spoofing Countermeasure for Automatic Speaker Verification," *Computer Speech & Language*, vol. 45, pp. 516–535, September 2017.
- [34] M. Sahidullah and G. Saha, "Design, Analysis, and Experimental Evaluation of Block Based Transformation in MFCC Computation for Speaker Recognition," *Speech Communication*, vol. 54, pp. 543–565, May 2012.
- [35] E. A. AlBadawy, S. Lyu, and H. Farid, "Detecting AI-Synthesized Speech Using Bispectral Analysis," *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition workshops*, pp. 104–109, June 2019, Long Beach, CA.
- [36] K. He, X. Zhang, S. Ren, and J. Sun, "Deep Residual Learning for Image Recognition," *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 770–778, June 2016, Las Vegas, NV.
- [37] L. Rabiner and R. Schafer, *Theory and Applications of Digital Speech Processing*, 1st ed. USA: Prentice Hall Press, 2010.
- [38] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Łukasz Kaiser, and I. Polosukhin, "Attention is All You Need," *Proceedings of the Neural Information Processing Systems*, December 2017, Long Beach, CA. [Online]. Available: https://proceedings.neurips.cc/ paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf
- [39] A. K. S. Yadav, E. Bartusiak, K. Bhagtani, and E. J. Delp, "Synthetic Speech Attribution using Self Supervised Audio Spectrogram Transformer," *Proceedings of the IS&T Media Watermarking, Security, and Forensics Conference, Electronic Imaging Symposium*, January 2023, san Francisco, CA.
- [40] T. Nosek, S. Suzić, B. Papić, and N. Jakovljević, "Synthesized Speech Detection Based on Spectrogram and Convolutional Neural Networks,"

Proceedings of the IEEE Telecommunications Forum, pp. 1–4, November 2019, Belgrade, Serbia.

- [41] Z. Zhang, X. Yi, and X. Zhao, "Fake Speech Detection Using Residual Network with Transformer Encoder," *Proceedings of the ACM Workshop* on *Information Hiding and Multimedia Security*, p. 13–22, June 2021, virtual Event, Belgium.
- [42] S. Borzì, O. Giudice, F. Stanco, and D. Allegra, "Is synthetic voice detection research going into the right direction?" *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pp. 71–80, June 2022, new Orleans, LA.
- [43] H. Tak, J. Patino, A. Nautsch, N. Evans, and M. Todisco, "An explainability study of the constant Q cepstral coefficient spoofing countermeasure for automatic speaker verification," *Proceedings of the Speaker and Language Recognition Workshop*, pp. 333–340, November 2020, Tokyo, Japan.
- [44] B. Chettri, S. Mishra, B. L. Sturm, and E. Benetos, "Analysing the predictions of a cnn-based replay spoofing detection system," *Proceedings of the IEEE Spoken Language Technology Workshop*, pp. 92–97, December 2018, Athens, Greece.
- [45] S.-Y. Lim, D.-K. Chae, and S.-C. Lee, "Detecting Deepfake Voice Using Explainable Deep Learning Techniques," *Applied Sciences*, vol. 12, no. 8, 2022.
- [46] W. Ge, J. Patino, M. Todisco, and N. Evans, "Explaining Deep Learning Models for Spoofing and Deepfake Detection with Shapley Additive Explanations," *Proceedings of the IEEE International Conference on Acoustics, Speech and Signal Processing*, pp. 6387–6391, May 2022, Singapore.
- [47] B. Halpern, F. Kelly, R. van Son, and A. Alexander, "Residual Networks for Resisting Noise: Analysis of an Embeddings-based Spoofing Countermeasure," *Proceedings of the Speaker and Language Recognition Workshop*, pp. 326–332, November 2020, Tokyo, Japan.
- [48] S. M. Lundberg and S.-I. Lee, "A Unified Approach to Interpreting Model Predictions," *Proceedings of the Advances in Neural Information Processing Systems*, vol. 30, December 2017, Long Beach, CA. [Online]. Available: https://proceedings.neurips.cc/paper/ 2017/file/8a20a8621978632d76c43dfd28b67767-Paper.pdf
- [49] M. T. Ribeiro, S. Singh, and C. Guestrin, ""Why Should I Trust You?": Explaining the Predictions of Any Classifier," *Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, p. 1135–1144, August 2016, San Francisco, CA.
- [50] Y. Li, K. K. Singh, U. Ojha, and Y. J. Lee, "MixNMatch: Multifactor Disentanglement and Encoding for Conditional Image Generation," *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8036–8045, June 2020, Virtual.
- [51] M. Luong and V. A. Tran, "Many-to-many voice conversion based feature disentanglement using variational autoencoder," *Proceedings of the Interspeech*, pp. 851–855, August 2021, Brno, Czech Republic.
- [52] P. Champion, D. Jouvet, and A. Larcher, "Are disentangled representations all you need to build speaker anonymization systems?" *Proceedings* of the Interspeech, pp. 2793–2797, September 2022, Incheon, Korea.
- [53] D. P. Kingma and M. Welling, "Auto-encoding variational bayes," arXiv preprint arXiv:1312.6114, 2013.
- [54] K. Koutini, J. Schlüter, H. Eghbal-zadeh, and G. Widmer, "Efficient Training of Audio Transformers with Patchout," *Proceedings of Interspeech*, pp. 2753–2757, September 2022, Incheon, Korea.
- [55] D. Niizumi, D. Takeuchi, Y. Ohishi, N. Harada, and K. Kashino, "Masked Spectrogram Modeling using Masked Autoencoders for Learning General-purpose Audio Representation," *Proceedings of Machine Learning Research*, vol. 166, pp. 1–24, Dec 2022. [Online]. Available: https://proceedings.mlr.press/v166/niizumi22a/niizumi22a.pdf
- [56] S. S. Stevens, J. Volkmann, and E. B. Newman, "A Scale for the Measurement of the Psychological Magnitude Pitch," *Journal of the Acoustical Society of America*, vol. 8, pp. 185–190, June 1937.
- [57] H. Wang, Y. Wang, Z. Zhou, X. Ji, D. Gong, J. Zhou, Z. Li, and W. Liu, "CosFace: Large Margin Cosine Loss for Deep Face Recognition," *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5265–5274, June 2018, Salt Lake City, Utah.
- [58] J. Yamagishi, M. Todisco, M. Sahidullah, H. Delgado, X. Wang, N. Evans, T. Kinnunen, K. Lee, V. Vestman, and A. Nautsch, "ASVspoof 2019: The 3rd Automatic Speaker Verification Spoofing and Countermeasures Challenge database," *University of Edinburgh. The Centre for Speech Technology Research*, March 2019. [Online]. Available: https://www.asvspoof.org/index2019.html

- [59] Josh Coalson, Xiph.Org Foundation, "FLAC: Free Lossless Audio Codec," https://xiph.org/flac/format.html, 2000.
- [60] A. Tharwat, "Classification Assessment Methods," Applied Computing and Informatics, vol. 17, no. 1, pp. 168–192, December 2021.
- [61] J. F. Gemmeke, D. P. Ellis, D. Freedman, A. Jansen, W. Lawrence, R. C. Moore, M. Plakal, and M. Ritter, "Audio set: An Ontology and Human-labeled Dataset for Audio Events," *Proceedings of the IEEE International Conference on Acoustics, Speech and Signal Processing*, March 2017, New Orleans, LA.
- [62] D. Kingma and J. Ba, "Adam: A Method for Stochastic Optimization," Proceedings of the International Conference for Learning Representations, May 2015, San Diego, CA.
- [63] I. Loshchilov and F. Hutter, "Decoupled Weight Decay Regularization," Proceedings of the International Conference on Learning Representations, May 2019, New Orleans, LA.
- [64] X. Liu, X. Wang, M. Sahidullah, J. Patino, H. Delgado, T. Kinnunen, M. Todisco, J. Yamagishi, N. Evans, A. Nautsch *et al.*, "Asvspoof 2021: Towards spoofed and deepfake speech detection in the wild," *arXiv* preprint, 2022.
- [65] L. van der Maaten and G. Hinton, "Visualizing High-Dimensional Data Using t-SNE," *Journal of Machine Learning Research*, vol. 9, pp. 2579–2605, November 2008. [Online]. Available: https://www.jmlr.org/ papers/v9/vandermaaten08a.html
- [66] P. C. Mahalanobis, "On the generalized distance in statistics," *Proceedings of the National Institute of Sciences (Calcutta)*, vol. 2, pp. 49–55, 1936. [Online]. Available: https://www.bibsonomy.org/bibtex/ 2aef303a4aba53e4fcd7b0e58f7c205b6/thoni
- [67] J. Yang, R. K. Das, and H. Li, "Significance of Subband Features for Synthetic Speech Detection," *IEEE Transactions on Information Forensics and Security*, vol. 15, pp. 2160–2170, November 2020.
- [68] N. M. Müller, P. Czempin, F. Dieckmann, A. Froghyar, and K. Böttinger, "Does audio deepfake detection generalize?" *Proceedings of the Inter-speech*, September 2022, Incheon, Korea.
- [69] E. R. Bartusiak, "Machine Learning for Speech Forensics and Hyper-

sonic Vehicle Applications," Ph.D. dissertation, Purdue University, West Lafayette, IN, June 2022.

- [70] K. Simonyan and A. Zisserman, "Very Deep Convolutional Networks for Large-Scale Image Recognition," arXiv preprint arXiv:1409.1556, 2014.
- [71] J. Lorenzo-Trueba, J. Yamagishi, T. Toda, D. Saito, F. Villavicencio, T. Kinnunen, and Z. Ling, "The voice conversion challenge 2018: Promoting development of parallel and nonparallel methods," *Proceedings* of the Speaker and Language Recognition Workshop, pp. 195–202, June 2018, Les Sables d'Olonne, France.
- [72] Z. Yi, W.-C. Huang, X. Tian, J. Yamagishi, R. K. Das, T. Kinnunen, Z.-H. Ling, and T. Toda, "Voice Conversion Challenge 2020 – Intralingual semi-parallel and cross-lingual voice conversion," *Proceedings* of the Joint Workshop for the Blizzard Challenge and Voice Conversion Challenge 2020, pp. 80–98, october 2020, Shanghai, China.
- [73] J. Herre and H. Purnhagen, "General Audio Coding," in *The MPEG-4 Book*, F. C. Pereira and T. Ebrahimi, Eds. Upper Saddle River, NJ, USA: Prentice Hall PTR, 2002, pp. 487–544.
- [74] International Organization for Standardization/International Electrotechnical Commission, "ISO/IEC 13818-3:1995 Information technology - Generic Coding of Moving Pictures and Associated Audio Information - Part 3: Audio," 1995. [Online]. Available: https://www.iso.org/standard/22991.html
- [75] —, "ISO/IEC 13818-7:1997 Information technology Generic Coding of Moving Pictures and Associated Audio Information -Part 7: Advanced Audio Coding (AAC)," 1997. [Online]. Available: https://www.iso.org/standard/25040.html
- [76] A. K. Singh Yadav, Z. Xiang, E. R. Bartusiak, P. Bestagini, S. Tubaro, and E. J. Delp, "ASSD: Synthetic Speech Detection in the AAC Compressed Domain," *Proceedings of the IEEE International Conference on Acoustics, Speech, and Signal Processing*, pp. 1–5, June 2023.
- [77] N. M. Müller, F. Dieckmann, P. Czempin, R. Canals, K. Böttinger, and J. Williams, "Speech is silver, silence is golden: What do asvspooftrained models really learn?" arXiv preprint, 2021.