Solving Tensor Low Cycle Rank Approximation

Yichuan Deng^{*} Yeqi Gao[†] Zhao Song[‡]

Abstract

Large language models have become ubiquitous in modern life, finding applications in various domains such as natural language processing, language translation, and speech recognition. Recently, a breakthrough work [Zhao, Panigrahi, Ge, and Arora Arxiv 2023] explains the attention model from probabilistic context-free grammar (PCFG). One of the central computation task for computing probability in PCFG is formulating a particular tensor low rank approximation problem, we can call it tensor cycle rank. Given an $n \times n \times n$ third order tensor A, we say that A has cycle rank-k if there exists three $n \times k^2$ size matrices U, V, and W such that for each entry in each

$$A_{a,b,c} = \sum_{i=1}^{k} \sum_{j=1}^{k} \sum_{l=1}^{k} U_{a,i+k(j-1)} \otimes V_{b,j+k(l-1)} \otimes W_{c,l+k(i-1)}$$

for all $a \in [n], b \in [n], c \in [n]$. For the tensor classical rank, tucker rank and train rank, it has been well studied in [Song, Woodruff, Zhong SODA 2019]. In this paper, we generalize the previous "rotation and sketch" technique in page 186 of [Song, Woodruff, Zhong SODA 2019] and show an input sparsity time algorithm for cycle rank.

^{*}ycdeng@cs.washington.edu. The University of Washington.

 $^{^{\}dagger}a9167552260 \texttt{gmail.com}.$ The University of Washington.

[‡]zsong@adobe.com. Adobe Research.

1 Introduction

Large Language Models (LLMs) are a type of artificial intelligence model that is designed to process and understand human language. These models are built using deep learning techniques and can be trained on massive amounts of data, allowing them to learn patterns and relationships in language that enable them to generate text, answer questions and complete other tasks that are related to language. Some of the most well-known LLMs include OPT [ZRG⁺22], PaLM [CND⁺22], GPT-3 [BMR⁺20], Transformer [VSP⁺17] and BERT [DCLT18], which have been used for a wide range of applications such as language translation [Sta20, FBS⁺21, LGG⁺20], and content generation [VSP⁺17, DCLT18, BMR⁺20, CND⁺22]. Large language models are becoming increasingly sophisticated and powerful, and are expected to play a major role in shaping the future of human-computer interaction and natural language processing [WDS⁺19, RPSW19, QSX⁺20, LYF⁺23].

As one of the large language models, the Transformer [VSP⁺17] has drawn the most attention in recent years. Recently, a beautiful and breakthrough work by Zhao, Panigrahi, Ge and Arora [ZPGA23] explore an interesting problem regarding whether the Transformer is capable of true parsing while attempting masked word prediction.

For solving the problem above, they first focus a Probabilistic Context-Free Grammar (PCFG) [Yng60] and parsing algorithm based on it. As a type of formal grammar, Probabilistic Context-Free Grammar (PCFG) is widely used in natural language processing [WDS⁺19, QSX⁺20] and computational linguistics [Mit22, BDS19]. With \mathcal{N} as the set of all the non-terminal symbols of the language grammar, $\mathcal{P} \subset \mathcal{N}$ as the set of pre-terminals, $\mathcal{I} \subset \mathcal{N}$ as the finite set of in-terminals and [n] as the set of all possible words and p is the relating probability for grammar parsing, a 5-tuple $\mathcal{G} := (\mathcal{N}, \mathcal{P}, \mathcal{I}, p, n)$ defines it.

In a PCFG, every grammar rule of the language is defined to be connected with a probability that represents how likely it is to be used in generating a sentence. These probabilities can be learned from a large corpus of text data using machine learning techniques such as the expectation-maximization algorithm. PCFGs have been widely used in various applications of natural language processing, including part-of-speech tagging [Chu89, TKMS03, Rat96], syntactic parsing [Cha96, KM03, PK07], and text generation [LK98].

A well-known approach for discovering the (unlabeled) parse tree of a sentence w using the PCFG model is the Labelled-Recall algorithm, which was introduced by [Goo96]. The algorithm aims to identify the tree T = (i, j) that maximizes the sum of scores, where the score of a span $v_i v_{i+1} \cdots v_j$ under a non-terminal a is defined as the marginal probability $\mu(i, j, a)$ calculated as follows: $\mu(i, j, a) = \max_{a \in \mathcal{N}} \Pr[a \to v_i v_{i+1} \cdots v_j, \operatorname{root} \to w | \mathcal{G}]$.

The marginal probabilities mentioned above can be computed using the Inside-Outside algorithm [MS99, Bak79]. In a recent study, [ZPGA23] attempted to explain the Transformer architecture from the perspective of Probabilistic Context-Free Grammar (PCFG) [MSM93].

With the aid of dynamic programming, the Inside-Outside algorithm can determine two types of probability terms. The inside type of probability is defined as

$$p_{\rm in}(i,j,a) := \Pr[a \to v_i v_{i+1} \dots v_j | \mathcal{G}]$$

while the outside type of probability is defined as

$$p_{\text{out}}(i, j, a) = \Pr[\mathsf{root} \to v_1 v_2 \dots v_{i-1} a v_{j+1} \dots v_L | \mathcal{G}]$$

for all ordered pairs (i, j) where $1 \le i \le j \le L$ and $a \in \mathcal{N}$. To be precise, the probabilities can be

defined with the following recursive form,

$$p_{\rm in}(i, j, a) = \sum_{b, c} \sum_{k=i}^{j-1} p_{\rm in}(i, k, b) p_{\rm in}(k+1, j, c) \Pr[a \to bc]$$

and

$$p_{\text{out}}(i, j, a) = \sum_{b, c} \sum_{k=1}^{i-1} p_{\text{in}}(k, i-1, c) p_{\text{out}}(k, j, b) \Pr[b \to ca] + \sum_{b, c} \sum_{k=j+1}^{L} p_{\text{in}}(j+1, k, c) p_{\text{out}}(i, k, b) \Pr[b \to ac]$$

given that for all $a, i, p_{in}(i, i, a) = \Pr[a \rightarrow v_i]$ and for all $a, p_{out}(1, L, root) = 1$. We can obtain the marginal probabilities using the following expressions

$$\mu(i, j, a) = \Pr[a \Rightarrow v_i v_{i+1} \dots v_j, \operatorname{root} \Rightarrow w | \mathcal{G}]$$

= $\Pr[\operatorname{root} \rightarrow v_1 v_2 \dots v_{i-1} a v_{j+1} \dots v_L | \mathcal{G}] \cdot \Pr[a \rightarrow v_i v_{i+1} \dots v_j | \mathcal{G}]$
= $p_{\operatorname{in}}(i, j, a) \cdot p_{\operatorname{out}}(i, j, a).$

In our paper, we will focus on the analysis of $p_{in}(i, j, a)$ and investigate $p_{in}(i, j, b)$, $p_{in}(k+1, j, c)$ and $\Pr[a \to bc]$ from a tensor perspective. By treating b, c, k as the cycle index and a, i, j as the tensor index transformed from $p_{in}(i, j, a)$, we can restructure the function in a new format. Drawing inspiration from the computation of $p_{in}(i, j, a)$, we define the cycle rank of a tensor for low-rank approximation as follows.

Definition 1.1 (Tensor Cycle-rank). Considering \overline{U} , \overline{V} , and \overline{W} , which are n-by-k-by-k tensors with real-valued entries, are the tensorizations of matrices $U \in \mathbb{R}^{n \times k^2}$, $V \in \mathbb{R}^{n \times k^2}$, and $W \in \mathbb{R}^{n \times k^2}$, we say a has cycle-rank provided that matrices U, V, and W belong to $\mathbb{R}^{n \times k^2}$ satisfying the following condition:

$$A_{i,j,l} = \sum_{a=1}^{k} \sum_{b=1}^{k} \sum_{c=1}^{k} U_{i,a+k(b-1)} V_{j,b+k(c-1)} v_{l,c+k(a-1)}$$

Alternatively, we can state that

$$A_{i,j,l} = \sum_{a=1}^{k} \sum_{b=1}^{k} \sum_{c=1}^{k} \overline{U}_{i,a,b} \overline{V}_{j,b,c} \overline{W}_{l,c,a}$$

We remark that there are other tensor ranks such as classical tensor rank, tensor train rank, and tensor tucker rank. Those ranks have been studied by [SWZ19c], however tensor cycle rank is not studied. We provide more detailed definition of other tensor ranks in Section 4.2.

1.1 Our Result

We present our main result as follows:

Theorem 1.2 (Cycle rank, informal version of Theorem 5.1). For any $k \ge 1$, $\epsilon \in (0,1)$, and a third-order tensor $a \in \mathbb{R}^{n \times n \times n}$, there is an algorithm that operates in

$$O(\operatorname{nnz}(A)) + n \operatorname{poly}(k, 1/\epsilon) + \exp(O(\operatorname{poly}(k)/\epsilon))$$

time and produces U, V, and W which are tensors of dimension $n \times k \times k$ satisfying the following condition:

$$\|\sum_{i=1}^{k}\sum_{j=1}^{k}\sum_{l=1}^{k}U_{*,i,j}\otimes V_{*,j,l}\otimes v_{*,l,i} - A\|_{F} \le (1+\epsilon)\min_{\text{cycle rank}-k}\|A_{k} - A\|_{F}^{2}$$

Roadmap. We divide the paper as follows. In Section 2 we discuss some related work. In Section 3 we give the overview of our techniques. In Section 4 we provide preliminaries for our work. In Section 5 we give our formal result and analysis.

2 Related Work

2.1 Transformer Theory

Optimization and Convergence In the realm of optimization, [SZKS21] concentrated on investigating the behavior of a single-head attention mechanism to emulate the process of learning a Seq2Seq model, while adaptive methods have been emphasized for attention models by [ZKV⁺20]. [GMS23] have recently become interested in the over-parametrization problem associated with exponential activation functions. The exponential activation function is the focus of study in [GMS23], where the convergence of an over-parameterized two-layer neural network is examined. The authors determine the minimum number of neurons required for convergence. Furthermore, [LSZ23] have addressed the issue of regularized exponential regression and proposed an algorithm running in input sparsity time. [LLR23] provides a comprehensive explanation of how transformers learn "semantic structure", which is in regard to their proficiency in capturing word co-occurrence patterns.

Fast Attention Computation The work of [ZHDK23] and [AS23] primarily focus on the static version of attention computation. In particular, on the positive side, [AS23] provides an algorithm, and on the negative side, [AS23] prove a hardness by assuming (strong) exponential time hypothesis. [BSZ23] define and investigate the dynamic version of the problem, presenting both positive and negative results. The algorithmic result of [BSZ23] is built on lazy update techniques in solving linear programming [CLS19, Bra20]. The hardness result of [BSZ23] is built on Hinted MV conjecture [BNS19]. [DMS23] consider the case where feature dimension is much larger than the length of sentence in attention computation, and they provide both randomized algorithm and deterministic algorithm to sparsify the feature dimension.

Learning in-context In a recent work $[ASA^+22]$, it is shown that, in-context learners based on transformers can perform conventional learning algorithms in an implicit manner by encoding smaller models within their activations and continuously updating these models as new examples are presented within the context. Concentrating on the clearly defined task of training a model under in-context conditions to learn a class of functions, such as linear functions, [GTLV22] aim to gain a deeper insight into in-context learning. Their research aims to determine if a model, when provided with data derived from some functions within a class, are able to be trained to learn the "majority" of functions in this class. $[ONR^+22]$ gave an explanation of the mechanisms of Transformers as in-context learners. They showed that the training process of the Transformers in in-context tasks have similarity of some meta-learning formulations based on gradient descent. **Privacy.** Considering the potential negative influence of the abuse of the LLMs, [KGW⁺23] propose a method for watermarking proprietary language models without adversely affecting text quality. A novel algorithm for detecting watermarks in language models without requiring access to the model's parameters or API is introduced by [KGW⁺23].

2.2 Numerical Linear Algebra

Low-rank Approximation Many variants of low-rank approximation problems have been studied, for example low-rank approximation with Frobenious norm [CW13, NN13], matrix CUR decomposition [BW14, SWZ17, SWZ19c], weighted low rank approximation [RSW16], entrywise ℓ_1 norm low-rank approximation [SWZ17, SWZ19a], general norm column subset selection [SWZ19b], tensor low-rank approximation [SWZ19c], and tensor regression [DSSW18, DJS⁺19, RSZ22, SWYZ21]. Low-rank approximation also has many applications in other problems such as cutting plane method [JLSW20], integral minimization [JLSZ23], training neural network [BPSW21, SZ221, Zha22].

Input Sparsity Algorithms For several years, there have been many works focused on designing input-sparsity time algorithms [CW13, NN13, WZ16, BWZ16, RSW16, SWZ17, SWZ19c, SYYZ22, DSW22]. For the problems of matrix low-rank approximation and linear regression, [CW13] gave the first input sparsity time. With a sparse embedding matrix S, one can compute its product with any input matrix A in the input-sparsity nnz(A) time. Another work [NN13] later gave some sketching matrices called Oblivious Sparse Norm Approximating Projections (OSNAPs), which improve the former dimension of sketch in [CW13]. [RSW16] gives an input sparsity time algorithm for weighted low-rank approximation. [SWZ17] generalize the Frobenius low rank approximation problem [CW13, NN13] to entry-wise ℓ_1 low rank approximation problem. [SWZ19c] studied the tensor low rank approximation problem. Recently, [SYYZ22] gave an algorithm for structured John Ellipsoid computation. It improves the previous work [CCLY19] to input sparsity time. Another recent work [DSW22] gave a novel algorithm which can minimizing the discrepancy in input sparsity time.

3 Technique Overview

With $U^* \in \mathbb{R}^{n^2 \times k^2}$, $V^* \in \mathbb{R}^{n^2 \times k^2}$ and $W^* \in \mathbb{R}^{n^2 \times k^2}$, we can rewrite A_k as follows

$$A_k = \sum_{i=1}^k \sum_{j=1}^k \sum_{l=1}^k U_{i+k(j-1)}^* \otimes V_{j+k(l-1)}^* \otimes W_{l+k(i-1)}^*$$

The main idea in our proof is to first establish the existence of a matrix decomposition for A, and then use a corresponding algorithm to confidently locate the desired matrix.

Rotate and Sketch Step 1. In the first step, we consider the hypothetical regression problem $\min_{U \in \mathbb{R}^{n \times k^2}} ||A_1 - UZ_1||_F^2$. With $r = O(k^2/\epsilon)$ and $S_1 \in \mathbb{R}^{n^2 \times r}$ with i.i.d. normal random variables denoted N(0, 1/r), and $\hat{U} = \operatorname{argmin}_{U \in \mathbb{R}^{n \times k^2}} ||UZ_1S_1 - A_1S_1||_F^2$, we have

$$||A_1 - \widehat{U}Z_1||_F^2 \le (1+\epsilon) \min_{U \in \mathbb{R}^{n \times k^2}} ||A_1 - UZ_1||_F^2.$$

By choosing $\hat{U} = A_1 S_1 (Z_1 S_1)^{\dagger}$, we can prove that at least a matrix \hat{U} can be found to satisfy the equation above.

Rotate and Sketch Step 2. According to the first step, we can create a rank-k tensor, defined as follows

$$B := \sum_{i=1}^{k} \sum_{j=1}^{k} \sum_{l=1}^{k} \widehat{U}_{i+k(j-1)} \otimes V_{j+k(l-1)}^{*} \otimes W_{j+k(i-1)}^{*}$$

from the matrix $\widehat{U}Z_1$.

Since \widehat{U} is in the column span of A_1S_1 , the set of rank-1 tensors $\{(A_1S_1)_{a+k(b-1)} \otimes V_{b+k(c-1)}^* \otimes W_{c+k(a-1)}^*\}_{a \in [r], b, c \in [k]}$ spans the space that contains B. It is possible to express a proper rank-k tensor B as a linear combination of rank-1 tensors of the form $\{U_{a+k(b-1)}^* \otimes (A_2S_2)_{b+k(c-1)} \otimes W_{c+k(a-1)}^*\}_{a,c \in [k], b \in [r]}$ and the set of rank-1 tensors $\{U_{a+k(b-1)}^* \otimes V_{b+k(c-1)}^* \otimes (A_3S_3)_{c+k(a-1)}\}_{a,b \in [k],c \in [r]}$ spans a subspace that contains a proper rank-k tensor B.

We first compute A_1S_1 , and write $\widehat{U} = A_1S_1(Z_1S_1)^{\dagger}$. Now, we redefine Z_2 with respect to \widehat{U} , which implies that, the rows of Z_2 is vectors where the (j, l)-th row is $\operatorname{vec}(\sum_{i=1}^k \widehat{U}_{i+k(j-1)} \otimes W_{l+k(i-1)}^*)$ for each $j \in [k]$ and $l \in [k]$. And we consider the regression problem in the following form,

$$\min_{V} \|VZ_2 - A_2\|_F^2$$

If $S_2 \in \mathbb{R}^{n^2 \times r}$ as a matrix of i.i.d. Gaussian entries, we have $\widehat{V} = A_2 S_2 (Z_2 S_2)^{\dagger}$ satisfies

$$\|\widehat{V}Z_2 - A_2\|_F^2 \le (1+\epsilon)^2 \|A_k - A\|_F^2.$$

The matrix B can be obtained by retensorizing $\hat{V}Z_2$ and then we will have

$$||B - A||_F^2 = ||\widehat{V}Z_2 - A_2||_F^2 \le (1 + \epsilon)^2 ||A_k - A||_F^2.$$

Rotate and Sketch Step 3. Recall that, the columns of \hat{V} are all in the row span of A_2S_2 , and the rows of Z_2 are defined to be $\operatorname{vec}(\sum_{i=1}^k \widehat{U}_{i+k(j-1)} \otimes W^*_{l+k(i-1)})$ for each $j \in [k]$ and $l \in [k]$, where the columns of \widehat{U} are in the row span of the matrix A_1S_1 , we have that, B is in the span of the set of rank-1 tensors

$$\{(A_1S_1)_{a+k(b-1)} \otimes (A_2S_2)_{b+k(c-1)} \otimes \widehat{V}_{c+k(a-1)}\}_{a,b \in [r], c \in [k]}$$

Given that $Z_3 \in \mathbb{R}^{r^2 \times n^2}$ as an matrix with rows $\operatorname{vec}((A_1S_1)_{a+k(b-1)} \otimes (A_2S_2)_{b+k(c-1)})$ for all pairs $a, b \in [r]$, we will focus on the following regression problem

$$\min_{W} \|WZ_3 - A_3\|_F^2$$

By solving another regression problem, $W \in \mathbb{R}^{n \times r^2}$ can be solved in polynomial time. After retensorizing WZ_3 to a new tensor B, we can find a rank- $r^2 = O(k^2/\epsilon^2)$ tensor B such that

$$||B - A||_F^2 \le (1 + \epsilon)^2 ||A_k - A||_F^2 = (1 + O(\epsilon)) ||A_k - A||_F^2.$$

Input sparsity reduction. To obtain the input-sparsity running time guarantee of $n \operatorname{poly}(k/\epsilon) + \operatorname{nnz}(A)$ for Theorem 4.15, while we can replace S_1 and S_2 using a sparse CountSketch matrix together with a Gaussian matrix, which enables us to compute A_1S_1 and A_2S_2 in the desired $\operatorname{nnz}(A) + n \operatorname{poly}(k/\epsilon)$ time.

For the next steps of solving $\min_{W} ||A_3 - WZ_3||_F^2$ quickly and writing matrix Z_3 without spending r^2n^2 time, a technique of TensorSketch is used, which is introduced in [Pag13, PP13]. But as shown in [ANW14], we need show some stronger properties of approximate matrix product (AMP) and subspace embedding (SE) to make it stand. When the AMP and SE is satisfied, we can solve the "sketched version" regression problem, in the form of

$$\min_{W} \|A_3 S_3 - W Z_3 S_3\|_F^2.$$

The point of this sketch is, matrix products A_3S_3 and Z_3S_3 can be computed in the sparsity time of $nnz(A) + n \operatorname{poly}(k/\epsilon)$. Combining them together, we can solve the problem in $n \operatorname{poly}(k/\epsilon)$ time.

In order to get the sparsity time of A, we use CounSketch matrices to boost the algorithm. To be specific, we choose three CountSketch matrices T_1, T_2, T_3 with sketching dimension of $t = n \cdot \text{poly}(k, 1/\epsilon)$.

We define

$$D := \sum_{i=1}^{k} \sum_{j=1}^{k} \sum_{l=1}^{k} (T_1 A_1 S_1 X_1)_{a,i+k(j-1)} \cdot (T_2 A_2 S_2 X_2)_{b,j+k(l-1)} \cdot (T_3 A_3 S_3 X_3)_{c,l+k(i-1)}.$$

Applying them to the iterative argument described above, now we try to minimize the following target polynomial function

$$\sum_{a,b,c\in[t]} (D - (A(T_1, T_2, T_3))_{a,b,c})^2$$

by choosing $3rk = O(k^2/\epsilon)$ indeterminates X_1, X_2, X_3 .

Solving small problem via polynomial system solver. With X_1, X_2 , and X_3 as $r \times k^2$ matrices of indeterminates, we can re-express \hat{U} as $A_1S_1X_1$, \hat{V} as $A_2S_2X_2$, and \hat{W} as $A_3S_3X_3$. We let the rows of Z_1 be $\operatorname{vec}(V_{j+k(l-1)}^* \otimes W_{l+k(i-1)}^*)$, the rows of Z_2 be $\operatorname{vec}(\hat{U}_{i+k(j-1)} \otimes W_{j+k(l-1)}^*)$, and the rows of Z_3 be $\operatorname{vec}(\hat{U}_{i+k(j-1)} \otimes V_{i+k(l-1)})$.

It follows that the rank-k tensor

$$B = \sum_{i=1}^{k} \sum_{j=1}^{k} \sum_{l=1}^{k} (A_1 S_1 X_1)_{i+k(j-1)} \otimes (A_2 S_2 X_2)_{j+k(l-1)} \otimes (A_3 S_3 X_3)_{l+k(i-1)}$$

where $||A - B||_F^2 \le (1 + \epsilon)^3 ||A - A_k||_F^2$.

The minimization task can be achieved by minimizing the degree-6 polynomial as follows

$$\sum_{a,b,c\in[n]} \left(\sum_{i=1}^{k} \sum_{j=1}^{k} \sum_{l=1}^{k} (A_1 S_1 X_1)_{a,i+k(j-1)} \cdot (A_2 S_2 X_2)_{b,j+k(l-1)} \cdot (A_3 S_3 X_3)_{c,l+k(i-1)} - A_{a,b,c}\right)^2$$

by choosing $3rk = O(k^2/\epsilon)$ indeterminates X_1, X_2, X_3 . We can get X_1, X_2, X_3 such that the solution is at least $(1 + O(\epsilon))$ -approximate.

Assuming that the entries of matrices U^*, V^*, W^* are all bounded by $2^{\text{poly}(n)}$, as stated in Theorem 4.17, the polynomial can be minimized up to an additive error of $2^{-\text{poly}(n)}$ in poly(n)time [Ren92, BPR96]. Similar approaches can also be used to obtain a relative error approximation of the ground truth value of OPT, and to deal with situations where A_k does not exist.

4 Preliminary

In this section we give preliminaries for our work. In Section 4.1, we introduce our notations. In Section 4.2, we provide definitions for different kinds of tensor ranks. In Section 4.3, we introduce definitions about the tensor cycle ranks. In Section 4.4, we introduce definitions of subspace embedding and approximate matrix product. In Section 4.5 we introduce results about the sketching techniques. In Section 4.6, we introduce the tensor low-rank approximation algorithm. In Section 4.7, we introduce the technique for input-sparsity approximation. In Section 4.8 we introduce a previous result for solving small problems.

4.1 Notations

We use the notation [n] to denote the set $1, 2, \dots, n$ for any positive integer n. Additionally, for a vector $x \in \mathbb{R}^n$, $||x||_2$ represents its ℓ_2 norm, which is defined as $||x||_2 := (\sum_{i=1}^{n} \sum_{j=1}^{n} A_{i,j}^2)^{1/2}$. For a matrix $A \in \mathbb{R}^{n \times n}$, we use $||A||_F$ to denote its Frobenius norm, i.e., $||A||_F := (\sum_{i=1}^{n} \sum_{j=1}^{n} A_{i,j,l}^2)^{1/2}$. For a tensor A, we use $||A||_F$ to denote its Frobenius norm, i.e., $||A||_F := (\sum_{i=1}^{n} \sum_{j=1}^{n} A_{i,j,l}^2)^{1/2}$. For any tensor A, we use $||A||_F$ to denote the number of non-zero entries in tensor A.

For an invertible and square matrix A, we use A^{-1} to denote its true inverse.

Let the SVD of $A \in \mathbb{R}^{n \times k}$ to be $M \Sigma N^{\top}$ where $M \in \mathbb{R}^{n \times k}$ and $N \in \mathbb{R}^{k \times k}$ have orthonormal columns, and $\Sigma \in \mathbb{R}^{k \times k}$ is a diagonal matrix. We denote the Moore-Penrose pseudoinverse matrix A as $A^{\dagger} \in \mathbb{R}^{k \times n}$, i.e., $A^{\dagger} = N \Sigma^{-1} M^{\top}$.

We define the following two definitions of the \otimes product.

Definition 4.1 (\otimes product for vectors). *Given three vectors* $a, b, c \in \mathbb{R}^n$, $a \otimes b \otimes c$ *is used to denote* a size $n \times n \times n$ tensor where i, j, l-th entry is $a_i b_j c_l$.

Definition 4.2 (\otimes product for matrices). For *m* matrices $A_1 \in \mathbb{R}^{n_1 \times k}$, $A_2 \in \mathbb{R}^{n_2 \times k}$, \cdots , $A_m \in \mathbb{R}^{n_m \times k}$, we denote the tensor product in the following form

$$A_1 \otimes A_2 \otimes \cdots \otimes A_q = \sum_{i=1}^k (A_1)_i \otimes (A_2)_i \otimes \cdots \otimes (A_q)_i \in \mathbb{R}^{n_1 \times n_2 \times \cdots \times n_m},$$

where we use $(A_i)_i$ to denote the *i*-th column of the matrix A_i .

We define the following vec() operation of converting a tensor into a vector,

Definition 4.3 (vec(), converting a tensor to a vector). For any tensor $T \in \mathbb{R}^{n_1 \times n_2 \times \cdots \times n_q}$, we define

$$\operatorname{vec}(T) \in \mathbb{R}^{1 \times \prod_{i=1}^{q} n_i}$$

to be a row vector. For $t = (j_1 - 1) \prod_{i=2}^q n_i + (j_2 - 1) \prod_{i=3}^q n_i + \dots + (j_{q-1} - 1)n_q + j_q$, where $j_1 \in [n_1], j_2 \in [n_2] \dots, j_q \in [n_q]$, the t-th entry of vec(T) is T_{j_1, j_2, \dots, j_q} .

As an illustration, given that
$$u = \begin{bmatrix} 5\\4 \end{bmatrix}$$
, $v = \begin{bmatrix} 3\\2\\1 \end{bmatrix}$ then $\operatorname{vec}(u \otimes v) = \begin{bmatrix} 15 & 10 & 5 & 12 & 8 & 4 \end{bmatrix}$.

4.2 Tensor Ranks

In this section, we define the following kinds of ranks for tensor.

Definition 4.4 (Classical rank). We say tensor $U \in \mathbb{R}^{n \times n \times n}$ has a classical rank of k if $k \in \mathbb{Z}_{\geq 0}$ is the smallest positive integer for which there exist three matrices $A, B, C \in \mathbb{R}^{n \times k}$ such that

$$U_{i,j,l} = \sum_{a=1}^{k} \sum_{b=1}^{k} \sum_{c=1}^{k} A_{i,a} B_{j,b} C_{l,c}$$

We define Tucker rank as follows:

Definition 4.5 (Tucker rank). We say tensor $U \in \mathbb{R}^{n \times n \times n}$ has a tucker rank of k if $k \in \mathbb{Z}_{\geq 0}$ is the smallest positive integer such that there exist three matrices $A \in \mathbb{R}^{n \times k}$, $B \in \mathbb{R}^{n \times k}$, $C \in \mathbb{R}^{n \times k}$, and a (smaller) tensor $D \in \mathbb{R}^{k \times k \times k}$ such that $\forall (i, j, l) \in [n] \times [n] \times [n]$, we have

$$U_{i,j,l} = \sum_{i'=1}^{k} \sum_{j'=1}^{k} \sum_{l'=1}^{k} D_{i',j',l'} A_{i,i'} B_{j,j'} C_{l,l'}.$$

Then, we define train rank,

Definition 4.6 (Train rank). We say tensor $U \in \mathbb{R}^{n \times n \times n}$ has a train rank of k if $k \in \mathbb{Z}_{\geq 0}$ is the smallest positive integer such that there exist three matrices $A \in \mathbb{R}^{1 \times n \times k}$, $B \in \mathbb{R}^{k \times n \times k}$, $C \in \mathbb{R}^{k \times n \times 1}$ such that $\forall i, j, l \in [n] \times [n] \times [n]$ we have,

$$U_{i,j,l} = \sum_{i_1=1}^{1} \sum_{i_2=1}^{k} \sum_{i_3=1}^{k} \sum_{i_4=1}^{1} A_{i_1,i_2} B_{i_2,j,i_3} C_{i_3,l,i_4}$$

4.3 Tensor Cycle Definitions

We give the formal definition of tensor cycle rank as follows.

Definition 4.7 (Cycle-rank). We say $U \in \mathbb{R}^{n \times n \times n}$ has cycle-rank k if there are three matrices $A, B, C \in \mathbb{R}^{n \times k^2}$ such that

$$U_{i,j,l} = \sum_{a=1}^{k} \sum_{b=1}^{k} \sum_{c=1}^{k} A_{i,a+k(b-1)} B_{j,b+k(c-1)} C_{l,c+k(a-1)}$$

or

$$A_{i,j,l} = \sum_{a=1}^{k} \sum_{b=1}^{k} \sum_{c=1}^{k} \overline{U}_{i,a,b} \overline{V}_{j,b,c} \overline{W}_{l,c,a}$$

where $\overline{U} \in \mathbb{R}^{n \times k \times k}$ is tensorization of $U \in \mathbb{R}^{n \times k^2}$, $\overline{V} \in \mathbb{R}^{n \times k \times k}$ is tensorization of $V \in \mathbb{R}^{n \times k^2}$, $\overline{W} \in \mathbb{R}^{n \times k \times k}$ is tensorization of $W \in \mathbb{R}^{n \times k^2}$.

4.4 Approximate Matrix Product and Subspace Embeddings

We define subspace embedding [Sar06] as follows.

Definition 4.8 (Subspace Embedding [Sar06]). For a matrix $A \in \mathbb{R}^{n \times d}$, we say matrix S is a Subspace Embedding SE (n, d, ϵ, δ) of A if

$$\Pr[\|SAx\|_{2}^{2} = (1 \pm \epsilon)\|Ax\|_{2}^{2}, \forall x \in \mathbb{R}^{d}] \ge 1 - \delta.$$

We define approximate matrix product (see [Woo14] for example) as follows.

Definition 4.9 (Frobenius Approximate Matrix Product). Let $\epsilon \in (0,1)$ denote an accuracy parameter. Let $\delta \in (0,1)$ denote a failure probability. Given matrices A and B, where A and B each have n rows. We say a matrix S is a Frobenius Norm Approximate Matrix Product (FAMP (n, ϵ, δ)) with respect to A, B if

$$\Pr[\|A^{\top}B - A^{\top}S^{\top}SB\|_{F} \le \epsilon \cdot \|A\|_{F} \cdot \|B\|_{B}] \ge 1 - \delta.$$

4.5 Gaussian Transforms and CountSketch

We define the following kinds of sketching matrices.

Definition 4.10 (CountSketch or Sparse Embedding matrix). We define the following,

- $\sigma \in \mathbb{R}$: a scalar;
- $D \in \mathbb{R}^{n \times n}$: a diagonal matrix, with each diagonal entry chosen independently from $\{-1, +1\}$ with equal probability;
- $h: [n] \to [m]$: a random map, where $\forall i \in [n], j \in [m]$, we define

$$\Pr[h(i) = j] = 1/m$$

• $\Pi \in \{0,1\}^{m \times n}$: a binary matrix, where for all $(j,i) \in [m] \times [n]$, the entries are defined as

$$\Phi_{j,i} := \begin{cases} 1 & \text{if } h(i) = j \\ 0 & \text{otherwise} \end{cases}$$

Then, the CountSketch matrix $\Pi \in \mathbb{R}^{m \times n}$ is defined as

$$\Pi := \sigma \cdot \Phi D.$$

For any real matrix $A \in \mathbb{R}^{n \times d}$, the matrix product ΠA can be computed in input-sparsity $O(\operatorname{nnz}(A))$ time. For any real tensor $A \in \mathbb{R}^{n \times d_1 \times d_2}$, the product ΠA can be computed in input-sparsity $O(\operatorname{nnz}(A))$ time. For three CountSketch matrices Π_i, Π_2, Π_3 , for any input 3-order tensor $A \in \mathbb{R}^{n_1 \times n_2 \times n_3}$, $A(\Pi_1, \Pi_2, \Pi_3)$ can be computed in input-sparsity $O(\operatorname{nnz}(A))$ time.

In the absence of specification, the scalar σ is assumed to be 1 in the above notation.

Definition 4.11 (Gaussian transform or Gaussian matrix). Let $\sigma \in \mathbb{R}$ be a scalar. Let $G \in \mathbb{R}^{m \times n}$ be a matrix such that each entry of it is chosen i.i.d. from $\mathcal{N}(0,1)$. Then we define $S = \sigma \cdot G \in \mathbb{R}^{m \times n}$ to be the Gaussian matrix or the Gaussian transform. For any input matrix $A \in \mathbb{R}^{n \times d}$, the matrix product SA can be computed in input sparsity time of $O(m \cdot \operatorname{nnz}(A))$ time. For any input tensor, the product can be computed in input-sparsity $O(m \cdot \operatorname{nnz}(A))$ time. In the absence of specification, the scalar σ is assumed to be $1/\sqrt{m}$ in the above notation. We use the CountSketch together Gaussian transforms to get the following transform:

Definition 4.12 (CountSketch + Gaussian transform). Let $\Pi \in \mathbb{R}^{t \times n}$ denote a CountSketch matrix (Definition 4.10). Let $S \in \mathbb{R}^{m \times t}$ denote a Gaussian matrix (Definition 4.11). We define $S' = S\Pi$. Then we have that, for any input matrix $A \in \mathbb{R}^{n \times d}$, the matrix product S'A can be computed in input-sparsity $O(\operatorname{nnz}(A) + dtm^{\omega-2})$ time, where we use ω to denote the matrix multiplication exponent.

For the above sketching matrix, we have the following useful result telling us its SE and FAMP properties.

Lemma 4.13 (Lemma B.22 in [SWZ19c]). Let $m_2 = \Omega(k^2 + k/\varepsilon)$, $m_1 = \Omega(k/\varepsilon)$. Let $\Pi \in \mathbb{R}^{m_2 \times n}$ be a CountSketch matrix (Definition 4.10). Let $S \in \mathbb{R}^{m_1 \times m_2}$ be a Gaussian matrix (Definition 4.11). Then we define S' using SII as Definition 4.12. Then for any fixed matrix $C \in \mathbb{R}^{n \times k}$, S' is an SE(n, k, 1/3, 0.01) (Definition 4.8). Also, for any two fixed matrix A and B with the same number of rows, it is an FAMP $(n, O(\epsilon/k), 0.01)$ (Definition 4.9).

Theorem 4.14 (Theorem 36 in [CW13]). Given $A \in \mathbb{R}^{n \times k}$, $B \in \mathbb{R}^{n \times d}$, suppose $S \in \mathbb{R}^{m \times n}$ is an $\mathsf{SE}(n,k,1/\sqrt{2},\delta)$ for A, and satisfies is an $\mathsf{FAMP}(n,O(\sqrt{\epsilon/k},\delta))$ matrices A and C where C has n rows and C depends on A and B. If

$$\widehat{X} = \arg\min_{X \in \mathbb{R}^{k \times d}} \|SB - SAX\|_F^2,$$

then

$$||B - A\widehat{X}||_F^2 \le (1 + \varepsilon) \min_{X \in \mathbb{R}^{k \times d}} ||B - AX||_F^2.$$

4.6 Tensor Low-rank Approximation

In this section, we provide the following algorithm for tenor low-rank approximation.

Theorem 4.15 (Theorem C.1 in page 31 in [SWZ19c]). If the following conditions holds

- Let n denote a positive integer.
- Let $A \in \mathbb{R}^{n \times n \times n}$ be a 3rd order tensor.
- For any integer $k \geq 1$.
- For any accuracy parameter $\epsilon \in (0, 1)$.

Then, an algorithm exists such that

- runs in $\exp(O(k^2/\epsilon) + n \operatorname{poly}(k, 1/\epsilon) + O(\operatorname{nnz}(A))$ time
- construct three matrices U, V, and W of dimension $n \times k$. such that

$$\left\|\sum_{i=1}^{k} U_i \otimes V_i \otimes W_i - A\right\|_F^2 \le (1+\epsilon) \min_{\operatorname{rank} - k} \|A_k - A\|_F^2$$

• the succeed probability is 9/10.

Algorithm 1 An algorithm for solving Frobenius norm low-rank approximation problem

1: procedure FLOWRANKAPPROX (A, n, k, ϵ) \triangleright Theorem 4.15 for $i = 1 \rightarrow 3$ do 2: $s_i \leftarrow O(k/\epsilon).$ 3: end for 4: Select sketching matrices $S_1 \in \mathbb{R}^{n^2 \times s_1}$, $S_2 \in \mathbb{R}^{n^2 \times s_2}$, $S_3 \in \mathbb{R}^{n^2 \times s_3}$. \triangleright Definition 4.12 5:for $i = 1 \rightarrow 3$ do 6: Compute $A_i S_i$. 7: 8: end for $Y_1, Y_2, Y_3, C \leftarrow \text{FINPUTSPARSITYREDUCTION}(A, A_1S_1, A_2S_2, A_3S_3, n, s_1, s_2, s_3, k, \epsilon).$ 9: \triangleright Algorithm 2 for $i = 1 \rightarrow 3$ do 10: Create variables for $X_i \in \mathbb{R}^{s_i \times k}$ 11: 12:end for Run polynomial system verifier for $||(Y_1X_1) \otimes (Y_2X_2) \otimes (Y_3X_3) - C||_F^2$. 13:return $A_1S_1X_1$, $A_2S_2X_2$, and $A_3S_3X_3$. 14:15: end procedure

4.7 Input Sparsity Reduction

Here in this section, we introduce following key lemma for achieving input-sparsity running time.

Lemma 4.16 (Lemma C.3 in page 35 in [SWZ19c]). If the following condition holds

- Let $\operatorname{poly}(k, 1/\epsilon) \ge b_1 b_2 b_3 \ge k$.
- Suppose there are three matrices $V_1 \in \mathbb{R}^{n \times b_1}$, $V_2 \in \mathbb{R}^{n \times b_2}$, and $V_3 \in \mathbb{R}^{n \times b_3}$.
- Given a $n \times n \times n$ size tensor A
- Let $\mathcal{T} = O(\operatorname{nnz}(V_1) + \operatorname{nnz}(V_2) + \operatorname{nnz}(V_3) + \operatorname{nnz}(A)) = O(n \operatorname{poly}(k/\varepsilon) + \operatorname{nnz}(A))$
- Let $c_1 = c_2 = c_3 = \text{poly}(k, 1/\epsilon)$

Suppose there is an algorithm that

- runs in \mathcal{T} time
- Constructs a tensor $C \in \mathbb{R}^{c_1 \times c_2 \times c_3}$
- Constructs three matrices $\hat{V}_1 \in \mathbb{R}^{c_1 \times b_1}$, $\hat{V}_2 \in \mathbb{R}^{c_2 \times b_2}$ and $\hat{V}_3 \in \mathbb{R}^{c_3 \times b_3}$
- with probability at least 0.99, for all $\alpha > 0, X_1, X'_1 \in \mathbb{R}^{b_1 \times k}, X_2, X'_2 \in \mathbb{R}^{b_2 \times k}, X_3, X'_3 \in \mathbb{R}^{b_3 \times k}$ satisfy that,

$$\left\|\sum_{i=1}^{k} (\widehat{V}_{1}X_{1}')_{i} \otimes (\widehat{V}_{2}X_{2}')_{i} \otimes (\widehat{V}_{3}X_{3}')_{i} - C\right\|_{F}^{2} \leq \alpha \left\|\sum_{i=1}^{k} (\widehat{V}_{1}X_{1})_{i} \otimes (\widehat{V}_{2}X_{2})_{i} \otimes (\widehat{V}_{3}X_{3})_{i} - C\right\|_{F}^{2},$$

Then,

$$\left\|\sum_{i=1}^{k} (V_1 X_1')_i \otimes (V_2 X_2')_i \otimes (V_3 X_3')_i - A\right\|_F^2 \le (1+\epsilon)\alpha \left\|\sum_{i=1}^{k} (V_1 X_1)_i \otimes (V_2 X_2)_i \otimes (V_3 X_3)_i - A\right\|_F^2.$$

Algorithm 2 In this algorithm, we reduce the size of the objective function's from poly(n) size to poly(k) size

1:	procedure FINPUTSPARSITYREDUCTION $(A, V_1, V_2, V_3, n, b_1, b_2, b_3, k, \epsilon)$	$\triangleright \text{ Lemma } 4.16$
2:	for $i = 1 \rightarrow 3$ do	
3:	$c_i \leftarrow \text{poly}(k, 1/\epsilon).$	
4:	end for	
5:	for $i = 1 \rightarrow 3$ do	
6:	Choose sparse embedding matrices $T_i \in \mathbb{R}^{c_i \times n}$	\triangleright Definition 4.10
7:	end for	
8:	for $i = 1 \rightarrow 3$ do	
9:	$\widehat{V}_i \leftarrow T_i V_i \in \mathbb{R}^{c_i \times b_i},$	
10:	end for	
11:	$C \leftarrow A(T_1, T_2, T_3) \in \mathbb{R}^{c_1 \times c_2 \times c_3}.$	
12:	return $\widehat{V}_1, \widehat{V}_2, \widehat{V}_3$ and C .	
13: end procedure		

4.8 Solving Small Problems

Here we introduce the following theorem for solving small problem of our algorithm.

Theorem 4.17 (Theorem D.11 in page 90 in [SWZ19c]). If the following conditions hold

- Suppose we have $\max\{t_1, d_1, t_2, d_2, t_3, d_3\} \le n$.
- Let A be a tensor that has size $t_1 \times t_2 \times t_3$
- Given three matrices

$$-t_1 \times d_1$$
 matrix T_1

$$-t_2 \times d_2$$
 matrix T_2

- $-t_3 \times d_3$ matrix T_3
- for any $\delta > 0$ there exists a solution to

$$\min_{X_1, X_2, X_3} \left\| \sum_{i=1}^k (T_1 X_1)_i \otimes (T_2 X_2)_i \otimes (T_3 X_3)_i - A \right\|_F^2 := \text{OPT},$$

and representing each element of X_i using $O(n^{\delta})$ bits is achievable.

Then there is an algorithm that

- runs in $n^{O(\delta)} \cdot \exp(O(d_1k + d_2k + d_3k))$ time
- constructs three matrices

$$- \hat{X}_1 \\ - \hat{X}_2 \\ - \hat{X}_3$$

• such that $||(T_1\widehat{X}_1) \otimes (T_2\widehat{X}_2) \otimes (T_3\widehat{X}_3) - A||_F^2 = OPT.$

5 Tensor Cycle Rank

In this section, we provide our main algorithm and its analysis.

Algorithm 3 Our Main Algorithm

1: procedure FLOWCYCLERANKAPPROX (A, n, k, ϵ) \triangleright Theorem 5.1 for $i = 1 \rightarrow 3$ do 2: $s_i \leftarrow O(k^2/\epsilon).$ 3: $t_i \leftarrow \text{poly}(k, 1/\epsilon).$ 4: Choose sketching matrices $S_i \in \mathbb{R}^{n^2 \times s_i}$ \triangleright Definition 4.12 5:Choose sketching matrices $T_i \in \mathbb{R}^{t_i \times n}$ 6: end for 7:for $i = 1 \rightarrow 3$ do 8: Compute $A_i S_i$ 9: end for 10: 11: for $i = 1 \rightarrow 3$ do Compute $T_i A_i S_i$ 12:end for 13:Compute $B \leftarrow A(T_1, T_2, T_3)$. 14: for $i = 1 \rightarrow 3$ do 15:Create variables for $X_i \in \mathbb{R}^{s_i \times k^2}$. 16:end for 17:Create variables for $C \in \mathbb{R}^{k^2 \times k^2 \times k^2}$. $D \leftarrow \|\sum_{i_1=1}^k \sum_{i_2=1}^k \sum_{i_3=1}^k (Y_1 X_1)_{i_1+k(i_2-1)} (Y_2 X_2)_{i_2+k(i_3-1)} (Y_3 X_3)_{i_3+k(i_1-1)} - B\|_F^2$ Run polynomial system verifier for D. 18:19: 20: return $A_1S_1X_1$, $A_2S_2X_2$, and $A_3S_3X_3$. 21:22: end procedure

Theorem 5.1 (Cycle rank, formal version of Theorem 1.2). For any $k \ge 1$, $\epsilon \in (0,1)$, and a third-order tensor $A \in \mathbb{R}^{n \times n \times n}$, there is an algorithm that operates in

$$O(\operatorname{nnz}(A)) + n\operatorname{poly}(k, 1/\epsilon) + \exp(O(k^6/\epsilon))$$

time and produces three tensors U, V, W of dimension $n \times k \times k$ satisfying the following condition:

$$\|\sum_{i=1}^{k}\sum_{j=1}^{k}\sum_{l=1}^{k}U_{*,i,j}\otimes V_{*,j,l}\otimes W_{*,l,i} - A\|_{F} \le (1+\epsilon)\min_{\text{cycle rank}-k}\|A_{k} - A\|_{F}^{2}$$

or equivalently

$$\left\|\sum_{i=1}^{k}\sum_{j=1}^{k}\sum_{l=1}^{k} (U_{2})_{*,i+k(j-1)} \otimes (V_{2})_{*,j+k(l-1)} \otimes (W_{2})_{*,l+k(i-1)} - A\right\|_{F}^{2} \leq (1+\epsilon) \min_{\text{cycle rank}-k} \|A_{k} - A\|_{F}^{2}$$

holds with probability 9/10.

Here

• $U_2 \in \mathbb{R}^{n \times k^2}$ is the flatten version of tensor $U \in \mathbb{R}^{n \times k \times k}$.

- $V_2 \in \mathbb{R}^{n \times k^2}$ is the flatten version of tensor $V \in \mathbb{R}^{n \times k \times k}$.
- $W_2 \in \mathbb{R}^{n \times k^2}$ is the flatten version of tensor $W \in \mathbb{R}^{n \times k \times k}$.

Proof. We define OPT as

$$OPT := \min_{\text{cycle rank} - k A'} \|A' - A\|_F^2.$$

Suppose the optimal

$$A_k = \sum_{i=1}^k \sum_{j=1}^k \sum_{l=1}^k U_{i+k(j-1)}^* \otimes V_{j+k(l-1)}^* \otimes W_{l+k(i-1)}^*.$$

Let $V^* \in \mathbb{R}^{n \times k^2}$ and $W^* \in \mathbb{R}^{n \times k^2}$ be fixed. We refer to the columns of V^* as $V_1^*, V_2^*, \cdots, V_{k^2}^* \in \mathbb{R}^n$ and the columns of W^* as $W_1^*, W_2^*, \cdots, W_{k^2}^* \in \mathbb{R}^n$. The optimization problem under consideration is as follows:

$$\min_{U \in \mathbb{R}^{n \times k^2}} \left\| \sum_{i=1}^k \sum_{j=1}^k \sum_{l=1}^k U_{i+k(j-1)} \otimes V_{j+k(l-1)}^* \otimes W_{l+k(i-1)}^* - A \right\|_F^2$$

which can be rewritten as

$$\min_{U \in \mathbb{R}^{n \times k^2}} \left\| U \cdot \begin{bmatrix} \sum_{l=1}^{k} V_{1+k(l-1)}^* \otimes W_{l+k\cdot 0}^* \\ \sum_{l=1}^{k} V_{2+k(l-1)}^* \otimes W_{l+k\cdot 0}^* \\ \vdots \\ \sum_{l=1}^{k} V_{k+k(l-1)}^* \otimes W_{l+k\cdot 1}^* \\ \sum_{l=1}^{k} V_{2+k(l-1)}^* \otimes W_{l+k\cdot 1}^* \\ \vdots \\ \sum_{l=1}^{k} V_{2+k(l-1)}^* \otimes W_{l+k\cdot 1}^* \\ \sum_{l=1}^{k} V_{1+k(l-1)}^* \otimes W_{l+k\cdot (k-1)}^* \\ \sum_{l=1}^{k} V_{2+k(l-1)}^* \otimes W_{l+k\cdot (k-1)}^* \\ \vdots \\ \sum_{l=1}^{k} V_{k+k(l-1)}^* \otimes W_{l+k\cdot (k-1)}^* \\ \vdots \\ \sum_{l=1}^{k} V_{k+k(l-1)}^* \otimes W_{l+k\cdot (k-1)}^* \\ \end{bmatrix}_F$$

We can represent a tensor $A \in \mathbb{R}^{n \times n \times n}$ as a matrix $A_1 \in \mathbb{R}^{n \times n^2}$ by flattening the tensor along the

first dimension. Matrix $Z_1 \in \mathbb{R}^{k^2 \times n^2}$ is defined as follows:

$$\begin{array}{c} \operatorname{vec}(\sum_{l=1}^{k} V_{1+k(l-1)}^{*} \otimes W_{l+k\cdot0}^{*}) \\ \operatorname{vec}(\sum_{l=1}^{k} V_{2+k(l-1)}^{*} \otimes W_{l+k\cdot0}^{*}) \\ \vdots \\ \operatorname{vec}(\sum_{l=1}^{k} V_{k+k(l-1)}^{*} \otimes W_{l+k\cdot0}^{*}) \\ \operatorname{vec}(\sum_{l=1}^{k} V_{1+k(l-1)}^{*} \otimes W_{l+k\cdot1}^{*}) \\ \operatorname{vec}(\sum_{l=1}^{k} V_{2+k(l-1)}^{*} \otimes W_{l+k\cdot1}^{*}) \\ \vdots \\ \operatorname{vec}(\sum_{l=1}^{k} V_{1+k(l-1)}^{*} \otimes W_{l+k\cdot(k-1)}^{*}) \\ \operatorname{vec}(\sum_{l=1}^{k} V_{2+k(l-1)}^{*} \otimes W_{l+k\cdot(k-1)}^{*}) \\ \operatorname{vec}(\sum_{l=1}^{k} V_{2+k(l-1)}^{*} \otimes W_{l+k\cdot(k-1)}^{*}) \\ \vdots \\ \operatorname{vec}(\sum_{l=1}^{k} V_{k+k(l-1)}^{*} \otimes W_{l+k\cdot(k-1)}^{*}) \\ \end{array}$$

Now we get the equivalent objective function as follows,

$$\min_{U\in\mathbb{R}^{n\times k^2}}\|UZ_1-A_1\|_F^2.$$

With $A_k = U^* Z_1$, we can have $\min_{U \in \mathbb{R}^{n \times k^2}} ||UZ_1 - A_1||_F^2 = \text{OPT}.$

We can formulate the following optimization problem by using a sketching matrix $S_1^{\top} \in \mathbb{R}^{s_1 \times n^2}$ defined in Definition 4.12, where $s_1 = O(k^2/\epsilon)$:

$$\min_{U \in \mathbb{R}^{n \times k^2}} \|UZ_1S_1 - A_1S_1\|_F^2.$$

The optimal solution to the optimization problem above is denoted by $\widehat{U} \in \mathbb{R}^{n \times k^2}$.

Then, we have

$$\widehat{U} = A_1 S_1 (Z_1 S_1)^{\dagger}$$

By Lemma 4.13 and Theorem 4.14, we have

$$\begin{split} \|\widehat{U}Z_1 - A_1\|_F^2 &\leq (1+\epsilon) \cdot \min_{U \in \mathbb{R}^{n \times k^2}} \|UZ_1 - A_1\|_F^2 \\ &= (1+\epsilon) \cdot \text{OPT}, \end{split}$$

which means that

$$\left\| \sum_{i=1}^{k} \sum_{j=1}^{k} \sum_{l=1}^{k} \widehat{U}_{i+k(j-1)} \otimes V_{j+k(l-1)}^{*} \otimes W_{l+k(i-1)}^{*} - A \right\|_{F}^{2} \le (1+\epsilon) \cdot \text{OPT}$$

In order to write down $\hat{U}_1, \dots, \hat{U}_{k^2} \in \mathbb{R}^n$, considering the matrix A_1 is given, and we create $s_1 \times k^2$ variables for matrix $(Z_1S_1)^{\dagger}$.

Now in the second step, let the two matrices $\widehat{U} \in \mathbb{R}^{n \times k^2}$ and $W^* \in \mathbb{R}^{n \times k^2}$ to be fixed, we convert the tensor A into the matrix A_2 .

We use $Z_2 \in \mathbb{R}^{k^2 \times n^2}$ to denote the matrix where for each $j \in [k]$ and $l \in [k]$, the (j, l)-th row is

$$\operatorname{vec}(\sum_{i=1}^{k}\widehat{U}_{i+k(j-1)}\otimes W_{l+k(i-1)}^{*})$$

Now we focus on the objective function:

$$\min_{V \in \mathbb{R}^{n \times k^2}} \|VZ_2 - A_2\|_F^2$$

where $(1 + \epsilon) \cdot \text{OPT}$ is the upper bound of its optimal cost. Given that $s_2 = O(k^2/\epsilon)$, we use $S_2^{\top} \in \mathbb{R}^{s_2 \times n^2}$ as a sketching matrix defined in Definition 4.12. We apply S_2 to the right hand side of the objective function and we get the following new objective function,

$$\min_{V \in \mathbb{R}^{n \times k^2}} \| V Z_2 S_2 - A_2 S_2 \|_F^2$$

We use $\widehat{V} \in \mathbb{R}^{n \times k^2}$ as the optimal solution above. Now, we have

$$\widehat{V} = \underbrace{A_2}_{n \times n^2} \underbrace{S_2}_{n^2 \times s_2} \underbrace{(Z_2 S_2)^{\dagger}}_{s_2 \times k^2}.$$

By Lemma 4.13 and Theorem 4.14, we have,

$$\begin{split} \|\widehat{V}Z_2 - A_2\|_F^2 &\leq (1+\epsilon) \cdot \min_{V \in \mathbb{R}^{n \times k}} \|VZ_2 - A_2\|_F^2 \\ &\leq (1+\epsilon)^2 \cdot \text{OPT}, \end{split}$$

which means that

$$\left\| \sum_{i=1}^{k} \sum_{j=1}^{k} \sum_{l=1}^{k} \widehat{U}_{i+k(j-1)} \otimes \widehat{V}_{j+k(l-1)} \otimes W_{l+k(i-1)}^{*} - A \right\|_{F}^{2} \leq (1+\epsilon)^{2} \operatorname{OPT}.$$

In order to obtain the columns $\hat{V}_1, \dots, \hat{V}_{k^2} \in \mathbb{R}^n$, recall the matrix $A_2 \in \mathbb{R}^{n^2 \times n}$ is given, we create

s₂ × k² variables for matrix $(Z_2S_2)^{\dagger}$. We set the matrices $\widehat{U} \in \mathbb{R}^{n \times k^2}$ and $\widehat{V} \in \mathbb{R}^{n \times k^2}$ to fixed values in the third step. The tensor $A \in \mathbb{R}^{n \times n \times n}$ is converted into matrix $A_3 \in \mathbb{R}^{n^2 \times n}$. Let matrix $Z_3 \in \mathbb{R}^{k^2 \times n^2}$ denote

$$\begin{bmatrix} \sum_{j=1}^{k} \operatorname{vec}(\widehat{U}_{1+k(j-1)} \otimes \widehat{V}_{j+k\cdot 0}) \\ \sum_{j=1}^{k} \operatorname{vec}(\widehat{U}_{2+k(j-1)} \otimes \widehat{V}_{j+k\cdot 0}) \\ \cdots \\ \sum_{j=1}^{k} \operatorname{vec}(\widehat{U}_{k+k(j-1)} \otimes \widehat{V}_{j+k\cdot 1}) \\ \sum_{j=1}^{k} \operatorname{vec}(\widehat{U}_{1+k(j-1)} \otimes \widehat{V}_{j+k\cdot 1}) \\ \cdots \\ \sum_{j=1}^{k} \operatorname{vec}(\widehat{U}_{2+k(j-1)} \otimes \widehat{V}_{j+k\cdot 1}) \\ \cdots \\ \sum_{j=1}^{k} \operatorname{vec}(\widehat{U}_{1+k(j-1)} \otimes \widehat{V}_{j+k\cdot (k-1)}) \\ \sum_{j=1}^{k} \operatorname{vec}(\widehat{U}_{2+k(j-1)} \otimes \widehat{V}_{j+k\cdot (k-1)}) \\ \cdots \\ \sum_{j=1}^{k} \operatorname{vec}(\widehat{U}_{k+k(j-1)} \otimes \widehat{V}_{j+k\cdot (k-1)}) \\ \cdots \\ \sum_{j=1}^{k} \operatorname{vec}(\widehat{U}_{k+k(j-1)} \otimes \widehat{V}_{j+k\cdot (k-1)}) \end{bmatrix}$$

The objective function as follows is considered by us,

$$\min_{W \in \mathbb{R}^{n \times k^2}} \|WZ_3 - A_3\|_F^2,$$

with at most $(1 + \epsilon)^2$ OPT optimal cost.

We can use a sketching matrix $S_3^{\top} \in \mathbb{R}^{s_3 \times n^2}$, defined in Definition 4.12, with sketch size $s_3 = O(k^2/\varepsilon)$, to reduce the size of the input. By sketching S_3 on the right of the objective function, we have

$$\min_{W \in \mathbb{R}^{n \times k^2}} \|WZ_3S_3 - A_3S_3\|_F^2.$$

Given that $\widehat{W} \in \mathbb{R}^{n \times k^2}$ is used as the optimal solution, we can obtain $\widehat{W} = A_3 S_3 (Z_3 S_3)^{\dagger}$. By Lemma 4.13 and Theorem 4.14, we have,

$$\begin{split} \|\widehat{W}Z_3 - A_3\|_F^2 &\leq (1+\epsilon) \min_{W \in \mathbb{R}^{n \times k^2}} \|WZ_3 - A_3\|_F^2 \\ &\leq (1+\epsilon)^3 \operatorname{OPT}. \end{split}$$

Thus, we have

$$\min_{X_1, X_2, X_3} \left\| \sum_{i=1}^k \sum_{j=1}^k \sum_{l=1}^k (A_1 S_1 X_1)_{i+k(j-1)} \otimes (A_2 S_2 X_2)_{j+k(l-1)} \otimes (A_3 S_3 X_3)_{l+k(i-1)} - A \right\|_F^2 \leq (1+\epsilon)^3 \text{ OPT}.$$

Let $V_1 = A_1S_1, V_2 = A_2S_2$, and $V_3 = A_3S_3$. We then apply Lemma 4.16, and we obtain $\hat{V}_1, \hat{V}_2, \hat{V}_3, B$. We utilize Theorem 4.17 to solve the problem efficiently. By rescaling ϵ by a constant factor, we can ensure the correctness of the algorithm.

Time complexity. The running time of the algorithm can be divided as follows,

• By Definition 4.12, Line 8 in Algorithm 3 takes time of

$$O(\operatorname{nnz}(A)) + n \operatorname{poly}(k, 1/\epsilon);$$

• By Lemma 4.16, Line 11 and Line 14 takes time of

$$\operatorname{nnz}(A) + n \operatorname{poly}(k, 1/\epsilon);$$

• By Theorem 4.17, Line 19 takes time of

 $\exp(O(k^6/\epsilon)),$

ignoring the bit complexity for simplicity.

Adding then together, the total running time is

$$O(\operatorname{nnz}(A)) + n \operatorname{poly}(k, 1/\epsilon) + \exp(O(k^6/\epsilon)).$$

Thus we complete the proof.

References

- [ANW14] Haim Avron, Huy Nguyen, and David Woodruff. Subspace embeddings for the polynomial kernel. Advances in neural information processing systems, 27, 2014.
 - [AS23] Josh Alman and Zhao Song. Fast attention requires bounded entries. arXiv preprint arXiv:2302.13214, 2023.
- [ASA⁺22] Ekin Akyürek, Dale Schuurmans, Jacob Andreas, Tengyu Ma, and Denny Zhou. What learning algorithm is in-context learning? investigations with linear models. *arXiv* preprint arXiv:2211.15661, 2022.
 - [Bak79] James K Baker. Trainable grammars for speech recognition. The Journal of the Acoustical Society of America, 65(S1):S132–S132, 1979.
 - [BDS19] Jill Burstein, Christy Doran, and Thamar Solorio. Proceedings of the 2019 conference of the north american chapter of the association for computational linguistics: Human language technologies, volume 1 (long and short papers). In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), 2019.
- [BMR⁺20] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. Advances in neural information processing systems, 33:1877–1901, 2020.
 - [BNS19] Jan van den Brand, Danupon Nanongkai, and Thatchaphol Saranurak. Dynamic matrix inverse: Improved algorithms and matching conditional lower bounds. In 2019 IEEE 60th Annual Symposium on Foundations of Computer Science (FOCS), pages 456–480. IEEE, 2019.
 - [BPR96] Saugata Basu, Richard Pollack, and Marie-Françoise Roy. On the combinatorial and algebraic complexity of quantifier elimination. Journal of the ACM (JACM), 43(6):1002– 1045, 1996.
- [BPSW21] Jan van den Brand, Binghui Peng, Zhao Song, and Omri Weinstein. Training (overparametrized) neural networks in near-linear time. In *ITCS*, 2021.
 - [Bra20] Jan van den Brand. A deterministic linear program solver in current matrix multiplication time. In Proceedings of the Fourteenth Annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 259–278. SIAM, 2020.
 - [BSZ23] Jan van den Brand, Zhao Song, and Tianyi Zhou. Algorithms and hardness for dynamic attention maintenance in large language models. arXiv preprint arXiv:2304.02207, 2023.
 - [BW14] Christos Boutsidis and David P Woodruff. Optimal cur matrix decompositions. In Proceedings of the forty-sixth annual ACM symposium on Theory of computing (STOC), pages 353–362, 2014.
 - [BWZ16] Christos Boutsidis, David P Woodruff, and Peilin Zhong. Optimal principal component analysis in distributed and streaming models. In *Proceedings of the forty-eighth annual* ACM symposium on Theory of Computing, pages 236–249, 2016.

- [CCLY19] Michael B Cohen, Ben Cousins, Yin Tat Lee, and Xin Yang. A near-optimal algorithm for approximating the john ellipsoid. In *Conference on Learning Theory*, pages 849–873. PMLR, 2019.
 - [Cha96] Eugene Charniak. Tree-bank grammars. In Proceedings of the National Conference on Artificial Intelligence, pages 1031–1036, 1996.
 - [Chu89] Kenneth Ward Church. A stochastic parts program and noun phrase parser for unrestricted text. In International Conference on Acoustics, Speech, and Signal Processing,, pages 695–698. IEEE, 1989.
 - [CLS19] Michael B Cohen, Yin Tat Lee, and Zhao Song. Solving linear programs in the current matrix multiplication time. In *STOC*, 2019.
- [CND+22] Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. arXiv preprint arXiv:2204.02311, 2022.
 - [CW13] Kenneth L Clarkson and David P Woodruff. Low-rank approximation and regression in input sparsity time. In *Journal of the ACM (JACM), A Preliminary version of this* paper is appeared at STOC, 2013.
- [DCLT18] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pretraining of deep bidirectional transformers for language understanding. arXiv preprint arXiv:1810.04805, 2018.
- [DJS⁺19] Huaian Diao, Rajesh Jayaram, Zhao Song, Wen Sun, and David Woodruff. Optimal sketching for kronecker product regression and low rank approximation. Advances in neural information processing systems, 32, 2019.
- [DMS23] Yichuan Deng, Sridhar Mahadevan, and Zhao Song. Randomized and deterministic attention sparsification algorithms for over-parameterized feature dimension. *arxiv* preprint: arxiv 2304.03426, 2023.
- [DSSW18] Huaian Diao, Zhao Song, Wen Sun, and David Woodruff. Sketching for kronecker product regression and p-splines. In *International Conference on Artificial Intelligence* and Statistics, pages 1299–1308. PMLR, 2018.
- [DSW22] Yichuan Deng, Zhao Song, and Omri Weinstein. Discrepancy minimization in inputsparsity time. arXiv preprint arXiv:2210.12468, 2022.
- [FBS⁺21] Angela Fan, Shruti Bhosale, Holger Schwenk, Zhiyi Ma, Ahmed El-Kishky, Siddharth Goyal, Mandeep Baines, Onur Celebi, Guillaume Wenzek, Vishrav Chaudhary, et al. Beyond english-centric multilingual machine translation. *The Journal of Machine Learning Research*, 22(1):4839–4886, 2021.
- [GMS23] Yeqi Gao, Sridhar Mahadevan, and Zhao Song. An over-parameterized exponential regression. arXiv preprint arXiv:2303.16504, 2023.
- [Goo96] Joshua Goodman. Parsing algorithms and metrics. arXiv preprint cmp-lg/9605036, 1996.

- [GTLV22] Shivam Garg, Dimitris Tsipras, Percy Liang, and Gregory Valiant. What can transformers learn in-context? a case study of simple function classes. arXiv preprint arXiv:2208.01066, 2022.
- [JLSW20] Haotian Jiang, Yin Tat Lee, Zhao Song, and Sam Chiu-wai Wong. An improved cutting plane method for convex optimization, convex-concave games and its applications. In STOC, 2020.
- [JLSZ23] Haotian Jiang, Yin Tat Lee, Zhao Song, and Lichen Zhang. Convex minimization with integer minima in $\widetilde{O}(n^4)$ time. arXiv preprint, 2023.
- [KGW⁺23] John Kirchenbauer, Jonas Geiping, Yuxin Wen, Jonathan Katz, Ian Miers, and Tom Goldstein. A watermark for large language models. arXiv preprint arXiv:2301.10226, 2023.
 - [KM03] Dan Klein and Christopher D Manning. Accurate unlexicalized parsing. In *Proceedings* of the 41st annual meeting of the association for computational linguistics, pages 423– 430, 2003.
- [LGG⁺20] Yinhan Liu, Jiatao Gu, Naman Goyal, Xian Li, Sergey Edunov, Marjan Ghazvininejad, Mike Lewis, and Luke Zettlemoyer. Multilingual denoising pre-training for neural machine translation. *Transactions of the Association for Computational Linguistics*, 8:726–742, 2020.
 - [LK98] Irene Langkilde and Kevin Knight. Generation that exploits corpus-based statistical knowledge. In COLING 1998 Volume 1: The 17th International Conference on Computational Linguistics, 1998.
 - [LLR23] Yuchen Li, Yuanzhi Li, and Andrej Risteski. How do transformers learn topic structure: Towards a mechanistic understanding. *arXiv preprint arXiv:2303.04245*, 2023.
 - [LSZ23] Zhihang Li, Zhao Song, and Tianyi Zhou. Solving regularized exp, cosh and sinh regression problems. *arXiv preprint*, 2303.15725, 2023.
- [LYF⁺23] Pengfei Liu, Weizhe Yuan, Jinlan Fu, Zhengbao Jiang, Hiroaki Hayashi, and Graham Neubig. Pre-train, prompt, and predict: A systematic survey of prompting methods in natural language processing. ACM Computing Surveys, 55(9):1–35, 2023.
 - [Mit22] Ruslan Mitkov. The Oxford handbook of computational linguistics. Oxford University Press, 2022.
 - [MS99] Christopher Manning and Hinrich Schutze. Foundations of statistical natural language processing. MIT press, 1999.
- [MSM93] Mitchell Marcus, Beatrice Santorini, and Mary Ann Marcinkiewicz. Building a large annotated corpus of english: The penn treebank. 1993.
 - [NN13] Jelani Nelson and Huy L Nguyên. Osnap: Faster numerical linear algebra algorithms via sparser subspace embeddings. In 2013 ieee 54th annual symposium on foundations of computer science, pages 117–126. IEEE, 2013.
- [ONR⁺22] Johannes von Oswald, Eyvind Niklasson, Ettore Randazzo, João Sacramento, Alexander Mordvintsev, Andrey Zhmoginov, and Max Vladymyrov. Transformers learn incontext by gradient descent. arXiv preprint arXiv:2212.07677, 2022.

- [Pag13] Rasmus Pagh. Compressed matrix multiplication. ACM Transactions on Computation Theory (TOCT), 5(3):1–17, 2013.
- [PK07] Slav Petrov and Dan Klein. Improved inference for unlexicalized parsing. In Human Language Technologies 2007: The Conference of the North American Chapter of the Association for Computational Linguistics; Proceedings of the Main Conference, pages 404–411, 2007.
- [PP13] Ninh Pham and Rasmus Pagh. Fast and scalable polynomial kernels via explicit feature maps. In Proceedings of the 19th ACM SIGKDD international conference on Knowledge discovery and data mining, pages 239–247, 2013.
- [QSX⁺20] Xipeng Qiu, Tianxiang Sun, Yige Xu, Yunfan Shao, Ning Dai, and Xuanjing Huang. Pre-trained models for natural language processing: A survey. Science China Technological Sciences, 63(10):1872–1897, 2020.
 - [Rat96] Adwait Ratnaparkhi. A maximum entropy model for part-of-speech tagging. In Conference on empirical methods in natural language processing, 1996.
 - [Ren92] James Renegar. On the computational complexity and geometry of the first-order theory of the reals. part i: Introduction. preliminaries. the geometry of semi-algebraic sets. the decision problem for the existential theory of the reals. *Journal of symbolic computation*, 13(3):255–299, 1992.
- [RPSW19] Sebastian Ruder, Matthew E Peters, Swabha Swayamdipta, and Thomas Wolf. Transfer learning in natural language processing. In Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: Tutorials, pages 15–18, 2019.
 - [RSW16] Ilya Razenshteyn, Zhao Song, and David P Woodruff. Weighted low rank approximations with provable guarantees. In *Proceedings of the forty-eighth annual ACM* symposium on Theory of Computing, pages 250–263, 2016.
 - [RSZ22] Aravind Reddy, Zhao Song, and Lichen Zhang. Dynamic tensor product regression. In NeurIPS, 2022.
 - [Sar06] Tamas Sarlos. Improved approximation algorithms for large matrices via random projections. In 2006 47th annual IEEE symposium on foundations of computer science (FOCS'06), pages 143–152. IEEE, 2006.
 - [Sta20] Felix Stahlberg. Neural machine translation: A review. Journal of Artificial Intelligence Research, 69:343–418, 2020.
- [SWYZ21] Zhao Song, David Woodruff, Zheng Yu, and Lichen Zhang. Fast sketching of polynomial kernels of polynomial degree. In *International Conference on Machine Learning*, pages 9812–9823. PMLR, 2021.
 - [SWZ17] Zhao Song, David P Woodruff, and Peilin Zhong. Low rank approximation with entrywise l1-norm error. In Proceedings of the 49th Annual ACM SIGACT Symposium on Theory of Computing, pages 688–701, 2017.

- [SWZ19a] Zhao Song, David Woodruff, and Peilin Zhong. Average case column subset selection for entrywise l₁-norm loss. Advances in Neural Information Processing Systems, 32, 2019.
- [SWZ19b] Zhao Song, David Woodruff, and Peilin Zhong. Towards a zero-one law for column subset selection. Advances in Neural Information Processing Systems, 32, 2019.
- [SWZ19c] Zhao Song, David P Woodruff, and Peilin Zhong. Relative error tensor low rank approximation. In Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms, pages 2772–2789. SIAM, 2019.
- [SYYZ22] Zhao Song, Xin Yang, Yuanyuan Yang, and Tianyi Zhou. Faster algorithm for structured john ellipsoid computation. arXiv preprint arXiv:2211.14407, 2022.
- [SZKS21] Charlie Snell, Ruiqi Zhong, Dan Klein, and Jacob Steinhardt. Approximating how single head attention learns. arXiv preprint arXiv:2103.07601, 2021.
 - [SZZ21] Zhao Song, Lichen Zhang, and Ruizhe Zhang. Training multi-layer over-parametrized neural network in subquadratic time. arXiv preprint arXiv:2112.07628, 2021.
- [TKMS03] Kristina Toutanova, Dan Klein, Christopher D Manning, and Yoram Singer. Featurerich part-of-speech tagging with a cyclic dependency network. In Proceedings of the 2003 Human Language Technology Conference of the North American Chapter of the Association for Computational Linguistics, pages 252–259, 2003.
- [VSP⁺17] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. Advances in neural information processing systems, 30, 2017.
- [WDS⁺19] Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. Huggingface's transformers: State-of-the-art natural language processing. arXiv preprint arXiv:1910.03771, 2019.
 - [Woo14] David P Woodruff. Sketching as a tool for numerical linear algebra. Foundations and Trends® in Theoretical Computer Science, 10(1-2):1-157, 2014.
 - [WZ16] David P Woodruff and Peilin Zhong. Distributed low rank approximation of implicit functions of a matrix. In 2016 IEEE 32nd International Conference on Data Engineering (ICDE), pages 847–858. IEEE, 2016.
 - [Yng60] Victor H Yngve. A model and an hypothesis for language structure. Proceedings of the American philosophical society, 104(5):444–466, 1960.
 - [Zha22] Lichen Zhang. Speeding up optimizations via data structures: Faster search, sample and maintenance. Master's thesis, Carnegie Mellon University, 2022.
- [ZHDK23] Amir Zandieh, Insu Han, Majid Daliri, and Amin Karbasi. Kdeformer: Accelerating transformers via kernel density estimation. arXiv preprint arXiv:2302.02451, 2023.
- [ZKV⁺20] Jingzhao Zhang, Sai Praneeth Karimireddy, Andreas Veit, Seungyeon Kim, Sashank Reddi, Sanjiv Kumar, and Suvrit Sra. Why are adaptive methods good for attention models? Advances in Neural Information Processing Systems, 33:15383–15393, 2020.

- [ZPGA23] Haoyu Zhao, Abhishek Panigrahi, Rong Ge, and Sanjeev Arora. Do transformers parse while predicting the masked word? In *arxiv*. https://arxiv.org/pdf/2303.08117.pdf, 2023.
- [ZRG⁺22] Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. Opt: Open pre-trained transformer language models. arXiv preprint arXiv:2205.01068, 2022.