Gradient-less Federated Gradient Boosting Trees with Learnable Learning Rates

Chenyang Ma, Xinchi Qiu, Daniel J. Beutel, Nicholas D. Lane

University of Cambridge

cm2196@cam.ac.uk

ABSTRACT

The privacy-sensitive nature of decentralized datasets and the robustness of eXtreme Gradient Boosting (XGBoost) on tabular data raise the needs to train XGBoost in the context of federated learning (FL). Existing works on federated XGBoost in the horizontal setting rely on the sharing of gradients, which induce per-node level communication frequency and serious privacy concerns. To alleviate these problems, we develop an innovative framework for horizontal federated XGBoost which does not depend on the sharing of gradients and simultaneously boosts privacy and communication efficiency by making the learning rates of the aggregated tree ensembles learnable. We conduct extensive evaluations on various classification and regression datasets, showing our approach achieves performance comparable to the stateof-the-art method and effectively improves communication efficiency by lowering both communication rounds and communication overhead by factors ranging from 25x to 700x.

1 INTRODUCTION

Federated Learning (FL) enables the training of a global model using decentralized datasets in a privacy-preserving manner, contrasting with the conventional centralized training paradigm [7, 23, 34, 36, 37]. Existing FL research [18, 21, 24, 28] and the developed techniques [3, 13, 32, 39] to optimize model convergence and reduce systematic privacy risks and costs mainly focus on neural networks (NN). The efforts of developing FL algorithms to support other machine learning (ML) models, on the other hand, remain under-explored.

EXtreme Gradient Boosting (XGBoost) [5] is a powerful and interpretable gradient-boosted decision tree (GBDT). In most of the cases, XGBoost outperforms deep learning methods for tabular data on medium-sized datasets under 10k training examples [10, 29, 35]. In the context of crosssilo FL, where the clients pool is typically made up from 2 to 100 [13] organizations, there is a growing need to deploy a federated XGBoost system on specific tasks such as survival analysis [1] and financial fraud detection [6, 31].

Existing works on federated XGBoost usually follow two settings (Fig. 1). The horizontal setting is defined to be the case when clients' datasets have identical feature spaces but different sample IDs. The central server sends the global model to all clients and then aggregates the updated model



Figure 1: Horizontal vs. vertical federated XGBoost.

parameters after each communication round. As for the vertical setting, first proposed by SecureBoost [6, 27], the concepts of passive parties and one active party were introduced, where passive parties and the active party share identical sample space but possess different features. As only the active party owns data labels, it naturally acts as the server.

Although the horizontal setting remains to be more common [12], the training of a horizontal federated XGBoost turns out to be harder, not easier, because finding the optimal split condition of XGBoost trees depends on the *order* of the data samples [26, 30] as we iterate the feature set and partition the data samples into left and right according to the feature constraints. Therefore, as all clients share the same sample IDs in the vertical setting, the passive parties only need to send the order of the samples to the active party. However, since the sample IDs are different across all clients in the horizontal setting, at every splitting point, each client needs to transmit the gradients, hessians, and/or sample splits based on the feature values to the server to find the optimal splitting condition [25]. Hence, we identify two key problems imposed by this vanilla approach.

1. *Per-node level communication frequency.* The server needs to communicate with all clients at every splitting point. We denote the depth of each tree as *L* and the number of trees in the tree ensemble as *M*. The number of nodes in the tree ensemble can scale up to $M \times 2^{L}$ [4], and so is the number of communication rounds. As a trained XGBoost model is common to have a depth of 8 and 500 trees [5], the number of communication rounds can reach ~100K. Moreover, in a real application of federated XGBoost, it is possible for the server to conduct more than one round of communication per node [22] and carry out

extra cryptographic calculations. Thus, the high communication overhead makes it difficult to deploy horizontal federated XGBoost for practical uses.

2. *Serious privacy concerns.* The sharing of gradients and even confident information was proved to be insecure in the distributed training of ML models [9, 40]. As the training data can be reconstructed using gradients, such sharing needs to be protected.

Existing research on horizontal federated XGBoost tackles the aforementioned two problems by seeking a trade-off between privacy and communication costs. A few works take stronger defenses against privacy leaks. FedXGB [22] developed a new secure aggregation protocol by applying homomorphic encryption and secret sharing on shared parameters directly. However, this induces high communication and computation overhead at per-node level communication frequency. Some works decrease the resolution of the raw data distribution by generating a surrogate representation using gradient histogram [4, 12, 25, 30]. Histogram-based methods accelerate the training process by building quantile sketch approximation, but the communication frequency still correlates to the depth of the trees. Besides, they can still leak privacy because the gradients related to the bins and the thresholds can be inferred [33]. Other works obfuscate the raw data distribution with methods including clusteringbased k-anonymity [38] and locality-sensitive hashing [17]. Although the required communication overhead is less than encryption-based methods, these approaches have a trade-off between model performance and the number of clients.

In this work, we ask the fundamental question: *if it is pos*sible not to rely on the sharing of gradients and hessians to construct a federated XGBoost in the horizontal setting? In this way, we can simultaneously boost privacy and disentangle the per-node level communication frequency. We find it to be possible by formulating an important intuition: as the local datasets of clients can be heterogeneous in the horizontal setting, using a fixed learning rate for each tree may be too weak since each tree can make different amounts of mistakes on unseen data with distribution shifts. To this end, we make the learning rates of the aggregated tree ensembles learnable by training a small one-layer 1D CNN with kernel size and stride equal to the number of trees in each client tree ensemble. We use the prediction outcomes as inputs directly. This novel framework preserves privacy. The clients only need to send the constructed tree ensemble to the server. The sharing of gradients and hessians, which may leak sensitive information, is not required. In addition, the number of communication rounds is independent of any hyperparameter related to the trained XGBoost. In practice, we find 10 communication rounds to be sufficient for the global federated XGBoost model to reach performance comparable

to the state-of-the-art method. Moreover, the total communication overhead to train a global federated XGBoost model is independent of the dataset size. Our approach induces total communication overhead lower than previous works in the order of tens to hundreds.

The main contributions of this work are summarized as:

- We propose a novel privacy-preserving framework, FedXG-Bllr, a federated XGBoost with learnable learning rates in the horizontal setting which do not rely on the sharing of gradients and hessians.
- Our framework disentangles the per-node level communication frequency when training a federated XGBoost.
- The total communication overhead of our framework is independent of the dataset size and is significantly lower (by factors ranging from 25x to 700x) than previous methods.
- We show that FedXGBllr is interpretable with carefully framed reasoning and analysis.
- We conduct extensive experiments on both classification and regression datasets with diverse feature dimensions and sizes. Experimental results of our approach are comparable to the state-of-the-art horizontal federated XGBoost.
- The implementation is made available and released under Flower [2], a comprehensive, end-to-end FL framework.

2 PRELIMINARIES

EXtreme Gradient Boosting (XGBoost) XGBoost is a gradient boosting tree and is an additive ensemble model. It adopts forward stagewise regression and consistently learns new trees to fit the residuals until a stop condition is met. Given a dataset $\{x_i, y_i\}_{i=1}^N$ where $x_i \in \mathbb{R}^D$, $y_i \in \mathbb{R}$ represent the features (with dimension *D*) and labels of the *i*-th sample, the final prediction is calculated by summing predictions of all *M* trees with a fixed learning rate η :

$$\hat{y}_i = \sum_{t=1}^M \eta f_t(x_i)$$
 (1)

where $f_t(x_i)$ is the prediction made by the *t*-th tree.

The objective of XGBoost is to minimize the sum of the loss of all the data samples. It first calculates the first ordergradient, g_i , and second-order hessian, h_i , of all samples:

$$g_i = \partial_{\hat{y}_i^{(t-1)}} L(y_i, \hat{y}_i^{t-1}), \quad h_i = \partial_{\hat{y}_i^{(t-1)}}^2 L(y_i, \hat{y}_i^{t-1}) \tag{2}$$

where $\hat{y}_i^{(t-1)}$ is the prediction made by the previous tree and $L(y_i, \hat{y}_i^{t-1})$ is the loss function. Then the gradient sums of instance set I_j on each node j can be calculated by:

$$G_j = \sum_{i \in I_j} g_i, \quad H_j = \sum_{i \in I_j} h_i \tag{3}$$

The optimal weight w_j^* and objective obj^* are derived from the objective function involving regularization terms:

$$w_j^* = -\frac{G_j}{H_j + \lambda}, \quad obj^* = -\frac{1}{2}\sum_{j=1}^T \frac{G_j^2}{H_j + \lambda} + \gamma T \qquad (4)$$

where *T* is the leaf node number and λ and γ are the regularization for the leaf weights and leaf number, respectively.

From root to leaf nodes, the best split can be found by maximizing $SplitGain = obj_{before}^* - obj_{after}^*$, which is:

$$SplitGain = \frac{1}{2} \left[\frac{G_L^2}{H_L + \lambda} + \frac{G_R^2}{H_R + \lambda} - \frac{G_L^2 + G_R^2}{H_L + H_R + \lambda} \right] - \gamma \quad (5)$$

where G_L and H_L , G_R , and H_R are the sums of the gradients and hessians of the data samples partitioned into the left and right branch based on the splitting point's feature constraint.

3 METHOD

In this section, we provide a detailed description of our approach. We first formulate our intuitions in Section 3.1. We then facilitate our intuitions in Section 3.2 and discuss how to learn the learning rates using proposed, interpretable onelayer 1D CNN in Section 3.3. Finally, we develop new frame-work **FedXGBIlr** to train federated XGBoost in Section 3.4.

3.1 Intuitions

A fixed learning rate is too weak Local datasets of clients participating in FL can be heterogeneous (i.e., non-IID). The trained model on the client's local dataset converges to its local optima. When the model is sent to other clients and evaluated on their local datasets, it suffers from degradation in performance because different clients' local optima are divergent. The adverse effects of data heterogeneity in FL over NN-based approaches are widely researched [14, 16, 18, 20]. More recent works demonstrate that XGBoost also experiences deterioration in model performance with heterogeneous local datasets [8, 12].

We argue that the core reason causing performance degradation, when the built XGBoost model is evaluated on other unseen datasets with distribution shifts, is that each tree in the tree ensemble makes different amounts of mistakes.

Consider the example illustrated in Fig. 2. We have an XGBoost model consisting of M trees in total where f_t denotes the *t*-th tree, t = 1..M. The XGBoost model is trained on the dataset $\{x_i^*, y_i^*\}_{i=1}^N$ for a regression task. We send this XGBoost model to two other clients and evaluate on their respective local datasets, S_1 and S_2 .

The prediction outcomes of the first three trees in the XGBoost tree ensemble on two data samples $\{x_a^1, y_a^1\} \in S_1$ and $\{x_b^2, y_b^2\} \in S_2$ are also labeled in Fig. 2. Their ground truths are equal such that $y_a^1 = y_b^2 = 100$. Since local datasets S_1 and S_2 belong to two heterogeneous clients, the trees



Figure 2: An example of the impact of local data heterogeneity on the performance of XGBoost model.

perform differently across data samples. For the first tree f_1 , it gives a good initial prediction for x_b^2 (110) but not for x_a^1 (60). The second and third trees f_2 and f_3 , on the contrary, sufficiently correct the residuals made by the first tree f_1 for x_a^1 (30, 5) but not for x_b^2 (-1, 20). In this case, a fixed learning rate (e.g., $\eta = 0.3$) may be too weak because ideally, we want a higher learning rate for $f_2(x_a^1)$ and $f_3(x_a^1)$ but a lower learning rate for $f_2(x_b^2)$ and $f_3(x_b^2)$.

Moving towards the global optima As explained previously, data heterogeneity causes the trained XGBoost models on different clients' local datasets to converge to local optima that are far from each other. Consequently, given an unseen data sample, these XGBoost tree ensembles output different prediction results. However, among all XGBoost tree ensembles, some can give more accurate predictions because the unseen data sample may be closer to the underlying distribution of their trained datasets. Thus, applying a weighted sum on the diverse prediction results given by all XGBoost tree ensembles can lead to a more accurate final prediction value, helping us to move towards the global optima.

It is important to point out that the approach of utilizing weighted sum to converge to the global optima is proved to be effective in the previous literature. FedAvg [24] used the weighted sum of the aggregated model parameters according to the number of data samples presented in the clients' local datasets, and many kinds of literature have given theoretical convergence guarantees for the method [14, 19]. Later FL strategies such as FedProx [18] also adopted the weighted sum of aggregated model parameters.

3.2 Tree Ensembles Aggregation

Suppose there are *K* clients participating in the training of federated XGBoost, and denote them as $(O_1, O_2, ..., O_K)$. All clients' local datasets have different sample IDs but the same feature dimension *D*. Each client trains a XGBoost tree ensemble consisting of *M* trees using its local dataset, where $f_{O_t^k}$ denotes the *t*-th tree constructed by client *k*, t = 1...M and k = 1...K. To facilitate our intuitions, the final prediction result given an arbitrary data sample with feature dimension *D* is calculated by the weighted sum of all trees from all



Figure 3: The aggregated tree ensemble. The final prediction given by the weighted sum of all trees.

clients as shown in Fig. 3. Each vertical tree chain is the tree ensemble built by one client, where W_t^k is the learning rate assigned to $f_{O_t^k}$ and Z_k is the weight applied to the prediction result calculated by client O_k 's tree ensemble. We refer to this system as the aggregated tree ensemble. Both $f_{O_t^k}$ and Z_k are learnable, which will be revealed in Section 3.3.

For all clients to calculate the final prediction result, each client needs to receive the aggregated tree ensemble with the help of the server. First, each client ensures that within its tree ensemble, all trees are sorted (i.e., if the tree ensemble is stored in an array, the *t*-th tree is at the *t*-th position). Then, as shown in Fig. 4(a), each client sends their built XGBoost tree ensemble and client ID (CID = k) to the server. The server sorts and concatenates all tree ensembles using CIDs such that the *k*-th tree ensemble is always adjacent to both (k - 1)-th and (k + 1)-th tree ensembles, as illustrated by the input layer of Fig. 4(b). Finally, the server broadcasts the sorted, aggregated tree ensembles to every client.

3.3 Learnable Learning Rates by One-layer 1D CNN

We develop a method to learn the learning rate W_t^k assigned to each tree $f_{O_t^k}$ by transforming the aggregated tree ensembles in Fig. 3 to a one-layer 1D CNN as shown in Fig. 4(b). In the first 1D convolution layer, the inputs are the prediction outcome of all trees. *G* is the chosen activation function.

Interpretability The small-sized model is interpretable. The kernel size and stride of the 1D convolution are equal to the number of trees, M, in each client's tree ensemble. Thus, each channel of the 1D convolution is the learnable learning rates (W_t^k) for all $f_{O_t^k}$ in the tree ensemble of a specific client k, and the number of convolution channels can be understood as the number of learning rate strategies that can be applied. The classification head, fully connected (FC) layer, contains the weighting factors (Z_k) to balance



Figure 4: The pipeline. (a) tree ensembles aggregation and (b) one-layer 1D CNN to study the learning rates and output the final prediction result.

the prediction outcomes of each client's tree ensemble and calculate the final prediction result, which is also updated during training. The incentive for introducing activation G is to avoid overfitting because a portion of the learned strategies will be deactivated. We set G to be the most used activation function, ReLU.

3.4 FedXGBllr

We introduce the new framework, FedXGBllr, to train a global federated XGBoost model by learning the learning rate for each tree with FL. The global federated XGBoost model consists of all clients' locally trained XGBoost tree ensembles and the globally trained one-layer 1D CNN. The detailed procedure is shown in Algorithm. 1. At round 0 (line 1 to 7), each client first trains its local XGBoost tree ensemble. The server then conducts tree ensemble aggregation and CNN initialization. After receiving the aggregated tree ensemble, all clients calculate the prediction outcomes given the aggregated tree ensemble on their local data samples. The calculated prediction outcomes are inputs of the CNN. It is worth noticing that the clients only build XGBoost models at round 0, and the aggregated tree ensemble is fixed after round 0. For the federated training of the one-layer 1D CNN after round 1 (line 8), the protocol follows the standard FL algorithm, and we use FedAvg [24].

In FedXGBllr, the number of communication rounds is equal to the FL training rounds (*R*) because we send the trees (at round 0) and CNN's model parameters (after round 1).

4 EXPERIMENTS

In this section, we conduct extensive experiments to validate the effectiveness of our approach. We start by describing experiment setup and implementation details in Section 4.1. We then discuss the experimental results with comparisons to the centralized baseline and the state-of-the-art method Algorithm 1: FedXGBllr.

Input: A server *C*. K clients $(O_1, O_2, ..., O_K)$, each with a local dataset $S_k \in \mathbb{R}^{N_k \times D}$. The number of trees to be trained *M*. FL training round *R*, local epoch *E*, local learning rate α , local minibatch size *B*. Initial one-layer 1D CNN parameters w_0 .

Output: Trained global federated XGBoost model

- 1 if round t = 0 then
- 2 Each O_k trains a XGBoost tree ensemble with M trees using local dataset;
- 3 Each O_k sends the trained XGBoost tree ensemble and *CID* to *C*;
- 4 C sorts and broadcasts the aggregated XGBoost tree ensemble (K ensembles total, MK trees total) with corresponded CID to all O_k (K clients);
- 5 *C* initializes w_0 for the one-layer 1D CNN;
- 6 Each O_k receives the aggregated XGBoost tree ensemble;
- 7 Each O_k evaluates the aggregated XGBoost tree ensembles on local dataset $S_k \in \mathbb{R}^{N_k \times D}$ so that prediction outcomes of all *MK* trees on all data samples, denoted as $S_k^* \in \mathbb{R}^{N_k \times MK}$, are acquired.

s for round t = 1 to R do

- 9 C selects all K clients;
- 10 C broadcasts w_t to all K clients;
- 11 **for** each client O_k in parallel do
- 12 $w_{t+1}^k = \text{ClientUpdate}(CID, w_t, E, B, \alpha);$

13
$$w_{t+1} = \sum_{k=1}^{K} \frac{N_k}{N} w_{t+1}^k;$$

Def ClientUpdate (*CID*, w, E, B, α): $\beta = \text{divide } S^*_{CID}$ into batches of size B; **for** local epoch e = 1 to E **do for** local batch $b \in \beta$ **do** $w = w - \alpha \Delta \ell(b; w);$ **return** w;

in Section 4.2. Finally, we provide ablation studies and analysis to justify the interpretability and low communication overhead of our approach in Section 4.3.

4.1 Experiment Setup and Implementations

Comparison methods We benchmark our method against one of the state-of-the-art and most influential works on horizontal federated XGBoost, SimFL [17], which adopts locality-sensitive hashing in the context of FL. Opposed to

Table 1: Summary of datasets

Dataset	Task Type	Data No.	Dimension	Size
a9a	classification	32,561	123	16MB
cod-rna	classification	59,535	8	2.1MB
ijcnn1	classification	49,990	22	4.4MB
real-sim	classification	72,309	20,958	6.1GB
HIGGS	classification	1,000,000	28	112MB
SUSY	classification	1,000,000	18	72MB
abalone	regression	4,177	8	253KB
cpusmall	regression	8,192	12	684KB
space_ga	regression	3,167	6	553KB
YearPredictionMSD	regression	515,345	90	615MB

our method, SimFL trains the global XGBoost model by sharing the weighted gradients across rounds. We also use the centralized XGBoost trained on the whole dataset as baseline.

Dataset Following SimFL [17], we evaluate our method on the same six tabular datasets for classification. We also conduct our experiment on four tabular datasets for regression. All datasets can be downloaded from LIBSVM data website ¹. The information of each dataset is summarized in Table. 1. For all datasets, the training set to test set ratio is 0.75 : 0.25 with random shuffling. The test set is used as the global test set at the server side. For the training set, we equally divide it according to the number of clients and assign the partitioned datasets to each client as their local dataset. SimFL [17] only conducts experiments using 2 clients. We also provide the results of our method using 5 and 10 clients.

Evaluation metric We report the performance on classification and regression datasets using Accuracy and Mean Squared Error (MSE) respectively, which is common practice.

Implementation details We use the Python package xgboost to train the local XGBoost models. Following SimFL [17], the maximum depth of all trees is set to 8. For our implementation, we set the number of trees in each tree ensemble to be 500 divided by the number of clients. The initial learning rate (η) is the same for all trees and is set to 0.1. Note that η is a fixed hyperparameter of XGBoost (explained in Section 2), and is not the learnable learning rates (W_t^k) that are refined by the one-layer 1D CNN (explained in Section 3.3). For the globally trained one-layer 1D CNN and FL infrastructures, including clients and a server, we implement our method with PyTorch under Flower [2], an end-to-end FL framework. For the CNN, we employ Kaiming initialization [11] and set the number of convolution channels to 64. For each client, we train the CNN using Adam [15] with learning rate (α) 0.001, β_1 momentum 0.5, and β_2 momentum 0.999. The local

¹https://www.csie.ntu.edu.tw/ cjlin/libsvmtools/datasets/

Table 2: Quantitative results of FedXGBllr compared to SimFL and centralized baseline - Accuracy \uparrow (for the first six classification datasets), MSE \downarrow (for the last four regression datasets).

Dataset	FedXGBllr			SimFL [17]	Centralized
	2 clients	5 clients	10 clients	2 clients	Baseline
a9a	85.1	85.1	84.7	84.9	84.9
cod-rna	97.0	96.5	95.8	94.0	93.9
ijcnn1	96.3	96.0	95.3	96.4	96.3
real-sim	93.4	93.8	92.7	92.9	93.5
HIGGS	71.5	70.9	70.3	70.7	70.7
SUSY	82.5	81.7	81.2	80.4	80.0
abalone	3.6	4.4	4.9	-	1.3
cpusmall	8.0	8.5	9.5	-	6.7
space_ga	0.024	0.033	0.034	-	0.024
YearPredictionMSD	80.3	82.7	91.6	-	80.5

epoch (*E*) is set to 100, and the batch size (*B*) is set to 64. We train on one Nvidia Tesla V100 GPU.

4.2 Experimental Results

Table. 2 demonstrates the quantitative results of FedXGBllr. The number of communication rounds (R) is set to 10. For all experiments, we take an average of 5 runs. From the results, our approach outperforms or reaches comparable accuracy to SimFL [17] and the centralized baselines on all six classification datasets with 2 clients. For the regression datasets, our approach achieves comparable or slightly higher MSE compared to the centralized baseline.

For both classification and regression datasets, our method performs better on larger datasets. We hypothesize this is due to the generalization capability of CNN scaling up with the volume of data. Additionally, as the number of clients increases from 2 to 5 and 10, the performance slightly decreases. We think it is reasonable because FL is harder with more clients [13].

The results suggest 10 rounds are sufficient for FedXGBllr to build a good global federated XGBoost model. However, it is worth mentioning that the number of rounds needed to reach good performance correlates with the number of local epochs (E) to train the one-layer 1D CNN on the client side. A higher E may require fewer communication rounds (consider the extreme when E = 1). Our implementation uses E = 100, and leaves the optimal trade-off of E and R for future studies.

4.3 Ablation Studies and Analysis

Communication overhead We compare the total communication overhead to build a global federated XGBoost model of our approach to baseline, SimFL [17]. For all comparisons, we assume the number of clients K to be 10 and the total number of built XGBoost trees M to be 500 with a depth L of 8 in order to be consistent with SimFL's efficiency experiments. The communications overhead of our approach is independent of the dataset size *N*, and can be expressed as:

$$2K(M \times SZ_t + R \times SZ_nn) \tag{6}$$

where *R* is the number of FL training rounds, SZ_t is the size of each tree in bytes, and SZ_nn is the size of the one-layer 1D CNN in bytes. Therefore, $2KM \times SZ_t$ is the communication overhead during tree ensembles aggregation at round 0, and $2KR \times SZ_t$ is the communication overhead of the federated training of the CNN from round 1 to *R*. We assume *R* to be 10 because this number is sufficient for our approach to reach good performance as explained in Section 4.2. SZ_nn is 0.03MB (Table. 5). In practice, SZ_t is negligible as the size of 500 trees built by the xgboost package is only 48 bytes.

The communication overhead of SimFL [17] in bytes is given by $8KN \times Hash + 8M[N + (2^L - 1)(K - 1)]$, where *Hash* is the number of hash functions. Table. 3 illustrates the comparison of the total communication overhead. We include the results using the six classification datasets because SimFL [17] provided the exact

Table	3:	Compari-
son of	f co	mmunica-
tion ov	verł	nead (MB).

Dataset	FedXGBllr	SimFL [17]
a9a	6.0	150.4 (25×)
cod-rna	6.0	249.3 (42×)
ijcnn1	6.0	218.4 (36×)
real-sim	6.0	323.1 (54×)
HIGGS	6.0	4216 (703×)
SUSY	6.0	4136 (689×)

values on them. We can see the communication overhead of our approach is significantly lower especially as the dataset size scales up. We save the communication cost by at least a factor of 25, and can save up to a factor of 700.

Although we did not compare the exact numbers, our communication overhead is also significantly lower than encryption-based methods such as FedXGB [22], whose training shares encryption keys and communication cost scales up linearly with both input size and the number of clients.

Model interpretability We want to know if the interpretability of our one-layer 1D CNN couples with the high performance? We change the first 1D convolution layer with kernel size and stride equal to the number of trees in each client tree ensemble with: 1) standard convolution with kernel size 3, stride 1, and 2) FC layer with dimension 256, and remove the flattened layer. The number of communication rounds is set to 10. We fix the number of clients to be 5. The results are shown in Table. 4. We also show the number of parameters and total size of each model in Table. 5.

From the results, our one-layer 1D CNN reaches the best performance on all datasets although it has the smallest number of parameters and total size. This suggests the effectiveness and interpretability of our CNN model. We find that for all datasets, the performance gap between our interpretable CNN and 2-layer FCNN is much larger than the gap

Table 4: Model interpretability. $k = kernel_size$, s = stride, $n = client_tree_num = 500/client_num$.

Dataset	1-layer 1D CNN (k = s = n)	1-layer 1D CNN (k = 3, s = 1)	2-layer FCNN
a9a	85.1	83.9	82.8
cod-rna	96.5	96.3	94.7
ijcnn1	96.0	95.1	92.2
real-sim	93.8	93.2	91.6
HIGGS	70.9	70.5	67.9
SUSY	81.7	81.3	77.5
abalone	4.4	4.4	5.8
cpusmall	8.5	9.2	12.6
space_ga	0.033	0.034	0.044
YearPredictionMSD	82.7	87.5	117.7

Table 5: Number of parameters and size of the models. $k = kernel_size$, s = stride, $n = client_tree_num = 500/client_num$.

	1-layer 1D CNN (k = s = n)		1-layer 1D CNN	2-laver FCNN	
	2 clients	5 clients	10 clients	(k = 3, s = 1)	2 myor r criti
Total params	16193	6,785	3905	32,257	128,513
F/b pass size (MB)	0.01	0.01	0.01	0.73	0.01
Params size (MB)	0.06	0.03	0.02	0.12	0.49
Total size (MB)	0.07	0.04	0.03	0.86	0.50

between our interpretable CNN and CNN with standard kernel size and stride. Also, the gap exaggerates as the dataset size increases. We argue that in addition to our reasoning in Section 3.3, it is because CNN can leverage the temporal information across the tree ensembles built by the clients, and our interpretable CNN has the right amount of temporal resolution (i.e., with kernel size = stride).

5 CONCLUSION AND FUTURE WORKS

We propose a novel framework, FedXGBllr, for horizontal federated XGBoost which does not rely on the sharing of gradients and hessians. Extensive evaluations prove our approach is robust, interpretable, and communication efficient. Specifically, we reach performance comparable to state-of-the-art method and reduce communication cost with factors ranging from 25x to 700x. We use FedAvg [24] in this work to learn the learnable learning rates by training a small one-layer 1D CNN. It is important to point out that more advanced FL training algorithms can also be applied and better performance may be achieved; however, we leave it for future studies as it is not the focus of this research. Future works also include extending FedXGBllr to vertical setting.

REFERENCES

- Avinash Barnwal, Hyunsu Cho, and Toby Dylan Hocking. 2020. Survival regression with accelerated failure time model in XGBoost. arXiv preprint arXiv:2006.04920 (2020).
- [2] Daniel J. Beutel, Taner Topal, Akhil Mathur, Xinchi Qiu, Titouan Parcollet, and Nicholas D. Lane. 2020. Flower: A Friendly Federated Learning Research Framework. arXiv preprint arXiv:2007.14390 (2020).
- [3] Kallista A. Bonawitz, Hubert Eichner, Wolfgang Grieskamp, Dzmitry Huba, Alex Ingerman, Vladimir Ivanov, Chloé Kiddon, Jakub Konečný, Stefano Mazzocchi, Brendan McMahan, Timon Van Overveldt, David Petrou, Daniel Ramage, and Jason Roselander. 2019. Towards Federated Learning at Scale: System Design. In Machine Learning and Systems.
- [4] Xiaomin Chang, Wei Li, and Albert Y. Zomaya. 2022. Fed-GBM: a cost-effective federated gradient boosting tree for non-intrusive load monitoring. In *International Conference on Future Energy Systems*. 63– 75.
- [5] Tianqi Chen and Carlos Guestrin. 2016. XGBoost: A Scalable Tree Boosting System (Conference on Knowledge Discovery and Data Mining). 785–794.
- [6] Kewei Cheng, Tao Fan, Yilun Jin, Yang Liu, Tianjian Chen, Dimitrios Papadopoulos, and Qiang Yang. 2021. SecureBoost: A Lossless Federated Learning Framework. *IEEE Intelligent Systems* (2021), 87–98.
- [7] Yiming Dou, Fengyu Yang, Yi Liu, Antonio Loquercio, and Andrew Owens. 2024. Tactile-Augmented Radiance Fields. In Conference on Computer Vision and Pattern Recognition.
- [8] Shuhui Fan, Haoran Xu, Shaojing Fu, and Ming Xu. 2020. Smart Ponzi Scheme Detection using Federated Learning. In *IEEE International Conference on High Performance Computing and Communications*. 881– 888.
- [9] Matt Fredrikson, Somesh Jha, and Thomas Ristenpart. 2015. Model Inversion Attacks that Exploit Confidence Information and Basic Countermeasures. In Conference on Computer and Communications Security. 1322–1333.
- [10] Léo Grinsztajn, Edouard Oyallon, and Gaël Varoquaux. 2022. Why do tree-based models still outperform deep learning on tabular data? arXiv preprint arXiv:2207.08815 (2022).
- [11] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2015. Delving deep into rectifiers: Surpassing human-level performance on ImageNet classification. In *IEEE International Conference on Computer Vision.* 1026–1034.
- [12] Katelinh Jones, Yuya Jeremy Ong, Yi Zhou, and Nathalie Baracaldo. 2022. Federated XGBoost on Sample-Wise Non-IID Data. arXiv preprint arXiv:2209.01340 (2022).
- [13] Peter Kairouz, H Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Kallista Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, et al. 2021. Advances and open problems in federated learning. *Foundations and Trends® in Machine Learning* (2021), 1–210.
- [14] Sai Praneeth Karimireddy, Satyen Kale, Mehryar Mohri, Sashank J. Reddi, Sebastian U. Stich, and Ananda Theertha Suresh. 2020. SCAF-FOLD: Stochastic Controlled Averaging for Federated Learning. In International Conference on Machine Learning. 5132–5143.
- [15] Diederik P. Kingma and Jimmy Ba. 2015. Adam: A Method for Stochastic Optimization. In International Conference on Learning Representations (ICLR).
- [16] Qinbin Li, Yiqun Diao, Quan Chen, and Bingsheng He. 2022. Federated Learning on Non-IID Data Silos: An Experimental Study. In *IEEE International Conference on Data Engineering*. 965–978.
- [17] Qinbin Li, Zeyi Wen, and Bingsheng He. 2020. Practical Federated Gradient Boosting Decision Trees. In AAAI. 4642–4649.

- [18] Tian Li, Anit Kumar Sahu, Manzil Zaheer, Maziar Sanjabi, Ameet Talwalkar, and Virginia Smith. 2020. Federated Optimization in Heterogeneous Networks. In *Machine Learning and Systems*.
- [19] Xiang Li, Kaixuan Huang, Wenhao Yang, Shusen Wang, and Zhihua Zhang. 2019. On the convergence of fedavg on non-iid data. arXiv preprint arXiv:1907.02189 (2019).
- [20] Xiang Li, Kaixuan Huang, Wenhao Yang, Shusen Wang, and Zhihua Zhang. 2020. On the Convergence of FedAvg on Non-IID Data. In International Conference on Learning Representations.
- [21] Xiaoxiao Li, Meirui Jiang, Xiaofei Zhang, Michael Kamp, and Qi Dou. 2021. FedBN: Federated Learning on Non-IID Features via Local Batch Normalization. In International Conference on Learning Representations.
- [22] Yang Liu, Zhuo Ma, Ximeng Liu, Siqi Ma, Surya Nepal, Robert H. Deng, and Kui Ren. 2020. Boosting Privately: Federated Extreme Gradient Boosting for Mobile Crowdsensing. In *IEEE International Conference* on Distributed Computing Systems. 1–11.
- [23] Chenyang Ma, Kai Lu, Ta-Ying Cheng, Niki Trigoni, and Andrew Markham. 2024. See, Imagine, Plan: Discovering and Hallucinating Tasks from a Single Image. arXiv preprint arXiv:2403.13438 (2024).
- [24] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Agüera y Arcas. 2017. Communication-efficient learning of deep networks from decentralized data. In *International Conference on Artificial Intelligence and Statistics*. 1273–1282.
- [25] Yuya Jeremy Ong, Yi Zhou, Nathalie Baracaldo, and Heiko Ludwig. 2020. Adaptive Histogram-Based Gradient Boosted Trees for Federated Learning. arXiv preprint arXiv:2012.06670 (2020).
- [26] Xinchi Qiu, Heng Pan, Wanru Zhao, Chenyang Ma, Pedro Porto Buarque de Gusmão, and Nicholas D. Lane. 2023. Efficient Vertical Federated Learning with Secure Aggregation. In Proceedings of the Federated Learning Systems (FLSys) Workshop at MLSys.
- [27] Xinchi Qiu, Heng Pan, Wanru Zhao, Chenyang Ma, Pedro P. B. de Gusmao, and Nicholas D. Lane. 2023. vFedSec: Efficient Secure Aggregation for Vertical Federated Learning via Secure Layer. arXiv preprint arXiv:2305.16794.
- [28] Sashank J. Reddi, Zachary Charles, Manzil Zaheer, Zachary Garrett, Keith Rush, Jakub Konečný, Sanjiv Kumar, and Hugh Brendan McMahan. 2021. Adaptive Federated Optimization. In *International Conference on Learning Representations.*
- [29] Ravid Shwartz-Ziv and Amitai Armon. 2022. Tabular data: Deep learning is not all you need. *Information Fusion* (2022), 84–90.
- [30] Zhihua Tian, Rui Zhang, Xiaoyang Hou, Jian Liu, and Kui Ren. 2020. FederBoost: Private Federated Learning for GBDT. arXiv preprint arXiv:2011.02796 (2020).
- [31] Daixin Wang, Yuan Qi, Jianbin Lin, Peng Cui, Quanhui Jia, Zhen Wang, Yanming Fang, Quan Yu, Jun Zhou, and Shuang Yang. 2019. A Semi-Supervised Graph Attentive Network for Financial Fraud Detection. In *IEEE International Conference on Data Mining*. 598–607.
- [32] Shaokai Wu and Fengyu Yang. 2023. Boosting Detection in Crowd Analysis via Underutilized Output Features. In Conference on Computer Vision and Pattern Recognition. 15609–15618.
- [33] Fuki Yamamoto, Seiichi Ozawa, and Lihua Wang. 2022. eFL-Boost: Efficient Federated Learning for Gradient Boosting Decision Trees. *IEEE Access* (2022), 43954–43963.
- [34] Fengyu Yang, Chao Feng, Ziyang Chen, Hyoungseob Park, Daniel Wang, Yiming Dou, Ziyao Zeng, Xien Chen, Rit Gangopadhyay, Andrew Owens, and Alex Wong. 2024. Binding Touch to Everything: Learning Unified Multimodal Tactile Representations. Conference on Computer Vision and Pattern Recognition.
- [35] Fengyu Yang and Chenyang Ma. 2022. Sparse and Complete Latent Organization for Geospatial Semantic Segmentation. In Conference on Computer Vision and Pattern Recognition. 1809–1818.

- [36] Fengyu Yang, Chenyang Ma, Jiacheng Zhang, Jing Zhu, Wenzhen Yuan, and Andrew Owens. 2022. Touch and Go: Learning from Human-Collected Vision and Touch. In *Conference on Neural Information Processing Systems Datasets and Benchmarks Track.*
- [37] Fengyu Yang, Jiacheng Zhang, and Andrew Owens. 2023. Generating Visual Scenes from Touch. International Conference on Computer Vision.
- [38] Mengwei Yang, Linqi Song, Jie Xu, Congduan Li, and Guozhen Tan. 2019. The Tradeoff Between Privacy and Accuracy in Anomaly Detection Using Federated XGBoost. arXiv preprint arXiv:1907.07157 (2019).
- [39] Hanbin Zhao, Fengyu Yang, Xinghe Fu, and Xi Li. 2022. RBC: Rectifying the Biased Context in Continual Semantic Segmentation. *European Conference on Computer Vision.*
- [40] Ligeng Zhu, Zhijian Liu, and Song Han. 2019. Deep Leakage from Gradients. In Advances in Neural Information Processing Systems. 14747– 14756.