Shunsuke Maeda ⊠©

Department of Pure and Applied Mathematics, Graduate School of Fundamental Science and Engineering, Waseda University, Japan

Yusuke Kaneko

Department of Applied Mathematics, School of Fundamental Science and Engineering, Waseda University, Japan

Hideaki Muramatsu

Department of Applied Mathematics, School of Fundamental Science and Engineering, Waseda University, Japan

Yukihiro Murakami 🖂 🗅

Delft Institute of Applied Mathematics, Delft University of Technology, The Netherlands

Momoko Hayamizu¹ \square \square

Department of Applied Mathematics, Faculty of Science and Engineering, Waseda University, Japan

— Abstract

Phylogenetic networks are used to represent the evolutionary history of species. They are versatile when compared to traditional phylogenetic trees, as they capture more complex evolutionary events such as hybridization and horizontal gene transfer. Distance-based methods such as the Neighbor-Net algorithm are widely used to compute phylogenetic networks from data. However, the output is necessarily an undirected graph, posing a great challenge to deduce the direction of genetic flow in order to infer the true evolutionary history. Recently, Huber *et al.* investigated two different computational problems relevant to orienting undirected phylogenetic networks into directed ones. In this paper, we consider the problem of orienting an undirected binary network into a tree-child network. We give some necessary conditions for determining the tree-child orientability, such as a tight upper bound on the size of tree-child orientable graphs, as well as many interesting examples. In addition, we introduce new families of undirected phylogenetic networks, the jellyfish graphs and ladder graphs, that are orientable but not tree-child orientable. We also prove that any ladder graph can be made tree-child orientable by adding extra leaves, and describe a simple algorithm for orienting a ladder graph to a tree-child network with the minimum number of extra leaves. We pose many open problems as well.

2012 ACM Subject Classification Applied computing \rightarrow Biological networks

Keywords and phrases Phylogenetic networks, tree-child networks, graph orientation problems

Funding Momoko Hayamizu: This work was supported by JST FOREST Program (Grant Number JPMJFR2135, Japan).

1 Introduction

Phylogenetics is a field that studies the evolutionary history and relationships among species. A widely used representation for these relationships is the phylogenetic tree, which shows the branching pattern of the evolutionary history. However, due to recombination and reticulate events, such as hybridization in plants and horizontal gene transfer in bacteria and viruses, the evolutionary relationships among species may not always follow a strictly tree-like pattern. In such cases, phylogenetic networks provide a more suitable representation [9].

¹ Corresponding author

The Neighbor-Net algorithm [2] is a popular approach to construct phylogenetic networks from distance data. It runs fast and always outputs a planar graph, making it easy to visualize biological data. However, the networks produced by this method are often complex and difficult to interpret, as they are undirected. In order to better understand the flow of genetic material among species, it is important to orient the edges of phylogenetic networks.

Despite its importance, the phylogenetic network orientation problem has received limited attention; conversely, the problem of orienting a phylogenetic tree has been investigated thoroughly [11, 15, 16]. In light of this, Huber et al. [8] recently proposed two types of problems for orienting undirected phylogenetic networks, along with solutions for each problem. The first problem called CONSTRAINED ORIENTATION asks one to determine if an undirected phylogenetic network can be oriented as a directed phylogenetic network, given a distinguished edge (called the root) and all in-degrees of each vertex. The idea is to subdivide the distinguished edge by a vertex and orient the edges incident to it away from the vertex. Because the in-degrees of each vertex are specified, one can then orient the edges of the whole network (if certain conditions are satisfied). Huber et al. proved that such an orientation is unique if it exists and provided a linear-time algorithm for computing an orientation from a given network. The second problem called C-ORIENTATION asks, given a binary undirected phylogenetic network N, whether there exists an orientation of N such that the resulting directed graph becomes a network of a desired class of directed phylogenetic networks. Huber et al. provided an FPT algorithm for solving the C-ORIENTATION problem, and also proved that the problem is NP-hard in the case when C is the class of so-called tree-based networks. Following this, Fischer and Francis [6] showed that one can characterize undirected tree-based networks as those that can be tree-base oriented.

In this paper, we discuss the C-ORIENTATION problem when C is a so-called tree-child network, *i.e.*, the problem of determining whether an undirected binary phylogenetic network can be rooted and oriented to be a tree-child network. Tree-child networks are prominent in the literature for its algorithmic ease of use (see, for example [14]), and as they can be biologically motivated as a class of networks in which every ancestor passes on genetic material to an extant species via means of vertical descent [3]. Here, we give necessary conditions for tree-child orientability in terms of number of edges as well as inter-leaf distances. Intuitively, our results imply that networks having too many edges, or networks in which leaves are pairwise too far apart cannot be tree-child oriented. Furthermore, we give two classes of undirected networks, called the jellyfish graph and the ladder graph. We show that jellyfish graphs cannot be tree-child oriented; we show that ladder graphs can only be tree-child orientable, we give a sharp lower bound on the number of leaves that must be added to make it tree-child orientable (Theorem 15).

The remainder of this paper is organized as follows. In Section 2, we set up the basic definitions and notation in the field of graph theory and combinatorial phylogenetics. In Section 3, we recall pertinent definitions and results regarding CONSTRAINED ORIENTATION and C-ORIENTATION. In Section 4, we give necessary conditions for the tree-child orientation problem. In Section 5, we give two classes of undirected networks, the jellyfish graph and the ladder graph, and explore their tree-child orientability. In Section 6, we discuss our results and provide open problems for future research.

2 Definitions and Notation

2.1 Graph theory

In this paper, we will only consider connected, finite, simple graphs, which we now define. A graph is an ordered pair (V, E) of a set V of vertices and a set E of edges between vertices. Given a graph G, its vertex-set and edge-set are denoted by V(G) and E(G), respectively. A graph G is said to be finite if V(G) and E(G) are finite sets. A directed graph is a graph where each edge has a direction associated with it, whereas an undirected graph is a graph where no edge has a direction. An edge of directed graph that is oriented from vertex u to vertex v is denoted by (u, v). An edge of undirected graph between vertices u and v is denoted by (u, v) or (v, u). A directed or undirected graph is simple if it contains neither loop (i.e. edge that starts and ends at the same vertex u) nor multiple edges (i.e. different edges (u, v), (u', v') with u = u', v = v'. Two simple graphs G_1 and G_2 are isomorphic if there exists a bijective function $\phi : V(G_1) \to V(G_2)$ such that $(u, v) \in E(G_1)$ if and only if $(\phi(u), \phi(v)) \in E(G_2)$. An undirected graph G is called the underlying graph of a directed graph \hat{G} if the undirected graph obtained by ignoring the direction of each edge of \hat{G} is isomorphic to G.

For a vertex v of an undirected graph G, the degree of v in G, denoted by $deg_G(v)$, is the number of edges incident to v. For a vertex v of a directed graph N, the *in-degree* of v in N, denoted by $indeg_N(v)$ or $d_N^-(v)$, is the number of edges incoming to v. Similarly, the out-degree of v, denoted by $outdeg_N(v)$ or $d_N^+(v)$, is the number of edges outgoing from v. A directed path is a directed graph G that can be represented by an alternating sequence of vertices and consecutive edges $v_1, (v_1, v_2), v_2, \ldots, (v_{k-1}, v_k), v_k$, where all vertices are distinct and we have $(indeg_G(v_1), outdeg_G(v_1)) = (0, 1), (indeg_G(v_k), outdeg_G(v_k)) = (1, 0)$ and $(indeg_G(v_i), outdeg_G(v_i)) = (1, 1)$ for any vertex v_i other than v_1, v_k . A directed cycle is a graph C that satisfies the above conditions except that $v_1 = v_k$ and we have $indeg_C(v_i) = outdeg_C(v_i) = 1$ for any vertex v_i . A directed graph containing no directed cycle is acyclic.

The concepts of path, cycle, and acyclic graphs are defined similarly for undirected graphs. An undirected graph is *connected* if there exists a path between any pair of vertices, whereas a directed graph G is *(weakly) connected* if the underlying graph of G is connected. Given two vertices u, v of a connected undirected graph G, the *distance* between u and v, denoted by $d_G(u, v)$, is the number of the edges in the shortest path between them.

2.2 Phylogenetic networks

Throughout the paper, X denotes a finite set with $|X| \ge 2$ that can be biologically interpreted as a set of present-day species. The set X is often referred to as a "label set" because each element of X is used to label a vertex of a graph. Recall that all networks considered here are connected, finite, simple graphs.

An undirected binary phylogenetic network N (on X) is a directed acyclic graph such that i) $X = \{v \in V(N) \mid deg_N(v) = 1\}$ and ii) for any $v \in V(N) \setminus X$, $deg_N(v) = 3$. The vertices in X are called *leaves* of N. We call an undirected phylogenetic network non-binary if it is not necessarily binary, i.e. if the above condition ii) is generalized as follows: for any non-leaf vertex v, $deg_N(v) \ge 3$. Note that we have defined undirected phylogenetic networks in such a way that they do not have degree-two vertices, simply by convention. It is possible to allow a finite number of degree-two vertices to exist, because their existence is trivial when orienting undirected phylogenetic networks (the formal definitions related to orientation will

be given in Section 3).

A directed binary phylogenetic network \hat{N} on X is a undirected acyclic graph such that i) $X = \{v \in V(N) \mid (indeg_N(v), outdeg_N(v)) = (1,0)\}$; ii) there exists a unique vertex $\rho \in V(\hat{N})$ with $(indeg_{\hat{N}}(\rho), outdeg_{\hat{N}}(\rho) = (0,2)$; iii) for any $v \in V(\hat{N}) \setminus (X \cup \{\rho\})$, $(indeg_{\hat{N}}(v), outdeg_{\hat{N}}(v)) \in \{(1,2), (2,1)\}$. The vertex ρ is called the root of \hat{N} , and the vertices in X are called *leaves* of \hat{N} . Each vertex of in-degree two is called a *reticulation*, while each non-leaf vertex of in-degree one is called a *tree vertex*. We call a directed phylogenetic network non-binary if it is not necessarily binary, i.e. if the condition iii) is generalized as follows: for any non-leaf non-root vertex v, $indeg_N(v) + outdeg_N(v) \ge 3$. The same remark regarding the definition of undirected non-binary networks also applies to the definition of directed non-binary networks.

Given an edge (u, v) of a directed phylogenetic network \hat{N} , u is a *parent* of v, and v is a *child* of u. A directed binary phylogenetic network \hat{N} is called a *tree-child network* if each non-leaf vertex of \hat{N} is a parent of either a tree vertex or a leaf of \hat{N} [4]. See Figure 1 for examples.



Figure 1 Examples of directed binary phylogenetic networks on $X = \{x_1, x_2, x_3, x_4, x_5\}$. The network shown in (a) is a tree-child network. The network shown in (b) is not a tree-child network.

3 Known results on orienting phylogenetic networks

Orienting undirected phylogenetic networks could find many biological applications in the future, but currently its mathematical and computational aspects are still at an early stage of research. In this section, we briefly recall the necessary definitions and summarize relevant results from Huber *et al.* [8], and then describe the problem we will consider in this paper.

3.1 Terminology: rooting and orienting phylogenetic networks

In the usual context of graph theory, given an undirected graph G, "orienting" G typically refers to the operation of creating a directed graph \hat{G} by orienting each edge of G, and \hat{G} is called an "orientation" of G. However, we must stress that, when it comes to an undirected phylogenetic network, the term "orienting" may refer to a different operation. More precisely, given a (not necessarily binary) undirected phylogenetic network N, Huber *et al.* [8] defined the operation of *orienting* N as the following procedure (see Figure 2(a)(b) and Figure 3(a)(b) for an illustration): 1) choose a unique edge e_{ρ} of N called a *root edge*; 2) insert the root ρ into e_{ρ} (the resulting graph is denoted by N_{ρ}); 3) assign a direction to each edge of N_{ρ} . In other words, orienting an undirected phylogenetic network N means orienting the root-inserted graph N_{ρ} , not of the original graph N.

We say that a directed phylogenetic network \hat{N} is an *orientation* of an undirected phylogenetic network N if it is possible to obtain \hat{N} by orienting N. If N is a tree, choosing

a root edge e_{ρ} automatically determines the directions of all edges of N_{ρ} , but in general, rooting N does not specify an orientation of \hat{N} . Therefore, to avoid ambiguity, we modify the terminology in Huber *et al.* [8]. In this paper, we will use the term *rooting* N to mean the process of selecting e_{ρ} and creating N_{ρ} from N, and *orienting* N to mean the entire process of rooting N and then assigning a direction to each edge of N_{ρ} . Strictly speaking, the rooting step can be seen as yielding a partially directed graph N'_{ρ} , because the root ρ automatically determines the direction of the two edges starting from ρ ; however, the only difference between N_{ρ} and N'_{ρ} is whether the two edges are assigned the obvious directions or not, so in this paper we use the same symbol N_{ρ} without distinguishing between them.

3.2 Orientation constrained by the root edge and in-degrees

The CONSTRAINED ORIENTATION is an orientation problem under the constraints of the position of the root edge e_{ρ} and the desired $indeg_{\hat{N}}(v)$ of each vertex (see also Figure 2).

▶ **Problem 1.** (CONSTRAINED ORIENTATION)

- **Input:** An undirected non-binary phylogenetic network N = (V, E) on X, an edge $e_{\rho} \in E$ into which a unique root ρ is inserted, and a labeling map $\delta_N^-: V \to \mathbb{N}$ that specifies $indeg_{\hat{N}}(v)$ for each vertex $v \in V$.
- **Output:** An orientation \hat{N} of $(N, e_{\rho}, \delta_N^-)$ if it exists, and NO otherwise.

Huber *et al.* [8] introduced the notion of a degree cut, which is the key ingredient for characterizing orientability. The notion of a degree cut is illustrated in Figure 2(d).

▶ Definition 2. Let N = (V, E) be an undirected non-binary phylogenetic network on X with $e_{\rho} \in E$ a distinguished edge, and let $N_{\rho} = (V_{\rho}, E_{\rho}, X)$ be the graph obtained from N by subdividing e_{ρ} by a new vertex ρ . Given the desired in-degree $d_{N}^{-}(v)$ of each vertex $v \in V$, a degree cut for (N, e_{ρ}, d_{N}^{-}) is an ordered pair (V', E') with $V' \subseteq V$ and $E' \subseteq E_{\rho}$ such that the following hold in N_{ρ} :

- 1. E' is an edge cut of N_{ρ} ; i.e. its removal makes N_{ρ} into a disconnected graph $N_{\rho} \setminus E'$ that consists of two or more connected components;
- **2.** ρ is not in the same connected component of $N_{\rho} \setminus E'$ as any $v \in V'$;
- **3.** each edge in E' is incident to exactly one element of V'; and
- 4. each vertex $v \in V'$ is incident to at least one and at most $d_N^-(v) 1$ edges in E'.

In particular, when N is binary, a degree cut is called a reticulation cut.

▶ **Theorem 3** (Theorems 1 and 2 in [8]). Let N = (V, E, X) be an undirected non-binary phylogenetic network, $e_{\rho} \in E$ be a distinguished edge, and $d_N^-(v)$ be the desired in-degree of each vertex $v \in V$, where $1 \leq d_N^-(v) \leq d_N(v)$. Then, the following statements hold.

- 1. N has an orientation \hat{N} that satisfy the constraints (e_{ρ}, d_{N}^{-}) if and only if (N, e_{ρ}, d_{N}^{-}) has no degree cut and $\sum_{v \in V} d_{N}^{-}(v) = |E| + 1$. (For binary N, $\sum_{v \in V} d_{N}^{-}(v) = |E| + 1$ is equivalent to |R| = |E| |V| + 1, where R is the set of vertices v with $d_{N}^{-}(v) = 2$.)
- **2.** Algorithm 1 in [8] decides whether \hat{N} exists, and finds \hat{N} if it exists both in O(|E|) time.
- **3.** If it exists, \hat{N} is the unique orientation of N under the constraints (e_{ρ}, d_{N}^{-}) .

3.3 Orientation to a desired class C of networks

Problem 1 was the problem of orienting an undirected graph under constraints on the position of the root edge and on the desired in-degree of each vertex. The next problem, called C-ORIENTATION, is an orientation problem with different constraints. This problem asks



Figure 2 An illustration of the Constraint Orientation Problem. (a) An undirected phylogenetic network N with a distinguished root edge e_{ρ} . (b) A phylogenetic network N_{ρ} obtained by inserting the root vertex ρ into e_{ρ} . (c) A phylogenetic network N with the constraints (e_{ρ}, d_N^-) , where the root edge e_{ρ} is chosen as in (a), and each vertex v is labeled by the desired in-degree $d_N^-(v)$. (d) If we let V' be the set of white vertices and E' be the set of dashed-line edges, then (V', E') is a degree cut for (N, e_{ρ}, d_N^-) (Definition 2). Then, the first statement in Theorem 3 tells us that there exists no feasible orientation of N under the constraint (e_{ρ}, d_N^-) .

whether a given graph can be oriented to be a directed phylogenetic network belonging to a desired class C, where the position of the root edge and the degree of entry of each vertex are unknown. Huber *et al.* [8] considered the C-orientation problem under the assumption that the input graph N is binary, unlike Problem 1.

▶ **Problem 4.** (*C*-ORIENTATION)

INPUT: An undirected binary phylogenetic network N on X, and a class C of directed binary phylogenetic network on X.

OUTPUT: A C-orientation \hat{N} of N if it exists, and NO otherwise.

As there are |E| ways to choose the root edge and $\binom{|V|}{|R|}$ ways to choose the |R| reticulations among |V| vertices, they described a simple exponential time to determine whether N is C-orientable or not, by checking all possible cases using the linear-time algorithm for solving Problem 1. They gave an FPT algorithm for a particular C satisfying several conditions, and also proved that the C-orientation problem is NP-complete when C is the class of tree-based networks. However, it is still not yet well understood for which class C the C-orientation problem is NP-complete or solvable in polynomial time.

We must emphasize that if the class C' is a subclass of C, this does not implies that C'-orientation is easier or harder than C-orientation. This motivates us to study the following problem.

▶ **Problem 5.** (*TREE-CHILD ORIENTATION*)

INPUT: An undirected binary phylogenetic network N on X and the class C of tree-child networks on X.

OUTPUT: A tree-child orientation \hat{N} of N if it exists, and NO otherwise.

We say that an undirected binary phylogenetic network N is tree-child orientable if \hat{N} in Problem 5 exists and call such an orientation \hat{N} a tree-child orientation of N (see Figure 3).

4 Necessary Conditions for Tree-Child Orientability

There is no previous study that has focused on Problem 5 so far. In this section, we will give some necessary conditions to ensure that N is tree-child orientable.



Figure 3 (a) An example of a tree-child orientable network N. (b) A tree-child orientation \hat{N} of N, where the black pentagon is the root ρ and white circles are reticulations. (c),(d) Examples of undirected graphs that are orientable to some phylogenetic networks but not tree-child orientable.

4.1 The number of edges of tree-child orientable graphs

We recall the following useful result together with its proof from [13] as it clarifies the relationships between the numbers of reticulations, tree vertices, leaves, and edges of directed binary phylogenetic networks.

▶ **Proposition 6** ([13, Lemma 2.1]). Let N = (V, A) be any directed binary phylogenetic network on X that has |X| leaves, r reticulations, t tree vertices and the root ρ with $outdeg(\rho) = 2$. Then, we have t = |X| + r - 2, |V| = 2t + 3, and |A| = 3r + 2|X| - 2.

Proof. Note first that |V| = r + |X| + t + 1. The hand-shaking lemma for directed graphs states that the sum of the out-degrees equals the number |A| of edges which, in turn, equals the sum of the in-degrees. Thus, we have r + 2t + 2 = |A| = 2r + t + |X|, which yields t = r + |X| - 2. The other equations follow easily. This completes the proof.

▶ **Proposition 7** ([4, Proposition 1]). For a directed binary phylogenetic network N on X with r reticulations, if N is a tree-child network, then $r \leq |X| - 1$ holds.

▶ Lemma 8. If \hat{N} is a directed binary phylogenetic network on X, then, at least one of the children of the root ρ of \hat{N} is a tree vertex.

Proof. By Theorem 3 in Huber *et al.* [8], if both children of ρ were reticulations, there would exist a reticulation cut as shown in Figure 4.



Figure 4 Proof of Lemma 8. The black vertex is the root and the white circles are reticulations. The set of the two edges in dotted line, together with the set of the two reticulations, forms a "reticulation cut", which is not allowed to exist in orientable networks by Theorem 3 in Huber *et al.* [8].

▶ **Theorem 9.** If a binary undirected phylogenetic network N = (V, E) on X is tree-child orientable, then $|E| \le 5|X| - 6$ holds. Moreover, this upper bound is tight.

Proof. If $\hat{N} = (\hat{V}, \hat{E})$ is a tree-child orientation of N, then $|\hat{E}| = |E| + 1$ holds because orienting N to \hat{N} involves the operation of inserting a root into an edge of N, i.e. subdividing an edge of N exactly once. The proof will be completed if we can show that $|\hat{E}| \leq 5|X| - 5$. Let r be the number of reticulations of \hat{N} . Then, Proposition 6 gives $|\hat{E}| = 2|X| + 3r - 2$,

and Proposition 7 gives $r \leq |X| - 1$. Thus, we obtain $|\hat{E}| \leq 2|X| + 3(|X| - 1) - 2 = 5|X| - 5$. The network in Figure 5 ensures the tightness of this bound. This completes the proof.



Figure 5 An example that shows the bound in Theorem 9 is tight. Left: a binary phylogenetic network with |X| = 3 leaves and 5|X| - 6 = 9 edges. Right: a tree-child orientation of the network (open circles represent reticulation vertices).

The condition given in Theorem 9 is not a sufficient condition but it is practically useful to check the tree-child orientability. For example, we can immediately see that the two graphs in Figure 3(c)(d) are not tree-child orientable.

4.2 The shortest-path distances between leaves and implications for appropriate rooting

Tree-child networks are a subclass of cherry-picking networks (also known as orchard networks) that were introduced in [5, 10]. Therefore, tree-child orientable networks need to be orchard-orientable. For the reader's convenience, we now recall the definitions of cherries and reticulated cherries from [1] as follows (see Figure 6 for an illustration).

Let \hat{N} be a directed binary phylogenetic network. A cherry of \hat{N} is a pair $\{x_i, x_j\}$ of leaves such that the parent x'_i of x_i and the parent x'_j of x_j are the same vertex of \hat{N} . A reticulated cherry of \hat{N} is a pair $\{x_i, x_j\}$ of leaves such that there exists an undirected path with two internal vertices between x_i and x_j in the underlying graph N, exactly one of which is a reticulation.



Figure 6 An illustration of a cherry and reticulated cherry (solid lines). In the above network, $\{(x_1, x_2)\}$ is a reticulated cherry and $\{(x_4, x_5)\}$ is a cherry.

▶ Proposition 10 ([1, Lemma 4.1]). Let N be a binary tree-child network on X. If $|X| \ge 2$, then N contains either a cherry or a reticulated cherry.

From the above lemma, we obtain the following result.

▶ Proposition 11. Let N be an undirected phylogenetic network on X. If N does not have leaves $x, x' \in X$ with either $d_N(x, x') = 2$ or $d_N(x, x') = 3$, then N is not tree-child orientable.

Proof. By Proposition 10, tree-child networks have a pair of leaves which is called cherry or reticulated cherry. This means that if N does not have a pair of leaves that are at a distance of 2 or 3 from each other, then N is not tree-child orientable. This completes the proof.

The condition in Proposition 11 is useful for appropriate rooting for tree-child orientation. For example, given the undirected graph in Figure 7, one can easily choose a right root edge e_{ρ} for tree-child orientation using the distance condition.



Figure 7 The possible choices (up to symmetry) for the root edge e_{ρ} for a tree-child orientable graph. It is possible to create a tree-child network if the root is introduced as in (a)–(d), but not if the root is placed as in (e)–(g).

4.3 The number of reticulation vertices

Even if we want to orient an undirected binary phylogenetic network N on X to any directed binary phylogenetic network \hat{N} on X without considering the tree-child property of \hat{N} , we must carefully determine which vertices of N are to be reticulations in \hat{N} . Fortunately, however, the number |R| of reticulations in \hat{N} is automatically determined by N and can be easily computed. The reticulation number R can be expressed by different formulas (for example, Proposition 6 gives $|R| = \frac{1}{3}(|E| - 2|X| + 3)$), but the following is more widely known. This can be proved by different proofs but we omit the proof because it is included in the first condition of Theorem 3.

▶ Proposition 12. For any undirected binary phylogenetic network N = (V, E) on X and for any orientation \hat{N} of N, the number |R| of reticulations in \hat{N} is given by |R| = |E| - |V| + 1.

Note that |E| - |V| + 1 is the minimum number of edges that need to be removed from a connected undirected graph G = (V, E) to make G a tree. This quantity is referred to using different terminology such as the circuit rank, the dimension of the cycle space, the first Betti number, and so on.

5 Undirected binary phylogenetic networks that are orientable but not tree-child orientable

In this Section, we introduce classes of undirected phylogenetic networks that are orientable but not tree-child orientable.

5.1 The jellyfish graph

The jellyfish graph J_k $(k \ge 1)$ is an undirected binary phylogenetic network on $X = \{x_1, \ldots, x_k\}$ with 2k + 6 vertices and 2k + 9 edges, where the neighbor x'_i of each leaf x_i forms a path x'_1, \ldots, x'_k as described in Figure 8. We will show that the jellyfish graph is orientable but not tree-child orientable.



Figure 8 Left: The jellyfish graph J_1 with one leaf. Right: The jellyfish graph J_5 with five leaves.

▶ Lemma 13. Let J_k be a jellyfish graph with a leaf-set $X = \{x_1, \ldots, x_k\}$ and the set $X' := \{x'_1, \ldots, x'_k\}$ of neighbors of the leaves. Then, X' contains at most one reticulation in any orientation \hat{J}_k of J_k .

Proof. We use J_5 in Figure 9 but the proof is the same for any k. Suppose the root edge e_{ρ} is neither a pendant edge (x_i, x'_i) nor an edge (x'_i, x'_{i+1}) between pendant edges, as shown in the left of Figure 9. Any directed path from ρ to a leaf x_i must include either the edge incoming to x'_1 or the edge incoming to x'_5 . Suppose x'_3 is a reticulation as described in the figure. Then, since the graph is binary, this specifies the direction of each solid-line edge, making any x'_i other than x'_3 a vertex with out-degree 2. Thus, we can conclude that there exists at most one reticulation among x'_i 's (white circle). When the root is inserted in a pendant edge (x_i, x'_i) or an edge (x'_i, x'_{i+1}) as described in the right of Figure 9, we obtain the same conclusion by a similar argument. This completes the proof.

▶ Theorem 14. The jellyfish graph J_k is not tree-child orientable for any $k \in \mathbb{N}$.

Proof. We use J_5 in Figure 9 but the proof is the same for any k. Let \hat{J}_k be any orientation of J_k . By Proposition 12, \hat{J}_k has exactly four reticulations. Let X and X' be as in Lemma 13. Lemma 13 allows us to focus on the following two cases. Case 1: When X' contains exactly one reticulation as in Figure 10. Case 2: When X' contains no reticulation as in Figure 11. Taking the symmetry of the jellyfish graph into account, we see that all the possibilities are listed in these figures. Recall that we cannot insert the root ρ in an edge whose ends are both reticulations (Lemma 8). As can be verified easily, regardless of the choice of the root edge e_{ρ} , each option ends up with having a forbidden configuration of tree-child networks (i.e. adjacent reticulations or a tree vertex with two reticulation children). Thus, the jellyfish graph is orientable but not tree-child orientable. This completes the proof.

5.2 The ladder graph

A ladder graph L_k is the undirected binary phylogenetic network on $X = \{a, b, c, d\}$ with vertices $\{t_i, b_i : i \in [k+1] = \{1, 2, \dots, k+1\}\}$ with paths $a t_1 \dots t_{k+1} c$ and $b b_1 \dots b_{k+1} d$,



Figure 9 Proof of Lemma 13. White vertices indicate reticulations.



Figure 10 Proof of Proposition 14 (Case 1).

together with edges $\{(t_i, b_i) : i \in [k]\}$ (see Figure 12 (a) for a ladder graph L_5). Observe that k = |E| - |V| + 1. It is easy to check that L_k (with 4 leaves) is tree-child orientable if and only if $k \leq 3$. However, as shown in Figure 12 (c)(d), it is possible to make L_k with $k \geq 4$ tree-child orientable by adding extra leaves at appropriate places. In this section, we will show that any L_k with $k \geq 4$ can be converted into a tree-child orientable ladder graph by adding extra leaves at appropriate places.

▶ **Theorem 15.** Let L_k be a ladder graph on leaves $\{a, b, c, d\}$ as described before. Then, one can construct a tree-child orientable network N from L_k by adding exactly k-3 leaves, but not by adding k-4 or fewer leaves.



Figure 11 Proof of Proposition 14 (Case 2).



Figure 12 (a) A ladder graph L_5 with five cycles, which is not tree-child orientable by Theorem 9. (b) A ladder obtained from L_5 by adding one extra leaf x_1 , which is still not tree-child orientable. (c) A ladder obtained by adding two extra leaves x_1 and x_2 , which is tree-child orientable as shown in (d).

Proof. We describe an algorithm for constructing a tree-child orientable network N by adding exactly k - 3 extra leaves to N. See Figure 13 for the construction.

Set the root edge $e_{\rho} := (t_{k-2}, b_{k-2})$. The idea is to place k-4 leaves to one side of e_{ρ} and 1 leaf to the other side of e_{ρ} . As for reticulations, we place k-3 reticulations to one side, 2 reticulations to the other side, and one on e_{ρ} itself (i.e. exactly one of t_{k-2} and b_{k-2} will be a reticulation in the orientation). Add leaf x_1 to edge (b_1, b_2) . Add leaf x_{2j} to edge (t_{2j+1}, t_{2j+2}) for $j = 1, 2, \ldots, \lceil \frac{k-3}{2} - 1 \rceil$. Add leaf x_{2j+1} to edge (b_{2j+2}, b_{2j+3}) for $j = 1, 2, \ldots, \lfloor \frac{k-3}{2} - 1 \rfloor$. If k is odd, add a leaf x_{k-3} to edge (b_k, b_{k+1}) and if k is even, add a leaf x_{k-3} to edge (t_k, t_{k+1}) . In total, we have added k-3 leaves to L_k . To show the resulting graph N is tree-child orientable, we now specify k vertices to be reticulations, and obtain a tree-child orientation \hat{N} . Let p_{x_i} denote the neighbour of leaf x_i for each $i \in [k-3]$. We let p_{x_1} be a tree vertex and let p_{x_i} be a reticulation for $i = 2, \ldots, k - 4$. We let b_1, b_2 be reticulations. If k is odd, let t_{k-2}, b_k, b_{k+1} be reticulations; if k is even, let b_{k-2}, t_k, t_{k+1} be reticulations. This allocation of the root and reticulations yields an orientation \hat{N} of the ladder graph N (and \hat{N} is unique for this allocation by Theorem 3). To see that \hat{N} is a tree-child network, observe that no two reticulations are adjacent and no two reticulations at distance 2 have a common parent in \hat{N} . Theorem 9 implies that at least k-3 additional leaves are necessary to obtain a tree-child orientable network. This completes the proof.



Figure 13 Proof of Theorem 15. An illustration for the case of k = 10. The open circles represent the vertices specified as reticulations.

We note that, unlike the case shown in Figure 12 (d), the ladder graph in Figure 14 is not tree-child orientable although it satisfies the necessary conditions for the tree-child orientability described in Theorem 9 and in Proposition 11.



Figure 14 An example of a ladder graph with additional leaves that is not tree-child orientable. If the position of the leaf x_3 is changed from the edge (u_6, u_{10}) to (u_{12}, u_{14}) , it becomes tree-child orientable (as shown in Figure 12 (d)).

6 Conclusion and open problems

In this paper, we have discussed the Problem 5 (TREE-CHILD ORIENTATION), which asks, given an undirected phylogenetic network N, whether it is possible to orient N to a tree-child network \hat{N} . To the best of our knowledge, this is the first study to focus on the tree-child orientation problem. While a characterization of tree-child orientable graphs is remains open, we have obtained several necessary conditions for the tree-child orientable graphs. In addition, based on the recent work of Huber *et al.* [8] on Problem 1 (CONSTRAINED ORIENTATION), we introduced new families of undirected phylogenetic networks, the jellyfish graphs and ladder graphs, which are orientable but not tree-child orientable. We also proved that any ladder graph can be made tree-child orientable by adding extra leaves, and described an algorithm for converting a ladder graph into a tree-child network with the minimum number of extra leaves.

While we conjecture that TREE-CHILD ORIENTATION is NP-complete, there are many other interesting directions for future research. What is a necessary and sufficient condition for tree-child orientable networks? This question is still interesting even if we restrict our attention to planar graphs, since a tree-child network is not necessarily planar (see the network in Figure 15). So which planar graphs are tree-child orientable? It is easy to see that undirected non-binary phylogenetic cactuses (defined in [7]) are tree-child orientable, but what about a more general subclass of planar graphs (e.g. outer-labeled planar graphs that are constructed by the Neighbor-Net algorithm)?

— References

¹ Magnus Bordewich and Charles Semple. Determining Phylogenetic Networks from inter-taxa distances. *Journal of Mathematical Biology*, 73(2):283–303, 2016.



Figure 15 An example of a non-planar tree-child phylogenetic network. Indeed, the graph is a directed binary tree-child network (i.e. each non-leaf vertex has at least one child that is a tree vertex) and also contains a subgraph that is homeomorphic to $K_{3,3}$. By Kuratowski's Theorem [12], the graph is not planar.

- 2 David Bryant and Vincent Moulton. Neighbor-net: an agglomerative method for the construction of phylogenetic networks. *Molecular biology and evolution*, 21(2):255–265, 2004.
- 3 Gabriel Cardona, Francesc Rossello, and Gabriel Valiente. Comparison of Tree-child Phylogenetic Networks. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 6(4):552–569, 2009. doi:10.1109/TCBB.2007.70270.
- 4 Gabriel Cardona, Francesc Rossello, and Gabriel Valiente. Comparison of Tree-Child Phylogenetic Networks. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 6(4):552–569, 2009.
- 5 Péter L Erdős, Charles Semple, and Mike Steel. A class of phylogenetic networks reconstructable from ancestral profiles. *Mathematical biosciences*, 313:33–40, 2019.
- 6 Mareike Fischer and Andrew Francis. How tree-based is my network? Proximity measures for unrooted phylogenetic networks. *Discrete Applied Mathematics*, 283:98–114, 2020.
- 7 Momoko Hayamizu, Katharina T Huber, Vincent Moulton, and Yukihiro Murakami. Recognizing and realizing cactus metrics. *Information Processing Letters*, 157:105916, 2020.
- 8 Katharina T. Huber, Leo van Iersel, Remie Janssen, Mark Jones, Vincent Moulton, Yukihiro Murakami, and Charles Semple. Orienting undirected phylogenetic networks, 2019. https: //arxiv.org/abs/1906.07430. doi:10.48550/ARXIV.1906.07430.
- 9 Daniel H. Huson, Regula Rupp, and Celine Scornavacca. Phylogenetic networks: concepts, algorithms and applications. Cambridge University Press, 2010.
- 10 Remie Janssen and Yukihiro Murakami. On cherry-picking and network containment. Theoretical Computer Science, 856:121–150, 2021.
- 11 Tonny Kinene, J Wainaina, Solomon Maina, and LM Boykin. Rooting trees, methods for. Encyclopedia of Evolutionary Biology, page 489, 2016.
- 12 Casimir Kuratowski. Sur le probleme des courbes gauches en topologie. Fundamenta mathematicae, 15(1):271–283, 1930.
- 13 Colin McDiarmid, Charles Semple, and Dominic Welsh. Counting Phylogenetic Networks. Annals of combinatorics, 19(1):205–224, 2015.
- 14 Charles Semple. Phylogenetic networks with every embedded phylogenetic tree a base tree. Bulletin of mathematical biology, 78(1):132–137, 2016.
- 15 Fernando Domingues Kümmel Tria, Giddy Landan, and Tal Dagan. Phylogenetic rooting using minimal ancestor deviation. Nature ecology & evolution, 1(7):0193, 2017.
- 16 Leo Van Iersel, Steven Kelk, Georgios Stamoulis, Leen Stougie, and Olivier Boes. On unrooted and root-uncertain variants of several well-known phylogenetic network problems. *Algorithmica*, 80:2993–3022, 2018.