
REVERSIBLE NUMERIC COMPOSITE KEY (RNCK)

A PREPRINT

 Nicola Asuni*

Tecnick.com LTD

Reading, UK

nicola.asuni@tecnick.com

June 8, 2023

ABSTRACT

In database design, Composite Keys are used to uniquely identify records and prevent data duplication. However, they require more memory and storage space than single keys, and can make queries more CPU-intensive. Surrogate Keys are an alternative that can overcome some of these limitations, but they can also introduce new disadvantages.

To address these challenges, a new type of key called a *Reversible Numeric Composite Key* (RNCK) has been developed. RNCK is a single number that encodes multiple data attributes, and can be decoded back to the original values. This makes it possible to achieve the benefits of both Composite Keys and Surrogate Keys, while overcoming some of their limitations.

RNCK has been shown to improve query performance and reduce memory and storage requirements. It can be used in relational databases, large static datasets, and key-value caching systems. RNCK has been successfully used in production systems for several years.

Keywords RNCK · Reversible Numeric Composite Key · composite key · data mining · database · decoding · encoding · hash · hashing · high-performance · hpc · software · surrogate key

1 Introduction

In data modeling, or database design, a Composite Key is a unique identifier made up of two or more attributes (database table columns). For example, a book record might be identified by its ISBN code, title, and author. These attributes cannot be used individually to identify a book. The ISBN code alone is not a unique identifier, because there could be two or more books with the same code. However, no two books will have the same combination of these attributes.

Composite Keys [1] generally help maintain data integrity and prevent data duplication. Compared to Surrogate Keys [2], which are artificial keys that are not based on real-world data, Composite Keys are easy to implement because they can be created using existing attributes that are often Natural Keys [3]. However, when a Composite Key is referenced in multiple data sets (database tables) as a Foreign Key [4], it uses more memory or storage space, as multiple attributes (columns) are required instead of just possibly one. This leads to a more complex schema. Queries become CPU-intensive, as every search and join requires comparing multiple attributes instead of just one in the case of a single key.

Surrogate Keys can overcome some of the Composite Key limitations at the expense of introducing other disadvantages. Surrogate Keys do not provide any information about the represented data, making it difficult to understand and interpret the data. They must be generated and maintained separately from the data they represent, in what can be an error-prone process. They may require more storage space for the creation of additional natural attribute indexes in order to avoid duplications and full table scans when fulfilling likely queries.

The performance of queries, including memory consumption, is also affected by the type of each attribute.

*<https://nicola.asuni.xyz>

Comparing integer numerical types is a very well-optimized operation in current computer architectures. Most current CPUs can perform multiple uint64 comparisons at the same time using SIMD (Single Instruction, Multiple Data) instructions. Generally, a x86 CPU with 16 computing cores can perform a theoretical maximum of 32 uint64 comparisons per clock cycle. With a 5.0 GHz CPU, this is a theoretical maximum of 160 billion comparisons per second. The actual number of uint64 comparisons that can be performed per second will depend on other factors, including the specific application and the number of other tasks that the CPU is running.

In contrast with the simplicity and high-performance of numerical comparisons, string comparisons are a slow operation, especially for large strings. This is because strings are typically stored as arrays of characters and each character must be compared individually. This is assuming the best scenario where each string has already been normalized to a common canonical form. This is not necessarily common, more complex and expensive comparisons can be required. Alternatively, string comparisons can be performed more efficiently by using a hash table, but this can introduce some disadvantages like space complexity, collisions, load factor, and hash function performance [5].

To combine the advantages of Composite Keys (CKs) and Surrogate Keys (SKs) while overcoming some of their limitations, a *Reversible Numeric Composite Key* (RNCK) is presented here.

RNCK can be used only in certain cases, when the total number and maximum size of CK attributes is relatively small. RNCK encodes one or more attributes into a number, such that it is possible to directly and efficiently decode the original attributes while preserving some attribute sorting and searching properties. In general, compared to CKs and SKs, the use of RNCK allows to increase query performance while reducing memory and storage requirements.

In addition to relational databases, RNCK can be a very effective index in large static datasets and key-value caching systems.

2 Definition

A Reversible Numeric Composite Key (RNCK) is a single number that uniquely represents a Composite Key (CK) or a single non-numeric Natural Key.

The RNCK number is generated from one or more data attributes using an encoding function. The code that is generated can be directly reversed to the original attributes using a decoding function. The encoding and decoding functions are bijective.

The RNCK format is designed to make encoding and decoding operations fast and inexpensive.

3 Normalization

Before encoding, a normalization step may be required to ensure a consistent and unambiguous representation of the CK attributes. For example, Unicode strings should be normalized to a canonical form.

Small in-memory lookup tables can be used by the encoding and decoding functions to efficiently enumerate limited attribute sets.

4 Format

In performance-focused applications, RNCK is typically a 64-bit unsigned integer (uint64), as this is natively supported by most current hardware platforms. Other data types compatible with binary operations can also be used, such as uint32 or uint128, if they are available.

A RNCK follows a binary pattern, where distinct sections of the binary number (groups of bits) represent different attributes or combinations of them. The binary sections are organized from the Most Significant Bit (MSB) to the Least Significant Bit (LSB) in the order of the sorting priority of each attribute. This allows sorting by RNCK to be equivalent to sorting by the attributes in order.

The number of bits required for each section is calculated from the maximum number of distinct possible values of the corresponding attribute. For example, for an attribute with a maximum of 100 distinct values (including the null value), a binary section of at least $\lceil \log_2(100) \rceil = 7$ bit is required. This is because $2^7 = 128$, which is greater than or equal to the maximum number of possible values (100).

5 Applicability and Limitations

RNCK can only be used instead of CK in certain cases, such as when the total number of attributes and the maximum size of each attribute is relatively small.

The use of RNCK is only possible if the underlying data type is large enough to contain the encoding of all CK attributes. Each binary section must be large enough to store all possible values of the corresponding attribute. In some cases, additional flag bits may be required to indicate special cases.

6 Partially Reversible Encoding

To overcome the RNCK capacity limitation, it is sometimes possible to adopt multiple encoding schemas that are indicated by bit flags.

For example, in VariantKey [6], some input variants may exceed the REF+ALT binary section capacity. This is true for only about 0.4% of the records in the reference dataset. In these rare cases, the least significant bit (LSB) is set to 1 and the remaining 30 bits are filled with a hash value that is used as a key for a relatively small lookup table. This alternate encoding is a good compromise because it is rarely used and still preserves some of the RNCK properties, such as the ability to sort and search the variants by chromosome (first binary section) and position (second binary section).

7 Properties

- Each RNCK code is unique for a given set of CK attributes.
- RNCK can be quickly encoded and decoded.
- Comparing two CK values by RNCK only requires comparing two numbers, which is a very well-optimized operation in current computer architectures.
- A RNCK can be represented as a fixed-length hexadecimal string. This is useful for compatibility with text-based data representation formats or as an interchange format.
- Sorting the fixed-length hexadecimal representation of RNCK in alphabetical order is equivalent to sorting the RNCK numerically.
- Sorting by RNCK is equivalent to sorting by the CK attributes in enumeration order.
- RNCK can be used to replace CK and SK in a database to simplify common searching, merging, and filtering operations.
- All types of database joins between two datasets (inner, left, right, and full) can be easily performed using RNCK as a single index.
- RNCK can reduce data storage, memory usage, and improve performance.
- RNCK can be used with existing key-value systems, including in-memory caches, where the key is RNCK.
- RNCK can be used with columnar data formats (e.g. Apache Arrow [7], Apache Parquet [8]) to perform really fast binary searches.
- In some cases, RNCK can be used to speed up CK searches in a given range. See the VariantKey Overlapping Regions [6] for more information.

8 Examples

Practical implementations of Reversible Numeric Composite Key (RNCK) in multiple programming languages have been successfully used in production systems for some time.

8.1 VariantKey

VariantKey is a RNCK for Human Genetic Variants [6].

A reference implementation of VariantKey in multiple programming languages can be found at [9]: <https://github.com/tecnickcom/variantkey>

The VariantKey is composed of 3 sections arranged in 64 bit:

-
- [4] May 2023. URL https://en.wikipedia.org/wiki/Foreign_key.
 - [5] Thomas H Cormen, Charles E Leiserson, Ronald L Rivest, and Clifford Stein. *Introduction to algorithms*. MIT press, 2022.
 - [6] Nicola Asuni and Steven Wilder. Variantkey: A reversible numerical representation of human genetic variants. *bioRxiv*, 2019. doi:10.1101/473744. URL <https://www.biorxiv.org/content/early/2019/02/15/473744>.
 - [7] Apache arrow columnar format, June 2023. URL <https://arrow.apache.org/docs/format/Columnar.html>.
 - [8] Apache parquet file format, June 2023. URL <https://parquet.apache.org/docs/file-format/>.
 - [9] Nicola Asuni. variantkey, May 2023. URL <https://github.com/tecnickcom/variantkey>.
 - [10] Nicola Asuni. numkey, May 2023. URL <https://github.com/tecnickcom/numkey>.