An introduction and tutorial to model-based clustering in education via Gaussian mixture modelling

Luca Scrucca^{1,*}, Mohammed Saqr², Sonsoles López-Pernas², Keefe Murphy³

Università degli Studi di Perugia School of Computing, University of Eastern Finland Department of Mathematics and Statistics, Hamilton Institute, Maynooth University *Corresponding author: Luca Scrucca, luca.scrucca@unipg.it

Abstract

Heterogeneity has been a hot topic in recent educational literature. Several calls have been voiced to adopt methods that capture different patterns or subgroups within students' behavior or functioning. Assuming that there is "an average" pattern that represents the entirety of student populations requires the measured construct to have the same causal mechanism, same development pattern, and affect students in exactly the same way. Using a person-centered method (Finite Gaussian mixture model or latent profile analysis), the present tutorial shows how to uncover the heterogeneity within engagement data by identifying three latent or unobserved clusters. This chapter offers an introduction to the modelbased clustering that includes the principles of the methods, a guide to choice of number of clusters, evaluation of clustering results and a detailed guide with code and a real-life dataset. The discussion elaborates on the interpretation of the results, the advantages of model-based clustering as well as how it compares with other methods.

Introduction

Statistical research is commonly performed with variable-centered methods using a sample from the population to devise central tendency measures or an "average" (i.e., mean or median). The average is assumed to represent the population under study and therefore, could be generalized to the population at large (Howard and Hoffman 2018; Hickendorff et al. 2018). Put another way, the statistical findings of variable-centered methods are thought to apply to all learners in the same way. In doing so, variable-centered methods ignore the individual differences that are universal across all domains of human function (Saqr et al. 2023). Learners are not an exception, they vary in their behavior, attitude and

dispositions, and they rarely —if at all— conform to a common pattern or an average behavior (Hickendorff et al. 2018; Törmänen et al. 2022). An "average" is thus a poor simplification of learners' heterogeneity; consequently, methods to capture individual differences have started to gain popularity with the increasing attention to patterns and differences among students.

Person-centered methods can be broadly grouped into two categories; heuristic, distance-based clustering algorithms (e.g., agglomerative hierarchical clustering, and partitional clustering algorithms like *k*-means) on one hand and *model-based* clustering (MBC) approaches (e.g., Gaussian mixture models, latent class or profile analysis) on the other. Though we focus here on the MBC paradigm, we note that —contrary to variable-centered methods— all person-centered methods are generally concerned with the modelling of heterogeneity by capturing the latent (e.g., unobserved or hidden) patterns within the data into subgroups of homogeneous "clusters" or "profiles" (Howard and Hoffman 2018; Hickendorff et al. 2018). Modelling the unobserved patterns within the data could reveal the qualitative differences between learners. For instance, where students may have different patterns of approaching their learning, capturing such patterns would make sense as each different approach may benefit from a certain course design, set of instructional methods, or scaffolding approach (Hickendorff et al. 2018). Similarly, dispositions such as engagement, motivation, and achievement are multidimensional and vary across students; capturing such differences requires a method that could handle such nonlinear multidimensional dispositions and identify the different patterns.

This chapter deals with one of the person-centered methods; namely, latent profile analysis (from the perspective of model-based clustering via finite Gaussian mixture models). This represents a *probabilistic* approach to statistical unsupervised learning that aims at discovering clusters of observations in a data set (Fraley and Raftery 2002). We also offer a walkthrough tutorial for the analysis of a data set on school engagement, academic achievement, and self-regulated learning using the popular **mclust** package (Fraley, Raftery, and Scrucca 2023) for R (R Core Team 2023) which implements the approach. Whereas mixture models and **mclust** have received growing attention within social science, they have not garnered widespread utilisation in the field of educational research and their adoption in learning analytics research has been relatively scarce.

Literature review

While examples of mixture models being applied in educational research settings are relatively scarce compared to other methods of clustering, some notable examples exist that address patterns in students' online learning, patterns in students' disposition, or collaborative roles.

Most studies in education research that applied mixture models used latent profile analysis (LPA) to identify students' profiles from self-reported data. For example, Yu et al. (2022) performed LPA on a data set of 318 students'

survey responses about emotional self-efficacy, motivation, self-regulation, and academic performance, and identified four profiles: "low", "average", "above average with a low ability to handle the emotions of others" and "high emotional self-efficacy". In the work by Cheng, Huang, and Hebert (2023), the authors analyzed 615 vocational education students' achievement emotions in online learning environments, and found three profiles: "blends of negative emotions", "nonemotional", and "pure positive emotion". Hoi (2023) employed LPA on self-report data on classroom engagement from 413 first-year university students in Vietnam and found three profiles: "highly engaged", "moderately engaged", and "minimally engaged". Scheidt et al. (2021) collected survey responses from 2,339 engineering undergraduates about 28 noncognitive and affective factors using a survey instrument and using Gaussian mixture models found four very distinct profiles of students.

The use of mixture models to analyze online trace log data —which is at the core of learning analytics data— is not nearly as common. In the study by Zhang et al. (2023), the authors applied LPA to variables related to debugging derived from students' programming problems submission traces. They found a profile with higher debugging accuracy and coding speed, another profile with lower debugging performance in runtime and logic errors, and a third profile with lower performance in syntactic errors who tended to make big changes in every submission. Studies covering online collaborative learning are even more scarce. A rare example is the study by Saqr and López-Pernas (2022), in which the authors used latent profile analysis to identify students' roles in collaboration based on their centrality measures. The mixture models identified three collaborative roles that represented a distinct pattern of collaboration: leaders, who contribute the most to the discussion, whose arguments are more likely to spread; mediators, who bridge others and moderate the discussions; as well as isolates, who are socially idle and do not contribute to the discussion.

A considerable number of studies that applied mixture models further investigate the association between profile membership and academic achievement. For example, in the aforementioned study by Yu et al. (2022), students with high emotional self-efficacy had higher academic performance than the other profiles. In the study by Zhang et al. (2023), the authors found that higher debugging accuracy was related to higher scores in all exams, whereas there were no differences between the two other identified profiles. By the same token, researchers have attempted to find reasons why a certain profile emerged, or what are the variables that are more associated with one profile more than the other. For example, Hoi (2023) found that peer support, provision of choice, and task relevance are the factors more likely to predict classroom engagement profile membership. Yu et al. (2022) found that self-regulation and motivation played significant roles in determining profile membership.

Clearly, there are plenty of opportunities for further exploration and investigation in this area that could augment our knowledge of learning, learners' behavior, and the variabilities of learning processes (Hickendorff et al. 2018). This is especially true given the numerous advantages of the MBC paradigm over more traditional, heuristic clustering algorithms, which we imminently describe. Subsequently, in the rest of this chapter we elaborate on the theoretical underpinnings of the family of Gaussian parsimonious clustering models implemented in the **mclust** R package and additionally explore some advanced features of the package, which we employ in an analysis of a real educational research application thereafter. Finally, we conclude with a brief discussion.

Model-based clustering

As stated above, clustering methods, in a general sense, are used to uncover group structure in heterogeneous populations and identify patterns in a data set which may represent distinct subpopulations. While there is no universally applicable definition of what constitutes a cluster (Hennig 2015), it is commonly assumed that clusters should be well separated from each other and cohesive in an ideal analysis (Everitt et al. 2011). Conversely, objects within a cluster should be more similar to each other in some sense, in such a way that an observation has a defined relationship with observations in the same cluster, but not with observations from other clusters.

Traditional clustering approaches, like the aforementioned *k*-means algorithm, and agglomerative hierarchical clustering, use distance-based heuristics to produce a "hard" partition of cases into groups, such that each observation is associated with exactly one cluster only. As such approaches are not underpinned by a statistical model, assessment of the optimal number of clusters is often a fraught task, lacking the guidance of principled statistical model selection criteria.

Conversely, the MBC paradigm assumes that data arise from a (usually finite) mixture of probability distributions, whereby each observation is assumed to be generated from a specific cluster, characterised by an associated distribution in the mixture (McLachlan and Peel 2000). Ideally, mixtures of distributions are supposed to provide a good model for the heterogeneity in a data set; that is, once an observation has been assigned to a cluster, it is assumed to be wellrepresented by the associated distribution. As such, MBC methods are based on a formal likelihood and seek to estimate parameters (e.g., means, variances, and covariances, which may or may not differ across groups) which best characterise the different distributions. Rather than yielding only a "hard" partition, each observation is assigned a probability of being associated with each mixture component —such that observations can have non-negative association with more than one cluster— from which a hard partition can be constructed. These probabilities are treated as weights when estimating the component parameters, which brings the advantages of minimising the effect of observations lying near the boundary of two natural clusters (e.g., a student with an ambiguous learning profile) and being able to quantity the uncertainty in the cluster assignment of a particular observation to provide a sense of cases for which further investigation

may be warranted. Compared to other approaches, the other main advantages of this statistical modelling framework are its ability to use statistical model selection criteria and inferential procedures for evaluating and assessing the results obtained.

Inference for finite mixture models is routinely achieved by means of the expectation-maximisation (EM) algorithm (Dempster, Laird, and Rubin 1977), under which each observation's component membership is treated as a "missing" latent variable which must be estimated. This formulation assumes that the data are *conditionally* independent and identically distributed, where the conditioning is with respect to a latent variable representation of the data in which the latent variable indicates cluster membership. Given the relative familiarity of latent class and latent profile terminology in the social sciences, we now explicitly cast MBC methods in the framework of latent variable modelling.

Latent variable models

Latent variable models are statistical models that aim to explain the relationships between observed variables by introducing one or more unobserved or latent variables. The idea behind latent variable models is that some of the underlying constructs or concepts we are interested in cannot be measured directly, but only through their effects on observable variables. Latent variable modelling has a relatively long history, dating back from the measure of general intelligence by factor analysis (Spearman 1904), to the structural equation modelling approach (Jöreskog 1970), from topic modelling, such as the latent Dirichlet allocation (LDA) algorithm (Blei, Ng, and Jordan 2003), to hidden Markov models for time series (Zucchini, MacDonald, and Langrock 2016). Latent variable models are widely used in various fields, including psychology, sociology, economics, and biology, to name a few. They are particularly useful when dealing with complex phenomena that cannot be easily measured or when trying to understand the underlying mechanisms that drive the observed data.

When discussing latent variable modelling, it is useful to consider the *taxonomy* presented by Bartholomew, Knott, and Moustaki (2011). This can be particularly helpful, as the same models are sometimes referred to by different names in different scientific disciplines. Bartholomew, Knott, and Moustaki (2011, Table 1.3) considered a cross-classification of latent variable methods based on the type of variable (manifest or latent) and its nature (metrical or categorical). If both the manifest and latent variables are metrical, the model is called a **factor analysis model**. If the manifest variables are categorical and the latent variables are metrical, the model is called a **latent trait model** or **item response theory model**. If the manifest variables are metrical and the latent variables are categorical, the model is called a **latent profile analysis model**. If both the manifest and latent variables are categorical, the model is called a **latent class model**.

In this scheme, finite Gaussian mixture models described in this chapter assume

that the observed variables are continuous and normally distributed, while the latent variable, which represents the cluster membership of each observation, is categorical. Therefore, Gaussian mixtures belong to the family of latent profile analysis models. This connection is made apparent by the **tidyLPA** R package (Rosenberg et al. 2018), which leverages this equivalence to provide an interface to the well-known **mclust** R package (Fraley, Raftery, and Scrucca 2023) used throughout this chapter, using tidyverse syntax and terminology which is more familiar in the LPA literature.

Finite Gaussian mixture models

As described above, finite mixture models (FMMs) provide the statistical framework for model-based clustering and allow for the modelling of complex data by combining simpler distributions. Specifically, a FMM assumes that the observed data are generated from a finite mixture of underlying distributions, each of which corresponds to a distinct subgroup or cluster within the data. Gaussian mixture models (GMMs) are a particularly widespread variant of FMMs which specifically assume that each of the underlying distributions is a (multivariate) Gaussian distribution. This means that the data within each cluster are normally distributed, but with potentially different means and covariance matrices. In this type of model, the latent variable represents the cluster assignment for each observation in the data; it is an indicator variable that takes the value 1 for the cluster to which the observation belongs and 0 for all the other clusters. It is well-known that any continuous density can be well-fitted by mixtures of Gaussians to arbitrary accuracy.

To estimate the parameters of a GMM with the associated latent variable for cluster membership, a likelihood-based approach is typically used. The likelihood function expresses the probability of observing the data, given the parameter values and the latent variable. The maximum likelihood estimation (MLE) method is commonly used to estimate the parameters and the latent variable which maximize the likelihood function. Usually, the number of clusters in a GMM is also unknown, and it is determined through a process known as model selection, which involves comparing models with different numbers of clusters and parameterisations and selecting the one which best fits the data.

In summary, model-based clustering from the perspective of latent variable modelling assumes that the data is generated from a probabilistic model with a specific number of clusters. A likelihood-based approach can be used to estimate the parameters of the model and the latent variable that represents the cluster assignment for each observation in the data, and guide the selection of the number of clusters. A GMM is a common framework for model-based clustering which assumes the data in each cluster is generated from a Gaussian distribution.

Gaussian parsimonious clustering models

For a continuous feature vector $x \in \mathbb{R}^d$, the general form of the density function of a Gaussian mixture model (GMM) with *K* components can be written as

$$
f(\boldsymbol{x}) = \sum_{k=1}^{K} \pi_k \phi_d(\boldsymbol{x}; \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k),
$$
 (1)

where π_k represents the mixing probabilities which control the **size** of each cluster, such that $\pi_k > 0$ and $\sum_{k=1}^K \pi_k = 1$, and $\phi_d(\cdot)$ is the *d*-dimensional multivariate Gaussian density with parameters (μ_k, Σ_k) for $k = 1, ..., K$. Clusters described by such a GMM are ellipsoidal, centered at the means μ_k , and with other geometric characteristics (namely volume, shape, and orientation) determined by the covariance matrices $\Sigma_1, \ldots, \Sigma_K$. Parsimonious parameterisations of covariance matrices can be controlled by imposing some constraints on the covariance matrices through the following eigen-decomposition (Banfield and Raftery 1993; Celeux and Govaert 1995):

$$
\Sigma_k = \lambda_k \mathbf{U}_k \mathbf{\Delta}_k \mathbf{U}_k^{\top},\tag{2}
$$

where $\lambda_k = |\mathbf{\Sigma}_k|^{1/d}$ is a scalar which controls the *volume*, $\mathbf{\Delta}_k$ is a diagonal matrix whose entries are the normalized eigenvalues of Σ_k in decreasing order, such that $|\Delta_k| = 1$, which controls the *shape* of the density contours, and \boldsymbol{U}_k is an orthogonal matrix whose columns are the eigenvectors of Σ_k , which controls the *orientation* of the corresponding ellipsoid.

Constraining these various quantities to be equal across clusters can greatly reduce the number of estimable parameters, and is the means by which GMMs obtain intermediate covariance matrices between homoscedasticity and heteroscedasticity. A list of the 14 resulting parameterisations available in the **mclust** package (Fraley, Raftery, and Scrucca 2023) for R (R Core Team 2023) is included in Table 2.1 of Scrucca et al. (2023). Of particular note is the nomenclature adopted by **mclust** whereby each model has a three-letter name with each letter pertaining to the volume, shape, and orientation, respectively, denoting whether the given component is equal (E) or free to vary (V) across clusters. Some model names also use the letter I in the third position to indicate that the covariance matrices are diagonal and two particularly parsimonious models have the letter I in the second position to indicate that the covariance matrices are isotropic. Thus, as examples, the fully unconstrained VVV model is one for which the volume, shape, and orientation are all free to vary across clusters, the EVE model constrains the clusters to have equal volume and orientation but varying shape, and the VII model assumes isotropic covariance matrices with cluster-specific volumes. The flexibility to model clusters with different geometric characteristics by modelling correlations according to various parameterisations represents another advantage over heuristic clustering algorithms. Taking the *k*-means algorithm as an example, a larger number of circular, Euclidean distance-based clusters may be required to fit the data well,

rather than a more parsimonious and easily interpretable mixture model with fewer non-spherical components.

Given a random sample of observations $\{x_1, x_2, \ldots, x_n\}$ in *d* dimensions, the log-likelihood of a GMM with *K* components is given by

$$
\ell(\boldsymbol{\theta}) = \sum_{i=1}^{n} \log \left\{ \sum_{k=1}^{K} \pi_k \phi_d(\boldsymbol{x}_i; \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k) \right\},
$$
\n(3)

where $\theta = (\pi_1, \ldots, \pi_{K-1}, \mu_1, \ldots, \mu_K, \Sigma_1, \ldots, \Sigma_K)$ denotes the collection of parameters to be estimated.

Maximizing the log-likelihood function in Equation [3](#page-7-0) directly is often complicated, so maximum likelihood estimation (MLE) of θ is usually performed using the EM algorithm (Dempster, Laird, and Rubin 1977) by including the component membership as a latent variable. The EM algorithm consists of two steps: the Estep (Expectation step) and the M-step (Maximisation step). In the E-step, the algorithm calculates the expected membership probabilities of each data point to each of the mixture components based on the current estimates of the model parameters. In the M-step, the algorithm updates the model parameters by maximizing the likelihood of the observed data given the estimated membership probabilities. These two steps are repeated until convergence or a maximum number of iterations is reached. Details on the use of EM algorithm in finite mixture modelling is provided by McLachlan and Peel (2000), while a thorough treatment and further extensions can be found in McLachlan and Krishnan (2008). For the GMM case, see Sec. 2.2 of Scrucca et al. (2023).

Following the fitting of a GMM and the determination of the MLEs of parameters, the maximum a posteriori (MAP) procedure can be used to classify the observations into the most likely cluster and recover a "hard" partition. For an observation x_i the posterior conditional probability of coming from the mixture component *k* is given by

$$
\widehat{p}_{ik} = \frac{\widehat{\pi}_k \phi_d(\boldsymbol{x}_i; \widehat{\boldsymbol{\mu}}_k, \widehat{\boldsymbol{\Sigma}}_k)}{\sum_{g=1}^K \widehat{\pi}_g \phi_d(\boldsymbol{x}; \widehat{\boldsymbol{\mu}}_g, \widehat{\boldsymbol{\Sigma}}_g)}
$$
\n(4)

Then, an observation is assigned to the cluster with the largest posterior conditional probability, i.e., $x_i \in C_{k^*}$ with $k^* = \arg \max_k \widehat{p}_{ik}$.

Model selection

Given that a wide variety of GMMs in Equation [1](#page-6-0) can be estimated by varying the number of mixture components and the covariance decompositions in Equation [2,](#page-6-1) selecting the appropriate model represents a crucial decision. A popular option consists in choosing the "best" model using the Bayesian information criterion

(BIC, Schwarz 1978), which, for a given model M , is defined as

$$
\text{BIC}_{\mathcal{M}} = 2\ell_{\mathcal{M}}(\widehat{\boldsymbol{\theta}}) - \nu_{\mathcal{M}} \log(n),
$$

where $\ell_{\mathcal{M}}(\theta)$ stands for the maximized log-likelihood of the data sample of size *n* under model M , and ν_M for the number of independent parameters to be estimated. Another option available in clustering is the Integrated Complete Likelihood (ICL, Biernacki, Celeux, and Govaert 2000) criterion given by

$$
ICL_{\mathcal{M}} = BIC_{\mathcal{M}} + 2\sum_{i=1}^{n} \sum_{k=1}^{K} c_{ik} \log(\widehat{p}_{ik}),
$$

where \hat{p}_{ik} is the conditional probability that x_i arises from the *k*-th mixture component from Equation [4,](#page-7-1) and $c_{ik} = 1$ if the *i*-th observation is assigned to cluster \mathcal{C}_k and 0 otherwise.

Both criteria evaluate the fit of a GMM to a given set of data by considering both the likelihood of the data given the model and the complexity of the model itself, represented by the number of parameters to be estimated. Compared to the BIC, the ICL introduces a further entropy-based penalisation for the overlap of the clusters. For this reason, the ICL tends to select models with well-separated clusters.

Whereas there is no consensus of a standard criteria for choosing the best model, there are guidelines that the researcher could rely on. To decide on the optimal model, examining the fit indices (such as the BIC and ICL), model interpretability, and conformance to theory can be of great help. The literature recommends estimating a 1-class solution for each model that serves as a comparative baseline and then increasing the number of classes one by one evaluating if adding another class yields a better solution in both statistical and conceptual terms (Nylund-Gibson and Choi 2018). Among all fit indices, lower BIC values seems to be the preferred method for selecting the best model. However, examining other indices (e.g., AIC, ICL) is also useful. Oftentimes, fit indices do not converge to a certain model. In such cases, the interrelation between the selected models, such as whether one model is an expanded version of another, should also be taken into consideration, as well as the stability of the different models, including the relative sizes of the emergent classes (each class should comprise more than 5-8% of the sample) (Nylund-Gibson and Choi 2018). Furthermore, the elbow method could be helpful in cases where no clear number of clusters can be easily determined from the fit indices (e.g., the BIC continues to decrease consistently when increasing the number of classes). This entails plotting the BIC values and finding an elbow shape where a drop in BIC is less noticeable with increasing number of classes or roughly an elbow followed by a relatively flat line. The choice of the best number of classes can and probably should be guided by theory; that is, in cases where previous research reported a certain number of clusters or patterns, it is recommended to take this guidance into account. For instance, research on engagement has repeatedly reported three levels of

engagement. Once we have chosen the most suitable model, it is suggested to compute model diagnostics (e.g., entropy and average posterior probability) to evaluate the selected model. These diagnostics are covered in Section .

mclust R package

mclust is an R package (R Core Team 2023) for model-based cluster analysis, classification, and density estimation using Gaussian finite mixture models (Scrucca et al. 2016, 2023). It is widely used in statistics, machine learning, data science, and pattern recognition. One of the key features of **mclust** is its flexibility in modelling quantitative data with several covariance structures and different numbers of mixture components. Additionally, the package provides extensive graphical representations, model selection criteria, initialisation strategies for the EM algorithm, bootstrap-based inference, and Bayesian regularisation, among other prominent features. **mclust** also represents a valuable tool in educational settings because it provides a powerful set of models that allows students and researchers to quickly and easily perform clustering and classification analyses on their data.

The main function implementing model-based clustering is called Mclust(), which requires a user to provide at least the data set to analyze. In the onedimensional case, the data set can be a vector, while in the multivariate case, it can be a matrix or a data frame. In the latter case, the rows correspond to observations, and the columns correspond to variables.

The Mclust() function allows for further arguments, including the optional argument G to specify the number of mixture components or clusters, and modelNames to specify the covariance decomposition. If both G and modelNames are not provided, Mclust() will fit all possible models obtained using a number of mixture components from 1 to 9 and all 14 available covariance decompositions, and it will select the model with the largest BIC. Notably, if the data set is univariate, only 2 rather than 14 models governing the scalar variance parameters are returned; that they are equal or unequal across components. Finally, computing the BIC and ICL criteria can be done by invoking the functions mclustBIC() and mclustICL(), respectively.

Other practical issues and extensions

Prior to commencing the cluster analysis of a data set on school engagement, academic achievement, and self-regulated learning measures, we first provide some theoretical background on some extensions of practical interest which will be explored in the analysis.

Bayesian regularisation

Including a prior distribution over the mixture parameters is an effective way to avoid singularities and degeneracies in maximum likelihood estimation. Furthermore, this can help to prevent overfitting and improve model performance. In latent class analysis, where the variables of interest are often discrete or take on only a few values, including a prior distribution can help to regularize the model.

Fraley and Raftery (2007) proposed using weekly informative conjugate priors to regularize the estimation process. The EM algorithm can still be used for model fitting, but maximum likelihood estimates (MLEs) are replaced by maximum a posteriori (MAP) estimates. A slightly modified version of BIC can be used for model selection, with the maximized log-likelihood replaced by the log-likelihood evaluated at the MAP or posterior mode.

The prior distributions proposed by Fraley and Raftery (2007) are:

- a uniform prior on the simplex for the mixture weights (π_1, \ldots, π_K) ;
- a Gaussian prior on the mean vector (conditional on the covariance matrix), i.e.,

$$
\mu \mid \Sigma \sim \mathcal{N}(\mu_p, \Sigma/\kappa_p) \tag{5}
$$

$$
\propto |\mathbf{\Sigma}|^{-1/2} \exp\left\{-\frac{\kappa_{\mathcal{P}}}{2} \operatorname{tr}\left((\boldsymbol{\mu}-\boldsymbol{\mu}_{\mathcal{P}})^{\top} \mathbf{\Sigma}^{-1} \left(\boldsymbol{\mu}-\boldsymbol{\mu}_{\mathcal{P}}\right)\right)\right\},\qquad(6)
$$

with $\mu_{\mathcal{P}}$ and $\kappa_{\mathcal{P}}$ being the hyperparameters controlling, respectively, the mean vector and the amount of shrinkage applied;

• an inverse Wishart prior on the covariance matrix, i.e.,

$$
\Sigma \sim \mathcal{IW}(\nu_p, \Lambda_p)
$$

$$
\propto |\Sigma|^{-(\nu_p + d + 1)/2} \exp\left\{-\frac{1}{2} \operatorname{tr}\left(\Sigma^{-1} \Lambda_p^{-1}\right)\right\},\tag{7}
$$

with the hyperparameters $\nu_{\mathcal{P}}$ and the matrix $\Lambda_{\mathcal{P}}$ controlling the degrees of freedom and scale of the prior distribution, respectively.

Adding a prior to GMMs estimated using the **mclust** R package is easily obtained by adding an optional prior argument when calling some of the fitting functions, such as $mclustBIC()$ and $Mclust()$. Specifically, setting prior = priorControl(functionName = "defaultPrior") allows to adopt the conjugate priors described above with the following default values for the hyperparameters:

- mean vector $\mu_p = \bar{x}$, the sample mean of each variable;
- shrinkage $\kappa_P = 0.1$;
- degrees of freedom $\nu_{\mathcal{P}} = d + 2$;
- scale matrix $\Lambda_p = \frac{6}{3}(K^{2/d})$, where $\frac{6}{3}$ is the sample covariance matrix.

Rationale for the above default values for the prior hyperparameters, together with the corresponding MAP estimates of the GMM parameters, can be found in Fraley and Raftery (2007, Table 2). These values should suffice for most applications, but experienced users who want to tune the hyperparameters can refer to the documentation available in the help pages for priorControl and defaultPrior(). Further details about specifying different hyperparameter values can be found in Scrucca et al. (2023, sec. 7.2).

Bootstrap inference

Likelihood-based inference in mixture models is complicated because asymptotic theory applied to mixture models require a very large sample size (McLachlan and Peel 2000, 299:42), and standard errors derived from the expected or the observed information matrix tend to be unstable (Basford et al. 1997). For these reasons, resampling approaches based on the bootstrap are often employed (O'Hagan et al. 2019).

The *bootstrap* (Efron 1979) is a general, widely applicable, powerful technique for obtaining an approximation to the sampling distribution of a statistic of interest. The bootstrap distribution is approximated by drawing a large number of samples, called *bootstrap samples*, from the empirical distribution. This can be obtained by resampling with replacement from the observed data (*nonparametric bootstrap*), or from a parametric distribution with unknown parameters substituted by the corresponding estimates (*parametric bootstrap*). A Bayesian version of the bootstrap, introduced by Rubin (1981), allows posterior samples to be obtained by resampling with weights for each observation drawn from a uniform Dirichlet distribution. A strictly related technique is the *weighted likelihood bootstrap* (Newton and Raftery 1994), where a statistical model is repeatedly fitted using weighted maximum likelihood with weights obtained as in Bayesian bootstrap.

Let θ be the estimate of a set of GMM parameters θ for a given model M, determined by the adopted covariance parameterisation and number of mixture components. The bootstrap distribution for the parameters of interest is obtained as follows:

- draw a bootstrap sample of size *n* using one of the resampling techniques described above to form the bootstrap sample (x_1^*, \ldots, x_n^*) ;
- fit a the GMM $\mathcal M$ to get the bootstrap estimates $\widehat{\pmb{\theta}}^{\star};$
- replicate the previous steps a large number of times, say *B*.

The bootstrap distribution for the parameters of interest, $\hat{\theta}_1^*$ $\hat{\theta}_1^*, \hat{\theta}_2^*$ $\hat{\theta}_B^{\star}, \ldots, \hat{\theta}_B^{\star}, \text{ can}$ then be used for computing the bootstrap standard errors (as the square root of the diagonal elements of the bootstrap covariance matrix) or the bootstrap percentile confidence intervals. More details can be found in Scrucca et al. (2023, sec. 2.4).

From a practical point of view, bootstrap resampling can be conducted in **mclust** by means of the function MclustBootstrap(). This function takes as arguments the fitted model object returned from e.g., $Mclust()$ or $mclustBIC()$, the optional argument type, which allows to specify the type of bootstrap samples

to draw ("bs" for nonparametric bootstrap, "pb" for parametric bootstrap, and "wlbs" for weighted likelihood bootstrap), and the optional argument nboot, which sets the number of bootstrap samples. At least 999 samples should be drawn if confidence intervals are needed.

Entropy and average posterior probabilities

The definition of entropy in information theory (Cover and Thomas 2006) refers to the average amount of information provided by a random variable. Following this definition, Celeux and Soromenho (1996) defines the entropy of a finite mixture model as follows

$$
E_{\text{FMM}} = -\sum_{i=1}^{n} \sum_{k=1}^{K} \widehat{p}_{ik} \log(\widehat{p}_{ik}),
$$

where \hat{p}_{ik} is the estimated posterior probability of case *i* to belong to cluster *k* (see Equation [4\)](#page-7-1). If the mixture components are well separated, $\hat{p}_{ik} \approx 1$ for the assigned cluster \mathcal{C}_k and 0 otherwise. Consequently, the entropy of the mixture model in this case is $E_{\text{FMM}} = 0$ (note that $0 \log(0) = 0$ by convention). On the contrary, in the case of maximal classification uncertainty, $\hat{p}_{ik} = 1/K$ for all clusters \mathcal{C}_k ($k = 1, ..., K$). As a result, the entropy of the mixture model is $E_{\text{FMM}} = n \log(K).$

In latent class and latent profile analysis, a slightly different definition of entropy is used as a diagnostic statistic to assess how well the fitted model assigns individuals to the identified clusters based on their response patterns. Thus, a normalized version of the entropy is defined as follows

$$
E = 1 - \frac{E_{\text{FMM}}}{n \log(K)} = 1 + \frac{\sum_{i=1}^{n} \sum_{k=1}^{K} \hat{p}_{ik} \log(\hat{p}_{ik})}{n \log(K)}.
$$

Entropy takes values on the range [0*,* 1], with higher entropy values indicating that the model has less uncertainty in assigning cases to their respective latent classes/profiles. Thus, high entropy values typically indicate a better model which is able to distinguish between the latent components and that the components are relatively distinct. An entropy value close to 1 is ideal, while values above 0*.*6 are considered acceptable, although there is no agreed upon optimal cutoff for entropy.

The contribution of each observation to the overall entropy can be defined as

$$
E_i = 1 + \frac{\sum_{k=1}^{K} \widehat{p}_{ik} \log(\widehat{p}_{ik})}{\log(K)},
$$

so that the overall entropy is obtained by averaging over the single contributions, i.e., $E = \sum_{i=1}^{n} E_i/n$. The single contributions E_i can also be used to compute the average entropy of each latent component, which indicates how accurately the model defines components. Average posterior probabilities (AvePP) are a closely related performance assessment measure, given by the average posterior membership probabilities \hat{p}_{ik} for each component for the observations most probably assigned to that component, for which a cutoff of 0*.*8 has been suggested to indicate acceptably high assignment certainty and well-separated clusters (Nylund-Gibson and Choi 2018). The analysis below presents the necessary code to calculate entropies and average posterior probabilities thusly from a fitted **mclust** model.

Application: School engagement, academic achievement, and self-regulated learning

A group of primary school students from northern Spain were evaluated in terms of their school engagement, self-regulation, and academic performance through the use of various measures. The school engagement measure (SEM) was employed to assess their engagement, while their self-regulation was evaluated with the self-regulation strategy inventory—self-report. The measure for academic achievement was based on the students' self-reported grades in Spanish and mathematics, which were rated on a scale of 1 to 5. This data set can be used to identify clusters of students based on their engagement and self-regulation. These clusters would represent distinct patterns or "profiles" of engagement. Finding such profiles would allow us to understand individual differences but more importantly to stratify support according to different engagement profiles.

Preparing the data

We start by loading the packages required for the analysis. We note in particular that version 6.0.0 of **mclust** is employed here, the latest release at the time of writing.

```
library(ggplot2)
library(ggridges)
library(mclust)
library(rio)
library(tidyverse)
```
Then, we read the data set from an online comma-separated-value (CSV) file, followed by some data cleaning and formatting to prepare the data for subsequent analysis. Note that the CSV file to be read is not in standard format, so we have to explicitly set the separator field using the optional argument sep = ";".

read the data
data <- import("https://raw.githubusercontent.com/sonsoleslp/labook-data/main/3_engSRLach/Manuscript_School%20Engagment.csv", sep = ";")

```
# select the variables to be analyzed
vars <- c("PRE_ENG_COND", "PRE_ENG_COGN", "PRE_ENG_EMOC")
x <- select(data, all_of(vars)) |>
 as_tibble() |>
 rename("BehvEngmnt" = "PRE_ENG_COND", # Behavioral engagement
       "CognEngmnt" = "PRE_ENG_COGN", # Cognitive engagement
       "EmotEngmnt" = "PRE_ENG_EMOC") # Emotional engagement
# print the data set used in the subsequent analysis
x
## # A tibble: 717 x 3
## BehvEngmnt CognEngmnt EmotEngmnt
## <dbl> <dbl> <dbl>
        ## 1 3.75 3.14 4.4
## 2 4 3.71 2
## 3 4.25 3.86 4
## 4 3.75 2.57 3
## 5 4.25 3 4
## 6 4 3.71 3.8
## 7 3.5 2.14 3.2
## 8 4.75 3.57 1.6
## 9 3.25 2.71 3
                ## 10 5 4.43 4.8
## # i 707 more rows
```
A table of summary statistics for the data set can be obtained as follows:

```
x |> pivot_longer(cols = colnames(x)) |>
 group by(name) |>
 summarize(N = n(),
          Nunq = n_distinct(value),
          Mean = mean(value),
          SD = sd(value),
          Min = min(value),
          Median = median(value),
          Max = max(value)## # A tibble: 3 x 8
## name N Nunq Mean SD Min Median Max
## <chr> <int> <int> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 BehvEngmnt 717 17 4.17 0.627 1 4.25 5
## 2 CognEngmnt 717 30 2.92 0.771 1 2.92 5
## 3 EmotEngmnt 717 22 3.61 0.911 1 3.61 5
```
Model estimation and model selection

To begin our latent profile analysis, we first fit a number of candidate GMMs with different numbers of latent components and covariance parameritations, and compute the Bayesian Information Criterion (BIC) to select the "optimal" model. This model selection criterion jointly takes into account both the covariance decompositions and the number of mixture components in the model.

As mentioned earlier, given the characteristics of the data, which consists of a small number of unique values relative to the number of observations, a prior is used for regularisation. We invoke the default priors described above, summarise the BIC values of the three best models, and visualise the BIC values of all fitted models.

```
BIC \leftarrow mclustBIC(x, prior = priorControl())
summary(BIC)
## Best BIC values:
## VVI,3 VVI,4 VVV,3
## BIC -4521.213 -4526.905884 -4533.57166
## BIC diff 0.000 -5.693183 -12.35896
plot(BIC)
```


Number of components

The selected model is a three-component GMM with diagonal covariance matrices of varying volume and shape, with axis-aligned orientation, indicated as '(VVI,3)'. Thus, the variables are independent within each cluster.

Examining model output

The fit of the optimal model is obtained using:

```
mod <- Mclust(x, modelNames = "VVI", G = 3, prior = priorControl())
summary(mod, parameters = TRUE)
## ----------------------------------------------------
## Gaussian finite mixture model fitted by EM algorithm
## ----------------------------------------------------
##
## Mclust VVI (diagonal, varying volume and shape) model with 3 components:
##
## Prior: defaultPrior()
##
## log-likelihood n df BIC ICL
## -2194.856 717 20 -4521.213 -4769.174
##
## Clustering table:
## 1 2 3
## 184 119 414
##
## Mixing probabilities:
## 1 2 3
## 0.2895147 0.1620776 0.5484078
##
## Means:
## [,1] [,2] [,3]
## BehvEngmnt 3.704041 4.713234 4.257355
## CognEngmnt 2.287057 3.699530 3.017293
## EmotEngmnt 2.738969 4.733899 3.737286
##
## Variances:
## [,,1]
## BehvEngmnt CognEngmnt EmotEngmnt
## BehvEngmnt 0.5022148 0.0000000 0.0000000
## CognEngmnt 0.0000000 0.3909235 0.0000000
## EmotEngmnt 0.0000000 0.0000000 0.7674268
## [,,2]
## BehvEngmnt CognEngmnt EmotEngmnt
## BehvEngmnt 0.0737948 0.0000000 0.00000000
## CognEngmnt 0.0000000 0.4150514 0.00000000
```


The shown output reports some basic information about the fit, such as the maximized log-likelihood (log-likelihood), the number of observations (n), the number of estimated parameters (df), the BIC criterion (BIC), and the clustering table based on the MAP classification. The latter indicates that the clusters also vary in terms of *size*. The optional argument parameters = TRUE in the summary() function call additionally prints the estimated parameters. Observe that the VVI model allows variance to vary across components while fixing all covariance parameters to zero.

A plot showing the classification provided by the estimated model can be drawn as follows:

plot(mod, what = "classification")

The estimated model identifies three clusters of varying size. The third group (shown as filled green triangles) accounts for more than 50% of the observations, while the first (shown as blue filled points) and the second (shown as red open squares) account for approximately 29% and 16%, respectively. The smallest cluster is also the group with the largest engagement scores.

The different engagement behaviour of the three identified clusters can be shown using a latent profiles plot of the estimated means with point sizes proportional to the estimated mixing probabilities:

```
# collect estimated means
means <- data.frame(Profile = factor(1:mod$G),
                   t(mod$parameters$mean)) |>
 pivot\_longer(cols = -1,names to = "Variable",
              values to = "Mean")
# convert variable names to factor
means$Variable <- factor(means$Variable,
                       levels = colnames(mod$data))
# add mixing probabilities corresponding to profiles
means <- means |>
 add_column(MixPro = mod$parameters$pro[means$Profile])
means
## # A tibble: 9 x 4
## Profile Variable Mean MixPro
## <fct> <fct> <dbl> <dbl>
## 1 1 BehvEngmnt 3.70 0.290
## 2 1 CognEngmnt 2.29 0.290
## 3 1 EmotEngmnt 2.74 0.290
## 4 2 BehvEngmnt 4.71 0.162
## 5 2 CognEngmnt 3.70 0.162
## 6 2 EmotEngmnt 4.73 0.162
           ## 7 3 BehvEngmnt 4.26 0.548
## 8 3 CognEngmnt 3.02 0.548
## 9 3 EmotEngmnt 3.74 0.548
ggplot(means, aes(x = Variable, y = Mean,group = Profile,
                 shape = Profile,
                 color = Profile)) +
  geom_point(aes(size = MixPro)) +
 geom line(linewidth = 0.5) +
 labs(x = NULL, y = "Latent profiles means") +scale_color_manual(values = mclust.options("classPlotColors")) +
  scale size(range = c(1, 3), guide = "none") +
```

```
theme_bw() +theme(legend.position = "top")
```


The smallest cluster (Profile 2) has the highest engagement scores for all three variables. All three scores are lower for the largest cluster (Profile 3), which are all in turn lower for Profile 1. All three profiles exhibit the lowest mean scores for the cognitive engagement attribute. For Profile 2, behavioural engagement and emotional engagement scores are comparable, whereas for the other two profiles, the mean scores for this attribute are lower than those for the behaviour engagement attribute. Taken together, we could characterise profiles 1, 3, and 2 as "low", "medium", and "high" engagement profiles, respectively.

To provide a more comprehensive understanding of the results presented in the previous graph, it would be beneficial to incorporate a measure of uncertainty for the estimated means of the latent profiles. This can be achieved by resampling using the function MclustBootstrap() as described above:

boot <- MclustBootstrap(mod, type = "bs", nboot = 999)

The bootstrap distribution of the mixing weights can be visualized using histograms with the code

 $par(mfcol = c(1, 3), mar = c(4, 4, 1, 1), mp = c(2, 0.5, 0))$ plot(boot, what = "pro", xlim = $c(0, 1)$)

while the bootstrap distribution of the components means with the code

 $par(mfcol = c(3, 3), mar = c(4, 4, 1, 1), mp = c(2, 0.5, 0))$ $plot(boot, what = "mean", conf.level = 0.95)$

In all the previous graphs, the GMM estimates are shown as dashed vertical lines, while the horizontal segments represent the percentile confidence intervals at the 95% confidence level.

Numerical output of the resampling-based bootstrap distributions is obtained as:

```
sboot \leq summary(boot, what = "ci")
sboot
## ----------------------------------------------------------
## Resampling confidence intervals
## ----------------------------------------------------------
## Model = VVI
## Num. of mixture components = 3
## Replications = 999
## Type = nonparametric bootstrap
## Confidence level = 0.95
##
## Mixing probabilities:
```

```
## 1 2 3
## 2.5% 0.1163335 0.09205218 0.4708275
## 97.5% 0.3914599 0.24915948 0.6840957
##
## Means:
## [,,1]
## BehvEngmnt CognEngmnt EmotEngmnt
## 2.5% 3.477729 1.838080 2.119603
## 97.5% 3.823994 2.436499 2.943870
## [,,2]
## BehvEngmnt CognEngmnt EmotEngmnt
## 2.5% 4.628794 3.525403 4.503787
## 97.5% 4.902464 3.927119 4.878830
## [,,3]
## BehvEngmnt CognEngmnt EmotEngmnt
## 2.5% 4.093381 2.833736 3.512896
## 97.5% 4.374219 3.153141 3.898397
##
## Variances:
## [,,1]
## BehvEngmnt CognEngmnt EmotEngmnt
## 2.5% 0.4003220 0.2231432 0.5528809
## 97.5% 0.8110118 0.4871179 0.9999560
## [,,2]
## BehvEngmnt CognEngmnt EmotEngmnt
## 2.5% 0.01584569 0.3138691 0.01899636
## 97.5% 0.10470006 0.5762498 0.15014816
## [,,3]
## BehvEngmnt CognEngmnt EmotEngmnt
## 2.5% 0.1610358 0.2874148 0.2312741
## 97.5% 0.2833726 0.3940830 0.4186933
```
The information above can then be used to plot the latent profile means with 95% confidence intervals shown as vertical errors bars as follows:

```
means <- means |>
 add_column(lower = as.vector(sboot$mean[1,,]),
          upper = as.vector(sboot$mean[2, 1))means
## # A tibble: 9 x 6
## Profile Variable Mean MixPro lower upper
## <fct> <fct> <dbl> <dbl> <dbl> <dbl>
## 1 1 BehvEngmnt 3.70 0.290 3.48 3.82
## 2 1 CognEngmnt 2.29 0.290 1.84 2.44
```

```
## 3 1 EmotEngmnt 2.74 0.290 2.12 2.94
## 4 2 BehvEngmnt 4.71 0.162 4.63 4.90
## 5 2 CognEngmnt 3.70 0.162 3.53 3.93
## 6 2 EmotEngmnt 4.73 0.162 4.50 4.88
            ## 7 3 BehvEngmnt 4.26 0.548 4.09 4.37
## 8 3 CognEngmnt 3.02 0.548 2.83 3.15
## 9 3 EmotEngmnt 3.74 0.548 3.51 3.90
ggplot(means, aes(x = Variable, y = Mean, group = Profile,shape = Profile, color = Profile)) +
 geom_point(aes(size = MixPro)) +
 geom\_line(lineared) = 0.5) +
 geom_errorbar(aes(ymin = lower, ymax = upper),
              linewidth = 0.5, width = 0.1) +
 labs(x = NULL, y = "Latent profiles means") +scale_color_manual(values = mclust.options("classPlotColors")) +
 scale_size(range = c(1, 3), guide = "none") +
 theme_bw() +theme(legend.position = "top")
```
Profile \rightarrow 1 \rightarrow 2 \rightarrow 3

The error bars for the cognitive and emotional engagement attributes are noticeably wider for the "low" engagement profile.

Finally, the entropy of the estimated classification, average entropy of each latent component, and average posterior probabilities are obtained via:

```
probs <- mod$z \longrightarrow # posterior conditional probs
probs_map <- apply(probs, 1, max) # maximum a posteriori probs
class <- mod$classification # latent classes for each obs
n <- mod$n # number of obs
K <- mod$G \# number of latent classes
# Entropy
E \leftarrow 1 + \text{sum}(\text{probs} * \text{log}(\text{probs})) / (n * \text{log}(K))E
## [1] 0.6890602
# Case-specific entropy contributions
Ei \leftarrow 1 + rowSums(probs * log(probs))/log(K)
sum(Ei)/n## [1] 0.6890602
df_entropy <- data.frame(class = as.factor(class), entropy = Ei)
df_entropy |>
  group_by(class) |>
  summarise(count = n(),
            mean = mean(entropy),
            sd = sd(entropy),
            min = min(entropy),
            max = max(entropy)## # A tibble: 3 x 6
## class count mean sd min max
## <fct> <int> <dbl> <dbl> <dbl> <dbl>
## 1 1 184 0.740 0.239 0.369 1.00
## 2 2 119 0.690 0.225 0.187 0.993
## 3 3 414 0.666 0.197 0.172 0.974
ggplot(df entropy, \text{aes}(y = \text{class}, x = \text{entropy}, \text{ fill} = \text{class})) +
  geom_density_ridges(stat = "binline", bins = 21,
                      scale = 0.9, alpha = 0.5) +scale_x_{continuous}(breaks = seq(0, 1, by=0.1)),limits = c(0, 1.05)) +scale_fill_manual(values = mclust.options("classPlotColors")) +
  geom_vline(xintercept = E, lty = 2) +
  \text{labs}(x = "Case-specific entropy contribution",y = "Latent class") +
  theme_ridges(center_axis_labels = TRUE) +
```

```
theme(legend.position = "none",
      panel.\,spacing = unit(1, "lines"),strip.text.x = element_test(size = 8))
```


```
# Average posterior probabilities by latent class:
df_AvePP <- data.frame(class = as.factor(class), pp = probs_map)
df_AvePP |>
 group_by(class) |>
 summarise(count = n(),
           mean = mean(pp),
           sd = sd(pp),
           min = min(pp),
           max = max(pp)## # A tibble: 3 x 6
## class count mean sd min max
## <fct> <int> <dbl> <dbl> <dbl> <dbl>
## 1 1 184 0.864 0.160 0.513 1.00
## 2 2 119 0.858 0.146 0.468 0.999
## 3 3 414 0.850 0.135 0.502 0.996
ggplot(df_AvePP, aes(y = class, x = pp, fill = class)) +geom_density_ridges(stat = "binline", bins = 21,
```


We note that all entropy and AvePP quantities appear satisfactory from the point of view of indicating reasonably well-separated clusters.

Discussion

Using a person-centered method (finite Gaussian mixture model), the present analysis uncovered the heterogeneity within the SEM engagement data by identifying three latent or unobserved clusters: low, medium, and high engagement clusters. Uncovering the latent structure could help understand individual differences among students, identify the complex multidimensional variability of a construct —engagement in our case— and possibly help personalize teaching and learning. Several studies have revealed similar patterns of engagement which —similar to the current analysis— comprise three levels that can be roughly summarized as high, moderate, and low (Saqr and López-Pernas 2021; Archambault and Dupéré 2016; Zhen et al. 2019). The heterogeneity of engagement has been demonstrated in longitudinal studies, in both face-to-face settings as well as online engagement (Saqr and López-Pernas 2021). Furthermore, the association between engagement and performance has been demonstrated to vary by achievement level, time of the year, as well as engagement state; that is, high achievers may at some point in their program descend to lower engagement states and still continue to have higher achievement (Saqr et al. 2023). Such patterns, variability, and individual differences are not limited to engagement, but has been reported for almost every major disposition in education psychology (Hickendorff et al. 2018).

On a general level, heterogeneity has been a hot topic in recent educational literature. Several calls have been voiced to adopt methods that capture different patterns or subgroups within students' behavior or functioning. Assuming that there is "an average" pattern that represents the entirety of student populations requires the measured construct to have the same causal mechanism, same development pattern, and affect students in exactly the same way. The average assumption is of course impossible and has been proven inaccurate across a vast number of studies (e.g., Hickendorff et al. (2018) and Törmänen et al. (2022)). Since heterogeneity is prevalent in psychological, behavioral, and physiological human data, person-centered methods will remain a very important tool for researchers (Bryan, Tipton, and Yeager 2021).

Person-centered methods can be grouped into traditional, algorithmic clustering methods on one hand and the model-based clustering paradigm on the other. The analysis of the SEM data centered here on the model-based approach, specifically the finite Gaussian mixture model framework. The **mclust** package enabled such models to be fitted quickly and easily and this framework exhibits many advantages over traditional clustering algorithms which rely on distancebased heuristics. Firstly, the likelihood-based underpinnings enable the selection of the optimal model using principled statistical model selection criteria. In particular, it is noteworthy in the present analysis that the model selection procedure was not limited to three-cluster solutions: mixtures with fewer or greater than three clusters were evaluated and the three-cluster solution supported by previous studies in education research— was identified as optimal according to the BIC. Secondly, the parsimonious modelling of the covariance structures provides the flexibility to model clusters with different geometric characteristics. In particular, the clusters in the present analysis, whereby each group is described by a single Gaussian component with varying volume and shape, but the same orientation aligned with the coordinate axes are more flexible than the spherical, Euclidean distance-based clusters obtainable under the *k*-means algorithm. Thirdly, the models relax the assumption that each observation is associated with exactly one cluster and yields informative clustermembership probabilities for each observation, which can be used to compute useful diagnostics such as entropies and average posterior probabilities which are unavailable under so-called "hard" clustering frameworks. Finally, the **mclust** package facilitates simple summaries and visualisations of the resulting clusters

and cluster-specific parameter estimates.

That being said, there are a number of methodological limitations of the GMM framework to be aware of in other settings. Firstly, and most obviously, such models are inappropriate for clustering categorical or mixed-type variables. **For clustering longitudinal categorical sequences, such as those in Chapter XXX**, model-based approaches are provided by the mixtures of exponentialdistance models framework of Murphy et al. (2021) (and the associated MEDseq) R package and the mixtures of hidden Markov models framework of Helske and Helske (2019) (and the associated seqHMM} package). Regarding mixed-type variables, McParland and Gormley (2016) provide a model-based framework (and the associated clustMD package.

Secondly, the one-to-one correspondence typically assumed between component distributions and clusters is is not always the case (Hennig 2010). This is only true if the underlying true component densities are Gaussian. When the assumption of component-wise normality is not satisfied, the performance of such models will deteriorate as more components are required to fit the data well. However, even for continuous data, GMMs tend to overestimate the number of clusters when the assumption of normality is violated. Two strategies for dealing with this are provided by the **mclust** package, one based on combining Gaussian mixture components according to an entropy criterion, and one based on a adding a so-called "noise component" —represented by a uniform distribution to the mixture. The noise component captures outliers with do not fit the prevailing patterns of Gaussian clusters, which would otherwise be assigned to (possibly many) small clusters and minimises their deleterious effect on parameter estimation for the other, more defined clusters. Further details of combining components and adding a noise component can be found in Scrucca et al. (2023, chap. 7). Alternatively, mixture models which depart from normality have been an active area of research in model-based clustering in recent years. Such approaches —some of which are available in the R package **mixture** (Pocuca, Browne, and McNicholas 2022)— replace the underlying Gaussian component distributions with e.g., generalised hyperbolic distributions, the multivariate *t* distribution, and the multivarate skew-*t* distribution.

A third main limitation of GMMs is their ineffectiveness in high-dimensional settings, when the data dimension *d* is comparable to or even greater than *n*. Among the 14 parsimonious parameterisations available in **mclust**, only models with diagonal covariance structures are tractable when $n \leq p$. Incorporating factor-analytic covariance decompositions in so-called finite Gaussian mixtures of factor analysers have been proposed for addressing this issue (Ghahramani and Hinton 1996; McLachlan, Peel, and Bean 2003). Imposing constraints on the parameters of such factor-analytic structures in the component covariance matrices in the spirit of **mclust** leads to another family of parsimonious Gaussian mixture models McNicholas and Murphy (2008), which are implemented in the R package **pgmm**. Model selection becomes increasingly difficult with such models, given the need to choose both the optimal number of mixture components and the

optimal number of latent factors (as well as the covariance parameterisation, in the case of **pgmm**). Infinite mixtures of infinite factor analysers —implemented in the R package **IMIFA**— are a recent, Bayesian extension which enable automatic inference of the number of components and the numbers of clusterspecific latent factors (Murphy, Viroli, and Gormley 2020).

Another recent extension, building directly on the 14 models from **mclust**, is the MoEClust model family of Murphy and Murphy (2020) and the associated **MoEClust** R package, which closely mimics its syntax. MoEClust effectively embeds Gaussian parsimonious clustering models in the mixtures of experts framework, enabling additional sources of heterogeneity in the form of covariates to be incorporated directly in the clustering model, to guide the construction of the clusters. Either, neither, or both the mixing proportions and/or component mean parameters can be modelled as functions of these covariates. The former is perhaps particularly appealing, given its analogous equivalence to latent profile *regression* (Dayton and Macready 1988). Hypothetically, assuming information on the gender and age of the students in the present analysis was available, such covariates would influence the probabilities of cluster membership under such a model, while the correspondence thereafter between the parameters of the component distributions and the clusters would have the same interpretation as per standard LPA models.

References

- Archambault, Isabelle, and Véronique Dupéré. 2016. "Joint Trajectories of Behavioral, Affective, and Cognitive Engagement in Elementary School." *The Journal of Educational Research* 110 (2): 188–98. [https://doi.org/10.1080/](https://doi.org/10.1080/00220671.2015.1060931) [00220671.2015.1060931.](https://doi.org/10.1080/00220671.2015.1060931)
- Banfield, J., and Adrian E. Raftery. 1993. "Model-Based Gaussian and Non-Gaussian Clustering." *Biometrics* 49 (3): 803–21. [https://doi.org/10.2307/](https://doi.org/10.2307/2532201) [2532201.](https://doi.org/10.2307/2532201)
- Bartholomew, David J, Martin Knott, and Irini Moustaki. 2011. *Latent Variable Models and Factor Analysis: A Unified Approach*. 3rd ed. Vol. 904. Wiley Series in Probability and Statistics. Chichester, UK: John Wiley & Sons.
- Basford, K E, D R Greenway, G J McLachlan, and D Peel. 1997. "Standard Errors of Fitted Component Means of Normal Mixtures." *Computational Statistics* 12 (1): 1–18.
- Biernacki, Christophe, Gilles Celeux, and Gérard Govaert. 2000. "Assessing a Mixture Model for Clustering with the Integrated Completed Likelihood." *IEEE Transactions on Pattern Analysis and Machine Intelligence* 22 (7): 719–25.
- Blei, David M, Andrew Y Ng, and Michael I Jordan. 2003. "Latent Dirichlet Allocation." *Journal of Machine Learning Research* 3: 993–1022.
- Bryan, Christopher J., Elizabeth Tipton, and David S. Yeager. 2021. "Behavioural Science Is Unlikely to Change the World Without a Heterogeneity Revolution." *Nature Human Behaviour* 5 (8): 980–89. [https:](https://doi.org/10.1038/s41562-021-01143-3)

[//doi.org/10.1038/s41562-021-01143-3.](https://doi.org/10.1038/s41562-021-01143-3)

- Celeux, Gilles, and Gérard Govaert. 1995. "Gaussian Parsimonious Clustering Models." *Pattern Recognition* 28 (5): 781–93. [https://doi.org/10.1016/0031-](https://doi.org/10.1016/0031-3203(94)00125-6) [3203\(94\)00125-6.](https://doi.org/10.1016/0031-3203(94)00125-6)
- Celeux, Gilles, and Gilda Soromenho. 1996. "An Entropy Criterion for Assessing the Number of Clusters in a Mixture Model." *Journal of Classification* 13 (2): 195–212.
- Cheng, Shonn, Jui-Chieh Huang, and Waneta Hebert. 2023. "Profiles of Vocational College Students' Achievement Emotions in Online Learning Environments: Antecedents and Outcomes." *Computers in Human Behaviour* 138: 107452. [https://doi.org/10.1016/j.chb.2022.107452.](https://doi.org/10.1016/j.chb.2022.107452)
- Cover, Thomas M, and Joy A Thomas. 2006. *Elements of Information Theory*. 2nd ed. Vol. 20. Wiley Series in Telecommunications and Signal Processing. New York, NY, USA: John Wiley & Sons.
- Dayton, C. M., and G. B. Macready. 1988. "Concomitant-Variable Latent-Class Models." *Journal of the American Statistical Association* 83 (401): 173–78.
- Dempster, A. P., N. M. Laird, and D. B. Rubin. 1977. "Maximum Likelihood from Incomplete Data via the EM Algorithm (with Discussion)." *Journal of the Royal Statistical Society: Series B (Statistical Methodology)* 39 (1): 1–38. [https://doi.org/10.1111/j.2517-6161.1977.tb01600.x.](https://doi.org/10.1111/j.2517-6161.1977.tb01600.x)
- Efron, Bradley. 1979. "Bootstrap Methods: Another Look at the Jackknife." *The Annals of Statistics* 7 (1): 1–26.
- Everitt, B. S., S. Landau, M. Leese, and D. Stahl. 2011. *Cluster Analysis*. Fifth. Vol. 848. Wiley Series in Probability and Statistics. New York, NY, USA: John Wiley & Sons.
- Fraley, Chris, and Adrian E. Raftery. 2002. "Model-Based Clustering, Discriminant Analysis, and Density Estimation." *Journal of the American Statistical Association* 97 (458): 611–31. [https://doi.org/10.1198/016214502760047131.](https://doi.org/10.1198/016214502760047131)
- ———. 2007. "Bayesian Regularization for Normal Mixture Estimation and Model-Based Clustering." *Journal of Classification* 24 (2): 155–81.
- Fraley, Chris, Adrian E. Raftery, and Luca Scrucca. 2023. *mclust: Gaussian Mixture Modelling for Model-Based Clustering, Classification, and Density Estimation*. [https://CRAN.R-project.org/package=mclust.](https://CRAN.R-project.org/package=mclust)
- Ghahramani, Z., and G. E. Hinton. 1996. "The EM Algorithm for Mixtures of Factor Analyzers." Department of Computer Science, University of Toronto.
- Helske, S., and J. Helske. 2019. "Mixture Hidden Markov Models for Sequence Data: The seqHMM Package in R." *Journal of Statistical Software* 88 (3): 1–32.
- Hennig, C. 2010. "Methods for Merging Gaussian Mixture Components." *Advances in Data Analysis and Classification* 4 (1): 3–34.
	- ———. 2015. "What Are the True Clusters?" *Pattern Recognition Letters* 64: 53–62.
- Hickendorff, Marian, Peter A Edelsbrunner, Jake McMullen, Michael Schneider, and Kelly Trezise. 2018. "Informative Tools for Characterizing Individual Differences in Learning: Latent Class, Latent Profile, and Latent Transition Analysis." *Learning and Individual Differences* 66: 4–15. [https://doi.org/10](https://doi.org/10.1016/j.lindif.2017.11.001)

[.1016/j.lindif.2017.11.001.](https://doi.org/10.1016/j.lindif.2017.11.001)

- Hoi, Vo Ngoc. 2023. "Transitioning from School to University: A Person-Oriented Approach to Understanding First-Year Students' Classroom Engagement in Higher Education." *Educational Review*, 1–21. [https://doi.org/](https://doi.org/10.1080/00131911.2022.2159935) [10.1080/00131911.2022.2159935.](https://doi.org/10.1080/00131911.2022.2159935)
- Howard, Matt C., and Michael E. Hoffman. 2018. "Variable-Centered, Person-Centered, and Person-Specific Approaches: Where Theory Meets the Method." *Organizational Research Methods* 21 (4): 846–76. [https://doi.org/10.1177/10](https://doi.org/10.1177/1094428117744021) [94428117744021.](https://doi.org/10.1177/1094428117744021)
- Jöreskog, Karl G. 1970. "A General Method for Analysis of Covariance Structures." *Biometrika* 57 (2): 239–51.
- McLachlan, G. J., and T. Krishnan. 2008. *The EM Algorithm and Extensions*. 2nd ed. Vol. 382. Wiley Series in Probability and Statistics. Hoboken, NJ, USA: Wiley-Interscience.
- McLachlan, G. J., and D. Peel. 2000. *Finite Mixture Models*. Vol. 299. Wiley Series in Probability and Statistics. New York, NY, USA: John Wiley & Sons.
- McLachlan, G. J., D. Peel, and R. W. Bean. 2003. "Modelling High-Dimensional Data by Mixtures of Factor Analyzers." *Computational Statistics & Data Analysis* 41: 379–88.
- McNicholas, P. D., and T. B. Murphy. 2008. "Parsimonious Gaussian mixture models." *Statistics and Computing* 18 (3): 285–96.
- McParland, D., and I. C. Gormley. 2016. "Model Based Clustering for Mixed Data: clustMD." *Advances in Data Analysis and Classification* 10 (2): 155–69.
- Murphy, Keefe, and Thomas Brendan Murphy. 2020. "Gaussian Parsimonious Clustering Models with Covariates and a Noise Component." *Advances in Data Analysis and Classification* 14 (2): 293–325. [https://doi.org/10.1007/s1](https://doi.org/10.1007/s11634-019-00373-8) [1634-019-00373-8.](https://doi.org/10.1007/s11634-019-00373-8)
- Murphy, Keefe, Thomas Brendan Murphy, Raffaella Piccarreta, and Isobel Claire Gormley. 2021. "Clustering Longitudinal Life-Course Sequences Using Mixtures of Exponential-Distance Models." *Journal of the Royal Statistical Society: Series A (Statistics in Society)* 184 (4): 1414–51. [https:](https://doi.org/10.1111/rssa.12712) [//doi.org/10.1111/rssa.12712.](https://doi.org/10.1111/rssa.12712)
- Murphy, Keefe, Cinzia Viroli, and I. Claire Gormley. 2020. "Infinite Mixtures of Infinite Factor Analysers." *Bayesian Analysis* 15 (3): 937–63.
- Newton, Michael A, and Adrian E Raftery. 1994. "Approximate Bayesian Inference with the Weighted Likelihood Bootstrap (with Discussion)." *Journal of the Royal Statistical Society: Series B (Statistical Methodology)* 56 (1): 3–48.
- Nylund-Gibson, K., and A. Y. Choi. 2018. "Ten Frequently Asked Questions about Latent Class Analysis." *Translational Issues in Psychological Science* 4 (4): 440–61.
- O'Hagan, Adrian, Thomas Brendan Murphy, Luca Scrucca, and Isobel Claire Gormley. 2019. "Investigation of Parameter Uncertainty in Clustering Using a Gaussian Mixture Model via Jackknife, Bootstrap and Weighted Likelihood Bootstrap." *Computational Statistics* 34 (4): 1779–1813. [https:](https://doi.org/10.1007/s00180-019-00897-9)

[//doi.org/10.1007/s00180-019-00897-9.](https://doi.org/10.1007/s00180-019-00897-9)

- Pocuca, Nik, Ryan P. Browne, and Paul D. McNicholas. 2022. *mixture: Mixture Models for Clustering and Classification*. [https://CRAN.R-project.org/pack](https://CRAN.R-project.org/package=mixture) [age=mixture.](https://CRAN.R-project.org/package=mixture)
- R Core Team. 2023. *R: A Language and Environment for Statistical Computing*. Vienna, Austria: R Foundation for Statistical Computing. [https://www.R](https://www.R-project.org/)[project.org/.](https://www.R-project.org/)
- Rosenberg, Joshua M., Patrick N. Beymer, Daniel J. Anderson, Caspar J. Van Lissa, and Jennifer A. Schmidt. 2018. "TidyLPA: An R Package to Easily Carry Out Latent Profile Analysis (LPA) Using Open-Source or Commercial Software." *Journal of Open Source Software* 3 (30): 978. [https://doi.org/10.21105/joss.00978.](https://doi.org/10.21105/joss.00978)
- Rubin, Donald B. 1981. "The Bayesian Bootstrap." *The Annals of Statistics* 9 $(1): 130-34.$
- Saqr, Mohammed, and Sonsoles López-Pernas. 2021. "The Longitudinal Trajectories of Online Engagement over a Full Program." *Computers & Education* 175 (December): 104325. [https://doi.org/10.1016/j.compedu.2021.104325.](https://doi.org/10.1016/j.compedu.2021.104325)
- ———. 2022. "How CSCL Roles Emerge, Persist, Transition, and Evolve over Time: A Four-Year Longitudinal Study." *Computers & Education* 189: 104581. [https://doi.org/10.1016/j.compedu.2022.104581.](https://doi.org/10.1016/j.compedu.2022.104581)
- Saqr, Mohammed, Sonsoles López-Pernas, Satu Helske, and Stefan Hrastinski. 2023. "The Longitudinal Association Between Engagement and Achievement Varies by Time, Students' Subgroups, and Achievement State: A Full Program Study." *Computers & Education* 199: 104787. [https://doi.org/10.1016/j.co](https://doi.org/10.1016/j.compedu.2023.104787) [mpedu.2023.104787.](https://doi.org/10.1016/j.compedu.2023.104787)
- Scheidt, Matthew, Allison Godwin, Edward Berger, John Chen, Brian P Self, James M Widmann, and Ann Q Gates. 2021. "Engineering Students' Noncognitive and Affective Factors: Group Differences from Cluster Analysis." *Journal of Engineering Education* 110 (2): 343–70. [https://doi.org/10.1002/](https://doi.org/10.1002/jee.20386) [jee.20386.](https://doi.org/10.1002/jee.20386)
- Schwarz, G. 1978. "Estimating the Dimension of a Model." *The Annals of Statistics* 6 (2): 461–64. [https://doi.org/10.1214/aos/1176344136.](https://doi.org/10.1214/aos/1176344136)
- Scrucca, Luca, Michael Fop, T. Brendan Murphy, and Adrian E. Raftery. 2016. "mclust 5: Clustering, Classification and Density Estimation Using Gaussian Finite Mixture Models." *The R Journal* 8 (1): 205–33. [https://doi.org/10.3](https://doi.org/10.32614/RJ-2016-021) [2614/RJ-2016-021.](https://doi.org/10.32614/RJ-2016-021)
- Scrucca, Luca, Chris Fraley, T. Brendan Murphy, and Adrian E. Raftery. 2023. *Model-Based Clustering, Classification, and Density Estimation Using mclust in R*. The R Series. London, UK: Chapman & Hall/CRC Press. [https:](https://doi.org/10.1201/9781003277965) [//doi.org/10.1201/9781003277965.](https://doi.org/10.1201/9781003277965)
- Spearman, C. 1904. "'General Intelligence,' Objectively Determined and Measured." *The American Journal of Psychology* 15 (2): 201–92. [https:](https://doi.org/10.2307/1412107) [//doi.org/10.2307/1412107.](https://doi.org/10.2307/1412107)
- Törmänen, Järvenoja, Saqr, Malmberg, et al. 2022. "A Person-Centered Approach to Study Students' Socio-Emotional Interaction Profiles and Regulation of Collaborative Learning." *Frontiers in Education* 7. [https://doi.org/](https://doi.org/10.3389/feduc.2022.866612)

[10.3389/feduc.2022.866612.](https://doi.org/10.3389/feduc.2022.866612)

- Yu, Jianhui, Changqin Huang, Tao He, Xizhe Wang, and Linjie Zhang. 2022. "Investigating Students' Emotional Self-Efficacy Profiles and Their Relations to Self-Regulation, Motivation, and Academic Performance in Online Learning Contexts: A Person-Centered Approach." *Education and Information Technologies* 27 (8): 11715–40. [https://doi.org/10.1007/s10639-022-11099-0.](https://doi.org/10.1007/s10639-022-11099-0)
- Zhang, Yingbin, Luc Paquette, Juan D Pinto, Qianhui Liu, and Aysa Xuemo Fan. 2023. "Combining Latent Profile Analysis and Programming Traces to Understand Novices' Differences in Debugging." *Education and Information Technologies* 28 (4): 4673–4701. [https://doi.org/10.1007/s10639-022-11343-7.](https://doi.org/10.1007/s10639-022-11343-7)
- Zhen, Rui, Ru-De Liu, Ming-Te Wang, Yi Ding, Ronghuan Jiang, Xinchen Fu, and Yan Sun. 2019. "Trajectory Patterns of Academic Engagement Among Elementary School Students: The Implicit Theory of Intelligence and Academic Self-Efficacy Matters." *British Journal of Educational Psychology* 90 (3): 618–34. [https://doi.org/10.1111/bjep.12320.](https://doi.org/10.1111/bjep.12320)
- Zucchini, Walter, Iain L MacDonald, and Roland Langrock. 2016. *Hidden Markov Models for Time Series: An Introduction Using R*. Vol. 105. Monographs on Statistics and Applied Probability. London, UK: Chapman & Hall/CRC Press.