The Spark Randomizer: a learned randomized framework for computing Gröbner bases

Shahrzad Jamshidi and Sonja Petrović¹

Abstract: We define a violator operator which captures the definition of a minimal Gröbner basis of an ideal. This construction places the problem of computing a Gröbner basis within the framework of violator spaces, introduced in 2008 by Gärtner, Matoušek, Rüst, and Škovroň in a different context. The key aspect which we use is their successful utilization of a Clarkson-style fast sampling algorithm from geometric optimization. Using the output of a machine learning algorithm, we combine the prediction of the size of a minimal Gröbner basis of an ideal with the Clarkson-style biased random sampling method to compute a Gröbner basis in expected runtime linear in the size of the violator space.

1. Introduction

The problem of finding a good basis for a polynomial system is the non-linear analogue of the computation of a reduced row echelon form. This problem is essential in statistics, optimization, and other fields of science and engineering that rely on solving systems of polynomial equations. A good basis is one that allows algorithms to run and return unique outputs, and a Gröbner basis is a canonical example; see Sturmfels (2005) for a high-level overview. A Gröbner basis of an ideal guarantees a solution to the ideal membership problem and the problem of detecting system feasibility, through the use of the multivariate polynomial division algorithm.

Since the mid 20th century, when Gröbner bases (Buchberger, 1965) and standard bases (Hironaka, 1964) were introduced, there has been a tremendous amount of activity in developing methods and software for solving polynomial systems. All mainstream computer algebra systems offer generic algorithms for computing Gröbner bases applicable to all kinds of input ideals. Despite this great success in the field, unfortunately, algebraic problems have bad worst-case complexity. Buchberger's groundbreaking algorithm is able to compute a Gröbner basis of any ideal, but its computational complexity is difficult to estimate due to a number of choices one can make during its implementation. What is known, for example by Dube (1990), is that the maximum of the degrees of polynomials in the reduced Gröbner basis is doubly exponential in the number of variables. Bardet et al. (2015) offer a nice overview of the upper and lower bounds that provide the general doubly exponential complexity result. Along a different avenue, Peifer (2021) discovered a new selection strategy for processing polynomials in Buchberger's algorithm using reinforcement learning.

In a few cases, specialized algorithms have been used to improve runtime, such as Beltrán and Pardo (2008, 2009); Cox et al. (2007). For the special case of toric ideals, De Loera et al. (2004) provide a polynomial time algorithm for Gröbner bases of toric ideals, which uses

 $^{^{1}}$ SJ is at Lake Forest College. SP is at Illinois Institute of Technology. Supported by DOE award #1010629 and the Simons Foundation Collaboration Travel Gift #854770.

Barvinok's short rational generating functions and it returns not a list of polynomials, but rather the rational generating function; see also De Loera et al. (2004) and 4ti2 (2018).

What is remarkable is that all known approaches for computing Gröbner bases of *general* ideals rely upon variants of Buchberger's approximately 60-year-old algorithm. Improvements on it, such as Faugère's famous F5 algorithm developed in Faugére et al. (1993, 2014), leverage the fact that the computation is a generalization of Gaussian elimination; see Bardet et al. (2015) for an overview of its complexity. As such, these methods construct nontrivial organizational techniques, for example, cleverly organizing monomials into large matrices, to judiciously perform Buchberger's key step: reduction of S-polynomials through multivariate division.

Our approach is distinct from these methods because we rely on a cleverly biased random sampling method rather than cleverly organized versions of Buchberger's algorithm. We take a departure from the standard algorithms based on S-polynomials and address the problem of computing Gröbner bases using violator spaces. As we will see, violator spaces allow for adaptation of randomized algorithms to computational non-linear algebra. Figure 1 provides a schematic view of the proposed computational framework. For the non-expert, the ideal notation, vocabulary, and the setup of violator spaces are explained in Section 2 on page 4.



FIG 1. A schematic view of the Spark Randomizer framework for a learned/randomized Gröbner computation. Given a generating set, $\{f_1, \ldots, f_s\}$ and a monomial order \prec , we predict two values using machine learning: the total degree (m) and the cardinality of a minimal Gröbner basis (k). From the generating set and m, we construct a set \mathcal{H} , from which we take samples of size k. We continually resample (biased) until we construct a minimal Gröbner basis $\{g_1, \ldots, g_k\}$, which is checked using the violator space primitive query. Note that prediction of k is critical, while that of m can be bypassed if there is an alternative way to construct \mathcal{H} for a specific problem instance.

The input and output to the problem are standard: the input consists of a set of polynomials f_1, \ldots, f_s and a monomial order, and the output is a minimal Gröbner basis of the ideal they generate. The two machine learning algorithms ("ML 1" and "ML 2" in the Figure) are used to predict the total degree (m) and the cardinality of the minimal Gröbner basis (k) of the ideal $\langle f_1, \ldots, f_s \rangle$; ML1 is optional. These algorithms guide the construction of the set \mathcal{H} and the size of each sample from it. We then use the framework of violator spaces and Clarkson-style algorithms to sample from the universe \mathcal{H} and solve small subproblems, embedded in an iterative biased sampling scheme. The small subproblems are solved using the violator space primitive query ("Check" in the Figure). In the end, the local information is used to make a global decision about the entire system. The expected runtime is linear in the number of input elements to the violator framework, $|\mathcal{H}|$.

The Spark Randomizer blends randomization and learning with symbolic computation:

Theorem 1.1 (The Spark Randomizer). Let $I = \langle f_1, \ldots, f_s \rangle \subset K[x_1, \ldots, x_n]$ be an ideal and fix a monomial ordering \prec . Let $\mathcal{H} \subset I$ be any finite set guaranteed to contain a minimal Gröbner basis of I. Let k be the output of a (machine learning) algorithm which predicts the size δ of a minimal \prec -Gröbner basis of I, with $k \geq \delta$.

Then there exists a sampling algorithm that outputs a Gröbner basis of I in an expected number $O(k|\mathcal{H}| + k^{O(k)})$ calls to the violator primitive query that solves a small monomial ideal membership problem.

In particular, if $k = \delta$, the output is a minimal Gröbner basis.

This main result will follow as a consequence of the new violator space construction, Theorem 3.3. It is a combination of Corollary 3.4 and the outputs of machine learning algorithms, once we set up the appropriate violator space, provide an estimate of its combinatorial dimension k, and machine-learn the sampling universe \mathcal{H} into existence. These three tasks are contents of Sections 3.1, 3.2, and 3.3, respectively. In particular, examples of worst-case universes \mathcal{H} appear on page 11.

Before providing the mathematical results, we summarize related work for further context.

Why randomization?

In other areas of computational mathematics, significant improvements in efficiency of deterministic algorithms have been obtained by algorithms that involve randomization. In 1992, Sharir and Welzl identified special kinds of geometric optimization problems that lend themselves to solution via repeated sampling of smaller subproblems: they called these LP-type problems. A powerful sampling scheme, devised in Clarkson (1995) for linear programming, works particularly well for geometric optimization problems in small number of variables. Examples of applications include convex and linear programming, integer linear programming, the problem of computing the minimum-volume ball or ellipsoid enclosing a given point set in \mathbb{R}^n , and the problem of finding the distance of two convex polytopes in \mathbb{R}^n . In 2008, Gärtner, Matoušek, Rüst and Škovroň Gärtner et al. (2008) invented violator spaces and showed they give a much more general framework to work with LP-type problems. In fact, violator spaces include all prior abstractions and were proven in Škovroň (2007) to be the most general framework in which Clarkson's sampling converges to a solution. It does so with expected runtime linear in the size of the input, as explained in Section 2.

In symbolic computation specifically, randomization can be used to improve algorithm performance as illustrated, for example, in De Loera et al. (2016); Solovay and Strasse (1977); Spielman and Teng (2001); Breiding et al. (2018).

Violator spaces in non-linear algebra

There exists a precedent for using violator spaces for problems involving polynomial ideals. Namely, De Loera et al. (2016) presented two violator operators: for computing minimal generating sets and certificate sub-systems for large polynomial systems. Their proof-of-concept implementation in Macaulay2 demonstrated the usefulness on an infeasible system built from a standard family of examples well-known for its Gröbner complexity, bringing down the computation time from > 20 hours to just seconds. The randomized algorithm's expected runtime is linear in the number of input polynomials. Violator spaces make an appearance in problems that have a natural linearization and a sampling size given by a combinatorial Helly number of the problem. While violator spaces and Clarkson's algorithm have already a huge range of applications, to our knowledge, De Loera et al. (2016) was the first time such biased sampling was used in computational algebraic geometry.

Machine learning for non-linear algebra

Machine learning can be used to predict various ingredients in symbolic algebraic computations. For example, He (2022) offers an overview of recent research on machine-learning mathematical structures; see also Lample and Charton (2020); Higham and Higham (2018). The thesis Silverstein (2019) uses features in neural network training to select the best algorithm to perform a Hilbert series computation by predicting a best choice of a monomial for one of the crucial steps of the computation, namely predicting a best pivot rule for the given input.

Peifer et al. (2020a) and Mojsilović et al. (2023) demonstrate how Buchberger's algorithm is well-suited for a machine learning approach, which is another precedent into which we lean. Specifically, Buchberger's algorithm computes a Gröbner basis using an iterative procedure based on multivariate long division. The runtime of each step of the algorithm is typically dominated by a series of polynomial additions, and the total number of these additions is a hardware-independent performance metric that is often used to evaluate and optimize various implementation choices. Mojsilović et al. predict, using just the generating set, the number of polynomial additions that will take place during one run of Buchberger's algorithm. Good predictions are useful for quickly estimating difficulty and understanding what features make Gröbner basis computation hard. They show that a multiple linear regression model built from a set of easy-to-compute ideal generator statistics can predict the number of polynomial additions somewhat well, better than an uninformed model, and better than regression models built on some intuitive commutative algebra invariants that are more difficult to compute. They also train a simple recursive neural network that outperforms these linear models. These results can directly be used for value models in the reinforcement learning approach to optimize Buchberger's algorithm introduced by Peifer et al. who, within the paradigm of using learning to improve algorithms that give the exact answer, use machine learning to discover new Spair selection strategies in Buchberger's algorithm which outperform state-of-the-art humandesigned heuristics by 20% to 40%.

Although these learning results are not used as direct input to Spark Randomizer—they are about Buchberger's algorithm heuristics—they support the following core belief: that many algorithms in symbolic computation that relate to solving some polynomial systems are well-suited for machine learning techniques. The machine learning methods we do use for our framework are detailed in Section 3.2.

2. Notation and background

Denote by K a field, for example the reader may keep $K = \mathbb{C}$ in mind. Let $f_1 = 0, \ldots, f_s = 0$ be a system of s polynomial equations in n variables with coefficients in K. We will denote by

 $\langle f_1, \ldots, f_s \rangle \subset R = K[x_1, \ldots, x_n]$ the ideal generated by these polynomials. If $F = \{f_1, \ldots, f_s\}$ is a set of polynomials, the ideal $\langle f_1, \ldots, f_s \rangle$ will equivalently be denoted by $\langle F \rangle$.

Fix a monomial order \prec on R and an ideal I. Denote by $LT_{\prec}(h)$ the initial term of $h \in R$, which is the \prec -largest monomial. The initial ideal of I with respect to \prec is the monomial ideal $LT_{\prec}(I) := \langle LT_{\prec}(h) : h \in I \rangle$. For the Gröbner basis definitions, Cox et al. (2007) is a standard textbook reference.

Definition 2.1. A finite subset $B \subset I$ is a *Gröbner basis* of $I \subset R$ with respect to \prec if the initial terms of B generate the entire initial ideal:

$$LT_{\prec}(B) := \langle LT_{\prec}(b) : b \in B \rangle = LT_{\prec}(I) := \langle LT_{\prec}(f) : f \in I \rangle.$$

A Gröbner basis is *minimal* if the monomial generators of the initial ideal are minimal generators.

A minimal Gröbner basis is not unique. Its size, on the other hand, is always the number of minimal generators, or the (0-th) total Betti number, of the initial ideal $LT_{\prec}(I)$.

Sturmfels (2005) offers a high-level overview of Gröbner bases and the textbook Cox et al. (2007) discusses various applications as well. Of the many applications we single out two that have generated tremendous interest in recent decades: discrete optimization De Loera et al. (2013); Thomas (1995) and statistics Robbiano (2011); Sturmfels (1991).

From a different part of mathematics, we now introduce the basics of violator spaces, which were defined in the following context. An abstract LP-type problem is a tuple (H, w, W, \leq) . A constraint $h \in H$ violates a set $G \subseteq H$ of constraints if $w(G \cup \{h\}) > w(G)$. The classical example is the smallest enclosing ball problem: H is a finite point set in \mathbb{R}^d and w(G) is the radius of the smallest ball that encloses all points of G. A point h violates a set G if it lies outside of the smallest ball enclosing G. The violator mapping of (H, w, W, \leq) is defined by $\mathsf{V}(G) = \{h \in H : w(G \cup \{h\}) > w(G)\}$. Thus, $\mathsf{V}(G)$ is the set of all constraints violating G. Finally, a violator space is defined as follows.

Definition 2.2 (Gärtner et al. (2008)). Let \mathcal{H} be a finite set and V a mapping $2^{\mathcal{H}} \to 2^{\mathcal{H}}$. A violator space is a pair $(\mathcal{H}, \mathsf{V})$ such that the following two axioms hold:

Consistency: $G \cap V(G) = \emptyset$ holds for all $G \subseteq \mathcal{H}$, and

Locality: V(G) = V(F) holds for all $F \subseteq G \subseteq H$ such that $G \cap V(F) = \emptyset$.

A basis of a violator space is defined in analogy to a basis of a linear programming problem: a minimal set of constraints that defines a solution space. Every proper subset of the basis is violated by a basis element. Violator spaces are also equipped with a natural combinatorial invariant, namely, the size of a largest basis.

Definition 2.3 ((Gärtner et al., 2008, Definitions 7 and 19)). A set $B \subseteq \mathcal{H}$ is a *basis* if $B \cap V(F) \neq \emptyset$ holds for all proper subsets $F \subset B$. For $G \subseteq \mathcal{H}$, a basis of G is a minimal subset B of G with V(B) = V(G). The size of a largest basis of a violator space (\mathcal{H}, V) is called the *combinatorial dimension* $\delta = \delta(\mathcal{H}, V)$ of (\mathcal{H}, V) .

Gärtner et al. proved that knowing the violations V(G) for all $G \subseteq \mathcal{H}$ is enough to compute the largest bases. To do so one can utilize Clarkson's randomized algorithm, which is built on the primitive operation used as a black box in all stages of the algorithm: **Definition 2.4.** Given a violator space $(\mathcal{H}, \mathsf{V})$, some set $G \subsetneq \mathcal{H}$, and some element $h \in \mathcal{H} \setminus G$, the *primitive test* decides whether $h \in \mathsf{V}(G)$.

The following key result, which we will use, concerns the complexity of finding a basis. The runtime is given in terms of the combinatorial dimension $\delta(\mathcal{H}, V)$ and the size of H.

Theorem 2.5. (Gärtner et al., 2008, Theorem 27) Using Clarkson's algorithms, a basis of \mathcal{H} in a violator space (\mathcal{H}, V) whose combinatorial dimension is δ can be found by answering the primitive query an expected $O\left(\delta |\mathcal{H}| + \delta^{O(\delta)}\right)$ times.

Remark 2.6. The key insight is that answering the primitive query many times for small subsets of the universe is orders of magnitude faster, on average, than answering it once for the entire universe, which would be the brute-force method to solving the problem.

The sampling method in Clarkson (1995) avoids a full brute-force approach of testing each subset of size δ to see if it is a basis. The sampling method is presented in two stages, referred to as Clarkson's first and second algorithm.

Algorithm 1: Clarkson's first algorithm, see also De Loera et al. (2016).

```
input : G \subseteq \mathcal{H}, \delta: combinatorial complexity of H
     output: \mathcal{B}, a basis for G
 1 if |G| < 9\delta^2 then
           return Basis2(G)
 \mathbf{2}
 3 else
           W \leftarrow \emptyset
 \mathbf{4}
 5
            repeat
                  R \leftarrow random subset of G \setminus W with |\delta \sqrt{|G|}| elements.
  6
                  C \leftarrow \text{Basis2}(W \cup R)
  \mathbf{7}
  8
                  V \leftarrow \{h \in G \setminus C \text{ s.t. } h \in \mathsf{V}(C)\}
                  if |V| \leq 2\sqrt{|G|} then
  9
                        W \leftarrow W \cup V
\mathbf{10}
                  end
\mathbf{11}
           until V = \emptyset
12
13 end
14 return C.
```

Clarkson's first algorithm, in the first iteration, draws a small random sample $R \subset G$, calls the second algorithm to calculate the basis C of R, and returns C if it is already a basis for the larger subset G. If C is not already a basis, but the elements of $G \setminus C$ violating R are few, it adds those elements to a growing set of violators W, and repeats the process with C being calculated as the basis of the set $W \cup R$ for a new randomly chosen small $R \subset G \setminus W$. The crucial point here is that |R| is much smaller than |G|.

Clarkson's second algorithm (Basis2) iteratively picks a random small ($6\delta^2$ elements) subset R of G, finds a basis C for R by exhaustively testing each possible subset (BruteForce), taking advantage of the fact that the sample R is very small, and then calculates the violators of $G \setminus C$. At each iteration, elements that appear in bases with small violator sets get a higher probability of being selected.

It is critical to realize that the sampling process biased in a way that some elements will be more likely to be chosen according to 'how likely' they are to be elements in a basis. The

Algorithm 2: Clarkson's second algorithm: Basis2(G), see also De Loera et al. (2016).

```
input : G \subseteq \mathcal{H}; \delta: combinatorial complexity of H.
     output: \mathcal{B}: a basis of G
 1 if |G| \leq 6\delta^2 then
           return BruteForce(G)
 \mathbf{2}
 3 else
           repeat
 \mathbf{4}
                  R \leftarrow random subset of G with 6\delta^2 elements.
  5
                  C \leftarrow \operatorname{BruteForce}(R)
  6
                  V \leftarrow \{h \in G \setminus C \text{ s.t. } h \in \mathsf{V}(C)\}
  7
                 if \mathfrak{m}(V) < \mathfrak{m}(G)/3\delta then
  8
                        for h \in V do
  9
                             \mathfrak{m}(h) \leftarrow 2\mathfrak{m}(h)
10
                        end
11
                 end
12
           until V = \emptyset
13
14 end
15 return C.
```

algorithm does this by associating with every element h of the set G a multiplicity $\mathfrak{m}(h)$, and the multiplicity of a set is the sum of the multiplicities of its elements. The value $\mathfrak{m}(h)$ penalizes frequent appearance of h as a violation of a given set.

The entire process is repeated until a basis of G is found, that is, until there are no violators of the selected (basis) set C.

3. Gröbner-violator framework

3.1. The violator operator that captures Gröbner bases

To adapt this sampling scheme to the problem of computing Gröbner bases, the key is to determine if there exists a violator space whose basis will be a Gröbner basis of an ideal. Given that violator bases are minimal subsets that capture all violations of a given set, the following definition is intuitive.

Definition 3.1. Fix a monomial ordering \prec . Let $\mathcal{H} \subset R$ be a finite set of polynomials and $S \subset \mathcal{H}$. Define the following mapping to capture the set of polynomials in the universe \mathcal{H} whose initial terms lie outside the initial ideal of S:

$$\mathsf{V}_{\prec}(S) := \{ h \in \mathcal{H} : \mathrm{LT}_{\prec}(S) \subsetneq \mathrm{LT}_{\prec}(S \cup \{h\}) \}.$$

This is the natural violator space for the problem of computing a minimal Gröbner basis because the violations are those polynomials that grow the initial ideal within the universe \mathcal{H} . Proposition 3.2 guarantees, for any monomial order \prec and any finite set $\mathcal{H} \subset R$, that the pair (\mathcal{H}, V_{\prec}) is a violator space.

Proposition 3.2. The operator $V_{\prec}(S)$ satisfies violator space axioms.

Proof. Consistency. Let $g \in G$. Then $LT_{\prec}(G) = LT_{\prec}(G \cup \{g\})$, thus $g \notin V_{\prec}(G)$. On the other hand, let $g \in V_{\prec}(G)$. Then $LT_{\prec}(G) \subsetneq LT_{\prec}(G \cup \{g\})$. In particular, $LT_{\prec}(g) \notin LT_{\prec}(G)$ and therefore $LT_{\prec}(g) \notin \{LT_{\prec}(f) : f \in G\}$, thus $g \notin G$.

Locality. Suppose $F \subseteq G$ with $G \cap V_{\prec}(F) = \emptyset$. The aim is to prove that the violating sets $V_{\prec}(F)$ and $V_{\prec}(G)$ agree. Note that $F \subset G$ immediately implies $V_{\prec}(G) \subset V_{\prec}(F)$, so we need only prove the other inclusion.

Given that no element of G violates F, $LT_{\prec}(F) = LT_{\prec}(F \cup \{g\})$ holds for all $g \in G$, and in particular $LT_{\prec}(g) \in LT_{\prec}(F)$ so $LT_{\prec}(F) = LT_{\prec}(G)$.

Suppose h violates F, that is, $LT_{\prec}(F) \subsetneq LT_{\prec}(F \cup \{h\})$. Then the following sequence of inclusions holds:

$$\mathrm{LT}_{\prec}(G) = \mathrm{LT}_{\prec}(\cup_{g \in G \setminus F} F \cup \{g\}) = \mathrm{LT}_{\prec}(F) \subsetneq \mathrm{LT}_{\prec}(F \cup \{h\}) \subseteq \mathrm{LT}_{\prec}(G \cup \{h\}),$$

and therefore $LT_{\prec}(G) \subsetneq LT_{\prec}(G \cup \{h\})$, in other words, h also violates G. Therefore $V_{\prec}(F) \subset V_{\prec}(G)$, as required.

Theorem 3.3. Fix a finite set of polynomials $\mathcal{H} \subset R$ and a monomial order \prec . Then a largest basis of the violator space (\mathcal{H}, V_{\prec}) contains all the elements in the minimal Gröbner basis of $\langle \mathcal{H} \rangle$ which live in \mathcal{H} .

In particular, for a fixed ideal $I \subset R$ and a finite subset $\mathcal{H} \subset I$ that is guaranteed to contain $a \prec$ -Gröbner basis of I, a largest basis of (\mathcal{H}, V_{\prec}) is a minimal Gröbner basis of I.

Proof. A basis B of a subset $G \subset \mathcal{H}$ is an inclusion-minimal subset B with the same violators as those of G. For the violator operator V_{\prec} , this translates to a set capturing the minimal generators of the initial ideal that live in G. One may think of any basis B of $G \subset \mathcal{H}$ as a partial minimal Gröbner basis of $I = \langle \mathcal{H} \rangle$: one that is built from elements in G only.

Since the universe \mathcal{H} is finite, there exists a largest basis \mathcal{B} of the violator space (\mathcal{H}, V_{\prec}) , namely, a set \mathcal{B} such that $\mathcal{B} \cap V_{\prec}(F) \neq \emptyset$ for all proper subsets $F \subsetneq \mathcal{B}$. A largest basis \mathcal{B} captures all violations of \mathcal{H} and consists of a set of polynomials in the universe \mathcal{H} whose initial terms minimally generate $LT_{\prec}(\mathcal{H})$.

In the case when $\mathcal{H} \subset I$ contains a Gröbner basis of I, we have $I = \langle \mathcal{H} \rangle$, and therefore any largest basis of the violator space is a minimal Gröbner basis of I.

We can now apply Clarkson's algorithms using the violator operator V_{\prec} from Definition 3.1.

Corollary 3.4. Let $I = \langle f_1, \ldots, f_s \rangle \subset K[x_1, \ldots, x_n]$ be an ideal and fix a monomial ordering \prec . Let $\mathcal{H} \subset I$ be any finite set guaranteed to contain a \prec -Gröbner basis of I. Let δ be the combinatorial dimension of the violator space (\mathcal{H}, V_{\prec}) .

Then there exists a sampling algorithm that outputs a minimal Gröbner basis of I in an expected number $O(\delta|\mathcal{H}|+\delta^{O(\delta)})$ calls to the primitive query that solves a small monomial ideal membership problem.

Note that the combinatorial dimension of the violator space (\mathcal{H}, V_{\prec}) is the size of any minimal \prec -Gröbner basis of the ideal *I*; see Definition 2.3.

The primitive query for the operator V_{\prec} decides whether an element $h \in \mathcal{H}$ satisfies $h \in V_{\prec}(S)$ for a *small* subset $S \subset \mathcal{H}$; see Definition 2.4. Running this primitive as a black box, as Clarkson does, requires *one* Gröbner basis computation to determine $LT_{\prec}(S)$, followed by

the monomial ideal membership, which is a simple divisibility check. We remind the reader of Remark 2.6, which says that many primitive queries outperform one large computation of a Gröbner basis. This is a consequence of how the biased sampling algorithm is set up.

Our results prove feasibility and correctness of the Spark Randomizer framework. What remains to make this framework *practical* are the following: the estimate of, or upper bound on, the combinatorial dimension δ , and the construction of the universe \mathcal{H} from which to sample. These are discussed in the next two sections; in particular, we use machine learning to predict the necessary combinatorial invariants.

3.2. Learning the combinatorial dimension of the Gröbner violator space

There do exist upper bounds on the size of a reduced Gröbner basis appear in Peifer et al. (2020b). In the generic case and for the grevlex monomial ordering, Bardet et al. (2015) provide a complexity result on the runtime of Faugère's F5 algorithm, and note that this is also a bound on the number of polynomials for a reduced Gröbner basis, independently of the algorithm used. The sizes of a reduced and a minimal Gröbner bases agree and they equal the combinatorial dimension of the violator space V_{\prec} . In the context of Spark Randomizer, in reality, one only needs a 'reasonable' upper bound on the combinatorial dimension δ for the algorithm to work correctly, where reasonableness is determined by an order of magnitude reduction from the size of the universe \mathcal{H} . If the prediction is tight, the output is a minimal Gröbner basis; if it is an upper bound, the output is a superset of it.

The question as to whether machine learning technology can reliably predict the cardinality and degree of a reduced Gröbner basis given the input polynomials was initially tackled by Jamshidi et al. (2023). In that paper, the authors restrict their study to random binomial ideals with a fixed number of variables, generators, and total degrees, and they train neural networks for the problem. They exploit a t-SNE visualization van der Maaten and Hinton (2008) to illustrate that it is difficult to classify the data for a lack of clustering and the absence of a decision boundary. A t-SNE plot, short for t-distributed stochastic neighbor embedding, is a common statistical method for such a visualization. It assigns each datapoint a location on a 2- or 3-dimensional map; the data are then color-coded by the output, in the given case, size of the reduced graded reverse-lexicographic Gröbner basis. The t-SNE algorithm relies on the Euclidean distance between these vectors and converting them to conditional probabilities in order to visualize data. This choice of distance is not an arbitrary choice precisely because the L^2 norm, or mean squared error, is used in training neural networks via back propagation (i.e., gradient descent).

From the point of view of machine learning, the main difficulty lies in the fact that the Gröbner size prediction problems are very much *unlike* traditional machine learning benchmark problems, in which the input is complex but the humans can quickly validate the prediction. As an illustration, consider a data set of 99,722 binomial ideals in 3 variables, each generated by 5 homogenous binomials with total degree 7. For a human to 'quickly validate the prediction' one either needs good folklore knowledge of the problem, which does not exist for a random ideal, or one needs a way to visualize this high-dimensional data in two or three dimensions. Jamshidi et al. represent each ideal through the natural exponent vector representation of the generators. The t-SNE plot of this data set in Figure 2 demonstrates a lack of clustering and the absence of a decision boundary. This suggests a difficult classification



FIG 2. A t-SNE plot for 99,722 binomial ideals in 3 variables, each generated by 5 binomials (not necessarily homogeneous) with total degree 7. Output color represents the size of the reduced graded reverse-lexicographic Gröber basis.

problem.

As there exist no benchmarks for this learning task, they compare the performance of their neural network again a simple linear regression model, and show that the neural network model predicted the reduced Gröbner basis size better than multilinear regression from degree vector representations. Jamshidi et al. generate and make available a large data set that is able to capture sufficient variability in Gröbner complexity. Neural networks were trained, on datasets of about one million binomial ideals, to predict the cardinality of a reduced Gröbner basis and the maximum total degree of its elements. Simulations provided performance statistics on the order of $r^2 = 0.6$, which outperform both naive guess or multiple regression models which had $r^2 = 0.180$. The r-squared statistic, or the coefficient of determination, is a statistical measure of how close the data lie to the estimated regression line. For example, the baseline model which always predicts the mean will have an r^2 value of 0, and the model that exactly matches the observed values will have $r^2 = 1$. Models that do worse than then baseline prediction will have a negative r^2 value; this often happens when the linear regression training and testing data sets are drawn from completely different distributions.

This demonstrates that the learning problem is highly nontrivial, but possible.

3.3. A universe for the Gröbner violator and implications to complexity

The violator operator V_{\prec} is a natural one for the Gröbner computation; however, the universe from which we need to sample to find a basis does not follow the same kind of a setup as traditionally covered by Clarkson's algorithm. Namely, in problems of LP-type, such as finding the smallest enclosing ball for a finite set of given points in space, a basis of the violator space will be any subset of points that defines the ball capturing the rest of the points. The key point is that the universe \mathcal{H} is the set of given input points. In prior use of violators for computation with polynomials, that the situation was the same: in De Loera et al. (2016), the large input system of polynomial equations is the universe from which one samples small subsets of polynomials to find a certificate of infeasibility. In contrast, the setup for the Spark Randomizer is different, in that the universe from which one draws small samples is not given to us by the input set of polynomials. Instead, we have to create it from the generating set. Because the Spark Randomizer's runtime, on average, is linear in the size of the violator universe, it comes as no surprise that the complexity of the problem lives in the size of \mathcal{H} . Thus, crafting and pruning of \mathcal{H} is where the biggest gains of computational efficiency can be had. To represent \mathcal{H} within the computer, we propose a tensor representation of choices of monomials that can enter the ideal. This can be stored recursively in tables—a kind of ad hoc database structure—relying on the specified order of the monomials. A second critical practical question is pruning \mathcal{H} . For example, if one uses machine learning to estimate the maximum number of terms $\hat{\gamma}$ for any polynomial within the reduced Gröbner basis, and $\hat{\gamma} << \ell \binom{d+n}{n}$, then $|\mathcal{H}|$ can be reduced by deleting entries in the tensor.

It is probably instructive to consider the worst case in several scenarios. Recall that the number of monomials of degree exactly d in n variables is $\binom{d+n}{d}$, and the number of monomials up to degree d is $\binom{d+n}{n}$. If $K = \mathbb{F}_{\ell}$ is a finite field with ℓ elements, then the total number of terms, γ , in each polynomial of degree at most d in R is at most $\ell\binom{d+n}{n}$, which grows as $O(\binom{n+d}{n}) = O((n+d)^{\min(n,d)})$. In the homogeneous case, the upper bound on $|\mathcal{H}|$ is $2^{\gamma} < 2^{\ell\binom{d+n}{d}}$, which for fixed d smaller than n, this grows polynomially with the number variables n, on the order of $O(n^d)$. Of course, this upper bound is both bad and far from sharp, because the only ideal that will contain all these possible polynomials is $\langle 1 \rangle$.

For the special case of *binomial* ideals, one could construct the universe \mathcal{H} by taking all pairs of monomials up to degree d to generate the universe of binomials, which can be done in time quadratic in the number of monomials, so $O(\binom{d+n}{n}^2)$. This is, again, much larger than necessary as it does not take into account information from the input ideal; still, it results in a universe of theoretically manageable size: $|\mathcal{H}| = O(n^{2d})$.

For the sake of efficiency, crafting and storing all of \mathcal{H} before running the algorithm is probably not the most efficient idea. One should borrow insights from algebraic statistics and generate polynomials from the universe dynamically, rather than precomputing and storing the entire universe before running the sampling algorithm. Two such examples are Dobra (2012) and Gross et al. (2015) which, for a given matrix A, randomly generate binomials in the toric ideal I_A . The former paper does so to generate minimal generating sets. The latter generates a superset of the Graver basis of a 0/1 matrix A using the combinatorial structure of the hypergraph whose incidence matrix is A; by construction, the output contains a valid \mathcal{H} for the Spark Randomizer, because the Graver basis contains all Gröbner bases of I_A for every monomial order. In a shortly forthcoming joint paper, Bakenhus and Petrović describe an efficient algorithm for generating large sets of binomials from any toric ideal so that the probability of generating every binomial in the Graver basis is nonzero. Its input is the matrix A and the runtime is linear in the number of columns, which is the number of variables of the toric ideal.

4. Problems and discussion

The Spark Randomizer provides a feasible and correct framework for the use of randomization and machine learning to compute a Gröbner basis. Naturally, one can pose many questions to make the idea faster, more practical, or more flexible on specific families of examples. We outline a few such questions here. The neural network model used in Jamshidi et al. (2023) predicted the reduced Grobner basis size better than multilinear regression. It performed especially well when the total maximum degree was fixed at 15. This is, in fact, exactly the outcome one would have hoped for—the learning problem is highly nontrivial, but possible. To a machine learning expert, both network architecture and algorithms used therein are straightforward. On the other hand, the authors found no neural network model that predicted the maximum total degree well, nor one that could predict from summary statistics better than multiple linear regression, which had a very low r^2 score (on the order of 0.1 or negative).

Problem 1. Train a neural network model to predict maximum total degree of a minimal Gröbner basis element for a given ideal and a given monomial ordering.

In all cases, there are likely more opportunities for improvement in tackling the learning problem by reconsidering some of the more complex hyperparameters in a neural network, such as the cost function. A cost function that is more meaningful to the problem could allow for significantly better convergence to an optimal outcome. The reader is referred to (Jamshidi et al., 2023, Section 3) for background on neural networks and an explanation of parameter choices.

A slightly different point of view is to take a set of summary statistics from ideal generators as input to a learning algorithm, rather than all of the information, that is, explicit polynomials in full form. One could say there is a precedent for attempting such a summary: Mojsilović et al. used a subset of features from a data set on binomial ideals which did a reasonably good job in predicting the number of additions during one run of Buchberger's algorithm. Jamshidi et al. failed to obtain similar results with *the same* set of summary statistics; but this is not a surprise, because performance metrics of Buchberger's algorithm need not correlate with complexity of Gröbner bases. Therefore, we ask:

Problem 2. Find a set of summary statistics, computable (in polynomial time) from the defining set of polynomials, that can be used to predict the maximum total degree of a minimal Gröbner basis element for a given monomial ordering. Does such a set of summary statistics exist?

There is a possibility that there exist other violator spaces that can be useful to inform the Gröbner computation. For example, Buchberger proved that the only polynomials one ever needs in a Gröbner basis are constructed as S-polynomials. During the algorithm, their remainders on division by the growing basis set are added to the basis. Thus it might be tempting to construct a universe \mathcal{H} consisting of all possible S-polynomials one can construct up to some degree D. This approach will neccesitate both an estimate of D and a different violator operator, such as : $V_{\prec}(S) := \{h \in \mathcal{H} : \text{ at least one term of } h \text{ is not in } \mathrm{LT}_{\prec}(S)\}$. While the operator is consistent, we have not checked if the locality axiom holds.

Problem 3. Are there other variants of the Gröbner violator operator which might lead to more efficient universes for sampling?

Related to the above considerations, we ask for conditions under which the Spark Randomizer will outperform Buchberger's algorithm in practice. One answer to the this part is when the *expected lineage* of S-pairs is very long relative to the complexity of the Gröbner basis. In Jamshidi and Petrović (2021), we define and provide a Macaulay2 package that can compute such lineages.

Definition 4.1 (Definition 1.1 from Jamshidi and Petrović (2021)). Let G be a Gröbner basis of $I = (f_0, \ldots, f_k)$. A *lineage* of a polynomial in G is a natural number, or an ordered pair of lineages, tracing its history in the given Gröbner basis computation using Buchberger's algorithm. It is defined recursively as follows:

- For the starting generating set, $Lineage(f_i) = i$,
- For any subsequently created S-polynomial S(f,g), the lineage of its remainder r on division is the pair Lineage(r) = (Lineage(f), Lineage(g)).

To illustrate, suppose $I = (x^2 - y, x^3 - z) \subset \mathbb{Q}[x, y, z]$ with graded reverse lexicographic order. Then $Lineage(x^2 - y) = 0$ and $Lineage(x^3 - z) = 1$. Two additional elements are added to create a (non-minimal) Gröbner basis: xy + z and $y^2 - xz$, with lineages (0, 1) and ((0, 1), 0), respectively. According to $Lineage(y^2 - xz)$, this element is constructed from $S(xy + z, x^2 - y)$. Lineages are expressions of the starting generating set and thus dependent on the choice and order of its elements.

The online documentation for our Macaulay2 package ThreadedGB.m2 offers an example of an S-polynomial with a long lineage but which becomes 1, turning the reduced Gröbner basis into unity.

Problem 4. Predict the length of the longest lineage in one run of Buchberger's algorithm from the input set of polynomials, a monomial ordering, and the S-polynomial processing order that the algorithm will use.

This problem, as stated, is a learning question that does not seem to be useful as direct input to the Spark Randomizer but, rather, to inform the theoretical understanding of algorithm complexity and comparison. On the other hand, recall that the violator space primitive query requires a small Gröner computation, as described on page 8. With the lineage information learned, this computation can be organized more cleverly to minimize the expected lineage length and further speed up the Spark Randomizer by making the black-box primitive more efficient.

In general, understanding how learning can further improve the algebraic versions of Clarkson's algorithm is an open problem wherein lies a promise of much of the computational gain.

References

- 4ti2 (2018). 4ti2-a software package for algebraic, geometric and combinatorial problems on linear spaces combinatorial problems on linear spaces.
- Bardet, M., Faugère, J.-C., and Salvy, B. (2015). On the complexity of the F5 Gröbner basis algorithm. *Journal of Symbolic Computation*, 70:49–70.
- Beltrán, C. and Pardo, L. (2008). On Smale's 17th problem: a probabilistic positive solution. Foundations of Computational Mathematics, 8(1):1–43.
- Beltrán, C. and Pardo, L. (2009.). Smale's 17th problem: average polynomial time to compute affine and projective solutions. J. Amer. Math. Soc., 22(2):363–385.

- Breiding, P., Sturmfels, B., Kališnik-Verovšek, S., and Weinstein, M. (2018). Learning algebraic varieties from samples. *Revista Matematica Complutense*, 31:545–593.
- Buchberger, B. (1965). Ein Algorithmus zum Auffinden der Basiselemente des Restklassenringes nach einem nulldimensionalen Polynomideal. PhD thesis, Leopold-Franzens University.
- Buchberger, B. (2006). Bruno Buchberger's PhD thesis 1965: An algorithm for finding the basis elements of the residue class ring of a zero dimensional polynomial ideal (English translation). Journal of Symbolic Computation, 41(3-4):475–511.
- Clarkson, K. L. (1995). Las Vegas algorithms for linear and integer programming. Journal of the ACM, 42(2):488–499.
- Cox, D., Little, J., and O'Shea, D. (2007). *Ideals, Varieties, and Algorithms: An Introduction to Computational Algebraic Geometry and Commutative Algebra.* Springer.
- De Loera, J., Haws, D., Hemmecke, R., Huggins, P., Sturmfels, B., and Yoshida, R. (2004). Short rational functions for toric algebra and applications. *Journal of Symbolic Computa*tion, 38(2):959–973.
- De Loera, J. A., Hemmecke, R., and Köppe, M. (2013). Algebraic and Geometric Ideas in the Theory of Discrete Optimization. MOS-SIAM Series in Optimization. SIAM.
- De Loera, J. A., Hemmecke, R., Yoshida, R., and Tauzer, J. (2004). Effective lattice point enumeration in rational convex polytopes. *Journal of Symbolic Computation*, 38(4):1273–1302.
- De Loera, J. A., Petrović, S., and Stasi, D. (2016). Random sampling in computational algebra: Helly numbers and violator spaces. *Journal of Symbolic Computation*, 77:1–15.
- Dobra, A. (2012). Dynamic Markov bases. *Journal of Computational and Graphical Statistics*, pages 496–517.
- Dube, T. (1990). The structure of polynomial ideals and Gröbner bases. SIAM Journal of Computing, 19(4):750–773.
- Faugére, J.-C., Gianni, P., Lazard, D., and Mora, T. (1993). Efficient computation of zero dimensional Gröbner bases by change of ordering. *Journal of Symbolic Computation*, 16(4):329–344.
- Faugére, J.-C., Spaenlehauer, P.-J., and Svartz., J. (2014). Sparse Gröbner bases: the unmixed case. arXiv preprint arXiv:1402.7205.
- Gärtner, B., Matoušek, J., Rüst, L., and Skovroň, P. (2008). Violator spaces: structure and algorithms. *Discrete Appl. Math.*, 156(11):2124–2141.
- Gross, E., Petrović, S., and Stasi, D. (2015). Goodness-of-fit for log-linear network models: Dynamic Markov bases using hypergraphs. Annals of the Institute of Statistical Mathematics. DOI: 10.1007/s10463-016-0560-2.
- He, Y.-H. (2022). Machine-learning mathematical structures. International Journal of Data Science in the Mathematical Sciences, 1(1):1–25.
- Higham, C. F. and Higham, D. J. (2018). Deep learning: An introduction for applied mathematicians. https://arxiv.org/abs/1801.05894.
- Hironaka, H. (1964). Resolution of singularities of an algebraic variety over a field of characteristic zero. Annals of Mathematics, Second Series, 79(1):109–326.
- Jamshidi, S., Kang, E., and Petrović, S. (2023+). Predicting the cardinality of a reduced gröbner basis. arXiv preprint arXiv:2302.05364.
- Jamshidi, S. and Petrović, S. (2021). Threaded Gröbner bases: a Macaulay2 package. Journal

of Software for Algebra and Geometry, 11:123–127.

- Lample, G. and Charton, F. (2020). Deep learning for symbolic mathematics. In *International Conference on Learning Representations*.
- Mojsilović, J., Peifer, D., and Petrović, S. (2023). Learning a performance metric of Buchberger's algorithm. *Involve, a Journal of Mathematics*, 16(2):227–248.
- Peifer, D. (2021). *Reinforcement learning in Buchberger's algorithm*. PhD thesis, Cornell University, Department of Mathematics.
- Peifer, D., Stillman, M., and Halpern-Leistner, D. (2020a). Learning selection strategies in Buchberger's algorithm. In Proceedings of the 37th International Conference on Machine Learning (ICML 2020).
- Peifer, D., Stillman, M., and Halpern-Leistner, D. (2020b). Learning selection strategies in Buchberger's algorithm: Supplementary material. Proceedings of the 37th International Conference on Machine Learning (ICML 2020).
- Robbiano, L. (2011). Gröbner Bases and applications, volume 251 of London Mathematical Society Lecture Note Series. Cambridge University Press.
- Sharir, M. and Welzl, E. (1992). A combinatorial bound for linear programming and related problems. In Proc. 9th Symposium on Theoretical Aspects of Computer Science (STACS), volume 577 of Lecture Notes in Computer Science, pages 569–579. Springer-Verlag.
- Silverstein, L. (2019). Probability and Machine Learning in Combinatorial Commutative Algebra. PhD thesis, University of California Davis.
- Skovroň, P. (2007). Abstract models of optimization problems. PhD thesis, Charles University, Prague.
- Solovay, R. and Strasse, V. (1977). A fast Monte-Carlo test for primality. SIAM Journal of Computing, 6(1).
- Spielman, D. and Teng, S. (2001). Smoothed analysis of algorithms: why the simplex algorithm usually takes polynomial time. *Journal of the ACM*.
- Sturmfels, B. (1991). Gröbner Bases and Convex Polytopes, volume 8 of University Lecture Series. American Mathematical Society.
- Sturmfels, B. (2005). What is... a Gröbner basis? Notices of the American Mathematical Society, 52(10):1199–1200.
- Thomas, R. R. (1995). A geometric buchberger algorithm for integer programming. *Mathe*matics of Operations Research, 20:864–884.
- van der Maaten, L. and Hinton, G. (2008). Visualizing data using t-sne. Journal of Machine Learning Research, 9:2579–2605.