SQL2Circuits: Estimating Metrics for SQL Queries with a Quantum Natural Language Processing Method

Valter Uotila University of Helsinki Helsinki, Finland valter.uotila@helsinki.fi

ABSTRACT

In recent years, advances in quantum computing have led to accelerating research on quantum applications across fields. Here, we introduce a quantum machine learning model as a potential solution to the classical question in database research: the estimation of metrics for SQL queries. This work employs a quantum natural language processing (QNLP)-inspired approach for constructing a quantum machine learning model that can classify SQL queries with respect to their cardinalities, costs, and execution times. The model consists of an encoding mechanism and a training phase, including classical and quantum subroutines. The encoding mechanism encodes SQL queries as parametrized quantum circuits. In the training phase, we utilize classical optimization algorithms, such as SPSA and Adam, to optimize the circuit parameters to make predictions about the query metrics. We conclude that our model reaches an accuracy equivalent to that of the QNLP model in the binary classification tasks. Moreover, we extend the previous work by adding 4-class classification tasks and compare the cardinality estimation results to the state-of-the-art databases. We perform a theoretical analysis of the quantum machine learning model by calculating its expressibility and entangling capabilities. The analysis shows that the model has advantageous properties that make it expressible but also not too complex to be executed on the existing quantum hardware.

1 INTRODUCTION

Quantum computing is a potentially powerful solution to computational challenges. Over the last few years, quantum technologies have progressed rapidly toward being able to solve problems that are presently impractical or excessively costly with current classical technologies. For example, quantum computing could bring benefits of around \$1.3 trillion by 2035 for industries including automotive, chemicals, financial services, and life sciences [6]. This development has occurred initially on the quantum hardware side. Figure 1 illustrates the previous and future qubit counts for the companies collected in [35].

The realm of quantum computing applied to databases stands as an emerging research domain [30, 73, 84, 88]. Quantum computing has demonstrated its potential utility in addressing various facets of database optimization, encompassing multiple query optimization [83], transaction synchronization [16, 17, 30], virtual machine and task allocation [85], index tuning [31], and join order optimization problem [69, 70, 87]. The main methods include the techniques of quantum annealing [70, 83, 85], and quantum machine learning [87]. For a detailed exploration of the subject, interested readers may refer to the recent survey paper [94] and tutorial [88].



Figure 1: A summary of quantum computing roadmaps for some of the main quantum computing hardware providers. Besides the number of qubits, their connectivity, quality, and decoherence times matter in applications.

In this work, our objective is to apply quantum computing to estimate the metrics of SQL queries. Given an SQL query, how to quickly estimate its cost, execution time, or cardinalities without execution? The estimation of metrics is useful for multiple applications for query optimization and transaction scheduling. In the past five decades, this problem has been tackled from different perspectives in the database community. The existing work includes synopsis-based [91], sampling-based [65], and machine learning-based methods [10, 28, 82, 92].

It is worth mentioning that our primary objective is not to surpass the state-of-the-art in terms of estimation accuracy. This is due to the limits of the current quantum computing hardware, such as small qubit count, short coherence times, high error rates, and partial connectivity in quantum circuits. On the practical side, access to these machines is limited, expensive, and slow. Given these inherent limitations, it is unrealistic to anticipate tangible, practical advantages over the existing state-of-the-art methodologies.

Despite the limitations, we argue that the database community should closely monitor and engage with the ongoing development of quantum-based solutions, even in light of the absence of established quantum advantages for any real-life problems. Several compelling reasons underpin this assertion. Firstly, our framework is the first quantum computing-based solution for the problem of estimating metrics. Secondly, even with the restrictions in quantum hardware, novel small-scale quantum solutions are rapidly developed across different research fields and industries [6]. While practical quantum computers are not yet available, the pursuit of this technology for databases is expected to yield new frameworks and approaches to solve challenges in data management.

In order to address the problem of estimating metrics with quantum computing, we convert the estimation problem into a query classification task. That is, given a predefined set of classes, we decide to which class this query belongs without executing it. The results of query classification can be used for query optimization.

Query Classification: Consider a database instance and a set of predefined classes with respect to the cost, execution time, or cardinality of queries. Given an SQL query, determine its class without executing the query.

Because each class is equipped with a range of values, the ranges provide estimations for the queries. Theoretically, this reformulation is not a big shortcoming. Later we will explain that the number of classes grows exponentially as a function of 2^n for every qubit that we add to the set of the target qubits in the quantum circuits used as classifiers. For example, just 30 qubits would give us $2^{30} \approx 10^9$ classes. As a comparison, IBM has a quantum computer of 433 qubits [5].

We develop a quantum machine learning model, which we call the SOL2Circuits model. Our quantum computing method is based on quantum natural language processing (ONLP) research [24, 26, 39, 50, 56, 62, 93, 95]. Developing a quantum machine learning model is comparable to developing a classical machine learning model, with some crucial differences and challenges. Before we describe how the model is trained, we briefly describe how it is used to optimize relational databases. First, the database user has an SQL query whose cardinality they would like to estimate in order to optimize its processing in their database. Then, a novel encoding mechanism is applied to encode the SQL query as a parametrized quantum circuit. From an optimized set of parameters, we substitute parameter values into the parametrized quantum circuit, which is executed on a quantum computer. Then, the circuit works as a classifier. In the post-processing phase, we interpret the circuit measurement result as a classification result. The result estimates the cardinality of the query, which can be further used to optimize query processing in the relational database. The same workflow applies to estimating query execution times and costs.

The main contributions of this paper are summarized as follows: **Quantum computing for database metrics**: The paper introduces the application of the quantum natural language processing -inspired quantum machine learning model to estimate metrics for SQL queries, specifically focusing on cardinality, cost, and execution time estimations. Unlike previous research that typically focused on a single metric, this work presents a unified model capable of estimating cardinalities, costs, and execution times for SQL queries.

Optimization methods for quantum machine learning: The paper delves into the optimization of parametrized quantum circuits, using classical optimization algorithms such as the Simultaneous Perturbation Stochastic Approximation (SPSA) algorithm [79, 80]. We implement the optimization process using multiple different quantum computing frameworks, such as lambeq [39] and Pennylane [14]. We furthermore introduce an iterative optimization

method which we use to scale up the number of circuits compared to the previous research [50]. Moreover, we implement optimization methods for both state and sample-based measurements.

Theoretical analysis: We provide a theoretical analysis of the expressibility and entangling capabilities of the model's circuits. This analysis indicates that the model has advantageous properties, which were also identified in the previous studies on the expressibility and entangling capabilities of circuits.

Experimental findings: The quantum machine learning model is experimentally evaluated for cardinality, cost, and execution times estimations. The cardinality estimations are compared to the results from state-of-the-art open-source and commercial databases. Although the qubit size of current quantum computers is limited, we show that the accuracy of binary and 4-class classification results is favorable and even comparable to the state-of-the-art databases.

The outline of the paper is the following. Section 2 briefly reviews the basics of quantum computing and quantum machine learning. Section 3 delves into the existing research on quantum natural language processing and database metrics estimation. In Section 4, we outline the process of encoding SQL queries into parametrized circuits and optimizing these circuit parameters using a variety of classical algorithms. Section 5 provides insight into the training pipeline of quantum circuits, and Section 6 presents both the experimental results and the corresponding settings. Moving forward, Section 7 is dedicated to a theoretical analysis of quantum circuits. Finally, in Section 8, we draw our conclusions. For further reference, the framework and datasets can be accessed online [1].

2 PRELIMINARIES

This work resides at the intersection of quantum computing, database research, diagrammatic reasoning, and category theory. In lieu of a comprehensive review of the fundamentals of these wideranging topics, we refer our readers to the following literature. The standard introduction to quantum computing is [58], and an introduction to quantum computing from the database optimization perspective is presented in [88]. The comprehensive introduction to diagrammatic reasoning, which works as the basis for the encoding mechanism from SQL queries into circuits, is [24]. Most of the quantum natural language processing research [39, 50, 56] also introduce the basics of diagrammatic reasoning. The foundations for diagrammatic reasoning are based on category theory [51, 66]. This work especially utilizes monoidal categories and functors.

2.1 Quantum computing

Several computing paradigms exist beyond classical computing. One of the most exciting paradigms is quantum computing which is based on quantum mechanics. Classical computations are based on bits, which are either 0 or 1. Instead of bits, quantum computers compute with quantum bits called *qubits*. Qubits can be in a superposition state of 0 and 1. Considering the 2-dimensional case of a single qubit, a qubit is a vector $|\varphi\rangle = \alpha |0\rangle + \beta |1\rangle$, where $|0\rangle = [1, 0]^{\top}$, $|1\rangle = [0, 1]^{\top}$ and $\alpha, \beta \in \mathbb{C}$ are complex coefficients (amplitudes) satisfying the equation $|\alpha|^2 + |\beta|^2 = 1$. Thus, qubits are vectors in a complex-valued Hilbert space. Using the standard tensor product for Hilbert spaces, we can create larger spaces and systems. A convenient way to visualize a single qubit system is a Bloch sphere in



Figure 2: Bloch sphere representation of a single qubit system

Figure 2. The angles θ and ϕ can be derived and used to represent the qubit.

The vectors as $|\varphi\rangle$ are called states which can be manipulated with *quantum logic gates*. The gates are formally unitary complexvalued matrices. The matrix U is unitary if its conjugate transpose U^{\dagger} is its inverse $UU^{\dagger} = U^{\dagger}U = I$. Applying quantum logic gates changes the state of the system. Considering the Bloch sphere, applying a gate means we rotate the point, i.e., the qubit around the sphere.

Usually, qubits are visualized as wires on which the quantum logic gates act. These constructions are called *circuits*, describing the quantum circuit model. Finally, the quantum system is *measured* collapsing it to a certain state with a probability defined by the squared lengths of the amplitudes. A result of measurement is a sequence of classical bits if the measurement is performed on a computational basis. Considering the Bloch sphere visualization again, measurement takes the point, i.e., the qubit, to either $|0\rangle$ or $|1\rangle$, which are the antipodal points on the sphere.

In this work, we apply parametrized gates meaning the gate operation depends on a variable. For example, the parameterized *Z*-rotation gate is defined by the matrix

$$\mathrm{RZ}(\theta) = \begin{bmatrix} e^{-i\theta/2} & 0\\ 0 & e^{i\theta/2} \end{bmatrix},$$

where $\theta \in [0, 2\pi]$ is a parameter.

2.2 Quantum machine learning

Quantum machine learning [15, 57, 72] is a rapidly growing subfield of machine learning utilizing computational capabilities of quantum computers in machine learning tasks.

The capabilities of current noisy intermediate-scale quantum (NISQ) [63] era quantum computers are still limited. One of the most suitable classes of algorithms for NISQ devices is the so-called hybrid quantum-classical algorithms. Usually, hybrid quantum-classical algorithms utilize parametrized circuits. Our approach falls into this category since its training process includes both quantum and classical subroutines. In the training phase, a quantum state is prepared with the current parameter configuration and measured. At each step, the circuit parameters are tuned based on the measured values from the quantum subroutine. The tuning of the parameters follows classical, usually stochastic, optimization algorithms such

as stochastic gradient descent. This process continues until the algorithm reaches the stop criterion.

In summary, the key characteristics in quantum machine learning are [71, 72]: (1) Quantum circuits form a machine learning model class. (2) Data encoding is a crucial challenge. (3) Gradient-based methods can be used to optimize the parameters in the circuits.

3 RELATED WORK

Searching for practical quantum advantage. Quantum advantage refers to the computational superiority of quantum computers over classical computers in solving certain problems or tasks. As an example, some of the most remarkable milestones in the search for quantum advantage are [11, 41, 52, 96, 97]. The characteristic of this research is a deep integration between the quantum hardware, quantum algorithms, and even the problem to be solved. Often the problem and algorithm have no practical applications but only demonstrate quantum advantage over the best known classical solutions. Thus one of the biggest challenges in practical quantum computing is to identify sufficiently hard, preferably NP-hard, reallife problems that would admit efficient quantum algorithms for the current and near-future quantum computers. To our knowledge, there has been no clear real-life use case that has benefited from quantum computing.

Despite being an extremely difficult task, the long-term objective of quantum computing is to find quantum advantage in practical applications. These advantages can be quantified through two key metrics: speedup and the quality of results. Also, the energy efficiency of quantum computing is an aspect that has been considered promising [22, 25].

Quantum natural language processing. This work is not quantum natural language processing (QNLP), but we utilize the quantum machine learning model, which was first developed for QNLP tasks [50, 95]. They utilize a similar category theoretical encoding mechanism which we will describe in Section 4. This encoding mechanism is based on the DisCoCat model, which has been widely used in NLP: modeling verbs [29, 40], relative pronouns [67], homonymy and polysemy [62], textual entailment [13, 48, 68], Combinatory Categorial Grammar (CCG) [93], and modeling music [56]. Although all of these tasks are NLP-related, we show that the model can be applied to query languages.

Cardinality estimations. Cardinality estimation methods are a widely studied topic in database research. The methods are divided into synopsis-based methods (histograms and sketches), sampling-based methods, and learning-based methods (regression, neural networks, graphical models, kernel density estimators) [46]. Considering the learning-based methods, cardinalities can also be estimated with deep autoregressive models [90], sum-product networks [36], deep neural networks [27, 32, 43], and gradient-boosted trees [27]. A recent comparison of existing methods is performed in [86].

Cost estimations. Survey on cardinality estimations and cost models is [46], where the authors divide the field into three categories: methods improving the current cost models [34, 38, 49], alternative cost models [21, 75, 81, 89], and query performance prediction. Alternative cost models are usually learning-based, and performance prediction is closely related to predicting execution time.



Figure 3: Summary of the encoding mechanism

Execution time and performance estimations. Query execution time estimations have been studied previously in [10, 28, 53, 54, 82, 91, 92]. The field can be divided into black-box and white-box methods. Black-box methods include various machine learning methods [10, 28, 82, 92] to predict query execution times. White-box methods [91] include, for example, methods defining mappings between cost models and execution times.

4 ENCODING SQL QUERIES INTO PARAMETRIZED CIRCUITS

In this section, we describe our data encoding mechanism, which encodes conjunctive SQL queries into parametrized quantum circuits. The encoding is formalized as a sequence of functor applications to the abstract syntax trees of queries modeled as monoidal categories. The detailed definitions of a functor and monoidal category can be found in [51, 66].

As described previously, quantum machine learning uses circuits as a model class. The field suffers from the fact that it is often difficult to justify the selection of well-performing circuits [76]. The selection is called a circuit architecture. The circuit architecture is often a sophisticated guess developed by quantum machine learning specialists based on their domain knowledge. Instead of using an arbitrary circuit architecture, we develop a mathematically precise method to map SQL queries into parametrized circuits.

4.1 Parsing SQL queries with CFG

In the initial implementation of the SQL2Circuits model, we focus on conjunctive SQL queries because they form a fundamental set of queries. We exploit the context-free grammar developed for SQLite [64], but generally, any standard SQL query dialect can be processed with our framework. We assume that the SELECT clause consists of either a list of attributes or a standard SQL function as defined in the grammar. The FROM clause includes a list of relations. The WHERE clause contains an expression that consists of predicates which are also expressions themselves, as defined in the SQLite grammar. The predicates evaluate true or false, and they can be divided into filtering or joining predicates.

Context-free grammar (CFG) [77], and its variations are the standard way to formalize query and programming languages, although they were first used to formalize natural languages.

Definition 4.1. Context-free grammar. A context-free grammar is a tuple (V, Σ, R, s) where V is a finite set of variables, Σ is a finite set of terminals and disjoint from V, R is a finite set of rules, and $s \in V$ is a start variable. The rules R are elements of the set $V \times (V \cup \Sigma)^*$ where ()* denotes the Kleene star operation.

In other words, the rule set R is a relation that describes how variables can be rewritten with sequences of variables and terminals. The set R is also called rewrite rules or productions of the grammar.

Context-free grammars induce a monoidal category. We describe how to construct the category, which we call a *monoidal context-free grammar category*. First, each variable in *V* and terminal in Σ is assigned a domain and codomain objects (which we call types) so that they become morphisms in the monoidal context-free grammar category. A fundamental object (i.e., type) of the monoidal contextfree grammar category is an identity type *I*, and every terminal in Σ has it as a codomain. The collection of the types becomes the collection of objects in the monoidal context-free grammar category. The Kleene star operation in Definition 4.1 induces the monoidal (tensor product) structure to the category.

Furthermore, every rewrite rule in R becomes a morphism. The domain and codomain of a rewrite rule are defined by the fact that the rewrite rule maps a variable to a sequence of variables and terminals. For example, consider the following rule, which we call the *S*-rule,

$$S \rightarrow aSb$$
,

where *S* is a variable and *a* and *b* are terminals. Then *S*, *a* and *b* have their corresponding types, for example, $S: \text{dom}(S) \rightarrow \text{cod}(S)$, $a: \text{dom}(a) \rightarrow I$ and $b: \text{dom}(a) \rightarrow I$. Thus, the type for the rule *S* in the monoidal context-free grammar category is

$$cod(S) \rightarrow dom(a) \otimes dom(S) \otimes dom(a).$$

Rewriting rules are special morphisms because their codomain is a tensor-product of the types, whereas variables and terminals always have a single type as domain and codomain. The start variable does not have a special role in the monoidal context-free grammar category.

The SQL parsers do not implement this type of typing, so the types, such as dom(S) and dom(a), are generated automatically at the point when the abstract syntax tree is translated into a monoidal context-free grammar category. The standard Python package to calculate with category theory is DisCoPy [26]. We use DisCoPy to create, store, modify, and draw the categories introduced in this work.

We parse SQL queries with ANTLR [18, 59–61] using the grammar definition for SQLite [64]. We have written an intermediate layer between the ANTLR modules and DisCoPy. The intermediate layer maps the abstract parse tree produced by ANTLR to a DisCoPy diagram. If we can construct a DisCoPy diagram, the construction itself proves that the result is a monoidal category. The intermediate layer we have created also performs the typing for the monoidal context-free grammar category. *Example* 1. In this paper, we fix the following simple example query that demonstrates the encoding from SQL queries into parametrized circuits. After the example query has been parsed with the SQL2Circuits model, the corresponding monoidal context-free grammar category represented as a diagram can be viewed in Figure 4.

SELECT cat_name, favorite_food
FROM cats
WHERE cat name = 'Whiskers';

4.2 Converting CFG to pregroup grammar

Here, we describe the rewriting process of transforming monoidal categories from context-free grammar representations into pregroup grammar categories. Both categories are expressed as diagrams using DisCoPy. The fact that the transformation is functorial ensures that the produced pregroup grammar category is also monoidal. The following definitions are based on [45], and we assume that the reader is familiar with the definition of an ordered monoid [23]. Although a similar framework has been applied in QNLP, this rewriting mechanism for SQL queries is our contribution.

Definition 4.2. Pregroup. A pregroup *P* is an ordered monoid where every element $a \in P$ has left a^l and right a^r adjoints which satisfy the following properties with respect to the ordering \leq of *P*:

 $a^l a \le 1 \le a a^l$ and $a a^r \le 1 \le a^r a$.

Let *B* be a set. The free pregroup P_B generated by *B* is the smallest (with respect to set inclusion) pregroup which includes *B*.

Definition 4.3. Pregroup grammar. A pregroup grammar is a tuple $G = (B, \Sigma, \Delta, s)$, where the set *B* is the finite set of basic types and the set Σ is the finite set of the vocabulary. Let P_B be the free pregroup generated by *B*. The set $\Delta \subset \Sigma \times P_B$ is a relation called the dictionary, and $s \in P_B$ is a designated sentence type. We require that Δ is finite. The sequence of words $w_1 \cdots w_n \in \Sigma^n$ is called *grammatical* if for every $i = 1, \ldots, n$ there exists a tuple $(w_i, t_i) \in \Delta$ so that $t_1 \cdots t_n \leq s$ in the pregoup P_B .

Now the pregoup grammar defines a (rigid) monoidal pregroup grammar category where objects are the elements of the disjoint union $B + \Sigma$, and the morphisms are given by the entries in the dictionary Δ so that if $(w, t) \in \Delta$, the domain of morphism (w, t) is the word w and the codomain is t.

The key idea is to define a functor from the context-free grammar category to the pregroup grammar category so that the pregroup grammar representations of the queries will be grammatical in the sense of Definition 4.3. The DisCoPy library implements a class called Functor, which enables us to functorially rewrite DisCoPy diagrams, which are interpreted as monoidal categories. We call this construction a CFG-pregroup functor. The Functor class follows the definition of a functor [51, 66]. It inputs an object and morphism mappings, after which it can be applied to a suitable monoidal category. Applying the given mappings to the objects and morphisms, the functor outputs a new diagram interpreted as a monoidal category. A concrete example of the mappings is illustrated in Figure 5. The fact that the transformation is functorial ensures that the structure of the domain category, i.e., the context-free grammar category, is preserved and the outputted pregroup grammar category is grammatical in the sense of Definition 4.3. Since the current quantum hardware is limited and cannot simulate large circuits, we must perform well-reasoned simplifications while applying the CFG-pregroup functor. When the simplifications are part of the functorial rewriting process, we ensure they do not modify the grammatical structure of the diagrams, which encodes important structural information about the queries (as well as sentences in QNLP). In practice, these simplifications are designed to map certain morphisms in the context-free grammar category to the identity morphisms of the category representing pregroup grammar.

To test and demonstrate the pregroup grammar diagram construction, we processed the previously obtained context-free grammar diagrams for the Join Order Benchmark [47] and produced the corresponding pregroup grammar diagrams. This demonstrates that we are able to encode realistic SQL queries using pregroup grammar representations. The pregroup grammar diagrams can be viewed on GitHub [1] as images or as serialized JSON documents.

Continuing Example 1, Figure 6a demonstrates one of the transformations that the CFG-pregroup functor performs at a lower level. Figure 7 shows the full pregroup grammar diagram transformed from the context-free grammar diagram in Figure 4. This transformation is a continuation to Example 1.

4.3 Converting pregroup grammar to circuits

Lambeq [39] is a modular and extensible high-level Python library for experimental quantum natural language processing. The package is heavily based on DisCoPy, and thus their integration is seamless. Lambeq implements a so-called IQPAnsatz-class [33, 74], which is a functor that transforms pregroup grammar diagrams into parameterized quantum circuits.

IQPAnsatz functor requires information on how many qubits we use for each pregroup grammar type. In our case, we have simply two types: s and n. We always map the type n, which only appears inside the pregroup grammar diagram, to a single qubit. We map the designated sentence type (which we also call an output type) s to one to *n* qubits depending on how accurately we want to classify the queries. Recall that we defined the special sentence type s in Definition 4.3. The number of classes grows exponentially as a function of 2^n , so in theory, the model's accuracy increases exponentially fast when we increase the number of qubits that are mapped to the sentence type s.

Besides the previous information, the IQPAnsatz functor requires an integer number of layers that we use in the circuit to create entanglement between the qubits and an integer of how many variables we use in the circuit for each single wire box in the pregroup grammar diagram. These values can be modified to produce circuits with different features, and it is an open experimental question of which type of construction performs the best. The previous research [37] has shown that adding single-qubit operations followed by entangling two-qubit operations in the parameterized circuit can enhance the model's learning.



Figure 4: Context-free grammar diagram of the query in Example 1



Figure 5: Part of the mapping which transforms context-free grammar diagrams into pregroup grammar diagrams. The full mapping is in the document pregroup_functor_data.json.

Before constructing the circuits, we perform a simplification process to remove the caps (and cups) from the pregroup grammar diagrams. Caps and cups denote the grammar reductions, and removing them is a standard rewriting technique [50]. Pregroup diagrams having no caps and cups lead to circuits with a smaller number of qubits and less need for costly post-processing. Besides, implementing a cup or cap requires obtaining expensive quantum measurement results that happen non-deterministically [50]. In our work, the cap removal procedure is also a functor between two pregroup grammar diagrams. See Figure 6b, which demonstrates one of the cap removal rewriting rules.

See Figure 6c as an example of a capless pregroup grammar diagram which is based on Example 1. The final circuit with randomly substituted variables is illustrated in Figure 8. The circuit representation finalizes the query encoding example, which we started in Example 1.

5 TRAINING PIPELINE

5.1 Data preprocessing

Data collection and splitting. Because quantum hardware is still limited, we have developed a set of queries to train, validate, and test the SQL2Circuits model to estimate SQL cardinalities, costs, and execution times. The set of queries is based on the Join Order Benchmark [47] and Internet Movie Database [2]. We have decomposed the JOB benchmark queries into two JSON documents which work as seeds for generating synthetic queries. The flexible generation of queries enables us to study how the SQL2Circuits model scales. Because quantum computing resources are limited, it is important to have control over the lengths of the queries. The length of the queries affects the length and depth of the parametrized circuits. Since we cannot efficiently run long circuits with many qubits on classical simulators or on the current quantum hardware, we have to use relatively simple SQL queries.

We executed the queries using PostgreSQL 14.2 running on a Lenovo Legion computer with AMD Ryzen 7 5800H, 3201 Mhz processors, and 32Gb RAM. The execution time and cardinality statistics are gathered from PostgreSQL using the EXPLAIN ANALYZE command. We have excluded queries whose running time was more than 2 minutes.

The queries have been randomly split into training, validation, and test queries. In all of the classification tasks, the number of training queries is 398, the number of validation queries is 135, and the number of test queries is 140.

Encoding. The generated queries are encoded as parametrized circuits following the procedure described in Section 4. The procedure gives us a method to draw a precise connection between a query and the corresponding encoded parametrized circuit. To summarize this connection, every SQL keyword, identifier, literal, function, and operator is mapped to a combination of parametrized gates. The connectivity between the qubits is roughly given by the number of keywords and operators in the query. Note that while there is



Figure 6: Functorial transformations to the context-free and pregroup grammar diagrams



Figure 7: The pregroup grammar diagram of the query in Example 1.

no unique way to perform the mapping, certain decisions have been made. For instance, in Figure 6c, the s-wire does not have to originate from the WHERE keyword; this placement is a matter of design choice.

5.2 Architecture and hyperparameter tuning

The summary of the training pipeline is presented in Figure 9. Before training, the training setup is defined in the main.py file. The different configuration options are listed in the

sql2circuits_config.json file. The files can be viewed on GitHub
[1].

As Part 4 in Figure 9 demonstrates, we have implemented a hyperparameter optimization module on top of the classical optimizer. The module employs a Bayesian hyperparameter optimization routine [3], and it can also connect to the standard grid search [4] over the hyperparameter space. The hyperparameter optimization module applies cross-validation to evaluate different hyperparameter configurations.

We want to emphasize that our model goes beyond estimating metrics solely from queries; it actively learns essential information directly from the underlying database. Instead of relying on classical histograms, correlations, or distributions to model the database, the model encodes the database as a set of optimized parameters that are used in the model's parametrized circuits.

5.3 Training procedure

Quantum subroutine. The SQL2Circuits model admits a quantum subroutine that is responsible for executing the parametrized circuits. We have implemented this subroutine in a way that enables us to use various modern quantum computing architectures: local simulators, cloud simulators, and real quantum computers. We have trained the model with the local simulators since we have easy, fast, and cheap access to them.

As Part 3 in Figure 9 demonstrates, the quantum subroutine inputs an executable set of circuits with the current parameter values substituted. In the first epoch, the parameters are initialized randomly. After accepting the circuits, they are executed on the selected quantum hardware. Following the quantum mechanical principles, the final operation in the execution is a measurement. The SQL2Circuits model implements two different ways to perform the measurement, which we call **state** and **sample**. In the state measurement, we let the simulator calculate the exact quantum state, which we can further use to calculate the classification result for a query. In the sample measurement, we execute the circuit sufficiently many times (1000 – 100 000 times depending on the number of qubits) and then obtain the classification result for the guery based on the probabilities calculated based on the samples.

Before we can interpret the classification result, we need to perform a post-selection [9] on the state or the sample measurement. Post-selection means that we condition the outcome of the measured result from the target qubits to be conditional to the measured result of the non-target qubits. Figure 8 shows an example of how post-selection is denoted in the case of binary classification. The target qubit is the top qubit in the figure, and the rest of the qubits

	х (0.5257) Н	R _X (0.6727)	
$q_1: 0\rangle - H$ $R_Z(4.471) R_X(4.255)$			
$q_2: 0\rangle - H - R_Z(0.2589) - R_X(1.956)$			
$q_3: 0\rangle - H$ $R_Z(0.5257)$ R	$R_X(1.331) = R_X(4.703)$		
$q_4: 0\rangle$ -H	R _Z (0.672	(727) R _X (3.261) H	$R_X(1.042) - R_X(4.272) - 0$ lec-
$q_5: 0\rangle - H$		R _Z (1.042)	$R_X (0.4325)$ $R_X (1.956)$ $ 0\rangle$ tion

Figure 8: The circuit corresponding the query in Example 1 with random parameter values

Task	#classes	ranges for training, validation and test				
execution time	2	[0, 264) & [264, 15603] (ms)				
cardinality	2	0 – 33181 & 33182 – 102540525 (rows)	Fig. 11b			
cost	2	0.0 - 83723.14 & 83723.14 - 1425540.85 (psql cost)	Fig. 12b			
execution time	4	[0,197) & [197, 264) & [264, 915) & [915, 15604] (ms)	Fig. 12d			
cardinality	4	0 - 7 & 8 - 33181 & 33182 - 635188 & 635189 - 102540525 (rows)	Fig. 11d			

Table 1: Statistics about the classification tasks



Figure 9: Summary of the training pipeline

are non-target qubits which are required to be 0-state after measurement. In the case when we have chosen to perform exact state computation, we calculate the probabilities for accepted outcomes and select the outcome with the highest probability.

In the case of sample measurement, we obtain an estimate for the probabilities. While the sampled result may not achieve the precision of an exact calculation, it remains crucial to develop samplebased approaches. This is because quantum mechanical principles inherently prohibit us from directly accessing the exact quantum state within a quantum computer [58]. Nevertheless, performing exact state calculations holds significant value in validating the functionality of the model in cases when the quantum states are small (less than ~ 20 qubits).

Classical subroutine. Besides the quantum subroutine, the model admits a classical subroutine that is responsible for optimizing the

parameters in the quantum circuits. In Figure 9, Part 3 illustrates the integration of the classical subroutine within the training pipeline.

Depending on whether we have performed state or sample measurements, we can select between various classical optimization algorithms, which are also commonly used in classical machine learning. The previous work [50] used Simultaneous Perturbation Stochastic Approximation (SPSA) [79, 80]. In addition to SPSA, we employ the Adam optimizer [42], which is available within the optax library [12]. Optax is a library designed for gradient processing and optimization in the JAX ecosystem [19].

The classical optimizer updates the parameters which are shared by the quantum circuits in the model. Depending on the hyperparameter configuration, the quantum and classical subroutines are repeated. Additionally, the model allows an iterative process: following each optimization cycle, the number of parameterized circuits is expanded, and optimization resumes from the previously identified optimized point.

5.4 Software and libraries

The SQL2Circuits model utilizes multiple modern quantum computing software libraries and classical machine learning frameworks. The SQL queries are parsed with ANTRL 4 [59] using the SQLite grammars [64]. We have integrated the ANTRL-based parser with DisCoPy [26], which is used to construct category theoretical mappings between the diagrams in the encoding phase. DisCoPy is frequently employed together with lambeq [39], which implements the mapping from grammatical diagrams to the quantum circuits. Lambeq is based on the Tket quantum circuit compiler [78].

We also wanted to study the model's performance on a different quantum compiler, so we included a circuit transformation from lambeq circuits into Pennylane [14] circuits. We chose Pennylane because its code can be easily executed on various simulators and hardware, for example, Pennylane's own simulators, Qiskit (including IBM quantum computers), Amazon Braket, Google Cirq, Microsoft QDK, IonQ, and Qulacs. Besides, Pennylane offers an easy integration with JAX. Pennylane does not offer optimization over a collection of circuits, so we needed to implement the feature.

The classical optimizers are based on the SPSA algorithm in noisyopt [55, 79], and the classical Adam optimizer in optax. JAX library [19], and its just-in-time (jit) compilation mechanism, can be used to speed up the code execution, but we noticed that jitcompilation is also memory intensive in this quantum machine learning application.

5.5 Reproducibility and ethical considerations

In order to support reproducibility, the SQL2Circuits model is available on GitHub [1]. We have utilized editions of PostgreSQL, MySQL, and SQL Server which are available without cost.

In this paper, we have taken into consideration SIGMOD inclusive writing guidelines to ensure that our language and terminology are sensitive to diverse perspectives. We have made efforts to use gender-neutral language, avoid stereotypes, and promote inclusivity throughout the text. For instance, Example 1 demonstrating the encoding mechanism is designed to be neutral.

6 EVALUATION

Performance metrics. The model is evaluated and trained against the true metrics obtained from the PostgreSQL database when the test queries are executed eagerly. In the case of execution time, we run the query 20 times and calculate the average running time. The cardinalities [7], costs [91], and execution times [8] are calculated as they are defined in PostgreSQL. Figure 10 provides an overview of the model evaluation process.

We utilize the standard cross-entropy as the loss function during training. Let T denote the training labels, let p denote the predicted distribution, and let L denote the distribution over the true labels. The cross-entropy is then defined

$$\operatorname{Loss}(p,q) = -\frac{1}{|T|} \sum_{x \in T} L(x) \log p(x).$$

Test results and comparison to state-of-the-art databases. We first discuss results regarding classification results obtained with the lambeq framework and the SPSA algorithm. First, we focus on the results obtained from binary classifying execution times. Figure 11a indicates that the model is able to learn while the iterative training process proceeds. We used a method where we optimized the model for every added circuit. The accuracy of the classifier is good and aligns with the results that were obtained in QNLP research [50]. In QNLP, the accuracy of a binary classifier for different types of sentences varied between 90, 6% and 72, 3%.

In evaluating the model in this case, we employed an approach designed to uncover the model's limitations and discover any prominent features. At each optimization step, after training a fixed number of circuits, we tested the model with all the test circuits that shared the currently trained parameters. During the iterative training process, this meant that we tested the model with possibly an unusually large number of test data points. As Figure ?? shows, we tested the model with a test data set whose size was 4 - 0.2 times the size of the training data during the iterative training.

The next point we want to make is the following. Figure 11a shows that the model's accuracy on the test data is around 80% with 150 training circuits. The test/training data ratio for 150 circuits in Figure 12a reveals that the number of test circuits we used to achieve 80% accuracy was around 70% of the training circuit size. This means we used over 100 circuits to test the model at that optimization point. This result indicates that the model was able to learn and generalize from a relatively small number of data points. The same evaluation setup was used for the binary classification of cardinalities 11b, and the results are very similar to the results we obtained for the binary classification of execution times.

Next, we focus on the result obtained from the 4-class classification of execution times and cardinalities. Again, we obtained these results using the lambeq framework and the SPSA algorithm. In this case, the circuits are one qubit larger than the circuits in the binary classification task, which doubles the required simulation resources. Thus, we increased the number of circuits we added at each iteration to speed up the training. In this case, the model was substantially more difficult to train with the SPSA algorithm since small modifications in the hyperparameter setup affected the learning.

Finally, we discuss the results we obtained using the Pennylane framework with Adam optimizer. Due to technical reasons behind Pennylane, all the parameters were included in the training phase from the start. First, we trained the model to predict cost estimations, and the results are shown in Figure 12b. Compared to the results from lambeq and SPSA, the accuracy is higher, and the results are clearly better. Compared to the SPSA algorithm, the Adam optimizer does not benefit from the cross-entropy loss calculated from the validation circuits, so the role of the validation data is to extend the test data. This means that we used around 400 circuits to train the model and 275 circuits to evaluate the model. Although the training/test data ratio is unusual, the performance of the model is outstanding, and the model is able to generalize from a relatively small number of data points, as Figure 12b shows.

Next, the 4-class cardinality classification results with Pennylane and Adam exhibit varying levels of performance. While the



Figure 10: Summary of the evaluation phase



tion times with lambeq and SPSA nalities with lambeq and SPSA tion times with lambeq and SPSA nalities with lambeq and SPSA

Figure 11: Binary and four-class classification results for cardinalities and latencies with noisyopt SPSA

model effectively optimizes parameters for training queries, its generalization to validation and test data falls short in comparison to binary classification. We believe that with the right classical optimizer, fine-tuned hyperparameters, and an appropriate circuit architecture, the model can achieve higher accuracy.

Comparison to state-of-the-art databases. In order to argue that the model performs well compared to the state-of-the-art databases, we migrated the Internet Movie Database from PostgreSQL to MySQL and SQL Server databases. Cost and execution time are hardware and database-dependent metrics. Since we trained the model to predict execution times and costs for PostgreSQL, it is difficult to generalize these results so that we would be able to predict execution times and costs of running queries on MySQL and SQL Server. On the other hand, cardinalities stay the same across different databases, which enables us to perform this comparison.

In order to perform the comparison, we needed to interpret the estimators in databases as query classifiers. The selected databases implement cardinality estimators, which estimate cardinalities without executing the queries. We used the estimators to collect estimates for the training, validation, and test queries. Then we used these estimates to classify the queries with respect to the same classes that our quantum machine learning model used. Table 2 shows the results of this classification task.

Firstly, in the binary classification task, our model performs worse than SQL Server but is close to the results of PostgreSQL. In all of the cases, MySQL is the worst. In this case, the classical subroutine used the SPSA algorithm. We noted that for cost estimations, we obtained higher accuracies when we used the Adam optimizer. It is highly probable that our model would reach accuracies close to SQL Server with a suitable classical optimizer.

Secondly, in the 4-class classification task, our model does to reach accuracies of PostgreSQL or SQL Server. In the 4-class classification task with Pennylane and Adam optimizer, we obtained similar results. This might indicate that we need to modify the circuit architecture and parametrization. In the next section of the theoretical analysis of our model, we also find indications that the model might require changes to the circuit architecture and parametrization in order to be expressible in 4-class and 8-class classification tasks.

7 ANALYSIS OF MODEL

7.1 Expressibility

Theoretical background. Intuitively, in the context of a single circuit with a single qubit, expressibility refers to the property of how well the circuit can express different pure quantum states, i.e., how well it covers the surface of the Bloch sphere [76]. Recall the Bloch sphere in Figure 2. Formally, the distribution that the circuit produces when executed with randomly initialized parameter settings is compared to the Haar distribution, which is the uniform distribution over the state space

$$\operatorname{Exp} := D_{KL}(P_{PQC}(F; S) || P_{\operatorname{Haar}}(F)),$$

where $P_{PQC}(F;S)$ is the estimated probability distribution of fidelities when randomly sampling states from the circuits in the



process for execution time estimations when using lambeq and SPSA

Adam

(d) 8-class classification of cardinalities with Pennylane and Adam with weight decay regularization using more expressible SIM14 circuit architecture

Figure 12: Test and training circuit ratio and classification results with Pennylane and Adam

Database	#classes	Accuracy on training queries	Accuracy on validation queries	Accuracy on test queries	Average accuracy
PostgreSQL	2	81.65	83.46	83.94	83.02
MySQL	2	47.29	49.62	50.36	49.09
SQL Server	2	90.96	92.48	91.97	91.80
SQL2Circuits (SPSA)	2	88.18	82.41	81.65	84.08
PostgreSQL	4	57.62	67.67	62.04	62.45
MySQL	4	27.65	30.83	33.58	30.68
SQL Server	4	61.76	68.42	61.31	63.83
SQL2Circuits (SPSA)	4	37.91	34.26	42.20	38.12
SQL2Circuits (Adam)	4	54.86	42.86	32.59	43.44

Table 2: The accuracy of the SQL2Circuits model compared to state-of-the-art database cardinality estimators when both are employed as query classifiers, using the same database and queries

SQL2Circuits model, and D_{KL} is the Kullback-Leibler divergence (also called relative entropy) [44] value which is commonly used also in classical machine learning. The set S refers to the uniformly randomly sampled parameter configurations. The code for calculating Exp value is on GitHub [1] in main_guantum_metrics.py file. The Haar distribution on a sphere, often referred to as the Haar measure on the sphere, is a probability distribution that is symmetric and uniform over the surface of a sphere. In this case, the Haar distribution $P_{\text{Haar}}(F)$ admits the closed form formula

$$P_{\text{Haar}}(F) := (N-1)(1-F)^{N-2}$$

where N is the dimension of the Hilbert space, and F corresponds to fidelity.

Results of the expressibility analysis. Expressibility for the training circuits for the binary classification of execution times is visualized in Figure 13a. The circuit architectures for cardinality and cost estimations are similar, so the calculations generalize to them as well. Compared to the studies performed in [76], we can deduce that the expressibility of the model is favorable because its Kullback-Leibler divergence value is 0.017, which is close to those divergence values that correspond to the well-performing circuits (Exp < 0.02) in [76]. We emphasize that we calculated expressibility over the whole model consisting of multiple circuits with post-selection. This is in accordance with the expected procedure since we should be comparing quantum machine learning models and not just single circuits.

Furthermore, we studied the expressibility of the circuits used in 4-class and 8-class classification. The histograms and the corresponding Haar distribution can be found in Figures 13b and 13c. The fact that the shape of the histograms follows the Haar distribution means that the distributions are close to each other. Since the Haard distribution corresponds to a uniform distribution over a sphere, it represents the most expressible case. Now we note that the expressibility of the circuits goes lower, being 0.032 and 0.056, respectively. These values are not yet considered poor, but they approach the values for which circuits were found to be sub-optimal (Exp > 0.09). This suggested that we probably need to modify the circuit layout in order to be able to represent the classification problem in the cases when the number of classes grows. This also aligns with the results that we obtained from evaluating the model: its performance started to decrease when the number of classes grew, as Figures 11d and 12d show.

Entangling capability 7.2

Theoretical background. The entangling capability of a circuit is related to the circuit's property to efficiently represent solutions utilizing entangled states, preferably with a small number of gates [76]. In this work, the entangling capability is calculated with the Meyer-Wallach entangling measure, although there exist other possible metrics [76]. The following formulation for the Meyer-Wallach



(a) The KL divergence value is 0.017 for the binary classification task.



(b) The KL divergence value is 0.032 for the 4-class classification task.



(c) The KL divergence value is (d) The average entangling capa-0.056 for the 8-class classification bility measure over the circuits is task. 0.517.

Figure 13: Theoretical analysis of the model

entangling measure was deduced in [20]

$$Q := \frac{2}{|S|} \sum_{\theta \in S} \left(1 - \frac{1}{n} \sum_{k=1}^{n} \operatorname{Tr}(\rho_k^2(\theta)) \right),$$

where *n* is the number of qubits, *S* is a collection of randomly sampled parameter vectors, Tr is the standard trace operation applied to the single qubit reduced states ρ_k for k = 1, ..., n. A single qubit reduced state corresponds to calculating the partial traces over the state vectors without including the single qubits k = 1, ..., n. In other words, *Q* is the average linear entropy over all the single qubit reduced states [76]. Entangling capability for the training circuits for the binary classification of execution times is visualized in Figure 13d. The code for calculating these values is on GitHub [1] in main_quantum_metrics.py file.

Results of the entanglement analysis. The average Meyer-Wallach entangling measure over the training circuits for binary classification of execution times is 0.517. In comparison to the entangling capabilities reported in [76], the circuits in our model have entangling capabilities equivalent to those of circuits with just a single entangling layer. The entangling capability of the circuits in our model is on the scale (0.4 - 0.7) of the favorable circuits identified in [76].

After calculating the average entangling measure for the circuits representing 4-class and 8-class classification tasks, we did not see a big difference in the entanglement results from the binary classification circuits. The values were 0.554 and 0.570, respectively. The histograms are very similar to Figure 13d, so we have omitted them. These results are expected because the circuit layout remains highly consistent across binary, 4-class, and 8-class classification tasks. The similar circuit layout creates an equal amount of entanglement between the qubits, which results in the entanglement measurements close to each other. One of our primary points is to balance the utilization of entanglement, which is a crucial quantum computational feature, and simultaneously design the circuits so that they can be executed on the current, limited quantum hardware.

8 CONCLUSION AND FUTURE WORK

In this work, we tackled the classical database problem of estimating cardinalities, costs, and execution times for SQL queries in relational databases. We developed SQL2Circuits quantum machine learning model using the methods from QNLP. We developed an encoding mechanism to translate SQL queries into parametrized circuits. We optimized the circuit parameters so that the model makes estimations about SQL queries. The results on the binary classification task align seamlessly with prior research in quantum natural language processing [50], and the multi-class classification results are a significant step forward. We studied the SQL2Circuits model's expressibility and entangling capabilities. The calculated metrics indicated that the SQL2Circuits quantum machine learning model has favorable properties compared to quantum machine learning models in previous research [76].

In the future, we aim to achieve better classification accuracy by increasing the number of target qubits, trying out different circuit architectures, and developing classical subroutines for parameter optimization. The binary classification results are good, but the 4-class classification results show that the problem becomes harder when the accuracy is doubled. We aim to find possibilities to train and evaluate the model on real quantum computing hardware.

We have not yet addressed the question of how to make the model adaptive to the changes in a database. Since the training process is iterative, it is possible that the iterative nature can be easily utilized in retraining when the database is updated. We will study how much the database needs to change before the model starts to perform worse.

Based on our understanding, it is unlikely that quantum computing will take an instant "quantum leap" to outperform classical computing. Instead, quantum computing will go through incremental improvements in software and hardware, leading to advantages in specific, computationally challenging tasks. Our current work constitutes a cutting-edge effort in quantum computing for databases, advancing us toward this goal.

REFERENCES

- [1] [n.d.]. https://anonymous.4open.science/r/SQL2Circuits-SIGMOD-2024/ README.md
- 2] [n.d.]. https://developer.imdb.com/non-commercial-datasets/
- [a] [n. d.]. https://scikit-optimize.github.io/stable/modules/generated/skopt. BayesSearchCV.html
- [4] [n.d.]. https://scikit-learn.org/stable/modules/generated/sklearn.model_ selection.GridSearchCV.html

- [5] [n. d.]. IBM Unveils 400 Qubit-Plus Quantum Processor and Next-Generation IBM Quantum System Two. https://newsroom.ibm.com/2022-11-09-IBM-Unveils-400-Qubit-Plus-Quantum-Processor-and-Next-Generation-IBM-Quantum-System-Two
- [6] [n.d.]. Record investments in quantum technology | McKinsey. https: //www.mckinsey.com/capabilities/mckinsey-digital/our-insights/quantumtechnology-sees-record-investments-progress-on-talent-gap
- [7] 2023. https://www.postgresql.org/docs/16/row-estimation-examples.html
- [8] 2023. https://www.postgresql.org/docs/16/sql-explain.html
- [9] Scott Aaronson. 2005. Quantum computing, postselection, and probabilistic polynomial-time. Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences 461, 2063 (Nov 2005), 3473–3482. https://doi.org/10.1098/ rspa.2005.1546
- [10] Mert Akdere, Ugur Çetintemel, Matteo Riondato, Eli Upfal, and Stanley B. Zdonik. 2012. Learning-based Query Performance Modeling and Prediction. In 2012 IEEE 28th International Conference on Data Engineering. 390–401. https://doi.org/10. 1109/ICDE.2012.64
- [11] Frank Arute, Kunal Arya, Ryan Babbush, Dave Bacon, Joseph C. Bardin, Rami Barends, Rupak Biswas, Sergio Boixo, Fernando G. S. L. Brandao, David A. Buell, Brian Burkett, Yu Chen, Zijun Chen, Ben Chiaro, Roberto Collins, William Courtney, Andrew Dunsworth, Edward Farhi, Brooks Foxen, Austin Fowler, Craig Gidney, Marissa Giustina, Rob Graff, Keith Guerin, Steve Habegger, Matthew P. Harrigan, Michael J. Hartmann, Alan Ho, Markus Hoffmann, Trent Huang, Travis S. Humble, Sergei V. Isakov, Evan Jeffrey, Zhang Jiang, Dvir Kafri, Kostyantyn Kechedzhi, Julian Kelly, Paul V. Klimov, Sergey Knysh, Alexander Korotkov, Fedor Kostritsa, David Landhuis, Mike Lindmark, Erik Lucero, Dmitry Lyakh, Salvatore Mandrà, Jarrod R. McClean, Matthew McEwen, Anthony Megrant, Xiao Mi, Kristel Michielsen, Masoud Mohseni, Josh Mutus, Ofer Naaman, Matthew Neeley, Charles Neill, Murphy Yuezhen Niu, Eric Ostby, Andre Petukhov, John C. Platt, Chris Quintana, Eleanor G. Rieffel, Pedram Roushan, Nicholas C. Rubin, Daniel Sank, Kevin J. Satzinger, Vadim Smelyanskiy, Kevin J. Sung, Matthew D. Trevithick, Amit Vainsencher, Benjamin Villalonga, Theodore White, Z. Jamie Yao, Ping Yeh, Adam Zalcman, Hartmut Neven, and John M. Martinis, 2019. Quantum supremacy using a programmable superconducting processor. Nature 574, 77797779 (Oct 2019), 505-510. https://doi.org/10.1038/s41586-019-1666-5
- [12] Igor Babuschkin, Kate Baumli, Alison Bell, Surya Bhupatiraju, Jake Bruce, Peter Buchlovsky, David Budden, Trevor Cai, Aidan Clark, Ivo Danihelka, Antoine Dedieu, Claudio Fantacci, Jonathan Godwin, Chris Jones, Ross Hemsley, Tom Hennigan, Matteo Hessel, Shaobo Hou, Steven Kapturowski, Thomas Keck, Iurii Kemaev, Michael King, Markus Kunesch, Lena Martens, Hamza Merzic, Vladimir Mikulik, Tamara Norman, George Papamakarios, John Quan, Roman Ring, Francisco Ruiz, Alvaro Sanchez, Laurent Sartran, Rosalia Schneider, Eren Sezener, Stephen Spencer, Srivatsan Srinivasan, Miloš Stanojević, Wojciech Stokowiec, Luyu Wang, Guangyao Zhou, and Fabio Viola. 2020. The DeepMind JAX Ecosystem. http://github.com/deepmind
- [13] Dea Bankova, Bob Coecke, Martha Lewis, and Dan Marsden. 2019. Graded hyponymy for compositional distributional semantics. *Journal of Language Modelling* 6, 2 (March 2019). https://doi.org/10.15398/jlm.v6i2.230
- [14] Ville Bergholm, Josh Izaac, Maria Schuld, Christian Gogolin, Shahnawaz Ahmed, Vishnu Ajith, M. Sohaib Alam, Guillermo Alonso-Linaje, B. AkashNarayanan, Ali Asadi, Juan Miguel Arrazola, Utkarsh Azad, Sam Banning, Carsten Blank, Thomas R Bromley, Benjamin A. Cordier, Jack Ceroni, Alain Delgado, Olivia Di Matteo, Amintor Dusko, Tanya Garg, Diego Guala, Anthony Hayes, Ryan Hill, Aroosa Ijaz, Theodor Isacsson, David Ittah, Soran Jahangiri, Prateek Jain, Edward Jiang, Ankit Khandelwal, Korbinian Kottmann, Robert A. Lang, Christina Lee, Thomas Loke, Angus Lowe, Keri McKiernan, Johannes Jakob Meyer, J. A. Montañez-Barrera, Romain Moyard, Zeyue Niu, Lee James O'Riordan, Steven Oud, Ashish Panigrahi, Chae-Yeun Park, Daniel Polatajko, Nicolás Quesada, Chase Roberts, Nahum Sá, Isidor Schoch, Borun Shi, Shuli Shu, Sukin Sim, Arshpreet Singh, Ingrid Strandberg, Jay Soni, Antal Száva, Slimane Thabet, Rodrigo A. Vargas-Hernández, Trevor Vincent, Nicola Vitucci, Maurice Weber, David Wierichs, Roeland Wiersema, Moritz Willmann, Vincent Wong, Shaoming Zhang, and Nathan Killoran. 2022. PennyLane: Automatic differentiation of hybrid quantum-classical computations. arXiv:1811.04968 [quant-ph]
- [15] Jacob Biamonte, Peter Wittek, Nicola Pancotti, Patrick Rebentrost, Nathan Wiebe, and Seth Lloyd. 2017. Quantum machine learning. *Nature* 549, 7671 (Sep 2017), 195–202. https://doi.org/10.1038/nature23474
- [16] Tim Bittner and Sven Groppe. 2020. Avoiding blocking by scheduling transactions using quantum annealing. In Proceedings of the 24th Symposium on International Database Engineering & Applications (IDEAS '20). Association for Computing Machinery, New York, NY, USA, 1–10. https://doi.org/10.1145/3410566.3410593
- [17] Tim Bittner and Sven Groppe. 2020. Hardware Accelerating the Optimization of Transaction Schedules via Quantum Annealing by Avoiding Blocking. Open Journal of Cloud Computing (OJCC) 7, 1 (2020), 1–21. http://nbn-resolving.de/urn: nbn:de:101:1-2020112218332015343957
- [18] Jean Bovet and Terence Parr. 2008. ANTLRWorks: an ANTLR grammar development environment. *Software: Practice and Experience* 38, 12 (Oct 2008), 1305–1332. https://doi.org/10.1002/spe.872

- [19] James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, George Necula, Adam Paszke, Jake VanderPlas, Skye Wanderman-Milne, and Qiao Zhang. 2018. JAX: composable transformations of Python+NumPy programs. http://github.com/google/jax
- [20] Gavin K. Brennen. 2003. An observable measure of entanglement for pure states of multi-qubit systems. *Quantum Information & Computation* 3, 6 (Nov 2003), 619–626.
- [21] Ronnie Chaiken, Bob Jenkins, Per-Åke Larson, Bill Ramsey, Darren Shakib, Simon Weaver, and Jingren Zhou. 2008. SCOPE: Easy and Efficient Parallel Processing of Massive Data Sets. *Proc. VLDB Endow.* 1, 2 (aug 2008), 1265–1276. https: //doi.org/10.14778/1454159.1454166
- [22] Sophia Chen. 2023. Are quantum computers really energy efficient? Nature Computational Science 3, 66 (June 2023), 457–460. https://doi.org/10.1038/s43588-023-00459-6
- [23] Bob Coecke. 2013. An alternative Gospel of structure: order, composition, processes. arXiv:1307.4038 (Jul 2013). https://doi.org/10.48550/arXiv.1307.4038 arXiv:1307.4038 [quant-ph].
- [24] Bob Coecke and Aleks Kissinger. 2017. Picturing Quantum Processes: A First Course in Quantum Theory and Diagrammatic Reasoning. Cambridge University Press, Cambridge. https://doi.org/10.1017/9781316219317
- [25] D-Wave. 2017. Computational Power Consumption and Speedup. https://www.dwavesys.com/resources/white-paper/computational-powerconsumption-and-speedup/
- [26] Giovanni de Felice, Alexis Toumi, and Bob Coecke. 2021. DisCoPy Monoidal Categories in Python. *Electronic Proceedings in Theoretical Computer Science* 333 (Feb 2021), 183–197. https://doi.org/10.4204/EPTCS.333.13
- [27] Anshuman Dutt, Chi Wang, Azade Nazi, Srikanth Kandula, Vivek Narasayya, and Surajit Chaudhuri. 2019. Selectivity estimation for range predicates using lightweight models. *Proceedings of the VLDB Endowment* 12, 9 (May 2019), 1044–1057. https://doi.org/10.14778/3329772.3329780
- [28] Archana Ganapathi, Harumi Kuno, Umeshwar Dayal, Janet L. Wiener, Armando Fox, Michael Jordan, and David Patterson. 2009. Predicting Multiple Metrics for Queries: Better Decisions Enabled by Machine Learning. In 2009 IEEE 25th International Conference on Data Engineering. 592–603. https://doi.org/10.1109/ ICDE.2009.130
- [29] Edward Grefenstette and Mehrnoosh Sadrzadeh. 2011. Experimental Support for a Categorical Compositional Distributional Model of Meaning. In Proceedings of the Conference on Empirical Methods in Natural Language Processing (Edinburgh, United Kingdom) (EMNLP '11). Association for Computational Linguistics, USA, 1394–1404.
- [30] Sven Groppe, Jinghua Groppe, Umut Çalıkyılmaz, Tobias Winker, and Le Gruenwal. 2023. Quantum Data Management and Quantum Machine Learning for Data Management: State-of-the-Art and Open Challenges. In Intelligent Systems and Machine Learning (Lecture Notes of the Institute for Computer Sciences, Social Informatics and Telecommunications Engineering), Sachi Nandan Mohanty, Vicente Garcia Diaz, and G. A. E. Satish Kumar (Eds.). Springer Nature Switzerland, Cham, 252–261. https://doi.org/10.1007/978-3-031-35081-8_20
- [31] Le Gruenwald, Tobias Winker, Umut Çalıkyılmaz, Jinghua Groppe, and Sven Groppe. 2023. Index Tuning with Machine Learning on Quantum Computers for Large-Scale Database Applications. Joint Workshops at 49th International Conference on Very Large Data Bases (VLDBW'23) – International Workshop on Quantum Data Science and Management (QDSM'23) (sep 2023).
- [32] Shohedul Hasan, Saravanan Thirumuruganathan, Jees Augustine, Nick Koudas, and Gautam Das. 2020. Deep Learning Models for Selectivity Estimation of Multi-Attribute Queries. In Proceedings of the 2020 ACM SIGMOD International Conference on Management of Data. ACM, Portland OR USA, 1035–1050. https: //doi.org/10.1145/3318464.3389741
- [33] Vojtěch Havlíček, Antonio D. Córcoles, Kristan Temme, Aram W. Harrow, Abhinav Kandala, Jerry M. Chow, and Jay M. Gambetta. 2019. Supervised learning with quantum-enhanced feature spaces. *Nature* 567, 7747 (mar 2019), 209–212. https://doi.org/10.1038/s41586-019-0980-2
- [34] Zhen He, Byung Suk Lee, and Robert Snapp. 2005. Self-Tuning Cost Modeling of User-Defined Functions in an Object-Relational DBMS. ACM Trans. Database Syst. 30, 3 (sep 2005), 812–853. https://doi.org/10.1145/1093382.1093387
- [35] Ian Hellström. [n. d.]. Quantum Computer Roadmaps. https://databaseline.tech/ quantum.html
- [36] Benjamin Hilprecht, Andreas Schmidt, Moritz Kulessa, Alejandro Molina, Kristian Kersting, and Carsten Binnig. 2020. DeepDB: learn from data, not from queries! Proceedings of the VLDB Endowment 13, 7 (Mar 2020), 992–1005. https://doi.org/ 10.14778/3384345.3384349
- [37] Abhinav Kandala, Antonio Mezzacapo, Kristan Temme, Maika Takita, Markus Brink, Jerry M. Chow, and Jay M. Gambetta. 2017. Hardware-efficient Variational Quantum Eigensolver for Small Molecules and Quantum Magnets. *Nature* 549, 7671 (Sep 2017), 242–246. https://doi.org/10.1038/nature23879 arXiv:1704.05018 [cond-mat, physics:quant-ph].
- [38] Zisis Karampaglis, Anastasios Gounaris, and Yannis Manolopoulos. 2014. A Bi-Objective Cost Model for Database Queries in a Multi-Cloud Environment. In Proceedings of the 6th International Conference on Management of Emergent

Digital EcoSystems (Buraidah, Al Qassim, Saudi Arabia) (*MEDES '14*). Association for Computing Machinery, New York, NY, USA, 109–116. https://doi.org/10. 1145/2668260.2668271

- [39] Dimitri Kartsaklis, Ian Fan, Richie Yeung, Anna Pearson, Robin Lorenz, Alexis Toumi, Giovanni de Felice, Konstantinos Meichanetzidis, Stephen Clark, and Bob Coecke. 2021. lambeq: An Efficient High-Level Python Library for Quantum NLP. arXiv preprint arXiv:2110.04236 (2021).
- [40] Dimitri Kartsaklis and Mehrnoosh Sadrzadeh. 2014. A Study of Entanglement in a Categorical Framework of Natural Language. *Electronic Proceedings in Theoretical Computer Science* 172 (May 2014). https://doi.org/10.4204/EPTCS.172.17
- [41] Youngseok Kim, Andrew Eddins, Sajant Anand, Ken Xuan Wei, Ewout van den Berg, Sami Rosenblatt, Hasan Nayfeh, Yantao Wu, Michael Zaletel, Kristan Temme, and Abhinav Kandala. 2023. Evidence for the utility of quantum computing before fault tolerance. *Nature* 618, 79657965 (Jun 2023), 500–505. https://doi.org/10.1038/s41586-023-06096-3
- [42] Diederik P. Kingma and Jimmy Ba. 2017. Adam: A Method for Stochastic Optimization. arXiv:1412.6980 [cs.LG]
- [43] Andreas Kipf, Thomas Kipf, Bernhard Radke, Viktor Leis, Peter A. Boncz, and Alfons Kemper. 2019. Learned Cardinalities: Estimating Correlated Joins with Deep Learning. In 9th Biennial Conference on Innovative Data Systems Research, CIDR 2019, Asilomar, CA, USA, January 13-16, 2019, Online Proceedings. www.cidrdb.org. http://cidrdb.org/cidr2019/papers/p101-kipf-cidr19.pdf
- [44] S. Kullback and R. A. Leibler. 1951. On Information and Sufficiency. The Annals of Mathematical Statistics 22, 1 (March 1951), 79–86. https://doi.org/10.1214/ aoms/1177729694
- [45] J. Lambek. 1999. Type Grammar Revisited. In Logical Aspects of Computational Linguistics (Lecture Notes in Computer Science), Alain Lecomte, François Lamarche, and Guy Perrier (Eds.). Springer, Berlin, Heidelberg, 1–27. https://doi.org/10. 1007/3-540-48975-4_1
- [46] Hai Lan, Zhifeng Bao, and Yuwei Peng. 2021. A Survey on Advancing the DBMS Query Optimizer: Cardinality Estimation, Cost Model, and Plan Enumeration. Data Science and Engineering 6, 1 (March 2021), 86–101. https://doi.org/10.1007/ s41019-020-00149-7
- [47] Viktor Leis, Andrey Gubichev, Atanas Mirchev, Peter Boncz, Alfons Kemper, and Thomas Neumann. 2015. How good are query optimizers, really? *Proceedings of the VLDB Endowment* 9, 3 (Nov 2015), 204–215. https://doi.org/10.14778/2850583. 2850594
- [48] Martha Lewis. [n.d.]. Modelling hyponymy for DisCoCat. Proceedings of the Applied Category Theory Conference ([n.d.]). https://www.cs.ox.ac.uk/ACT2019/ preproceedings/Martha%20Lewis.pdf
- [49] Feilong Liu and Spyros Blanas. 2015. Forecasting the Cost of Processing Multi-Join Queries via Hashing for Main-Memory Databases. In Proceedings of the Sixth ACM Symposium on Cloud Computing (Kohala Coast, Hawaii) (SoCC '15). Association for Computing Machinery, New York, NY, USA, 153–166. https: //doi.org/10.1145/2806777.2806944
- [50] Robin Lorenz, Anna Pearson, Konstantinos Meichanetzidis, Dimitri Kartsaklis, and Bob Coecke. 2023. QNLP in Practice: Running Compositional Models of Meaning on a Quantum Computer. J. Artif. Int. Res. 76 (apr 2023), 38 pages. https://doi.org/10.1613/jair.1.14329
- [51] Saunders Mac Lane. 1978. Categories for the Working Mathematician (2 ed.). Graduate Texts in Mathematics, Vol. 5. Springer New York, New York, NY. https://doi.org/10.1007/978-1-4757-4721-8
- [52] Lars S. Madsen, Fabian Laudenbach, Mohsen Falamarzi Askarani, Fabien Rortais, Trevor Vincent, Jacob F. F. Bulmer, Filippo M. Miatto, Leonhard Neuhaus, Lukas G. Helt, Matthew J. Collins, Adriana E. Lita, Thomas Gerrits, Sae Woo Nam, Varun D. Vaidya, Matteo Menotti, Ish Dhand, Zachary Vernon, Nicolás Quesada, and Jonathan Lavoie. 2022. Quantum computational advantage with a programmable photonic processor. *Nature* 606, 79127912 (Jun 2022), 75–81. https://doi.org/10. 1038/s41586-022-04725-x
- [53] Ryan Marcus, Parimarjan Negi, Hongzi Mao, Chi Zhang, Mohammad Alizadeh, Tim Kraska, Olga Papaemmanouil, and Nesime Tatbul. 2019. Neo: A Learned Query Optimizer. Proc. VLDB Endow. 12, 11 (jul 2019), 1705–1718. https://doi. org/10.14778/3342263.3342644
- [54] Ryan Marcus and Olga Papaemmanouil. 2019. Plan-Structured Deep Neural Network Models for Query Performance Prediction. Proc. VLDB Endow. 12, 11 (jul 2019), 1733–1746. https://doi.org/10.14778/3342263.3342646
- [55] Andreas Mayer, Thierry Mora, Olivier Rivoire, and Aleksandra M. Walczak. 2016. Diversity of immune strategies explained by adaptation to pathogen statistics. Proceedings of the National Academy of Sciences of the United States of America 113, 31 (Aug. 2016), 8630–8635. https://doi.org/10.1073/pnas.1600663113
- [56] Eduardo Reck Miranda, Richie Yeung, Anna Pearson, Konstantinos Meichanetzidis, and Bob Coecke. 2022. A Quantum Natural Language Processing Approach to Musical Intelligence. Springer International Publishing, Cham, 313–356. https://doi.org/10.1007/978-3-031-13909-3_13
- [57] Kosuke Mitarai, Makoto Negoro, Masahiro Kitagawa, and Keisuke Fujii. 2018. Quantum Circuit Learning. *Physical Review A* 98, 3 (Sep 2018), 032309. https: //doi.org/10.1103/PhysRevA.98.032309 arXiv:1803.00745 [quant-ph].

- [58] Michael A. Nielsen and Isaac L. Chuang. 2010. Quantum computation and quantum information (10th anniversary ed ed.). Cambridge University Press, Cambridge; New York.
- [59] Terence Parr. 2012. The definitive ANTLR 4 reference. The Pragmatic Bookshelf, Dallas, Texas. https://parrt.cs.usfca.edu/
- [60] Terence Parr and Kathleen Fisher. 2011. LL(*): the foundation of the ANTLR parser generator. In Proceedings of the 32nd ACM SIGPLAN conference on Programming language design and implementation - PLDI '11. ACM Press, San Jose, California, USA, 425. https://doi.org/10.1145/1993498.1993548
- [61] T. J. Parr and R. W. Quong. 1995. ANTLR: A predicated-LL(k) parser generator. Software: Practice and Experience 25, 7 (Jul 1995), 789–810. https://doi.org/10. 1002/spe.4380250705
- [62] Robin Piedeleu, Dimitri Kartsaklis, Bob Coecke, and Mehrnoosh Sadrzadeh. 2015. Open System Categorical Quantum Semantics in Natural Language Processing. (2015), 20 pages. https://doi.org/10.4230/LIPICS.CALCO.2015.270
- [63] John Preskill. 2018. Quantum Computing in the NISQ era and beyond. Quantum 2 (Aug 2018), 79. https://doi.org/10.22331/q-2018-08-06-79
- [64] Anthr Project. 2022. Grammars written for ANTLR v4 SQLite. https://github.com/anthr/grammars-v4 Accessed on 2023-06-14. https://github.com/anthr/grammars-v4.
- [65] Yuan Qiu, Yilei Wang, Ke Yi, Feifei Li, Bin Wu, and Chaoqun Zhan. 2021. Weighted Distinct Sampling: Cardinality Estimation for SPJ Queries. In SIGMOD '21: International Conference on Management of Data, Virtual Event, China, June 20-25, 2021, Guoliang Li, Zhanhuai Li, Stratos Idreos, and Divesh Srivastava (Eds.). ACM, 1465–1477.
- [66] Emily Riehl. 2017. Category theory in context. Dover Publications, United States. https://math.jhu.edu/~eriehl/context.pdf
- [67] M. Sadrzadeh, S. Clark, and B. Coecke. 2013. The Frobenius anatomy of word meanings I: subject and object relative pronouns. *Journal of Logic and Computation* 23, 6 (Dec. 2013), 1293–1317. https://doi.org/10.1093/logcom/ext044
- [68] Mehrnoosh Sadrzadeh, Dimitri Kartsaklis, and Esma Balkir. 2018. Sentence entailment in compositional distributional semantics. Annals of Mathematics and Artificial Intelligence 82, 4 (April 2018), 189–218. https://doi.org/10.1007/s10472-017-9570-x
- [69] Manuel Schönberger, Stefanie Scherzinger, and Wolfgang Mauerer. 2023. Ready to Leap (by Co-Design)? Join Order Optimisation on Quantum Hardware. Proc. ACM Manag. Data 1, 1, Article 92 (may 2023), 27 pages. https://doi.org/10.1145/3588946
- [70] Manuel Schönberger, Immanuel Trummer, and Wolfgang Mauerer. 2023. Quantum Optimisation of General Join Trees. In VLDB Workshops (CEUR Workshop Proceedings, Vol. 3462). CEUR-WS.org.
- [71] Maria Schuld and Nathan Killoran. 2022. Is quantum advantage the right goal for quantum machine learning? arXiv:2203.01340 [quant-ph] (Mar 2022). http: //arxiv.org/abs/2203.01340 arXiv: 2203.01340.
- [72] Maria Schuld and Francesco Petruccione. 2018. Supervised Learning with Quantum Computers (1st ed. 2018 ed.). Springer International Publishing : Imprint: Springer, Cham. https://doi.org/10.1007/978-3-319-96424-9
- [73] Manuel Schönberger. 2022. Applicability of Quantum Computing on Database Query Optimization. In Proceedings of the 2022 International Conference on Management of Data. ACM, Philadelphia PA USA, 2512–2514. https://doi.org/10. 1145/3514221.3520257
- [74] Dan Shepherd and Michael J. Bremner. 2009. Temporally unstructured quantum computation. Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences 465, 2105 (feb 2009), 1413–1439. https://doi.org/10.1098/ rspa.2008.0443
- [75] Tarique Siddiqui, Alekh Jindal, Shi Qiao, Hiren Patel, and Wangchao Le. 2020. Cost Models for Big Data Query Processing: Learning, Retrofitting, and Our Findings. In Proceedings of the 2020 ACM SIGMOD International Conference on Management of Data (Portland, OR, USA) (SIGMOD '20). Association for Computing Machinery, New York, NY, USA, 99–113. https://doi.org/10.1145/3318464.3380584
- [76] Sukin Sim, Peter D. Johnson, and Alan Aspuru-Guzik. 2019. Expressibility and entangling capability of parameterized quantum circuits for hybrid quantumclassical algorithms. Advanced Quantum Technologies 2, 12 (Dec 2019), 1900070. https://doi.org/10.1002/qute.201900070 arXiv:1905.10876 [quant-ph].
- [77] Michael Sipser. 1997. Introduction to the theory of computation (2 ed.). PWS Pub. Co, Boston. https://fuuu.be/polytech/INFOF408/Introduction-To-The-Theory-Of-Computation-Michael-Sipser.pdf
- [78] Seyon Sivarajah, Silas Dilkes, Alexander Cowtan, Will Simmons, Alec Edgington, and Ross Duncan. 2020. TKET: A Retargetable Compiler for NISQ devices. *Quantum Science and Technology* 6 (Nov. 2020). https://doi.org/10.1088/2058-9565/ab8e92
- [79] J.C. Spall. 1998. Implementation of the simultaneous perturbation algorithm for stochastic optimization. *IEEE Trans. Aerospace Electron. Systems* 34, 3 (Jul 1998), 817–823. https://doi.org/10.1109/7.705889
- [80] James C Spall. 1999. Stochastic optimization: stochastic approximation and simulated annealing. Encyclopedia of electrical and electronics engineering 20 (1999), 529–542.
- [81] Ji Sun and Guoliang Li. 2019. An End-to-End Learning-Based Cost Estimator. Proc. VLDB Endow. 13, 3 (nov 2019), 307–319. https://doi.org/10.14778/3368289.3368296

- [82] Sean Tozer, Tim Brecht, and Ashraf Aboulnaga. 2010. Q-Cop: Avoiding bad query mixes to minimize client timeouts under heavy loads. In 2010 IEEE 26th International Conference on Data Engineering (ICDE 2010). 397–408. https://doi. org/10.1109/ICDE.2010.5447850
- [83] Immanuel Trummer and Christoph Koch. 2015. Multiple Query Optimization on the D-Wave 2X Adiabatic Quantum Computer. arXiv:1510.06437 [quant-ph] (Oct 2015). http://arxiv.org/abs/1510.06437 arXiv: 1510.06437.
- [84] Valter Uotila. 2022. Synergy between Quantum Computers and Databases. Proceedings of the VLDB 2022 PhD Workshop co-located with the 48th International Conference on Very Large Databases (VLDB 2022) 3186 (Sept. 2022), 4.
- [85] Valter Uotila and Jiaheng Lu. 2023. Quantum Annealing Method for Dynamic Virtual Machine and Task Allocation in Cloud Infrastructures from Sustainability Perspective. In 2023 IEEE 39th International Conference on Data Engineering Workshops (ICDEW). 105–110. https://doi.org/10.1109/ICDEW58674.2023.00023
- [86] Xiaoying Wang, Changbo Qu, Weiyuan Wu, Jiannan Wang, and Qingqing Zhou. 2021. Are We Ready For Learned Cardinality Estimation? Proceedings of the VLDB Endowment 14, 9 (May 2021), 1640–1654. https://doi.org/10.14778/3461535. 3461552 arXiv:2012.06743 [cs].
- [87] Tobias Winker, Umut Çalikyilmaz, Le Gruenwald, and Sven Groppe. 2023. Quantum Machine Learning for Join Order Optimization Using Variational Quantum Circuits. In Proceedings of the International Workshop on Big Data in Emergent Distributed Environments (Seattle, WA, USA) (BiDEDE '23). Association for Computing Machinery, New York, NY, USA, Article 5, 7 pages. https://doi.org/10.1145/3579142.3594299
- [88] Tobias Winker, Sven Groppe, Valter Uotila, Zhengtong Yan, Jiaheng Lu, Maja Franz, and Wolfgang Mauerer. 2023. Quantum Machine Learning: Foundation, New Techniques, and Opportunities for Database Research. In Companion of the 2023 International Conference on Management of Data (Seattle, WA, USA) (SIGMOD/PODS '23). Association for Computing Machinery, New York, NY, USA, 45–52. https://doi.org/10.1145/3555041.3589404
- [89] Chenggang Wu, Alekh Jindal, Saeed Amizadeh, Hiren Patel, Wangchao Le, Shi Qiao, and Sriram Rao. 2018. Towards a Learning Optimizer for Shared Clouds. *Proc. VLDB Endow.* 12, 3 (nov 2018), 210–222. https://doi.org/10.14778/3291264. 3291267
- [90] Peizhi Wu and Gao Cong. 2021. A Unified Deep Model of Learning from both Data and Queries for Cardinality Estimation. In Proceedings of the 2021 International Conference on Management of Data (SIGMOD '21). Association for Computing Machinery, New York, NY, USA, 2009–2022. https://doi.org/10.1145/3448016.

3452830

- [91] Wentao Wu, Yun Chi, Shenghuo Zhu, Junichi Tatemura, Hakan Hacigümüs, and Jeffrey F. Naughton. 2013. Predicting query execution time: Are optimizer cost models really unusable?. In 2013 IEEE 29th International Conference on Data Engineering (ICDE). 1081–1092. https://doi.org/10.1109/ICDE.2013.6544899
- [92] Pengcheng Xiong, Yun Chi, Shenghuo Zhu, Junichi Tatemura, Calton Pu, and Hakan HacigümüŞ. 2011. ActiveSLA: a profit-oriented admission control framework for database-as-a-service providers. In *Proceedings of the 2nd ACM Symposium on Cloud Computing (SOCC '11)*. Association for Computing Machinery, New York, NY, USA, 1–14. https://doi.org/10.1145/2038916.2038931
- [93] Richie Yeung and Dimitri Kartsaklis. 2021. A CCG-Based Version of the DisCoCat Framework. (2021). https://doi.org/10.48550/ARXIV.2105.07720
- [94] Gongsheng Yuan, Jiaheng Lu, Yuxing Chen, Sai Wu, Chang Yao, Zhengtong Yan, Tuodu Li, and Gang Chen. 2023. Quantum Computing for Databases: A Short Survey and Vision. In Joint Proceedings of Workshops at the 49th International Conference on Very Large Data Bases (VLDB 2023), Vancouver, Canada, August 28 -September 1, 2023 (CEUR Workshop Proceedings, Vol. 3462). CEUR-WS.org.
- [95] William Zeng and Bob Coecke. 2016. Quantum Algorithms for Compositional Natural Language Processing. *Electronic Proceedings in Theoretical Computer Science* 221 (Aug. 2016), 67–75. https://doi.org/10.4204/EPTCS.221.8
- [96] Han-Sen Zhong, Hui Wang, Yu-Hao Deng, Ming-Cheng Chen, Li-Chao Peng, Yi-Han Luo, Jian Qin, Dian Wu, Xing Ding, Yi Hu, Peng Hu, Xiao-Yan Yang, Wei-Jun Zhang, Hao Li, Yuxuan Li, Xiao Jiang, Lin Gan, Guangwen Yang, Lixing You, Zhen Wang, Li Li, Nai-Le Liu, Chao-Yang Lu, and Jian-Wei Pan. 2020. Quantum computational advantage using photons. *Science* 370, 6523 (Dec 2020), 1460–1463. https://doi.org/10.1126/science.abe8770
- [97] Qingling Zhu, Sirui Cao, Fusheng Chen, Ming-Cheng Chen, Xiawei Chen, Tung-Hsun Chung, Hui Deng, Yajie Du, Daojin Fan, Ming Gong, Cheng Guo, Chu Guo, Shaojun Guo, Lianchen Han, Linyin Hong, He-Liang Huang, Yong-Heng Huo, Liping Li, Na Li, Shaowei Li, Yuan Li, Futian Liang, Chun Lin, Jin Lin, Haoran Qian, Dan Qiao, Hao Rong, Hong Su, Lihua Sun, Liangyuan Wang, Shiyu Wang, Dachao Wu, Yulin Wu, Yu Xu, Kai Yan, Weifeng Yang, Yang Yang, Yangsen Ye, Jianghan Yin, Chong Ying, Jiale Yu, Chen Zha, Cha Zhang, Haibin Zhang, Kaili Zhang, Yiming Zhang, Han Zhao, Youwei Zhao, Liang Zhou, Chao-Yang Lu, Cheng-Zhi Peng, Xiaobo Zhu, and Jian-Wei Pan. 2022. Quantum computational advantage via 60-qubit 24-cycle random circuit sampling. *Science Bulletin* 67, 3 (Feb 2022), 240–245. https://doi.org/10.1016/j.scib.2021.10.017