Simple Opinion Dynamics for No-Regret Learning

John Lazarsfeld Yale University, IST Austria jlazarsfeld@gmail.com Dan Alistarh IST Austria dan.alistarh@ist.ac.at

Abstract

We study a cooperative multi-agent bandit setting in the distributed GOSSIP model: in every round, each of n agents chooses an action from a common set, observes the action's corresponding reward, and subsequently exchanges information with *a single* randomly chosen neighbor, which may inform its choice in the next round. We introduce and analyze families of memoryless and time-independent protocols for this setting, inspired by opinion dynamics that are well-studied for other algorithmic tasks in the GOSSIP model.

For stationary reward settings, we prove for the first time that these simple protocols exhibit best-of-both-worlds behavior, simultaneously obtaining constant cumulative regret scaling like $R(T)/T = \tilde{O}(1/T)$, and also reaching consensus on the highest-mean action within $\tilde{O}(\sqrt{n})$ rounds. We obtain these results by showing a new connection between the global evolution of these decentralized protocols and a class of zero-sum multiplicative weights update processes. Using this connection, we establish a general framework for analyzing the population-level regret and other properties of our protocols. Finally, we show our protocols are also surprisingly robust to adversarial rewards, and in this regime we obtain sublinear regret scaling like $R(T)/T = \tilde{O}(1/\sqrt{T})$ as long as the number of rounds does not grow too fast as a function of n.

1 Introduction

The multi-armed bandit problem, where a single learning agent chooses actions over a sequence of rounds in order to maximize its total reward, is among the most well-studied in online learning. Distributed, multi-agent variants of this problem have also been widely studied under various constraints; one particular such line of work is the *cooperative multi-agent bandit setting*, where agents are connected over a communication graph and play against a common bandit instance, choosing actions in parallel over T rounds. Each agent locally runs a bandit algorithm that may involve communication with neighbors, and the information exchanged can be used to determine an agent's future actions. This cooperative setting has been studied for both stochastic [SBFH+13, LSL16, KJG18, MRKR19, SGS19] and non-stochastic bandits [AK08, CBGMM16, BOM19], where communication between agents has been shown to improve an agent's regret on average, compared to each agent locally running a centralized bandit algorithm without any communication.

However, most prior works in this setting require that every agent communicate with *all its neighbors* in each round (as pointed out by Cesa-Bianchi et al. [CBGMM16], this resembles the LOCAL model of distributed computation [Lin92]). When the underlying graph is dense, this volume of communication may be prohibitively large, which is a known bottleneck in many practical settings, including in distributed machine learning [AGL⁺17, KLSJ19, KSJ19].

In contrast, much less is known about cooperative multi-agent bandits in more lightweight decentralized models of distributed communication, such as the GOSSIP model [BGPS06, S⁺09] In this model, at every round, each agent is randomly connected to one of its neighbors, and thus the total number of information exchanges per-round scales only linearly in the size of the population, even for dense communication graphs. Algorithms for general distributed tasks have been studied extensively in the GOSSIP model, both in modern machine learning and optimization settings [LZZ⁺17, ALBR19, EBB⁺21], and also in the context of simple, memoryless opinion dynamics, where simple local transition rules can be shown to solve more complex global tasks like consensus and majority [AL12, Ald13, CLP10b, BGS21, BCN20, BCP⁺24].

Yet, much less is known about the power of this model in the cooperative bandit setting, and in particular on the learning properties of simple opinion-dynamic-like protocols that have been studied in other contexts. This line of inquiry is the focus of the paper, and our main results prove that simple protocols of this type can obtain both sublinear regret guarantees and reach consensus on the best action in this setting. For concreteness, we begin by introducing the setting more precisely:

1.1 Problem Setting

Cooperative Bandits in the GOSSIP Model. Consider n anonymous agents distributed over a communication graph G, and interacting with an m-armed bandit over T rounds. In each round t:

- (i) Every agent $u \in [n]$ chooses an action $j \in [m]$.
- (ii) Each action $j \in [m]$ generates a reward $g_j^t \sim \nu_j^t$. Each agent choosing action j observes g_j^t .
- (iii) Every agent pulls information from a single neighbor sampled uniformly at random.

In this setting, we assume each agent is equipped with a fixed local (possibly randomized) protocol \mathcal{P} . Based on an agent's observed rewards and any information exchanged with its neighbor, the protocol \mathcal{P} determines its action choice at the next round. When every agent uses the protocol \mathcal{P} to choose its actions, we measure its global performance via a *population-level* regret. For this, we let $\mathbf{p}^t := (p_1^t, \ldots, p_m^t) \in \Delta_m$ denote the discrete distribution whose coordinates specify the

fraction of n agents choosing each action j at round t. At time t = 0, we assume each agent is deterministically initialized with an action choice j such that $\mathbf{p}^0 = (1/m, \ldots, 1/m)$. Moreover, we denote by $\mathbf{g}^t := (g_1^t, \ldots, g_m^t)$ the vector of realized rewards at round t. Then we define the following:

Definition 1.1 (Population-level Regret). Given a time horizon T and a reward sequence $\{\mathbf{g}^t\}$, the regret of the sequence $\{\mathbf{p}^t\}$ generated by \mathcal{P} is $R(T) := \max_{j \in [m]} \sum_{t \in [T]} \mathbf{E}[g_j^t - \mathbf{E}\langle \mathbf{p}^t, \mathbf{g}^t \rangle].$

In words, R(T) measures difference between the cumulative expected reward of the best *fixed* action and the expected cumulative reward of the population *averaged* over all agents (i.e., weighted at each round by the distribution \mathbf{p}^t). We make the following additional remarks:

- In the problem setting, each agent (from a local perpsective) receives only bandit feedback on the reward of its chosen action, while from a global perspective, the full reward vector \mathbf{g}^t can be distributed across the population. Globally, the problem can thus be viewed as a decentralized instance of the *prediction with expert advice (experts)* setting from online learning [CBL06]. This is similar to the model of other prior works on cooperative bandits [CBGMM16, BOM19].
- The regret definition R(T) is sometimes referred to as the average welfare regret or social regret and is the same notion considered in related works [LSL16, CBGMM16, CKV17, MRKR19, BOM19] The gold standard in online learning and bandit settings is to ensure R(T) grows sublinearly in T (meaning R(T) = o(T), or equivalently R(T)/T = o(1)). If a protocol \mathcal{P} achieves this goal, we say \mathcal{P} obtains sublinear regret, or that \mathcal{P} is a no-regret learning protocol [BCB12, LS20].

The primary focus on this work is the *stationary reward setting*, where the distributions ν_j^t remain fixed over rounds (this is sometimes referred to as the *stochastic rewards* setting, and is in contrast to an *adversarial rewards* setting, where reward means may change over time). Other than several standard boundedness conditions, we make no other distributional assumptions. Defined formally:

Assumption 1 (Stationary Rewards). For each $j \in [m]$, assume for all rounds $t \in [T]$ that $g_j^t \sim \nu_j$, where for some $\sigma \geq 1$, ν_j has support $[0, \sigma]$ and mean $\mu_j := \mathbf{E}[\nu_j] \in [0, 1]$. We assume each μ_j is an absolute constant, and without loss of generality, we assume $1 \geq \mu_1 > \mu_2 \geq \cdots \geq \mu_m \geq 0$.

Algorithmic focus: learning via simple opinion dynamics Most prior works on cooperative bandits under the more powerful LOCAL communication model employ adaptations of common single-agent bandit algorithms (such as UCB and EXP3 [BCB12]) to the multi-agent setting. While this approach can lead to sublinear regret bounds in both stationary and adversarial reward settings, these adaptations usually require agents to locally maintain a probability distribution over the full set of actions at each round, and to carefully aggregate information received from multiple neighbors in order to determine future choices [LSL16, KJG18, MRKR19, CBGMM16, BOM19].

In contrast, the main algorithmic focus of this work is to understand whether extremely simple protocols related to *opinion dynamics* — studied extensively for other problems in the GOSSIP model — can obtain no-regret guarantees in this learning setting. In particular, in the general GOSSIP model, opinion dynamics are local protocols in which an agent's current state (opinion) is updated based only on the state of the agent it interacted with in the most recent round [BCN20]. These dynamics model fully decentralized scenarios in which agents are anonymous, extremely computationally limited, and are only able to employ some fixed, time-independent update rule.

Despite their simplicity, opinion dynamics have been shown to exhibit complex global behavior, and many recent works have proven their ability to solve consensus [DGM⁺11, BCP⁺24], majority [BCN⁺14, GP16], and other synchronization tasks [BGS21] important in distributed settings. From this perspective, in the present cooperative bandit setting, it is natural to view an agent's action choice at round t as its current opinion, and this opinion (action choice) can be updated in the subsequent round based only on the information exchanged with its randomly sampled neighbor. This raises the natural question of whether, in the cooperative bandit setting, simple protocols of this form can effectively learn at a population level. To make this precise, we define the following *memoryless and time-independent* property to describe protocols with opinion-dynamic-like attributes:

Property 1. A protocol \mathcal{P} is memoryless and time-independent if (i) an agent's action choice at round t + 1 depends only on its own action choice and observed reward from round t, and those of its random interaction partner, and (ii) the decision rule used by an agent is identical in all rounds.

In other words, using a memoryless and time-independent protocol means an agent's action choice only depends on information exchanged in its most recent interaction, and not on maintaining cumulative, time-dependent statistics (e.g., the number of times a certain action was chosen). This precludes adaptations of common single-agent bandit algorithms like UCB and EXP3 from satisfying Property 1. Thus given these opinion dynamic-like attributes, our main algorithmic question is:

(Q1) Is there a memoryless and time-independent protocol \mathcal{P} that obtains sublinear regret?

Best-action consensus Note that in addition to the standard goal of obtaining sublinear regret, in (single-agent) online learning and multi-armed bandits settings with stationary rewards, a common separate objective is *best-action identification* [LS20]. A successful algorithm for this task identifies (with some desired probability) the action with the highest-mean reward and continues to choose this action in future rounds in perpetuity.

In the present multi-agent setting, this corresponds to the distribution \mathbf{p}^t reaching (and remaining in for all subsequent rounds) a point mass on the highest-mean action (i.e., *all n* agents continue to choose this optimal action at every round). In the general context of the distributed GOSSIP model, such behavior corresponds to reaching *consensus* on the highest-mean action. Defined more formally:

Definition 1.2 (Best-Action Consensus). Under the stationary reward setting of Assumption 3, we say a protocol \mathcal{P} reaches *best-action consensus* in τ rounds if $\mathbf{p}^t = (1, 0, \dots, 0)$ for all $\tau \leq t \leq T$.

As mentioned, in the GOSSIP model, many simple opinion dynamics have been proven to quickly reach consensus (i.e., within at most a number of rounds polynomial in the size of the population n). Thus in the present setting, in addition to understanding whether simple opinion dynamic protocols can obtain sublinear regret, a second natural question to ask is the following:

(Q2) Is there a memoryless and time-independent protocol \mathcal{P} that reaches best-action consensus within poly(n) rounds?

Related works with GOSSIP communication Recent works of Celis et al. [CKV17] and Su et al. [SZL19] considered protocols in closely related settings that made initial attempts at answering these questions. In particular, Celis et al. proposed a simple dynamics satisfying Property 1 in a slight variant of the GOSSIP model, and they considered a stationary reward setting restricted to Bernoulli distributions. However, the regret bounds obtained for their protocol cannot be made sublinear unless n is exponentially large in T. The work of Su et al. [SZL19] considered a similar dynamics, again in the stationary Bernoulli reward setting, and they proved that best-arm consensus is eventually reached as $T \to \infty$, but without providing any quantitative rate. Thus together, these two works have left open obtaining positive answers to questions (Q1) and (Q2).

1.2 Our Contributions

In this work, we introduce and analyze families of local protocols that satisfy Property 1 and answer questions (Q1) and (Q2) affirmatively. Specifically, we restrict our focus to the **complete** communication graph, and we show that a simple instantiation of our family of protocols simultaneously obtains both sublinear regret and quickly reaches best-action consensus:

Main Results (Informal): There is a memoryless and time-independent protocol such that:

- Constant regret (see Theorem 2.8): for any time horizon $T \ge 1$, in the stationary reward setting, the protocol obtains regret at most $R(T) \le O(\sigma \log m + \log^5 n)$.
- Fast best-action consensus (see Theorem 2.9): in the stationary reward setting, with probability at least 1-o(1), the protocol reaches best-action consensus in $O(\sqrt{n}\log^3 n)$ rounds.

Together, these results demonstrate the surprising power of a simple opinion-dynamic protocol in the cooperative bandit setting, and for better interpretation we make the following remarks:

- First, not only does our protocol obtain sublinear regret, but it obtains only constant regret with respect to T, scaling only with logarithmic dependencies on m and n. With respect to T and m, this bound matches the optimal rate for the single-agent experts setting [AHK12], and it improves by at least a $O(\log T)$ factor over the best single-agent bandit regret bounds, which are of order $O(m \log T)$ (assuming a constant gap $(\mu_1 - \mu_2)$) [BCB12, LS20]. Thus in this cooperative bandit setting, our protocol leads to improved regret guarantees over the best single-agent methods.
- While the bound on R(T) has a polylogarithmic dependence on n, this quantity becomes negligible as T grows large, which is the main setting of interest. In other words, our protocol guarantees for any time horizon that $\frac{R(T)}{T}$ decays at a rate of roughly 1/T. Moreover, this bound holds for any family of distributions satisfying the boundedness conditions of Assumption 1, which extends beyond the Bernoulli reward setting considered in related work [CKV17, SZL19].
- In addition to obtaining only constant regret, Theorem 2.9 also establishes that this same algorithm reaches best action consensus within roughly \sqrt{n} rounds. While there do exist other opinion dynamics for reaching consensus in more general GOSSIP model settings in only O(polylog(n)) rounds, the combination of no-regret learning and best-action consensus achieved by our protocol exhibits the type of *best-of-both-worlds* behavior that is generally sought after in other multi-agent learning settings [HSP24].

Moreover, using similar techniques as in the proof of Theorem 2.8, we show the additional surprising result that our protocol is also robust to *adversarial rewards*. In this more challenging reward setting, the distributions ν_j^t may now vary over time (we state this formally in Section 8). In particular, we obtain a sublinear regret bound for our protocol under this reward setting, so long as the time horizon T does not grow too large with respect to n:

Sublinear regret for adversarial rewards (see Theorem 2.10): there is a memoryless and time-independent protocol such that, in the adversarial reward setting, when $T \leq (0.5 - \epsilon) \log_5 n$ for any $\epsilon \in (0, 0.5)$, the protocol obtains regret $R(T) \leq O(\sqrt{T \log m})$.

Thus even in a setting with adversarially changing reward distributions, our simple opinion-dynamics protocol still exhibits no-regret learning behavior. We again make several additional remarks:

- First, note that from a single-agent perspective with adversarial rewards, the sublinear $O(\sqrt{T \log m})$ rate is optimal (with respect to both T and m) for the *experts* setting [AHK12], and it improves by a \sqrt{m} factor over the optimal $O(\sqrt{Tm \log m})$ regret bounds in the bandit setting [BCB12]. Thus similarly to the stationary rewards case, our protocol leads to better regret guarantees over the best single-agent method in this cooperative setting. Moreover, our bound in this setting also answers an open question of Celis et al. [CKV17], who asked whether this type of simple dynamics could obtain sublinear regret guarantees under time-varying reward distributions.
- On the other hand, this result restricts the time horizon T to grow only logarithmically in n. The main barrier in allowing for larger T is related to the fact that, in this setting, the mass in each \mathbf{p}^t corresponding to the best action may still be relatively small. Thus the noise of the random agent communications may outweigh any meaningful signal on good action choices for large T.

In particular, in Section 8 we also prove for our protocol a lower bound on R(T) that scales like $\Omega(T)$ once T is roughly $\widetilde{\Omega}(\sqrt{n})$. Thus in general, our work leaves open the question of whether there exist other simple protocols (i.e., satisfying Property 1) that can obtain sublinear regret under adversarial rewards for longer time horizons.

Summary of techniques Our main technical insight is to show that, for several families of very simple protocols satisfying the memoryless and time-indepenence attributes of Property 1, the evolution of the resulting distributions $\{\mathbf{p}^t\}$ is closely related to a certain family of (centralized) multiplicative weights update (MWU) processes [AHK12]. Using this connection allows us to develop a general analysis framework, where we bound the regret of $\{\mathbf{p}^t\}$ by using bounds on the regret of the corresponding MWU process. At a high-level, this approach is similar in spirit to the analysis of [CKV17], which can be viewed as a special case of our framework.

Structure of paper The remainder of the paper is structured as follows: in Section 1.3, we briefly summarize several lines of related work. In Section 2, we then give present a more detailed technical overview of our protocols and main results, and in Section 3 we mention several open questions. We defer most proofs to the subsequent sections.

1.3 Other Related Work

Multi-armed bandits and online learning In the single-agent case, algorithms for the multiarmed bandit and experts settings have been studied extensively over the past several decades, and for background, we refer the reader to several introductory texts [CBL06, BCB12, LS20]. Note that the cooperative bandit setting of the present work is distinct from other multi-player bandit settings where agents seek to avoid choosing the same action in a given round [BP19, BB20].

Opinion and consensus dynamics Simple opinion dynamics for consensus, majority, and other algorithmic tasks have been extensively studied in the GOSSIP model and its common variants. We refer the interested reader to the survey of Becchetti et al. [BCN20]. These types of protocols are more generally related to other simple time-independent and memoryless dynamics for averaging [AL12, Ald13] and rumor-spreading [CLP10b, CLP10a, FPS12, GS12, Gia14].

Global dynamics from local protocols Finally, we remark that our results and analysis adds to a growing body of work that analyze local protocols in distributed models by relating their global evolution to centralized optimization algorithms [MMM18, EBB⁺21, PSV16, PV16].

2 Technical Overview

Notation and Other Preliminaries Throughout, we deal with multiple sequences of vectors indexed over rounds $t \in [T]$, for which we use the short hand notation $\{\mathbf{p}^t\} := \{\mathbf{p}^0, \mathbf{p}^1, \dots, \mathbf{p}^t\}$. We often compute expectation (resp., probabilities) conditioned on two sequences $\{\mathbf{p}^t\}$ and $\{\mathbf{g}^t\}$ simultaneously, and we denote this double conditioning by $\mathbf{E}_t[\cdot]$. When we wish to condition just on a single vector \mathbf{p}^t , we will write $\mathbf{E}_{\mathbf{p}^t}[\cdot]$. Given $\mathbf{p} = (p_1, \dots, p_m)$, we write $\mathbf{E}[\mathbf{p}]$ to denote the vector $(\mathbf{E}[p_1], \dots, \mathbf{E}[p_m])$. Throughout, we use the fact that for a non-negative random variable x, if $x \leq \alpha$ w.p. at least $1 - \gamma$, then $\mathbf{E}[x] \leq \alpha + \gamma$. We say with high probability to mean with probability at least $1 - n^{-\Omega(1)}$ and we say n sufficiently large when we require n larger than some absolute constant. We use the notation $\widetilde{O}(\cdot)$ to hide lower-order logarithmic dependencies.

2.1 Adoption and Comparison Protocols

We begin by introducing two families of very simple local protocols for this problem setting:

Family 1 (Adoption Protocols). Fix a non-decreasing adoption function $f : \mathbb{R} \to [0, 1]$.

- Then running an adoption protocol with function f means for each agent $u \in [n]$ the following:
- (i) At round t, assume: agent u chose action j; u sampled agent v; and v chose action $k \in [m]$.
- (ii) Then at round t + 1: agent u chooses action k with probability $f(g_k^t)$ and action j otherwise.

Family 2 (Comparison Protocols). Fix a non-decreasing score function $h : \mathbb{R} \to \mathbb{R}_{\geq 0}$.

- Then running a comparison protocol with function h means for each agent $u \in [n]$ the following:
- (i) At round t, assume: agent u chose action j; u sampled agent v; and v chose action $k \in [m]$.
- (ii) Then at round t + 1: defining $\rho_j \propto h(g_j^t)$ and $\rho_k \propto h(g_k^t)$, agent u chooses action k with probability ρ_k and action j with probability ρ_j .

In both families of protocols, each agent's action choice at round t + 1 is either its own action choice at round t, or that of its randomly sampled neighbor. Thus both families of protocols satisfy the memorlyess and time-independence attributes of Property 1. Moreover, in addition to the connection with opinion dynamics, both adoption and comparison protocols are more generally related to frameworks from social learning [EF95, KZP⁺16], pairwise comparison processes from evolutionary game theory [San10, AN14, SCS19], and algorithmic concepts like the power-of-two-choices [Mit01].

For concreteness, in this work we focus mainly on the simplest instantiation of an adoption protocol, β -adopt, which uses the adoption function $f_{\beta}(g) := \beta g$. With this instantiation an agent uat round t + 1 chooses the previous action of its neighbor with probability βg_j^t , and chooses its own previous action with probability $1 - \beta g_j^t$. Defined formally:

Protocol 1. Let β -adopt be the adoption protocol using the function $f_{\beta}(g) := \beta \cdot g$ for $\beta \in (0, \frac{1}{\sigma}]$.

Evolution in Conditional Expectation Regardless of the function f, we show that every instantiation of an adoption protocol is very closely related to a certain (global) multiplicative weights update process. To make this precise, consider the sequence of distributions $\{\mathbf{p}^t\}$ induced when each agent runs an adoption protocol with reward sequence $\{\mathbf{g}^t\}$. Then in conditional expectation, the coordinates of \mathbf{p}^{t+1} (corresponding to the fraction of agents choosing each action at the next round) evolve multiplicatively as follows:

Proposition 2.1. Consider running an adoption protocol with function f. Let $f(\mathbf{g}^t)$ denote the coordinate-wise application of f on \mathbf{g}^t . Then $\mathbf{E}_t[p_j^{t+1}] = p_j^t (1 + f(g_j^t) - \langle \mathbf{p}^t, f(\mathbf{g}^t) \rangle)$ for every t and j.

The proof of the proposition is given in Section 4. In words, this result shows that in conditional expectation, the coordinates of \mathbf{p}^{t+1} generated via an adoption protocol with function f grow multiplicatively, with weights depending on the strength of $f(\mathbf{g}_j^t)$ relative to the global average $\langle \mathbf{p}^t, f(\mathbf{g}^t) \rangle$. In Proposition 4.2 of Section 4, we also show that the coordinate-wise updates to \mathbf{p}^{t+1} generated via a comparison protocol have a similar multiplicative weights update structure (but now depending on the values ρ_i and ρ_k).

Together, Propositions 2.1 and 4.2 demonstrate that *every* adoption and comparison protocol follows a more general *zero-sum* multiplicative weights update structure in conditional expectation. More specifically, letting $\hat{\mathbf{p}}^{t+1} := \mathbf{E}_t[\mathbf{p}^{t+1}]$, the coordinates of $\hat{\mathbf{p}}^{t+1}$ evolve by

$$\widehat{p}_j^{t+1} := \mathbf{E}_t[p_j^{t+1}] = p_j^t \cdot \left(1 + F_j(\mathbf{p}^t, \mathbf{g}^t)\right), \qquad (1)$$

where the set of *m* functions $\{F_j\}_{j=1}^m$ satisfies the *zero-sum* condition $\sum_{j\in[m]} p_j \cdot F_j(\mathbf{p}, \mathbf{g}) = 0$ for all $\mathbf{p} \in \Delta_m$ and $\mathbf{g} \in \mathbb{R}^m$. For example, for adoption protocols with function *f*, Proposition 2.1 shows that each $F_j(\mathbf{p}, \mathbf{g}) = f(g_j) - \langle \mathbf{p}, f(\mathbf{g}) \rangle$.

Zero-Sum Multiplicative Weights Update The form of expression (1) is the key structural property that we use to analyze the regret bounds and consensus guarantees of our adoption and comparison protocols, and it more generally demonstrates a deeper connection between the global evolution of these local protocols and multiplicative weights update processes.

However, while the coordinates of the distribution $\mathbf{E}_t[\mathbf{p}^{t+1}]$ are updated multiplicatively as in (1), these updates are applied to the *realized* distribution \mathbf{p}^t , and thus the sequence $\{\mathbf{E}_t[\mathbf{p}^{t+1}]\}$ may not be *smooth*. Nevertheless, to analyze and bound the regret of the sequence $\{\mathbf{p}^t\}$, we can consider an idealized process $\{\mathbf{q}^t\}$ whose coordinates *do* evolve by composing this update structure in each round using the same family $\{\mathcal{F}\}$. We define these *zero-sum multiplicative weights update* (zero-sum MWU) processes as follows:

Definition 2.2 (Zero-Sum MWU). Let $\mathcal{F} = \{F_j\}$ be a family of m function $F_j : \Delta_m \times \mathbb{R}^m \to [-1, 1]$ satisfying the zero-sum condition $\sum_{j \in [m]} q_j \cdot F_j(\mathbf{q}, \mathbf{g}) = 0$ for all $\mathbf{q} \in \Delta_m$ and $\mathbf{g} \in \mathbb{R}^m$. Then we say $\{\mathbf{q}^t\}$ is a zero-sum MWU process with reward sequence $\{\mathbf{g}^t\}$ if for all $t \in [T]$ and $j \in [m]$: $q_j^{t+1} = q_j^t \cdot (1 + F_j(\mathbf{q}^t, \mathbf{g}^t)).$

Compared to the standard (linear) versions of multiplicative weights update processes [AHK12], the zero-sum condition $\sum_{j\in[m]} q_j \cdot F_j(\mathbf{q}, \mathbf{g})$ ensures that each \mathbf{q}^{t+1} always remains a distribution, without a renormalization step (i.e., the simplex Δ_m is invariant to $\{\mathbf{q}^t\}$). In addition, zero-sum MWU processes can be viewed as a discrete time approximation of the continuous time replicator dynamics, which are systems of the form $(dq_j^t/dt) = (u(g_j^t) - \langle \mathbf{q}^t, u(\mathbf{g}_j^t) \rangle)$ for some utility function u, which are very well studied in the context of evolutionary dynamics [SS83, HS⁺98, Cab00, San10]. On the other hand, discrete-time processes with these zero-sum update factors are not as well-studied.

2.2 Analysis Framework for Bounding R(T)

In order to analyze the sequences $\{\mathbf{p}^t\}$ generated by our families of protocols, we leverage the connection between the conditionally expected updates to $\{\mathbf{p}^t\}$ and zero-sum MWU processes. In particular, we construct a general analysis framework that couples the sequence $\{\mathbf{p}^t\}$ with a zero-sum MWU process $\{\mathbf{q}^t\}$ that starts at the same initial distribution, uses the same family \mathcal{F} , and runs on the same reward sequence. This framework is leveraged to prove our main results, and we proceed to introduce its components in more detail:

Definition 2.3 (Coupled Trajectories). Let $\mathcal{F} = \{F_j\}$ be a family of zero-sum functions as in Definition 2.2. Given a reward sequence $\{\mathbf{g}^t\}$, consider the sequences of distributions $\{\mathbf{p}^t\}$, $\{\widehat{\mathbf{p}}^t\}$, and $\{\mathbf{q}^t\}$, each initialized at $\mathbf{p}^0 \in \Delta_m$, such that for all $j \in [m]$:

$$q_j^{t+1} := q_j^t \cdot \left(1 + F_j(\mathbf{q}^t, \mathbf{g}^t)\right), \tag{2}$$

$$\hat{p}_i^{t+1} := p_i^t \cdot \left(1 + F_i(\mathbf{p}^t, \mathbf{g}^t)\right), \tag{3}$$

and where \mathbf{p}^t is the empirical average of *n* i.i.d. samples from the distribution $\widehat{\mathbf{p}}^t$.

Given this coupling definition, a straightforward calculation shows that we can over-approximate the regret R(T) of the sequence $\{\mathbf{p}^t\}$ by (i) regret of the sequence $\{\mathbf{q}^t\}$ and (ii) an additional error term incurred by this coupling. More formally, given the setting of Definition 2.3, we have:

Proposition 2.4. $R(T) \leq \widehat{R}(T) := \max_{j \in [m]} \sum_{t \in [T]} \mu_j^t - \mathbf{E}[\langle \mathbf{q}^t, \mathbf{g}^t \rangle] + \sigma \sum_{t \in [T]} \mathbf{E} \|\mathbf{q}^t - \mathbf{p}^t\|_1.$ Given this proposition, our approach for bounding R(T) is to derive bounds for the regret of the

process $\{\mathbf{q}^t\}$ and for the error terms separately. We describe these approaches as follows:

Regret Bounds for Zero-Sum MWU Processes To bound the regret of a zero-sum MWU process $\{\mathbf{q}^t\}$, the key step is to relate the function value $F_j(\mathbf{q}, \mathbf{g})$ in conditional expectation to the quantity $\mu_j^t - \langle \mathbf{q}, \boldsymbol{\mu}^t \rangle$. to this end we make the following assumptions on \mathcal{F} :

Assumption 2. Let $\mathcal{F} = \{F_j\}$ be a family of functions as in Definition 2.2, and let $\{\mathbf{g}^t\}$ be any reward sequence. Assume there exists $\alpha \in (0, 1/2], \delta \in [0, 1]$, and L > 0 such that

- (i) for all $\mathbf{p} \in \Delta_m$ and $j \in [m]$: $\frac{\alpha}{2} \left(\mu_j^t \langle \mathbf{q}, \boldsymbol{\mu}^t \rangle \delta \right) \leq \mathbf{E}_{\mathbf{q}} [F_j(\mathbf{q}, \mathbf{g}^t)] \leq \frac{\alpha}{2} \left(\mu_j^t \langle \mathbf{q}, \boldsymbol{\mu}^t \rangle + \delta \right)$
- (ii) for all $\mathbf{p}, \mathbf{q} \in [m]$: $|F_j(\mathbf{q}, \mathbf{g}^t) F_j(\mathbf{p}, \mathbf{g}^t)| \le L \cdot ||\mathbf{p} \mathbf{q}||_1$.

Roughly speaking, condition (i) of the assumption ensures that in (conditional) expectation, each $F_j(\mathbf{q}, \mathbf{g})$ is multiplicatively correlated with the regret of action j at round t, up to some additive slack δ , and condition (ii) ensures that each F_j is *L*-Lipschitz. We emphasize that many natural instantiations of the adoption and comparison protocols from Section 2.1 satisfy the conditions of the assumption. For example, for the β -adopt protocol, we show the following (proved in Section 4):

Proposition 2.5. The family \mathcal{F} induced by the β -adopt protocol satisfies Assumption 2 with $\alpha := 2\beta$, $\delta := 0$, and L := 2, for any $0 < \beta \le \min(1/4, 1/\sigma)$.

Under Assumption 2, we prove (in Section 5) the following bound on the expected regret of a zero-sum MWU process, which is parameterized with respect to the constants α and δ :

Theorem 2.6 (Regret of Zero-sum MWU). Consider a process $\{\mathbf{q}^t\}$ from Definition 2.2 with reward sequence $\{\mathbf{g}^t\}$ and using a family \mathcal{F} that satisfies Assumption 2 with parameters α and δ . Assume that $q_j^0 \ge \rho > 0$ with probability at least $1 - \gamma$. Let $\widetilde{R}(T) := \max_{j \in [m]} \sum_{t \in [T]} \mu_j - \mathbf{E}[\langle \mathbf{q}^t, \mathbf{g}^t \rangle]$. Then:

- In the stationary reward setting and assuming $\delta = 0$: $\widetilde{R}(T) \leq \frac{4}{\alpha} \cdot \log(1/\rho) + \gamma$
- Moreover, in the adversarial reward setting: $\widetilde{R}(T) \leq \frac{2}{\alpha} \cdot \log(1/\rho) + 2(\alpha + \delta)T + \gamma$.

To interpret these bounds, suppose $q^0 = 1/m$ deterministically and that $\delta = 0$. Then with stationary rewards, the regret of $\{\mathbf{q}^t\}$ is at most $O(\log m)$ (i.e., constant with respect to T). Additionally, for general adversarial rewards, the regret of $\{\mathbf{q}^t\}$ grows like $O((\log m)/\alpha + \alpha T)$. If α can be tuned to $\Theta(\sqrt{(\log m)/T})$, then this regret again scales sublinearly like $O(\sqrt{T \log m})$.

Thus Theorem 2.6 shows these zero-sum MWU processes obtain regret that match the optimal rates (in both reward settings) for standard MWU processes (cf., [CBL06, AHK12, LS20]).

Bounds on Coupling Error The second step is to bound the error terms $\sum_{t \in [T]} \mathbf{E} \| \mathbf{p}^t - \mathbf{q}^t \|_1$. For this, we leverage the fact that each $\mathbf{E}_t[\mathbf{p}^t]$ and \mathbf{q}^t are both defined with the same family \mathcal{F} and depend similarly on \mathbf{g}^{t-1} . Then using condition (ii) of Assumption 2 along with standard concentration bounds, we derive an overall bound on $\sum_{t \in [T]} \mathbf{E} \| \mathbf{p}^t - \mathbf{q}^t \|_1$, which we state as Lemma 6.1 in Section 6.

General τ -step Regret Bounds By the decomposition of R(T) from Proposition 2.4, we can then combine the zero-sum MWU regret bound of Theorem 2.6 and the coupling error bound of Lemma 6.1 to obtain the following, τ -step regret guarantee for the process $\{\mathbf{p}^t\}$:

Proposition 2.7. Let $R(\tau)$ be the regret of the sequence $\{\mathbf{p}^t\}$ induced by a local protocol \mathcal{P} that satisfies Assumption 2 with parameters α , δ and L. Let $\kappa := 3 + L$, fix $c \geq 1$, and consider n sufficiently large. Let $\widetilde{R}(\tau)$ be the regret of the corresponding zero-sum MWU process $\{\mathbf{q}^t\}$. Then $R(\tau) \leq \widetilde{R}(\tau) + O(\sigma \kappa^{\tau} \cdot \sqrt{\frac{mc \log n}{n}} + \frac{\sigma \tau}{n^c}).$

Equipped with this general analysis framework, we can now formally present our main results on the regret guarantees and consensus behavior of our protocols.

2.3 Main Result: Regret Bounds and Consensus for Stationary Rewards

The coupling introduced in the previous section provides a general framework for analyzing the regret of any adoption or comparison protocol. For concreteness and simplicity, we focus on the guarantees of the β -adopt protocol introduced in Section 2.1. We prove this adoption protocol obtains only *constant regret* (with respect to T) in the stationary reward setting, which provides an affirmative answer to first main algorithmic question (Q1) from Section 1.1.

Theorem 2.8. Let R(T) be the regret of the β -adopt protocol in the stationary reward setting with $\beta := \min(1/4, 1/\sigma)$. Then assuming $m = o(\log^{1.5} n)$ and n sufficiently large: $R(T) \leq O(\sigma \log m + \log^3 n)$.

Proof sketch of Theorem 2.8: As mentioned, we use the general τ -step regret bound of the analysis framework from Section 2.2 in conjunction with several additional arguments depending on the magnitude of the time horizon T. Specifically, we decompose the regret R(T) into three distinct phases. For this, we let $T_{\text{phase-1}} := \sqrt{n} \cdot \frac{\log m}{\sqrt{m \log n}}$ and $T_{\text{phase-2}} := 2\sqrt{n} \cdot \log^3 n$, and we moreover define:

$$\begin{split} R_{\mathsf{phase-1}} &:= \sum_{t=1}^{\min(T_{\mathsf{phase-1}},T)} \mu_1 - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle] ,\\ R_{\mathsf{phase-2}} &:= \sum_{t=T_{\mathsf{phase-1}}}^{\min(T_{\mathsf{phase-2}},T)} \mu_1 - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle] & \text{if } T \geq T_{\mathsf{phase-1}}, \text{ and } 0 \text{ otherwise},\\ R_{\mathsf{phase-3}} &:= \sum_{t=T_{\mathsf{phase-2}}}^{T} \mu_1 - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle] & \text{if } T \geq T_{\mathsf{phase-2}}, \text{ and } 0 \text{ otherwise}. \end{split}$$

Using this decomposition, we can write $R(T) = \sum_{t \in [T]} \mu_1 - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle] = R_{\mathsf{phase-1}} + R_{\mathsf{phase-2}} + R_{\mathsf{phase-3}}$. We then derive bounds on each of $R_{\mathsf{phase-1}}$, $R_{\mathsf{phase-2}}$, and $R_{\mathsf{phase-3}}$ individually:

• Bound on $R_{\text{phase-1}}$: to start, in the first $T_{\text{phase-1}}$ rounds, we repeatedly apply the τ -step regret bound of Proposition 2.7 via an epoch-based approach similar to that of Celis et al. [CKV17]. However, the core tool in obtaining a sharp bound in this first phase is to leverage the structure of the sequence $\{\mathbf{p}^t\}$ generated by the β -adopt protocol. In particular, we derive a lower bound on the growth of p_1^t over rounds, which allows us to show that the regret in each of the τ -round epochs is sufficiently shrinking. Together, this leads to the bound $R_{\text{phase-1}} \leq O(\sigma \log m)$. • Bounds on $R_{phase-2}$ and $R_{phase-3}$: For $T \ge T_{phase-1}$, we require additional techniques to bound the quantities $R_{phase-2}$ and $R_{phase-3}$. For this, our key technical insight is to show that, with probability at least 1 - O(1/n), within at most $T_{phase-1}$ rounds, the mass p_1^t is at least $1 - O((\log^2 n)/\sqrt{n})$ for every remaining round, By a straightforward calculation, each subsequent per-round regret is then at most $O((\log^2 n)/\sqrt{n})$. Thus in this regime, we resort to using expected hitting time bounds for supermartingale processes [Len20] to further show that, with probability at least 1 - o(1), the mass p_1^t reaches and remains at 1 within $T_{phase-2}$ rounds. Together, this leads to bounds of $O(\log^5 n)$ and o(1) on $R_{phase-2}$ and $R_{phase-3}$, respectively.

Summing these individual bounds yields $R(T) \leq O(\sigma \log m + \log^5 n)$, which holds for any $T \geq 1$. The structure of the three phases and corresponding regret guarantees are summarized in Figure 1.

$$Best-action \ consensus \ w.p. \ \ge 1 - o(1).$$

$$R_{Phase-1} \le O(\sigma \log m) \qquad \qquad R_{Phase-2} \le O(\log^5 n) \qquad \qquad R_{Phase-3} \le o(1)$$

$$T_{Phase-1 \approx \sqrt{n}} \qquad \qquad T_{Phase-2 \approx \sqrt{n} \log^3 n}$$

Figure 1: An depiction of the three phase structure used in the proof of Theorem 2.8, and the corresponding cumulative regret bound of each phase. The dotted vertical line denotes the time at which best-action consensus is reached with probability at least 1 - o(1) in Theorem 2.9.

Reaching Best-Action Consensus In addition to the guarantee that the β -adopt protocol obtains only sublinear regret scaling like $R(T) \leq \tilde{O}(1)$, as a byproduct of the proof of Theorem 2.8 (and in particular the bound on $R_{phase-2}$), we establish the following additional guarantee that the population reaches best action consensus after at most $\tilde{O}(\sqrt{n})$ rounds with probability at least 1 - o(1), and after at most $\tilde{O}(n)$ rounds with high probability:

Theorem 2.9. Consider the β -adopt protocol in the stationary reward setting of Theorem 2.8. Then $p_1^t = 1$ for all rounds $t \ge 2\sqrt{n}\log^3 n$ simultaneously with probability at least $1 - O(1/\log n)$, and for all rounds $t \ge n\log^2 n$ simultaneously with probability at least $1 - O(n^{-1/2})$.

Thus Theorem 2.9 answers affirmatively the second main algorithmic question (Q2) from Section 1.1, and together with the regret bound of Theorem 2.8, these two results demonstrate the surprising ability of a simple opinion-dynamic-like protocol to globally solve the online learning task of the present setting. The full proofs of Theorem 2.8 and Theorem 2.9 are developed in Section 7, and while these results are stated specifically for the β -adopt protocol, we suspect other instantiations of the adoption and comparison protocol families from Section 2.1 yield similar guarantees.

2.4 Robustness of Protocols to Adversarial Rewards

As a consequence of the connection between the evolution of our local adoption and comparison protocols and zero-sum MWU processes, we additionally show that these protocols obtain sublinear regret in an *adversarial* reward setting (formally defined in Section 8). Specifically, for the β -adopt protocol, we obtain the following regret bound scaling like $\tilde{O}(\sqrt{T})$:

Theorem 2.10. Let R(T) be the regret of the β -adopt protocol running in a general adversarial reward setting with $\beta := \sqrt{(\log m)/T}$. Let $T \leq (0.5 - \epsilon) \log_5 n$ for any $\epsilon \in (0, 0.5)$, and assume $m = o(\log^{1.5} n)$. Then for n sufficiently large: $R(T) \leq O(\sqrt{T \log m})$.

The proof of the theorem again uses the bound of Proposition 2.7 from the general analysis framework, and we present the details in Section 8. While the result shows the additional ability of the β -adopt protocol to obtain sublinear regret in this more challenging reward setting, the theorem restricts the time horizon T to grow only logarithmically in n. In Section 8, we further prove in Proposition 8.1 that for the β -adopt protocol, there exist adversarial reward sequences that force $R(T) \geq \Omega(T)$ once $T \geq \widetilde{\Omega}(\sqrt{n})$. We leave the study of whether other simple protocols can obtain sublinear regret for longer time horizons in the adversarial reward setting as future work.

3 Discussion and Open Problems

In this work, we proved that a simple opinion-dynamic-like protocol is a no-regret learning algorithm in the cooperative bandit setting. Moreover, we showed this protocol simultaneously reaches bestarm consensus in the stationary reward setting, and still obtains sublinear regret guarantees in the adversarial reward setting. Our results leave open several lines of questions:

- First, notice that Theorems 2.8, 2.9, and 2.10 all assume the size of the action set m grows no more than polylogarithmically in n. While this constraint is relatively mild (given that the main parameter of interest in these regret bounds is the dependence on T), establishing whether this constraint on m can be loosened is left for future work.
- In this work, we considered the complete communication graph as an initial case study for understanding the regret and consensus guarantees of our simple families of protocols. Thus a second immediate question is to quantify the regret of these simple protocols when the underlying communication graph is non-complete.

For general, non-complete topologies, we would expect the regret of our algorithms to have some dependence on the expansion or other combinatorial properties of the underlying graph. This is a phenomenon that appears in other cooperative bandit works within different communication models [CBGMM16, BOM19, MRKR19], as well as in the convergence guarantees of opinion dynamics for other tasks in the GOSSIP model [CLP10b, GS12, Gia14, MMM18].

• Finally, it remains open to establish whether other memoryless and time-independent protocols can obtain sublinear regret guarantees in the adversarial reward setting beyond the $O(\log n)$ -round time horizon of Theorem 2.10.

4 Details on Local Protocols

In this section, we provide more details on the families of adoption and comparison protocols introduced in Section 2.1. To start, we make the following remark regarding the neighbor sampling mechanism of the GOSSIP model that is assumed in the problem setting:

Remark 4.1. Recall in this work that we consider a *complete* communication graph. We assume further this communication graph contains self-loops, which is a standard assumption in the GOSSIP model [BGPS06, S⁺09, BCN⁺14, BCN20]. Moreover, we use the terminology "the neighbor sampled by an agent u" to refer to the uniformly random neighbor that agent u exchanges information with under the GOSSIP-style communication of the problem setting.

However, we remark these random information exchanges should be viewed as being "scheduled" by the model. In other words, in the GOSSIP model, the agent u does not explicitly perform the

neighbor sampling itself, but rather the model stipulates that in each round, every agent u has a (one-sided) information exchange with a uniformly random neighbor.

4.1 Evolution of Adoption Algorithms

For adoption algorithms, we prove Proposition 2.1, which derives the structure of their coordinatewise updates in conditional expectation. We restate the both the definition of Adoption Protocols and the proposition here for convenience:

Family 1 (Adoption Protocols). Fix a non-decreasing adoption function $f : \mathbb{R} \to [0, 1]$.

Then running an adoption protocol with function f means for each agent $u \in [n]$ the following:

(i) At round t, assume: agent u chose action j; u sampled agent v; and v chose action $k \in [m]$.

(ii) Then at round t + 1: agent u chooses action k with probability $f(g_k^t)$ and action j otherwise.

Proposition 2.1. Consider running an adoption protocol with function f. Let $f(\mathbf{g}^t)$ denote the coordinate-wise application of f on \mathbf{g}^t . Then $\mathbf{E}_t[p_j^{t+1}] = p_j^t (1 + f(g_j^t) - \langle \mathbf{p}^t, f(\mathbf{g}^t) \rangle)$ for every t and j.

Proof. First, letting $c_u^{t+1} \in [m]$ denote the action chosen by agent $u \in [n]$ in round t+1, observe that

$$\mathbf{E}_t[p_j^{t+1}] = \frac{1}{n} \sum_{u \in [n]} \mathbf{Pr}_t[c_u^{t+1} = j] ,$$

which follows from the fact that p_j^{t+1} is the average of the *n* indicators $\mathbf{1}\{c_u^{t+1}=j\}$. By the local symmetry of the algorithm and communication model, $\mathbf{Pr}_t[c_u^{t+1}=j]$ is identical for all agents *u*. However, this value is dependent on c_u^t (i.e., the action choice of *u* at the previous round *t*).

Thus using the law of total probability, for any agent u we can write

$$\begin{aligned} \mathbf{Pr}_t[c_u^{t+1} = j] &= \mathbf{1}\{c_u^t = j\} \cdot \mathbf{Pr}_t[c_u^{t+1} = j | c_u^t = j] \\ &+ \sum_{k \neq j \in [m]} \mathbf{1}\{c_u^t = k\} \cdot \mathbf{Pr}_t[c_u^{t+1} = j | c_u^t = k] . \end{aligned}$$

Now fix agent u, and let $v \in [n]$ denote the agent that u samples in round t. Now recall from the definition of the algorithm that if $c_u^t = k \neq j$, then $c_u^{t+1} = j$ with probability $f(g_j^t)$ only if agent v chose action j in round t, i.e., $c_v^t = j$. On the other hand, if $c_u^t = j$, then $c_u^{t+1} = j$ either if $c_v^t = j$, or if $c_v^t = k \neq j$ and agent u rejects adopting action k with probability $1 - f(g_k^t)$.

Thus we have

$$\begin{aligned} \mathbf{Pr}_t[c_u^{t+1} &= j | c_u^t = j] &= p_j^t + \sum_{k \neq j \in [m]} p_k^t \cdot (1 - f(g_k^t)) \\ \text{and} \quad \mathbf{Pr}_t[c_u^{t+1} &= j | c_u^t = k] &= p_j^t \cdot f(g_j^t) \quad \text{for } k \neq j \;. \end{aligned}$$

Combining these cases, noting also that $\frac{1}{n} \sum_{u \in [v]} \mathbf{1}\{c_u^t = k\} = p_k^t$ for any $k \in [m]$, and using the fact that $\sum_{k \in [m]} p_k^t = 1$, we can then write

$$\begin{split} \mathbf{E}_t[p_j^{t+1}] &= p_j^t \cdot \left(p_j^t + \sum_{k \neq j \in [m]} p_k^t \cdot (1 - f(g_k^t)) \right) + \sum_{k \neq j \in [m]} p_k^t \cdot \left(p_j^t \cdot f(g_j^t) \right) \\ &= p_j^t \cdot \left(1 + \sum_{k \neq j \in [m]} p_k^t \cdot \left(f(g_j^t) - f(g_k^t) \right) \right) \\ &= p_j^t \cdot \left(1 + f(g_j^t) - \left\langle \mathbf{p}^t, f(\mathbf{g}^t) \right\rangle \right), \end{split}$$

which concludes the proof.

Importantly, we also verify that such multiplicative updates in every coordinate j still lead to a proper distribution: for this, it is easy to check that

$$\sum_{j \in [m]} \mathbf{E}_t[p_j^{t+1}] = \sum_{j \in [m]} p_j^t \cdot \left(1 + f(g_j^t) - \langle \mathbf{p}^t, f(\mathbf{g}^t) \rangle\right)$$
$$= \sum_{j \in [m]} p_j^t + \langle \mathbf{p}^t, f(\mathbf{g}^t) \rangle - \langle \mathbf{p}^t, f(\mathbf{g}^t) \rangle = 1,$$

which holds since \mathbf{p}^t is a distribution.

4.1.1 Example Instantiation: the β -adopt protocol

As introduced in Section 2, the simplest instantiation of an adoption protocol is β -adopt:

Protocol 1. Let β -adopt be the adoption protocol using the function $f_{\beta}(g) := \beta \cdot g$ for $\beta \in (0, \frac{1}{\sigma}]$.

Using the zero-sum MWU terminology of Definition 2.2 and Assumption 2, observe by Proposition 2.1 that running this protocol induces the zero-sum family $\mathcal{F} = \{F_j\}_{j \in [m]}$ where $F_j(\mathbf{p}, \mathbf{g}) = \sum_{i \in [m]} p_j \cdot (f_\beta(g_j) - f_\beta(g_k))$ for each $j \in [m]$. For β -adopt, this simplifies to

$$F_j(\mathbf{p}, \mathbf{g}) = \beta \cdot (g_j - \langle \mathbf{p}, \mathbf{g} \rangle) \tag{4}$$

for all $j \in [m]$. Then we can show this algorithm statisfies Assumption 2 as follows:

Proposition 2.5. The family \mathcal{F} induced by the β -adopt protocol satisfies Assumption 2 with $\alpha := 2\beta$, $\delta := 0$, and L := 2, for any $0 < \beta \le \min(1/4, 1/\sigma)$.

Proof. By expression (4), and taking expectations conditioned on \mathbf{p} , we have

$$\mathbf{E}_{\mathbf{p}}[F_j(\mathbf{p},\mathbf{g})] = \beta \mu_j - \beta \langle \mathbf{p}, \boldsymbol{\mu} \rangle = \beta \cdot (\mu_j - \langle \mathbf{p}, \boldsymbol{\mu} \rangle)$$

where we define $\boldsymbol{\mu} = \mathbf{E}[\mathbf{g}]$. Thus β -adopt trivially satisfies Assumption 2 with $\delta = 0$ and $\alpha = 2\beta$ for $\beta \leq \min\{\frac{1}{4}, \frac{1}{\sigma}\}$. In particular, the constraint $\beta \leq \frac{1}{4}$ ensures $\alpha \leq \frac{1}{2}$, and the constraint $\beta \leq \frac{1}{\sigma}$ ensures $f_{\beta}(g_j) \leq 1$. Also, assuming $\beta \leq \min\{\frac{1}{4}, \frac{1}{\sigma}\}$, notice that $|f_{\beta}(g_j) - f_{\beta}(g_k)| \leq 2$ for any $g_j, g_k \in [0, \sigma]$, and thus setting L = 2 is sufficient to satisfy condition (ii) of the assumption.

We remark that other natural choices of adoption functions f include the sigmoid function, but for simplicity we focus mainly on the guarantees obtained by the β -adopt protocol.

4.2 Evolution of Comparison Protocols

Recall the definition of comparison protocols from Section 2.1:

Family 2 (Comparison Protocols). Fix a non-decreasing score function $h : \mathbb{R} \to \mathbb{R}_{\geq 0}$. Then running a comparison protocol with function h means for each agent $u \in [n]$ the following: (i) At round t, assume: agent u chose action j; u sampled agent v; and v chose action $k \in [m]$. (ii) Then at round t + 1: defining $\rho_j \propto h(g_j^t)$ and $\rho_k \propto h(g_k^t)$, agent u chooses action k with probability ρ_k and action j with probability ρ_j .

Natural choices for the score function h include an exponential function. However, regardless of the choice of h, the conditionally expected coordinate-wise updates to \mathbf{p}^t have a multiplicative structure similar to that of Adoption protocols. Specifically, we derive the following proposition, analogous to Proposition 2.1:

Proposition 4.2. Let $\{\mathbf{p}^t\}$ be the sequence induced when every agent runs the comparison protocol with score function h and reward sequence $\{\mathbf{g}^t\}$. Furthermore, for any $\mathbf{g} \in \mathbb{R}^m$ and $j \in [m]$, let $H(\mathbf{g}, j) \in [-1, 1]^m$ be the m-dimensional vector whose k th coordinate is given by $\rho_j - \rho_k$. Then $\mathbf{E}_t[p_j^{t+1}] = p_j^t \cdot (1 + \langle \mathbf{p}^t, H(\mathbf{g}^t, j) \rangle)$ for every t and j.

Proof. Fix $j \in [m]$ and $t \in [T]$. Again let $c_i^t \in [m]$ denote the action chosen by agent $i \in [n]$ at round t. Then observe that we can write

$$\begin{aligned} \mathbf{E}_t \big[p_j^{t+1} \big] &= \frac{1}{n} \sum_{i \in [n]} \mathbf{Pr}_t \big[c_i^{t+1} = j \big] = \frac{1}{n} \sum_{i \in [n]} \left(\mathbf{1} \{ c_i^t = j \} \cdot \mathbf{Pr}_t \big[c_i^{t+1} = j \mid c_i^t = j \big] \\ &+ \sum_{k \neq j \in [m]} \mathbf{1} \{ c_i^t = k \} \cdot \mathbf{Pr}_t \big[c_i^{t+1} = j \mid c_i^t = k \big] \right). \end{aligned}$$

In the case that $c_i^t = j$, note that $c^{t+1} = j$ with probability 1 if agent *i* samples an agent *u* that also chose action *j* in round *t*. Otherwise, if agent *u* chose some action $k \neq j$, then agent *i* chooses action *j* with probability $1 - h(g_k^t) / (h(g_j^t) + h(g_k^t))$. Together, this means that

$$\mathbf{Pr}_{t}\left[c_{i}^{t+1} = j \mid c_{i}^{t} = j\right] = p_{j}^{t} + \sum_{k \neq j \in [m]} p_{k}^{t} \left(1 - \frac{h(g_{k}^{t})}{h(g_{j}^{t}) + h(g_{k}^{t})}\right)$$
$$= 1 - \sum_{k \neq j \in [m]} p_{k}^{t} \cdot \frac{h(g_{k}^{t})}{h(g_{j}^{t}) + h(g_{k}^{t})} \quad .$$
(5)

In the other case when $c_i^t = k \neq j$, then $c^{t+1} = j$ only when agent *i* samples a neighbor that chose action *j* in round *t*, and thus

$$\mathbf{Pr}_t \left[c_i^{t+1} = j \mid c_i^t = k \right] = p_j^t \cdot \frac{h(g_j^t)}{h(g_j^t) + h(g_k^t)} .$$
(6)

Now observe that for any $k \in [m]$, $\frac{1}{n} \sum_{i \in [n]} \mathbf{1}\{c_i^t = k\} = p_k^t$ by definition. Then together with expression (5) and (6), we have

$$\begin{split} \mathbf{E}_{t} \begin{bmatrix} p_{j}^{t+1} \end{bmatrix} &= p_{j}^{t} \left(1 - \sum_{k \neq j \in [m]} p_{k}^{t} \cdot \frac{h(g_{k}^{t})}{h(g_{j}^{t}) + h(g_{k}^{t})} \right) + \sum_{k \neq j \in [m]} p_{k}^{t} \cdot p_{j}^{t} \frac{h(g_{j}^{t})}{h(g_{j}^{t}) + h(g_{k}^{t})} \\ &= p_{j}^{t} \cdot \left[1 + \sum_{k \neq j \in [m]} p_{k}^{t} \cdot \frac{h(g_{j}^{t}) - h(g_{k}^{t})}{h(g_{j}^{t}) + h(g_{k}^{t})} \right] \\ &= p_{j}^{t} \cdot \left[1 + \left\langle \mathbf{p}^{t}, H(\mathbf{g}^{t}, j) \right\rangle \right], \end{split}$$

which concludes the proof.

Again, we also verify that for any $\mathbf{p} \in \Delta_m$ and $\mathbf{g} \in [0, 1]^m$, the family of functions $\{\langle \mathbf{p}, H(\mathbf{g}, j) \rangle\}_{j \in [m]}$ satisfies the zero-sum property $\sum_{j \in [m]} p_j \cdot \langle \mathbf{p}, H(\mathbf{g}, j) \rangle = 0$. To see this, observe that

$$\sum_{j \in [m]} p_j \cdot \langle \mathbf{p}, H(\mathbf{g}, j) \rangle = \sum_{j \in [m]} p_j \cdot \sum_{k \in [m]} p_k \cdot \frac{h(g_j^t) - h(g_k^t)}{h(g_j^t) + h(g_k^t)} = \sum_{(j,k) \in [m] \times [m]} p_j \cdot p_k \cdot \left(\frac{h(g_j^t) - h(g_k^t)}{h(g_j^t) + h(g_k^t)} + \frac{h(g_k^t) - h(g_j^t)}{h(g_j^t) + h(g_k^t)} \right) = 0.$$

5 Details on Zero-Sum MWU Regret Bounds

In this section, we prove Theorem 2.6, which bounds the regret of a Zero-Sum MWU process from Definition 2.2. The regret bound relies on some smoothness assumptions of the zero-sum MWU process which are summarized in Assumption 2. We restate the assumptions and theorem here:

Assumption 2. Let $\mathcal{F} = \{F_j\}$ be a family of functions as in Definition 2.2, and let $\{\mathbf{g}^t\}$ be any reward sequence. Assume there exists $\alpha \in (0, 1/2], \delta \in [0, 1]$, and L > 0 such that

- (i) for all $\mathbf{p} \in \Delta_m$ and $j \in [m]$: $\frac{\alpha}{2} \left(\mu_j^t \langle \mathbf{q}, \boldsymbol{\mu}^t \rangle \delta \right) \leq \mathbf{E}_{\mathbf{q}}[F_j(\mathbf{q}, \mathbf{g}^t)] \leq \frac{\alpha}{2} \left(\mu_j^t \langle \mathbf{q}, \boldsymbol{\mu}^t \rangle + \delta \right)$
- (ii) for all $\mathbf{p}, \mathbf{q} \in [m]$: $|F_i(\mathbf{q}, \mathbf{g}^t) F_i(\mathbf{p}, \mathbf{g}^t)| \le L \cdot ||\mathbf{p} \mathbf{q}||_1$.

Theorem 2.6 (Regret of Zero-sum MWU). Consider a process $\{\mathbf{q}^t\}$ from Definition 2.2 with reward sequence $\{\mathbf{g}^t\}$ and using a family \mathcal{F} that satisfies Assumption 2 with parameters α and δ . Assume that $q_j^0 \ge \rho > 0$ with probability at least $1 - \gamma$. Let $\widetilde{R}(T) := \max_{j \in [m]} \sum_{t \in [T]} \mu_j - \mathbf{E}[\langle \mathbf{q}^t, \mathbf{g}^t \rangle]$. Then:

- In the stationary reward setting and assuming $\delta = 0$: $\widetilde{R}(T) \leq \frac{4}{\alpha} \cdot \log(1/\rho) + \gamma$
- Moreover, in the adversarial reward setting: $\widetilde{R}(T) \leq \frac{2}{\alpha} \cdot \log(1/\rho) + 2(\alpha + \delta)T + \gamma$.

Under the conditions of Assumption 2, the proof of Theorem 2.6 leverages standard "potential function" approaches to proving MWU regret bounds (i.e., in the spirit of Arora et al. [AHK12]), but with some additional bookkeeping to account for the α and δ parameters. In the stationary reward setting and assuming $\delta = 0$, we can further use the fact that $\mu_1 \geq \langle \mathbf{p}^t, \boldsymbol{\mu} \rangle$ for all rounds t to derive a much smaller cumulative regret bound that is only a constant with respect to T.

Note that we also allow for a probabilistic lower bound on the initial mass of the coordinate corresponding to the action with greatest cumulative mean reward, which is useful in later applications of the theorem where the distribution \mathbf{q}^0 is initialized at a random \mathbf{p}^0 .

Proof. Fix $j \in [m]$ and $t \in [T]$. Recall that in round t, both \mathbf{q}^t and \mathbf{g}^t are random variables, where \mathbf{q}^t depends on the randomness in both $\{\mathbf{q}^{t-1}\}$ and $\{\mathbf{g}^{t-1}\}$. Then conditioning on both of these sequences (which is captured in the notation $\mathbf{E}_{t-1}[\cdot]$), we can use the form of the zero-sum MWU update rule of Definition 2.2 to write

$$\mathbf{E}_{t-1} \begin{bmatrix} q_j^t \end{bmatrix} = \mathbf{E}_{t-1} \begin{bmatrix} q_j^t \cdot \left(1 + F_j(\mathbf{q}^t, \mathbf{g}^t) \right) \end{bmatrix}$$

= $q_j^t \cdot \mathbf{E}_{t-1} \begin{bmatrix} 1 + F_j(\mathbf{q}^t, \mathbf{g}^t) \end{bmatrix} = q_j^t \cdot \left(1 + \mathbf{E}_{t-1} \begin{bmatrix} F_j(\mathbf{q}^t, \mathbf{g}^t) \end{bmatrix} \right) .$

Here, the second equality comes from the fact that \mathbf{q}^t is a constant when conditioning on $\{\mathbf{q}^{t-1}\}$ and $\{\mathbf{g}^{t-1}\}$, and thus $\mathbf{E}_{t-1}[q_i^t] = q_i^t$. Now for readability, let us define

$$m_j^t := \mathbf{E}_{t-1} [F_j(\mathbf{q}^t, \mathbf{g}^t)],$$

1

and that m_j^t is deterministic (meaning $\mathbf{E}[m_j^t] = m_j^t$), since the only remaining randomness after the conditioning is with respect to \mathbf{g}^t . Thus using the law of iterated expectation, we can ultimately write

$$\mathbf{E}[q_j^{t+1}] = \mathbf{E}[\mathbf{E}_{t-1}[q_j^{t+1}]] = \mathbf{E}[q_j^t] \cdot (1+m_j^t)$$

By repeating the preceding argument for each of $\mathbf{E}[q_j^{t-1}], \ldots, \mathbf{E}[q_j^1]$, and setting T = t + 1, we find that

$$\mathbf{E}[q_j^T] = q_j^0 \cdot \prod_{t \in [T-1]} \left(1 + m_j^t\right).$$
⁽⁷⁾

From here, we roughly follow a standard multiplicative weights analysis: first, define the sets M_j^+ and M_j^- as

$$M_j^+ = \{t \in [T-1] : m_j^t \ge 0\}$$

and $M_j^- = \{t \in [T-1] : m_j^t < 0\}$

where clearly $M_j^+ \cup M_j^- = [T]$. Then we can rewrite expression (7) as

$$\mathbf{E}[q_j^T] = q_j^0 \cdot \prod_{t \in M_j^+} \left(1 + m_j^t\right) \cdot \prod_{t \in M_j^-} \left(1 + m_j^t\right) \cdot$$

Now for each t, define $\Delta_j^t := \mu_j^t - \langle \mathbf{q}^t, \boldsymbol{\mu}^t \rangle \in [-1, 1]$. Here, the bounds on the range of each Δ_j^t follows from the assumption that all $\mu_j^t \in [0, 1]$. Using this notation, observe that Assumption 2 implies $m_j^t \geq \frac{\alpha}{2} \cdot (\Delta_j^t - \delta)$ for every t and j. Observe that if $\Delta_j^t < 0$, then we must have $m_j^t < 0$. On the other hand, when $\Delta_j^t \geq 0$, the sign of m_j^t is ambiguous. To distinguish the two cases, we define the additional two sets G_j^+ and G_j^- as

$$G_j^+ = \{ t \in [T-1] : \Delta_j^t - \delta \ge 0 \}$$

and $G_j^- = \{ t \in [T-1] : \Delta_j^t - \delta < 0 \}.$

Combining the pieces above, it follows that we can write

$$\begin{split} \mathbf{E}[q_j^T] \; &\geq \; q_j^0 \cdot \prod_{t \in M_j^+} \left(1 + \frac{\alpha(\Delta_j^t - \delta)}{2} \right) \cdot \prod_{t \in M_j^-} \left(1 + \frac{\alpha(\Delta_j^t - \delta)}{2} \right) \\ &= \; q_j^0 \cdot \prod_{t \in M_j^+ \cap G_j^+} \left(1 + \frac{\alpha(\Delta_j^t - \delta)}{2} \right) \cdot \prod_{t \in M_j^+ \cap G_j^-} \left(1 + \frac{\alpha(\Delta_j^t - \delta)}{2} \right) \cdot \prod_{t \in M_j^-} \left(1 + \frac{\alpha(\Delta_j^t - \delta)}{2} \right) \,. \end{split}$$

Observe also that each $|\Delta_j^t - \delta| \in [-2, 2]$ by the definition of Δ_j^t and by the assumption that $\delta \in [0, 1]$. Thus we can then use the facts that $(1 + \alpha x) \ge (1 + \alpha)^x$ for $x \in [0, 1]$, and that $(1 + \alpha x) \ge (1 - \alpha)^{-x}$ for $x \in [-1, 0]$, which allows us to further simplify and write

$$\mathbf{E}[q_j^T] \geq q_j^0 \cdot \prod_{t \in M_j^+ \cap G_j^+} (1+\alpha)^{\frac{(\Delta_j^t - \delta)}{2}} \cdot \prod_{t \in M_j^+ \cap G_j^-} (1-\alpha)^{-\frac{(\Delta_j^t - \delta)}{2}} \cdot \prod_{t \in M_j^-} (1-\alpha)^{-\frac{(\Delta_j^$$

Now using the fact that $q_j^T \leq 1$, taking logarithms, and multiplying through by 2, we find

$$0 \geq 2 \log q_j^0 + \sum_{t \in M_j^+ \cap G_j^+} \log(1+\alpha) (\Delta_j^t - \delta) \\ - \sum_{t \in M_j^+ \cap G_j^-} \log(1-\alpha) (\Delta_j^t - \delta) - \sum_{t \in M_j^-} \log(1-\alpha) (\Delta_j^t - \delta) .$$
(8)

From here, we conclude the proof by considering the stationary and adversarial reward settings separately.

Stationary reward setting with $\delta = 0$: We start with stationary reward setting (as specified in Assumption 1) and further assume that $\delta = 0$. Consider j = 1, and observe by the assumption of on the ordering of coordinates in $\boldsymbol{\mu}$ that $\Delta_1^t = \mu_1 - \langle \mathbf{q}^t, \boldsymbol{\mu} \rangle \ge 0$ for all \mathbf{q}^t . Thus by definition, we have $M_1^+ \cap G_1^+ = T$, and expression (8) simplifies to

$$0 \geq 2 \log q_j^0 + \sum_{t \in [T]} \log(1+\alpha) \Delta_1^t \; .$$

Using the identity $\log(1+x) \ge x - x^2 \ge x/2$ (which holds for all $x \in (0, 1/2]$) and rearranging terms then yields

$$\sum_{t \in [T]} \Delta_1^t \leq \frac{4 \log(1/q_j^0)}{\alpha} . \tag{9}$$

By definition, we have $\Delta_1^t = \mu_1 - \langle \mathbf{q}^t, \boldsymbol{\mu} \rangle$ for each t, and thus we can write $\langle \mathbf{q}^t, \boldsymbol{\mu} \rangle = \langle \mathbf{q}^t, \mathbf{E}[\mathbf{g}^t] \rangle = \mathbf{E}_{\mathbf{q}^t}[\langle \mathbf{q}^t, \mathbf{g}^t \rangle]$. Moreover, by the assumption that $\mathbf{q}_1^0 \ge \rho > 0$ with probability at least $1 - \gamma$, we have with this same probability that

$$\sum_{t \in [T]} \mu_1 - \mathbf{E}_{\mathbf{q}^t}[\langle \mathbf{q}^t, \mathbf{p}^t \rangle] \leq \frac{4 \log(1/\rho)}{\alpha}$$

Then taking expectations and using the law of iterated expectation, we have

$$\widetilde{R}(T,1) = \sum_{t \in [T]} \mu_1 - \mathbf{E}[\langle \mathbf{q}^t, \mathbf{p}^t \rangle] \leq \frac{4 \log(1/\rho)}{\alpha} + \gamma ,$$

which proves the claim for the stationary case.

General adversarial reward setting: We now consider the general adversarial reward setting and pick back up from expression (8). By definition, recall that $(\Delta_j^t - \delta)$ is non-negative for $t \in M_j^+ \cap G_j^+$, and negative for $t \in M_j^+ \cap G_j^-$ and $t \in M_j^-$. Thus again using the identities $\log(1+x) \ge x - x^2$ and $-\log(1-x) \le x + x^2$, which both hold for all $x \in [0, \frac{1}{2}]$, we can further bound expression (8)

and rearrange to find

$$2\log(1/q_{j}^{0}) \geq \sum_{t \in M_{j}^{+} \cap G_{j}^{+}} (\alpha - \alpha^{2})(\Delta_{j}^{t} - \delta) + \sum_{t \in M_{j}^{+} \cap G_{j}^{-}} (\alpha + \alpha^{2})(\Delta_{j}^{t} - \delta) + \sum_{t \in M_{j}^{-}} (\alpha + \alpha^{2})(\Delta_{j}^{t} - \delta)$$

$$= \sum_{t \in M_{j}^{+} \cap G_{j}^{+}} \Delta_{j}^{t} \alpha - \sum_{t \in M_{j}^{+} \cap G_{j}^{+}} \Delta_{j}^{t} \alpha^{2} - \sum_{t \in M_{j}^{+} \cap G_{j}^{+}} \delta(\alpha - \alpha^{2})$$

$$+ \sum_{t \in M_{j}^{+} \cap G_{j}^{-}} \Delta_{j}^{t} \alpha + \sum_{t \in M_{j}^{+} \cap G_{j}^{-}} \Delta_{j}^{t} \alpha^{2} - \sum_{t \in M_{j}^{+} \cap G_{j}^{-}} \delta(\alpha + \alpha^{2})$$

$$+ \sum_{t \in M_{j}^{-}} \Delta_{j}^{t} \alpha + \sum_{t \in M_{j}^{-}} \Delta_{j}^{t} \alpha^{2} - \sum_{t \in M_{j}^{-}} \delta(\alpha + \alpha^{2}) .$$
(10)

Now in expression (10), there are nine individual summations. We collect these into into four groups, and then bound and simplify as follows:

$$\begin{array}{lll} (\mathrm{i}) & \sum_{t \in M_j^+ \cap G_j^+} \Delta_j^t \alpha \ + \sum_{t \in M_j^+ \cap G_j^-} \Delta_j^t \alpha \ + \sum_{t \in M_j^-} \Delta_j^t \alpha \ = \ \alpha \sum_{t \in [T]} \Delta_j^t \\ (\mathrm{ii}) & - \sum_{t \in M_j^+ \cap G_j^+} \Delta_j^t \alpha^2 \ + \sum_{t \in M_j^+ \cap G_j^-} \Delta_j^t \alpha^2 \ + \sum_{t \in M_j^-} \Delta_j^t \alpha^2 \ \ge \ -\alpha^2 \sum_{t \in [T]} |\Delta_j^t| \\ (\mathrm{iii}) & - \sum_{t \in M_j^+ \cap G_j^+} \delta(\alpha - \alpha^2) \ - \sum_{t \in M_j^+ \cap G_j^-} \delta(\alpha + \alpha^2) \ - \sum_{t \in M_j^-} \delta(\alpha + \alpha^2) \ \ge \ -2\alpha \sum_{t \in [T]} \delta \ . \end{array}$$

In the above, we use in (ii) the fact that $\Delta_j^t \ge -|\Delta_j^t|$ for any t, and in (iv) the facts that $\alpha - \alpha^2 \le 2\alpha$ and $\alpha + \alpha^2 \le 2\alpha$. Then substituting these groups back into expression (10), we ultimately find that

$$2\log(1/q_j^0) \geq \alpha \sum_{t \in [T]} \Delta_j^t - \left((\alpha^2 + \sum_{t \in [T]} |\Delta_j^t| + 2\alpha \sum_{t \in [T]} \delta \right)$$
$$\geq \alpha \sum_{t \in [T]} \Delta_j^t - \left((\alpha^2 + \delta\alpha) \cdot 2T \right),$$

where the final inequality comes from the fact that $|\Delta_j^t| \leq 2$ and the assumption that $\delta \leq 1$. Thus using the definition $\Delta_j^t = \mu_j^t - \langle \mathbf{q}^t, \boldsymbol{\mu}^t \rangle$, we can rearrange to write

$$\sum_{t \in [T]} \mu_j^t - \langle \mathbf{q}^t, \boldsymbol{\mu}^t \rangle \leq \frac{4 \log(1/q_j^0)}{\alpha} + 2(\alpha + \delta) \cdot T .$$

Finally, as in the stationary case, observe for each $t \in [T]$ that $\langle \mathbf{q}^t, \boldsymbol{\mu}^t \rangle = \langle \mathbf{q}^t, \mathbf{E}[\mathbf{g}^t] \rangle = \mathbf{E}_{\mathbf{q}^t}[\langle \mathbf{q}^t, \mathbf{g}^t \rangle]$, and recall also by assumption that $q_j^0 \ge \rho > 0$, with probability at least $1 - \gamma$. Thus with this same probability:

$$\sum_{t \in [T]} \mu_j^t - \mathbf{E}_{\mathbf{q}^t}[\langle \mathbf{q}^t, \mathbf{g}^t \rangle] \leq \frac{2\log(1/\rho)}{\alpha} + 2(\alpha + \delta) \cdot T$$

Then taking expectations on both sides and using the law of iterated expectation, we find

$$\sum_{t \in [T]} \mu_j^t - \mathbf{E}[\langle \mathbf{q}^t, \mathbf{g}^t \rangle] \leq \frac{2\log(1/\rho)}{\alpha} + 2(\alpha + \delta) \cdot T + \gamma ,$$

which concludes the proof for the general, adversarial reward setting.

6 Details on Coupling Error Bounds

In this section, we develop the proof of the following lemma, which bounds the error on the coupling from Definition 2.3:

Lemma 6.1. Consider the sequences $\{\mathbf{p}^t\}$, $\{\widehat{\mathbf{p}}^t\}$, and $\{\mathbf{q}^t\}$ from Definition 2.3 with a reward sequence $\{\mathbf{g}^t\}$ and using a family \mathcal{F} that satisfies Assumption 2 with parameter L. Let $\kappa := (3+L)$, and assume $n \geq 3c \log n$ for some $c \geq 1$. Then for any $\tau \geq 1$: $\sum_{t \in [\tau]} \mathbf{E} \|\mathbf{q}^t - \mathbf{p}^t\|_1 \leq O(\kappa^{\tau} \cdot \sqrt{\frac{mc \log n}{n}} + \frac{3\tau}{n^c})$.

We start by recalling the overview of the argument, which was briefly introduced in Section 2.2 First, recall by the law of iterated expectation that for each $t \in [\tau]$:

$$\mathbf{E} \| \mathbf{q}^{t+1} - \mathbf{p}^{t+1} \|_{1} = \mathbf{E} \left[\mathbf{E}_{t} \| \mathbf{q}^{t+1} - \mathbf{p}^{t+1} \|_{1} \right].$$

Then by the triangle inequality and linearity of expectation, it follows that

$$\sum_{t \in [T]} \mathbf{E} \| \mathbf{q}^{t+1} - \mathbf{p}^{t+1} \|_{1} \leq \mathbf{E} \Big[\sum_{t \in [T]} \mathbf{E}_{t} \| \mathbf{q}^{t+1} - \widehat{\mathbf{p}}^{t+1} \|_{1} + \mathbf{E}_{t} \| \widehat{\mathbf{p}}^{t+1} - \mathbf{p}^{t+1} \|_{1} \Big] \\ = \mathbf{E} \Big[\sum_{t \in [T]} \mathbf{E}_{t} \| \mathbf{q}^{t+1} - \widehat{\mathbf{p}}^{t+1} \|_{1} + \| \widehat{\mathbf{p}}^{t+1} - \mathbf{p}^{t+1} \|_{1} \Big].$$
(11)

Here, the final equality is due to the fact that both $\hat{\mathbf{p}}^{t+1}$ and \mathbf{p}^{t+1} are functions of $\{\mathbf{p}^t\}$ and $\{\mathbf{g}^t\}$, which means $\mathbf{E}_t \|\hat{\mathbf{p}}^{t+1} - \mathbf{p}^{t+1}\|_1 = \|\hat{\mathbf{p}}^{t+1} - \mathbf{p}^{t+1}\|_1$ for each t. Thus in expression (11), we have decomposed the error (in conditional expectation) at each round t+1 as the sum of the distances between \mathbf{q}^{t+1} and $\hat{\mathbf{p}}^{t+1}$ and $\hat{\mathbf{p}}^{t+1}$ and \mathbf{p}^{t+1} . As mentioned in Section 2.2, we control each of these sets of terms as follows:

- To bound each $\|\mathbf{q}^{t+1} \mathbf{p}^{t+1}\|_1$, recall the distributions are related (coordinate-wise) are related under the randomness of \mathbf{g}^t and the same zero-sum family $\mathcal{F} = \{F_j\}_{j \in [m]}$. Thus if \mathbf{q}^t and \mathbf{p}^t are close, we can show \mathbf{q}^{t+1} and $\hat{\mathbf{p}}^{t+1}$ must also be close.
- For terms $\|\widehat{\mathbf{p}}^{t+1} \mathbf{p}^{t+1}\|$, recall that \mathbf{p}^{t+1} can be viewed as the empirical average of n i.i.d samples from $\widehat{\mathbf{p}}^{t+1}$. Thus using the fact that $\widehat{\mathbf{p}}^{t+1}$ is a discrete probability distribution, we can use standard concentration bounds to control the error $\|\widehat{\mathbf{p}}^{t+1} \mathbf{p}^{t+1}\|$.

We make this intuition precise via the following two propositions:

Proposition 6.2. For every $t \ge 1$: $\mathbf{E}_t \| \widehat{\mathbf{p}}^{t+1} - \mathbf{q}^{t+1} \|_1 \le (2+L) \cdot \mathbf{E}_{t-1} \| \mathbf{p}^t - \mathbf{q}^t \|_1$.

Proposition 6.3. Fix $\tau \ge 1$ and $c \ge 1$. For $n \ge 3c \log n$, it holds for all $t \in [\tau]$ simultaneously that

(i)
$$|p_j^t - \hat{p}_j^t| \leq \sqrt{\frac{3c\log n}{n}}$$
 for any fixed $j \in [m]$,
and (ii) $\|\mathbf{p}^t - \widehat{\mathbf{p}}^t\|_1 \leq \sqrt{\frac{9m \cdot c\log(2n)}{n}}$,

with probability at least $1 - \frac{3\tau}{n^c}$.

Granting both propositions true for now, we can then prove the main lemma:

Proof (of Lemma 6.1). Fix $c \ge 1$ and assume $n \ge 3c \log n$. For readability, let us define

$$\Phi := \frac{\sqrt{9mc\log(2n)}}{\sqrt{n}}$$

Then by substituting the bound of claim (ii) of Proposition 6.3 into expression (11), we find that

$$\mathbf{E}_{t} \| \mathbf{q}^{t+1} - \mathbf{p}^{t+1} \|_{1} \leq \mathbf{E}_{t} \| \mathbf{q}^{t+1} - \widehat{\mathbf{p}}^{t+1} \|_{1} + \| \widehat{\mathbf{p}}^{t+1} - \mathbf{p}^{t+1} \|_{1} \\
\leq \mathbf{E}_{t} \| \mathbf{q}^{t+1} - \widehat{\mathbf{p}}^{t+1} \|_{1} + \Phi$$
(12)

for all $t \in [\tau]$ simultaneously with probability at least $1 - \frac{3\tau}{n^c}$. Then substituting the bound of Proposition 6.2 into expression (12), for each t we find that

$$\sum_{t \in [\tau]} \mathbf{E}_t \| \mathbf{q}^{t+1} - \mathbf{p}^{t+1} \|_1 \le (2+L) \cdot \mathbf{E}_{t-1} \| \mathbf{q}^t - \mathbf{p}^t \|_1 + \Phi$$

simultaneously with probability at least $1 - \frac{3\tau}{n^c}$. Now recall by definition that $\mathbf{p}^0 = \mathbf{q}^0$, which implies $\mathbf{E}_0[\mathbf{q}^1] = \mathbf{E}_0[\mathbf{\hat{p}}^1]$. Then unrolling the recurrence yields

$$\mathbf{E}_t \| \mathbf{q}^{t+1} - \mathbf{p}^{t+1} \|_1 \le (3+L)^t \cdot \Phi$$

for each $t \in [\tau]$, again with probability at least $1 - \frac{3\tau}{n^c}$. Reindexing and summing over all t yields with probability at least $1 - \frac{3\tau}{n^c}$:

$$\sum_{t \in [\tau]} \mathbf{E}_{t-1} \| \mathbf{q}^t - \mathbf{p}^t \|_1 \le \sum_{t \in [\tau]} (3+L)^{t-1} \cdot \Phi \le (3+L)^{\tau} \cdot \Phi$$

Finally, taking expectations and recalling the definitions of Φ and $\kappa := 3 + L$, we conclude

$$\sum_{t \in [\tau]} \mathbf{E} \| \mathbf{q}^t - \mathbf{p}^t \|_1 \leq \kappa^{\tau} \cdot \sqrt{\frac{9cm\log(2n)}{n}} + \frac{3\tau}{n^c} \,.$$

It now remains to prove Propositions 6.2 and 6.3, which we do in the following subsections.

6.1 Proof of Proposition 6.2

For convenience, we restate the proposition:

Proposition 6.2. For every
$$t \ge 1$$
: $\mathbf{E}_t \| \widehat{\mathbf{p}}^{t+1} - \mathbf{q}^{t+1} \|_1 \le (2+L) \cdot \mathbf{E}_{t-1} \| \mathbf{p}^t - \mathbf{q}^t \|_1$

Proof. Recall by definition that

$$q_j^{t+1} = q_j^t \cdot \left(1 + F_j(\mathbf{q}^t, \mathbf{g}^t)\right)$$

and $\hat{p}_j^{t+1} = p_j^t \cdot \left(1 + F_j(\mathbf{p}^t, \mathbf{g}^t)\right)$

for all $j \in [m]$. For readability we will write $\hat{\mathbf{p}}', \mathbf{p}', \mathbf{q}'$ for $\hat{\mathbf{p}}^{t+1}, \mathbf{p}^{t+1}, \mathbf{q}^{t+1}$, and $\mathbf{p}, \mathbf{q}, \mathbf{g}$ for $\mathbf{p}^t, \mathbf{q}^t, \mathbf{g}^t$, respectively. It follows that

$$\begin{aligned} \mathbf{E}_t \| \widehat{\mathbf{p}}' - \mathbf{q}' \|_1 &= \sum_{j \in [m]} \mathbf{E}_t | p_j - q_j + p_j \cdot F_j(\mathbf{p}, \mathbf{g}) - q_j \cdot F_j(\mathbf{q}, \mathbf{g}) | \\ &\leq \sum_{j \in [m]} \mathbf{E}_t | p_j - q_j | + \mathbf{E}_t | (p_j - q_j) \cdot F_j(\mathbf{p}, \mathbf{g}) | + \mathbf{E}_t | q_j \cdot (F_j(\mathbf{p}, \mathbf{g}) - F_j(\mathbf{q}, \mathbf{g})) | \\ &\leq \mathbf{E}_t \| \mathbf{p} - \mathbf{q} \|_1 + \sum_{j \in [m]} \mathbf{E}_t | p_j - q_j | + q_j \left(L \cdot \mathbf{E}_t \| \mathbf{p} - \mathbf{q} \|_1 \right) \\ &= (2 + L) \cdot \mathbf{E}_t \| \mathbf{p} - \mathbf{q} \|_1 . \end{aligned}$$

Here, the first line follows from two applications of the triangle inequality, and the second line comes from applying the boundedness and L-Lipschitz property of each F_j from Definition 2.2 and part (ii) of Assumption 2.

Finally, because $\mathbf{p}^t = \mathbf{p}$ and $\mathbf{q}^t = \mathbf{q}$ are functions only of $\{\mathbf{p}^{t-1}\}\$ and $\{\mathbf{g}^{t-1}\}\$, it follows that $\mathbf{E}_t \|\mathbf{p} - \mathbf{q}\|_1 = \mathbf{E}_{t-1} \|\mathbf{p} - \mathbf{q}\|$. Thus we conclude that $\mathbf{E}_t \|\mathbf{\hat{p}}' - \mathbf{q}'\|_1 \le (2+L) \cdot \mathbf{E}_{t-1} \|\mathbf{p} - \mathbf{q}\|_1$. \Box

6.2 Proof of Proposition 6.3

For convenience, we restate the proposition:

Proposition 6.3. Fix $\tau \ge 1$ and $c \ge 1$. For $n \ge 3c \log n$, it holds for all $t \in [\tau]$ simultaneously that

$$\begin{array}{ll} (i) \quad \left| p_j^t - \hat{p}_j^t \right| \; \leq \; \sqrt{\frac{3c \log n}{n}} & \text{for any fixed } j \in [m] \;, \\ \\ and \quad (ii) \quad \left\| \mathbf{p}^t - \widehat{\mathbf{p}}^t \right\|_1 \; \leq \; \sqrt{\frac{9m \cdot c \log(2n)}{n}} \;, \end{array}$$

with probability at least $1 - \frac{3\tau}{n^c}$.

Proof. We start by proving claim (i). Using a standard multiplicative Chernoff bound [MU05, Corollary 4.6], we have for each $j \in [m]$ and $t \in [\tau]$ that

$$\mathbf{Pr}_{t-1}\left(\left|p_j^t - \mathbf{E}_{t-1}[p_j^t]\right| \ge \mathbf{E}_{t-1}[p_j^t] \cdot \delta\right) \le 2 \cdot \exp\left(-\frac{n}{3} \cdot \mathbf{E}_{t-1}[p_j^t] \cdot \delta^2\right),$$

for any $0 < \delta \le 1$. Fix $c \ge 1$, and consider the case when $\sqrt{\frac{3c \log n}{n}} \le \mathbf{E}_{t-1}[p_j^t] \le 1$. Then setting $\delta = \frac{1}{\mathbf{E}_{t-1}[p_j^t]} \cdot \sqrt{\frac{3c \log n}{n}} \le 1$ implies

$$\mathbf{Pr}_{t-1}\left(\left|p_j^t - \mathbf{E}_{t-1}[p_j^t]\right| \ge \sqrt{\frac{3c\log n}{n}}\right) \le 2 \cdot \exp\left(\frac{-c\log n}{\mathbf{E}_{t-1}[p_j^t]}\right) \le \frac{2}{n^c}.$$

On the other hand, when $0 \leq \mathbf{E}_{t-1}[p_j^t] < \sqrt{\frac{3c \log n}{n}}$, setting $\delta = 1$ implies

$$\mathbf{Pr}_{t-1}\left(\left|p_j^t - \mathbf{E}_{t-1}[p_j^t]\right| \ge \sqrt{\frac{3c\log n}{n}}\right) \le 2 \cdot \exp\left(-\frac{1}{3} \cdot \sqrt{3cn\log n}\right) \le \frac{2}{n^c},$$

where the final inequality holds for all $n \ge 3c \log n$. Summing over all τ rounds and taking a union bound proves that statement (i) of the proposition holds with probability at least $1 - 2\tau/n^c$.

To prove statement (ii), one approach would be to simply take a union bound over all m coordinates, which would result in a linear dependence on m. However, recall that each \mathbf{p}^t is a discrete *m*-dimensional distribution, and $\hat{\mathbf{p}}^t$ is by definition the empirical average of n i.i.d. samples from \mathbf{p}^t . Thus to bound each $\|\mathbf{p}^t - \hat{\mathbf{p}}^t\|$, we use a standard tool from discrete distribution learning (e.g., of Cannone [Can20, Theorem 1]), which states:

$$\mathbf{Pr}_{t-1}\left[\|\mathbf{p}^t - \widehat{\mathbf{p}}^t\|_1 > 2\epsilon + \sqrt{\frac{m}{n}}\right] \leq \frac{1}{n^c}$$

so long as $n \ge \max\left\{\frac{m}{\epsilon^2}, \frac{2c}{\epsilon^2}\log(2n)\right\}$. Then setting $\epsilon := \sqrt{\frac{mc\log n}{n}}$ ensures that for $n \ge 3c\log n$, each $\|\mathbf{p}^t - \widehat{\mathbf{p}}^t\|_1 \le 3\sqrt{\frac{mc\log(2n)}{n}}$ with probability at least $1 - 1/n^c$. Then taking a union bound over all τ rounds means the claim holds simultaneously for all $t \in [\tau]$ with probability at least $1 - \tau/n^c$.

Finally, taking a union bound over claims (i) and (ii) of the proposition ensures both claims hold simultaneously with probability at least $1 - 3\tau/n^c$.

7 Proof of Regret and Consensus for Stationary Rewards

In this section we develop the proof of our main results, Theorem 2.8 and Theorem 2.9, which we restate here:

Theorem 2.8. Let R(T) be the regret of the β -adopt protocol in the stationary reward setting with $\beta := \min(1/4, 1/\sigma)$. Then assuming $m = o(\log^{1.5} n)$ and n sufficiently large: $R(T) \leq O(\sigma \log m + \log^3 n)$.

Theorem 2.9. Consider the β -adopt protocol in the stationary reward setting of Theorem 2.8. Then $p_1^t = 1$ for all rounds $t \ge 2\sqrt{n}\log^3 n$ simultaneously with probability at least $1 - O(1/\log n)$, and for all rounds $t \ge n\log^2 n$ simultaneously with probability at least $1 - O(n^{-1/2})$.

As introduced in Section 2.3, the proof of these results relies on decomposing the T rounds into three distinct phases and bounding each of their individual regrets. Before reviewing the exact setup of the phases, in order to streamline the development of the proof, we summarize the setting and assumptions of Theorem 2.8 and Theorem 2.9 in the following assumption:

Assumption 3. Consider the sequence $\{\mathbf{p}^t\}$ from Definition 2.3 generated by the β -adopt protocol with a stationary reward sequence $\{\mathbf{g}^t\}$. Assume $\mathbf{p}^1 = \mathbf{1}/m$ deterministically. As in Assumption 1, assume that each $\mathbf{g}^t \in [0, \sigma]^m$ has mean $\boldsymbol{\mu} := (\mu_1, \ldots, \mu_m)$, where all μ_j and $\sigma \ge 1$ are asbolute constants. Without loss of generality assume $0 \le \mu_m \le \cdots \le \mu_2 < \mu_1 \le 1$. Moreover, assume $\beta \in (0, \min(1/4, 1/\sigma)]$ is an absolute constant, meaning by Proposition 2.5 that the family $\{F_j\}$ induced by the β -adopt protocol satisfies Assumption 2 with parameters $\alpha = 2\beta$, $\delta = 0$, and L = 2. Finally, assume that $m = o(\log^{1.5} n)$.

Recap of phase structure and overview of proof: We now review the overview of the proof of Theorem 2.8 (and as a byproduct, the proof of Theorem 2.9) and the structure of the three phases introduced in Section 2.3. Specifically, recall that we define $T_{phase-1} := \sqrt{n} \cdot \frac{\log m}{\sqrt{m \log n}}$ and

 $T_{\mathsf{phase-2}} := 2\sqrt{n} \cdot \log^3 n$, and we define

$$\begin{split} R_{\mathsf{phase-1}} &:= \sum_{t=1}^{\min(T_{\mathsf{phase-1}},T)} \mu_1 - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle] ,\\ R_{\mathsf{phase-2}} &:= \sum_{t=T_{\mathsf{phase-1}}}^{\min(T_{\mathsf{phase-2}},T)} \mu_1 - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle] \text{ if } T \geq T_{\mathsf{phase-1}}, \text{ and } 0 \text{ otherwise},\\ R_{\mathsf{phase-3}} &:= \sum_{t=T_{\mathsf{phase-2}}}^{T} \mu_1 - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle] \text{ if } T \geq T_{\mathsf{phase-2}}, \text{ and } 0 \text{ otherwise}, \end{split}$$

which means that $R(T) = R_{\text{phase-1}} + R_{\text{phase-2}} + R_{\text{phase-3}}$. We also introduce the two times τ_{bounded} and $\tau_{\text{consensus}}$ defined as follows:

$$\tau_{\text{bounded}} := \min\left\{n^2, \min\left\{t \in [T] : p_1^t > 1 - \frac{\log^2 n}{\sqrt{n}}\right\}\right\}$$
(13)

$$\tau_{\text{consensus}} := \min\left\{n^2, \min\left\{t \in [T] : p_1^t = 1\right\}\right\}.$$
(14)

In other words:

- τ_{bounded} is the first round t such that the mass p_1^t is bounded below by $1 \widetilde{O}(1/\sqrt{n})$ for every subsequent round $\tau_{\text{bounded}} \leq t \leq n^2$
- $\tau_{\text{consensus}}$ is the first round such that $p^t = 1$ (meaning the population reaches and remains in consensus on the highest-mean action) for every subsequent round $\tau_{\text{consensus}} \leq t \leq T$.

Note that the "double minimum" in the definition of τ_{bounded} and $\tau_{\text{consensus}}$ is to ensure these two random variables are well-defined in the (provably low-probability) event that the inner-most set is empty. Given these definitions, the proofs of Theorem 2.8 and Theorem 2.9 then rely on the following sequence of intermediate lemmas:

- Phase 1 Lemma 7.2: we prove $R_{phase-1} \leq O(\sigma \log m)$ by applying the τ -step regret bound of Proposition 2.7 over a sequence of D epochs, where $D \approx T_{phase-1}$.
- Phase 2 Lemma 7.3: we prove $R_{phase-2} \leq O(\log^5 n)$ by showing first that, with high probability, $\tau_{bounded} \leq T_{phase-1}$. This implies that the per-round regret for each round $T_{phase-1} \leq t \leq T_{phase-2}$ is at most $O(\log^2 n)$.
- Phase 3 Lemma 7.4: we prove $R_{phase-3} \leq o(1)$ by first establishing in Lemma 7.5 that $\tau_{consensus} \leq T_{phase-2}$ with probability at least $1 O(1/\log n)$. In other words, the population reaches and remains in consensus on the highest-mean action within $T_{phase-2} \leq O(n \log^3 n)$ rounds with this same probability. As a consequence, we can guarantee that the cumulative regret $R_{phase-3}$ over all subsequent rounds $t \geq T_{phase-2}$ is at most $O(1/\log n)$.
- High probability consensus via Lemma 7.5: Moreover, the proof of Lemma 7.5 allows us to further show that $\tau_{\text{consensus}} \leq O(n \log^2 n)$ with probability at least $1 - O(n^{-1/2})$. This establishes the proof of Theorem 2.9 and boosts the bound on the number of rounds until consensus to a high-probability result (i.e., with probability at least $1 - 1/n^{\Omega(1)}$).
- Core tool: sufficient growth of p_1^t Lemma 7.1: The core tool used in each of the previous intermediate results is Lemma 7.1, where we establish probabilistic guarantees on the growth of the best action's mass p_1^t over time. In particular, this allows us to establish the tightest possible regret guarantees for $R_{phase-1}$ in Lemma 7.2, and to establish the probabilistic claims that $\tau_{pounded} \leq T_{phase-1}$ and $\tau_{consensus} \leq T_{phase-2}$ used in phases 2 and 3 respectively.

Given this overview, we begin by proving the sufficient growth guarantees of Lemma 7.1, and we develop the proofs of the remaining intermediate lemmas in the subsequent subsections.

7.1 Sufficient Growth of p_1^t

Lemma 7.1. Consider the setting of Assumption 3. Then the following statements hold simultaneously with probability at least 1 - 3/n for sufficiently large n:

(i) for all
$$t \in [n]$$
: $p_1^{t+1} \ge \min\left\{p_1^t, 1 - \frac{\log^2 n}{\sqrt{n}}\right\}$
(ii) for all $t \in [\tau_{\text{bounded}}]$: $p_1^{t+1} \ge \frac{1}{2m}\left(1 + \frac{\beta(\mu_1 - \mu_2) \cdot \log^2 n}{\sqrt{n}}\right)^t$
(iii) $\tau_{\text{bounded}} \le \frac{3}{\beta(\mu_1 - \mu_2)} \cdot \frac{\sqrt{n}\log m}{\log^2 n}$.

Proof. Based on the settings of Assumption 3, we have that the β -adopt protocol satisfies Assumption 2 with parameters $\alpha := 2\beta$ and $\delta = 0$. It follows that in the stationary reward setting, we have in conditional expectation that

$$\mathbf{E}_{\mathbf{p}^{t}}[p_{1}^{t+1}] \geq p_{1}^{t} \left(1 + \frac{\alpha}{2}(\mu_{1} - \langle \mathbf{p}^{t}, \boldsymbol{\mu} \rangle)\right) \geq p_{1}^{t} \left(1 + \beta(\mu_{1} - \mu_{2}) \cdot (1 - p_{1}^{t})\right).$$

For readability, let $\gamma := \beta(\mu_1 - \mu_2)$. Now by statement (i) of Proposition 6.3, we have with probability at least $1 - 3n^2/n^3 = 1 - 3/n$ simultaneously for all $t \in [n]$ that $p_1^{t+1} \ge \mathbf{E}_{\mathbf{p}^t}[p^{t+1}] - \sqrt{\frac{9\log n}{n}}$. We can therefore write:

$$p_1^{t+1} \geq p_1^t \left(1 + \gamma \cdot (1 - p_1^t)\right) - \sqrt{\frac{9\log n}{n}} = p_1^t + \gamma \cdot p_1^t (1 - p_1^t) - \sqrt{\frac{9\log n}{n}} .$$
 (15)

We now start by proving part (i) of the lemma. For this, observe that the right hand side of (15) is concave and increasing in p_1^t . Thus suppose $p_1^t = 1 - ((\log^2 n)/\sqrt{n})$ and that the right hand side of (15) is at least $1 - ((\log^2 n)/\sqrt{n})$ (which means p_1^{t+1} is also at least this large). Then this implies that $p_1^{t+1} \ge 1 - ((\log^2 n)/\sqrt{n})$ when initially $p_1^t > 1 - ((\log^2 n)/\sqrt{n})$. Thus to prove part (i) of the lemma, it suffices to check that $p_1^{t+1} \ge p_1^t$ when $1/m \le p_1^t \le 1 - ((\log^2 n)/\sqrt{n})$. For this, observe by the concavity of $p_1^t(1-p_1^t)$ and the constraints on p_1^t that

$$\gamma \cdot p_1^t (1 - p_1^t) - \sqrt{\frac{9\log n}{n}} \ge \gamma \cdot \left(\frac{\log^2 n}{\sqrt{n}} - \frac{4\log^2 n}{n}\right) - \sqrt{\frac{9c\log n}{n}} \ge \gamma \cdot \frac{\log^2 n}{2\sqrt{n}}$$

for sufficiently large n. Substituting this back into equation (15) and using the fact that $\gamma > 0$ yields $p_1^{t+1} \ge p_1^t$, which finishes the proof for part (i) of the lemma.

To prove part (ii), recall by definition of τ_{bounded} that $p_1^t \leq 1 - \frac{\log^2 n}{\sqrt{n}}$ for all $t \in [\tau_{\text{bounded}}]$. Then reusing the calculation from expression (15), we have

$$p_1^{t+1} \ge p_1^t \left(1 + \gamma \cdot \frac{\log^2 n}{\sqrt{n}}\right) - \sqrt{\frac{9\log n}{n}}$$

$$\tag{16}$$

for all $t \in [\tau_{\text{bounded}}]$ with probability at least 1 - 3/n. Now for readability let $\lambda := \gamma(\log^2 n)/\sqrt{n}$,

and let $\Phi := \sqrt{(9 \log n)/n}$, and recall that $p_1^0 = 1/m$. Then unrolling the recurrence in (16), we find

$$p_1^{t+1} \geq \frac{1}{m} (1+\lambda)^t - \Phi \cdot \left(\sum_{i=0}^{t-1} (1+\lambda)^i\right)$$

= $\frac{1}{m} (1+\lambda)^t - \Phi \cdot \left(\frac{(1+\lambda)^t - 1}{\lambda}\right)$
 $\geq \frac{1}{m} (1+\lambda)^t - \Phi \cdot \left(\frac{(1+\lambda)^t}{\lambda}\right) = (1+\lambda)^t \cdot \left(\frac{1}{m} - \frac{\Phi}{\lambda}\right),$

where in the second line we apply the definition of a finite geometric series. Moreover, we have $\Phi/\lambda = 3/(\gamma \log^{1.5} n) \le 1/(2m)$, where the inequality holds when $m = o(\log^{1.5} n)$. Then together with the definitions of γ and λ , we have for all $t \in [\tau_{\text{bounded}}]$ that

$$p^{t+1} \geq \frac{1}{2m} \left(1 + \gamma \cdot \frac{\log^2 n}{\sqrt{n}} \right)^t, \tag{17}$$

which proves part (ii) of the lemma.

To prove part (iii), we use the lower bound in equation (17) and the fact that $1 + x \ge e^{x/2}$ for all $x \in (0, 1)$ to write

$$p^{\tau_{\text{bounded}}} \geq \frac{1}{2m} \cdot \exp\left((\tau_{\text{bounded}} - 1) \cdot \frac{\gamma \log^2 n}{\sqrt{n}}\right)$$

Then it follows that

$$\tau_{\mathsf{bounded}} = \frac{\sqrt{n}}{\gamma \log^2 n} \cdot \log\left(2m\left(1 - \frac{\log^2 n}{\sqrt{n}}\right)\right) + 1 \le \frac{3}{\beta(\mu_1 - \mu_2)} \cdot \frac{\sqrt{n}\log m}{\log^2 n}$$

is sufficient to ensure that $p^{\tau_{\text{bounded}}+1} \ge 1 - ((\log^2 n)/\sqrt{n})$ with probability at least 1 - 3/n. This proves part (iii) of the lemma.

7.2 Phase 1 Regret

We now derive the following bound on the phase 1 regret $R_{phase-1}$:

Lemma 7.2. Consider the setting of Assumption 3. Then $R_{phase-1} \leq O(\sigma \log m)$.

As mentioned in the overview, the proof of this lemma uses the τ -step regret bound of Proposition 2.7, which we restate here for reference:

Proposition 2.7. Let $R(\tau)$ be the regret of the sequence $\{\mathbf{p}^t\}$ induced by a local protocol \mathcal{P} that satisfies Assumption 2 with parameters α , δ and L. Let $\kappa := 3 + L$, fix $c \geq 1$, and consider n sufficiently large. Let $\widetilde{R}(\tau)$ be the regret of the corresponding zero-sum MWU process $\{\mathbf{q}^t\}$. Then $R(\tau) \leq \widetilde{R}(\tau) + O(\sigma \kappa^{\tau} \cdot \sqrt{\frac{mc \log n}{n}} + \frac{\sigma \tau}{n^c}).$

Observe that the second term in the bound above (stemming from Lemma 6.1) can in the worst case grow exponentially with τ . To obtain sharper bounds, for large values of τ , we can run multiple "epochs" of the coupling (similar to the analysis of Celis et al. [CKV17]) where at the start of each epoch, the process $\{\mathbf{q}^t\}$ is reinitialized to the most recent \mathbf{p}^t .

Proof. Recall that we define $R_{\mathsf{phase-1}} := \sum_{t=1}^{\min(T_{\mathsf{phase-1}},T)} \mu_1 - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle]$ where $T_{\mathsf{phase-1}} := \sqrt{n} \cdot \frac{\log m}{\sqrt{m \log n}}$. For readability, let $\widehat{T} := \min(T_{\mathsf{phase-1}},T)$. By Proposition 2.4, observe that we can write

$$R_{\mathsf{phase-1}} \leq \sum_{t \in [\widehat{T}]} \mu_1 - \mathbf{E}[\langle \mathbf{q}^t, \mathbf{g}^t \rangle] + \sigma \sum_{t \in [\widehat{T}]} \mathbf{E} \|\mathbf{q}^t - \mathbf{p}^t\|_1 := \widehat{R}_{\mathsf{phase-1}}$$

To bound the quantity $\widehat{R}_{phase-1}$, we will repeatedly apply the general τ -step regret bound of Proposition 2.7 over a sequence of D epochs. In particular, we assume each epoch $d \in [D]$ consists of τ rounds with the following properties:

- (i) Let $D = \widehat{T}/\tau$. For each $d \in [D]$, let epoch \mathcal{E}_d be the set of rounds $\mathcal{E}_d := \{d\tau, \ldots, (d+1)\tau 1\}$.
- (ii) Set $\mathbf{p}^0 = \mathbf{q}^0 = \mathbf{1} \cdot \frac{1}{m}$.
- (iii) For $d \ge 1$, set $\mathbf{q}^{d\tau} = \mathbf{p}^{d\tau}$.
- (iv) Then in each epoch, run the coupling as in Definition 2.3 for τ rounds, until \hat{T} total rounds have passed.

In other words, at the start of each epoch, the trajectory of \mathbf{q}^t is initialized at the most recent point \mathbf{p}^t from the end of the previous epoch. This allows for a tighter coupling of $\{\mathbf{q}^t\}$ and $\{\mathbf{p}^t\}$ over all T rounds, as we can guarantee that the trajectories stay closer when the number of rounds τ is smaller than T. Note that these epochs are defined purely for obtaining sharper regret bounds for the sequence $\{\mathbf{p}^t\}$, and that this sequence $\{\mathbf{p}^t\}$ is never restarted.

Using the general τ -step regret bound from Proposition 2.7), we can then bound the overall regret $\hat{R}_{phase-1}$ by the sum of (the upper bounds on) the regret of each epoch. In particular, we define for each $d \in [D]$

$$\widehat{R}(\mathcal{E}_d) = \sum_{t \in \mathcal{E}_d} \mu_1 - \mathbf{E}[\langle \mathbf{q}^t, \mathbf{g}^t \rangle] + \sum_{t \in \mathcal{E}_d} \sigma \mathbf{E} \| \mathbf{q}^t - \mathbf{p}^t \|_1,$$

meaning that $R_{\text{phase-1}} \leq \widehat{R}_{\text{phase-1}} = \sum_{d \in [D]} \widehat{R}(\mathcal{E}_d)$. Now recall from Lemma 7.1 that

$$p_1^{t+1} \geq \frac{1}{2m} \Big(1 + \frac{\beta(\mu_1 - \mu_2) \cdot \log^2 n}{\sqrt{n}} \Big)^t$$

simultaneously for all $t \in [T_{phase-1}]$ with probability at least 1 - 3/n. Thus applying the τ -step regret bound of Proposition 2.7 to each $\widehat{R}(\mathcal{E}_d)$ (and given the setting of Assumption 3 and value of $T_{phase-1}$), it follows that

$$\sum_{d\in[D]} \widehat{R}(\mathcal{E}_d) \leq O\left(\frac{1}{\beta} \sum_{d\in[D]} \log\left(1/p_1^{d\tau}\right)\right) + O\left(D\sigma\kappa^{\tau}\sqrt{\frac{2m\log n}{n}} + \frac{1}{n}\right)$$
$$= O\left(\sum_{d\in[D]} \log(2m) - \sum_{d\in[D]} \log\left(1 + \frac{\log^2 n}{\sqrt{n}}\right)^{\tau d}\right) + O\left(D\sigma\kappa^{\tau}\sqrt{\frac{2m\log n}{n}} + \frac{1}{n}\right)$$
$$\leq O\left(D\log(2m) - \tau D^2\log\left(1 + \frac{\log^2 n}{\sqrt{n}}\right)\right) + O\left(D\sigma\kappa^{\tau}\sqrt{\frac{2m\log n}{n}} + \frac{1}{n}\right).$$
(18)

We now set $\tau = \Theta(1)$, which means $D \leq \widehat{T} \leq T_{\mathsf{phase-1}} = \sqrt{n} \cdot \frac{\log m}{\sqrt{m \log n}}$. It follows that, for sufficiently large n, the first term of expression (18) is at most $O(\log m)$, and the second term is at most $O(\sigma \log m + 1/n) \leq O(\log m)$. Thus $R_{\mathsf{phase-1}} \leq \widehat{R}_{\mathsf{phase-1}} = \sum_{d \in [D]} \widehat{R}(\mathcal{E}_d) \leq O(\sigma \log m)$, which concludes the proof.

7.3 Phase 2 Regret

Using the probabilistic guarantees of Lemma 7.1, we show in the folloing lemma that $\tau_{\text{bounded}} \leq T_{\text{phase-1}}$, which implies a bound on $R_{\text{phase-2}}$:

Lemma 7.3. Consider the setting of Assumption 3. Then $\tau_{\text{bounded}} \leq T_{\text{phase-1}}$ with probability at least 1 - O(1/n). Moreover, $R_{\text{phase-2}} \leq O(\log^5 n)$.

Proof. Assuming that $T \ge T_{phase-1}$, recall that $R_{phase-2} := \sum_{t=T_{phase-1}}^{\min(T_{phase-2},T)} \mu_1 - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle]$, where $T_{phase-2} := 2\sqrt{n} \cdot \log^3 n$. To derive an upper bound on $R_{phase-2}$, observe that for each t, we have

$$\mu_1 - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle] \le (\mu_1 - \mu_2) \cdot \mathbf{E}[(1 - p_1^t)], \qquad (19)$$

which follows by the fact that the randomness in \mathbf{g}^t is independent from that of \mathbf{p}^t , and from the stationary reward setting structure of Assumption 3.

Now recall from Lemma 7.1 that simultaneously with probability at least 1 - 3/n:

$$\tau_{\text{bounded}} \leq \frac{3}{\beta(\mu_1 - \mu_2)} \cdot \frac{\sqrt{n}\log m}{\log^2 n} \quad \text{and} \quad p_1^t \geq 1 - \frac{\log^2 n}{\sqrt{n}} \quad \text{for all } \tau_{\text{bounded}} \leq t \leq n$$

Observe further that by definition of $T_{phase-1}$,

$$au_{\mathsf{bounded}} \leq \frac{3}{eta(\mu_1 - \mu_2)} \cdot \frac{\sqrt{n}\log m}{\log^2 n} \leq \sqrt{n} \cdot \frac{\log m}{\sqrt{m\log n}} = T_{\mathsf{phase-1}}$$

so long as $m \leq \frac{\beta(\mu_1 - \mu_2) \log^3 n}{3}$, which holds under the stronger assumption that $m = o(\log^{1.5} n)$. Thus $\tau_{\text{bounded}} \leq T_{\text{phase-1}}$ with probability at least 1 - 3/n, which proves the first statement of the lemma.

To prove the second statement, observe that the first statement and the result of Lemma 7.1 together imply that $p_1^t \ge 1 - (\log^2 n) / \sqrt{n}$ simultaneously for all $T_{phase-1} \le t \le T_{phase-2}$ with probability at least 1 - O(1/n). Moreover, observe by definition of $T_{phase-1}$ and $T_{phase-2}$ that

$$\min(T_{\mathsf{phase-2}}, T) - T_{\mathsf{phase-1}} \leq T_{\mathsf{phase-2}} - T_{\mathsf{phase-1}} = 2\sqrt{n} \cdot \log^3 n - \sqrt{n} \cdot \frac{\log m}{\sqrt{m \log n}} \leq \sqrt{n} \cdot \log^3 n + \frac{\log m}{\sqrt{m \log n}} \leq \sqrt{m \log n} + \frac{\log m}{\sqrt{m \log n}} \leq \sqrt{m \log n} < \frac{\log m}{\sqrt{m \log n}} \leq \sqrt{m \log n} < \frac{\log m}{\sqrt{m \log n}} < \frac{\log m}{\sqrt{m$$

Based on the bound in expression (19), it then follows that

$$R_{\text{phase-2}} \leq \sum_{t=T_{\text{phase-1}}}^{\min(T_{\text{phase-2}},T)} (\mu_1 - \mu_2) \mathbf{E}[(1 - p_1^t)] \leq O\left(\sqrt{n} \log^3 n \cdot \frac{\log^2 n}{\sqrt{n}} + \frac{3}{n}\right) \leq O\left(\log^5 n\right). \quad \Box$$

7.4 Phase 3 Regret

We now prove the following bound on $R_{phase-3}$:

Lemma 7.4. Consider the setting of Assumption 3. Then $R_{phase-3} \leq O(1/\log n)$.

The proof of this lemma relies on two steps, similar to that of Lemma 7.3. The key first step is to show that $\tau_{\text{consensus}}$ (the first time such that $p_1^t = 1$) occurs before the start of phase 3 with probability at least 1 - o(1). Conditioned on this event, the expected regret in each round $T_{\text{phase-2}} \leq t \leq T$ is 0, and thus $R_{\text{phase-3}} = o(1)$. In particular, we first prove the following lemma:

Lemma 7.5. Consider the setting of Assumption 3. Then $\tau_{\text{consensus}} \leq T_{\text{phase-2}}$ with probability at least $1 - O(1/\log n)$.

The proof of Lemma 7.5 leverages the following result of Lengler [Len20], which bounds the expected hitting time of a real-valued random processed with additive drift:

Theorem 7.6 ([Len20]). Let $\{y^t\}$ be a sequence of non-negative random variables with state space $\{0, \ldots, n\}$. Let $\tau := \min\{t \ge 0 : y^t = n\}$. Suppose there exists $\Delta > 0$ such that $\mathbf{E}_{y^t}[y^{t+1} - y^t] \ge \Delta$ for all $0 \le i < n$. Then $\mathbf{E}[\tau] \le \frac{n - \mathbf{E}[y^0]}{\Delta}$.

Equipped with this result, we now prove Lemma 7.5:

Proof (of Lemma 7.5). We will use the bound on expected hitting times of drift processes from Theorem 7.6 to bound $\tau_{\text{consensus}}$. For this we introduce the following notation:

- Let $c_i^t \in [m]$ denote the action chosen by agent $i \in [n]$ in round $t \in [T]$.
- Let x_i^t denote the number of agents choosing action $j \in [m]$ in round $t \in [T]$.

Clearly, we have $x_j^t := \sum_{i \in [n]} \mathbf{1}\{c_i^t = j\}$ for all $j \in [m]$ and $\sum_{j \in [m]} x_j^t = n$ for every $t \in [T]$. Moreover, by definition of \mathbf{p}^t , we have $p_j^t = (x_j^t/n)$ for all $t \in [T]$ and $j \in [m]$. With this notation, it follows that $\tau_{\mathsf{consensus}}$ (from (14)) can be equivalently written as:

$$\tau_{\text{consensus}} := \min\left\{n^2, \ \min\left\{t \in [T] \colon x_1^t = n\right\}\right\}.$$

We will further write $\tau_{\text{consensus}} = T_{\text{phase-1}} + \hat{\tau}$, where $\hat{\tau}$ is the number of additional rounds after round $T_{\text{phase-1}}$ until $x_1^t = n$. Then recalling that $T_{\text{phase-1}} = \sqrt{n} \cdot \frac{\log m}{\sqrt{m \log n}} \leq \sqrt{n} \cdot \log^3 n$, it suffices to show that $\hat{\tau} \leq \sqrt{n} \cdot \log^3 n$ with probability at least $1 - O(1/\log n)$ in order to prove that $\tau_{\text{consensus}} \leq T_{\text{phase-2}} = 2\sqrt{n} \log^3 n$ with probability at least $1 - O(1/\log n)$.

For this, recall that by combining the results of Lemma 7.1 and Lemma 7.3, we have simultaneously with probability at least 1 - O(1/n) that $\tau_{\text{bounded}} \leq T_{\text{phase-1}}$ and thus $x_1^t \geq n - \sqrt{n} \cdot \log^2 n$ for all $T_{\text{phase-1}} \leq t \leq n$. Conditioned on this event, which we denote by \mathcal{A} , we now compute the expected drift $\mathbf{E}_{\mathcal{A},\mathbf{p}^t}[x_i^{t+1} - x_i^t]$. In particular, we start by additionally conditioning on the reward vector \mathbf{g}^t and write

$$\mathbf{E}_{\mathcal{A},t}[x_i^{t+1}] = \mathbf{E}_{\mathcal{A},t}\left[\sum_{i=1}^n \mathbf{1}\{c_i^{t+1} = 1\}\right] \\
= \mathbf{E}_{\mathcal{A},t}\left[\sum_{i=1}^n \mathbf{1}\{c_i^{t+1} = 1 \text{ and } c_i^t = 1\}\right] + \mathbf{E}_{\mathcal{A},t}\left[\sum_{i=1}^n \mathbf{1}\{c_i^{t+1} = 1 \text{ and } c_i^t \neq 1\}\right].$$
(20)

For the first term of expression (20), recall by the definition of the β -adopt protocol that if an agent chooses action 1 in round t, then in round t + 1 it chooses action 1 with probability 1 if it samples a neighbor that also chose action 1 in round t, and it chooses action 1 with probability $1 - \beta g_j^t$ if it sampled a neighbor that chose action $j \neq 1$ in round t. Thus we can write

$$\mathbf{E}_{\mathcal{A},t} \Big[\sum_{i=1}^{n} \mathbf{1} \{ c_i^{t+1} = 1 \text{ and } c_i^t = 1 \} \Big] = x_1^t \Big(\frac{x_1^t}{n} + \sum_{j \neq 1} \frac{x_j^t}{n} \big(1 - \beta g_j^t \big) \Big) .$$
(21)

For the second term of expression (20), recall again by the definition of the β -adopt protocol that if an agent chooses some other action $j \neq 1$ in round t, then in round t + 1 it chooses action 1 with probability βg_1^t if it samples a neighbor that chose action 1 in round t, and with probability 0 otherwise. This means we can write

$$\mathbf{E}_{\mathcal{A},t} \Big[\sum_{i=1}^{n} \mathbf{1} \{ c_i^{t+1} = 1 \text{ and } c_i^t \neq 1 \} \Big] = (n - x_1^t) \cdot \left(\frac{x_1^t}{n} \cdot \beta g_1^t \right).$$
(22)

Substituting expressions (21) and (22) back into expression (20) and taking expectation over the randomness of \mathbf{g}^t , we then find

$$\mathbf{E}_{\mathcal{A},\mathbf{p}^{t}}[x_{i}^{t+1}] = x_{1}^{t} \left(\frac{x_{1}^{t}}{n} + \sum_{j \neq 1} \frac{x_{j}^{t}}{n} (1 - \beta \mu_{j}) \right) + (n - x_{1}^{t}) \cdot \left(\frac{x_{1}^{t}}{n} \cdot \beta \mu_{1} \right) \\
\geq x_{1}^{t} \left(\frac{x_{1}^{t}}{n} + \left(1 - \frac{x_{1}^{t}}{n} \right) \cdot \left(1 - \beta \mu_{2} \right) \right) + (n - x_{1}^{t}) \cdot \left(\frac{x_{1}^{t}}{n} \cdot \beta \mu_{1} \right),$$
(23)

where the inequality follows from the ordering of the coordinates of μ in Assumption 3. Further simplifying expression (23) then yields

$$\mathbf{E}_{\mathcal{A},\mathbf{p}^t}[x_i^{t+1}] \geq x_1^t + x_1^t \cdot \left(1 - \frac{x_1^t}{n}\right) \cdot \beta(\mu_1 - \mu_2) + \beta(\mu_1 - \mu_2)$$

which means that

$$\mathbf{E}_{\mathcal{A},\mathbf{p}^t}[x_i^{t+1} - x_i^t] \geq x_1^t \cdot \left(1 - \frac{x_1^t}{n}\right) \cdot \beta(\mu_1 - \mu_2) .$$

$$(24)$$

Now conditioned on the event \mathcal{A} , we have that $x_1^t \ge n - 2\log^2 n \cdot \sqrt{n}$ for all $T_{\mathsf{phase-1}} \le t \le n$. Thus by concavity, it follows that while $x_1^t \le n - 1$, we have for all $T_{\mathsf{phase-1}} \le t \le n$ that

$$\mathbf{E}_{\mathcal{A},\mathbf{p}^{t}}[x_{i}^{t+1}-x_{i}^{t}] \geq (n-1)(1/n) \cdot \beta(\mu_{1}-\mu_{2}) = (1-(1/n)) \cdot \beta(\mu_{1}-\mu_{2}) \geq \frac{\beta(\mu_{1}-\mu_{2})}{2},$$

where the final inequality holds with for *n* sufficiently large. Let $\Delta := \frac{\beta(\mu_1 - \mu_2)}{2}$. Then by Theorem 7.6, it follows that

$$\mathbf{E}_{\mathcal{A}}[\hat{\tau}] \leq \frac{n - \mathbf{E}_{\mathcal{A}}[x_1^{T_{\mathsf{phase-1}}}]}{\Delta} \leq \frac{4\sqrt{n} \cdot \log^2 n}{\beta(\mu_1 - \mu_2)} \,.$$
(25)

By Markov's inequality, we further have

$$\mathbf{Pr}_{\mathcal{A}}\left[\widehat{\tau} \ge \sqrt{n} \cdot \log^{3} n\right] \le \frac{\mathbf{E}_{\mathcal{A}}[\widehat{\tau}]}{\sqrt{n} \cdot \log^{3} n} \le O\left(\frac{1}{\log n}\right).$$
(26)

Finally, recalling that the event \mathcal{A} occurs with probability at least O(1/n) we conclude using a union bound that $\hat{\tau} \leq \sqrt{n} \cdot \log^3 n$ (and thus $\tau_{\text{consensus}} \leq T_{\text{phase-2}}$) with total probability at least $1 - O(1/n + 1/\log n) \geq 1 - O(1/\log n)$.

Given Lemma 7.5, we can now prove the bound on $R_{phase-3}$ in Lemma 7.4:

Proof (of Lemma 7.4). Recall that for $T \ge T_{phase-2}$ we define $R_{phase-3} = \sum_{t=T_{phase-2}}^{T} \mu_1 - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle]$. Now by Lemma 7.5, we have with probability $1 - O(1/\log n)$ that $\tau_{consensus} \le T_{phase-2}$. By definition, conditioning on this event, which we denote by \mathcal{B} , means that $p_1^t = 1$ for all $t \ge T_{phase-2}$, and thus $\sum_{t=T_{phase-2}}^{T} \mu_1 - \mathbf{E}_{\mathcal{B}}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle] = 0$. Then taking expectation, it follows that $R_{phase-3} \le \mathbf{Pr}[\mathcal{B}] \le O(1/\log m)$.

7.5 Proof of Theorem 2.8

Using the results of previous subsections, we can now finish the proof of the overall bound on the regret R(T) from Theorem 2.8.

Proof. By Lemmas 7.2, 7.3, and 7.4, we have under the assumptions of the Theorem that $R_{phase-1} \leq O(\sigma \log m)$, $R_{phase-2} \leq O(\log^5 n)$, and $R_{phase-3} \leq o(1)$, respectively. By definition, it follows that

$$R(T) := R_{\text{phase-1}} + R_{\text{phase-2}} + R_{\text{phase-3}} \le O(\sigma \log m + \log^5 n) .$$

7.6 Proof of Theorem 2.9

The proof of Theorem 2.9, which derives a high-probability bound on $\tau_{\text{consensus}}$, comes directly from the proof of Lemma 7.5:

Proof. The first statement of the theorem follows directly from Lemma 7.5. For the second statement, let \mathcal{A} be the event that the statements of Lemma 7.1 hold, and recall that $\mathbf{Pr}[\mathcal{A}] \geq 1 - O(1/n)$. Then from expression (25) in the proof of that Lemma 7.5, we have that $\mathbf{E}_{\mathcal{A}}[\tau_{\mathsf{consensus}}] \leq O(\sqrt{n} \cdot \log^2 n)$. Then by Markov's inequality, it follows that

$$\mathbf{Pr}_{\mathcal{A}}\Big[\tau_{\mathsf{consensus}} \ge n \log^2 n\Big] \le \frac{\mathbf{E}_{\mathcal{A}}[\tau_{\mathsf{consensus}}]}{n \log^2 n} \le O\left(\frac{1}{\sqrt{n}}\right).$$

Taking a union bound implies $\tau_{\text{consensus}} \leq O(n \log^2 n)$ rounds with probability at least $1 - O(1/n + 1/\sqrt{n}) \geq 1 - O(n^{-1/2})$. Finally, note that by definition of the β -adopt protocol, once $p_1^{\tau} = 1$, then $p_1^t = 1$ for all subsequent $t \geq \tau$ with probability 1.

8 Details on Regret Bounds for Adversarial Rewards

In this section, we develop the proof of Theorem 2.10 (restated below), which gives a regret bound for the β -adopt protocol in the general, adversarial reward setting. To start, we formally define the assumptions of the adversarial reward setting:

Assumption 4 (Adversarial Rewards). For each $j \in [m]$, assume for all rounds $t \in [T]$ that $g_j^t \sim \nu_j^t$, where for some $\sigma \ge 1$, ν_j^t has support $[0, \sigma]$ and mean $\mu_j^t := \mathbf{E}[\nu_j] \in [0, 1]$. We assume that each μ_j^t can depend on the distribution \mathbf{p}^t .

Then to restate the claims of Theorem 2.10:

Theorem 2.10. Let R(T) be the regret of the β -adopt protocol running in a general adversarial reward setting with $\beta := \sqrt{(\log m)/T}$. Let $T \leq (0.5 - \epsilon) \log_5 n$ for any $\epsilon \in (0, 0.5)$, and assume $m = o(\log^{1.5} n)$. Then for n sufficiently large: $R(T) \leq O(\sqrt{T \log m})$.

We remark that the main technical barriers in allowing for longer horizons in our analysis stems from the facts that (i) the optimal setting of β has a dependence on $1/\sqrt{T}$ and (ii), we cannot leverage any structure in the reward sequence to establish a sufficient growth condition on the mass of the highest-reward action in \mathbf{p}^t . Thus for larger T, we cannot leverage the epoch-based approach used in the proof of Theorem 2.8, and we resort to using a single application of Proposition 2.7 to obtain the result. Proof (of Theorem 2.10). We will use the T round regret bound from Proposition 2.7. For this, first recall from Proposition 2.5 that the β -adopt protocol induces a zero-sum family $\{\mathcal{F}\}$ that satisfies Assumption 2 with parameters $\alpha = 2\beta$, $\delta = 0$, and L = 2, for $\beta \in (0, \min(1/4, 1/\sigma)]$. Moreover, setting $\beta := \sqrt{(\log m)/T}$ ensures that the constraint on β is satisfied for sufficiently large n.

Then setting $\kappa := 3 + L = 5$ we apply the bound from Proposition 2.7 with c = 1 and $\alpha = 2\beta = \Theta(\sqrt{(\log m)/T})$. This yields

$$R(T) \leq O\left(\frac{\log m}{\beta} + \beta T\right) + O\left(\frac{\sigma \kappa^T \cdot \sqrt{m \log n}}{\sqrt{n}} + \frac{\sigma T}{n^2}\right)$$
$$\leq O\left(\frac{\log m}{\beta} + \beta T\right) + O\left(\frac{\sigma \sqrt{m \log n}}{n^{\epsilon}} + \frac{\sigma T}{n^2}\right).$$
(27)

Here, the final line comes from the assumption that $T \leq (0.5 - \epsilon) \log_{\kappa} n$ for some $\epsilon \in (0, 0.5)$, and thus $\kappa^T/(\sqrt{n}) \leq O(1/n^{\epsilon})$. Moreover, by the bound on T, and assuming $m = o(\log^{1.5} n)$, it follows that the second term in (27) is at most $O(\sqrt{T \log m})$. Finally, using the setting $\beta := \Theta(\sqrt{(\log m)/T})$, the first term in (27) is also bounded by $O(\sqrt{T \log m})$. Thus we conclude $R(T) \leq O(\sqrt{T \log m})$. \Box

8.1 Regret Lower Bound for β -adopt Protocol

In light of the constraint on T in the adversarial regret bound of Theorem 2.10, we prove here that in this adversarial reward setting, the β -adopt algorithm cannot do much better. In particular, we show that there exist reward sequences such that, for $T \ge \Omega(\sqrt{n} \log^3 n)$, $R(T) \ge \Omega(T)$.

Proposition 8.1. Let R(T) be the regret of the β -adopt protocol with $\beta \leq (0, \min(1/4, 1/\sigma) \text{ an absolute constant. Then there exists an adversarial reward sequence such that, for n sufficiently large and <math>T \geq \Omega(\sqrt{n}\log^3 n), R(T) \geq \Omega(T).$

Proof. The proof of the proposition relies on generating a reward sequence such that is stationary for the first $O(\sqrt{n} \log^3 n)$, and then "switches" to an adversarial sequence once \mathbf{p}^t has reached consensus on one coordinate. For simplicity, consider the case where m = 2, and note that the following construction can easily be lifted to any larger n. Let $\tau_1 := 2\sqrt{n} \log^3 n$ (i.e., the same value of $T_{\text{phase-1}}$ from the setup of Theorems 2.8 and 2.9. Deterministically define $\mathbf{g}^t := (1,0)$ for all $0 \le t \le T_{\text{phase-1}}$ and $\mathbf{g}^t := (0,1)$ for all $t > T_{\text{phase-1}}$.

Now observe by Theorem 2.9 that in the stationary reward setting, with probability at least $1 - O(1/\log n)$, the β -adopt protocol reaches best-action consensus within $T_{phase-1}$ rounds. Let \mathcal{A} be the event that this claim holds. Then for all $t > T_{phase-1}$, we must have by construction that $\mathbf{E}_{\mathcal{A}}[g_2^t - \langle \mathbf{p}^t, \mathbf{g}^t \rangle] = 1$. Moreover, for any $T \geq 3\sqrt{n} \log^2 n$ action 2 must have maximal cumulative mean reward, again by construction. It follows that for this range of T we have

$$R(T) = \sum_{t \in [T]} g_2^t - \mathbf{E}[\langle \mathbf{p}^t, \mathbf{g}^t \rangle] \ge (T - T_{\mathsf{phase-1}})(1 - (1/\log n)) \ge \Omega(T) ,$$

which concludes the proof.

References

[AGL⁺17] Dan Alistarh, Demjan Grubic, Jerry Li, Ryota Tomioka, and Milan Vojnovic. Qsgd: Communication-efficient sgd via gradient quantization and encoding. Advances in Neural Information Processing Systems (NeurIPS), 30, 2017.

- [AHK12] Sanjeev Arora, Elad Hazan, and Satyen Kale. The multiplicative weights update method: a meta-algorithm and applications. *Theory Comput.*, 8(1):121–164, 2012.
- [AK08] Baruch Awerbuch and Robert Kleinberg. Online linear optimization and adaptive routing. Journal of Computer and System Sciences, 74(1):97–114, 2008.
- [AL12] David Aldous and Daniel Lanoue. A lecture on the averaging process. *Probability* Surveys, 9:90 – 102, 2012.
- [ALBR19] Mahmoud Assran, Nicolas Loizou, Nicolas Ballas, and Mike Rabbat. Stochastic gradient push for distributed deep learning. In International Conference on Machine Learning (ICML), pages 344–353. PMLR, 2019.
- [Ald13] David Aldous. Interacting particle systems as stochastic social dynamics. *Bernoulli*, 19(4):1122 1149, 2013.
- [AN14] Benjamin Allen and Martin A Nowak. Games on graphs. *EMS Surveys in Mathematical Sciences*, 1(1):113–151, 2014.
- [BB20] Sébastien Bubeck and Thomas Budzinski. Coordination without communication: optimal regret in two players multi-armed bandits. In *Conference on Learning Theory* (*COLT*), pages 916–939. PMLR, 2020.
- [BCB12] Sébastien Bubeck and Nicolo Cesa-Bianchi. Regret analysis of stochastic and nonstochastic multi-armed bandit problems. Foundations and Trends® in Machine Learning, 5(1):1–122, 2012.
- [BCN⁺14] Luca Becchetti, Andrea Clementi, Emanuele Natale, Francesco Pasquale, and Riccardo Silvestri. Plurality consensus in the gossip model. In Proceedings of the twenty-sixth annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 371–390. SIAM, 2014.
- [BCN20] Luca Becchetti, Andrea Clementi, and Emanuele Natale. Consensus dynamics: An overview. ACM SIGACT News, 51(1):58–104, 2020.
- [BCP⁺24] Luca Becchetti, Andrea Clementi, Francesco Pasquale, Luca Trevisan, Robin Vacus, and Isabella Ziccardi. The minority dynamics and the power of synchronicity. In Proceedings of the 2024 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 4155–4176. SIAM, 2024.
- [BGPS06] Stephen Boyd, Arpita Ghosh, Balaji Prabhakar, and Devavrat Shah. Randomized gossip algorithms. *IEEE Transactions on Information Theory*, 52(6):2508–2530, 2006.
- [BGS21] Paul Bastide, George Giakkoupis, and Hayk Saribekyan. Self-stabilizing clock synchronization with 1-bit messages. In *Proceedings of the 2021 ACM-SIAM Symposium* on Discrete Algorithms (SODA), pages 2154–2173. SIAM, 2021.
- [BOM19] Yogev Bar-On and Yishay Mansour. Individual regret in cooperative nonstochastic multi-armed bandits. Advances in Neural Information Processing Systems (NeurIPS), 32, 2019.

- [BP19] Etienne Boursier and Vianney Perchet. Sic-mmab: synchronisation involves communication in multiplayer multi-armed bandits. Advances in Neural Information Processing Systems (NeurIPS), 32, 2019.
- [Cab00] Antonio Cabrales. Stochastic replicator dynamics. International Economic Review, 41(2):451–481, 2000.
- [Can20] Clément L Canonne. A short note on learning discrete distributions. arXiv preprint arXiv:2002.11457, 2020.
- [CBGMM16] Nicol'o Cesa-Bianchi, Claudio Gentile, Yishay Mansour, and Alberto Minora. Delay and cooperation in nonstochastic bandits. In *Conference on Learning Theory (COLT)*, pages 605–622. PMLR, 2016.
- [CBL06] Nicolo Cesa-Bianchi and Gábor Lugosi. *Prediction, learning, and games.* Cambridge University Press, 2006.
- [CKV17] L. Elisa Celis, Peter M. Krafft, and Nisheeth K. Vishnoi. A distributed learning dynamics in social groups. In *PODC*, pages 441–450. ACM, 2017.
- [CLP10a] Flavio Chierichetti, Silvio Lattanzi, and Alessandro Panconesi. Almost tight bounds for rumour spreading with conductance. In *Proceedings of the forty-second ACM* Symposium on Theory of Computing (STOC), pages 399–408, 2010.
- [CLP10b] Flavio Chierichetti, Silvio Lattanzi, and Alessandro Panconesi. Rumour spreading and graph conductance. In Proceedings of the twenty-first annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 1657–1663. SIAM, 2010.
- [DGM⁺11] Benjamin Doerr, Leslie Ann Goldberg, Lorenz Minder, Thomas Sauerwald, and Christian Scheideler. Stabilizing consensus with the power of two choices. In Proceedings of the Twenty-third Annual ACM Symposium on Parallelism in Algorithms and Architectures (SPAA), pages 149–158, 2011.
- [EBB⁺21] Mathieu Even, Raphaël Berthier, Francis R. Bach, Nicolas Flammarion, Hadrien Hendrikx, Pierre Gaillard, Laurent Massoulié, and Adrien B. Taylor. Continuized accelerations of deterministic and stochastic gradient descents, and of gossip algorithms. In Advances in Neural Information Processing Systems (NeurIPS), 2021.
- [EF95] Glenn Ellison and Drew Fudenberg. Word-of-mouth communication and social learning. The Quarterly Journal of Economics, 110(1):93–125, 1995.
- [FPS12] Nikolaos Fountoulakis, Konstantinos Panagiotou, and Thomas Sauerwald. Ultrafast rumor spreading in social networks. In Proceedings of the twenty-third annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 1642–1660. SIAM, 2012.
- [Gia14] George Giakkoupis. Tight bounds for rumor spreading with vertex expansion. In Proceedings of the twenty-fifth annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 801–815. SIAM, 2014.

[GP16] Mohsen Ghaffari and Merav Parter. A polylogarithmic gossip algorithm for plurality consensus. In Proceedings of the 2016 ACM Symposium on Principles of Distributed *Computing (PODC)*, pages 117–126, 2016. [GS12] George Giakkoupis and Thomas Sauerwald. Rumor spreading and vertex expansion. In Proceedings of the twenty-third annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 1623–1641. SIAM, 2012. $[HS^{+}98]$ Josef Hofbauer, Karl Sigmund, et al. Evolutionary games and population dynamics. Cambridge University Press, 1998. Shuyue Hu, Harold Soh, and Georgios Piliouras. The best of both worlds in network [HSP24] population games: Reaching consensus and convergence to equilibrium. Advances in Neural Information Processing Systems (NeurIPS), 36, 2024. [KJG18] Ravi Kumar Kolla, Krishna Jagannathan, and Aditya Gopalan. Collaborative learning of stochastic bandits over a social network. IEEE/ACM Transactions on Networking, 26(4):1782-1795, 2018.[KLSJ19] Anastasia Koloskova, Tao Lin, Sebastian U Stich, and Martin Jaggi. Decentralized deep learning with arbitrary communication compression. In International Conference on Learning Representations (ICLR), 2019. [KSJ19] Anastasia Koloskova, Sebastian U. Stich, and Martin Jaggi. Decentralized stochastic optimization and gossip algorithms with compressed communication. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, Proceedings of the 36th International Conference on Machine Learning (ICML), volume 97 of Proceedings of Machine Learning Research, pages 3478–3487. PMLR, 2019. $[KZP^+16]$ Peter M Krafft, Julia Zheng, Wei Pan, Nicolás Della Penna, Yaniv Altshuler, Erez Shmueli, Joshua B Tenenbaum, and Alex Pentland. Human collective intelligence as distributed bayesian inference. arXiv preprint arXiv:1608.01987, 2016. [Len20] Johannes Lengler. Drift analysis. Theory of evolutionary computation: Recent developments in discrete optimization, pages 89–131, 2020. [Lin92] Nathan Linial. Locality in distributed graph algorithms. SIAM Journal on computing, 21(1):193-201, 1992.[LS20] Tor Lattimore and Csaba Szepesvári. Bandit Algorithms. Cambridge University Press, 2020.[LSL16] Peter Landgren, Vaibhav Srivastava, and Naomi Ehrich Leonard. Distributed cooperative decision-making in multiarmed bandits: Frequentist and bayesian algorithms. In 2016 IEEE 55th Conference on Decision and Control (CDC), pages 167–172. IEEE, 2016. $[LZZ^{+}17]$ Xiangru Lian, Ce Zhang, Huan Zhang, Cho-Jui Hsieh, Wei Zhang, and Ji Liu. Can decentralized algorithms outperform centralized algorithms? a case study for decentralized parallel stochastic gradient descent. Advances in Neural Information Processing Systems NeurIPS, 30, 2017.

- [Mit01] Michael Mitzenmacher. The power of two choices in randomized load balancing. *IEEE Transactions on Parallel and Distributed Systems*, 12(10):1094–1104, 2001.
- [MMM18] Frederik Mallmann-Trenn, Cameron Musco, and Christopher Musco. Eigenvector computation and community detection in asynchronous gossip models. In Ioannis Chatzigiannakis, Christos Kaklamanis, Dániel Marx, and Donald Sannella, editors, 45th International Colloquium on Automata, Languages, and Programming (ICALP), volume 107 of LIPIcs, pages 159:1–159:14. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2018.
- [MRKR19] David Martínez-Rubio, Varun Kanade, and Patrick Rebeschini. Decentralized cooperative stochastic bandits. Advances in Neural Information Processing Systems (NeurIPS), 32, 2019.
- [MU05] Michael Mitzenmacher and Eli Upfal. Probability and Computing: Randomized Algorithms and Probabilistic Analysis. Cambridge University Press, 2005.
- [PSV16] Ioannis Panageas, Piyush Srivastava, and Nisheeth K Vishnoi. Evolutionary dynamics in finite populations mix rapidly. In Proceedings of the twenty-seventh annual ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 480–497. SIAM, 2016.
- [PV16] Ioannis Panageas and Nisheeth K Vishnoi. Mixing time of markov chains, dynamical systems and evolution. In 43rd International Colloquium on Automata, Languages, and Programming (ICALP 2016). Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik, 2016.
- $[S^+09]$ Devavrat Shah et al. Gossip algorithms. Foundations and Trends® in Networking, 3(1):1-125, 2009.
- [San10] William H Sandholm. Population games and evolutionary dynamics. MIT press, 2010.
- [SBFH⁺13] Balazs Szorenyi, Róbert Busa-Fekete, István Hegedus, Róbert Ormándi, Márk Jelasity, and Balázs Kégl. Gossip-based distributed stochastic bandit algorithms. In International Conference on Machine Learning (ICML), pages 19–27. PMLR, 2013.
- [SCS19] Laura Schmid, Krishnendu Chatterjee, and Stefan Schmid. The evolutionary price of anarchy: Locally bounded agents in a dynamic virus game. In 23rd International Conference on Principles of Distributed Systems (OPODIS 2019), volume 153, page 21. Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik, 2019.
- [SGS19] Abishek Sankararaman, Ayalvadi Ganesh, and Sanjay Shakkottai. Social learning in multi agent multi armed bandits. Proc. ACM Meas. Anal. Comput. Syst., 3(3):53:1– 53:35, 2019.
- [SS83] Peter Schuster and Karl Sigmund. Replicator dynamics. *Journal of Theoretical Biology*, 100(3):533–538, 1983.
- [SZL19] Lili Su, Martin Zubeldia, and Nancy A. Lynch. Collaboratively learning the best option on graphs, using bounded local memory. Proc. ACM Meas. Anal. Comput. Syst., 3(1):11:1–11:32, 2019.