P has polynomial-time finite-state verifiers*

M. Utkan Gezer[†] utkan.gezer@bogazici.edu.tr

A. C. Cem Say say@bogazici.edu.tr

Department of Computer Engineering, Boğazici University, Bebek 34342, İstanbul, Türkiye

Abstract

Interactive proof systems whose verifiers are constant-space machines have interesting features that do not have counterparts in the better studied case where the verifiers operate under reasonably large space bounds. The language verification power of finite-state verifiers is known to be sensitive to the difference between private and public randomization. These machines also lack the capability of imposing worst-case superlinear bounds on their own runtime, and long interactions with untrustable provers can involve the risk of being fooled to loop forever. We analyze such verifiers under different bounds on the numbers of private and public random bits that they are allowed to use. This separate accounting for the private and public coin budgets as resource functions of the input length provides interesting characterizations of the collections of the associated languages. When the randomness bound is constant, the verifiable class is NL for private-coin machines, but equals just the regular languages when one uses public coins. Increasing the public coin budget while keeping the number of private coins constant augments the power: We show that the set of languages that are verifiable by such machines in expected polynomial time (with an arbitrarily small positive probability of looping) equals the complexity class P. This hints that allowing a minuscule probability of looping may add significant power to polynomial-time finite-state automata, since it is still not known whether those machines can verify all of P when required to halt with probability 1, even with no bound on their private coin usage. We also show that logarithmic-space machines which hide a constant number of their coins are limited to verifying the languages in P.

Keywords: interactive proof systems, probabilistic finite automata, multihead finite automata, alternating finite automata

1 Introduction

In addition to providing a new perspective on the age-old concept of "proof" and offering possibilities for weak clients to check the correctness of difficult computations that they delegate to powerful servers, interactive proof systems also play an important role in the characterization of computational complexity classes [14, 15, 20]. These systems involve a computationally weak "verifier" (a probabilistic Turing machine with small resource bounds) engaging in a dialogue with a strong but possibly malicious "prover", whose aim is to convince the verifier that a common input string is a member of the language under consideration. If the input is a non-member, the prover may well "lie" during this exchange to mislead the verifier to acceptance, or to trick it into running forever instead of rejecting. Interestingly, this setup allows the weak machines to be able to verify (that

^{*}This research was partially supported by Boğaziçi University Research Fund Grant Number 19441. An earlier version of this paper [10] was presented in the 24th Italian Conference on Theoretical Computer Science, Palermo, Italy, September 13–15, 2023. This is a substantially extended version.

[†]Utkan Gezer's participation in this work is supported by the Turkish Directorate of Strategy and Budget under the TAM Project number 2007K12-873.

is, to determine the membership status of any given string with low probability of being fooled) a larger class of languages than they can manage to handle in a "stand-alone" fashion, *i.e.*, without engaging with a prover.

Several specializations of the basic model described above have been studied until now. One parameter is whether the prover can "see" the outcomes of the random choices made by the verifier or not. A "private-coin" system hides the results of the verifier's coin flips from the prover, and the verifier only sends information that it deems necessary through the communication channel. "Publiccoin" systems, on the other hand, hide nothing from the prover, who can be assumed to observe the coin flips and deduce the resulting changes to the configuration of the verifier as they unfold. It is known [7] that private-coin systems are more powerful (*i.e.*, can verify more languages) than public-coin ones when the verifiers are restricted to be constant-space machines, but this distinction vanishes when the space restriction is lifted [13].

In this paper, we study the capabilities of constant-space verifiers (essentially, two-way probabilistic finite-state automata) which are allowed to hide some, but not necessarily all, of their coin flips from the prover. The separate accounting for the private and public coin "budgets" as resource functions of the input length provides new characterizations of the collections of associated languages in terms of well known complexity classes.

The rest of the paper is structured as follows: Section 2 provides the preliminaries. A definition of interactive proof systems which allows separate accounting of private and public coin usage is given in Section 2.1, together with notation that generalizes the standard IP classes in an accordingly parameterized manner. Since some of our constructions involve verifiers which do not halt with probability 1, we introduce notation that enables us to talk about resource bounds that apply in the (highly probable) cases where the machines do halt. Our main result uses a technique that depends on the relationship between logarithmic-space computation and multihead finite automata. Section 2.2 contains a quick review of that fact, and Section 2.3 describes two methods for implementing probabilistic "clocks" for later use in our proofs.

We start Section 3 by noting that finite-state verifiers which are only allowed to flip O(1) private coins are already known to outperform deterministic verifiers, and consider the analogous question about public coins. It turns out (Theorem 6) that finite-state verifiers tossing only O(1) public coins can verify only regular languages. This section also includes a technical result (Theorem 8) establishing that one has to consider bounds on expected, rather than worst-case, runtimes of finite-state verifiers to be able to conduct a meaningful study of superlinear resource bounds.

Our main result (Theorem 9, Section 4) is a demonstration of the equality the set of languages verifiable by polynomial-time finite-state machines that flip O(1) private coins and polynomially many public coins to the complexity class P. (The verifiers in question are allowed to be fooled by malicious provers to run forever without halting, but the probability of this "error" can be bounded below any desired positive value. The bounds on the runtime and number of public coin flips apply to halting computations.) The proof builds on previous work [2, 9, 15, 19] on logarithmic-space verification, prover-aided "simulation" of multihead automata by single-head probabilistic finite automata, and specialized loop avoidance techniques for such verifiers. Notably, Theorem 9 hints that allowing a minuscule probability of looping may add significant power to polynomial-time finite-state machines, since it is still not known whether those machines can verify all of P when required to halt with probability 1, even with no bound on their private coin usage. We also show that logarithmic-space machines which hide a constant number of their coins are limited to verifying the languages in P, even with arbitrarily large time and public-coin budgets.

Section 5 lists some open problems. Detailed proofs of some of the preliminary theorems are presented in the Appendix to avoid cluttering the main text.

2 Background

2.1 Interactive proof systems

We start by providing definitions of interactive proof systems and related language classes that are general enough to cover finite-state verifiers with both private and public coins, as well as the more widely studied versions with greater memory bounds [1, 7, 14].

An interactive proof system (IPS) for some language L is a protocol between a verifier and a prover. The verifier is a probabilistic Turing machine tasked with determining whether the prover's argument is sufficiently convincing to conclude that the input string is a member of L. The messages of the prover at any step during its communication with the verifier are determined by a (not necessarily computable) function of the input string and the transcript of the communication up to that point. This function maximizes the probability that the verifier accepts if the input is in L, and minimizes the probability that it rejects otherwise.

The verifier has a read-only input tape, a read-write work tape, and a read-write communication cell for "talking" with the prover. It is modeled as a 6-tuple $(Q, \Sigma, \Phi, \Gamma, \delta, q_0)$, with the following components:

- 1. Q is the finite set of states. The following subsets of Q are not necessarily disjoint:
 - Q_{pri} is the set of states that flip private coins.
 - Q_{pub} is the set of states that flip public coins.
 - Q_{com} is the set of communication states, *i.e.*, those that write to the communication cell. $Q_{\text{pub}} \subseteq Q_{\text{com}}$.
 - $\{q_{\rm acc}, q_{\rm rej}\}\$ are the accept and reject states, respectively. $q_{\rm acc}, q_{\rm rej} \notin Q_{\rm pri} \cup Q_{\rm com}$.
- 2. Σ is the input alphabet.
- 3. Φ is the work tape alphabet, containing the special blank symbol \Box .
- 4. Γ is the communication alphabet. $\square \in \Gamma$.
- 5. δ is the transition function, described below.
- 6. q_0 is the initial state. $q_0 \in Q$.

The computation of a verifier on an input string $w \in \Sigma^*$ is initialized as follows:

- The input tape contains $\triangleright w \triangleleft$, where $\triangleright, \triangleleft \notin \Sigma$ are the left and right end-markers, respectively. The input tape head starts on the left end-marker.
- The work tape is filled with blank symbols, and the work tape head is positioned at the beginning of the tape.
- The communication cell is also blank.

Let $\Sigma_{\bowtie} = \Sigma \cup \{ \rhd, \lhd \}$. Let $\Delta = \{ -1, 0, +1 \}$ be the set of possible head movements, where -1 means "move left", 0 means "stay put", and +1 means "move right". Let \overline{A} denote the complement of a set A, e.g., $\overline{Q_{\text{pri}}} = Q \setminus Q_{\text{pri}}$. The computation of the verifier is governed by its transition function δ , which is defined in parts in the manner depicted in Table 1 and explained below:

At each step of its computation, the verifier executes the following procedure:

1. It reads the symbols $(\sigma, \phi, \gamma) \in \Sigma \times \Phi \times \Gamma$ from its input tape, work tape, and communication cell respectively. If its current state q is in Q_{pri} , it tosses a private coin, obtaining the outcome $b_{\text{pri}} \in \{0, 1\}$. If $q \in Q_{\text{pub}}$, it tosses a public coin, obtaining the outcome $b_{\text{pub}} \in \{0, 1\}$.

Table 1: Parts of the verifier's transition function.

Case	Mapping
$q \in Q_{\mathrm{pri}} \cap Q_{\mathrm{pub}}$	$\delta(q, \sigma, \phi, \gamma, b_{\text{pri}}, b_{\text{pub}}) = (q', \phi', \gamma', d_i, d_w)$
$q \in Q_{\operatorname{pri}} \cap \overline{Q_{\operatorname{pub}}} \cap Q_{\operatorname{com}}$	$\delta(q,\sigma,\phi,\gamma,b_{\mathrm{pri}}) = (q',\phi',\gamma',d_i,d_w)$
$q \in Q_{\operatorname{pri}} \cap \overline{Q_{\operatorname{pub}}} \cap \overline{Q_{\operatorname{com}}}$	$\delta(q, \sigma, \phi, \gamma, b_{\text{pri}}) = (q', \phi', d_i, d_w)$
$q \in \overline{Q_{\mathrm{pri}}} \cap Q_{\mathrm{pub}}$	$\delta(q, \sigma, \phi, \gamma, b_{\text{pub}}) = (q', \phi', \gamma', d_i, d_w)$
$q \in \overline{Q_{\mathrm{pri}}} \cap \overline{Q_{\mathrm{pub}}} \cap Q_{\mathrm{com}}$	$\delta(q, \sigma, \phi, \gamma) = (q', \phi', \gamma', d_i, d_w)$
$q \in \overline{Q_{\mathrm{pri}}} \cap \overline{Q_{\mathrm{pub}}} \cap \overline{Q_{\mathrm{com}}} \setminus \{ q_{\mathrm{acc}}, q_{\mathrm{rej}} \}$	$\delta(q, \sigma, \phi, \gamma) = (q', \phi', d_i, d_w)$

2. The value of δ corresponding to this tuple (see the template of the corresponding part of δ in Table 1) dictates that the machine will switch to state $q' \in Q$, write $\phi' \in \Phi$ to its work tape, and move its input and work tape heads in the directions $d_i, d_w \in \Delta$, respectively. The verifier overwrites the communication cell with $\gamma' \in \Gamma$ if $q \in Q_{\text{com}}$. If $q \in Q_{\text{pub}}$, the outcome of the public coin flip (b_{pub}) is also communicated to the prover through a separate channel.

Each time the verifier writes a symbol to the shared communication cell, the prover overwrites that symbol with a (possibly different) member of Γ , determined as a function of w, the history of public coin outcomes, and the communication symbols written to the communication cell up to that point. Since the prover is supposed to embody the "best" possible function to convince (or, when the input string is not in the language L, to deceive) the verifier, one can assume that the prover "knows" the algorithm of the verifier. Note, however, that the prover does not "see" the private coin outcomes, tape head positions, work tape content, and internal state of the verifier.

We define the *configuration* of a verifier at any given time as the tuple composed of its state, the contents of its work tape, the symbol in the communication cell, and the positions of its input and work tape heads.

A verifier halts with acceptance (rejection) when it executes a transition entering $q_{\rm acc}$ ($q_{\rm rej}$). Any transition that moves the input head beyond an end-marker delimiting the string written on the read-only input tape leads to a rejection, unless that last move enters $q_{\rm acc}$. Note that the verifier may possibly never halt, in which case it is said to be looping.

We say a verifier V in an IPS verifies a language L with error $\varepsilon = \max(\varepsilon^+, \varepsilon^-)$ if there exist numbers $\varepsilon^+, \varepsilon^- < 1/2$ satisfying the following:

- For all input strings $w \in L$, there exists a prover P such that V halts by accepting with probability at least $1 \varepsilon^+$ when started on w and interacting with P.
- For all input strings $w \notin L$ and for all provers P^* , V halts by rejecting with probability at least $1 \varepsilon^-$ when started on w and interacting with P^* .

The terms ε^+ and ε^- bound the two possible types of error corresponding to failing to accept and reject, respectively.

We will be using the notation IP(resource₁, resource₂, ..., resource_k) to denote the class of languages that can be verified with error ε (for some $\varepsilon < 1/2$) by machines that operate within the resource bounds indicated in the parentheses. These may represent budgets for runtime, work tape (space) usage, and number of public and private random bits, given as a function of the length of the input string, in asymptotic terms. We reserve the symbol n to denote the length of the input string. The terms con, log, linear, and poly will be used to represent the well-known types of functions to be

considered as resource bounds, with "con" standing for constant functions of the input length, the others being self evident, to form arguments like "poly-private-coins" or "con-space". The symbol ∞ will be used to indicate that no upper bound limits the usage of a resource under consideration, as in " ∞ -time". The absence of a specification for a given type of resource (e.g., private coins) shall indicate that that type of resource is simply unavailable to the verifiers of that class.

By default, a given resource budget should be understood as a worst-case bound, indicating that it is impossible for the verifier to exceed those bounds. To indicate bounds in terms of statistical expectations, we will add the " $_{\%}$ " denotation as a subscript, such as "poly $_{\%}$ -time" to indicate polynomial expected runtime. Some of the interactive protocols to be discussed have the property that the verifier has a probability $\varepsilon^{\text{loop}}$ of being fooled to run forever by a malicious prover trying to prevent it from rejecting the input. The designer of such protocols can set $\varepsilon^{\text{loop}}$ to any desired small positive value. The denotation "%" will be used, this time as a superscript, to mark that the indicated amount corresponds to such a machine's expected consumption of a specific resource with the remaining (high) probability $1-\varepsilon^{\text{loop}}$. For instance, "poly $^{\%}$ -time" will indicate that the verifier's expected runtime is polynomially bounded with probability almost, but possibly not exactly, 1.

Some verifier algorithms we describe in this article will have "dials" that allow one to tune them to set their error bounds to any desired (positive) constant. Such verifiers will be qualified as verifying their language with *(arbitrarily) low error*. To denote classes of languages that are verifiable with arbitrarily low error, we will be using the $IP_*(...)$ denotation instead of IP(...).

We will also be considering verifiers with "one-sided error": A verifier V for language L is said to have *perfect completeness* if there exists a prover whose interaction with V leads it to accept any string in L with probability 1, and no prover can convince L to accept a string that is not in L with probability 1.

In one of our proofs in Section 4, we will be considering verifiers with multiple input tape heads that the machine can move independently of one another. This type of verifier can be modeled easily by modifying the tuples in the transition function definitions above to accommodate more scanned input symbols and input head directions. Section 2.2 provides more information on automata with multiple input heads and their relationships with the standard Turing machine model.

2.2 Multihead finite automata and log-space machines

A k-head nondeterministic finite automaton (2nfa(k)) is a nondeterministic finite-state machine with k read-only heads that move on an input string flanked by two end-marker symbols. Each head can be made to stay put or move to an adjacent tape cell in each computational step. Formally, a 2nfa(k) is a 4-tuple (Q, Σ, δ, q_0) , where

- 1. Q is the finite set of internal states, which includes the two halting states $q_{\rm acc}$ and $q_{\rm rej}$,
- 2. Σ is the finite input alphabet,
- 3. $\delta: Q \times \Sigma_{\bowtie}^k \to \mathcal{P}\big(Q \times \Delta^k\big)$ is the transition function describing the sets of alternative moves the machine may perform at each execution step, where each move is associated with a state to enter and whether or not to move each head, given the machine's current state and the list of symbols that are currently being scanned by the k input heads, and Σ_{\bowtie} and Δ are as defined previously in Section 2.1, and
- 4. $q_0 \in Q$ is the initial state.

Given an input string $w \in \Sigma^*$, a 2nfa(k) $M = (Q, \Sigma, \delta, q_0)$ begins execution from the state q_0 , with $\triangleright w \triangleleft$ written on its tape, and all k of its heads on the left end-marker. At each step, M nondeterministically updates its state and head positions according to the choices dictated by its

¹Constant-space verifiers which do not use their work tape at all are also called *finite-state verifiers*. (A Turing machine that is restricted to scan O(1) work tape cells can be simulated by a finite-state machine.) "Stand-alone" finite-state verifiers (that do not "listen" to what the prover says) are called *probabilistic finite automata*.

transition function. Computation halts if one of the states $q_{\rm acc}$ or $q_{\rm rej}$ has been reached, or a head has moved beyond either end-marker.

M is said to accept w if there exists a sequence of nondeterministic choices where it reaches the state $q_{\rm acc}$, given w as the input. M is said to reject w if every sequence of choices either reaches $q_{\rm rej}$, ends with a transition whose associated set of choices is \emptyset , or by a head moving beyond an end-marker without a final state being entered. M might also loop on the input w, neither accepting nor rejecting it.

The language recognized by M is the set of strings that it accepts.

Let $\mathcal{L}(2\text{nfa}(*))$ denote the set of languages that have a 2nfa(k) recognizer (for some k > 0), and $\mathcal{L}(2\text{nfa}(*), \text{linear-time})$ denote the set of languages that have a 2nfa(k) recognizer running in linear time.

Our characterization of P (Section 4) makes use of the equivalence of multiple input heads and logarithmic amounts of memory, discovered by Hartmanis [16]. The following theorem, whose proof is given in Appendix A.1, reiterates one direction of that result in detail, and will be useful for our purposes.

Theorem 1. Any language recognized by a Turing machine that uses at most $\lceil \log n \rceil$ space with a work tape alphabet of size at most 2^c (for some integer constant c > 0) and in t(n) time can also be recognized by a (c+5)-head finite automaton in $t(n) \cdot ((2c+3)n+c+1)$ time.

2.3 Probabilistic clocks

A logarithmic-space Turing machine can "clock" its own execution to satisfy any desired polynomial-time bound by counting up to that bound in the logarithmic space available. The constant-space machines we construct in Section 4 will employ a different technique using randomness, which is illustrated in the following lemma, to obtain the same bound on expected runtime.

Lemma 2. For any constant t > 0, integer-valued function $f(n) \in O(n^t)$, and desired "error" bound $\varepsilon_{premature} > 0$, there exists a probabilistic finite automaton with expected runtime in $O(n^{t+1})$, such that the probability that this machine halts in fewer than f(n) time-steps is $\varepsilon_{premature}$.

The proof of Lemma 2, based on the idea of the machine performing a sequence of random walks with its head on the input tape, is given in Appendix A.2.

In the proof of Lemma 12 in Section 4, we describe a probabilistic log-space machine that uses a timer which is expected to run out after at least $2^{2^{p(n)}}$ "ticks", where p is some polynomial, and n is the length of the machine's input string. We describe the main idea below; a detailed analysis can be found in Appendix A.3.

It will be helpful to imagine that we have fair coins of two colors, say, red and blue. The timer mechanism consists of a subroutine that embodies a single tick, and a global Boolean variable that tracks whether all the red coins flipped since the last reset of this variable came out heads. Each call of the tick subroutine flips one red coin and p(n) blue coins. If one or more blue coins come out tails, the subroutine call ends with the timer still running. If all the blue coin outcomes are heads, but the Boolean variable indicates that one or more red coins flipped since the last reset came out tails, the variable is reset, and the subroutine ends with the timer still running. If all the blue coin outcomes are heads, and if all the red coins flipped since the last reset also came out heads, the timer runs out.

The expected number of ticks is at least double exponential in p(n), since the timer runs out when an all-heads sequence of red coins is observed, and the expected length of this critical sequence is exponential in p(n).

3 Private vs. public coins and worst-case time bounds

In their seminal paper, Dwork and Stockmeyer [7] showed that finite-state verifiers employing only private coins are strictly more powerful than those using only public coins, even when the former machines are bounded to operate in polynomial expected time:

Fact 3. $IP(con\text{-space}, \infty\text{-public-coins}, \infty\text{-time}) \subseteq IP_*(con\text{-space}, poly_\%\text{-private-coins}, poly_\%\text{-time}).$

A witness for the inequality in Fact 3 is the language of palindromes,

$$L_{\text{pal}} = \{ w \in \{ 0, 1 \}^* \mid w = w^R \},$$

where x^R denotes the reverse of string x. The constant-space verifier provided for L_{pal} by Dwork and Stockmeyer uses only a constant number of private coins, irrespective of the length of the input. This inspired the study [9, 11, 19] of machines that flip a fixed number of coins, leading to the following results:

Fact 4. $\mathcal{L}(2nfa(*), linear-time) \subseteq IP_*(con-space, con-private-coins, linear^\%-time)$ [9].

Fact 5. IP(con-space, con-private-coins, ∞ -time) = NL [19].

In contrast to Fact 5, we now show that the ability to use constant number of *public* coin flips provides no additional language verification power over determinism to constant-space machines.

Theorem 6. IP(con-space, con-public-coins, ∞ -time) = REG.

Proof. Let V be a finite-state machine that verifies a language L with some error bound $\varepsilon < 1/2$, flipping at most r > 0 public coins for any input. Let the prover that interacts with V be named P.

We recall the following facts about two-way alternating finite automata [18]: Each non-halting state in such an automaton is either existential or universal. It is helpful to visualise a "prover" (whose aim is to make the machine accept the input) as dictating which move to make when the transition function allows multiple outgoing choices from a configuration with an existential state, and a "refuter" (with the opposite aim) as similarly dictating moves from configurations with universal states. The input string w is accepted by the machine if and only if the prover has a winning strategy, whereby it can lead the machine from the initial configuration associated with w to an accepting configuration, no matter what moves are made by the refuter, in this perfect information game. We say that the machine recognizes the set of strings that it accepts.

We will construct a two-way alternating finite automaton M that recognizes L. This will be enough to conclude that L is regular, by the fact [18] that two-way alternating finite automata recognize all and only the regular languages.

The construction is based on the following idea: Consider the set of all possible bit sequences of length r. Each execution of V would use (a prefix of) one of these sequences as its public coin outcomes during its interaction with the prover. Any input string w is in L if and only if a majority of the members of this set of sequences leads V to acceptance during this interaction. M will be designed so that it accepts w if and only it verifies that this condition is satisfied. Note that simply simulating V's behavior "sequentially" on one coin sequence after another would not work, since this would give the simulated prover the opportunity to "cheat" by violating the condition that its responses to V given two coin sequences with the same prefix (like p0 and p1, for some prefix $p \in \{0,1\}^*$) should be identical up to the point when the coin sequences finally differ. M will use the "parallel computation" nature of alternation to enforce this consistency on the simulated prover.

M starts with an existential state, where it guesses a prefix-free set S of public coin sequences (of length at most r) whose probabilities add up to a value greater than $^{1}/_{2}$. (Since there are only

²Recall from the definition of our IP complexity class notation in Section 2 that the verifier's runtime can be infinite with at most a small probability $\varepsilon^{\text{loop}}$, and its expected runtime is bounded as indicated with the remaining large probability.

finitely many sets of bit sequences with this property, this choice can be made in a single step.) Recall that such choices of moves from existential states can be viewed as being made by a "prover", which we will name P_M . By this first choice, P_M would be "claiming" that all of these coin sequences would lead V to acceptance in an interaction with P.

M attempts to verify this claim: M's transition function is based on that of V; essentially, M uses alternation to create a "parallel" simulation of V (and its interaction with P) on all the coin sequences in the set S obtained at the start. At every step, M keeps a record of the (simulated) coin sequence used up to that point in the present branch of its computation. Whenever its simulation of V reaches a new coin-flipping state, M checks this record and rejects if it determines that it is in a branch that would use a coin sequence that is not a member of S. If only one of the outcomes of the coin to flipped at the present state is consistent with S, M "plugs" that bit into V to advance the simulation. If, on the other hand, both of the 0 and 1 outcomes are consistent with S, M makes a universal choice (controlled by the "refuter" R_M) to determine which bit to feed V. Each communication symbol sent by P to V is obtained by an existential choice (as if P_M is supplying that information). The accept state of M corresponds to the accept state of V.

We see that M recognizes L by noting that any w is in L if and only if there exists a set of random bit sequences with total probability greater than $^{1}/_{2}$ such that all members of this set lead V to acceptance of input w after an interaction with P, and M accepts all and only such input strings by design.

We will focus on the computational power of constant-space verifiers with a fixed private-coin budget when they are also allowed to use public coins. Although some of Dwork and Stockmeyer's results (e.g., [7, Theorem 3.12]) involve such "mixed-coin" constructions, the asymptotic bounds on private and public coin tosses are equal in their machines. In those setups, all public coins can simply be replaced by private coins by a straightforward modification that increases the runtime of the protocol by a constant factor. The proof of the following lemma is in Appendix A.4.

Lemma 7. The following is true for all functions s(n), f(n), g(n), and t(n):

```
IP_*(O(s(n))\text{-space}, O(f(n))\text{-private-coins}, O(g(n))\text{-public-coins}, O(t(n))\text{-time}) \subseteq IP_*(O(s(n))\text{-space}, O(f(n)+g(n))\text{-private-coins}, O(t(n))\text{-time}).
```

This inclusion also holds for the IP(...) variants of the classes, and when worst-case time bounds are replaced with those corresponding to expected usage.

Lemma 7 implies that allowing the finite-state verifiers in the constructions of Facts 4 and 5 to use a constant number of public coins in addition to their private-coin budgets would not enlarge the corresponding classes of verified languages.

Our main result to be presented in the next section involves constant-space verifiers that flip a constant number of private coins and superlinear amounts of public coins. We note that expected (rather than worst-case) time bounds are appropriate for studying that scenario, since the imposition of any worst-case bound on the runtime of a finite-state verifier precludes it from benefiting from superlinear amounts of any kind of resource.

Theorem 8. For any time complexity function t(n),

```
\begin{split} \text{IP}_*(\text{con-space}, \infty\text{-private-coins}, \infty\text{-public-coins}, O(t(n))\text{-time}) \subseteq \\ \text{IP}_*(\text{con-space}, \text{linear-private-coins}, \text{linear-public-coins}, \text{linear-time}). \end{split}
```

The same is true also for the IP(...) variants of the two classes.

Proof. The number of configurations available to a constant-space verifier V running on an input of length n is in O(n).

If V's transition function allows it to enter the same configuration more than once with nonzero probability for some input string, it will do so arbitrarily many times with positive probability, exceeding any preset time bound. Therefore, all constant-space verifiers with a worst-case time bound t(n) are actually limited to run within a linear bound. The linear bounds on coin usage are established by noting that a machine that can run for at most t steps is restricted to flipping at most t coins of any type.

4 A new characterization of P

Let us now examine finite-state verifiers employing a constant amount of private coins and an expected polynomial amount of public coins (unless they are tricked to loop forever with some arbitrarily small probability). This setup turns out to provide a new characterization of the complexity class P, corresponding to the collection of languages decidable by deterministic Turing machines in polynomial time and space.

Theorem 9. The following three classes are equal:

- 1. IP_{*}(con-space, con-private-coins, poly[%]-public-coins, poly[%]-time)
- 2. IP(log-space, con-private-coins, ∞ -public-coins, ∞ -time)
- *3.* P

Theorem 9 follows from Lemmas 10 and 12.

Lemma 10. $P \subseteq IP_*(\text{con-space}, \text{con-private-coins}, \text{poly}^{\%}\text{-public-coins}, \text{poly}^{\%}\text{-time}).$

Proof. Let L be any language in P. As Goldwasser et al. have proven in [15], there exists a publiccoin verifier V_1 verifying L with the following properties:

- V_1 has perfect completeness;
- For any string w not in L and any prover P^* , the probability that V_1 is convinced to accept w by P^* is at most 1/2; and
- For any input of length n, V_1 uses $O(\log n)$ space and time $O(n^t)$ (for some t > 1). (These are worst-case bounds.)

We will assume that exactly $\lceil \log n \rceil$ cells are used in the work tape of V_1 , and a "multi-track" alphabet (e.g., as in [16]) is used to accommodate for the required amount of memory.

In the following discussion, let any prover facing V_1 be called P_1 .

There exists a constant-space, public-coin, k-head verifier V_2 that can verify L by simply executing V_1 's program, simulating V_1 's logarithmic-length work tape by the technique of Theorem 1. (Note that k depends on the precise worst-case memory requirement of V_1 .) Since the simulation is direct and does not involve any additional use of randomness, V_2 verifies L with the same amount of one-sided error as V_1 . The only time overhead is caused by the simulation of the logarithmically bounded memory, so, by Theorem 1, V_2 will complete its execution in $O(n^{t+1})$ time. V_2 's prover, say, P_2 , is supposed to follow the same protocol as P_1 .

We now describe V_3 , a constant-space, single-head verifier that uses a constant number of private coins, in addition to the public coins that it flips at almost *every* step, to emulate V_2 's verification of L^3

³This is an adaptation of a technique introduced by Say and Yakaryılmaz [19] for "simulating" a multihead nondeterministic automaton in an interactive proof system whose verifier is a (single-head) probabilistic finite automaton.

 V_3 performs the following m-round procedure:⁴

Each round begins with V_3 flipping r of its private coins. Using this randomness, it picks one of the k heads of V_2 . Each head has the same very small probability $p = 2^{-r}$ of being selected. (How V_3 operates with the remaining high probability 1 - kp will be explained later.) V_3 then engages in an interaction with its own prover, say, P_3 , to simulate the execution of V_2 , including V_2 's interaction with P_2 about the input string.

Note that V_2 flips coins in some, but not necessarily all of its computation steps, whereas V_3 flips a public coin at each step of the simulation. Only some of these coin outcomes are used to stand in for V_2 's public coins. What V_3 does with the remaining public random bits will be explained below.

To simulate V_2 , V_3 traces the selected head of V_2 with its own single head, and relies on P_3 to provide an unbroken stream of information about what the other heads of V_2 would be reading at every step of its execution. In its response to any coin flip of V_3 , P_3 is expected to transmit its claims about the readings of all k heads of V_2 at that step of the simulated interaction (and P_2 's response to V_2 , if the currently simulated transition of V_2 emanated from a communication state). When the simulation arrives at an actual coin-flipping state of V_2 , P_3 is supposed to interpret the latest coin outcome as a public coin flipped by V_2 .

At any step, V_3 checks the part of P_3 's claims regarding the head it had chosen in private, and rejects if it sees any discrepancy. If the information sent by P_3 has led the simulation of V_2 to reach acceptance at the current step, V_3 has not been able to catch a "lie" up to that point, and if this was not the mth round, V_3 moves its head back to the left end of the input tape without flipping coins, and proceeds to the next round.

The probability p_{head} that V_3 will attempt to use its head to control the claims of P_3 in the manner described above is just kp. With the remaining high probability p_{timer} (i.e., $1 - p_{\text{head}}$), V_3 simulates V_2 by relying on P_3 's claims about the head readings and P_2 responses blindly, while using its own head and the coins it flips to simultaneously operate as a probabilistic timer (Appendix A.2) in this round. This timer has an expected runtime of $O(n^{t+2})$, and exceeds V_2 's runtime with probability $1 - \varepsilon_{\text{premature}}$, for some positive $\varepsilon_{\text{premature}}$ that can be set to be arbitrarily close to 0, by the premise of Lemma 2. If the simulation of V_2 fed by P_3 reaches acceptance before the timer runs out, then V_3 completes this round of verification without rejecting. Otherwise (if the timer runs out before the simulation ends), V_3 rejects.

 V_3 accepts if it does not reject for m rounds of verification. The total number of private coins used is mr.

The rest of the proof is an analysis of the error probability and runtime of V_3 .

Arbitrarily small verification error. For any input string that is a member of L, P_3 can simply tell V_3 the truth about what V_2 would read with its k heads, and emit the messages that P_2 would send to V_2 alongside those readings. Even when communicating with such a truthful P_3 , V_3 may erroneously reject at any given round, due to a premature timeout of the probabilistic timer. The probability of that is at most $p_{\text{timer}} \cdot \varepsilon_{\text{premature}}$. To accept a member of L, V_3 must go through m consecutive rounds of verification without this event occurring. The maximum probability with which V_3 can fail to accept a string in L is therefore

$$\varepsilon_3^+ \le 1 - (1 - p_{\text{timer}} \cdot \varepsilon_{\text{premature}})^m$$
.

We will now determine a bound for ε_3^- , the probability with which V_3 may fail to reject an input string that is not a member of L. Unlike ε_3^+ , ε_3^- is a value that P_3 "wants" to maximize, so one has to be careful to include all possible strategies for the prover in this consideration. The program of V_3 dictates that there are exactly m+1 different ways (corresponding to alternative strategies for P_3) in which V_3 may fail to reject a string w not in L:

⁴The precise settings of V_3 's parameters (like m) will be discussed below.

- V_3 may "pass" all m rounds by carrying out an "assisted simulation" of V_2 that ends in what seems to it to be acceptance. We denote this event by P^m .
- V_3 may be tricked (as will be described below) by P_3 into entering an infinite loop during the j+1st round, after passing the first j rounds, for $j \in \{0, \ldots, m-1\}$. Such an event will be denoted by P^jL .

Recall that P_3 is expected to feed V_3 with information about the symbols that would be scanned by V_2 's input heads at any point of its execution, and the transmissions of P_2 . For $w \notin L$, if P_3 always tells the truth, V_3 can pass any round with the probability (at most 2^{-1}) that V_2 would be deceived about w, and finally accept with probability at most 2^{-m} . Since P_2 's messages are "optimal" for convincing V_2 , whose program is hard-coded in V_3 , P_3 's only option for achieving better odds of deceiving V_3 is by "lying" about the head readings of V_2 .

Since V_3 is able to track only one of V_2 's input heads with its own head, it is dependent on P_3 to carry out the simulation. If V_3 has picked some head h of V_2 to track, a lie by P_3 about the symbol seen at that step by some other head h' of V_2 may be enough to deceive V_3 into eventually believing that V_2 accepts w in that round. V_3 can catch such a lie only if it has previously picked the head that is being lied about, and detects the discrepancy between P_3 's claim and its own scan.

Unlike P_1 and P_2 , which deal with verifiers that have sufficient memory to clock their own runtimes, P_3 also has the capability to trick V_3 , whose number of different possible configurations is, in general, less than the runtime of V_2 , which it is supposed to be simulating, into running forever. It is common (see, for instance, Appendix A.1) for multihead finite automata to require a head to wait at a tape location while another head is walking towards a specific symbol, e.g., an end-marker. If V_3 has picked to track such a "waiting" head of V_2 with its own head, it can be tricked into getting stuck in that configuration by an endless stream of claims from P_3 that the other head is still walking in the required direction. V_3 can catch such a lie directly, if it has picked the head that is being lied about; or indirectly, if it has been running in "timer mode".

Our analysis of the error probabilities associated with the m+1 alternative strategies for the prover mentioned above requires setting bounds for the two following values:

- ε_L , the probability that V_3 is tricked to enter an infinite loop in a particular round.
- ε_{P} , the probability that V_3 is led to complete a round without rejection when $w \notin L$.

 V_3 cannot run forever in any round in which it has selected to act as a timer. The probability that V_3 has selected to simulate V_2 with a head that P_3 would lie about is at least p. We conclude that

$$\varepsilon_{\mathsf{L}} \le p_{\mathsf{head}} - p = (k-1) \cdot p.$$

There are two different ways in which the prover can cause V_3 to complete a round without rejection when $w \notin L$:

- 1. P_3 can be truthful. With probability at most 1/2, the public coin flips would lead the resulting faithful simulation to end in V_2 's accept state.
- 2. P_3 can lie about a reading of a head of V_2 . In this case, V_3 may be tricked into believing that V_2 accepts w if V_3 has not selected to track that head. The probability of this event is at most 1-p.

In this scenario, P_3 can maximize its chances of leading V_3 to passing a round by basing its decision about whether to lie or not on the public coin outcomes: Call a public coin sequence lucky if it leads V_2 to accepting w when guided by P_2 . In such cases, honesty is the best P_3 policy, since it involves zero probability of rejection as a result of being caught lying. For unlucky coin sequences, honesty has no chance of success, and P_3 would have to lie for V_3 to complete the round.

To obtain an easy upper bound for ε_P , we grant P_3 certain additional "superpowers" that allow it to always make the correct decision in the situations described above: In particular, we assume that P_3 can always correctly foresee whether the entire public coin sequence of the present round will be a lucky one or not, and that it is able to communicate with V_3 (mimicking P_2 or lying about a single V_2 head) accordingly. Under these extremely favorable circumstances, P_3 can manage to be truthful exactly when the public coin sequence of the present round is a lucky one, and lie in the remaining cases. The probability of a lucky sequence is, as mentioned before, at most 1/2. We therefore have

$$\varepsilon_{\mathsf{P}} \leq \frac{1}{2} + \left(1 - \frac{1}{2}\right) \cdot (1 - p) = 1 - \frac{p}{2}.$$

We can now establish bounds for the probabilities of the m+1 "failure to reject" events listed above.

The probability that V_3 is led to accept $w \notin L$ through P^m is

$$\varepsilon_{\mathsf{P}^m} = \varepsilon_{\mathsf{P}}^m \le \left(1 - \frac{p}{2}\right)^m.$$

The probability that V_3 is made to fail to reject w through $\mathsf{P}^j\mathsf{L}\ (j\in\{0,\ldots,m-1\})$ is

$$\varepsilon_{\mathsf{P}^{j}\mathsf{L}} = \varepsilon_{\mathsf{P}}^{j}\varepsilon_{\mathsf{L}} \leq \left(1 - \frac{p}{2}\right)^{j} \cdot (k - 1) \cdot p.$$

Although the prover has the ability to use the public coins to implement a probabilistic "mixture" of the m+1 mutually exclusive strategies in its repertory, it is easy to see that P_3 must focus only on the strategies associated with the highest "success" probabilities from its own point of view:

$$\varepsilon_3^- \le \max(\varepsilon_{\mathsf{P}^0\mathsf{L}}, \varepsilon_{\mathsf{P}^1\mathsf{L}}, \dots, \varepsilon_{\mathsf{P}^m}).$$

Since $\varepsilon_{\mathsf{P}^0\mathsf{L}}$ is clearly the maximum among all $\varepsilon_{\mathsf{P}^j\mathsf{L}}$'s, we have

$$\varepsilon_3^- \leq \max(\varepsilon_{\mathsf{P}^0\mathsf{L}}, \varepsilon_{\mathsf{P}^m}).$$

Let us show that we can "tune" V_3 so that it verifies L with error $\varepsilon_3 = \max(\varepsilon_3^+, \varepsilon_3^-)$, for any small positive value ε_3 . Since

$$p = 2^{-r}$$
 and $p_{\text{timer}} = 1 - p_{\text{head}} = \frac{2^r - k}{2^r}$,

we have established that the following three quantities should be less than or equal to the allowed error bound:

$$\varepsilon_3^+ \le 1 - (1 - p_{\text{timer}} \cdot \varepsilon_{\text{premature}})^m = 1 - \left(1 - \frac{2^r - k}{2^r} \cdot \varepsilon_{\text{premature}}\right)^m$$

$$\varepsilon_{\mathsf{P}^m} \le \left(1 - \frac{p}{2}\right)^m = \left(1 - 2^{-r-1}\right)^m$$

$$\varepsilon_{\mathsf{P}^0\mathsf{L}} \le (k-1) \cdot p = (k-1) \cdot 2^{-r}$$

Given some desired ε_3 ,

- 1. Set r to a value that ensures ε_{P^0} does not exceed ε_3 .
- 2. Set m to a value that ensures that $\varepsilon_{\mathbb{P}^m}$ does not exceed ε_3 .
- 3. Set $\varepsilon_{\text{premature}}$ so that ε_3^+ does not exceed ε_3 . This can be achieved by arranging the number of states in the implementation of the probabilistic timer, as described in Appendix A.2.

Note that the parameters r, m, and $\varepsilon_{\text{premature}}$ are independent, allowing each of them to be set without affecting the values of the other two.

Polynomial expected runtime with arbitrarily high probability. With ε_3 (and thereby also the probability of looping) set to a desired tiny value, V_3 will be running for at most m rounds with the remaining high probability. At each of those rounds, V_3 will either complete V_2 's simulation in $O(n^{t+1})$ time, or will operate as a probabilistic timer that has expected runtime $O(n^{t+2})$. Thus, it is expected to run in $O(n^{t+2})$ time with probability at least $1 - \varepsilon_3$.

We conclude that $L \in \mathrm{IP}_*(\text{con-space}, \text{con-private-coins}, \text{poly}^{\%}\text{-public-coins}, \text{poly}^{\%}\text{-time}).$

The following corollary to Lemma 10 depicts that the class NC has finite-state verifiers flipping a fixed number of private coins and with a tighter upper bound on their public coin budget compared to those for P.

Corollary 11. NC \subseteq IP_{*}(con-space, con-private-coins, $O(n^4)^{\%}$ -public-coins, $O(n^4)^{\%}$ -time).

Proof. Fortnow and Lund have proven [8] that

$$NC \subseteq IP_*(log-space, O(n log^2 n)-public-coins, O(n log^2 n)-time).$$
 (1)

The verifiers described in [8] for the right-hand side of (1) have perfect completeness. One can apply the sequence of constructions described in the proof of Lemma 10, starting with such a verifier playing the role played by V_1 in that proof, to obtain the claimed result.

Lemma 12. IP(log-space, con-private-coins, ∞ -public-coins, ∞ -time) $\subseteq P$.

Proof. Let V_1 be a log-space verifier that uses at most r private coins and an unlimited budget of public coins to verify a language L with some error bound $\varepsilon_1 < 1/2$, for some constant r. In the following, the prover that V_1 interacts with will be named P_1 . The length of the input string is denoted by n.

We will now demonstrate the existence of a log-space verifier V_2 that verifies the same language L with an error bound close to that of V_1 without using any private coins. V_2 also has an unlimited budget of public coins. In a nutshell, V_2 will interact with its prover, which we name P_2 , to simulate V_1 parallelly for all the 2^r different possible private random bit sequences, feeding all of these simulations with the same public random bit sequence that it will generate on the fly, while checking that P_2 is not trying to cheat by supplying messages that would be impossible for P_1 , or by attempting to trick V_2 into an unnecessarily long conversation. V_2 will be operating a probabilistic clock to ensure that its expected runtime will be within $2^{2^{\Omega(p(n))}}$, for a suitably chosen polynomial p. When this timer finally runs out, V_2 will pick one of the parallel simulations at random to imitate V_1 's decision. We now present a detailed discussion of each of these points.

The interaction between V_2 and P_2 . As mentioned above, V_2 will be running 2^r parallel simulations ("sims") of V_1 , where the *i*th sim S_i (for $i \in \{0, \dots, 2^r - 1\}$) is hardwired to use the bits of the binary representation of the number i as its private "random" bits. At each step of its interaction with V_2 , P_2 is supposed to supply the responses that P_1 would supply to each sim at the corresponding point, according to the convention that will be explained below. Whenever V_2 is ready to receive the next P_2 symbol, it will use the communication cell to indicate this. As we will see, V_2 will flip public coins in some, but not necessarily all, of its communication steps.

The execution of V_2 proceeds in *stages* delimited by its (public) coin flips. Each stage consists of one or more *segments* delimited by communication steps. Originally starting each S_i from its initial state, V_2 proceeds in each segment by going through all the S_i 's sequentially,⁵ continuing the simulation of each sim until that sim has accepted, rejected, entered a communication state, or is determined to have entered an infinite loop. (Note that there exists a polynomial q, dependent

⁵Note that V_2 's logarithmic-space budget is sufficient to trace the executions of all the 2^{τ} sims and store the configurations of those that are paused.

on V_1 , such that a sim that runs for more than q(n) steps without entering a communication state must be in an infinite loop. V_2 has sufficient memory to count deterministically up to q(n), which is simply the number of different possible configurations of V_1 on the present input string.) If no sims are in a communication state at the end of this scan of the S_i 's, the overall simulation has finished. Otherwise, one or more sims are "waiting" for a response from the prover, and therefore V_2 should request the next P_2 symbol.

At this point, it may be the case that some sims are waiting in (communication) states that flip a public coin, whereas some other sims are in communication states that do not flip a coin. Since V_2 is designed to present the same public coin sequence to every sim, it performs a coin flip (which ends the present stage) only if *all* the waiting sims are in coin-flipping states. Otherwise, V_2 flips no coin during its request to P_2 ; in this case, the sims waiting at coin-flipping states will be suspended in the subsequent segments of this stage, until the occurrence of the flip.

In response to V_2 's request, P_2 is supposed to provide a 2^r -tuple whose ith element is the symbol that P_1 would send to S_i if S_i is a waiting sim that V_2 is going to continue simulating in the next segment, and a filler symbol otherwise. (Since V_2 employs no private coins, P_2 has complete information about all of the sims' configurations, as well as all the communication symbols any sim would have transmitted had it been interacting with V_1 , at this point.) V_2 performs some additional controls (to be detailed below under separate headings) upon receipt of this symbol, rejecting if it detects a "cheating" attempt by P_2 at this juncture.

After the single coin flip at the end of each stage, V_2 calls the "double exponential timer tick" subroutine, described in Section 2.3.⁶ If the timer does not run out in this call, simulation proceeds with the next stage. If the timer does run out, V_2 considers the overall simulation finished.

When the overall simulation is finished, V_2 flips r more coins to select one of the sims. If the selected sim has already been determined to have rejected, or to have entered an infinite loop, V_2 rejects. Otherwise, it accepts.

Members of L are accepted by V_2 with sufficiently high probability. Consider an "intermediate" verifier V_1' , which is obtained by modifying V_1 so that it calls the same double exponential timer tick subroutine that we mentioned above in V_2 's description after every actual public coin toss of V_1 to determine whether it should time out and accept. Since the only difference between V_1 and V_1' is that V_1' may accept some input strings (which can get involved in very long computations that are cut off by the timer) with higher probability than V_1 , P_1 is clearly able to convince V_1' to accept any member of L with probability at least $1 - \varepsilon_1$. We claim that P_2 will be able to convince V_2 to accept any member of L with the same probability, by simply obeying the protocol described above and transmitting precisely the symbols that P_1 would have transmitted in response to communications from V_1 at every step: In this case, P_2 's interaction with V_2 would be a perfectly faithful imitation of P_1 's interaction with V_1' , with identical probabilities of acceptance, determined by the public coins flipped during the simulations, and the r final public random bits that stand for the r private coin flips of V_1' .

 P_2 cannot trick V_2 into looping forever within a stage. We have already noted that each sim can have at most q(n) different configurations, for some polynomial q. Consider the 2^r -tuple consisting of the configurations of all the sims, which we will refer to as the "collective configuration". Clearly, the number of different possible collective configurations is $g(n) \in O(q(n)^{2^r})$, which is another polynomial in n. Considering the collective configurations at the end of each segment, a stage which has continued for more than g(n) segments must have therefore repeated an end-of-segment collective configuration. Note that, within any particular stage of the execution of V_2 , P_2 has complete, deterministic control of the evolution of the collective configuration between subsequent

 $^{^6}V_2$ flips polynomially many additional public coins for each such subroutine call. P_2 waits for the subroutine to finish and the next stage of V_2 's execution to resume.

communication steps, through the responses it sends. This would give a malevolent prover a chance to trick the verifier into looping forever within a stage. Since any "honest" prover-verifier interaction that eventually terminates with the verifier reaching a halting state can be shortened to avoid all such collective configuration repetitions without changing the outcome, V_2 expects P_2 to respect this convention, and rejects if it sees that the present stage contains more than g(n) segments.

 P_2 will be caught if it does not mimic P_1 . As noted above, P_2 has complete information about all the sims that it is communicating with. This is quite different than the situation of P_1 , which does not see the private bits of the verifier. It is sometimes possible for P_1 to deduce information about the private random bits used by V_1 by noting the communication symbols that it transmits during the interaction, but P_1 has no way of distinguishing two probabilistic branches of V_1 corresponding to distinct private coin sequences that have both communicated exactly the same string of symbols, punctuated with public coin flips in identical locations, up to the present point. This presents a devious P_2 an opportunity to attempt to achieve a lower rejection probability than P_1 by transmitting different messages to sims that would be indistinguishable to (and would therefore have to receive the same message from) P_1 . As a countermeasure, V_2 maintains an up-to-date list of groups of sims that should be presently indistinguishable to P_1 , and rejects whenever it sees that the P_2 symbol is trying to convey different messages to different sims in the same group. As a result, any interaction where P_2 attempts to send messages that are not " P_1 -compliant" in this sense leads to rejection with probability 1.

Double exponential runtime is enough for V_2 to reject non-members of L with sufficiently high probability. It remains to analyze the probability that V_2 fails to reject a non-member of L. Since P_2 is unable to make V_2 loop forever, and any attempt to deviate from the protocol described above would be caught, all we need to focus on is the additional error possibly introduced by V_2 cutting off sims with very long computations, and regarding them as having accepted. Fortunately, Condon and Lipton have shown [3, 5] that the execution of a verifier whose space consumption is logarithmically bounded can be cut off after a double-exponentially large number of steps without a significant change in the acceptance and rejection probabilities. By the reasoning in the proof of Theorem 6.1 of [5], for any desired small positive value of ε_x , there exists a polynomial p(n) such that the log-space verifier V_1 will have rejected any non-member input string of length n with probability at least $1 - \varepsilon_1 - \varepsilon_x$ within at most $2^{2^{p(n)}}$ computational steps. By tuning the parameters (Section 2.3, Appendix A.3) of the double exponential timer, we can therefore set the error bound of V_2 to any desired value in the interval $(\varepsilon_1, 1/2)$.

We conclude the proof by noting that the language L verified by V_2 is in P, due to the fact that

 $IP(log\text{-space}, \infty\text{-public-coins}, \infty\text{-time}) = P,$

which was proven by Condon in [2].

Since it is obvious that

 $\mathrm{IP}_*(\mathrm{con\text{-}space}, \mathrm{con\text{-}private\text{-}coins}, \mathrm{poly}^{\%}\text{-}\mathrm{public\text{-}coins}, \mathrm{poly}^{\%}\text{-}\mathrm{time}) \subseteq$

IP(log-space, con-private-coins, ∞ -public-coins, ∞ -time),

Lemma 12 concludes the proof of Theorem 9.

⁷The verifier model in [5] uses only private coins. The validity of this result for our verifiers is a simple consequence of the argument in the proof of Lemma 7.

5 Concluding remarks

We end with some remaining open questions on finite-state verifiers.

Focusing on verifiers which halt with probability 1, Dwork and Stockmeyer [7] proved that the class IP(con-space, poly%-private-coins, poly%-time) contains all context-free languages and some NP-complete languages, but whether $P \subseteq IP(con\text{-space}, poly%-private-coins}, poly%-time)$ or not is still an open question. On the other hand, our Theorem 9 establishes that polynomial-time finite-state machines (even those with our additional restrictions on private-coin usage) which are allowed to be tricked into looping with an arbitrarily small probability have the capability to verify all languages in P. Does imposing the requirement that a constant-space machine should halt with probability 1 preclude it from verifying some languages?

It has been proven [12] that every language verifiable with arbitrarily low error by a polynomial-time verifier (with no bound imposed on the space consumption) is also verifiable with such a verifier that has perfect completeness. We do not know whether a counterpart of this result holds for finite-state verifiers. (Note that the construction of Lemma 10 creates verifiers without perfect completeness.)

It would be interesting to characterize the classes that are associated by reducing the public coin budgets in Section 4, like $\mathrm{IP}_*(\text{con-space}, \text{con-private-coins}, \log^{\%}$ -public-coins, ∞ -time). Does Condon and Ladner's result showing that logarithmic-space verifiers that flip only logarithmically many public coins cannot verify any language outside the class LOGCFL [4] have a counterpart for the constant-space case?

We also note that the following question, posed more than 30 years ago by Dwork and Stock-meyer [7], is still open:

Is there a nonregular language in IP(con-space, poly_%-public-coins, poly_%-time)?

Acknowledgments

We thank the user with the pseudonym obscurans at Mathematics Stack Exchange for their help with the analysis in the proof of Lemma 2.

References

- [1] L. Babai. Trading group theory for randomness. In *Proceedings of the Seventeenth Annual ACM Symposium on Theory of Computing*, STOC '85, pages 421–429, New York, NY, USA, 1985. Association for Computing Machinery.
- [2] A. Condon. Computational Models of Games. MIT Press, 1989.
- [3] A. Condon. The complexity of space bounded interactive proof systems. In *Complexity Theory:* Current Research, pages 147–189. Cambridge University Press, USA, 1993.
- [4] A. Condon and R. Ladner. Interactive proof systems with polynomially bounded strategies. Journal of Computer and System Sciences, 50(3):506–518, 1995.
- [5] A. Condon and R. J. Lipton. On the complexity of space bounded interactive proofs. In 30th Annual Symposium on Foundations of Computer Science, pages 462-467, 1989. (Extended version: https://www.cs.ubc.ca/~condon/papers/condon-lipton89.pdf).
- [6] T. H. Cormen, C. E. Leiserson, R. L. Rivest, and C. Stein. Introduction to Algorithms. MIT Press, 3rd edition, 2009. ISBN 0262033844.

⁸Dwork and Stockmeyer do construct finite-state verifiers that halt with probability 1 for all languages in DTIME($2^{O(n)}$), but those verifiers have double exponential runtime. [7]

- [7] C. Dwork and L. Stockmeyer. Finite state verifiers I: The power of interaction. J. ACM, 39(4): 800–828, Oct. 1992. ISSN 0004-5411.
- [8] L. Fortnow and C. Lund. Interactive proofs and alternating time-space complexity. *Theoretical Computer Science*, 113:55–73, 1993.
- [9] M. U. Gezer and A. C. C. Say. Constant-space, constant-randomness verifiers with arbitrarily small error. *Information and Computation*, 288:104744, 2022.
- [10] M. U. Gezer and A. C. C. Say. Finite state verifiers with both private and public coins. In G. Castiglione and M. Sciortino, editors, Proceedings of the 24th Italian Conference on Theoretical Computer Science, Palermo, Italy, September 13–15, 2023, volume 3587 of CEUR Workshop Proceedings, pages 241–253. CEUR-WS.org, 2023.
- [11] M. U. Gezer, Ö. Dolu, N. Ersoy, and A. C. C. Say. Real-time, constant-space, constant-randomness verifiers. *Theoretical Computer Science*, 976:114155, 2023.
- [12] O. Goldreich, Y. Mansour, and M. Sipser. Interactive proof systems: Provers that never fail and random selection. In 28th Annual Symposium on Foundations of Computer Science (SFCS 1987), pages 449–461, 1987.
- [13] S. Goldwasser and M. Sipser. Private coins versus public coins in interactive proof systems. In Proceedings of the Eighteenth Annual ACM Symposium on Theory of Computing, pages 59–68. Association for Computing Machinery, 1986.
- [14] S. Goldwasser, S. Micali, and C. Rackoff. The knowledge complexity of interactive proof systems. SIAM Journal on Computing, 18(1):186–208, 1989.
- [15] S. Goldwasser, Y. T. Kalai, and G. N. Rothblum. Delegating computation: Interactive proofs for muggles. *J. ACM*, 62(4), Sept. 2015.
- [16] J. Hartmanis. On non-determinancy in simple computing devices. *Acta Informatica*, 1(4): 336–344, 1972.
- [17] J. Kemeny and J. Snell. Finite Markov Chains. Van Nostrand, 1960. ISBN 9780442043285.
- [18] R. E. Ladner, R. J. Lipton, and L. J. Stockmeyer. Alternating pushdown automata. In Proceedings of 19th Annual IEEE Symposium on Foundations of Computer Science, pages 92–106. IEEE Computer Society, oct 1978.
- [19] A. C. C. Say and A. Yakaryılmaz. Finite state verifiers with constant randomness. Logical Methods in Computer Science, 10(3), Aug. 2014.
- [20] A. Shamir. IP = PSPACE. J. ACM, 39(4):869–877, oct 1992.

Appendix

A.1 Proof of Theorem 1

Theorem 1. Any language recognized by a Turing machine that uses at most $\lceil \log n \rceil$ space with a work tape alphabet of size at most 2^c (for some integer constant c > 0) and in t(n) time can also be recognized by a (c+5)-head finite automaton in $t(n) \cdot ((2c+3)n+c+1)$ time.

Proof. Let M be any logarithmic-space Turing machine as described in the theorem statement, and L be its language. Without loss of generality, let the work tape alphabet of M be the set of c-digit binary numbers from 0 to $2^c - 1$ where 0 corresponds to the blank symbol of the alphabet. Each transition of M consists of two parts:

- 1. "Sensing" by the current configuration; which involves taking account of the internal state of the machine and reading the symbols under both the input and work tape heads.
- 2. "Acting" on the current configuration; which can involve changing the internal state, the symbol under the work tape head, and the positions of both the input and work tape heads.

We will construct a (c+5)-head finite automaton R, whose heads will be denoted $h_1, \ldots, h_c, h_\alpha, h_\beta, h_\gamma, h_\delta$, and h_ϵ . R is to recognize L by simulating M. It will maintain the positions of heads h_1 through h_c on the input tape to match the content of M's work tape, such that the ith "row" of the work tape (i.e., the $\lceil \log n \rceil$ -bit string obtained by concatenating the ith bit of each symbol on the work tape) represents the index (location) of h_i on the input tape (with the location of the leftmost cell containing \triangleright denoted 0) in binary and in reverse. h_α will mimic M's input tape head exactly, and h_β will mimic M's work tape head in its position, albeit being on the input tape of R. The remaining three heads will be used to facilitate the manipulations of the indices of h_1 through h_c , necessary to simulate M's memory.

R will simulate each transition of M using a sequence of transitions of its own, as described below, and report the same decision as M. The rest of the proof describes the "sense" and "act" parts of each simulated transition.

Sensing. R traces M's current state in its own finite memory and reads its input tape with h_{α} to obtain the symbol M is scanning with its input head.

Obtaining the symbol under M's work tape head requires sophistication. Let b denote the index of h_{β} , which is at the same index as M's work tape head in M's work tape. To decode the symbol under M's work tape head from the positions of heads h_1 through h_c , essentially, the least significant b-1 bits of their indices will be truncated and the last bits of what remains will be retrieved (which are the bth bits of the original indices). This will be performed sequentially for each head, in order to back-up and restore the original positions of the heads. More precisely, the following routine will be carried out:

- **0.** (At this point, h_{γ} , h_{δ} , and h_{ϵ} are guaranteed to be on \triangleright .)
- **1.** Do the following for $i = 1, \ldots, c$:
- **2.** Walk h_i to the left so that its index (on the input string) at the end of this walk equals $\lfloor j/2^{b-1} \rfloor$ where j is the current index of h_i . To achieve this, repeat the following until h_β reads \triangleright :
- 3. Move h_i to the left such that its index is "halved", *i.e.*, is reduced to $\lfloor j/2 \rfloor$ from its original value j.¹⁰

⁹It is possible to use more heads to perform this in parallel and expedite the sensing routine.

¹⁰In detail, move h_i towards \triangleright while moving h_δ to the right in every second movement of h_i . Then, reidentify h_δ as h_i , and vice versa.

- **4.** Move h_{β} once to the left.
- 5. Check the parity of h_i 's index. If it is odd, "read" the *i*th bit of the symbol under M's simulated work tape head as 0. Otherwise, read it as $1.^{11}$
- **6.** Move h_i and h_β back to their locations at the beginning of the procedure. ¹²

The reader should note that h_1, \ldots, h_c , and h_{β} (after the reidentifications) are located at exactly where they were before the procedure. We will justify the statement at Stage 0 by the end of this proof.

The procedure above completes the "sense" part of the simulation of an M-transition. Sensing the current simulated state and the input symbol can be handled parallelly with the procedure described above, and would incur no additional time cost. "Reading" the symbol under the simulated work tape head with the above procedure incurs up to

$$c \cdot (\underbrace{n + n/2 + n/4 + \dots + 1}_{\text{Stages 2 and 5}}) \le c + 2cn$$

steps.

Acting. Updating the internal state and head positions of the simulated machine is again straightforward: R updates the simulated machine's state in its own finite memory. It also moves h_{α} and h_{β} , which mimic M's input and work tape heads, in the required directions, after simulating the changes in M's work tape contents at that step.

Changing the work tape contents is accomplished as follows. Once again, let b denote the index of h_{β} . To change M's simulated work tape's contents, R updates the positions of h_1 through h_c by moving each of them either 2^b cells to the left (if the bit on that track of the simulated work tape symbol at the index b needs to be changed from 1 to 0) or to the right (if the change is from 0 to 1), or leave them where they are (if no change is needed at the corresponding bit), by doing the following:

- **0.** (At this point, h_{γ} , h_{δ} and h_{ϵ} are guaranteed to be on \triangleright .)
- **1.** Bring h_{ϵ} to the 2^b th index on the input tape. To do so, move h_{ϵ} one step to the right, and then repeat the following until h_{β} reads \triangleright :
- **2.** Move h_{ϵ} to the right such that its index is doubled.¹³
- **3.** Move h_{β} once to the left and h_{γ} once to the right.
- **4.** Reidentify h_{γ} as h_{β} , and vice versa.
- 5. For all the bits of the work tape symbol that should undergo a change, do the following simultaneously:
- 6. Move h_i to the right by 2^b cells if the *i*th bit should change from 0 to 1, and to the left if it should change from 1 to 0. This is performed in tandem with h_{ϵ} moving to the left until it reaches \triangleright .

Once again, the reader should note that the head identified as h_{β} is located at the same place at the start and end of this procedure.

The procedure above completes the "act" part of M's transition's simulation. Changing the simulated current state and the simulated input and work heads' positions would incur a single step by themselves, and are handled in parallel with the above procedure, thereby incurring no additional

¹¹To do the parity check, move h_i to \triangleright ; the parity is odd if h_i reaches there in an odd number of steps, and even otherwise.

¹²To do so, h_{γ} is made to mirror the movements of h_{β} throughout, and h_{ϵ} is made to mirror the movements of h_{i} as it is moving towards ▷ during the first execution of Stage 3. Finally, the mirror-pairs are reciprocally reidentified in Stage 6.

¹³In detail, move h_{ϵ} to \triangleright while moving h_{δ} to the right twice as fast. Then, reidentify h_{δ} as h_{ϵ} , and vice versa.

time. Finally, changing the symbol under the simulated work tape head with the above procedure incurs up to

$$\underbrace{1+2+4+8+\cdots+n}_{\text{Stage 1}} + \underbrace{n}_{\text{Stg. 5}} \le 1+3n$$

steps.

The two routines for reading and changing the simulated memory contents are carried out back to back, and they both leave the heads h_{γ} , h_{δ} , and h_{ϵ} on the left end-marker as they finish. Moreover, these heads are on the left end-marker also when R begins its execution, by definition. The assumptions in Stage 0 of both routines are thus justified.

The two parts together take at most 1+c+3n+2cn steps, which is an upper bound to the multiplicative runtime overhead of R simulating M. Thus, R completes its simulation in $t(n) \cdot (1+c+3n+2cn)$ steps.

A.2 Proof of Lemma 2

Lemma 2. For any constant t > 0, integer-valued function $f(n) \in O(n^t)$, and desired "error" bound $\varepsilon_{premature} > 0$, there exists a probabilistic finite automaton with expected runtime in $O(n^{t+1})$, such that the probability that this machine halts in fewer than f(n) time-steps is $\varepsilon_{premature}$.

Proof. By the implications of $f(n) \in O(n^t)$, let c > 0 and $n_0 > \varepsilon_{\text{premature}}^{-1}$ be integers large enough to satisfy $f(n) \le c \cdot n^t$ for all $n \ge n_0$. The extra constraint upon n_0 to be larger than $\varepsilon_{\text{premature}}^{-1}$ will be evident by the end of the proof. Then, let M_{t,c,n_0} be a constant-space verifier with the following algorithm:

 M_{t,c,n_0} = "On input w:

- 1. If $n < n_0$, pause for f(n) time-steps and halt.
- **2.** If $t \le 1$, move the input head back to \triangleright . Then, move the input head to right until it reaches \triangleleft , while pausing it for c-1 time-steps after each movement, then halt.
- **3.** Repeat the following [t] times:
- **4.** Move the input head to the beginning of w.
- **5.** Perform a random walk with the input head (*i.e.*, repeatedly move the input head towards left or right by the flips of a coin) until the input head reaches \triangleright or \triangleleft . Pause for c-1 time-steps after each step moving the input head.
- **6.** If any of the last $\lceil t \rceil$ random walks have ended with the input head reaching \triangleright , go back to Stage 3.
- **7.** *Halt.*"

Stage 1 starts with $\min(n+2, n_0+1)$ steps to check whether $n < n_0$. If so, M_{t,c,n_0} runs for a total of n+2+f(n) time-steps and then halts, which yields a runtime within desired bounds with certainty.

When $n \ge n_0$ and $t \le 1$, M_{t,c,n_0} halts after running for $2n_0 + cn + 2$ steps in Stages 1 and 2 combined, which is again within the expected and minimum time limits, and with certainty.

The rest of the proof will examine the claims for $n \ge n_0$ and t > 1.

Expected runtime. Each random walk at Stage 5 is commonly known as the *gambler's ruin*, and the probability of each ending at the right-hand side of the input tape is $(n+1)^{-1}$ by their Markov chain analysis [17, Section 7.1]. Consequently, the probability of having a "terminating batch" (*i.e.*, a batch of $\lceil t \rceil$ random walks where each of them ends up at the right-hand side of the input tape) is $(n+1)^{-\lceil t \rceil}$.

The expected number of independent trials to observe a binomial event is the reciprocal of its occurrence probability [6, Section C.4]. Therefore, the expected number of batches until termination is $(n+1)^{\lceil t \rceil}$, and the same for random walks is $\lceil t \rceil \cdot (n+1)^{\lceil t \rceil}$.

The expected runtime of each random walk is cn steps [17, Section 7.1]. The reset in Stage 4 takes exactly $n_0 + 2$ steps before the first random walk, and it is expected to take

$$\underbrace{(n+1)^{-1} \cdot (n+2)}_{\text{resetting from } \triangleleft} + \underbrace{(1-(n+1)^{-1}) \cdot 1}_{\text{resetting from } \triangleright} = 2$$

steps before every subsequent one. Taking Stage 1 into account as well, the expected runtime of M_{t,c,n_0} is

$$\lceil t \rceil \cdot (n+1)^{\lceil t \rceil} \cdot (cn+2) + 2n_0 + 1 \in O(n^{\lceil t \rceil + 1}).$$

Minimum runtime. For simplicity, we note that $(n+1)^{-\lceil t \rceil}$, the probability of a terminating batch occurring, is less than n^{-t} .

It is evident that the execution of a terminating batch takes more than $\lceil t \rceil \cdot nc \ge tnc$ time-steps, and thus, in a time frame of $f(n) \le c \cdot n^t$ steps, there are at most $\frac{n^{t-1}}{t}$ opportunities for terminating batches to occur, which is less than n^{t-1} (given t > 1).

The probability of an event with an occurrence probability less than n^{-t} happening at least once given less than n^{t-1} opportunities, is less than

$$g_t(n) = 1 - (1 - n^{-t})^{n^{t-1}}.$$

Consider its binomial series:

$$g_t(n) = 1 - \left(\sum_{k=0}^{\infty} (-1)^k \cdot \binom{n^{t-1}}{k} \cdot n^{-tk}\right)$$
$$= \frac{n^{t-1}}{n^t} - \frac{n^{t-1}}{n^t} \cdot \frac{n^{t-1} - 1}{2n^t} + \frac{n^{t-1}}{n^t} \cdot \frac{n^{t-1} - 1}{2n^t} \cdot \frac{n^{t-1} - 2}{3n^t} - \cdots$$

Since the series is alternating and the magnitudes are decreasing, we have

$$g_t(n) < \frac{n^{t-1}}{n^t} = n^{-1}.$$

 $g_t(n)$ constitutes an upper bound to the "error" of M_{t,c,n_0} halting sooner than the desired lower bound of f(n) time-steps. Since $g_t(n)$ is monotone decreasing, $g_t(\bar{n}) < \varepsilon_{\text{premature}}$ follows for all $\bar{n} \geq n_0$ (recalling that $n_0 > \varepsilon_{\text{premature}}^{-1}$). With Stage 1 ensuring that M_{t,c,n_0} waits long enough for the strings shorter than n_0 with probability 1, the probability of M_{t,c,n_0} halting prematurely will be less than $\varepsilon_{\text{premature}}$ for strings of any length. Note that $\varepsilon_{\text{premature}}$ can be set to any desired small positive value by simply employing a suitably large number of states (to make n_0 appropriately large) in the implementation of Stage 1.

A.3 The double exponential timer

Let us restate the "tick" subroutine described in Section 2.3. Recall that we also maintain a global Boolean variable T that tracks whether the all red coins flipped since the last reset of this variable came out heads. The integers c and t are parameters that we can use for setting the expected number of ticks.

- 1. Toss a red coin and update the Boolean variable T according to the outcome.
- **2.** Toss $p(n) = c \cdot n^t$ blue coins.
- 3. If any blue coin outcome at Stage 2 was tails, return with the timer still running.
- 4. (Arriving at this stage implies that all the blue coins of Stage 2 came up heads.) If T indicates that one or more red coins flipped since the last reset came out tails, reset T and return with the timer still running.
- **5.** (Arriving at this stage implies that all red coins flipped at Stage 1 since the last reset of T were all heads.) Return and announce that the timer has run out.

To analyze the expected amount of subroutine calls (ticks) before the timer runs out, we define the following random variables to represent the described counts:

- X: Times the subroutine is called.
- Y: Times the tick advances control to Stage 4, i.e., all p(n) blue coins come up heads.
- Z: Number of red coins flipped since the last reset as the tick advances to Stage 4 (at any given time).
- Z_i : Number of red coins flipped since the last reset as the tick advances to Stage 4 for the *i*th time.

Let $\mathbb{E}[O]$ denote the expected value of a random variable O. The expected value that we are after is $\mathbb{E}[X]$.

The probability that any tick advances to Stage 4 (i.e., p(n) blue coins come up heads) is $2^{-p(n)}$. Hence, we expect there to be $2^{p(n)}$ attempts, each one flipping another red coin, before control advances to Stage 4 in some subroutine call. Thus, we have

$$\mathbb{E}[Z] = 2^{p(n)}.$$

We can say the following for X, trivially by the fact that each tick flips exactly one red coin at its Stage 1:

$$X = Z_1 + Z_2 + \dots + Z_Y.$$

Since the expected value operator is a linear operator, we have

$$\mathbb{E}[X] = \mathbb{E}[Z_1] + \mathbb{E}[Z_2] + \dots + \mathbb{E}[Z_Y].$$

Since each $\mathbb{E}[Z_i]$ trivially equals $\mathbb{E}[Z]$, for a particular Y = y, we have

$$\mathbb{E}[X \mid Y = y] = 2^{p(n)} \cdot y,$$

and by the Law of Total Expectation, we have

$$\mathbb{E}[X] = \mathbb{E}[\mathbb{E}[X \mid Y]] = \mathbb{E}\left[2^{p(n)} \cdot Y\right] = 2^{p(n)} \cdot \mathbb{E}[Y].$$

To determine $\mathbb{E}[Y]$, consider a subroutine call in which control has just advanced to Stage 4. Let z denote the number of red coins flipped since the last reset if the program had reached Stage 4 before, and since the beginning of the program's run otherwise. Such a subroutine call will advance further to Stage 5, indicating time-out, if all z coin outcomes were heads. The probability of this is 2^{-z} . If we had Z=z at any given time Stage 4 was reached, then we would expect Stage 5 to be reached after Stage 4 having been reached the following number of times:

$$\mathbb{E}[Y \mid Z = z] = 2^z.$$

Then, by the Law of Total Expectation, we have

$$\mathbb{E}[Y] = \mathbb{E}[\mathbb{E}[Y \mid Z]] = \mathbb{E}\big[2^Z\big].$$

By Jensen's Inequality, we have

$$\mathbb{E}[2^Z] \ge 2^{\mathbb{E}[Z]}.$$

If we multiply both sides with $2^{p(n)}$ and then make the substitutions by the equalities we established, we obtain our lower bound:

$$\begin{split} 2^{p(n)} \cdot \mathbb{E} \big[2^Z \big] &\geq 2^{p(n)} \cdot 2^{\mathbb{E}[Z]}, \\ 2^{p(n)} \cdot \mathbb{E}[Y] &\geq 2^{p(n)} \cdot 2^{2^{p(n)}}, \\ \mathbb{E}[X] &\geq 2^{p(n)} \cdot 2^{2^{p(n)}}. \end{split}$$

This proves that the expected number of subroutine calls is in $2^{2^{\Omega(n^t)}}$.

A.4 Proof of Lemma 7

Lemma 7. The following is true for all functions s(n), f(n), g(n), and t(n):

$$\begin{split} \mathrm{IP}_*(O(s(n))\text{-space}, O(f(n))\text{-private-coins}, O(g(n))\text{-public-coins}, O(t(n))\text{-time}) \subseteq \\ \mathrm{IP}_*(O(s(n))\text{-space}, O(f(n)+g(n))\text{-private-coins}, O(t(n))\text{-time}). \end{split}$$

This inclusion also holds for the IP(...) variants of the classes, and when worst-case time bounds are replaced with those corresponding to expected usage.

Proof. Let $V_1 = (Q_1, \Sigma, \Phi, \Gamma_1, \delta_1, q_0)$ be a verifier that uses O(f(n)) private and O(g(n)) public random bits for some functions f and g. We construct a verifier $V_2 = (Q_2, \Sigma, \Phi, \Gamma_2, \delta_2, q_0)$ that uses O(f(n) + g(n)) private random bits and no public coins. The protocol that V_2 engages in with the prover is almost identical to that of V_1 , with the exception that V_1 's public coin outcomes are emulated by private random bits of V_2 that are sent through the communication cell.

 Q_2 is a superset of Q_1 , where all the states that flip public coins in V_1 have been rebranded as states that flip only private coins in V_2 . V_2 's program inherits all transitions of V_1 emanating from states that do not flip public coins. V_2 simulates each transition of V_1 from a state q that involves such a flip as described below.

If q does not flip a private coin, the V_1 transition (cf. Table 1)

$$\delta_1(q, \sigma, \phi, \gamma, b_{\text{pub}}) = (q', \phi', \gamma', d_i, d_w)$$

is replaced in V_2 by the transition

$$\delta_2(q, \sigma, \phi, \gamma, b_{\text{pri}}) = (q', \phi', (\gamma', b_{\text{pri}}), d_i, d_w),$$

making use of an additional symbol in Γ_2 that conveys both the original communication symbol γ' and the simulated public coin outcome in a single package. Note that q remains a communication state in V_2 in this case.

If, on the other hand, q flips a private coin as well, the corresponding V_1 transition

$$\delta_1(q, \sigma, \phi, \gamma, b_{\text{pri}}, b_{\text{pub}}) = (q', \phi', \gamma', d_i, d_w)$$

is simulated by two V_2 transitions

$$\delta_2(q, \sigma, \phi, \gamma, b_{\text{pri},1}) = ((q, b_{\text{pri},1}), \phi, 0, 0),$$

$$\delta_2((q, b_{\text{pri},1}), \sigma, \phi, \gamma, b_{\text{pri},2}) = (q', \phi', (\gamma', b_{\text{pri},2}), d_i, d_w),$$

that flip two private coins, utilize new states in Q_2 to store the first coin outcome temporarily, and then send the required information through the communication cell. In this case, q becomes a non-communication state in V_2 . The two new states (q,0) and (q,1) (introduced for each such q) are branded as communication states that also flip (only) private coins.

For each public coin flip removed from V_2 's transition function (and thereby its execution), exactly one private coin flip is introduced. V_2 emulates V_1 , operating with the same verification error. Its runtime is at most double that of V_1 . V_2 uses the same amount of work tape as V_1 .