

Clickbait Detection via Large Language Models

Han Wang¹, Yi Zhu^{1(*)}, Ye Wang¹, Yun Li¹, Yunhao Yuan¹ and Jipeng Qiang¹

¹School of Information Engineering, Yangzhou University, Yangzhou, China

zhuyi@yzu.edu.cn, wanghanhan0102@163.com, wangye_lj@163.com, {liyun, yhyuan, jpqiang}@yzu.edu.cn

Abstract

Clickbait, which aims to induce users with some surprising and even thrilling headlines for increasing click-through rates, permeates almost all on-line content publishers, such as news portals and social media. Recently, Large Language Models (LLMs) have emerged as a powerful instrument and achieved tremendous success in a series of NLP downstream tasks. However, it is not yet known whether LLMs can be served as a high-quality clickbait detection system. In this paper, we analyze the performance of LLMs in the few-shot and zero-shot scenarios on several English and Chinese benchmark datasets. Experimental results show that LLMs cannot achieve the best results compared to the state-of-the-art deep and fine-tuning PLMs methods. Different from human intuition, the experiments demonstrated that LLMs cannot make satisfied clickbait detection just by the headlines.

1 Introduction

With the rapid development of online applications, some content publishers try to utilize clickbait for generating profits [Chen *et al.*, 2015]. Clickbait refers to deliberately enticing users to click with some curious and chilling headlines, which are always unrelated to the real content or even the advertising promotion [Chakraborty *et al.*, 2016]. The popularity of clickbait will inevitably lead to the experience degradation or even the disgust of users, there is an urgent demand to develop effective automatic clickbait detection methods [Liu *et al.*, 2022].

In the last decade, the research methods for clickbait detection evolved from feature engineering to neural networks and, more recently, into Pre-trained Language Models (PLMs). Feature engineering methods extracted features such as semantic and linguistic features for detection [Biyani *et al.*, 2016; Wei and Wan, 2017]. The deep neural network methods can learn more abstract and higher-level features by disentangling explanatory factors of variations behind news titles and content for clickbait detection [Yoon *et al.*, 2019; Zheng *et al.*, 2021]. Recently, fine-tuning PLMs methods, such as BERT [Devlin *et al.*, 2018], has shown superiority

in clickbait detection tasks. However, feature engineering-based methods and deep neural networks typically require large-scale labeled data since the detection is regarded as a classification method. In the PLMs methods, the huge gap between pre-training and fine-tuning prevents detection tasks from fully utilizing pre-training knowledge.

More recently, Large Language Models (LLMs) have demonstrated the powerful ability in various NLP downstream tasks [Brown *et al.*, 2020; Chowdhery *et al.*, 2022; Thoppilan *et al.*, 2022], which can achieve awesome performance even in the few-shot or even zero-shot scenarios. Nevertheless, it remains unclear how LLMs perform in clickbait detection tasks compared to current methods. To address this issue, in this paper, we conduct a systematic evaluation of the few-shot and zero-shot learning capabilities of LLMs. The experiments are validated on both English and Chinese open datasets, and we conducted an empirical comparison of the performance between ChatGPT with the GPT3.5 model (gpt-3.5-turbo) and other state-of-the-art methods such as prompt-tuning.

To the best of our knowledge, this is the first attempt to validate the performance of LLMs on clickbait detection, we provide a preliminary evaluation including detection results and robustness. The key findings and insights are summarized as follows:

- LLMs achieves unsatisfying results in the few-shot and zero-shot scenarios compared to the state-of-the-art clickbait detection methods. We found that fine-tuning PLMs and prompt-tuning can achieve better results just based on the titles, which is consistent with humans in the real-world.
- ChatGPT is a monolithic model capable of supporting multiple languages, which makes it a comprehensive multilingual clickbait detection technique. After evaluating the performance of ChatGPT on the task of clickbait detection across two languages (English and Chinese), we observed that it achieved stable results on almost all evaluation metrics. This also confirms that LLMs can be adapted to other languages.

It is worth mentioning that the source code and all the results of this paper are available at <https://github.com/zhuyiYZU/chatGPTforClickbait>.

2 Related Work

2.1 Clickbait Detection

Clickbait detection is an emerging field that has attracted increasing attention in recent years. On most online services, such as e-commerce, social media, and news portals, more clicks mean more profit and commercial revenue. Early clickbait detection methods mainly focus on extracting a variety of features for detection tasks, such as semantic [Rony *et al.*, 2017], linguistics [Blom and Hansen, 2015], and multi-modal features [Chen *et al.*, 2015]. However, these methods require expert knowledge for feature selection, and the handcrafted features are limited in representing more abstract and higher-level information.

In recent years, deep neural network models facilitate crossing and combination among even more diverse and sophisticated features, which has shown fairly good performance in clickbait detection. The popular deep neural networks, such as Recurrent Neural Networks (RNN) [Anand *et al.*, 2017], Convolutional Neural Networks (CNN) [Agrawal, 2016], Attention Mechanism [Mishra *et al.*, 2020], and Graph Attention Networks [Liu *et al.*, 2022], have already been devoted to the clickbait detection tasks. Despite the success of deep learning methods, due to the requirements on large-scale labeled training datasets, lead to high costs in collecting eligible training data. Recently, some domain adaptation [López-Sánchez *et al.*, 2018] and data augmentation [Yoon *et al.*, 2019] methods have been proposed to address the issues, however, these methods may bring additional noise in detection tasks.

More recently, pre-trained language models (PLMs) such as BERT [Devlin *et al.*, 2018], RoBERTa [Liu *et al.*, 2019], and T5 [Raffel *et al.*, 2020] have emerged as a powerful instruments for language understanding and generation. Through the fine-tuning PLMs on the special downstream task, the rich knowledge distributed in PLMs can be stimulated to better serve downstream tasks including clickbait detection [Indurthi *et al.*, 2020; Yi *et al.*, 2022]. Despite the success of fine-tuning PLMs, some recent studies find one of its critical challenges is the significant gap of objective forms in pre-training and fine-tuning, which restricts taking full advantage of knowledge in PLMs.

2.2 Large Language Models

Represented by GPT-3 [Brown *et al.*, 2020], Large Language Models (LLMs) have achieved superior performance, especially in few-shot learning scenarios [Brown *et al.*, 2020; Chowdhery *et al.*, 2022; Thoppilan *et al.*, 2022]. Different from the previous PLMs methods, LLMs has two distinct advantages. The first is the larger scale, LLMs have a much larger scale in terms of model parameters and training data. Secondly, without fine-tuning PLMs, LLMs can prompt few-shot learning that requires no additional neural layer and shows excellent performance. However, there is no work on the capabilities of LLMs on clickbait detection tasks.

3 Methodology

Through the rich knowledge in upstream large models, they can achieve excellent performance in downstream tasks with

low resources. Considering the lack of large-scale training corpus for clickbait detection tasks, we will test the performance of LLMs in few-shot and zero-shot scenarios on clickbait detection.

LLMs typically use prompts (i.e. specific templates) to guide the model in predicting output or answers, without requiring specific training on the data. Utilizing this form of prompt, we conducted experiments with different prompts on OpenAI’s largest available model GPT3.5 (gpt-3.5-turbo) for ChatGPT.

3.1 Prompt

To stimulate the rich knowledge distributed in LLMs, we manually designed the prompts for validating the performance of clickbait detection. The details of the prompts are illustrated in Table 1. For the two prompts, {Clickbait Sentence} and {Not-Clickbait Sentence} refer to the input sentence, {Yes, it is a clickbait} and {No, it is not a clickbait} are the corresponding labels respectively. {Results} is that place that carries the outputs of LLMs.

Table 1: The hand-crafted prompts for clickbait detection.

Prompts	
P1	I want you to detect whether the input sentence is clickbait or not. Input: {Clickbait Sentence} Output: {Yes, it is a clickbait}
	Input: {Not-Clickbait Sentence} Output: {No, it is not a clickbait}
	... Input: {Clickbait or Not-Clickbait Sentence} Output: {Results}
P2	Sentence: {Clickbait Sentence} Question: Detect the above sentence is clickbait or not. Answer: {Yes, it is a clickbait}
	Sentence: {Not-Clickbait Sentence} Question: Detect the above sentence is clickbait or not. Answer: {No, it is not a clickbait}
	... Sentence: {Clickbait or Not-Clickbait Sentence} Question: Detect the above sentence is clickbait or not. Answer: {Results}

In the first prompt (P1), the {guide-input-output} pattern is employed to guide LLMs for detecting clickbaits. In the second prompt (P2), the {sentence-question-answer} pattern is utilized to detect clickbait in the form of a question. It is worth mentioning that the specialized guide words, such as "Output:" and "Answer:", are added to the prompts, then the clickbait detection is regarded as the close-style task for LLMs, which ensures to achievement of a unique output. When performing multilingual clickbait detection tasks, we translate these two prompts into Chinese used in specific tasks in Table 2.

Table 2: The hand-crafted prompts for clickbait detection.

	提示
P1	请帮我检测
	以下输入是或不是点击诱饵。
	输入: {点击诱饵句子}
	输出: {是, 这是一个点击诱饵}
P2	输入: {非点击诱饵句子}
	输出: {不, 这不是一个点击诱饵}
	...
	输入: {点击诱饵或非点击诱饵句子}
	输出: {结果}
P1	句子: {点击诱饵句子}
	问题: 检测上面的句子是或不是点击诱饵。
	回答: {是, 这是一个点击诱饵}
	句子: {非点击诱饵句子}
P2	问题: 检测上面的句子是或不是点击诱饵。
	回答: {不, 这不是一个点击诱饵}
	...
	句子: {点击诱饵或非点击诱饵句子}
	问题: 检测上面的句子是或不是点击诱饵。
	回答: {结果}

3.2 Zero-shot

In the clickbait detection experiments in zero-shot scenarios, just one {guide-input-output} or {sentence-question-answer} pattern is directly input into the LLMs for the detection result.

3.3 Few-shot

In the few-shot scenario, some instances follow the {guide-input-output} or {sentence-question-answer} pattern provided as the training data for the detection tasks. Notably, in the first prompt (P1), the guidance does not need to be repeated, only the input-output is repeated for some instance sentences and corresponding labels are stacked. In the second prompt (P2), the sentence-question-answer is repeated for each sample as training data.

4 Experiments

4.1 Datasets

To evaluate the performance of LLM for clickbait detection in English and Chinese, we conducted experiments on seven datasets. The DL-Clickbait (DLC), Clickbait news detection (CND), and SC-Clickbait (SCC) are three well-known public English datasets. Sina, Tencent, WeChat, and Paper are four Chinese clickbait detection datasets. The statistical details of all the datasets are presented in Table 3.

4.2 Baseline

We compare our ChatGPT with the following deep neural network and fine-tuning PLMs methods.

CNN [Agrawal, 2016] CNN utilizes kernels with different sizes to find various features from the input text. These features are automatically detected and are used to train a neural network for the corresponding task. It understands the input

text from different perspectives, and can be applied to various nature language processing tasks.

BiLSTM [Kumar *et al.*, 2018] A bidirectional LSTM with an attention mechanism to learn the extent to which a word contributes to the clickbait score of a social media post in a different way. It used a Siamese net to detect similarities between the source and target data.

GATED_CNN [Yang *et al.*, 2019] The method can be stacked to represent large context sizes and extract hierarchical features over larger and larger contexts with more abstractive features.

FAST_TEXT [Joulin *et al.*, 2016] FAST_TEXT is a text-classification method, and the sequence of words is considered in it, which is a model learning distributed representations of words based on ordered words.

BERT [Devlin *et al.*, 2018] The BERT method uses words and sentences to distinguish the context of words in a sentence.

MFWCD-BERT [Liu *et al.*, 2022] The multi-feature WeChat clickbait detection method, which incorporates semantic, syntactic, and auxiliary information, achieves excellent performance. It leverages an enhanced Graph Attention Network (GAT) to aggregate title and local syntactic structures, using an attention mechanism to capture valuable structural features.

PT [Liu *et al.*, 2023] PT is a technique known as prompt tuning, which incorporates a cloze-style task during the model fine-tuning process. This approach enables a more effective utilization of pre-training information, thereby further enhancing the model’s performance in few-shot learning scenarios.

PEPT [Wu *et al.*, 2023] PEPT is a method that introduces prompt learning into clickbait detection. It effectively performs classification tasks and part-of-speech tagging using pre-trained language models by training them on specific tasks. It’s worth noting that this approach is inspired by typical grammar and semantic features of clickbait, and it achieves grammar-guided semantic understanding, which can perform well in both low-resource and full-scale scenarios.

4.3 Implementation Details and Evaluation Metrics

Few-shot settings

In the experiments, we randomly selected K (5,10,20) instances as the training set for our ChatGPT, and selected part of the samples as the test set. Considering that too few training samples may greatly affect the effectiveness of the baselines, we select different training samples from different datasets, where the number of training samples is 200/300/600, 300/600/1200, and 500/1000/2000 for English datasets (DL-Clickbait, CND, and SC-Clickbait datasets) and 200/400/800, 400/800/1600, 400/800/1600 and 800/1600/3200 for Chinese datasets(Sina, Tencent, WeChat and Paper), corresponding to 5/10/20 shots. Considering that different choices of few-shot training during training affect the test results, we repeatedly sample the same data on K random seeds simultaneously and calculate their mean values as reported. Considering more intuitive approaches to training the ChatGPT model, here are a few specific examples. As

Table 3: Statistics of the news datasets. "#” and "avg.#” denote "the number of” and "the average number of”.

Statistic	DLC	CND	SCC	Sina	Tencent	WeChat	Paper
#total headline	2345	8324	32000	1912	2546	2800	30800
#train sets	1638	5801	22400	1338	1782	1960	21560
#test sets	707	2523	9600	574	764	840	9240
avg.# words per sentence	11	13	9	21	25	21	22

shown in Figure 1, examples are provided for training the model using few-shot (5-shot) methods, along with the corresponding results.

Parameter settings

For using ChatGPT for clickbait detection, we have chosen the latest available LLMs GPT-3.5 (gpt-3.5-turbo), to interact with. To establish communication with the model, we have opted to use the ChatGPT API. First, we need to register and apply for a ChatGPT API key from OpenAI. This API key will be used to access the API. Then, we send an HTTP POST request to the API endpoint to engage in a conversation with the ChatGPT model. In this process, we set up an array of messages, including user messages and system messages, corresponding to the two roles, "user" and "assistant". Based on the input of users, messages will be alternately added to the array as user messages and system messages. Subsequently, we extract the assistant’s responses from the JSON response returned by the API. It’s important to note that using the ChatGPT API incurs a cost, and the text content of API requests must not exceed the maximum token limit of the model, which, in this case, is 4096 tokens, roughly equivalent to 70 news headlines. Additionally, there are rate limits for API requests, with a maximum of three news headlines per minute and no more than two hundred requests in a day. In addition, for the few-shot experiments, we select a few sentences that ChatGPT got wrong from the seven data sets mentioned above as examples of clickbait detection. Figure 1 shows ChatGPT detecting clickbait errors.

We also provide a detailed description of the parameter settings for our text classification models (CNN, BiLSTM, and FastText) used in the clickbait detection task. For the CNN model, we employ three convolutional layers, each with a kernel size of 3x3 and 64, 128, and 256 kernels, respectively. The stride is set to 1, and padding is "same." Following each convolutional layer, we incorporate max-pooling layers with a kernel size of 2x2 and a stride of 2. After the convolutional layers, we have two fully connected layers with 512 and 256 neurons, respectively. Additionally, we apply ReLU activation functions after each convolutional and fully connected layer. For the BiLSTM model, we utilize two layers of bidirectional LSTM, with 64 and 128 LSTM units in each layer. Since the BiLSTM layers are bidirectional, the total number of LSTM units is 256 (128 * 2). After the BiLSTM layers, we add two fully connected layers with 512 and 256 neurons, respectively. Similarly, ReLU activation functions are applied after each fully connected layer. In the case of the FastText model, we represent the text data as bag-of-words vectors. We set up a fully connected layer with two neurons, corre-

sponding to the binary classification task. After the fully connected layer, we use the Sigmoid activation function. For all three models, we employ binary cross-entropy loss functions as the objective functions to measure model performance. We use the Adam optimizer, with a typical training batch size of 64 and 50 training epochs. We conducted hyperparameter tuning, including learning rates, the number of convolutional kernels, LSTM unit numbers, bag-of-words sizes, and word vector dimensions, selecting the best hyperparameter values through random search.

For the BERT model, we employed the BERT-base-uncased variant and conducted training over 10 epochs using a batch size of 32. For training prompt-based learning models (PT, PEPT), we utilized the xlm-roberta-large pretrained language model. To prevent overfitting, we applied a dropout rate of 0.5 during the training process. We configured the learning rate at 3e-5 and set the batch size to 16, incorporating a weight decay of 1e-5. Additionally, we performed validation steps to fine-tune the model’s hyperparameters. Across all our small-scale experiments, we maintained a consistent number of 10 epochs for comprehensive training and reliable results. We employed the Adam optimizer to optimize the model parameters.

The experimental outcomes were derived from a server configuration featuring an NVIDIA GeForce RTX 3090 Founders Edition GPU, an Intel(R) Core(TM) i9-10980XE CPU clocked at 3.00 GHz, and 125 GB of RAM.

Evaluation metrics

To test the effect of detection, we conduct four evaluation metrics to evaluate our method in experiments, such as accuracy, precision, recall and F1-score.

accuracy The accuracy can be defined as the ratio of correctly predicted samples to the total number of samples.

$$Acc = \frac{TP + TN}{TP + TN + FP + FN} \quad (1)$$

precision The positive prediction rate can be defined as the ratio of correctly predicted positive samples to the total number of positive samples in the prediction.

$$Pre = \frac{TP}{TP + FP} \quad (2)$$

recall The positive precision can be defined as the ratio of correctly predicted positive samples to the total number of samples labeled positive.

$$Rec = \frac{TP}{TP + FN} \quad (3)$$

WA I want you to detect whether the input sentence is clickbait or not.
 Input: {Saudi-led airstrikes in Yemen kill at least 5, damage UNESCO site}
 Output: {No, it is not a clickbait}
 Input: {German chancellor Angela Merkel urges Europe to take MORE refugees as she: Islam 'isn't the source of terror?'}
 Output: {No, it is not a clickbait}
 Input: {Manus Island, Nauru refugees fingerprinted as processing for US-Australia resettlement deal begins}
 Output: {No, it is not a clickbait}
 Input: {Revealed: The true scale of Tony Blair's global business empire}
 Output: {No, it is not a clickbait}
 Input: {How Mike Pence is poised to be a uniquely powerful VP}
 Output: {No, it is not a clickbait}
 Input: {Ra-ra-ah-ah: The 7 Best Lady Gaga Songs for Karaoke}
 Output: {Yes, it is a clickbait}
 Input: {Clemson Tigers 'Get Back' Coach Puts in Work During the Offseason}
 Output: {Yes, it is a clickbait}
 Input: {8 Changes Your Bedroom Needs So You Can Sleep Better}
 Output: {Yes, it is a clickbait}
 Input: {Self-charging battery could put an end to your phone dying}
 Output: {Yes, it is a clickbait}
 Input: {There is only one man worse at Twitter than Donald Trump}
 Output: {Yes, it is a clickbait}
 Input: {Texas Woman Sentenced to 8 Years in Prison for Illegal Voting}
 Output:

WA 请帮我检测以下输入是或不是点击诱饵。
 输入: {官方: 加强县级医院重症和传染病医疗资源建设}
 输出: {不, 这不是一个点击诱饵}
 输入: {张文宏: "刀片株""干饭株"仍属于轻症}
 输出: {不, 这不是一个点击诱饵}
 输入: {偷拍张家慧打麻将致其落马, "包工头"被判无罪}
 输出: {不, 这不是一个点击诱饵}
 输入: {跨年夜最冷大城市排行榜出炉 这些地区降温明显}
 输出: {不, 这不是一个点击诱饵}
 输入: {多地公布新冠感染率调查情况, 最高在60%以上}
 输出: {不, 这不是一个点击诱饵}
 输入: {核酸检测公司的2023年, 变天了}
 输出: {是, 这是一个点击诱饵}
 输入: {“泄透式”辞职成2022反腐热词, 释放出什么信号?}
 输出: {是, 这是一个点击诱饵}
 输入: {新冠变异株奥密克戎亚型XBB更危险吗}
 输出: {是, 这是一个点击诱饵}
 输入: {北京日报: "限制中国旅客"再显某些人的双标与无能}
 输出: {是, 这是一个点击诱饵}
 输入: {“新中国设计第一人”周令钊去世, 享年104岁}
 输出: {是, 这是一个点击诱饵}
 输入: {淘宝可以改账号名了! 网友: 终于可以"重新做人"了}
 输出:

No, it is not a clickbait

不, 这不是一个点击诱饵。

(a) English P1

(b) Chinese P1

WA Sentence: {Parma man faces possible felony for making parody Parma Police Department Facebook page}
 Question: Detect the above sentence is clickbait or not.
 Answer: {No, it is not a clickbait}
 Sentence: {Illinois Senate votes to decriminalize possession of up to 10 grams of?marijuas}
 Question: Detect the above sentence is clickbait or not.
 Answer: {No, it is not a clickbait}
 Sentence: {At least 33 US cities used water testing 'cheats' over lead concerns}
 Question: Detect the above sentence is clickbait or not.
 Answer: {No, it is not a clickbait}
 Sentence: {Company that hiked drug price 5,000% now under antitrust?probe}
 Question: Detect the above sentence is clickbait or not.
 Answer: {No, it is not a clickbait}
 Sentence: {Man dies after being run over by WWII tank on Jelly Belly chairman's property}
 Question: Detect the above sentence is clickbait or not.
 Answer: {No, it is not a clickbait}
 Sentence: {This is why your laptop charging cord has that little cylinder!}
 Question: Detect the above sentence is clickbait or not.
 Answer: {Yes, it is a clickbait}
 Sentence: {This Is Why Your Nose Looks Like It Does}
 Question: Detect the above sentence is clickbait or not.
 Answer: {Yes, it is a clickbait}
 Sentence: {Why releasing 1.5 million balloons at once is a BAD IDEA!}
 Question: Detect the above sentence is clickbait or not.
 Answer: {Yes, it is a clickbait}
 Sentence: {This unlikely tactic could help you dominate the world of?Scrabble}
 Question: Detect the above sentence is clickbait or not.
 Answer: {Yes, it is a clickbait}
 Sentence: {Pressing This Spot on Your Forehead Will Help You Cure Headaches and Migraines (13 Pics)}
 Question: Detect the above sentence is clickbait or not.
 Answer: {Yes, it is a clickbait}
 Sentence: {Guess Who's Complaining About Obama's New Overtime Regulations Now}
 Question: Detect the above sentence is clickbait or not.
 Answer:

WA 句子: {回顾全国各地首例病童: 新冠病毒从武汉到覆盖全国花了20天}
 问题: 检测上面的句子是或不是点击诱饵。
 回答: {不, 这不是一个点击诱饵}
 句子: {错过的救治和照料机会: 父亲被隔离后17岁脑瘫儿之死}
 问题: 检测上面的句子是或不是点击诱饵。
 回答: {不, 这不是一个点击诱饵}
 句子: {一个高铁"密切接触者"的自白: 他就坐在我旁边, 没戴过口罩}
 问题: 检测上面的句子是或不是点击诱饵。
 回答: {不, 这不是一个点击诱饵}
 句子: {黄冈确诊病例过千, 市长称防控不力, 曾一天问责135人}
 问题: 检测上面的句子是或不是点击诱饵。
 回答: {不, 这不是一个点击诱饵}
 句子: {武汉接到两个硬任务: 收治所有确诊病人 三天内检测全部疑似病例}
 问题: 检测上面的句子是或不是点击诱饵。
 回答: {不, 这不是一个点击诱饵}
 句子: {离开"思想道德课"后自杀的年轻人}
 问题: 检测上面的句子是或不是点击诱饵。
 回答: {是, 这是一个点击诱饵}
 句子: {风暴中的獐子岛, 有员工"希望公司尽快倒闭"}
 问题: 检测上面的句子是或不是点击诱饵。
 回答: {是, 这是一个点击诱饵}
 句子: {权健董事长束昱辉被公诉: 部分火疗馆还在营业, 有信徒仍不信其骗人}
 问题: 检测上面的句子是或不是点击诱饵。
 回答: {是, 这是一个点击诱饵}
 句子: {90后美女去植发被剃成秃子, 诊所: 不能植, 你有抑郁症}
 问题: 检测上面的句子是或不是点击诱饵。
 回答: {是, 这是一个点击诱饵}
 句子: {一文读懂神秘人叛子"梅姨": 记住这张脸, 找到她!}
 问题: 检测上面的句子是或不是点击诱饵。
 回答: {是, 这是一个点击诱饵}
 句子: {劳动课回归, 你家小朋友今天煮饭了吗?}
 问题: 检测上面的句子是或不是点击诱饵。
 回答:

Yes, it is a clickbait.

{不, 这不是一个点击诱饵}

(c) English P2

(d) Chinese P2

Figure 1: The example of ChatGPT detecting clickbait errors.

Table 4: The Accuracy, Precision, Recall, F1-scores results (%) on both English (DLC, CND and SCC) and Chinese (Sina, Tencent, Wechat and Paper) clickbait datasets in zero-shot scenario.

metrics	Dataset						
	CND	SCC	DLC	Sina	Tencent	Wechat	Paper
Acc	63.66	53.87	76.44	61.23	53.80	62.02	63.59
Pre	47.88	53.69	75.87	54.61	53.13	57.71	61.71
Rec	74.79	49.68	77.53	57.84	64.40	90.00	71.54
F1	58.38	51.61	76.69	57.18	58.22	70.33	66.26

F1-score The F1-score can be defined as the harmonic average of precision and recall.

$$F1 = \frac{2 \times Pre \times Rec}{Pre + Rec} \quad (4)$$

4.4 Experimental Results

The main results of the experiments on clickbait detection in English and Chinese datasets on zero-shot and few-shot scenarios are listed in Tables 4, 5 and 6 respectively. We can see that the performance of ChatGPT has not demonstrated the best results on all four metrics over the seven datasets. Compared to the deep neural networks and fine-tuning PLMs, ChatGPT has a lot of room for improvement in clickbait detection. In addition, with the increase of pre-trained information, the effectiveness of clickbait detection, sometimes, is worse. Therefore, we can observe that a small amount of pre-training information does not significantly impact the performance of ChatGPT in detecting clickbait. Moreover, we can observe that ChatGPT can achieve stable results on almost all evaluation metrics. The results confirmed that LLMs can be adapted to other languages, and ChatGPT is a monolithic model capable of supporting multiple languages, which makes it a comprehensive multilingual clickbait detection technique.

Moreover, we have provided a detailed analysis of four news headlines where ChatGPT correctly classified them using the prompt method but made errors when detecting clickbait. For example, given the English not-clickbait headline "Tigers 'starved to death' to make \$500 aphrodisiac wine with their bones," ChatGPT misclassified it as clickbait. This is primarily because, first, the headline touches on sensitive topics such as animal abuse, illegal wildlife trade, and ethical controversies, which can easily elicit emotional responses from readers. Secondly, terms like "starved to death" and "aphrodisiac" are strong verbs and adjectives often used exaggeratedly or emotionally, and these words may match common vocabulary found in clickbait articles. Thirdly, in the absence of additional context, ChatGPT may be more inclined to categorize sentences with controversial or extreme characteristics as clickbait. For the Chinese not-clickbait headline "扬州通报'网传副市长与副局长生活作风问题': 建议对二人免职" (Yangzhou reports 'alleged misconduct in the personal conduct of deputy mayor and deputy director': Suggests dismissal of the two individuals.), ChatGPT misclassified it as clickbait. This is mainly because it is an attention-grabbing topic with relatively complex grammatical structures, including multiple parallel phrases and verb phrases.

This complexity can lead the model to struggle in interpreting the sentence. It's also important to note that the phrase "网传" (spread on the internet) may have contributed to ChatGPT's classification as spreading false information. For the English clickbait headline "This is America's favorite fast food restaurant," ChatGPT misclassified it as not-clickbait. This is primarily because it is a topic related to American food culture and consumption habits, falling under the category of everyday life. Furthermore, the headline uses proper grammatical structure to pose a clear question, making it appear as a reasonable query rather than clickbait. For the Chinese clickbait headline "与你有关! 一批重要国家标准, 今天发布!" (Related to You! A batch of important national standards released today!), ChatGPT misclassified it as not-clickbait. This is mainly because national standards and regulations are a topic of practical significance, and the proper grammatical structure is used to present a statement. These factors may have led ChatGPT to mistakenly classify it as a legitimate news headline rather than clickbait.

In general, ChatGPT performs well in handling objective questions with clear, standardized answers. However, when it comes to addressing personalized questions, which often lack a fixed standard answer, it can be influenced by certain specific features. Moreover, conducting multiple tests on the same news may yield different results, leading to suboptimal performance in metrics like accuracy for clickbait detection.

4.5 Ablation Study

We compared the results between different prompts (as shown in Table 1 and Table 2) for clickbait detection tasks. As same as the main experiments, we select GPT3.5 as a backbone for the prompts experiments. The results comparison of different Prompts are shown in Table 7.

Generally speaking, there is no significant performance gap between the first prompt (P1) and the second prompt (P2) in terms of effectiveness for clickbait detection. Specifically, the performance of P1 is significantly better than that of P2 in the dataset WeChat. In dataset Sina, the opposite is true.

5 Conclusion and Future Work

In this paper, we present a study of the performance of LLMs (ChatGPT with GPT3.5) for clickbait detection. During the benchmark experiments on both English and Chinese datasets, LLMs did not perform as well as the current state-of-the-art deep neural networks and fine-tuning PLMs methods in the realm of multilingual clickbait detection. In our subsequent efforts, we will try to design more effective methods

Table 5: The Accuracy, Precision, Recall, F1-scores results (%) on English datasets (DLC, CND, and SCC). 200/5,300/10, and 600/20 denote the training number of not-prompt-tuning(CNN, BiLSTM, GATED-CNN, FAST-TEXT, BERT, and MFWCD-BERT) and prompt-tuning(PT, PEPL, and ChatGPT) methods. Ditto above.

Data	Method	Shot											
		200/5				300/10				600/20			
		Acc	Pre	Rec	F1	Acc	Pre	Rec	F1	Acc	Pre	Rec	F1
DLC	CNN	77.86	79.36	77.77	79.27	80.50	79.00	80.83	79.12	80.59	80.70	80.64	80.35
	BiLSTM	77.28	78.71	79.83	75.49	79.11	79.07	78.37	78.72	79.10	82.19	80.16	80.49
	GATED-CNN	77.80	80.05	75.41	78.01	79.34	79.86	78.16	78.43	78.39	79.71	79.93	79.66
	FAST-TEXT	65.23	72.31	63.84	72.32	74.89	71.07	74.30	65.58	75.13	78.33	73.60	77.63
	BERT	71.25	72.00	71.25	71.00	77.54	78.28	76.46	77.49	82.52	83.16	81.08	82.94
	MFWCD-BERT	79.13	80.44	79.13	78.91	82.19	82.21	82.19	82.19	85.00	85.90	85.00	84.91
	PT	81.86	82.69	81.86	80.60	82.70	82.43	82.70	82.42	84.79	84.60	84.79	84.52
	PEPL	83.31	82.70	79.29	80.53	87.41	90.11	82.40	84.74	88.97	89.58	85.67	87.16
	ChatGPT	80.75	69.06	82.79	73.56	79.33	69.51	88.02	70.88	82.07	75.66	82.64	73.67
		300/5				600/10				1200/20			
		Acc	Pre	Rec	F1	Acc	Pre	Rec	F1	Acc	Pre	Rec	F1
CND	CNN	73.74	69.70	71.57	68.82	76.47	74.83	74.33	75.70	73.19	72.05	75.27	66.61
	BiLSTM	75.18	75.78	74.06	73.50	75.74	79.54	78.28	79.15	71.79	81.70	80.08	82.71
	GATED-CNN	70.92	71.41	70.18	67.69	71.26	74.53	76.04	72.28	68.00	74.54	74.23	75.39
	FAST-TEXT	54.18	66.01	64.12	61.22	72.51	71.61	69.57	53.51	79.25	77.76	74.47	79.69
	BERT	73.17	73.19	73.17	73.16	76.90	80.65	76.90	76.71	83.28	85.69	83.02	83.80
	MFWCD-BERT	75.07	75.18	74.98	74.99	78.09	79.54	79.11	78.97	80.58	81.89	80.16	80.94
	PT	53.07	54.04	53.07	50.05	62.89	63.34	62.89	62.57	66.58	68.09	66.58	65.86
	PEPL	58.19	61.50	58.19	54.95	62.73	64.47	62.73	61.58	63.08	63.46	63.08	62.83
	ChatGPT	60.00	59.02	68.36	62.06	59.44	60.76	61.00	60.13	60.90	63.33	66.88	62.57
		500/5				1000/10				2000/20			
		Acc	Pre	Rec	F1	Acc	Pre	Rec	F1	Acc	Pre	Rec	F1
SCC	CNN	91.59	91.51	91.56	91.66	93.32	93.04	93.19	92.84	94.53	94.14	94.71	94.72
	BiLSTM	86.69	86.45	85.91	86.48	87.36	86.08	88.20	87.97	89.58	88.45	88.24	89.14
	GATED-CNN	92.07	91.78	91.90	91.67	93.56	93.14	93.27	93.56	93.22	94.67	94.28	94.45
	FAST-TEXT	84.09	83.66	83.18	82.52	85.99	85.76	85.27	85.74	86.67	86.96	86.60	86.68
	BERT	78.82	79.23	78.16	78.18	85.81	88.91	85.81	85.83	91.42	92.54	91.42	91.37
	MFWCD-BERT	81.94	81.95	81.94	81.94	83.82	83.91	83.82	83.81	85.69	86.10	85.69	85.65
	PT	90.91	91.12	90.91	90.90	92.94	92.45	92.47	92.42	93.37	93.44	93.37	93.37
	PEPL	83.10	85.57	83.11	82.81	95.00	95.00	95.00	95.00	96.53	96.54	96.53	96.53
	ChatGPT	83.94	88.63	90.01	83.08	86.14	92.41	86.93	85.09	88.73	95.54	87.81	87.82

Table 6: The Accuracy, Precision, Recall, F1-scores results (%) on Chinese datasets (Sina, Tencent, WeChat, and Paper). 200/5,400/10, and 800/20 denote the training number of not-prompt-tuning(CNN, BiLSTM, GATED-CNN, FAST-TEXT, BERT, and MFWCD-BERT) and prompt-tuning(PT, PEPL and ChatGPT) methods. Ditto above.

Data	Method	Shot											
		200/5				400/10				800/20			
		Acc	Pre	Rec	F1	Acc	Pre	Rec	F1	Acc	Pre	Rec	F1
Sina	CNN	72.13	72.02	72.47	72.70	77.00	74.85	75.61	75.84	75.96	77.60	77.35	78.19
	BiLSTM	74.74	71.83	58.71	70.88	74.39	72.32	72.65	75.40	75.60	76.11	72.65	74.01
	GATED-CNN	73.87	72.09	71.25	71.37	75.61	76.07	77.35	75.66	77.00	76.20	75.61	76.93
	FAST-TEXT	56.10	62.23	52.79	63.94	74.04	71.45	72.13	72.74	73.17	73.76	74.04	71.81
	BERT	52.36	52.92	44.25	48.20	55.25	57.69	46.51	51.50	65.96	71.43	55.56	62.50
	MFWCD-BERT	77.80	79.49	77.41	77.24	82.43	85.15	82.93	82.39	85.28	88.56	85.22	85.77
	PT	79.14	79.17	79.13	78.91	82.54	82.65	82.58	82.11	86.05	86.12	86.17	86.08
	PEPL	77.51	80.04	77.24	77.34	79.28	79.17	79.13	79.20	84.92	85.44	84.62	84.01
	ChatGPT	70.73	76.21	60.28	67.32	69.16	71.65	63.41	67.28	75.30	83.80	62.85	71.83
		400/5				800/10				1600/20			
		Acc	Pre	Rec	F1	Acc	Pre	Rec	F1	Acc	Pre	Rec	F1
Tencent	CNN	54.58	53.97	56.94	54.42	59.55	56.16	59.16	57.41	61.65	59.29	59.69	62.75
	BiLSTM	53.80	54.06	50.65	52.87	53.27	58.43	59.69	54.90	59.03	59.87	57.85	57.56
	GATED-CNN	55.37	56.28	56.54	55.63	60.60	60.29	57.33	55.71	60.08	60.74	57.98	60.31
	FAST-TEXT	53.53	50.58	51.05	56.49	56.28	57.75	57.07	49.95	55.37	57.94	58.12	58.20
	BERT	47.71	47.55	43.19	45.27	52.80	54.20	47.26	50.49	59.54	62.00	53.26	57.30
	MFWCD-BERT	81.44	86.34	81.40	81.02	83.78	84.01	83.70	83.41	87.71	88.03	87.61	87.20
	PT	79.72	82.48	79.82	79.46	81.76	84.48	81.35	78.62	82.59	82.65	82.58	82.54
	PEPL	74.87	74.90	74.82	74.70	76.72	77.03	76.65	76.61	80.03	80.05	80.00	80.81
	ChatGPT	59.34	57.91	71.13	63.84	56.02	54.71	69.90	61.38	59.08	57.17	71.99	63.73
		400/5				800/10				1600/20			
		Acc	Pre	Rec	F1	Acc	Pre	Rec	F1	Acc	Pre	Rec	F1
WeChat	CNN	72.14	70.64	69.40	70.60	86.67	84.38	85.12	83.59	85.83	86.70	87.38	86.72
	BiLSTM	64.29	61.93	67.74	62.24	81.67	81.52	76.55	81.61	83.57	81.78	80.95	83.49
	GATED-CNN	67.74	69.17	69.17	67.62	83.45	86.31	84.29	85.27	87.74	88.16	86.67	86.02
	FAST-TEXT	58.10	62.59	60.48	61.56	81.07	83.26	81.79	83.13	84.17	84.60	84.29	81.18
	BERT	45.05	44.76	41.67	43.16	49.54	50.73	44.73	47.54	57.06	59.39	51.48	55.15
	MFWCD-BERT	85.92	89.12	85.81	85.76	88.86	89.59	88.79	88.31	90.31	92.12	90.58	91.21
	PT	78.27	78.54	78.27	78.25	81.37	82.34	81.40	81.32	83.96	84.72	83.96	83.87
	PEPL	76.35	81.10	76.37	76.18	80.11	82.27	80.45	80.25	84.55	86.61	84.26	84.03
	ChatGPT	60.12	56.69	85.71	68.24	60.41	56.16	93.99	70.26	64.48	59.93	90.24	71.01
		800/5				1600/10				3200/20			
		Acc	Pre	Rec	F1	Acc	Pre	Rec	F1	Acc	Pre	Rec	F1
Paper	CNN	68.87	73.27	68.76	66.11	71.45	74.28	70.47	71.16	72.38	72.12	71.32	72.29
	BiLSTM	64.36	68.41	65.96	65.89	68.44	68.07	66.26	64.94	69.78	68.23	69.03	69.85
	GATED-CNN	68.44	72.40	68.63	67.29	71.41	74.78	69.36	65.84	71.79	72.02	71.04	72.91
	FAST-TEXT	67.93	70.25	66.03	65.53	68.45	72.88	68.96	67.85	71.10	72.15	72.23	70.39
	BERT	50.16	50.20	40.02	44.54	51.92	52.21	41.51	46.26	54.17	54.48	43.60	48.44
	MFWCD-BERT	78.75	80.01	78.69	78.90	80.84	80.83	80.79	81.03	84.54	85.02	84.11	84.51
	PT	72.07	76.98	72.24	71.33	75.61	76.05	75.61	75.51	80.41	80.55	80.41	80.39
	PEPL	70.14	74.46	70.14	70.53	73.62	73.88	73.62	73.55	78.28	78.77	78.28	78.19
	ChatGPT	68.33	72.18	62.70	66.42	68.32	70.40	63.88	66.98	70.94	72.14	67.21	69.59

Table 7: Comparison of different prompts for GPT3.5(%).

Data	Method	Shot											
		5				10				20			
Comparison of different prompts for GPT3.5 on English datasets													
DLC	GPT3.5+P1	80.75	69.06	78.69	73.56	79.33	69.51	70.08	69.79	82.07	75.66	70.08	72.76
	GPT3.5+P2	67.98	52.20	82.79	64.03	75.25	59.33	88.02	70.88	79.80	66.45	82.64	73.67
CND	GPT3.5+P1	58.41	59.02	49.36	53.76	59.44	60.76	50.08	54.91	60.90	63.33	49.20	55.38
	GPT3.5+P2	60.00	56.83	68.36	62.06	59.00	59.28	61.00	60.13	60.63	58.78	66.88	62.57
SCC	GPT3.5+P1	83.94	88.63	78.19	83.08	86.14	92.41	78.85	85.09	88.73	95.54	81.26	87.82
	GPT3.5+P2	81.49	76.54	90.01	82.73	84.39	82.71	86.93	84.77	87.52	87.30	87.81	87.55
Comparison of different prompts for GPT3.5 on Chinese datasets													
Sina	GPT3.5+P1	65.33	68.80	56.10	61.80	60.80	60.69	61.32	61.00	63.94	64.60	61.67	63.10
	GPT3.5+P2	70.73	76.21	60.28	67.32	69.16	71.65	63.41	67.28	75.30	83.80	62.85	0.7183
Tencent	GPT3.5+P1	59.34	57.91	71.13	63.84	52.88	52.89	52.62	52.75	58.51	57.17	67.80	62.03
	GPT3.5+P2	58.64	56.96	70.68	63.08	56.02	54.71	69.99	61.38	59.08	57.17	71.99	63.73
WeChat	GPT3.5+P1	60.12	56.69	85.71	68.24	60.41	56.10	93.99	70.26	58.57	55.25	90.24	68.54
	GPT3.5+P2	55.71	53.99	77.38	63.60	58.69	56.16	79.29	65.75	64.48	59.93	87.11	71.01
Paper	GPT3.5+P1	68.33	70.60	62.70	66.42	68.32	70.40	63.88	66.98	68.70	70.84	61.94	66.09
	GPT3.5+P2	68.13	72.18	59.59	65.28	66.43	69.54	55.77	61.9	70.94	72.14	67.21	69.59

with the help of LLMs that can significantly and consistently outperform SOTA clickbait detection methods.

References

- [Agrawal, 2016] Amol Agrawal. Clickbait detection using deep learning. In *2016 2nd international conference on next generation computing technologies (NGCT)*, pages 268–272. IEEE, 2016.
- [Anand *et al.*, 2017] Ankesh Anand, Tanmoy Chakraborty, and Noseong Park. We used neural networks to detect clickbaits: You won’t believe what happened next! In *Proceedings of the European Conference on Information Retrieval*, pages 541–547, 2017.
- [Biyani *et al.*, 2016] Prakhar Biyani, Kostas Tsioutsoulis, and John Blackmer. ”8 amazing secrets for getting more clicks”: detecting clickbaits in news streams using article informality. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, pages 94–100, 2016.
- [Blom and Hansen, 2015] Jonas Nygaard Blom and Kenneth Reinecke Hansen. Click bait: Forward-reference as lure in online news headlines. *Journal of Pragmatics*, 76:87–100, 2015.
- [Brown *et al.*, 2020] Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. In *Neural Information Processing Systems*, pages 1877–1901, 2020.
- [Chakraborty *et al.*, 2016] Abhijnan Chakraborty, Bhargavi Paranjape, Sourya Kakarla, and Niloy Ganguly. Stop clickbait: Detecting and preventing clickbaits in online news media. In *Proceedings of the IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining (ASONAM)*, pages 9–16, 2016.
- [Chen *et al.*, 2015] Yimin Chen, Niall J Conroy, and Victoria L Rubin. Misleading online content: recognizing clickbait as ”false news”. In *Proceedings of the ACM on workshop on Multimodal Deception Detection*, pages 15–19, 2015.
- [Chowdhery *et al.*, 2022] Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.
- [Devlin *et al.*, 2018] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.
- [Indurthi *et al.*, 2020] Vijayasaradhi Indurthi, Bakhtiyar Syed, Manish Gupta, and Vasudeva Varma. Predicting clickbait strength in online social media. In *Proceedings of the International Conference on Computational Linguistics*, pages 4835–4846, 2020.
- [Joulin *et al.*, 2016] Armand Joulin, Edouard Grave, Piotr Bojanowski, and Tomas Mikolov. Bag of tricks for efficient text classification. *arXiv preprint arXiv:1607.01759*, 2016.
- [Kumar *et al.*, 2018] Vaibhav Kumar, Dhruv Khattar, Siddhartha Gairola, Yash Kumar Lal, and Vasudeva Varma. Identifying clickbait: A multi-strategy approach using neural networks. In *The 41st International ACM SIGIR*

- Conference on Research & Development in Information Retrieval*, pages 1225–1228, 2018.
- [Liu *et al.*, 2019] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.
- [Liu *et al.*, 2022] Tong Liu, Ke Yu, Lu Wang, Xuanyu Zhang, Hao Zhou, and Xiaofei Wu. Clickbait detection on wechat: A deep model integrating semantic and syntactic information. *Knowledge-Based Systems*, 245:108605, 2022.
- [Liu *et al.*, 2023] Pengfei Liu, Weizhe Yuan, Jinlan Fu, Zhengbao Jiang, Hiroaki Hayashi, and Graham Neubig. Pre-train, prompt, and predict: A systematic survey of prompting methods in natural language processing. *ACM Computing Surveys*, 55(9):1–35, 2023.
- [López-Sánchez *et al.*, 2018] Daniel López-Sánchez, Jorge Revuelta Herrero, Angélica González Arrieta, and Juan M Corchado. Hybridizing metric learning and case-based reasoning for adaptable clickbait detection. *Applied Intelligence*, 48(9):2967–2982, 2018.
- [Mishra *et al.*, 2020] Rahul Mishra, Piyush Yadav, Remi Calizzano, and Markus Leippold. Musem: Detecting incongruent news headlines using mutual attentive semantic matching. In *Proceedings of the IEEE International Conference on Machine Learning and Applications (ICMLA)*, pages 709–716, 2020.
- [Raffel *et al.*, 2020] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *The Journal of Machine Learning Research*, 21(1):5485–5551, 2020.
- [Rony *et al.*, 2017] Md Main Uddin Rony, Naeemul Hassan, and Mohammad Yousuf. Diving deep into clickbaits: Who use them to what extents in which topics with what effects? In *Proceedings of the IEEE/ACM international conference on advances in social networks analysis and mining 2017*, pages 232–239, 2017.
- [Thoppilan *et al.*, 2022] Romal Thoppilan, Daniel De Freitas, Jamie Hall, Noam Shazeer, Apoorv Kulshreshtha, Heng-Tze Cheng, Alicia Jin, Taylor Bos, Leslie Baker, Yu Du, et al. Lamda: Language models for dialog applications. *arXiv preprint arXiv:2201.08239*, 2022.
- [Wei and Wan, 2017] Wei Wei and Xiaojun Wan. Learning to identify ambiguous and misleading news headlines. pages 4172–4178, 2017.
- [Wu *et al.*, 2023] Yin Wu, Mingpei Cao, Yueze Zhang, and Yong Jiang. Detecting clickbait in chinese social media by prompt learning. In *2023 26th International Conference on Computer Supported Cooperative Work in Design (CSCWD)*, pages 369–374. IEEE, 2023.
- [Yang *et al.*, 2019] Kai-Chou Yang, Timothy Niven, and Hung-Yu Kao. Fake news detection as natural language inference. *arXiv preprint arXiv:1907.07347*, 2019.
- [Yi *et al.*, 2022] Xiaoyuan Yi, Jiarui Zhang, Wenhao Li, Xiting Wang, and Xing Xie. Clickbait detection via contrastive variational modelling of text and label. In *Proceedings of the Thirty-First International Joint Conference on Artificial Intelligence (IJCAI)*, pages 4475–4481, 2022.
- [Yoon *et al.*, 2019] Seunghyun Yoon, Kunwoo Park, Joongbo Shin, Hongjun Lim, Seungpil Won, Meeyoung Cha, and Kyomin Jung. Detecting incongruity between news headline and body text via a deep hierarchical encoder. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, volume 33, pages 791–800, 2019.
- [Zheng *et al.*, 2021] Jiaming Zheng, Ke Yu, and Xiaofei Wu. A deep model based on lure and similarity for adaptive clickbait detection. *Knowledge-Based Systems*, 214:106714, 2021.