A Smoothed FPTAS for Equilibria in Congestion Games

Yiannis Giannakopoulos*

April 28, 2024

Abstract

We present a fully polynomial-time approximation scheme (FPTAS) for computing equilibria in congestion games, under *smoothed* running-time analysis. More precisely, we prove that if the resource costs of a congestion game are randomly perturbed by independent noises, whose density is at most ϕ , then *any* sequence of $(1 + \varepsilon)$ -improving dynamics will reach a $(1 + \varepsilon)$ -approximate pure Nash equilibrium (PNE) after an expected number of steps which is strongly polynomial in $\frac{1}{\varepsilon}$, ϕ , and the size of the game's description. Our results establish a sharp contrast to the traditional worst-case analysis setting, where it is known that better-response dynamics take exponentially long to converge to α -approximate PNE, for *any* constant factor $\alpha \geq 1$. As a matter of fact, computing α -approximate PNE in congestion games is PLS-hard.

We demonstrate how our analysis can be applied to various different models of congestion games including general, step-function, and polynomial cost, as well as fair cost-sharing games (where the resource costs are decreasing). It is important to note that our bounds do not depend explicitly on the cardinality of the players' strategy sets, and thus the smoothed FPTAS is readily applicable to network congestion games as well.

1 Introduction

The systematic study of congestion games has its origins in the seminal work of Rosenthal [Ros73]. Rosenthal, via a remarkably elegant construction, proved that (unweighted) congestion games are potential games [MS96], establishing in that way that they always have pure Nash equilibria (PNE). Since then, congestion games have been extensively studied in (algorithmic) game theory and combinatorial optimization, since they provide a powerful abstraction for modelling incentives in problems where different agents compete over a common collection of resources.

From a computational perspective, the problem of computing a PNE of a congestion game is a "canonical" local optimization problem, being a prominent member of the complexity class PLS introduced by Johnson, Papadimitriou, and Yannakakis [JPY88]. As a matter of fact, as was first shown by Fabrikant, Papadimitriou, and Talwar [FPT04], the problem is PLS-complete. This hardness is two-fold. First, it implies that, unless P = PLS, there does not exist an efficient algorithm to compute equilibria in congestion games. Secondly, it proves that better-response dynamics, which is simply the implementation of standard local search in congestion games, can take exponentially long to converge to a PNE. It is important to emphasize that the latter result is *unconditional*, that is, it does not depend on any complexity-theoretic assumptions. Ackermann, Röglin, and Vöcking [ARV08] showed that the PLS-completeness is also valid for network congestion games, that are defined succinctly over a graph structure, and even for combinatorially very simple instances, with linear resource cost functions.

^{*}School of Computing Science, University of Glasgow. Email: yiannis.giannakopoulos@glasgow.ac.uk

Given the aforementioned hardness results, the natural direction to investigate is the complexity of computing *approximate* PNE. Unfortunately, it turns out that the problem does not become easier: for *any* given constant α , Skopalik and Vöcking [SV08] showed that computing an α -PNE is PLS-complete, and furthermore, proved the unconditional existence of exponentially long better-response sequences, even for "well-behaved" resource costs.

Our goal in this paper is to demystify this dramatic complexity barrier, by proving that the hard instances in congestion games are actually rather "fragile". To do to this formally, we deploy the framework of smoothed analysis.

Smoothed analysis was first introduced in the groundbreaking work of Spielman and Teng [ST04], as a model for providing rigorous justification for the empirical fact that the Simplex algorithm for linear programming, although provably having exponential worst-case running-time, in practice performs exceptionally well. Their idea was very natural and remarkably effective: after an input instance has been adversarially fixed, random perturbations are introduced by "nature", independently, to all numerical parameters. Then, the running-time of an algorithm is measured *in expectation* with respect to this randomness, termed *smoothed running-time*.

In the original model of [ST04], the perturbations are Gaussian around 0, parameterized by their standard deviation $\sigma > 0$; as $\sigma \to 0$ this stochastic model converges to the original, fixed worst-case instance. The seminal result of Spielman and Teng says that the smoothed running-time of Simplex (under the shadow-vertex pivot rule) is polynomial in $\frac{1}{\sigma}$ (and the size of the input). One way to interpret this, is that the "bad" instances for the performance of Simplex (see, e.g., the Klee-Minty cube [KM72]) are "rare" or "isolated", and exponential precision is needed in their description in order to be effective.

Since [ST04], smoothed analysis has been successfully applied to a wide range of combinatorial problems, including, e.g., integer programming [BV06; RV07], the k-means method for clustering [AMR11], multiobjective optimization [BR15], TSP [ERV16; ERV14], and an impressive line of work on Local Max-Cut [ET11; ER17; ABPW17; CGVYZ20; BCC21]. As far as game-theoretic problems are concerned, Boodaghians, Kulkarni, and Mehta [BKM20] studied the smoothed complexity of finding PNE in network coordination games. Congestion games had not been studied from a smoothed analysis perspective until very recently, when Giannakopoulos, Grosz, and Melissourgos [GGM22] showed that (exact) PNE can be found in smoothed polynomial time for a (rather restrictive) class of games that satisfy a certain "constant-restraint" assumption. For a more in-depth view of smoothed analysis we refer to, e.g., [Rou21; ST09; BV06; GGM22]. A more detailed presentation of the specific smoothness framework that we employ in this paper is given in Section 2.1.1.

We discuss further related work, in particular regarding various results about the computability of approximate equilibria for the different models of congestion games that we study in this paper, in the following, more technical sections.

1.1 Our Results and Techniques

In this paper we study the smoothed complexity of computing (approximate) pure Nash equilibria (PNE) in (unweighted) congestion games. For our smoothed analysis framework we follow the one recently proposed in [GGM22] for congestion games, where the cost of the resources on the different possible loads are independently perturbed according to an arbitrary probability distribution with density at most ϕ . We formalize our general congestion game model in Section 2, where we also define all necessary game-theoretic fundamentals.

In Section 3 we discuss (approximate) better-response dynamics (BRD) and define our FPTAS (see Algorithm 1). Our main result is stated in Theorem 1: in general congestion games, a $(1 + \varepsilon)$ -approximate PNE can be computed in *smoothed* strongly polynomial time in $\frac{1}{\varepsilon}$ (and

the size of the game's description). More precisely, $(1 + \varepsilon)$ -approximate BRD terminate after at most $\tilde{O}(\varepsilon^{-1}\phi n^2 m^3)$ iterations (in expectation), where n is the number of players and m the number of resources. The proof is given in Section 3.2 and the exact bound can be found in (13).

Furthermore, Theorem 1 contains similar positive results for additional, well-established special classes of congestion games. These differ from general congestion games, in the way in which the resource cost functions are defined and represented. Namely, we study: step-function costs with (a total number of) d break points; polynomial costs of constant degree d (and nonnegative coefficients); and fair cost-sharing games where a fixed cost is equally split among the players who use it. The corresponding smoothed complexity bounds on the number of iterations of $(1 + \varepsilon)$ -BRD are, respectively: $\tilde{O}(\varepsilon^{-1}\phi nmd^2)$ (see Section 3.3.1 for the proof), $\tilde{O}(\varepsilon^{-1}\phi n^{d+1}m^3)$ (Section 3.3.2), and $\tilde{O}(\varepsilon^{-1}\phi nm^3)$ (Section 3.3.3).

It is worth mentioning that the aforementioned bounds hold for any starting configuration of the dynamics, and for any choice of the intermediate pivoting rule for the player deviations. Furthermore, all our results are immediately valid for *network* congestion games (see Section 2.1 for a definition and Section 3 for a discussion) as well, since the running time of our FPTAS does not depend on the number of strategies available to the players (which, for network games, can be exponential in n and m).

The technique for achieving the smoothed polynomial complexity bounds in this paper can be distilled in two core steps. First, we establish that the number of iterations of BRD can be upper bounded by an appropriate function of the ratio between the maximum and minimum resource costs of our game; for general congestion games, for example, this can be seen in (11). Similar inequalities hold for the other special congestion game models that we study, and they all arise from the algebraic relation between player costs and the value of Rosenthal's potential (see Section 2.1 for definitions).

Secondly, we show that when this expression is paired with a simple (exponential, based on exhaustive search) bound on the running time (see (12)), the expectation of the resulting quantity grows polynomially. This probabilistic property is the cornerstone for our derivation, and we present it in its own Section 3.1, before we dive into the rest of the technicalities in our proofs. The presentation in Section 3.1 is essentially self-contained, independent of congestion games, and Lemma 1 applies to general ϕ -smooth random variables. As a result, it may prove useful for future work in smoothed analysis, whenever similar bounds involving the ratios of the numerical parameters of the problem can be shown to hold.

2 Model and Notation

We will use \mathbb{N} , \mathbb{R} , and \mathbb{R}_+ to denote the set of nonnegative integer, real, and nonnegative real numbers, respectively. For $n \in \mathbb{N}$ we denote $[n] \coloneqq \{1, 2, \ldots, n\}$ and $[0..n] \coloneqq \{0\} \cup [n]$. For a random variable X we use F_X for its cumulative distribution function (cdf) and f_X for its probability density function (pdf). In this paper we only deal with (absolutely) continuous, real-valued random variables. We will use \leq_{st} for the usual (first-order) stochastic ordering; that is, for two random variables $X, Y: X \leq_{st} Y$ if and only if $F_Y(t) \leq F_X(t)$ for all $t \in \mathbb{R}$.

2.1 Congestion Games

A congestion game $\mathcal{G} = (N, R, \{S_i\}_{i \in N}, \{c_r\}_{r \in R})$ is defined by (1) a finite set of players N = [n], (2) a finite set of resources $R = \{r_1, r_2, \ldots, r_m\}$, (3) for each player *i*, a strategy set $S_i \subseteq 2^R \setminus \{\emptyset\}$; each element $s_i \in S_i$ is thus a nonempty set of resources, and is called a strategy for player *i*, and (4) for each resource $r \in R$, a cost function $c_r : [n] \longrightarrow \mathbb{R}_+$; $c_r(\ell)$ is interpreted as the cost (or congestion) of resource *r* when ℓ players use it. A network congestion game is a congestion game where the strategy sets $\{S_i\}_{i\in N}$ are not given explicitly, but induced via an underlying graph structure. More precisely, we are given a directed graph G = (V, E) and, for each player $i \in N$ a pair of nodes $(o_i, d_i) \in V$. The resources of the game are exactly the edges of the graph, i.e. R = E. Then, the strategies of player i are all simple $o_i \to d_i$ paths in G.

Notice how, in the definition above, we do not enforce any monotonicity requirement on the resource cost functions, since our main result does not depend on such an assumption and applies to general congestion games with arbitrary cost functions (see case (a) of Theorem 1 and the corresponding proof in Section 3.2). We discuss more specialized congestion game models, including step-function and polynomial costs (which are nondecreasing) and cost-sharing games (where the costs are decreasing) in their corresponding Sections 3.3.1 to 3.3.3. In such models, the resource costs $c_r(\ell)$ are not given explicitly, but rather via a more succinct functional expression.

A strategy profile of a congestion game \mathcal{G} is a collection of strategies, one for each player: $\mathbf{s} = (s_1, s_2, \ldots, s_n) \in \mathbf{S} \coloneqq S_1 \times S_2 \times \cdots \times S_n$. For a strategy profile \mathbf{s} , we use $\ell_r(\mathbf{s})$ for the load it induces on a resource $r \in R$, that is, the number of players that use it: $\ell_r(\mathbf{s}) \coloneqq |\{i \in N \mid r \in s_i\}|$. This induces a cost to the players, equal to the sum of the cost of the resources that they are using. That is, the cost of player $i \in N$ under a strategy profile $\mathbf{s} \in \mathbf{S}$ is:

$$C_i(\boldsymbol{s}) \coloneqq \sum_{r \in s_i} c_r(\ell_r(\boldsymbol{s})).$$

For an $\alpha \geq 1$, we will say that a strategy profile is an α -approximate pure Nash equilibrium (α -PNE) if no player can improve their cost more than a (multiplicative) factor of α , by unilaterally deviating to another strategy. Formally, $s \in S$ is an α -PNE if¹

$$C_i(\boldsymbol{s}) \le \alpha \cdot C_i(s'_i, \boldsymbol{s}_{-i}), \quad \text{for all } i \in N, \ s'_i \in S_i.$$

$$\tag{1}$$

For the special case of $\alpha = 1$ this definition coincides with the stricter, standard notion of a pure Nash equilibrium. To emphasize this, sometimes a 1-PNE is called an *exact* PNE. Notice that any exact PNE is also an α -PNE, for any $\alpha \ge 1$.

The Rosenthal potential of a congestion game \mathcal{G} is the function $\Phi: \mathbf{S} \longrightarrow \mathbb{R}_+$ given by

$$\Phi(\boldsymbol{s}) \coloneqq \sum_{r \in R} \sum_{j=1}^{\ell_r(\boldsymbol{s})} c_r(j).$$
(2)

This is due to the work of Rosenthal [Ros73] who first defined the quantity in (2) and proved that, for all strategy profiles s of a congestion game we have

$$\Phi(\boldsymbol{s}) - \Phi(s'_i, \boldsymbol{s}_{-i}) = C_i(\boldsymbol{s}) - C_i(s'_i, \boldsymbol{s}_{-i}).$$
(3)

An immediate consequence of (3), also shown by Rosenthal [Ros73], is that a minimizer of Rosenthal's potential $s^* \in \operatorname{argmin}_{s \in S} \Phi(s)$ is an exact PNE. This establishes the existence of α -PNE (for any $\alpha \geq 1$) in all congestion games.

The goal of the present paper is to study computationally efficient methods for computing such an α -PNE, for a factor α as close to 1 as possible.

¹Here we are using the standard game-theoretic notation of s_{-i} to denote the (n-1)-dimensional vector that remains from the *n*-dimensional vector s if we remove its *i*-th coordinate. In that way, for any vector s we can write $s = (s_i, s_{-i})$.

2.1.1 Smoothed Congestion Games

In this paper we study the complexity of our algorithms under smoothed analysis (see, e.g., [Rou21, Part 4]). In a ϕ -smooth congestion game, we assume that the resource costs $\{c_r(\ell)\}_{r\in R, \ell\in[n]}$ are independent random variables; then, we measure running-times in expectation with respect to their realizations. In more detail, we assume that the resource costs are continuous random variables, taking values in [0, 1], and that their density functions are upper-bounded by a universal parameter $\phi \geq 1$. More generally, we will call such a random variable X with $f_X : [0, 1] \longrightarrow [0, \phi]$, a ϕ -smooth random variable.

Notice here that the normalization of the resource costs within [0, 1] is without loss for our purposes: one can just divide all costs by their maximum, and get a totally equivalent game that fully maintains the equilibrium structure. Such a scaling is done to facilitate the smoothed analysis modelling, and is standard in the field (see, e.g., [ERV16; ER17; GGM22]).

Parameter ϕ allows smoothed analysis to interpolate between average-case analysis ($\phi = 1$) where all costs are uniformly i.i.d., and worst-case analysis ($\phi = \infty$) where the ϕ -smooth resource costs degenerate to single values. The aim of smoothed analysis is to capture the complexity of an algorithm, asymptotically as ϕ grows large. To see it from another perspective, smoothed analysis can be seen as introducing small, independent, random perturbations to the numerical values of a problem instance, *before* performing a traditional, worst-case running-time analysis. The magnitude of this random noise can be "controlled" by a parameter $\sigma = \frac{1}{\phi} \rightarrow 0$. A detailed discussion of the fundamentals and subtleties of smoothed analysis is beyond the scope of this paper; for such a treatment, the interested reader is referred to, e.g., [Rou21; ST04; BV06].

It is important to clarify that, in this section we introduced our smoothness framework only for general congestion games. Due to its nature, smoothed analysis depends heavily on the representation and the numerical parameters of each problem instance; therefore, different special models of congestion games require their own, tailored smoothness treatment. To assist readability, we have decided to defer the discussion of smoothness for step-functions, polynomial, and fair cost-sharing games to their corresponding Sections 3.3.1 to 3.3.3. For most of these models, we adopt the smoothness frameworks for congestion games that were first proposed recently by [GGM22]; except for cost-sharing games (see Section 3.3.3) for which, to the best of our knowledge, this is the first time that they've been studied from a smoothed analysis perspective.

3 The Smoothed FPTAS

In this section we present our FPTAS (see Algorithm 1). It is a based on a very simple, but fundamental idea. Fix an arbitrary game \mathcal{G} and a parameter $\alpha \geq 1$. If a strategy profile s of \mathcal{G} is not an α -approximate PNE, then (by simply considering the negation of (1)) there has to exist a player i and a strategy s'_i of i that improves their cost by a factor larger than α ; formally:

$$\alpha C_i(s'_i, \boldsymbol{s}_{-i}) < C_i(\boldsymbol{s}) \tag{4}$$

Such a deviation $s \to (s'_i, s_{-i})$, that satisfies (4), is called an α -improving move for game \mathcal{G} .

This gives rise to the following natural process for finding approximate equilibria in games, called α -better-response dynamics (α -BRD): starting from an arbitrary strategy profile, repeatedly perform α -improving moves. When no such move exists any more, it must be that an α -PNE has been reached. For a more formal description, see Algorithm 1.

Notice how in Line 2 of Algorithm 1 there might be multiple valid α -improving moves $s \to (s'_i, s_i)$ to choose from. Our definition deliberately leaves this underdetermined, as all the results presented in this paper hold for *any* choice of the α -improving moves. Furthermore,

Algorithm 1 α -Approximate Better-Response Dynamics (α -BRD), $\alpha \geq 1$ Input: Congestion game $\mathcal{G} = (N, R, \{S_i\}_{i \in N}, \{c_r\}_{r \in R})$; strategy profile $s \in S$ Output: An α -PNE of \mathcal{G} 1: while s is not an α -PNE do 2: Choose $i \in N, s'_i \in S_i$ such that: $\alpha C_i(s'_i, s_{-i}) < C_i(s)$ 3: $s \leftarrow (s'_i, s_{-i})$ 4: end while 5: return s

we have made the starting profile to be part of the input, in order to emphasize the fact that this can be adversarially selected; again, all our bounds are robust to the choice of an initial configuration.

The main result of our paper is that, under smoothed running-time analysis, approximate better-response dynamics converge fast to approximate equilibria:

Theorem 1. In ϕ -smooth congestion games, $(1 + \varepsilon)$ -BRD always find a $(1 + \varepsilon)$ -PNE, after an expected number of iterations which is strongly polynomial in $\frac{1}{\varepsilon}$, ϕ , and the description of the game. This holds for (a) general, (b) step-function, (c) polynomial, and (d) cost-sharing congestion games, and even under a succinct network representation of all models (a)-(d).

More precisely, the expected number of iterations is at most $\left(1+\frac{1}{\varepsilon}\right) \operatorname{poly}(\phi, n, m)$ where n is the number of players and m the number of resources.

Notice that Theorem 1 gives a bound on the number of *iterations* of our dynamics (i.e., the while-loop of Lines 1-3), and not the *total running time*. This is due to fact that, checking whether a given strategy profile is an (approximate) equilibrium (Line 1 of Algorithm 1) and, if not, returning an improving move (Line 2), can both be done in polynomial time (in the description of the game), for all congestion game models studied in this paper; therefore, the total running time is indeed dominated by the number of improving-move steps.

To see that indeed that's the case, first consider the standard representation of congestion games, where the strategy sets $\{S_i\}_{i\in N}$ of the players are *explicitly* given in the input, each S_i being a list of, at most k, subsets of elements of the ground set of resources R. Then, one can actually compute all α -improving moves by simply exhaustively going over all players $i \in N$, and all strategy deviations $s'_i \in S_i$, checking whether $\frac{C_i(s)}{C_i(s'_i, s_{-i})} > \alpha$; this can be done in O(nk) time. On the other hand, for congestion game representations where the strategy sets are *implicitly* given, it might not be possible to efficiently perform such an exhaustive search. Then, one needs to have access to the fundamental game-theoretic primitive of a *best-response*, i.e., for every player i and any strategy profile $\mathbf{s}_{-i} \in \mathbf{S}_{-i}$, being able to efficiently compute an element

$$s_i' \in \operatorname*{argmin}_{s_i \in S_i} \left\{ C_i(s_i, \boldsymbol{s}_{-i}) \right\}.$$
(5)

Then, finding an α -improving move can still be done in polynomial time, since it boils down to going over the players $i \in N$, computing a best-response s'_i , and checking whether $\frac{C_i(s)}{C_i(s'_i, s_{-i})} > \alpha$. If this check fails for all players, then it must be that s is an α -PNE. In particular, this applies to network congestion games (recall the definition from Section 2.1) where each strategy set S_i is succinctly described as a set of paths between two fixed nodes, and therefore its cardinality might be exponential. However, for such games, best-responses in (5) are simply shortest-path computations, and thus they can indeed be performed efficiently. The rest of our paper is devoted to proving Theorem 1 and describing the smoothness frameworks for all the different congestion game models (a), (b), (c), and (d) that are involved in the statement of Theorem 1 and which we study in this paper.

3.1 The Key Probabilistic Lemma

A critical step in the proof of our main results (Theorem 1) is that of identifying a key property about ϕ -smooth random variables. In order to highlight its importance, we decided to disentangle it from the rest of the running-time analysis of our FPTAS, and present it beforehand here in its own section, together with its proof (see Lemma 1). Furthermore, since it is completely independent of congestion games, it can be of particular interest for future work on smoothed analysis.

To provide intuition first, consider some combinatorial optimization problem involving numerical inputs w_1, w_2, \ldots, w_m , normalized in (0, 1]. For example, these could be the weights of a knapsack instance, or the coefficients of an integer program. Then, $W = \max_i \frac{1}{w_i} = \frac{1}{\min_i w_i}$ effectively captures the "magnitude" of the numbers that are involved in our computation. A running time which is polynomial on W does not, in general, imply efficient computation; for example, this is highlighted by many NP-hard problems that are known to admit pseudopolynomial solutions (like knapsack, for example). Nevertheless, what if, under the more optimistic lens of smoothed analysis, one could show that the magnitude of W is "well-behaved" with "high probability"?

The following observation immediately shatters such hopes: consider a uniformly distributed random variable X over [0, 1], and observe that the expectation $\mathbb{E}\begin{bmatrix}\frac{1}{X}\end{bmatrix} = \int_0^1 \frac{1}{x} \, dx = \infty$ of its reciprocal is actually unbounded. Nevertheless, it turns out that a small patch is enough to do trick: truncating the random variable $\frac{1}{X}$ from above, even at an exponentially large threshold, results in a polynomially bounded expectation. This is formalized in the following:

Lemma 1. Let $X_1, X_2, \ldots, X_{\mu}$ be independent ϕ -smooth random variables over [0,1]. For any reals $\alpha \geq 1$, $\beta \geq 0$ it holds that:

$$\mathbb{E}\left[\min\left\{\max_{i\in[\mu]}\frac{\alpha}{X_i},\mu^{\beta}\right\}\right] \le \phi\alpha(\beta+1)\mu\ln\mu + 1 = \tilde{O}(\phi\alpha\beta\mu).$$
(6)

Proof. To simplify notation, we first define function $g:[0,1] \longrightarrow \mathbb{R}$ with

$$g(t) \coloneqq \min\left\{ rac{lpha}{t}, \mu^{eta}
ight\}.$$

Notice that function g is nonincreasing and that the expectation in (6) can now be more simply expressed as $\mathbb{E}[g(\min_i X_i)]$.

Now let $Y_1, Y_2, \ldots, Y_{\mu}$ be independent uniformly distributed random variables over $[0, \frac{1}{\phi}]$. Notice that they are ϕ -smooth and their cdf is given by $F_Y(y) = \phi y$ for $0 \le y \le \frac{1}{\phi}$. Let us also define the random variable $Z := \frac{1}{\min_{i \in [\mu]} Y_i}$. Observe that Z takes values in $[\phi, \infty)$ and its cdf and pdf are given by

$$F_Z(z) = \operatorname{Prob}\left[Z \le z\right] = \prod_{i=1}^{\mu} \operatorname{Prob}\left[Y_i \ge \frac{1}{z}\right] = \prod_{i=1}^{\mu} \left[1 - F_Y\left(\frac{1}{z}\right)\right] = \left(1 - \frac{\phi}{z}\right)^{\mu},$$

and

$$f_Z(z) = \frac{\mathrm{d} F_Z(z)}{\mathrm{d} z} = \mu \left(1 - \frac{\phi}{z}\right)^{\mu - 1} \frac{\phi}{z^2}$$

respectively, for $z \ge \phi$. From these expressions, for all $z \ge \phi$ we furthermore get the bounds

$$F_Z(z) \ge 1 - \frac{\mu\phi}{z}$$
 and $f_Z(z) \le \frac{\mu\phi}{z^2}$, (7)

where the first inequality can be derived by using Bernoulli's inequality.²

Next, we argue that $Y_i \leq_{st} X_i$, where \leq_{st} denotes the usual (first-order) stochastic order. Indeed, since each X_i is ϕ -smooth, its cdf is upper-bounded by

$$F_{X_i}(x) \le \int_0^x \phi \,\mathrm{d}t = \phi x = F_Y(x),$$

for all $0 \le x \le \frac{1}{\phi}$; obviously, $F_{X_i}(x) \le 1 = F_Y(x)$ for all $x \ge \frac{1}{\phi}$ as well. Since order statistics preserve stochastic dominance (see, e.g., [BSS98, p. 100]), it must be that $\min_i Y_i \le_{st} \min_i X_i$. Thus, by the monotonicity of function g it must be that (see, e.g., [Ros96, Proposition 9.1.2])

$$\mathbb{E}\left[g\left(\min_{i} X_{i}\right)\right] \leq \mathbb{E}\left[g\left(\min_{i} Y_{i}\right)\right] = \mathbb{E}\left[\min\{\alpha Z, \mu^{\beta}\}\right].$$
(8)

Using this, and denoting $z^* := \phi \mu^{\beta+1} \ge \phi$ for convenience, we can finally upper bound the expectation in (6) by:

$$\mathbb{E}\left[g\left(\min_{i} X_{i}\right)\right] = \int_{\phi}^{\infty} \min\{\alpha z, \mu^{\beta}\} f_{Z}(z) \, \mathrm{d}z$$

$$\leq \int_{\phi}^{z^{*}} \alpha z f_{Z}(z) \, \mathrm{d}z + \int_{z^{*}}^{\infty} \mu^{\beta} f_{Z}(z) \, \mathrm{d}z$$

$$= \alpha \int_{\phi}^{z^{*}} z f_{Z}(z) \, \mathrm{d}z + \mu^{\beta} \left[1 - F_{Z}(z^{*})\right]$$

$$\leq \alpha \int_{\phi}^{z^{*}} z \frac{\mu \phi}{z^{2}} \, \mathrm{d}z + \mu^{\beta} \left[1 - \left(1 - \frac{\mu \phi}{z^{*}}\right)\right], \qquad \text{by using (7),}$$

$$= \alpha \mu \phi \ln \frac{z^{*}}{\phi} + \frac{\mu^{\beta+1} \phi}{z^{*}}$$

$$= \alpha \mu \phi (\beta + 1) \ln \mu + 1, \qquad \text{since } z^{*} = \phi \mu^{\beta+1}.$$

3.2 General Congestion Games

In this section we prove part (a) of Theorem 1. We have already introduced our smoothness model for general congestion games in Section 2.1.1. Recall that, under traditional worst-case analysis, computing an α -PNE of a congestion game is PLS-complete, for any constant α [SV08]. Finally, we emphasize that in general congestion games we make no monotonicity assumptions, and therefore our results hold for arbitrary (positive) resource costs. In case one wants to enforce an increasing assumption (which is common in the literature of congestion games), the step-function model of the following Section 3.3.1 can be used instead, in order for the monotonicity to be preserved under smoothness.

Fix an arbitrary congestion game, with n players and |R| = m resources. For simplicity, we will denote the maximum and minimum resource costs by

$$c_{\max} \coloneqq \max_{r \in R, j \in [n]} c_r(j)$$
 and $c_{\min} \coloneqq \min_{r \in R, j \in [n]} c_r(j)$.

²Bernoulli's inequality (for a proof see, e.g., Mitrinović [Mit70, §0.2]) states that, for all positive integers m and all reals $y \ge -1$ it holds that $(1+y)^m \ge 1+my$. Instantiating this with $y \leftarrow -\frac{\phi}{z} \ge -1$ and $m \leftarrow \mu$ we get the desired first inequality in (7).

First observe that, at any outcome $s \in S$, Rosenthal's potential (2) can be upper-bounded by

$$\Phi(\boldsymbol{s}) = \sum_{r \in R} \sum_{j=1}^{\ell_r(\boldsymbol{s})} c_r(j) \le \sum_{r \in R} \sum_{j=1}^n c_r(j) \le mn \cdot c_{\max}$$
(9)

and trivially lower-bounded by $\Phi(s) \ge 0$. At the same time, the cost of any player *i* can be lower-bounded by

$$C_i(\boldsymbol{s}) = \sum_{r \in s_i} c_r(\ell_r(\boldsymbol{s})) \ge \min_{r \in R} c_r(\ell_r(\boldsymbol{s})) \ge c_{\min}.$$
(10)

If $s \to s' = (s'_i, s_{-i})$ is a move during the execution of our $(1 + \varepsilon)$ -BRD, then it must be that $(1 + \varepsilon)C_i(s') < C_i(s)$. So, we can lower-bound the improvement of the potential by:

$$\Phi(\boldsymbol{s}) - \Phi(\boldsymbol{s}') = C_i(\boldsymbol{s}) - C_i(\boldsymbol{s}') > rac{arepsilon}{1+arepsilon} C_i(\boldsymbol{s}) \stackrel{(10)}{\geq} rac{arepsilon}{1+arepsilon} c_{\min}.$$

Therefore, after T steps $s^0 \to s^1 \to \cdots \to s^T$ of the $(1 + \varepsilon)$ -BRD it must be that

$$T \cdot \frac{\varepsilon}{1+\varepsilon} c_{\min} < \Phi(s^0) - \Phi(s^T) \stackrel{(9)}{\leq} mnc_{\max},$$

which gives the following upper bound on the number of steps for our dynamics:

$$T < \left(1 + \frac{1}{\varepsilon}\right) nm \frac{c_{\max}}{c_{\min}}.$$
(11)

On the other hand, recall that our dynamics goes over strategy profiles, strictly decreasing the potential at every step; therefore, no two profiles with the same potential value can be visited via our dynamics. Additionally, observe that the values $\Phi(s)$ of Rosenthal's potential (2) are fully determined by the configuration of resource loads $\{\ell_r(s)\}_{r\in R}$ under profile s, and do not directly depend on the actual identities of the players that use each edge. As a result, we deduce that the total number of iterations cannot be larger than the number of possible different resource-load profiles. Since each resource can be used by at most n players, this is at most $(n+1)^{|R|} = (n+1)^m$. Combining this with (11) we can derive that $(1 + \varepsilon)$ -BRD terminates after at most

$$T \le \min\left\{ \left(1 + \frac{1}{\varepsilon}\right) nm \frac{c_{\max}}{c_{\min}}, (n+1)^m \right\} \le \min\left\{ \left(1 + \frac{1}{\varepsilon}\right) \frac{nm}{c_{\min}}, (nm)^m \right\}$$
(12)

iterations. For the last inequality we used the fact that $c_{\max} \leq 1$ and $n + 1 \leq nm$, since we can without loss of generality assume that the number of resources is at least $m \geq 2$; otherwise our congestion game is degenerate, having only a single strategy profile (and thus the dynamics trivially converge in constant time).

Since the resource costs $\{c_r(j)\}_{r \in R, j \in [n]}$ are independent ϕ -smooth random variables, we can now deploy Lemma 1, with the choice of parameters $\mu \leftarrow |R|n = mn, \beta \leftarrow m$, and $\alpha \leftarrow \left(1 + \frac{1}{\varepsilon}\right) nm$, in order to finally bound the *expected* number of steps of $(1 + \varepsilon)$ -BRD in (12) by

$$\phi \cdot \left(1 + \frac{1}{\varepsilon}\right) mn \cdot (m+1) \cdot mn \ln(mn) + 1 = \tilde{O}\left(\frac{1}{\varepsilon}\phi n^2 m^3\right).$$
(13)

3.3 Special Congestion Game Models

3.3.1 Step-Function Games

In this section we formally describe the model of step-function congestion games, and prove the corresponding part (b) of Theorem 1. It is important to mention that the PLS-hardness of approximation of Skopalik and Vöcking [SV08], that we have already mentioned for general congestion games, actually uses nondecreasing costs, so it applies to step-functions as well.

In step-function congestion games, each resource cost function c_r is represented by a set of d_r integer break points $1 = b_{r,1} < b_{r,2} < \cdots < b_{r,d_r} \leq n$ and corresponding value jumps $a_{r,1}, a_{r,2}, \ldots, a_{r,d_r} \in (0,1]$. More precisely, the cost of resource r on a load of $\ell \in [n]$ players is then given by

$$c_r(\ell) \coloneqq a_{r,1} + a_{r,2} + \dots + a_{r,\kappa}, \quad \text{where } \kappa = \max\left\{j \in [d_r] \mid b_{r,j} \le \ell\right\}$$

Let $d \coloneqq \sum_{r \in R} d_r$ denote the total number of break points across the entire representation.

For our smoothed analysis, we follow the framework recently proposed by [GGM22] for step-function congestion games, assuming that the jumps $\{a_{r,j}\}$ are independent ϕ -smooth random variable. We emphasize, though, that the break points $\{b_{r,j}\}$ are not perturbed but are (adversarially) fixed.

Similarly to (10) for general congestion games (see Section 3.2), if we denote $a_{\min} := \min_{r \in R, j \in [d_r]} a_{r,j}$ and $a_{\max} := \max_{r \in R, j \in [d_r]} a_{r,j}$, the cost of any player *i*, at any strategy profile *s*, can be lower-bounded by

$$\Phi(\mathbf{s}) \ge na_{\min}$$
 and $C_i(\mathbf{s}) \ge a_{\min}$. (14)

Also, since all cost functions c_e are now nondecreasing, from (9) the potential can be upperbounded as:

$$\Phi(s) \le \sum_{r \in R} nc_r(n) = n \sum_{r \in R} \sum_{j=1}^{d_r} a_{r,j} \le n \sum_{r \in R} d_r a_{\max} = n da_{\max}.$$
(15)

In a totally analogous way to (12), following the steps of the proof of Section 3.2, we can now bound the expected number of steps of $(1 + \varepsilon)$ -BRD by

$$\mathbb{E}\left[T\right] \le \mathbb{E}\left[\min\left\{\left(1+\frac{1}{\varepsilon}\right)\frac{nd}{a_{\min}}, (n+1)^m\right\}\right]$$

Choosing this time parameters $\mu \leftarrow d$, $\alpha \leftarrow \left(1 + \frac{1}{\varepsilon}\right) nd$ and $\beta \leftarrow m \frac{\ln(n+1)}{\ln d}$, we can rewrite this as

$$\mathbb{E}\left[T\right] \le \mathbb{E}\left[\min\left\{\frac{\alpha}{a_{\min}}, \mu^{\beta}\right\}\right].$$
(16)

Noticing that the expectation in (16) is taken with respect to the independent ϕ -smooth random variables $\{a_{r,j}\}_{r\in R, j\in [d_r]}$, which are $d = \mu$ many, we can again deploy Lemma 1 to finally get a bound of:

$$\mathbb{E}\left[T\right] = \tilde{O}\left(\phi\alpha\beta\mu\right) = \tilde{O}\left(\phi\cdot\left(1+\frac{1}{\varepsilon}\right)nd\cdot m\frac{\ln(n+1)}{\ln d}\cdot d\right) = \tilde{O}\left(\frac{1}{\varepsilon}\phi nmd^2\right).$$

3.3.2 Polynomial Games

In this section we introduce the model of polynomial congestion games, and prove the corresponding part (c) of Theorem 1. In this model the resource cost functions are polynomials of a constant maximum degree d, with nonnegative coefficients. It is arguably the most established, and well-studied congestion game model in algorithmic game theory. Although finding *exact* equilibria in polynomial congestion games is still a PLS-complete problem [ARV08; Rou16; GGM22], no hardness of approximation results are known. At the same time, the only positive computational results that we have are for efficiently computing $d^{O(d)}$ -approximate PNE [CFGS11; FGKS17; GNS22]. Closing this gap in our understanding of computability of approximate PNE in polynomial games is one of the most important remaining open problems in the field.

To continue with the formal definition of our model, each cost function c_r is represented by a set of coefficients $\{a_{r,j}\}_{j\in[0..d]} \in [0, 1]$, where $d \in \mathbb{N}$, so that for all loads $\ell \in [n]$

$$c_r(\ell) \coloneqq a_{r,0} + a_{r,1}\ell + \dots + a_{r,d}\ell^d.$$

$$\tag{17}$$

We emphasize that the normalization of the coefficients within [0,1] here is without loss of generality.

To perform smoothed analysis in this congestion game model, the natural choice is to consider perturbations on the coefficients of the polynomial costs. However, special care needs to be taken with respect to zero coefficients: any random noise on them would "artificially" introduce monomial terms that did not exist in the original cost function This, arguably, will distort the combinatorial aspect of our instance. Therefore, for our smoothness framework we will assume that only the *nonzero* polynomial coefficients $\{a_{r,j}\}$ are (independent) ϕ -smooth random variables.

For that reason, it will be technically convenient to introduce notation

$$J_r \coloneqq \{j \in [0..d] \mid a_{r,j} > 0\}, \qquad d_r \coloneqq |J_r|, \qquad \text{and} \qquad \tilde{d} \coloneqq \sum_{r \in R} d_r \le m(d+1)$$

for the set of indices of the non-trivial cost coefficients of resource r; then, (17) can now be written as $c_r(\ell) = \sum_{j \in J_r} a_{r,j} \ell^j$. We also let $a_{\min} = \min_{r \in R, j \in J_r} a_{r,j}$ and $a_{\max} = \max_{r \in R, j \in J_r} a_{r,j}$ for the minimum and maximum nonzero coefficients across all resources.

It is not hard to verify that we can again derive the same lower bound as in (14) for the player costs, and for the upper bound on the potential, due to the monotonicity of the resource cost function, similarly to (15) we can now get:

$$\Phi(\boldsymbol{s}) \le n \sum_{r \in R} c_r(n) = n \sum_{r \in R} \sum_{j \in J_r} a_{r,j} n^j \le n \sum_{r \in R} d_r a_{\max} n^d = \tilde{d} n^{d+1} a_{\max}.$$

Following along the lines of the derivations for the previous Sections 3.2 and 3.3.1, we can now bound the expected number of steps of $(1 + \varepsilon)$ -BRD by

$$\mathbb{E}\left[T\right] \le \mathbb{E}\left[\min\left\{\left(1+\frac{1}{\varepsilon}\right)\frac{\tilde{d}n^{d+1}}{a_{\min}}, (n+1)^m\right\}\right]$$

Choosing parameters $\mu \leftarrow \tilde{d} \leq m(d+1) = O(m)$, $\alpha \leftarrow \left(1 + \frac{1}{\varepsilon}\right) \tilde{d}n^{d+1} = O\left(\frac{1}{\varepsilon}mn^{d+1}\right)$, and $\beta \leftarrow m\frac{\ln(n+1)}{\ln \tilde{d}} = \tilde{O}(m)$, similarly to the proof in Section 3.3.1 we can again derive the bound in (16). Thus, applying Lemma 1 for the $\tilde{d} = \mu$ many independent ϕ -smooth random variables $\{a_{r,j}\}_{r \in R, j \in J_r}$, we can now bound the expected number of steps of our dynamics by:

$$\mathbb{E}\left[T\right] = \tilde{O}\left(\phi\alpha\beta\mu\right) = \tilde{O}\left(\phi\cdot\frac{1}{\varepsilon}mn^{d+1}\cdot m\cdot m\right) = \tilde{O}\left(\frac{1}{\varepsilon}\phi n^{d+1}m^3\right).$$

3.3.3 Cost-Sharing Games

This section deals with the proof of part (d) of Theorem 1. Fair cost-sharing games are congestion games where the cost of resources are given by $c_r(\ell) = \frac{a_r}{\ell}$, where $a_r > 0$. Notice that these are decreasing functions; they can be interpreted as a fixed edge cost a_r being equally split among the players that use it. It is known that the problem of finding an exact PNE in fair cost-sharing games is PLS-complete, even in network games [Syr10], and that better-response dynamics take exponentially long to converge [ADKTWR08]. To the best of our knowledge, no positive results exist regarding the efficient computation of approximate PNE, apart from the very special case of metric network facility location games, with uniform costs [HT09].

Unlike the previous congestion game models studied in this paper, no smoothness framework has been proposed before for cost-sharing games. Therefore, we propose here to consider a_r as independent ϕ -smooth random variables; arguably, this seems as the most natural approach.

Like before, we denote $a_{\min} \coloneqq \min_{r \in R} a_r$ and $a_{\max} \coloneqq \max_{r \in R} a_r$. Given that resource costs are now decreasing, we can lower-bound the player costs at any profile s by

$$C_i(\boldsymbol{s}) \ge \min_{r \in R} c_r(\ell_r(\boldsymbol{s})) \ge \min_{r \in R} c_r(n) = \min_{r \in R} \frac{a_e}{n} = \frac{1}{n} \cdot a_{\min}.$$

Furthermore, we can upper-bound the potential values by

$$\Phi(s) = \sum_{r \in R} \sum_{j=1}^{\ell_r(s)} c_r(j) \le m \max_{r \in R} \sum_{j=1}^n c_r(j) = m \max_{r \in R} \sum_{j=1}^n \frac{a_r}{j} = m H_n \cdot a_{\max},$$

where $H_n \coloneqq \sum_{j=1}^n \frac{1}{j}$ is the harmonic numbers function.

Using the above inequalities, we get the following bound on the expected number of steps of $(1 + \varepsilon)$ -BRD, analogously to (12):

$$\mathbb{E}\left[T\right] \le \mathbb{E}\left[\min\left\{\left(1+\frac{1}{\varepsilon}\right)\frac{nmH_n}{a_{\min}}\ln\left(\frac{m}{a_{\min}}\right), (n+1)^m\right\}\right].$$

Similarly to our derivation in Section 3.3.1, we can deploy Lemma 1, this time with parameters $\mu \leftarrow m, \alpha \leftarrow \left(1 + \frac{1}{\varepsilon}\right) nmH_n = O\left(\frac{1}{\varepsilon}mn\log n\right) = \tilde{O}\left(\frac{1}{\varepsilon}mn\right)$ and $\beta \leftarrow m\frac{\ln(n+1)}{\ln m} = \tilde{O}(m)$, to get the following bound

$$\mathbb{E}\left[T\right] = \tilde{O}\left(\phi\alpha\beta\mu\right) = \tilde{O}\left(\phi\cdot\frac{1}{\varepsilon}mn\cdot m\cdot m\right) = \tilde{O}\left(\frac{1}{\varepsilon}\phi nm^3\right).$$

Acknowledgments I am truly grateful to the anonymous reviewer of EC'24 who suggested the current, simplified approach over a previous version of the analysis in Section 3.2, and which resulted in an improved bound in (11), saving a logarithmic factor. The same reviewer also suggested a modification in the proof of Lemma 1, that resulted in an improvement in the bound in (6) as well. This allowed us to improve some powers of the polynomial factors in all our smoothed running time bounds.

References

- [ABPW17] Omer Angel, Sébastien Bubeck, Yuval Peres, and Fan Wei. "Local Max-Cut in Smoothed Polynomial Time". In: Proceedings of the 49th Annual Symposium on Theory of Computing (STOC). ACM, 2017, pp. 429–437. DOI: 10.1145/ 3055399.3055402 (cit. on p. 2).
- [ADKTWR08] Elliot Anshelevich, Anirban Dasgupta, Jon Kleinberg, Éva Tardos, Tom Wexler, and Tim Roughgarden. "The Price of Stability for Network Design with Fair Cost Allocation". In: *SIAM Journal on Computing* 38.4 (2008), pp. 1602–1623. DOI: 10.1137/070680096 (cit. on p. 12).
- [AMR11] David Arthur, Bodo Manthey, and Heiko Röglin. "Smoothed Analysis of the k-Means Method". In: *Journal of the ACM* 58.5 (2011), 19:1–19:31. DOI: 10. 1145/2027216.2027217 (cit. on p. 2).
- [ARV08] Heiner Ackermann, Heiko Röglin, and Berthold Vöcking. "On the Impact of Combinatorial Structure on Congestion Games". In: *Journal of the ACM* 55.6 (2008), pp. 1–22. DOI: 10.1145/1455248.1455249 (cit. on pp. 1, 11).
- [BCC21] Ali Bibak, Charles Carlson, and Karthekeyan Chandrasekaran. "Improving the Smoothed Complexity of FLIP for Max Cut Problems". In: ACM Transactions on Algorithms 17.3 (2021), 19:1–19:38. DOI: 10.1145/3454125 (cit. on p. 2).
- [BKM20] Shant Boodaghians, Rucha Kulkarni, and Ruta Mehta. "Smoothed Efficient Algorithms and Reductions for Network Coordination Games". In: 11th Innovations in Theoretical Computer Science Conference (ITCS). Vol. 151. 2020, 73:1–73:15. DOI: 10.4230/LIPIcs.ITCS.2020.73 (cit. on p. 2).
- [BR15] Tobias Brunsch and Heiko Röglin. "Improved Smoothed Analysis of Multiobjective Optimization". In: *Journal of the ACM* 62.1 (2015), 4:1–4:58. DOI: 10.1145/2699445 (cit. on p. 2).
- [BSS98] Philip J. Boland, Moshe Shaked, and J. George Shanthikumar. "Stochastic Ordering of Order Statistics". In: *Handbook of Statistics*. Ed. by N. Balakrishnan and C. R. Rao. Vol. 16. Elsevier, 1998. Chap. 5, pp. 89–103. DOI: 10.1016/s0169-7161(98)16007-8 (cit. on p. 8).
- [BV06] Rene Beier and Berthold Vöcking. "Typical Properties of Winners and Losers in Discrete Optimization". In: SIAM Journal on Computing 35.4 (2006), pp. 855–881. DOI: 10.1137/s0097539705447268 (cit. on pp. 2, 5).
- [CFGS11] Ioannis Caragiannis, Angelo Fanelli, Nick Gravin, and Alexander Skopalik.
 "Efficient Computation of Approximate Pure Nash Equilibria in Congestion Games". In: Proceedings of the 52nd IEEE Annual Symposium on Foundations of Computer Science (FOCS). 2011, pp. 532–541. DOI: 10.1109/focs.2011.50 (cit. on p. 11).
- [CGVYZ20] Xi Chen, Chenghao Guo, Emmanouil-Vasileios Vlatakis-Gkaragkounis, Mihalis Yannakakis, and Xinzhi Zhang. "Smoothed Complexity of Local Max-Cut and Binary Max-CSP". In: Proceedings of the 52nd Annual Symposium on Theory of Computing (STOC). 2020, pp. 1052–1065. DOI: 10.1145/3357713.3384325 (cit. on p. 2).
- [ER17] Michael Etscheid and Heiko Röglin. "Smoothed Analysis of Local Search for the Maximum-Cut Problem". In: *ACM Transactions on Algorithms* 13.2 (2017), 25:1–25:12. DOI: 10.1145/3011870 (cit. on pp. 2, 5).

- [ERV14] Matthias Englert, Heiko Röglin, and Berthold Vöcking. "Worst Case and Probabilistic Analysis of the 2-Opt Algorithm for the TSP". In: *Algorithmica* 68.1 (2014), pp. 190–264. DOI: 10.1007/s00453-013-9801-4 (cit. on p. 2).
- [ERV16] Matthias Englert, Heiko Röglin, and Berthold Vöcking. "Smoothed Analysis of the 2-Opt Algorithm for the General TSP". In: *ACM Transactions on Algorithms* 13.1 (2016), pp. 1–15. DOI: 10.1145/2972953 (cit. on pp. 2, 5).
- [ET11] Robert Elsässer and Tobias Tscheuschner. "Settling the Complexity of Local Max-Cut (Almost) Completely". In: International Colloquium on Automata, Languages, and Programming (ICALP). Ed. by Luca Aceto, Monika Henzinger, and Jiří Sgall. 2011, pp. 171–182. DOI: 10.1007/978-3-642-22006-7_15 (cit. on p. 2).
- [FGKS17] Matthias Feldotto, Martin Gairing, Grammateia Kotsialou, and Alexander Skopalik. "Computing Approximate Pure Nash Equilibria in Shapley Value Weighted Congestion Games". In: Proceedings of the 13th International Conference on Web and Internet Economics (WINE). 2017, pp. 191–204. DOI: 10.1007/978-3-319-71924-5_14 (cit. on p. 11).
- [FPT04] Alex Fabrikant, Christos Papadimitriou, and Kunal Talwar. "The Complexity of Pure Nash Equilibria". In: *Proceedings of the 36th Annual ACM Symposium on Theory of Computing (STOC)*. 2004, pp. 604–612. DOI: 10.1145/1007352. 1007445 (cit. on p. 1).
- [GGM22] Yiannis Giannakopoulos, Alexander Grosz, and Themistoklis Melissourgos. "On the Smoothed Complexity of Combinatorial Local Search". In: *CoRR* abs/2211.07547 (Nov. 2022). arXiv: 2211.07547 (cit. on pp. 2, 5, 10, 11).
- [GNS22] Yiannis Giannakopoulos, Georgy Noarov, and Andreas S. Schulz. "Computing Approximate Equilibria in Weighted Congestion Games via Best-Responses".
 In: Mathematics of Operations Research 47.1 (2022), pp. 643–664. DOI: 10. 1287/moor.2021.1144 (cit. on p. 11).
- [HT09] Thomas Dueholm Hansen and Orestis A. Telelis. "Improved Bounds for Facility Location Games with Fair Cost Allocation". In: 3rd International Conference on Combinatorial Optimization and Applications (COCOA). Ed. by Ding-Zhu Du, Xiaodong Hu, and Panos M. Pardalos. 2009, pp. 174–185. DOI: 10.1007/978-3-642-02026-1_16 (cit. on p. 12).
- [JPY88] David S. Johnson, Christos H. Papadimitriou, and Mihalis Yannakakis. "How easy is local search?" In: *Journal of Computer and System Sciences* 37.1 (1988), pp. 79–100. DOI: 10.1016/0022-0000(88)90046-3 (cit. on p. 1).
- [KM72] Victor Klee and George J. Minty. "How Good is the Simplex Slgorithm". In: Inequalities III. Ed. by O. Sisha. New York, 1972, pp. 159–175 (cit. on p. 2).
- [Mit70] Dragoslav S. Mitrinović. *Elementary Inequalities*. P. Noordhoof, 1970 (cit. on p. 8).
- [MS96] Dov Monderer and Lloyd S. Shapley. "Potential games". In: Games and Economic Behavior 14.1 (1996), pp. 124–143. DOI: 10.1006/game.1996.0044 (cit. on p. 1).
- [Ros73] Robert W. Rosenthal. "A Class of Games Possessing Pure-Strategy Nash Equilibria". In: International Journal of Game Theory 2.1 (1973), pp. 65–67. DOI: 10.1007/BF01737559 (cit. on pp. 1, 4).

[Ros96]	Sheldon M. Ross. <i>Stochastic Processes</i> . Second. John Wiley & Sons, 1996. ISBN: 978-0-471-12062-9 (cit. on p. 8).
[Rou16]	Tim Roughgarden. "Pure Nash Equilibria and PLS-Completeness". In: <i>Twenty Lectures on Algorithmic Game Theory</i> . Cambridge University Press, 2016, pp. 261–278. DOI: 10.1017/CB09781316779309.020 (cit. on p. 11).
[Rou21]	Tim Roughgarden, ed. <i>Beyond the Worst-Case Analysis of Algorithms</i> . Cambridge University Press, 2021. DOI: 10.1017/9781108637435 (cit. on pp. 2, 5).
[RV07]	Heiko Röglin and Berthold Vöcking. "Smoothed analysis of Integer Programming". In: <i>Mathematical Programming</i> 110.1 (2007), pp. 21–56. DOI: 10.1007/s10107-006-0055-7 (cit. on p. 2).
[ST04]	Daniel A. Spielman and Shang-Hua Teng. "Smoothed analysis of algorithms". In: <i>Journal of the ACM</i> 51.3 (2004), pp. 385–463. DOI: 10.1145/990308.990310 (cit. on pp. 2, 5).
[ST09]	Daniel A. Spielman and Shang-Hua Teng. "Smoothed Analysis: An Attempt to Explain the Behavior of Algorithms in Practice". In: <i>Commun. ACM</i> 52.10 (2009), pp. 76–84. DOI: 10.1145/1562764.1562785 (cit. on p. 2).
[SV08]	Alexander Skopalik and Berthold Vöcking. "Inapproximability of pure Nash equilibria". In: <i>Proceedings of the 40th Annual ACM Symposium on Theory of Computing (STOC)</i> . 2008, pp. 355–364. DOI: 10.1145/1374376.1374428 (cit. on pp. 2, 8, 10).
[Syr10]	Vasilis Syrgkanis. "The Complexity of Equilibria in Cost Sharing Games". In: 6th International Workshop on Internet and Network Economics. Ed. by Amin Saberi. 2010, pp. 366–377. DOI: 10.1007/978-3-642-17572-5_30 (cit. on p. 12).