Stability Analysis of Trajectories on Manifolds with Applications to Observer and Controller Design

Dongjun Wu¹, Bowen Yi² and Anders Rantzer¹

Abstract— This paper examines the local exponential stability (LES) of trajectories for nonlinear systems on Riemannian manifolds. We present necessary and sufficient conditions for LES of a trajectory on a Riemannian manifold by analyzing the complete lift of the system along the given trajectory. These conditions are coordinate-free which reveal fundamental relationships between exponential stability and incremental stability in a local sense. We then apply these results to design tracking controllers and observers for Euler-Lagrangian systems on manifolds; a notable advantage of our design is that it visibly reveals the effect of curvature on system dynamics and hence suggests compensation terms in the controller and observer. Additionally, we revisit some wellknown intrinsic observer problems using our proposed method, which largely simplifies the analysis compared to existing results.

I. INTRODUCTION

Many physical systems are naturally modelled on Riemannian manifolds. The most important example may refer to a class of mechanical systems with configuration spaces being Riemannian manifolds, rather than Euclidean spaces [1]. Another well known example appears in quantum systems [2], in which systems state lives on Lie groups [3].

It is well known that local stability of equilibria for systems, whose state space is on Riemannian manifolds, can be analyzed via linearization in local coordinate—similar to the case in Euclidean space—known as the Lyapunov indirect method. In many practically important control tasks, we are very interested in the stability of a particular solution $X(\cdot)$, the problem of which widely arises in observer design, trajectory tracking [4], orbital stabilization [5], and synchronization [6]. In Euclidean space, these tasks, or equivalently the stability of a solution $X(\cdot)$, may be solved by introducing an error variable and then studying the error dynamics, which is usually a nonlinear time-varying system. In particular, the local exponential stability (LES) of $X(\cdot)$ for a given nonlinear system can be characterized by the linearization of its error dynamics near the trajectory.

A similar problem arises in contraction and incremental stability analysis [7], [8], in which we are interested in the attraction of any two trajectories to each other, rather than a particular one $X(\cdot)$. The basic idea is to explore the stability of a linearized dynamics, regarded as first-order approximation, to obtain the incremental stability of the given system. Indeed, studying the stability of a *particular* solution via first-order approximation has already been used, which, from the perspective of incremental stability, is known as partial (or virtual) contraction [8], [9]. As discussed above, some excitation conditions of the given trajectory may be needed to continue stability analysis.

² B. Yi is with Robotics Institute, University of Technology Sydney, Sydney, NSW 2006, Australia bowen.yi@uts.edu.au. A successful application may be found in [10] for the stability of extended Kalman filter (EKF).

For the system evolving on Riemannian manifolds, however, the stability analysis of a solution $X(\cdot)$ is much more challenging. The difficulty arises from two aspects. On one hand, the "error dynamics" for such a case is more involved—there are, indeed, no generally preferred definition of tracking (or observation, synchronization) errors—the induced Riemannian distance on manifolds can hardly be used to derive error dynamics directly. In practice, one has to choose an error vector according to the structure of the manifold, see [4], [11], [12] for examples. On the other hand, the alternative method, via first-order approximation (or partial contraction), is non trivial to be applied to Riemannian manifolds, since it is usually a daunting task to calculate the differential dynamics on Riemannian manifolds, and also some complicated calculations of parallel transport are involved. Overcoming these two major challenges is the main motivation of the paper.

To address this, we provide in this paper an alternative way to study LES of trajectories on Riemannian manifolds, namely, LES will be characterized by the stability of the *complete lift* of the system along the trajectory, in this way removing the need of obtaining error dynamics. Complete lift, or tangent lift, has been used to study various control problems, see for example [1], [13]–[16]. Among the listed references, the most relevant work to ours are [15], [16]. In [16] the authors have remarked that the complete lift can be seen as a linearization procedure. However, the verification of stability of the complete lift system is challenging since it is a system living in the tangent bundle and thus how to effectively use the aforementioned characterization to guide controller and observer design is an open question. We address this question in this paper.

The main contributions of the paper are three folds.

- Establish the relationship between LES of a solution to the stability of the complete lift along this solution on a Riemannian manifold, which can be seen as the Lyapunov indirect method on manifolds. Then show that LES of a solution is equivalent to local contraction near the solution $X(\cdot)$.
- Propose an alternative approach for analysis of LES based on the characterization of complete lift system. This novel approach obviates the calculation of complete lift and hence facilitates the analysis of local exponential stability and contraction. We demonstrate the efficiency of the proposed methods by revisiting some well-known research problems.
- Two main types of application problems are studied, namely, controller and observer design, especially for mechanical systems on manifolds. These results largely simplify the analysis in some existing works. In particular, the proposed method is quite efficient for analyzing a class of systems called Killing systems.

Notation. Throughout this paper we use rather standard notations from Riemannian geometry [17], [18]. Denote M the Riemannian manifold of dimension n, $\langle \cdot, \cdot \rangle$ the metric, ∇ the Levi-Civita connection, R(X, Y)Z the Riemannian curvature, $\pi : TM \to M$ the natural projection of the tangent bundle. We use ∇ and grad (\cdot) interchangeably to represent the gradient operator. Let Hess (\cdot) be

^{*}This project has received funding from the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme under grant agreement No 834142 (Scalable-Control).

D. Wu and A. Rantzer are with the Department Automatic Control, University, Box of Lund 118. SE-221 00 Lund, Sweden dongjun.wu@control.lth.se, anders.rantzer@control.lth.se.

the Hessian, $\exp(\cdot)$ the exponential map, $P_x^y : T_xM \to T_yM$ the parallel transport from T_xM to T_yM , d(x,y) the Riemannian distance between x and y, and $B_c(x) = \{\xi \in M | d(\xi, x) \leq c\}$ the Riemannian ball. Let $\phi^f(t; t_0, x_0)$ be the flow of the equation $\dot{x} = f(x, t)$; and we sometime write $\phi(\cdot)$ when clear from the context. The notation L_fY stands for Lie derivative of Y along f.

II. LOCAL EXPONENTIAL STABILITY ON RIEMANNIAN MANIFOLDS

A. Theory: LES and Complete Lift

Consider a system

$$\dot{x} = f(x, t) \tag{1}$$

with the system state x on the Riemannian manifold M, and $X(\cdot)$ a particular solution, *i.e.*, $\dot{X}(t) = f(X(t), t)$ from the initial condition $X(t_0) = X_0 \in M$. We study the local exponential stability of the solution X(t). Some definitions are recalled below.

Definition 1: The solution $X(\cdot)$ of the system (1) is *locally exponentially stable* (LES) if there exist positive constants c, K and λ , all independent of t_0 , such that

$$d(x(t), X(t)) \le K d(x(t_0), X(t_0)) e^{-\lambda(t-t_0)},$$

for all $t \ge t_0 \ge 0$ and $x(t_0)$ satisfying $d(x(t_0), X(t_0)) < c$.

Remark 1: For the case that X(t) is a trivial solution at an equilibrium, *i.e.*, $X(t) \equiv X_0$, $\forall t \ge t_0$, Definition 2 coincides with the standard definition of LES of an equilibrium. We should also notice the peculiarity of this definition—it may happen that the union of LES solutions forms into a dense set. For example, every solution of $\dot{x} = Ax$ is LES when A is Hurwitz.

We recall the definition of complete lift of a vector field, see [19], [20] for more detailed discussions.

Definition 2 (Complete Lift): Consider the time-varying vector field f(x,t). Given a point $v \in TM$, let $\sigma(t,s)$ be the integral curve of f with $\sigma(s,s) = \pi(v)$. Let V(t) be the vector field along σ obtained by Lie transport of v by f. Then (σ, V) defines a curve in TM through v. For every $t \ge s$, the complete lift of f into TTM is defined at v as the tangent vector to the curve (σ, V) at t = s. We denote this vector field by $\tilde{f}(v,t)$, for $v \in TM$.

Definition 3: Given the system (1), and a solution X(t). Define the complete lift of the system (1) along X(t) as

$$\dot{v} = f(v,t), \ v(t) \in T_{X(t)}M \tag{2}$$

where \tilde{f} is the complete lift of f as in Definition 2.

The most important property of the complete lift system is *linearity* at a fixed fibre. We refer the reader to [15] for coordinate expression of (2). From this definition, one can easily verify that the solution to (2), *i.e.*, v(t) has the property that $\pi v(t) = X(t)$. Hence we say that (2) defines a dynamical system along the particular solution X(t).

The following simple characterization is the theoretical basis of this paper. It can be viewed as an analogue of the Lyapunov indirect method on Riemannian manifolds.

Theorem 1: Assume the system (1) is forward complete for $t \ge 0$. If the solution X(t) is LES, then the complete lift of the system (1) along $X(\cdot)$ is exponentially stable. If the solution $X(\cdot)$ is bounded, the converse is also true.

Proof: (\Longrightarrow) Assume that the solution X(t) is LES. Denote the minimizing normalized (*i.e.* with unit speed) geodesic joining $X(t_0)$ to $x(t_0)$ as $\gamma : [0, \hat{s}] \to M$, with $\gamma(0) = X(t_0)$, $\gamma(\hat{s}) = x(t_0)$ and $0 \le \hat{s} = d(X(t_0), x(t_0))$. Let $v_0 \in TM$ with $\pi(v_0) = X(t_0)$ and $v_0 = \gamma'(0)$, and v(t) be the solution to the complete lift system (2). Then

$$\hat{s} |v(t)| = d\left(\exp_{X(t)}\left(\hat{s}v(t)\right), X(t)\right),\tag{3}$$

where $\exp_x : TM \to M$ is the exponential map, by choosing \hat{s} sufficiently small such that \exp is defined. Using the metric property of d, we have

$$d\left(\exp_{X(t)}\left(\hat{s}v(t)\right), X(t)\right)$$

$$\leq d\left(\exp_{X(t)}\left(\hat{s}v(t)\right), x(t)\right) + d(x(t), X(t)) \tag{4}$$

$$\leq d\left(\exp_{X(t)}\left(\hat{s}v(t)\right), x(t)\right) + K\hat{s}e^{-\lambda(t-t_0)},\tag{5}$$

where the second inequality follows from Definition 1. Fixing t at the moment and invoking (3) and (5) we get

$$|v(t)| \leq \kappa(\hat{s}) + Ke^{-\lambda(t-t_0)}$$

$$\kappa(\hat{s}) := \frac{d\left(\exp_{X(t)}\left(\hat{s}v(t)\right), x(t)\right)}{\hat{s}}.$$
(6)

Note that more precisely κ is a function of both t and \hat{s} . But omitting the t argument does not affect the following analysis.

Now we need to show the term $\kappa(\hat{s})$ is of order $O(\hat{s})$. Since $x(t_0) = \gamma(\hat{s})$, this term can be rewritten as

$$(s) = \frac{d\left(\exp_{X(t)}\left(sv(t)\right), \phi(t; t_0, \gamma(s))\right)}{s}$$

where we have replaced \hat{s} by s. To this end, we consider two functions $\alpha_1(s) = \exp_{X(t)}(sv(t)), \alpha_2(s) = \phi(t; t_0, \gamma(s))$. Similarly, we have omitted the t argument which does not affect the proof. We have $\alpha_1(0) = \alpha_2(0) = X(t)$ and $\alpha'_1(0) = \alpha'_2(0) = v(t)$. Thus

$$\kappa(s) = \frac{1}{s}d(\alpha_1(s), \alpha_2(s)) = O(s),$$

where we have used Lemma 3 given in Appendix. Now letting $\hat{s} \to 0$ in (6) and noticing that the geodesic is unit speed, we have

$$|v(t)| \le K|v(t_0)|e^{-\lambda(t-t_0)}$$

for any $v(t_0) \in T_{X(t_0)}M$.

 κ

(\Leftarrow) A consequence of Proposition 1 (see Section II-B): If the complete lift along $X(\cdot)$ is ES, then the proof of Proposition 1 shows that the system is contractive on a bounded set B_c and thus the LES of $X(\cdot)$.

Remark 2: Theorem 1 provides a characterization for LES of trajectories on manifolds via complete lift. Unfortunately, the original form of this theoretical result lacks practical utility for applications. The main reason is that the complete lift on manifolds is difficult to obtain, and quite often, its calculation of it relies on local coordinates, which is in conflict with the purpose (coordinate-free design) of this paper. To circumvent this issue, we propose an alternative approach in Section II-C based on Theorem 1, which will be much more efficient to use. But we must emphasize that Theorem 1 plays the fundamental role for the rest of the paper.

From Theorem 1, we can derive the following interesting corollary which says that there no unbounded LES solution exists for *autonomous* systems.

Corollary 1: For a time invariant system $\dot{x} = f(x)$, a LES solution X(t) should always be bounded and non-periodic.

Proof: The complete lift of $\dot{x} = f(x)$ is $\dot{v} = \frac{\partial f}{\partial x}v$, $v \in T_x \mathbb{R}^n$. Clearly, $v = \dot{x}$ is a solution to the complete lift system. Then by Theorem 1, $|\dot{X}(t)| \leq k |\dot{X}(0)| e^{-\lambda t}$, hence X(t) cannot be periodic. Further more, $|X(t)| \leq |X(0)| + \int_0^t k |\dot{X}(0)| e^{-\lambda s} ds = |X(0)| + \frac{k |\dot{X}(0)|}{\lambda} (1 - e^{-\lambda t}) < |X(0)| + \frac{k |\dot{X}(0)|}{\lambda}$.

In [21, Lemma 1], the authors obtain a similar result for autonomous systems, *i.e.*, there is a unique attractive equilibrium in an invariant set, in which the system is incrementally exponentially stable.

B. Contraction and LES

Contraction theory has become a powerful tool for analysis and design of control systems, see [6]–[8], [22]–[24] and the references therein. In Section II-A, we have studied LES of solutions to the system (1). In this subsection, we will show the close connection between the proposed result and contraction analysis on manifolds [15], [25]. The reader may refer to [22], [26] for the case on Euclidean space.

We say that the system (1) is contractive on a set C if there exist positive constants K, λ , independent of t_0 such that

$$d(\phi(t;t_0,x_1),\phi(t;t_0,x_2)) \le K d(x_1,x_2) e^{-\lambda(t-t_0)},$$
(7)

for all $x_1, x_2 \in C, t \geq t_0 \geq 0$. For technical ease, we have slightly modified the definition of contraction by allowing the set C to be not forward invariant. Based on Theorem 1, we have the following proposition, which can be viewed as a bridge from LES to local contraction.

Proposition 1: A bounded solution X(t) to the system (1) is LES if and only if there exists a constant c such that the system (1) is contractive on a bounded set B_c whose interior contains $X(\cdot)$.

Proof: Assume that X(t) is LES. Then the complete lift system along X(t) is exponential stable (ES) by Theorem 1. By converse Lyapunov theorem, there exists a C^1 function V(t, v), quadratic in v satisfying

$$c_1|v|^2 \le V(t,v) \le c_2|v|^2, \ \forall v \in T_{X(t)}M$$
 (8)

and

$$\dot{V}(t,v) = \frac{\partial V}{\partial t}(t,v) + L_{\tilde{f}}V(t,v) \le -c_3|v|^2, \ \forall v \in T_{X(t)}M, \ (9)$$

for all $t \ge t_0 \ge 0$ and three positive constants c_1, c_2, c_3 .

Due to the smoothness of V, we have

$$|\dot{V}(t, P_{X(t)}^{x(t)}v) - \dot{V}(t, v)| \le c_4 d_{TM}(P_{X(t)}^{x(t)}v, v) = c_4 d_M(x(t), X(t)).$$

Thus

$$\sup_{\substack{|w|=1,\\w\in T_{X(t)}M}} \dot{V}(t,w) = \sup_{\substack{|v|=1,\\v\in T_{X(t)}M}} \dot{V}(t,P_{X(t)}^{x(t)}v)$$
$$= \sup_{\substack{|v|=1,\\v\in T_{X(t)}M}} \dot{V}(t,v) + \dot{V}(t,P_{X(t)}^{x(t)}v) - \dot{V}(t,v)$$
$$\leq -c_3 + c_4 d(x(t),X(t)) < -c_5 < 0,$$

for c small enough such that d(x(t), X(t)) will be small enough for all $t \ge t_0$ when $x(t_0) \in B_c(X(t_0))$. Since \dot{V} is quadratic in v (due to the linearity of the complete lift system and that V(t, v) is quadratic in v), this implies

$$\dot{V}(t,v) \leq -c_5 |v|^2, \ \forall v \in T_{x(t)}M, \ t \geq t_0$$

for all $x(t_0) \in B_c(X(t_0))$. Then the system (1) is contractive on $B_c := \bigcup_{t_0 \ge 0} B_c(X(t_0))$ which is bounded as is $X(\cdot)$ (use Theorem 2 [15]). The converse is obvious, and hence the proof is completed.

The following corollary is a straightforward consequence.

Corollary 2: Assume that the system (1) has an equilibrium point $x_{\star} \in M$. Then x_{\star} is LES if and only if there exists an open neighborhood of x_{\star} on which the system is contractive.

In [27], the authors proved similar result to this corollary for *autonomous* systems in Euclidean space. The paper [22] focuses on asymptotic stability and asymptotic contraction, also in Euclidean space.

C. A More Usable Form

As remarked earlier, Theorem 1 is not suitable for practical applications due to the difficulty of calculating the complete lift system. In this subsection, we propose a more usable version of Theorem 1 (still intrinsic) which will make the analysis of LES a routine task.

For reasons that will be clear later, we rename the state x in the system (1) as q. Fig. 1 is drawn to illustrate our idea. In Fig. 1, the solid curve represents a trajectory of the system system (1), say $q : \mathbb{R}_{\geq 0} \to M$, whose velocity vectors are drawn as black arrows, denoted \dot{q} . The dashed curves are flows of the initial curve $\gamma : s \mapsto \gamma(s) \in M$. The blue arrows emanating from the curve q are the (transversal) velocities of the dashed curve, denoted as q', or in precise language, $q' = \frac{\partial q(s,t)}{\partial s}$ for the parameterized curve $(s,t) \mapsto q(s,t)$. We call q' a variation along $q(\cdot)$.



Fig. 1. Illustration of \dot{q} and q'.

Two important observations can be made from the figure:

- By construction, q' is the solution to the complete lift of the system (1) along the trajectory $q(\cdot)$. Thanks to this, the Lie bracket $[\dot{q}, q']$ vanishes for all $t \ge t_0$ along $q(\cdot)$.¹
- The map $(s,t) \mapsto q(s,t)$ forms a parameterized surface in M. Then due to the torsion-free property of Levi-Civita connection, there holds $\frac{D}{dt} \frac{\partial q}{\partial s} = \frac{D}{ds} \frac{\partial q}{\partial t}$ (see (35) and [17, Lemma 3.4]), which implies that $\nabla_{\dot{q}} \dot{q}' = \nabla_{q'} \dot{q} = \nabla_{q'} f$.

Now that q' is the solution to the complete lift system, it is sufficient to analyze the dynamics of q'. This may seem naïve at the first thought and that the novelty seems to be only at a notational level. The fact is, however, due to the above two observations, we now have access to rich results in Riemannian geometry. In particular, we will see how LES on Riemannian manifold is affected by curvature – the most important ingredient of a Riemannian manifold.

D. Revisit of some existing results

1) Contraction on Riemannian manifolds [25]: The following result is obtained in [25] (the contraction version):

Theorem 2 ([25]): Let $q(\cdot)$ be a solution to the system (1), if

$$\langle \nabla_v f, v \rangle \leq -k \langle v, v \rangle, \ \forall v \in T_{q(t)} M, \ t \geq 0,$$

for some positive constant k, then the solution q(t) is LES. The proof of this theorem will now simplify to a few lines: *Proof:* It suffices to show the exponential convergence of the metric $\langle q', q' \rangle$. Indeed,

$$\frac{1}{2}\frac{d}{dt}\langle q',q'\rangle = \left\langle \nabla_{\dot{q}}q',q'\right\rangle = \left\langle \nabla_{q'}f,q'\right\rangle \le -k\left\langle q',q'\right\rangle.$$

Thus $\langle q', q' \rangle$ converges exponentially.

Notice that we have used the fact that $[q', \dot{q}] = 0$.

¹Recall that
$$[X,Y] = \frac{d}{dt}\Big|_{t_0} (\phi_t^X)^* Y(t_0),$$
 thus $[\dot{q},q'] = \frac{d}{dt}\Big|_{t_0} (\phi_t^f)^* (\phi_t^f)_* q'(t_0) = \frac{d}{dt}\Big|_{t_0} q'(t_0) = 0.$

2) Intrinsic reduced observer [28]: The following lemma was among the key results in [28]:

Lemma 1 ([28]): Let M be a smooth Riemannian manifold. Let $P \in M$ be fixed. On the subspace of M defined by the injectivity radius at P, we consider

$$\dot{q} = -\frac{1}{2\lambda} \operatorname{grad} d(q, P)^2, \quad \lambda > 0.$$
 (10)

If the sectional curvature is non-positive, the dynamics is a contraction in the sense of [7], i.e., if δx is a virtual displacement at fixed t, we have

$$\frac{d}{dt}\left\langle \delta q, \delta q \right\rangle \le -\frac{2}{\lambda}\left\langle \delta q, \delta q \right\rangle. \tag{11}$$

If the sectional curvature is upper bounded by A>0, then (12) holds for $d(q,P)<\pi/(4\sqrt{A})$.

The proof provided in [28] is a bit technical. We now give a simplified proof using the methods developed in this paper and provide a new estimation of the convergence rate.

Lemma 2: Let M be a smooth Riemannian manifold whose curvature is upper bounded by $A \ge 0$. Let $P \in M$ be fixed. Then the dynamics (10) is globally contractive if A = 0, and locally contractive otherwise, with contraction rate $\gamma(q) = \frac{2\sqrt{Ad(q,P)}}{\lambda \tan(\sqrt{Ad(q,P)})}^2$, i.e.,

$$\frac{d}{dt} \langle \delta q, \delta q \rangle \leq -\gamma \langle \delta q, \delta q \rangle .$$
(12)
Proof: Let $F(q) = \frac{1}{2} d(q, P)^2$ and we estimate

$$\frac{d}{dt} \left\langle q', q' \right\rangle = 2 \left\langle -\frac{1}{\lambda} \nabla_{q'} \nabla F, q' \right\rangle$$
$$= -\frac{2}{\lambda} \operatorname{Hess} F(q', q')$$

where the last equality follows from the definition of the Hessian operator, see (36). The conclusion follows invoking comparison for the Hessian of square distance (e.g., [29, Theorem 6.6.1]):

$$\operatorname{Hess} F \geq \sqrt{A}d(q,P)\cot(\sqrt{A}d(q,P))\operatorname{Id}$$

for all $q \in inj(P)$ if A > 0 and for all $q \in M$ if A = 0.

Remark 3: The second part of the Lemma 1 [28] seems incorrect: by Rauch comparison (see [18, Theorem 6.4.3]), for manifold with sectional curvature lower bounded by k > 0, there holds Hess $F \le (1 - kF)g$, where g is the Riemannian metric. Therefore, the contraction rate is strictly less than $\frac{2}{\lambda}$ in any neighborhood of P.

Remark 4: Since $\text{Hess } F|_P = g$, if the Hessian is continuous at P, then the dynamics (10) is always locally contractive without assumptions on curvature, which also implies that P is an LES equilibrium.

The above method is not limited to study contraction of distance, in fact, it can be easily adapted to study k-contraction [30] (Hausdorff measure such as area and volume) on Riemannian manifolds. As an example, let us consider the contraction of volume. Suppose that $\{q'_1, \dots, q'_n\}$ forms a frame at q and denote $vol(q'_1, \dots, q'_n)$ the signed volume of the parallelepiped spanned by this frame and we study the change of the volume under the dynamics (12):

$$\frac{d}{dt}\operatorname{vol}(q'_1, q'_2, \cdots, q'_n)$$

= $-(\operatorname{div} \nabla F/\lambda)\operatorname{vol}(q'_1, q'_2, \cdots, q'_n)$ (13)
= $-\frac{\Delta F}{\lambda}\operatorname{vol}(q'_1, q'_2, \cdots, q'_n)$

where Δ is the Laplace-Beltrami operator [29]. Now $\Delta F = \text{tr}(G^{-1} \text{Hess } F)$, with G the Riemannian metric, we can conclude that the condition in Lemma 2 implies exponential contraction of

 ${}^{2}\gamma(P)$ is understood as $\lim_{d(q,P)\to 0} \gamma(q) = \frac{2}{\lambda}$. Notice that γ is monotone decreasing and strictly positive on the interval $[0, \frac{\pi}{2})$

volume (on non-positive curvature manifold). Since ΔF is controlled by $\operatorname{tr}(G^{-1} \operatorname{Hess} F)$, non-positive curvature assumption is too restrictive. In fact, $\Delta F = 1 + H(q, P)d(q, P)$, where H(q, P) is the mean curvature, thus the same conclusion can be drawn for manifold with non-positive mean curvature.

Remark 5: From the proof of Lemma 2 we see that the function F need not be the square distance. It can be replaced by any function whose Hessian has the required property, as the next example shows.

3) Filtering on SO(3): Consider first the attitude control problem

$$\dot{R} = Ru \tag{14}$$

where $R \in SO(3)$ and the control input $u \in \mathfrak{so}(3)$. The control objective is to exponentially stabilize a solution $R_*(t) \in SO(3)$, which verifies $\dot{R}_*(t) = R_*(t)\Omega(t)$, where $\Omega(t)$ is some known signal. The Lie group SO(3) is a Riemannian manifold with the bi-invariant metric $\langle X, Y \rangle = \operatorname{tr}(X^\top Y)$. Due to the bi-invariance of the metric, the Levi-Civita connection is simply $\nabla_X Y = \frac{1}{2}[X, Y]$, see (38). Consider the function

$$F(R, R_*) = \frac{1}{2} ||R - R_*||^2,$$

where $||\cdot||$ is the Frobenius norm (*F* is not the square distance). The gradient and Hessian of *F* can be calculated as $\nabla F = \frac{1}{2}R(R_*^{\top}R - R^{\top}R_*)$, Hess $F(RY, RZ) = \frac{1}{4}\operatorname{tr}(Z^{\top}YR_*^{\top}R)$, with $X, Y \in \mathfrak{so}(3)$ respectively. Clearly, $R_*(\cdot)$ is the solution to

$$\begin{split} \dot{R} &= -k\nabla F(R,R_*) + R\Omega(t) \\ &= -\frac{k}{2}R(R_*^{\top}(t)R - R^{\top}R_*(t)) + R\Omega(t). \end{split}$$

Let us check the LES of the $R_*(\cdot)$. For $T_RSO(3) \ni R' = RX$ for some $X \in \mathfrak{so}(3)$, we calculate

$$\frac{1}{2}\frac{d}{dt}\left\langle R',R'\right\rangle = -k\operatorname{Hess} F(R',R') + \left\langle \nabla_{R'}(R\Omega(t)),R'\right\rangle$$
$$= -k\operatorname{Hess} F(R',R') + \frac{1}{2}\left\langle [R',R\Omega(t)],R'\right\rangle$$
$$= -k\operatorname{Hess} F(R',R') + \frac{1}{2}\operatorname{tr}\{(X^{\top}X - XX^{\top})\Omega\}$$
$$= -k\operatorname{Hess} F(R',R')$$

since $X^{\top}X - XX^{\top}$ is symmetric. Note that the Hessian of F is positive definite at $R = R_*$. Hence the controller

$$u = -\frac{k}{2} (R_*^{\top}(t)R - R^{\top}R_*(t)) + \Omega(t).$$

renders the trajectory $R_*(\cdot)$ LES as expected.

The extension to the design of a low pass filter becomes straightforward: the following dynamics

$$\dot{\hat{R}} = -\frac{k}{2}\hat{R}(R^{\top}\hat{R} - R^{\top}\hat{R}) + \hat{R}\Omega$$
(15)

is a locally exponential observer (filter) for $\dot{R} = R\Omega$. This result has been obtained in [11], see also [12].

E. Killing system

1) Low-pass filter for Killing system: Consider a system defined by a time-varying Killing field [18, Chapter 8] on a Riemannian manifold (M, g):

$$\dot{q} = f(t, q) \tag{16}$$

i.e., $L_f g = 0$, see also (39) in Appendix. We call such system a Killing system. When the system (16) is perturbed by some noise, it is tempting to design a low pass filter to reconstruct the system state from the corrupted data q. For that, we propose the simple filter

$$\hat{q} = f(t, \hat{q}) - k\nabla F(\hat{q}, q), \tag{17}$$

where $F(q,p) = \frac{1}{2}d(q,p)^2$ and k is a positive constant. To verify the convergence of this filter, we calculate as before

$$\frac{1}{2}\frac{d}{dt}\langle \hat{q}', \hat{q}' \rangle = \langle \nabla_{\hat{q}'}(f - k\nabla F), \hat{q}' \rangle$$
$$= \langle \nabla_{\hat{q}'}f, \hat{q}' \rangle - k \langle \nabla_{\hat{q}'}\nabla F, \hat{q}' \rangle$$
$$= -k \langle \nabla_{\hat{q}'}\nabla F, \hat{q}' \rangle \text{ (by (39))}$$
$$= -k \operatorname{Hess} F(\hat{q}', \hat{q}').$$

Since Hess is locally positive definite, the filter converges at least locally. If in addition, the manifold has non-positive curvature, then the convergence is global recalling that Hess $F \ge g$ for manifold with non-positive curvature. This is the case for the manifold of symmetric positive definite matrices: SPD := $\{P \in \mathbb{R}^{n \times n} : P = P^{\top} > 0\}$ equipped with the metric $\langle X, Y \rangle := \operatorname{tr}(XP^{-1}YP^{-1})$ for $X, Y \in T_P$ SPD, see e.g., [31].

2) Discretization: Let us now consider the discretization of this filter. First, notice that f is Killing, thus the discretization of (16) may be written as $x_{k+1} = \tau \cdot x_k$ for some isometric action $\tau \in \text{Iso}(M)$ (τ is time-invariant since (16) is autonomous). This model has been considered in for example [32], where the manifold is the set of symmetric positive definite matrices and it is called a "linear system" on Riemannian manifolds. Next, viewing $-k\nabla F(\hat{q}, q)$ as disturbance, we may discretize (17) as

$$\hat{q}_{k+1} = \exp_{\tau \cdot \hat{q}_k} \left(k \Delta t \log_{\hat{q}_k} q_k \right)$$

where Δt is the sampling time and we use the standard notation $\log_x y = \exp_x^{-1} y$, see e.g. [33]. Indeed, fix q and let r(x) = d(x,q), then $\nabla r(x) = -\frac{\exp_x^{-1} q}{||\exp_x^{-1} q||}$, see [29, Lemma 5.1.3]. Thus $\nabla F = -\log_{\hat{q}} q$. For example, in Euclidean space $-\log_{\hat{q}} q = \hat{q} - q$, which is in accordance with $\nabla_{\hat{q}} \frac{1}{2} ||\hat{q} - q||^2$. Let $e_k = \log_{\hat{q}_k} q_k$ be the error, then

$$e_{k+1} = \log_{\hat{q}_{k+1}} q_{k+1}$$

= $\log_{\exp_{\tau} \cdot \hat{q}_k} (k\Delta t \log_{\hat{q}_k} q_k) \tau \cdot q_k$
 $\approx \log_{\tau} \cdot \hat{q}_k \tau \cdot q_k - k\Delta t \log_{\hat{q}_k} q_k$
= $D\tau \cdot \log_{\hat{q}_k} q_k - k\Delta t \log_{\hat{q}_k} q_k$
= $(D\tau - k\Delta t \operatorname{Id})e_k$

By assumption, $D\tau$ is a linear isometric mapping (unitary), therefore, e_k tends to zero exponentially for all sufficiently small sampling time.

3) Revisit of filter on SO(3): For a Lie group G equipped with a left- (resp. right-) invariant metric g, it is known that any right- (resp. left-) invariant vector fields are Killing fields, see for example [18, Chapter 8]. Indeed, equip G with a right-invariant metric and consider a left-invariant vector field $V(x) := dL_x(v)$ for $v \in \mathfrak{g}$ and $x \in G$, whose flow reads $F^t(x) = R_{\exp(tv)}x$; here L and R represent left and right action respectively. Thus $DF^t = dR_{\exp(tv)}$. Hence for any right-invariant vector fields $W_1(x) = dR_x(w_1), W_2(x) = dR_x(w_2)$, for $w_1, w_2 \in \mathfrak{g}$, we have

$$\left\langle DF^{t}(W_{1}), DF^{t}(W_{2}) \right\rangle = \left\langle dR_{\exp(tv)}(W_{1}), dR_{\exp(tv)}(W_{2}) \right\rangle$$
$$= \left\langle W_{1}, W_{2} \right\rangle_{x}$$
(right-invariant metric)
$$= \left\langle w_{1}, w_{2} \right\rangle,$$

which is constant for all $t \ge 0$. Summarizing, a system defined by left-invariant vector field (right-invariant is similar) e.g.,

$$\dot{x} = dL_x(v(t)), \quad x \in G, \ v(t) \in \mathfrak{g}, \ \forall t \ge 0$$
(18)

is a Killing system when the underling metric of G is right-invariant. Therefore, a low-pass filter can be designed using formula (17). In particular, for the system (14) on SO(3), when u is known, it reads $\hat{R} = \hat{R}u + k \log_{\hat{R}} R = \hat{R}u + k \log_{\hat{R}} R$ when SO(3) is equipped with the standard bi-invariant metric. Thus we obtain another low-pass filter for left-invariant dynamics on SO(3).

III. APPLICATION TO EULER-LAGRANGIAN SYSTEMS

In this section, we utilize the proposed methods to study LES of trajectories of Euler-Lagrangian (EL) systems. As pointed out in Section I, trajectory tracking and observer design are two typical important applications which involve the analysis of LES of trajectories. Compared to the analysis of stability of equilibrium, these tasks are generally much harder on manifolds. Most existing results rely on calculations in local coordinates, which is usually a daunting task. We demonstrate in this section that, the proposed approach can be efficiently used to design and analyze controllers and observers for mechanical systems, while obviating the calculation in local coordinates.

There are two pervasive approaches – Lagrangian and Hamiltonian – for modelling of mechanical systems [34]. These two different approaches have led to different design paradigms. Amongst the vast literature, we mention two books that include some of the most important results in the two fields: the book of R. Ortega *et. al.* [35] (Lagrangian approach) and the book of van der Schaft [36] (Hamiltonian approach).

In this paper, we focus on the Lagrangian approach. Since we will work on manifolds (the configuration space is a manifold rather than Euclidean), we adopt the geometric modelling which is well documented in [1]. Briefly speaking, one starts with a configuration space Q and then calculates the kinetic energy $\langle v_q, v_q \rangle$ and potential energy V(q). The kinetic energy thus defines a Riemannian metric on the configuration space, which depends only on the inertial of system. Using principles of classical mechanics (e.g., d'Alembert principle), one can derive the following so called Euler-Lagrangian (EL) equation:

$$\nabla_{\dot{q}}\dot{q} = -\operatorname{grad} V(q) + \sum_{i=1}^{m} u_i B_i(q) \tag{19}$$

where \dot{q} is the velocity, ∇ is the Levi-Civita connection associated with the metric, B_i are some tangent vectors, and u_i are external forces (viewed as input in our setting) taking values in \mathbb{R} .

A. Tracking controllers for EL systems

Suppose that $(q_*(\cdot), \dot{q}_*(\cdot), u_*(\cdot))$ is a feasible pair of the system (19), i.e., $\nabla_{\dot{q}_*}\dot{q}_* = -\nabla V(q_*) + \sum_{i=1}^m u_{i*}(t)B_i(q_*)$. The objective is to design a controller $u(\cdot)$ such that $(q_*(\cdot), \dot{q}_*(\cdot))$ is LES. Before moving on however, we must stop for a moment to clarify the statement that " $(q_*(\cdot), \dot{q}_*(\cdot))$ is LES". Unlike $q(\cdot)$, the curve $(q_*(\cdot), \dot{q}_*(\cdot))$ lives in the tangent bundle TM, which is not equipped with a distance function *a priori*. Thus in order to talk about convergence, a topology should be defined on TM. This is achieved via the so-called Sasaki metric [19]. Due to the importance of this metric, we briefly recall its construction in the following.

Let $V, W \in TTM$ be two tangent vectors at $(p, v) \in TM$ and

$$\alpha: t \mapsto (p(t), v(t)), \ \beta: t \mapsto (q(t), w(t)),$$

are two curves in TM with p(0) = q(0) = p, v(0) = w(0) = v, $\alpha'(0) = V$, $\beta'(0) = W$. Define the inner product on TM by

$$\langle V, W \rangle_{\rm s} := \left\langle p'(0), q'(0) \right\rangle + \left\langle v'(0), w'(0) \right\rangle \tag{20}$$

in which we write $v'(0) = \frac{Dv(t)}{dt}\Big|_{0}$. The Sasaki metric is well-known to be a *bona fide* Riemannian metric on TM. For details, see [19].

For a curve w(s) = (c(s), v(s)) lying in TM, we can calculate its length under the Sasaki metric as:

$$\ell(w) = \int \sqrt{\langle w'(s), w'(s) \rangle_{s}} ds$$
$$= \int \sqrt{\langle c'(s), c'(s) \rangle + \langle v'(s), v'(s) \rangle} ds$$

in which v'(s) is understood as the covariant derivative of $v(\cdot)$ along $c(\cdot)$.

Assumption 1: In the sequel we assume that for each pair of points (q, v) and (p, w) in TM, the minimizing geodesic that joins (q, v) to (p, w) always exists.

Now that the EL equation (19) defines a system on TM, it seems that to analyze LES of solutions of the EL equation, one has to consider variation (see Section II-C) of the form (q', v'), with $v' \in TTM$. The next theorem shows that this is not needed.

Theorem 3: Consider a dynamical system on a Riemannian manifold (M, g):

$$\nabla_{\dot{q}}\dot{q} = f(q, \dot{q}) \tag{21}$$

where f is smooth. Let $(q(\cdot), \dot{q}(\cdot))$ be a trajectory of the system and q' any variation along $q(\cdot)$. Then the system (21) is contractive if the following system

$$\frac{D}{dt} \begin{bmatrix} q'\\ \frac{Dq'}{dt} \end{bmatrix} = F\left(\begin{bmatrix} q'\\ \frac{Dq'}{dt} \end{bmatrix} \right)$$
(22)

is exponentially stable along any $q(\cdot)$.

Remark 6: Notice that $(q', Dq'/dt) \in T_qM \times T_qM$, thus exponential stability can be defined in the obvious way for the system (22) using Sasaki metric.

Proof: Given a point $(q_1, v_1) \in TM$, and the integral curve $\eta_1(t) = (q_1(t), \dot{q}_1(t))$ of the system (21) passing through it at time t = 0. Let $\eta_0(t) = (q(t), \dot{q}(t))$ be another integral curve with initial condition (q_0, v_0) . By assumption, there exists a minimizing geodesic $\gamma(s) = (q(s), v(s)), s \in [0, 1]$ joining (q_0, v_0) to (q_1, v_1) , that is, $\gamma(0) = (q_0, v_0), \gamma(1) = (q_1, v_1)$. Let q(s, t) be the solution to the system (21) with initial condition $\gamma(s)$, then the parameterized curve $s \mapsto (q(s, t), \frac{\partial q(s, t)}{\partial t})$ forms a variation between the curves $\eta_0(\cdot)$ and $\eta_1(\cdot)$. Therefore, the following estimation of the distance between the two points $\eta_0(t)$ and $\eta_1(t)$ is obvious:

$$d_{TM}(\eta_0(t), \eta_1(t)) \le \int_0^1 \sqrt{\left|\frac{\partial q}{\partial s}(s, t)\right|^2 + \left|\frac{D}{ds}\frac{\partial q}{\partial t}\right|^2} ds = \int_0^1 \sqrt{\left|\frac{\partial q}{\partial s}(s, t)\right|^2 + \left|\frac{D}{dt}\frac{\partial q}{\partial s}\right|^2} ds$$
(23)

The conclusion follows immediately after replacing $\frac{\partial q}{\partial s}$ by q'.

As we have remarked earlier, due to Theorem 3, the analysis of LES and contraction does not require variation of the form (q', v') and that q' alone is sufficient. This observation is crucial for the rest of this section.

With the preceding preparations, we are now in a position to study tracking controller for the EL system. We focus on fully-actuated system:

$$\nabla_{\dot{q}}\dot{q} = -\operatorname{grad}V(q) + u \tag{24}$$

and assume $(q_*(\cdot), \dot{q}_*(\cdot), u_*(\cdot) \equiv 0)$ is a bounded feasible solution to the EL equation, i.e., $\nabla_{\dot{q}_*}\dot{q}_* = -\nabla V(q_*)$ (solution with non-zero u_* is similar). We propose a controller with structure $u = u_P + u_V + u_R$ to locally exponentially stabilize $(q_*(\cdot), \dot{q}_*(\cdot), where$

$$u_{P}(q) = -k_{2}\nabla F(q, q_{*}),$$

$$u_{D}(q, \dot{q}) = -k_{1}(\dot{q} - P_{q_{*}}^{q}\dot{q}_{*}),$$

$$u_{R}(q, \dot{q}_{*}) = R(\dot{q}, \nabla F(q, q_{*}))\dot{q}$$
(25)

As before, F is half of the square distance function. k_1 and k_2 are constants to be determined and P_q^p is the parallel transport from q to p, $R(\cdot, \cdot)$ is the curvature tensor. Heuristically, this can be seen as a PD-controller [35], with a curvature compensation term. By construction, $(q_*(\cdot), \dot{q}_*(\cdot))$ is a solution to the closed loop system since $u(q_*, \dot{q}_*) \equiv 0$. Hence it remains to show the LES of this solution.

Thanks to Theorem 3 and Proposition 1, we need only check the exponential stability of the system (22) along $q_*(\cdot)$. For this we calculate

$$\begin{aligned} \nabla_{q'} \nabla_{\dot{q}} \dot{q} &= \nabla_{\dot{q}} \nabla_{q'} \dot{q} + R(\dot{q}, q') \dot{q} \\ &= \nabla_{\dot{q}} \nabla_{\dot{q}} q' + R(\dot{q}, q') \dot{q} \\ &= \frac{D^2 q'}{dt^2} + R(\dot{q}, q') \dot{q} \end{aligned} \tag{26}$$

where we used the basic fact about the curvature tensor: $\frac{D}{dt}\frac{D}{ds}X - \frac{D}{ds}\frac{D}{dt}X = R(\dot{q}, q')X$, see e.g., [17, Lemma 4.1]. The following calculations are in order (notice that we calculate along $q_*(\cdot)$, otherwise these are invalid):

$$\begin{aligned}
\nabla_{q'} u_P &= -k_2 \nabla_{q'} \nabla F = k_2 q' \\
\nabla_{q'} u_D &= -k_1 \nabla_{q'} (\dot{q} - P^q_{q_*} \dot{q}_*) = -k_1 \nabla_{\dot{q}} q' \\
\nabla_{q'} u_R &= \nabla_{q'} R(\dot{q}, \nabla F) \dot{q} \\
&= (\nabla_{q'} R) (\dot{q}, \nabla F) \dot{q} + R(\nabla_{q'} \dot{q}, \nabla F) \dot{q} \\
&+ R(\dot{q}, \nabla_{q'} \nabla F) \dot{q} + R(\dot{q}, \nabla F) \nabla_{q'} \dot{q} \\
&= R(\dot{q}, \nabla_{q'} \nabla F) \dot{q} \\
&= R(\dot{q}, q') \dot{q}
\end{aligned}$$
(27)

where we have used the fact that $\nabla_{q'} \nabla F(q, \dot{q}_*)|_{q=q_*(t)} = q'$, $\nabla F(q_*, q_*) = 0$. The second line of (27) holds because one can take $s \mapsto q(s, t)$ as a geodesic. Substituting (26) and (27) into the EL equation we immediately get

$$\frac{D^2 q'}{dt} = -k_1 \frac{Dq'}{dt} - k_2 q' - \nabla_{q'} \nabla V.$$
 (28)

Theorem 4: Let $(q_*(\cdot), \dot{q}_*, u_* \equiv 0)$ be a bounded feasible solution to the fully-actuated Euler-Lagrangian system (24). If the Hessian of the potential function V is bounded along $q_*(\cdot)$, then the controller (25) renders $(q_*(\cdot), \dot{q}_*(\cdot))$ LES for $k_1 > 0$ and $k_2 > 0$ large enough.

Proof: If the Hessian of V is bounded along $q_*(\cdot)$, then it is obvious that the "linear system" (28) is exponentially stable setting $k_1 > 0$ and choosing $k_2 > 0$ large enough. The theorem follows invoking Theorem 3.

Remark 7: Note that the assumption of Theorem 4 holds if $V \in C^2$ as $q_*(\cdot)$ is bounded. If V is (weakly) convex, then the Hessian of V is positive semi-definite, hence the same holds true for arbitrary positive constants k_1, k_2 .

Remark 8: In equation (28), we have in fact obtained the celebrated Jacobi equation by setting u = 0 and V = 0:

$$\frac{D^2 q'}{dt^2} = -R(\dot{q}, q')\dot{q}.$$
(29)

Since in this case the EL equation reads $\nabla_{\dot{q}}\dot{q} = 0$ (geodesic equation), equation (29) characterizes the effect of curvature to the geodesic flow. The Jacobi equation plays a significant role in Riemannian geometry and has many important implications. In order to help readers from the control community appreciate this equation, we now provide a control flavour to it.

For (29), choose a "Lyapunov function"

$$V(\dot{q},q') = \langle \frac{Dq'}{dt}, \frac{Dq'}{dt} \rangle + \langle R(\dot{q},q')\dot{q},q' \rangle.$$

Since we work only locally, let us consider a constant curvature manifold, that is

$$\langle R(\dot{q},q')\dot{q},q'\rangle = K\langle \dot{q},\dot{q}\rangle\langle q',q'\rangle, \quad \forall \dot{q},q$$

for some constant K. The time derivative of V reads

$$\begin{split} \dot{V} &= 2\langle \frac{D^2 q'}{dt^2}, \frac{Dq'}{dt} \rangle + \langle R(\dot{q}, \frac{Dq'}{dt}) \dot{q}, q' \rangle + \langle R(\dot{q}, q') \dot{q}, \frac{Dq'}{dt} \rangle \\ &= 2\langle -R(\dot{q}, q') \dot{q}, \frac{Dq'}{dt} \rangle + 2\langle R(\dot{q}, q') \dot{q}, \frac{Dq'}{dt} \rangle \\ &= 0, \end{split}$$

where we have used the fact that $\frac{D\dot{q}}{dt} = 0$. Remember that $q(\cdot)$ is a geodesic, we may assume $|\dot{q}| = 1$, then it follows that

$$V(\dot{q},q') = |Dq'/dt|^2 + K|q'|^2 = \text{ constant}$$

Therefore, we can draw the following non-rigorous conclusions:

- K > 0: along a given geodesic, nearby geodesics oscillate around it (see Fig. 2).
- K < 0: along a given geodesic, nearby geodesics have a trend to diverge.
- K = 0: the geodesics neither converge nor diverge.



Fig. 2. For K > 0, the geodesics oscillate near a given geodesic.

In the above we have studied tracking controller design for fullyactuated EL systems. This problem becomes more involved for underactuated systems. In that case, we may apply energy shaping method to obtain some matching conditions and then try to solve some PDEs on the manifolds [37], see also [38] and the references therein.

B. Speed Observer for EL Systems

Consider the EL system without input

$$\nabla_{\dot{q}}\dot{q} = -\nabla V(q) \tag{30}$$

where V(q) is the potential energy. The objective is to design a speed observer for $\dot{q}(\cdot)$ knowing $q(\cdot)$. In [39], Aghannan and Rouchon proposed the following intrinsic speed observer for the system (30) when there is no potential energy in the EL equation:

$$\begin{cases} \dot{\hat{q}} = \hat{v} - \alpha \nabla F(\hat{q}, q) \\ \nabla_{\dot{\hat{q}}} \hat{v} = -\beta \nabla F(\hat{q}, q) + R(\hat{v}, \nabla F) \hat{v}. \end{cases}$$
(31)

where F is half of the square distance as before. The convergence of this observer was analyzed in local coordinates via contraction analysis [39], which was, in our opinion, quite tedious.

Remark 9: Using the notation introduced in Section II-E, we may rewrite (31) as

$$\begin{cases} \dot{\hat{q}} = \hat{v} + \alpha \log_{\hat{q}} q \\ \nabla_{\dot{\hat{q}}} \hat{v} = \beta \nabla \log_{\hat{q}} q - R(\hat{v}, \log_{\hat{q}} q) \hat{v}. \end{cases}$$

obviating the use of the square distance function.

In this subsection, we provide a much simpler proof using the methods developed in this paper. Note that our model contains non-vanishing potential energy function, thus it is an extension to the free Lagrangian case in [39].

To cope with the potential energy, we consider a slightly modified version of (31):

$$\begin{cases} \dot{\hat{q}} = \hat{v} - \alpha \nabla F(\hat{q}, q) \\ \nabla_{\dot{\hat{q}}} \hat{v} = -\beta \nabla F(\hat{q}, q) + R(\hat{v}, \nabla F) \hat{v} - P_q^{\hat{q}} \nabla V(q). \end{cases}$$
(32)

Note that by construction, $(q(\cdot), \dot{q}(\cdot))$ is a solution to the observer. Hence it suffices to study LES of $(q(\cdot), \dot{q}(\cdot))$.

Substituting $\hat{v} = \dot{\hat{q}} + \alpha \nabla F(\hat{q}, q)$ into the second line of (32), we get

$$\nabla_{\dot{\hat{q}}}(\dot{\hat{q}} + \alpha \nabla F) = -\beta \nabla F + R(\dot{\hat{q}} + \alpha \nabla F, \nabla F)(\dot{\hat{q}} + \alpha \nabla F) - P_{\hat{q}}^{\hat{q}} \nabla V(q)$$

or

$$\begin{split} \nabla_{\dot{q}}\dot{\dot{q}} &= -\alpha \nabla_{\dot{q}} \nabla F - \beta \nabla F + R(\dot{q}, \nabla F)(\dot{q} + \alpha \nabla F) \\ &- P_q^{\hat{q}} \nabla V(q) \end{split}$$

Taking covariant derivative along $q(\cdot)$ on both sides yields

$$\nabla_{q'} \nabla_{\dot{q}} \dot{\dot{q}} = \frac{D^2 q'}{dt^2} + R(\dot{\dot{q}}, q') \dot{\dot{q}}, \tag{33}$$

on the left, and

$$\begin{aligned} &-\alpha \nabla_{q'} \nabla_{\dot{q}} \nabla F - \beta \nabla_{q'} \nabla F + \nabla_{q'} [R(\dot{q}, \nabla F)(\dot{q} + \alpha \nabla F)] \\ &= -\alpha \nabla_{\dot{q}} \nabla_{q'} \nabla F - \alpha R(\dot{q}, q') \nabla F - \beta \nabla_{q'} \nabla F \\ &+ \nabla_{q'} [R(\dot{q}, \nabla F)(\dot{q} + \alpha \nabla F)] \\ &= -\alpha \nabla_{\dot{q}} q' - \beta q' + R(\dot{q}, \nabla_{q'} \nabla F) \dot{q} \\ &= -\alpha \nabla_{\dot{q}} q' - \beta q' + R(\dot{q}, q') \dot{q}, \end{aligned}$$

on the right, where we have used the relations $\nabla F|_{\hat{q}=q} = 0$, $\nabla_{q'} \nabla F|_{\hat{q}=q} = q'$ and $\nabla_{q'} P_q^{\hat{q}} \nabla V(q) = 0$ (be q' tangent to a geodesic). Combining this with (33) yields

$$\frac{D^2q'}{dt^2} + \alpha \frac{Dq'}{dt} + \beta q' = 0.$$
(34)

This, together with Theorem 3 shows the local exponential convergence of the observer.

Remark 10: Notice that in both the tracking controller and observer design, we have to calculate the geodesic distance. Although there are efficient computation schemes, it is still tempting to avoid computing geodesics. This may be solved by embedding the system into Euclidean space and use equivalent distance functions in Euclidean spaces. The example of observer design on SO(3) in Section II-D has used this method.

IV. CONCLUSION

In this paper, we have proposed a novel intrinsic approach for analyzing local exponential stability of trajectories and contraction. The advantages of our approach have been justified by applications and improved analysis of some existing works in the literature. We leave studies of concrete examples including under-actuated mechanical systems for future research.

V. ACKNOWLEDGEMENT

We thank Prof. Antoine Chaillet, who gave important comments and suggestions through the writing of the paper.

VI. APPENDIX

We collect some elementary formulas in Riemannian geometry as a reference for the reader. They can be found in standard texts such as [17], [18]. Let (M, g) be a smooth Riemannian manifold. The Levi-Civita connection on M is compatible with the metric g: for any three vector fields $X, Y, Z \in \Gamma(M), X \langle Y, Z \rangle = \langle \nabla_X Y, Z \rangle + \langle Y, \nabla_X Z \rangle$. The Levi-Civita connection is torsion-free in the sense that $\nabla_X Y \nabla_Y X = [X, Y]$, where [X, Y] is the Lie bracket. Given a curve

 $\forall YX = [X, T]$, where [X, T] is the Lie bracket. Other a curve $q: t \mapsto q(t)$ in M and a vector field v(t) along $q(\cdot)$, the covariant derivative of $v(\cdot)$ along $q(\cdot)$ is defined as $\frac{Dv(t)}{dt} := \nabla_{\dot{q}(t)}v(t)$. Given a 2-surface parameterized by $(s, t) \mapsto q(s, t)$, then there holds

$$\frac{D}{ds}\frac{\partial q}{\partial t} = \frac{D}{dt}\frac{\partial q}{\partial s}.$$
(35)

The gradient of a scalar function f on M is defined as the unique vector ∇f satisfying $\langle \nabla f, X \rangle = df(X)$. The Hessian of a scalar function is a symmetric bilinear form on TM defined as

$$\operatorname{Hess} f(X,Y) := \langle \nabla_X \nabla f, Y \rangle, \ \forall X, Y \in \Gamma(M).$$
(36)

For a parameterized surface $(s,t) \to q(s,t)$ and a vector field along the surface, there holds

$$\frac{D}{ds}\frac{DX}{dt} - \frac{D}{dt}\frac{DX}{ds} = R\left(\frac{\partial q}{\partial t}, \frac{\partial q}{\partial s}\right)X.$$
(37)

A metric on a Lie group G is bi-invariant if it is both leftinvariant, i.e., $dL_x \langle v, w \rangle = \langle v, w \rangle$ and right-invariant. For a biinvariant metric, the Levi-Civita connection admits a simple formula

$$\nabla_X Y = \frac{1}{2} [X, Y]. \tag{38}$$

A vector field X on is called a Killing field (w.r.t. g) if $L_X g = 0$. Consequently, if X is Killing, Y an arbitrary vector field, there holds

$$g(\nabla_Y X, Y) = 0. \tag{39}$$

Lemma 3: Given $\gamma_1, \gamma_2 \in C^1(\mathbb{R}_+; M)$, where M is a Riemannian manifold. If $\gamma_1(0) = \gamma_2(0) = x$ and $\gamma'_1(0) = \gamma'_2(0) = v$, then $d(\gamma_1(s), \gamma_2(s)) = O(s^2)$ when s > 0 is sufficiently small.

REFERENCES

- F. Bullo and A. D. Lewis, Geometric Control of Mechanical Systems: Modeling, Analysis, and Design for Simple Mechanical Control Systems. Springer, 2019, vol. 49.
- [2] D. d'Alessandro, Introduction to Quantum Control and Dynamics. CRC press, 2007.
- [3] V. Jurdjevic and H. J. Sussmann, "Control systems on Lie groups," *Journal of Differential Equations*, vol. 12, no. 2, pp. 313–329, 1972.
- [4] F. Bullo and R. M. Murray, "Tracking for fully actuated mechanical systems: a geometric framework," *Automatica*, vol. 35, no. 1, pp. 17– 34, 1999.
- [5] B. Yi, R. Ortega, D. Wu, and W. Zhang, "Orbital stabilization of nonlinear systems via Mexican sombrero energy shaping and pumpingand-damping injection," *Automatica*, vol. 112, 2020, art. no. 108861.
- [6] V. Andrieu, B. Jayawardhana, and L. Praly, "Transverse exponential stability and applications," *IEEE Transactions on Automatic Control*, vol. 61, no. 11, pp. 3396–3411, 2016.
- [7] W. Lohmiller and J.-J. E. Slotine, "On contraction analysis for non-linear systems," *Automatica*, vol. 34, no. 6, pp. 683–696, 1998.
- [8] F. Forni and R. Sepulchre, "A differential Lyapunov framework for contraction analysis," *IEEE Transactions on Automatic Control*, vol. 59, no. 3, pp. 614–628, 2014.
- [9] W. Wang and J.-J. E. Slotine, "On partial contraction analysis for coupled nonlinear oscillators," *Biological Cybernetics*, vol. 92, no. 1, pp. 38–53, 2005.
- [10] S. Bonnabel and J.-J. Slotine, "A contraction theory-based analysis of the stability of the deterministic extended Kalman filter," *IEEE Transactions* on Automatic Control, vol. 60, no. 2, pp. 565–569, 2014.
- [11] C. Lageman, J. Trumpf, and R. Mahony, "Gradient-like observers for invariant dynamics on a Lie group," *IEEE Transactions on Automatic Control*, vol. 55, no. 2, pp. 367–377, 2009.

- [13] J. Cortés, A. van der Schaft, and P. E. Crouch, "Characterization of gradient control systems," *SIAM Journal on Control and Optimization*, vol. 44, no. 4, pp. 1192–1214, 2005.
- [14] A. van der Schaft, "A geometric approach to differential Hamiltonian systems and differential Riccati equations," in 2015 54th IEEE Conference on Decision and Control (CDC). IEEE, 2015, pp. 7151–7156.
- [15] D. Wu and G.-R. Duan, "Further geometric and Lyapunov characterizations of incrementally stable systems on Finsler manifolds," *IEEE Transactions on Automatic Control*, vol. 67, no. 10, pp. 5614–5621, 2021.
- [16] F. Bullo and A. D. Lewis, "Reduction, linearization, and stability of relative equilibria for mechanical systems on Riemannian manifolds," *Acta Applicandae Mathematicae*, vol. 99, no. 1, pp. 53–95, 2007.
- [17] M. P. d. Carmo, Riemannian Geometry. Birkhäuser, 1992.
- [18] P. Petersen, S. Axler, and K. Ribet, *Riemannian Geometry*. Springer, 2006, vol. 171.
- [19] K. Yano and S. Ishihara, *Tangent and Cotangent Bundles: Differential Geometry*. Dekker, 1973, vol. 16.
- [20] M. Crampin and F. Pirani, *Applicable Differential Geometry*. Cambridge University Press, 1986, vol. 59.
- [21] M. Giaccagli, D. Astolfi, V. Andrieu, and L. Marconi, "Sufficient conditions for output reference tracking for nonlinear systems: A contractive approach," in 59th IEEE Conference on Decision and Control, 2020.
- [22] B. S. Rüffer, N. Van De Wouw, and M. Mueller, "Convergent systems vs. incremental stability," *Systems & Control Letters*, vol. 62, no. 3, pp. 277–285, 2013.
- [23] I. R. Manchester and J.-J. E. Slotine, "Control contraction metrics: Convex and intrinsic criteria for nonlinear feedback design," *IEEE Transactions on Automatic Control*, vol. 62, no. 6, pp. 3046–3053, 2017.
- [24] Z. Aminzare and E. D. Sontag, "Contraction methods for nonlinear systems: A brief introduction and some open problems," in 53rd IEEE Conference on Decision and Control. IEEE, 2014, pp. 3835–3847.
- [25] J. W. Simpson-Porco and F. Bullo, "Contraction theory on Riemannian manifolds," Systems & Control Letters, vol. 65, pp. 74–80, 2014.
- [26] D. Angeli, "A Lyapunov approach to incremental stability properties," *IEEE Transactions on Automatic Control*, vol. 47, no. 3, pp. 410–421, 2002.
- [27] F. Forni, A. Mauroy, and R. Sepulchre, "Differential positivity characterizes one-dimensional normally hyperbolic attractors," arXiv preprint arXiv:1511.06996, 2015.
- [28] S. Bonnabel, "A simple intrinsic reduced-observer for geodesic flow," *IEEE Transactions on Automatic Control*, vol. 55, no. 9, pp. 2186–2191, 2010.
- [29] J. Jost, Riemannian Geometry and Geometric Snalysis, Seventh Edition. Springer, 2017.
- [30] C. Wu, I. Kanevskiy, and M. Margaliot, "k-contraction: Theory and applications," Automatica, vol. 136, p. 110048, 2022.
- [31] C. Criscitiello and N. Boumal, "An accelerated first-order method for non-convex optimization on manifolds," *Foundations of Computational Mathematics*, pp. 1–77, 2022.
- [32] A. Tyagi and J. W. Davis, "A recursive filter for linear systems on Riemannian manifolds," in 2008 IEEE Conference on Computer Vision and Pattern Recognition. IEEE, 2008, pp. 1–8.
- [33] X. Pennec, P. Fillard, and N. Ayache, "A Riemannian framework for tensor computing," *International Journal of Computer Vision*, vol. 66, pp. 41–66, 2006.
- [34] R. Abraham and J. E. Marsden, Foundations of Mechanics. American Mathematical Soc., 2008, no. 364.
- [35] R. Ortega, A. Loría, P. J. Nicklasson, and H. Sira-Ramírez, *Passivity-based Control of Euler-Lagrange Systems: Mechanical, Electrical and Electromechanical Applications*. Springer Science & Business Media, 2013.
- [36] A. van der Schaft, L₂-gain and Gassivity Techniques in Nonlinear Control. Springer, 2017.
- [37] R. Ortega, M. W. Spong, F. Gómez-Estern, and G. Blankenstein, "Stabilization of a class of underactuated mechanical systems via interconnection and damping assignment," *IEEE Transactions on Automatic Control*, vol. 47, no. 8, pp. 1218–1233, 2002.
- [38] G. Blankenstein, R. Ortega, and A. J. Van Der Schaft, "The matching conditions of controlled Lagrangians and IDA-passivity based control," *International Journal of Control*, vol. 75, no. 9, pp. 645–665, 2002.
- [39] N. Aghannan and P. Rouchon, "An intrinsic observer for a class of Lagrangian systems," *IEEE Transactions on Automatic Control*, vol. 48, no. 6, pp. 936–945, 2003.