arXiv:2306.12575v2 [math.CO] 23 Sep 2024

Distance-Restricted Firefighting on Finite Graphs

Andrea C. Burgess¹, John Hawkin², Alexander Howse³, John Marcoux⁴, and David A. Pike⁵

¹Department of Mathematics and Statistics, University of New Brunswick, Saint John, NB, E2L 4L5, Canada. andrea.burgess@unb.ca
²Nasdaq Verafin, 18 Hebron Way, St. John's, NL, A1A 0L9. john.hawkin@nasdaq.com
³Nasdaq Verafin, 18 Hebron Way, St. John's, NL, A1A 0L9. alexander.howse@nasdaq.com
⁴Department of Mathematics, Toronto Metropolitan University, Toronto, ON, M5B 2K3, Canada. jmarcoux@torontomu.ca
⁵Department of Mathematics and Statistics, Memorial University of Newfoundland, St. John's, NL, A1C 5S7, Canada. dapike@mun.ca

September 24, 2024

Abstract

In the classic version of the game of firefighter, on the first turn a fire breaks out on a vertex in a graph G and then b firefighters protect b vertices. On each subsequent turn, the fire spreads to the collective unburnt neighbourhood of all the burning vertices and the firefighters again protect b vertices. Once a vertex has been burnt or protected it remains that way for the rest of the game. In *distance-restricted firefighting* the firefighters' movement is restricted so they can only move up to some fixed distance d and they may or may not be permitted to move through burning vertices. In this paper we establish the NP-completeness of the distance-restricted versions of b-FIREFIGHTER even on bipartite graphs and present an integer program for computing the exact value. We also discuss some interesting properties of the *Expected Damage* function.

1 Introduction

The firefighter problem, introduced by Hartnell in 1995 [15], is a turn-based game played on a graph where fire is a proxy for some contagion that spreads from a set of 'burning' vertices to their collective neighbourhoods on each turn. For our purposes we consider the game to be a two player game where the players are an arsonist and a brigade of firefighters. On turn 0, one or more vertices are selected by the arsonist as the initial burning vertices and some fixed number of firefighters are placed as well. Each firefighter protects a single vertex from the fire, the consequence being that the fire does not spread to these vertices for the remainder of the game. On each subsequent turn, the fire spreads to the unprotected neighbourhoods of the burning vertices and the firefighters protect a new set of vertices. The notion of *distancerestricted* firefighting was introduced in [4] as a new variant of the firefighter problem. In this version the firefighters were restricted to moving up to some distance d each turn and could not move through any burning vertices. Up to this point, distance-restricted firefighting has only been studied in the context of the containment problem on infinite graphs [4, 6, 8] whereas the present paper focuses on problems on finite graphs.

One of the key items of interest in firefighting is the Maximum Vertices Saved (MVS(G,F;b)) function. Given a graph G, a set F of initially burning vertices, and a number b of firefighters, MVS(G,F;b) is equal to the maximum number of vertices the firefighters can save. The related decision problem asking if MVS(G,F;b) is at least some constant k is referred to as b-FIREFIGHTER. Another decision problem is (S,b)-FIRE where given a graph, a set of initially burning vertices and a set of vertices S we ask if all the vertices in S can be saved using only b firefighters. Both b-FIREFIGHTER and (S,b)-FIRE are known to be NP-complete even when restricted to certain classes of trees. These are both consequences of the main result from [3] (which builds on a result from [13]) where it is shown that the MAX (S,b)-FIRE problem is NP-complete.

MAX (S,b)-FIRE **Input:** A graph G, a set of vertices $S \subseteq V(G)$, and a vertex $u \in V(G)$ **Question:** What is the maximum number of vertices in S which can be saved using b firefighters if a fire breaks out at u?

We recommend the survey by Finbow and MacGillivray [14] and the recent thesis by Wagner [18] for further reading on these problems as well as other variants of the firefighter problem.

For our purposes we define two variants of the MVS function, *Distance-Restricted Maximum Vertices Saved* (DRMVS(G,F;b,d)) and *Distance-Path-Restricted Maximum Vertices Saved* (DPRMVS(G,F;b,d)). With DRMVS each firefighter can move up to some fixed distance d (which is now included in the problem parameters). For DPRMVS the fire-

fighters can move up to some fixed distance d and in addition the firefighters cannot move through the fire. We will see in Section 2 that although these games may seem similar they can behave in very different ways in certain contexts.

A common approach for optimization problems like these is to restate them as decision problems and analyze their complexity. In order to do this we first consider the b-FIREFIGHTER decision problem, studied in [3].

b-FIREFIGHTER **Input:** A graph G, a set of vertices $F \subseteq V(G)$, and a positive integer k**Question:** Is $MVS(G,F;b) \ge k$?

This is easily extended to the two decision problems which will be the focus of this paper.

DR-b-FF	
Input:	A graph G, a set of vertices $F \subseteq V(G)$, an integer $d \ge 1$, and a positive
	integer k
Question:	Is $\text{DRMVS}(G,F;b,d) \ge k?$
DPR- <i>b</i> -FF	
Input:	A graph G, a set of vertices $F \subseteq V(G)$, an integer $d \ge 1$, and a positive
	integer k
Question:	Is $\text{DPRMVS}(G,F;b,d) \ge k?$

It is also worth noting that if we allow the case where d = 0, DPR-b-FF and DR-b-FF are both similar to the FIREBREAK problem [1] where the firefighters defend for only the first turn and then allow the fire to spread as much as possible. In this case the only difference is that for our problems the number of firefighters is part of the problem statement but for FIREBREAK it is part of the problem input. Note as well that if d is the diameter of the graph then DR-b-FF is equivalent to b-FIREFIGHTER but under the same conditions DPR-b-FF is not equivalent to b-FIREFIGHTER in general.

In the remaining sections of the paper, we first discuss the complexity of DR-*b*-FF and DPR-*b*-FF by showing their NP-completeness on graphs in general. We also show that the complexity of DPR-*b*-FF is greatly reduced on trees and pose questions about the complexity of solving DPR-*b*-FF different graph classes. Following this, an extension of a 0, 1-integer program for solving the original MVS function is explored which is capable of computing DRMVS and a second extension which computes DPRMVS is considered as well. In the penultimate section of the paper, the concept of expected damage is explored for distance-restricted and distance-path-restricted firefighting and an important difference between expected damage in the original game and in the distance-restricted game is shown to be true. The final section poses some problems which we consider natural next steps for this variant of firefighting.

2 Complexity of DR-*b*-FF and DPR-*b*-FF

One of the ever present questions for problems like DR-b-FF and DPR-b-FF is whether or not they can be solved efficiently. It is already known that b-FIREFIGHTER is NP-complete even when restricted to trees of maximum degree b+2 [3]. For DR-b-FF and DPR-b-FF we must first examine a fundamental building block of the game, which is determining whether or not a move is valid. Clearly if we cannot efficiently decide whether or not a move is valid then it is unlikely that we can solve either of these decision problems efficiently. To deal with this problem of checking a move's validity, we first build an auxiliary bipartite graph where one partite set A represents the vertices defended at time t and the other partite set B represents the vertices defended at time t + 1. We add the edge uv if the vertex from the original graph represented by $u \in A$ is distance at most d from the vertex represented by $v \in B$ in the original graph. Of course in the path restricted case we modify this edge condition so the distance is determined in the subgraph induced by the unburnt vertices. It is clear that a valid move in the game exists if and only if this auxiliary graph has a perfect matching, which can be determined in polynomial time [11].

Now we can move on to the main theorem of this section, Theorem 2.1

Theorem 2.1. DR-*b*-FF and DPR-*b*-FF are NP-complete.

In order to show this we begin by noting that the problems are both in NP since we can use the sequence of defended vertices as an easily verifiable certificate.

Lemma 2.2. DR-b-FF and DPR-b-FF are in NP.

We now show that both problems are NP-hard. Consider an instance of b-FIREFIGHTER and let d be the diameter of the graph. Clearly the firefighter can move between any pair of vertices if we use this value of d for DR-b-FF and thus the optimal strategies for b-FIREFIGHTER and DR-b-FF will be exactly the same. Thus we have the following result which concludes the proof of the first half of Theorem 2.1.

Theorem 2.3. DR-b-FF is NP-hard.

Now for DPR-*b*-FF things are not quite so straightforward. The major issue is that our transformation from an instance of *b*-FIREFIGHTER to an instance of DPR-*b*-FF must allow for the firefighters to be able to move between any pair of unburnt vertices, which is exactly what the path restrictions stop the firefighters from doing. In order to show that DPR-*b*-FF is NP-hard we will first introduce the related problem, WEIGHTED-DPR-*b*-FF.

WEIGHTED-DPR-b-FF

Input:	A graph G, a set of vertices $F \subseteq V(G)$, an integer $d \ge 1$, a set of real
	valued vertex weights w_v , and a positive integer k
Question	Can b firefighters save a set of vertices whose weights sum to at least k

Question: Can b firefighters save a set of vertices whose weights sum to at least k while moving at most distance d and without passing through a burning vertex if a fire breaks out at all the vertices in F?

Lemma 2.4. WEIGHTED-DPR-b-FF and DPR-b-FF are NP-hard.

Proof. Consider an instance (G, F, k) of b-FIREFIGHTER. We aim to transform this into an equivalent instance $(G', F', d, \{w_v\}_{v \in V(G')}, k')$ of WEIGHTED-DPR-b-FF.

Let r be the number of vertices in the original graph G and let $t = \binom{r}{2} - |E(G)|$. Now construct G' from G in the following way. First, for every pair of non-adjacent vertices u, vadd an edge between them and subdivide it 2r times, that is to say, subdivide until 2r vertices have been added to the graph. Now assign a weight of 1 to all these new vertices and assign a weight of 2rt + 1 to the vertices which came from V(G) to obtain the set $\{w_v\}_{v \in V(G')}$. Now our problem is whether or not we can save a total weight of k' = k(2rt + 1) with d = 2r + 1if a fire breaks out at $F' = F \subseteq V(G) \subseteq V(G')$.

To show that the instance of WEIGHTED-DPR-b-FF obtained above is equivalent to our original instance of b-FIREFIGHTER we need only note a few things. First, by our choice of dwe can always move between any pair of unburnt vertices. Second, by our choice of weights the new vertices we added do not matter since saving all of them saves less total weight than saving a single one of the high-weight vertices. Third, after r turns the fire will only be spreading across the long paths we added which will leave r turns for the firefighters to backtrack and defend any of the unburnt high-weight vertices which have not been defended yet. Clearly any successful strategy for the instance of b-FIREFIGHTER can be translated into a strategy for the instance of WEIGHTED-DPR-b-FF by defending the same vertices from $V(G) \subseteq V(G')$ and then defending the remaining unburnt vertices. Similarly if we cannot save at least k vertices in our instance of b-FIREFIGHTER then we cannot save a total weight of k' in our instance of WEIGHTED-DPR-b-FF. To see this first note that in the instance of WEIGHTED-DPR-b-FF, if a firefighter defends a vertex along one of the subdivisions we added then it would lead to the exact same result for the decision problem if they defended one of the unburnt ends of the subdivision since the total weight of all the vertices on all the subdivisions is very small. It is easy to see that this implies the firefighters will only ever defend vertices in $V(G) \subseteq V(G')$ and thus any strategy for this instance of WEIGHTED-DPR-b-FF could be translated to a strategy for the instance of b-FIREFIGHTER. Thus since b-FIREFIGHTER is NP-complete, WEIGHTED-DPR-b-FF is NP-hard.

Now consider the instance $(G', F', d, \{w_v\}_{v \in V(G')}, k')$ we created. Note that all the weights are positive integers. We now produce an equivalent instance (G'', F'', d, k') of DPR-b-FF

from this instance. To produce G'', take each vertex v and add $w_v - 1$ leaves to v. Call each of these sets of leaves L_v and let $F'' = \bigcup_{v \in F'} (L_v \cup \{v\})$. To see that these instances are equivalent note that by defending a vertex u which is not in any L_v , we certainly save w_u vertices. Note that it is never advantageous to defend a vertex in one of the L_v since if a firefighter can get there they must have passed through the adjacent vertex and defending that would save at least one additional vertex. Note as well that once the fire reaches a vertex u there is no way for the firefighters to defend any vertex in L_u so the entire weight of that vertex is lost. Thus these instances are equivalent and DPR-*b*-FF is NP-hard. \Box

While it is not the focus of this paper, the weighted variant of firefighter is of independent interest since it helps to unify the different firefighter decision problems. For example, we can immediately use this to phrase a distance-path-restricted version of (S,b)-FIRE as a WEIGHTED-DPR-b-FF problem since we can assign a weight of n (the number of vertices) to the vertices in S and a weight of 1 to the rest of the vertices and ask if it is possible to save a weight of n|S|.

We also note the following corollary.

Corollary 2.5. DPR-b-FF is NP-complete even when restricted to bipartite graphs.

To see this, note that if we start with a bipartite graph then the only ingredient of our reduction that can introduce an odd cycle is the step where we add the subdivisions. However, if we increase the value of d by 1 and we increase the length of the subdivision by 1 whenever the corresponding vertices are in the same partite set then we never introduce any odd cycle and so our reduction produces instances of DPR-*b*-FF where the graph is bipartite. Thus since *b*-FIREFIGHTER is NP-complete on bipartite graphs DPR-*b*-FF is also NP-complete on bipartite graphs. We will see next that while this result is similar to the result for the original game from [17], the result for trees from [13] is in sharp contrast with the following lemma.

Lemma 2.6. DPR-*b*-FF is solvable in linear time on trees whenever |F| = 1 regardless of the value of d.

Proof. First, we root the tree at the initial burning vertex u and label the neighbours of u as $v_1, \ldots, v_{d(u)}$. Define the quantities S_{v_i} to be the number of vertices in the component of $T \setminus u$ containing v_i . We claim that the best possible strategy is to defend the b vertices in $\{v_1, \ldots, v_{d(u)}\}$ which have the largest S_{v_i} values. To see this, we first note that any firefighter can only defend vertices in one component of $T \setminus u$ since moving to another component would require moving through u. Now, we see that if the firefighter defends one of these v_i then they save all vertices in that component of $T \setminus u$ and since they certainly cannot do better than saving all of the vertices in the chosen component this will always be optimal. From

here it is clear that the claim is true. Now note that the S_{v_i} can be calculated by a depth first search and so the problem is solvable in linear time.

A natural question which arises here is whether or not DPR-*b*-FF exhibits a dichotomy similar to the constraint satisfaction problem (CSP) [2] since it is NP-complete on bipartite graphs and polynomial time solvable on trees, or if it could somehow give rise to intermediate problems. The original *b*-FIREFIGHTER problem is known to satisfy the dichotomy based on a degree condition and it is natural to believe that DPR-*b*-FF will as well. However, the degree condition which trivially makes the problem polynomial time for *b*-FIREFIGHTER does not have the same effect here and it seems that any degree condition would not be sufficient. It is possible that some of the ingredients of the integer program in the next section could be used to rephrase the problem as a CSP which is amenable to the algebraic approaches outlined in [2] when restricted to certain classes of bipartite graphs. Otherwise it may be helpful to examine a different approach to the integer program specifically for bipartite graphs as was done for trees in [17].

3 Integer Programming Solutions

A natural question to ask about any NP-complete problem is whether there are ways to solve it using 'relatively efficient' methods. Solving these problems by transforming them into something that can be passed as input to an integer program solver or a SAT solver allows us to take advantage of very well optimized pieces of software like HiGHS [16]. Of course, since our problem is in NP such a method for solving our problem certainly exists, but using something like this may be less conducive to recovering the optimal strategy for the firefighters. Having access to a method for finding solutions where we can easily recover the firefighter strategy also allows us to formulate conjectures such as Conjecture 3.1 which are not necessarily obvious without solving many instances of DR-*b*-FF. The original MVS function was shown in [9] to be computable by a 0, 1-integer program which is depicted in Figure 3.1. The program encodes whether or not a vertex is burned at a particular point in time using the $b_{x,t}$ variables and similarly encodes whether or not a vertex is defended using the $d_{x,t}$ values. Note that we use a capital *B* here to denote the number of firefighters so it is disambiguated from the $b_{x,t}$ values and we use *S* to denote the set of initially burning vertices.

$$\begin{array}{ll} \text{Minimize } \displaystyle\sum_{x \in V(G)} b_{x,T}, \text{ subject to:} \\ \\ b_{x,t} \geq b_{x,t-1} & x \in V(G), 1 \leq t \leq T \\ d_{x,t} \geq d_{x,t-1} & x \in V(G), 1 \leq t \leq T \\ b_{x,t} + d_{x,t} \geq b_{y,t-1} & x \in V(G), y \in N(x), 1 \leq t \leq T \\ b_{x,t} + d_{x,t} \leq 1 & x \in V(G), 1 \leq t \leq T \\ \\ \displaystyle\sum_{y \in N(x)} b_{y,t-1} \geq b_{x,t} & x \in V(G), 1 \leq t \leq T \\ \\ \displaystyle\sum_{x \in V(G)} (d_{x,t} - d_{x,t-1}) \leq B & 1 \leq t \leq T \\ d_{x,0} = 0 & x \in V(G) \\ b_{x,0} = \begin{cases} 1 & \text{if } x \in S \\ 0 & \text{otherwise} \end{cases} & x \in V(G) \\ b_{x,t}, d_{x,t} \in \{0,1\} & x \in V(G), 0 \leq t \leq T \end{cases}$$

Figure 3.1: A 0, 1-integer program for solving firefighter MVS, due to Develin and Hartke [9].

While this program can compute the original MVS function, its encoding of the information loses certain features that are needed to impose distance and path restrictions on the problem. In particular, if a firefighter moves onto a previously defended vertex, then the set of defended vertices does not change, and that firefighter's current position is now unknown. Thus on the next turn it is impossible to validate that firefighter's move since it is impossible to know exactly which vertex the firefighter was on.

In order to construct an extension to the Develin and Hartke program that computes DRMVS, we first have to re-encode the firefighters' positions in a way that solves the aforementioned information loss problem, but also in a way which lends itself well to linear transformations. Our solution is to encode the firefighters' positions on any given turn as a one-hot¹ encoded vector of length $\binom{|V(G)|+B-1}{B-1}$, as that is the number of weak compositions² of |V(G)| into B parts and we can order the compositions lexicographically. We use this approach because weak compositions are in correspondence with positions the firefighters can occupy since each element of the composition corresponds to a vertex of the graph and

¹A one-hot encode refers to a vector where all entries but one are zero and the remaining entry is a 1.

²A weak composition of n into k parts is an ordered sum of k non-negative integers which sum to n.

the quantity corresponds to the number of firefighters on that vertex. Thus if the firefighters' positions at time t correspond to the i^{th} weak composition we represent the position with the one-hot encoded vector with a 1 in the i^{th} coordinate and we label this vector p_t .

We now need to make these position vectors force the $d_{x,t}$ to take on their corresponding values. The first step in doing this is to extract which vertices are occupied from the onehot encoded position vector, which we do by constructing a matrix A with |V(G)| rows and $\binom{|V(G)|+B-1}{B-1}$ columns where the i^{th} entry in the j^{th} row is 1 if the j^{th} entry of the weak composition corresponding to the i^{th} position is positive and the entry is 0 otherwise. Multiplication by A takes a position vector and yields a binary vector where the i^{th} entry being 1 implies that the i^{th} vertex is occupied, and thus the corresponding $d_{x,t}$ needs to be 1 as well. In order to set the $d_{x,t}$ value we want to take the maximum of all the entries corresponding to vertex x in the vectors Ap_{τ} where $\tau \leq t$. This is achieved in two parts. First set the sum of all these values as an upper bound on $d_{x,t}$ since if all of these values are zero then $d_{x,t}$ will also be zero. Secondly set each of the values individually as a lower bound on $d_{x,t}$, then if any of the values are 1, $d_{x,t}$ will be 1 as well.

So we can now associate a one-hot encoded position vector to each time step, and this can be used to construct a bilinear form which determines if the move from the positions at time t to the positions at time t + 1 is valid. Define M_d to be a $\binom{|V(G)|+B-1}{B-1}$ square matrix where the i^{th} entry in the j^{th} row is 0 if there is a valid move from position i to position j and 1 if that is not the case. This allows us to use $p_t^T M_d p_{t+1}$ to determine if the given move is valid, and we can in fact replace the bilinear form M_d with a dot product by instead encoding the vector $a_t = p_t \otimes p_{t+1}$ for each time step and noting that we can recover p_t from a_t using a projection map μ . This does also now require us to ensure that the projection to the second factor of the tensor product in a_t and the projection to the first factor of the tensor product in a_{t+1} are in fact equal. Figure 3.2 depicts the extension to the Develin and Hartke program which computes DRMVS.

$$W = \{0, 1\}^{\binom{n+\ell-1}{\ell-1}}$$

$$\{S_i\} = \text{ indexed weak compositions}$$

$$p_t \in W$$

$$p_t^i = \begin{cases} 1 & \text{If } S_i \text{ is occupied at time } t \\ 0 & \text{Otherwise} \end{cases} \qquad \begin{array}{l} 1 \cdot a_{t'}^i = 1, \ t' > 1 \\ 1 \cdot a_0^i = 0 \\ 1 \cdot p_t^i = 1 \\ \mu_1 : W \otimes W \to W \\ \mu_1 (a_t) = p_t \\ \mu_2 : W \otimes W \to W \\ \mu_2 (a_t) = p_{t+1} \\ M_d : W \otimes W \to \{0, 1\} \end{cases} \qquad \begin{array}{l} M_d(p_t \otimes p_{t+1}) = \begin{cases} 0 & \text{If there is a valid move} \\ 1 & \text{Otherwise} \end{cases}$$

Figure 3.2: An extension to the 0, 1-integer program which computes DRMVS.

We can see that this implements all the pieces discussed in the previous paragraphs. The a_t values are our tensor products of position vectors, the μ_i projection maps ensure that a_t and a_{t+1} are compatible, the transformation M_d validates moves, and the last two lines force $d_{x,t}$ to take on the values corresponding to p_t .

It is relatively straightforward to construct a program which takes a DRMVS problem instance as input and outputs the corresponding linear program. We used such a program as well as the HiGHS solver [16] to solve a 13×13 square grid (i.e. $P_{13} \Box P_{13}$) with d = 3and a single firefighter with a runtime of approximately 28 days on a 6-core Zen+ desktop platform. We also used this to solve a large number of instances on square grids with d = 1which led to Conjecture 3.1.

Conjecture 3.1.

$$\lim_{n \to \infty} \frac{\text{DRMVS}\left(P_n \Box P_n, \left(\left\lceil \frac{n}{2} \right\rceil, \left\lceil \frac{n}{2} \right\rceil\right); 1, 1\right)}{n^2} = \frac{1}{8}$$

This conjecture is based on finding that the optimal solution for many small grids would save an $\frac{n}{4}$ by $\frac{n}{2}$ piece of the grid in the corner, thus saving one eighth of the grid. This strategy works for a grid of any size but it is yet to be shown that it is optimal as n becomes large.

It is also possible to extend this program to compute DPRMVS. The idea is that for each pair of positions and each value of d there is some finite set of 'connectors', which are sets of vertices the firefighters can move through to get from one position to the other. By encoding all these connector sets for a pair of positions in a binary vector, and also encoding which of them contain a burning vertex in another vector, their dot product can encode whether or not any of the sets are unburnt. This is all doable using similar mapping techniques as with the linear program for computing DRMVS and the connectors can be computed in polynomial time using a variation of Djikstra's algorithm [10].

4 Expected Damage

Another area of interest for firefighting is determining the *expected damage* sustained by a graph given a fixed number q of initial burning vertices and a fixed number b of firefighters. This is equivalent to computing the *surviving rate* defined in [5]. The expected damage is denoted as E(G; q, b) and is computed as:

$$E(G;q,b) = \sum_{F \subset V(G), |F|=q} \frac{|V(G)| - \mathrm{MVS}(G,F;b)}{\binom{|V(G)|}{q}}$$

The expected damage can be extended to the distance-restricted variant by replacing MVS by DRMVS, and to the distance path restricted variant by replacing MVS by DPRMVS. We denote these expected damage functions by E(G; q, b, d) and $E_{pr}(G; q, b, d)$, respectively.

A classic problem for expected damage is to determine which connected graphs of order n minimize the expected damage [7, 12]. These are typically referred to as *optimal graphs*. For the original problem, the optimal graphs with a single fire and firefighter were completely characterized in [12] and the optimal graphs with two fires and two firefighters were completely characterized in [7]. For a single fire and a single firefighter the optimal graphs are stars and caterpillars where any vertices of degree at least three are at least a distance of three apart. Since the optimal strategy on $K_{1,n-1}$ only involves a single placement of the firefighter we can achieve the same minimum in the distance-restricted and distance-path-restricted games. Thus with a single fire and a single firefighter we can narrow our search for optimal graphs from all graphs to graphs which are optimal in the original game. We will soon see that this is not possible with two fires and two firefighters, and in fact determining the optimal graphs when there are distance and/or path restrictions can be much more difficult than in the original version of firefighter.

Theorem 4.1. When $d \leq 2$ or there are path restrictions the optimal graphs with one fire and one firefighter are stars and graphs formed by taking a star and adding leaves to one leaf of the star.

Proof. First we show that the optimal expected value is $2 - \frac{2}{n}$. Consider the star on n vertices. When the fire starts on one of the n-1 leaves only one vertex burns and when the fire starts in the center n-1 vertices burn. Thus in total (n-1)+(n-1) vertices burn, and we then divide by $\binom{n}{1}$ to get that the expected damage is $\frac{(n-1)+(n-1)}{n} = 2 - \frac{2}{n}$. This is clearly also obtainable for $d \leq 2$ and if there are path restrictions. This shows that the optimal graphs with path restrictions or $d \leq 2$ must be contained in the set of optimal graphs for the original game. This is true since we certainly cannot have a smaller expected damage in our variants of the game, but as we have just shown we can achieve the same value.

We now show that the remaining graphs from the theorem statement are optimal. Suppose we have an edge with ℓ leaves on one end of the edge and t leaves on the other end. If the fire starts on one of the $\ell + t$ leaves only one vertex burns, if it starts on one of the higher degree vertices either $\ell + 1$ or t + 1 vertices burn. Thus we get $\ell + t + \ell + 1 + t + 1$ vertices burning in total, and $\ell + t = n - 2$ so we get 2(n - 2) + 2 = 2n - 2 burning in total. We take that and divide by n to get $2 - \frac{2}{n}$.

Now we show that any other caterpillar graph is non-optimal. Here we take advantage of the fact that since the firefighters are either path-restricted or can only move a distance less than or equal to 2 they can only really defend once and then let the fire spread. First it is necessary to define some quantities relating to our caterpillars. First we require that the spine of our caterpillar only contains vertices of degree greater than 1 and we define the number of vertices on the spine to be p. Now define the number of vertices on the spine with a neighbour not on the spine to be R and for each such vertex let the number of non-spine neighbours be r_i . Note that based on our definition of the spine the case of p = 1 corresponds to stars and the case of p = 2 corresponds to our other class of optimal graphs so we need not concern ourselves with either of these cases.

Case 1: R = 2, p > 2: It is easy to see here from the way our caterpillar is defined that the two end vertices of the spine are the only spine vertices that can have non-spine neighbours. If $p = 3, r_1 = \ell$ and $r_2 = t$ with $\ell \ge t$ we can see that at least $\ell + t + \ell + 1 + t + 1 + t + 2$ vertices will burn. Using the fact that $\ell + t = n - 3$ we get 2(n - 3) + 4 + t, which, when divided by n, yields $2 - \frac{2}{n} + \frac{t}{n} > 2 - \frac{2}{n}$. **Case 1A:** R = 2, p = 4: Let $\ell = r_1 \ge r_2 = k$ again. We again see that at least

Case 1A: R = 2, p = 4: Let $\ell = r_1 \ge r_2 = k$ again. We again see that at least $\ell + t + \ell + 1 + t + 1 + t + 2 + t + 2$ vertices will burn, we divide by n and use the fact that $\ell + t = n - 4$ to get $2 - \frac{2}{n} + \frac{2k}{n} > 2 - \frac{2}{n}$. **Case 1B:** R = 2, p > 4: Now suppose R = 2, p > 4 and note that there are n - p

Case 1B: R = 2, p > 4: Now suppose R = 2, p > 4 and note that there are n - p non-spine vertices. From the leaves we have n - p vertices burning, from the ends of the spine we get another n - p + 2 burning, from the interior vertices of the spine we get 2(p - 2)

vertices burning since that vertex as well as one of its spine neighbours will burn, and from the vertices on the spine that are at distance 2 or more from the both ends of the spine (which are guaranteed to exist since p > 4) we get an additional spine vertex burning thus giving us an additional p - 4 vertices burnt. Adding these all up gives 2n + p - 6, dividing by n gives $2 + \frac{p-6}{n}$ which is greater than $2 - \frac{2}{n}$ since p > 4.

Case 2: R > 2, p > 2: First, each of the non-spine vertices gets burnt once when they are a source and once when their nearest spine vertex is a source (which also burns that spine vertex), which gives 2(n-p) + R burnt vertices. Second, every spine vertex with non-spine neighbours except for the outermost such vertices will cause another spine vertex with non-spine neighbours to burn, thus burning at least an additional $(R-2)\min\{r_i\}$ vertices. Every spine vertex with all their neighbours on the spine will always burn a spine vertex with neighbours off the spine since we forced the endpoints of the spine to have neighbours off the spine, thus burning at least an additional $(p-R)\min\{r_i\}$ vertices. Finally, every spine vertex that is not an endpoint of the spine (which is guaranteed to exist since p > 2) will burn an additional vertex on the spine, thus burning an additional p-2 vertices. This yields $2n - 2p + R + (R-2)\min\{r_i\} + (p-R)\min\{r_i\} + p-2$ which is greater than or equal to 2n - 2p + R + R - 2 + p - R + p - 2 = 2n + R - 4. Now dividing by n gives $2 + \frac{R-4}{n}$ which is greater than $2 - \frac{2}{n}$ since R > 2.

As previously mentioned, we cannot use the same strategy to find the optimal graphs with two fires and two firefighters with distance-restrictions and path-restrictions. This is because the optimal graphs of order at least 14 are stars with four of their original edges subdivided, and the expected damage is strictly larger with $d \leq 2$ or with path restrictions compared to the original game on these graphs. Simply consider the case where one fire starts on the central vertex and the other starts on an adjacent leaf vertex. The optimal strategy for the original game is to defend two of the non-leaf vertices adjacent to the center and then defend the two leaf vertices which have not yet burned but are about to burn. This strategy is depicted in Figure 4.1. The orange diamond vertices represent the initial fires, the black star shaped vertices represent the vertices defended on the first turn.



Figure 4.1: An optimal strategy in the original game which is not feasible with path restrictions or small d

Clearly, the above strategy is not possible with path restrictions. As a result we cannot match the minimum from the original game and so there could be graphs whose expected damage with path restrictions sits between the expected damage without path restrictions and the expected damage with path restrictions of the graph in Figure 4.1. Therefore the optimal graph with path restrictions need not be the same as the optimal graph without path restrictions.

Finding these optimal graphs gets particularly interesting once we consider the fact that in the original game the optimal graphs are always trees, but this need not be the case for our game. It is easy to see that in the original game the removal of an edge does not affect the firefighters since they are not moving within the graph but it can limit the spread of the fire. Since the firefighters move within the graph in the distance-restricted game, this is not necessarily always the case since it could be the case that every optimal strategy requires moving across that edge for some set of initial burning vertices.

First we consider the path-restricted $d = \infty$ case with one fire and one firefighter on a cycle on 7 vertices as well as on a path which spans that cycle. On the cycle it is easy to see that the expected damage is 2 since the firefighter will defend a vertex adjacent to the fire, the fire will spread to its other neighbour, and the firefighter will then move around the cycle and stop the fire from spreading further. Contrast this to the path where the optimal strategy is to defend whichever side of the fire contains a longer subpath and then let the fire spread until it cannot spread anymore. Clearly on the path the only cases where less than two vertices burn is when the fire is on a leaf, but if we pair those up with the cases where the fire starts distance 2 from a leaf they average out to 2 vertices burning. Thus since in every other case at least two vertices burn, and there are guaranteed to be some remaining cases where at least four burn, the path will have higher expected damage with path restrictions than without.

So what about the case of interest with two fires and two firefighters? It turns out that for b fires and b firefighters, there exist graphs where the expected damage of a graph is strictly less than the expected damage of one of its connected spanning subgraphs.

Theorem 4.2. Let G_A be a connected graph on at least b+1 vertices and let G_B be a connected graph on exactly b+1 vertices. For any integer $\ell > 0$, create G_ℓ as follows. Number the vertices of G_B 1 to b+1 and select a (b+1)-subset of the vertices of G_A to do the same. For each vertex in G_B connect it via a path with ℓ internal vertices to the vertex in G_A with the same label.³ If ℓ is sufficiently large then $E_{pr}(G_\ell; b, b, \infty) < E_{pr}(G_\ell - E(G_B); b, b, \infty)$. Furthermore, the ratio $\frac{E_{pr}(G_\ell; b, b, \infty)}{E_{pr}(G_\ell - E(G_B); b, b, \infty)}$ can be arbitrarily large.

Proof. First we show that $\binom{|V(G_{\ell})|}{b} E_{pr}(G_{\ell}; b, b, \infty) \in \mathcal{O}(\ell^{b})$. Notice that $|V(G_{\ell})| \in \mathcal{O}(\ell)$ and that there are $\mathcal{O}(\ell^{b-1})$ initial burning configurations where at least one vertex is in $V(G_A) \cup V(G_B) \cup N(V(G_A)) \cup N(V(G_B))$.⁴ Thus since at most $\mathcal{O}(\ell)$ vertices can burn in these $\mathcal{O}(\ell^{b-1})$ scenarios, we have that this set of initial configurations contributes at most $\mathcal{O}\left(\ell^{b}\right)$ to $\binom{|V(G_{\ell})|}{b}E_{pr}\left(G_{\ell};b,b,\infty\right)$. The remaining initial configurations are configurations where no initial burning vertices are in $V(G_A) \cup V(G_B) \cup N(V(G_A)) \cup N(V(G_B))$. Here we can show that at most 2b vertices burn in any of these configurations. The strategy to do this is for each fire, one firefighter defends the neighbour of the fire which is closest to G_A . On the next turn the firefighters each do one of two things. If the firefighter has no clear path to G_A they simply move as far as possible along their path towards G_A and defend that vertex. Otherwise the firefighter has a clear path to G_A , so they move through G_A , through the path which has no fire, and then through G_B to block any fires moving towards G_B . At this point the fire can no longer spread since the initially burning vertices were all of degree two, their neighbours were of degree two, the firefighters defended one of the neighbours, and the firefighters defended the vertex at distance 2 on the other side from that neighbour.⁵ So in these situations every initially burning vertex burned at most one other vertex. Thus in these initial configurations there are at most $2b\binom{(b+1)(\ell-2)}{b} \in \mathcal{O}(\ell^b)$ vertices burning.

We now show that $\binom{|V(G_{\ell})|}{b}E_{pr}(G_{\ell}-E(G_B);b,b,\infty) \in \Omega(\ell^{b+1})$. Select one path (which now terminates at a leaf) to be empty and place one fire on each of the remaining paths so that the fire is at least distance $\frac{\ell}{4}$ from the leaf and from G_1 . There are $(\frac{\ell}{2})^b$ such configurations and in each configuration one of two things happens. Either the firefighters all initially defend on the leaf side of the fires, in which case at least $\frac{\ell}{4}$ vertices burn, or at least one fire has no firefighter between itself and the leaf, in which case at least $\frac{\ell}{4}$ vertices burn. Thus in these configurations at least $(\frac{\ell}{4})(\frac{\ell}{2})^b \in \Omega(\ell^{b+1})$ vertices burn.

 $^{^{3}}$ For an example of this construction see Figure 4.2.

⁴We use N(S) here to represent vertices which are not in S but have a neighbour in S.

⁵Note that if the fires are close together it could cause this strategy to be invalid, but it is easy to see that a combination of removing invalid moves and having the firefighter defend the other side of the fire yields a strategy which will perform just as well in these cases.



Figure 4.2: G_3 with b = 2 when G_A is K_4 and G_B is K_3

It is also worth noting that we can take G_A to be a tree and we get a spanning subtree of the graph G_{ℓ} in Theorem 4.2, which tells us that we can remove as many edges as possible without disconnecting the graph and still have a graph that is worse for the firefighters than the original graph.

5 Discussion and Open Problems

This paper establishes the NP-completeness of DR-*b*-FF and DPR-*b*-FF, but there are still many questions to be asked. For instance, we showed that DPR-*b*-FF is NP-complete on bipartite graphs and polynomial time on trees when |F| = 1, but it is still open whether or not the problem satisfies a dichotomy. Our description of DPR-*b*-FF also allowed us to choose an appropriate value of *d* during the reduction. Is the problem still NP-complete if the value of *d* is fixed beforehand? For DRMVS we know that there is a value of *d* where DRMVS and MVS are the same. How hard is it to find the smallest such *d*?

We also discussed the idea of expected damage. Section 4 characterizes the optimal graphs with a single fire and firefighter for all values of d with and without path restrictions. We saw however that the lack of monotonicity with path restrictions makes it hard to determine optimal graphs for more fires and firefighters. This lack of monotonicity is particularly interesting and characterizing exactly when a subgraph has smaller expected damage could be an interesting direction of research. From a complexity standpoint one could consider a decision problem where a certain, fixed number s of edges can be added to the graph and the question is whether or not the path-restricted expected damage can be reduced by the addition of at most s edges.

Acknowledgements

Authors A.C. Burgess and D.A. Pike acknowledge research support from NSERC Discovery Grants RGPIN-2019-04328 and RGPIN-2022-03829, respectively. Author J. Marcoux acknowledges support from the Mitacs Accelerate Program and Verafin.

References

- [1] Kathleen D. Barnetson, Andrea C. Burgess, Jessica Enright, Jared Howell, David A. Pike, and Brady Ryan, *The firebreak problem*, Networks **77** (2021), no. 3, 372–382.
- [2] Libor Barto, Zarathustra Brady, Andrei Bulatov, Marcin Kozik, and Dmitriy Zhuk, Unifying the three algebraic approaches to the CSP via minimal Taylor algebras, TheoretiCS 3 (2024), Art. 14, 76.
- [3] Cristina Bazgan, Morgan Chopin, and Bernard Ries, *The firefighter problem with more than one firefighter on trees*, Discrete Appl. Math. **161** (2013), no. 7-8, 899–908.
- [4] Andrea C. Burgess, John Marcoux, and David A. Pike, *Firefighting with a distance-based restriction*, arXiv preprint arXiv:2204.01908 (2022).
- [5] Leizhen Cai and Weifan Wang, The surviving rate of a graph for the firefighter problem, SIAM J. Discrete Math. 23 (2009/10), no. 4, 1814–1826.
- [6] Xujin Chen, Xiaodong Hu, Changjun Wang, and Ying Zhang, Continuous firefighting on infinite square grids, Theory and applications of models of computation, Lecture Notes in Comput. Sci., vol. 10185, Springer, Cham, 2017, pp. 158–171.
- [7] Stuart Crosby, Art Finbow, Bert Hartnell, Rania Moussi, Kate Patterson, and Dania Wattar, *Designing fire resistant graphs*, vol. 173, 2005, 36th Southeastern International Conference on Combinatorics, Graph Theory, and Computing, pp. 207–222.
- [8] Sarah Days-Merrill, *Firefighter problem played on infinite graphs*, Honors thesis, Bridgewater State University, 2019.
- [9] Mike Develin and Stephen G. Hartke, Fire containment in grids of dimension three and higher, Discrete Appl. Math. 155 (2007), no. 17, 2257–2268.
- [10] E. W. Dijkstra, A note on two problems in connexion with graphs, Numer. Math. 1 (1959), 269–271.
- [11] Jack Edmonds, Paths, trees, and flowers, Canadian J. Math. 17 (1965), 449–467.
- [12] Stephen Finbow, Bert Hartnell, Qiyan Li, and Kyle Schmeisser, On minimizing the effects of fire or a virus on a network, J. Combin. Math. Combin. Comput. 33 (2000), 311–322.

- [13] Stephen Finbow, Andrew King, Gary MacGillivray, and Romeo Rizzi, The firefighter problem for graphs of maximum degree three, Discrete Math. 307 (2007), no. 16, 2094– 2105.
- [14] Stephen Finbow and Gary MacGillivray, The firefighter problem: a survey of results, directions and questions, Australas. J. Combin. 43 (2009), 57–77.
- [15] Bert Hartnell, Firefighter! An application of domination, 25th Manitoba Conference on Combinatorial Mathematics and Computing, 1995.
- [16] Qi Huangfu and J. A. Julian Hall, Parallelizing the dual revised simplex method, Math. Program. Comput. 10 (2018), no. 1, 119–142.
- [17] Gary MacGillivray and Ping Wang, On the firefighter problem, Journal of Combinatorial Mathematics and Combinatorial Computing 47 (2003), 83–96.
- [18] Connor Wagner, A new survey on the firefighter problem, Masters thesis, University of Victoria, 2021.