

A Logic-Based Framework for Database Repairs

Nicolas Fröhlich

Arne Meier

nicolas.froehlich@thi.uni-hannover.de

meier@thi.uni-hannover.de

Institut für Theoretische Informatik, Leibniz Universität
Hannover
Hannover, Germany

Nina Pardal

Jonni Virtema

n.pardal@sheffield.ac.uk

j.t.virtema@sheffield.ac.uk

University of Sheffield
Sheffield, UK

ABSTRACT

We introduce a general abstract framework for database repairing in which the repair notions are defined using formal logic. We differentiate between integrity constraints and the so-called query constraints. The former are used to model consistency and desirable properties of the data (such as functional dependencies and independencies), while the latter relates two database instances according to their answers for the query constraints. The framework also admits a distinction between hard and soft queries, allowing to preserve the answers of a core set of queries as well as defining a distance between instances based on query answers.

We exemplify how various notions of repairs from the literature can be modelled in our unifying framework. Furthermore, we initiate a complexity-theoretic analysis of the problems of consistent query answering, repair computation, and existence of repair within the new framework. We present both coNP- and NP-hard cases that illustrate the interplay between computationally hard problems and more flexible repair notions. We show general upper bounds in NP and the second level of the polynomial hierarchy. Finally, we relate the existence of a repair to model checking of existential second-order logic.

CCS CONCEPTS

• **Theory of computation** → **Database theory; Incomplete, inconsistent, and uncertain databases; Logic and databases; Problems, reductions and completeness; Complexity theory and logic.**

KEYWORDS

Database repairs, Complexity, Consistent query answering

1 INTRODUCTION

Inconsistency is a common phenomenon when dealing with large collections of data. In real-world applications, data is often made available from non-trustworthy sources (e.g., the Internet, or social media), resulting in very diverse quality of data, which can lead to problems related to the integrity of databases and repositories. *Database repairing*, one of the main approaches for dealing with inconsistency, focuses on frameworks that allow inconsistencies to be identified in order to then obtain a database that satisfies the constraints imposed. The usual approach is to search for a ‘similar’ database that satisfies the constraints. This new database is called a *repair*, and in order to define it properly one must determine the meaning of ‘similar’. Repairs have been studied from different perspectives and several frameworks have been presented, including

the introduction of preference criteria represented by weights, as well as both soft and hard constraints. Some of the most prominent notions of repairs are set-based repairs [3, 25], attribute-based repairs [27], and cardinality-based repairs [18]. Another approach to deal with inconsistency is to use an inconsistency measure, which can be either a function that counts the number of integrity constraints violated, an abstract non-negative mapping to some partial order, or even a numerical measure based on an abstract repair semantics [4, 7, 17, 22]. In this setting, a repair need not satisfy all the required integrity constraints but instead repairs are tolerant for a certain amount of inconsistency.

A database may admit multiple (a priori) incomparable repairs in the sense that it is not always clear what is the best way to repair an inconsistent database. *Consistent Query Answering* (CQA) aims to generalise the notion of cautious reasoning (or certain answers, in database parlance) in the presence of inconsistent knowledge. In the setting of CQA, a “valid” answer to a query is one that can be found in every possible repair. This problem has been analysed for different data models and different types of integrity constraints, under the most prominent repair semantics.

Data provenance provides means to describe the origins of data, allowing to give information about the witnesses to a query, or determining how a certain output is derived. Provenance semirings were introduced by Green et al. [12] to devise a general framework that allows to uniformly treat extensions of positive relational algebra, where the tuples have annotations that reflect very diverse information. Some motivating examples of said relations come from incomplete and probabilistic databases, and bag semantics. This semiring framework captures a notion of data provenance called *how-provenance*, where the semiring operations essentially capture how each output is produced from the source. Following this framework, semiring semantics for full first-order logic (FO) were developed by Grädel and Tannen [10]. The semiring semantics for FO refines, in particular, the classical Boolean semantics by allowing formulae to be evaluated as values from a semiring. If K is a semiring, then a K -relation is a relation whose records are annotated with elements from K .

In this paper, we consider repairs and consistent query answering in the setting of K -databases, which are relational databases, whose tables are K -relations. This is a general approach that encompasses relational databases under set and bag semantics, as well as repairs in conjunction with K -relations that encode some provenance data.

Our contribution. We present an abstract framework for defining database repairs that allows us to unify and simultaneously incorporate diverse notions that have been used in the literature to

deal with inconsistency. We allow a distinction between integrity constraints, which allows us to classify properties of data as either necessary or merely desirable to preserve in a repair. The latter are essentially used to define a measure for inconsistency-tolerant repairs. The repair notions in our framework are expressed through the preservation of a given core set of query answers; together with integrity constraints, this yields the space for possible repairs. The distance between databases is computed using distances between the answers of specified queries in each instance. The technical definitions are presented in Section 3. We show examples of how well-known repair notions from literature can be expressed in our framework and exemplify the flexibility of the framework by generating novel repair notions.

Our framework enables us to simultaneously prove complexity results for a wide family of repair notions. We exemplify this in the simple setting of set-based databases, where we obtain results for the complexity of the most important computational problems. Table 1 summarises our results on the complexity of CQA, Table 3 for the complexity of computing a repair, and Table 2 for the complexity of deciding the existence of a repair. Our results extend and generalise existing results on the complexity of repairing and pinpoint problems that are complete for the first and second level of the polynomial hierarchy. Intuitively, the tables contain (possible) restrictions for each of the four components of our framework: hard/soft constraints (C_h, C_s) as well as hard/soft queries (Q_h, Q_s). For instance, FO for C_h means that the hard constraints can only be specified by (sets of) first-order formulae, and LAV and GAV refer to *local-as-view* and *global-as-view* tuple generating dependencies; see Section 5.1 for the definitions. Our complexity results here exemplify how our approach can be utilised to yield complexity bounds for a diverse class of repair notions. We return to this topic in the end of the following related work paragraph.

Related work. Most of the previous research on repairs has been conducted within the data management community, while the problem of measuring inconsistency has been approached mostly by the knowledge representation community. From a logical perspective, some work explores reasoning within inconsistencies in knowledge bases and ontologies as a means to compute consistent answers and repairs, as well as to produce meaningful repair candidates (see, e.g., [11, 24, 29]). In 2019, Burdick et al. [5] address the problem of repairing using entity linking, using weights and consistent answers to determine the strength of the links, thus allowing the repair to be performed only on a given part of the schema. In the repair literature, a set of integrity constraints and a distance between instances is always presented. In some cases, the distance is represented by an inconsistency measure. However, while there are approaches to repair that reflect the evaluation of important queries as criteria for determining preference, these usually focus on how to resolve conflicts and provide meaningful query answers despite the inconsistency [6, 23]. On the other hand, the idea of having a core set of query answers that need to be preserved is similar to Belief Revision (BR) concepts. The AGM theory for Belief Change, defined by Alchourron et al. [2], represents *belief sets* as sets of formulae closed under a consequence operator, and a list of postulates describes how the revision operator incorporates new information, even if this information is inconsistent with what is

ICs		repair notions		\mathcal{R} -CQA	
C_h	C_s	Q_h	Q_s	Complexity	
LAV	\emptyset	LIT	ATOMS	coNP-hard	[Prop. 5.5]
GAV	\emptyset	LIT	ATOMS	coNP-hard	[26, Thm. 5.5]
GAV	\emptyset	COQ \cup LIT	\emptyset	coNP-complete	[Thm. 5.9]
FO	\emptyset	FO	\emptyset	coNP-complete	[Thm. 5.9]
tgds	\emptyset	LIT	ATOMS	Π_2^P -complete	[Thm. 5.10]
FO	\emptyset	FO	FO	Π_2^P -complete	[Thm. 5.10]

Table 1: Complexity results overview for consistent query answering. Hardness results hold already for conjunctive queries, while inclusions are proven for first-order queries. Upper/lower bounds transfer to respective classes, e.g., the membership result for FO applies also to subclasses like LIT or ATOMS.

ICs		repair notions		$\exists\mathcal{R}$ -repair	
C_h	C_s	Q_h	Q_s	Complexity	
GAV	\emptyset	COQ \cup LIT	\emptyset	NP-complete	[Prop. 5.6]
FO	\emptyset	FO	ANY	NP-complete	[Thm. 5.7]

Table 2: Complexity results overview for existence of a repair.

ICs		repair notions		F- \mathcal{R} -repair	
C_h	C_s	Q_h	Q_s	Complexity	
GAV	\emptyset	LIT	ATOMS	FNP-hard, in $F\Sigma_2^P$	[Prop. 5.3]
LAV	\emptyset	LIT	ATOMS	FNP-hard, in $F\Sigma_2^P$	[Prop. 5.4]

Table 3: Complexity results overview for repair computation.

believed. Guerra and Wassermann [13] give a characterisation of model repair in terms of BR by introducing a new postulate that preserves the core of a belief set in the repair model unless the result obtained is not strictly better in terms of preserving said core set. We are not aware of existing repair frameworks that simultaneously incorporate the impositions given by a set of integrity constraints and preserve the answers of a given set of queries, as well as allow the introduction of shades of inconsistency or truth as part of an inconsistency measure or minimality criteria.

In 2012, ten Cate et al. [25] gave a systematic study of the data complexity of the CQA and repair checking problems for set-based repairs. The restrictions imposed to the integrity constraints arise from classes of tuple-generated dependencies, vital in data exchange and data integration. The results of ten Cate et al. [25] can be framed as results concerning particular \mathcal{R} -repairs. More precisely, our results can be seen as a generalisation of their results, by refining the components of our framework.

Organisation. Section 2 begins with an introduction to basic mathematical concepts, relational structures, and databases. We then introduce the necessary concepts from logic and query languages, as well as related to repairs and consistent query answering. In Section 3, we present our unified framework for repairs and show via examples how well-known repair notions can be expressed in the framework. In Section 4, we exemplify the flexibility of our framework by defining various novel repair notions. In Section 5, we initiate a complexity-theoretic study of central problems related to database repairs and consistent query answering in our framework. Finally, we present a conclusion and an outlook.

2 PRELIMINARIES

We assume that the reader is familiar with some basic notions related to first-order logic and foundations of databases (see, e.g., [1, 16] for in-depth expositions) as well as computational complexity theory [21].

2.1 Notation and elementary mathematics

We write \vec{a} to denote a finite tuple (a_1, \dots, a_n) of elements from some set A . A *multiset* is a generalisation of a set that keeps track of the multiplicities of its elements. We write $\{\{\cdot\cdot\}\}$ to denote a multiset whose elements are written between the double curly brackets. For instance, $\{\{a, a, b\}\}$ is a multiset that has two copies of a and a single copy of b . For a multiset A , we write $\text{Supp}(A)$ to denote the underlying set of A , which is called the *support* of A , e.g., $\text{Supp}(\{\{a, a, b\}\}) = \{a, b\}$. For a set or a multiset A , we write $|A|$ for the cardinality of A . We say that a set or a multiset is finite if its cardinality is a natural number.

Definition 2.1 (Semiring). A *semiring* is a tuple $K = (K, +, \cdot, 0, 1)$, where $+$ and \cdot are binary operations on a set K , $(K, +, 0)$ is a commutative monoid with identity element 0, $(K, \cdot, 1)$ is a monoid with identity element 1, \cdot left and right distributes over $+$, and $x \cdot 0 = 0 = 0 \cdot x$ for all $x \in K$. The semiring K is called *commutative* if $(K, \cdot, 1)$ is a commutative monoid. For convenience, we often write ab instead of $a \cdot b$.

If a semiring K satisfies $ab = 0$ for some $a, b \in K$ where $a \neq 0 \neq b$, we say that K has *divisors of 0*. Furthermore, a semiring K is considered *+positive* if $a + b = 0$ implies that $a = b = 0$. If a semiring is both *+positive* and has no divisors of 0, it is called *positive*. For example, the modulo two integer semiring \mathbb{Z}_2 is not positive since it is not *+positive* (even though it has no divisors of 0). Conversely, an example of a semiring with divisors of 0 is \mathbb{Z}_4 . Throughout the paper we consider only ordered commutative semirings which are positive, and write $<$ for the order relation. Technically, our definitions also work for non-positive semirings. Below we list some examples of semirings.

Example 2.2. The *Boolean semiring* $\mathbb{B} = (\mathbb{B}, \vee, \wedge, 0, 1)$ models logical truth or set-based data, and is formed from the two-element Boolean algebra. It is the simplest example of a semiring that is not a ring. The *semiring of natural numbers* $\mathbb{N} = (\mathbb{N}, +, \cdot, 0, 1)$ consists of natural numbers with their usual operations and can be used, e.g., to model multisets of data. The *probability semiring* $\mathbb{R}_{\geq 0} = (\mathbb{R}_{\geq 0}, +, \cdot, 0, 1)$ consists of the non-negative reals with standard addition and multiplication.

An *aggregate function* σ (for a semiring K) is a function that maps multisets of elements of K into one element of K . For instance, the sum and product of the elements in a multiset are examples of aggregate functions.

Definition 2.3. Let K be a semiring, A a set, and $n \in \mathbb{N}$ a natural number. An *n -ary K -relation* is a function $R: B \rightarrow K$, where $B \subseteq A^n$. We define the *support* of R via $\text{Supp}(B) := \{b \in B \mid R(b) \neq 0\}$. By convention B is often identified with A^n by setting $R(b) = 0$ for $b \in A^n \setminus B$.

Note that K -relations, for $K = \mathbb{B}$ (the Boolean semiring) or $K = \mathbb{N}$ (the semiring of natural numbers), are essentially sets and multisets, respectively.

2.2 Relational structures and databases

A *finite purely relational vocabulary* is a finite set $\{R_1, \dots, R_n\}$ of relation symbols. Each relation symbol R_i has a fixed *arity* $\text{ar}(R_i) \in \mathbb{N}$. Since in the database setting it is often assumed that all data values can be represented by symbols in queries, we consider relational vocabularies τ , which are extensions of finite purely relational vocabularies with a countable set of constant symbols c_i , for $i \in \mathbb{N}$. A τ -*interpretation* is a function I that maps each n -ary relation symbol to an n -ary relation $I(R_i) \subseteq A^n$ and each constant symbol c to some element $I(c) \in A$, over some *domain* set A . If instead, the interpretations of n -ary relation symbols are K -relations with support from A^n , we call I a (τ, K) -*interpretation*. A *finite τ -structure* (or finite (τ, K) -*structure*, resp.) \mathfrak{D} is a tuple consisting of a finite domain set A and the interpretations of the symbols in τ , which in the case of (τ, K) -structures are K -relations. We often write $R^{\mathfrak{D}}$ and $c^{\mathfrak{D}}$ to denote the interpretations $I(R)$ and $I(c)$ of R and c in \mathfrak{D} , respectively.

For our purposes, a database schema is essentially a relational vocabulary, where relation symbols correspond to database table names and their coordinates correspond to attribute names. Moreover, interpretations are restricted to take values from a fixed set of values. Formally, a *database schema* \mathcal{S} expands a relational vocabulary τ with a finite set Att of attributes and countable sets of possible values $\text{Ran}(x)$, for each $x \in \text{Att}$. The *domain* of the schema $\text{Dom}(\mathcal{S})$ consists of the union of $\text{Ran}(x)$ for $x \in \text{Att}$. We write Dom instead of $\text{Dom}(\mathcal{S})$, when \mathcal{S} is clear from the context. Furthermore, \mathcal{S} fixes the type $\text{type}(R_i) \in \text{Att}^n$ of each n -ary relation symbol R_i and the type $\text{type}(c) \in \text{Att}$ of each constant symbol c . A *database* or an *instance* \mathfrak{D} over \mathcal{S} is obtained via an interpretation that maps each constant symbol $c \in \tau$ to an element $c^{\mathfrak{D}} \in \text{Ran}(\text{type}(c))$ and each n -ary relation symbol $R \in \tau$ to a finite relation $R^{\mathfrak{D}} \subseteq \text{Ran}(\text{type}(R))$, where $\text{Ran}(x_1, \dots, x_n)$ is defined as $\text{Ran}(x_1) \times \dots \times \text{Ran}(x_n)$.

The *active domain* $\text{ADOM}(\mathfrak{D})$ of a database \mathfrak{D} of schema \mathcal{S} is the smallest finite set such that $R^{\mathfrak{D}} \subseteq \text{ADOM}(\mathfrak{D})^{\text{ar}(R)}$ and $c^{\mathfrak{D}} \in \text{ADOM}(\mathfrak{D})$ for each relation symbol R and constant symbol c of the schema. We denote the set of all databases over \mathcal{S} by $\mathcal{D}(\mathcal{S})$ and write \mathcal{D} when the schema is clear from the context.

If K is a semiring and \mathcal{S} is a database schema, a *K -database* is obtained from a database of schema \mathcal{S} by reinterpreting its relation symbols by K -relations of the same support.

Instances of a database schema can naturally be interpreted as finite relational structures over the underlying schema vocabulary, extended by unary relation symbols R_x , for each $x \in \text{Att}$,

interpreted as $\text{Ran}(x)$. The domain of the finite relational structure corresponding to a database \mathfrak{D} is the active domain $\text{ADOM}(\mathfrak{D})$ of \mathfrak{D} . In the same way, K -databases can be interpreted as finite (τ, K) -structures for a suitable τ . From now on we will identify τ -structures as databases and (τ, K) -structures as K -databases.

Let \mathfrak{D} be a database (K -database, resp.) and R be a relation (K -relation, resp.) of the database. The atomic formula $R(\vec{a})$ is called a *fact*, if $\vec{a} \in R^{\mathfrak{D}}$ (resp., $\vec{a} \in \text{Supp}(R^{\mathfrak{D}})$). Similarly, $\neg R(\vec{a})$ is a *negated fact*, if $\vec{a} \notin R^{\mathfrak{D}}$ ($\vec{a} \notin \text{Supp}(R^{\mathfrak{D}})$, resp.). If $R(\vec{a})$ is a fact, then \vec{a} is a *record* of R and \mathfrak{D} . In the set-based environment, we sometimes define databases by listing all the facts in the database. For example, the database $\mathfrak{D} = \{C(a), C(b), T(a, c), T(a, b)\}$ consists of two tables C and T , each of which consists of two facts. Using the above convention, we define that the *symmetric difference* $\mathfrak{D} \oplus \mathfrak{D}'$ of two database instances \mathfrak{D} and \mathfrak{D}' is the database that contains all the facts that belong to exactly one of \mathfrak{D} or \mathfrak{D}' . Similarly, we write that $\mathfrak{D} \subseteq \mathfrak{D}'$ if every fact of \mathfrak{D} is also a fact of \mathfrak{D}' . We use other set comparison symbols and operations on sets analogously.

2.3 Logics and query languages

We will consider logics \mathcal{L} which are syntactic fragments and extensions of first-order logic, whose satisfaction relations \models are defined over databases (i.e., relational structures) or K -databases. More importantly, formulae of these logics have well-defined notions of *free* and *bounded variables*. Formulae without free variables are called *sentences*. Logical formulae can naturally be interpreted as database queries; sentences correspond to *Boolean queries* and formulae with k free variables correspond to *k-ary queries*. If ϕ is a formula of some logic with free variables in \vec{x} , and \vec{a} is a tuple of domain elements of the same length, we write $\phi(\vec{a}/\vec{x})$ to denote that the variables \vec{x} are interpreted as \vec{a} . If $s: \text{Var} \rightarrow D$ is a variable assignment, we set

$$s[a/x](y) := \begin{cases} a, & \text{if } y = x, \\ s(y), & \text{otherwise.} \end{cases}$$

The two main approaches to defining logics for K -databases are the logics for *meta-finite structures* of Grädel and Gurevitch [9] and the use of semiring semantics as defined by Grädel and Tannen [10]. We adopt an approach close to the latter, where in addition to having K -relations, “truth” values of sentences are also elements of a semiring. K -databases can be seen as a special kind of model-defining K -interpretations of Grädel and Tannen.

Definition 2.4. Let $K = (K, +, \cdot, 0, 1)$ be some semiring and \mathfrak{D} a K -database. Given a variable assignment $s: \text{Var} \rightarrow D$, the value $\llbracket \phi \rrbracket_{\mathfrak{D}, s}$ of a formula $\phi \in \text{FO}$ under s is defined recursively as follows:

$$\begin{aligned} \llbracket R(\vec{x}) \rrbracket_{\mathfrak{D}, s} &= R^{\mathfrak{D}}(s(\vec{x})) & \llbracket \phi \wedge \psi \rrbracket_{\mathfrak{D}, s} &= \llbracket \phi \rrbracket_{\mathfrak{D}, s} \cdot \llbracket \psi \rrbracket_{\mathfrak{D}, s} \\ \llbracket \neg \phi \rrbracket_{\mathfrak{D}, s} &= \llbracket \text{nfn}(\neg \phi) \rrbracket_{\mathfrak{D}, s} & \llbracket \phi \vee \psi \rrbracket_{\mathfrak{D}, s} &= \llbracket \phi \rrbracket_{\mathfrak{D}, s} + \llbracket \psi \rrbracket_{\mathfrak{D}, s} \\ \llbracket \forall x \phi \rrbracket_{\mathfrak{D}, s} &= \prod_{a \in D} \llbracket \phi \rrbracket_{\mathfrak{D}, s[a/x]} & \llbracket \exists x \phi \rrbracket_{\mathfrak{D}, s} &= \sum_{a \in D} \llbracket \phi \rrbracket_{\mathfrak{D}, s[a/x]} \\ \llbracket \neg R(\vec{x}) \rrbracket_{\mathfrak{D}, s} &= \begin{cases} 1, & \text{if } \llbracket R(\vec{x}) \rrbracket_{\mathfrak{D}, s} = 0 \\ 0, & \text{otherwise,} \end{cases} & \llbracket x \sim y \rrbracket_{\mathfrak{D}, s} &= \begin{cases} 1, & \text{if } s(x) \sim s(y) \\ 0, & \text{otherwise,} \end{cases} \end{aligned}$$

where $\sim \in \{=, \neq\}$ and $\text{nfn}(\neg \phi)$ is the formula obtained from $\neg \phi$ by pushing all the negations to atomic level using the usual dualities. We write $\phi \rightarrow \psi$ as a shorthand for $\neg \phi \vee \psi$, and $\phi \leftrightarrow \psi$ as a

shorthand for $(\phi \rightarrow \psi) \wedge (\psi \rightarrow \phi)$. For sentences ϕ , we write $\llbracket \phi \rrbracket_{\mathfrak{D}}$ as a shorthand for $\llbracket \phi \rrbracket_{\mathfrak{D}, s_0}$, where s_0 is the empty assignment. We write $\mathfrak{D}, s \models \phi$ ($\mathfrak{D} \models \phi$, resp.), if $\llbracket \phi \rrbracket_{\mathfrak{D}, s} \neq 0$ ($\llbracket \phi \rrbracket_{\mathfrak{D}} \neq 0$, resp.). We define $\llbracket \phi \rrbracket_{\mathfrak{D}}^B = 1$, if $\mathfrak{D}, s \models \phi$, and $\llbracket \phi \rrbracket_{\mathfrak{D}}^B = 0$ otherwise.

If \mathfrak{D} is a database instance and ϕ is a query, then a *query answer* over a database \mathfrak{D} is a tuple of elements \vec{a} from $\text{Dom}(\mathfrak{D})$ such that $\mathfrak{D} \models \phi(\vec{a}/\vec{x})$. We write $\text{Ans}(\mathfrak{D}, \phi) := \{\vec{a} \in D^n \mid \mathfrak{D} \models \phi(\vec{a}/\vec{x})\}$ to denote the set of answers to the query in the database. We write

$$w_{\mathfrak{D}, \phi}(\vec{a}) := \llbracket \phi(\vec{a}/\vec{x}) \rrbracket_{\mathfrak{D}},$$

to indicate the annotated answers to the query in the database.

2.4 Repairs and consistent query answering

Integrity constraints (ICs) are sentences in some logic that describe the necessary properties that we need the data to comply so that it is consistent with the reality it intends to model. Given a set of ICs C , we say that \mathfrak{D} is *consistent (w.r.t. C)* if \mathfrak{D} satisfies C , that is, $\mathfrak{D} \models \phi$ for every $\phi \in C$. Otherwise, we say that \mathfrak{D} is *inconsistent*. A set of integrity constraints is *consistent* if there exists a database instance \mathfrak{D} that makes the ICs true. The classical definition of a repair involves a set of ICs C and a way to measure the distance between instances. Given a distance d between instances and $\mathfrak{D}_1, \mathfrak{D}_2, \mathfrak{D}_3 \in \mathcal{D}$, we write $\mathfrak{D}_2 \leq_{d, \mathfrak{D}_1} \mathfrak{D}_3$ if $d(\mathfrak{D}_1, \mathfrak{D}_2) \leq d(\mathfrak{D}_1, \mathfrak{D}_3)$. A database \mathfrak{D}_2 is a *repair* of \mathfrak{D}_1 , if \mathfrak{D}_2 is \leq_{d, \mathfrak{D}_1} -minimal in the set $\{\mathfrak{D} \in \mathcal{D} \mid \mathfrak{D} \models C\}$.

Set-based repairs are one of the most prominent types of repairs [3, 25]. The goal is to find a consistent database instance, with the same schema as the original one, that satisfies the repair semantics (e.g., *subset*, *superset* and *symmetric difference*) and differs from the original by a minimal set of records under set inclusion. Given a set of integrity constraints C , the instance \mathfrak{D}' is a *symmetric difference repair* of \mathfrak{D} w.r.t. C if $\mathfrak{D}' \models C$ and there is no instance \mathfrak{D}'' such that $\mathfrak{D}'' \models C$ and $\mathfrak{D} \oplus \mathfrak{D}'' \subseteq \mathfrak{D} \oplus \mathfrak{D}'$. The instance \mathfrak{D}' is a *subset repair* of \mathfrak{D} w.r.t. C if $\mathfrak{D}' \subseteq \mathfrak{D}$ and \mathfrak{D}' is a symmetric difference repair of \mathfrak{D} . *Superset repair* is defined analogously. Cardinality-based repairs as defined in [18] aim to find repairs of the original database that minimise the cardinality of the symmetric difference between instances.

In the example below, we use counting quantifiers as a shorthand notation: $\exists^{\geq n} x \phi(x)$ is a shorthand for

$$\exists x_1 \dots \exists x_n \left(\bigwedge_{1 \leq i < j \leq n} x_i \neq x_j \wedge \bigwedge_{1 \leq i \leq n} \phi(x_i/x) \right),$$

and $\exists^{\leq k} x \phi(x) := \neg \exists^{\geq k+1} x \phi(x)$.

Example 2.5. Consider a database schema consisting of a binary relation $T(x, y)$ and a unary relation $C(y)$, where $\text{Ran}(x) = \{t_1, t_2, t_3\}$ and $\text{Ran}(y) = \{a, b, c, d\}$. Consider a set of integrity constraints $C = \{\forall y (C(y) \leftrightarrow \exists x T(x, y))\}$ and an inconsistent instance $\mathfrak{D} = \{C(c), C(d), T(t_1, a), T(t_2, a), T(t_3, a), T(t_2, b)\}$. Then,

$$\begin{aligned} \mathfrak{D}_1 &:= \{C(a), C(b), C(c), C(d), T(t_1, a), T(t_2, a), \\ &\quad T(t_3, a), T(t_2, b), T(t_2, c), T(t_3, d)\} \end{aligned}$$

is both a superset and a symmetric difference repair, for it minimises the symmetric difference $\mathfrak{D} \oplus \mathfrak{D}_1 = \{C(a), C(b), T(t_2, c), T(t_3, d)\}$. Notice there are no non-trivial subset repairs.

Consider then another set of ICs $C' = \{\forall x \exists^{\leq 2} y T(x, y)\}$. Now $\mathfrak{D}_2 = \{C(c), C(d), T(t_1, a), T(t_3, a), T(t_2, b)\}$ is a subset repair that is also a symmetric difference repair. In this case, there are no superset repairs. Finally, if the integrity constraints are $C \cup C'$, then there are no subset or superset repairs. Moreover,

$$\mathfrak{D}_3 = \{C(a), C(b), T(t_1, a), T(t_3, a), T(t_2, b)\}$$

is a symmetric difference repair.

Related to the problem of repairs, *consistent query answering* (CQA) aims to generalise the notion of cautious reasoning (or certain answers, in database parlance) in the presence of inconsistent knowledge. A database may allow multiple (a priori) equally good repairs. For its part, CQA proposes that an answer to a query on a database must be such that it is an answer to the query in any possible repair of the original database. More formally, given a database \mathfrak{D} , a set of ICs C , and a query $q(\vec{x}) \in \mathcal{L}$, the consistent answers to q w.r.t. \mathfrak{D} and C , denoted by $CQA(q, \mathfrak{D}, C)$, is the set of tuples \vec{a} such that $\vec{a} \in \text{Ans}(\mathfrak{D}', q)$ for each repair \mathfrak{D}' of \mathfrak{D} w.r.t. C . That is, we evaluate the query q in each repair \mathfrak{D}' of \mathfrak{D} , and keep the answers that prevail in all of them. For Boolean queries (i.e., sentences) q computing the consistent answers of q is equivalent to determining if $\mathfrak{D}' \models q$ for every repair \mathfrak{D}' . Hence, $CQA(q, \mathfrak{D}, C)$ contains \top (resp. \perp) if $\mathfrak{D}' \models q$ (resp. $\mathfrak{D}' \not\models q$) for all repairs \mathfrak{D}' of \mathfrak{D} . Consistent query answering has been analysed for different data models, different repair semantics, and different types of integrity constraints, generally for those where the repair problem has been thoroughly studied.

Repairs can be interpreted as database instances that eliminate the inconsistency of the original database since all the constraints that were violated in the first place are now satisfied in the repair instance. One could relax this notion and simply look for a “reduction” of the inconsistency to some acceptable level, rather than eliminating the inconsistency altogether, giving way to the notion of *inconsistency-tolerant repairs*. In this modified setting, it is sufficient to find a new instance that might eliminate some, but not all, of the violations, while not introducing any new unforeseen violations of the constraints. To do this, one needs to formalise a way of measuring inconsistency, which can be done by defining *inconsistency measures*: These are usually functions that take values in \mathbb{R} and satisfy a set of desired postulates, which in most cases vary according to the semantics chosen and the structures to which they are applied. This notion has been studied not only for repairs in classical database settings, but also for query answering over inconsistent knowledge bases and ontologies [7, 19, 20, 28]

It is also possible to consider a measure of inconsistency in a semiring setting. Although a standard definition would take values in $\mathbb{R}_{\geq 0}$, we consider a more general one that measures inconsistency by taking values in a semiring.

Definition 2.6. Given a set of ICs C and an instance \mathfrak{D} , an *inconsistency measure* (IM) \mathcal{M} is a function that maps (C, \mathfrak{D}) to a non-negative value in a semiring K .

Inconsistency measures are often expected to satisfy some postulates describing how an inconsistency measure should behave. Most importantly, we assume that the *consistency postulate* “ $\mathfrak{D} \models C$ implies $\mathcal{M}(C, \mathfrak{D}) = 0$ ” holds.

In general, a repair concept can be defined by using a methodology that computes a distance between any two database instances, and using another methodology to determine how inconsistent different databases are with respect to a set of integrity constraints. In the next section, we introduce an abstract approach to defining database repair notions for K -databases, using logics as the basis of these methods.

3 UNIFIED FRAMEWORK FOR REPAIRS

There is always a cost associated with repairing a database. This cost could be measured in terms of the number of records that need to be changed to achieve consistency; some facts may be more costly to change than others, while other facts may always need to be left untouched. In some cases, inconsistency in the resulting data may be more desirable than facing the cost of repairing to an inconsistency-intolerant state. In any case, there is a need for diverse repair notions for different applications.

Inconsistency measures are usually defined in terms of the integrity constraints of a database, but sometimes some of the constraints imposed are more flexible than others. To allow for this distinction, we split the ICs into two parts: one consisting of those ICs that *must* be satisfied (*hard-constraints* C_h), and another to encompass the constraints for which some degree of inconsistency is allowed (*soft-constraints* C_s). Hard-constraints represent those properties usually referred to as “integrity constraints”.

We propose a fine-grained repair framework that allows the use of both hard-constraints and soft-constraints, and incorporates so-called *hard-queries* and *soft-queries*. Hard-queries (Q_h) are used to specify the space of potential repairs (such as subsets of relations in subset repairs), while soft-queries (Q_s) are used to specify the minimality criteria (such as the cardinality of the symmetric difference between the original database and the repair candidate). We start with two simple examples, before elaborating on the motivation behind the remaining components of the repair framework.

Example 3.1. Consider a finite simple undirected graph $G = (V^G, E^G)$ representing a railway network. Each node of the graph represents a station and each edge represents an existing direct rail link between stations. The effect of setting

$$C_h := \{\text{“maximum degree of the graph is at most 2”}\}$$

as hard constraints, and setting the hard queries Q_h as

$$\{\text{“there is a path of length at most 3 between } a \text{ and } b \text{”} \mid a, b \in V^G\}$$

is that the space of repairs consists of those graphs $H = (V^H, E^H)$ that represent networks with stations having at most 2 direct connections (from C_h), and such that every pair of stations at distance at most 3 in the original network remains connected with distance at most 3 in the repair (from Q_h). These constraints can be easily expressed in navigational logics for graphs (e.g., *ReGXPath*) or in FO. Note that C_h contains the properties that must hold in the repair and may not hold in the original database, while Q_h lists properties whose satisfaction is transferred from the original to the repair. If $Q_s = \{E(x, y)\}$, the distance used to determine the repair H is

obtained by minimising the cardinality of the symmetric difference

$$\{E(a, b) \mid G \models E(a, b), a, b \in V^G\} \\ \oplus \{E(a, b) \mid H \models E(a, b), a, b \in V^H\}.$$

Example 3.2. Consider a students' database, containing students' ID number, name and nationality in one table, and courses in which each student is currently enrolled in another table:

Stud(StudentID, Name, Nationality), Reg(StudentID, Course).

The database has some inconsistencies caused by merging smaller databases from different campuses. We would like to obtain a repair in such a way that the number of students will remain as close to the original number as possible. This may result in some students being reassigned or removed from some courses. The *soft-queries* determine the minimality concept, which in this case is based on the total number of students in each instance:

$Q_s = \{\text{"What is the number of distinct students in the database?"}\}$

In previous years each student was enrolled on at least 2 courses and we want to maintain this. We do not want to achieve consistency by removing students from "too many" courses. So the condition is added to the *hard-queries* describing the properties that remain in the repair:

$Q_h = \{\text{"A student } x \text{ is enrolled in at least 2 courses."}\}$

Finally, for consistency, we impose a hard-constraint that the student ID number is unique for each student.

$C_h = \{\text{"StudentID is a key of Stud table."}\}$

Hard-Queries. Hard-queries yield a core set of answers that we want to preserve in a repair. For any Boolean query $\phi \in Q_h$, if \mathcal{D}' is a repair of \mathcal{D} , we want $\mathcal{D} \models \phi$ to imply $\mathcal{D}' \models \phi$. Similarly, for non-Boolean queries, we want the answers to a hard-query in \mathcal{D} to be retrieved in \mathcal{D}' , so $\mathcal{D} \models \phi(\vec{a}/\vec{x})$ implies $\mathcal{D}' \models \phi(\vec{a}/\vec{x})$, for any suitable \vec{a} . Formally (in the setting of Boolean annotations), given an instance \mathcal{D} and a query ϕ , we require $\text{Ans}(\mathcal{D}, \phi) \subseteq \text{Ans}(\mathcal{D}', \phi)$ for each query $\phi \in Q_h$.

If the annotations are not Boolean, the above notion should be generalised to reflect the annotations. For every $\phi \in Q_h$ and $\vec{a} \in \text{DOM}^n$, we require that $w_{\mathcal{D}, \phi}(\vec{a}) \leq w_{\mathcal{D}', \phi}(\vec{a})$. For example, if annotations reflect multiplicities in a multiset, this means that the corresponding multiplicities can only increase in repairs.

Example 3.3. Consider the K -database \mathcal{D} as in Example 2.5, such that every tuple \vec{t} in \mathcal{D} has weight 1. Set the hard-queries as $Q_h = \{\exists y T(x, y)\}$. The query answers in \mathcal{D} are the values in $\{t_1, t_2, t_3\}$ that appear in the first coordinate of the relation T , as many times as they appear in the first coordinate. More precisely, we get the multiset $\{\{t_1, t_2, t_3, t_2\}\}$. Then, we have that $w_{\mathcal{D}, \phi}(\vec{t}_1) = w_{\mathcal{D}, \phi}(\vec{t}_3) = 1$, and $w_{\mathcal{D}, \phi}(\vec{t}_2) = 2$.

In the following, we stipulate that distances are always pseudo-metrics (i.e., symmetric functions that satisfy the triangle inequality).

Soft-Queries. Soft-queries Q_s reflect query answers which are deemed important, but not necessary to maintain. They define a distance d_{Q_s} between database instances according to some distance between answers to queries in Q_s . To simplify the presentation, we will define the notion using Boolean queries, but will later extend this to formulae as well. Let σ be a symmetric aggregate function that takes values in $K_{\geq 0}$ that will combine all the values assigned to sentences in Q_s into a single value. Finally, we consider $\Delta: K \times K \rightarrow K$ to be some function that computes a distance between any two semiring values. We define a distance between instances in terms of Q_s as

$$d_{Q_s}(\mathcal{D}, \mathcal{D}') := \sigma\{\{\Delta(\llbracket \phi \rrbracket_{\mathcal{D}}, \llbracket \phi \rrbracket_{\mathcal{D}'}) \mid \phi \in Q_s\}\}.$$

Soft-Constraints. The soft-constraints, modelled using sentences, are used to define an inconsistency measure \mathcal{M} that will allow to obtain degrees of tolerance in the repair. Let $f_{sc}: \mathcal{D} \times \mathcal{L} \rightarrow K_{\geq 0}$ be a function, and let σ be an aggregate function taking values in $K_{\geq 0}$. The function σ combines all the values assigned via f_{sc} to C_s into a single value. The value $f_{sc}(\mathcal{D}, \phi)$ indicates how inconsistent \mathcal{D} is according to ϕ , e.g., how far the property defined by ϕ is of being true in \mathcal{D} . We define an inconsistency measure in terms of C_s as $\mathcal{M}(\mathcal{D}, C_s) := \sigma\{\{f_{sc}(\mathcal{D}, \phi) \mid \phi \in C_s\}\}$.

In the following we give an example where σ is the aggregate sum defined by the $+$ of the semiring of natural numbers. We give two examples of the function f_{sc} , which depicts how inconsistent a sentence ϕ is with respect to a database \mathcal{D} . In the first, we use the truth value of a negated formula $\neg\phi$ as a measure of the inconsistency of ϕ . In the latter, we use the semiring value $\llbracket \neg\phi \rrbracket_{\mathcal{D}}$ directly.

Example 3.4. Consider the K -database \mathcal{D}_1 as in Example 2.5, such that each tuple that has t_i is annotated with weight i , for $i \in \{1, 2, 3\}$. Define the following constraints:

$$C_h = \{\forall y (C(y) \leftrightarrow \exists x T(x, y))\}, \\ C_s = \{\exists^{\leq 2} y T(x, y) \mid x \in \{t_1, t_2, t_3\}\},$$

and write ϕ_i for $\exists^{\leq 2} y T(t_i, y)$. We can define

$$\mathcal{M}(\mathcal{D}_1, C_s) := \sum \left\{ \left\{ \llbracket \neg\phi_i \rrbracket_{\mathcal{D}_1}^B \mid \phi_i \in C_s \right\} \right\} = 0 + 1 + 0 = 1.$$

Another possibility that considers the annotations of each tuple is

$$\mathcal{M}(\mathcal{D}_1, C_s) := \sum \left\{ \left\{ \llbracket \exists^{\geq 3} y T(t_i, y) \rrbracket_{\mathcal{D}_1} \mid i \in \{1, 2, 3\} \right\} \right\} \\ = 0 + 12 + 0 = 12.$$

We now formally define a fine-grained repair framework that incorporates all the concepts discussed previously.

Definition 3.5 (repair framework). Fix a database schema \mathcal{S} and a logic \mathcal{L} over the schema. Fix an inconsistency measure \mathcal{M} and a distance function d_{Q_s} that are defined in terms of \mathcal{L} -sentences as described above. A *repair framework* $\mathcal{R} = (C_h, C_s, Q_h, Q_s, \mathcal{M}, d_{Q_s})$ is a tuple, where C_h and C_s are finite sets of \mathcal{L} -sentences representing *hard* and *soft-constraints*, respectively, and Q_h and Q_s are finite sets of \mathcal{L} -formulae representing *hard* and *soft-queries*, respectively. We require C_h to be consistent.

Given a database \mathfrak{D} and a repair framework, we define the following relativised sets of \mathcal{L} -sentences

$$\begin{aligned} \mathcal{Q}_h^{\mathfrak{D}} &:= \{\varphi(\vec{a}/\vec{x}) \mid \varphi(\vec{x}) \in \mathcal{Q}_h, \vec{a} \subseteq \text{ADOM}(\mathfrak{D}) \text{ of suitable type}\}, \\ \mathcal{Q}_s^{\mathfrak{D}} &:= \{\varphi(\vec{a}/\vec{x}) \mid \varphi(\vec{x}) \in \mathcal{Q}_s, \vec{a} \subseteq \text{ADOM}(\mathfrak{D}) \text{ of suitable type}\}. \end{aligned}$$

This shift from sets of formulae to sets of sentences is not crucial but it does make the presentation of the following definition slightly lighter. Note that if \vec{b} contains an element that is not in the active domain of \mathfrak{D}' then the interpretations of atoms $R(\vec{b})$ (and their negations) are computed as if the elements belonged to the active domain of \mathfrak{D}' . That is,

$$\llbracket R(\vec{b}) \rrbracket_{\mathfrak{D}'} = \llbracket R(\vec{b}) \rrbracket_{\mathfrak{D}}^B = 0, \quad \llbracket \neg R(\vec{b}) \rrbracket_{\mathfrak{D}'} = \llbracket \neg R(\vec{b}) \rrbracket_{\mathfrak{D}}^B = 1.$$

REMARK 1. Let K be a semiring where the modulus $|a - b|$ has a canonical interpretation for all $a, b \in K$. When we consider repairs over K -databases, we write $(C_h, C_s, \mathcal{Q}_h, \mathcal{Q}_s)$ to denote the repair framework, where the inconsistency measure \mathcal{M} is defined as in Example 3.4 (annotation aware variant), and the distance between databases is defined using the modulus $|a - b|$ and the aggregate sum of the semiring as follows

$$d_{\mathcal{Q}_s}(\mathfrak{D}, \mathfrak{D}') := \sum \left\{ \left| \llbracket \phi \rrbracket_{\mathfrak{D}} - \llbracket \phi \rrbracket_{\mathfrak{D}'} \right| \mid \phi \in \mathcal{Q}_s^{\mathfrak{D}} \right\}.$$

Finally, an annotation unaware $(C_h, C_s, \mathcal{Q}_h, \mathcal{Q}_s)$ is obtained when all references to $\llbracket \phi \rrbracket_{\mathfrak{D}}$ are replaced with $\llbracket \phi \rrbracket_{\mathfrak{D}}^B$.

Definition 3.6 (\mathcal{R} -repair). Given $\mathcal{R} = (C_h, C_s, \mathcal{Q}_h, \mathcal{Q}_s, \mathcal{M}, d_{\mathcal{Q}_s})$ a repair framework, a K -database \mathfrak{D} , and a threshold $\epsilon \geq 0$, we say that \mathfrak{D}' is an ϵ - \mathcal{R} -repair of \mathfrak{D} if

- (1) $\text{ADOM}(\mathfrak{D}') \subseteq \text{ADOM}(\mathfrak{D})$,
- (2) $\mathfrak{D}' \models C_h$,
- (3) $\llbracket \phi \rrbracket_{\mathfrak{D}} \leq \llbracket \phi \rrbracket_{\mathfrak{D}'}$, for all $\phi \in \mathcal{Q}_h^{\mathfrak{D}}$,
- (4) $\mathcal{M}(\mathfrak{D}', C_s) \leq \epsilon$,
- (5) \mathfrak{D}' is minimal with respect to $\leq_{d_{\mathcal{Q}_s}, \mathfrak{D}}$.

The instance \mathfrak{D}' is an *annotation unaware repair* if instead of (3), we require that $\llbracket \phi \rrbracket_{\mathfrak{D}}^B \leq \llbracket \phi \rrbracket_{\mathfrak{D}'}$, for every $\phi \in \mathcal{Q}_h^{\mathfrak{D}}$. Note that, if $\epsilon > 0$, the above notions are meaningful, even if C_s is inconsistent. Finally, we drop the ϵ from ϵ - \mathcal{R} -repair, if $\epsilon = 0$ or $C_s = \emptyset$.

The framework facilitates the creation of diverse repair notions. For instance, by using (3) it is straightforward to specify a repair notion which is a subset repair with respect to some relation R (put $R(\vec{x})$ in \mathcal{Q}_h), a superset repair with respect to some other relation S (put $\neg S(\vec{x})$ in \mathcal{Q}_h), and where the interpretation of a third relation T must remain unchanged (put both $T(\vec{x})$ and $\neg T(\vec{x})$ in \mathcal{Q}_h). The notions of minimality facilitated by (5) are also diverse. The definition given by $d_{\mathcal{Q}_s}$ is in a sense 1-dimensional, as it aggregates distances between interpretations of formulae in \mathcal{Q}_s into a single semiring value. It would not be difficult to define an even more general notion by using the semiring values of the formulae in \mathcal{Q}_s directly as $|\mathcal{Q}_s|$ -tuples instead of multisets and without aggregation; this would lead to a distance which is $|\mathcal{Q}_s|$ -dimensional. Here we focus on the simpler 1-dimensional case. Finally, in (1) we chose to limit the active domains of repairs. With this restriction, it is possible to use more expressive logics in the different parts of the framework without increasing the computational complexity too much; see Section 5.3 for our upper bounds. Confer [26, Thm 7.2],

where a very simple instance of CQA is shown undecidable. Note that any inconsistent database instance can be provided with sets of fresh data values, which can then be used as fresh data values for the repairs without affecting our complexity results.

If $C_s = \emptyset$ or $\epsilon = 0$, Definition 3.6 yields a classical definition of a repair, where the desired minimality and repair criteria is defined through \mathcal{Q}_h and \mathcal{Q}_s . If instead $0 < \epsilon \leq \mathcal{M}(C_s, \mathfrak{D})$, it resembles the definition of inconsistency-tolerant repair given in [7]. For instance, \mathcal{R}' of Example 3.8 (below) represents the standard superset cardinality repair.

Some properties are expected when dealing with repairs, for example, a consistent \mathfrak{D} should not need to be repaired. Indeed, if \mathfrak{D} satisfies C_h and C_s , then in particular $\mathcal{M}(C_s, \mathfrak{D}) = 0$ and it follows from the $\leq_{d_{\mathcal{Q}_s}, \mathfrak{D}}$ -minimality of \mathfrak{D} that \mathfrak{D} is a repair. It is often desirable that any \mathfrak{D} can always be repaired. However, our framework can express both ICs and critical properties of databases that should be kept unchanged (expressed using \mathcal{Q}_h). Assuming that the set of ICs is consistent, there will always be some \mathfrak{D}' which satisfies the ICs and thus $\mathfrak{D}' \models C_h$ and $\mathcal{M}(C_s, \mathfrak{D}') = 0$. However, this is not sufficient to ensure that $\text{Ans}(\mathfrak{D}, \mathcal{Q}_h) \subseteq \text{Ans}(\mathfrak{D}', \mathcal{Q}_h)$. Furthermore, if we want to find an inconsistency-tolerant repair and only assume C_h to be consistent, this is not sufficient to ensure that $\mathcal{M}(C_s, \mathfrak{D}') \leq \epsilon$ for an instance \mathfrak{D}' that satisfies C_h . Hence, deciding the *existence of a repair* turns out to be a meaningful problem in our framework. Next, we give some examples of how to use the repair framework.

Example 3.7 (*Example 3.2 cont.*). The hard-constraints set C_h contains the formula:

$$\forall x \forall y \forall z \forall s \forall t (\text{Student}(x, y, z) \wedge \text{Student}(x, s, t) \rightarrow (y = s \wedge z = t)).$$

We set the hard-queries by

$$\mathcal{Q}_h := \{\exists yz (\text{Courses}(x, y) \wedge \text{Courses}(x, z) \wedge y \neq z)\},$$

where the range of the first attribute of the Courses table lists all possible data values for the student ID number. Finally, the soft-queries can be defined as

$$\mathcal{Q}_s := \{\text{Count}_{\text{id}}\},$$

where Count_{id} is an aggregate function that counts the number of different student IDs in the Student table. We use this to define a distance between instances via

$$d_{\mathcal{Q}_s}(\mathfrak{D}, \mathfrak{D}') := \left| \llbracket \text{Count}_{\text{id}} \rrbracket_{\mathfrak{D}} - \llbracket \text{Count}_{\text{id}} \rrbracket_{\mathfrak{D}'} \right|.$$

A similar minimality concept can be obtained by using formulae of first-order logic over the semiring of natural numbers by setting

$$\mathcal{Q}_s := \{\exists y \exists z \text{Student}(x, y, z)\}$$

and setting $d_{\mathcal{Q}_s}(\mathfrak{D}, \mathfrak{D}')$ to be the annotation aware distance defined in Remark 1. Here, the repair minimises the cardinality of the symmetric difference between the student IDs that appear in the original database and its repair.

Example 3.8 (*Example 2.5 cont.*). Consider the schema of Example 2.5, where the instances contain all teaching allocations of a semester for a department. The database schema determines the sets T_{ID} and C_{ID} of possible data values for the attributes *Teacher* and *Course*. Now, the relation $C(a)$ is true if there is a course named a in

the syllabus, and $T(a, b)$ indicates that teacher a has been assigned to lecture course b this semester.

Consider the following collections of constraints:

$$\begin{aligned} C_h &:= \{\forall y(C(y) \rightarrow \exists x T(x, y))\}, & C_s &:= \{\exists^{\leq 2} y T(x, y)\}, \\ Q_h &:= \{C(y), \neg C(y)\}, & Q'_h &:= \{C(y), T(x, y)\}, \\ Q_s &:= \{T(x, y)\}, & Q'_s &:= \{C(y), T(x, y)\}. \end{aligned}$$

If we consider the annotation unaware $\mathcal{R} = (C_h, C_s, Q_h, Q_s)$, we obtain a teaching allocation repair (only T may be modified) that minimises the symmetric difference for the table $T(x, y)$. The ICs stipulate that each course must be assigned a lecturer and that, up to a pre-defined threshold, each lecturer may teach in a maximum of two courses. The hard query Q_h dictates that no changes may be made to the $C(y)$ table, whereas Q_s leads to minimising the symmetric difference for the $T(x, y)$ table in a repair.

If instead, we have annotation unaware $\mathcal{R}' = (C_h, C_s, Q'_h, Q'_s)$, then this framework represents the standard superset cardinality repair. We get the *subset cardinality* repair by replacing $C(y)$ and $T(x, y)$ with $\neg C(y)$ and $\neg T(x, y)$ in Q'_h .

Finally, if we set

$$Q''_h := \{T(x, y), \neg T(x, y)\} \cup \{\exists y C(y), \exists y \neg C(y)\},$$

and the annotation unaware repair framework is over the semiring of natural numbers, we obtain an *attribute-based* repair. Note that the effect of Q''_h is that we cannot delete or insert tuples in the relation T and the cardinality of C remains the same; in other words, in this repair notion, deletions and insertions of whole tuples are not permitted, only the modification of values for the table C .

4 ALTERNATIVE REPAIR NOTIONS

In the previous section, we saw how standard repair semantics (i.e., subset, superset) can be modelled in the repair framework. We now show examples of other repair concepts that can be modelled using this approach.

Example 4.1 (Cont. of Example 2.5). Consider an annotation unaware repair framework $(C_h, C_s, Q_h, Q_s, \mathcal{M}, d_{Q_s})$, where

$$\begin{aligned} C_h &:= \{\forall y(C(y) \rightarrow \exists x T(x, y)), \neg T(t_4, c), \neg C(a)\}, \\ C_s &:= \{\}, \\ Q_h &:= \{T(t_1, c), T(t_2, d), C(b), C(c), C(d)\}, \\ Q_s &:= \{\phi_i = \forall x \exists^{\leq i} y(C(y) \wedge T(x, y)) \mid 1 \leq i \leq 10\}. \end{aligned}$$

The sentence ϕ_i expresses that every teacher is assigned to at most $1 \leq i \leq 10$ courses; so 10 is the maximum teaching load. From Q_s , we define a distance between instances to describe a minimality concept that is neither set-based nor cardinality-based:

$$d_{Q_s}(\mathcal{D}, \mathcal{D}') := \sum_{\phi_i \in Q_s} \Delta(\llbracket \phi_i \rrbracket_{\mathcal{D}}^B, \llbracket \phi_i \rrbracket_{\mathcal{D}'}^B),$$

where $\Delta(x_1, x_2) := |x_1 - x_2|$. The distance prioritises those instances that have a similar maximum allocation per teacher.

Consider a database instance \mathcal{D} , defined as follows:

$$\begin{aligned} \mathcal{D} &:= \{T(t_1, c), T(t_2, d), T(t_1, b), T(t_4, c), \\ &\quad C(a), C(b), C(c), C(d), C(e)\}. \end{aligned}$$

For instance, $\llbracket \phi_i \rrbracket_{\mathcal{D}}^B = 1$ for every $i \geq 2$, and $\llbracket \phi_i \rrbracket_{\mathcal{D}}^B = 0$ for $i = 1$. Hence,

$$\mathcal{D}' = \{T(t_1, c), T(t_2, d), T(t_1, b), T(t_4, e), C(b), C(c), C(d), C(e)\}$$

is a repair that satisfies that every course in $C(y)$ has at least one teacher assigned, the facts $T(t_4, c)$ and $C(a)$ are no longer in the database, and prioritises the criteria that maximum allocation per teacher is as similar as possible as in \mathcal{D} ; thus it is a minimal repair. The framework allows us to express prioritised repairs in terms of formulae, which differs from the approach of using predefined priority criteria studied in the repair literature.

We will next give an example of a repair framework in a graph database. For simplicity, we consider simple labelled directed graphs.

Example 4.2. Consider graph databases that are first-order structures of vocabulary $\{E, P_1, P_2\}$, where E is a binary relation symbol, and P_1 and P_2 are unary. Let $(C_h, C_s, Q_h, Q_s, \mathcal{M}, \leq_{d_{Q_s}})$ be a repair framework over the semiring of natural numbers, where C_h specifies some ICs, $C_s := \emptyset$, and

$$Q_h := \{\psi_i(\vec{x}_i) \mid 1 \leq i \leq 10\} \cup \{P_1(x), \neg P_2(x)\},$$

where $\psi_i(\vec{x}_i)$ expresses that $\vec{x}_i = (x_0, \dots, x_i)$ induces a cycle of length $1 \leq i \leq 10$, which can be expressed as

$$\psi_i(\vec{x}_i) := x_0 = x_i \wedge \bigwedge_{\substack{0 \leq j \leq i \\ 0 \leq k < i \\ j \neq k}} x_j \neq x_k \wedge \bigwedge_{0 \leq j < i} E(x_j, x_{j+1}).$$

Finally, we set $Q_s := \{\exists x(x = x)\}$. The distance $\leq_{d_{Q_s}}$ is the annotation aware distance defined in Remark 1. Given a graph database G , the space of repairs of G described by C_h and Q_h are those labelled graphs G' that satisfy the ICs in C_h , include all vertices for which either P_1 or $\neg P_2$ in G with those labels intact, and include every short cycle of G with possibly different labels. The minimal elements of $\leq_{d_{Q_s}, G}$ are those G' which are closest to G in cardinality.

5 ANNOTATION UNAWARE CASE

Following the definitions and conventions of Definition 3.6 and Remark 1, from now on we will focus on annotation unaware repairs of annotation unaware repair frameworks (C_h, C_s, Q_h, Q_s) using the semiring of natural numbers. Hence, we essentially consider set-based databases (that is \mathbb{B} -databases) that are encoded as \mathbb{N} -databases to obtain richer repair frameworks.

Next, we summarise our assumptions. We consider repair frameworks $(C_h, C_s, Q_h, Q_s, \mathcal{M}, d_{Q_s})$, where C_h and C_s are finite sets of first-order sentences of which C_h is assumed to be consistent, Q_h, Q_s are finite sets of first-order formulae, the inconsistency measure \mathcal{M} is defined as

$$\mathcal{M}(\mathcal{D}, C_s) := \sum \left\{ \left\{ \llbracket \neg \phi \rrbracket_{\mathcal{D}}^B \mid \phi \in C_s \right\} \right\},$$

and the distance between databases d_{Q_s} is defined as

$$d_{Q_s}(\mathcal{D}, \mathcal{D}') := \sum \left\{ \left\{ \left| \llbracket \phi \rrbracket_{\mathcal{D}}^B - \llbracket \phi \rrbracket_{\mathcal{D}'}^B \right| \mid \phi \in Q_s^{\mathcal{D}} \right\} \right\}.$$

Recall that, for a database \mathcal{D} ,

$$\begin{aligned} Q_h^{\mathcal{D}} &:= \{\varphi(\vec{a}/\vec{x}) \mid \varphi(\vec{x}) \in Q_h, \vec{a} \subseteq \text{ADOM}(\mathcal{D}) \text{ of suitable type}\}, \\ Q_s^{\mathcal{D}} &:= \{\varphi(\vec{a}/\vec{x}) \mid \varphi(\vec{x}) \in Q_s, \vec{a} \subseteq \text{ADOM}(\mathcal{D}) \text{ of suitable type}\}, \end{aligned}$$

and that if \vec{b} has an element outside of the active domain of a database \mathcal{D}' then

$$\llbracket R(\vec{b}) \rrbracket_{\mathcal{D}'}^B = 0, \text{ and } \llbracket \neg R(\vec{b}) \rrbracket_{\mathcal{D}'}^B = 1.$$

We consider annotation-unaware ϵ - \mathcal{R} repairs. That is, a database \mathcal{D}' is a repair of \mathcal{D} if

- (1) $\text{ADOM}(\mathcal{D}') \subseteq \text{ADOM}(\mathcal{D})$,
- (2) $\mathcal{D}' \models C_h$,
- (3) $\llbracket \phi \rrbracket_{\mathcal{D}}^B \leq \llbracket \phi \rrbracket_{\mathcal{D}'}^B$, for all $\phi \in \mathcal{Q}_h^{\mathcal{D}}$,
- (4) $M(\mathcal{D}', C_s) \leq \epsilon$,
- (5) \mathcal{D}' is minimal with respect to $\leq_{d_{Q_s}, \mathcal{D}}$.

We consider (set-based) relational databases that are treated as \mathbb{N} -databases.

5.1 Classical results on complexity of repair

In the literature, the complexity of database repairs is often characterised for integrity constraints specified in different fragments of tuple-generating dependencies. Queries used for consistent query answering are often conjunctive queries. Next, we define the fragments of first-order logic of interest.

We write ATOMS for the sets of *atomic formulae*, that is, those that are of the form $R(\vec{x})$, where R is a relation and \vec{x} is a tuple of variables. We write LIT for the set of *literals*, that is, the set of atomic formulae and their negations. A *tuple-generating dependency* (*tgd*) is a first-order sentence of the form

$$\forall \vec{x}(\varphi(\vec{x}) \rightarrow \exists \vec{y}\psi(\vec{x}, \vec{y})),$$

where φ, ψ are conjunctions of atomic formulas, $\vec{x} = (x_1, \dots, x_n)$ and $\vec{y} = (y_1, \dots, y_m)$ are tuples of variables, and every universally quantified variable x_i occurs in φ .

A *local-as-view* (LAV) *tgd* is a *tgd* in which φ is a single atomic formula. A *global-as-view* (GAV) *tgd* is a *tgd*

$$\forall \vec{x}(\varphi(\vec{x}) \rightarrow \psi(\vec{x}'))$$

in which ψ is a single atomic formula such that the variables in \vec{x}' are among the variables of \vec{x} .

A conjunctive query is a formula of first-order logic of the form

$$\exists x_1 \dots \exists x_n (\phi_1 \wedge \dots \wedge \phi_m),$$

where each ϕ_i is an atomic formula. We write COQ for the set of conjunctive queries.

Next, we show in a running example the use of the repair framework in relation to these first-order fragments.

Example 5.1 (Cont. of Example 2.5). Consider the following collections of constraints:

$$\begin{aligned} C_h &:= \{\forall y(C(y) \rightarrow \exists x T(x, y))\}, \\ C_s &:= \{\forall x y_1 y_2 ((T(x, y_1) \wedge T(x, y_2)) \rightarrow x = y)\}. \end{aligned}$$

The hard constraints C_h are as in Example 2.5, that is, they require that every course is taught by (at least) one teacher. If we consider the annotation aware inconsistency measure of Example 3.4, the soft constraints C_s enforce that up to some threshold of error, teachers teach in only one course. The inconsistency measure is computed

as follows:

$$\begin{aligned} M(\mathcal{D}, C_s) &:= \llbracket \neg \forall x y_1 y_2 ((T(x, y_1) \wedge T(x, y_2)) \rightarrow y_1 = y_2) \rrbracket_{\mathcal{D}} \\ &= \llbracket \exists x y_1 y_2 ((T(x, y_1) \wedge T(x, y_2)) \wedge x \neq y) \rrbracket_{\mathcal{D}} \\ &= \sum_{\substack{a, b, c \in D \\ b \neq c}} (T^{\mathcal{D}}(a, b) \times T^{\mathcal{D}}(a, c)). \end{aligned}$$

Here C_h is a LAV and C_s is a GAV *tgds*.

In the following, we are interested in a list of computational problems:

- (1) Checking the existence of a repair.
- (2) Computing a repair if one exists.
- (3) Checking whether a tuple is a consistent query answer.

These problems are formally defined below:

Definition 5.2. Let \mathcal{R} be a repair framework and q a k -ary query. We define the following two decision problems:

Problem: Consistent query answering (\mathcal{R} -CQA(q))

Instance: Database \mathcal{D} , a tuple $\vec{t} \in \text{ADOM}(\mathcal{D})^*$

Question: Is $\vec{t} \in \text{Ans}(\mathcal{D}', q)$ for every \mathcal{R} -repair of \mathcal{D} ?

Problem: Existence of repair ($\exists \mathcal{R}$ -repair)

Instance: Database \mathcal{D}

Question: Does \mathcal{D} have an \mathcal{R} -repair?

and the following function problem:

Problem: Repair computing (\mathcal{F} - \mathcal{R} -repair)

Instance: Database \mathcal{D}

Output: An \mathcal{R} -Repair \mathcal{D}' of \mathcal{D} .

If \mathcal{R} is replaced with a classical repair notion in the definitions above, we obtain the usual classical decision and function problems.

In 2012, ten Cate et al. [25] presented a thorough study on the data complexity of CQA and repair checking problems for set-based repairs. As our study deals with so-called cardinality-based repairs, their results are not directly applicable. Our results generalise cardinality-based variants of these repair notions.

5.2 Complexity of simple repair notions

For simplicity, we focus on notions where $C_s = \emptyset$.

PROPOSITION 5.3. *Let $\mathcal{R} = (\text{GAV}, \emptyset, \text{LIT}, \text{ATOMS})$ be a repair notion. Then \mathcal{F} - \mathcal{R} -repair is FNP-hard and included in $\text{F}\Sigma_2^P$.*

PROOF. We reduce an instance of the problem \mathcal{F} - \mathcal{R} -repair for $\mathcal{R} = (\text{GAV}, \emptyset, \text{LIT}, \text{ATOMS})$ from the functional problem MAXCLIQUE of finding a maximum clique, which is FNP-complete [15]. For that purpose, we define:

$$\begin{aligned} C_h &:= \{\forall x \forall y ((C(x) \wedge C(y) \wedge D(x, y)) \rightarrow E(x, y))\}, \\ Q_h &:= \{E(x, y), \neg E(x, y), D(x, y), \neg D(x, y)\}, \\ Q_s &:= \{C(x)\}. \end{aligned}$$

Let $G = (V, E)$ be a graph. We define the instance \mathcal{D} as follows:

$$\begin{aligned} E^{\mathcal{D}} &:= \{(x, y) \mid (x, y) \in E(G)\}, & C^{\mathcal{D}} &:= \{x \mid x \in V(G)\}, \\ D^{\mathcal{D}} &:= \{(x, y) \mid x \neq y \text{ and } x, y \in V(G)\}. \end{aligned}$$

That is, we encode the graph via the binary relation $E(x, y)$. Additionally, two relations are defined: $C(x)$ contains all vertices, and $D(x, y)$ represents inequality between vertices.

Let $V' \subseteq V$ be a maximum clique of G . Then \mathcal{D}' defined as

$$E^{\mathcal{D}'} := E^{\mathcal{D}}, \quad C^{\mathcal{D}'} := V', \quad D^{\mathcal{D}'} := D^{\mathcal{D}}$$

is a repair of \mathcal{D} . The hard constraint is obviously satisfied, because V' is a clique, and there is no other repair with a smaller d_{Q_s} -distance because finding one would imply finding a clique larger than V' .

Now, let \mathcal{D}' be a repair of \mathcal{D} . It follows from the hard constraint that the elements in $C^{\mathcal{D}'}$ are a clique of G . Because \mathcal{D}' has the minimal distance from \mathcal{D} with respect to the soft queries, it follows immediately that $C^{\mathcal{D}'}$ must be of maximal size. Therefore, $V' = C^{\mathcal{D}'}$ is a maximum clique of G .

As for the upper bound, note that membership in $F\Sigma_2^P$ (the function variant of $\Sigma_2^P = \text{NP}^{\text{NP}}$) is trivial: First, a repair candidate is guessed nondeterministically; the repair conditions can be checked in polynomial time, and minimality can be determined with a coNP oracle call. \square

PROPOSITION 5.4. *Let $\mathcal{R} = (\text{LAV}, \emptyset, \text{LIT}, \text{ATOMS})$. Then $F\text{-}\mathcal{R}$ -repair is FNP-hard and included in $F\Sigma_2^P$.*

PROOF. The upper bound follows as in Proposition 5.3. We show a reduction from **MINDOMINATING-SET**, which asks for a minimum dominating set of a graph. This problem is FNP-complete [14, 15]. We specify the components as follows:

$$\begin{aligned} C_h &:= \{\forall x V(x) \rightarrow \exists y (S(y) \wedge A(x, y))\}, \\ Q_h &:= \{V(x), \neg V(x), A(x, y), \neg A(x, y)\}, \\ Q_s &:= \{S(x)\}. \end{aligned}$$

Let $G = (V, E)$ be a graph. We define the instance \mathcal{D} as follows:

$$\begin{aligned} A^{\mathcal{D}} &:= \{(x, y) \mid (x, y) \in E(G) \text{ or } x = y\}, \\ V^{\mathcal{D}} &:= \{x \mid x \in V(G)\}, \\ S^{\mathcal{D}} &:= \{\}. \end{aligned}$$

That is, A encodes the structure of the graph and adds self-loops. The relation V simply contains all vertices of G , and S will contain

Let $V' \subseteq V$ be a minimum dominating set of G . Notice that \mathcal{D}' defined by

$$A^{\mathcal{D}'} := A^{\mathcal{D}}, \quad V^{\mathcal{D}'} := V^{\mathcal{D}}, \quad S^{\mathcal{D}'} := V'$$

is a repair of \mathcal{D} . Clearly, the hard constraint is satisfied given that V' is a dominating set. Minimum distance to \mathcal{D} follows directly from V' being a minimum dominating set.

Next, let \mathcal{D}' be a repair of \mathcal{D} . Because of the hard constraints, $S^{\mathcal{D}'}$ has to contain a dominating set of G . Moreover, since a repair has minimum d_{Q_s} -distance to the original database \mathcal{D} , $S^{\mathcal{D}'}$ must be a minimum dominating set. \square

REMARK 2. *For $\mathcal{R} = (\text{GAV}, \emptyset, \text{LIT}, \text{ATOMS})$, the existence of a conjunctive query q such that $\mathcal{R}\text{-CQA}(q)$ is coNP-hard follows from the proof of [26, Thm. 5.5] in a straightforward manner. A proof sketch can be found in the appendix.*

PROPOSITION 5.5. *Let $\mathcal{R} = (\text{LAV}, \emptyset, \text{LIT}, \text{ATOMS})$. There exists a conjunctive query q such that $\mathcal{R}\text{-CQA}(q)$ is coNP-hard.*

PROOF. We construct a reduction from the complement of **3-COLOURABILITY** to the problem of finding consistent answers. The components of the repair framework are defined as follows:

$$\begin{aligned} C_h &:= \left\{ \forall x \forall y \left(E(x, y) \rightarrow \exists j \exists k (C(x, j) \wedge C(y, k) \wedge D(j, k)) \right) \right\}, \\ C_s &:= \{\}, \\ Q_h &:= \{E(x, y), \neg E(x, y), D(j, k), \neg D(j, k)\}, \\ Q_s &:= \{C(x, j)\}. \end{aligned}$$

Let $G = (V, E)$ be a graph. The instance \mathcal{D} is defined as follows:

$$\begin{aligned} E^{\mathcal{D}} &:= \{(x, y) \mid (x, y) \in E(G)\}, \\ C^{\mathcal{D}} &:= \{\}, \\ D^{\mathcal{D}} &:= \{1, 2, 3\}^2 \setminus \{(1, 1), (2, 2), (3, 3)\}. \end{aligned}$$

Let q be the following conjunctive query:

$$\exists x \exists j \exists k (C(x, j) \wedge C(x, k) \wedge D(j, k)).$$

The intuition of the relational symbols is as follows: E encodes the edges of the graph G , C assigns to each vertex a colour and D encodes inequality between the three possible colours. Now, we claim that the following is true for all \mathcal{R} -repairs \mathcal{D}' of \mathcal{D} : $\text{Ans}(\mathcal{D}', q)$ is nonempty if and only if $G \notin \text{3-COLOURABILITY}$.

If $G \notin \text{3-COLOURABILITY}$, then there is no valid colouring. It follows that in all repairs there must be a vertex x which is assigned two colours to satisfy the hard constraint, thereby satisfying the query q .

If $G \in \text{3-COLOURABILITY}$, then there exists a valid colouring f for G . Let \mathcal{D}_f be the following instance:

$$\begin{aligned} E^{\mathcal{D}_f} &:= E^{\mathcal{D}}, \\ C^{\mathcal{D}_f} &:= \{(x, f(x)) \mid x \in V(G)\}, \\ D^{\mathcal{D}_f} &:= D^{\mathcal{D}}. \end{aligned}$$

It is easy to see, that \mathcal{D}_f is a repair of \mathcal{D} and $q(\mathcal{D}_f)$ is false, so the consistent answers to q cannot be nonempty. Since **3-COLOURABILITY** is NP-complete, the claim follows. \square

PROPOSITION 5.6. *Let $\mathcal{R} = (\text{GAV}, \emptyset, \text{COQULIT}, \emptyset)$. Then $\exists \mathcal{R}$ -repair is NP-complete.*

PROOF. We show NP-hardness; inclusion to NP is due to Theorem 5.7. We again present a reduction from **3-COLOURABILITY**.

$$\begin{aligned} C_h &:= \left\{ \begin{aligned} \phi_1 &= \forall x \forall j \forall k \left((C(x, j) \wedge C(x, k) \wedge D(j, k)) \rightarrow \text{false} \right), \\ \phi_2 &= \forall x \forall y \forall j \forall k \left((E(x, y) \wedge C(x, k) \wedge C(y, j)) \rightarrow D(k, j) \right) \end{aligned} \right\} \\ Q_h &:= \{\varphi(x) = \exists j C(x, j), E(x, y), \neg E(x, y), D(j, k), \neg D(j, k)\} \end{aligned}$$

Let $G = (V, E)$ be a graph. The instance \mathcal{D} is defined as follows:

$$\begin{aligned} E^{\mathcal{D}} &:= \{(x, y) \mid (x, y) \in E(G)\}, \\ C^{\mathcal{D}} &:= \{(x, j) \mid x \in V(G), j \in \{1, 2, 3\}\}, \\ D^{\mathcal{D}} &:= \{1, 2, 3\}^2 \setminus \{(1, 1), (2, 2), (3, 3)\}. \end{aligned}$$

The intuition for the relational symbols is the same as in the proof of Proposition 5.5. For the hard constraints and queries we have

that ϕ_1 ensures that each vertex has at most one colour, ϕ_2 ensures that the vertices of an edge have different colours and $\phi(x)$ ensures that each vertex that has a colour in \mathfrak{D} has at least one colour in its repair.

We now show correctness. By construction, if G has a 3-colouring via f , then \mathfrak{D}_f is a repair of \mathfrak{D} .

Now, if \mathfrak{D}' is a repair of \mathfrak{D} , we know that $E^{\mathfrak{D}'} = E^{\mathfrak{D}}$, $D^{\mathfrak{D}'} = D^{\mathfrak{D}}$ and $C^{\mathfrak{D}'} \subseteq C^{\mathfrak{D}}$. It follows from $\phi(x)$ and ϕ_1 , that each vertex x has exactly one colour. Let $f(x) = j$ with $(x, j) \in C^{\mathfrak{D}'}$. With ϕ_2 we can conclude that f is a valid colouring of G , because no colour has an edge to a vertex with the same colour. \square

5.3 Existence of a repair and second-order logic

We now show how the existence of a repair can be reduced to model checking of existential second-order logic, and obtain general upper bounds for existence of repair and CQA.

THEOREM 5.7. *Let $\mathcal{R} = (C_h, \emptyset, Q_h, Q_s)$, where $C_h, Q_h \subseteq \text{FO}$ and Q_s is arbitrary. Then $\exists\mathcal{R}$ -repair is in NP. Moreover, the problem is NP-complete for some $C_h, Q_h \subseteq \text{FO}$.*

PROOF. The NP-hardness was shown already in Proposition 5.6. Here we establish inclusion to NP. Fix a finite relational vocabulary $\tau_1 = \{R_1, \dots, R_n\}$ of some schema \mathcal{S} and let $\tau_2 = \{S_1, \dots, S_n\}$ denote a disjoint copy of τ_1 . We consider databases and repair notions with schema \mathcal{S} . Let $\mathfrak{R} := (C_h, \emptyset, Q_h, Q_s)$ be a repair notion as described in the theorem. Note first that Q_s does not affect the existence of a repair, so we may assume that $Q_s = \emptyset$. Given a database \mathfrak{D} over \mathcal{S} , let $(C_h, \emptyset, Q_h^{\mathfrak{D}}, \emptyset)$ be the repair notion, where $Q_h^{\mathfrak{D}}$ is the relativisation of Q_h to \mathfrak{D} computed from Q_h and \mathfrak{D} in polynomial time. The existence of an \mathfrak{R} -repair of \mathfrak{D} can be reduced to model checking as follows: The database \mathfrak{D} has an \mathfrak{R} -repair if and only if \mathfrak{D} satisfies the formula

$$\exists S_1 \dots \exists S_n \left(\bigwedge_{\varphi \in Q_h^{\mathfrak{D}}} \forall \vec{x} (\varphi(\vec{x}) \rightarrow \varphi^*[\vec{S}/\vec{R}](\vec{x})) \wedge \bigwedge_{\varphi \in C_h} \varphi^*[\vec{S}/\vec{R}] \right),$$

where $\varphi^*[\vec{S}/\vec{R}]$ denotes the formula obtained from φ by substituting \vec{R} by \vec{S} and bounding its first-order qualifications to the active domain of the repair obtained from the interpretations of $\exists S_1 \dots \exists S_n$. The fact that the above model checking can be decided in NP with respect to the size of \mathfrak{D} follows essentially from Fagin's theorem; the fact that data complexity of existential second-order logic is NP suffices. Note first that S_1, \dots, S_n are of polynomial size, since n and their arities are constant. The fact that the satisfaction of the subsequent formula can be checked in NP follows from the fact that $Q_h^{\mathfrak{D}}$ and C_h are polynomial size sets of FO-formulae of constant size. Recall that \mathfrak{R} is fixed and \mathfrak{D} is the input, and thus the size of φ^* is constant as well. \square

Note also that the above model checking problem could easily be transformed into a FO satisfiability problem. Simply append the constructed formula above to the FO description of \mathfrak{D} and remove all (existential) second-order quantifiers that are interpreted existentially in the satisfiability problem.

LEMMA 5.8. *Let $\mathcal{R} = (C_h, C_s, Q_h, Q_s)$. Then $\exists\mathcal{R}$ -repair is reducible in logarithmic space to complement problem of \mathcal{R} -CQA(q), where $q \in \text{COQ}$.*

PROOF. By ten Cate et al. [26, Thm. 7.1] the query $q = \exists x P(x)$ with a fresh relation P suffices. That is, given an instance \mathfrak{D} , we have that $\top \in \text{CQA}(q, \mathfrak{D}, \mathcal{R})$ if and only if \mathfrak{D} has no repair. \square

THEOREM 5.9. *Let $\mathcal{R} = (C_h, \emptyset, Q_h, \emptyset)$, where $C_h, Q_h \subseteq \text{FO}$. Then \mathcal{R} -CQA(q) is in coNP for any $q \in \text{FO}$. Moreover, the problem is coNP-complete for some $C_h \subseteq \text{GAV}$, $Q_h \subseteq \text{COQ} \cup \text{LIT}$, and $q \in \text{COQ}$.*

PROOF. Hardness for coNP follows from Proposition 5.6 and Lemma 5.8, we proceed to show inclusion. Fix a finite relational vocabulary $\tau_1 = \{R_1, \dots, R_n\}$ of some schema \mathcal{S} and let $\tau_2 = \{S_1, \dots, S_n\}$ denote a disjoint copy of τ_1 . We consider databases and repair notions with schema \mathcal{S} . Let $\mathfrak{R} := (C_h, \emptyset, Q_h, \emptyset)$ be a repair notion as described in the theorem and $q(\vec{x}) \in \text{FO}$. Given a database \mathfrak{D} over \mathcal{S} , let $Q_h^{\mathfrak{D}}$ be the relativisation of Q_h to \mathfrak{D} computed from Q_h and \mathfrak{D} in polynomial time. \mathcal{R} -CQA(q) for \mathfrak{D} can be reduced to model checking as follows: A tuple \vec{t} is in the consistent answers of $q(\vec{x})$ in \mathfrak{D} with respect to \mathfrak{R} if and only if

$$\mathfrak{D} \models \forall S_1 \dots \forall S_n \left(\left(\bigwedge_{\varphi \in Q_h^{\mathfrak{D}}} \forall \vec{x} (\varphi(\vec{x}) \rightarrow \varphi^*[\vec{S}/\vec{R}](\vec{x})) \right) \wedge \bigwedge_{\phi \in C_h} \phi^*[\vec{S}/\vec{R}] \rightarrow q^*[\vec{S}/\vec{R}](\vec{t}/\vec{x}) \right),$$

where $\phi^*[\vec{S}/\vec{R}]$ and $q^*[\vec{S}/\vec{R}]$ are as defined in the proof of Theorem 5.7. The fact that the above model checking can be done in coNP is proven analogously as the inclusion to NP was done in Theorem 5.7, with the distinction that data complexity of universal second-order logic is in coNP. \square

THEOREM 5.10. *Let $\mathcal{R} = (C_h, \emptyset, Q_h, Q_s)$, where $C_h, Q_h, Q_s \subseteq \text{FO}$. Then \mathcal{R} -CQA(q) is in Π_2^P for all $q \in \text{FO}$. Moreover, \mathcal{R} -CQA(q) is Π_2^P -hard for some $q \in \text{COQ}$ and $\mathcal{R} = (C_h, \emptyset, Q_h, Q_s)$, where C_h is a set of tgds, $Q_h \subseteq \text{LIT}$, $Q_s \subseteq \text{ATOMS}$.*

PROOF. We will show how the Π_2^P -hard instance of a proof of ten Cate et al. [26, Thm 6.3] can be formulated in our setting. In their proof ten Cate et al. reduce from the problem: given a quantified Boolean formula (qBf) φ of the form $\forall p_1 \dots \forall p_n \exists q_1 \dots \exists q_k \psi$, where ψ is a conjunction of clauses with three literals, does φ evaluate to true? We define an instance of the repair framework and a query $q \in \text{COQ}$ such that φ is true if and only if $\top \in \text{CQA}(q, \mathfrak{D}, \mathcal{R})$.

Let C_h consist of the union of $\{\phi_1, \phi_2, \phi_3, \phi_4\}$ and the formulas in $\{\phi_{a_1 a_2 a_3}(X_1, X_2, X_3) \mid a_i \in \{0, 1\}, X_i \in \{P, Q\}\}$, where

$$\begin{aligned} \phi_1 &:= \forall q \forall v (Q(q, v) \rightarrow \exists s A(s)), \\ \phi_2 &:= \forall s \forall q \left((A(s) \wedge Q'(q)) \rightarrow \exists v Q(q, v) \right), \\ \phi_3 &:= \forall q \forall v \forall v' \left((Q(q, v) \wedge Q(q, v')) \rightarrow E(v, v') \right), \\ \phi_4 &:= \forall p \forall v \forall v' \left((P(q, v) \wedge P(q, v')) \rightarrow E(v, v') \right), \end{aligned}$$

and $\phi_{a_1 a_2 a_3}(X_1, X_2, X_3)$ is defined as

$$\begin{aligned} & \forall x_1 \forall x_2 \forall x_3 \forall s \left((R_{a_1 a_2 a_3}(x_1, x_2, x_3) \wedge A(s) \right. \\ & \quad \wedge X'_1(x_1) \wedge X'_2(x_2) \wedge X'_3(x_3)) \\ & \quad \rightarrow \exists v_1 \exists v_2 \exists v_3 (X_1(x_1, v_1) \wedge X_2(x_2, v_2) \wedge \\ & \quad \quad \quad \left. X_3(x_3, v_3) \wedge T_{a_1 a_2 a_3}(v_1, v_2, v_3)) \right). \end{aligned}$$

Next, for the hard queries we set

$$\begin{aligned} \mathcal{Q}_h := & \{ Q'(q), \neg Q'(q), P'(p), \neg P'(p), E(u, v), \neg E(u, v), \\ & \neg A(s), \neg Q(q, v), \neg P(p, v) \} \cup \{ R_{a_1 a_2 a_3}(x_1, x_2, x_3), \\ & \neg R_{a_1 a_2 a_3}(x_1, x_2, x_3), T_{a_1 a_2 a_3}(v_1, v_2, v_3), \\ & \neg T_{a_1 a_2 a_3}(v_1, v_2, v_3) \mid a_i \in \{0, 1\} \}, \end{aligned}$$

and for the soft queries take $\mathcal{Q}_s := \{A(s)\}$. Finally, let $q := \exists s A(s)$ be the query.

We define the instance \mathfrak{D} from a qBf $\forall p_1 \dots \forall p_n \exists q_1 \dots q_k \psi$ as follows:

$$\begin{aligned} A^{\mathfrak{D}} &= \{1\}, \\ (Q')^{\mathfrak{D}} &= \{q_i \mid 1 \leq i \leq k\}, \\ (P')^{\mathfrak{D}} &= \{p_i \mid 1 \leq i \leq n\}, \\ Q^{\mathfrak{D}} &= \{(q_i, v) \mid 1 \leq i \leq k, v \in \{0, 1\}\}, \\ P^{\mathfrak{D}} &= \{(p_i, v) \mid 1 \leq i \leq n, v \in \{0, 1\}\}, \\ E^{\mathfrak{D}} &= \{(0, 0), (1, 1)\}, \\ T_{a_1 a_2 a_3}^{\mathfrak{D}} &= \{(v_1, v_2, v_3) \mid \forall 1 \leq i \leq 3, v_i \in \{0, 1\}, \\ & \quad (v_1, v_2, v_3) \neq (a_1, a_2, a_3)\}, \\ R_{a_1 a_2 a_3}^{\mathfrak{D}} &= \{(x_1, x_2, x_3) \mid x_1 \vee x_2 \vee x_3 \text{ is a clause of } \psi \\ & \quad \text{and } \forall 1 \leq i \leq 3, \text{is}(x_i) = a_i\}, \end{aligned}$$

where $\text{is}(x)$ is the *inverse sign* of x , that is $\text{is}(x)$ is 0 if x is a positive literal, and 1 otherwise.

We omit the proof of correctness here since it is similar to that of ten Cate et al. [26, Thm 6.3].

Now, for the Π_2^P membership, fix a finite relational vocabulary $\tau_1 = \{R_1, \dots, R_n\}$ of some schema \mathcal{S} and let $\tau_2 = \{S_1, \dots, S_n\}$ denote a disjoint copy of τ_1 . We consider databases and repair notions over schema \mathcal{S} . Let $\mathfrak{R} := (C_h, \emptyset, \mathcal{Q}_h, \mathcal{Q}_s)$ be a repair notion as the one previously described. Given a database \mathfrak{D} over \mathcal{S} , let $\mathcal{Q}_h^{\mathfrak{D}}$ and $\mathcal{Q}_s^{\mathfrak{D}}$ be the relativisations of \mathcal{Q}_h and \mathcal{Q}_s to \mathfrak{D} computed from $\mathcal{Q}_h, \mathcal{Q}_s$, and \mathfrak{D} in polynomial time. We show a Π_2^P algorithm for deciding $\mathcal{R}\text{-CQA}(q)$, for any fixed $q(\vec{x}) \in \text{FO}$.

Since the data complexity of FO is in P, we can compute the sets

$$\begin{aligned} \mathcal{TQ}_h^{\mathfrak{D}} &:= \{\varphi \in \mathcal{Q}_h^{\mathfrak{D}} \mid \mathfrak{D} \models \varphi\}, \\ \mathcal{TQ}_s^{\mathfrak{D}} &:= \{\varphi \in \mathcal{Q}_s^{\mathfrak{D}} \mid \mathfrak{D} \models \varphi\}, \\ \mathcal{FQ}_s^{\mathfrak{D}} &:= \mathcal{Q}_s^{\mathfrak{D}} \setminus \mathcal{TQ}_s^{\mathfrak{D}} \end{aligned}$$

in polynomial time. We will then compute the smallest $n \leq |\mathcal{Q}_s^{\mathfrak{D}}|$ such that there exist sets $F \subseteq \mathcal{TQ}_s^{\mathfrak{D}}$ and $T \subseteq \mathcal{FQ}_s^{\mathfrak{D}}$ such that

$|T \cup F| = n$ and

$$\begin{aligned} \mathfrak{D} \models & \exists S_1 \dots \exists S_n \left(\bigwedge_{\varphi \in C_h} \varphi^*[\vec{S}/\vec{R}] \wedge \bigwedge_{\varphi \in \mathcal{TQ}_h^{\mathfrak{D}}} \varphi^*[\vec{S}/\vec{R}] \right. \\ & \left. \wedge \bigwedge_{\varphi \in (\mathcal{T} \cup \mathcal{TQ}_s^{\mathfrak{D}}) \setminus F} \varphi^*[\vec{S}/\vec{R}] \wedge \bigwedge_{\varphi \in (\mathcal{F} \cup \mathcal{FQ}_s^{\mathfrak{D}}) \setminus T} \neg \varphi^*[\vec{S}/\vec{R}] \right), \end{aligned}$$

where $\varphi^*[\vec{S}/\vec{R}]$ is as defined in the proof of Theorem 5.7. Clearly, this can be done in NP. Note that, since we are presenting an Π_2^P algorithm, the computation of such n is postponed to the NP part of the algorithm.

A tuple \vec{t} is in the consistent answers of $q(\vec{x})$ in \mathfrak{D} with respect to \mathfrak{R} if and only if for every database \mathfrak{D}' over schema \mathcal{S} with active domain $\text{ADOM}(\mathfrak{D}') \subseteq \text{ADOM}(\mathfrak{D})$ at least one of the following holds:

- (1) $\mathfrak{D}' \models q(\vec{t}/\vec{x})$
- (2) $\mathfrak{D}' \not\models C_h \wedge \mathcal{TQ}_h$
- (3) there exist sets $F \subseteq \mathcal{TQ}_s^{\mathfrak{D}}$ and $T \subseteq \mathcal{FQ}_s^{\mathfrak{D}}$ such that $|T \cup F| \geq n + 1$ and

$$\mathfrak{D}' \models (T \cup \mathcal{TQ}_s^{\mathfrak{D}}) \setminus F \wedge \bigwedge_{\varphi \in (\mathcal{F} \cup \mathcal{FQ}_s^{\mathfrak{D}}) \setminus T} \neg \varphi.$$

It is straightforward to check that the most evident implementation of the above can be done in Π_2^P : it boils down to, first, universally guessing a polynomial-size interpretation for \mathfrak{D}' followed by the computation of n , and existentially quantifying the polynomial-size sets T and F . The final model checking can be then done in polynomial time. \square

6 CONCLUSIONS AND FUTURE WORK

We introduced a novel abstract framework for defining database repairs. Instances $\mathcal{R} = (C_h, C_s, \mathcal{Q}_h, \mathcal{Q}_s, \mathcal{M}, d_{\mathcal{Q}_s})$ of the framework use the hard-constraints in C_h to describe properties of data necessary to hold in a repair, whereas soft-constraints in C_s describe properties that are merely desired, and help us define inconsistency-tolerant repairs together with the inconsistency measure \mathcal{M} . Hard-queries \mathcal{Q}_h , together with the integrity constraints, determine the space of repairs; the answers for the hard-queries are required to be included in the corresponding answers of queries in any repair. Soft-queries \mathcal{Q}_s are used to define a distance between instances; the distances between the answers for the soft-queries are used to define the minimality notion related to repairs using the aggregate method defined by $d_{\mathcal{Q}_s}$.

When dealing with inconsistency, we may not have permission to change the data to obtain a repair, or it simply may not be the best option. This is a scenario in which the CQA problem comes in handy to obtain consistent answers from inconsistent databases without modifying the data. In our setting CQA is defined as usual; the *consistent answer* of a query is the intersection of the answers of all the (minimal) repairs. However, since our framework is based on logic, e.g., the non-emptiness of the consistent answers can be formulated as a satisfiability problem in logic.

Furthermore, we initiated a study of complexity within the bounds of our new framework and presented several intractability results for repairing and CQA. We focused on tgds, LAV and GAV, and exhibited problems complete for the first and second level of

the polynomial hierarchy (see also Tables 1–3 on page 2 for an overview of our complexity results).

We conclude with some future directions and open questions.

- Our complexity results are mainly negative, as we show intractable cases. Can we pinpoint \mathcal{R} -repairs where the related complexities are below NP? Does considering parameterised complexity [8] help here?
- What complexity characterisations can we obtain for enumeration complexity of repairs, or repair checking?
- Does there exist, for every level of the polynomial hierarchy, a fixed repair framework \mathcal{R} such that the existence of repair is complete for that level of the hierarchy?
- Our complexity considerations are focused on relational databases and set semantics. A natural direction for future work includes complexity considerations under bag semantics, and related to K -databases in general.

ACKNOWLEDGEMENTS

Nicolas Fröhlich and Arne Meier are funded by the German Research Foundation (DFG) under project ME 4279/3-1. Nina Pardal and Jonni Virtema are funded by DFG project VI 1045/1-1.

REFERENCES

- [1] Serge Abiteboul, Richard Hull, and Victor Vianu. 1995. *Foundations of Databases*. Addison-Wesley.
- [2] Carlos E. Alchourrón, Peter Gärdenfors, and David Makinson. 1985. On the Logic of Theory Change: Partial Meet Contraction and Revision Functions. *J. Symb. Log.* 50, 2 (1985), 510–530. <https://doi.org/10.2307/2274239>
- [3] Pablo Barceló and Gaëlle Fontaine. 2017. On the data complexity of consistent query answering over graph databases. *J. Comput. System Sci.* 88 (2017), 164–194.
- [4] Leopoldo E. Bertossi. 2019. Repair-Based Degrees of Database Inconsistency. In *Logic Programming and Nonmonotonic Reasoning - 15th International Conference, LPNMR 2019, Philadelphia, PA, USA, June 3-7, 2019, Proceedings (Lecture Notes in Computer Science, Vol. 11481)*, Marcello Balduccini, Yuliya Lierler, and Stefan Woltran (Eds.). Springer, 195–209. https://doi.org/10.1007/978-3-030-20528-7_15
- [5] Douglas Burdick, Ronald Fagin, Phokion G. Kolaitis, Lucian Popa, and Wang-Chiew Tan. 2019. Expressive power of entity-linking frameworks. *J. Comput. Syst. Sci.* 100 (2019), 44–69. <https://doi.org/10.1016/j.jcss.2018.09.001>
- [6] Marco Calautti, Sergio Greco, Cristian Molinaro, and Irina Trubitsyna. 2022. Preference-based inconsistency-tolerant query answering under existential rules. *Artif. Intell.* 312 (2022), 103772. <https://doi.org/10.1016/j.artint.2022.103772>
- [7] Hendrik Decker. 2017. Inconsistency-Tolerant Database Repairs and Simplified Repair Checking by Measure-Based Integrity Checking. *Trans. Large Scale Data Knowl. Centered Syst.* 34 (2017), 153–183. https://doi.org/10.1007/978-3-662-55947-5_7
- [8] Rodney G. Downey and Michael R. Fellows. 1999. *Parameterized Complexity*. Springer.
- [9] Erich Grädel and Yuri Gurevich. 1998. Metafinite Model Theory. *Inf. Comput.* 140, 1 (1998), 26–81. <https://doi.org/10.1006/inco.1997.2675>
- [10] Erich Grädel and Val Tannen. 2017. Semiring Provenance for First-Order Model Checking. *CoRR* abs/1712.01980 (2017).
- [11] Gianluigi Greco, Sergio Greco, and Ester Zumpano. 2003. A Logical Framework for Querying and Repairing Inconsistent Databases. *IEEE Trans. Knowl. Data Eng.* 15, 6 (2003), 1389–1408. <https://doi.org/10.1109/TKDE.2003.1245280>
- [12] Todd J. Green, Gregory Karvounarakis, and Val Tannen. 2007. Provenance semirings. In *Proceedings of the Twenty-Sixth ACM SIGACT-SIGMOD-SIGART Symposium on Principles of Database Systems, June 11-13, 2007, Beijing, China*, Leonid Libkin (Ed.). ACM, 31–40. <https://doi.org/10.1145/1265530.1265535>
- [13] Paulo T. Guerra and Renata Wassermann. 2019. Two AGM-style characterizations of model repair. *Ann. Math. Artif. Intell.* 87, 3 (2019), 233–257. <https://doi.org/10.1007/s10472-019-09656-4>
- [14] Stephen T. Hedetniemi and Renu C. Laskar. 1990. Bibliography on domination in graphs and some basic definitions of domination parameters. *Discret. Math.* 86, 1-3 (1990), 257–277. [https://doi.org/10.1016/0012-365X\(90\)90365-O](https://doi.org/10.1016/0012-365X(90)90365-O)
- [15] Richard M. Karp. 1972. Reducibility Among Combinatorial Problems. In *Proceedings of a symposium on the Complexity of Computer Computations, held March 20-22, 1972, at the IBM Thomas J. Watson Research Center, Yorktown Heights, New York, USA (The IBM Research Symposia Series)*, Raymond E. Miller and James W. Thatcher (Eds.). Plenum Press, New York, 85–103. https://doi.org/10.1007/978-1-4684-2001-2_9
- [16] Leonid Libkin. 2004. *Elements of Finite Model Theory*. Springer. <https://doi.org/10.1007/978-3-662-07003-1>
- [17] Ester Livshits, Rina Kochirgan, Segev Tsur, Ihab F. Ilyas, Benny Kimelfeld, and Sudeepa Roy. 2021. Properties of Inconsistency Measures for Databases. In *SIGMOD '21: International Conference on Management of Data, Virtual Event, China, June 20-25, 2021*, Guoliang Li, Zhanhui Li, Stratos Idreos, and Divesh Srivastava (Eds.). ACM, 1182–1194. <https://doi.org/10.1145/3448016.3457310>
- [18] Andrei Lopatenko and Leopoldo E. Bertossi. 2007. Complexity of Consistent Query Answering in Databases Under Cardinality-Based and Incremental Repair Semantics. In *Proceedings ICDT-2007 (LNCS, Vol. 4353)*. Springer, 179–193.
- [19] Thomas Lukasiewicz, Enrico Malizia, Maria Vanina Martinez, Cristian Molinaro, Andreas Pieris, and Gerardo I. Simari. 2022. Inconsistency-tolerant query answering for existential rules. *Artif. Intell.* 307 (2022), 103685. <https://doi.org/10.1016/j.artint.2022.103685>
- [20] Thomas Lukasiewicz, Enrico Malizia, and Andrius Vaicenavicius. 2022. Complexity of Inconsistency-Tolerant Query Answering in Datalog+/- under Cardinality-Based Repairs. In *Proceedings of the 30th Italian Symposium on Advanced Database Systems, SEBD 2022, Tirrenia (PI), Italy, June 19-22, 2022 (CEUR Workshop Proceedings, Vol. 3194)*, Giuseppe Amato, Valentina Bartalesi, Devis Bianchini, Claudio Gennaro, and Riccardo Torlone (Eds.). CEUR-WS.org, 530–537. <https://ceur-ws.org/Vol-3194/paper62.pdf>
- [21] Christos H. Papadimitriou. 2007. *Computational complexity*. Academic Internet Publ.
- [22] Francesco Parisi and John Grant. 2023. On measuring inconsistency in definite and indefinite databases with denial constraints. *Artif. Intell.* 318 (2023), 103884. <https://doi.org/10.1016/j.artint.2023.103884>
- [23] Slawek Staworko, Jan Chomiccki, and Jerzy Marcinkowski. 2012. Prioritized repairing and consistent query answering in relational databases. *Ann. Math. Artif. Intell.* 64, 2-3 (2012), 209–246. <https://doi.org/10.1007/s10472-012-9288-8>
- [24] V. S. Subrahmanian and Leila Amgoud. 2007. A General Framework for Reasoning about Inconsistency. In *IJCAI 2007, Proceedings of the 20th International Joint Conference on Artificial Intelligence, Hyderabad, India, January 6-12, 2007*, Manuela M. Veloso (Ed.), 599–604. <http://ijcai.org/Proceedings/07/Papers/095.pdf>
- [25] Balder ten Cate, Gaëlle Fontaine, and Phokion G. Kolaitis. 2012. On the Data Complexity of Consistent Query Answering. In *Proceedings of the 15th International Conference on Database Theory (ICDT '12)*, 22–33.
- [26] Balder ten Cate, Gaëlle Fontaine, and Phokion G. Kolaitis. 2015. On the Data Complexity of Consistent Query Answering. *Theory Comput. Syst.* 57, 4 (2015), 843–891. <https://doi.org/10.1007/s00224-014-9586-0>
- [27] Jef Wijsen. 2002. Condensed Representation of Database Repairs for Consistent Query Answering. In *Proceedings of the 9th International Conference on Database Theory (ICDT '03)*. Springer-Verlag, 378–393.
- [28] Bruno Yun, Srdjan Vesic, Madalina Croitoru, and Pierre Bisquert. 2018. Inconsistency Measures for Repair Semantics in OBDA. In *Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence, IJCAI 2018, July 13-19, 2018, Stockholm, Sweden, Jérôme Lang (Ed.)*. ijcai.org, 1977–1983. <https://doi.org/10.24963/IJCAI.2018/273>
- [29] Xiaowang Zhang, Kewen Wang, Zhe Wang, Yue Ma, Guilin Qi, and Zhiyong Feng. 2017. A distance-based framework for inconsistency-tolerant reasoning and inconsistency measurement in DL-Lite. *Int. J. Approx. Reason.* 89 (2017), 58–79. <https://doi.org/10.1016/j.ijar.2016.08.003>

A APPENDIX

REMARK 2. For $\mathcal{R} = (\text{GAV}, \emptyset, \text{LIT}, \text{ATOMS})$, the existence of a conjunctive query q such that $\mathcal{R}\text{-CQA}(q)$ is coNP-hard follows from the proof of [26, Thm. 5.5] in a straightforward manner.

PROOF. We adapt the proof of ten Cate et al. [26, Thm. 5.5] to our setting, which shows a reduction from the complement of Positive 1-in-3-SAT to CQA. The NP-complete problem POSITIVE 1-IN-3-SAT is defined as follows: Given a Boolean formula φ in conjunctive normal form, where each clause is of the form $(x_1 \vee x_2 \vee x_3)$ and contains only positive literals, is there a truth assignment such that exactly one variable is true in each clause? We define an instance of the repair framework and a query $q \in \text{COQ}$ such that $\varphi \notin \text{POSITIVE 1-IN-3-SAT}$ if and only if $\top \in \text{CQA}(q, \mathfrak{D}, \mathcal{R})$.

Let the components of the repair framework be as follows:

$$\begin{aligned} C_h &:= \{\forall x \forall u, \forall u' (P(x, u) \wedge P(x, u') \rightarrow E(u, u'))\}, \\ Q_h &:= \{E(x, y), \neg E(x, y), R(x, y, z), \neg R(x, y, z), \\ &\quad S(u, v), \neg S(u, v), \neg P(x, u)\} \\ Q_s &:= \{P(x, u)\}. \end{aligned}$$

For the query we have

$$\begin{aligned} q &:= \exists x_1, \exists x_2, \exists x_3, \exists u_1, \exists u_2, \exists u_3 (R(x_1, x_2, x_3) \\ &\quad \wedge P(x_1, u_1) \wedge P(x_2, u_2) \wedge P(x_3, u_3) \wedge S(u_1, u_2, u_3)). \end{aligned}$$

We define the instance \mathfrak{D} w.r.t φ as:

$$\begin{aligned} R^{\mathfrak{D}} &:= \{(x_{i1}, x_{i2}, x_{i3}) \mid 1 \leq i \leq n\} \\ P^{\mathfrak{D}} &:= \{(x_{ij}, 0), (x_{ij}, 0) \mid 1 \leq i \leq n, \mid 1 \leq j \leq 3\} \\ E^{\mathfrak{D}} &:= \{(1, 1), (0, 0)\}, \\ S^{\mathfrak{D}} &:= \{0, 1\}^3 \setminus \{(1, 0, 0), (0, 1, 0), (0, 0, 1)\}. \end{aligned}$$

We omit the proof of correctness here as it is analogous to the proof of ten Cate et al. [26, Thm. 5.5]. \square