BEYOND NEURAL-ON-NEURAL APPROACHES TO SPEAKER GENDER PROTECTION

Loes van Bemmel^{1,2,3}, Zhuoran Liu¹, Nik Vaessen¹, Martha Larson^{1,3}

¹Institute for Computing and Information Sciences, ²Department of Artificial Intelligence, ³Center for Language Studies Radboud University Nijmegen, the Netherlands

ABSTRACT

Recent research has proposed approaches that modify speech to defend against gender inference attacks. The goal of these protection algorithms is to control the availability of information about a speaker's gender, a privacy-sensitive attribute. Currently, the common practice for developing and testing gender protection algorithms is "neural-on-neural", i.e., perturbations are generated and tested with a neural network. In this paper, we propose to go beyond this practice to strengthen the study of gender protection. First, we demonstrate the importance of testing gender inference attacks that are based on speech features historically developed by speech scientists, alongside the conventionally used neural classifiers. Next, we argue that researchers should use speech features to gain insight into how protective modifications change the speech signal. Finally, we point out that gender-protection algorithms should be compared with novel "vocal adversaries", human-executed voice adaptations, in order to improve interpretability and enable before-the-mic protection. Code is available at https: //github.com/Loes5307/VocalAdversary2022

Index Terms— adversarial speech, gender inference, neural classifiers, interpretablity, attribute inference

1. INTRODUCTION

Recently, researchers have proposed approaches to protect spoken audio against gender inference attacks [1, 2, 3]. The aim of these approaches is to protect speakers' privacy by modifying their speech signal in a way that impedes the ability of a classifier to infer their gender. The modified speech must retain its utility, which is generally taken to mean that it must remain understandable to people and have minimal impact on automatic speech recognition (ASR).

This paper is motivated by our observation that current research devoted to developing and testing gender protection algorithms is overwhelmingly *neural-on-neural*. In other words, protective perturbations are generated with a neural approach and also tested against neural gender inference attacks. The main contribution of this paper are experimental results demonstrating the importance and usefulness of classic, non-neural speech features in attacking and analyzing



Fig. 1. Gender prediction accuracy on the VoxCeleb2 test set for 1) a single-feature classifier (linear ridge using mean pitch), and 2) a neural classifier (WavLM). Neural perturbations (reference model WavLM) do not affect the simple classifier, but highly impact the performance of the neural classifier (rightmost bar). Classifiers are trained on LibriSpeech.

gender protecting approaches, and motivating "vocal adversaries", non-neural protection created by the human voice.

The importance of going beyond neural-on-neural approaches is illustrated by the gender inference attacks in Fig. 1. For the original, unperturbed data (left side), a simple classifier based on a single feature (mean pitch) is outperformed by a neural classifier (WavLM). However, for data perturbed with a neural adversary (right side) the situation changes dramatically. The neural classifier can no longer correctly classify the speech samples, while the simple classifier maintains its performance. If researchers only test a neural classifier, as is common practice, e.g., [1, 2, 3], the vulnerability of the gender protection to a simple classifier based on speech features would go unnoticed.

The context of our work is the privacy threat represented by paralinguistic information inherent in speech, which has been gaining widespread attention recently [1, 4]. Gender is a privacy-sensitive attribute and concerns about gender classification being used for invasive or harmful targeting are growing [5, 6]. Further, targeting on the basis of binary notions of gender represents a grave reduction of the sociocultural concept of gender [7, 8]. We aim to move research on gender privacy protection closer to the real world. This aim motivates our focus on protecting the raw signal, rather than speech representations, as has been studied by [9, 10, 11]. It also pushes

Table 1. Overview of datasets

		#speakers		#utterances	
data	avg. duration	F	М	F	Μ
LS100h (training)	12.7 s	125	126	14 342	14 197
LS960h (training)	12.3 s	1 128	1 1210	135 889	143 352
vox (training)	7.8 s	2 312	3 682	397 032	694 977
Voxtest (testing)	7.9 s	39	79	10 711	25 526

us to look beyond neural attacks to extend the threat models under investigation to include non-neural modifications and before-the-mic scenarios. Initial efforts in these directions, and the closest work to our own, is [3], who tested a simple non-neural pitch shifting gender protection approach, and [12], who investigate before-the-mic speech protection created by having speakers speak through a tube. In contrast, in our work we propose, for the first time, "vocal adversaries", speakers speaking with adaptations created using their own voices.

The paper is structured around three sets of experiments corresponding to the three ways in which we propose that it is important for speaker gender protection research to go beyond current neural-on-neural approaches. In Sec. 2, we argue that researchers should be aware of the effect shown in Fig. 1 and investigate gender inference attacks that use speech features historically developed by speech scientists, alongside neural classifiers. In Sec. 3, we demonstrate how researchers can make use of speech features to seek insight into the ways in which protective modifications change the speech signal. In Sec. 4, we argue that neural approaches should not be considered the sole source of gender protection. Rather, we propose and introduce the promising "vocal adversaries", human executed voice adaptations.

2. BEYOND NEURAL ATTACKS

In this section, we demonstrate the vulnerability of typical neural gender protection to both neural classifiers as well as a classifier that uses classic speech features.

2.1. Experimental Setup

Data Table 1 presents the data for Male (M) and Female (F) speech. For the LibriSpeech [13] data set, we use the train-clean-100 (LS100h) subset as well as all training data (LS960h). LibriSpeech is known to be relatively 'clean', meaning that the recordings do not contain significant background noise. For Voxceleb [14], which is known as a noisier dataset, the Voxceleb2 development set (designated as 'vox') is used for training and the Voxceleb2 test set ('Voxtest') is used for testing. All audio recordings are in English, have a sample rate of 16kHz and are normalized to the [0,1] range. For testing we pad or cut each utterance to the first 6 seconds, similar to previous work [1].

Neural classifiers We train two neural models for gender classification, which are later also used to create the neural perturbations. M5 [15] is a convolutional neural network

consisting of four convolutional layers with batch normalization, ReLU activation and a pooling layer, followed by a fully connected (FC) layer to classify gender. WavLM [16] is a self-supervised pre-trained transformer network that achieves state of the art results on the SUPERB benchmark.¹ To perform gender classification with WavLM, we take the average of the output sequence from the transformer, and add three FC layers for classification. M5 is trained from scratch on either LS100h, LS960h or vox for gender classification. WavLM's backbone is pre-trained on LS960h,² then it is fine-tuned on either LS100h, LS-960h, or vox for the gender classification task. We used Adam with a maximum learning rate (LR) of 1e-4 for M5 and 1e-5 for WavLM. All models are trained for 50k steps, with a cyclic learning rate schedule (triangular, 12.5 k steps per cycle, minimum LR 1e-8). We use a batch size of 32 audio files and use raw waveforms as input. From each file, we randomly select a 3 second chunk for training. During evaluation, the first 6 seconds of the fragment is used. For WavLM, we freeze everything but the last classification layers for the first cycle, before we unfreeze the transformer network. The feature extraction CNN of WavLM is kept frozen for the whole training duration.

Classic classifiers using speech features Traditionally, speech research uses handcrafted features extracted from audio [17]. These features have the advantage of having been designed by speech scientists, and, as such, reflect the underlying characteristics of speech. We extract 35 features with Praat [18], including number of Pulses, Periods and Voicebreaks. The degree of Voicebreaks, the fraction of Unvoiced parts, jitter (local, local absolute, rap, ppq5), shimmer (local, local dB, apq3, apq5, apq11), mean of the autocorrelation, Noise-to-Harmonics-Ratio (NHR), Harmonics-to-Noise-Ratio (HNR), mean and standard deviation of period and the min, max, mean, median and standard deviation of pitch. We also included duration, intensity (min, max, mean, standard deviation), the fundamental frequency F0, first three formants and the centre of gravity. These features were chosen for their widespread use in the acoustic community, as well as their interpretability with regards to speech production. We use the speech features in an SVM classifier trained on LS100h with a linear kernel to reduce overfitting.

Feature selection We select the top-10 features for the Female vs. Male classification using Recursive Feature Elimination (RFE) [19] with a linear SVM. Any SVM used in feature selection is not used for final classification. SVM-RFE is a wrapper feature selection that utilizes the support vectors to discard the least important feature in each iteration, until a top-n is left. The top-10 features can be seen in Table 2. These features and the selection method will also be used in Sec 3 for analysis of neural perturbations.

Neural gender protection We protect speakers' genders with neural perturbations created by applying Projected Gradient

¹https://superbbenchmark.org/leaderboard ²https://huggingface.co/microsoft/wavlm-base

Table 2. The top-10 features ordered by importance for M vs.F classification obtained with SVM-RFE for LS100h.

Feature	Description	Higher for:
pitch_mean	mean of pitch	Female
autocor_mean	mean of autocorrelation	Female
nhr_mean	mean of Noise-to-Harmonics-Ratio	Male
pitch_std	standard deviation of pitch	Female
pitch_max	max of pitch	Female
intensity_mean	mean of intensity	Male
shimmer_apq11	shimmer computed with 11 neighbours	Male
shimmer_apq3	shimmer computed with 2 neighbours	Male
intensity_max	max of intensity	Male
jitter_local_absolute	absolute jitter	Male

Descent (PGD) [20] to trained neural networks ('reference models') in order to generate adversarial speech examples. Compared to the single-step approach FGSM [21] used in [1], PGD is a stronger iterative version widely adopted in the adversarial machine learning community [22]. PGD updates the perturbations iteratively:

$$\boldsymbol{x}_{i+1} = \boldsymbol{x}_i + \alpha \cdot \operatorname{sign}(\nabla J(\boldsymbol{x}_i, y)) \tag{1}$$

where x_i is the perturbed waveform in iteration *i*, and *y* is the label. *J* denotes the Cross-Entropy loss. Perturbations are generated by calculating *J* on the reference model. In each iteration, we clip values to 0.1 to ensure that the perturbed speech is in a valid range to preserve utility on ASR systems. We use a perturbation rate $\alpha = 0.0005$, 100 iterations for perturbations generated with the M5 networks and 10 iterations for WavLM networks. The perturbations are generated using the first 6 second fragments of the audio.

Neural perturbations are considered to make a contribution to privacy if they reduce the accuracy of classifiers carrying out gender inference attacks either to random (0.5 in the case of balanced data), which protects a group of speakers, or to zero, which allows individual speakers to 'flip' their gender. The utility of the perturbed speech on ASR systems is measured by Word Error Rate (WER) of transcriptions. Here, we compare the transcripts of Original speech to transcripts of protected speech using DeepSpeech 2 [23].

2.2. Results of Neural Attacks

Table 3 shows the gender classification accuracy of the different neural models against conventional neural adversaries. We use M5 and WavLM trained on different data sets as reference models to generate adversarial speech. When the reference model has the same architecture and training data as the attack classifier (i.e., white-box adversaries), the classification accuracy on perturbed speech (on the diagonal and marked with underline) is low, as expected. In other words, neural perturbations are effective against gender classification in a white-box setting. Interestingly, in quite a few cases with differences between the reference model and attack classifier (i.e., grey-box adversaries off the diagonal, which are more relevant for real-world settings) some protection is still possi-

Table 3. Gender prediction accuracy on Voxtest protected with neural perturbations. Format: All (F/M). "Ref model" specifies the reference model used to generate the perturbations. White-box accuracy is underlined. The Relative WER (rel WER) w.r.t. DeepSpeech 2 transcription of the 'Original' data is reported as a measure of ASR utility.

-			•		
	Attack classifier				
Ref Model	ightarrow M5-LS100h	ightarrow M5-LS960h	ightarrow M5-vox	rel WER	
Original	92.5 (95.5 / 91.3)	95.5 (93.8 / 96.1)	97.1 (94.6 / 98.1)		
M5-LS100h	0.2 (0.3 / 0.2)	11.7 (2.1 / 15.6)	51.1 (37.7 / 56.6)	28	
M5-LS960h	14.2 (4.1 / 18.3)	0.8 (0.1 / 1.2)	31.9 (16.5 / 38.2)	27	
M5-vox	59.9 (49.5/ 64.1)	48.8 (18.3 / 61.2)	<u>0.3</u> (<u>0.2</u> / <u>0.3</u>)	27	
	\rightarrow WavLM-LS100h	\rightarrow WavLM-LS960h	\rightarrow WavLM-vox		
Original	97.7 (97.5 /97.9)	97 (97.6 / 96.8)	99 (98.2 / 99.4)		
WavLM-LS100h	<u>3.0 (5.8 / 1.8)</u>	26.7 (26.6 / 26.7)	35 (42.2 / 31.9)	32	
WavLM-LS960h	47.1 (81.4 / 32.7)	3.9 (5.5 / 3.3)	57.6 (76.6/49.7)	27	
WavLM-vox	85.1 (86.9 / 84.3)	81.1 (73.8 / 84.1)	$\underline{6.3} (\underline{9.4} / \underline{4.9})$	22	

Table 4. Gender prediction accuracy of an SVM using speech features on Voxtest protected with neural perturbations. Format: All (F/M). "Ref model" specifies the reference model used to generate the perturbations. Left column: SVM with top-10 features selected with SVM-RFE; Right column: SVM with all 35 features.

	Attack classifier			
Ref Model	SVM top-10	SVM full		
Original	87.6 (91.3 / 86)	79.7 (95.9 / 72.9)		
M5-LS100h	88.1 (90.7 / 87)	80.9 (95.2 / 74.9)		
M5-LS960h	88 (90.7 / 86.9)	82.7 (94 / 77.9)		
M5-vox	88.3 (90.9 / 87.2)	82.9 (94 / 78.3)		
WavLM-LS100h	87.6 (91.1 / 86.1)	82.7 (94.4 / 77.8)		
WavLM-LS960h	87.2 (91.2 / 85.5)	81.8 (94.8 / 76.3)		
WavLM-vox	87.8 (91.3 / 86.3)	81.7 (94.8 / 76.1)		

ble. Code and more results of different adversarial speech on different classifiers can be found in our GitHub repository.³

2.3. Results of Speech Feature Attack

Table 4 demonstrates SVMs with speech features (both top-10 and the full 35 features) are effective gender classifiers with an accuracy somewhat lower than neural models on the original data. We also see that neural perturbations do not provide effective protection against speech-feature-based SVMs. Neural-on-neural approaches would have missed this important vulnerability. Interestingly, neural perturbations boost SVM accuracy slightly, suggesting enhancement of feature robustness. Additional experiments on LibriSpeech's test set indicate that this effect is data set specific, as can be seen on the GitHub page.³

3. ANALYZING NEURAL PERTURBATIONS

The high accuracies in Table 4 suggest that the underlying aspects of speech that are important for speech-feature-based gender classifiers are missed by neural perturbations, or are not sufficiently modified. In this section, we analyze the

³https://github.com/Loes5307/VocalAdversary2022

Table 5. The intersection of the top-10 Male vs. Female features (listed in Table 2) and Non-perturbed vs. Perturbed features (on Voxtest perturbed with different models, listed in 'Ref model')

Ref model	intersection of top-10 features
WavLM-LS100h	autocor_mean, nhr_mean, intensity_mean, shimmer_apq3
WavLM-LS960h	pitch_mean, nhr_mean, intensity_mean, shimmer_apq3
WavLM-vox	pitch_mean, nhr_mean, intensity_mean
M5-LS100h	shimmer_apq3
M5-LS960h	autocor_mean, nhr_mean, shimmer_apq3
M5-vox	pitch_mean, autocor_mean, nhr_mean

overlap between the features that are changed by neuralperturbation and the features that discriminate between genders.

We use SVM-RFE to obtain the top-10 contributing features distinguishing perturbed vs. non-perturbed speech. Table 5 presents the intersection of these features and the top-10 features relevant for classifying gender given in Table 2. This list provides insight into which features are relevant for protecting against both neural and speech-feature-based attacks.

4. VOCAL ADVERSARIES

Since intensity (a measure of loudness) and pitch were found to be important for protection of gender in speech in Sec. 3, our vocal adversaries leverage these features. As a proof of concept, twenty voice adaptations inspired by the voice disguise literature [24] were recorded by two speakers (one male, one female) reading the same passage of a story ("The Patchwork Girl of Oz" [25]). Four of these adaptations are reported in Table 6, where 'default' refers to speaking normally, 'lowrobot' and 'highrobot' refer to speaking monotone like a robot in low and high pitch respectively and 'overlyhappy' refers to speaking with a high pitch while smiling broadly. We found that some vocal adversaries, e.g., 'overlyhappy', can impede a gender inference attack. These results establish the viability of future interest on vocal adversaries. Note that the WER for the vocal adversary is computed with Deep-Speech 2 against a manual transcription, and is relatively high for all speech reflecting out-of-vocabulary words in the story. For some adaptations, the WER does not drop, indicating that the vocal adversary does not necessarily have the privacyutility trade off characteristic of neural perturbations. A full overview and more details of the vocal adversaries can be found in the GitHub repository.³

5. DISCUSSION AND OUTLOOK

In this paper, we have presented three sets of experiments whose results show three ways in which researchers should strive to move beyond neural-on-neural approaches when developing and testing speaker gender protection algorithms. In Sec. 2, we have shown that neural perturbations are often effective against neural gender inference. This point is not particularly surprising, given the effectiveness of neural perturbations in the image [22] and the non-speech audio domain [26]. In many cases, neural perturbations transfer from the reference model to a different attack classifier, which makes them seem highly effective at first consideration. However, speech has an important distinction from images and non-speech audio: it is produced by the human body and enjoys regularities in underlying structure that reflect phonation and the resonances of the vocal tract. The consequence is that a single feature can already be used to draw a useful decision boundary (Fig. 1), and an SVM based on classic speech features (Sec. 2) can perform nearly on par with a neural classifier. Neural perturbations that protect gender apparently fail to influence the underlying characteristics of speech sufficiently, since they provide little protection against gender inference attacks based on speech features. This conclusion is supported by the fact that SVMs are less successful in defeating neural perturbations in non-speech audio [26].

Moving forward, researchers in the area of attribute inference are well served to attempt to analyze the impact of perturbations on speech in more detail. Some papers have moved in this direction by providing spectrograms of protected speech or by describing how it sounds [2, 3]. Here, we suggest that speech features are useful for explaining the effect of perturbations in a way that is closely related to speech production. Future work should further evolve the analysis presented in Sec. 3.

Finally, we have shown in Sec. 4 that a vocal adversary has potential to defend against both neural and speechfeature-based attacks. The human-executed voice adaptations that we tested required no special voice training, and open a new avenue for research on real-world protection against gender inference attacks in, i.e., smart speakers.

6. ACKNOWLEDGEMENTS

The first author was supported by a master-level ELLIS excellence fellowship at Radboud University Nijmegen.

Table 6. Gender prediction accuracy of different models for four voice adaptations of vocal adversaries. Format: All (F/M). The WER per voice adaptation is reported on the left as 'F/M' w.r.t. manual transcription.

	I					I I I		
WER	data	M5-LS100h	M5-LS960h	M5-vox	WavLM-LS100h	WavLM-960h	WavLM-vox	SVM-full
35/31	default	100 (100 / 100)	96 (92 / 100)	63 (25 / 100)	100 (100 / 100)	100 (100 / 100)	100 (100 / 100)	100 (100 / 100)
67 / 89	whisper	50 (96 / 4)	50 (0 / 100)	50 (0 / 100)	94 (100 / 88)	94 (100 / 88)	98 (96 / 100)	50 (100 / 0)
25/38	lowrobot	100 (100 / 100)	63 (25 / 100)	50 (0 / 100)	100 (100 / 100)	100 (100 / 100)	100 (100 / 100)	100 (100 / 100)
27 / 42	highrobot	100 (100 / 100)	98 (96 / 100)	71 (42 / 100)	100 (100 / 100)	100 (100 / 100)	100 (100 / 100)	100 (100 / 100)
39 / 51	overlyhappy	50 (100 / 0)	52 (88 / 17)	63 (33 / 92)	56 (100 / 13)	71 (100 / 42)	67 (100 / 33)	50 (100 / 0)

7. REFERENCES

- Y. Gong and C. Poellabauer, "Crafting adversarial examples for speech paralinguistics applications," *DY-NAMICS*, 2018.
- [2] D. Stoidis and A. Cavallaro, "Generating genderambiguous voices for privacy-preserving speech recognition," *INTERSPEECH*, pp. 4237–4241, 2022.
- [3] P. Wu, P. P. Liang, J. Shi, R. Salakhutdinov, S. Watanabe, and L.-P. Morency, "Understanding the tradeoffs in client-side privacy for downstream speech tasks," *AP-SIPA ASC*, 2021.
- [4] N. Tomashenko, B. M. L. Srivastava, X. Wang, E. Vincent, A. Nautsch, J. Yamagishi, N. Evans, J. Patino, J.-F. Bonastre, P.-G. Noé *et al.*, "Introducing the voiceprivacy initiative," *INTERSPEECH*, pp. 1693–1697, 2020.
- [5] L. Tuncay Zayer and C. A. Coleman, "Advertising professionals' perceptions of the impact of gender portrayals on men and women: a question of ethics?" *Journal of Advertising*, vol. 44, no. 3, pp. 1–12, 2015.
- [6] J. Turow, "The voice catchers," in *The Voice Catchers*. Yale University Press, 2021.
- [7] M. Lebourdais, M. Tahon, A. Laurent, and S. Meignier, "Overlapped speech and gender detection with wavlm pre-trained features," *INTERSPEECH*, pp. 5010–5014, 2022.
- [8] L. Zimman, "Gender diversity and the voice," *The Routledge handbook of language, gender, and sexuality*, pp. 69–90, 2021.
- [9] R. Aloufi, H. Haddadi, and D. Boyle, "Privacypreserving voice analysis via disentangled representations," in *Cloud Computing Security Workshop*, 2020.
- [10] P.-G. Noé, M. Mohammadamini, D. Matrouf, T. Parcollet, A. Nautsch, and J.-F. Bonastre, "Adversarial disentanglement of speaker representation for attribute-driven privacy preservation," *INTERSPEECH*, pp. 1902–1906, 2021.
- [11] D. Stoidis and A. Cavallaro, "Protecting gender and identity with disentangled speech representations," *IN-TERSPEECH*, pp. 1699–1703, 2021.
- [12] S. Ahmed, Y. Wani, A. S. Shamsabadi, M. Yaghini, I. Shumailov, N. Papernot, and K. Fawaz, "Pipe overflow: Smashing voice authentication for fun and profit," *arXiv*:2202.02751, 2022.
- [13] V. Panayotov, G. Chen, D. Povey, and S. Khudanpur, "Librispeech: an ASR corpus based on public domain audio books," *ICASSP*, pp. 5206–5210, 2015.

- [14] J. S. Chung, A. Nagrani, and A. Zisserman, "Voxceleb2: Deep speaker recognition," *INTERSPEECH*, pp. 1086– 1090, 2018.
- [15] W. Dai, C. Dai, S. Qu, J. Li, and S. Das, "Very deep convolutional neural networks for raw waveforms," *ICASSP*, pp. 421–425, 2017.
- [16] S. Chen, C. Wang, Z. Chen, Y. Wu, S. Liu, Z. Chen, J. Li, N. Kanda, T. Yoshioka, X. Xiao *et al.*, "Wavlm: Large-scale self-supervised pre-training for full stack speech processing," *IEEE Journal of Selected Topics in Signal Processing*, vol. 16, no. 6, pp. 1505–1518, 2022.
- [17] T. Bocklet, A. Maier, J. G. Bauer, F. Burkhardt, and E. Noth, "Age and gender recognition for telephone applications based on gmm supervectors and support vector machines," *ICASSP*, pp. 1605–1608, 2008.
- [18] P. Boersma and D. Weenik, "Praat: doing phonetics by computer (version 6.2.14)," http://www.praat.org, 2020.
- [19] I. Guyon, J. Weston, S. Barnhill, and V. Vapnik, "Gene selection for cancer classification using support vector machines," *Machine learning*, vol. 46, no. 1, pp. 389– 422, 2002.
- [20] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu, "Towards deep learning models resistant to adversarial attacks," in *ICLR*, 2018.
- [21] I. J. Goodfellow, J. Shlens, and C. Szegedy, "Explaining and harnessing adversarial examples," in *ICLR*, 2015.
- [22] F. Tramer, N. Carlini, W. Brendel, and A. Madry, "On adaptive attacks to adversarial example defenses," *NeurIPS*, pp. 1633–1645, 2020.
- [23] D. Amodei, S. Ananthanarayanan, R. Anubhai, J. Bai, E. Battenberg, C. Case, J. Casper, B. Catanzaro, Q. Cheng, G. Chen *et al.*, "Deep speech 2: End-to-end speech recognition in english and mandarin," *ICML*, pp. 173–182, 2016.
- [24] C. Zhang and T. Tan, "Voice disguise and automatic speaker recognition," *Forensic science international*, vol. 175, no. 2-3, pp. 118–122, 2008.
- [25] L. F. Baum, Oz, the Complete Collection, Volume 3: The Patchwork Girl of Oz; Tik-Tok of Oz; The Scarecrow of Oz. Simon and Schuster, 1913.
- [26] M. Esmaeilpour, P. Cardinal, and A. L. Koerich, "A robust approach for securing audio classification against adversarial attacks," *IEEE Transactions on information forensics and security*, vol. 15, pp. 2147–2159, 2019.